webMethods Error Message Reference

Version 10.3

October 2018

WEBMETHODS

This document applies to webMethods Product Suite Version 10.3 and all subsequent releases.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at http://softwareag.com/licenses.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at http://softwareag.com/licenses/ and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at http://softwareag.com/licenses and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

Document ID: XSU-MESSAGES2-103-20181011

Table of Contents

1 About this Documentation 1
    Document Conventions 2
    Online Information and Support 2
    Data Protection 3
2 ActiveTransfer Messages 5
3 Application Designer Messages 11
4 Application Development Plug-in Messages 13
5 Application Platform Server Messages 29
6 Business Rules Messages 51
7 CentraSite Messages 61
8 CloudStreams Messages 365
9 Command Central Messages 457
10 Common Monitoring Provider Messages 537
11 Database Component Configurator Messages 579
12 Deployer Messages 581
13 Designer Composite Application Framework 667
14 Digital Event Services 671
15 Event-Driven Architecture Tools Messages 701
16 Event Persistence Messages 711
17 Installer Messages 783
18 Integration Server Messages 787
19 Mediator Messages 1343
20 My webMethods Server Messages 1391
21 OSGi Messages 1549
22 Platform Manager Messages 1567
23 Process Engine Messages 1663
24 Realtime Monitoring Messages 1727
25 Security Messages 1877
26 Tamino Messages 1905
27 Trading Network Messages 2373
28 webMethods Social BPM Messages 2627
29 Web Services Stack Messages 2635
30 Universal Messaging Messages 2671

1 About this Documentation

- Document Conventions 2
- Online Information and Support 2
- Data Protection 3

Document Conventions

Convention	Description
Bold	Identifies elements on a screen.
`Monospace font`	Identifies service names and locations in the format *`folder.subfolder.service`*, APIs, Java classes, methods, properties.
`Italic`	Identifies: Variables for which you must supply values specific to your own situation or environment. New terms the first time they occur in the text. References to other documentation sources.
`Monospace font`	Identifies: Text you must type in. Messages displayed by the system. Program code.
{ }	Indicates a set of choices from which you must choose one. Type only the information inside the curly braces. Do not type the { } symbols.
|	Separates two mutually exclusive choices in a syntax line. Type one of these choices. Do not type the | symbol.
[ ]	Indicates one or more options. Type only the information inside the square brackets. Do not type the [ ] symbols.
...	Indicates that you can type multiple options of the same type. Type only the information. Do not type the ellipsis (...).

Online Information and Support

Software AG Documentation Website

You can find documentation on the Software AG Documentation website at **http://documentation.softwareag.com**. The site requires credentials for Software AG's Product Support site Empower. If you do not have Empower credentials, you must use the TECHcommunity website.

Software AG Empower Product Support Website

If you do not yet have an account for Empower, send an email to empower@softwareag.com with your name, company, and company email address and request an account.

Once you have an account, you can open Support Incidents online via the eService section of Empower at **https://empower.softwareag.com/**.

You can find product information on the Software AG Empower Product Support website at **https://empower.softwareag.com**.

To submit feature/enhancement requests, get information about product availability, and download products, go to **Products**.

To get information about fixes and to read early warnings, technical papers, and knowledge base articles, go to the **Knowledge Center**.

If you have any questions, you can find a local or toll-free number for your country in our Global Support Contact Directory at **https://empower.softwareag.com/public_directory.asp** and give us a call.

Software AG TECHcommunity

You can find documentation and other technical information on the Software AG TECHcommunity website at **http://techcommunity.softwareag.com**. You can:

- Access product documentation, if you have TECHcommunity credentials. If you do not, you will need to register and specify "Documentation" as an area of interest.
- Access articles, code samples, demos, and tutorials.
- Use the online discussion forums, moderated by Software AG professionals, to ask questions, discuss best practices, and learn how other customers are using Software AG technology.
- Link to external websites that discuss open standards and web technology.

Data Protection

Software AG products provide functionality with respect to processing of personal data according to the EU General Data Protection Regulation (GDPR). Where applicable, appropriate steps are documented in the respective administration documentation.

2 ActiveTransfer Messages

1003	**Error while initializing ActiveTransfer database connection.The original error message was: {0}**
2001	**Invalid or unsupported RDBMS vendor: {0}.**
2002	**The database connection pool associated with ActiveTransfer should allow at least 2 connections. Your ActiveTrasnfer pool is currently configured with a maximum of {0} connections. Aborting TN startup. Please increase your ActiveTransfer database pool maximum and restart the server.**
2003	**There was an error while reading the dbops.sql file. The original error message was: {0}**
2004	**There was an error while reading the dblimits.cnf file. The original error message was: {0}**
2005	**A connection was returned to the connection pool with autoCommit = false. This may indicate some changes to the database were not committed properly. The changes will be rolled back. Stack trace {0}**

2006	**ActiveTransfer database pool is not configured. Please configure a database pool for functional alias "ActiveTransfer".**
2007	**There was an error while connecting to ActiveTrasnfer connection pool.The original error message was: {0}**
2008	**ActiveTransfer database pool is not configured properly. Make sure that a valid database pool is assigned for functional alias "ActiveTransfer".**
2009	**Error while reading the database configuration. The exception message is : {0}**
2011	**ActiveTransfer could not retrieve data from your database. Go to the JDBC Pools page in the Integration Server Administrator and make sure your database URL, user name, and password are set correctly. Also make sure you created the ActiveTrasnfer database tables as described in the Product Installation Guide.**
3001	**A scheduled action with this name already exists.**
3004	**Unable to save scheduled archive service "{0}".**
3009	**Interval value for fixed interval {0} cannot be empty.**
3010	**Interval value is not valid.**
3011	**Interval must be greater than zero.**
3012	**The scheduled {0} is invalid. Format must be YYYY/MM/DD.**
3013	**The scheduled {0} is invalid. Format must be hh:mm:ss.**

3020	**The scheduled delivery date/time is in the past.**
3021	**If an end time is supplied, an end date must also be supplied.**
3022	**End date/time is in the past.**
3023	**End date/time is before start date/time.**
3024	**Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.**
3025	**Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss".**
3031	**A post process event with this name already exists.**
3032E	**The action name "{0}" repeats for multiple actions in this event. Retry with unique action names.**
Explanation	Each action defined in an ActiveTransfer event must have a unique name.
Action	Specify a unique name for each action in an ActiveTransfer event.
3033	**The action name cannot be null.**
3034E	**Scheduled event "{0}" does not exist. Retry with an existing scheduled event.**
Explanation	The scheduleName parameter provided for the wm.mft.schedule:executeEvent service is not a valid scheduled event in ActiveTransfer.
Action	Ensure that the scheduled event name specified by the scheduleName parameter is defined in ActiveTransfer.
4003E	**Update of asset failed.**
Explanation	ActiveTransfer Server could not update the asset.
Action	Check the ActiveTransfer error logs for details.

4005E	**Insertion of asset failed.**
Explanation	ActiveTransfer could not insert the asset on the target server.
Action	Check the ActiveTransfer error logs for details.

4006E	**The export file name cannot be null.**
Explanation	The exportData service could not execute because no export file was specified.
Action	In the exportFileName parameter, specify the path and name of the XML file in which to save the exported assets.

4007E	**The import file name cannot be null.**
Explanation	The importData service could not execute because no import file was specified.
Action	In the importDataFileName parameter, specify the path and name of the XML file containing the assets to import.

4008E	**The import file {0} does not exist.**
Explanation	The specified file containing the assets to import does not exist.
Action	In the importDataFileName parameter, specify a valid path and name of the XML file containing the assets to import.

4009E	**The import file {0} cannot be read.**
Explanation	ActiveTransfer Server could not read the specified import file.
Action	In the importDataFileName parameter, specify a file name that ActiveTransfer Server can access.

4010E	**Specify values for input parameter {0} or set input parameter all to true.**
Explanation	The "all" input parameter for the importData service is set to "false," but no assets are specified to import.
Action	Either set the "all" input parameter to "true" or specify the assets to import in the "importData" parameter.

4011E	**The value of input parameter assetType of {0}[{1}] is null. Specify a value for the asset type.**
Explanation	ActiveTransfer Server could not import the asset for the indicated importData document because no asset type was specified.
Action	Specify a value in the assetType variable for each asset type you want to import.

4012E **No assets to import.**

Explanation The export file is blank or the assets selected for import are not in the export file.

4013E **The version information in the import file cannot be null.**

Explanation The version information in the import file is null. ActiveTransfer supports import of assets into ActiveTransfer 9.5 or later. The server could not find version information in the file the importData service is attempting to import.

4014E **The version information provided in the file for Import operation is {0}, only the data exported from version {1} can be imported.**

Explanation ActiveTransfer supports the export of assets from version 9.5 or later. This export file was created from an earlier version of ActiveTransfer

4015E **A reference is not available on the target server. Reference details- type:{0}, name:{1}, and ID:{2}.**

Explanation A reference to a server instance is not available on the target server.

4016 **assetType element not found in XML.**

7001 **A server with the same protocol and 'host + port' combination already exists.**

7002 **A server tunnel with the same name already exists.**

7003 **Error while updating the server. Check the logs.**

7004 **A proxy instance with the same host and port combination already exists.**

7005 **A proxy instance with the same name already exists.**

8001 **An invalid template has been specified for the user. Template ID:{0}**

8002	**A user template with the same name already exists.**
8003	**A user with the specified id does not exist. User ID:{0}**
8004	**The user does not have an associated template. User ID:{0}**
8005	**The user "{0}" already exists.**
8006	**No default user template is defined in ActiveTransfer. Please create a default user template before creating a user.**
8007	**Default template cannot be deleted.**
8101	**A virtual folder with the same name already exists.**

3 Application Designer Messages

INMBAE0001	**Login failed. The reason could be an incorrect username and/or password, or a database access error.**
Explanation	The system could not log you on. An error occurred during authentication.
Action	Specify correct user name (possibly including domain name) and password. Note that letters in passwords must be typed using the correct case. You may also want to check whether the CentraSite server is started.

INMBAE0002	**Please enter an appropriate value.**
Explanation	Please enter an appropriate value.
Action	Please enter an appropriate value.

INMBAE0003	**Cannot uninstall plug-in with id {0}, is required e.g. by plug-in with id {1}.**
Explanation	The plug-in you wish to uninstall cannot be uninstalled because another plug-in depends on it.
Action	Check whether to uninstall the dependent plug-in as well.

INMBAE0005	**Failed to delete {0}.**
Explanation	The given file or directory could not be deleted.
Action	Check whether in use by another program.

INMBAE0006	**Unable to load JAAS Configuration. The jaas.config file may have syntax errors.**
Explanation	JAAS Configuration seems to be invalid and hence cannot be loaded. The jaas.config file may have syntax errors
Action	Ensure the syntax correctness of jaas.config file. Fix any additional issues as pointed out in the error message

INMBAE0009	**Subject does not supply credentials. The subject instance is {0}.**
Explanation	Authenticated subject does not have credentials after authentication.
Action	This is most probably due to a CentraSite security misconfiguration.

INMBAE0010	**Connection handler {0} failed to establish connection.**
Explanation	Connection handler {0} failed to establish connection.
Action	Check logs.

INMBAE0011	**Plug-in {0} has been disabled.**
Explanation	Plug-in {0} has been disabled.
Action	Check logs for reason.

INMBAE0012	**Database access error. Can't connect to server CentraSite.**
Explanation	CentraSite Server is not running.
Action	Start CentraSite Server.

INMBAW0004	**Forced uninstall of plug-in with id {0} will cause disabling of dependent plug-in with id {1}.**
Explanation	When the plug-in is uninstalled, the dependent plug-in will no longer be usable.
Action	The dependent plug-in will be re-enabled when the required plug-in is available again.

4 Application Development Plug-in Messages

JmxServiceConnectError – Designer was unable to physicaly connect to the server over JMX on port {0}. Verify the Server view's JMX port configuration matches the port configuration for the server. Verify the server is started and listening for socket connections on this port.

Explanation Application Platform uses a JMX service to communicate with a server at design time.

Action Verify the Server view's JMX port configuration matches the port configuration for the server. Verify the server is started and listening for socket connections on this port.

JmxServiceNoInstanceError – Designer is connected to the server over JMX as required; however, the App Platform remote service is unavailable. Verify the 'Application Platform Support' component is installed for this server.

Explanation Application Platform is using a JMX service to communicate with the server on port {0}. It connected to the server; however, the service is not available.

Action The 'Application Platform Support' component must be installed for each server. Verify this component was installed; otherwise, please contact Global Support. Please provide the Designer and server logs.

JmxServiceServerError – An error occurred while executing an Application Platform Designer remote JMX service on the server.

Explanation Application Platform is using a JMX service to communicate with the server. An exception occurred on the server while executing a task.

Action Determine the source of this server-side error and contact Global Support if unable to resolve the issue.

PLDBBCE0000	**Unable to establish a JMX connection to the {0} server over port {1}. Cause: {2}**
Explanation	Designer failed to establish a JMX to the remote development server.
Action	Verify that the server is started and that the installed PLS bundle deploy service bundle is active.

PLDBBCE0001	**Unable to access the bundle publisher service.**
Explanation	The Dependency Manager was unable to access the publisher service when the remote server was started. The dependency manager needs the publisher service in order to obtain the list of deployed bundles in the server's OSGi container.
Action	Restart Designer and verify that the PLD bundle deploy client bundle is active.

PLDBBCE0002	**Unable to access the Dependency Manager service.**
Explanation	The Dependency Manager service is contributed to the OSGi service registry but it is not registered to it.
Action	Restart Designer and verify that the PLD bundle builder core bundle is active.

PLDBBUE0000	**An error occurred while resolving the list of libraries in the Application Platform common classpath container for project: {0}. Cause: {1}**
Explanation	The list of libraries that are automatically created by Application Platform for the project cannot be resolved. One or more libraries, provided by Application Platform, must be present for projects with Application Platform project facets.
Action	Remove the Application Platform core project facet from the project and add it again. Verify that the Application Platform bundles exist in the target installation path under 'common/runtime/bundles/pls-core/eclipse/plugins' and 'common/runtime/bundles/applatform/eclipse/plugins'. If these directories do not exist, verify that all of the Application Platform components were selected during installation.

PLDBBUE0001	**An error occurred while initializing the Application Platform classpath container for project {0}. Cause: {1}**
Explanation	Designer could not initialize the classpath container for the existing project during the workspace initialization. The error is isolated to the initializer of this container.
Action	Remove the Application Platform core project facet from the project and add it again. Verify that the Application Platform bundles exist in the target installation path under 'common/runtime/bundles/pls-core/eclipse/plugins' and 'common/runtime/bundles/applatform/eclipse/plugins'. If these directories do not exist, verify that all of the Application Platform components were selected during installation.

PLDBMGE0000	**An exception occurred while reloading the Bundle Manager view. Cause: {0}**
Explanation	Designer could not reload the Bundle Manager view. Reloading the Bundle Manager view involves the following sources: a selected project, a connected server, and a configured set of directories.
Action	Determine the source where the error occurred (directory, project or server).

PLDBMGE0001	**An exception was produced while accessing the Dependency Manager Service.**
Explanation	Designer could not access the Dependency Manager Service. The Dependency Manager Service is an OSGi service. Aplication Platform uses this service for verifying bundles and their relationships to other bundles.
Action	Restart Designer and try again. If the error persists, contact Software AG Global Support.

PLDBMGE0002	**An exception was produced while accessing the Bundle Manager Service.**
Explanation	Designer could not access the Bundle Manager Service. The Bundle Manager Service is an OSGi service used by the Application Platform Bundle Manager View.
Action	Restart Designer and try again. If the error persists, contact Software AG Global Support.

PLDBMGE0003	**An error occurred while restoring the Bundle Manager to its default settings. Cause: {0}**
Explanation	An error occurred while resetting the Bundle Manager to its default values. The configuration settings of the Bundle Manager are stored by the Eclipse preferences API.
Action	Check the details of the exception and try to resolve the problem.

PLDBMGE0005	**Error opening Bundle Manager configuration settings dialog. Cause: {0}**
Explanation	The Bundle Manager configuration settings dialog failed to open. The configuration settings dialog contains configuration settings that impact the Bundle Manager view.
Action	Restart Designer and try again. Try to access the Bundle Manager configuration settings dialog from the Windows/Preferences/SoftwareAG/Bundle Manager menu path.

PLDBMGE0006	**Invalid number format for the App Platform server configuration key: {0}. Value: {1}**
Explanation	The server configuration property received an invalid value. A numeric value is required for the App Platform server configuration key.
Action	Verify that the server configuration value is non-null and that it is numeric.

PLDBMGE0007	**Bundle Manager encountered an error while publishing bundle {0} into the server's repository. Cause: {1}**
Explanation	The Bundle Manager could not publish the selected bundle to the server's bundle repository. The bundle must be published to the repository before it can be installed to the server's OSGi container. For this purpose, the bundle is first copied to a staging directory. Designer transfers the bundle to this directory by using a JMX interface via the port number, configured in the WST server
Action	Review the contents of the staging directory under the server's installation directory, for example: profiles/IS_default/workspace/temp/app-platform/deployer/bundles/. Verify that the configuration of the WST server is correct and that the server is started and it is listening on the JMX port.

PLDBMGE0008	**Bundle Manager encountered an error while installing bundle {0} to the server's OSGi container. Cause: {1}**
Explanation	The Bundle Manager failed to install the bundle to the server's OSGi container.
Action	Verify that the bundle was copied from the staging directory to the repository directory under the installation directory, for example: profiles/IS_default/workspace/app-platform/deployer/bundles/. If required bundles or imported packages are missing, review the OSGi dependencies to ensure that all required dependencies are met.

PLDBMGE0009	**Bundle Manager encountered an error while unpublishing the bundle {0} from the server's repository. Cause: {1}**
Explanation	The Bundle Manager failed to unpublish the bundle from the server's repository. The bundle can be unpublished from the server's repository after it is uninstalled from the OSGi container.
Action	Verify that the bundle was successfully removed from the repository directory under the installation folder, for example: profiles/IS_default/workspace/app-platform/deployer/bundles/. If the bundle is still in the directory, delete it manually by removing the file from this directory and restarting the server.

PLDBMGE0010	**Bundle Manager encountered an error while removing bundle {0} from the server's OSGi container. Cause: {1}**
Explanation	The Bundle Manager failed to uninstall the bundle from the server's OSGi container. The bundle must be uninstalled from the OSGi container before it can be unpublished from the p2 repository.
Action	Verify that the bundle was successfully removed from the repository directory under the installation folder, for example: profiles/IS_default/workspace/app-platform/deployer/bundles/. If the bundle is still in the directory, delete it manually by removing the file from this directory and restarting the server.

PLDBMGE0011	**The Bundle Manager encountered an unexpected error while executing the update server task. Cause: {0}**
Explanation	The Bundle Manager failed to update the server. The Bundle Manager runs an update server task when a server is started or bundle changes are committed.
Action	Review the contents of the staging directory under the server's installation directory. Verify that the configuration of the WST server is correct and that the server is started and it is listening on the JMX port. If you have uninstalled bundles from the server, verify that they bundle were successfully removed from the repository directory under the installation folder. If one or more bundles are still in the directory, delete it manually by removing the file from this directory and restarting the server.

PLDBMGE0012	**An Application Platform server must be configured and started for this operation.**
Explanation	This Application Platform operation in Designer requires access to a server instance. A server configuration must be created and successfully started.
Action	From the Servers view create an Application Platform server and start it.

PLDBMGE0015	**Error creating wrapper bundle. Cause: {0}**
Explanation	An unexpected error occurred while creating a wrapper bundle for the set of jars.
Action	Verify that the jar files and the bundle manifest are valid. If they are valid and the error persists, contact Software AG Global Support.

PLDBMGE0017	**An error occurred while creating a wrapper bundle. Cause: {0}**
Explanation	The Bundle Manager view failed to create a wrapper bundle for the given plain jar(s).
Action	Verify that the jars to be included in the wrapper jar are valid Java archives. Review the generated OSGi manifest entry in the jar (META-INF/MANIFEST.MF) and verify that the target directory, where the bundle is to be created, exists and has appropriate file permissions for the current user.

PLDBMGE0019	**Error removing wrapper bundle. Cause: {0}**
Explanation	An unexpected error occurred while removing one or more wrapper bundles.
Action	Verify that the associated jar files exist and that they are not opened in another application.

PLDBMGE0021	**File {0} was not installed on the server. The file is not a bundle.**
Explanation	The file you attempted for publishing to the server is not an OSGi bundle. Designer can only publish OSGi bundlers to the product server.
Action	Review the file contents and publish only OSGi bundles to the server.

PLDBMGE0022	**Unable to validate project {0}'s bundle file before attempting to publish or unpublish.**
Explanation	The file could not be validated by Designer. Designer needs a valid project archive file with OSGi bundle headers before it can perform publisher-related operations against a server.
Action	Rebuild the project to ensure its contents are up to date.

PLDBMGI0020	**The server must be started before bundles can be removed. The server is used to confirm they the bundles are not installed.**
Explanation	You cannot remove bundles when the server is started. Published bundles cannot be removed, so the server must first confirm that the selected bundles for removal are not installed.
Action	Start the Application Platform server in Designer and select unpublished bundles for removal.

PLDBMGW0014	**Clear the text filter to ensure that all bundles or jars are included in this action.**
Explanation	The filter cannot be cleared programmatically before the selected task is runned because the task is running on the same UI thread.
Action	Clear the text box and repeat the operation.

PLDCDGE0000	**Unknown data type from DataKey annotation for field {0}; type: {1}**
Explanation	The DataKey annotation is incorrect. The DataKey annotation identifies an element to be used in IS service signature. These signatures support only a limited set of data types. The data type of the field identified here is not supported.
Action	Update the DataKey annotation to use a supported data type.

PLDCDGE0001	**Unable to create POJO wrappers for IS node: {0}**
Explanation	The node is not recognized by the IS server as a defined service or a shared doctype or specification reference.
Action	Make sure that the selected node is valid on the selected IS server.

PLDCDGE0002	**Unexpected Integration Server node-type {0} for node {1}, expecting {2}**
Explanation	An unexpected node-type was found in the Integration Server node that was retrieved. This may be caused by an incorrect node name.
Action	Correct the Integration Server node name.

PLDCDGE0003 **Unable to retrieve Integration Server {0} description for node {1}; caught: {2}**

Explanation Retrieving the service or record details for the given Integration Server node was unsuccessful. This error may result from improper configuration either in the IS server identification, or in the IS service.

Action Check the error logs for more details about this error.

PLDCDGE0004 **Unexpected signature node type: {0}; field is {1}, generating bean: {2}.{3}**

Explanation The field-type used when generating a Java source for the IS service signature was not recognized. This may occur because of an unsupported IS serice configuration.

Action Contact Software AG Global Support.

PLDCDGE0005 **Cannot use a connection that is null or disconnected: {0}**

Explanation Failed to connect to Integration Server. Application Platform attempted to generate a code for an IS service but the connection is not working.

Action Verify that the connection to Integration Server is working. If the error persists with a working connection, contact Software AG Global Support.

PLDCDGE0006 **Unable to retrieve Integration Server {0} description for package {1}; caught: {2}**

Explanation Retrieving the details for the given Integration Server package was unsuccessful. This error may result from improper configuration either in the IS server identification, or in the IS package.

Action Check the error logs for more details about this error.

PLDCFTE0000 **An error occurred while creating Application Platform project facets in the project template. Cause: {0}**

Explanation The creation of Application Platform project facets failed. Designer uses a template of Eclipse project facets when creating a service project. The Application Platform server uses these facets to determine if it can publish a project's module.

Action Verify that all of the Application Platform components were installed in Designer.

PLDCFTE0001 **An error occurred in the Application Platform service project wizard while creating a project. Cause: {0}**

Explanation The Application Platform service project wizard failed to create a project. The service project wizard creates a Designer project and performs tasks for each of the selected project facets.

Action Review the error and verify that the project facet selections are valid.

PLDCSPE0001	**An error occurred while unpublishing a project resource from the server, configured for Application Platform.**
Explanation	An unexpected error occurred while unpublishing a project resource to the configured server.
Action	Verify that the project is still deployed on the server, that the server configuration is complete, and that the server can be started successfully.

PLDCSPE0003	**An error occurred while publishing a project resource to the Application Platform server.**
Explanation	An unexpected error occurred while publishing a project resource to the configured server.
Action	Verify that the project contents are valid, that the server configuration is complete, and that the server can be started successfully.

PLDCSPE0004	**Designer was unable to confirm the server's status during startup/shutdown. Details: {0}**
Explanation	The configured Application Plaform server uses a polling ping approach to confirm if the remote server was successfully started or stopped. An error occurred during the ping operation and the status of the server could not be confirmed.
Action	If you are running the server via its native shell scripts, stop the server. Then try to restart the server in Designer.

PLDCSPE0005	**An exception was encountered while trying to synchronize the Application Platform server {0}'s run status in the Servers view. Cause: {1}**
Explanation	Designer was unable to synchronize the status of the Application Platform server. The Servers view for Application Platform has a configuration setting, which is used to control how Designer synchronizes its status against the server.
Action	Verify that the configuration parameters are correct. If the server properties section does not show any properties, delete the server configuration and recreate it.

PLDCSPE0006	**An error occurred while refreshing the Bundle Manager during the server status update to {1}. Cause: {2}**
Explanation	Designer failed to refresh the Bundle Manager when the server was started or stopped.
Action	Restart Designer. If the error persists, contact Software AG Global Support.

PLDCSPE0009 **An error occured while updating the Application Platform server run status {0}. Cause: {1}**

Explanation The Server's view for the Application Platform includes an entry for each configured server. Designer has received a WST server event, but an error has occurred while Designer attempted to update a server's run state.

Action Review the server configuration in the Servers view and verify that the required server data is present. If the data is incorrect or some server properties are not displayed, delete the server configuration and recreate it.

PLDCSPE0010 **Error getting a URL for server {0} for verifying the run status of Integration Server. Cause: {1}**

Explanation Designer was unable to obtain a URL for the server. The URL is needed in order to perform a ping operation against the server and to determine its current status.

Action Verify that the server configuration properties are correct and try again.

PLDCSPE0011 **Unable to create Application Platform custom module.**

Explanation Application Platform was unable to create a custom module. Application Platform uses a custom module in order to differentiate its server from other servers, like Tomcat, for example. The custom module is needed for adding all application projects containing the Application Platform project facets to the server. This is a critical component required for publishing bundles to the server.

Action Contact Software AG Global Support.

PLDCSPE0012 **An unexpected error occured while validating a project facet for module {0}. Cause: {1}**

Explanation Designer could not validate a project facet for the module. Designer projects use facets in order to define capabilities, supported by the servers that host the projects. This ensures that no attempts for publishing a project to a server that does not support that project can be made.

Action Review the error details and verify that the correct project facets are added to the project.

PLDCSPE0013 **An error occurred while adding server {0} to the lifecycle listener. Cause: {1}**

Explanation Designer failed to add the server to the lifecycle listener. A collection of listeners is maintained for servers that are added or removed from Designer. The listeners contain all the information that is needed for performing server actions, like publishing or unpublishing project bundles.

Action Restart Designer.

PLDCSPE0014	**An error occurred while synchronizing WST Servers View configuration updates. Cause: {0}**
Explanation	Application Platform uses the Eclipse WST subsystem server configuration data. An exception occurred while updating Application Platform plugins.
Action	Restart Designer.

PLDCSPE0015	**Missing credentials for server connection to the following url: {0}**
Explanation	No credentials have been provided to verify the server status.
Action	Verify that the server connection has appropriate credentials.

PLDCSPW0000	**An attempt was made to publish or unpublish a project module to a server that is not started.**
Explanation	An error occurred while publishing or unpublishing the project module because the server is not started. You can only publish or unpublish Application Server projects to a server, which is started.
Action	Verify that the server is started and repeat the action.

PLDCSPW0002	**No project modules were specified for the Application Platform publish operation.**
Explanation	The Application Platform publisher received a publish request but no project modules were included in the request.
Action	Confirm that there is at least one project added to the Application Platform server configuration and try to publish again.

PLDCSPW0008	**You must stop and restart the server after you change and save the server settings.**
Explanation	You must restart the server after you change the server settings. Many of the server settings you can configure in Designer update server configurations, such as port numbers.
Action	Restart the server, and then restart the configured server in Designer.

PLDCUIE0001	**An unexpected error occurred while configuring an Application Platform runtime environment.**
Explanation	The Application Platform runtime configuration failed. The runtime preference page is used to define the runtime instance used for Application Platform server and project configurations.
Action	Go to the Window/Preferences/Server/Runtime Environments preference panel and create a runtime instance for the Application Platform server. If no server entry is displayed, confirm that all the required Application Platform components were installed.

PLDCUIE0002	**Unable to verify preference setting {0} from the imported preferences file. Cause: {1}**
Explanation	Application Platform verifies all directory path preference settings during the import step. An error occurred while verifying one of the preference settings.
Action	Update the preference setting manually.

PLDCUIE0003	**{0} preference setting's directory path does not exist. ({1})**
Explanation	While importing Designer preferences, Application Platform encountered a preference setting that contains a non-existent directory path.
Action	Update the imported preference setting with a valid directory path.

PLDCUII0000	**No Application Platform runtime instance configuration was found.**
Explanation	Designer could not find an Application Platform runtime instance configuration. The Application Platforrm server and projects require a runtime configuration.
Action	Create a runtime instance in the 'Runtime Environments' preference page in Designer.

PLDISPE0000	**No Integration Server connections with valid URLs are defined in 'Window/Preferences/SoftwareAG/Integration Servers' for this Designer instance.**
Explanation	The Application Platform server was not able to start because there are no valid Integration Server connections defined.
Action	Configure a valid connection to a local Integration Server via the configuration panel. You can find the configuration panel in Window/Preferences/Software AG/Integration Servers.

PLDISPE0007	**An error occurred while retrieving the list of Integration Server connections. Details: {0}**
Explanation	Designer failed to retrieve the list of Integration Server connections. Designer maintains the list of connections in Window/Preferences/SoftwareAG/Integration Servers view.
Action	Contact Software AG Global Support.

PLDISPE0008	**No server connections are accessible in Window/Preferences/SoftwareAG/Integration Servers.**
Explanation	The Application Platform server configuration must have a Designer Integration Server connection defined for the same host and port. No servers were returned from the server connection manager.
Action	Verify that at least one server connection is defined in the preference view.

PLDISWE0000	**An error occurred while executing a task in the IS service wizard.**
Explanation	An error occurred while using the IS service wizard for creating POJO bean wrappers for Integration Server services.
Action	Restart Designer and try again.

PLDISWE0001	**The IS service wizard encountered an error while generating POJO classes for IS service: {0}**
Explanation	Application Platform was unable to produce Java POJO service wrappers for the selected IS service(s).
Action	Verify that the IS service is properly defined and retry the code generation step.

PLDISWE0002	**An Application Platform IS facet is not installed on this project.**
Explanation	The project is not configured to use the custom Application Platform facet for Integration Server extensions.
Action	Enable the Application Platform IS facet on the project's properties page.

PLDISWI0003	**IS services from IS product packages are not supported. Do not use this in a production setting.**
Explanation	The checkbox for selecting all IS services is provided only for demonstration purposes.
Action	Create new services to be used with the Application Platform.

PLDNAVE0000	**{0} model class is missing its identifier.**
Explanation	Every graph node in the Visual Navigator must have a unique identifier, which is provided by the model node provider implementation.
Action	Check if the class type is produced by a custom model node provider implementation and try to resolve the problem.

PLDNAVE0002	**Exception creating model node for object type {0}. Details: {1}**
Explanation	An error occurred while creating the model content for a graph node.
Action	Check if this is a custom implementation and try to resolve the problem.

PLDNAVE0003	**A class type is required when creating a category for a model object. Category name: {0}**
Explanation	You must provide a class type for all categories that you create for model node providers.
Action	Check if this is a custom implementation and try to resolve the problem.

PLDNAVE0004	**Exception creating list of package fragments from {0}. Details: {1}**
Explanation	An error occurred while the Visual Navigator was rendering a graph for the class dimension.
Action	Verify that there are no compilation errors in your projects and try again.

PLDNAVE0005	**Exception loading method {0}'s references. Details: {1}**
Explanation	The Method dimension in the navigator view could not find a reference to the method in Designer when rendering the graph view.
Action	Check the details of the exception and try to resolve the problem.

PLDNAVE0006	**Exception creating model nodes for class type {0} from native object {1}. Details: {2}**
Explanation	The Visual Navigator uses the currently selected object as input when it switches from one dimension to another. An error occurred while extracting the model from this input for the next dimension graph.
Action	Check the details of the exception and try to resolve the problem.

PLDNAVE0007	**Exception loading projects {0}'s references. Details: {1}**
Explanation	The Project dimension in the navigator view could not find a reference to the project in Designer when rendering the graph view.
Action	Check the details of the exception and try to resolve the problem.

PLDNAVE0008	**Exception loading resource {0}'s references. Details: {1}**
Explanation	The Resource dimension in the navigator view could not find a reference to the resource in Designer when rendering the graph view.
Action	Check the details of the exception and try to resolve the problem.

PLDNAVE0010	**Error executing model node providers for dimension {0} in the navigator view. Details: {1}**
Explanation	The Visual Navigator encountered an error while building the object model for its graph view.
Action	Check the details of the exception and try to resolve the problem.

PLDNAVE0013	**Universe with id {0} does not exist.**
Explanation	You can register universes containing unique IDs through the Visual Navigator API. However, the specified ID does not match any registered universe.
Action	Contact Software AG Global Support.

PLDNAVE0014	**Model node classname is required when creating an instance key.**
Explanation	Every graph node, created in the Visual Navigator must have a unique ID, which includes the model node class name.
Action	Contact Software AG Global Support.

PLDNAVW0009	**Unable to load annotation provider {0} for the navigator view. Details: {1}**
Explanation	The Visual Navigator failed to load the annotation provider, which is required for extending the content added to the graph view.
Action	Check the details of the exception and try to resolve the problem.

PLDUTLE0000	**An error occurred while updating Application Platform {0} project classpath. Cause: {1}**
Explanation	The project classpath failed to updated. The project classpath is updated when Application Platform project facets are installed or removed.
Action	Manually update the project classpath in Designer.

PLDUTLE0001	**Unable to resolve OSGi service: {0}**
Explanation	Designer could not resolve the OSGi service. This suggests that the OSGi service interface has no implementations in the service registry. A possible reason is that the bundle contributing an implementation did not activate as expected or is missing from the container.
Action	Restart Designer and retry.

PLDWSE0000	**An error occurred while adding Application Platform classpath containers to the {0} project. Cause: {1}**
Explanation	Adding Application Platform classpath containers failed with an error. When Application Platform project facets are added to a project, additional classpath containers are also added to the project. This error can be caused by a corrupt Java project.
Action	Delete the Java project and create it again. While creating the project, make sure that you do not delete project contents.

PLDWSE0001 **An invalid number format was found for Application Platform server configuration key: {0}. Value: {1}**

Explanation The Application Platform server configuration key has an invalid number format. A numeric value is required.

Action Verify that the server configuration value is non-null and numeric.

PLDWSE0002 **An attempt was made to register an Application Platform WST server instance with no server name.**

Explanation A registration attempt was made for an Application Platform WST server instance with no server name. A server name is required.

Action Verify that the server configuration has a server name and restart the server instance.

PLDWSE0003 **An error occurred while removing Application Platform classpath containers from the {0} project. Cause: {1}**

Explanation Removing Application Platform classpath containers from the project faield with an error. When Application Platform project facets are removed from a project, additional classpath containers are also removed from the project. This error can be caused by a corrupt Java project.

Action Delete the Java project and create it again. While creating the project, make sure that you do not delete project contents.

ProfilesPageContentProvider_0 – Cannot resolve the server profiles from the base directory: {0}.

Explanation An error occured while resolving the server profiles using the base installation directory.

Action Check if the ECLIPSE_HOME classpath variable for Designer points to the correct location. The default location is SAG_INSTALL_DIR/Designer/eclipse.

5 Application Platform Server Messages

PLSAPPE0000	**Need instance of MethodMetadataImpl, can not use type: {0}**
Explanation	Not all implementations of the metadata interfaces can be used for service invocation.
Action	Change your service configuration to use an acceptable implementation.

PLSAPPE0001	**OsgiService.validate failed because it cannot work with null metadata.**
Explanation	The OSGi service object was not properly initialized because of null metadata.
Action	Contact Software AG Global Support.

PLSAPPE0002	**OsgiService.initializeService failed with exception: type({0}), msg({1})**
Explanation	The OSGi service was not properly initalized.
Action	Check the error logs for more details about this error.

PLSAPPE0003	**OsgiService.baseInvoke found a non-null svc object for {0} from an unexpected class loader; expected {1}, found {2}**
Explanation	The OSGi service invocation used a service class from an unknown, unexpected class loader. This has caused an OSGi container or a bundle configuration problem.
Action	Contact Software AG Global Support.

PLSAPPE0004	**OsgiService.baseInvoke: unable to get service object for {0} from registry**
Explanation	Integration Server is expected to register an OSGi service to expose Integration Server artifacts in Application Platform. The OSGi service could not be found.
Action	Contact Software AG Global Support.

PLSAPPE0005	**Error initializing App Platform generated service binding {0}. Details: {1}**
Explanation	Integration Server (IS) calls Application Platform services that are exposed to IS by using a generated IS service.
Action	Unpublish the Application Platform service project and republish it again.

PLSBDSE0000	**Bundle deployment changes could not be initiated.**
Explanation	The Software AG Common Platform OSGi service, responsible for installing a bundle into the container, is missing.
Action	Restart the server and try again.

PLSBDSE0001	**The required OSGi deployment service is missing.**
Explanation	The Software AG Common Platform OSGi service, responsible for installing a bundle into the container, is missing.
Action	Restart the server and try again.

PLSBDSE0006	**{0} failed due to error: {1}**
Explanation	The install/uninstall operation failed because of the indicated error. The project bundle operation did not complete successfully and had to be retried after fixing the error.
Action	Review the error logs for more details about this error.

PLSBDSE0007	**Bundle installed, but failed to activate due to error: {0}**
Explanation	The project bundle was successfully installed in the runtime but its activation failed due to the specified error.
Action	Verify that all required libraries, with which the project has dependencies, are installed and available in the runtime.

PLSBDSE0008	**Installation failed! Bundle not present in installed bundles list**
Explanation	A bundle deploy call failed to install the specified bundle in the runtime. A possible cause is that the bundle deploy call was made to a runtime that does not contain the bundle jar file in the staging directory.
Action	If both runtime instance you are using and the server runtime configured in Designer are local, verify that they are the same.

PLSBDSE0009	**An exception was raised while uninstalling bundle {0}. Cause: {1}**
Explanation	The server encountered a fatal error while attempting to uninstall the referenced bundle.
Action	Check the error logs for more details about this error.

PLSBDSE0010	**An exception was raised while installing bundle {0}. Cause: {1}**
Explanation	The server encountered a fatal error while attempting to install the referenced bundle.
Action	Check the error logs for more details about this error.

PLSBDSE0011	**The bundle was not installed. The server was unable to copy {0} bundle into the bundle repository.**
Explanation	The bundle installation failed because the bundle could not be copied to the bundle repository.
Action	Perform a clean build and republish the bundle, if it is a project bundle. Inspect the server's bundle repository directory and the staging directories to determine condition of the bundle jar.

PLSBDSE0014	**An error occurred while transferring chunk {0} of bundle {1} from source {2}. Cause: {3}**
Explanation	The server encountered an exception while processing a chunk of resource transferred from Designer.
Action	Check the error logs for more details about this error.

PLSBDSE0017	**No test bundle with symbolic name: ''{0}'' and version: ''{1}'' is installed in the runtime! Unable to run test method: ''{2}'' in class: ''{3}''**
Explanation	The bundle containing the JUnit App Platform Integration tests with the specified bundle symbolic name and version failed to install in the runtime.
Action	Deploy the project containing the integration tests to the running runtime instance before running the JUnit test through Designer.

PLSBRME0000	**The repository manager operation was not performed due to missing bundle key.**
Explanation	The repository manager operation failed because of a missing bundle key. Designer operations for publishing and unpublishing bundles from the server require a bundle key object.
Action	Contact Software AG Global Support.

PLSBRME0001	**Could not determine the location of the bundle repository from the location of the configured server.**
Explanation	Obtaining the bundle repository directory path failed. This directory contains project bundles and other bundles that are installed by the Bundle Publisher on the server's OSGi container. The bundle repository location is determined by the value, defined for the 'osgi.instance.area' configuration of the OSGi container running on the server.
Action	Verify that the server's config.ini file has a valid value for 'osgi.instance.area'.

PLSBRME0002	**Could not determine the server's OSGi instance area.**
Explanation	The 'osgi.instance.area' key, which is the value of the server's OSGi instance area could not be determined. The key is part of the required data included in the server's config.ini file. The problem may be caused by a corrupted config.ini file.
Action	Review the contents of the config. ini file.

PLSBRME0004	**Could not determine the bundle repository staging location from the location of the configured server.**
Explanation	Obtaining the bundle repository staging directory path failed. This is the directory path on the server where project bundles and other bundles, installed by the Bundle Publisher, are located when they are initially transferred to the server. This initial transfer is made prior to installing the bundles to OSGi container. The bundle repository location is determined by the value, defined for the 'osgi.instance.area' configuration of the OSGi container running in the server.
Action	Verify that the server's config.ini file has a valid value for 'osgi.instance.area'.

PLSBRME0007	**Unable to create directory path. {0}**
Explanation	The specified directory path could not be created.
Action	Verify that the specified path is valid on the file system and that there are no processes that are using it or that have locked it. Retry the operation afterwards.

PLSBRME0008	**An attempt was made to install or uninstall a bundle before the bundle has been transferred to the server's staging directory. {0}**
Explanation	Installing or uninstalling the bundle failed because the fundle is not transferred to the server. Bundles must first be transferred to the server before they can be installed or removed from its OSGi container.
Action	Retry the operation and verify that the bundle is transferred to the staging directory under the server profile's workspace.

PLSBRME0009	**An error occurred while refreshing the Application Platform project bundles in the bundle repository. {0}**
Explanation	Refreshing the Application Platform project bundles failed with an error. When you refresh the repository manager, the repository directory path is retrieved prior to registering the jars located there.
Action	Check the error logs for more details about this error.

PLSBRME0010	**Unable to refresh bundle file {0} in the bundle repository. {1}**
Explanation	Refreshing the bundle file in the bundle repository failed with an error. When you refresh the repository manager, it checks the OSGi manifest for each jar file in the directory. In this way the repository manager prepares for registering each bundle prior to installation.
Action	Check the error logs for more details about this error and try to determine if the jar file is corrupt.

PLSBRME0011	**Bundle {0}, which is transferred from Designer, does not match manifest {1} for this jar {2}.**
Explanation	The transferred bundle does not match the manifest for this jar. When Designer publishes bundles to the server, the bundle's name and version are included with the transfer request and they must match the name and version, declared in the jar file's OSGi manifest file.
Action	Perform a clean project build and repeat the operation.

PLSBRME0012	**Attempt to uninstall a bundle that is missing from the bundle repository manager. {0}**
Explanation	The Application Platform bundle repository manager maintains a map of all the bundles provisioned into the server. A bundle with this symbolic name and version was not found. This may have occurred because of changing the version of the project bundle without unpublishing the project bundle first.
Action	Unpublish the project bundle with the prior version and then update the project with the new version.

PLSBRME0013	**Attempt to uninstall a bundle missing from the bundle repository manager. {0}. (Note, another bundle version ({1}) is provisioned in the server.)**
Explanation	The Application Platform bundle repository manager maintains a map of all the bundles provisioned into the server. A bundle with this symbolic name and version was not found. This may have occurred because of changing the version of the project bundle without unpublishing the project bundle first.
Action	Unpublish the project bundle with the prior version and then update the project with the new version.

PLSCOME0001	**Unable to resolve the required OSGi service: {0}**
Explanation	A service implementation for the required OSGi service was not found in the OSGi registry.
Action	Check the error logs for more details about this error.

PLSCOME0002	**Data corruption was found on chunk {0} of bundle {1} during transfer from Designer to the server.**
Explanation	The hash computed by the server did not match the value computed by the sender. This may be caused by a faulty network or a modification from an intermediary.
Action	Verify that there are no network issues on proxy servers and so on.

PLSCOME0003	**Unable to delete this file: {0}**
Explanation	Your attempt to remove the file has failed according to your operating system.
Action	Verify that the file permissions are appropriate for the user that is running the server.

PLSCOME0004	**Unable to create this file: {0}**
Explanation	Your attempt to create the file has failed according to your operating system.
Action	Verify that the file permissions are appropriate for the user that is running the server.

PLSCOME0005	**Unable to create this directory path: {0}**
Explanation	Your attempt to create the directory path has failed according to your operating system.
Action	Verify that the file permissions are appropriate for the user that is running the server.

PLSCOME0006	**An illegal sequence was detected during a file transfer.**
Explanation	A chunk of a file resource that was transferred to the server had an unexpected sequence number.
Action	Repeat the failed operation.

PLSCOME0007	**Unable to read a non-existent file. {0}**
Explanation	An attempt was made to transfer a non-existent resource to the server.
Action	Verify that the expected files exist and repeat the operation.

PLSCOME0008	**The server does not have any of the expected message digest algorithms. {0}. At least one of these is required.**
Explanation	No message digest algorithms were found on the server. Application Platform needs a message digest to verify the integrity of data transferred from Designer to the server.
Action	Update Application Platform to include one of the digest algorithms.

PLSCOME0009	**File {0} is not a valid zip archive or it does not contain a manifest file.**
Explanation	The file is invalid. A Java archive file with manifest is expected.
Action	Review the file contents and update as necessary.

PLSCOME0010	**File {0} is not a valid bundle.**
Explanation	The file is invalid. An OSGi bundle with a valid manifest, containing the required OSGi headers, is expected.
Action	Review the file contents and update as necessary.

PLSCOME0011	**Connect operation timed out: {0}**
Explanation	A socket timeout error occurred when trying to connect to the JMX endpoint.
Action	Verify that target server is running and that the JMX port matches the server-side configuration.

PLSGWIE0000	**GatewayServiceImpl cannot work with NULL method metadata**
Explanation	The code, which calls GatewayServiceImpl, fails with an error. GatewayServiceImpl has no metadata and parameter details, which are required for identifying the service and invoking its method.
Action	Make sure that the code does not call the method, unless the required metadata is available.

PLSGWIE0001	**GatewayServiceImpl.delegateInvoke: unable to extract parameter values from IData for service ({0}.{1}); caught: ({2}), msg({3})**
Explanation	The conversion of IData contents to Java method parameters failed. This may be caused by a mismatch between expected parameter types (as specified in metadata) and actual pipeline values (as presented during runtime). Check the exception message for more information about the cause.
Action	Compare the actual parameter values with the expected types, specified in the metadata.

PLSGWIE0002	**GatewayServiceImpl.delegateInvoke: unable to invoke targeted service ({0}.{1}); caught: ({2}), msg({3})**
Explanation	The invocation of the indicated method failed. This may be caused by a mismatch between expected parameter types (as specified in metdata) and actual pipeline values (as presented during runtime). Another possible cause is that the expected service is not registered with OSGi. Check the exception message for more information about the cause.
Action	Verify that the expected OSGi service is registered. Compare the actual parameter values with the expected types, specified in the metadata.

PLSGWIE0003	**GatewayServiceImpl.delegateInvoke: unable to extract IData from the object returned by ({0}.{1}); caught: ({2}), msg({3})**
Explanation	The conversion of Java object to IData failed. This may be caused by a mismatch between expected parameter types (as specified in metadata) and actual pipeline values (as presented during runtime). Check the exception message for more information about the cause.
Action	Compare the actual parameter values with the expected types, specified in the metadata.

PLSGWIE0004	**Unable to convert class name string ({0}) to class object using loader from {1}; caught type({2}), msg({3})**
Explanation	The named class from the metadata could not be loaded. This may be caused by a dependency issue.
Action	Make sure that the bundle that is hosting the targeted service can access the class.

PLSGWIE0005	**Unable to find method {0}({1}) on class {2}; caught type({3}), msg({4})**
Explanation	The method, expecting the indicated parameter types list, could not be found on the indicated class. This may be caused by a mismatch between expected parameter types (as specified in metadata) and available method signatures. Check the exception message for more information about the cause.
Action	Verify that the metadata is consistent with the targeted class.

PLSGWIE0012	**Unable to invoke method ({0}), a problem occurred with the conversion of input pipeline: {1}**
Explanation	The Application Platform gateway service encountered a problem converting the Integration Server pipeline to Java method parameters.
Action	Contact Software AG Global Support.

PLSGWIE0013	**Cannot invoke method {0}.{1}, no OSGi service is registered for {1}**
Explanation	The OSGi service was not found. GatewayService requires registration of the OSGi service.
Action	Verify that the indicated service is exposed by an active Application Platform bundle.

PLSGWIE0014	**Failed attempt to execute App Platform service {0} due to missing required metadata.**
Explanation	App Platform service implementations published to the Integration Server must contain additional metadata in a META-INF/gatewayMetadata.xml file. This information is required to assist with the transformation to and from the Integration Server data model.
Action	Review the server logs for any errors. Inspect the project bundle and verify its metadata file is present. Redeploy the project, if necessary.

PLSGWIE0015	**Failed attempt to execute App Platform service {0}'s method {1}. The method signature does not match the signature expected by the Integration Server's generated service binding.**
Explanation	When Integration Server services execute service bindings of App Platform OSGi services, the IO signatures must match the OSGi service implementation.
Action	Republish the App Platform service project and verify that the generated IS service bindings are updated.

PLSGWIW0006	**IData2Pojo.createCollectionValue: unable to convert collection object type: {0}**
Explanation	The Application Platform gateway failed to convert the indicated collection type from IData to Java type.
Action	Contact Software AG Global Support.

PLSGWIW0007	**IData2Pojo.valueFromDataArray: unable to convert collection property type: {0}**
Explanation	The Application Platform gateway failed to convert the indicated property type from IData to Java type.
Action	Contact Software AG Global Support.

PLSGWIW0008	**IData2Pojo.constructList(): expected element {0} to be IData but found {1} instead.**
Explanation	An unexpected data type was found in an IData parameter array.
Action	Verify that the calling code uses appropriate data types.

PLSGWIW0009	**IData2Pojo.constructList(): expected pipeline to hold an array but found {0} instead.**
Explanation	An unexpected data type was found in an IData parameter array.
Action	Verify that the calling code uses appropriate data types.

PLSGWIW0010	**IData2Pojo.constructCollection(): unexpected collection type: {0}**
Explanation	Application Platform encountered an unexpected collection data type while converting from IData to Java object.
Action	Verify that the calling code uses appropriate data types.

PLSGWIW0011	**Pojo2IData.collectionToData: unexpected collection data type: {0}**
Explanation	The Application Platform conversion from Java object to IData encountered an unexpected collection data type.
Action	Verify that the calling code uses appropriate data types.

PLSOBEE0000	**Unable to invoke service {0} after trying with {1} principal names.**
Explanation	None of the principal names associated with the current session were allowed to invoke the designated service.
Action	Check the log for previous entries that show failed invocation attempts by each principal. Make sure that you use a valid Integration Server user ID for the IS service invocation.

PLSOBEE0002	**An exception was caught while attempting to identify the Subject for the current session; attempting to invoke authorization service {0}; caught: {1}**
Explanation	Attempting to identify the Subject for the current session failed with an exception. This exception may be caused by a problem with the Authorization Service in Software AG Common Platform.
Action	Contact Software AG Global Support.

PLSOBEE0003	**Cannot introspect a NULL service for IS package {0}, metadata: {1}.**
Explanation	An attempt was made to construct a PipelineGenerator around a null OSGi Service object. This could indicate a problem with the Application Platform project preparation.
Action	Check the package name and metadata details in order to identify the targeted service.

PLSOBEE0004	**Cannot introspect a NULL class for IS package {0}, service: {1}, methods: {2}.**
Explanation	An attempt was made to construct a PipelineGenerator around a null Class object. This could indicate a problem with the Application Platform project preparation.
Action	Check the package name and metadata details in order to identify the targeted class.

PLSOBEE0005	**Unable to parse source details string {0}; caught this: type ({1}), msg({2})**
Explanation	An error was encountered while attempting to parse an XML string into source details objects.
Action	Contact Software AG Global Support.

PLSOBEE0006	**Unable to read contents from bundle URL {0}; caught this: type ({1}), msg({2})**
Explanation	An error was encountered while attempting to extract the contents of a file.
Action	Contact Software AG Global Support.

PLSOBEE0007	**A failure occurred during JAX-B unmarshalling from URL {0}; caught this: type ({1}), msg({2})**
Explanation	An error was encountered while attempting to convert the contents of a file.
Action	Contact Software AG Global Support.

PLSOBEE0008	**Unable to load class {0} from bundle {1}; caught this: type ({2}), msg({3})**
Explanation	The OSGi bundle was expected to contain the identified class.
Action	Contact Software AG Global Support.

PLSOBEE0009	**Unable to create IS services representing method {0} from the {1} class, in IS package {2}; caught this: type ({3}), msg({4})**
Explanation	Creating IS services representing the method failed. The problem may originated in the IS service creation or in the preparation of the IS pipeline used for service creation.
Action	Contact Software AG Global Support.

PLSOBEE0010	**A mismatch was found between source details and source annotation; class ({0}) has annotation, but source details have no element: {1}**
Explanation	The source details and source annotation do not match because the annotation service does not have an entry in the source details. This could indicate a problem in the Application Platform project preparation.
Action	Contact Software AG Global Support.

PLSOBEE0011	**Improper initialization using IS Service({0}), authz service ({1}), user({2}), cannot use null IS Service reference.**
Explanation	The initialization failed because the Metadata Extender did not find one or more elements. The element may be unavailable only for a short period.
Action	Try a subsequent invocation.

PLSOBEE0012	**Unable to initalize Bundle Tracker for Application Platform extender; caught this: type ({0}), msg({1})**
Explanation	This is an internal bundle initialization error. The bundle tracker that monitors user bundles for IS service metadata files could not be initialized correctly due to the specified error.
Action	Contact Software AG Global Support.

PLSOBEE0013	**PackageInstaller cannot write IS package zip into replicate directory ({0}); caught: type({1}), msg({2})**
Explanation	The PackageInstaller failed to put the package Zip file into the IS installation. This can be caused by the permission configuration on the file system.
Action	Verify that the directory permissions on the file system allow this operation.

PLSOBEE0014	**An attempt to extract the file ({0}) from the Jar file failed; caught: type({1}), msg({2})**
Explanation	The IS package Zip file could not be extracted from the Application Platform extender bundle.
Action	Contact Software AG Global Support.

PLSOBEE0015	**PackageInstaller cannot obtain a reference to Bundle Context after waiting {0} {1}; caught: type({2}), msg({3})**
Explanation	A problem was encountered while waiting for the extender bundle context.
Action	Contact Software AG Global Support.

PLSOBEE0016	**An attempt to invoke the IS service ({0}) failed; caught: type({1}), msg({2})**
Explanation	The Application Platform Package Installer failed to invoke the IS service(s), which are required for installation.
Action	Contact Software AG Global Support.

PLSOBEE0017	**IS Service({0}) returned NULL IData**
Explanation	The Application Platform Package Installer received a null result from the IS service.
Action	Contact Software AG Global Support.

PLSOBEE0018	**Improper initialization using IS Service({0}), authz service ({1}), user({2}), cannot use null authorization service reference.**
Explanation	The Metadata Extender could not find one or more expected elements. The elements may be unavailable only for a short period.
Action	Try a subsequent invocation.

PLSOBEE0019	**Improper initialization using IS Service({0}), authz service ({1}), user({2}), cannot use null/empty user ID.**
Explanation	The Metadata Extender could not find one or more expected elements. The elements may be unavailable only for a short period.
Action	Try a subsequent invocation.

PLSOBEE0020	**Unable to load class for service: {0}, from bundle BSN/ID: {1}/{2}, IS package: {3}**
Explanation	An interface named for exposure as an IS service could not be found. This means that the .class file for the interface could not be found.
Action	Verify that the fully qualified path to the interface is present in the classpath and that it is spelled correctly.

PLSOBEE0022	**Unable to load {0} bundle with state: {1}. Details: {2}**
Explanation	Application Platform was unable to access the bundle because of its state.
Action	Contact Software AG Global Support.

PLSOBEE0023	**Unable to remove IS services representing method {0} from the {1} class, in IS package {2}; caught this: type ({3}), msg({4})**
Explanation	Failed to remove the IS services that represent the method. The problem may originate in the IS service creation, or in the preparation of the IS pipeline used for service creation.
Action	Contact Software AG Global Support.

PLSOBEE0024	**Unable to create Integration Server client bindings for annotated OSGi service(s) in bundle {0}.**
Explanation	The generated project bundle is missing its OSGi manifest headers.
Action	Verify that the project bundle's META-INF/MANIFEST.MF file is valid for the App Platform project bundle.

PLSOBEE0025	**The project bundle containing service class {0} is missing its gatewayMetadata.xml file.**
Explanation	When a project bundle that contains App Platform services is published to the server runtime conatiner, a dedicated metadata file is created and inserted in that project bundle. The metadata file is missing, or it is corrupted.
Action	Review the Integration Server OSGi server logs for errors. If the project bundle is created by using Asset Build Environment (ABE), review the configuration settings and inspect the ABE logs for errors.

PLSOBEE0026	**The project bundle containing service class {0} is missing its Integration Server package annotation.**
Explanation	App Platform service implementations, which are exposed to Integration Server, must include the @ExposeToIS class annotation with packageName attribute set to a valid Integration Server package.
Action	Verify that the source file is properly annotated and the package name is defined in the gatewayMetadata.xml file included in the deployed project bundle.

PLSOBEE0027	**Metadata mismatch for App Platform service class {0}'s {1} method. The number of parameters detected in the class ({2}) does not match the number defined in the gatewayMetadata.xml file ({3}).**
Explanation	The metadata of the project bundle's META-INF/gatewayMetadata.xml file does not match the method signature of the currently deployed service.
Action	Rebuild and deploy the project bundle.

PLSOBEE0028	**Exception while introspecting App Platform service class {0}. Details: {1}**
Explanation	When an App Platform service contains complex request or response messages, Java Bean Introspection is used. The Java Bean Introspection analyzes the class types in order to produce the necessary metadata to marshal the data to and from Integration Server.
Action	Review the class and verify that it is a proper Java Bean.

PLSOBEE0029	**Illegal use of App Platform services with a recursive data model. Affected class: {0}.**
Explanation	App Platform service implementations with recursive object models are not supported.
Action	Do not use App Platform service implementations with recursive object models.

PLSOBEI0001	**An exception was caught while invoking IS service {0} with user {1}: {2}**
Explanation	The designated service could not be invoked.
Action	Check the exception message for more information about the cause of the failure. Attempt the same invocation with the service invoker using different user IDs. If one attempt succeeds, the failures may be ignored.

PLSOBEW0021	**Cannot change user ID to null/empty value, keeping previous value {0}**
Explanation	The default user ID was dynamically updated with an inappropriate value.
Action	Provide a non-empty value string.

PLSSECE0000	**Unauthorized! Method {0} execution not allowed**
Explanation	The specified method cannot be invoked by the currently logged user. The method has the @DenyAll annotation specified directly on it, or inherited from the type level.
Action	Change the method access security level by removing @DenyAll annotation and specifying the users that are allowed by using the @RolesAllowed annotation.

PLSSECE0001	**Unauthorized! Methods in type {0} cannot be invoked!**
Explanation	The methods in the specified class cannot be invoked because the @DenyAll annotation is invoked on them.
Action	Remove the @DenyAll annotation from the class level. Optionally, also specify explicitly the user roles that are allowed.

PLSSECE0002	**Unauthorized! User not in allowed roles to execute this method**
Explanation	The user that is currently logged in does not belong to the list of allowed roles to execute this method.
Action	Login as a user with a role that belongs to the list of allowed roles to execute the method and call the method again.

PLSSECE0003	**No valid authenticated subject found! An authenticated user is required when invoking this method.**
Explanation	In order to access this service method, you must be logged in with a user tat has a valid account for the connected runtime.
Action	Ensure that the logged in user accound has access rights to invoke the methods in the service.

PLSSECE0005	**Error injecting SecurityContext instance in field {0}! Reason: {1}**
Explanation	An error occurred while injecting an instance of the SecurityContext class into the field with the same type in the POJO service.
Action	Review the error log for more details about this error.

PLSSECW0004	**No security annotations found for @Secure annotated service type!**
Explanation	The service class with @Secure annotation does not contain any expected security annotations. Unless runtime authorization checks are performed, invocations will be allowed for all service methods.
Action	Ensure that correct authorization checks are performed for the methods in this service.

PLSSISE0000	**Error creating filter {0} IS_Transport login realm delegate may not be initialized properly! Reason: {1}**
Explanation	An error occurred while initializing the OSGi filter in order to obtain the IS_Transport Login Realm service.
Action	Review error logs for more information about this error.

PLSUPGC0006	**Unexpected error while verifying product source directory: {0}. Cause: {1}**
Explanation	The migration utility encountered an unexpected error.
Action	Confirm that the source directory path contains a product installation.

PLSUPGE0002	**App Platform server migration did not complete successfully. Cause: {0}**
Explanation	An error occurred while executing the server migration steps.
Action	Contact Software AG Global Support.

PLSUPGE0003	**Unable to determine App Platform product version for source installation using this product property file. {0}**
Explanation	The migration utility requires a product source version in order to determine the required migration tasks.
Action	Provide the product version by using the migration utility "-srcVersion" parameter.

PLSUPGE0005	**No servers are installed in this directory. {0}**
Explanation	To be rendered as a valid path, the specified directory must contain a 'profiles' directory, which contains one or more servers.
Action	Select another directory path that contains server profiles.

PLSUPGE0007	**Please ensure the current working directory contains the App Platform migrate.sh|bat script.**
Explanation	The migration utility locates required components by using relative paths, which are offset from the current working directory.
Action	Update the working to a directory that contains the required Application batch script.

PLSUPGE0008	**The product properties file does not exist. {0}**
Explanation	Application Platform uses the product properties file in order to automatically detect the product version during migration.
Action	Ensure that the directory path is correct and it contains the product properties file.

PLSUPGE0009	**Unable to locate version string in product properties file.**
Explanation	The Application Platform migration script uses the product property file to detect the version, installed in the specified directory.
Action	Verify that the directory path is correct.

PLSUPGE0011	**Overinstall is not supported. The source and destination paths must be different.**
Explanation	The migration script can be run only in for side-by-side upgrade.
Action	Ensure that the source and the destination directories are different.

PLSUPGE0012	**Error resolving canonical path for directory: {0}. Cause: {1}**
Explanation	Application Platform uses relative paths to locate key directories. An error occurred while resolving a path to its canonical form. For example, this can happen when the parent path references have been removed (/../).
Action	Verify that the directory path exists.

PLSUPGE0021 **Error copying project file "{0}" to destination directory: {1}. Cause: {2}**

Explanation An error occurred while migrating the file to the destination directory.

Action Copy the file manually.

PLSUPGE0040 **Error creating the war file in {0} directory from the migrated IS package ({1}) web project. Reason: {2}**

Explanation The migration tool was unable to upgrade this IS package due an unexpected error.

Action Migrate this IS package manually.

PLSUPGI0022 **{0} files NOT migrated due to errors.**

Explanation An error occurred while migrating some the files.

Action Review the migration log in the installation directory's 'install/logs' folder to determine which project files were affected. Copy the required files manually.

PLSUPGI0029 **Project bundle files**

PLSUPGI0030 **{0} existing project bundles copied to destination (files from the destination were copied to the archive directory before overwriting).**

Explanation The target installation contained project bundle file(s), and these files were replaced with the migrated ones. Copies of these files may be found in the archive directory under the common/migrate/ directory.

Action No action necessary.

PLSUPGI0034

PLSUPGI0035 **Integration Server WmTomcat packages converted to Web Archives**

PLSUPGI0038 **{0} IS packages NOT migrated to war files due to errors.**

Explanation An error occurred while migrating some of the web application files.

Action Review the migration log in the installation directory's 'install/logs' folder to determine which project files were affected. Migrate the IS project manually.

PLSUPGI0041	**Note: Tomcat configuration cannot be upgraded automatically. Compare the WmTomcat source configuration (found here {0}) to the Tomcat target configuration (found here {1}), and make changes as needed.**
Explanation	The Apache Tomcat upgrade documentation advises its users to not simply copy configuration files when upgrading to newer versions of Tomcat of a different major version.
Action	Review and update the Tomcat configuration settings as needed.

PLSUPGW0010	**Unable to detect product version for the specified directory. Cause: {0}**
Explanation	Application Platform was unable to determine the version of the installation path that was provided. This may have happened because the 'install/products' directory was deleted.
Action	Enter the version manually.

PLSUPGW0017	**These instances are missing in the destination installation. {0}**
Explanation	The source installation contains server instances that do not exist in the target installation. These servers will not be migrated for Application Platform.
Action	If required, create the missing server instances. Otherwise, proceed with the migration.

PLSUPGW0019	**Project file ''{0}'' overwritten in destination directory: {1}**
Explanation	The migration utility detected that a project file already exists in the destination directory. The contents are not overwritten.
Action	If you require to replace the old file with the new one, review the new file and copy it manually. This will overwrite the old file in the destination directory.

PLSUPGW0028	**Unable to archive existing files. Cause: {0}**
Explanation	If possible, the migration utility saves existing files before overwriting with migrated versions.
Action	No action is required. The migration will progress normally. However, the original files will not be retained.

PLSUPGW0031	**No zip entries detected in project file ''{0}''.**
Explanation	This suggests the project file was either an empty archive or its contents could not be migrated.
Action	Verify the file is a valid zip archive and copy it manually to the destination directory if necessary.

PLSUPGW0032	**Bundle {0} is missing its manifest.**
Explanation	OSGi bundles require manifests in the META-INF/MANIFEST directory of the archive. The migration tool will skip this bundle.
Action	No action required.

PLSUPGW0033	**Project bundle {0} contains a package {1} with import version range {2} that must be upgraded manually.**
Explanation	The migration utility has detected a customer project bundle, which has a dependency to a different version of the Application Platform API.
Action	Update the source project to use the new Application Platform API version.

PLSWRPE0002	**Unable to invoke service {0} after trying up to {1} principal names; caught: {2}**
Explanation	Invoking the service failed. This can be caused by a credentials issue, in which none of the principals associated with the current session was allowed to invoke the designated service. Another possible cause is a problem with the input parameters.
Action	Check the error logs for more details about this error. If the problem is caused by an authentication or authorization error, then search the log for more details about which prinicpal names were successful or not. Verify that you are using a valid Integration Server user ID.

PLSWRPE0003	**An exception was caught while marshalling input object to IData for service {0}: {1}**
Explanation	The conversion of input bean to IData for the designated service failed with an exception.
Action	Check the exception message for more information about this error.

PLSWRPE0004	**An exception was caught while unmarshalling IData to output object for service {0}: {1}**
Explanation	The conversion of IData to output bean for the designated service failed with an exception.
Action	Check the exception message for more information about this error.

PLSWRPE0005	**Input argument to ServiceWrapper.invoke() needs 'InputData' annotation.**
Explanation	The invoke method requires specific type characteristics.
Action	Use a different input type, or add the required annotation.

PLSWRPE0006	**Return type for ServiceWrapper.invoke() needs 'OutputData' annotation**
Explanation	The invoke method requires specific output type characteristics.
Action	Use a different return type, or add the required annotation.

PLSWRPE0007	**Unable to fill data for key {0} with parameter ({1}), dim>1 not yet supported**
Explanation	This is a temporary shortcoming in the implementation.
Action	Contact Software AG Global Support.

PLSWRPE0008	**Unable to fill object {0} for key ({1}), dim>1 not yet supported**
Explanation	This is a temporary shortcoming in the implementation.
Action	Contact Software AG Global Support.

PLSWRPE0010	**An exception was caught while attempting to identify the Subject for the current session in order to invoke IS service {0}; current user is identified by {1}, exception: {2}**
Explanation	Identifying the Subject for the current session failed with an exception. This can indicate a problem with the Authorization Service in the Software AG Common Platform.
Action	Contact Software AG Global Support.

PLSWRPE0012	**ServiceWrapper cannot work with NULL return type.**
Explanation	An attempt was made for ServiceWrapper to work with a NULL return type. This can be caused by a problem with the Authorization Service source code generation.
Action	Contact Software AG Global Support.

PLSWRPI0009	**An exception was caught while invoking IS Service ({0}) with user ({1}): {2}**
Explanation	Invoking the designated service failed with an exception. Check the exception message for more information about the cause of failure.
Action	Attempt the same invocation with the service invoker using different user IDs. If one attempt succeeds, the failures may be ignored.

6 Business Rules Messages

AbstractMainPage_projectOutdatedError – The project is outdated. Please upgrade to the current version.

Explanation The version of the rule project to be exported is outdated.

Action Right-click the rule project in the Rules Explorer view and select Upgrade project.

AbstractMainPage_serverVersionOutdated – The server version is outdated. Please upgrade the server to the current version.

Explanation The version of the rules environment on the server is older than the version of the rule project to be exported.

Action Upgrade the server.

ActionSelectionWizardPage_InputOrOutputDataModelIsMissing – The selected action is invalid, because one of its data models is missing.

Explanation An action can have multiple data models. The data model files are referenced in the xml of the action. If one or more of the data models are missing, this error occurs. Action data models are not shown in the Rules Explorer view.

Action Clean all projects in Software AG Designer. If that did not help and the data models are not shown in the Navigator view, the action might be corrupted. Try to create an action that uses the same type of data models. If this should fail, please contact your system administrator.

EditorProjectToNewComposite_ErrorDescription – Could not open the editor:

Explanation There is an asset in the specified rule project that has a version newer than the version of the installed Rules Development plugin.

Action Update the Rules Development plugin of Software AG Designer.

EditorProjectToNewComposite_ErrorMessage – The rule project "{0}" was created with a newer version of Software AG Designer ({1}). Please upgrade the Rules Development feature.

Explanation There is an asset in the specified rule project that has a version newer than the verison of the installed Rules Development plugin.

Action Update the Rules Development plugin of Software AG Designer.

EditorUpgradeComposite_ErrorMessage – The rule project "{0}" is outdated.

Explanation The rule project "{0}" is outdated. It needs to be updated first.

Action Right-click the rule project in the Rules Explorer view and select "Update".

EditorUtility_file_must_not_be_null – File must not be null

Explanation An error occurred while opening the editor for the file.

Action Try to refresh your rule project. See error log for additional information.

EditorUtility_no_active_WorkbenchPage – No active workbench page

Explanation No active workbench could be obtained for opening the file.

Action Try to restart Software AG Designer. See log for additional errors.

EditorUtility_no_editorInput – Could not get an editor input for the given element

Explanation No editor input could be created for the file.

Action Check, if the file is corrupt. See log for detailed information about the error.

EventModelSourceSelectionPage_FileNotFoundError – There is no file at the specified location.

Explanation In the textbox on page two of the New Event Model wizard, the given location for the schema file is invalid.

Action Use the browse button on the same page to search for an existing schema file, or enter a valid location for a schema file.

EventModelSourceSelectionPage_File_Not_Parsed – Error while importing Event Type. File could not be parsed.

Explanation Problem while trying to parse an NSRecord from the chosen XSD.

Action Make sure the chosen file is an event type (payload), or select a different file.

EventModelSourceSelectionPage_Stream_Null – Error while retrieving contents of Event Type.

Explanation NSRecords could not be created from the given schema file.

Action Make sure the selected schema file is a valid event type (payload), or select a different file.

ExportWizard_ExportFailedMessage – Export failed

Explanation Export failed.

Action Please consult the log file for further information.

ExportWizard_ExportFailedReason – Could not export project. Make sure you have selected the right server and that it is configured correctly. See documentation, the Eclipse Error Log and check the IS Server log for more detailed information about the error.

Explanation The rule project could not be exported.

Action Make sure that you have selected the right server and that it is configured correctly. For more information, consult the product documentation and the Eclipse Error Log.

ISExporter_ServerNotFound – Couldn't find server: "{0}"

Explanation The specified Integration Server could not be found.

Action In Software AG Designer preferences, check if the selected Integration Server is available and configured properly.

MWS_InternalError An internal server error occurred. To resolve the problem please check the My webMethods Server log.

Explanation This happens when an error in Rule Management Console occurs.

Action Check the Eclipse and MWS log for more information.

MainIsExportPage_pingServiceNotExisting – Unable to contact the Rule engine server.

Explanation An error occured while invoking the ping service on the Integration Server.

Action Try again. Check the versions of Software AG Designer and the Integration Server. Check connection.

MainMwsImportPage_ProjectToNewErrorMessage – The remote rule project "{0}" was created with a newer version of Software AG Designer ({1}). Please upgrade the Rules Development feature.

Explanation Cannot import a rule project that was created with a newer version of the Rules Development feature.

Action Upgrade the Software AG Designer plugins.

MainMwsImportPage_WillUpgradeImportedProjectInfo – Outdated rule projects will be automatically upgraded to the current version of the Rules Development feature.

Explanation The rule project in the My webMethods Server repository is outdated. It will be updated in a temporary location before it is copied into the workspace.

Action n/a

MetaphorCorrectionProcessor_error_quickassist_message – An error occurred while computing quick assists. Check log for details.

Explanation An error occurred while computing quick assists.

Action Check log for details.

MetaphorCorrectionProcessor_error_quickfix_message – An error occurred while computing quick fixes. Check log for details.

Explanation An error occurred while computing quick fixes.

Action Check log for details.

MetaphorCorrectionProcessor_error_status – Exception while processing quick fixes or quick assists

Explanation An error occurred while computing quick fixes or quick assists.

Action Check log for details.

MetaphorSuppressWarningsProposal_Error_Msg – An exception occurred while applying the quick fix

Explanation An error occurred while applying the quick fix.

Action Please see the dialog and/or error log for additional information on the error.

NewEventModelWizard_ErrorCreatingEventModel – Error creating event model

Explanation An error occurred while importing the event type .xsd-file. NSRecord (event model) files may have not been created.

Action Try again, or try another schema file. Refer to the logged exception.

ParameterSelectionComposite_SelectAtLeastOne_Error – Select at least one data model for a parameter.

Explanation No data model is selected as an input or output parameter.

Action On the current wizard page, select a data model and move it to the right to make it available as parameter.

Resources_OutOfSyncResources_Msg – Some resources are out of synch

Explanation One or more resources are out of synch with the file system. They need to be refreshed inside Software AG Designer.

Action Please refresh your rule project.

Resources_OutOfSync_Msg – Resource ''{0}'' is out of synch with the file system

Explanation One or more resources are out of synch with the file system. They need to be refreshed inside Software AG Designer.

Action Please refresh your rule project.

RuleFile_ErrorParsingDTXMLForProcessingMode – Error parsing decision table XML for ProcessingModeType.

Explanation An error occurred while parsing one of the selected files.

Action Try to deselect the files and retry your selection.

RuleLocalLaunchRunner_ErrorUndeploying_Msg – An error occurred while undeploying the rule project [%s].

Explanation The execution of the launch was terminated abnormally, and an attempt was made to clean up the rule project. The attempt failed.

Action Start Software AG Designer with -clean option. If the problem persists, send the details of this exception to your technical support.

WOKDELE0016 Unable to invoke REST call to get Business Rules dashboard

WOKDELI0013 Close

WOKDELI0014 Click to view/edit decision entity

WOKDELI0015 View/Hide

WOKDTDE0003 Unable to retrieve Business Rules decision entity from REST service.

WOKDTDE0004 **Selected decision entity not found.**

WOKDTDE0005 **Rule project name not found**

WOKDTDE0006 **Rule decision entity name not found**

WOKDTDI0000 **Decision Table**

WOKDTDI0001 **More...**

WOKDTDI0002 **No Data Available**

WOKDTDI0007 **In Effect**

WOKDTDI0008 **ALWAYS**

WOKDTDI0009 **Inferential**

WOKDTDI0010 **Sequential First**

WOKDTDI0011 **Sequential All**

WOKDTDI0012 **OTHERWISE**

WOKDTDI0013 **Loading...**

WOKDTDI0022 **Last 60 days**

WOKDTDI0023 **Last 365 days**

WOKDTSE0007 **Unable to retrieve Business Rules decision entity from REST service.**

WOKDTSI0000 **Info**

WOKDTSI0001 **Processing Mode:**

WOKDTSI0002 **Description:**

WOKMRIE0011 **Operation not supported**
Explanation The operation attempted to be executed is not supported

WOKMRIE0012 **{0} is required**
Explanation If configuration is enabled, {0} is required

WOKMRIE0016 **The URL "{0}" is invalid**
Explanation The URL resulting from the entered values is invalid.

WOKMRII0006 **The Integration Server is online.**
Explanation The Integration Server is online.

WOKMRII0009 **Business verification**
Explanation Business verification REST server configuration
Action Configure here the one single REST server for doing business verification

WOKMRII0010 **Master Integration Server**
Explanation Connection Master Integration Server (wM Business Rules)

WOKMRII0013 **The configuration is valid.**

Explanation The configuration is valid.

WOKMRII0014 **Data provider**

Explanation Data provider REST service configuration

Action Configure here the one single REST service for the Data provider

WOKMRII0015 **Principal types**

Explanation Principal types configuration

Action Here you can configure the principal types that should be visible in the PrincipalPicker

WOKMRII0017 **Auditing**

Explanation Auditing configuration

WOKMRIW0000 **An internal error occured**

Explanation Integration Server URL is not accessible: {0}

Action Please check specified host and port and make sure Integration Server is running.

WOKMRIW0001 **Integration Server credentials are missing.**

Explanation Username and password are needed for authentication.

Action Please provide values for username and password.

WOKMRIW0002 **Integration Server password is missing.**

Explanation The password is needed for authentication.

Action Please provide a password for the Integration Server.

WOKMRIW0003 **Integration Server host and/or port are missing.**

Explanation A valid hostname and port are needed to access Integration Server.

Action Please provide host and port to access Integration Server.

WOKMRIW0005	**The server specified is not an Integration Server**
Explanation	A server has been contacted with the information provided. However it does not seem to be an Integration Server.
Action	Please check whether the server specified is an Integration Server. If this is the case this warning can be ignored.

WOKMRIW0008	**Authentication failed.**
Explanation	Authentication failed with the credentials provided. Please check username and password.
Action	Please check username and password.

7 CentraSite Messages

E_assertionNotFound30000 – Signifies that a particular publisher assertion (consisting of two businessKey values, and a keyed reference with three components) cannot be identified in a save or delete operation.

Explanation The specified publisher assertion does not exist in the registry.

Action Please make sure the publisher assertion exists before deleting or updating it.

E_authTokenRequired10120AUTH – The authentication token value is missing in the authInfo argument of the UDDI request.

Explanation The authInfo element is not present in the UDDI request. CentraSite requires the authInfo element to be present in the request with a valid authToken.

Action Please make sure that authInfo is present in UDDI request.

E_authTokenRequired10120DEF – Signifies that an invalid authentication token was passed to an API call that requires authentication.

Explanation The authentication token passed is not valid.

Action Please fetch the authentication token using get_authToken API and use it in the API.

E_authTokenRequired10120INVAUTH – The authentication token value {0} passed in the authInfo argument of the UDDI request is not valid.

Explanation The authentication token passed is not valid.

Action Please fetch the authentication token again using get_authToken API and use it in the API.

E_fatalError10500 **{0}**

Explanation Fatal error occurred while processing the request.

Action Please retry and make sure the UDDI request is valid.

E_fatalError10500APPDOWN – UDDI application not properly initialized. Please try restarting the CentraSite server.

Explanation UDDI application received UDDI API calls before the UDDI web application initialized properly.

Action Restart the CentraSite server.

E_fatalError10500CUSTOWN – Custody and Ownership Transfer API calls are not supported when security policy is Deactivated

Explanation CentraSite needs a security policy to be activated for processing the Custody and Ownership Transfer API.

Action Please activate a security policy.

E_fatalError10500INFOSEL – Attribute infoSelection is not present in request.

Explanation The get_registeredInfo API requires the infoSelection attribute. If it is not present in the request then this error will occur.

Action Please make sure the infoSelection attribute is present in the get_registeredInfo request.

E_fatalError10500INVFINDGET – Invalid find_xx or get_xx api specified in the subscriptionFilter

Explanation The subscriptionFilter does not contain the valid UDDI v3 subscription filter.

Action Please make sure the subscription filter in the save_subscription request is valid.

E_fatalError10500KREFNATB – KeyedReference does not contain required attribute.

Explanation The KeyedReference should contain the keyValue attribute.

Action Please make sure the keyedReference in the request has attribute keyValue.

E_fatalError10500MISCFAT – Saving subscription failed due to internal registry error.

Explanation Internal registry error.

Action Please retry the request.

E_fatalError10500MSE – Search limit exceeded, maximum allowed is {0}. Contact node operator to increase the search limit.

Explanation Maximum search limit reached.

Action Please reduce the number of search keys in the inquiry request or increase the search limit via the System Management Hub.

E_fatalError10500PERF – Performance metrics with key {0} cannot be saved. Please make sure Performance Log is enabled in SMH.

Explanation The user is trying to save performance metrics, but the performance log is disabled in SMH. Performance metrics will be saved only if the performance log is enabled in SMH.

Action Please make sure the performance log is enabled in SMH.

E_fatalError10500SUBKEXP – The subscription with subscriptionKey {0} has expired. Please renew this subscription.

Explanation The subscription has expired as the specified expiration date has been reached.

Action Please renew the subscription by saving it with a new expiration date.

E_invalidCombination40500QUA – The combination of Qualifiers is not allowed

Explanation Invalid find qualifier combinations were found in the request.

Action Please make sure the combination of find qualifiers present in the inquiry request is valid. The invalid combinations are: andAllKeys, orAllKeys and orLikeKeys are mutually exclusive; sortByNameAsc and sortByNameDesc are mutually exclusive; sortByDateAsc and sortByDateDesc are mutually exclusive; combineCategoryBags, serviceSubset and bindingSubset are mutually exclusive; exactMatch and approximateMatch are mutually exclusive; exactMatch and caseInsensitiveMatch are mutually exclusive; binarySort and UTS-10 are mutually exclusive, as are all collation algorithm tModels with each other; diacriticSensitiveMatch and diacriticInsensitiveMatch are mutually exclusive; exactMatch and diacriticInsensitiveMatch are mutually exclusive; caseSensitiveSort and caseInsensitiveSort are mutually exclusive; caseSensitiveMatch and caseInsensitiveMatch are mutually exclusive.

E_invalidCompletionStatus30100 – {0} is not a valid completion status.

Explanation An invalid value was passed for completion status argument. Valid completion status are status:complete, status:fromKey_incomplete, status:toKey_incomplete and status:both_incomplete.

Action Please provide a proper completion status.

E_invalidKeyPassed10210 – No matching key found in the registry for {0}.

Explanation CentraSite does not contain any UDDI entity with the key specified in the UDDI request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210BEBEK – Could not find the business entity corresponding to the business key.

Explanation CentraSite does not contain any business entity with the key specified in the UDDI request.

Action Please make sure the business key specified in the request is valid.

E_invalidKeyPassed10210BEBK – Could not find the business service corresponding to the binding key {0}.

Explanation CentraSite does not contain a business service corresponding to the service key specified in the binding template.

Action Please make sure the service key specified in the request is valid.

E_invalidKeyPassed10210BEMAT – No businessEntity in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain any business entity with the key specified in the UDDI request.

Action Please make sure the business key specified in the request is valid.

E_invalidKeyPassed10210BKBE – Tried to get a businessEntity with key {0}, but key did not match with any existing businessEntities.

Explanation CentraSite does not contain any business entity with the business key specified in the UDDI request.

Action Please make sure the business entity with the specified business key exists in CentraSite.

E_invalidKeyPassed10210BKINV – BusinessKey invalid.

Explanation The BusinessKey specified in the request is invalid.

Action Please make sure the specified businessKey is valid.

E_invalidKeyPassed10210BKMAT – No bindingTemplate in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain a binding template with the key specified in the UDDI request.

Action Please make sure the binding key specified in the request is valid.

E_invalidKeyPassed10210BSMAT – No businessService in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain a business service with the key specified in the UDDI request.

Action Please make sure the service key specified in the request is valid.

E_invalidKeyPassed10210BSNE – A businessService with key {0} does not exist.

Explanation CentraSite does not contain a business service with the key specified in the UDDI request.

Action Please make sure the service key specified in the request is valid.

E_invalidKeyPassed10210BSNF – Could not find the businessService corresponding to the service key {0}

Explanation CentraSite does not contain a business service corresponding to the service key specified in the binding template.

Action Please make sure the service key specified in the request is valid.

E_invalidKeyPassed10210BT – The bindingKey of the bindingTemplate to save does not match any existing bindingTemplate in the UDDI registry.

Explanation CentraSite does not contain a binding template with the key specified in the UDDI request.

Action Please make sure the binding key specified in the request is valid.

E_invalidKeyPassed10210BTNF – Could not find the binding Template corresponding to the binding key {0}

Explanation CentraSite does not contain a binding template with the key specified in the UDDI request.

Action Please make sure the binding key specified in the request is valid.

E_invalidKeyPassed10210BTSK – The bindingTemplate to save does not contain a serviceKey.

Explanation The binding template to be saved does not contain the service key required for this binding template. The service key has to be specified when saving a binding template.

Action Please specify a valid service key in the UDDI request.

E_invalidKeyPassed10210CAT – Invalid tModelKey in categoryBag.

Explanation The category bag should contain keyedReference/KeyedReferenceGroups with valid values for tModelKey and KeyValue.

Action Please specify valid values for tModelKey/KeyValue in the category bag.

E_invalidKeyPassed10210DBE – Tried to delete a businessEntity with key {0}, but key did not match with any existing businessEntities.

Explanation CentraSite does not contain any business entity with the business key specified in the delete request.

Action Please make sure the business key specified in the request is valid.

E_invalidKeyPassed10210DEF – Signifies that the uuid_key value passed did not match with any known key values.

Explanation CentraSite does not contain any UDDI entity with the key specified in the UDDI request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210DELSUB – Tried to delete a subscription with key {0}, but key did not match with any existing subscriptions.

Explanation CentraSite does not contain any subscription with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210EMTTMBAG – Tmodel bag is empty

Explanation TModelBag cannot be empty, but the UDDI request contains an empty tModelBag.

Action Please make sure tModelBag contains the required values.

E_invalidKeyPassed10210FRMK – No businessEntity in the UDDI registry matched the fromKey {0}

Explanation The fromKey specified in the add_publisherAssertion request is either invalid, or no business entity matched the fromKey.

Action Please make sure the fromKey specified in the request is valid.

E_invalidKeyPassed10210HIDTM – Tried to delete a tModel with key {0} which is not hidden.

Explanation Hidden Tmodels cannot be deleted.

Action Hidden tModels cannot be deleted. Please update the tModel and delete it.

E_invalidKeyPassed10210IBAG – Invalid tModelKey in identifierBag.

Explanation The identifier bag should contain keyedReference/KeyedReferenceGroups with valid values for tModelKey and KeyValue.

Action Please specify valid values for tModelKey/KeyValue in the identifier bag.

E_invalidKeyPassed10210INVKEY – The Key {0} is invalid.

Explanation The specified key is not valid.

Action Please make sure the key is valid according to the UDDI standard.

E_invalidKeyPassed10210INVTMK – Invalid tModelKey {0}.

Explanation CentraSite does not contain a TModel with the key specified in the UDDI request.

Action Please specify a valid tModelKey in the UDDI request.

E_invalidKeyPassed10210KBAGK – key {0} passed in the key bag does not match any businessEntity or tModel.

Explanation CentraSite does not contain a business entity or tModel with the key specified in key bag of the discard_transferToken request.

Action Please specify a valid business key or tModel key in the key bag.

E_invalidKeyPassed10210KREF – KeyedReference should be passed !

Explanation The publisher assertion should contain a keyedReference and it is missing in the UDDI request.

Action Please specify a KeyedReference for the publisher assertion.

E_invalidKeyPassed10210MITS – Multiple instances of the same {0} {1} were passed.

Explanation Keys should be unique for all UDDI entities. The UDDI request contains an existing UDDI entity key.

Action Please provide a unique key for the UDDI entity.

E_invalidKeyPassed10210MREF – The tModelKey cannot have multiple references to be deleted.

Explanation Multiple references of a tModelKey were specified in the UDDI request.

Action Please make sure that a single reference exists for a single tModelKey in the request.

E_invalidKeyPassed10210NBE – Tried to update a businessEntity with key {0}, but no businessEntity in the UDDI registry matched the key.

Explanation CentraSite does not contain any business entity with the business key specified in the save request.

Action Please make sure the business key specified in the request is valid.

E_invalidKeyPassed10210NULTM – Tried to delete a tModel with key, but the key did not match with any existing tModel or it is null.

Explanation CentraSite does not contain any TModel with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210OPINFMAT – No OperationalInfo in the UDDI registry matched the key {0}.

Explanation The operational info cannot be found for the given key.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210PAINV – The Publisher Assigned Key {0} is not a valid key.

Explanation The key provided for the UDDI entity by the publisher is not valid.

Action Please specify the key according to the UDDI standard

E_invalidKeyPassed10210PANAL – The Publisher Assigned Key is not allowed.

Explanation The user is not allowed to assign keys for the UDDI entity (CentraSite object).

Action Save the UDDI entity without assigning a key to it.

E_invalidKeyPassed10210SUBMAT – No subscription in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain any subscription with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210SUBNE – The subscription having subscriptionKey as {0} does not exist.

Explanation CentraSite does not contain any subscription with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210TMIBK – Invalid tModelKey in tModelInstanceInfo for BindingKey {0}.

Explanation The specified binding template does not contain a valid tModelKey in tModelInstanceInfo.

Action Please make sure the tModelKey specified in tModelInstanceInfo of the binding template is valid.

E_invalidKeyPassed10210TMKN – TModelvalue should not be null !

Explanation The key value of KeyedReference does not contain a valid value.

Action Please specify a valid key value for the KeyedReference.

E_invalidKeyPassed10210TMKNF – No matching tmodelkey was found. Please check that the tModelKey is of relationship type.

Explanation CentraSite does not contain a tModel with the key specified in the UDDI request.

Action The tModelKey of the keyedReference in the publisher assertion must be the key of the uddi-org:relationships tModel.

E_invalidKeyPassed10210TMKREF – tModelKey not specified in one of the keyedReferenceGroup.

Explanation The tModel key has to be specified for all KeyedReferenceGroups.

Action Please specify a valid tModel key for all KeyedReferenceGroups.

E_invalidKeyPassed10210TMMAT – No tModel in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain a tModel with the key specified in the UDDI request.

Action Please specify a valid tModel key in the UDDI request.

E_invalidKeyPassed10210TMNF – The specified tModelkey {0} cannot be found.

Explanation CentraSite does not contain a TModel with the key specified in the UDDI request.

Action Please specify a valid tModelKey in the UDDI request.

E_invalidKeyPassed10210TOK – No businessEntity in the UDDI registry matched the toKey {0}

Explanation The toKey specified in the add_publisherAssertion request is either invalid or no business entity matched the toKey.

Action Please make sure the toKey specified in the request is valid.

E_invalidKeyPassed10210USUBK – Tried to update a subscription with key {0}, but no subscription in the UDDI registry matched the key.

Explanation CentraSite does not contain any subscription with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210UTM – Tried to update a TModel with key {0}, but no TModel in the UDDI registry matched the key.

Explanation CentraSite does not contain a TModel with the key specified in the UDDI request.

Action Please specify a valid tModelKey in the UDDI request.

E_invalidProjection20230 – No businessService with service key {0} exists in the UDDI registry.

Explanation CentraSite does not contain a business service with the key specified in the UDDI request.

Action Please make sure the service key specified in the request is valid.

E_invalidTime40030 Invalid time period specified or the date/time pair is invalid.

Explanation The date/time provided in the UDDI request is not valid.

Action Please provide the date/time in the format specified in UDDI specification.

E_invalidValue20200EXPAFTDAT – The specified expiresAfter date value is incorrect

Explanation The specified expiresAfter value for the subscription is not in the proper format.

Action Please provide expiresAfter in the proper format.

E_invalidValue20200EXPAFTVAL – expiresAfter has a value older than the current date/time.

Explanation The expiresAfter element of the subscription denotes when the subscription will expire. However, the value specified in the expiresAfter element is older than the current time.

Action Please provide a newer date/time value than the current time for the expiresAfter attribute.

E_invalidValue20200INV – {0} is not a valid value

Explanation The specified attribute does not contain a valid value in the UDDI request.

Action Please provide a valid value.

E_invalidValue20200INVVAL – Invalid Value: {0}

Explanation The key value of the relationship KeyedReference is invalid.

Action Please provide a valid key value.

E_invalidValue20200KNAMNUL – keyName and keyValue should be specified for {0} keyedReference

Explanation In UDDI, the keyedReference with tModelKey "uddi:uddi.org:categorization:general_keywords or uuid:A035A07C-F362-44dd-8F95-E2B134BF43B4" has different behavior. Unchecked value sets can be specified using this KeyedReference. Since this is unchecked, the value sets keyName and KeyValue are mandatory.

Action Please provide a value for KeyName and the KeyValue attribute of the uddi-org:general_keywords KeyedReference.

E_invalidValue20200KVALINV – The attribute keyValue {0} for keyedReference {1} failed validation.

Explanation Validation failed for the KeyedReference as it does not contain a proper key value.

Action Please provide valid key value.

E_invalidValue20200KVALNUL – The attribute keyValue should not be null for a keyedReference.

Explanation KeyValue is a mandatory attribute and it should contain a valid value.

Action Please provide a value for the KeyValue attribute of KeyedReference.

E_invalidValue20200MAXENT – maxEntities has a negative value.

Explanation The maxEntities attribute of the subscription should contain a positive number.

Action Please provide a positive value for the maxEntities attribute.

E_invalidValue20200NOVAL – For asynchronous subscription, both the bindingKey and notificationInterval values should be specified

Explanation To identify whether a subscription is asynchronous or synchronous, the elements bindingKey and notificationInterval are used. Element bindingKey is used to identify to which web service/email address the notification has to be sent. Element notificationInterval is used to identify how often the notification has to be sent. Both elements are required for asynchronous subscription.

Action Please provide values for the bindingKey and notificationInterval attributes for asynchronous subscription.

E_invalidValue20200NTFINT – {0} is not a valid value for notification interval.

Explanation The notificationInterval attribute has to be specified in xsd:duration format.

Action Please provide notificationInterval attribute in xsd:duration format.

E_tokenAlreadyExists40070 – Token Generated for key {0} has expired or the token is already occupied for the specified entities.

Explanation CentraSite already generated a transfer token for the specified entities.

Action Please re-generate the token or use the existing token for the specified entities.

E_transferNotAllowed40600DEF – Transfer Not Allowed!!

Explanation CentraSite does not allow this transfer. The specified transfer token is not present in CentraSite. It might be discarded.

Action Transfer of the entities are not allowed

E_transferNotAllowed40600DNE – TransferToken does not exist.

Explanation The specified transfer token does not exist in CentraSite. It might be invalid or discarded.

Action Please generate new transfer token.

E_transferNotAllowed40600INV – Transfer not allowed. Custody (Operator) or ownership are not same.

Explanation CentraSite does not allow the entities to be transferred if the owners or operator are not the same.

Action Operator and ownership must be the same to transfer entities.

E_transferNotAllowed40600TCBE – Transfer the custody of this businessEntity {0} to the node {1} on which it is modified.

Explanation CentraSite does not support transferring the node businessEntity.

Action The transfer is not allowed for this business entity.

E_transferNotAllowed40600TCBS – Transfer the custody of this businessService {0} to the node {1} on which it is modified.

Explanation The node of the businessService does not match the CentraSite node businessEntity.

Action Transfer is not allowed for this businessService.

E_transferNotAllowed40600TCBT – Transfer the custody of this bindingTemplate {0} to the node {1} on which it is modified.

Explanation The node of the bindingTemplate does not match the CentraSite node businessEntity.

Action Transfer is not allowed for this bindingTemplate.

E_transferNotAllowed40600TCTM – Transfer the custody of this tModel {0} to the node {1} on which it is modified.

Explanation The node of the tModel does not match the CentraSite node businessEntity.

Action Transfer is not allowed for this tModel.

E_transferNotAllowed40600TTNEX – This TransferToken does not exist.

Explanation CentraSite does not contain the specified transfer token.

Action Please fetch a new transfer token.

E_unknownUser10150ID – User ID {0} and password pair passed in a get_authToken API is unknown to the UDDI node or is not valid.

Explanation A user ID in the get_authToken request is mandatory, but the userId element in the get_authTokenRequest request is null.

Action Please provide a valid user ID and password in the get_authToken request.

E_unknownUser10150PASS – User ID and password {0} pair passed in a get_authToken API is unknown to the UDDI node or is not valid.

Explanation The cred element in the get_authToken request is mandatory, but the cred element in the get_authTokenRequest request is null.

Action Please provide a valid user ID and password in the get_authToken request.

E_unrecognizedVersion10040 – Namespace {0} is unsupported by the node being queried.

Explanation The request is not a valid UDDI request or the request cannot be processed by CentraSite.

Action Please provide a valid UDDI request as defined in the UDDI specification.

E_unsupported10050 Feature {0} is not supported.

Explanation The request is not a valid UDDI request or the request cannot be processed by CentraSite.

Action Please provide a valid UDDI request as defined in the UDDI specification.

E_unsupported10050AUTH – authInfo element present in get_assertionStatusReport element is required.

Explanation Authorization is required to process the get_assertionStatusReport call.

Action Please provide an authInfo element with a proper authToken in the get_assertionStatusReport call. Please fetch the authToken using a get_authToken call.

E_unsupported10050INVFINDGET – Invalid find_xx or get_xx api specified in the subscriptionFilter or some part of the subscription to be saved is invalid.

Explanation The subscription filter for the subscription is not valid.

Action Please provide the subscription filter for the subscription according to the UDDI specification.

E_unsupported10050INVFQ – {0} is not a valid find qualifier value in version {1}.

Explanation The provided find qualifier is not valid. The valid qualifiers can be found in UDDI specification.

Action Please provide find qualifiers compliant with the UDDI specification.

E_unsupported10050NINV – The notification interval specified is less than {0}. Please increase the notification interval.

Explanation UDDI configuration parameter UDDIMinimalNotificationInterval specified the minimal notification interval that the UDDI engine can handle. If the given value is less than the UDDIMinimalNotification interval then this error will occur.

Action Please increase the notification interval

E_unsupported10050QUA – This Qualifier is not allowed with FindBinding Inquiry API.

Explanation The find qualifiers binarySort, bindingSubset, caseInsensitiveSort, caseSensitiveSort, combineCategoryBags, sortByNameAsc, sortByNameDesc, serviceSubset and suppressProjectedServices are not supported in the find_binding call.

Action Please specify find qualifiers other than binarySort, bindingSubset, caseInsensitiveSort, caseSensitiveSort, combineCategoryBags, sortByNameAsc, sortByNameDesc, serviceSubset and suppressProjectedServices for the find_binding call.

E_unsupported10050QUARELB – This Qualifier is not allowed with FindRelatedBusinesses Inquiry API.

Explanation The find qualifiers andAllKeys, bindingSubset, combineCategoryBags, orAllKeys, orLikeKeys, serviceSubset and suppressProjectedServices are not supported in the find_relatedBusinesses call.

Action Please specify find qualifiers other than andAllKeys, bindingSubset, combineCategoryBags, orAllKeys, orLikeKeys, serviceSubset and suppressProjectedServices for the find_relatedBusinesses call.

E_unsupported10050QUARSER – This Qualifier is not allowed with FindService Inquiry API.

Explanation The serviceSubset find qualifier is not supported in the find_service call.

Action Please remove the serviceSubset find qualifier from the find_service request.

E_unsupported10050QUARTM – This Qualifier is not allowed with FindTModel Inquiry API.

Explanation The find qualifiers bindingSubset, combineCategoryBags, serviceSubset and suppressProjectedServices are not supported in the find_tModel call.

Action Please specify find qualifiers other than bindingSubset, combineCategoryBags, serviceSubset and suppressProjectedServices for the find_tModel call.

E_unvalidatable20220UNVALID – The referenced tModel has been marked unvalidatable.

Explanation CentraSite does not allow an unvalidatable KeyedReference to be present in the UDDI request.

Action The specified tModel cannot be used in the keyedReference.

E_userMismatch10140 – Signifies that an attempt was made to use the publishing API to change data that is controlled by another party.

Explanation An access violation exception occurred as the user tried to modify a UDDI entity owner by another user.

Action Please make sure proper permissions are assigned to the user to update the entity.

E_userMismatch10140DELSUBUSR – Tried to delete a subscription that is controlled by another individual.

Explanation An access violation exception occurred as the user tried to delete the subscription owned by another user.

Action Please provide the authToken of the user who owns the subscription.

E_userMismatch10140DIFSUB – The owner of the subscription is different.

Explanation The subscription is not owned by the specified user.

Action Please provide the authToken of the user who owns the subscription.

E_userMismatch10140FRMTOK – USER-MISMATCH for publisherAssertion fromKey {0} and toKey {1}.

Explanation The user should own the business specified in fromKey or toKey.

Action Please provide the business key owned by the user either in fromKey or in toKey.

E_userMismatch10140PBE – You are not authorized to publish a businessEntity.

Explanation The user does not have permission to create a business in CentraSite.

Action Please make sure the user has permission to create a business in CentraSite.

E_userMismatch10140TT – You are not authorized to get the TransferToken for the key {0} which is owned by another publisher.

Explanation The transfer token for an entity can be fetched by the user who owns the entity. Transfer token for the entities which the user does not own cannot be fetched.

Action Please provide the key of the owned UDDI entity.

E_userMismatch10140UEK – Tried to update the {0} {1} that is controlled by another individual.

Explanation	The user does not own or does not have permission to update the UDDI entity.
Action	Make sure the user has permission to update the UDDI entity, or make sure the user owns the UDDI entity.

E_userMismatch10140USUBUSR – Tried to update the subscription with key {0}, that is controlled by another individual.

Explanation	The subscription is not owned by the specified user.
Action	Please provide the authToken of the user who owns the subscription.

E_valueNotAllowed20210NODE – This checked category system is only permitted to be used by the node itself.

Explanation	The node business cannot be updated by the user.
Action	The node business cannot be updated by the user.

INMAFE0001	**The registry object must not be null.**
Explanation	The constructor CSAppFixedRegistryObject() is trying to create a new instance so the registry object passed can't be null.
Action	Pass valid registry object.

INMAFE0002	**A fixed registry object's name cannot be changed.**
Explanation	This is a fixed Registry Object. It's name must not be changed.
Action	Don't change a fixed registry object's name.

INMAFE0003	**Different object with duplicate key already registered: {0}**
Explanation	Two different objects that have the same keys are being registered.
Action	Check for any reasons why the duplicate keys exist or change one of the object's keys.

INMAFE0004	**Different association type with duplicate name already registered {0}**
Explanation	Two different associations that have the same names are being registered.
Action	Change one of the association's names.

INMAFE0005	**Different object type with duplicate name already registered {0}**
Explanation	Object types have to have unique names.
Action	Change the object type name to a unique one.

INMAFE0006	**Different child list already registered for parent path: {0}**
Explanation	for this path there is already a defined child list.
Action	Create another parent path to add the new child list.

INMAFE0007	**Unknown taxonomy: {0}**
Explanation	The desired taxonomy does not exist.
Action	Use an existing Taxonomy.

INMAFE0008	**Multiple taxonomies named {0} found.**
Explanation	Taxonomies must have unique names.
Action	Find a way to make the used taxonomies have a unique name.

INMAFE0010	**Different object with duplicate name already registered: {0}**
Explanation	The objects are classification schemes, their names must be unique.
Action	Find a way to change the object names to unique ones.

INMAFE0011	**No such concept: {0}**
Explanation	This Concept does not exist in the database.
Action	Create such a Concept or change to an existing one.

INMAFE0012	**No such classification scheme: {0}**
Explanation	This classification scheme does not exist in the database.
Action	Create a new one or change to an existing classification scheme.

INMAFE0013	**No such association type: {0}**
Explanation	This association type does not exist in the database.
Action	Create a new one or change to an existing association type.

INMAFE0014 **No such object type: {0}**

Explanation This object type does not exist in the database.

Action Create a new one or change to an exisitng object type.

INMAFE0015 **Child list not available for parent {0}, did you set the cache strategy 'childs'?**

Explanation The cache strategy "childs" needs to be set in order to access child concepts.

Action Set the cache strategy 'childs'.

INMAFE0017 **Child list not available for taxonomy {0}, did you set the cache strategy 'childs'?**

Explanation The cache strategy "childs" needs to be set in order to access child concepts.

Action Set the cache strategy 'childs'.

INMAFE0018 **Child list not available for parent concept {0}, did you set the cache strategy 'childs'?**

Explanation The cache strategy "childs" needs to be set in order to access child concepts.

Action Set the cache strategy childs.

INMAFE0019 **No object with key {0} is known by the pool.**

Explanation No fixed RegistryObject was found in the bean pool.

Action The fixed registry object must be added to the bean pool.

INMAFE0021 **Invalid element {0}, expected either of {1}**

Explanation The specified element is not contained in the list of expected elements.

Action Use or change the element to one of the expected types.

INMAFE0023 **Missing attribute: {0}**

Explanation The searched attribute is mandatory and must be provided.

Action Provide the missing attribute or change it so it is not mandatory any more.

INMAFE0024 **Empty attribute: {0}**

Explanation The attribute is empty.

Action Provide data for the attribute.

INMAFE0025 **Duplicate objectType name: {0}**

Explanation Object Types must have unique names.

Action Provide a unique name for the object type, delete or rename the existing one.

INMAFE0026 **Duplicate associationType name: {0}**

Explanation The assoiation type name must be unique.

Action Provide a unique association type name, delete or rename the exisitng one.

INMAFE0027 **Duplicate taxonomy name: {0}**

Explanation Taxonomy name must be unique.

Action Provide unique name for the Taxonomy, rename or delete the existing one.

INMAFE0028 **Invalid value for {0}**

Explanation The specified value is invalid.

Action Provide valid value.

INMAFE0029 **Invalid element {0}, expected {1}**

Explanation The specified element does not match the expected element.

Action The element must be changed accordingly to the expected item.

INMAFE0031 **Duplicate concept value for taxonomy {0}**

Explanation Taxonomy must have a unique concept value.

Action Provide a unique concept value for the taxonomy.

INMAFE0032 **Duplicate concept value for concept {0}**

Explanation Concept must have a unique concept value.

Action Provide a unique concept value for the concept.

INMAFE0033 **Invalid argument: {0}**

Explanation The specified argument is invalid.

Action Provide a valid argument.

INMAFE0034	**The class {0} has no annotation of type {1} or has an empty 'implementation' attribute.**
Explanation	The given class does not have the expected annotation, or the annotation's "implementation" attribute is empty.
Action	Provide an annotation of the given type or fill in the 'implementation' attribute.

INMAFE0037	**The object type's qualified name must not be null.**
Explanation	One of the arguments has a null value.
Action	Provide arguments with a valid value.

INMAFE0038	**A classification's scheme must not be null.**
Explanation	The classification has a null value.
Action	Provide a valid value for classification.

INMAFE0039	**A classification's value must not be null.**
Explanation	The classification has a null value.
Action	Provide a valid value for classification.

INMAFE0040	**The object type's qualified name must not be null.**
Explanation	The object type's qualified name has null value.
Action	Provide a valid value for object type's qualified name.

INMAFE0041	**The classification schemes must not be null.**
Explanation	The classification schemes have a null value.
Action	Provida a valid value for the classification schemes.

INMAFE0042	**This object is unmodifiable.**
Explanation	The object cannot be modified.
Action	Do not try to modify the object.

INMAFE0043	**Unknown property {0}**
Explanation	The property has unknown value.
Action	Provide a valid value for the property.

INMAFE0044 **The IOC annotation of the field {0} has no ID or an empty ID.**

Explanation Some annotation has an empty ID or no ID.

Action Provide a valid ID for the annotation.

INMAFE0045 **The object to initialize must not be null.**

Explanation The initializer has a null value.

Action Provide a valid value for the initializer.

INMAFE0046 **The document must not be null.**

Explanation The document is null.

Action Provide a valid value for the document.

INMAFE0047 **The QName {0} is invalid, because it contains no terminating '}' character.**

Explanation The value argument has no enclosing '}' character.

Action Make sure the value argument has an enclosing '}' character.

INMAFE0049 **Expected {0} element, got {1}**

Explanation The element is different than expected.

Action Make sure the element type is as expected.

INMAFE0051 **Missing attribute for {0}**

Explanation The attribute has a null value.

Action Provide a valid value for the attribute.

INMAFE0052 **Invalid attribute {0} for element {1}**

Explanation The attribute has an invalid value.

Action Provide a valid value for the attribute.

INMAFE0054 **The attribute {0} for element {1} is using an invalid prefix: {2}**

Explanation Some of the attributes have an invalid prefix.

Action Make sure the attribute has a valid prefix.

INMAFE0056	**Missing attribute: {0}**
Explanation	Attribute is missing.
Action	Provide attribute.

INMAFE0057	**Empty attribute: {0}**
Explanation	Attribute is missing.
Action	Provide attribute.

INMAFE0058	**The class {0} doesn't implement {1}**
Explanation	Wrong class provided.
Action	Provide a valid class.

INMAFE0116	**Missing @RegistryObject annotation on persistent class {0}**
Explanation	The processed class has no @RegistryObject annotation. As long as there is no such annotation the persistent class cannot be considered a RegistryBean and cannot be processed.
Action	Add a @RegistryObject annotation to the persistent class interface or use different RegistryBean.

INMAFE0119	**The given registry bean is managed by another pool: {0}**
Explanation	A registry bean instance can be managed by one bean pool only. For example it is not allowed to read a bean with one bean pool instance and update it with another.
Action	Check for multiple beanPool instances managing your registry beans. For a single thread, make one bean pool instance to handle the registry beans.

INMAFE0121	**The given registry bean is not managed by the pool: {0}**
Explanation	The registry bean is being used by a bean pool it does not belong to.
Action	Find and use the bean pool instance that this registry bean belongs to. For exmaple if a registry bean is read or created by one bean pool instance, this is the instance it belongs to and it cannot be managed by another one.

INMAFE0123	**Missing information for attribute with name {0} of type {1}**
Explanation	This attribute should have an attribute description but it does not. For example, attribute description is required for @Relationship , @DateAttribute and other attributes.
Action	When using @Relationship, @DateAttribute etc. an attributeName property must be specified, which corresponds to the name of an existing AttributeDescription. Either create new attribute description, or change the name of the attributeName property to an existing one.

INMAFE0128	**The RegistryObject must be an association, but is a {0}**
Explanation	The RegistryObject to be processed must be a javax.xml.registry.infomodel.Association. The method is trying to create a RegistryBean instance from a javax.xml.registry.infomodel.Association instance.
Action	Check the mapping of theRegistryBean that is being created for any inconsistencies.

INMAFE0129	**AssociationTarget property of {0} is null. Association target cannot be null.**
Explanation	While creating a javax.xml.registry.infomodel.Association instance from a registry bean Association instance. The target of the association must be present in order to create a javax.xml.registry.infomodel.Association.
Action	Set target for the association.

INMAFE0130	**Unable to determine object type. Missing RegistryObject annotation for class {0}.**
Explanation	Either the processed registry bean is not a registry bean at all, or it is missing its RegistryObject annotation. Without it the registry bean cannot be created and it is not considered a registry bean.
Action	Either use a different registry bean that has a RegistryObject annotation, or add the annotation in the used registry bean interface.

INMAFE0131	**Missing concept with key {0}.**
Explanation	The key that is specified is either wrong or does not belong to a concept instance.
Action	Use a different object type key for this annotation.

INMAFE0132	**Missing concept with name {0}**
Explanation	The name that is specified is either wrong or does not belong to a concept instance.
Action	Use a different object type name for this annotation.

INMAFE0133	**The RegistryObject must be a classification.**
Explanation	The registry object to be processed must be a javax.xml.registry.infomodel.Classification instance.
Action	Use a registry object that is an instance of javax.xml.registry.infomodel.Classification.

INMAFE0134	**ClassificationConcept property of {0} is null. The concept for internal classification cannot be null.**
Explanation	The classification's concept property is not specified.
Action	Specify a concept for this classification.

INMAFE0135	**Missing {0} annotation. {1} must be classified instance.**
Explanation	The ClassifiedInstances annotation is missing. It must be present in order to create a ClassifiedInstances property.
Action	Add the ClassifiedInstances annotation to the registry bean.

INMAFE0136	**{0} is not specified as ClassifiedInstance**
Explanation	None of the bean interfaces is a classified instance in the ClassifiedInstances annotation's instances.
Action	Specify a bean interface as ClassifiedInstance.

INMAFE0137	**Cannot find the required classification on {0}**
Explanation	There is no corresponding classification for the given registry object.
Action	Provide the classification.

INMAFE0138	**BeanInfo {0} for {1} must be instance of {2}**
Explanation	The BeanInfo instance is not of type BackedBeanInfo.
Action	Make the BeanInfo an instance of BackedBeanInfo.

INMAFE0139	**No setter found for property {0} in class {1}**
Explanation	The name of the setter is different and a corresponding setter cannot be found in the jaxr representation of this registry bean.
Action	Change the name of the setter in the registry bean interface.

INMAFE0140	**Missing type information for {0}**
Explanation	The BeanType for this jaxr registry object cannot be found in the registry object model. It is not supported by CSAF.
Action	Add BeanType for the required jaxr registry object type in the registry object model.

INMAFE0141	**Getter returns unexpected value type: {0} . Expected: Collection. For property: {1} in class: {2}**
Explanation	The value returned by the getter method does not match the return type specified in the bean interface.
Action	Change the return type to collection or change the annotation used for this property.

INMAFE0142	**No instance of SlotHandler registered for the type {0}**
Explanation	None of the existing slot handlers handles the given property type.
Action	Add a slot handler or change the property type.

INMAFE0143	**Expected RegistryObject of type javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization {0}**
Explanation	The javax.xml.registry.infomodel.TelephoneNumbers support type can only be found in a javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization instance.
Action	Use a javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization instance for operations with javax.xml.registry.infomodel.TelephoneNumbers.

INMAFE0144	**A Collection is expected {0}**
Explanation	TelephoneNumbers is always a collection. Single property is not allowed.
Action	Use a collection of TelephoneNumbers.

INMAFE0145	**Expected RegistryObject of type User or Organization RegistryBeans {0}**
Explanation	The CSAF support type TelephoneNumbers can only be found in a User or Organization RegistryBean instance.
Action	Use a User or Organization RegistryBean instance for operations with CSAF TelephoneNumbers.

INMAFE0146	**Beans to restore must be of BackedBeanInfo instance**
Explanation	Only BackedBeanInfo instances can provide access to the underlying RegistryObject.
Action	Use BackedBeanInfo to provide access to the RegistryObject that is standing behind the RegistryBean.

INMAFE0147	**Invalid bean mode**
Explanation	The bean mode of a configuration can be BACKED or SIMPLE (has been deprecated). Any other bean mode set to the configuration will result in this exception.
Action	Set the bean mode of the configuration to BACKED. The BACKED constant is located under com.softwareag.centrasite.appl.framework.persistence.BeanMode.java.

INMAFE0148	**The object to be read must be a RegistryObject instance: {0}**
Explanation	The object to be read must be an instance of javax.xml.registry.infomodel.RegistryObject but is not.
Action	Read a different object that is of javax.xml.registry.infomodel.RegistryObject instance.

INMAFE0149	**Unsupported value type passed: {0}**
Explanation	The value type passed is not supported by this method and cannot be processed.
Action	Change the value Type or change the method you are using to process this value. For example, the toJaxrValue() method expects one of the support types defined in CSAF (EmailAddress, TelephoneNumbers etc.) and processes it to a JAXR support type , while the toBeanValue method does the opposite.

INMAFE0150	**Missing type information for {0}**
Explanation	No BeanType found in the registry object model for the given registry object. It is not supported by CSAF.
Action	Create a BeanType and add it to the registry object model for the given registry object type.

INMAFE0151	**The BulkResponse collection must currently be java.util.List {0}**
Explanation	The result method of the Search class always has to return a java.util.List object.
Action	Change the Search's BulkResponse collection to java.util.List.

INMAFE0152	**Missing type information for {0}**
Explanation	No BeanType found in the registry object model for the given registry object. It is not supported by CSAF.
Action	Create a BeanType and add it to the registry object model for the given registry object type.

INMAFE0153	**Property is null, this kind of predicate is not allowed**
Explanation	A predicate has bean created for a property that does not exist.
Action	Check the search criteria for wrong property names.

INMAFE0154	**The given class: {0} is not supported**
Explanation	No BeanType found for the given class in the registry object model.
Action	Add BeanType in the registry object model for the desired class.

INMAFE0159	**Invalid attribute name. Attribute name must not contain a space or special characters.**
Explanation	Creating a slot attribute with spaces or special characters in it's name is not allowed.
Action	Use camel case (example: SlotAttribute) or '_' (example: Slot_Attribute) in the name instead of space, or change the name in a different way that it does not contain spaces.

INMAFE0160	**Invalid slot attribute data type.**
Explanation	The data type passed when creating slot attribute is not supported.
Action	Change the data type to one that is supported. Constants with supported data types can be found in AttributeDescription class.

INMAFE0161	**Unknown Error**
Explanation	The error that has been thrown has unknown reasons.
Action	Contact your software supplier.

INMAFE0162	**The parent concept must not be null.**
Explanation	The Concept must have a parent.
Action	Add parent to the concept.

INMAFE0163	**Invalid namespace prefix: {0}**
Explanation	The namespace prefix is invalid.
Action	Change the namespace to a valid one.

INMAFE0164	**Don't know how to handle skipped entity: {0}**
Explanation	The Parser has encountered a skipped entity. CSAF does not support skipped entities.
Action	Exclude the skipped entities from the entity list.

INMAFE0165	**Expected empty stack.**
Explanation	The Parser has reached the end of the file, and its stack should be empty.
Action	Check the file for any inconsistencies or errors.

INMAFE0166	**No getter for property {0} found in class {1}**
Explanation	In order to access a RegistryBean property it must have a getter method.
Action	Provide a getter method for this RegistryBean property. In some cases the getter methods are not provided for a purpose. These RegistryBeans should be documented.

INMAFE0167	**The method {0} in class {1} must be public, and neither static, nor abstract.**
Explanation	There is a restriction that must be followed.
Action	Change the method to public and remove any static or abstract modifiers.

INMAFE0168	**Failed to parse getter name: {0}**
Explanation	A getter method follows a rule when created. It must begin with either get or is. Any other case will result in this exception.
Action	Rename the getter method so it follows the described rule.

INMAFE0169	**The setter {0} in class {1} has return type {2} , not void.**
Explanation	A setter method must have a void return type.
Action	Change the setter return type to void.

INMAFE0170	**The method {0} in class {1} must be public, and not static.**
Explanation	There is a restriction to this method, namely it must be public and not static.
Action	Follow the restriction.

INMAFE0171	**Failed to parse method name: {0}**
Explanation	The method must start with either get, set, has or is. This is necessary in order to be recognized by the parser so a property name can be extracted.
Action	Change the method name accordingly.

INMAFE0172	**Illegal access to default constructor of class {0} : {1}**
Explanation	Nested exception is thrown here. The constructor has to be called with an empty expression list, or check {1} for more information.
Action	Change the constructor accordingly.

INMAFE0173	**Failed to instantiate class {0} : {1}**
Explanation	Nested exception is thrown here. More details are found in {1}
Action	Handle according to the nested exception message.

INMAFE0174	**Illegal access to default constructor of class {0} : {1}**
Explanation	Nested exception is thrown here. The constructor has to be called with an empty expression list, or check {1} for more information.
Action	Change the constructor accordingly.

INMAFE0175	**Failed to instantiate class {0} : {1}**
Explanation	Nested exception is thrown here. More details are found in {1}
Action	Handle according to the nested exception message.

INMAFE0176	**Failed to invoke constructor of class {0} : {1}**
Explanation	Nested Exception. See {1} for more information.
Action	Handle the case according to information in {1}.

INMAFE0177	**No field named {0} found in class {1} or any of its superclasses.**
Explanation	The desired field is not present in the class, nor in any of the superclasses.
Action	Provide the missing field, or change the field name being searched.

INMAFE0178	**Illegal access to field {0} in class {1} : {2}**
Explanation	Nested Exception thrown, see {2} for more details.
Action	Handle according to the information in {2}.

INMAFE0179	**Failed to load the class named {0}.**
Explanation	The class with the given name was not found.
Action	Provide the missing class.

INMAFE0180	**Invalid property specification: {0}**
Explanation	The property has opening bracket [but no closing bracket].
Action	Provide the closing bracket] .

INMAFE0181	**Invalid property specification: {0}**
Explanation	The property was not specified correctly.
Action	Make sure that the property follows all rules.

INMAFE0182	**No list was returned for property specification {0}**
Explanation	This property is expected to return a list.
Action	Check the property for any inconsistencies.

INMAFE0183	**No add method found for property {0} in class {1}**
Explanation	The property must correspond to an add method, but it doesn't.
Action	Provide an add method, change the property or check the property for inconsistencies.

INMAFE0184	**No remove method found for property {0} in class {1}**
Explanation	The property must correspond to a remove method, but it doesn't.
Action	Provide a remove method, change the property or check the property for inconsistencies.

INMAFE0185	**A fixed registry object's description cannot be changed.**
Explanation	This registry object description cannot be changed.
Action	Don't attempt to change a fixed registry object's description.

INMAFE0186	**The interface {0} doesn't have its implementation attribute set in the {1} annotation.**
Explanation	Each interface bean needs to specify its implementation class.
Action	Please use correct value for the annotation attribute.

INMAFE0187	**The key must not be null.**
Explanation	Each key must have a non-null id value.
Action	Provide non-empty, unique key value.

INMAFE0188	**The concept key must point to a Concept: {0}**
Explanation	Classifications can only ne based on concepts.
Action	Make sure that the Classification's concept key is actually pointing to a Concept registry object.

INMAFE0189	**The registry object type key must point to a Concept from the ObjectType taxonomy: {0}**
Explanation	The required object needs to be a child of the "ObjectType" taxonomy.
Action	Make sure that object type key points to a Concept from the ObjectType taxonomy (Classification Scheme).

INMAFE0190	**The association type key must point to a Concept from the AssociationType taxonomy: {0}**
Explanation	The required object needs to be a child of the "AssociationType" taxonomy.
Action	Make sure that association type key points to a Concept from the AssociationType taxonomy (Classification Scheme).

INMAFE0191	**The property is null.**
Explanation	The getMapper() method requires a non-null property argument.
Action	Make sure the property is available.

INMAFE0192	**No property mapper found for Property {0}**
Explanation	The property mapper for the desired property does not exist.
Action	Make sure that a suitable property mapper is available for this property.

INMAFE0193	**Wrong value type passed. Expected Collection<com.softwareag.centrasite.appl.framework.beans.standard.TelephoneNumber>**
Explanation	The method requires an argument of type "Collection".
Action	Make sure the correct value type is used.

INMAFE0194	**Cannot parse string to long(timestamp) {0}**
Explanation	The given value does not match the syntax rules for long numeric values.
Action	Expected long numeric value.

INMAFE0195	**Cannot parse date string {0}**
Explanation	The given value does not match the syntax rules for dates.
Action	Make sure the string is in the proper date format.

INMAFE0196	**Unsupported value passed: {0}. String value expected: either {namespace}localPart or localPart only.**
Explanation	The method expects a vlue of type "String".
Action	Please provide the correct value.

INMAFE0197	**Unsupported value type {0}**
Explanation	The KeyPredicate value type must be one of "String", "Key", or "RegistryBean".
Action	Please provide a valid value.

INMAFE0198	**Unable to create predicate for : {0}. Check the passed sequence and try again.**
Explanation	The values specified for the predicate cannot be properly converted to a query criterion.
Action	Please provide a valid predicate.

INMAFE0199	**The given object is not a RegistryObject.**
Explanation	The method requires a RegistryObject parameter.
Action	Please provide the correct object.

INMAFE0200	**Given object is not Classification: {0}**
Explanation	The method requires a Classification object.
Action	Please provide a valid Classification object.

INMAFE0201	**Unsupported collection. Should be java.util.List or java.util.Set.**
Explanation	The method requires a parameter of type List or Set.
Action	Please provide a collection of valid type.

INMAFE0202	**Only attributes of type Slot can be indexed.**
Explanation	Index definitions are only possible for Slot attributes.
Action	Use an attribute of valid type.

INMAFE0203	**Value and forward label must not be null.**
Explanation	When creating a new association type it is mandatory to specify a value and a forward label.
Action	Correct the application program.

INMAFE0204	**Object type to be generated not found: {0}**
Explanation	The object type name specified when calling the RegistryBeanGenerator does not exist.
Action	Specify an existing type name.

INMAFE0205	**Invalid object ({0}) passed to delete operation**
Explanation	The delete operation only accepts RegistryBean instances. In particular, NULL pointers are rejected.
Action	Call the delete operation with correct RegistryBean instances.

INMAPE0001	**The user {0} does not have the view permission; contact the asset owner or administrator for help.**
Explanation	If the current user has no permission to view this object, then this error will be thrown.
Action	The user needs to be provided proper permission to view this object.

INMBUE0002	**Invalid URI {0}.**
Explanation	You have entered an invalid URI.
Action	Enter a valid URI.

INMBUE0003	**Invalid phone number.**
Explanation	You have entered an invalid phone number.
Action	Enter a valid phone number.

INMBUE0004	**Search scope is empty.**
Explanation	You have not entered a valid search scope in the recipe.
Action	Enter a valid search scope.

INMBUE0007 **Saved search token is not valid.**

Explanation You have entered an invalid saved search token in the URL.

Action Enter a valid saved search token.

INMBUE0009 **Failed to initialize the Unwatch action on selected assets.**

Explanation Could not initialize the Unwatch action on selected assets; possibly because one or more of the selected assets are not already watched.

Action Choose the assets that are already watched.

INMBUE0011 **Enter a valid IP address**

Explanation Enter a valid IP address

Action Enter a valid IP address

INMBUE0012 **Duplicate values for {0}**

Explanation A user was selected as an administrator, but this user has already been selected.

Action Avoid selecting a user as administrator that has already been chosen.

INMBUE0013 **Invalid URL**

Explanation You have entered an invalid URL.

Action Enter a valid URL.

INMBUE0014 **Enter a valid Administrator**

Explanation You have entered an invalid administrator name.

Action Enter a valid administrator name.

INMBUE0015 **Group name is empty**

Explanation You have not entered a group name while creating a local group.

Action Enter a group name.

INMBUE0016 **Invalid URI.**

Explanation You have entered an invalid URI.

Action Enter a valid URI.

INMBUE0017 **Invalid numeric value in attribute.**

Explanation You have entered an invalid numeric value for this attribute.

Action Enter a valid numeric value.

INMBUE0018 **Invalid attribute value.**

Explanation You have entered an invalid attribute value for the chosen type.

Action Enter a valid value for the chosen type.

INMBUE0019 **Required attribute value is empty.**

Explanation You have entered a blank value for the required attribute.

Action Enter a value for the required attribute.

INMBUE0020 **Enter a valid string value for the attribute.**

Explanation You have entered an invalid value for this string attribute.

Action Enter a valid string value.

INMBUE0021 **Enter a valid IP address.**

Explanation You have entered an invalid IP address.

Action Enter a valid IP address.

INMBUE0022 **Enter a valid email address.**

Explanation You have entered an invalid email address. You must enter a valid email address (e.g. example@example).

Action Enter a valid email address (e.g. example@example).

INMBUE0023 **Invalid category name.**

Explanation You have entered an invalid category name for this classification attribute.

Action Enter a valid category name for the defined taxonomy.

INMBUE0024 **Refresh interval is empty.**

Explanation Number. Required. An input denoting the time interval for refreshing a portlet automatically is not specified.

Action Enter a value (in seconds) for refresh interval.

INMBUE0025 **Required attribute value is empty.**

Explanation You have entered a blank value for the required attribute.

Action Enter a value for the required attribute.

INMBUE0026 **Invalid search condition.**

Explanation An invalid search condition has occurred. A search condition consists of one or more predicates, each joined by a keyword (ALL or ANY). A predicate can be a comparison predicate, such as an Equals predicate, NotEquals predicate, StartsWith predicate, or a Contains predicate. This error occurs when none of the above search conditions are met.

Action Correct the search condition.

INMBUE0028 **Invalid combination of x and y axes; at least one of the axes must have a numeric attribute for the graph to render properly.**

Explanation One of the attribute in the x or y axis should have a numeric value.

Action Choose a numeric attribute in one of the two axes.

INMBUE0029 **Invalid search for charts; you must choose at least one numeric attribute.**

Explanation The chosen search does not have a numeric attribute to plot the chart. To plot a chart you must have a combination of non-numeric attribute and numeric attribute.

Action Choose a search with at least one numeric attribute.

INMBUE0030 **Organization name is empty**

Explanation The organization name field is empty, but the organization name must be provided when creating an organization.

Action Enter the organization name.

INMBUE0031 **Role name is empty**

Explanation The role name field is empty, but the role name must be provided when creating a role.

Action Enter a role name.

INMBUE0032	**Enter a valid consumer application name.**
Explanation	The consumer application name specified is either invalid or empty.
Action	Enter a valid consumer application name.

INMBUE0035	**Base URL should not be empty.**
Explanation	The Base URL is empty.
Action	Enter the Base URL.

INMBUE0036	**Add at least one method to the resource.**
Explanation	A resource should have at least one HTTP method to perform a certain operation. This error occurs when an attempt is made to add a resource in the API without specifying at least one method.
Action	Add at least one HTTP method for the resource.

INMBUE0037	**Parameter name must not be empty.**
Explanation	The parameter name is empty.
Action	Enter the parameter name.

INMBUE0038	**Method name must not be empty.**
Explanation	The method name is empty.
Action	Enter the method name.

INMBUE0039	**Resource name must not be empty.**
Explanation	The resource name is empty.
Action	Enter the resource name.

INMBUE0040	**Resource path must not be empty.**
Explanation	The resource path is empty.
Action	Enter the resource path.

INMBUE0041	**Default value should be a value in the possible values list.**
Explanation	The default value does not match with any of the values in the list of possible values.
Action	Enter a value from the list of possible values.

INMBUE0042	**The resource already exists.**
Explanation	An attempt was made to add a resource with the same name as an existing resource in the same service.
Action	Enter a new resource name that is not already in use in the service.

INMBUE0043	**Resource with path already exists in this API.**
Explanation	An attempt was made to add a resource with the same path as an existing resource in the same API.
Action	Enter a new resource path which is not already in use in the API.

INMBUE0044	**Parameter already exists for this parameter type.**
Explanation	An attempt was made to add a parameter with the same name as an existing parameter for the given parameter type.
Action	Enter a new parameter name that is not already available for the parameter type.

INMBUE0045	**Select at least one resource to virtualize.**
Explanation	An attempt was made to virtualize a REST service without selecting the resource.
Action	Select at least one resource to virtualize the REST service.

INMBUE0046	**Request message cannot be empty.**
Explanation	You have not entered a request message when adding sample request and response to the REST service.
Action	Enter the sample request message.

INMBUE0051	**API Portal Name field cannot be empty.**
Explanation	You have not entered the name of API Portal when registering API Portal in CentraSite.
Action	Enter the API Portal name.

INMBUE0052	**API Portal Alias field cannot be empty.**
Explanation	You have not entered the name of API Portal alias when registering API Portal in CentraSite.
Action	Enter the API Portal alias name.

INMBUE0053	**Deployment Endpoint field cannot be empty.**
Explanation	You have not entered the deployment endpoint address when registering API Portal in CentraSite.
Action	Enter a valid deployment endpoint.

INMBUE0054	**CentraSite Alias field cannot be empty.**
Explanation	You have not entered the name of CentraSite alias when registering API Portal in CentraSite.
Action	Enter the CentraSite alias name.

INMBUE0055	**Consumer Onboarding Organization field cannot be empty.**
Explanation	You have not entered the name of the consumer onboarding organization when registering API Portal in CentraSite.
Action	Enter the consumer onboarding organization name.

INMBUE0056	**The base URL already exists.**
Explanation	An attempt was made to add a base URL with the same value as an existing base URL in the same service.
Action	Enter a new base URL value that is not already in use in the service.

INMBUE0058	**Select at least one API Portal to publish.**
Explanation	An attempt was made to publish the API without selecting at least one API Portal.
Action	Select at least one API Portal to publish the API.

INMBUE0059	**Username field cannot be empty.**
Explanation	You have not entered the CentraSite username when registering API Portal in CentraSite.
Action	Enter a valid CentraSite username.

INMBUE0060	**Password field cannot be empty.**
Explanation	You have not entered the CentraSite password when registering API Portal in CentraSite.
Action	Enter a valid CentraSite password.

INMBUE0062	**Gateway URL is not valid. Specify a valid URL, and try again.**
Explanation	The gateway URL is not valid, or not in the correct format.
Action	Specify a valid gateway URL, and try again.

INMBUE0063	**Invalid value**
Explanation	Value entered is not valid.
Action	Enter a valid value and try again.

INMBUE0065	**Maximum payload size cannot take the value "0".**
Explanation	You have specifed the value "0" for the maximum payload size parameter.
Action	Specify "-1" for unlimited size or an integer value greater than "0" for the maximum payload size, and try again.

INMBUE0066	**Select at least one request content type.**
Explanation	A request content type is required if you have added either a schema or an example content for request.
Action	Add at least one content type for request.

INMBUE0067	**Select at least one response content type.**
Explanation	A respons content type is required if you have added either a schema or an example content for response.
Action	Add at least one content type for response.

INMBUE0068	**The request(s) of this method do not consume the content type(s) {0}.**
Explanation	There is a mismatch between the method's request Content-Types and the Content-Type set for the request.
Action	Provide the correct method content type that matches the request content type.

INMBUE0069	**The response(s) of this method do not consume the content type(s) {0}.**
Explanation	There is a mismatch between the method's response Content-Types and the Content-Type set for the Response.
Action	Provide the correct method content type that matches the response content type.

INMBUE0074 **The error status code is not valid.**

Explanation You have entered an incorrect error status code.

Action Enter an error status code between 400 to 500.

INMBUE0076 **Message Subject field cannot be empty.**

Explanation You have not entered the subject line of the email which is used for the consumer notifications.

Action Enter the subject line of the email in the Message Subject field.

INMBUE0077 **Message Body field cannot be empty.**

Explanation You have not entered the message content of the email which is used for the consumer notifications.

Action Enter the message content of the email in the Message Body field.

INMBUE0078 **Required alias '${sys:dyn-Endpoint}' is missing in the Route Through field.**

Explanation You have not specified the alias '${sys:dyn-Endpoint}' in the Route Through field.

Action Make sure the alias '${sys:dyn-Endpoint}' is specified in the Route Through field.

INMBUE0079 **Taxonomy name cannot be empty.**

Explanation You have not provided a name for the taxonomy.

Action Provide a name for the taxonomy.

INMBUE0080 **Asset type name cannot be empty.**

Explanation You have not provided a name for the asset type.

Action Provide a name for the asset type.

INMBUE0081 **Invalid profile name.**

Explanation The entered value for profile name is not valid.

Action Enter a valid profile name.

INMBUE0082 **Invalid attribute name.**

Explanation The entered value for attribute name is not valid.

Action Enter a valid attribute name.

INMBUE0083	**Lifecycle stage name cannot be empty.**
Explanation	You have not entered a name for the lifecycle stage.
Action	Enter the lifecycle stage name.

INMBUE0084	**Lifecycle stage endpoint cannot be empty.**
Explanation	You have not entered an endpoint URL for the lifecycle stage.
Action	Enter a valid lifecycle stage endpoint.

INMBUE0085	**Invalid lifecycle stage endpoint.**
Explanation	The specified lifecycle stage URL is invalid.
Action	Specify a valid lifecycle stage endpoint and try again. If the problem persists, contact your administrator.

INMBUI0005	**No document(s) available.**
Explanation	Documents are not available to download.
Action	No action required.

INMBUI0006	**Selected item(s) not applicable for Export**
Explanation	The selected item(s) are not applicable for export.
Action	No action required.

INMBUI0008	**No target found for deployment.**
Explanation	No target found was for deployment
Action	Register a target for deployment before initiating the Publish action.

INMBUI0010	**Error while instantiating the activity {0}.**
Explanation	Could not instantiate the activity {0}. The failure is likely to be cause by incorrect configuration.
Action	Verify that the activity has been configured correctly.

INMBUI0027	**Unable to view the profile information.**
Explanation	You do not have sufficient access right to view the profile information.
Action	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMBUI0033	**Enter the base URL for API requests.**
Explanation	Base URL is mandatory for making requests to the API.
Action	Enter the base URL for API requests.

INMBUI0034	**Enter a namespace.**
Explanation	A namespace should be specified for the API.
Action	Enter a valid namespace.

INMBUI0057	**Select a sandbox for base URL.**
Explanation	No sandbox has been selected for the base URL. A base URL is classified with a sandbox environment such as a Development, Production or Test to indicate the usage.
Action	Select a sandbox for the base URL.

INMBUI0075	**Enter the Endpoint Prefix for the API.**
Explanation	Endpoint Prefix is optional for Virtual API.
Action	Enter the Endpoint Prefix for the API.

INMBUW0001	**Invalid search query.**
Explanation	You have entered an invalid search query, possibly because the query is not available in the CentraSite repository.
Action	The search query {0} is not available. Configure your portlet with a valid search query.

INMBUW0047	**Specified value is a duplicate value. Specify a valid unique value.**
Explanation	An alias value is already defined for this target.
Action	Specify a valid unique value.

INMBUW0048	**A value is already specified for the target. Select a different gateway.**
Explanation	This is an alias value already defined for this target.
Action	Select a different gateway.

INMBUW0049 **Provide an alias value.**

Explanation You have to provide an alias value.

Action No action required.

INMBUW0050 **Specify a value for this target, else delete the row.**

Explanation You must specify a value for this target.

Action Specify target specific alias value or else delete the entire row.

INMBUW0061 **To add multiple resources, you must manually reconfigure the Route to endpoint field. To reconfigure the Route to endpoint, append the resource path tokenizer ${sys:resource_path} with the base URL of the native API in the format <base-url>/${sys:resource_path}. For more information about handling multiple resources, see the documentation Run-Time Goveranance with CentraSite.**

Explanation To add multiple resources, you must manually reconfigure the Route to endpoint field. To reconfigure the Route to endpoint, append the resource path tokenizer ${sys:resource_path} with the base URL of the native API in the format <base-url>/${sys:resource_path}. For more information about handling multiple resources, see the documentation Run-Time Goveranance with CentraSite.

Action To add multiple resources, you must manually reconfigure the Route to endpoint field. To reconfigure the Route to endpoint, append the resource path tokenizer ${sys:resource_path} with the base URL of the native API in the format <base-url>/${sys:resource_path}. For more information about handling multiple resources, see the documentation Run-Time Goveranance with CentraSite.

INMBU_ERR_EMPTY_ERROR_TEMPLATE – Select an error template in the Use as Default option.

Explanation You have not specified an error template to use as the default in the Use as Default option.

Action Configure a default error template for the error condition and try again.

INMBU_ERR_SAME_TYPE_MULTIPLE_SELECTION – Multiple error templates are not permitted for same content type.

Explanation You have selected more than one error template for the same content type.

Action Remove duplicate error templates with same content type and try again.

INMBU_LBL_API_UNPUBLISH_WARNING – If you unpublish an API from API Portal, the API keys associated with the API will be lost.

INMBU_LBL_USER_BEEPER_PHONE – Beeper

INMBU_LBL_USER_DOMAIN_NAME – Display Name

INMBXE0003	**Enter a valid username or passsword.**
Explanation	You have entered an invalid username or password. To log in to CentraSite, you must enter a valid username and password.
Action	Enter a valid username or password.

INMBXE0004	**Enter your username (full email address).**
Explanation	You have entered an invalid username. To log in to CentraSite, you must enter your email address as username.
Action	Enter a valid username.

INMBXE0005	**Enter a valid email address (e.g. example@example)**
Explanation	You have entered a wrong or blank email address. You must enter a valid email address (e.g. example@example).
Action	Enter a valid email address (e.g. example@example).

INMBXE0009	**Enter your password.**
Explanation	To request an account in CentraSite, you must enter a password.
Action	Enter a valid password.

INMBXE0010	**Enter your first name. Example: John.**
Explanation	To request an account in CentraSite, you must enter your first name.
Action	Enter your first name.

INMBXE0011	**Enter your last name. Example: Smith.**
Explanation	To request an account in CentraSite, you must enter your last name.
Action	Enter your last name.

INMBXE0012	**Enter a reason for requesting access to CentraSite.**
Explanation	To register an account in CentraSite, you must provide a valid reason for requesting the account to CentraSite.
Action	Enter a valid reason for requesting access to CentraSite.

INMBXE0016	**Password does not match**
Explanation	The password for Confirm Password does not match the given password.
Action	Confirm the given password by entering the same password again.

INMBXE0017	**Access is denied.**
Explanation	Could not log in to the CentraSite Business UI as a guest user, probably because the guest access is disabled.
Action	Verify the centrasite.xml file. Make sure that the property element "Guest visiblity" is set to "true". For more information about the usage of "Guest visiblity" property, see the CentraSite Administrator's Guide. If the property is already set to "true" and the error persists, contact your administrator.

INMBXI0001	**CentraSite gives your organization a single place to store, find and reuse service and process assets. That speeds up development. Automatic policy enforcement helps you ensure new services and processes perform consistently and to the quality standards you've set.**
Explanation	This message provides an introduction to CentraSite in the login page.
Action	Get an overview of the product.

INMBXI0002	**Log in to Your Account**
Explanation	Enter the user account credentials to log in to CentraSite.
Action	Log in to CentraSite.

INMBXI0006	**Create Your Account**
Explanation	Request for an account in CentraSite.
Action	Enter the user credentials and create an account in CentraSite.

INMBXI0008 **Thank you for your registration in CentraSite.**

Explanation Thank you for your registration. We will contact you soon and inform you of the next steps. In the meantime you may visit CentraSite as a guest.

Action Log in to CentraSite as a guest.

INMBXI0013 **You will be contacted by a CentraSite administrator.**

Explanation The CentraSite administrator will process your registration request and contact you shortly.

Action The CentraSite Administrator will process your request and contact you shortly.

INMBXI0014 **Access CentraSite as a guest.**

Explanation You may access CentraSite as a guest.

Action Access CentraSite as a guest.

INMBXW0015 **JavaScript is not enabled in your web browser.**

Explanation If JavaScript is already installed but the application does not work, you may need to enable JavaScript in your web browser.

Action Enable the JavaScript in your web browser.

INMBX_LBL_ERROR_PAGE – Enable your CentraSite license

Explanation Members of the CentraSite Community Edition (CE) are not allowed to use the CentraSite Business UI. This is because the Community Edition is a free-of-charge version of CentraSite that does not include a CentraSite license. In order to use the CentraSite Business UI, you must have the CentraSite license installed.

Action Install the CentraSite license. For further information contact your software supplier.

INMBX_LBL_IE8_COMPATIBILITY_TEXT – CentraSite Business UI is not designed to run in compatibility mode. Disable the compatibility mode to render the Business UI.

Explanation CentraSite Business UI is not designed to run in compatibility mode.

Action Disable the compatibility mode to render the Business UI.

INMBX_LIC_ACCESS_ERROR – Error accessing license information. Check the error log for more information.

Explanation Error encountered while accessing the CentraSite license information.

Action If this error persists, contact your administrator.

INMCBE0009	**You do not have sufficient access rights to modify this object.**
Explanation	You do not have sufficient access rights to modify this object.
Action	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMCBE0012	**Invalid password specified.**
Explanation	You have specified an invalid password.
Action	Correct password and try again.

INMCBE0013	**HTTP response {0} received while updating password.**
Explanation	While updating the password, the user received an http error with the given error code.
Action	Analyse the reason for this error based on the http error code.

INMCBE0014	**Error occurred when reading configuration file at {0}.**
Explanation	An error occurred when reading the user-specific configuration file at the given location.
Action	Refer to the stack trace - you may need to delete the given file from the repository.

INMCBE0015	**You have entered no file or folder name.**
Explanation	You have entered no file or folder name.
Action	Enter a name.

INMCBE0016	**The name you have entered is invalid. Web Folder names cannot include any of the following characters: :*?<>|\/"**
Explanation	The name you have entered is invalid. Web folder names cannot include any of the following characters: :*?<>|\/"
Action	Specify another name.

INMCBE0017	**The name you have entered exceeds the maximum allowed name length.**
Explanation	The name you have entered exceeds the maximum allowed name length.
Action	Specify a shorter name.

INMCBE0018	**No report definition is linked to given report object**
Explanation	The report must have an external link referencing the report definition created via BIRT.
Action	Repeat the import of the report either via the "Import Report" command in the user interface or via the "Export to CentraSite" command in the BIRT plugin of Eclipse.

INMCBE0020	**Failed to obtain value of parameter {0}**
Explanation	Could not determine value for the parameter with given name.
Action	Contact your software supplier.

INMCBE0021	**The domain of the specified user is invalid.**
Explanation	The domain of the specified user is invalid. For non-windows platforms, only the domain LOCAL or LDAP is allowed.
Action	Enter a valid domain. For non-Windows platforms, only the domain LOCAL or LDAP is allowed.

INMCBE0022	**Object no longer available**
Explanation	The selected object does not exist, possibly because it has been implicitly discarded before or an import has failed.
Action	Check recent activities.

INMCBE0024	**The passwords you typed do not match.**
Explanation	The passwords you typed do not match.
Action	Enter the new password in both text boxes.

INMCBE0027	**The specified user does not exist.**
Explanation	The specified user is not present in CentraSite.
Action	Specify a valid user.

INMCBE0029	**Error occurred when initializing CentraSite Control - disabling plug-in.**
Explanation	An error occurred when initializing CentraSite Control.
Action	Check details of error message for further information.

INMCBE0030 **Invalid change of data type for existing data.**

Explanation An attempt is being made to change the data type of a property that already has data present that is not of the type specified.

Action Select a data type that matches the existing data.

INMCBE0032 **Asset name must not be empty.**

Explanation No name is specified for the asset.

Action Enter a valid asset name.

INMCBE0033 **Asset type not valid.**

Explanation The selected asset type is not valid for this operation.

Action Select a valid asset type.

INMCBE0035 **The associated object of type Associated with could not be deleted**

Explanation User does not have permission to delete the associated object

Action Grant delete permission to the user for the associated object

INMCBE0036 **The associated object of type WS-Policy attachment could not be deleted**

Explanation The user does not have permission to delete the WS-Policy associated with the virtual service.

Action Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMCBE0037 **The associated object of type External Link could not be deleted**

Explanation The user does not have permission to delete associated external links.

Action Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMCBE0038 **Asset with name {0} already exists of type {1}**

Explanation There is a duplicate asset name.

Action Enter another name for the asset.

INMCBI0001	**New ExternalLink has been copied to the internal clipboard. It can be added to arbitrary registry objects now.**
Explanation	The newly created ExternalLink object has been copied to the internal clipboard. It can be used to add the ExternalLink to any registry object via the tab "External Links".
Action	No action required.

INMCBW0002	**Resource cannot be deleted as it is the target of one or more ExternalLink objects.**
Explanation	You cannot delete this resource as it is referenced by one or more external links.
Action	You may run the impact analysis in order to determine the registry objects that have an external link referencing this resource.

INMCBW0003	**Folder cannot be deleted as it is the target of one or more ExternalLink objects.**
Explanation	You cannot delete this folder as it is referenced by one or more External Links.
Action	You may run the impact analysis in order to determine the registry objects that have an external link depending on this folder.

INMCBW0004	**Resource cannot be renamed as it is the target of one or more ExternalLink objects.**
Explanation	You cannot rename this resource as it is referenced by one or more registry objects.
Action	You may run the impact analysis in order to determine the registry objects that have an external link depending on this resource.

INMCBW0007	**No report is linked to type {0}.**
Explanation	No report has been associated to the type via the 'Link Reports' command.
Action	You can associate a report via the command 'Link Reports' for the respective type.

INMCBW0010	**No operation is defined for type {0}.**
Explanation	The definition of the respective type does not contain any operations.
Action	You can add operations via the 'Modify Type' command for the respective type.

INMCBW0011	**You are connected as a read-only user. This will lead to limited functionality being available.**
Explanation	A read-only user does not have privileges to modify registry objects.
Action	Log in as another user if you want to modify registry objects.

INMCBW0019	**No items have been exported**
Explanation	No items have been exported - this may happen if items selected for export are embedded into other objects and thus cannot be exported without their parent objects.
Action	Select the parent object for export.

INMCBW0031	**File cannot be deleted as it is the target of one or more Favorite objects of My CentraSite.**
Explanation	You cannot delete this file as it is referenced by one or more External Links in My CentraSite.
Action	You may run the impact analysis in order to determine the Favorite Object in My CentraSite that has an external link referencing this resource.

INMCCE0001	**Command {0} is not supported by CentraSite command line tool**
Explanation	The specified command cannot be executed by the CentraSite command line tool. It is not in the list of supported commands.
Action	Please check the usage of CentraSiteCommand and make sure you specify the command which is listed in the usage.

INMCCE0002	**Exception while fetching email properties**
Explanation	CentraSiteCommand is not able to fetch the email properties from CentraSite.
Action	Please make sure all the parameters are valid and re-execute the command.

INMCCE0003	**Exception while storing email properties**
Explanation	CentraSiteCommand is not able to store the email properties into CentraSite.
Action	Please make sure all the parameters are valid and re-execute the command.

INMCCE0006	**Parsing failed! Please make sure configuration file syntax and path are correct.**
Explanation	Parsing the CentraSiteCommand option and/or configFile failed.
Action	Please make sure the CentraSiteCommand options are specified properly and configFile exists in the specified location.

INMCCE0007	**Parsing failed! Please make sure configuration file syntax and path are correct.**
Explanation	This error can occur because of two reasons. 1) The syntax of the configuration file is not valid. 2) The specified configuration file path is incorrect.
Action	Please refer to the documentation for information on creating a valid configuration file.

INMCCE0008	**Failed to execute command {0}**
Explanation	Error occurred while executing the command.
Action	Please check the error message for details.

INMCCE0009	**Internal error occurred**
Explanation	This error may occur because of problems in the system execution.
Action	Please contact the administrator.

INMCCE0010	**{0} is an invalid log unit, possible values are {1}**
Explanation	The provided log unit is invalid. This can occur when the user specifies a log unit other than the supported ones.
Action	Please refer to the error message for the possible values.

INMCCE0011	**{0} is invalid log unit value, possible values are {1}**
Explanation	The provided log unit value is invalid. This can occur when the user specifies a log unit value other than the supported ones.
Action	Please refer to the error message for the possible values.

INMCCE0012	**Purger unavailable for {0}**
Explanation	No purger was found for the given log unit. This error can occur if an appropriate purger is not found/available for the given log unit.
Action	Please ensure the correct log units are provided in the configuration file.

INMCCE0013	**Purging stopped for {0} as there is no write permission for export location {1}**
Explanation	This error will occur when the user does not have the required write permission for the export location.
Action	Please provide required permissions before purging.

INMCCE0014	**Insufficient disk space in {0}. Required space {1}. Available space {2}.**
Explanation	The specified export location does not contain enough space for the exported logs. Please refer to the error message for the available and required space.
Action	Please choose a different export location.

INMCCE0015	**Purging Failed. Following error occurred {0}.**
Explanation	Purging failed for the log unit mentioned in the error message. Some failures may happen because of network time out and similar problems.
Action	Please try again later or contact the administrator for assistance.

INMCCE0016	**Unable to archive the export directory {0}**
Explanation	The archiving of the exported logs failed. This may happen because of files being accessed by an other application.
Action	Please close the other application and try again.

INMCCE0017	**Unable to create the export directory {0}**
Explanation	This error can occur when the user does not have the required write permission for the export location or the export location is invalid.
Action	Please provide required permissions before purging or make sure the export location is valid.

INMCCE0018	**Command {0} is not supported by CentraSite command line tool**
Explanation	The displayed command is invalid. This can occur when the user specifies a command other than the supported ones. For example, to purge logs, you should specify -command purge_logs.
Action	Please refer to the documentation for the list of supported commands and their usage.

INMCCE0019	**castUri option is mandatory for the command {1}**
Explanation	The castUri option is required for the specified commands.
Action	Please specify the cast URI in the -castUri option.

INMCCE0020	**CentraSite Application Server Object (CAST) already registered in CentraSite with the specified castUri {0}**
Explanation	The CAST will be identified using the host present in castUri option, and CentraSite already contains a CAST registered with the specified host.
Action	Specify a different value in the castUri option or de-register the existing CAST and register it again. A CAST can be de-registered using the deregister_cast command.

INMCCE0021	**{0} and {1} both present in configuration for log unit {2}**
Explanation	The tags Until and OlderThan are both present in the configuration file.
Action	Please use only one of the given tags in the configuration file. For more information, please refer to the Administration guide.

INMCCE0022	**Unable to obtain policy query manager. Cause: {0}**
Explanation	It was not possible to obtain the policy query manager.
Action	Verify your installation or contact the administrator.

INMCCE0023	**Exception occurred during restore operation. Cause: {0}.**
Explanation	An exception occurred during the restore operation.
Action	Please check the exception message for more details.

INMCCE0024	**Archive seal error. Invalid start/end date entries in the archive seal properties for the Archive file {0} located in {1}.**
Explanation	An archive seal error occurred. There are invalid start/end date entries in the archive seal properties.
Action	Please verify the seal properties file for correctness.

INMCCE0025	**Error creating archive seal file. Cause {0}.**
Explanation	An error occurred while creating the archive seal file.
Action	Please check the error message for more details.

INMCCE0026	**Command option {0} missing**
Explanation	The specified command requires a command option.
Action	See the usage information for the correct command syntax.

INMCCE0028	**Domain {0} not found**
Explanation	The domain to be processed does not exist.
Action	Correct the specified domain name.

INMCCE0029 **Domain {0} already exist**

Explanation A domain entry with the specified name is already present.

Action Correct the specified domain name.

INMCCE0030 **Error processing configuration file: {0}**

Explanation The configuration file does not contain a valid domain entry.

Action Correct the domain entry in the configuration file.

INMCCE0031 **Error deleting domain entry: {0}**

Explanation The specified domain entry could not be deleted.

Action Contact your support center.

INMCCE0039 **{0} is not a LDAP domain**

Explanation The validate command is only supported for LDAP domains.

Action Specify an LDAP domain for validating an authentication configuration.

INMCCE0040 **LDAP basic configuration validation error**

Explanation The basic LDAP configuration is invalid.

Action Check the basic settings for the specified domain.

INMCCE0041 **LDAP user login validation error**

Explanation The user could not log on with supplied user name and password.

Action Check if the user name and password were specified correctly. Check the settings for the specified domain.

INMCCE0042 **LDAP user properties validation error**

Explanation The user properties configuration is invalid.

Action Check the user properties settings for the specified domain.

INMCCE0043 **LDAP group resolution validation error**

Explanation The group resolution configuration is invalid.

Action Check the group resolution settings for the specified domain.

INMCCE0046	**CS Admin user {0} not created**
Explanation	An error occurred while attempting to create a user with the CentraSite Administrator role.
Action	See the additional information provided to find the reason.

INMCCE0047	**CS Admin user {0} ({1}) not created**
Explanation	An error occurred while attempting to create a user with the CentraSite Administrator role.
Action	See the additional information provided to find the reason.

INMCCE0053	**{0} No Users found!**
Explanation	Searched users are not found
Action	user has to retry the search

INMCCE0054	**{0} No group properties found!**
Explanation	The group properties entered for the configuration are not correct.
Action	Correct the group properties.

INMCCE0055	**Can't get group properties. {0}**
Explanation	{0} --> error message from the LDAP
Action	re-configuration needs to be done

INMCCE0056	**cannot read user property {0}**
Explanation	{0} --> user property configured
Action	Re-configure the user properities

INMCCE0058	**cannot read user property {0}**
Explanation	{0} --> user property
Action	Re-configure the property

INMCCE0059	**{0} No user properties found!**
Explanation	{0} --> status warning message
Action	Re-configure the user properties

INMCCE0060 **Cannot contact the server. {0}**

Explanation An attempt to connect to the server failed with the error message {0}.

Action Re-configure the server properties.

INMCCE0066 **Unable to connect to socket!**

Explanation There was a problem while connecting to the socket.

Action Re-configure the connection.

INMCCE0067 **The old file is not deleted**

Explanation An SSX trace file already exists and should be deleted.

Action The SSX trace file needs to be deleted manually.

INMCCE0068 **Unable to listen to port**

Explanation It was not possible to connect to the given port.

Action Re-configure the port.

INMCCE0088 **Cannot write to log4j.**

Explanation A message could not be written to the log4j log file.

Action Check your log4j configuration.

INMCCE0089 **Cannot write in the {0}**

Explanation A message could not be written to the SSX trace file {0}.

Action Chekc your trace file configuration.

INMCCE0090 **cannot connect to database - possibly password wrong?**

Explanation An error was detected while trying to connect to the database.

Action Check that you entered the correct pasword.

INMCCE0091 **Database 'CentraSite' not running**

Explanation The database 'CentraSite' is not running.

Action Start the CentraSite database.

INMCCE0092	**{0} User authentication for "{0}" failed!**
Explanation	{0} --> State error {1} --> user name
Action	Re-enter the user authentication

INMCCE0093	**The user repository cannot be created with parameters: {0}**
Explanation	The user repository cannot be created with the given parameters.
Action	Re-configure the repository.

INMCCE0094	**{0} open SSXRepository - {1}**
Explanation	The SSX repository is not connected. The state error is {0} and the error message is {1}.
Action	Re-configure the connection to the repository.

INMCCE0096	**Can't get users {0}**
Explanation	The user mapping does not match any entry on the LDAP server.
Action	Provide a user mapping that matches an entry in LDAP.

INMCCE0100	**Can't get member of group {0}**
Explanation	An incorrect group ID was specified.
Action	Provide a correct group ID.

INMCCE0103	**Can't get groups for user {0}**
Explanation	No groups were found for the given user.
Action	Provide a proper group resolution.

INMCCE0105	**db 'CentraSite' not running**
Explanation	The database "CentraSite" is not currently active.
Action	Restart the "CentraSite" database.

INMCCE0111	**Failed to obtain the user {0} folder from CentraSite**
Explanation	Could not obtain the folder for the user with given name. The username is used to store a search definition in CentraSite.
Action	Make sure the user is registered in CentraSite.

INMCCE0112	**Search definition {0} already exists in CentraSite**
Explanation	An attempt was made to overwrite the existing report search definition.
Action	Make sure that you publish a new module or pass the argument -overwrite option_value.

INMCCE0113	**File {0} not found**
Explanation	The file {0} was not found in the folder.
Action	Check the availability of the file in the specified path.

INMCCE0114	**Retrieving the namespace from {0} failed because the namespace is null.**
Explanation	Cannot retrieve the namespace in the search definition since the namespace is null.
Action	Make sure a valid namespace is declared in the search definition.

INMCCE0115	**Namespace does not match with the module**
Explanation	The specified namespace does not match with the new module and search definition.
Action	Make sure that the namespace matches with the new module and search definition.

INMCCE0116	**Error loading the module**
Explanation	Failed to load the new module into CentraSite.
Action	Make sure the module format is correct.

INMCCE0117	**The namespace {0} is already used by a module in CentraSite**
Explanation	The specified namespace {0} was already used by a module. The module namespace should be unique in CentraSite.
Action	Difine a new module namespace or use -overwrite TRUE to overwrite the existing module with this new namespace.

INMCCE0118	**The user you specified does not exist**
Explanation	The user you specified is not a known user.
Action	Specify the name of a known user.

INMCCE0119	**The number of Arguments for the command SetAsymmetricBindingConfigurations is not sufficient**
Explanation	The number of Arguments for the command SetAsymmetricBindingConfigurations is not sufficient
Action	Please provide proper number of Arguments

INMCCE0120	**Additional arguments provided to the Command SetAsymmetricBindingConfiguration**
Explanation	Additional arguments provided to the Command SetAsymmetricBindingConfiguration
Action	Please delete the unwanted arguments

INMCCE0121	**Required parameters missing**
Explanation	Alleat one of the parameters among InitiatorTokenInclusion,RecipientTokenInclusion,AlgorithmSuite and Layout required for the command.
Action	Please Add one of InitiatorTokenInclusion,RecipientTokenInclusion,AlgorithmSuite or Layout

INMCCE0122	**Invalid values provided for InitiatorTokenInclusion**
Explanation	InitiatorTokenInclusion value can only be one among Always,AlwaysToRecipient,AlwaysToInitiator,Once,Never
Action	Please provide one value among Always,AlwaysToRecipient,AlwaysToInitiator,Once,Never

INMCCE0123	**Invalid values provided for RecipientTokenInclusion**
Explanation	RecipientTokenInclusion value can be one among AlwaysToRecipient,Always,AlwaysToInitiator,Once,Never
Action	Please provide one among AlwaysToRecipient,Always,AlwaysToInitiator,Once,Never

INMCCE0124	**Invalid values provided for AlgorithmSuite**
Explanation	Invalid values provided for AlgorithmSuite
Action	Please provide a valid value

INMCCE0125	**Invalid value provided for Layout**
Explanation	Layout can have one value among Strict,Lax,LaxTsFirst,LaxTsLast
Action	Please provide one value among Strict,Lax,LaxTsFirst,LaxTsLast

INMCCE0126	**Exception writing the values to the repository .Reason : {0}**
Explanation	{0}
Action	{0}

INMCCE0127	**Exception while reading from the repository .Reason : {0}**
Explanation	{0}
Action	{0}

INMCCE0129	**The target for federation cannot be configured in the file at {0}**
Explanation	While trying to configure a target for federation, the file at location {0} will be modified to include the configuration. This error occurs if the "multicast" element cannot be found in the file.
Action	Check to ensure that the "multicast" element is available after "from" in the file {0}.

INMCCE0130	**The mandatory parameter(s), {0} is/are not specified for the command**
Explanation	The command requires some parameters for proper execution and they are not specified. Without these mandatory parameters, the execution cannot proceed.
Action	Provide the parameters needed for the command execution. If you don't know the command format, just provide the command name alone to get the usage for the command.

INMCCE0131	**The provided configFile {0} is not configured with the {1} element.**
Explanation	While parsing the XML configFile, {0}, the parser cannot obtain the {1} element which is needed for the command execution.
Action	Check the configFile {0} to see if the {1} element is configured. If it is not, provide the necessary details.

INMCCE0132	**The given federation id {0} does not have any target associated with it.**
Explanation	The provided ID {0} is not configured to have a federation target.
Action	Use show_uddi_federation to determine the list of configured federation targets and identifiers.

INMCCE0139	**An Internal Error occurred**
Explanation	An Internal Error occurred
Action	An Internal Error occurred

INMCCE0140	**Invalid Credentials**
Explanation	Invalid Credentials provided
Action	Please provide valid credentials

INMCCE0141E	**Provide details for any one of the following parameters: api, accessToken, apiPortal**
Explanation	An error occurred while sending the access tokens using the send AccessTokens command because the details for more than one of the parameters was provided.
Action	Provide details for any one of the parameters.

INMCCE0142	**Invalid Virtual Service name**
Explanation	The specified virtual service name is invalid.
Action	Enter a valid virtual service name.

INMCCE0144	**Invalid Target name**
Explanation	The target is not created or is invalid for virtual services to be deployed, undeployed or redeployed.
Action	Please provide a valid target name.

INMCCE0152	**Command execution failed. Parameter value cannot be null or empty.**
Explanation	A command parameter value was not entered.
Action	Before you execute a command, make sure that you set a value for every parameter in the command.

INMCCE0153	**Command execution failed. Description of the path already exists.**
Explanation	Description of the command path already exists.
Action	Before you execute a command, make sure that you set a valid command path.

INMCCE0154	**Command execution failed. Combination of the path already exists.**
Explanation	Combination of the command path already exists.
Action	Before you execute a command, make sure that you set a valid command combination.

INMCCE0155	**Command execution failed. The name for command token is not valid.**
Explanation	You have entered an invalid name for the command token.
Action	Enter a valid name for the command token.

INMCCE0156	**Command execution failed. The input for command token is not valid.**
Explanation	You have entered invalid input for the command token.
Action	Enter a valid input for the command token.

INMCCE0157	**Command execution failed. Path already exists for the tokens: {0}**
Explanation	The path already exists for the command tokens: {0}.
Action	Before you execute a command, make sure that you set a valid path for the tokens.

INMCCE0158	**Command execution failed. Parameter value cannot be null or empty.**
Explanation	A command parameter value was not entered.
Action	Before you execute a command, make sure that you set a value for every parameter in the command.

INMCCE0159	**Command execution failed. Token or parameter value cannot be null or empty.**
Explanation	A command token or parameter value was not entered.
Action	Before you execute a command, make sure that you set a value for every token and parameter in the command.

INMCCE0160	**Command execution failed. Combination of the command tokens {} already exists.**
Explanation	An attempt was made to specify the same token that is already present in the command.
Action	Before you execute a command, make sure that you set a valid token in the command.

INMCCE0161	**Parameter {0} should not empty.**
Explanation	The '{0}' parameter is mandatory.
Action	Enter a value for the {0} parameter.

INMCCE0162	**Check the length of the command help.**
Explanation	The command help text you have entered does not meet the minimum requirement of {0} characters.
Action	Correct the help text appropriately.

INMCCE0163	**Command execution failed. Unable to join null or empty strings, or a single string.**
Explanation	The combination of a null and empty string, or a null and single string is not valid.
Action	Before you execute a command, make sure that you set valid combination of strings in the command.

INMCCE0164	**Configuration property {0} cannot be empty.**
Explanation	The configuration property '{0}' was not specified.
Action	Specify the property {0}.

INMCCE0165	**Command execution failed. Invalid value {0} for configuration parameter {1}.**
Explanation	The value {0} for configuration parameter {1} is not valid.
Action	Before you execute a command, make sure that you set a valid value for parameter {1} in the command.

INMCCE0166	**Invalid input file.**
Explanation	The specified input file is invalid, possibly because there are one or more elements which are not allowed for this command.
Action	Specify a valid input file and try again. If the problem persists, contact your administrator.

INMCCE0170	**The default domain {0} cannot be deleted.**
Explanation	The specified domain entry is the domain displayed by default and cannot be deleted.
Action	To delete the default domain first designate a different domain as the default domain.

INMCCE0171 **The "set Log" command failed due to incorrect data.**

Explanation This is an internal error probably because the "set Log" command expects starting element {0} instead of {1}.

Action Verify the config.xml contents. Make sure the configuration has starting element as <LogSettings>. For more information about the usage of "set Log" command, see the CentraSite Administrator's Guide. Contact your administrator if the problem persists.

INMCCE0172 **The "set Log" command failed due to incorrect data.**

Explanation This is an internal error probably because the specified "set Log" command expects child element {0} instead of {1}.

Action Verify the config.xml contents. Make sure the configuration has child element as <LogUnit>. For more information about the usage of "set Log" command, see the CentraSite Administrator's Guide. Contact your administrator if the problem persists.

INMCCE0173 **The "set Log" command failed due to incorrect data.**

Explanation This is an internal error probably because the "set Log" command expects a <LogUnit> element {0} instead of {1}.

Action Verify the config.xml contents. Make sure the configuration contain <LogUnit> element with attribute <name>. For more information about the usage of "set Log" command, see the CentraSite Administrator's Guide. Contact your administrator if the problem persists.

INMCCE0174 **Upload failed! The file {0} has an invalid extension.**

Explanation An attempt was made to upload the specified file {0} with extension other than .xml.

Action Upload a valid XML file.

INMCCE0175 **Failed to obtain the Organization folder of the user {0} from CentraSite.**

Explanation Could not fetch the Organization folder of the specified user {0}, possibly because the user has been deleted from the CentraSite registry.

Action Make sure the specified user exists in the CentraSite registry. If the user exists and the error persists, contact your administrator.

INMCCE0178 **The set gateway command failed. {0}**

Explanation The gateway command has failed to create a new gateway or update the specified gateway. You might not have the necessary permissions to create/update a gateway in CentraSite or CentraSite might be down.

Action Ensure that you have the necessary permissions in CentraSite and that CentraSite is up and running. Also, provide all the mandatory parameters when you run the command to create/update a gateway.

INMCCE0180	**Gateway deletion failed. {0}**
Explanation	The gateway command has failed to delete the specified gateway. You might not have the necessary permissions to delete a gateway in CentraSite or CentraSite might be down.
Action	Ensure that you have the necessary permissions in CentraSite and that CentraSite is up and running. Also, ensure that you have provided the correct gateway name or ID.

INMCCE0181	**The list gateways command failed. {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0183	**Unable to find a gateway in CentraSite with the name or key "{0}".**
Explanation	You have provided a gateway name or key that does not exist in CentraSite. The delete gateway command failed to delete the specified gateway.
Action	Ensure that the gateway name or ID that you specify is correct and exists in CentraSite.

INMCCE0184	**Unable to find an organization in CentraSite with the specified name or key "{0}".**
Explanation	You have provided an organization name or key that does not exist in CentraSite. The set gateway command failed to create a new gateway.
Action	Ensure that the organization name or key that you specify is correct and exists in CentraSite.

INMCCE0185	**Unable to find a sandbox in CentraSite with the specified name or key "{0}".**
Explanation	You have provided a name or key of a sandbox category that does not exist in CentraSite. The set gateway command failed to create a new gateway.
Action	Ensure that the sandbox category with the specified name or key exists in CentraSite.

INMCCE0186	**Report with that name doesn't exist or name is not unique.**
Explanation	Either the name is misspelled or multiple reports with that name exist.
Action	Check the report name and provide a valid report name.

INMCCE0187	**Sharing of report failed.**
Explanation	Sharing of report failed possibly due to an internal error.
Action	Contact your local support.

INMCCE0189E	**Error occurred while publishing API Key {0} to API Portal {1}.**
Explanation	An error occurred while trying to publish API Key {0} to API Portal {1}.
Action	Ensure that the API Portal server is up and running. If the problem persists, contact your administrator.

INMCCE0191E	**Error occurred while publishing OAuth token {0} to API Portal {1}.**
Explanation	An error occurred while trying to publish OAuth token {0} to API Portal {1}.
Action	Ensure that the API Portal server is up and running. If the problem persists, contact your administrator.

INMCCE0197	**"{0}" is not a valid value for "{1}".**
Explanation	You have provided a value which is not part of the specified list.
Action	Ensure that the provided value is part of the specified list.

INMCCE0198	**Report with name "{0}" was not found.**
Explanation	You have provided a report name that does not exists in CentraSite.
Action	Ensure that the report name that you specified is correct and exists in CentraSite.

INMCCE0199	**More than one reports with the name "{0}" found.**
Explanation	You have provided a report name which is not unique in CentraSite.
Action	If the report name is not unique in CentraSite specify the report id.

INMCCE0200	**Unable to add a new Report to CentraSite.**
Explanation	An error occurred during the "add report" operation.
Action	A new report could not be created. For more information check the CentraSiteCommand log.

INMCCE0201	**Unable to delete the report with the id "{0}".**
Explanation	An error occurred during the "delete report" operation.
Action	Ensure that the report id is correct and exists in CentraSite. For more information check the CentraSiteCommand log.

INMCCE0202	**Unable to access the specified Report Template file.**
Explanation	You have provided a path to a report template file which does not exist.
Action	Ensure that the specified report template file exists.

INMCCE0203	**Unable to update the report with id "{0}".**
Explanation	An error occurred during the "update report" operation.
Action	Ensure that the report id is correct and exists in CentraSite. For more information please check the CentraSiteCommand log.

INMCCE0204	**Scheduled report with name "{0}" was not found.**
Explanation	You have provided a scheduled report name that does not exist in CentraSite.
Action	Ensure that the scheduled report name that you specified is correct and exists in CentraSite.

INMCCE0205	**More than one scheduled report with the name "{0}" found.**
Explanation	You have provided a scheduled report name which is not unique in CentraSite.
Action	If the scheduled report name is not unique in CentraSite the scheduled report id has to be specified.

INMCCE0206	**Unable to add a new scheduled report to CentraSite.**
Explanation	An error occurred during the "add scheduled report" operation.
Action	A new scheduled report could not be created. For more information check the CentraSiteCommand log.

INMCCE0207	**Unable to delete the scheduled report with the id "{0}"**
Explanation	An error occurred during the "delete scheduled report" operation.
Action	Ensure that the scheduled report id is correct and exists in CentraSite. For more information please check the CentraSiteCommand log.

INMCCE0208	**Unable to trigger the execution of the scheduled report with the id "{0}".**
Explanation	An error occurred during the "trigger scheduled report" operation.
Action	Ensure that the scheduled report id is correct and exists in CentraSite. For more information check the CentraSiteCommand log.

INMCCE0209	**Unable to update the scheduled report with the id "{0}".**
Explanation	An error occurred during the "update scheduled report" operation.
Action	Ensure that the scheduled report id is correct and exists in CentraSite. For more information check the CentraSiteCommand log.

INMCCE0210	**The property "{0}" is mandatory.**
Explanation	You have provided a configuration file where the property is missing.
Action	Ensure that the property is set in the configuration file.

INMCCE0211	**Unable to download the report template for the report id "{0}".**
Explanation	An error occurred during the "download report template" operation.
Action	Ensure that the report id is correct and exists in CentraSite. For more information check the CentraSiteCommand log.

INMCCE0215	**File {0} already exists.**
Explanation	The specified file already exists.
Action	Provide the correct file name.

INMCCE0217	**User level scope is not allowed.**
Explanation	You have provided the scope as user level.
Action	Change the scope either to global or org.

INMCCE0218	**Provide details for any one of the following parameters: scope, targetUser**
Explanation	An error occurred while copying the saved search because details for more than one of the parameters was provided.
Action	Provide details for any one of the parameters.

INMCCE0219	**Cannot find saved search with name {0}.**
Explanation	Cannot find saved search with name {0} while performing copy saved search operation.
Action	Make sure the saved search with name {0} is present.

INMCCE0220	**Specify a value for scope or targetUser.**
Explanation	You have not provided a value for both scope and targetUser.
Action	Enter a valid value for scope or targetUser.

INMCCE0222	**Insufficient privilege for user "{0}" to execute copy search command.**
Explanation	To execute copy search the user should be either an CentraSite Administrator or an Organization Administrator.
Action	Please make sure you have sufficient privileges.

INMCCE0224	**Insufficient privilege for user "{0}" to execute add search command in organization scope.**
Explanation	To execute add search in organization scope the user should be either an CentraSite Administrator or an Organization Administrator.
Action	Please make sure you have sufficient privileges.

INMCCE0225	**LDAP server {0} is not known.**
Explanation	The specified LDAP server {0} is not known, probably because the IP address or the host name of the LDAP server could not be determined.
Action	Enter a valid IP address, or the fully qualified host name of the LDAP server.

INMCCE0226	**LDAP server {0} is not reachable.**
Explanation	The specified LDAP server {0} is not reachable.
Action	Make sure that the LDAP server is reachable.

INMCCE0227	**Authentication failed {0}.**
Explanation	An error occurred while trying to access the LDAP server, possibly because of invalid credentials.
Action	Make sure the credentials for accessing the LDAP server are valid.

INMCCE0231	**The temporary configuration file name {0} already exists.**
Explanation	The name you are giving the temporary configuration file already exists for another file in CentraSite.
Action	Enter a configuration file name that does not already exist in CentraSite.

INMCCE0234	**Invalid object class.**
Explanation	The specified object class for users or groups does not exist in the LDAP server.
Action	Make sure the specified object class name exists in the LDAP server.

INMCCE0235	**Invalid root DN.**
Explanation	The specified root DN (distinguished name) for user or group searches does not exist in the LDAP server.
Action	Make sure the specified root DN exists in the LDAP server.

INMCCE0238	**Invalid attribute name.**
Explanation	The specified attribute name does not exist in the LDAP server.
Action	Make sure the specified attribute name exists in the LDAP server.

INMCCE0259	**Dynamic configuration property files of domain {0} are not unique.**
Explanation	The dynamic configuration property files of the specified domain {0} are not unique. The dynamic configuration files include the property files for the domain, and the property files for the alias declaration.
Action	Remove either the property files for the domain, or the property files for the alias declaration.

INMCCE0260	**The Truststore Type and Truststore URL fields or the Keystore Type and Keystore URL fields cannot be empty.**
Explanation	You have not entered values for the required Truststore Type and Truststore URL fields, or the Keystore Type and Keystore URL fields, when using LDAP over SSL (LDAPS).
Action	Enter valid values for either the Truststore Type and Truststore URL fields, or the Keystore Type and Keystore URL fields.

INMCCE0261	**Malformed URL.**
Explanation	Either no legal protocol could be found in the URL string or the URL string could not be parsed.
Action	Enter a valid URL.

INMCCE0262	**URL is not accessible.**
Explanation	An exception occurred when trying to connect to the specified URL.
Action	Check that the URL is correct.

INMCCE0266	**Target user {0} does not exist in the CentraSite registry.**
Explanation	Could not find the specified target user {0}, possibly because the user has been deleted from the CentraSite registry.
Action	Make sure the specified target user exists in the CentraSite registry. If the target user exists and the error persists, contact your administrator. If the target user does not exist, enter a valid CentraSite username.

INMCCE0267	**Incorrect date format {0}.**
Explanation	The specified date format is incorrect.
Action	Specify a valid date in the format yyyy-mm-dd.

INMCCE0268	**The access key or token does not match the authentication option.**
Explanation	The specified access key or token does not match the given authentication option.
Action	Specify the correct access key or token configured in the authentication option.

INMCCE0269	**Incorrect value for year {0}.**
Explanation	The specified value for year is incorrect.
Action	Specify a valid value for year in the format 'yyyy'.

INMCCE0270	**Incorrect value for month {0}.**
Explanation	The specified value for month is incorrect.
Action	Specify a valid value for month in the format 'mm'.

INMCCE0271	**Incorrect value for date {0}.**
Explanation	The specified value for date is incorrect.
Action	Specify a valid value for date in the format 'dd'.

INMCCE0272	**Failed to purge access token {0}.**
Explanation	Could not purge the specified access token using the CentraSite Command "purge accesstokens", possibly because of insufficient permissions or CentraSite database server is down.
Action	Make sure the CentraSite database server is up and running, and you have sufficient permissions to purge access tokens.

INMCCE0273	**The specified key is not available in DB.**
Explanation	The specified key is not available in DB .
Action	The specified key is not available in DB.

INMCCE0274	**Type with the given name does not exist or is not unique in the CentraSite registry.**
Explanation	Type with the given name does not exist or multiple type with the same name exist in the CentraSite registry.
Action	Provide a valid type name.

INMCCE0276	**{0} is the current logged in user.**
Explanation	An attempt was made to delete the logged in user.
Action	Ensure that the selected user for deletion is not the current logged in user.

INMCCE0277	**{0} is the primary contact of {1}.**
Explanation	The logged in user tried to delete the primary contact of an organization.
Action	Ensure that the selected user for deletion is not the primary contact of an organization.

INMCCE0278	**{0} is the CentraSite Administrator.**
Explanation	The logged in user tried to delete the user who is the CentraSite Administrator.
Action	Ensure that the selected user for deletion is not the CentraSite Administrator.

INMCCE0279	**At least one {0} should be present.**
Explanation	This is possible because there is only one user with the CentraSite Administrator or Organization Administrator role, and an attempt is made to delete this user.
Action	Make sure there is at least one CentraSite Administrator or Organization Administrator user at any time.

INMCCE0280	**User {0} has pending approvals and cannot be deleted.**
Explanation	The user selected for deletion has one or more pending approvals.
Action	Approve or reject the pending approvals for the selected user.

INMCCE0281	**Provide details for any one of these parameters: forceDelete, targetUser**
Explanation	An error occurred while deleting organization because details for more than one of these parameters were provided: forceDelete, targetUser.
Action	Provide details for any one of these parameters.

INMCCE0282	**Could not delete the organization that has deployed service(s).**
Explanation	Could not delete the organization, possibly because there is at least one service with key {0} deployed to a gateway.
Action	Undeploy the services before deleting the organization.

INMCCE0284	**Insufficient permissions for user "{0}" to execute delete search command in organization scope.**
Explanation	To execute delete search in organization scope the user should be either an CentraSite Administrator or an Organization Administrator.
Action	Make sure you have sufficient permissions to execute delete search command in organization scope.

INMCCE0285	**Insufficient permissions for user "{0}" to execute delete search command in global scope.**
Explanation	To execute delete search in global scope the user should be an CentraSite Administrator.
Action	Make sure you have sufficient permissions to execute delete search command in global scope.

INMCCE0286	**The list Action Categories command failed: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0287	**Action category with the given name {0} already exists.**
Explanation	Action category with the given name {0} already exists.
Action	Specify an unique ID (uuid) to rename the action category.

INMCCE0289	**Invalid ID(uuid) {0}.**
Explanation	Action category with the given ID(uuid) {0} does not exist.
Action	Provide valid UDDI key for the action category.

INMCCE0292	**Action category named {0} is updated successfully, but could not update the category type.**
Explanation	N/A
Action	N/A

INMCCE0293	**The add Action Category command failed: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0294	**The delete Action Category command failed: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0295	**Action category deletion failed. The category includes at least one active policy action. \nPolicy Action details: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0297	**The list Action Categories command failed: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0303	**The add action template command failed. {0}**
Explanation	Could not execute the add action template command.
Action	Check the CentraSite logs for the reason for the failure. Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0313	**The delete Action Category command failed: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0314	**The update action template command failed. {0}**
Explanation	Could not execute the update action template command.
Action	Check the CentraSite logs for the reason for the failure. Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0315	**The download Action Template command failed: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0317	**The get action template command failed. {0}**
Explanation	Could not execute the get action template command.
Action	Check the CentraSite logs for the reason for the failure. Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0319	**File path does not exist.**
Explanation	Destination Directory does not exist.
Action	Create Directory and execute the command again

INMCCE0321	**The setup Custom Action command failed: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0322	**The sync Ldap group command failed: {0}**
Explanation	Check the CentraSite logs for the reason for the failure.
Action	Run the command again after you have identified and fixed the issue(s). Ensure that all the parameters are correct and valid before you run the command. If the issue persists, contact Software AG support.

INMCCE0327	**Could not retrieve keystore aliases: {0}.**
Explanation	An error occurred while trying to retrieve the keystore aliases, possibly becuase of an invalid keystore format.
Action	Contact your administrator.

INMCCI0027	**Domain {0} not found**
Explanation	The domain to be processed does not exist.
Action	Correct the specified domain name.

INMCCI0032	**Domain {0} successfully added**
Explanation	The domain entry of the authentication configuration was created.
Action	No action required.

INMCCI0033	**Domain {0} successfully removed**
Explanation	The domain entry of the authentication configuration was removed.
Action	No action required.

INMCCI0034 **Validating LDAP domain {0}**

Explanation The validate command has started.

Action No action required.

INMCCI0035 **The LDAP server configuration has been successfully validated.**

Explanation The specified LDAP server configuration is valid.

Action No action required.

INMCCI0036 **LDAP user login validated successfully**

Explanation The user could log on with supplied user name and password.

Action No action required.

INMCCI0037 **LDAP user properties validated successfully**

Explanation The user properties configuration is valid.

Action No action required.

INMCCI0038 **LDAP group resolution validated successfully**

Explanation The group resolution settings are valid.

Action No action required.

INMCCI0044 **Creating CS Admin user {0} for domain {1}**

Explanation The processing for creating a user with the CentraSite Administrator role has started.

Action No action required.

INMCCI0045 **CS Admin user {0} created**

Explanation A user with the CentraSite Administrator role has been successfully created.

Action No action required.

INMCCI0048 **Do you want to see the LDAP search trace? {0}:**

Explanation This prompt asks you whether or not you want to see the LDAP search results.

Action Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.

INMCCI0049	**User elements found: {0}. Do you want to see them?**
Explanation	The LDAP search found the given number of users.
Action	Type Y to see the results, otherwise N.

INMCCI0050	**Do you want to see all the users? (Y/N) [N]:**
Explanation	This prompt asks you whether or not to display all of the users.
Action	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.

INMCCI0051	**User with filter: {0}**
Explanation	User search filter
Action	search filter needs to be entered

INMCCI0052	**{0} The following group was found:**
Explanation	{0} --> ok
Action	No action

INMCCI0057	**Can't get user properties. {0}**
Explanation	{0} --> error message
Action	re-configure the user properties

INMCCI0061	**{0} User authenticated successfully**
Explanation	The user authentication was successful. The returned status is {0}.
Action	No action required.

INMCCI0062	**Trying to ping the server now...**
Explanation	An attempt is being made to connect to the server.
Action	No action required.

INMCCI0063	**Is the connection to the server protected with SSL? (Y/N) [N]:**
Explanation	This prompt asks you whether or not the LDAP connection to the server is protected with SSL.
Action	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.

INMCCI0064	**Do you want use LDAP Technical User? (Y/N) [N]:**
Explanation	The prompt asks whether or not you wish to use the LDAP Technical User.
Action	Type Y (for yes) or N (for no) as required. The default is N.

INMCCI0065	**Provide the LDAP Technical User credentials file:**
Explanation	The credentials file of the the LDAP Technical User needs to be given as input.
Action	Specify the credentials file.

INMCCI0069	**Direct binding using the constructed DN was successful.**
Explanation	A direct binding using the constructed DN was successful.
Action	No action required.

INMCCI0070	**Do you want use LDAP Technical User Key file?**
Explanation	User key file needs to be given or not
Action	File path will be given as input

INMCCI0071	**Trying to connect to LDAP at: {0}:{1}**
Explanation	An attempt is being made to connect to LDAP at host {0} and port {1}.
Action	No action required.

INMCCI0072	**To test the connection, please provide the credentials of a valid LDAP user.**
Explanation	To test the connection, the credentials of a valid LDAP user are required.
Action	Provide the credentials of a valid LDAP user.

INMCCI0074	**Do you want to save the configuration to CentraSite? (Y/N) [N]:**
Explanation	The prompt asks you whether or not to save the modified configuration to CentraSite.
Action	Reply Y (for yes) or N (for no). The default value is N.

INMCCI0075	**To store the connection, please provide the credentials of a user with role "CentraSite Administrator".**
Explanation	The connection can only be stored by a user with the role "CentraSite Administrator".
Action	Provide the credentials of a user with the role "CentraSite Administrator".

INMCCI0076	**Repeat configuration step {0}, Continue, or End? (R/C/E) [C]:**
Explanation	You can either repeat the given configuration step, continue to the next step, or end the processing.
Action	Type R, C or E to select the required option. The default is C.

INMCCI0077	**Repeat configuration step {0} or End? (R/E) [R]:**
Explanation	You can repeat the given configuration step or end the processing.
Action	Type R or E to select the required option. The default is R.

INMCCI0078	**Check {0} - Validating LDAP server configuration. Please wait...**
Explanation	This message is displayed when validating the LDAP server configuration settings.
Action	No action required.

INMCCI0079	**Check 2: LDAP User >> PLEASE WAIT...**
Explanation	This message is shown when the configuration of the LDAP user is being checked.
Action	No action required.

INMCCI0080	**Check 3: LDAP User Authentication >> PLEASE WAIT...**
Explanation	This message is shown when the configuration of the LDAP user authentication is being checked.
Action	No action required.

INMCCI0081	**Check 3: LDAP User Properties >> PLEASE WAIT...**
Explanation	This message is shown when the configuration of the LDAP user properties is being checked.
Action	No action required.

INMCCI0082	**Check 4: LDAP User Search >> PLEASE WAIT...**
Explanation	This message is shown when the configuration of the LDAP user search is being checked.
Action	No action required.

INMCCI0083 **Check 5: LDAP Group >> PLEASE WAIT...**

Explanation This message is shown when the configuration of the LDAP group is being checked.

Action No action required.

INMCCI0084 **Check 6: LDAP Group Mapping >> PLEASE WAIT...**

Explanation This message is shown when the configuration of the LDAP group mapping is being checked.

Action No action required.

INMCCI0085 **Check 7: LDAP Group Search >> PLEASE WAIT...**

Explanation This message is shown when the configuration of the LDAP group search is being checked.

Action No action required.

INMCCI0086 **Check 8: LDAP Group Resolution Host >> PLEASE WAIT...**

Explanation This message is shown when the configuration of the LDAP group resolution host is being checked.

Action No action required.

INMCCI0087 **Check 9: Displaying and saving configuration in CentraSite >> PLEASE WAIT...**

Explanation This message is shown when the checked LDAP configuration is being saved in CentraSite.

Action No action required.

INMCCI0095 **Do you want to see the complete trace? {0} :**

Explanation The prompt asks you whether or not you want to see the complete trace.

Action Type Y (yes) or N (no) as required. The default is N.

INMCCI0097 **Group elements found: {0} . Do you want to see them?**

Explanation This is a confirmation message indicating that group elements have been found.

Action Reply Yes if you want to see the group elements.

INMCCI0098	**Do you want to see all groups? {0} :**
Explanation	This prompt asks you if you want to see all groups.
Action	Reply Yes if you want to see the groups.

INMCCI0099	**Groups with filter: {0}**
Explanation	This is a confirmation message indicating that groups have been found with the filter.
Action	No action required.

INMCCI0101	**Groups for user found: {0} Do you want to see them?**
Explanation	Groups were found for the given user.
Action	Reply Yes if you want to see the groups that were found.

INMCCI0107	**Do you want to use the LDAP Technical User {0}:**
Explanation	This prompt asks you whether you want to use the LDAP Technical User (LDAP Principal) to access the LDAP user repository. If you reply Y, all authentication requests sent to the LDAP server will be made using this user. If you reply N, the client has to send its own credentials to LDAP to access a user record.
Action	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.

INMCCI0108	**Provide the LDAP Technical User credentials file.**
Explanation	This prompt asks you to provide the LDAP Technical User credentials file.
Action	Provide the LDAP Technical User credentials file.

INMCCI0109	**Provide the LDAP Technical User Key file**
Explanation	This prompt asks you to provide the LDAP Technical User Key file.
Action	Provide the LDAP Technical User key file.

INMCCI0110	**Trying to connect to LDAP at: {0}**
Explanation	An attempt is being made to connect to the LDAP Server with the given host name and port.
Action	No action required.

INMCCI0133	**The target identified by "{0}" has been removed from the configured federation targets.**
Explanation	The target identified by "{0}" has been removed from the configured federation targets during the execution of the command.
Action	No action required.

INMCCI0134	**A target is already associated with the given federation id "{0}".**
Explanation	The provided federation identifier already has a target associated with it.
Action	To obtain more details about the target associated with ID "{0}", execute the command show_uddi_federation.

INMCCI0135	**Do you want to update/overwrite the target at {0} ? {1} :**
Explanation	While running the add_uddi_federation command with the ID {0}, it may be already configured with another target. Then you should choose whether you want to update the target or not.
Action	Enter either y (Yes) to update/overwrite the target, or n (No) to do no modification. The default is y (Yes).

INMCCI0136	**Not overwriting the current configuration. Please provide another federation identifier**
Explanation	While executing the add_uddi_federation command, if an already existing identifier is provided, and you choose not to overwrite the target, then this message is displayed.
Action	You can provide a new identifier which does not already exist. To obtain the list of configured federation identifiers, execute the command show_uddi_federation.

INMCCI0137	**Overwriting/updating the target identified by "{0}"**
Explanation	While executing the command add_uddi_federation, if the provided federation identifier already exists, and you choose to overwrite/update the target, then you get this message.
Action	No action required.

INMCCI0138	**A target has been added/updated with the federation identifier {0}**
Explanation	This message is displayed if a target for federation has been successfully configured with the provided federation ID.
Action	No action required.

INMCCI0143	**Number of targets configured for federation : {0}**
Explanation	This message displays the number of targets configured for federation. {0} - Number of targets
Action	No action required.

INMCCI0145	**Deployment succeeded**
Explanation	The deployment succeeded.
Action	No action required.

INMCCI0147	**There are no Consumer Applications to deploy.**
Explanation	There are no consumer applications created in CentraSite to deploy.
Action	Create consumer applications in CentraSite to deploy to Mediator.

INMCCI0148	**The XML configuration of the Federation target "{0}":**
Explanation	The XML configuration of the federation target identified by {0} will be displayed in the console.
Action	No action required.

INMCCI0149	**The XML configuration of the Federation target "{0}" has been written to file "{1}"**
Explanation	This message informs that the XML configuration of the federation target identified by {0} has been written to the file located at {1}.
Action	No action required.

INMCCI0150	**The XML log configuration can be seen below:**
Explanation	The XML log configuration will be displayed to the console.
Action	No action required.

INMCCI0151	**The XML log configuration has been written to the file "{0}"**
Explanation	This message informs that the XML log configuration has been written to the file located at {0}.
Action	No action required.

INMCCI0176 **Domain {0} not found in jaas.config**

Explanation The domain to be processed does not exist in jaas.config

Action Correct the specified domain name.

INMCCI0228 **Do you really want to save the configuration {0}**

Explanation When the end of the command is reached, the user is asked if the created LDAP configuration should be added to the current jaas.config file.

Action Reply Y (for yes) or N (for no). There is no default value.

INMCCI0229 **The configuration has been saved successfully.**

Explanation The LDAP configuration has been added successfully to the current jaas.config file.

Action No action required.

INMCCI0232 **Check {0} - Validating LDAP user configuration. Please wait...**

Explanation This message is displayed when validating the LDAP user configuration settings.

Action No action required.

INMCCI0233 **The LDAP user configuration has been successfully validated.**

Explanation The specified LDAP user configuration is valid.

Action No action required.

INMCCI0236 **Check {0} - Validating LDAP user mapping configuration. Please wait...**

Explanation This message is displayed when validating the LDAP user mapping configuration settings.

Action No action required.

INMCCI0237 **The LDAP user mapping configuration has been successfully validated.**

Explanation The specified LDAP user mapping configuration is valid.

Action No action required.

INMCCI0239 **The following attributes have been retrieved for the LDAP user {0}:**

Explanation Displays a list of mapped user attributes for the LDAP user {0}.

Action No action required.

INMCCI0240	**No attributes could be retrieved for user {0}.**
Explanation	Could not retrieve attributes for the specified LDAP user {0}, possibly because all of the attributes are empty.
Action	No action required.

INMCCI0241	**No users were found matching search criteria {0}.**
Explanation	Could not find any users matching the specified search criteria {0}.
Action	No action required.

INMCCI0242	**The following users match the search criteria {0}:**
Explanation	Displays a list of LDAP users matching the search criteria {0}.
Action	No action required.

INMCCI0243	**The following users match the search criteria {0}. The following list only displays the first ten users matching the specified search criteria:**
Explanation	Displays the first ten users matching the search criteria {0}.
Action	No action required.

INMCCI0244	**No attributes could be retrieved for group {0}.**
Explanation	Could not retrieve attributes for the specified LDAP group {0}, possibly because all of the attributes are empty.
Action	No action required.

INMCCI0245	**No groups were found matching search criteria {0}.**
Explanation	Could not find any groups matching the specified search criteria {0}.
Action	No action required.

INMCCI0246	**The following groups match the search criteria {0}:**
Explanation	Displays a list of LDAP groups matching the search criteria {0}.
Action	No action required.

INMCCI0247 **The following groups match the search criteria {0}. The following list only displays the first ten groups matching the specified search criteria:**

Explanation Displays the first ten groups matching the search criteria {0}.

Action No action required.

INMCCI0248 **The LDAP group mapping configuration has been successfully validated.**

Explanation The specified LDAP group mapping configuration is valid.

Action No action required.

INMCCI0249 **Check {0} - Validating LDAP group mapping configuration. Please wait...**

Explanation This message is displayed when validating the LDAP group mapping configuration settings.

Action No action required.

INMCCI0250 **The following attributes have been retrieved for the LDAP group {0}:**

Explanation Displays a list of mapped group attributes for the LDAP group {0}.

Action No action required.

INMCCI0251 **Check {0} - Validating LDAP group configuration. Please wait...**

Explanation This message is displayed when validating the LDAP group configuration settings.

Action No action required.

INMCCI0252 **The specified LDAP group could not be found.**

Explanation Could not find the specified LDAP group in the LDAP server.

Action No action required.

INMCCI0253 **The LDAP group configuration has been successfully validated.**

Explanation The specified LDAP group configuration is valid.

Action No action required.

INMCCI0254 **Check {0} - Validating LDAP group resolution configuration. Please wait...**

Explanation This message is displayed when validating the LDAP group resolution configuration settings.

Action No action required.

INMCCI0255 **User {0} belongs to the following groups:**

Explanation Displays a list of LDAP groups to which the user with name {0} belongs to.

Action No action required.

INMCCI0256 **The LDAP group resolution configuration has been successfully validated.**

Explanation The specified LDAP group resolution configuration is valid.

Action No action required.

INMCCI0257 **User {0} belongs to the following groups:**

Explanation Displays the first ten LDAP groups to which the user with name {0} belongs to.

Action No action required.

INMCCI0258 **No groups were found to which the user {0} belongs to.**

Explanation Could not find any groups to which the specified user with name {0} belongs to.

Action No action required.

INMCCI0263 **Test user has successfully logged in.**

Explanation Test user has successfully logged in.

Action No action required.

INMCCI0265 **Search for user was successful.**

INMCCI0288 **Action category named {0} is created successfully.**

Explanation N/A

Action N/A

INMCCI0290 **Action category named {0} is updated successfully.**

Explanation N/A

Action N/A

INMCCI0291 **No changes available**
Explanation N/A
Action N/A

INMCCI0296 **Action category named {0} is deleted successfully.**
Explanation NA
Action NA

INMCCI0298 **Action template named {0} is created successfully.**
Explanation N/A
Action N/A

INMCCI0310 **Action template named {0} is updated successfully.**
Explanation N/A
Action N/A

INMCCI0312 **Action template named {0} is deleted successfully.**
Explanation NA
Action NA

INMCCI0316 **Action template named {0} is downloaded successfully to {1}.**
Explanation NA
Action NA

INMCCI0318 **Action template named {0} is downloaded successfully to {1}.**
Explanation NA
Action NA

INMCCI0320 **Custom policy action setup successful at {0}.**
Explanation NA
Action NA

INMCCI0323	**Group {0} synchronized successfully.**
Explanation	N/A
Action	N/A

INMCCI0324	**Members of the group {0} are already registered in CentraSite.**
Explanation	NA
Action	NA

INMCCW0004	**Default Organization is not present in CentraSite. Hence UDDI configurations cannot be saved.**
Explanation	UDDI Configurations for CentraSite will be stored in "Default Organization". CentraSiteCommand is not able to find the "Default Organization" in CentraSite and hence cannot store the UDDI configurations.
Action	Make sure the user provided to execute the command has permission to update the "Default Organization".

INMCCW0005	**No CentraSite Application Server Tier (CAST) found in CentraSite with specified cast URI {0}. Please specify fully qualified host name in -casturi option.**
Explanation	UDDI configurations for a CAST will be stored in an Application Server object. The object will have the host and port details. This object is required to store the local configurations for the CAST. CentraSiteCommand is not able to find the ApplicationServer object with the host specified in the cast URI option.
Action	Please make sure the value specified for the option cast URI is valid. Please specify the host as a fully qualified domain name in the cast URI option.

INMCCW0104	**unknown host**
Explanation	The host name provided is not the name of a known host.
Action	Provide a proper host name.

INMCCW0128	**An error occurred while trying to close a resource - {0}**
Explanation	Occasionally an error might be encountered while trying to close open connections, streams, etc., This is just a warning that an error was encountered and can be ignored.
Action	Make sure that the resource in question is not opened and/or modified by another program/application.

INMCCW0146	**Deployment failed**
Explanation	The deployment failed.
Action	Check related messages to find the reason why the deployment failed.

INMCCW0168	**Missing <LogSetting> attribute for <LogUnit> {0}.**
Explanation	The <LogSetting> attribute used to configure <LogUnit> {0} is missing.
Action	The <LogSetting> attribute is specified as an attribute name when configuring log unit in the config.xml file. For more information about log settings, see the CentraSite Administrator's Guide.

INMCCW0169	**The <LogUnit> {0} has a null value for the <LogSetting> attribute.**
Explanation	Required <LogSetting> attribute value is missing.
Action	The <LogSetting> value is specified as an attribute value when configuring log unit in the config.xml file. For more information about log settings, see the CentraSite Administrator's Guide.

INMCCW0230	**Configuration was not saved on user request!**
Explanation	The configuration was not saved, possibly because the user chose to reject it.
Action	No action required.

INMCCW0264	**Test User was not found.**
Explanation	Could not find the specified test user.
Action	No action required.

INMCCW0275	**You cannot deactivate the user(s). Reason**
Explanation	The user cannot be deactivated for the following reason(s):
Action	Check for the above reasons and then try again.

INMCCW0299	**Implementation-File parameter cannot be empty. Enter the name of a Java implementation file for policy action.**
Explanation	N/A
Action	N/A

INMCCW0300 **Action category named {0} does not exist.**

Explanation N/A

Action N/A

INMCCW0301 **Template-File parameter cannot be empty. Enter the name of an output file to download the action template.**

Explanation N/A

Action N/A

INMCCW0302 **Action template named {0} already exists.**

Explanation N/A

Action N/A

INMCCW0304 **Action must be associated at least to one object type.**

Explanation N/A

Action N/A

INMCCW0305 **Event type should have at least one value.**

Explanation N/A

Action N/A

INMCCW0306 **Parameter name cannot be empty.**

Explanation N/A

Action N/A

INMCCW0307 **Parameter type cannot be empty.**

Explanation N/A

Action N/A

INMCCW0308 **Policy action template with the given name {0} does not exist.**

Explanation NA

Action NA

INMCCW0309 **Implementation file of predefined action templates cannot be modified.**

Explanation NA

Action NA

INMCCW0311 **One or more required parameters in the action template configuration are missing.**

Explanation NA

Action NA

INMCCW0325 **Group with the given name {0} does not exist in {1}.**

Explanation NA

Action NA

INMCCW0326 **The specified object group {0} has wrong type.**

Explanation NA

Action NA

INMCLE0005 **CentraSite cannot delete the gateway. {0}**

Explanation An error occured while deleting a gateway in CentraSite.

Action Contact your system administrator with the stack trace information in the CentraSite log.

INMCLE0013 **Caught an exception while retrieving the configurator instance.**

Explanation This is an internal error. It is probably because of an invalid data in the configuration file.

Action Verify that the data in configuration file are valid.

INMCLE0014 **System is unable to retrieve value for {0}.**

Explanation This is an internal error. It is probably because of an invalid data in the configuration file.

Action Verify that the data in configuration file are valid.

INMCLE0015 **Invalid path {0}.**

Explanation You have entered an invalid path.

Action Enter a valid path.

INMCLE0017 **Failed to check whether or not property of {0} is read-only.**

Explanation Could not check whether or not the property of the given path {0} is read-only. The cause is not immediately known.

Action Check the stack trace for detailed information.

INMCLE0018 **Caught an exception while retrieving the configuration file of type {0}.**

Explanation This is an internal error. It is probably because of an invalid data in the configuration file.

Action Verify that the data in configuration file are valid.

INMCLE0019 **Caught an exception while trying to save the configuration file of type {0}.**

Explanation This is an internal error. It is probably because of an invalid data in the configuration file.

Action Verify that the data in configuration file are valid.

INMCLE0020 **Failed to remove {0}.**

Explanation This is an internal error. The cause is not immediately known.

Action Check the stack trace for detailed information.

INMCLE0021 **Caught an exception while trying to get the configuration file URL for type {0}.**

Explanation Could not get configuration file URL for type {0}, possibly because of an invalid data in the configuration file.

Action Verify that the data in configuration file are valid.

INMCLE0022 **Path or property value is empty.**

Explanation You have entered an empty path or property value.

Action Enter a valid path or property value.

INMCLE0023	**Failed to set configuration(s) for the path(s), {0}**
Explanation	Unable to set configuration(s) for the path(s). This is probably because of the following reasons: 1) configuration file is modified 2) failed to save the configuration file.
Action	Check to make sure that the configuration in a higher level is not already protected. Else, check the stack trace for detailed information.

INMCLE0024	**Failed to setProtectAll.**
Explanation	Unable to set ProtectAll configuration. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0025	**Failed to getAllItems.**
Explanation	Unable to get one or more configuration items. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0026	**Unable to construct ActivityMenuItem for id {0}.**
Explanation	Could not construct ActivityMenuItem for the given id {0}, possibly because the XPath of the ActivityMenuItem is invalid.
Action	Verify that the XPath of the ActivityMenuItem is valid.

INMCLE0027	**Unable to construct activity for id {0}.**
Explanation	Could not construct activity for the given id {0}, possibly because the XPath of the activity is invalid.
Action	Verify that the XPath of the activity is valid.

INMCLE0028	**Unable to construct ActivityMenuItem for activity {0}.**
Explanation	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
Action	Check to make sure that the XPath of the ActivityMenuItem and Activity is correct and the corresponding Activity could be created.

INMCLE0029	**Failed to instantiate class {0}.**
Explanation	Could not instantiate the implementation class {0}, possibly because the class does not follow a valid syntax.
Action	Verify that the implementation class follows a valid syntax. Refer to the documentation reference for Activity Implementation class.

INMCLE0030	**Unable to find activity entry for id {0}.**
Explanation	Could not find an activity entry for the given id {0}, possibly because the id is invalid.
Action	Verify that the given activity id is correct.

INMCLE0031	**Unable to construct an ActivityMenu using activities.**
Explanation	Could not construct an ActivityMenu using the given activities. It is probably because, the activities do not exist.
Action	Verify that the activities exist. If the problem persists, contact the CentraSite administrator.

INMCLE0033	**Failed to remove ActivityMenuItems.**
Explanation	Could not remove the ActivityMenuItems from given configuration file. It is possibly because of the following reasons: 1) XPath to remove the ActivityMenuItem is invalid. 2) ActivityMenuItem does not exist.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.

INMCLE0034	**Failed to save ActivityMenuItems.**
Explanation	Could not save the ActivityMenuItems from given configuration file. It is possibly because of the following reasons: 1) XPath to save the ActivityMenuItem is invalid. 2) ActivityMenuItem does not exist.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.

INMCLE0035	**User has not passed the CentraSite connection object. For a valid diagnostics configuration, CentraSite connection object is mandatory.**
Explanation	User has not passed the CentraSite connection object, which is mandatory for a valid diagnostics configuration.
Action	Enter a valid CentraSite connection object.

INMCLE0036	**Email address is empty,**
Explanation	You have not entered the email address for diagnostics configuration. An email address is mandatory to send the diagnostic information.
Action	Enter a valid email address.

INMCLE0037	**Email subject and template are empty.**
Explanation	You have not entered the email subject and template for diagnostics configuration. An email template is mandatory to send the diagnostic information. Refer to the CentraSite online documentation's section "Message Handling and Diagnostics".
Action	Enter the email subject and a valid template.

INMCLE0038	**Failed to get all activities.**
Explanation	Could not get all the activities, possibly because the activity classes are not set in the classpath.
Action	Verify that the activity classes are set in the classpath. If the problem persists, contact the CentraSite administrator.

INMCLE0039	**Failed to remove activity for given id {0}.**
Explanation	Could not remove the activity for given id {0}, possibly because the activity id is invalid.
Action	Verify that the given activity id is valid.

INMCLE0040	**Failed to show one or more activity menu items that are associated with activity menu.**
Explanation	Could not display one or more activity menu items, possibly because the menu items are not associated with the activity menu.
Action	Verify that all the activity menu items are associated with activity menu.

INMCLE0041	**Failed to populate diagnostic context.**
Explanation	Could not populate the diagnostic context object, possibly because the CentraSite Connection object is incorrect.
Action	Verify that the CentraSite Connection object is correct.

INMCLE0042	**Invalid CentraSite connection URL {0}.**
Explanation	You have entered an invalid CentraSite Connection URL.
Action	Enter a valid CentraSite Connection URL.

INMCLE0043	**User has not passed CLLException object. For a valid diagnostics configuration, CLLException object is mandatory.**
Explanation	User has not passed the CLLException object which is mandatory for the diagnostics configuration.
Action	Enter a valid CLLException object.

INMCLE0044	**Unable to fetch email template from repository {0}.**
Explanation	Could not fetch the email template from given repository {0}, possibly because of the following reasons: 1) email template does not exists 2) repository URL is invalid.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.

INMCLE0045	**Error loading implementation class for ActivityManager.**
Explanation	An unexpected error occurred while trying to load the implementation class for given ActivityManager. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0046	**Error loading diagnosticHandler implementation class.**
Explanation	An unexpected error occurred while trying to load the diagnosticHandler implementation class. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0048	**Failed to instantiate class {0}.**
Explanation	Could not instantiate the given class {0}, possibly because of the following reasons: 1) class file does not exist 2) classpath is incorrect.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.

INMCLE0049	**Failed to initialize {0}.**
Explanation	Could not initialize the given component {0}.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0050	**Failed to get CentraSite registry object property {0}.**
Explanation	Could not get the CentraSite registry object property. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0051	**Failed to set registry object property {0}.**
Explanation	Could not set the CentraSite registry object property. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0052	**Failed to save CentraSite object {0}.**
Explanation	An error occurred while trying to save CentraSite model object. Possible reasons: {1}
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0053	**Failed to delete CentraSite object {0}.**
Explanation	Could not delete the CentraSite object. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0054	**Failed to get CentraSite object for id {0}.**
Explanation	Could not get CentraSite object for the given id {0}, possibly because the object id is invalid.
Action	Verify that the object id is valid.

INMCLE0055	**Failed to create CentraSite object {0}.**
Explanation	You cannot create the CentraSite object {0}, possibly because of the following reasons: 1) insufficient privileges to create the object 2) object type is invalid.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0056	**Failed to delete CentraSite object.**
Explanation	You cannot delete the CentraSite object {0}, possibly because you do not have the required permission to delete the object.
Action	Verify that you have the required permission to delete the CentraSite object. Contact your administrator and request permission if necessary and try again.

INMCLE0057	**Unable to get list of CentraSite objects: {0}.**
Explanation	You cannot retrieve the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to retrieve the objects.
Action	Verify that you have the required permission to retrieve the given objects. Contact your administrator and request permission if necessary and try again.

INMCLE0058	**Unable to save list of CentraSite objects: {0}**
Explanation	You cannot save the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to save the objects.{0}
Action	Verify that you have the required permission to save the given objects. Contact your administrator and request permission if necessary and try again.

INMCLE0059	**Unable to delete list of CentraSite objects:**
Explanation	You cannot delete the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to delete the objects.
Action	Verify that you have the required permission to delete the given objects. Contact your administrator and request permission if necessary and try again.

INMCLE0060	**Caught an unexpected exception while converting concept to CentraSiteObjectType.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0061	**Failed to populate ObjectType for given name {0}.**
Explanation	Could not populate the ObjectType for display name {0}, possibly because the given display name is incorrect.
Action	Verify that the display name is correct.

INMCLE0062	**Error retrieving the list of gateways.**
Explanation	CentraSite could not retrieve the list of existing gateways because of an error during gateway name validations.
Action	Contact your CentraSite Administrator.

INMCLE0063	**Unsupported attribute {0} for object type {1}.**
Explanation	This is an internal error. Cannot find the attribute {0} of the specified object type {1}.
Action	Check to make sure that the attribute {0} is present in the object type {1}.

INMCLE0064	**Failed to fetch attributes for {0}.**
Explanation	Could not fetch attributes for {0}, possibly because the object type {1} is invalid.
Action	Verify that the object type {1} is valid.

INMCLE0065	**Unable to obtain value for attribute {0}.**
Explanation	Could not obtain the value for attribute {0}. The cause is not immediately known.
Action	Verify integrity of the object and try later.

INMCLE0066	**Unsupported method for attribute {0} of object type {1}.**
Explanation	This method is not applicable for attribute {0} of object type {1}.
Action	Do not use this method for attribute {0} of object type {1}.

INMCLE0067	**Error while initializing CentraSiteConnector {0}.**
Explanation	Could not initialize the CentraSiteConnector {0}. It is probably because of the following reasons: 1) invalid class as CentraSite Connection Factory 2) invalid system property (com.softwareag.centrasite.common.connection.impl) for initializing.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0068	**Failed to create an ActivityMenuItem for id {0}.**
Explanation	Could not create the ActivityMenuItem for above id, possibly because of the invalid configurations.
Action	Verify that the activity id and class name are configured properly.

INMCLE0069	**Error when closing connection {0}.**
Explanation	Error occurred when trying to close the underlying connection.
Action	Initialize before opening a connection.

INMCLE0070	**Failed to log in {0}.**
Explanation	Could not log in {0}, possibly because the login credentials are invalid.
Action	Enter valid login credentials.

INMCLE0071	**Cannot instantiate CentraSiteConnector class {0}.**
Explanation	Could not instantiate the CentraSiteConnector implementation class, possibly because the implementation class in invalid.
Action	Check to make sure that the CentraSiteConnector class is valid.

INMCLE0072	**Error loading email template {0} {1}.**
Explanation	Error when loading the admin and/or user email templates, possibly because the email template path is invalid.
Action	Verify that the email template path is valid.

INMCLE0073	**Email address is empty.**
Explanation	You have not entered an email address.
Action	Enter a valid email address.

INMCLE0074	**Invalid attribute {0} {1}.**
Explanation	The attribute {1} is not a valid {0} attribute.
Action	Check to make sure that the {1} attribute is valid.

INMCLE0075	**Usage of {0} operation in object {1} is not supported.**
Explanation	This operation is not supported on the given object {1}.
Action	Refer to the usage document for further information on the supported APIs.

INMCLE0076	**Unable to obtain relationship details of attribute {0} to object type {1}.**
Explanation	Could not obtain the relationship details of attribute {0} associated to the above object type {1}.
Action	Make sure that the attribute {0} is a valid relationship attribute for the object type {1}.

INMCLE0077	**Failed to execute query {0}.**
Explanation	Could not execute the query {0}, possibly because the query syntax is incorrect.
Action	Correct the query syntax.

INMCLE0078	**Failed to execute query {0}.**
Explanation	Could not execute the query {0}, possibly because the query syntax is incorrect.
Action	Correct the query syntax.

INMCLE0079	**Failed to get objectTypeValue from given ObjectType.**
Explanation	Could not get the objectTypeValue from ObjectType, possibly because the given ObjectType is invalid.
Action	Check to make sure that the given ObjectType is valid.

INMCLE0080	**Failed to construct search query.**
Explanation	Could not construct the search query. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0081	**Caught an exception while getting iterator from CSOSearchResult.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0082	**Failed to get search result count.**
Explanation	Could not get the number of results displayed on the Search Results page. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0083	**Unable to fetch next object for id {0}.**
Explanation	An unexpected exception occurred while trying to fetch the next object for above id.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0084	**The configuration file is invalid; attribute {0} is mandatory for multi-valued elements.**
Explanation	The required attribute for multi-valued elements is not specified in the XML configuration file.
Action	Before you save the configuration file, check to make sure that all the required attributes are specified.

INMCLE0085	**The configuration file is invalid; attribute {0} is mandatory for multi-valued elements.**
Explanation	The required attribute for multi-valued elements is not specified in the XML configuration file.
Action	Before you save the configuration file, check to make sure that all the required attributes are specified.

INMCLE0086	**Failed to fetch common attribute {0}.**
Explanation	Could not fetch the common attribute {0}, possibly because the attribute does not exist.
Action	Verify that the common attribute {0} is valid.

INMCLE0087	**Caught an exception while trying to set value for attribute {0}.**
Explanation	Could not set a value for attribute {0}. It is probably because of the following reasons: 1) attribute does not exist 2) attribute is read-only.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0088	**Failed to retrieve attribute {0}.**
Explanation	Could not retrieve attribute {0}, possibly because the attribute does not exist.
Action	Verify that the attribute is valid.

INMCLE0089	**{0} based search has null or empty value.**
Explanation	Could not execute {0} based search, possibly because of a null or empty value in the search criteria.
Action	Check to make sure that the search criteria is valid.

INMCLE0090	**Data type {0} in search criteria is invalid.**
Explanation	The specified data type {0} in search criteria is not supported.
Action	Specify a valid data type. Refer to the CentraSite online documentation's section "Attribute Data Types" for a list of the supported data types.

INMCLE0091	**The number of values provided in the search criteria does not match with the mandatory number allowed for the operator {0}.**
Explanation	Every operator will support only the specified number of values. This error occurs when the number of values entered is less than or greater than the specified number.
Action	Refer to the CentraSite online documentation's section "Searching the CentraSite Catalog".

INMCLE0092	**Failed to serialize search {0}.**
Explanation	Could not serialize the above search, possibly because of invalid parameters in the search criteria.
Action	Check to make sure that the mandatory parameters are specified in search criteria.

INMCLE0093	**Failed to create folder in WebDav.**
Explanation	Could not create folder in the WebDav, possibly because you do not have the necessary permission to create a folder or intermediate folder in WebDav.
Action	Verify that you have the required permission to create a folder or intermediate folder in WebDav.

INMCLE0094	**Failed to retrieve file from given URI {0}.**
Explanation	Could not retrieve file from the above URI. This is probably because of the following reasons: 1) file does not exist 2) insufficient permissions to read the file.
Action	Check for the above possible reasons and execute again. If the problem persists, contact your service provider.

INMCLE0095	**Search cannot be executed with given URI {0}.**
Explanation	Could not execute a search with URI {0}, possibly because the given URI is invalid.
Action	Verify that the specified URI is valid. If the problem persists, contact the CentraSite administrator.

INMCLE0096	**Failed to parse persisted search output {0}.**
Explanation	Could not parse the search output, possibly because of an invalid XML syntax.
Action	Verify that the XML syntax is correct.

INMCLE0097	**Failed to convert input {0} to bytes.**
Explanation	Could not convert the given input {0} to bytes. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0098	**Failed to read output.**
Explanation	Failed to read the output, possibly because the input or output stream is closed.
Action	Make sure that the input or output stream is open.

INMCLE0099	**Failed to initialize parser.**
Explanation	Error: could not initialize parser. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0100	**Failed to get search data stored in folder {0}.**
Explanation	Could not get search data files that were stored in the above folder, possibly because you do not have insufficient permission to access the files.
Action	Verify that you have required permissions to access the data files.

INMCLE0101	**Cannot instantiate class{0}.**
Explanation	Could not instantiate the above class, possibly because the class is incorrect.
Action	Check to make sure that the implementation class is correct and follows a specified syntax. Refer to the documentation reference for Action Implementation class.

INMCLE0102	**Failed to load actions from system configurations.**
Explanation	Could not load specific actions from the system configuration file because of the following reasons: 1) class name for action is incorrect 2) action is not configured.
Action	Check to make sure that the class name for actions is correct and is configured in your system.xml file.

INMCLE0103	**Unable to retrieve actions for null parameter.**
Explanation	Internal error. It is possibly because you are trying to pass parameter with null value.
Action	Check if the parameter contains a null value.

INMCLE0104	**Failed to get configurator {0}**
Explanation	Could not get the above configurator, possibly because you do not have the required permissions.
Action	Verify that you have the required permission to get configurator. Contact your administrator and request permission if necessary and try again.

INMCLE0105	**Failed to get owner from connection.**
Explanation	Could not get the owner from connection, possibly because you do not have the required permissions.
Action	Verify that you have the required permission to get owner from connection. Contact your administrator and request permission if necessary and try again.

INMCLE0106	**Login failed.**
Explanation	Failed to login to CentraSite. It is possibly because of the following reasons: 1) incorrect CentraSite URL 2) invalid authentication credentials.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0107	**{0} object is null.**
Explanation	Error: given object is null.
Action	Check to make sure that the given object is not null.

INMCLE0108	**Failed to get an instance of component {0}.**
Explanation	Could not get an instance of the above component. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0111	**Failed to remove file {0} from WebDaV.**
Explanation	Could not create a folder in WebDav. It is probably because of the following reasons: 1) file does not exist in WebDav 2) insufficient permission to remove a file from WebDav.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0112	**Failed to create a file in {0}.**
Explanation	Could not create a file in {0}, possibly because the parent directory does not exist in the given location.
Action	Verify that parent directory exists in the given location.

INMCLE0113	**Could not instantiate AccessControlElement.**
Explanation	Unable to instantiate the AccessControlElement. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0114	**Failed to find resource exists for given URL {0}.**
Explanation	Could not find the file for given URL. It is probably because the file does not exist in the given URL.
Action	Check to make sure that the file exists in given URL.

INMCLE0115	**Failed to purge older versions of CentraSite object.**
Explanation	Could not purge older versions of the CentraSite object. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0116	**Unable to version CentraSite object.**
Explanation	Could not create a new version of the CentraSite object. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0117	**Unable to obtain base type for {0}.**
Explanation	Could not obtain the base type for {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0118	**Failed to retrieve profiles for {0}.**
Explanation	Could not retrieve profiles for {0} because of the following reasons: 1) failure in retrieving profiles from type 2) insufficient permission for accessing the profiles.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0119	**Failed to retrieve information for profile {0}.**
Explanation	Could not retrieve the information for profile. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0120	**Failed to choose assets for {0}.**
Explanation	Could not choose the assets for executing above action, possibly because the action is not in the 'initial' state.
Action	Verify that the action is in 'initial' state.

INMCLE0122	**Failed to retrieve immediate allowed states.**
Explanation	This is an unexpected exception. It is probably because the current lifecycle state does not have at least one immediate state.
Action	Check to make sure that the current lifecycle state has at least one immediate state.

INMCLE0123	**Failed to retrieve immediate preferred state**
Explanation	This is an unexpected exception. It is probably because the current lifecycle state does not have at least one immediate state.
Action	Check to make sure that the current lifecycle state has at least one immediate state.

INMCLE0124	**Failed to retrieve current state.**
Explanation	This is an unexpected exception. It is probably because the object is not associated with any of the lifecycle model.
Action	Check to make sure that the object type is associated with at least one lifecycle model.

INMCLE0125	**Failed to retrieve pending state.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.

INMCLE0126	**Failed to identify if state of object is pending or not.**
Explanation	Could not identify if state of the object is in pending or not. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.

INMCLE0127	**Failed to get lifecycle model assigned types.**
Explanation	Could not get the lifecycle model assigned types. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.

INMCLE0128	**Failed to identify initial state of lifecycle model.**
Explanation	Could not identify initial state of the lifecycle model. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.

INMCLE0129	**Failed to get applicable states of lifecycle model.**
Explanation	Could not get applicable states of the lifecycle model. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.

INMCLE0130	**Failed to identify if given lifecycle model is global or not.**
Explanation	Could not identify if the given lifecycle model belongs to the global category. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.

INMCLE0131	**Mandatory parameters to identify applicable lifecycle models are empty.**
Explanation	An attempt is made to pass one or more of the mandatory parameters (CentraSiteObjectType or Organization) empty.
Action	Enter valid value for the mandatory parameters.

INMCLE0132	**Mandatory parameters to identify applicable lifecycle models are empty.**
Explanation	An attempt is made to pass one or more of the mandatory parameters (Keyword, CentraSiteObjectType or Organization) empty.
Action	Enter valid value for the mandatory parameters.

INMCLE0133	**setParameter value for a CSOSearch is empty.**
Explanation	An attempt is made to pass an empty list of values for the setParameter of CSOSearch.
Action	Enter a valid list of values for the CSOSearch.

INMCLE0134	**Invalid authentication credentials.**
Explanation	You have entered invalid authentication credentials.
Action	Enter valid authentication credentials.

INMCLE0135	**Folder {0} does not exist.**
Explanation	The specified folder does not exist in WebDav.
Action	Create the folder in WebDav and try again.

INMCLE0136	**Choose the CentraSite Object(s) to perform this action.**
Explanation	You have not chosen the CentraSite Object(s) for performing this action.
Action	Choose the CentraSite Object(s) to perform this action.

INMCLE0137	**Failed to perform {0} on multiple CentraSite objects.**
Explanation	You cannot perform {0} on multiple CentraSite objects at a time.
Action	Ensure you choose only one CentraSite object for performing {0}.

INMCLE0138	**Failed to check if {0} is applicable or not.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0139	**Failed to perform {0} on specified CentraSite object(s).**
Explanation	Could not perform {0} on the specified CentraSite object(s) due to one or more of the following reasons: (1) inufficient permission (2) CentraSite object is in 'Pending' state (3) CentraSite object is locked for editing by another user.
Action	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

INMCLE0140 **Failed to verify if current user has Edit permission on {0}.**

Explanation This is an unexpected exception. The cause is not immediately known.

Action Check the stack trace for detailed information.

INMCLE0141 **You are trying to modify an outdated asset.**

Explanation You are trying to modify an asset which is outdated.

Action Before you start to edit an asset, refresh the details page.

INMCLE0142 **Failed to verify if user has Move permission on CentraSite object.**

Explanation This is an unexpected exception. The cause is not immediately known.

Action Check the stack trace for detailed information.

INMCLE0143 **Failed to cancel {0}.**

Explanation This is an unexpected exception. The cause is not immediately known.

Action Check the stack trace for detailed information.

INMCLE0144 **Error loading saved search with name {0}.**

Explanation This is an unexpected exception. The cause is not immediately known.

Action If the problem persists, contact our technical support.

INMCLE0145 **{0} is required for CSOSearch.**

Explanation Mandatory property {0} for executing a CSOSearch is missing.

Action Check to make sure that the mandatory property is specified.

INMCLE0146 **Mismatch of attribute {0} specified in {1} with {2}.**

Explanation The attribute in {1} does not match with the given {2}.

Action Remove the faulty {1} and execute again.

INMCLE0147 **Caught an exception while getting profile id for {0}.**

Explanation Could not retrieve the profile id for {0}. The cause is not immediately known.

Action Check the stack trace for detailed information.

INMCLE0148	**{0} with name {1} used in {2} does not exist.**
Explanation	{0} with name {1} used in {2} does not exist.
Action	Contact the CentraSite administrator.

INMCLE0149	**Object {0} is null.**
Explanation	Could not get the object {0}.
Action	The object should be initialized before executing this operation.

INMCLE0150	**Caught an exception while trying to fetch pending approval requests.**
Explanation	Could not fetch pending approval requests for the logged in user. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0151	**Caught an exception while trying to verify if the logged in user has CentraSite Administrator role.**
Explanation	Could not verify if the logged in user has CentraSite Administrator role. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0152	**Wrong usage of {0} method.**
Explanation	Wrong usage of {0} method. This method is allowed only in the following scenarios: (1) if the action is in {1} state (2) before triggering the finishAllSteps() execution.
Action	Make sure that the method is used in one of the above scenarios. If the problem persists, contact the CentraSite administrator.

INMCLE0153	**{0} execution without comments is invalid.**
Explanation	{0} execution without comments is invalid. The approver has not specified his/her comments for {0}.
Action	Enter the comments for {0} using {1} API.

INMCLE0154	**Failed to execute {0}.**
Explanation	Could not execute {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0155	**Failed to execute {0}**
Explanation	Could not execute {0} due to one or more of the following reasons: (1) {0} is not allowed at the time of execution (2) assets for {0} are in 'Completed' state (3) for a Revert action, the you should have the CentraSite administrator role (4) you do not have a pending approval flow to proceed with {0}.
Action	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

INMCLE0157	**Invalid state transition from {0} by invoking {1} operation.**
Explanation	The state transition from {0} by invoking the {1} operation is not valid.
Action	See the Action Java API documentation for more details.

INMCLE0158	**One or more assets you have selected is not the most recent version of the asset.**
Explanation	One or more selected assets is not the most recent version of the asset.The New Version action does not apply to assets with intermediate version.
Action	Check to make sure that the selected assets for versioning are in their most recent version.

INMCLE0159	**Failed to create new version assets.**
Explanation	Error occured when trying to create new version assets. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0160	**Caught an exception while invoking {0} operation.**
Explanation	An unexpected exception occurred while trying to execute the {0} operation.
Action	Check the stack trace for detailed information.

INMCLE0161	**Could not exclude a CentraSite object in {0} state from export. The object should be in "Export Preview" state.**
Explanation	CentraSite object in a state other than "Export Preview" cannot be excluded from export. The CentraSite object in "Export Preview" state will only have the option to preview and modify the export list.
Action	Verify that the CentraSite object is in "Export Preview" state. Read the usage instructions of Export action before use.

INMCLE0162	**Could not obtain export archive of a CentraSite object in {0} state. The object should be in "Completed" state.**
Explanation	You cannot obtain an export archive of the CentraSite object, if the object is in a state other than "Completed".
Action	Verify that the CentraSite object is in "Completed" state. Read the usage instructions of Export action before use.

INMCLE0163	**Failed to execute Consume action.**
Explanation	Could not execute a Consume action, possibly because of one or more of the following reasons: 1) username is invalid 2) password is invalid 3) connection URL is incorrect.
Action	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

INMCLE0164	**An action in {0} state will not have Export List viewable. The action should be in "Export Preview" state.**
Explanation	You cannot view an export list if the action is in a state other than "Export Preview".
Action	Verify that the action is in "Export Preview" state. Read the usage instructions of Export action before use.

INMCLE0165	**Failed to execute Consume action.**
Explanation	{0} execution can fail due to one or more of the following reasons: (1) consumers are not selected (2) consumer requests are not registered.
Action	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

INMCLE0166	**CentraSiteObject type list is empty.**
Explanation	You have not entered a CentraSiteObject type list.
Action	Enter a valid CentraSiteObject type list.

INMCLE0167	**Invalid object {1} for object type {2}.**
Explanation	The specified CentraSite object {1} does not belong to CentraSiteObject type {2}.
Action	Enter a valid CentraSite object of type {2}.

INMCLE0168	**Caught an exception while trying to convert CentraSite objects.**
Explanation	This is an unexpected exception. This is probably because an attempt is made to convert RegistryObjects to CentraSiteObjects, and vice versa.
Action	Check the stack trace for detailed information.

INMCLE0169	**Invalid value set for {0}. Expected value : {1} Current value : {2}.**
Explanation	The specified values for search condition does not match with the expected value.
Action	See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.

INMCLE0170	**Failed to verify if user {0} is watching asset {0}.**
Explanation	Could not verify if the user {0} is watching the given asset. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0171	**Invalid operator set for {0}. Current operator: {1}. Supported operators for {2} type are {3}.**
Explanation	The specified operator for search does not match with the attribute's applicable operators.
Action	See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.

INMCLE0172	**Failed to get existing lists.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0173	**List {0} does not exist.**
Explanation	An attempt is made to pass the list {0} that is not available for the current user.
Action	Check to make sure that the list you pass for setExistingList(..) is available for the current user.

INMCLE0174	**Wrong usage of Add to List action API.**
Explanation	Incorrect usage of the Add to List action API. This problem occurs, when the '{0}' method is triggered with action in a state other than 'Show Available Lists'.
Action	Before you execute the {0} method, verify that the Add to List action is in 'Show Available Lists' state.

INMCLE0175	**List to add selected assets is not set.**
Explanation	List to add the selected set of assets is not set. Use the {0} method to set this list.
Action	Make sure that you use the {0} method to set the list to add selected assets.

INMCLE0176	**Failed to execute {0}.**
Explanation	{0} execution can fail for a number of reasons: (1) action is not allowed (2) action is not applicable at the time of execution (3) action is in 'Completed' state.
Action	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

INMCLE0177	**Failed to create a new list {0}.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0178	**Failed to add selected assets to the list.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0179	**Choose a document to attach to asset.**
Explanation	The document to attach to the asset is not specified.
Action	Call the setDocument method before invoking the execute method in Attach Document action.

INMCLE0180	**Failed to create {0}**
Explanation	Failed to create resources or asset. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.

INMCLE0182	**Data of type {0} is ignored.**
Explanation	Data of the above type defined for a CSOParameter is not supported.
Action	Use the supported data types for CSOParameter. See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.

INMCLE0183	**Current CSOSearch has unresolved parameters: {0}.**
Explanation	Current CSOSearch holds parameters that have a null value.
Action	Enter values for the unresolved parameters.

INMCLE0184	**Number of parameters defined in CSOSearch differs from parameters defined for the XQuery module.**
Explanation	Number of Parameters defined in the XQuery: {0} Number of Parameters defined in the CSOSearch: {1}.
Action	Validate your CSOSearch against the XQuery module.

INMCLE0185	**Missing parameters**
Explanation	The XQuery module used by the current CSOSearch requires {0} parameters.
Action	Validate the CSOSearch definition against the XQuery module that is being used.

INMCLE0186	**Cannot find Xquery module {1} in namespace {0}.**
Explanation	Could not find or load the XQuery module($0}:{1}) used by CSOSearch.
Action	Load the module / correct the CSOSearch definition.

INMCLE0187	**No CentraSite object is available for Export action.**
Explanation	You have not chosen the CentraSite objects for Export action.
Action	Choose the CentraSite objects for Export action.

INMCLE0188	**Configuration base directory is not set.**
Explanation	The configuration base directory specified by the path "com.softwareag.centrasite.api.configuration.basedir" is not set.
Action	Set the configuration base directory correctly. See the CentraSite online documentation for more details.

INMCLE0189	**Type {0} not valid for Attach Document action.**
Explanation	Could not perform the Attach Document action on selected type {0}.
Action	Enter a valid file. If the problem persists, contact the CentraSite administrator.

INMCLE0190	**Failed to attach given document.**
Explanation	Could not attach the given document, possibly because the document is invalid.
Action	Enter a valid document.

INMCLE0191	**CentraSite object {0} does not belong to any of the given types {1}.**
Explanation	The specified CentraSite object {0} does not belong to any of the given types {1}. Only objects that belong to the given types {1} are applicable for the Consume action.
Action	Choose a CentraSite object that belongs to one of the types {1}.

INMCLE0192	**Could not choose consumer object in current state {0}.**
Explanation	You cannot choose a consumer object in the current state {0}. The object should be in state {1}.
Action	Make sure that the consumer is in state {1}. Read the usage instructions of Consume action before use.

INMCLE0193	**List of consumers is empty.**
Explanation	An attempt is made to add an empty list of consumers for the Consume action.
Action	Choose a valid list of consumers. Read the usage instructions of Consume action before use.

INMCLE0194	**Error: Timeout - The Document Processor Thread timed out waiting for the required inputs.**
Explanation	You have not entered the required inputs within the time that the Document Processor was prepared to wait.
Action	Enter the required inputs as soon as prompted.

INMCLE0195	**Failed to process missing resources, {0}.**
Explanation	Could not process because the following resources are missing: {0}.
Action	Check to make sure that the required resources are specified.

INMCLE0196	**Failed to initialize AttachDocumentProcessorThread.**
Explanation	This is an internal error. The cause is not immediately known.
Action	Check to make sure that the mandatory inputs are specified.

INMCLE0198	**Failed to attach given document(s), Reason : {0}.**
Explanation	An exception occurred while trying to attach the document(s). This is probably because of the following reasons: 1) document is invalid 2) network failure.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0199	**Failed to get applicable reports for object {0}.**
Explanation	An unexpected exception occurred while trying to get applicable reports for {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0200	**Wrong usage of the View Report action API {0}.**
Explanation	Incorrect usage of the View Report action API. This problem occurs, when the '{0}' method is triggered with action in a state other than '{1}'.
Action	Before you execute the '{0}' method, verify that the action is in '{1}' state.

INMCLE0201	**Could not get selected report.**
Explanation	Failed to get the selected report, possibly because the report is not implicitly set for retrieval.
Action	Use the 'setSelectedReport(..)' to set a report for this action.

INMCLE0202	**Could not generate the selected report {0}.**
Explanation	An unexpected exception occurred while trying to generate the selected report {0}. The cause is not immediately known.
Action	Check the log file for detailed information.

INMCLE0203	**Failed to execute {0}.**
Explanation	You do not have permission to perform this action.
Action	Before executing {0} make sure that you have the 'Use the Reports UI' permission. Contact your CentraSite administrator and if necessary request access and then try again.

INMCLE0204	**Failed to close Centrasite ResourceAccessManager.**
Explanation	Caught an exception while trying to close the ResourceAccessManager. This is a system error.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0205	**CentraSite cannot create a gateway because the gateway already exists. Gateway type: {0}, gateway name: {1}. Specify another name for the gateway.**
Explanation	You are trying to create a gateway in CentraSite with an existing name and gateway type.
Action	Provide another name for the gateway and try the "set gateway" command again.

INMCLE0206	**Failed to export {0}.**
Explanation	Could not export the asset (s). This is probably because of the following reasons: 1) mandatory input is missing 2) prerequisite not satisfied.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.

INMCLE0207	**Exception in Export Processor Thread**
Explanation	Export Processor Thread caught an unhandled exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0208	**Specify mandatory {0}s for performing operation {1}.**
Explanation	To perform this operation you should set the mandatory inputs.
Action	Check to make sure that the mandatory inputs are specified.

INMCLE0209	**List to remove the selected assets is not set.**
Explanation	The list to remove the selected assets is not set. Use the {0} method to set this list.
Action	Make sure that you use the {0} method to set the list to remove the selected assets.

INMCLE0210	**Caught an unexpected exception when setting notification options for user {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0211	**Invalid file; specify a valid path to external file {0}.**
Explanation	You have entered an invalid file path.
Action	Enter a valid file path.

INMCLE0212	**Exception occurred when setting the specified email addresses for user {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0213	**Exception occurred when adding the specified telephone number for user {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0214	**Exception occurred when setting the specified name for user {0}.**
Explanation	An unexpected exception occurred when trying to set one of the specified name (First Name, Middle Name or Last Name) for the user {0}.
Action	Check the stack trace for detailed information.

INMCLE0215	**Parameter passed for {0} is null.**
Explanation	An attempt is made to specify the mandatory parameter {0} with a null value.
Action	Check to make sure that the {0} has a valid value.

INMCLE0216	**Exception occurred when trying to store the given profile picture in WEBDAV for user {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0217	**Exception occurred when trying to check for pending consumer registrations for user {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0218	**Exception occurred when trying to get Approval Request Reason for {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0219	**Exception occurred when trying to get Approval Workflow Name for {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0220	**{0} is triggered for consumer registration approval / rejection process; accessing {1} is invalid.**
Explanation	The {0} is triggered for consumer registration approval / rejection; accessing {1} is not valid.
Action	Accessing the {1} method for this kind of {0} is not valid. Ensure that you do not call this method here.

INMCLE0221	**Could not create/update a gateway because the gateway type is not specified. Specify the gateway type and try again.**
Explanation	The gateway type attribute is required to identify a gateway along with the gateway name. You have not specified the gateway type for the "set gateway" command in CentraSite.
Action	Specify the gateway type along with the name and other mandatory parameters, and try the "set gateway" command again.

INMCLE0222	**Exception occurred when trying to get Consumer Registration Requestor for {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0223	**Exception occurred when trying to get profile picture for user {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0224	**Exception occurred when getting the notification options for user {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0225	**Error loading predefined notification concepts**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0226	**Invalid phone type {0}.**
Explanation	You have entered an invalid phone type. The phone type should match one of the predefined types.
Action	Refer to CLL API documentation for details on predefined phone types.

INMCLE0228	**Invalid name {0}.**
Explanation	You have entered an invalid name.
Action	Enter a valid name without special characters.

INMCLE0229	**CentraSite could not create the gateway. You might not have permission to create a Mediator gateway.**
Explanation	User is not authorized to create a Mediator gateway in CentraSite.
Action	Contact your CentraSite administrator.

INMCLE0230	**Failed to create {0} for given URI {1}.**
Explanation	Failed to create a {0} for the given URI {1}, possibly because the Save operation is applicable only for WebDav resources.
Action	Save is applicable only for WebDaV resources.

INMCLE0231	**Failed to get content type for given URI {0}.**
Explanation	Failed to get content type for given URI {0}, possibly because the content type could not find the external URI.
Action	Failed to get content type for given URI {0}, possibly because the content type could not find the external URI.

INMCLE0232	**Unable to fetch folders from external URL {0}.**
Explanation	Could not get folders from an external URL, because this operation is only supported for a WebDaV URL.
Action	Enter a valid WebDav URL.

INMCLE0233	**Unable to fetch files from external URL {0}.**
Explanation	Could not fetch files from an external URL, because this operation is only supported for a WebDav URL.
Action	Enter a valid a WebDav URL.

INMCLE0234	**Failed to read XQuery from file {0}.**
Explanation	Could not read the XQuery from file, possibly because the file does not exist.
Action	Enter a valid file path.

INMCLE0235	**Parameter passed to the method {0} is null.**
Explanation	The parameter passed to the method {0} is null.
Action	Pass a valid parameter to the method {0}.

INMCLE0236	**Invalid values for keyword condition**
Explanation	Keyword condition takes only one string value as input. The value should be put in the collection and then set to keyword condition.
Action	Check to make sure that valid values are set as input to the keyword condition.

INMCLE0237	**Failed to get TransformedContent {0}.**
Explanation	Failed to get the TransformedContent, possibly because of a connection failure.
Action	Check the network connection. If the problem persists, contact CentraSite administrator.

INMCLE0240	**{0} cannot be reset.**
Explanation	An attempt is made to reset the {0} that already has a value specified and that is read-only.
Action	{0} is read-only.

INMCLE0241	**Exception occured while trying to get the webdav location of computed profile template.**
Explanation	An unexpected exception occurred while trying to get the webdav location of computed profile template, possibly because the template does not exist.
Action	Check to make sure that the uploaded archive contains the computed profile template.

INMCLE0242	**Exception occured while loading the implementation class of computed profile.**
Explanation	An unexpected exception occurred while loading the implementation class of computed profile, possibly because the class does not exist.
Action	Check to make sure that the uploaded archive contains the implementation class.

INMCLE0243	**Database access is denied.**
Explanation	Access to the database is denied.
Action	Login again.

INMCLE0244	**Exception while trying to retrieve the computed profile data.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Make sure that the getProfileDataAsJson() implementation is correct.

INMCLE0245	**Exception while trying to compute the profile data.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Make sure that the computeProfileData implementation is correct.

INMCLE0246	**Required input is missing.**
Explanation	The required input is missing.
Action	Enter a valid input.

INMCLE0247	**Error loading profile data.**
Explanation	An unexpected error occurred while trying to load the profile data, possibly because of the following reasons: {0}.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.

INMCLE0248	**Search cannot be saved.**
Explanation	The current search contains validation errors.
Action	Correct the validation errors and try again.

INMCLE0249	**Error establishing a database connection.**
Explanation	Unable to connect the database, possibly because the database server is down.
Action	Start the database server.

INMCLE0250	**Failed to convert the given duration {0} to date.**
Explanation	Exception occurred while trying to convert the given duration to date; possibly because the duration string is invalid.
Action	Enter a valid duration.

INMCLE0251	**Failed to covert the given string {0} to date.**
Explanation	Exception occurred while trying to convert the given string to date; possibly because the string is invalid.
Action	Check to make sure that the string is valid and it supports the date format like "E MMM dd HH:mm:ss Z yyyy".

INMCLE0252	**Failed to create a new {0}.**
Explanation	The {0} could not be created; possibly because the inputs were invalid.
Action	Make sure the inputs are valid.

INMCLE0253	**Failed to save an asset with the given permissions.**
Explanation	Failed to save an asset with the given permissions; possibly because the asset is unlocked.
Action	Make sure the asset is locked and available for editing.

INMCLE0254	**Exception fetching the asset's instace-level and profile-level permissions.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Contact your system administrator if the problem persists.

INMCLE0255	**Display Interval {0} is invalid.**
Explanation	Specify the time interval how frequently you want to collect metrics for the service. The expected format is 3m 2d 6h; where m indicates the month, d indicates the day and h indicates the hour.
Action	Check to make sure that the time interval is specified in exactly the above format.

INMCLE0256	**Exception {0} occurred while trying to fetch the list of targets.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the exception stack trace information.

INMCLE0257	**Target {0} is not active.**
Explanation	The target {0} is not active. The cause is not immediately known.
Action	Check the stack trace information for details.

INMCLE0258	**Failed to deploy asset {0} on gateway {1}.**
Explanation	Could not deploy the asset {0} on the specified gateway {1}. Possible reason: {2}
Action	Check the stack trace information for details.

INMCLE0259	**Unable to fetch policy with UUID '{0}'.**
Explanation	Could not fetch policies with the given UUID '{0}'; possibly because of the following reasons: 1. A policy with a UUID '{0}' does not exist. 2. Logged in user does not have the required permission on policy.
Action	Ensure that at least one policy exists with the given UUID and the logged in user has the required permissions on the policy.

INMCLE0260	**Unable to fetch policies with name pattern '{0}'.**
Explanation	Could not fetch policies with the given name pattern '{0}'; possibly because of the following reasons: 1. A policy with a name pattern '{0}' does not exist. 2. Logged in user does not have the required permission on policy.
Action	Ensure that at least one policy exists with the given name pattern and the logged in user has the required permissions on the policy.

INMCLE0261	**The policy action template is invalid.**
Explanation	Invalid action template; possibly because one or more vital parameters are null or not available.
Action	Enter valid parameters for the action template.

INMCLE0262	**Unable to fetch policy actions with UUID '{0}'.**
Explanation	Could not fetch policy actions with the given UUID '{0}'; possibly because of the following reasons: 1. A policy action with a UUID '{0}' does not exist. 2. Logged in user does not have the required permission on action.
Action	Ensure that at least one policy action exists with the given UUID and the logged in user has the required permissions on the action.

INMCLE0263	**Unable to fetch policy actions with name pattern '{0}'.**
Explanation	Could not fetch policy actions with the given name pattern '{0}'; possibly because of the following reasons: 1. A policy action with a name pattern '{0}' does not exist. 2. Logged in user does not have the required permission on policy action.
Action	Ensure that at least one policy action exists with the given name pattern and the logged in user has the required permissions on the policy action.

INMCLE0264	**Unable to fetch {0}.**
Explanation	Could not fetch the {0}. The cause is not immediately known.
Action	Check the exception stack trace information.

INMCLE0266	**Failed to identify the consumers for the asset {0}.**
Explanation	Could not identify the consumers for the given asset {0}
Action	This is an internal error. If the problem persists, contact the system administrator.

INMCLE0267	**Failed to identify the targets to which the asset {0} is deployed.**
Explanation	Exception occurred when populating the targets to which the asset {0} is deployed.
Action	This is an internal error. If the problem persists, consult the system administrator.

INMCLE0268	**Failed to identify the events for the given search filter.**
Explanation	Exception occurred when populating events for the given search filter.
Action	This is an internal error. If the problem persists, consult the system administrator.

INMCLE0269	**Failed to revoke profile permissions.**
Explanation	Caught an exception when trying to revoke the profile permissions.
Action	This is an internal error. If the problem persists, consult the system administrator.

INMCLE0270	**Failed to set profile permissions.**
Explanation	Caught an exception when trying to set the profile permissions.
Action	This is an internal error. If the problem persists, consult the system administrator.

INMCLE0271

INMCLE0272	**Error obtaining the classifications for object {0}.**
Explanation	Caught an unexpected exception occurred while trying to obtain the classifications of object {0} and which prevented the application from proceeding further.
Action	Check the stack trace information for details.

INMCLE0273	**Missing attribute in virtualization.**
Explanation	Mandatory attribute (Virtual Alias or Endpoint) is missing. Virtual Alias and Endpoint attributes are mandatory for virtualizing an API.
Action	Set the Virtual Alias and Endpoint attributes.

INMCLE0274	**Invalid Display Interval {0}.**
Explanation	The display interval specified is invalid.
Action	Specify a valid interval (ex. 1m 1d 1h) and try again.

INMCLE0275	**Failed to configure the API Key.**
Explanation	Could not configure the API Key for the given asset; possibly because of missing parameters.
Action	Check to make sure all the required parameters are set.

INMCLE0276	**Failed to load approval groups from the CentraSite registry.**
Explanation	One or more approval groups could not be loaded from the CentraSite registry.
Action	Make sure that an approval group exists and try again.

INMCLE0277	**Error checking permissions or validity over objects.**
Explanation	Could not check permissions or validity over the specified objects.
Action	Verify the user and asset type are valid in the CentraSite registry.

INMCLE0278	**Failed to check if the current user has Manage Organizations permission.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0279	**Unable to delete/remove the selected {0} {1}**
Explanation	You cannot delete the {0} {1}, because you do not have the required permission to delete/remove the {0}.
Action	Verify that you have the required permission to delete/remove the {0}. Contact your administrator, request permission if necessary and try again.

INMCLE0280	**Unable to delete the selected user {0}.**
Explanation	{1}. A user cannot be deleted if the user owns/modifies object(s), or if the user has any pending actions or if the user is the sole administrator for an organization. Also, if the user modified some object, and the corresponding audit trail entry is still present, deletion is rejected.{0} - The user that was attempted to be deleted.
Action	Delete all of the objects owned by the user, complete all pending actions, ensure another user is appointed as administrator for the corresponding organization and after all modification audit trail entries are purged (if any), user deletion will be allowed.

INMCLE0281	**Unable to delete the selected group {0}**
Explanation	{1}. You cannot delete the selected group either because you do not have the required permission or the group is associated with another object which creates a dependency to the group.
Action	Verify that you have the required permission to delete the user. Ensure that the group does not have any associations to other objects and try deleting the associations (if any) before attempting to delete the group again.

INMCLE0282	**Unable to delete the selected role {0}**
Explanation	{1}. You cannot delete the selected role either because you do not have the required permission, or the role is a pre-defined system role which cannot be deleted, or the role is associated with another object which is dependent on it.
Action	Verify that you have the required permission to delete the role. Ensure that you are not attempting to delete a pre-defined role.

INMCLE0283	**Unable to delete the selected Child Organization**
Explanation	{0}. You cannot delete the selected Child Organization either because you do not have the required permission, or the organization has policies which are active, or other objects are associated with the organization.
Action	Verify that you have the required permission to delete the Child Organization. Ensure that organization dependencies are resolved before attempting to delete again.

INMCLE0284	**Unable to delete/modify the selected group {0}**
Explanation	You cannot modify the users of/delete pre-defined groups of CentraSite such as "Users" and "Members". Since the group {0} is a pre-defined object, the deletion/modification of the group has been rejected.
Action	Ensure that the group that you are trying to delete/modify is not a pre-defined object.

INMCLE0285	**Unable to delete the selected role {0}**
Explanation	You cannot delete the OrganizationAdministrator role of an organization. This is because this role indicates the Administrator(s) of an organization.
Action	Ensure that the role you are trying to delete is not that of the OrganizationAdministrator.

INMCLE0286	**Caught an Exception while creating the VSProcessingStepsAdapter instance**
Explanation	This is an internal error. It is probably because of an invalid connection.
Action	Verify that the user session is valid.

INMCLE0287	**Invalid Native service.**
Explanation	This is an internal error. It is probably because the native service Registry Object is null.
Action	Verify that the native service is valid.

INMCLE0288	**Unable to virtualize the native service**
Explanation	This is an internal error. It is probably because of an invalid MessageFlow.
Action	Verify that the MessageFlow is valid.

INMCLE0289	**Cannot Construct MessageFlow from VirtualService.**
Explanation	This is an internal error. It is probably because of an invalid VirtualService.
Action	Verify that the VirtualService is valid.

INMCLE0290	**Invalid Virtual service.**
Explanation	This is an internal error. It is probably because the virtual service Registry Object is null.
Action	Verify that the virtual service is valid.

INMCLE0291	**Falied to edit the VirtualService .**
Explanation	Cannot edit the VirtualService. It is probably because of an invalid MessageFlow.
Action	Verify the MessageFlow for the virtual service.

INMCLE0292	**Caught an Exception while creating Default StraightThrough routing for the Virtual Service**
Explanation	This is an internal error. It is probably because of an invalid route-to.
Action	Verify the endpoints for the virtualization

INMCLE0293	**Caught an Exception while creating Default Routing Endpoints for the Virtual Service.**
Explanation	This is an internal error. It is probably because of an invalid route-to.
Action	Verify the endpoint properties for the virtualization.

INMCLE0294	**Cannot build Processing steps with Empty MessageFlow.**
Explanation	This is an internal error. It is because the MessageFlow is empty.
Action	Verify the MessageFlow for the virtual service.

INMCLE0295	**Caught an Exception while building Processing steps for the VirtualService.**
Explanation	This is an internal error. It is probably because of an invalid MessageFlow.
Action	Verify that the MessageFlow is valid.

INMCLE0296	**Cannot add the PolicyActionInstance with templateId {0} to Routing Step**
Explanation	This probably occurs because the PolicyActionInstance does not belong to the routing step.
Action	Verify that the PolicyActionInstance is valid.

INMCLE0297	**Cannot add empty Default StraightThrough routing and empty Default Routing Endpoints for a Virtual Service.**
Explanation	Default routing and endpoint properties are mandatory for a virtual service and cannot be deleted.
Action	Verify that the default routing and endpoint properties are not deleted.

INMCLE0298	**Cannot add the PolicyActionInstance with templateId {0} to Enforce Step.**
Explanation	This probably occurs because the policy action instance does not belong to the enforce step.
Action	Verify that the policy action instance is valid.

INMCLE0299	**Virtualization is not supported for type {0}**
Explanation	The asset passed to the virtualization action is not supported for virtualization.
Action	Verify that the asset is suitable for virtualization.

INMCLE0300	**Unable to delete the selected asset.**
Explanation	{0}. You cannot delete the selected asset either because you do not have the required permission or the asset has dependencies/associations with other objects (Example: pending approval of assets).
Action	Verify that you have the required permission to delete the asset. Also delete all dependencies with the asset and then attempt the deletion again.

INMCLE0301	**Unable to remove the selected role(s) for the user {0}**
Explanation	{1} Removal of role(s) for the user may have failed if you are trying to delete role(s) inherited through group membership, or if there are dependencies/associations between the objects.
Action	Ensure that all dependencies are resolved, and do not attempt to delete roles inherited through group memberships.

INMCLE0302	**Unable to remove the selected role(s) for the group {0}**
Explanation	{1}. Removal of role(s) from the group may have failed if a role has dependencies/associations and hence the role removal for the group may fail.
Action	Ensure that the roles do not have any dependencies and then try again.

INMCLE0303	**Unable to remove the group membership {0} for the user**
Explanation	{1}. You may not be able to remove a user's group membership if the user has dependencies/associations with the group (example: due to an approval policy). In such cases, membership removal for a user will be rejected.
Action	Ensure that all dependencies are resolved between the user and the group, then try again.

INMCLE0304	**Unable to retrieve {0} of a {1}**
Explanation	{2}. The retrieval may have failed because you do not have required permission, or due to database access error.
Action	Verify that you have required permissions and also ensure that the database is running, then try again.

INMCLE0305	**Failed to instantiate class {0}**
Explanation	Could not instantiate the given class {0}, possibly because of the following reasons: 1) class file does not exist 2) classpath is incorrect.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.

INMCLE0306	**Failed to check User {0} has Role {1}**
Explanation	An exception occurred while checking the role {1} for the user {0}.
Action	This is an internal error. Please contact the system administrator.

INMCLE0307	**Invalid Super User**
Explanation	The given super user configuration in CentraSite web.xml is invalid.
Action	Please provide a valid super user ID for the com.softwareag.centrasite.service.privilege.user.id Init-Param property under CentraSite web.xml.

INMCLE0308	**Invalid Super User Role**
Explanation	The super user configured under CentraSite web.xml does not have the required role to perform the privileged service.
Action	Please assign the CentraSite Administrator role for the super user or provide a user ID that has the CentraSite Administrator role.

INMCLE0309	**Invalid Calling User Role**
Explanation	The calling user does not have the appropriate role to execute a privileged service.
Action	Please assign an appropriate role to the user in order to perform the privileged service.

INMCLE0310	**API Key settings cannot be updated or deleted**
Explanation	A policy related to API Key settings is in the pending state, hence the settings cannot be updated.
Action	Ask the approvers to process the pending approval request pertaining to this asset.

INMCLE0311	**Cannot find a category for the policy.**
Explanation	This is an internal error. The category type cannot be found.
Action	Please verify the message flow.

INMCLE0312	**Caught an Exception while retrieving Default StraightThrough routing endpoint for the Virtual Service**
Explanation	This is an internal error. It is probably because of an invalid route-to.
Action	Verify the endpoints for the virtualization

INMCLE0313	**Caught an Exception while creating Default HTTP Authentication for the Virtual Service.**
Explanation	This is an internal error. It is probably because of an invalid policy instance.
Action	Verify the policy instance.

INMCLE0314	**Unable to create/edit the selected {0}.**
Explanation	You cannot create the {0} {1}, because you do not have the required permission to create/edit the {0}.
Action	Verify that you have the required permission to create/edit the {0}. Contact your administrator, request permission if necessary and try again.

INMCLE0315	**Unable to modify the selected group {0}**
Explanation	Since the group you are trying to modify is associated with an external repository, you will not be able to modify the external group.
Action	Ensure that the group that you are trying to modify is not an external group.

INMCLE0316	**Unable to remove the selected role**
Explanation	The logged in user and the user for whom roles are attempted to be removed are the same. This is not allowed.
Action	Please make sure that you are not trying to remove roles assigned to you. It can only be done by the CentraSite Administrator or your Organization Administrator.

INMCLE0317	**Failed to find the alias which exists with the given name {0}**
Explanation	An exception occurred while trying to find the asset which already exists with the given name {0}.
Action	Please make sure the given asset name does not have any special characters.

INMCLE0319	**Email address already registered in CentraSite**
Explanation	This email address is already registered to a user in CentraSite.
Action	Enter a different email address.

INMCLE0320	**Please wait while we process your registration.**
Explanation	User registration with the given email address is being processed by the administrator.
Action	Please wait while we process your registration.

INMCLE0321	**Configure parameters for the New Account Registration policy**
Explanation	The parameters required for the New Account Registration Policy are missing.
Action	Configure parameters (such as, Approver Group, Approval Mode) for the New Account Registration policy.

INMCLE0322	**Failed to publish the asset**
Explanation	Unable to publish the asset; possibly because of an incorrect attribute.
Action	Check to make sure that the specified input parameters are correct.

INMCLE0323	**Failed to get the publish progress**
Explanation	An exception occurred while getting the publish progress information.
Action	Please make sure that the request end point, request and header parameters are correct.

INMCLE0324	**Failed to get the publish failed targets**
Explanation	An exception occurred while getting the deployment failed targets information.
Action	Please make sure that the request end point, request and header parameters are correct

INMCLE0325	**Failed to cancel publish operation**
Explanation	An exception occurred while canceling the publish operation.
Action	Please make sure that the request end point, request and header parameters are correct.

INMCLE0326	**Privileged user credentials are not configured.**
Explanation	The expected privileged user credentials are not configured in {0}.
Action	Check to make sure that the privilege user credentials are configured in {0}.

INMCLE0327	**Required roles to perform the publish are missing**
Explanation	One or more roles that are required to perform the publish are missing.
Action	Please contact the administrator to add roles required to perform the publish.

INMCLE0328	**Aliases or Targets input is empty**
Explanation	The publish request does not contains aliases or tagets information.
Action	Please make the you have provided the aliases and targets required to perform the publish operation.

INMCLE0329	**You do not have sufficient permissions to execute {0}.**
Explanation	You do not have sufficient permissions to execute {0}.
Action	Verify that you have the "Manage Organizations" permission. Contact your administrator and request permission if necessary and then try again.

INMCLE0330	**Unauthorized: Access is denied.**
Explanation	Access to the service is denied possibly because of insufficient permissions.
Action	Check to make sure that you have the required permissions for accessing the service.

INMCLE0331	**Forbidden: Access is denied.**
Explanation	Request is forbidden at the moment; possibly because the API key is pending for a renewal request.
Action	Kindly retry after sometime.

INMCLE0332	**Required policies to execute the API key renewal and/or revocation are not found.**
Explanation	Could not process the renewal and/or revocation requests for the API key; possibly because the requried policies are not found.
Action	Check to make sure that the API key settings are configured for renewal and/or reovcation. If the problem persists, contact your system administrator.

INMCLE0333	**The Message Flow stage {0} that includes the action {1} must include at least one of the following dependent actions: Require Signing, Require Encryption, Require SLL, Require WSS X.509 Token.**
Explanation	This action {1} depends on the following actions: Require Signing, Require Encryption, Require SLL, Require WSS X.509 Token.
Action	Choose at least one of the dependent actions for {1}.

INMCLE0339	**The Message Flow stage {0} that includes the action {1} must also include {2} of the following dependent action(s): {3}.**
Explanation	This action {1} mandate that at least one of the dependent actions {3} be included in the message flow.
Action	Choose at least one of the dependent actions for {1}.

INMCLE0340	**Required field is missing**
Explanation	Required field {0} for the policy action {1} cannot be empty.
Action	Enter a value for the required field {0}.

INMCLE0341	**No action is defined for policy.**
Explanation	The Message Flow area in the indicated policy does not contain any actions.
Action	Add one or more actions to the Message Flow area in the indicated policy.

INMCLE0342 **Value set of Message Flow is null.**

Explanation Value returned by Message Flow is null.

Action Set a value for the Message Flow.

INMCLE0343 **{0} attribute not valid.**

Explanation The specified attribute {0} is not a valid policy constraint.

Action Specify a valid attribute.

INMCLE0344 **One or more dependent actions or action parameters are not configured.**

Explanation There are no dependent actions or action parameters configured for the Message Flow.

Action Configure the dependent actions and action parameters in the Message Flow area.

INMCLE0345 **Failed to change lifecycle state of {0}.**

Explanation Could not change lifecycle state of this {0}, possibly because it has been implicitly locked by the server for an ongoing modification.

Action Please try after some time.

INMCLE0346 **Failed to change lifecycle state of {0}.**

Explanation Could not change lifecycle of this {0}, possibly because you do not have the required permissions.

Action Check to make sure that you have the required permissions to change state of this{0}.

INMCLE0347 **Failed to delete {0}.**

Explanation Could not delete this {0}, possibly because you do not have the required permissions.

Action Check to make sure that you have the required permissions to delete this {0}.

INMCLE0348 **Failed to delete {0}.**

Explanation Could not delete this {0}, possibly because it has been implicitly locked by the server for an ongoing modification.

Action Please try after some time.

INMCLE0349Error	**CentraSite could not create the runtime alias. {0}**
Explanation	Error while creating a runtime alias in CentraSite.
Action	Check if a runtime alias with the same name already exists and if the parameters specified for the runtime alias are correct.

INMCLE0350Error	**CentraSite failed to publish the runtime alias to targets. {0}**
Explanation	Error while publishing runtime alias from CentraSite to target(s).
Action	Check the log file for more information.

INMCLE0351	**{0} action failed because the required objects {1} are not set.**
Explanation	Action {0} requires that the objects be set before it can execute.
Action	Ensure that the required objects {1} are set accordingly for the action.

INMCLE0352	**You must select valid objects for publishing/unpublishing to/from API Portals.**
Explanation	One or more of the selected registry objects cannot be published/unpublished to/from the specified API Portals. This is possibly because, one or more of the selected objects does not belong to the asset type "Service" or its variants.
Action	Make sure that the objects selected for publishing/unpublishing are of the asset type "Service" or any of its variants.

INMCLE0353	**{0} ERROR: Could not publish/unpublish APIs to API Portals.**
Explanation	An error {0} occurred while trying to publish/unpublish APIs to/from API Portals, possibly because one or more of the API Portal servers were unavailable.
Action	Make sure the API Portal servers are up and running. If the problem persists, contact your administrator.

INMCLE0354	**Category {0} does not belong to the taxonomy "Sandbox".**
Explanation	An attempt was made to classify an endpoint with the taxonomy "Sandbox", but the specified category {0} does not exist in the taxonomy "Sandbox".
Action	Make sure the category exists in the taxonomy "Sandbox".

INMCLE0355	**Failed to publish asset {0} to target.**
Explanation	Could not publish the specified asset {0} to the target, possibly because the specified asset is under the control of a lifecycle model (LCM), and is in a non-deployable state.
Action	Make sure you switch the asset to an active, ready-to-deploy state, before trying to publish asset to the target.

INMCLE0356Error	**Error while deploying runtime aliases. {0}**
Explanation	CentraSite could not deploy runtime aliases.
Action	Check the stack trace information in the log file for more information.

INMCLE0357Error	**Error while undeploying runtime aliases. {0}**
Explanation	CentraSite cannot undeploy runtime aliases.
Action	Check the stack trace information in the log file for more information.

INMCLE0358	**Could not get information from API Portal {0}, because of invalid user credentials.**
Explanation	An error occurred while getting an information from the specified API Portal {0}, possibly because of invalid username and/or password.
Action	Enter a valid username and/or password, and then try again.

INMCLE0359	**Could not get information from API Portal {0}.**
Explanation	An error occurred while getting an information from the specified API Portal {0}. There could be multiple reasons why this might have occurred: (1) API Portal server is down or inaccessible (2) invalid user credentials (3) application error on the CentraSite or API Portal server.
Action	Make sure the API Portal server is up and running, and the user credentials are correct.

INMCLE0360	**The API is published successfully but cannot be associated with API Portal.**
Explanation	The API was successfully published to the API Portal server, but could not be associated with it. This could be caused by an application error.
Action	Make sure the API Portal server is up and running. If the problem persists, contact your administrator.

INMCLE0361	**The API is unpublished successfully, but existing association with API Portal cannot be revoked.**
Explanation	The API was successfully unpublished from the API Portal server, but its existing association with API Portal could not be revoked. This could be caused by an application error.
Action	Make sure the API Portal server is up and running. If the problem persists, contact your administrator.

INMCLE0362	**Could not find API id {0} in the CentraSite registry.**
Explanation	An attempt was made to publish or unpublish the specified API which is not found in the CentraSite registry.
Action	Verify the API id is correct. If the API id is correct and the error persists, contact your administrator.

INMCLE0363	**Could not find API Portal id {0} in the CentraSite registry.**
Explanation	An attempt was made to publish or unpublish an API to the specified API Portal which is not found in the CentraSite registry.
Action	Verify the API Portal id is correct. If the API Portal id is correct and the error persists, contact your administrator.

INMCLE0364	**Could not find status id {0} of the publish/unpublish action in the CentraSite registry.**
Explanation	The publish or unpublish status could not be determined. The identifier used to get the status of the action is no longer valid, possibly because the action has already been completed.
Action	Verify the status id is correct. If the status id is correct and the error persists, contact your administrator.

INMCLE0365	**Database access error. Could not connect to the CentraSite Registry Repository.**
Explanation	The CentraSite Registry Repository is unavailable.
Action	Restart the Software AG CentraSite Registry Repository and Software AG Runtime. If the problem persists, contact your administrator.

INMCLE0366	**One or more of the selected resources have HTTP methods that are not supported for virtualization.**
Explanation	Resources with GET, POST, PUT, PATCH and DELETE methods are only allowed for virtualization. The following resource(s) have been found to have unsupported HTTP methods: {0}
Action	Select the resources that have supported HTTP methods.

INMCLE0367	**Could not set attribute {0} of the REST/XML service.**
Explanation	{1}: An error occurred while trying to set the attribute {0} of the REST/XML service. There could be multiple reasons why this might have occurred: (1) insufficient permissions (2) transaction timeouts (3) trying to modify an outdated service (4) invalid value for the attribute.
Action	Ensure that you have sufficient permissions to modify the service. If the underlying error is a transaction timeout or an outdated service, try setting the attribute again.

INMCLE0368	**Could not save the web service "{0}".**
Explanation	{1}: An error occurred while trying to save the specified REST/XML service {0}. There could be multiple reasons why this might have occurred: (1) insufficient permissions (2) transaction timeouts (3) trying to modify an outdated service (4) invalid property values for the service (5) a policy denies the save.
Action	Ensure that you have sufficient permissions to modify and save the service. Check for enabled policies denying the save. If the underlying error is a transaction timeout or an outdated service, try saving the service again.

INMCLE0369	**Failed to virtualize web service.**
Explanation	Could not virtualize the web service, possibly because the specified service doesn't reference any WSDL:binding element.
Action	Make sure that the WSDL contains a binding element.

INMCLE0370	**Failed to register CentraSite in the following API Portals: {0}**
Explanation	An error occurred while registering CentraSite in the indicated API Portals {0}. There could be multiple reasons why this might have occurred: (1) API Portal server is down or inaccessible (2) invalid user credentials (3) application error on the API Portal server.
Action	Make sure the API Portal server is up and running, and the user credentials are correct.

INMCLE0371	**Failed to delete the API {0}.**
Explanation	The selected API {0} cannot be deleted, because it is published to one or more API Portals.
Action	To delete the selected API first unpublish it from all the API Portals and then try again.

INMCLE0373	**Trying to access a resource {0} in API Portal {1} is forbidden.**
Explanation	A HTTP 403 error occurred while trying to access the resource {0} in API Portal {1} , possibly because you do not have sufficient access rights to access the specified resource in API Portal.
Action	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMCLE0374	**Resource {0} is not found in API Portal {1}.**
Explanation	A HTTP 404 error occurred while trying to access the resource {0} in API Portal {1}. There could be multiple reasons why this might have occurred: (1) API Portal server is down or inaccessible (2) invalid resource endpoint.
Action	Make sure the API Portal server is up and running, and the resource endpoint is correct. If the problem persists, contact your administrator.

INMCLE0375	**Technical error encountered in API Portal {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Contact your system administrator with exception stack trace information present in the error log.

INMCLE0376	**An error occurred while creating a gateway in CentraSite.**
Explanation	One or more gateway configuration parameters are null.
Action	Specify the mandatory gateway parameters, and try again.

INMCLE0377	**An error occurred while creating a gateway in CentraSite. {0}**
Explanation	An error occurred while creating a gateway in CentraSite. Check the CentraSite logs for details.
Action	Fix the error(s) and retry the "set gateway" command. If the issue persists, contact Software AG support with the log information.

INMCLE0379	**Unable to find a gateway in CentraSite with the ID, "{0}".**
Explanation	A gateway with the specified identifier does not exist in CentraSite.
Action	Specify a valid gateway ID, and try again.

INMCLE0380	**CentraSite cannot retrieve the gateway details because the mandatory attribute, gateway ID is not available.**
Explanation	Gateway ID for the gateway is not available in CentraSite.
Action	Check if the gateway ID set in CentraSite is valid.

INMCLE0381	**CentraSite could not delete the gateway because the gateway ID is not specified.**
Explanation	The mandatory gateway ID parameter is not specified for the "remove gateway" command in CentraSite.
Action	Specify the gateway ID parameter and try and command again.

INMCLE0382	**CentraSite could not create/update a gateway because a mandatory attribute for the command is not specified. Attribute not specified: {0}, gateway: {1}**
Explanation	A mandatory attribute is not specified for the set gateway command in CentraSite.
Action	Specify the mandatory parameter and try the "set gateway" command again.

INMCLE0383	**Error in synchronizing consumers with Mediator gateway.**
Explanation	An error occurred while synchronizing consumers with the Mediator gateway. There could be multiple reasons why this might have occurred: (1) Mediator is down or inaccessible. (2) At least one consumer application is not available for synchronizing.
Action	Make sure that Mediator is up and running, and at least one consumer application is available for synchronizing with the gateway.

INMCLE0384	**You do not have permission in CentraSite to publish/unpublish the API Portal, {0}.**
Explanation	To perform publish/unpublish operation on an API Portal, you must have either API Portal Administrator role or the modify permission on the selected API Portal(s).
Action	Contact the CentraSite administrator to add roles/permissions required to perform the publish or unpublish APIs.

INMCLE0385	**Error publishing CentraSite communication details to Mediator.**
Explanation	CentraSite cannot publish communication details to Mediator. Possible reasons could be: (1) Mediator is down or inaccessible (2) invalid user credentials or (3) Error in Mediator when you publish information from CentraSite to Mediator.
Action	Check Mediator and CentraSite log files and take corrective actions.

INMCLE0386	**Could not publish CentraSite Communication Details to Mediator.**
Explanation	An error occurred while trying to publish CentraSite Communication Details to Mediator. There could be multiple reasons why this might have occurred: (1) Integration Server on which Mediator is running is down or inaccessible (2) invalid user credentials (3) application error on the CentraSite server or Integration Server.
Action	Make sure the Integration Server is up and running, and the user credentials are correct. If the problem persists, contact your administrator.

INMCLE0387	**Could not deploy 'CentraSite Communication Details' to Mediator due to HTTP connection failure.**
Explanation	Failure of HTTP connection between CentraSite and Mediator.
Action	Check if the Mediator credentials and endpoint URL specified are valid and try again.

INMCLE0388	**Mediator endpoint URL format is not correct. Format: <PROTOCOL>://<HOSTNAME>:<PORT>or <PROTOCOL>://<HOSTNAME>**
Explanation	The Mediator endpoint URL should be specified in one of the following formats:(1) <PROTOCOL>://<HOSTNAME>:<PORT>(2) <PROTOCOL>://<HOSTNAME>
Action	Enter the Mediator endpoint URL in the correct format and try again.

INMCLE0389	**Could not unpublish instances of API Portal.**
Explanation	An error occurred while unpublishing the selected instances of API Portal. There could be multiple reasons why this might have occurred: (1) API Portal server was down or inaccessible (2) instances of API Portal was successfully unpublished, but its existing association with published APIs and access tokens could not be revoked, possibly because of an application error.
Action	Make sure the API Portal server is up and running. Try unpublishing the selected instances of API Portal using the "Force Unpublish" action. If the problem persists, contact your administrator.

INMCLE0390	**Path parameters can only be defined at the Resource level.**
Explanation	Path parameters can be defined at the Resource level; but cannot be defined at the API level or Method level.
Action	Specify a path parameter at the Resource level.

INMCLE0391	**Error while publishing/un-publishing to/from the gateways selected.**
Explanation	You do not have permission to publish/un-publish to/from one or more of the selected gateways.
Action	Check if you have permission to publish/un-publish to/from the selected targets, and try again.

INMCLE0392	**Download Documents action failed.**
Explanation	An attempt was made to execute the Download Documents action without selecting an asset of the type Service.
Action	Select an asset of the type Service to execute this action.

INMCLE0393	**No document(s) to download.**
Explanation	Service doesn't have any documents to download.
Action	Ensure there is at least one document to download. Service owner has to first upload documents which can be downloaded later.

INMCLE0394	**Organization field cannot be empty.**
Explanation	You have not entered the name of the submitting organization when creating an asset in CentraSite.
Action	Enter the organization name.

INMCLE0395	**Failed to create an asset because the required specification file is invalid.**
Explanation	Could not create an asset, possibly because the given {0} specification file is invalid.
Action	Upload a valid {0} specification file. If the problem persists, contact your administrator.

INMCLE0396	**Unable to initialize and load {0} importer implementation.**
Explanation	{1}: An error occurred while initializing the {0} importer implementation. There could be multiple reasons why this might have occurred: (1) incorrec importer implementation class is incorrect (2) importer implementation class could not be identified (3) importer implementation class failed to instantiate.
Action	Make sure that the importer implementation and specifications are correct. For more information about importer specifications, see the document Working with REST-based APIs. Contact your administrator if the problem persists.

INMCLE0397	**Failed to create an asset of type {0} from the specification type {1}.**
Explanation	In CentraSite, certain asset types require a particular type of specification file for creating asset instances of that type. An asset could not be created if the given type of specification file is not supported for that asset type.
Action	For a list of the asset types and their supported specification files, see the document Working with REST-based APIs. Contact your administrator if the problem persists.

INMCLE0398	**Could not create or modify {1} asset from the {0} specification file.**
Explanation	{2}: An error occurred while trying to import the specification file. There could be multiple reasons why this might have occurred: (1) specification file is invalid (2) data type or specification type is not supported in CentraSite (3) an internal error in saving the asset.
Action	Make sure the specification file is valid. For information on the mappings between the specification file and asset in CentraSite, see the document Working with REST-based APIs. Contact your administrator if the problem persists.

INMCLE0399	**Error occurred while importing the archive file: {0}**
Explanation	An error occurred while importing the archive file.
Action	Check the stack trace for the cause of the failure and if required, contact your system administrator.

INMCLE0400	**{0} ERROR: Could not unpublish APIs from API Portals.**
Explanation	An error {0} occurred while trying to unpublish APIs from API Portals, possibly because one or more of the API Portal servers were unavailable.
Action	Make sure the API(s) are already published and API Portal servers are up and running. If the problem persists, contact your administrator.

INMCLE0401	**Could not generate access token for API Portal.**
Explanation	An attempt was made to request access token through an API Portal, but the specified API Portal UUID {0} does not exist in the CentraSite registry.
Action	Make sure the API Portal UUID exists in the CentraSite registry.

INMCLE0402	**Could not generate access token for API Portal user, possibly because the user does not have an E-mail address.**
Explanation	A request for the access token triggered by an API Portal user could not processed, possibly because the specified user does not have an E-mail address.
Action	Enter a valid E-mail address.

INMCLE0403	**CentraSite cannot update the gateway. {0}**
Explanation	An error occured while updating a gateway in CentraSite.
Action	Contact your system administrator with exception stack trace information in the CentraSite log.

INMCLE0407	**Failed to undeploy the asset {0} on target {1}.**
Explanation	Could not undeploy the asset {0} on given target {1}. Possible reason: {2}
Action	Check the stack trace information for details.

INMCLE0409	**Could not find user with email address {0}**
Explanation	No user with the specified email address was found.
Action	Correct the parameter value of '__consumerEmailAddress' in the configuration file and try again.

INMCLE0410	**Could not find CentraSite object with id {0}**
Explanation	A CentraSite object with the specified id was not found.
Action	Correct the CentraSite object id and try again.

INMCLE0411	**User is not a CentraSite Administrator.**
Explanation	The user does not have necessary permission to perform the service.
Action	Log in with a CentraSite Administrator role.

INMCLE0412	**Value for parameter '{0}' is missing.**
Explanation	The value for the mandatory parameter {0} is missing.
Action	Provide a value for the mandatory parameter {0}.

INMCLE0413	**Failed to remove consumer/s {0} from asset/s {1}. Possible reason for failure: {2}**
Explanation	You may encounter an error while trying to remove a consumer from an asset. It could be due to one of the following reasons: (1) Insufficient permissions (2) The consumer is not properly associated (3) The consumed asset is in Pending state (4) Internal error occurred while removing the consumer.
Action	Ensure that you have modify permission on the asset whose consumer or consumed assets you are trying to remove. If it is an internal error, please retry the operation after sometime.

INMCLE0414	**API does not have a valid end point.**
Explanation	The API to be published to API Portal does not have a valid end point.
Action	Ensure that the API has valid endpoint. If there is an endpoint available, ensure that the endpoint is categorized with the category which is chosen during the API publish. For example, if the API endpoint is categorized as “production” endpoint and the publisher chooses to publish only “Test” endpoint, then technically API has no endpoint to publish.

INMCLE0415	**Failed to get applicable usecases for object {0}.**
Explanation	An unexpected exception occurred while trying to get applicable usecases for {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0416	**Wrong usage of the Impact Analysis action API {0}.**
Explanation	Incorrect usage of the Impact Analysis action API. This problem occurs, when the '{0}' method is triggered with action in a state other than '{1}'.
Action	Before you execute the '{0}' method, verify that the action is in '{1}' state.

INMCLE0417	**Could not retrieve the selected usecase.**
Explanation	Failed to retrieve the selected usecase, possibly because the report is not implicitly set for retrieval.
Action	Use the 'setSelectedUseCase(..)' to set a report for this action.

INMCLE0418	**Failed to execute {0}.**
Explanation	You do not have necessary permission to perform this action.
Action	Before executing {0} make sure that you have the permission. Contact your CentraSite administrator and if necessary request access and then try again.

INMCLE0419	**CentraSite could not create/update the gateway because a gateway with the gateway name specified in the command already exixts.**
Explanation	A gateway already exists with the gateway name given in the command.
Action	Modify the gateway name and try the "set gateway" command again.

INMCLE0420	**Could not retrieve the parameters of the selected report {0}.**
Explanation	An unexpected exception occurred while trying to retrieve the parameters of the selected report {0}. The cause is not immediately known.
Action	Check the log file for detailed information.

INMCLE0421	**Error while fetching action for template-id {0} from enforce-actions.**
Explanation	Invalid Template Id found while fetching action for template-id {0} from enforce-actions.
Action	Contact your CentraSite Administrator.

INMCLE0422	**Cannot register consumers since there are no consumable types defined for {0} type.**
Explanation	You cannot register consumers for this asset since the asset type {0} does not have any consumable types defined for it. Asset instances of the defined consumable types can only be registered as consumers.
Action	Ensure that the type {0} has consumable types defined for it. Refer to the documentation to define consumable types for an asset type.

INMCLE0423	**Could not save a scheduled report.**
Explanation	An unexpected exception occurred while trying to save a scheduled report. The cause is not immediately known.
Action	Check the log file for detailed information.

INMCLE0424	**Invalid parameter name {0}.**
Explanation	You have entered an invalid parameter name.
Action	Provide a valid parameter name without special characters and try again.

INMCLE0425	**Invalid parameter type {0}.**
Explanation	You have entered an invalid parameter type.
Action	Provide a valid parameter type and try again.

INMCLE0426	**Failed to delete the asset {0}.**
Explanation	The selected asset {0} cannot be deleted because it is consumed by one or more assets.
Action	Make sure you unconsume all consumers from the asset, before trying to delete it.

INMCLE0428	**Exception occurred while searching for Gateways.**
Explanation	An exception occurred while searching for Gateways.
Action	Contact your System Administrator.

INMCLE0429	**Failure in performing resource synchronization for virtual alias {0} during virtualization.**
Explanation	An error occurred while performing resource synchronization for the virtual alias {0}. This may be due to improper resource selection during synchronization or an invalid message flow.
Action	Verify the resources that you have selected for synchronization with the native service and verify the message flow for the virtual service.

INMCLE0430	**Error while fetching saved search {0}.xml**
Explanation	An error occurred because the specified saved search resource cannot be found.
Action	Make sure the specified saved search is available.

INMCLE0431	**Invalid Consumer Certificate {0}.**
Explanation	The attached consumer certificate is invalid.
Action	Attach a valid consumer certificate and try again.

INMCLE0432	**Failed to create an OData service due to unsupported version {0} of OData.**
Explanation	Could not create OData service in the CentraSite registry. This is because the specified OData version {0} is not supported in CentraSite.
Action	For a list of supported OData versions, see the CentraSite documentation.

INMCLE0433	**Failed to publish CentraSite details to the following Mediators: {0}**
Explanation	An error occurred while publishing CentraSite details in the indicated Mediators {0}. There could be multiple reasons why this might have occurred: (1) Mediator server is down or inaccessible (2) invalid user credentials (3) application error on the Mediator server.
Action	Make sure the Mediator server is up and running, and the user credentials are correct.

INMCLE0434	**Failed to execute {0}.**
Explanation	Could not execute {0}. This is possibly because you do not have the sufficient permissions to execute {0}.
Action	Verify that you have the sufficient permissions. Contact your administrator and request permission if necessary and then try again.

INMCLE0435	**Failed to create an OData service due to unexpected metadata at {0}.**
Explanation	The metadata of the specified OData service has unexpected content. One or more of the required elements are missing.
Action	Check the metadata of the given OData service.

INMCLE0436	**An error occurred while executing an extension enabled for the CentraSite Business UI.\nError Message: {0}**
Explanation	A detailed explanation of the error thrown by the extension can be found here. Explanation: {1}
Action	Possible action steps to take: {2}\nIf the information provided by this error message is insufficient, please refer to the logs or contact your Administrator.

INMCLE0437	**Failed to check the permissions of the current user.**
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0438	**Error publishing CentraSite communication details to Mediator.**
Explanation	CentraSite cannot publish communication details to Mediator version older than 9.8.
Action	Configure a supported version of Mediator.

INMCLE0439	**Could not remove API Key configuration because one or more API Key consumers are associated to the virtual service.**
Explanation	All API Key consumers associated to the virtual service must be deleted before revoking the API Key option in API Consumption Settings.
Action	Delete all associations between the virtual service and API Key consumers and try again.

INMCLE0440	**Could not remove OAuth configuration because one or more OAuth consumers are associated to the virtual service.**
Explanation	All OAuth consumers associated to the virtual service must be deleted before revoking the OAuth option in API Consumption Settings.
Action	Delete all associations between the virtual service and OAuth consumers and try again.

INMCLE0441	**Failed to initialize an action class.**
Explanation	Could not initialize the action class. Check the CentraSite logs for the action class name and for more details.
Action	Check to make sure that the implementation class is correct and follows a specified syntax. Refer to the documentation reference for Action Implementation class.

INMCLE0445	**Could not publish CentraSite communication details to {0}.**
Explanation	An error occurred while trying to publish the CentraSite communication details to {0}. There could be multiple reasons why this might have occurred: (1) {0} is down or inaccessible (2) invalid user credentials (3) application error in {0}.
Action	Make sure {0} is up and running, user credentials are correct, and then try again.

INMCLE0446	**Failed to publish CentraSite communication details to {0}.**
Explanation	Could not publish the CentraSite communication details to {0}, possibly because of a HTTP connection failure between CentraSite and {0}.
Action	Make sure the endpoint URL is valid, user credentials are correct, and then try again.

INMCLE0447	**{0} endpoint URL is invalid.**
Explanation	The specified {0} endpoint URL is invalid, possibly because it does not comply to the following formats:(1) <PROTOCOL>://<HOSTNAME>:<PORT>(2) <PROTOCOL>://<HOSTNAME>
Action	Enter a valid {0} endpoint URL and try again.

INMCLE0448	**Failed to publish CentraSite communication details to {0}.**
Explanation	Could not publish the CentraSite communication details to {0}, possibly because the SNMP configuration is not accessible.
Action	Please contact your administrator.

INMCLE0449	**Failed to register CentraSite in {0}.**
Explanation	An error occurred while registering CentraSite in {0}, possibly because {0} is already registered with another instance of CentraSite.
Action	Deregister the existing CentraSite instance from {0}, and then register CentraSite again.

INMCLE0450	**Failed to deregister CentraSite from {0}.**
Explanation	An error occurred while deregistering CentraSite from {0}. There could be multiple reasons why this might have occurred: (1) {0} is down or inaccessible (2) invalid user credentials (3) application error in {0}.
Action	Make sure {0} is up and running, user credentials are correct, and then try again.

INMCLE0451	**Failed to load SNMP configuration file.**
Explanation	Could not load the SNMP configuration file, possibly because the configuration file is missing or the file path is incorrect.
Action	Please contact your administrator.

INMCLE0452	**Failed to parse SNMP configuration file.**
Explanation	Could not parse the SNMP configuration file, possibly because the configuration file structure is not as expected.
Action	Please contact your administrator.

INMCLE0453	**Could not update the publish or unpublish status of API Gateway asset.**
Explanation	An error occurred while trying to update the publish or unpublish status of API Gateway asset.
Action	Please contact your administrator.

INMCLE0454	**Could not update the publish or unpublish status of API Gateway asset.**
Explanation	An error occurred while trying to update the publish or unpublish status of API Gateway asset, possibly because the update gateway status call does not have a valid value for the gateway ID.
Action	Please contact your administrator.

INMCLE0455	**Could not update the publish or unpublish status of API Gateway asset.**
Explanation	An error occurred while trying to update the publish or unpublish status of API Gateway asset, possibly because the update gateway status call does not have a valid value for the status parameter.
Action	Please contact your administrator.

INMCLE0457	**Asset type with the namespace URI {0} already exists.**
Explanation	An asset type with the given namespace URI {0} already exists.
Action	Change the name of the asset type and try it again.

INMCLE0458	**Failed to add a new asset type.**
Explanation	Could not add the new asset type.
Action	Check the stack trace information in the log file for more information.

INMCLE0459	**Failed to get the relationship types.**
Explanation	Could not fetch the relationship types.
Action	Check the stack trace information in the log file for more information.

INMCLE0460 **Failed to get the association types.**

Explanation Could not fetch the association types.

Action Check the stack trace information in the log file for more information.

INMCLE0461 **Failed to get the object types.**

Explanation Could not fetch the object types.

Action Check the stack trace information in the log file for more information.

INMCLE0462 **Failed to get the consumable types.**

Explanation Could not fetch the consumable types.

Action Check the stack trace information in the log file for more information.

INMCLE0463 **Failed to set the consumable types.**

Explanation Could not set the consumable types.

Action Check the stack trace information in the log file for more information.

INMCLE0464 **Unable to get the option {0} for asset type {1}.**

Explanation Could not fetch the option {0} for asset type {1}.

Action Check the stack trace information in the log file for more information.

INMCLE0465 **Unable to update option {0} for asset type {1}.**

Explanation Could not update the option {0} for asset type {1}.

Action Check the stack trace information in the log file for more information.

INMCLE0466 **Failed to add attribute {0} to asset type {1}.**

Explanation Could not add the attribute {0} to asset type {1}.

Action Check the stack trace information in the log file for more information.

INMCLE0467 **Failed to modify attribute {0} of asset type {1}.**

Explanation Could not modify the attribute {0} of asset type {1}.

Action Check the stack trace information in the log file for more information.

INMCLE0468 **Failed to delete attribute {0} from asset type {1}.**

Explanation Could not delete the attribute {0} from asset type {1}.

Action Check the stack trace information in the log file for more information.

INMCLE0469 **Failed to set the profile sequence for asset type {0}.**

Explanation Could not set the profile sequence for asset type {0}.

Action Check the stack trace information in the log file for more information.

INMCLE0470 **Failed to get the profiles of asset type {0}.**

Explanation Could not fetch the profiles of asset type {0}.

Action Check the stack trace information in the log file for more information.

INMCLE0471 **Failed to add profile {0} to asset type {1}.**

Explanation Could not add the profile {0} to asset type {1}.

Action Check the stack trace information in the log file for more information.

INMCLE0472 **Failed to modify profile {0} of asset type {1}.**

Explanation Could not modify the profile {0} of asset type {1}.

Action Check the stack trace information in the log file for more information.

INMCLE0473 **Failed to delete profile {0} from asset type {1}.**

Explanation Could not delete the profile {0} from asset type {1}.

Action Check the stack trace information in the log file for more information.

INMCLE0474 **Failed to create a template for computed attribute or profile {0}.**

Explanation Could not create a template for computed attribute or profile {0}.

Action Check the stack trace information in the log file for more information.

INMCLE0475 **Failed to update the template for computed attribute or profile {0}.**

Explanation Could not update the template for computed attribute or profile {0}.

Action Check the stack trace information in the log file for more information.

INMCLE0476	**Failed to save asset type {0}.**
Explanation	An error occurred while trying to save the asset type {0}.
Action	Check the stack trace information in the log file for more information.

INMCLE0477	**Unable to initialize and load {0} exporter implementation.**
Explanation	{1}: An error occurred while initializing the {0} exporter implementation. There could be multiple reasons why this might have occurred: (1) exporter implementation class is incorrect (2) exporter implementation class could not be identified (3) exporter implementation class failed to instantiate.
Action	Make sure that the exporter implementation and specifications are correct. Contact your administrator if the problem persists.

INMCLE0478	**Could not delete lifecycle models '{0}'. {1}**
Explanation	An error occurred while trying to delete the lifecycle models. There could be multiple reasons why this might have occurred: (1) insufficient permissions (2) lifecycle model is in Productive state (3) lifecycle model is an intermediate version.
Action	Ensure that you have sufficient permissions to delete the lifecycle model. Ensure that the lifecycle model you are trying to delete is either in a New or Retired state. Ensure that you are trying to delete the most recent version of lifecycle model.

INMCLE0479	**Could not delete lifecycle stages '{0}'. {1}**
Explanation	An error occurred while trying to delete the lifecycle stages. There could be multiple reasons why this might have occurred: (1) insufficient permissions (2) lifecycle stage is assigned to the final state of a lifecycle model.
Action	Ensure that you have sufficient permissions to delete the lifecycle stage. Ensure that the lifecycle stage you are trying to delete is not assigned to the final state of a lifecycle model.

INMCLE0480	**Failed to undeploy asset {0} from gateway {1}.**
Explanation	Could not undeploy the asset {0} from given gateway {1}. Possible reason: {2}
Action	Check the stack trace information for details.

INMCLE0481	**Failed to set initial state for lifecycle model {0}. {1}**
Explanation	An error occurred while trying to set an initial state for the lifecycle model {0}, possibly because the specified state is not defined for the lifecycle model.
Action	Check the logs to obtain more detailed information about the error. Contact your administrator if the problem persists.

INMCLE0482	**Failed to set states for lifecycle model {0}. {1}**
Explanation	An error occurred while trying to set states for the lifecycle model {0}, possibly because the specified states are not valid.
Action	Check the logs to obtain more detailed information about the error. Contact your administrator if the problem persists.

INMCLE0483	**Failed to set organization for lifecycle model {0}. {1}**
Explanation	An error occurred while trying to set organization for the lifecycle model {0}. There could be multiple reasons why this might have occurred: (1) insufficient permissions (2) organization is invalid or unavailable.
Action	Check the logs to obtain more detailed information about the error. Contact your administrator if the problem persists.

INMCLE0484	**Failed to save lifecycle model {0}. {1}**
Explanation	An error occurred while trying to save the lifecycle model {0}. There could be multiple reasons why this might have occurred: (1) initial state of the LCM is not set. (2) final state is not set (3) one or more defined states are not reachable from the initial state. (4) organization to which the LCM belongs is not set.
Action	Make sure the lifecycle model is not violating any of the above mentioned criteria. Check the logs to obtain more detailed information about the error. Contact your administrator if the problem persists.

INMCLE0485	**Failed to set asset types for lifecycle model {0}. {1}**
Explanation	An error occurred while trying to set the applicable asset types for the lifecycle model {0}. There could be multiple reasons why this might have occurred: (1) an asset type already enabled for an active lifecycle model cannot be added to another active model (2) if an asset is already associated to a lifecycle state, then its asset type cannot be removed from the enabled types for the model. (3) an asset type that is added is not enabled to be associated with the model.
Action	Make sure the lifecycle model is not violating any of the above mentioned criteria. Check the logs to obtain more detailed information about the error. Contact your administrator if the problem persists.

INMCLE0486	**Could not unpublish assets from Mediator instances: '{0}'**
Explanation	An error occurred while trying to unpublish assets from Mediator instances, possibly because one or more of the Mediator instances are down or inaccessible.
Action	Make sure the Mediator instances are up and running. If the problem persists, contact your administrator.

INMCLE0487	**Failed to set property {0} for lifecycle state {1}. {2}**
Explanation	An error occurred while trying to set the property {0} for the lifecycle state {1}. There could be multiple reasons why this might have occurred.
Action	Make sure the lifecycle state is not violating any of the above mentioned criteria. Check the logs to obtain more detailed information about the error. Contact your administrator if the problem persists.

INMCLE0488	**Could not delete Policy {0} . {1}**
Explanation	An error occurred while trying to delete the policy. There could be multiple reasons why this might have occurred: (1) insufficient permissions (2) Policy model is in Productive state (3) Policy is an intermediate version
Action	Ensure that you have sufficient permissions to Policy. Ensure that the Policy you are trying to delete is either in a New or Retired state. Ensure that you are trying to delete the most recent version of policy.

INMCLI0001	**Parsing failed. Make sure the configuration file syntax (or) path is correct.**
Explanation	This is probably because of the following reasons: 1) syntax of the configuration file is invalid 2) specified configuration file path is incorrect.
Action	Check for the above possible reasons and execute again. Refer to the CentraSite documentation for creating a valid configuration file.

INMCLI0002	**Internal error.**
Explanation	An unexpected error occurred due to failure in the system execution.
Action	Contact the CentraSite administrator.

INMCLI0003	**Error while executing command ${0}.**
Explanation	Unexpected error occurred while executing the command.
Action	Check the error message for details.

INMCLI0004	**${0} is an invalid log unit; possible values are ${1}.**
Explanation	The specified log unit is not supported. Possible values are ${1}.
Action	Refer to the error message for a list of possible values.

INMCLI0006	**Purger is unavailable for ${0}.**
Explanation	Purger is not available for the specified log unit.
Action	Check to make sure that the log units specified in the XML configuration file are valid. Else, contact the CentraSite administrator.

INMCLI0007	**Purging stopped for ${0} as there is no write permission for export location ${1}.**
Explanation	Purging stopped for the log unit, possibly because you do not have the explicit permission to write to the export location.
Action	Verify if the user has required permissions for purging to the export location.

INMCLI0008	**Insufficient disk space in ${0}. Required space ${1}. Available space ${2}.**
Explanation	The specified export location does not contain enough space for the exported logs. Refer to error message for the available space and required space.
Action	Choose a different export location.

INMCLI0009	**Purging Failed. Following error occurred ${0}.**
Explanation	Purging failed for the log unit due to a network connection timeout.
Action	Try again later or contact CentraSite administrator.

INMCLI0010	**Unable to archive export directory ${0}.**
Explanation	An unexpected exception occurred while trying to archive the exported logs. This is probably because the files may be accessed by another application.
Action	Close the application and retry the operation.

INMCLI0011	**Unable to create export directory ${0}.**
Explanation	An unexpected exception occurred while trying to create the export directory. This is probably because of the following reasons: 1) you do not have the explicit permission to write to the export location 2) export location is invalid.
Action	Check for the above possible reasons and execute again. If the problem persists, conctact the CentraSite administrator.

INMCLI0012	**Command ${0} is invalid.**
Explanation	The specified command is not supported. For example, to purge logs you must specify -command purge_logs.
Action	Refer to CentraSite documentation for a list of the supported commands and their usage.

INMCLI0016	**Attribute {0} does not exist for specified path {1}.**
Explanation	The given attribute does not exist for the specified path.
Action	Verify that the attribute and path values are configured properly.

INMCLI0121	**Error: Invalid session.**
Explanation	CentraSite session has expired (or) already closed.
Action	Close your browser and log in again.

INMCLI0156	**Parameters for New Version action can only be set in "Show Params" state. Current state of action is {0}.**
Explanation	Parameters for versioning an asset can only be set in "Show Params" state. Current state of the action is {0}.
Action	Refer to the CSOAction related java document.

INMCLI0181	**Current search criteria is invalid.**
Explanation	The current search criteria is invalid. Validate the search criteria before you run.
Action	Check to make sure that the current search criteria is valid.

INMCLI0239	**No list available to perform {0}.**
Explanation	List is not available to perform {0}.
Action	Make sure that at least one of the selected items is added to the logged in user's list already.

INMCLI0265	**Failed to create the custom activity {0}.**
Explanation	The custom activity syntax in the configuration file was invalid.
Action	Check the activity syntax in the configuration file.

INMCLI0334	**This action cannot be added to the Message Flow more than {0} time(s).**
Explanation	You cannot include this action more than the allowed number of time(s) in the Message Flow.
Action	Do not include this action more than the allowed number of time(s) in the Message Flow.

INMCLI0335	**This action cannot co-exist with {0}.**
Explanation	This action cannot co-exist with the existing {0} in the Message Flow. This is possibly because, the two actions are mutually exclusive.
Action	Check to make sure that there are no mutually exclusive actions in the Message Flow.

INMCLI0336	**{0} of the dependent actions {1} should be configured in the Message Flow.**
Explanation	This action mandates that at least one of the dependent actions {1} be included in the Message Flow.
Action	Choose at least one of the dependent actions for {1}.

INMCLI0337	**This action cannot be added to the Message Flow more than once.**
Explanation	You cannot include this action more than once in the Message Flow.
Action	Do not include this action more than once in the Message Flow.

INMCLI0338	**This action is not applicable to the {0} Message Flow stage.**
Explanation	You cannot include this action in the {0} Message Flow stage.
Action	Ensure that you include the action in the applicable Message Flow stage.

INMCLI0442	**Provide a valid IP address range.**
Explanation	You cannot specify only one IP address for a type.
Action	Ensure you have provided both the From and To IP address values.

INMCLW0032	**Activity {0} is not applicable for given user.**
Explanation	Activity {0} is not applicable for the given user.
Action	Assign the activity to given user.

INMCLW0047	**Failed to synchronize configurator items with other configurators.**
Explanation	Could not synchronize or update the configurator item changes with other configurators.
Action	Reset the configurator items. If the problem persists, contact the CentraSite administrator.

INMCLW0109	**Failed to retrieve guest locale. Instead, returns the default locale {0}.**
Explanation	An unexpected exception occurred while trying to retrieve the locale for logged in user. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite adminsitrator.

INMCLW0110	**Exception occurred when closing connection.**
Explanation	An unexpected exception occurred when trying to close the underlying connection.
Action	Initialize before opening a connection.

INMCLW0197	**Duplicate search condition.**
Explanation	An attempt is made to specify a duplicate condition in the search recipe.
Action	Remove the duplicate condition from search recipe.

INMCLW0227	**Search name '{0}' already exists.**
Explanation	The same name is not allowed for two different searches. This error occurs when an attempt is made to save a search with a name that already exists.
Action	Enter a different search name.

INMCLW0238	**Enable at least one notification option in User Preferences.**
Explanation	At least one notification options in the User Preferences page should be selected to allow the current user to receive notifications through email and/or Inbox.
Action	Enable at least one notification option in the User Preferences page before subscribing to an asset.

INMCLW0318	**Action {0} is not applicable for the message flow step {1}.**
Explanation	The chosen action {0} is not applicable for the message flow step {1}.
Action	Choose a valid action for the message flow.

INMCLW0456	**The service published to API Gateway could not be activated in API Gateway.**
Explanation	The service published to API Gateway could not be activated in API Gateway. Reason: {0}
Action	Check for reasons and solve the problem in API Gateway.

INMCL_COMMON_ATTR_PENDING_APPROVALS – Pending Approvals

INMCL_COMMON_ATTR_PENDING_APPROVALS_DEC – Pending approvals for the asset

INMCL_USECASE_ASSETDEPENDENCY – Asset Dependency

Explanation Displays the list of assets which the selected asset is depending upon.

INMCL_USECASE_ASSETUSAGE – Asset Usage

Explanation Displays the list of assets which make use of the selected asset.

INMCL_USECASE_ASSET_VERSIONING_AND_CONSUMERS – Asset Versioning And Consumers

Explanation Displays the different versions of the selected asset and the consumers for each of the versions.

INMCL_USECASE_DEPLOYMNENT – Deployment Overview

Explanation Displays the list of gateways to which the selected asset is deployed.

INMCL_USECASE_ORG Organization Structure

Explanation Displays the list of organizations and their related objects.

INMCL_USECASE_RUNTIMELANDSCAPEVIEW – Runtime Landscape View

Explanation Displays the list of gateways and the assets deployed to them.

INMCL_USER_ATTR_AVATAR_URL_DESC – The WebDAV URL of the Avatar for the User

INMCL_USER_ATTR_AVATAR_URL_NAME – Avatar URL Location

INMCL_USER_ATTR_EMAIL_DESC – The email address for the user

INMCL_USER_ATTR_EMAIL_NAME – Email Address

INMCL_USER_ATTR_FIRSTNAME_DESC – The details of the user's first name

INMCL_USER_ATTR_FIRSTNAME_NAME – First Name

INMCL_USER_ATTR_LASTNAME_DESC – The details of the user's last name

INMCL_USER_ATTR_LASTNAME_NAME – Last Name

INMCL_USER_ATTR_PHONE_DESC – The user's telephone number details

INMCL_USER_ATTR_PHONE_NAME – Telephone Number

INMCSE0006	**Select a taxonomy to delete**
Explanation	Attempting to execute the delete action without selecting a taxonomy.
Action	Select a taxonomy to be deleted.

INMCSE0007	**Select JPG, GIF or PNG image format**
Explanation	Adding files other than JPG, GIF or PNG formats into a taxonomy or concept object.
Action	Add only files with JPG, GIF or PNG formats into a taxonomy or concept object.

INMCSE0008	**The given URL is not a proper WebDAV URL.**
Explanation	Wrong WebDAV URL or resource added into the taxonomy.
Action	Enter a correct WebDAV URL or resource.

INMCSE0011	**Select at least one user**
Explanation	At least one user should be selected.
Action	Select at least one user.

INMCSE0012 **Select at least one permission**

Explanation At least one permission should be selected.

Action Select at least one permission.

INMCSE0013 **Select an organization to delete**

Explanation An attempt was made to delete an organization without selecting an organization object.

Action Select an organization object to delete.

INMCSE0014 **Select the property to delete**

Explanation An attempt was made to delete a property without selecting a property.

Action Select the property to delete.

INMCSE0015 **Select at least one administrator**

Explanation At least one administrator should be selected.

Action Select at least one administrator.

INMCSE0018 **Organization {0} already exists**

Explanation The same name is not allowed for two different organizations. This error occurs when an attempt is made to create an organization with a name that already exists.

Action Enter a different organization name.

INMCSE0019 **Select a user to delete**

Explanation An attempt was made to delete a user without selecting the user object.

Action Select the user object to delete.

INMCSE0020 **Enter a valid user**

Explanation A valid user is required.

Action Enter a valid user.

INMCSE0033 **Enter the mandatory fields**

Explanation Some mandatory fields were not entered.

Action Enter the mandatory fields.

INMCSE0038	**Enter a valid user**
Explanation	A valid user has not been entered.
Action	Enter a valid user.

INMCSE0042	**Select permission to remove**
Explanation	At least one permission should be selected.
Action	Select at least one permission.

INMCSE0044	**E-mail address is not valid**
Explanation	An invalid E-mail address has been specified.
Action	Enter a valid E-mail address.

INMCSE0045	**Check the length of the contact input**
Explanation	The length of the contact input exceeds the limit.
Action	Check the length of the contact input.

INMCSE0046	**Enter valid contact input**
Explanation	A wrong value was entered in the contact input.
Action	Enter valid contact input.

INMCSE0047	**First name should not be empty**
Explanation	An empty first name was entered.
Action	Enter a value for the first name.

INMCSE0051	**A request with status 'Pending' can’t be deleted.**
Explanation	It is not possible to perform an unregister if a selected request has 'InProgress' as its status.
Action	Ensure that none of the selected requests has the status 'InProgress'.

INMCSE0052	**Enter valid IP values**
Explanation	Valid IP values are required.
Action	Enter valid IP values.

INMCSE0062	**{0} is the current logged in user**
Explanation	An attempt was made to delete the logged in user.
Action	Ensure that selected user is not the current logged in user.

INMCSE0063	**{0} is the primary contact of {1}**
Explanation	The logged in user tried to delete the primary contact of an organization.
Action	Ensure that the selected user-{0} is not the primary contact of an organization-{1}.

INMCSE0064	**{0} is the CentraSite Administrator**
Explanation	The logged in user tried to delete the user who is the CentraSite Administrator.
Action	Ensure that the selected user to delete is not the CentraSite Administrator.

INMCSE0068	**Group {0} already exists in this organization**
Explanation	An attempt was made to create a group with the same name as an existing group in the same organization.
Action	Use a new group name which is not already in use in the organization.

INMCSE0074	**At least one {0} should be present**
Explanation	When there is only one user with the role CentraSite Administrator or Organization Administrator, and if that user is deleted, this error will be thrown.
Action	There should be at least one CentraSite Administrator or Organization Administrator user. Make sure that another user with the same role is available in CentraSite.

INMCSE0075	**Database access error. Can't connect to server CentraSite.**
Explanation	The CentraSite Server is not running.
Action	Start the CentraSite Server.

INMCSE0076	**There are no results matching your search criteria**
Explanation	No results were found that match the search criteria.
Action	No action required.

INMCSE0077	**The WSDL file is unreachable. Make sure the input information is correct.**
Explanation	The URL for the given WSDL is wrong.
Action	Verify the URL given for this WSDL file.

INMCSE0084	**{0} has child organization(s) and cannot be deleted.**
Explanation	An organization cannot be deleted if there is at least one child organization associated to it.
Action	Make sure that the parent organization is not associated with any child organization, and then the parent organization can be deleted.

INMCSE0085	**Select an attribute to move**
Explanation	If a user tries to re-order the attribute without selecting anything, this error will be thrown. For this the user has to first select any attribute and then do the re-ordering.
Action	Select an attribute to move.

INMCSE0086	**Reordering multiple attributes is not allowed**
Explanation	While assigning attributes to the profile, a user can re-order the attributes. If the user tries to re-order multiple attributes simultaneously, this error will be thrown.
Action	Ensure that you do not select multiple attributes for reordering.

INMCSE0087	**HTTP Methods cannot be empty**
Explanation	HTTP methods for an XML / REST service cannot be empty during import.
Action	Please select any one of the HTTP methods for the XML / REST service.

INMCSE0090	**User {0} not found in external user store**
Explanation	The sychronization of users can be done only with users who belong to the current default external user store.
Action	Deselect the users who do not belong to the default external user store.

INMCSE0091	**Users not found in external user store**
Explanation	The sychronization of users can be done only with users who belong to the current default external user store.
Action	Deselect the users who do not belong to the default external user store.

INMCSE0092	**No endpoint defined**
Explanation	For the namespace to be defined, declare the endpoint of the service.
Action	Provide the endpoint information for the service before giving the namespace.

INMCSE0093	**Only CentraSite Administrator can change the ownership**
Explanation	Only a CentraSite Administrator can change the ownership or the organization.
Action	If you want to change the ownership or the organization, ensure that you are a CentraSite Administrator.

INMCSI0071	**It is not allowed to add multiple associations if Relationship attribute is not multi-value**
Explanation	For any single value relationship attribute, multiple value is not possible.
Action	Verify the given value for the single value relationship attribute.

INMCSW0053	**Define the primary contact**
Explanation	A primary contact is required when creating the organization.
Action	Define the primary contact.

INMCSW0060	**{0} cannot be deleted**
Explanation	You can only delete an organization if you have the necessary permissions.
Action	Ensure that you have the necessary permissions to delete an organization.

INMCSW0061	**Default organization cannot be deleted**
Explanation	The default organization cannot be deleted by any user.
Action	It is not possible to delete the default organization.

INMEUE0001	**A connection with the same name already exists.**
Explanation	A CentraSite connection name should be unique.
Action	Enter another connection name.

INMEUE0002	**Could not connect to host.**
Explanation	The specified host could not be connected. But the connection can be saved in the workspace.
Action	Enter a reachable host name.

INMEUE0003	**Could not resolve host address.**
Explanation	The specified host could not be reached. But the connection can be saved in the workspace.
Action	Enter a reachable host name.

INMEUE0004	**Log on failed. Make sure your user name and password are correct.**
Explanation	A logon failed due to invalid credentials.
Action	Make sure your user name and password are correct.

INMEUE0005	**Connection Name should not be empty**
Explanation	The required name for the connection is missing.
Action	Enter a name for the connection.

INMEUE0006	**An error has occurred. See error log for more details.**
Explanation	An internal error has been occurred. Refer to the log files for more details.
Action	Refer to the log files for more details.

INMEUE0007	**Cannot connect to server. Verify the specified connection information!\nMaybe the application server or the registry is currently not available.**
Explanation	Maybe the application server or the registry is currently not available.
Action	Check whether the application server and CentraSite are available and accessible.

INMEUE0008	**Cannot initialize predicate editors.**
Explanation	Due to non-compliance with the Eclipse UI, the UI rendering failed.
Action	Check your implementation and make sure it handles the predicate properly.

INMEUE0009	**No editor found for predicate class {0}**
Explanation	No editors are associated with the predicate.
Action	Check whether the implementation of IPredicateEditor is associated in your plugin description.

INMEUE0010	**Profile already exists**
Explanation	The specified profile already exists with the asset type.
Action	Create another profile if required.

INMEUE0011	**Attribute already exists**
Explanation	An attribute with the same name already exists.
Action	Enter another name for the attribute if required.

INMEUE0012	**You cannot modify this predicate. Delete it and create a new one instead.**
Explanation	Predefined profiles are not modifiable.
Action	Delete it and/or create a new one instead.

INMEUE0013	**Could not save. Correct the input errors first!**
Explanation	The input value is not compatible with the selected type.
Action	Enter an input value that is compatible with the selected type.

INMEUE0014	**The object cannot be deleted because it still has incoming associations.**
Explanation	An object with incoming/outgoing association cannot be deleted.
Action	If you want to delete this object, first delete the associations.

INMEUE0015	**{0} cannot be renamed as it is the target of one or more ExternalLink objects.**
Explanation	If this object is the target of any ExternalLink object, the name cannot be modified.
Action	No action required.

INMEUE0016	**{0} cannot be deleted as it is the target of one or more ExternalLink objects.**
Explanation	If this object is the target of any ExternalLink object, the object cannot be deleted.
Action	No action required.

INMEUI0001	**You do not have the required authority.**
Explanation	The permission required to do this operation has not been granted.
Action	Contact the CentraSite administrator to get sufficient permission to do this operation if required.

INMFEE0011	**Error occurred while trying to publish UDDI object(s) : {0}**
Explanation	While trying to publish UDDI object(s), if the program encounters any errors, it displays this message. {0} - The Disposition Report Fault Message exception.
Action	Ensure that the object in question is valid and any dependency required by the object is already federated to the target registry. For example, key generators specific to the source registry might not be recognized by the target.

INMFEE0012	**Cannot find the taxonomy object : {0}, {1}**
Explanation	The taxonomy processor is looking for the taxonomy object in the target registry and cannot find it. {0} - Object name {1} - Object key
Action	This error occurs very rarely. So make sure that a connection to the target registry can be obtained and re-execute the program.

INMFEE0013	**Concept publish failed**
Explanation	If you are using the taxonomy processor, then it will attempt to publish concepts and classification schemes to the target regsistry. If not all the concepts can be published, then this error occurs.
Action	Make sure that the concepts have valid values and try to re-execute the program.

INMFEE0014	**The TModel for the key {0} is not available in the federated data.**
Explanation	This message is displayed by the taxonomy processor. While trying to federate the data, if a particular TModel is identified as a taxonomy, then it looks for the TModel in the federated data. If the data is not available, then this error occurs. {0} - TModel key
Action	Provide the TModel name for federation in the configuration file and re-execute the program.

INMFEE0018	**The given default Business Entity name "{0}" is not available in the target registry.**
Explanation	In the configuration file, you will provide a default business entity name for the target, so that services can be associated with this business. If this business entity name does not have any businesses in the target registry, then this error occurs. {0} Business entity name.
Action	Provide the right business entity name after ensuring that it exists in the target registry.

INMFEE0022	**The {0} registry details are not configured properly**
Explanation	The federation takes the data specification from the provided configuration file. If the {0} registry details are not configured in the configuration file, you will get this error. {0} source / target.
Action	Make sure the {0} registry details are provided with the proper syntax in the configuration file. To get more details, please refer to the product documentation.

INMFEE0023	**The provided configFile is not configured properly.**
Explanation	The configuration file provided does not have the required elements eventTypeStoreLoc and nervAssetsLoc. These elements should be present in the configFile.
Action	Ensure that these two elements are provided in the configuration XML file. Also ensure that you provide a valid path.

INMFEE0026	**Cannot obtain OSGi instance for federation process.**
Explanation	The OSGi instance is required to emit events across the event bus for federation. It could be that the OSGi container initialization is aborted.
Action	Restart your default OSGi container. Wait until the OSGI container is initialized before you begin the federation process.

INMFEI0001	**No data available for federation. Terminating program execution.**
Explanation	The configuration file specifies the data that has to be inquired from the source registry. If the result of the inquiry does not have any data, then the federation cannot proceed and the program will terminate.
Action	Make sure that the configuration file specifies the correct data that is needed for federation.

INMFEI0002	**Results of inquiring the source registry :**
Explanation	CentraSite is currently inquiring the source registry and will display the results of the inquiry.
Action	No action required.

INMFEI0003	**Obtained number of {0} : {1}**
Explanation	This message displays the number of business objects obtained from inquiring the source registry {0} - Business(es) {1} - Number
Action	No action required.

INMFEI0004	**Timestamp based update will be performed**
Explanation	The federated objects will be compared with the modification timestamp and the update will be performed based on that.
Action	No action required.

INMFEI0005	**Timestamp based update will not be performed**
Explanation	The federated objects will be published, irrespective of whether the object to be published is the same or modified.
Action	No action required.

INMFEI0006	**Key generator processor : Modifying the keys to belong to the domain {0}**
Explanation	The UDDI keys of the federated objects will go through the key generator processor which will modify the UDDI keys such that they belong to the provided domain {DomainKey} {0} - Domain Key
Action	No action required.

INMFEI0007	**The federated data is received as the following event :**
Explanation	The Federation framework enables event emission. So the data is federated as events. This message informs that the emitted event is received for publishing to the target registry.
Action	No action required.

INMFEI0008	**Time taken for publishing the data : {0} seconds**
Explanation	The time taken for publishing the UDDI objects to the target registry is displayed by this message {0} - Time taken.
Action	No action required.

INMFEI0009	**The given UDDI object(s) were federated to this target registry.**
Explanation	The federation operation has completed and the required UDDI objects were published to this target registry.
Action	No action required.

INMFEI0010 **Trying to update/publish {0} : {1}, {2}**

Explanation This message is displayed when an attempt is made to publish a UDDI object. The object can be identified by the object name and the UDDI key which will be displayed in the message. {0} Business / Service / TModel {1} Name of the UDDI object {2} UDDI key.

Action No action required.

INMFEI0015 **Taxonomy processor : Categories (Concepts) and Taxonomies (Classification Schemes) were identified and published to the target registry**

Explanation The taxonomies and categories were identified from the provided data and published to the target registry.

Action No action required.

INMFEI0016 **No {0} were found with the provided UDDIv3 Inquiry API parameters**

Explanation The UDDI object to be inquired should be specified in the configuration file for federation. It is provided as UDDI v3 Inquiry API calls, find_business, find_service, find_tModel. If no UDDI object could be inquired with the provided Inquiry API, then this message is displayed. {0} - Business(es) / Service(s) / TModel(s).

Action Make sure that the Inquiry API adheres to the UDDI standards and that the inquiry parameters can inquire the data from the registry.

INMFEI0017 **UDDI registry configured for {0} with the following properties: user {1}, {2} Authentication.**

Explanation This message is displayed if a connection could be established to the UDDI registry with the provided details. {0} - host {1} - user {2} - AuthToken, Basic

Action No action required.

INMFEI0019 **The above mentioned {0} is published to the target registry**

Explanation The UDDI object identified by the given name and the UDDI key has been updated/published in the target registry. {0} Business / Service / TModel.

Action No action required.

INMFEI0020 **Not updating {0} : {1}, {2} in the target registry**

Explanation While the program was performing timestamp based updates in the target registry, the UDDI object identified by the given name and the UDDI key was not updated/published in the target registry because it is already available in the target. {0} - Business, Service, TModel {1} - Name of the UDDI object {2} - UDDI key.

Action No action required.

INMFEI0021	**Number of {0} received for publishing : {1} , number published : {2}**
Explanation	This message displays the number of {0} that were published to the target registry. {0} - Business(es) / Service(s) / TModel(s) {1} - Number of objects received {2} - Number published.
Action	No action required.

INMFEI0024	**The federated data has reached the target : {0}**
Explanation	There can be multiple targets configured for federation. This message displays the details of the target which has received the federated data through the federation ID {0}.
Action	No action required.

INMFEW0025	**An error occurred while trying to close a resource - {0}**
Explanation	Occasionally an error might be encountered while trying to close open connections, streams, etc. This is just a warning that an error was encountered and can be ignored.
Action	Make sure that the resource in question is not opened and/or modified by another program/application.

INMIEE0001	**The call to the registry layer of CentraSite has failed.**
Explanation	During export and import, access to the registry layer of CentraSite is required. The call to the registry layer of CentraSite has failed.
Action	Please contact your software supplier.

INMIEE0002	**The archive file {0} could not be opened.**
Explanation	The archive file is used to store the registry objects for export and import. The access to this archive file has failed.
Action	Please make sure that the archive file name is correct and you have sufficient access rights to access this file.

INMIEE0003	**The archive file {0} could not be closed.**
Explanation	The archive file is used to store the registry objects for export and import. The closing of this archive file has failed.
Action	Please make sure that the archive file has not been removed meanwhile.

INMIEE0005	**The object with name {0}, type {1} and key {2} references another object in the context {3}. The referenced object has the key {4}, but it does not exist in the registry.**
Explanation	Referenced object cannot be resolved, neither from the import set nor by existing objects.
Action	Add the referenced object.

INMIEE0006	**The registry object cannot be imported, because it is older than the existing registry object.**
Explanation	The import of the registry object has been rejected, because the timestamp of the existing registry object is newer than the timestamp of the import registry object. You can set the replace option of the import operation to overwrite the existing registry object with an older import object.
Action	You can set the replace option of the import operation to overwrite the existing registry object with an older import object.

INMIEE0007	**The import object refers to the invalid object "{0}" and thus cannot be imported either.**
Explanation	The import object refers to the specified invalid object, and thus cannot be imported either.
Action	Check why the referenced object is invalid by analyzing its error message.

INMIEE0013	**The object cannot be imported because the embedded object {0} which is embedded in the existing object does not exist and is referenced by object {1}.**
Explanation	The existing object contains an embedded object which is not defined in the object to be imported. This embedded object is referenced by another object either directly or through one of its embedded objects.
Action	Please add the missing object and try importing the object.

INMIEE0014	**The external link with URI {0} could not be found.**
Explanation	Specified resource could not be found. It may have been previously deleted.
Action	No action required.

INMIEE0016	**The user has no read/write privilege to access/modify already existing registry objects**
Explanation	The user wants to access or write an object for which the user has no privileges.
Action	The action must be performed by a more privileged user.

INMIEE0017	**The user has no write privilege to modify existing registry objects**
Explanation	The user wants to modify an object for which the user has no modify privileges.
Action	The action must be performed by a more privileged user.

INMIEE0018	**The database with the URL {0} cannot be accessed.**
Explanation	A connection to the database cannot be established.
Action	Check whether the URL is correct.

INMIEE0019	**The connection to database {0} cannot be closed.**
Explanation	The database connection has been lost and cannot be closed.
Action	Please contact your software supplier.

INMIEE0021	**The registry object could not be deleted.**
Explanation	The registry object should have been deleted after the export, but the deletion has failed.
Action	Please contact your software supplier.

INMIEE0022	**The lifecycle stage URL of the registry object does not match the URL of the import registry, which is {0}**
Explanation	The registry object carries information about valid target registries. This information is called the lifecycle stages of the particular lifecycle state of this registry object. This registry object thus can only be imported into matching target registries.
Action	The registry object can be imported into matching target registries only.

INMIEE0025	**The import of a user registry object has failed, because a user with identical name and key {0} already exists.**
Explanation	The user registry object already exists.
Action	No action required.

INMIEE0026	**The import of a group registry object has failed, because a group with identical name and key {0} already exists.**
Explanation	The group registry object already exists.
Action	No action required.

INMIEE0027	**The import operation has failed, because the update of the security information has failed, object "{0}" ({1}).**
Explanation	The update of the security information has failed.
Action	Please contact your software supplier.

INMIEE0028	**The import archive does not have the expected compatibility level of {0}.**
Explanation	The import archive must contain a file named MANIFEST.TXT which contains the compatibility level of the import archive. The compatibility level of the import archive must be the same as the compatibility level of the CentraSite version used.
Action	Use the same CentraSite version for exporting and importing.

INMIEE0030	**The provided import organization key {0} does not exist in the registry.**
Explanation	The lookup of this key in the registry was not successful.
Action	Please provide a valid import organization key.

INMIEE0031	**The provided import organization key {0} does not refer to an organization.**
Explanation	The provided key exists in the registry, but the referred object is not an organization object.
Action	Please provide a valid import organization key.

INMIEE0032	**The setting of the import organization {0} has failed.**
Explanation	During import, the setting of the import organization has failed.
Action	Please contact your software supplier.

INMIEE0034	**The deletion of the repository resource {0} has failed.**
Explanation	The option delete after export has been set and the deletion of a repository resource has failed.
Action	Please contact your software supplier.

INMIEE0035	**The query to find all external links with the external URI {0} has failed.**
Explanation	The option delete after export has been set and the query to find all external links with the same URI has failed.
Action	Please contact your software supplier.

INMIEE0036	**The collection of the registry objects of the policy {0} has failed.**
Explanation	The delete after export option is active and the policy is to be deleted after export. The collection of the registry objects belonging to the policy has failed.
Action	Please contact your software supplier.

INMIEE0040	**The import of a role registry object has failed, because a role with identical name and key {0} already exists.**
Explanation	Role objects cannot be replaced.
Action	Re-establish the organization's roles.

INMIEE0041	**The import of a permission registry object has failed, because a permission with identical name and key {0} already exists.**
Explanation	Permission objects cannot be replaced.
Action	Re-establish the organization's permission.

INMIEE0044	**The user has no privilege to create/update an asset type ({0})**
Explanation	The user has not enough permission to create or update an asset type.
Action	Check the roles of the user.

INMIEE0046	**The import of the organization with key {0} has failed, because the organization has not been exported with the option to include users, groups, roles and permissions.**
Explanation	You can only import an organization together with its users, groups, roles and permissions. However, if the organization already exists, then it is possible to just import an organization without its users, groups, roles and permissions.
Action	Export the organization with the option to include users, groups, roles and permissions.

INMIEE0048	**Creating/updating of asset type "{0}" failed with internal error: {1}**
Explanation	An asset type cannot be imported or updated because of an internal registry problem.
Action	View the internal error reason and the stack trace in the log.

INMIEE0049	**Replacement of asset type "{0}" failed due to layout mismatch**
Explanation	The asset type cannot be replaced because the layout of the importing type is incompatible with the exisiting one.
Action	View the stack trace for the details.

INMIEE0050	**The asset type "{0}" references another object with key {1}, but it does not exist in the registry.**
Explanation	A reference from the asset type to be imported is not in the registry. This is usually a referenced asset type and must be present. Due to internal reasons the import cannot continue.
Action	Check that the referenced object (asset type) is present in the target registry.

INMIEE0055	**Asset to be imported does not fit to Asset type definition with attribute mismatch, attribute: {0}**
Explanation	The asset does not match the asset type. Possibly the asset has an attribute which is not defined for the given asset type.
Action	Check the asset type for missing attributes. Import the asset type which matches the asset.

INMIEE0057	**Selective import not supported with old export archives**
Explanation	No selective import is possible, only importing the whole archive is supported.
Action	Do not select particular keys.

INMIEE0061	**User {0} not found**
Explanation	The requested user name was not found in the registry.
Action	Use a valid user name.

INMIEE0063	**The document cannot be imported, because the associated asset type will be rejected**
Explanation	The schema file of an asset type cannot be imported because the asset type itself will be rejected for another reason.
Action	Analyze the existing asset type.

INMIEE0064	**Replacement of asset type {0} failed due to layout mismatch, reason: {1}**
Explanation	The given asset type cannot be replaced because it would change or remove used information, e.g. attributes.
Action	Check the attributes of the existing asset type. There are assets with attributes which would be removed by the import.

INMIEE0066	**The document cannot be imported, because its parent was rejected**
Explanation	The repository document will not be imported because its parent object (e.g. an ExternalLink object) was rejected.
Action	Check why the parent object was rejected.

INMIEE0067	**The object cannot be replaced, because it would lose its attribute {0}, which is referenced within registry by: {1}**
Explanation	The given object cannot be replaced, because the object that is already present has an attribute which would disappear as a result of the replacement. This attribute is referenced by others, therefore the attribute must be kept.
Action	Check the existing object and its references.

INMIEE0068	**No privilege to update object**
Explanation	The user has no privilege to update an object, present in the archive, to the registry. This could happen when updating asset types or taxonomies.
Action	Check if you can import the archive as a user with more privileges.

INMIEE0072	**Cannot update asset type because of version mismatch ("{0}" / "{1}")**
Explanation	The asset type to be imported has a lower version number than the one in the registry. The type is incompatible to the registry and therefore a replacement would destroy relevant information.
Action	The asset type from a previous version cannot be imported.

INMIEE0074	**Insufficient permissions to access CentraSite's webdav for user {0} at resource {1}.**
Explanation	The user {0} tries to access the CentraSite webdav resource without insufficient permissions.
Action	Make sure the user has insufficient permissions to access the CentraSite webdav resource.

INMIEE0075	**Invalid credentials for promotion user {0}.**
Explanation	The promotion user defined in the asset promotion policy does not have the sufficient permissions to access the target CentraSite.
Action	Make sure the user has insufficient permissions to access the target CentraSite.

INMIEI0010	**The registry object is not imported, because it has the same timestamp as the existing object.**
Explanation	The object to be imported already exists with the same timestamp.
Action	No action required.

INMIEI0011	**The imported registry object has replaced the existing object.**
Explanation	The registry object to be imported already exists and has been replaced.
Action	No action required.

INMIEI0012	**The imported registry object has been created.**
Explanation	The registry object to be imported has been created.
Action	No action required.

INMIEI0020	**The registry object with key {0} was deleted after it has been exported.**
Explanation	The option delete after export has been set and the registry object has been deleted after the export.
Action	Please contact your software supplier.

INMIEI0023	**The document cannot be imported, because it is older than the existing document.**
Explanation	The import of the document has been rejected, because the timestamp of the existing document is newer than the timestamp of the import document. You can set the replace option of the import operation to overwrite the existing document with an older import document.
Action	You can set the replace option of the import operation to overwrite the existing document with an older import document.

INMIEI0024	**The document was not imported, because it has the same timestamp as the existing document.**
Explanation	The import document and the existing document have the same timestamp. No import is necessary.
Action	No action required.

INMIEI0033 **The repository resource was deleted after it has been exported.**

Explanation The option delete after export has been set and the registry object has been deleted after the export.

Action No action required.

INMIEI0039 **Referenced object not in export set: {0} --> {1}**

Explanation The target object is not in the export set.

Action Before importing, the referenced (target) objects must be present in the registry.

INMIEI0065

INMIEI0069 **The document cannot be imported because it is already present**

Explanation The document, which contains executable code, is not imported because it is already present.

Action No action required.

INMIEI0070 **The registry object is not imported, because it is already present**

Explanation The object cannot be replaced because the root object was not imported.

Action No action required.

INMIEW0008 **Embedded objects cannot be exported.**

Explanation Embedded objects like Classification, AuditableEvent, ExternalIdentifier, ServiceBinding, SpecificationLink and Association cannot be exported.

Action Deselect object from list of objects to be exported.

INMIEW0009 **Export of selected object does not find any objects to be exported.**

Explanation Export of selected object does not find any objects to be exported.

Action Remove object from list of objects to be exported.

INMIEW0029 **The referenced registry object with key {0} is not part of the export archive.**

Explanation A referenced object is not selected for export. Therefore there might be problems at import.

Action Check your associated objects and decide whether to add them to the export.

INMIEW0037	**Delete of registy objects failed, reason: {0}**
Explanation	The deletion of one or more registry objects has failed during the export with delete option. The export archive however is complete.
Action	See the reason for the rejection within the message.

INMIEW0038	**The referenced registry object with key {0} is not part of the export archive. It is referenced from object: "{1}"**
Explanation	A referenced object is not selected for export. Therefore there might be problems later when you try to import the archive.
Action	Check your associated objects and decide whether to add them to the export.

INMIEW0042	**Delete after export of object "{0}" is not supported**
Explanation	It is currently not supported to delete specified object with the delete-after-export function.
Action	Delete the object manually.

INMIEW0043	**User "{0}" could not be deleted from organization**
Explanation	The user cannot be deleted from an organization after import because this user is already in use.
Action	Clean up the user manually with the imported organization.

INMIEW0047	**Object {0} modified due to unreferenced association**
Explanation	The association to an unreferenced target object was removed from the object.
Action	Check the object and repair it if necessary.

INMIEW0051	**Unprivileged reference to key: {0}**
Explanation	An exported object has a reference to an object that the user has no privilege to access. This means for import that the referenced object must be present and the importing user must have privileges to access this object.
Action	Keep this situation in mind for a later import.

INMIEW0052	**One ore more asset types may be corrupted, key: {0}**
Explanation	Due to resolving an access violation situation, it may happen that asset types may be corrupted.
Action	Import the archive as CentraSite Administrator.

INMIEW0053	**{0} association to object "{1}" removed**
Explanation	The association to the given object has been removed during import because the target object is not present.
Action	Re-establish the removed association if possible.

INMIEW0054	**Classification "{0}" removed because of unreferenced category**
Explanation	The classification has been removed from the object because its concept is not present in the registry.
Action	Re-establish the classification if possible.

INMIEW0058	**External link reference removed from object "{0}"**
Explanation	An external link reference which does not exist for the object has been removed.
Action	Check if the external link can be re-inserted manually.

INMIEW0059	**Lifecycle state removed because of missing model**
Explanation	The object has a lifecycle state at import, however the associated lifecycle model is not present in the target registry.
Action	Import the lifecycle model first.

INMIEW0060	**User object cannot be imported because of a missing name, key: {0}**
Explanation	The import processing detected an invalid user element and ignored the import.
Action	Verify the user entry in the archive.

INMIEW0062	**contains unprivileged reference**
Explanation	The object given contains a reference to an object which cannot be exported because the user has no privilege of that object. Only the reference gets exported. At import, this reference is checked and possibly removed from the object if the referenced object is not present.
Action	Check if a more privileged user should export the object.

INMIEW0071	**ServiceBinding "{0}" removed because of unreferenced specificationObject**
Explanation	A service binding points to a specification object, which is not present in the archive or registry. Therefore the service binding gets removed from the service.
Action	Check the service and its specification objects.

INMIEW0073 **Asset type is replaced with a lower version number.**

Explanation An older version of the asset type has been replaced in the registry.

Action Consider that some values are changed in the type, for example, attributes no longer there.

INMIEW0076 **{0} {1} is imported without valid credentials.**

Explanation The import cannot restore passwords in a target CentraSite. Please verify user and password settings.

Action Specify a valid username and password for the alias or policy.

INMIME0001 **ObjectType {0} does not exist.**

Explanation The required object type does not exist in CentraSite.

Action Make sure the required object type is available in CentraSite and create an instance of it.

INMIME0002 **Asset {0} not found.**

Explanation A required asset is not available in CentraSite.

Action Create the required asset.

INMIME0003 **Error while executing JAXR operation.**

Explanation An internal JAXR operation failed.

Action Retry your request.

INMIME0004 **XPDL file {0} not found.**

Explanation An XPDL file does not exist in the location specified.

Action Make sure the given XPDL file is in the specified location.

INMIME0005 **Error while parsing the XPDL file.**

Explanation The XPDL file does not match the XPDL format.

Action Make sure the given XPDL format is valid.

INMIME0006	**Error while connecting to CentraSite.**
Explanation	It is not possible to establish a connection to the CentraSite database.
Action	Make sure the CentraSite database URL and CentraSite user credentials are valid.

INMIME0007	**Given XPDL File not supported.**
Explanation	The given XPDL file is not supported by CentraSite. CentraSite supports only XPDL 2.x.
Action	Make sure the given XPDL version is 2.x.

INMIME0008	**Specified process {0} is not available**
Explanation	There is no process with the specified asset ID
Action	Check the asset ID provided in the request

INMIME0009	**Required id is missing in Pool**
Explanation	While parsing the XPDL file, a pool element has been found but the attribute "id" is missing.
Action	Please make sure the specified XPDL file is valid.

INMIME0010	**From reference is missing in Transition**
Explanation	While parsing the XPDL, a transition element has been found but the "from reference" is missing in the transition element.
Action	Please make sure the "from reference" element contains a proper value.

INMIME0011	**To reference is missing in Transition**
Explanation	While parsing the XPDL, a transition element has been found but the "to reference" is missing in the transition element.
Action	Please make sure the "to reference" element contains a proper value.

INMIME0012	**Id is missing in Transition**
Explanation	While parsing the XPDL, a transition element has been found but the "id" is missing in the transition element.
Action	Please make sure "id" is present in the transition element and contains a proper value.

INMIME0013 **Id is missing in lane element**

Explanation While parsing the XPDL, a lane element has been found but the "id" is missing in the transition element.

Action Please make sure the "id" is present in the lane element and contains a proper value.

INMIME0014 **Id is missing in activity element**

Explanation While parsing the XPDL, a lane element has been found but the "id" is missing in the activity element.

Action Please make sure "id" is present in the activity element and contains a proper value.

INMJRE0001 **Database access error: {0}**

Explanation An error occurred while accessing the database. The corresponding stack trace contains a "caused by" message with the reason of the failure.

Action Please contact your software supplier if you can't analyze the reason of the database access error.

INMJRE0002 **Expected {0} objects**

Explanation Certain operations that accept a collection of input objects (such as for example LifeCycleManager.saveOrganizations()) expect certain object types ("Organization" in this example). The affected operation can be found in the stack trace.

Action Correct the client program.

INMJRE0003 **Invalid property name "{0}"**

Explanation The name of a property must be a valid NCName as in XML schema, e.g. it must not contain colon or whitespace.

Action Correct the name.

INMJRE0004 **Invalid object in {0} parameter**

Explanation Certain operations that accept a collection of input objects expect certain object types. The affected operation can be found in the stack trace.

Action Correct the client program.

INMJRE0005	**Mutually exclusive find qualifiers: {0}, {1}**
Explanation	The listed find qualifiers are mutually exclusive with respect to the performed operation.
Action	Correct the client program.

INMJRE0006	**Found multiple matches**
Explanation	The performed query method is supposed to return zero or one result object, however the database contains multiple matches.
Action	Please contact your software supplier.

INMJRE0007	**The javax.xml.registry.queryManagerURL property is not set**
Explanation	Before creating a new Connection, the javax.xml.registry.queryManagerURL property has to be set to a non-null value.
Action	Correct the client program.

INMJRE0008	**The credentials parameter must not be null**
Explanation	The setCredentials() method was called with a null value for the credentials parameter.
Action	Correct the client program.

INMJRE0009	**Re-connect failed**
Explanation	An error occurred while recreating the database connection according to the given credentials. The stack trace contains a "caused by" message with the reason of the failure.
Action	Please contact your software supplier.

INMJRE0010	**Invalid credentials: expected PasswordAuthentication**
Explanation	The credentials have to be passed as an instance of java.net.PasswordAuthentication.
Action	Correct the client program.

INMJRE0011	**User name is not unique: {0}, only readonly access granted**
Explanation	For each user, there should be only one user object in the database. For the given user however, several objects with the same name were found. When the user tries to log in he is granted readonly access.
Action	Log in using a different user (probably an administrator) and delete or rename the duplicate user objects.

INMJRE0012	**The declarative query manager is not supported by this implementation**
Explanation	The declarative query manager is not supported by this implementation.
Action	See the documentation for the available query functionality.

INMJRE0013	**Invalid interface name parameter: {0}**
Explanation	The method LifeCycleManager.createObject() was called with an illegal interface name.
Action	Correct the client program.

INMJRE0014	**Invalid XML response when saving documents**
Explanation	This is an internal error.
Action	Please contact your software supplier.

INMJRE0015	**The object to be undeprecated ({0}) is not in deprecated state**
Explanation	Only deprecated objects may be undeprecated.
Action	Select only deprecated objects for undeprecation.

INMJRE0016	**Illegal object type: {0}**
Explanation	A delete operation was called with an illegal object type.
Action	Correct the client program.

INMJRE0017	**Internal error: object with key "{0}" lost from cache**
Explanation	This internal error indicates an inconsistency in the object cache.
Action	Please contact your software supplier.

INMJRE0018	**Invalid null value in {0} parameter**
Explanation	The method QueryManager.getRegistryObjects() was called with a null value.
Action	Correct the client program.

INMJRE0019	**The object identified by the ConnectionFactory property {0}="{1}" is not a classification scheme**
Explanation	The default postal scheme was not specified correctly.
Action	Specify a correct default postal scheme.

INMJRE0020	**This implementation does not support makeRegistrySpecificRequest()**
Explanation	This implementation does not support makeRegistrySpecificRequest().
Action	See the documentation for the available query functionality.

INMJRE0021	**Invalid schema name "{0}", please consult the documentation for correct syntax**
Explanation	The schema name of a type must be a valid NCName as in XML schema, e.g. it must not contain colon or whitespace.
Action	Correct the name.

INMJRE0022	**An association cannot have itself as source object**
Explanation	An association cannot have itself as source object.
Action	Specify a correct association.

INMJRE0023	**An association cannot have itself as target object**
Explanation	An association cannot have itself as target object.
Action	Specify a correct association.

INMJRE0024	**Association type must not be null**
Explanation	When creating a new association the association type must not be null.
Action	Specify a correct association.

INMJRE0025	**The object to be deleted is not of type {0}**
Explanation	The delete operation specified that only objects of a particular type should be deleted, however at least one of the given keys points to a different object.
Action	Specify only keys of the requested type.

INMJRE0026	**An auditable event object cannot be deleted**
Explanation	It is not allowed to delete an auditable event.
Action	Correct the client program.

INMJRE0027	**Concept must have a classification scheme ancestor**
Explanation	The concept used for an internal classification has to belong to a classification scheme.
Action	Supply a correct concept for an internal classification.

INMJRE0028	**{0} parameter must not be null**
Explanation	The function shown on the call stack must not be called with a null value.
Action	Correct the client program.

INMJRE0029	**Concept must not have a parent**
Explanation	If a ClassificationScheme is created from a concept, then this concept must not have a parent.
Action	Supply a correct concept.

INMJRE0030	**Invalid value type: {0}**
Explanation	ClassificationScheme.setValueType() was called with an invalid value type.
Action	Supply a valid value type.

INMJRE0031	**The classification scheme to be deleted still has children**
Explanation	A classification scheme cannot be deleted if it has child concepts.
Action	Delete the child concepts before deleting the classification scheme.

INMJRE0032	**Parent not allowed for concept**
Explanation	The parent of a concept has to be a classification scheme or another concept.
Action	Supply a valid parent.

INMJRE0034	**The concept to be deleted still has children**
Explanation	A concept cannot be deleted if it has child concepts.
Action	Delete the child concepts before deleting the concept.

INMJRE0035	**Invalid value for {0} ({1})**
Explanation	An internal error occurred during the XML serialization of Java objects.
Action	Please contact your software supplier.

INMJRE0036	**Invalid string value for {0} ({1})**
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.

INMJRE0037	**The external link to be deleted still has linked objects**
Explanation	An external link cannot be deleted if it has linked objects.
Action	Remove the external link from its linked objects before deleting it.

INMJRE0039	**Cannot add a non-KeyRef to a KeyRefList**
Explanation	Internal error.
Action	Please contact your software supplier.

INMJRE0040	**toArray failed with attached JAXRException while resolving an object reference**
Explanation	An exception occurred while copying a collection to an array. See the "caused by" message in the stack trace for the cause of the problem.
Action	Please contact your software supplier.

INMJRE0041	**RegistryObjectIterator failed with attached JAXRException while resolving an object reference**
Explanation	An exception occurred while iterating a query result. See the "caused by" message of the stack trace for the cause of the problem.
Action	Please contact your software supplier.

INMJRE0042	**Invalid locale**
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.

INMJRE0043	**The organization to be deleted still has child organizations**
Explanation	An organization cannot be deleted if it has child organizations.
Action	Delete the child organizations before deleting the organization.

INMJRE0044	**The organization to be deleted still has services**
Explanation	An organization cannot be deleted if it has child services.
Action	Remove the services before deleting the organization.

INMJRE0045	**The organization to be deleted still has users**
Explanation	An organization cannot be deleted if it has users.
Action	Remove the users before deleting the organization.

INMJRE0046	**Invalid stability value: {0}**
Explanation	The setStability() method was called with an invalid stability value.
Action	Supply a valid stability value.

INMJRE0047	**This registry provider does not support client supplied keys**
Explanation	This registry provider does not support client supplied keys.
Action	Do not call the setKey() method.

INMJRE0048	**Internal error: duplicate key in object cache "{0}"**
Explanation	This internal error indicates an inconsistency in the object cache.
Action	Please contact your software supplier.

INMJRE0049	**Cannot modify object type classification**
Explanation	An instance of a user-defined type cannot be assigned another object type classification.
Action	Correct the client program.

INMJRE0050	**Duplicate object type classification**
Explanation	An instance of a user-defined type can only be classified with one concept from the "ObjectType" classification scheme.
Action	Correct the client program.

INMJRE0051	**Cannot remove object type classification**
Explanation	For instances of user-defined types it is not allowed to remove the classification that represents the object type.
Action	Correct the client program.

INMJRE0052	**This object ({0}) is deprecated and must not be referenced**
Explanation	A deprecated object must not be referenced in any way by another object.
Action	Do not create references to deprecated objects.

INMJRE0053	**An object to be deleted has not been previously saved**
Explanation	Only objects that have been previously saved can be deleted.
Action	Correct the client program.

INMJRE0054	**The "{0}" object to be deleted ({1}) is the target of the "{2}" association "{3}". The source of the association is the {4} object "{5}" with key "{6}".**
Explanation	An object cannot be deleted if it is still the target of an association.
Action	Delete the association before deleting the object.

INMJRE0055	**The registry package to be deleted still has members**
Explanation	A registry package cannot be deleted if it has member objects.
Action	Remove the member objects from the package before deleting it.

INMJRE0056	**Cannot modify the name of a slot after it was added to a registry object**
Explanation	The name of a slot cannot be changed after the slot was added to a registry object.
Action	Correct the client program.

INMJRE0057	**Invalid namespace "{0}" of type**
Explanation	The namespace of a type must be a valid URI.
Action	Correct the namespace.

INMJRE0058	**Invalid XML stream**
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.

INMJRE0059	**XML parsing error**
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.

INMJRE0060	**STAX configuration error**
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.

INMJRE0061 **Invalid URL value**

Explanation An internal error occurred while deserializing an XML document to a Java object.

Action Please contact your software supplier.

INMJRE0062 **Invalid boolean value for attribute {0}**

Explanation An internal error occurred while deserializing an XML document to a Java object.

Action Please contact your software supplier.

INMJRE0063 **Incomplete object ({0} is missing or does not have a value)**

Explanation The indicated required part of an object was missing when an object was to be saved.

Action Correct the client program.

INMJRE0064 **Cannot add an existing association to another object**

Explanation It is not possible to add the same association object to several separate registry objects.

Action Create a new association object.

INMJRE0065 **Cannot add an existing classification to another object**

Explanation It is not possible to add the same classification object to several separate registry objects.

Action Create a new classification object.

INMJRE0066 **Cannot add an existing external identifier to another object**

Explanation It is not possible to add the same external identifier object to several separate registry objects.

Action Create a new external identifier object.

INMJRE0067 **Unexpected owner type**

Explanation This is an internal error.

Action Please contact your software supplier.

INMJRE0068 **Cannot delete the pre-defined object with key "{0}"**

Explanation The CentraSite Registry/Repository database is installed with some pre-defined JAXR objects that are required for CentraSite operation. These objects must not be deleted.

Action Do not delete pre-defined objects.

INMJRE0069	**Incomplete principal**
Explanation	A CentraSitePrincipal has to be either an href representing a user or a group, or an "all" indicator, or an "authenticated" indicator, or an "unauthenticated" indicator. None of these were set.
Action	Create a correct CentraSitePrincipal object.

INMJRE0070	**Cannot set instance based security for objects of type {0}**
Explanation	Instance based security cannot be set for the following object types: AuditableEvent, Association, Classification, ExternalIdentifier, ServiceBinding and SpecificationLink.
Action	Do not try to set instance based security for these object types.

INMJRE0071	**Failed with attached JAXRException**
Explanation	Comparison of two key references failed. See the "caused by" message in the stack trace for the cause of the failure.
Action	Please contact your software supplier.

INMJRE0072	**A ServiceBinding cannot have both a TargetBinding and an AccessURI**
Explanation	For a ServiceBinding object, TargetBinding and AccessURI are mutually exclusive.
Action	Choose either TargetBinding or AccessURI.

INMJRE0073	**Expected empty XML element {0}, but found content "{1}"**
Explanation	An internal error occurred while deserializing instance based security information to a Java object.
Action	Please contact your software supplier.

INMJRE0074	**Trying to use a closed connection (created by {0} at "{1}", closed at "{2}")**
Explanation	A previously closed connection must not be used any more.
Action	Open a new connection.

INMJRE0075	**A concept object must not have a HasParent association**
Explanation	In order to allow for a proper mapping between JAXR and UDDI, a concept object must not have a HasParent association.
Action	Do not create HasParent associations for concept objects.

INMJRE0076	**Internal error: object type concept not found**
Explanation	Internal error.
Action	Please contact your software supplier.

INMJRE0077	**The operation "{0}" can only be called for objects of type "{1}"**
Explanation	Each operation belongs to one object type, and it can only be executed on objects of that type.
Action	Call the operation only for objects of the correct type.

INMJRE0078	**Internal error: method should not be called**
Explanation	Internal error.
Action	Do not call this method.

INMJRE0079	**Invalid status value: {0}**
Explanation	An invalid status value was specified.
Action	See the JAXR javadoc for correct status values.

INMJRE0080	**The status of the deprecated object ({0}) cannot be modified**
Explanation	The status of a deprecated object cannot be modified.
Action	Undeprecate the object before modifying its status.

INMJRE0082	**A concept ({0}) in the ObjectType classification scheme is to be saved without an external link to an XML schema file**
Explanation	Concepts in the ObjectType classification scheme represent JAXR object types. These concepts have to have an external link to an XML schema file (XSD).
Action	Supply an XSD file for this concept.

INMJRE0087	**Invalid value "{0}" of property "{1}"**
Explanation	The given value does not match the declared datatype of the property.
Action	Correct the value.

INMJRE0088	**The concept to be deleted ({0}) is used by a classification ({1}). The classification belongs to the {2} object with key "{3}".**
Explanation	A concept must not be deleted if it is used by a classification.
Action	Remove the classification before deleting the concept.

INMJRE0089	**Trying to add a concept with the already existing value "{0}" under the parent object with key "{1}".**
Explanation	Concepts under the same parent object must have unique values.
Action	Choose a different value for the new concept.

INMJRE0090	**Invalid slot name: "{0}"**
Explanation	In the CentraSite JAXR implementation a JAXR slot name has to have the format {uri}localname, where the {uri} part is optional. The localname has to be a valid NCName according to the XML specification. Basically this means it may start with a letter or an '_' character, followed by letters, digits, or the characters '_', '.', '-'. In particular, the localname must not contain any whitespace characters.
Action	Supply a valid slot name.

INMJRE0091	**Invalid concept used as association type: "{0}"**
Explanation	Only concepts from the classification scheme "AssociationType" may be used as association types.
Action	Choose a valid concept.

INMJRE0092	**Commit or rollback not allowed if connection does not have client controlled transactions**
Explanation	Only JAXR connections that were created with com.centrasite.jaxr.ClientTransaction=yes support commit and rollback operations.
Action	Correct the JAXR client program.

INMJRE0093	**The value "{0}" of slot "{1}" is not a valid "{2}".**
Explanation	The given value does not conform to the datatype as specified in the type definition.
Action	Specify a valid value.

INMJRE0094	**Trying to modify the value of the ObjectType concept "{0}".**
Explanation	It is not allowed to modify the value of a concept in the classification scheme ObjectType.
Action	Correct the client program.

INMJRE0095	**Invalid concept value: {0}**
Explanation	As described in the JAXR standard, a concept value has to be a valid NCName.
Action	Provide a valid concept value.

INMJRE0096	**Trying to use an internal classification scheme ({0}) for an external classification.**
Explanation	An external classification requires an external classification scheme.
Action	Supply a correct classification scheme.

INMJRE0097	**Trying to save object "{0}" which is marked to be modified without lock.**
Explanation	Objects which are marked to be modified without lock cannot be saved.
Action	Correct the client program.

INMJRE0098	**Trying to modify an outdated object ("{0}")**
Explanation	The application tried to modify a registry object which has been modified by someone else in the meantime.
Action	Make sure to modify only the latest version of a registry object.

INMJRE0099	**Repository access error.**
Explanation	An error occurred accessing the repository.
Action	Ensure the repository is available. Check there are no resource issues (e.g. lack of disk space).

INMJRE0100	**Lock not available for object "{0}"**
Explanation	The requested lock could not be granted.
Action	Wait until the lock is available.

INMJRE0103	**Cannot handle a collection of values with a simple ParameterInstance**
Explanation	A simple non-array ParameterInstance is associated with a single value.
Action	Use a single value.

INMJRE0104	**ParameterType mismatch: requested {0}, present {1}**
Explanation	The value(s) of a ParameterInstance have to correspond to the type of the respective ParameterTemplate.
Action	Read / set values according to the ParameterType.

INMJRE0105	**The readonly property "{0}" must not be modified.**
Explanation	Readonly properties can only be added to new objects. Existing property values must not be changed.
Action	Do not modify readonly properties. Do not add readonly properties to existing objects.

INMJRE0106	**Login rejected, user "{0}" not registered**
Explanation	Each user has to be registered before being used for login.
Action	Register the user.

INMJRE0107	**The "login user" option must not be modified for existing users.**
Explanation	The "login user" option can only be assigned to new users.
Action	Do not modify an existing user's "login user" option.

INMJRE0108	**For an existing user with "login user" option, the name must not be changed.**
Explanation	A user with "login user" option has to keep his name.
Action	Do not modify the name of a user with "login user" option.

INMJRE0109	**Invalid URI specified for principal: {0}.**
Explanation	The URI specified for the principal is not valid. It must be an absolute URI or one with an absolute path. The scheme of "ino:" is not a valid scheme.
Action	Ensure that the URI is valid.

INMJRE0110	**"post insert" policy event failed for RegistryObject ("{0}")**
Explanation	The enclosed exception explains the reason of the failure.
Action	Analyze the enclosed exception.

INMJRE0111	**"post update" policy event failed for RegistryObject ("{0}")**
Explanation	The enclosed exception explains the reason of the failure.
Action	Analyze the enclosed exception.

INMJRE0112	**"post delete" policy event failed for RegistryObject ("{0}")**
Explanation	The enclosed exception explains the reason of the failure.
Action	Analyze the enclosed exception.

INMJRE0113	**Please set the mandatory parameter {0} before activating the policy**
Explanation	The policy activation verifies whether all mandatory paramters are set. 0 - Name of the mandatory parameter which was not set.
Action	Please set all the mandatory parameters before activating the policy

INMJRE0114	**Action {0} does not match the scope of the policy {1}**
Explanation	The selected action does not match the scope of the policy 0 - Name of the action 1 - Name of the policy.
Action	Please ensure that the selected action matches the scope of the policy.

INMJRE0115	**The name of the default organization must not be changed.**
Explanation	The name of the default organization must not be changed.
Action	None

INMJRE0117	**Name not specified for user with "login user" option**
Explanation	A user without a name cannot have the "login user" option.
Action	Specify a user name.

INMJRE0119	**Enumeration not allowed for data type {0}**
Explanation	Enumerations are not allowed for data types InternationalString and InternationalRichText.
Action	Do not specify the enumeration option for these data types.

INMJRE0120	**Internal error: missing ExternalLink to schema document**
Explanation	This is an internal error.
Action	Please contact your software supplier.

INMJRE0121	**Internal error: target of {0} external link does not exist.**
Explanation	This is an internal error.
Action	Please contact your software supplier.

INMJRE0122	**Duplicate type name {0}**
Explanation	Each object type is identified by a name consisting of a namespace and a schema name. This name has to be unique.
Action	Provide a unique type name.

INMJRE0123	**Trying to remove the primary contact from organization {0} ({1}).**
Explanation	Each organization has to have a primary contact. It is not allowed to remove the primary contact.
Action	Do not remove the primary contact from an organization.

INMJRE0124	**Cannot delete an ObjectType concept ({0})**
Explanation	The taxonomy "ObjectType" contains concepts that represent object types. It is not allowed to delete these concepts.
Action	Do not delete ObjectType concepts.

INMJRE0125	**The user "{0}" ({1}) is the owner of, or modified the "{2}" object "{3}" ({4})**
Explanation	A user who still owns an object cannot be deleted. Also, if the user modified some object, and the corresponding audit trail entry is still present, deletion is rejected. However, the audit trail can be purged, and after all modification audit trail entries are purged, user deletion will be allowed.
Action	Delete all of the user's objects before deleting the user.

INMJRE0126	**Attempt to modify a readonly privilege**
Explanation	Readonly privileges must not be modified.
Action	Do not modify a readonly privilege.

INMJRE0127	**Unsupported data type '{0}'**
Explanation	The requested datatype is not supported.
Action	This is an internal error. Please contact your software supplier.

INMJRE0128	**Illegal usage of deny ACE**
Explanation	An ACE with deny can only be used with principal ALL and privilege ALL.
Action	Correct the ACE.

INMJRE0129	**Not a valid revision object**
Explanation	The object specified is not a object from the revision part.
Action	Check objects for the revision restore.

INMJRE0130	**Expected revision object not present**
Explanation	Unexpectedly a revision object could not be located. Obviously there is no version present of the actual object.
Action	Contact your software supplier because there is a structural problem with the revision part.

INMJRE0131	**Revision object must not be modified ("{0}")**
Explanation	Revision object must not be modified, these objects are readonly.
Action	Check your objects.

INMJRE0132	**Invalid revision object encountered ("{0}")**
Explanation	Invalid revision object encountered. The keys must be the same but are different.
Action	Check registry objects.

INMJRE0133	**The "{0}" to be deleted ({1}) is an intermediate version object**
Explanation	The object to be deleted is a target of a version association and must not be explicitly deleted.
Action	To delete objects of old versions use the purge() methods of the VersionManager interface.

INMJRE0134	**Login rejected, user "{0}" not active**
Explanation	Deactivated users cannot log in.
Action	Activate the user.

INMJRE0135	**Association type "{0}" already used in this asset type**
Explanation	There can be only one association of type "Implements" per asset type. You attempted to create such an attribute, but one exists already.
Action	Use a different association type.

INMJRE0136	**Uploaded computed profile zip does't contain computed implementation**
Explanation	the zip does not the class which implements the interfaces like {0}
Action	Make sure the computed profile implementation bundled in zip

INMJRE0138	**User "{0}" is still the primary contact of organization "{1}"**
Explanation	A user cannot be deleted if this user is still the primary contact of an organization.
Action	Do not delete primary contact users.

INMJRE0139	**Taxonomy "{0}" still used to classify object "{1}"**
Explanation	An external taxonomy cannot be deleted as long as it is referenced by classifications.
Action	Remove the classifications before deleting the taxonomy.

INMJRE0140	**The association type to be deleted ({0}) is used by an association ({1}). The association belongs to the {2} object "{3}".**
Explanation	An association type cannot be deleted if there are still associations of that type.
Action	Delete all associations of that type before deleting the association type.

INMJRE0141	**Untyped RegistryEntry "{0}" must not be saved**
Explanation	Java RegistryEntry objects are used to represent instances of user-defined types. In order to make a RegistryEntry an instance of a type, it has to be classified with the corresponding type concept.
Action	Save only typed RegistryEntries.

INMJRE0142 **must not replace existing type concept**

Explanation This is an internal error.

Action Please contact your software supplier.

INMJRE0143 **duplicate target type "{0}"**

Explanation For a RelationShip attribute the same target type was specified twice.

Action Specify each target type only once.

INMJRE0144 **invalid maxOccurs value "{0}"**

Explanation Allowed values for maxOccurs are "1" and "unbounded".

Action Specify a valid value.

INMJRE0145 **invalid minOccurs value "{0}"**

Explanation Allowed values for minOccurs are "0" and "1".

Action Specify a valid value.

INMJRE0146 **Missing taxonomy for classification attribute "{0}"**

Explanation Each classification attribute needs a taxonomy.

Action Specify a taxonomy.

INMJRE0147 **For the classification attribute "{0}", the default value "{1}" does not belong to the taxonomy "{2}".**

Explanation The default value needs to belong to the taxonomy.

Action Select a concept from the taxonomy as the default value.

INMJRE0148 **Missing association type for relationship attribute "{0}"**

Explanation Each relationship attribute needs an association type.

Action Specify an association type.

INMJRE0149 **duplicate attribute name "{0}"**

Explanation Attribute names have to be unique within classification, relationship, and file attributes.

Action Choose a unique attribute name.

INMJRE0150	**trying to access a deleted type**
Explanation	After a type was deleted, the corresponding Java instance must no longer be used.
Action	Correct the client program.

INMJRE0151	**must not rename existing type's schema name**
Explanation	The schema name uniquely identifies a type, it must not be modified.
Action	Do not rename an existing schema name.

INMJRE0152	**Cannot save object due to missing lifecycle state. The object "{0}" is classified with lifecycle state "{1}" which does not exist.**
Explanation	A call to saveObjects fails, when a saved object contains a lifecycle state classification which does not exist. This can occur after importing objects, when the lifecycle model data has not been imported beforehand.
Action	Make sure that any referenced lifecycle models are available in the registry before importing objects that refer to them.

INMJRE0153	**Invalid attribute "{0}" applied to object of type "{1}"**
Explanation	A setAttributeValue() or getAttributeValue() operation was issued against a registry object whose type does not contain the specified attribute.
Action	Correct the application.

INMJRE0154	**Conflicting aggregation settings**
Explanation	A relationship attribute can be aggregating, or reversely aggregating, but not both.
Action	Choose a correct aggregation setting.

INMJRE0155	**"{0}" is not a virtual type**
Explanation	The given type concept is not a virtual type.
Action	Please supply a virtual type.

INMJRE0156	**The delete operation failed due to a hidden association.**
Explanation	The object to be deleted is still the target of an association. However, the user that tries to delete the object does not have view permissions on the association and its source object. Probably a CentraSite administrator with full permissions is required to perform the delete operation.
Action	Please contact your CentraSite administrator.

INMJRE0158	**The locale {0} is not contained in the set of restricted locales.**
Explanation	The set of restricted locales defines which locales may be used when creating a value for an InternationalString.
Action	Choose a different locale.

INMJRE0159	**Invalid or missing default locale**
Explanation	When defining the set of restricted locales, exactly one locale needs to be marked as the default locale.
Action	Specify a proper default locale.

INMJRE0160	**The "{0}" package to be deleted ({1}) still has members, e.g. the {2} object "{3}" with key "{4}".**
Explanation	A registry package cannot be deleted if it still has members.
Action	Delete the members before deleting the registry package.

INMJRE0161	**no value provided for required attribute {0} of {1} "{2}"**
Explanation	The attribute is defined with the "required" option, but the attribute value was not supplied when storing the object.
Action	Provide a value for the attribute.

INMJRE0162	**too many values provided for single-value attribute {0} of {1} "{2}"**
Explanation	For single-value attributes, at most one value may be provided.
Action	Provide a correct attribute value.

INMJRE0163	**Internal error: cannot construct a RegistryObject from {0}.**
Explanation	This is an internal error.
Action	Contact your software provider.

INMJRE0164	**Internal error: missing object id for {0}**
Explanation	This is an internal error.
Action	Contact your software provider.

INMJRE0165	**Cannot modify attribute {0} of type {1} to be required, because it does not exist in the object with key "{2}"**
Explanation	While updating a type description, an attribute was modified to be a required attribute. This modification however can only be done when the attribute is already present in all existing objects of the type (which is trivially true if there are no existing objects), or it has been equipped at the same time with a default value.
Action	Define a default value for the attribute, or refrain from setting the attribute to "required", then retry the modification only after the attribute has been added to all existing objects of the given type.

INMJRE0166	**Failed to check that the given profile is a computed profile**
Explanation	While parsing the uploaded zip file, an unexpected exception occurred.
Action	Please make sure the uploaded zip file is not corrupted.

INMJRE0167	**Uploaded computed profile implementation zip file does not contain profile implementation class, which implements the interface like {0}**
Explanation	The uploaded computed profile implementation zip file does not contain the class that implements the interface like {0}.
Action	Please make sure the zip file contains the computed profile implementation.

INMJRE0168	**Default value should be given for all required attributes when the types have instances. Please provide the default value for the required attribute "{0}".**
Explanation	When updating an asset type which already has instances, all the required attributes of that type should be provided with default values.
Action	Ensure that all the required attributes of the edited asset type have default values.

INMJRE0169	**The predefined attribute cannot be deleted**
Explanation	You cannot delete the predefined attributes.
Action	You cannot delete the predefined attribute.

INMJUE0001	**Check your access rights and the proxy settings**
Explanation	The accessing user does not have sufficient privileges for the target object.
Action	Do the action as a more privileged user.

INMJUE0005	**No privilege to access target object from object: {0}**
Explanation	The accessing user does not have sufficient privileges for the target object.
Action	Do the action with a more privileged user.

INMJUE0006	**Uploaded computed profile implementation zip does't contain profile implementation class, which implements the interface like {0}**
Explanation	The uploaded computed profile implementation zip file does not contain the class that implements the interface like the one shown.
Action	Make sure the zip file contains the computed profile implementation.

INMJUE0007	**Failed to check that a given profile is a computed profile**
Explanation	While parsing the uploaded zip file an unexpected exception occurred.
Action	Make sure that the uploaded zip file is not corrupted.

INMJUW0002	**The associated object of type "External Link" could not be deleted**
Explanation	This can happen while deleting virtual services.
Action	No action required.

INMJUW0003	**The associated object of type "WS-Policy attachment" could not be deleted**
Explanation	This can happen when deleting virtual services.
Action	No action required.

INMJUW0004	**The associated object of type "Associated with" could not be deleted**
Explanation	This can happen when deleting virtual services.
Action	No action required.

INMLFE0001	**Provider not set for {0}**
Explanation	The LCM factory could not be initialized since the property for the provider class is not set appropriately.
Action	Please check the javadoc of the LCM API to set the appropriate property.

INMLFE0002	**Provider {0} not found**
Explanation	The LCM provider class could not be loaded.
Action	Please check that the name of provider class is appropriately set and is available for class loading.

INMLFE0003	**Provider {0} could not be instantiated**
Explanation	An exception occurred while trying to load the provider class.
Action	Please check that the name of provider class is appropriately set and is available for class loading

INMLFE0004	**No initial state defined**
Explanation	There should be an initial state defined for any lifecycle model.
Action	Please make sure that there is an initial state defined for the lifecycle model.

INMLFE0005	**The state(s) {0} are unreachable**
Explanation	It should be possible to traverse to each state within a lifecycle model from the initial state 0 - name(s) of the state(s) unreachable from the initial state.
Action	Please make sure that each state is reachable from the initial state in the lifecycle model.

INMLFE0006	**A lifecycle model should have at least one end state**
Explanation	Any lifecycle model should have at least one state that does not have a next state.
Action	Please make sure that the lifecycle model has at least one end state.

INMLFE0007	**The given object type {0} cannot be LCM enabled**
Explanation	Only asset types, policies and lifecycle models can be LCM enabled 0 - name of the invalid object type
Action	Please make sure that an appropriate object type that can be LCM enabled is used.

INMLFE0008	**The state {0} cannot be set as an initial state. The state is currently not present in the lifecycle model.**
Explanation	Only states which are already part of the lifecycle model can be set as an initial state.
Action	Please make sure that you add the state to the lifecycle model before setting it as the initial state.

INMLFE0009	**The state {0} cannot be set as a preferred next state. The state is currently not a next state.**
Explanation	Only states which are part of the next states can be set as preferred next state 0 - name of the invalid preferred next state.
Action	Please ensure that the state is part of the next states before setting it as the preferred next state.

INMLFE0010	**Each lifecycle model should belong to an organization**
Explanation	Each LCM should belong to one organization.
Action	Please assign an organization to which the lifecycle model belongs.

INMLFE0011	**It is only possible to define a lifecycle model for lifecycle models in CentraSite Active SOA version**
Explanation	A lifecycle model for lifecycle models can only be defined in the CentraSite Active SOA edition.
Action	No action required.

INMLFE0012	**{0] is not a type in CentraSiteRegistryTypes taxonomy**
Explanation	The concept used for the registry type should belong to the predefined CentraSiteRegistryTypes taxonomy 0 - key of the invalid concept.
Action	Please use a concept that belongs to the predefined CentraSiteRegistryTypes taxonomy.

INMLFE0014	**A type with the given name {0} was not found**
Explanation	No object type was found with the given name 0 - name of the given object type.
Action	Please specify a valid type name.

INMLFE0015	**No active lifecycle model for the given registry object found**
Explanation	The given registry object is not associated with any active lifecycle model.
Action	No action required.

INMLFE0016	**The given state {0} is not a valid follow up state of {1} for the given registry object {2}**
Explanation	The current state of the registry object does not have a state transition to the specified target state. 0 - specified target state 1 - current state of the registry object 2 - name of the registry object.
Action	Please ensure that there is a valid state transition from the current state of the registry object to the specified target state.

INMLFE0017	**The given registry object is never in a work flow to change its state**
Explanation	The given registry object cannot be approved or rejected since it was never in a work flow to change its state.
Action	No action required.

INMLFE0018	**For each object type, only one lifecycle model can be active per organization**
Explanation	For any object type and organization, there can be at most one active LCM.
Action	Please make sure that there are no active LCMs associated with the given object type and organization, before trying to activate this LCM.

INMLFE0019	**A promotion node can be set only on the final states of the lifecycle model**
Explanation	Promotion nodes be only be set for final states of a lifecycle model.
Action	Please make sure that promotion nodes are set only for final states.

INMLFE0020	**The registry object is in a workflow to change its state**
Explanation	Next states cannot be determined for a registry object with a pending state change.
Action	No action required.

INMLFE0021	**The given registry object is not a user or a role or a group that could be used to restrict transitions to the state**
Explanation	The registry object used to restrict transitions to the state should be either a user or group or role. No other type of registry object can be used.
Action	Please make sure that the registry object used to restrict transitions to the state is either a user or a group or a role.

INMLFE0022	**The current user is not allowed to perform the state transition**
Explanation	The current user does not have the necessary permissions to perform the requested state transition.
Action	Please make sure that the current user has the necessary permissions to perform the requested state transition.

INMLFE0024	**Failed to set the initial state for the registry object {0}**
Explanation	The registry object could not be set to the initial state of the life cycle model since there is an approval work flow.
Action	Please make sure that there are no approval work flows triggered for the initial state of the LCM.

INMLFE0026	**The lifecycle model is deleted!**
Explanation	Deleted lifecycle models cannot be reused.
Action	Please use an existing lifecycle model and do not refer to deleted lifecycle models.

INMLFE0027	**The lifecycle model is not associated with any types**
Explanation	Each lifecycle model should be associated with at least one object type.
Action	Please choose at least one object type which will be associated with the lifecycle model.

INMLFE0028	**Internal error: User {0}/{1} does not belong to any organization**
Explanation	The logged in user does not belong to any organization 0 - Name of the user 1 - Key of the user.
Action	Please make sure that the logged in user belongs to some organization.

INMLFE0029	**Internal error: please specify the organization for which the lifecycle model has to be found**
Explanation	A lifecycle model can be found only in the context of an organization for which the registry object is to be created.
Action	Please specify the organization for which the lifecycle model has to be found.

INMLFE0030	**{0} lifecycle model cannot be modified**
Explanation	A lifecycle model which is active or in a state after active cannot be modified.
Action	Please ensure that the lifecycle model is in a state before active so that it can be modified.

INMLFE0031	**The lifecycle model cannot be deleted!**
Explanation	The lifecycle model could not be deleted because of an internal exception.
Action	Please look at the exception for more details.

INMLFE0032	**The model cannot be set to state {0}**
Explanation	The lifecycle model could not be set to the given state since it is not a valid transition from the current state of the model 0 - name of the invalid state.
Action	Please make sure that the model is set to a state that is a valid transition from its current state.

INMLFE0033	**Transition from any state to initial state is not allowed**
Explanation	Transition from any state to initial state is not allowed.
Action	Transition from any state to initial state is not allowed.

INMLFE0034	**The lifecycle model cannot be activated since the older version of this model could not be superseded**
Explanation	The lifecycle model which is a newer version of some other model could not be activated since the older version model could not be marked as superseded.
Action	Please ensure that the older version model can be marked as superseded before activating the newer lifecycle model.

INMLFE0035	**An active lifecycle model cannot be deleted**
Explanation	An attempt was made to delete an active lifecycle model.
Action	An active lifecycle model cannot be deleted.

INMLFE0036	**State transition can only be made between states which belong to the same lifecycle model**
Explanation	There are state transitions which have been made between states which belong to different lifecycle models.
Action	Please ensure that the state transitions are not made between states of two different lifecycle models.

INMLFE0037	**Lifecycle Model for Lifecycles cannot be deleted**
Explanation	The predefined lifecycle model for lifecycles cannot be deleted.
Action	No action required.

INMLFE0038	**Policy Lifecyle cannot be deleted**
Explanation	The predefined lifecycle model for policies cannot be deleted.
Action	No action required.

INMLFE0041	**Intermediate versions of a Lifecycle cannot be deleted using 'Delete' option**
Explanation	There are two options to delete a lifecycle and its version objects, namely 'Delete' and 'Purge'. The 'Delete' option can be used only for the latest version of the lifecycle.
Action	Deletion will not be allowed.

INMLYE0002	**Lifecycle Model Name should not be empty**
Explanation	The model name is mandatory.
Action	Enter the model name.

INMLYE0003	**Stage Name should not be empty**
Explanation	The stage name is mandatory.
Action	Enter the stage name.

INMLYE0005	**Only one row can be moved down**
Explanation	For the order of the lifecycle state, only one row can be moved up or down.
Action	While moving down any lifecycle state, please ensure that only one state is selected.

INMLYE0007	**Only one row can be moved up**
Explanation	To order the LC State, only one row can be moved up.
Action	Lifecycle state order.

INMLYE0008	**Lifecycle model(s) should be selected for saving report**
Explanation	Saving a report should have one LCM object.
Action	Saving a report should have one LCM object.

INMLYE0009	**Two state names cannot have the same name**
Explanation	There is a duplicate state name.
Action	Choose a unique state name.

INMPEE0003	**Namespace {0} does not match any of the possible namespaces {1}**
Explanation	Service namespace is validated against the set of possible namespaces as specified by the policy. 0 - Namespace of the service 1 - Allowed namespaces from policy.
Action	Please ensure that the namespace of the service matches at least one of the allowed namespaces.

INMPEE0009	**Policy {0} cannot be deactivated since an approval triggered by the policy for {1} {2} is in progress**
Explanation	Since there is an approval which is in progress, this policy cannot be deactivated. 0 - Name of the policy 1 - Type of the object which is pending 2 - Name of the object which is pending.
Action	Please complete the approval flow for the specific object and then deactivate the policy.

INMPEE0013	**Organization {0} should have Administrator**
Explanation	Every organization should have an administrator assigned 0 - Name of the organization
Action	Please ensure that the organization has an administrator assigned to it.

INMPEE0016	**{0} {1} must be classified by taxonomy {2}**
Explanation	The given registry object is validated to be classified by the given taxonomy. 0 - Type name of the object 1 - Registry Object name 2 - Taxonomy node name.
Action	Please ensure that the registry object is classified by the given taxonomy.

INMPEE0021	**Policy without any actions cannot be executed**
Explanation	A policy without any actions cannot be executed.
Action	Please assign some actions to this policy.

INMPEE0030	**Service WSDL size {0} does not conform with the specified size {1}**
Explanation	The service WSDL size does not match the size specified by the policy. 0 - WSDL size of the service 1 - WSDL size specified in the policy.
Action	Please ensure that the WSDL size of the service conforms with the specified size.

INMPEE0031	**{0} name {1} does not conform with the pattern {2}**
Explanation	The registry object name does not match the specified pattern. 0 - Type of the registry object 1 - Name of the registry object 2 - Name pattern specified in the policy.
Action	Please ensure that the name of registry object conforms to the specified pattern.

INMPEE0039	**Service Binding Type(s) {0} are missing in the WSDL. The mandatory bindings specified in the policy are {1}**
Explanation	The binding types of the service are validated against the specified bindings. 0 - Violating binding types of the service 1 - Binding types specified by the policy.
Action	Please ensure that the service binding types conform to the specified binding types.

INMPEE0043	**User does not have the permission to create {0}**
Explanation	The user does not have the required permission to create an object of the given type. {0} refers to the object type for which the user is creating an instance.
Action	Please assign the necessary permissions to the user before trying to create an object of the type.

INMPEE0045	**Namespace cannot be empty for {0} {1}**
Explanation	The namespace of the applied object is empty. {0} - type of the applied object {1} - name of the applied object.
Action	Please ensure that the namespace is provided for the object.

INMPEE0046	**Description is empty for {0} {1}**
Explanation	The description of the registry object is empty. 0 - Type of the registry object 1 - Name of the registry object.
Action	Please make sure that the registry object has a non-empty and valid description.

INMPEE0047	**Name is empty for {0}**
Explanation	The name of the registry object is empty 0. - Type of the registry object.
Action	Please make sure that the registry object has a non-empty and valid name.

INMPEE0048	**Policy {0} cannot be activated since there is a newer active version of this policy**
Explanation	Since there is a newer version of this policy which is active, the policy cannot be activated.
Action	Please use the newest active version of the policy for enforcement.

INMPEE0049	**Policy {0} cannot be activated since the older version of the policy could not be superseded**
Explanation	The policy which is a newer version of some other policy could not be activated since the older version could not be marked as superseded.
Action	Please ensure that the older version policy can be marked as superseded before activating the newer policy.

INMPEE0052	**{0} description {1} does not conform with the pattern {2}**
Explanation	The registry object description does not conform to the pattern specified in the policy. 0 - Type of the registry object 1 - Description of the registry object 2 - Description pattern specified in the policy.
Action	Please ensure that the description of the registry object conforms to the specified pattern.

INMPEE0057	**{0} {1} does not belong to an LCM state**
Explanation	The registry object does not belong to an LCM state. 0 - Type name of the object 1 - Name of the object.
Action	Please ensure that the registry object is set to an appropriate LCM state.

INMPEE0059	**{0} {1} belongs to state {2} which does not conform to the allowed states {3}**
Explanation	The LCM state of the registry object is validated against the allowed states specified in the policy. 0 - Type name of the registry object 1 - Name of the registry object 2 - Current state name of the registry object 3 - Allowed states specified in the policy.
Action	Please ensure that the registry object is set to an appropriate LCM state.

INMPEE0064	**{0} {1} does not have a value set for attribute {2}**
Explanation	The registry object does not have a value set of the specified attribute. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute name specified in the policy.
Action	Please ensure that the object has a value set for the specific attribute.

INMPEE0066	**{0} {1} has value {2} set for attribute {3} which does not conform to the allowed values {4}**
Explanation	The registry object has a value set of the specified attribute which does not conform to the allowed values. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute value of the registry object 3 - Attribute name specified in the policy 4 - Allowed attribute values specified in the policy.
Action	Please ensure that the object has an appropriate value set for the specific attribute.

INMPEE0069	**Policy {0} cannot be activated as some mandatory action parameters are not set**
Explanation	The policy has some mandatory parameters which are not set, so the policy cannot be activated. 0 - Name of the policy.
Action	Please ensure that all mandatory parameters of the policy are set before activation.

INMPEE0071	**Priority for a policy should be between {0} and {1}**
Explanation	The priority for a policy should be within the specified limits.
Action	Please enter a priority within the specified limits.

INMPEE0072	**Policy action rule {0} is invalid**
Explanation	The action.properties file is not accessible for this policy action rule. 0- name of the policy action.
Action	Please enter the correct rule file for the policy action.

INMPEE0073	**{0} is not a valid Groovy script**
Explanation	The action file is not a valid Groovy script. 0 – name of the Groovy script.
Action	Please upload a valid Groovy script.

INMPEE0074	**Result message not set for Groovy action {0}**
Explanation	The Groovy script did not set the result object. 0 – name of the Groovy action.
Action	Set the result inside the Groovy action.

INMPEE0087	**Active user {0} cannot be deleted.**
Explanation	Only deactivated users can be deleted in CentraSite. {0} specifies the user name.
Action	Deactivate the user before deletion.

INMPEE0089	**Organization level permission for {0} is not created yet for organization {1}**
Explanation	Firstly we have to create an organization before creating any registry object for an organization. This is because organization level permissions of that organization are used in instance level permission for those registry objects. 0 – name of the registry object 1 – name of the organization.
Action	Create the organization first.

INMPEE0091	**User cannot update the role {0} with permissions that he does not have**
Explanation	A user can assign permissions that he has to a role. If a user tries to update a role with a permission that he does not have, then this error will be thrown. 0 – name of the role.
Action	Please ensure that the user has the permissions that he is assigning to a role.

INMPEE0092	**{0} cannot be deleted**
Explanation	The default organization cannot be deleted.
Action	Do not try to delete the default organization.

INMPEE0094	**Policy {0} cannot be activated since an active older version of the policy has a pending approval**
Explanation	Since there is an older version of this policy which is active and has a pending approval, this newer policy version cannot be activated. 0 – name of the policy.
Action	Please ensure that any approval triggered by the older active version of this policy gets completed before activating the newer version.

INMPEE0102	**Organization Primary Contact has to be an active user**
Explanation	A deactivated user cannot become the primary contact of an organization.
Action	Please assign an active user as the primary contact of an organization.

INMPEE0104	**User cannot assign the role {0} to a user/group that he cannot manage**
Explanation	If a user with "Manage Users" permission in one organization tries to assign a role from another organization or a system level role to his own organization's user, then this error message will be thrown.
Action	The user needs to have the "Manage Users" permission of the role's organization (if it is an organization level role) or the user should have the "Manage System-wide Roles" permission if it is a system level role. Only then can the user assign that role to a user.

INMPEE0105	**User cannot create the Role {0} with permissions that the user does not have**
Explanation	A user can update the role only with the permissions that he possesses. If a user with Organization level "Manage Users" permission or "Manage System-wide Roles" permission tries to update a role then this user can assign only the permission that he/she already has, otherwise this error message will be thrown.
Action	Please ensure that the user has the permissions that he/she is assigning to a role.

INMPEE0106	**Action class {0} not found in {1}**
Explanation	The action class mentioned in the properties file should be present in the action rule archive. 0 – name of the executable class, 1 – name of the action rule archive.
Action	The action class mentioned in the properties file is not present in the action rule archive. Please make sure the class mentioned in the property file is present in the archive.

INMPEE0110	**WS-I actions should not be combined with other actions in a single policy**
Explanation	A policy containing WS-I actions cannot contain any actions other than WS-I policy actions
Action	Make sure WS-I actions are not combined with other actions in a single policy.

INMPEE0111	**Dependent actions {0} for {1} is not included**
Explanation	Dependent actions of a WS-I action are not included. 0 – name of the missing dependent WS-I action, 1 - name of the included WS-I action.
Action	Dependent actions of a WS-I action should be included in a policy.

INMPEE0113	**There are no lifecycle states associated with the {0} event for the policy {1} and hence this policy cannot be activated**
Explanation	The pre/post state change policy does not have any lifecycle states associated with it and hence the policy will not be executed for any state transition. Hence this policy cannot be activated. 0 - Pre/Post State Change event, 1 - Name of the policy.
Action	Please ensure that the policy is associated with the appropriate lifecycle states for the pre/post state change events

INMPEE0114	**Lifecycle state {0} from {1} does not match the scope of the policy {2}**
Explanation	The lifecycle state associated with the policy does not correspond to the object types specified in the scope of the policy. 0 - Name of the lifecycle state associated with this policy, 1 - Name of the lifecycle model to which this state belongs, 2 - Name of the policy.
Action	Please ensure that the lifecycle states associated to the policy belong to a lifecycle model whose object type conform to the object types specified in the policy scope

INMPEE0115	**Consumer Registration Request {0} is not associated with any asset**
Explanation	A consumer registration request object must be associated with an asset. 0 – Name of the consumer registration request.
Action	Associate the consumer registration request object with an asset using an association with the association type "relatedTo". The source object of the association is the consumer registration request. The target object of the association is the asset.

INMPEE0118	**{0} {1} is pending on state change. So it cannot be modified or deleted.**
Explanation	The object has a pending state change. So this object cannot be modified or deleted. 0 - Type of the object 1 - Name of the object.
Action	If you want to modify or delete the object, release the object from the pending state. If there are pending approvals, get them completed.

INMPEE0120	**Attribute {0} is read only and hence cannot be set for {1} {2}**
Explanation	Since the attribute is read only, the given attribute value cannot be set for the registry object. 0 - Name of the read only attribute, 1 - Type of the registry object, 2 - Name of the registry object.
Action	Please ensure that the chosen attribute is not a read only attribute.

INMPEE0129	**Initial State {0} cannot be used to define policy on Pre-State Change event**
Explanation	Pre-state change policies cannot be defined on initial states of any lifecycle model. 0 - Name of the initial state associated with the policy.
Action	Please use a lifecycle state other than the initial state to define the pre-state change policy.

INMPEE0136	**Policy action {0} is used, so it cannot be edited or deleted**
Explanation	If the policy action is used by any other policy, the policy action can't be edited or deleted.
Action	Before editing or deleting any policy action, the user has to verify whether any policy is using this action or not.

INMPEE0142	**{0} {1} has a pending approval and hence cannot be moved**
Explanation	The registry object has an approval in pending state. So it cannot be moved to a new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
Action	Please complete the pending approval for the registry object before moving it.

INMPEE0143	**{0} {1} has a pending consumer registration request and hence cannot be moved**
Explanation	The registry object has a pending consumer registration, so it cannot be moved to a new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
Action	Please complete the consumer registration request for the registry object before moving it.

INMPEE0144	**{0} {1} is an internal object of CentraSite and hence cannot be moved**
Explanation	Internal objects of CentraSite cannot be moved.
Action	Internal objects of CentraSite cannot be moved.

INMPEE0145	**{0} {1} cannot be moved to inactive or internal users of CentraSite**
Explanation	Ownership of the registry object cannot be transferred to inactive or internal users of CentraSite. 0 - Type of the registry object 1 - Name of the registry object.
Action	Please ensure that the new owner for the registry object is an active and non-internal user of CentraSite.

INMPEE0146	**The mandatory attribute {0} does not have value for this object**
Explanation	An attribute should have a value for a registry object if it is marked as required.
Action	Provide appropriate value(s).

INMPEE0148	**Only user with CentraSite Administrator role can do the change ownership action**
Explanation	Only a user with the CentraSite Administrator role can do the change ownership action.
Action	Please make sure that you log in as a user who has CentraSite Administrator role to perform the ownership change.

INMPEE0149	**Only user with CentraSite Administrator role can do the change organization action**
Explanation	Only a user with the CentraSite Administrator role can do the change organization action for assets.
Action	Please make sure that you log in as a user who has the CentraSite Administrator role to perform the organization change.

INMPEE0150	**Internal users cannot be moved across organizations.**
Explanation	If the user is trying to move any of the predefined or internal users from one organization to another organization, this error message will be displayed.
Action	Remove the predefined/internal users from the list for moving users across organizations.

INMPEE0151	**Owner for the object {0} of type {1} is not present in CentraSite**
Explanation	The owner for the object is not present in CentraSite. {0} - Name of the object {1} - Type of the object.
Action	The owner should not be allowed to be removed from CentraSite while owning some objects. So, identify how the owner was removed from CentraSite with this object dependency and report a bug.

INMPEE0153	**View permission on {0} {1} is not available for {2} {3}**
Explanation	The view permission on the registry object is not available for the specific user or group. 0 - Type of the registry object for which the profile permissions are being set 1 - Name of the registry object 2 - User or Group 3 - Name of the user or group.
Action	Please set the view permission on the registry object for the specific user or group before setting the profile permissions.

INMPEE0154	**Modify permission on {0} {1} is not available for {2} {3}**
Explanation	The modify permission on the registry object is not available for the specific user or group. 0 - Type of the registry object for which the profile permissions are being set 1 - Name of the registry object 2 - User or Group 3 - Name of the user or group.
Action	Please set the modify permission on the registry object for the specific user or group before setting the profile permissions.

INMPEE0156	**The new owner {0} does not have create asset permission in organization {1}**
Explanation	An attempt was made to move an asset to a user who does not have "create assets" permission in the asset's organization.
Action	Assign the Asset Provider role or any custom role which contains the "create assets" permission in the asset' organization to the target user.

INMPEE0167	**The RejectHandler policy prohibited the operation for {0} {1}**
Explanation	Operations like "move", "delete", etc. are only allowed for specific object types.
Action	Correct the application program.

INMPEE0175	**Virtual Service {0} cannot be deleted because it has been deployed to the target.**
Explanation	This error message is thrown when you are attempting to delete the virtual service which is deployed to a target.
Action	Undeploy the virtual service before attempting to delete.

INMPEE0176	**Target information not available for the deployment operation.**
Explanation	A target is mandatory for deployment operations of Virtual Service/Virtual XML service/Virtual REST service/Consumer Application/Aliases.
Action	Trigger deployment from the deployment profile.

INMPEE0180	**IS Service Interface {0} should have at least one associated IS Service Object, hence the corresponding REST service is not created.**
Explanation	The IS Service Interface object should have at least one associated IS Service Object.
Action	Make sure at least one IS Service Object (HTTP methods get, put, post and delete) is associated to the IS Service Interface and also make sure the name of the IS Service Object should contain the following strings (get, put, post and delete) appropriate to the method definition.

INMPEE0181	**REST Service {0} should have at least one native endpoint, hence the corresponding REST service is not created.**
Explanation	The REST service published from the webMethods product suite should have at least one native endpoint.
Action	Make sure the port attribute (IS Server object) has a value defined.

INMPEE0184	**Cannot remove the existing life cycle state from the object {0}**
Explanation	It is not possible to remove the existing life cycle state from the given object
Action	No action required.

INMPEE0185	**{0} {1} must be classified by at least one of {2}**
Explanation	The given registry object is validated to be classified by the given taxonomy or category. 0 - Type name of the object 1 - Registry Object name 2 - Taxonomy node name or category node name.
Action	Please ensure that the registry object is classified by the given taxonomy or category.

INMPEE0190	**Unable to delete the exported archive file**
Explanation	The intermediate archive file created for asset promotion could not be deleted.
Action	No action required.

INMPEE0204	**The mandatory attribute {0}, of {1} "{2}" does not have a value**
Explanation	The mandatory attribute {0} of {2} created from type {1} does not have a value. Attribute {0} has been marked "required" in the definition of type {2} and hence should have a value.
Action	Provide a value for the attribute {0} or provide a default value for the attribute in the definition of type {2}.

INMPEE0206	**The validation pattern "{0}" is invalid for policy "{1} at {2}". Repair the regular expression pattern.**
Explanation	The validation policy action of the specified policy contains an invalid/unsupported regular expression pattern.
Action	Specify a syntactically correct regular expression for the policy action.

INMPEE0210	**Key Generator Policy is not enabled for the API {0}**
Explanation	The Key Generator Policy for the given API is not generated.
Action	Contact the API provider.

INMPEE0211	**Onboarding Organization {0} with Administrator User {1} has failed**
Explanation	Onboarding the given organization with the given administrator user of that organization has failed.
Action	Contact the CentraSite administrator.

INMPEE0212	**Onboarding User {0} in Organization {1} has failed**
Explanation	Onboarding of the given user has failed in the given organization.
Action	Contact the organization administrator.

INMPEE0218	**API key revocation failed.**
Explanation	The specified API key could not be revoked. This problem can occur because the requestor does not have the required permisison to revoke API key.
Action	Only a user with Administrator or Asset Provider role can revoke API keys.

INMPEE0225Error	**CentraSite cannot delete the alias because it is already deployed to the target. Alias: {0}**
Explanation	You are trying to delete an alias which is already deployed to a target.
Action	You must undeploy an alias before you delete it.

INMPEE0226	**The user {0} of the API Portal cannot be deleted.**
Explanation	You do not have sufficient access rights to delete the specified user {0} of API Portal, who has onboarded in the CentraSite registry. To delete the specified user, you must belong to the CentraSite Administrator role.
Action	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMPEE0227	**Could not send key revocation notice to the user configured in the API consumption settings.**
Explanation	An email notification for the key revocation status could not be sent to the user configured in the API consumption settings, possibly because the user specified has been deleted from the CentraSite registry.
Action	Verify that the specified user exists in the CentraSite registry. If the user exists and the error persists, contact your administrator. If the user does not exist, remove the user from the API consumption settings.

INMPEE0228	**API Portal user {0} was off-boarded.**
Explanation	The API Portal user {0} has been off-boarded prior to the key generation/renewal operation.
Action	Onboard the API Portal user and try again.

INMPEE0229	**Key revocation policy must be enabled for the API.**
Explanation	The key revocation policy required for revoking an API's key has not been enabled for the API.
Action	Contact the API provider.

INMPEE0230	**Failed to delete the API {0}.**
Explanation	Could not delete the specified API {0} from CentraSite registry, possibly because the specified API is published to one or more API Portals.
Action	Make sure you unpublish the API from all of the API Portals, before trying to delete it.

INMPEE0231	**Failed to create object {0} in organization {1}.**
Explanation	Could not create the object {0} in the organization {1}, possibly because of insufficient permissions.
Action	Ensure that you have sufficient permissions to create the object in the selected organization.

INMPEE0234	**The asset {0} cannot be deleted, because it is consumed by one or more assets.**
Explanation	The asset {0} cannot be deleted, because it is consumed by one or more assets.
Action	Make sure you unconsume all consumers from the asset, before trying to delete it.

INMPEE0236	**The WSDL does not have any service element for {0}.**
Explanation	The WSDL cannot be validated if there are no service elements in it.
Action	If the service {0} is a Virtual type, the service element will be available only after it is deployed to a Mediator gateway.

INMPEI0002	**Namespace {0} matches one of the possible namespaces {1}**
Explanation	The service namespace validated against the set of possible namespaces as specified by the policy. 0 - Namespace of the service 1 - Allowed namespaces from policy.
Action	No action required.

INMPEI0004	**User {0} does not have the role specified in the policy**
Explanation	Since the user does not have the role specified in the policy, the role group policy is not applicable for the user 0 - Name of the user.
Action	No action required.

INMPEI0005	**Attribute {0} is not applicable for {1} {2}**
Explanation	The specified attribute is not applicable for the given object. 0 - Name of the attribute 1 - Type of the object 2 - Name of the object.
Action	No action required.

INMPEI0006	**Policy {0} was successfully validated for activation**
Explanation	The policy was successfully validated for activation. 0 - Name of the policy.
Action	No action required.

INMPEI0007	**LC Model {0} was successfully validated for activation**
Explanation	The lifecycle was successfully validated for activation. 0 - Name of the lifecycle model.
Action	No action required.

INMPEI0008	**Policy {0} was successfully validated for deactivation**
Explanation	The policy was successfully validated for deactivation. 0 - Name of the policy.
Action	No action required.

INMPEI0010	**Permissions assigned successfully for {0} {1}**
Explanation	Default permissions were assigned successfully for the given registry object. 0 - Type of the object 1 - Name of the object.
Action	No action required.

INMPEI0012	**User {0} was assigned to organization groups successfully**
Explanation	The user was assigned to organization groups successfully. 0 - Name of the user.
Action	No action required.

INMPEI0014	**Organization {0} has Administrator**
Explanation	The given organization has an administrator assigned to it. 0 - Name of the organization.
Action	No action required.

INMPEI0015	**{0} {1} is classified by taxonomy {2}**
Explanation	The given registry object is validated to be classified by the given taxonomy. 0 - Type name of the object 1 - Registry object name 2 - Taxonomy node name.
Action	No action required.

INMPEI0017	**Default Roles, Permissions and Groups created successfully for Organization {0}**
Explanation	Default roles, permissions and groups were created successfully for the given organization. 0 - Name of the organization.
Action	No action required.

INMPEI0018	**Default Roles, Permissions and Groups deleted successfully for Organization {0}**
Explanation	Default roles, permissions and groups were deleted successfully for the given organization. 0 - Name of the organization.
Action	No action required.

INMPEI0019	**Adding {0} privilege for {1} {2} on {3} {4}**
Explanation	The chosen privilege on the given registry object was successfully added for the particular user/group. 0 - View/Modify 1 - User/Group 2 - Name of the user/group 3 - Type of the registry object 4 - Name of the registry object.
Action	No action required.

INMPEI0022 **Default roles, groups, permissions and SDL for organization {0} created successfully**

Explanation Default roles, groups, permissions and SDL were created successfully for the given organization. 0 - Name of the organization.

Action No action required.

INMPEI0023 **Default roles, groups, permissions for organization {0} removed successfully**

Explanation Default roles, permissions and groups were removed successfully for the given organization. 0 - Name of the organization.

Action No action required.

INMPEI0024 **User creation policy for User {0} was successful**

Explanation The user was successfully added to the default groups of the organization to which the user belongs. 0 - Name of the user.

Action No action required.

INMPEI0025 **Request Approval Flow {0} for {1} created successfully**

Explanation Request approval flow with the specified name was created successfully for the object. 0 - Approval Flow Name 1 - Name of the object for which approval is triggered.

Action No action required.

INMPEI0026 **Default instance level permissions for Asset {0} were assigned successfully**

Explanation Default instance level permissions were successfully assigned for the given asset. 0 - Name of the asset.

Action No action required.

INMPEI0027 **Email with subject {0} successfully sent to {1}**

Explanation An email with the given subject was successfully sent to the recipients. 0 - Subject of the sent email 1 - email address of the recipient(s).

Action No action required.

INMPEI0029 **Service WSDL size {0} conforms with the specified size {1}**

Explanation The service WSDL size validated against the size specified by the policy. 0 - WSDL size of the service 1 - WSDL size specified in the policy.

Action No action required.

INMPEI0032	**{0} name {1} conforms with the pattern {2}**
Explanation	The registry object name matches the specified pattern. 0 - Type of the registry object 1 - Name of the registry object 2 - Name pattern specified in the policy.
Action	No action required.

INMPEI0033	**Default instance level permissions for Group {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given group. 0 - Name of the group.
Action	No action required.

INMPEI0034	**Default instance level permissions for Lifecycle Model {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given lifecycle model. 0 - Name of the lifecycle model.
Action	No action required.

INMPEI0035	**Default instance level permissions for Policy {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given policy. 0 - Name of the policy.
Action	No action required.

INMPEI0036	**Default instance level permissions for Report Template {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given report template. 0 - Name of the report template.
Action	No action required.

INMPEI0037	**Default instance level permissions for Role {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given role. 0 - Name of the role.
Action	No action required.

INMPEI0038	**Default instance level permissions for Taxonomy {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given taxonomy. 0 - Name of the taxonomy.
Action	No action required.

INMPEI0040	**Service Binding Type(s) conform with the specified bindings {0}**
Explanation	The binding types of the service validated against the specified bindings. 0 - Binding types specified by the policy.
Action	No action required.

INMPEI0041	**Default instance level permissions for User {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given user 0 - Name of the User
Action	No action required

INMPEI0042	**Default instance level permissions for Policy Action {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given policy action. 0 - Name of the policy action.
Action	No action required.

INMPEI0050	**{0} {1} successfully classified by specified taxonomies {2}**
Explanation	The given registry object has been classified with the specified taxonomy nodes. 0 - Type name of the registry object 1 - Name of the registry object 2 - Name(s) of the taxonomy nodes.
Action	No action required.

INMPEI0051	**{0} {1} successfully unclassified from specified taxonomies {2}**
Explanation	The given registry object has been unclassified from the specified taxonomies. 0 - Type name of the registry object 1 - Name of the registry object 2 - Name(s) of the taxonomies.
Action	No action required.

INMPEI0053	**{0} description {1} conforms with the pattern {2}**
Explanation	The registry object description validated with the specified pattern. 0 - Type of the registry object 1 - Description of the registry object 2 - Description pattern specified in the policy.
Action	No action required.

INMPEI0054 **{0} {1} was triggered to change to initial state {2}**

Explanation The registry object has been triggered to change to initial state of the corresponding lifecycle model. 0 - Type name of the object 1 - Name of the registry object 2 - Name of the initial state of the corresponding lifecycle model.

Action No action required.

INMPEI0055 **Object type of {0} - {1} is not LCM-enabled**

Explanation The type of the registry object is not lifecycle-enabled. 0 - Name of the object 1 - Type name of the object.

Action No action required.

INMPEI0056 **{0} {1} was triggered to change activation to {2}**

Explanation The registry object has been triggered to change activation to Active/Inactive. 0 - Type name of the object 1 - Name of the object 2 - Change activation to Active/Inactive.

Action No action required.

INMPEI0058 **{0} {1} belongs to state {2} which conforms to the allowed states {3}**

Explanation The lifecycle state of the registry object is validated against the allowed states specified in the policy. 0 - Type name of the registry object 1 - Name of the registry object 2 - Current state name of the registry object 3 - Allowed states specified in the policy.

Action No action required.

INMPEI0060 **State change to {0} is not applicable for {1} {2}**

Explanation The state change to the specified state is not applicable for the given object. 0 - Change to state name specified in the policy 1 - Type of the registry object 2 - Name of the registry object.

Action No action required.

INMPEI0061 **State change to {0} is initiated for {1} {2}**

Explanation The state change to the specified state has been initiated for the given object. 0 - Change to state name specified in the policy 1 - Type of the registry object 2 - Name of the registry object.

Action No action required.

INMPEI0062	**{0} {1} cannot be applied role groups policy**
Explanation	Role groups policy can be applied only to user objects. 0 - Type of the registry object 1 - Name of the registry object.
Action	No action required

INMPEI0063	**User {0} was added or removed from group {1}**
Explanation	The given user was added or removed from the specified group. 0 - Name of the user 1 - Name of the group where the user was added or removed.
Action	No action required.

INMPEI0065	**{0} {1} has value {2} set for attribute {3} which conforms to the allowed values {4}**
Explanation	For the specified attribute of the given registry object, a value has been set which conforms to the allowed values. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute value of the registry object 3 - Attribute name specified in the policy 4 - Allowed attribute values specified in the policy.
Action	No action required.

INMPEI0067	**Attribute {2} of {0} {1} was set to value {3}**
Explanation	The specified attribute of the registry object was set to the specified value. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute name specified in the policy 3 - Attribute value specified in the policy.
Action	No action required

INMPEI0068	**LC Model {0}'s enabled object type instances were initiated into initial state {1}**
Explanation	The instances of the object types which are LCM enabled by the given LC Model have been triggered to change to the initial state of the LC Model. 0 - Name of the LC Model 1 - Name of the initial state of the LC Model.
Action	No action required

INMPEI0076	**Default instance level permissions for Target {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given target. 0 - Name of the target
Action	No action required.

INMPEI0077	**Default instance level permissions for Lifecycle State {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given lifecycle state. 0 - Name of the lifecycle state.
Action	No action required.

INMPEI0078	**Default instance level permissions for Asset Type {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given asset type. 0 - Name of the asset type.
Action	No action required.

INMPEI0079	**Default instance level permissions for Taxonomy {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given taxonomy. 0 - Name of the taxonomy.
Action	No action required.

INMPEI0080	**Default instance level permissions for Event Type {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given event type. 0 - Name of the event type
Action	No action required.

INMPEI0081	**Default instance level permissions for Profile {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given profile. 0 - Name of the profile
Action	No action required.

INMPEI0082	**Default instance level permissions for UDDI Subscription {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given UDDI subscription. 0 - Name of the UDDI subscription
Action	No action required.

INMPEI0083	**Default instance level permissions for Federation {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given federation. 0 - Name of the federation.
Action	No action required.

INMPEI0084	**Default instance level permissions for Concept {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given concept. 0 - Name of the concept.
Action	No action required.

INMPEI0085	**Taxonomy {0} instance level permissions were assigned successfully to its child objects**
Explanation	The instance level permissions of the taxonomy were successfully assigned to its children concepts. 0 - Name of the taxonomy.
Action	No action required.

INMPEI0086	**Policy {0} instance level permissions were assigned successfully to its child objects**
Explanation	Policy has child objects like Policy Condition and Policy Parameter. When we assign the instance level permission to a Policy, the permission should be assigned also to its child objects. The message states that this action was performed successfully.
Action	No action required.

INMPEI0088	**User {0} is not active**
Explanation	The user is not active and hence can be deleted. 0 - Name of the user.
Action	No action required.

INMPEI0095	**Pending state transition was terminated by CSA**
Explanation	The CentraSite administrator has terminated the pending state transition on the registry object.
Action	No action required.

INMPEI0103	**Organization Primary Contact is an active user**
Explanation	The primary contact of the organization is an active user and hence the validation for updating the organization is successful.
Action	No action required.

INMPEI0119	**Default instance level permissions for ConsumerRegistrationRequest {0} were assigned successfully**
Explanation	Default instance level permissions for the consumer registration request were assigned successfully. 0 – Name of the consumer registration request.
Action	No action required.

INMPEI0134	**Default instance level permissions for ExternalLink {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given external link. 0 - Name of the external link.
Action	No action required.

INMPEI0135	**Default instance level permissions for ExtrinsicObject {0} were assigned successfully**
Explanation	Default instance level permissions were successfully assigned for the given extrinsic object. 0 - Name of the extrinsic object.
Action	No action required.

INMPEI0137	**Collector was successfully executed for {0} {1}**
Explanation	The collector policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
Action	No action required.

INMPEI0138	**Default delete handler was successfully executed for {0} {1}**
Explanation	The default delete handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
Action	No action required.

INMPEI0140	**WSDL regeneration skipped for Service {0} since the service is not a VirtualService, VirtualXMLService or VirtualRESTService**
Explanation	WSDL regeneration can be performed only for a virtual service, virtual XML service or virtual REST service.
Action	Make sure the asset is a virtual service, virtual XML service or virtual REST service.

INMPEI0141	**{0} {1} moved successfully**
Explanation	The registry object has been moved successfully to the new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
Action	No action required.

INMPEI0147	**Registry Object {0} has been validated successfully against its mandatory attributes of type Classification, File and Relationship**
Explanation	All the mandatory classification, file and relationship attributes for the given registry object have been populated. 0 - Name of the registry object.
Action	No action required.

INMPEI0155	**Profile permissions for {0} {1} were assigned successfully**
Explanation	The profile level permissions for the given registry object were successfully assigned.
Action	No action required.

INMPEI0158	**Organization export handler was successfully executed for {0}**
Explanation	The organization export handler was executed successfully for the given organization.
Action	No action required.

INMPEI0159	**Taxonomy/Concept export handler was successfully executed for {0} {1}**
Explanation	The Taxonomy/Concept export handler was executed successfully for the given object.
Action	No action required.

INMPEI0160	**Default export handler was successfully executed for {0} {1}**
Explanation	The default export handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
Action	No action required.

INMPEI0161	**Asset type export handler was successfully executed for {0} {1}**
Explanation	The asset type export handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
Action	No action required.

INMPEI0164	**Metrics does not contain serviceKey hence will not be saved in Runtime Metrics Collection**
Explanation	Metrics must be saved against a service. But the user is trying to save a metrics object without classifying it with a proper service key. This metrics will be discarded.
Action	Please classify the metrics objects with the classificationScheme “uddi:centrasite.com:management:service.key”. The value of the classification must be the key of the service to which the metrics belongs.

INMPEI0168	**The required permissions are already available for {0} {1}**
Explanation	The permissions to be set by the policy are already available in the registry object. 0 - Type of the registry object 1 - Name of the registry object.
Action	No action required.

INMPEI0169	**Request Approval Flow {0} for {1} was automatically approved**
Explanation	The approval flow for the registry object was automatically approved since the triggering user is part of the approver group.
Action	No action required.

INMPEI0170	**CentraSite does not contain an object of type {0} and with name {1}**
Explanation	The policy executed successfully, since CentraSite does not contain an object of the specified type and with specified name.
Action	No action required.

INMPEI0171	**CentraSite already contains an object of type {0} and with name {1}**
Explanation	This policy enforces uniqueness in names of the object. As the user tried to create an object using a name which already exists in CentraSite, this policy failed.
Action	Please use a different name

INMPEI0173	**Notified Webservice endpoint {0} hosted in application server {1} successfully.**
Explanation	A Webservice request has been published to the endpoint successfully.
Action	No action required.

INMPEI0174	**Failed to notify Webservice endpoint {0} hosted in application server {1}: Error Message {2}**
Explanation	The Webservice request could not be published to the specified endpoint.
Action	Provide a valid webservice endpoint which can accept the SOAP message configured in the notify policy.

INMPEI0177	**{0} {1} has kept the current LCM state**
Explanation	The LCM state has been retained during the import.
Action	No action required.

INMPEI0178	**Successfully deleted the rest service of IS Service Interface '{0}'**
Explanation	Rest service deletion has completed successfully while retracting the IS Service Interface from the Designer.
Action	No action required.

INMPEI0179	**Failed to delete the rest service '{0}' ({1}) used by IS Service Interface '{2}'**
Explanation	The deletion of the Rest Service failed while retracting the IS Service Interface from the Designer.
Action	No action required.

INMPEI0182	**IS Service Interface {0} object has been transformed successfully into REST service {1}.**
Explanation	The IS Service Interface object has been transformed successfully into a REST service in CentraSite.
Action	No action required.

INMPEI0183	**The given object {0} does not contain the state**
Explanation	The given object 0 does not contain the state.
Action	No action required.

INMPEI0186	**Target Group not applicable for the operation**
Explanation	The target group is not applicable for the operation.
Action	No action required.

INMPEI0187	**Target Group created for the Target**
Explanation	The target group was created for the target.
Action	No action required.

INMPEI0188	**Target Group not created for the Target**
Explanation	The target group was not created for the target.
Action	No action required.

INMPEI0189	**{0} {1} promoted successfully**
Explanation	The registry object has been promoted successfully to the specified target stage. 0 - Type of the registry object 1 - Name of the registry object.
Action	No action required.

INMPEI0191	**Not updating Consumer WSDL for VirtualService {0} as it does not contain WSDL or Consumer WSDL is already contains the proper WSDL file.**
Explanation	The Consumer WSDL attribute will not get updated if the Virtual Service does not have WSDL associated with it. Also the attribute will get updated if it contains the proper value in it.
Action	No Action Required, as this policy get triggered when WSDL is attached to the Virtual Service

INMPEI0193	**Consumer WSDL attribute is populated with proper WSDL**
Explanation	Policy Action successfully executed by populated the Consumer WSDL attribute with proper WSDL
Action	No action required

INMPEI0194	**Not updating Consumer WSDL for {0} since it is not a Service**
Explanation	Consumer WSDL attribute is applicable only for Virtual Service and hence it can't be updated for other objects
Action	Please make sure applicable object for "Consumer WSDL Generator" policy is set only to Virtual Service

INMPEI0201	**,**
Explanation	This is a user display name separator.
Action	No action required.

INMPEI0202	**{0} {1} {2}**
Explanation	This is a user display name.
Action	No action required.

INMPEI0203	**Ownership of {0} {1} was changed successfully to user {2}**
Explanation	The ownership of the given asset was changed successfully to the specified user. 0 - Type of the object; 1 - Name of the object; 2 - New owner of the object.
Action	No action required.

INMPEI0205	**{0} of type {1} has been validated for all mandatory Slot, Classification, File and Relationship attribute types.**
Explanation	The "required" attributes of the registry object {0} of type {1} have been identified and all such "required" attributes have been provided with values.
Action	No action required.

INMPEI0207	**The API Key is deployed successfully to target {0}**
Explanation	The specified API key was successfully deployed to the specified target.
Action	No action required.

INMPEI0208	**A new API Key is generated.**
Explanation	A new API key has been generated.
Action	No action required.

INMPEI0209	**Onboarded user {0} proceeds with consume API request for {1}**
Explanation	The onboarding of the user was successful, and the consume API request for the API has been triggered.
Action	User registration completion information will be sent as an email.

INMPEI0213	**Onboarding User {0} in Organization {1} is successful**
Explanation	Onboarding of the user in API Management solution was successful.
Action	The Consume API request will be generated automatically for the onboarded user.

INMPEI0214	**Onboarding Organization {0} with Administrator User {1} is successful**
Explanation	Onboarding of the given Organization with the given User in API Management solution was successful.
Action	The Consume API request will be generated automatically for the the onboarded administrator user.

INMPEI0215	**Congratulations from API management team**
Explanation	Email subject for successful onboarding of user.
Action	No action.

INMPEI0216	**API key deleted successfully from target {0}.**
Explanation	The API key is deleted successfully from the target {0}.
Action	None. Informational only.

INMPEI0220	**WSDL regeneration skipped for virtual service {0} as WSDL related objects are not modified.**
Explanation	WSDL regeneration is needed only if JAXR binding is updated, else WSDL update not required. CentraSite updates it only if it really required.
Action	No action required.

INMPEI0221	**API key has been renewed successfully.**
Explanation	API key has been renewed successfully.
Action	No action required

INMPEI0232	**OAuth2 Client is revoked successfully.**
Explanation	The OAuth2 Client was revoked successfully.
Action	No action required.

INMPEI0235	**Swagger2.0 file is generated successfully for the API {0}.**

INMPEW0028	**WSDL URL is empty for {0}**
Explanation	The service WSDL URL is empty. 0 - Name of the service.
Action	Please ensure that the service has a WSDL URL.

INMPEW0172	**Could not send notification to application server as it is not configured with APG_SERVICE_ENDPOINT**
Explanation	The notification will be send only if the application server is configured with APG_SERVICE_ENDPOINT in the object specific property.
Action	Configure a valid webservice endpoint to the application server which is associated to the registry object.

INMPEW0192	**Consumer WSDL attribute is not found Virtual Service type**
Explanation	This policy action will update the Consumer WSDL attribute with WSDL which may contain WS Policy in it. So this policy action requires Consumer WSDL attribute
Action	Please make sure Consumer WSDL file attribute exists for Service type

INMPEW0217	**Failed to delete API key from target {0} .**
Explanation	The specified API key could not be deleted from the target {0}. This problem can occur because the requestor does not have the required permisison to delete API key.
Action	Only a user with Administrator role can delete API key from targets.

INMPEW0219	**You can revoke an access token only once.**
Explanation	The access token is revoked twice.
Action	Revoke an access token only once.

INMPEW0233	**Failed to revoke OAuth2 Client from Mediator.**
Explanation	Could not revoke the OAuth2 Client from the specified Mediator. There could be multiple reasons why this might have occurred: (1) Integration Server on which Mediator is running is down or inaccessible (2) invalid user credentials (3) application error on the Integration Server.
Action	Make sure the Integration Server on which Mediator is up and running, and the user credentials are correct.

INMPUE0003	**Action category and action template types are mismatched**
Explanation	For a design time/ change time category, the action template type should be programmatic. If the action template type does not match the design time/ change time category, this causes an error.
Action	Ensure that the action category and action template types are matched.

INMPUE0006	**Action template name already exists**
Explanation	An action template name should be unique across the system, otherwise this will create confusion for the user. So this error occurs if a user tries to create an action template with a name that is already in use.
Action	Use a different action template name.

INMPUE0015	**WS-I actions cannot be combined with other actions**
Explanation	While creating a policy, WS-I actions should not be combined with other actions. If a user tries to do so, this problem will happen.
Action	WS-I actions cannot be combined with other actions.

INMPUE0020	**Reordering multiple actions is not allowed**
Explanation	While assigning actions to the policy, a user can re-order the actions. If the user tries to re-order multiple actions at a time, this error will be thrown.
Action	Reordering multiple actions is not allowed.

INMPUE0028	**Select an action to move**
Explanation	If a user tries to re-order the actions without selecting anything, this error will be thrown. For this the user has to first select any action and then do the re-ordering.
Action	Select an action to move.

INMPUE0029	**Action category with name {0} already available**
Explanation	Action category names are unique across the system. If a user tries to create an action category with a name that exists already, this error will be thrown.
Action	Enter a valid action category name.

INMPUE0030	**Provide the URL of ZIP file**
Explanation	When creating an action template with the selected rule type of Java, the user has to provide a valid zip file, otherwise this error will be thrown.
Action	Enter the URL of the ZIP file.

INMPUE0032	**Set Profile Permission action cannot be applied to multiple object types**
Explanation	If the policy applies to multiple object types, then the set profile permission action cannot be applied
Action	Change the object types or create a new policy with a single object type

INMPUE0033	**Provide the correct Attribute Values**
Explanation	The attribute value provided is incorrect for the chosen type.
Action	Provide the correct attribute value for the chosen type.

INMPUE0034	**You must specify a value for Attribute Name**
Explanation	The required value forthe duration attribute name is missing.
Action	Supply a correct value for the duration attribute name.

INMRAE0001	**Cannot obtain {0} from closed Resource Access Manager.**
Explanation	The Resource Access Manager is closed and thus not yet initialized.
Action	Make sure that the Resource Access Manager is opened before using it.

INMRAE0002	**No configuration set.**
Explanation	No configuration info set was found.
Action	Please provide a configuration info set. Refer to the Resource Access javadoc for additional information.

INMRAE0003	**No valid credentials found.**
Explanation	No valid credentials were found.
Action	Please provide valid credentials.

INMRAE0004	**Found {0} while expecting instance of XmlServerRoleManager.**
Explanation	Failed authentication against CentraSite server or absence of XmlServerLoginModule from security configuration.
Action	Check logs and security configuration.

INMRAE0005	**SagRoleManagementPrincipal instance not available for the authenticated subject.**
Explanation	The SagRoleManagementPrincipal security artefact is missing.
Action	Check the security configuration.

INMRAE0006	**Authenticated Subject cannot be null.**
Explanation	After successful authentication, the Subject instance was not found.
Action	Contact your software supplier.

INMRAE0007	**No representation of the Group to be associated in external user repository.**
Explanation	The external group, to be associated with a local group, is no longer present in the external repository.
Action	External user repositories are managed outside of CentraSite.

INMRAE0008	**Error during System level permission copy.**
Explanation	Error during System level permission copy.
Action	Contact your software supplier.

INMRAE0009	**An organization must be set.**
Explanation	A permission has to belong to an organization.
Action	Assign an organization to the permission instance.

INMRAE0010	**Organization level permission needs to have a corresponding system level permission.**
Explanation	An organization level permission needs to have a corresponding system level permission.
Action	Assign the system level permission to the organization level permission instance.

INMRAE0011	**A Role needs to belong to an Organization.**
Explanation	A role needs to belong to an organization.
Action	Assign an organization to the role instance.

INMRAE0012	**The user does not have a working Organization set.**
Explanation	The user does not have a working organization set.
Action	Set the working organization of the user.

INMRAE0013	**Roles can be assigned only to registered users.**
Explanation	Roles can be assigned only to registered users associated with an external user repository.
Action	Register a user instance to CentraSite.

INMRAE0014	**Unsupported collection type.**
Explanation	The passed collection is of an unsupported type.
Action	The collection expected is a list-backed one.

INMRAE0015	**Got {0} while expecting {1}**
Explanation	Passed in Registry Object instance is not of group type.
Action	Make sure that passed in Registry Object instance is of group type.

INMRAE0016	**Cannot obtain external user repository type.**
Explanation	Cannot retrieve the currently effective external user repository type.
Action	Check the security configuration.

INMRAE0017	**Unsupported external user repository type {0}.**
Explanation	The currently effective external user repository type is unknown.
Action	Check the security configuration.

INMRAE0018	**Currently effective external user repository type {0} does not support custom predicate.**
Explanation	Currently effective external user repository type does not support custom predicate.
Action	Use predicates instead.

INMRAE0019	**Currently effective external user repository type {0} does not support predicates.**
Explanation	Currently effective external user repository type does not support predicates.
Action	Use custom predicate instead.

INMRAE0020	**SagUserPrincipal instance not available for the authenticated subject.**
Explanation	The SagUserPrincipal security artefact is missing. It is possible that authentication against the external user repository is not performed, for example internal user accounts such as the Guest user account.
Action	Check the security configuration.

INMRAE0021	**PersonName must be added**
Explanation	A user instance must have PersonName.
Action	When creating a User object, the first name, middle name and last name of the user object need to be provided.

INMSOE0001	**HTTP Routing Protocol not enabled**
Explanation	During configuration of routing protocol, if any of the routing types are StraightThrough/LoadBalance/ContentBased/ContextBased routing, then the transport of the routing should be HTTP enabled.
Action	Enable the HTTP transport for routing protocol.

INMSOE0002	**JMS Routing Protocol not enabled**
Explanation	During configuration of the routing protocol, if the routing type is JMS routing, then the transport of the routing should be JMS enabled.
Action	Enable the JMS transport for routing protocol.

INMSOE0007	**TargetType definition file missing**
Explanation	The input JAR file provided does not contain the relevant TargetType definition XML.
Action	Add the relevant TargetType definition XML to the input JAR file.

INMSOE0008	**Transformation definition file missing**
Explanation	The input JAR file provided does not contain the relevant transformation file.
Action	Add the relevant transformation file to the input JAR file.

INMSOE0010	**Target Type name should not be empty**
Explanation	The input JAR file provided does not contain the target type name in the Target Type Definition file.
Action	Provide the Target Type name.

INMSOE0011	**Event Type definition file missing**
Explanation	The input JAR file provided does not contain the relevant Event Type definition.
Action	Add the relevant Event Type definition to the input JAR file.

INMSOE0012	**Target Type name already exists**
Explanation	The Target Type already exists with the provided name in Target Type definition file.
Action	Change the Target Type name.

INMSOE0013	**Service WSDL does not contain the WSDL Service Element**
Explanation	The imported WSDL does not contain the service element.
Action	Make sure service element is present in the service WSDL.

INMSOE0015	**Service WSDL is mandatory for deployment operations**
Explanation	The WSDL is not present for the created virtual service.
Action	Make sure the created virtual service contains the WSDL.

INMSOE0016	**Deployment activity {0} is the current activity log for {1} {2}**
Explanation	An activity log which is the latest deployment log for a deployed asset cannot be deleted.
Action	Unselect the particular deployment log from the deployment history before deleting other old entries.

INMSOE0019	**The consumer application defined in the routing rule of the asset is no longer available in CentraSite. Specify a valid consumer application in the routing rule.**
Explanation	The consumer application used as part of the context based routing condition of the asset to be deployed is not available in the CentraSite Repository.
Action	Provide a valid consumer application in the routing rule.

INMSOE0020	**Data type mismatch during attribute mapping for RuntimeEventType: {0}. Expected data type for attribute {1} is {2}, while the supplied data type is {3}.**
Explanation	This exception is thrown when a data type mismatch is encountered when mapping SNMP Trap attributes from EventType.xml to RuntimeEventType attributes.
Action	Ensure the data type matches.

INMSOE0021	**Entry protocol not defined for asset {0}**
Explanation	The inbound transport information is not defined for the asset to be deployed to the Mediator.
Action	Configure the entry protocol in the processing steps profile of the asset to be deployed.

INMSOE0022	**WSDL not found for native service**
Explanation	A WSDL is not available for the native service to be virtualized.
Action	Attach the WSDL for the native service to be virtualized.

INMSOE0023	**Cannot virtualized this WebService since the service does not contain any wsdl:bindings**
Explanation	Service must contain at least one service binding, otherwise it cannot be virtualized
Action	Getting error while virtualizing the service without service binding

INMSOE0027	**TrapOID (Object Identifier) {0} is duplicated in the EventType.xml inside the provided Target Type definition jar file**
Explanation	During target type creation, if the SNMP Trap OID is duplicated in EventType.xml, this exception is thrown.
Action	SNMP Trap OIDs should be unique within and across target types.

INMSOE0028	**TrapOID {0} already defined in existing Target Type {1}**
Explanation	During target type creation, if the SNMP Trap OID is already present in an existing target type, this exception is thrown.
Action	SNMP Trap OIDs should be unique within and across target types.

INMSOE0031	**Scoped Virtual Service deployment will not be triggered since dependent assertion {0} does not exist**
Explanation	Scoped Virtual Service deployment will not be triggered since some of the dependent assertions are missing in the Runtime Policy.
Action	Ensure dependent assertions exist.

INMSOE0033	**Scoped Virtual Service deployment will not be triggered since dependent assertion {0} does not exist**
Explanation	Virtual Service will have policies associated with it. These policies may be dependent on other policies. If the dependent policies are not applied for the virtual service, this exception will arise.
Action	Please create the dependent runtime policy and make sure it is applicable for the virtual service to be deployed.

INMSOE0036	**Error in API Key Creation**
Explanation	An error occurred while creating an API Key instance.
Action	Check if there are any related messages in the log to determine the cause of the problem.

INMSOE0037	**Mandatory parameters are not present for creation of API Key instance**
Explanation	Mandatory parameters were not provided while creating API Key object
Action	Provide the mandatory parameters.

INMSOE0039	**Invalid parameter {0} is selected which is not supported in the version of Mediator installed**
Explanation	The version of mediator to which the asset is being deployed does not support the parameter {0}.
Action	Change the parameter to one that is supported in the mediator version installed.

INMSOE0041	**Error occurred during creation of OAuth2 Client asset**
Explanation	An error was encountered while creating the OAuth2 Client asset.
Action	Check if there are any related messages in the log to determine the cause of the problem.

INMSOE0042	**Mandatory parameters are missing for creation of OAuth2 client instance**
Explanation	Mandatory parameters were missing while creating OAuth2 client object.
Action	Check if the mandatory parameters 'Service' and 'Consumer' are missing.

INMSOE0043	**Cannot enforce evaluate actions ApiKey and OAuth2 for the service.**
Explanation	When both API Keys and OAuth2 are enforced for an API in AND condition, this exception is thrown.
Action	Change the enforce condition to OR.

INMSOE0044	**Deployment of the Virtual Service failed. Check the Integration Server log.**
Explanation	The deployment of the Virtual Service has failed.
Action	Check the Integration Server log.

INMSOE0045Error	**You might not be authorized to view the runtime alias type**
Explanation	Alias Key Name Map is not initialized.
Action	Check if you have permission to use the alias type.

INMSOE0049Error	**Default value not specified for the runtime alias. CentraSite cannot save the alias.**
Explanation	CentraSite cannot save the runtime alias because the default value for the alias is not specified.
Action	Retry after you specify a default value for the runtime alias.

INMSOE0050Error	**Required values are missing for runtime target: {0} for alias {1}**
Explanation	An error occurred while trying to associate a target to a runtime alias, possibly because some of the required values are missing.
Action	Provide target-specific values for the runtime alias, and try again.

INMSOE0053Error	**CentraSite does not support alias deployment for runtime target Mediator version {0}. Runtime alias deployment is supported only for Mediator version {1} and above.**
Explanation	CentraSite cannot deploy runtime aliases because they are not support in the Mediator version installed.
Action	If you would like to create and deploy runtime aliases, upgrade to Mediator 9.7

INMSOE0054	**Alias with name {0} already exists. Provide a different name.**
Explanation	CentraSite cannot have aliases with same name as this will have issues when it is deployed to the same Mediator.
Action	Provide a different name for alias and save it.

INMSOE0055Error	**Runtime alias is already deployed to target(s). You must disassociate the alias from the services and undeploy it before you change the alias name.**
Explanation	You are trying to change the alias name of a runtime alias that is already deployed to its target(s).
Action	Disassociate the alias from the services and undeploy it before you change the alias name.

INMSOE0056Error	**Runtime alias not found. Alias name: {0}**
Explanation	You are trying to use a runtime alias that is not defined in CentraSite.
Action	Check if the alias is defined in CentraSite or use an alias that is already defined.

INMSOE0057Error	**The authentication type in the secure alias does not match the authentication type in the virtual service. Secure alias: {0}, virtual service: {1}. Check the authentication type of the secure alias that you published and change it to match the authentication type used in the virtual service**
Explanation	The authentication type specified in the secure alias does not match with the outbound authentication policy specified in CentraSite.
Action	Check the authentication type of the secure alias that you published and change it to match the authentication type used in the virtual service.

INMSOE0058	**Target does not support deployment of REST services with more than one resource and/or tokenized routing endpoints.**
Explanation	Older Mediators before version 9.7 do not support more than one REST resource and tokenized routing endpoints.
Action	Make sure that you deploy to a newer version of Mediator.

INMSOE0059	**Invalid deployment endpoint.**
Explanation	The deployment endpoint is not valid.
Action	Provide a valid deployment endpoint.

INMSOE0061	**HTTP protocol is not supported for Kerberos. Select HTTPS protocol only.**
Explanation	HTTP protocol is not supported for Kerberos. Only, HTTPS protocol is supported.
Action	Select HTTPS protocol only during virtualization.

INMSOE0062	**The Custom Error Variable name field must not be empty.**
Explanation	You have not entered a name while adding a Custom Error Variable in the Conditional Error Processing step.
Action	Enter a name for the Custom Error Variable.

INMSOE0063	**The Custom Error Variable Xpath expression cannot be empty.**
Explanation	You have not entered an Xpath expression while adding Custom Error Variable in the Conditional Error Processing step.
Action	Provide an Xpath expression for the Custom Error Variable.

INMSOE0064	**Gateway with version {0} does not support OData services.**
Explanation	The gateway is too old for deploying OData services.
Action	Use a newer gateway (>= 9.10)

INMSOE0065	**Service {0} is not of supported type for {1}.**
Explanation	The service is not supported for the give action. This is an internal problem.
Action	Check the type of service.

INMSOE0066	**VSD cannot be generated for virtual service {0}.**
Explanation	The VSD document of a virtual service cannot be generated due to internal problems.
Action	Check the details of the virtual service.

INMSOE0067	**Gateway with version {0} does not support the HTTP PATCH method for REST service {1}.**
Explanation	The deployed REST service exposes the HTTP PATCH method, which is not supported by this version of Mediator.
Action	Deploy the REST service with HTTP PATCH method to a newer version of Mediator.

INMSOE0068	**The REST service {0} uses the HTTP PATCH method, however the deployment mode is not set to "axis-free".**
Explanation	The REST service {0} uses the HTTP PATCH method, however the deployment mode is not set to "axis-free". This is becasue only the axis-free deployment mode supports the PATCH method.
Action	Check if you can activate the axis-free deployment mode in centrasite.xml.

INMSOE0069	**Incompatible gateway types.**
Explanation	The gateway types of the CentraSite registry object and the running instance are not the same type.
Action	Check your running target and the CentraSite gateway object.

INMSOE0070	**REST service deployment to API Gateway requires "axis-free" setting.**
Explanation	REST service deployment to API Gateway is only supported if the CentraSite deployment mode was set to axis-free.
Action	Configure the axis-free mode in CentraSite.

INMSOE0071	**Could not publish the virtual service because the associated {0} {1} has no valid credentials.**
Explanation	An error occurred while trying to publish the runtime alias, possibly because the associated {0} {1} has no valid credentials.
Action	Specify a valid username and password for the runtime alias, and try again

INMSOE0072	**Failed to connect to deployment endpoint. {0}.**
Explanation	An error occurred while trying to connect to the deployment endpoint of a target. There could be multiple reasons why this might have occurred: (1) target deployment endpoint is down or inaccessible (2) invalid user credentials.
Action	Make sure the target deployment endpoint is up and running, and the user credentials are correct.

INMSOE0073	**Gateway not active or accessible.**
Explanation	The selected gateway is not active or accessible.
Action	Check the accessibility of gateway.

INMSOE0074	**Invalid credentials**
Explanation	Invalid username or password specified for accessing the gateway.
Action	Check the username and passord for accessing the gateway.

INMSOE0075	**Unknown host: {0}**
Explanation	The host to be accessed is unknown.
Action	Check if the host is accessible.

INMSOE0077	**Deployment timout value of {0} seconds exceeded**
Explanation	The timeout value of a deployment request to a gateway has been exceeded
Action	Configure a greater timeout value or specify one with a CentraSiteCommand option

INMSOI0017	**Connection to deployment endpoint failed**
Explanation	This occurs if no connection can be established to the deployment endpoint defined in a target during deployment/undeployment/syncconsumers operations. This could be because the deployment endpoint is down or the credentials used for accessing the deployment endpoint are wrong.
Action	Check if the deployment endpoint is up and running. Also check if the credentials defined in the target for accessing the deployment endpoint are correct.

INMSOI0035	**API Key for {0} of {1}**
Explanation	This is how the name of the API key will be generated where the service name is passed as a parameter.
Action	No action required.

INMSOI0040	**OAuth2 Client for {0} of {1}**
Explanation	This is how the name of the OAuth2 Client is created when the service name and consumer name are passed as parameters.
Action	No action required.

INMSOW0034	**The parameter(s)/action(s) {0} were ignored as it is not supported by Mediator {1}**
Explanation	Virtual Service can be deployed from latest version of CentraSite to Mediator version 8.2.2 and above. If you deploy any service to older version of Mediator from latest version of CentraSite, some policy parameters or actions cannot be executed on older version of Mediator. Such policy parameters or actions will be ignored. This warning message will list those ignored parameter/actions.
Action	If the ignored parameters or actions need to be executed, then Mediator has to be upgraded to version in which CentraSite is running. If the ignored parameter or actions are not needed, then this warning message can be ignored.

INMSOW0076	**Service is published to API gateway but activation is denied.**
Explanation	Service was successfully published to API gateway but the service is still in deactivation state.
Action	Log into API Gateway and try to activate the service.

INMSTE0001	**Referenced service does not exist ("{0}")**
Explanation	Internal error.
Action	Please contact your software supplier.

INMSTE0002	**Dangling reference ("{0}")**
Explanation	Internal error.
Action	Please contact your software supplier.

INMSTE0003 **Conflicting state ({0})**

Explanation Internal error.

Action Please contact your software supplier.

INMSTE0004 **Invalid Reference ("{0}")**

Explanation Internal error.

Action Please contact your software supplier.

INMSTE0005 **Type concept is not found in ImportList**

Explanation Internal error.

Action Please contact your software supplier.

INMSTE0006 **No schema definition generated**

Explanation Internal error.

Action Please contact your software supplier.

INMSTE0007 **schemaName for selected concept is null**

Explanation Internal error.

Action Please contact your software supplier.

INMSTE0008 **At least one instance does not comply with the type modifications.**

Explanation A type is being modified in a way that is not compliant with the existing instances of that type.

Action Modify the type in a compliant way.

INMSTE0009 **Type concept not found for "{0}"**

Explanation While updating or deleting a JAXR object type, the corresponding type concept was not found in the registry.

Action This is an internal error. Please contact your software supplier.

INMSUE0001 **Reordering multiple actions is not allowed**

Explanation Reordering multiple actions not allowed.

Action Reordering multiple actions not allowed.

INMSUE0002 **You must select valid jar file**

Explanation The selected jar file(s) are not valid.

Action Select valid jar files.

INMSUE0003 **Enter unique name**

Explanation The event type name already exists.

Action Enter a unique name for the event type

INMSUE0004 **Target name should not be empty**

Explanation An attempt was made to add a target object without a name.

Action Supply a target name.

INMSUE0005 **Target type should not be empty**

Explanation An attempt was made to add a target type object without a name.

Action Supply a target type name.

INMSUE0006 **Policy name cannot be empty**

Explanation An attempt was made to add a policy object without a name.

Action Supply a policy name.

INMSUE0007 **Select an Asset Type for the policy**

Explanation For creating a runtime policy object, the object needs an associated object type.

Action Select an object type for the policy.

INMSUE0008 **Select a target type for the policy**

Explanation The target type for the policy is missing.

Action Select a target type for the policy.

INMSUE0009 **Default route cannot be empty**

Explanation The default route is missing.

Action Define a default route.

INMSUE0010 **XPath expression cannot be empty**

Explanation An empty XPath expression was supplied.

Action Supply an XPath expression.

INMSUE0011 **Enter the valid XPath to the 'Element Required to be Signed'**

Explanation The correct XPath to the 'Element Required to be Signed' is required.

Action Enter the valid XPath to the 'Element Required to be Signed'.

INMSUE0012 **Virtual Service name should not be empty**

Explanation The required name is missing.

Action Supply the name.

INMSUE0013 **Version cannot be empty**

Explanation A version was not entered.

Action Enter a version.

INMSUE0014 **No WSDL Found**

Explanation For the given URL, there is no WSDL available.

Action Supply a WSDL for the URL.

INMSUE0015 **Virtual service with name {0} already exists**

Explanation A virtual service with the given name already exists.

Action Supply a different name for the virtual service.

INMSUE0016 **Assign actions for the policy**

Explanation The actions required for the runtime policy object are missing.

Action Assign actions for the policy.

INMSUE0017 **Create target type before creating runtime policy**

Explanation The target type required for creating the runtime policy is not available.

Action Create the target type before creating the runtime policy.

INMSUE0018 **Create target type before creating target**

Explanation The target type must be created before the target can be created.

Action Create the target type before creating the target.

INMSUE0019 **Select at least one target to deploy**

Explanation No target was selected to deploy.

Action Select at least one target to deploy.

INMSUE0020 **Default route cannot be empty**

Explanation The default route was not specified.

Action Specify a default route

INMSUE0022 **JMS alert destination cannot be empty**

Explanation The JMS alert destination was not specified.

Action Specify the JMS alert destination.

INMSUE0023 **Select at least one consumer application**

Explanation No consumer applications have been selected.

Action Select at least one consumer application.

INMSUE0024 **Rule name already exists**

Explanation The specified rule name already exists.

Action Specify a different rule name.

INMSUE0025 **Endpoint URL cannot be empty**

Explanation An empty endpoint URL was specified.

Action Specify a value for the endpoint URL.

INMSUE0026 **Consumer application cannot be empty**

Explanation The consumer application was not specified.

Action Specify the consumer application.

INMSUE0027 **Invalid hour given**

Explanation The input for hour is invalid.

Action Enter a valid hour.

INMSUE0028 **Invalid minute given**

Explanation The input for minute is invalid.

Action Enter a valid minute.

INMSUE0029 **Date cannot be empty**

Explanation A date was not entered.

Action Enter a date.

INMSUE0030 **Assertion type not found**

Explanation The assertion type was not found.

Action Specify an assertion type.

INMSUE0031 **Virtual service name cannot be same as web service name**

Explanation The virtual service name should not be the same as the web service name.

Action Specify a different virtual service name.

INMSUE0032 **HTTP header value cannot be empty**

Explanation An HTTP header value was not entered.

Action Enter an HTTP header value.

INMSUE0033 **HTTP header name cannot be empty**

Explanation The HTTP header name is empty.

Action Enter an HTTP header name.

INMSUE0034 **JMS message property name cannot be empty**

Explanation The JMS message property name is empty.

Action Enter a JMS message property name.

INMSUE0035 **JMS message property value cannot be empty**

Explanation The JMS message property value is empty.

Action Enter a JMS message property value.

INMSUE0036 **Virtual service name cannot have # character**

Explanation The virtual service name contains the "#" character.

Action Ensure that the name of the virtual service does not contain the "#" character.

INMSUE0037 **JMS header name cannot be empty**

Explanation The JMS header name is empty.

Action Enter the JMS header name.

INMSUE0038 **JMS header value cannot be empty**

Explanation The JMS header value is empty.

Action Enter the JMS header value.

INMSUE0039 **Select a policy to delete**

Explanation No policy has been selected for deletion.

Action Select a policy to delete.

INMSUE0062 **Undeploy the Service(s) before deleting the Target**

Explanation Before deleting the target, undeploy all virtual services from the target.

Action Make sure that the target instance has no deployed virtual services before trying to delete the target.

INMSUE0066 **Virtual XML Service with name {0} already exists**

Explanation A virtual XML service with the given name already exists.

Action Supply a different name for the virtual XML service.

INMSUE0067 **HTTP Methods not declared for the native XML Service**

Explanation HTTP methods required for the XML service being virtualized were not declared.

Action Update the HTTP methods of the native XML service being virtualized.

INMSUE0068 **HTTP Methods are not declared for the XML Service**

Explanation The HTTP methods cannot be empty when creating an XML service.

Action Select any one of the HTTP methods provided to create an XML Service.

INMSUE0069 **Select an HTTP Method for Entry Protocol**

Explanation HTTP Methods for an entry protocol policy of a virtual XML service cannot be empty

Action Select any one of the options available for HTTP Methods for an Entry Protocol policy

INMSUE0070 **Select the data type for predefined context variable**

Explanation The data type for the predefined context variable should be selected.

Action Select either the String or Int data type for the predefined context variable.

INMSUE0071 **Select the name for predefined context variable**

Explanation The context variable name cannot be empty.

Action Select any of the available context variable names.

INMSUE0072 **Enter the value for predefined context variable**

Explanation The context variable value cannot be empty.

Action Enter the value of the selected context variable.

INMSUE0073 **Select the data type for custom context variable**

Explanation The data type for the selected custom context variable is invalid.

Action Select the data type of the custom context variable.

INMSUE0074 **Enter the name for custom context variable**

Explanation The name of the custom context variable cannot be empty.

Action Enter the custom context variable name.

INMSUE0075 **Enter the value for custom context variable**

Explanation The value for the custom context variable cannot be empty.

Action Enter the value for the custom context variable.

INMSUE0076	**Virtual REST Service with name {0} already exists**
Explanation	A virtual REST service with the given name already exists.
Action	Supply a different name for the virtual REST service.

INMSUE0077	**Select at least one asset to deploy**
Explanation	There are no assets selected for deployment
Action	Please select the assets to be deployed

INMSUE0078	**User does not have permission to create groups in the organization**
Explanation	When a target is created, a corresponding synchronization group is created in the organization selected with the given target name, but the user who is trying to create the target does not have permission to create a group in the organization he belongs to or the selected organization.
Action	Grant manage users permission to the user.

INMSUE0079	**Abstract WSDL services cannot be virtualized**
Explanation	The chosen service is an abstract service and hence cannot be virtualized
Action	Please choose a service which has concrete service definitions to virtualize

INMSUE0080	**Reserved characters except _ and - and non-ASCII characters are not allowed in the virtual service name.**
Explanation	The virtual service name can only contain the letters A-Z, a-z, numbers from 0-9, _ and - characters.
Action	Remove the special characters from the virtual service name.

INMSUE0081	**Logged in user {0} does not have permission to deploy the asset**
Explanation	To deploy an asset to the target, the user must have manage targets permission.
Action	Request the manage targets permission from the CentraSite administrator and try again.

INMSUE0083	**Hard Limit value should not be empty**
Explanation	Number. Required. Specifies the maximum number of invocations allowed per Interval before stopping the processing of further requests and issuing an alert. Typically, this limit should be higher than the soft limit.
Action	On Save of Throttling Policy

INMSUE0085	**Select Consumer Application to Limit traffic**
Explanation	Specifies the consumer application(s) that this action applies to. To specify multiple consumer applications, use the plus button to add rows, or select Any Consumer
Action	Specifies the consumer application(s) that this action applies to. To specify multiple consumer applications, use the plus button to add rows, or select Any Consumer

INMSUE0086	**Soft Limit value should not be empty**
Explanation	Number. Optional. Specifies the maximum number of invocations allowed per Interval before issuing an alert. Reaching the soft limit will not affect further processing of requests (until the Hard Limit is reached.
Action	On Save of Throttling Policy

INMSUE0087	**Soft Limit should not be higher than the Hard Limit**
Explanation	Hard limit should be higher than the soft limit
Action	On Save of Throttling Policy

INMSUE0089	**Reserved characters except _ and - and non-ASCII characters are not allowed in the target name.**
Explanation	The target name can only contain the letters A-Z, a-z, numbers from 0-9, _ and - characters.
Action	Remove the special characters from the target name.

INMSUI0082	**Service URL is invalid**
Explanation	Service URL should not contain characters like *
Action	Replace character ' * ' with a valid character.

INMSUI0084	**Interval should not be empty.**
Explanation	Specifies the amount of time for the soft limit and hard limit to be reached.
Action	Specifies the amount of time for the soft limit and hard limit to be reached.

INMSUI0088	**Please enter a valid URL or URI**
Explanation	A URL or URI was specified that is an invalid endpoint.
Action	Specify a valid URL or URI.

INMUCE0001	**Error while creating Axis2 SOAP Service Stub for UDDI Security API**
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure that the classpath has the correct version of Axis2 jars.

INMUCE0002	**Error while creating Axis2 SOAP Service Stub for UDDI Inquiry API**
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.

INMUCE0003	**Error while creating Axis2 SOAP Service Stub for UDDI Publish API**
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.

INMUCE0004	**Error while creating Axis2 SOAP Service Stub for UDDI Subscription API**
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.

INMUCE0005	**Error while creating Axis2 SOAP Service Stub for Taxonomy API**
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.

INMUCE0006	**Not able to connect to the UDDI Registry. get_authToken call failed.**
Explanation	Remote exception thrown while connecting to UDDI registry.
Action	Please make sure the host and port provided in RegistryConfiguration are valid.

INMUCE0007	**Not able to connect to the UDDI Registry. discard_authToken call failed.**
Explanation	Remote exception thrown while connecting to UDDI registry.
Action	Please make sure the host and port provided in RegistryConfiguration are valid.

INMUCE0008	**Not able to fetch the modified date of service with key {0}. get_operationalInfo call failed due to RemoteException.**
Explanation	Remote exception was thrown while getting operational info for the given service.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.

INMUCE0009	**Not to able to fetch the virtual services for the specified target {0}**
Explanation	Not to able to fetch the virtual services for the specified target {0}, as remote exception was caught in find_service call.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.

INMUCE0011	**Not able to fetch the service with name {0}. find_service call failed due to RemoteException.**
Explanation	Remote exception was thrown while inquiring the registry for services.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.

INMUCE0012	**Not able to fetch the details of the service {0}. get_serviceDetail call failed due to RemoteException.**
Explanation	Remote exception was thrown while inquiring the registry for service details.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.

INMUCE0013	**Not able to fetch the details of the tModel {0}. get_tModelDetail call failed due to RemoteException.**
Explanation	Remote exception was thrown while inquiring the registry for tModel details.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.

INMUCW0010	**Unable to find the virtual service with specified name {0}**
Explanation	There is not virtual service with the specified name in the UDDI registry.
Action	Please make sure the UDDI registry has a virtual service with the specified name. If it exists please make sure the user provided in RegistryConfiguration has the privilege to view the virtual service.

INMVSE0001	**Internal JAXR error happened**
Explanation	An exception inside JAXR occurred.
Action	Analyze the JAXR exception given by the stack.

INMVSE0002	**Invalid NULL parameter given**
Explanation	A version interface method was called with invalid parameters containing NULL.
Action	Correct the usage of the version management interface.

INMVSE0003	**Object of type {0} not supported for External Link versioning**
Explanation	This object must not be used for duplicating external links.
Action	Do not use this kind of object.

INMVSE0004	**Invalid external link for versioning, must be a WebDAV one. URI: {0}**
Explanation	The external link object provided for versioning is not supported. It must be an external link of a WebDAV resource.
Action	Do not use this kind of external link.

INMVSE0005	**Unexpected external link. URI: {0}**
Explanation	During external link versioning the exteranl link handling was unexpected.
Action	Check your WebDAV resources of external links.

INMVSE0006	**Object of type {0} not supported for a versioning operation**
Explanation	A non-versionable object was found during a versioning operation.
Action	Check your registered objects.

INMVSE0007	**Unexpected: no new external link in duplication list**
Explanation	Internal error: an element was not properly duplicated during versioning.
Action	Contact your software supplier.

INMVSE0008	**Object to be versioned ({0}) does not have the highest version number**
Explanation	The registry object to be versioned is an intermediate one in the versioning hierarchy, which is not permitted.
Action	Use only the highest versioned object for a versioning action.

INMVSE0009	**Object ({0}) is not granted for a versioning operation.**
Explanation	A registered listener rejected the object for the given versioning operation.
Action	Check your registry entries and why the listener has denied the action.

INMVSE0010	**Invalid association ID specified: {0}**
Explanation	An invalid association type was specified by the user of the API.
Action	Correct the association type, e.g. for HasParent, Uses, etc.

INMVSE0011	**Invalid WebDAV URL: {0}**
Explanation	The WebDAV URL has an invalid format.
Action	Correct the format.

INMVSE0012	**WebDAV cannot be accessed**
Explanation	Failure on WebDAV access.
Action	Inspect the original exception.

INMVSE0013	**Resource cannot be stored to WebDAV**
Explanation	Internal error on storing a file to WebDAV.
Action	Inspect the original exception.

INMVSE0014	**Unexpected: copied object not found in list**
Explanation	An object which was duplicated was not found in the list holding those elements.
Action	No action required.

INMVSE0015 **Unsupported copy mode for a Package object**

Explanation The copy mode for versioning a package is not supported.

Action Use only supported copy modes.

INMVSE0016 **Error retrieving checkpoint objects for ID: {0}**

Explanation The revision or checkpoint object cannot be determined.

Action See the embedded exception description.

INMVSE0017 **Error finding checkpoint records**

Explanation Checkpoint records couldn't be determinded during a find with qualifiers.

Action See the embedded exception description.

INMVSE0018 **The restore of revision objects failed**

Explanation The replacement of the current object with an older revision of the object was not successful.

Action See the embedded exception description.

INMVSE0019 **The method is not allowed if revision feature not enabled**

Explanation The revision feature must be enabled in CentraSite before using certain methods.

Action Enable CentraSite's revision feature.

INMVSE0020 **Checkpoint label {0} already in use**

Explanation A checkpoint label must only be used once in the system.

Action Use another label or delete the label first.

INMVSE0021 **Setting of checkpoint label '{0}' failed**

Explanation Setting of checkpoint label to revision objects failed.

Action See embedded exception description.

INMVSE0022 **Error reading checkpoint with label '{0}'**

Explanation Reading revision objects failed due to an internal reason.

Action See embedded exception description.

INMVSE0023 **Error on finding checkpoint label names**

Explanation Retrieving all checkpoint label names was not successful.

Action See embedded exception description.

INMVSE0024 **Error during deletion of checkpoint label '{0}'**

Explanation Deleting checkpoint labels from objects was not successful.

Action See embedded exception description.

INMVSE0025 **Checkpoint label count cannot be determined**

Explanation The checkpoint label count cannot be determined due to internal problems.

Action Please contact your software supplier.

INMVSE0026 **Error getting minor version of object: {0}**

Explanation Error getting minor version of object.

Action See embedded exception description.

INMVSE0027 **Error getting checkpoint label of object: {0}**

Explanation Error getting checkpoint label of object.

Action See embedded exception description.

INMVSE0028 **Invalid keepCount parameter**

Explanation Invalid keepCount parameter.

Action Correct the keepCount parameter.

INMVSE0029 **Error purging checkpoints of object: {0}**

Explanation Error purging checkpoints of object.

Action See embedded exception description.

INMVSE0030 **Revision and Checkpoint enablement failed**

Explanation Revision and Checkpoint enablement failed.

Action See embedded exception description.

INMVSE0031 **Disable of Revision and Checkpoint failed**

Explanation Disable of Revision and Checkpoint failed.

Action See embedded exception description.

INMVSE0032 **Base collection not present**

Explanation The base CentraSite collection is not available. The registry seems to be inconsistent.

Action Please contact your software supplier.

INMVSE0033 **The common CentraSite schema is not present.**

Explanation Schema CentraSiteObjects is not present.

Action Check the CentraSite environment.

INMVSE0034 **Asset Type ({0}) does not support the Versioning Capability**

Explanation An instance of an asset type should get a new version, but the asset type does not support this.

Action Check the properties of your asset type.

INMWSE0001 **Unable to connect to {0} using the provided username and password.**

Explanation The service was unable to connect to the provided CentraSite address.

Action Make sure the CentraSite address is valid and the username and password are correct.

INMWSE0002 **Error reading {0}.**

Explanation The service was unable to read the document.

Action Make sure that the document is accessible and valid.

INMWSE0003 **Unable to import service.**

Explanation The application was unable to import the service in the CentraSite registry.

Action Make sure the arguments are correct or manually check the CentraSite registry for problems.

INMWSE0004 **Error retrieving product with name {0}.**

Explanation The service was unable to find the product with the provided product name.

Action Make sure that the product name is correct and exists in the CentraSite registry.

INMWSE0005	**Unable to import {0} {1}.**
Explanation	The service was unable to import the file.
Action	Make sure the arguments are correct or manually check the CentraSite registry for problems.

INMWSE0006	**Failed to retrieve the imported service ID.**
Explanation	Unable to retrieve the UDDI key of the service which has been imported.
Action	Check connection to CentraSite server. Check the logs for errors.

INMWSE0007	**Unable to retrieve the registered BPEL process ID.**
Explanation	The application was unable to retrieve the imported BPEL process ID.
Action	Check connection to CentraSite server. Check the logs for errors.

INMWSE0008	**Unable to import BPEL process.**
Explanation	The application was unable to import the BPEL process in the CentraSite registry.
Action	Make sure the arguments are correct or manually check the CentraSite registry for problems.

INMWSE0009	**Unable to import XSD schema.**
Explanation	The service was unable to import the XSD schema in the CentraSite registry.
Action	Make sure the arguments are correct or manually check the CentraSite registry for problems.

INMWSE0010	**Missing attachment with content ID {0}.**
Explanation	The service was unable to retrieve the attachment.
Action	Make sure the content ID of the attachment is valid.

INMWSE0011	**Invalid file descriptor. Missing file type.**
Explanation	The value for file type was missing.
Action	Make sure the arguments are valid.

INMWSE0012	**Invalid file descriptor. Missing file name.**
Explanation	The value for the file name was missing.
Action	Make sure the arguments are valid.

INMWSE0013	**Invalid file descriptor. Missing content ID string.**
Explanation	The value for the content ID string was missing.
Action	Make sure the arguments are valid.

INMWSE0014	**Invalid file type. Must be XSD, WSDL, BPEL, XPDL, META_INFO, DOCUMENT or REFERENCED.**
Explanation	CentraSite web services will only accept the following file types: XSD, WSDL, BPEL, XPDL, META_INFO, DOCUMENT or REFERENCED.
Action	Please provide valid file type.

INMWSE0015	**Missing Authorization header.**
Explanation	Authorization header for HTTP basic authentication was not found in the request.
Action	Provide username and password to connect to the CentraSite server.

INMWSE0016	**The creation of a folder in the temp directory has failed.**
Explanation	The creation of a folder in the temp directory has failed. The folder could not be created in the temp directory which is determined by the system property java.io.tmpdir.
Action	Please make sure that the temp directory has enough free space.

INMWSE0017	**The creation of folder {0} has failed.**
Explanation	The specified folder could not be created.
Action	Please make sure that you have sufficient privileges to create the folder.

INMWSE0018	**Exception while importing XPDL**
Explanation	An exception occurred while importing the XPDL file.
Action	Please make sure the SOAP request has all required parameters filled with proper values.

INMWSE0019	**Referenced file {0} not found**
Explanation	The XPDL file to be imported has a reference to a web service. But the WSDL file for the referenced file was not passed to the XPDL importer service.
Action	Please create a file descriptor for the referenced WSDL file and send it to ImportXPDLService.

INMWSE0020	**Response from XPDL importer does not contain any registry objects**
Explanation	The XPDL Importer didn't report any error. Also it didn't return any response which needs to be filled for a web service response.
Action	Please make sure the XPDL file contains the Process element which will be created in CentraSite and returned in the web service response.

INMWSE0021	**Error while fetching LCM state for process**
Explanation	A system error has occurred while loading the LCM state of the process.
Action	Please check whether the Process object is in a valid state. If it is in a valid state, please retry the request.

INMWSE0022	**Parameter name (wild card) is mandatory input**
Explanation	This operation requires a keyword as a parameter. In the request, the keyword is not set.
Action	Please set the keyword in the SOAP request.

INMWSE0023	**Error while fetching processes from CentraSite**
Explanation	A system error has occurred while fetching process objects from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
Action	Please check whether the CentraSite Server is up and running.

INMWSE0024	**Error while fetching services from CentraSite**
Explanation	A system error has occurred while fetching services from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
Action	Please check whether the CentraSite Server is up and running.

INMWSE0025	**Error while fetching organizations from CentraSite**
Explanation	A system error has occurred while fetching organizations from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
Action	Please check whether the CentraSite Server is up and running.

INMWSE0026	**Invalid LCM states {0} are used in search filters**
Explanation	At least one lifecycle state provided in the search filter is not valid.
Action	Please provide proper lifecycle states in the search filter.

INMWSE0027	**Invalid file descriptor.**
Explanation	The value for file type was missing.
Action	Make sure the arguments are valid.

INMWSE0028	**The XPDL is not passed as FileDescriptor in the request**
Explanation	The request does not contain a file descriptor.
Action	Please pass the XPDL content as the file descriptor in the request.

INMWSE0029	**Specified organization key {0} is not valid**
Explanation	CentraSite does not contain an organization with the provided key.
Action	Please make sure the organization key provided in the request is valid.

INMWSE0030	**Specified product {0} is not valid**
Explanation	CentraSite does not contain the product concept with the specified key.
Action	Please make sure the product specified in the request is valid.

INMWSE0031	**Exception while fetching the properties from META-INFO**
Explanation	The user can provide attributes with values in the request. CentraSite is not able to fetch the properties from the provided META-INFO file descriptor.
Action	Please provide the properties in the format which is supported by CentraSite. Please refer http://localhost:53307/wsstack/services/Property.xsd for the CentraSite supported format. Please replace the host and port in the above URL accordingly.

INMWSE0032	**Referenced file {0} not found**
Explanation	The WSDL file to be imported imports another WSDL/XSD. But the other imported WSDL/XSD file was not passed to the WSDL importer service.
Action	Please create a file descriptor for the referenced WSDL/XSD file and send it to ImportWSDLService.

INMWSE0033	**Exception occurred while executing getApprovalHistory operation**
Explanation	An internal issue occurred while performing the getApprovalHistory operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.

INMWSE0034	**Exception occurred while executing getPendingApprovals operation**
Explanation	An internal issue occurred while performing the getPendingApprovals operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.

INMWSE0035	**Exception occurred while approving the approval flow using approve operation**
Explanation	An internal issue occurred while performing the approve operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.

INMWSE0036	**Exception occurred while executing getApprovalRequests operation**
Explanation	An internal issue occurred while performing the getApprovalRequests operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.

INMWSE0037	**Exception occurred while executing getApprovalActions operation**
Explanation	An internal issue occurred while performing the getApprovalActions operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.

INMWSE0038	**Revert Pending State operation can only be performed by CentraSite Administrator**
Explanation	Not all users have permission to revert the pending state of a registry object. The user should have the CentraSite Administrator role to perform a revert pending state operation.
Action	Please provide the user with CentraSite Administrator role for the revert pending state operation.

INMWSE0039	**CentraSite does not contain a registry object with the specified key {0}.**
Explanation	The revert pending state operation requires a key of the registry object which exists in CentraSite. The pending state change cannot be reverted for a registry object that does not exist in CentraSite.
Action	Please make sure a registry object exists in CentraSite with the specified key.

INMWSE0040	**Exception occurred while executing revertPendingStateChange operation**
Explanation	An internal issue occurred while reverting a pending state change. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.

INMWSE0041	**Exception occurred while executing reject operation**
Explanation	An internal issue occurred while performing the reject operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.

INMWSE0042	**applicationServeKeyOrName parameter is missing in the request**
Explanation	This error happens when the user does not set the applicationServerKeyOrName in the request parameter.
Action	Set the applicationServerKeyOrName in the request parameter.

INMWSE0043	**serviceKey parameter is missing in the request message**
Explanation	This error happens when the user does not set serviceKey in the request parameter.
Action	Set the serviceKey in the request parameter.

INMWSE0044	**Invalid product {0} has been specified in the request**
Explanation	The value given as product parameter is invalid.
Action	Give a valid product name in the product parameter.

INMWSE0045	**Found {0} {1} application server instances during search. Use application server key to find unique instance.**
Explanation	This error happens if the search result matches more than one application server instance.
Action	Use the key to find a unique application server instance in the web service request operation.

INMWSE0046	**Failed to associate the given application server {0} and service {1}**
Explanation	This error may happen if the given CentraSite location is wrong or because of invalid credentials.
Action	Check the CentraSite location and its credentials. Also check if the application server instance exists.

INMWSE0047	**Invalid application server {0}**
Explanation	The given application server key or name is not valid.
Action	Give the correct application server key in the request parameter.

INMWSE0048	**Parameter name (serviceKeys) is mandatory input**
Explanation	The serviceKeys element is mandatory for the GetServiceDetails request.
Action	Specify at least one service key for the GetServiceDetails request.

INMWSE0049	**Error while retrieving service detail**
Explanation	Verify that the given request parameters are appropriate for the getServiceDetails call.
Action	Validate the parameters supplied for the getServiceDetails operation.

INMWSE0050	**Error while retrieving associated type for Lifecycle model {0}**
Explanation	An error occurred while retrieving an associated type for a lifecycle model.
Action	Verify that the associated types for the lifecycle model are appropriate.

INMWSE0051	**Error while retrieving transition state for the Lifecycle model {0}**
Explanation	An error occurred while retrieving the transition state for the lifecycle state and lifecycle model.
Action	Verify that the transition states are appropriate for the retrieved lifecycle state.

INMWSE0052	**Error while retrieving LC State for the LC Model {0}**
Explanation	An error occurred while retrieving a lifecycle state for the lifecycle model.
Action	Verify that the lifecycle states are appropriate for the retrieved lifecycle model.

INMWSE0053 **Error while retrieving LC Model {0}**

Explanation An error occurred while retrieving the lifecycle model.

Action Verify that the retrieved lifecycle model is correct.

INMWSE0054 **Failed to process getLifecycleModels operation**

Explanation The getLifecycleModels operation could not be processed.

Action Verify that the parameters are appropriately specified in the request.

INMWSE0055 **Error while registering the application server {0}**

Explanation An error occurred while registering the application server.

Action Verify that the parameters are appropriately specified in the request.

INMWSE0056 **Error while deregistering the application server**

Explanation An error occurred while deregistering the application server.

Action Verify that the parameters are appropriately specified in the request.

INMWSE0057 **Error while reading product version information**

Explanation An error occurred while getting the application server version.

Action Verify that the parameters are specified in the request.

INMWSE0058 **Error while retrieving installed language information from CentraSite**

Explanation Error while retrieving installed language information from CentraSite.

Action Validate the web service request or contact the CentraSite administrator.

INMWSE0059 **Invalid owner key {0} specified in request**

Explanation The request XML contains an invalid owner key.

Action Specify the appropriate owner key in the request XML.

INMWSE0060 **Invalid organization key {0} specified in request**

Explanation The request contains an invalid organization key.

Action Specify an appropriate organization key in the request.

INMWSE0061	**Invalid object type {0} specified in request**
Explanation	The request contains an invalid object type.
Action	Specify an appropriate object type string in the request.

INMWSE0062	**Object Type is mandatory when Organization Key is specified in request**
Explanation	The object type is mandatory when the organization key is specified in the request.
Action	Specify a valid object type string in the request.

INMWSE0063	**Service {0} is not available in organization {1}**
Explanation	The organization key specified for this service is not correct.
Action	Provide the correct organization key of this service.

INMWSE0064	**Invalid asset key {0} passed in the request**
Explanation	The request contains an invalid asset key.
Action	Pass a valid asset key in the request.

INMWSE0065	**Error while processing getAssociatedServices request**
Explanation	An error occurred while processing a getAssociatedServices request.
Action	Check if the given request parameters are correct.

INMWSE0066	**Error while processing releaseProcesses request**
Explanation	It was not possible to process the releaseProcesses request.
Action	Check if the given request parameters are correct.

INMWSE0067	**CentraSite does not contain an Application Server with the specified key or name {0}.**
Explanation	A CentraSite web service received a RegisterApplicationServer request with a key or name specified. The web service tried to update the object with the specified key or name, but the web service was not able to find any Application Server object with the specified key or name.
Action	Please check whether an Application Server object exists in CentraSite with the specified key or name. If an object exists in CentraSite, please make sure the requested user has view/edit permission on the Application Server object.

INMWSE0068	**Specified application server {0} does not exist**
Explanation	The application server name or key given in the request is not valid.
Action	Check the given application server name or key and correct it.

INMWSE0073	**Invalid application server key {0}**
Explanation	The request contains an invalid application server key.
Action	Specify a valid application server key.

INMWSE0074	**Exception while parsing XPDL file {0}**
Explanation	CentraSite will parse the specified XPDL file to create corresponding objects in CentraSite. CentraSite is not able to parse the specified the XPDL file as the given XPDL file does not comply with the XML and XPDL specification.
Action	Please make sure the specified XPDL file is in accordance with the XML and XPDL specification.

INMWSE0075	**The given organization key {0} in the request does not match the key of the existing asset's organization {1}**
Explanation	The organization key given in the importWSDL request does not match the organization key of the existing asset's organization.
Action	Provide the existing asset's organization key in the request.

INMWSE0077	**Failed to find application server in given name {0}.**
Explanation	This exception is unexpected. The cause is not immediately known.
Action	If the problem persists, contact CentraSite administrator.

INMWSE0078	**Application Server name is empty**
Explanation	No name was supplied for the application server.
Action	Provide a valid application server name.

INMWSE0079	**Unsupported Association Type {0}**
Explanation	The specified association type is not supported.
Action	Correct the association type.

INMWSE0080	**Check your access rights and proxy settings.**
Explanation	You do not have sufficient privileges to access the target object.
Action	Execute the action with sufficient privileges.

INMWSE0081	**The {0} parameter value is null.**
Explanation	The function shown on the call stack is called with a null value.
Action	Correct the client program.

INMWSE0082	**The credentials parameter value is null.**
Explanation	The setCredentials() method is called with a null value for the credentials parameter.
Action	Correct the client program.

INMWSE0083	**Specified process {0} is unavailable.**
Explanation	Process with the specified asset ID is not available.
Action	Check the asset ID provided in the request.

INMWSI0069	**Asset {0} is already associated with the server {1}**
Explanation	The given asset key request is already associated with the specified application server.
Action	Remove the asset key from the request.

INMWSI0070	**Asset {0} has been associated with the server {1} successfully**
Explanation	The asset {0} has been associated with the server {1} successfully.
Action	The association between the asset key and the server was created successfully.

INMWSI0071	**The asset {0} has not been associated with the server {1}**
Explanation	The asset is not associated with the specified server.
Action	Associate the asset and the server first before disassociating.

INMWSI0072	**Asset {0} has been disassociated from the server {1} successfully**
Explanation	The given asset has been disassociated from the server successfully.
Action	The given asset has been disassociated from the server successfully.

INMWSI0076	**Application server does not exist for given name {0}.**
Explanation	An application server does not exist in the given name.
Action	Create an application server in the given name.

INOQJE0001	**XQConnection for {0} is closed!**
Explanation	The connection to the specified database is closed.
Action	Make sure that the connection in use is not closed prior to any later operation.

INOQJE0002	**XQExpression is closed!**
Explanation	The underlying expression is already closed.
Action	Make sure that the expression / connection in use is not closed prior to any later operation.

INOQJE0003	**XQItemType mismatch! Item is not of type {0}.**
Explanation	The specified item is not of the declared item type.
Action	Check for the compatibility of item types.

INOQJE0004	**No cursor handle given!**
Explanation	The cursor associated with the query handle was not found.
Action	This happens if there is no proper result set associated with the specified query.

INOQJE0005	**Error reading from file - {0}**
Explanation	This exception is thrown by the Java run-time architecture when an input error has occurred while reading from the specified file.
Action	Possible causes for this exception are an error reading from the specified file or the specified file is not found.

INOQJE0006	**Error while parsing the XMLStream - {0}**
Explanation	This is an error for unexpected errors during processing / XML handling, namely, to report well-formedness errors as well as unexpected processing conditions.
Action	The error message contains the explanation from the StAX parser. Modify the XML accordingly.

INOQJE0007	**Parser configuration error - {0}**
Explanation	Indicates a serious configuration error. An exception occurred during configuration of the XML parser being used.
Action	Add the corresponding XML parser jars in the CLASSPATH.

INOQJE0008	**Factory Configuration Error - {0}**
Explanation	A problem with configuration of the Parser Factories exists. This error will typically be thrown when the class of a parser factory specified in the system properties cannot be found or instantiated.
Action	Add the XML parser jars to the CLASSPATH and set the JAXP factory names.

INOQJE0009	**Cannot access the XQItem of type XQITEMTYPE_ATTRIBUTE**
Explanation	Indicates that the base item type of the current item is an attribute while writing the current item to a SAX stream.
Action	The current item should not be of type attribute.

INOQJE0010	**SAX Parse Error - {0}**
Explanation	Represents a general SAX error or warning.
Action	Possible causes for this error are if the value of the "org.xml.sax.driver" system property is null or the class cannot be loaded and instantiated.

INOQJE0011	**I/O Error - {0}**
Explanation	This exception is thrown by the Java run-time architecture when an input / output error of some kind has occurred while reading from the specified input source.
Action	Refer to the Java documentation for the error message.

INOQJE0012	**End of the sequence is reached**
Explanation	Execution of an XQuery returns a sequence of results. You can traverse the sequence of results using the XQResultSequence API.
Action	Reading or trying to modify items in the sequence after reaching the end of the sequence will result in this error.

INOQJE0013	**Positioned before the start of the sequence**
Explanation	Execution of an XQuery returns a sequence of results. You can traverse the sequence of results using the XQResultSequence API. Invoking the next() method for the first time will get to the first item in the sequence. If any operations are tried before this, this will result in this error.
Action	Invoke the next() method to get the first item.

INOQJE0014	**Server {0} unavailable**
Explanation	The specified database or server is not running.
Action	Provide the correct database URL, and check if the database is stopped.

INOQJE0015	**Error when attempting to change the transaction mode**
Explanation	The attempt to change the transaction mode failed.
Action	Check the Server documentation for the specified error code in the error message.

INOQJE0016	**Error closing the {0}**
Explanation	An attempt to close the underlying connection or result sequence that is specified along with the error failed.
Action	Make sure that the underlying connection is not closed before closing the result sequence.

INOQJE0017	**Transaction failed while committing the changes**
Explanation	Committing the changes failed.
Action	Check the Server documentation for the specified error code in the error message.

INOQJE0018	**Transaction failed while rolling back the changes**
Explanation	Rolling back the changes failed.
Action	Check the Server documentation for the specified error code in the error message.

INOQJE0019	**The scrollability type {0} is not supported**
Explanation	The mentioned scrollability type is not supported.
Action	Set a valid value for the scrollability type.

INOQJE0020	**The property {0} is not supported**
Explanation	The mentioned property is not supported.
Action	Provide a valid property.

INOQJE0021	**A property mentioned in the list is not supported**
Explanation	One of the mentioned properties in the property list is not supported.
Action	Check if all the properties in the property list are supported by the current implementation.

INOQJE0022	**Error executing the server command : {0}**
Explanation	An error occurred while executing the specified database command.
Action	Please refer to the documentation of the specified command.

INOQJE0023	**XQTypeException thrown - Error Code : {0} Message : {1}**
Explanation	External variable binding to XQuery failed.
Action	Check the server documentation for the error code displayed in the error.

INOQJE0024	**Error fetching cursor**
Explanation	Indicates a cursor based failure when fetching a number of documents from a cursor.
Action	Check the server documentation for the error code displayed in the error.

INOQJE0025	**XQuery exception: {0}**
Explanation	Error in the XQuery.
Action	Please check the XQuery for errors.

INOQJE0026	**Error while opening cursor**
Explanation	Indicates a failure when opening a cursor.
Action	Check the server documentation for the error code displayed in the error.

INOQJE0027	**Error executing XQuery {0}: {1}**
Explanation	Executing the XQuery failed. See the error code for more information.
Action	Check the server documentation for the error code displayed in the error.

INOQJE0028	**Sequence is non-scrollable**
Explanation	Cannot scroll on a non-scrollable sequence.
Action	Avoid scrolling, because the sequence is non-scrollable.

INOQJE0029	**Failed because of following exception**
Explanation	The cause of the exception is specified in the error message.
Action	Check the server documentation for the specified error code in the error message.

INOQJE0030	**Error creating the cached item**
Explanation	Creating a cached item failed.
Action	Check if the items are closed.

INOQJE0031	**Error binding the {0} Message - {1}**
Explanation	Binding the specified value to the expression / prepared expression failed.
Action	Check if the values declared and bound to the query are the same.

INOQJE0032	**Error executing the request with error [{0} {1} {2} {3}]**
Explanation	The message appears with the specific error code and information from the server.
Action	Refer to the server documentation for the specified error code.

INOQJE0033	**Sequence not scrollable**
Explanation	Cannot scroll a non scrollable sequence.
Action	Avoid scrolling, because the sequence is non-scrollable.

INOQJE0034	**Expected type {0} Current type {1} Location {2}**
Explanation	The expected type and the current type specified do not match.
Action	Check the types mentioned in the error at the specified location.

INOQJE0035	**Expected start or end tag {0}**
Explanation	When trying to move to the next tag in the resulting XML Stream, any white space , COMMENT, or PROCESSING_INSTRUCTION is skipped until a START_ELEMENT or END_ELEMENT is reached. If anything other than white space characters, COMMENT, PROCESSING_INSTRUCTION, START_ELEMENT, END_ELEMENT is encountered, this error is thrown along with the location number.
Action	Check the error message for the missing start or end in the XML.

INOQJE0036 **{0} cannot be null!**

Explanation The underlying object specified is null.

Action Make sure that the underlying object is properly initialized.

INOQJE0037 **The {0} method is not supported**

Explanation The method specified in the error message is not supported.

Action The specified method is not supported by the current XQJ implementation.

INOQJE0038 **XQPreparedExpression is closed!**

Explanation The underlying prepared expression is already closed.

Action Make sure that the XQPreparedExpression is not closed before any usage.

INOQJE0039 **XQSequence is closed!**

Explanation The underlying sequence is already closed.

Action Make sure that the XQSequence is not closed before any usage.

INOQJE0040 **XQItem is closed!**

Explanation The underlying item is already closed.

Action Make sure that the XQItem is not closed before any usage.

INOQJE0041 **The value for the property {0} cannot be null**

Explanation The value for the specified property in the error message cannot be null.

Action Mention a property value for the specified property name in the error message.

INOQJE0042 **Access Failure Exception - {0}**

Explanation The cause for the exception is specified in the error message.

Action Check the server documentation for the specified error code in the error message.

INOQJE0043 **Invalid user ID or password**

Explanation The supplied user ID and password combination is invalid.

Action Check the user ID and password.

INOQJE0044	**Cannot access the XQItem of type XQITEMKIND_ATTRIBUTE**
Explanation	This indicates that the item kind of the current item is an attribute while writing the current item to a SAX stream.
Action	The current item should not be of type attribute.

INOQJE0045	**Error creating the XQ item**
Explanation	An error occurred while creating an XQ item.
Action	Check if the items are closed.

INOQJE0046	**Binding to {0} not supported**
Explanation	While binding an external variable to an XQuery, the type specification was not valid. Either the type is not supported at all for binding external variables, or it was used with a binding method that does not support this specific type.
Action	Use one of the supported types with a proper binding method.

UDDIE00002	**No businessKey was defined**
Explanation	Keys have to be specified to fetch the details.
Action	Please provide keys in the UDDI request to fetch the details.

UDDIE00005	**At least keyBag or transferToken should be specified**
Explanation	The discard_transferToken request is not valid. It has to be according to the UDDI v3 specification.
Action	Please specify transferToken to discard it.

UDDIE00006	**The value of the attribute maxRows is not a valid number.**
Explanation	The value for the maxRows attribute in the UDDI request should be a number.
Action	Please specify an integer value for the maxRows attribute in the UDDI request.

UDDIE00007	**{0} is not a valid find qualifier value in version {1}.**
Explanation	The find qualifier is not supported in the specified version.
Action	Please specify find qualifiers corresponding to the UDDI version.

UDDIE00008	**No entityKey was defined**
Explanation	Keys have to be specified to fetch the operationa info.
Action	Please provide keys in the get_operationalInfo request to fetch the operational information.

UDDIE00011	**Publisher assertions are null**
Explanation	The add_publisherAssertions, delete_publisherAssertions and set_publisherAssertions requests should have publisher assertions in them.
Action	Please add the publisherAssertions element in add_publisherAssertions, delete_publisherAssertions and set_publisherAssertions requests.

UDDIE00012	**Exactly one BusinessKey must be defined.**
Explanation	Either fromKey, toKey or businessKey should be specified.
Action	Please specify a value for the toKey or fromKey or businessKey attribute of the find_relatedBusiness call.

UDDIE00013	**Only one keyedReference element may be defined in a find_relatedBusinesses message.**
Explanation	The publisher assertion should contain only one keyedReference element.
Action	Please provide one KeyedReference in the find_relatedBusiness call.

UDDIE00014	**{0} is not a valid UUID.**
Explanation	The specified key is not valid.
Action	Please make sure the key is valid according to the UDDI standard.

UDDIE00015	**The specified names are not valid for version**
Explanation	The names are not specified according to the UDDI specification.
Action	Please specify valid names.

UDDIE00016	**Only one key may be defined**
Explanation	Multiple keys are defined for the UDDI entity.
Action	Please specify a single key for the UDDI entity.

UDDIE00017	**The fromKey element is mandatory in a publisherAssertion document**
Explanation	The fromKey element does not contain a valid value.
Action	Please provide values for the fromKey element in the publisherAssertion element.

UDDIE00018	**The toKey element is mandatory in a publisherAssertion document**
Explanation	The toKey element does not contain valid value.
Action	Please provide values for the toKey element in the publisherAssertion element.

UDDIE00019	**The keyedReference element is mandatory in a publisherAssertion document**
Explanation	The keyedReference element does not contain valid value.
Action	Please provide values for the keyedReference element in the publisher assertion element.

UDDIE00020	**The keyedReference element in a publisherAssertion must be defined exactly one time**
Explanation	The publisher assertion should contain only one keyedReference element.
Action	Please provide one KeyedReference in the publisher assertion element.

UDDIE00022	**{0} is not a valid findQualifier value**
Explanation	Provided findQualifier is not valid. The valid qualifiers can be found in UDDI specification.
Action	Please provide findQualifiers according to the UDDI specification

UDDIE00024	**The string representation may not be empty.**
Explanation	A value for the element in the UDDI request is not according to the UDDI specification.
Action	Please make sure the UDDI request is valid according to UDDI specification.

UDDIE00025	**A tag of the language code must have at least one character and no more than eight characters.**
Explanation	A value for the language code in the UDDI request does not comply with the UDDI specification.
Action	Please make sure the UDDI request is valid according to UDDI specification.

UDDIE00026	**A language code may only contain ASCII alphanumerics.**
Explanation	A value for the language code in the UDDI request does not comply with the UDDI specification.
Action	Please make sure the UDDI request is valid according to UDDI specification.

UDDIE00027	**Could not authenticate the user {0}**
Explanation	The user specified in the UDDI request is not valid.
Action	Please specify a valid CentraSite user.

UDDIE00042	**{0} does not represent a businessKey.**
Explanation	CentraSite does not contain any business entity with the specified key.
Action	Please make sure the business key specified in the request is valid.

UDDIE00043	**No businessKey in the registry matches the key {0}.**
Explanation	CentraSite does not contain any business entity with the specified key.
Action	Please make sure the business key specified in the request is valid.

UDDIE00045	**No entity in the registry matches the key {0}.**
Explanation	CentraSite does not contain any UDDI entity with the specified key.
Action	Please make sure the key specified in the request is valid.

UDDIE00047	**The value of maxRows parameter is not a valid number.**
Explanation	The value for the maxRows attribute in the UDDI request should be a number.
Action	Please specify an integer value for the maxRows attribute in the UDDI request.

UDDIE00049	**The contact {0} already exists. Please specify a different contact.**
Explanation	The specified contact already exists in the CentraSite. A contact cannot be present in multiple businesses
Action	Please make sure the contact is not present in any other business

UDDIE00050	**The value of maxEntities parameter is not valid**
Explanation	The maxEntities attribute of the subscription should contain an valid non-negative number.
Action	Please provide valid non-negative number for the maxEntities attribute.

uddi:107e04bd-bdf4-11e2-b6b3-c566c3aaf997 – Verify Required Attributes

Explanation During asset instance creation and modification, verifies whether the required attributes of that Asset Type are provided with values

uddi:18bf0e3d-bdf4-11e2-b6b3-886f1ce73523 – Verify Required Attributes Policy

Explanation During asset instance creation and modification, this policy verifies whether the required attributes of that Asset Type are provided with values.

uddi:44e3e2de-064c-432f-b67a-8fbca0fb04d6 – Invoke webMethods Integration Server

Explanation Processing steps calling an Integration Server (IS) Service which will be executed when the consumer invokes the Virtual Service.

8 CloudStreams Messages

0010.0715E	**CloudStreams Upgrade, did not complete successfully.**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. This message indicates the upgrade was not successful. There should be a previous error message in the server log that indicates the problem.
Action	See actions for message ID '0010.0702'

0030.0099	**PublisherPropsObserver - Unknown wrapper factory data type ({0})**
Explanation	This message has incorrect text. It should indicate an invalid data type for UDDP publisher bean.
Action	Update the pg configuration file to use a proper UDDI publisher data type.

0030.0100	**PublisherPropsObserver - Unable to find wrapper factory**
Explanation	There is no UDDI publisher configured, but its properties are being changed.
Action	Update the configuration file. Either configure a UDDI publisher or unregister the UDDI properties observer.

0030.0109	**PublisherPropsObserver - Can't convert string ({0}) to integer for publishing interval, ignoring input**
Explanation	The value received for performance data reporting interval was not a valid numeric string.
Action	Make sure a numeric value is input.

0030.0113	**PublisherPropsObserver - Unknown pg service deployer data type ({0})**
Explanation	The data typi of the PG Service Deployer bean is invalid.
Action	Update the pg configuration file to use a proper PG Service Deployer data type.

0030.0301	**ConsumerApplicationManager.convert - cannot handle null request**
Explanation	Unable to create Consumer deployment object for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0302	**ConsumerApplicationManager.convert - cannot convert consumer with null {0}**
Explanation	Invalid Consumer deployment object was found.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0303	**VirtualServiceDeployer.{0} - cannot handle null {1}**
Explanation	A null reference was found during a deployment activity. The object and activity are identified in the message.
Action	Probably bad SOAP request for deployment, fix request.

0030.0304	**VirtualServiceDeployer.deploy - service ({0}) already deployed, undeploying**
Action	Info level message, no action required.

0030.0306	**VirtualServiceDeployer.{0} - caught this: type({1}) message({2})**
Explanation	Unable to deploy virtual service. See exception message for more details.
Action	Address the problem indicated by exception and try to deploy again.

0030.0309	**ClusteredServiceDeployer{0} - cannot handle null {1}**
Explanation	Unable to create VS deployment object for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0315	**ClusteredConsumerManager.updateConsumer - cannot handle null consumer**
Explanation	Unable to create Consumer object for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0318	**ClusteredServiceDeployer - cannot deploy null info to cache**
Explanation	A problem occurred while attempting to convert a PGService for deployment to shared cache. There should be another message describing the conversion or deployment issue.
Action	Fix the conversion or deployment problem.

0030.0319	**ClusteredServiceDeployer - cannot undeploy null service name from cache**
Explanation	Virtual service undeployment requires a non-empty service name. This is problem with undeployment request payload.
Action	Fix the undeployment request payload.

0030.0328	**ConsumerApplicationManager.{0} - cannot handle null update request**
Explanation	Invalid Consumer deployment request for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0330	**ConsumerApplicationManager - not updating consumer ({0}), modification date, ({1}), is no more recent**
Action	Info level message, no action required.

0030.0333	**ConsumerApplicationManager.{0} - caught this: type({1}) message({2})**
Explanation	Unable to create and persist Consumer object for update.
Action	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.

0030.0336	**Consumer Application Update Failed; requested update has invalid {0} field**
Explanation	Invalid consumer name or key in remove request.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0337	**Consumer Application Remove Failed; consumer ({0}) does not exist**
Explanation	Attempt to remove consumer failed.
Action	Reply to CentraSite Deployment attemp should indicate error. Try redeploying this consumer or resynchronizing all consumers.

0030.0343	**RegisteredConsumerNamesManager.{0} - cannot handle null update request**
Explanation	Invalid RegisteredConsumerNames deployment request for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0344	**Registered Consumer Names Update Failed; requested update has invalid {0} field**
Explanation	Invalid service name or consumer names in registered consumer names update request.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0346	**RegisteredConsumerNamesManager - not updating consumer names registered to ({0}), modification date, ({1}), is no more recent**
Action	Info level message, no action required.

0030.0347	**RegisteredConsumerNamesManager.{0} - cannot handle null update request**
Explanation	Invalid RegisteredConsumerNames deployment request for remove.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0348	**Registered Consumer Names Remove Failed; requested update has invalid {0} field**
Explanation	Invalid service consumer name in remove request.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0350	**Registered Consumer Names Remove Failed; service ({0}) has no registered consumers**
Explanation	Invalid request to remove RegisteredConsumerNames, must include at least one consumer name.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0352	**RegisteredConsumerNamesManager.{0} - caught this: type({1}) message({2})**
Explanation	Unable to create and persist RegisteredConsumerNames object for update.
Action	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.

0030.0356	**VirtualServiceDeployer - unable to get endpoints for {0}, caught this: type({1}), msg({2})**
Explanation	Unable to obtain endpoint for deployed service.
Action	Probably bad SOAP request to Deployer or bad VSD, fix one or both.

0030.0357	**ClusteredRegisteredConsumerNamesDeployer.updateConsumerNames - cannot handle null reg names object**
Explanation	Unable to create RegisteredConsumerNames object for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0358	**Consumer Application Remove Failed; requested update has invalid name and key fields, both are empty**
Explanation	Consumer remove request must have either name or key to identify consumer; both were null or empty.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0359	**ConsumerApplicationManager - Consumer update request has invalid IP range; from ({0}) to ({1})**
Explanation	Consumer update request had invalid IP address range.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0361	**VirtualServiceDeployer - redeploying undeployed service ({0}), deployment failed for newer version**
Action	Info level message, no action required.

0030.0362	**VirtualServiceDeployer - a problem was encountered during deployment, ({0}) will be undeployed and replaced if necessary**
Action	Info level message, no action required.

0030.0363	**VirtualServiceDeployer.{0} - service({1}) caught this: type({2}) message({3})**
Explanation	Message context encountered an exception while attempting to redeploy or undeploy a virtual service. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0030.0364	**Deployment request for service: {0}. Registered consumer name element was processed, but the existing modification date is the same as the request. {1}**
Action	Info level message, no action required.

0030.0366	**UddiPropertiesObserver - Password lookup failed; type ({0}), message ({1})**
Explanation	A problem was encoutnered by attempting to retrieve stored password. There should be an exception with more specific trouble description.
Action	Fix the problem identified by the exception message.

0030.0367	**UddiPropertiesObserver - Unable to activate performance date policies; type ({0}), message ({1})**
Explanation	The performance data deployer was unable to run. This message should include more details regarding the reason.
Action	Fix the problem identified by the exception message.

0030.0370	**UddiPropertiesObserver - Unable to connect to UDDI: ({0}); property updates saved, but data collection is OFF.**
Explanation	A problem was encountered during publisher test.
Action	This is probably a bad configuration parameter, fix it.

0030.0371	**UddiPropertiesObserver - Unable to convert port string ({0}) to integer, using default port {1}**
Explanation	The value input for 'UDDI port' number is non-numeric.
Action	Input an numeric port value.

0050.0001	**Unable to find Policy Element in the VSD:{0}**
Explanation	An exception was encountered while attempting to extract a policy element from VSD. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0002	**Unable to create Rampart properties:{0}**
Explanation	An exception was encountered while attempting to assemble Rampart keystore properties. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0003	**Unable to replace static Rampart configuration with configured properties:{0}**
Explanation	An exception was encountered while attempting to re-configure Rampart keystore properties. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0004	**Unable to create Rampart Configuration Element:{0}**
Explanation	An exception was encountered while attempting to convert Rampart configuration string to XML. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0005	**Unable to create XPath to select first Policy Alternative:{0}**
Explanation	An exception was encountered while attempting to create an Xpath object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0006	**Error while removing existing RampartConfig elements:{0}**
Explanation	An exception was encountered while attempting to remove configuration elements. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0007	**Required configuration information to enable WS-Security processing is missing. Unable to process service: {0}. Please ensure Keystore/Truststore information is configured**
Explanation	Service could not be initialized due to a problem with keystore/trustore configuration.
Action	Fix the security configuration.

0050.0011	**Exception while determining hostname or IP address of the server:{0}**
Explanation	An exception was encountered while attempting to resolve a host name or IP address. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0013	**CloudStreams needs the repository location of the SOAP stack**
Explanation	Configuration does not include a valid location for Axis2 repositoryconfiguration.
Action	Fix the axis2 configuration.

0050.0016	**ServerManager ready for processing**
Action	Info level message, no action required.

0050.0017	**CloudStreams encountered exception while starting ServerManager:{0}**
Explanation	An exception was encountered during configuration of Axis2 listeners. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0018	**Invalid Port specified. Using default configuration: {0}**
Explanation	The 'port' property has a non-numeric string value, the value configured in Axis is used.
Action	Make sure the property value to numeric.

0050.0019	**Port {0} is already in use. Trying alternate**
Explanation	The port indicated in the message is not available to use with a new socket.
Action	Specify another port value in the system 'port' property or Axis configuration.

0050.0020	**Exception while creating "id" selection XPath: {0}**
Explanation	Message context encountered an exception while attempting to create an XPath object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0021	**Found Element within Resources element with id: {0}**
Action	Info level message, no action required.

0050.0022	**Exception while selecting element with id:{0} in Resources Element: {1}**
Explanation	Message context encountered an exception while attempting to extract the indicated element from XML. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0023	**CloudStreams received a response for the request with message Id :{0} But a callback is not registered (anymore) to process this response**
Explanation	No callback was registered at the time this response was processed.
Action	This is probably a VS configuration problem.

0050.0024	**CloudStreams received a response message without a message Id**
Explanation	There was a problem relating the native service response to a virtual service request.
Action	Look for previously logged message indicating that message Id was not used.

0050.0025	**CloudStreams encountered an exception: {0}. No error handlers found - [Message Dropped]**
Explanation	This could be a configuration problem. An exception was encountered while attempting to handle a fault. The associated exception message should include more details regarding the problem.
Action	Fix the configuration, or other problem identified by the exception message.

0050.0026	**Outbound client can't locate policy from the property :{0}**
Explanation	The Synapse message context does not contain an entry for theproperty key identified in the message.
Action	This is a policy configuration problem.

0050.0027	**CloudStreams outbound client encountered error:{0}**
Explanation	Client encountered an exception while attempting to send a message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0029	**VSD with incorrect Namespace:{0}. Unable to create PGService.**
Explanation	The namespace found in the VSD is unknown.
Action	This is a virtual service configuration problem.

0050.0031	**The {0} element is required for a CloudStreams service**
Explanation	Some element used during service deployment was found to be null. The specific element should be identified in the message text.
Action	This is a virtual service configuration problem.

0050.0032	**The {0} sequence element is required for a CloudStreams service**
Explanation	The VSD is missing the sequence element identified in the message.
Action	This is a virtual service configuration problem.

0050.0033	**The inSequence for VSD:{0} is invalid.**
Explanation	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
Action	This is a virtual service configuration problem.

0050.0034	**The outSequence for VSD:{0} is invalid.**
Explanation	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
Action	This is a virtual service configuration problem.

0050.0035	**Exception while parsing Virtual Service String Definition:{0}**
Explanation	An exception was encountered while attempting to parse the virtual service description. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0036	**Unable to create Virtual Service Definition**
Explanation	Unable to create XML object from the VSD string.
Action	This is a virtual service configuration or deployment problem.

0050.0037	**PGServiceFactory encountered and exception while creating the PGService: {0}**
Explanation	An exception was encountered while attempting to validate input or output sequence or during WSDL URI processing. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0038	**Invalid parameter specified for PGService: {0}**
Explanation	The attribute named in the message has no value in the VSD.
Action	This is a virtual service configuration problem.

0050.0039	**Exception {0} for PGService: {1}**
Explanation	An exception was encountered while attempting during service creation. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0040	**No PGService found with name: {0}**
Explanation	Attempting to undeploy or get endpoints for a service that does not exist.
Action	Make sure the virtual service exists before operating on it.

0050.0041	**WSStack exception processing service: {0} Cause: {1}**
Explanation	An AxisFault was encountered while attempting to either undeploy or get endpoints for the virtual service named in the message. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0042	**Unable to locate the WSStack configuration. Can't deploy Virtual Service:{0}**
Explanation	The Synapse configuration cannot supply an Axis configuration.
Action	This is an Axis2/Synapse/WS-Stack configuration problem.

0050.0043	**A Virtual Service with name:{0} already exists. Unable to deploy.**
Explanation	Cannot deploy an Axis service when one already exists with the same name.
Action	Undeploy the existing service before attempting to redeploy or use the same name.

0050.0044	**Unable to locate WSStack configuration. Please check if WSStack is enabled/correctly configured.**
Explanation	Unable to retrieve the configuration context supplier bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.

0050.0045	**Invalid parameter passed for Virtual Service creation:{0}**
Explanation	An attempt to persist the VSD for a service found a null element. The VSD is not allowed to be null.
Action	This may be the result of invalid deployment payload; fix the VSD.

0050.0046	**Unable to persist VSD:{0} to disk. Encountered error:{1}**
Explanation	An exception was encountered while attempting to serialize the VSD for the service identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0047	**Unable to {0} VSD:{1}. Error:{2}**
Explanation	This message is used in several different error conditions, as indicated by the object of 'unable to...'.
Action	Fix the 'unable to...' problem for the service identified by 'VSD:'.

0050.0048	**Error getting endpoints for service:{0}, Cause: {1}**
Explanation	An exception was encountered while attempting to get endpoints. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0049	**Exception while creating PGService: {0}, Cause: {1}**
Explanation	An AxisFault was encountered while checking if deploying service already exists or while attempting to register service with Axis2. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0050	**Error while engaging module: {0}**
Explanation	An AxisFault was encountered while attempting to engage the Axis2 module indicated in the message. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0052	**Axis was unable to load module {0}**
Explanation	An exception was encountered while attempting to load and engage module identified in message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0053 **Loading the WSDL : {0}**

Action Info level message, no action required.

0050.0055 **PGService {0} encountered error while converting wsdl element to a StreamSource:{0}**

Explanation An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0057 **Unknown WSDL format for PGService:{0}, neither WSDL 1.1 nor WSDL 2.0**

Explanation The current WSDL element has unknown or no namespace associated.

Action This is a virtual service configuration problem.

0050.0060 **Populating SOAP service using WSDL**

Action Info level message, no action required.

0050.0061 **Unable to find a WSDL for the PGService:{0}. Assuming a POX or Legacy service**

Action Info level message, no action required.

0050.0062 **PGService: {0} is available on transports {1}**

Action Info level message, no action required.

0050.0063 **Adding PGService:{0} to the SOAP Stack**

Action Info level message, no action required.

0050.0064 **Removing PGService:{0} due to error: axisFault.getMessage()**

Action Info level message, no action required.

0050.0065 **Exception while setting policy on PGService:{0}**

Explanation An exception was encountered while attempting to engage WS-Policy module. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0066	**Setting policy with id:{0} on CloudStreams service:{1}**
Action	Info level message, no action required.

0050.0068	**Successfully created service in SOAP Stack for PGService:{0} containing {1} endpoint(s).**
Action	Info level message, no action required.

0050.0069	**Error{1} on setting parameter :{0} on CloudStreams service**
Explanation	An exception was encountered while attempting to set a parameter into an Axis service. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0070	**creating new CloudStreams service: {0}**
Action	Info level message, no action required.

0050.0071	**Unable to find service directory for service {0}**
Explanation	Unable to persist WSDL assets because the virtual service directory does not exist.
Action	Redeploying the virtual service should create the service directory.

0050.0074	**Error: {0} while reading from file {1}**
Explanation	An exception was encountered while attempting to read the proxy file identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0076	**Scheduled task[{0}] with startup delay of {1} ms and interval of {2} ms**
Action	Info level message, no action required.

0050.0077	**Error initializing JMS transport listener. Cause: {0}**
Explanation	An exception was encountered while attempting to register JMS listener. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0078	**Unable to stop TransportListener called:{0}. Exception:{1}**
Explanation	An AxisFault was encountered while attempting to stop the JMS transport listener during bean initialization. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0083	**Error {0} occurred while updating the load balancer properties**
Explanation	An AxisFault was encountered while attempting to add load balancer URL to an Axis transport description. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0084	**Loadbalanced Endpoint: [{0}] failed!**
Explanation	A mediation operation to a load balanced endpoint has failed. The endpoint indicated in the message is not available. This usually indicates a communication problem with the targeted server.
Action	Fix the targeted server.

0050.0086	**Unable to get the IS keystore manager - please check your configuration!**
Explanation	Unable to retrieve the keystore manager bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.

0050.0089	**Unable to get the Rampart Configuration Handler - please check your configuration!**
Explanation	Unable to retrieve the Rampart creation handler bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.

0050.0099	**VSD proxy loader, Unable to delete file: {0}**
Explanation	The file or directory indicated in the message could not be deleted.
Action	Determine why the file or directory could not be deleted and make it deletable.

0050.0100	**VSD proxy loader, Unable to delete directory: {0}**
Explanation	The directory indicated in the message could not be deleted.
Action	Determine why the directory could not be deleted and make it deletable.

0050.0105	**Unable to determine the fault cause. Check the log file for more information.**
Explanation	This error indicates that CloudStreams could not determine the cause for the error when trying to extract the soap fault message from the response. Additional errors, if any, would be present in the Integration Server log file (server.log).

0050.0208	**Error resolving WSDL URI. Cause {0}**
Explanation	An exception was encountered while attempting to resolve URI elements into XML source. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0209	**Error initializing virtual service factory. Cause: {0}**
Explanation	An exception was encountered while attempting to initialize XPath elements. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0210	**Error setting location of virtual service proxies directory. Path: {0} Cause: {1}**
Explanation	An exception was encountered while attempting to use the directory identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0211	**Unable to determine service endpoint URI for this service: {0} No transport listener defined for the virtual service's transport protocol.**
Explanation	The configuration context's listener manager cannot find an endpoint for the current service. This may indicate that the hosting IS does not have an appropriate listener registered.
Action	This is a configuration problem, either in IS ports or VSD

0050.0212	**Unknown exception deploying virtual service: {0} Cause: {1}**
Explanation	An exception was encountered while attempting to get an endpoint reference from the context listener manager. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0214	**Error {0} manifest from external resources associated with virtual service: {1}. Cause: {2}**
Explanation	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0215	**Error initializing virtual service transformation bean with this xslt: {0} Cause: {1}**
Explanation	An exception was encountered while attempting to read the transformation file. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0221	**CloudStreams has an internal configuration error. It's deploy-time xslt transformation file path does not exist. Path: {0}**
Explanation	An exception was encountered while attempting to read the file identified in the message. The associated exception message should include more details regarding the problem.
Action	This is a configuration problem; make sure the file identified in the message exists and contains the transformation.

0050.0235	**URI creation error: {0}**
Explanation	An exception was encountered while attempting to resolve an endpoint URI. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0250	**Could not find user-specified value for HTTP method! Defaulting to inbound request HTTP method {0}**
Explanation	The 'routing method' context variable has an invalid value.
Action	If the value indicated in the message is acceptable, no action is required. Otherwise virtual service configuration must be changed.

0050.0252	**Could not set HTTP method for outgoing request for endpoint: {0}**
Explanation	The outgoing request's message context is null.
Action	This is a virtual service/policy configuration problem.

0050.0300	**Context variable name "{0}" is already declared. Multiple declarations in the same context is not allowed.**
Explanation	Context variable names must be unique for a service.
Action	This is a service configuration problem.

0050.0303	**Attempt to reference context variable without providing a message context. Custom context variables may only be declared with a 'session' scope at this time. Other scopes are not supported.**
Explanation	Attempting to get context variable or context variable map, but the message context (or session) is null.
Action	Earlier error messages should provide clues to help determine why a valid message context is null.

0050.0306	**Context variable name is required for variable declaration.**
Explanation	Variable name validation failed, QName is null or is missing a local part.
Action	This is a context variable configuration problem.

0050.0307	**Namespace URI and prefix is required for custom variable declaration. varName: {0}**
Explanation	Variable name validation failed, Namespace URI and prefix must both be neither null nor empty.
Action	This is a context variable configuration problem.

0050.0308	**Context variable name must be a valid identifer (alpha-numeric, $, or _ permitted) Found: {0}**
Explanation	Variable name validation failed, name has invalid characters.
Action	This is a context variable configuration problem.

0050.0309	**Core Context variables cannot have a namespace or prefix as part of its declaration. varName: {0}**
Explanation	Variable name validation failed, prefix for core variables must be empty.
Action	This is a context variable configuration problem.

0050.0310	**Either a Message context or axis service name is required when creating a custom context variable. varName: {0}**
Explanation	Both service name and Axis2 message context are null, this is not acceptable. This is probably the result of attempting to deploy a service with no service name.
Action	Verify that service configuration is correct.

0050.0311	**Attempt to create a custom variable using a message context with no AxisService. varName: {0}**
Explanation	The axis2 message context is corrupted, it should identify a service.
Action	Earlier error messages should provide clues to help determine why a valid message context could not be created.

0050.0312	**Unexpected error creating custom CloudStreams context variable. varName: {0} reason: {1}**
Explanation	An exception was encountered while attempting to create a custom context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0313	**Unexpected error removing custom CloudStreams context variable for service: {0} reason: {1}**
Explanation	An exception was encountered while attempting to remove or inject a custom context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0314	**Unexpected error initializing core CloudStreams context variables. reason: {0}**
Explanation	An exception was encountered while attempting to create a context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0316	**Unexpected error getting CloudStreams context variable value. varName: {0} reason: {1}**
Explanation	An exception was encountered while attempting to get the valuue of the context variable named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0317	**Unexpected error setting CloudStreams context variable value. varName: {0}, value:{1}, reason: {2}**
Explanation	An exception was encountered while attempting to set the context variable value named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0318	**Expected a virtual service name for this method operation, but none was provided.**
Explanation	Attempting to get context variable map for a null service name.
Action	Earlier error messages should provide clues to help determine why a valid service name is null.

0050.0321	**CloudStreams context variable adapter unable to locate this type: {0}**
Explanation	The context variable type indicated in the message is unknown.
Action	This is a context variable configuration problem.

0050.0322	**Unexpected error getting core CloudStreams context variable value from adapter. type: {0}**
Explanation	An exception was encountered while attempting to get the context variable value named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0323	**Only string and int schema types are supported at this time. Type: {0}, declared with ''{1}'' context variable is not supported.**
Explanation	The context variable schema type is not among the accepted types.
Action	This is a service configuration problem.

0050.0324	**Context variable name declarations cannot contain $ sign symbols in the name since that is used as a reference operator. varName: {0}**
Explanation	Variable name validation failed, name must include substitution character, (dollar sign).
Action	This is a context variable configuration problem.

0050.0325	**Unable to return list of context variables declared for this service: {0} Reason: {1}**
Explanation	An AxisFault was encountered while attempting to retrieve a list of context variable names. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0326	**Unable to return list of context variables declared for this message context: {0} Reason: {1}**
Explanation	An AxisFault was encountered while attempting to get a list of context variables or list of variable keys. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0327	**Context variable name deployed with virtual service {0} references an unknown namespace prefix. name attribute: {1}**
Explanation	Context variable identified in message has invalid namespace.
Action	This is a context variable configuration problem.

0050.0328	**Exception while copying context variables from request to response message context. Reason: {0}**
Explanation	An AxisFault was encountered while attempting to copy context variable names between contexts. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0329	**Could not create backup directory for failed services! Dir tried = {0}**
Explanation	An attempt to create the 'failed services' directory has failed.
Action	Determine why the directory could not be created. Either fix the creation problem or specify a different directory.

0050.0331	**Error occurred when getting backup directory for path {0}**
Explanation	An exception was encountered while attempting to determine directory for backing up failed services. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0333	**Error occurred while resolving URI; message = {0}**
Explanation	An exception was encountered during URI resolution. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0337	**Previously selected {0} port {1} is no longer enabled or available!**
Explanation	The message indicates port number and type. The requested port is not available.
Action	Select a new port number for the indicated port type.

0050.0343	**Context variable API expected an IData object for ctx variable, {0}, but received this: {1}**
Explanation	The data element from which a context variable is to be extracted has an unknown data type.
Action	This is probably a flow configuration problem; where the pipeline was populated with an invalid value.

0050.0344	**Attempt to insert {0} core ctx variable with invalid value type: {1}. Expected a collection of this type: {2}**
Explanation	.The allowable data type for a core context variable is restricted, depending on variable type.
Action	.This is a context variable configuration problem.

0050.0345	**Unable to access array element [{0}] in SOAP_HEADERS core ctx variable. Cause: {1}**
Explanation	The index value indicated in the message must be numeric.
Action	This is a context variable configuration problem.

0050.0346	**Invalid array or key reference for core ctx variable. This substitution string has mismatched braces: {0}**
Explanation	The context variable substitution string is invalid, mismatched brace characters were found.
Action	This is a context variable configuration problem.

0050.0347	**Attempt to create an IData value for a ctx variable from an unsupported class type. CtxVar: {0} Bad type: {1}**
Explanation	The context variable to be converted to IData has an unknown data type.
Action	This is a context variable configuration problem.

0050.0348	**Unable to append header block to the end of the soap header. Cause: {0}, soapHeader element: {1}**
Explanation	An exception was encountered while attempting to add append new SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0349	**Unable to prepend header block to the beginning of the soap header. Cause: {0}, soapHeader element: {1}**
Explanation	An exception was encountered while attempting to add prepend new SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0350	**Unable to remove header block from the soap header. Cause: {0}, soapHeader: {1}**
Explanation	An exception was encountered while attempting to remove a SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0351	**Unable to set header block at position {0} of the soap header. Cause: {1}, soapHeader element: {2}**
Explanation	An exception was encountered while attempting to replace a SOAP header block with a new one. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0357	**Error occurred when getting STS configurations directory for path {0}**
Explanation	An exception was encountered while attempting to create the directory indicated in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0362	**Error occurred when creating STS client**
Explanation	An exception was encountered while attempting to create an STS client object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0364	**Error occurred when initializing default STS configuration store**
Explanation	An exception was encountered while attempting to create JAXB marshaller/unmarshaller pair. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0367	**Error occurred when saving STS configuration to disk**
Explanation	An exception was encountered while attempting to marshal configuration object into file. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0368	**Error occurred when reading STS configuration from file {0}**
Explanation	An exception was encountered while attempting to unmarshal configuration file indicated in the message into JAXB object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0371	**Error getting IS keystore manager instance!**
Explanation	An exception was encountered while attempting to get a reference to the keystore manager. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0373	**Error occurred when adding rampart configuration to STS policy**
Explanation	An exception was encountered while attempting to configure the STS policy. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0379 **Error occurred when adding assertion to STS policy**

Explanation An exception was encountered while attempting to add an assertion to a WS-Policy artifact. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0382 **Error occurred when adding OnBehalfOf element to WS-Trust request element**

Explanation An exception was encountered while attempting to add the WS-Trust element to a request. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0383 **Error occurred when sending WS-Trust request to STS to obtain SAML assertion**

Explanation An exception was encountered while attempting to add SAML assertion to pipeline. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0389 **Adding OnBehalfOf element in WS-Trust request for IS user {0}**

Action Info level message, no action required.

0050.0390 **Could not find base STS policy file: {0} !**

Explanation An exception was encountered while attempting to load a WS-Policy artifact from the file indicated in the message. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0391 **Error occurred when getting STS configurations! Check to see if the ISTSClientConfigManager bean is configured!**

Explanation The STS configuration manager bean could not be found.

Action This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.

0050.0394 **Error occurred when getting key aliases for keystore {0}: Error: {1}**

Explanation An exception was encountered while attempting to add a list of certificate aliases to the pipeline. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0395	**Error occurred when getting keystore handles {0}**
Explanation	An exception was encountered while attempting to add a list of keystore handles to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0396	**Error when signing SAML assertion and SOAP request body**
Explanation	An exception was encountered while attempting to sign a SAML assertion and request body. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0397	**Error occurred when adding ws-addressing headers to outbound soap request; Error: {0}**
Explanation	An exception was encountered while attempting to add WS-Addressing headers. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0400	**Using default timestamp value of 300s, because input TTL {0} is invalid (-ve or too big)**
Explanation	The input value was not valid, a default was used.
Action	If the default is acceptable, no action is required. Otherwise update the configuration.

0050.0404	**Response content type was empty! Falling back to original request content-type [{0}]**
Explanation	The response message context contained an empty 'ContentType', so the type from the original request was used.
Action	This may be acceptable. If not, then configuration update will be required.

0050.0507	**ScaDeploymentPayload.extractParts found no virtual service requests**
Action	Info level message, no action required.

0050.0508	**Unexpected exception, attempting to {0}, caught: type({1}), msg({2})**
Explanation	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0509	**ScaDeploymentPayload.extractParts - Unable to find consumer file {0}, for component {1})**
Explanation	The SCA deployment package was expected to contain a file to define the consumer identified in the message. The file was not found.
Action	This is a deployment payload construction problem.

0050.0510	**Unexpected exception, attempting to process {0} request, caught: type({1}), msg({2})**
Explanation	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0515	**ScaCompositeConfiguration found component with implementation type ({0})**
Action	Info level message, no action required.

0050.0516	**{0} - unable to convert string ({1}) to XMLGregorianDate: exception message ({2})**
Explanation	The date element from the deployment payload has an unexpected format.
Action	This is problem with the contents of the deployment payload.

0050.0517	**DeploymentPayload.{0} - input pipeline does not contain expected key ({1})**
Explanation	The deployment payload must include an element with the key indicated in the message.
Action	This is problem with the contents of the deployment payload.

0050.0519	**ScaDeploymentPayload - unable to delete temporary zip file: ({0})**
Explanation	The file indicated in the message could not be deleted.
Action	Determine why the file could not be deleted and make it deletable.

0050.0520	**DeploymentPayload - invalid request type: {0}**
Explanation	The deployment payload type is unknown.
Action	This is a deployment payload construction problem.

0050.0528	**DeploymentPayload - found null/empty virtual service descriptor for service {0}**
Explanation	The deployment payload must contain a VSD. The VSD for the service identified in the message was not found.
Action	This is a deployment payload construction problem.

0050.0603	**Error occurred when adding UsernameToken to SOAP Envelope: {0}**
Explanation	An exception was encountered while attempting to add username token to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0605	**Error occurred when adding X.509 token to SOAP Envelope: {0}**
Explanation	An exception was encountered while attempting to add X509 token to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0100.0001	**The specified node {0} could not be found.**

0100.0002	**You have specified an invalid transformer service {0} for the cloud service node {1}.**

0100.0003	**Error occurred while handling the custom service signature for the cloud service node {0}. Error is {1}.**

0100.0004	**You have specified an invalid transformer service {0} for the cloud service node {1}. The transformer service should have a signature with Input/Output prefixes.**

0100.0005	**You have specified an invalid transformer service {0} for the cloud service node {1}. The root of the transformer service signature should be a document type only.**

0101.0206	**Invalid threshold value specified during large data configuration. Please specify long value greater than '0'.**

0101.0311 **Error occurred while validating certificate "{0}". Error is "{1}"**

Explanation An error occurred while validating a certificate. This can be due to an invalid certificate or a non-existent certificate.

Action Ensure that the certificate specified is valid and exists in the filesystem.

0101.0316 **Database Publishing cannot be enabled. Configure the CloudStreams JDBC pool from the Settings > JDBC Pools page in Integration Server Administrator.**

0101.0318 **You have exceeded the maximum number of retry attempts [{0}] !**

Explanation CloudStreams has failed to establish a connection with the maximum retry counts.

0103.0041 **Failed to connect within {0} ms during a handshake with the endpoint: {1}.To view the channel meta events in the server log, configure logging level of CloudStreams Streaming component to Debug or above in Integration Server Administrator.**

0103.0090 **Proxy settings for alias "{0}" does not exist.**

Explanation The configuration for proxy alias specified in the connection alias is missing.

Action Ensure that the proxy alias specified in the connection, points to a valid proxy configuration in Integration Server.

0103.0091 **Proxy settings for alias "{0}" is disabled.**

Explanation The configuration for proxy alias specified in the connection alias is disabled.

Action Ensure that the proxy alias specified in the connection, points to an enabled proxy configuration in Integration Server.

0103.LOG_INVOCATION – Log Invocation

Explanation Write incoming event data to the server log.

0103.SERVICE_INVOCATION – Service Invocation

0103.serviceName.displayName – Service Name

Explanation Integration Server service.

0201.0047	**Large payload found for 'CollectionKey' : ''{0}'', 'Name' : ''{1}'', 'Provider' : ''{2}''. Note that large payload will not be logged into the transaction logs.**
Explanation	Request and response payloads greater than threshold size will not be logged into the transaction logs. This is to avoid flooding your DB or server logs with large payloads. Large payloads are those payloads whose length is greater than the threshold value. This value is configured at the CloudStreams server level.
Action	You can increase a default threshold value in case you want to log the payload into transaction logs. But note that the stream smaller than the threshold value will be in memory. Hence you must tune your IS JVM heap space based on your load and payload sizes.

0300.0048.description – Define any custom configurations specific to the SaaS provider.

0300.0049 OAuth Alias

0300.0049.description – Define the OAuth tokens alias to be used for the connection.

0300.0101.description – Define the required connection configurations to initiate communication with the SaaS provider.

0300.0102.description – Define configurations needed for the username and password based authentication to the SaaS provider.

0300.0103.description – Define the HTTP request header contents that will be used while making a request to a SaaS provider.

0300.0104.description – Define configurations needed for the HTTP protocol that the connection will use to connect to the SaaS provider.

0300.0126.description – Define configurations needed for Amazon web services requests requiring AWS Signature Version 2 authentication.

0300.0127.description – Indicates that the group is defined for the Amazon S3 authentication scheme and it uses the Access Key and the Secret Key of the client to authenticate the requests.

0300.0128.description – Define configurations needed for Amazon web services requests requiring AWS Signature Version 4 authentication.

0300.0129	**Invalid proxy server alias specified "{0}". Ensure that proxy server alias "{0}" exists and is valid.**
Explanation	Invalid proxy server alias is provided in the cloud connection.
Action	Ensure that proxy server alias exists and is valid.

0300.0130.description – Define the configurations needed for the OAuth version 1.0a authentication scheme.

0300.0131.description – Define configurations needed for the OAuth version 2.0 authentication scheme.

0300.0132	**'Refresh Token' value is required when "{0}" is selected as 'Refresh Request Type' for refreshing the OAuth V2.0 access token**
Explanation	'Refresh Token' is a required field when 'Refresh Access Token' is 'true' and option selected for 'Refresh Request Type' is '{0}' in the OAuth V2.0 configuration screen
Action	Specify a value for the 'Refresh Token' field

0300.0133	**'Refresh URL' value is required when "{0}" is selected as 'Refresh Request Type' for refreshing the OAuth V2.0 access token**
Explanation	'Refresh URL' is a required field when 'Refresh Access Token' is 'true' and option selected for 'Refresh Request Type' is '{0}' in the OAuth V2.0 configuration screen
Action	Specify a value for the 'Refresh URL' field

0300.0134	**'Custom ESB Service Name' value is required when "Custom ESB Service" is selected as 'Refresh Request Type' for refreshing the OAuth V2.0 access token**
Explanation	'Custom ESB Service Name' value is required when "Custom ESB Service" is selected as 'Refresh Request Type' for refreshing the OAuth V2.0 access token
Action	Specify a value for the 'Custom ESB Service Name' field

0300.bayeux_http_long_polling.displayName – Bayeux HTTP Long Polling

0300.bu.handshakeRetryInterval.displayName – Handshake Retry Interval

0300.cn.clientKeyAlias – Alias to reference a key inside a key store file

0300.cn.clientKeyAlias.displayName – Client Key Alias

0300.cn.clientKeyPassword – Overrides the value defined for ''cr.clientKeyAlias''

0300.cn.clientKeyPassword.displayName – Client Key Password

Explanation this is used to override the cn.clientKeyAlias' field value.

0300.cn.idleTimeout – Time period after which idle connections in the pool will be closed

0300.cn.idleTimeout.displayName – Idle Timeout

0300.cn.keepAliveInterval – The time period for which the connection will be kept alive, if the back-end does not return a Keep-Alive header. -1 implies that the connection will be kept alive forever.

0300.cn.keepAliveInterval.displayName – Keep Alive Interval

0300.cn.keystoreAlias – Alias for the Integration Server key store configuration

0300.cn.keystoreAlias.displayName – Keystore Alias

0300.pr.redirectStrategy – The HTTP Redirection Strategy

0300.pr.redirectStrategy.displayName – HTTP Redirection Strategy

0501.0005Error	**Error while initializing the connector ''{0}''. Details: {1}**
Explanation	An error occurred while trying to initialize the specified connection definition. The Details describe the exact cause of the error.
Action	For more information, see the Integration Server logs. Try to correct the error and reload the provider package.

0501.0009Error	**I/O exception, while trying to load manifest for connector: {0}. Details: {1}**
Explanation	An error occurred while reading the connector manifest file at the specified location. The error occurs if the manifest file is missing or corrupted, or the manifest file does not contain the required attribute definitions.
Action	Re-install the connector.

0501.0025Warning	**Duplicate definition found for operation: {0} in connector definition for: {1}. Ignoring!**
Explanation	The specified connector descriptor contains more than one operation definition against the specified name {0}. The duplicate definition will be ignored.
Action	Correct the connector descriptor and ensure that each operation name definition is unique.

0501.0028Warning	**No operations defined in the connector definition: {0}, while the WSDL model contains {1} operation(s).**
Explanation	The connector descriptor does not include any valid operation definition, while the WSDL definition contains one or more operation definitions.
Action	Include one or more valid operation definitions in the connector descriptor.

0501.0030Warning	**No abstract type defined in service: {0}. Ignoring complex type check for interaction: {1}, connector: {2}**
Explanation	One or more interactions are marked as COMPLEX, but the connector descriptor does not define any 'abstractObject' definition. The interaction will be treated as a SIMPLE interaction.
Action	Consider either including an 'abstractObject' definition for the specified service or mark the interaction type as SIMPLE.

0501.0031Warning	**Exception while populating the abstract definition for operation: {0}. Details: {1}**
Explanation	Unable to populate the abstract definition for the specified operation. The operation will be treated as SIMPLE operation.
Action	For more information, see the Integration Server log. Correct the error based on the information from the log or mark the operation type as SIMPLE.

0501.0052Error	**Unable to {0} the document type package "{1}" for connector: {2}. Details: {3}**
Explanation	The error occurred while performing the specified operation on the connector.
Action	For more information, see the Integration Server log.

0501.0080Error	**Error loading the model for resource: {0}**
Explanation	A parsing error occurred while loading the connector descriptor for the specified resource.
Action	For more information, see the Integration Server log.

0501.0082	**Unable to load resource file {0}. Details: {1}**
Explanation	Error occurred while loading the resource file or no schema definition file found at {0}. No schema validation would be performed.
Action	Ensure that the necessary XML Schema file {0} exists at the location

0501.0202Warning	**At least one connection for the connector: {0} is enabled. Disable all the connections for this connector.**
Explanation	You tried to disable a connector that contains one or more enabled connections.
Action	You must disable all the connections created for the connector, before disabling the connector.

0501.0218Warning	**No provider registered with name: {0}**
Explanation	No provider with the specified name is registered with webMethods CloudStreams.
Action	Check the provider name. Typically, the provider name is the same as the provider package name for the package that contains the connector definitions.

0501.0219Warning	**No connector registered with name: {0}**
Explanation	No connector descriptor is registered with webMethods CloudStreams for the specified identifier.
Action	Check the connector identifier. See the 'connector-Key' in the manifest.cpd file for the connector unique identifier.

0501.0224Warning	**Unable to delete the connector: {0}, the connector is enabled.**
Explanation	The connector cannot be deleted, because it is currently enabled.
Action	When you want to delete the connector, you must first disable the connector. You cannot recover a connector after deleting it and you lose all the connector-related artificats.

0501.0227Error	**Error initializing the provider registry and meta-data handler factory. Details: {0}**
Explanation	Unable to initialize and load the provider registry.
Action	For more information, see the Integration Server log.

0501.0231Error	**Error {0} provider: {1}. Details: {2}**
Explanation	The error occurred when registering or unregistering the provider.
Action	For more information, see the Integration Server log.

0501.0262	**Invalid mapping "{0}" found. Source type "{1}" and target type "{2}".**
Explanation	The specified mapping defined in the connector XML of a Provider is invalid.
Action	Correct the mapping and ensure that the source and target types are valid, and the source type supports the output to a given target type. See Administering webMethods CloudStreams guide for more details.

0501.0265	**An exception occurred while creating a connection for the connector: {0}. Details: {1}**

0501.0266	**Connection created successfully.**

0501.0267	**Connection updated successfully.**

0501.0268	**An exception occurred while updating the connection: {0}. Details: {1}**

0501.0269	**Connection deleted successfully.**

0501.0270	**An exception occurred while deleting the connection : {0}. Details: {1}**

0502.0004Error	**Error occurred while registering connection node: "{0}".**
Explanation	If the connection is enabled as per the node definition, Integration Server tries to enable the connection during restart or package reload. During this process, no connection is established with the SaaS provider and an exception occurs.
Action	Check if the connection parameters are valid and if a connection can be established using those parameters. Also, in the connector configuration file, check if the mappings and operation names/document types are configured correctly for the connection type.

0502.0006Error	**Error while unregistering connection alias: "{0}".**
Explanation	This error may occur under different circumstances. The Integration Server log contains the details of the error that explain the root cause for the error.
Action	For more information, see the Integration Server error log.

0502.0007Error	**Error while making a copy of connection alias: "{0}".**
Explanation	If you make a copy of a connection node using Designer, the copy of the source connection node might not be available in the file system.
Action	Check if the node.ndf file of the source connection node is available for read and that it is valid.

0502.0017Error	**Unable to create node "{0}" in the server namespace.**
Explanation	This error may occur under different circumstances. The Integration Server log contains the details of the error that explain the root cause for the error.
Action	For more information, see the Integration Server error log.

0502.0047Error	**Error occurred while destroying a connection instance of the alias: "{0}". Details: {1}**
Explanation	The error occurs when disabling a connection and 1/ The SaaS provider is not accessible. 2/ The logout request can not be created succesfully, because of incorrect mappings or document types specified in the connector configuration file.
Action	For more information, see the Integration Server logs.

0502.0056Error	**Updating the connection alias {0} failed because the connection is enabled. Disable the connection and try updating again.**
Explanation	The error occurs when you attempt to delete or update a connection alias when the connection is enabled.
Action	Disable the connection alias and try updating or deleting the connection again.

0502.0118	**Unable to set {0} connection state to "{1}". The following dependent listeners are enabled: [{2}]**
Explanation	Connection state cannot be changed if dependent listeners are enabled.

0502.0224	**Error occurred while initializing the connection metadata builder for the given connection ''{0}''**
Explanation	An error occurred while loading the connection metadata (connection attributes) associated with the specified connection.
Action	Ensure that all the connection attributes are valid for the specified connection. Check the server log for the Integration Server for more details.
0502.0225	**'Session Management' under 'Connection Management Properties' must be enabled when OAuth V2.0 'Refresh Access Token' is configured to 'true'**
Explanation	'Session Management' under 'Connection Management Properties' must be configured to 'idle' or 'fixed' when OAuth V2.0 'Refresh Access Token' is configured to 'true'
Action	Either configure 'Session Management' under 'Connection Management Properties' to 'idle' or 'fixed' or configure 'OAuth V2.0' 'Refresh Access Token' to 'false'
0502.0226	**'Refresh Access Token' under 'OAuth V2.0' configuration must be configured to 'true' when 'Session Management' under 'Connection Management Properties' is enabled**
Explanation	'Refresh Access Token' under 'OAuth V2.0' configuration must be configured to 'true' when 'Session Management' under 'Connection Management Properties' is configured to 'idle' or 'fixed'
Action	Either configure 'Refresh Access Token' under 'OAuth V2.0' configuration to 'true' or disable 'Session Management' under 'Connection Management Properties' by configuring it to 'none'
0503.0101	**Error while retrieving the service list from provider. Connection name ''{0}''. Details: {1}**
Explanation	The CloudStreams server cannot load the connector model for the specified connection name.
Action	Ensure that the associated connector model is valid or exists, and that the model loads without an error.
0503.0106	**Error creating CloudStreams connector service: ''{0}''. Details: {1}**
Explanation	The inputs provided or configured when creating the connector service are incomplete, invalid, or not supported. The error also occurs when the CloudStreams server is trying to load an existing CloudStreams service node that is corrupted.
Action	Ensure that the service is configured properly. If you are using a custom connector, ensure that it is valid and that the service node is not corrupted.

0503.0108	**Error occured while registering the cloud connector service {0} with connector virtual service.**
Explanation	A CloudStreams connector service is registered with a connector virtual service whenever the cloud connector service is created or updated. The registration is required for generating Analytics information.
Action	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.

0503.0109	**Unable to invoke CloudStreams connector service "{0}". Details: {1}.**
Explanation	Internal error while executing the cloud connector service.
Action	Contact Software AG Global Support.

0503.0112	**Unable to invoke CloudStreams connector service "{0}" because the associated connection "{1}" is not found.**
Explanation	The connection associated with the specified CloudStreams connector service or the connection alias passed at runtime does not exist.
Action	Ensure that the associated or specified connection exists and that the connection is enabled.

0503.0113	**Unable to invoke CloudStreams connector service "{0}" because the associated connection "{1}" is disabled.**
Explanation	The connection associated with the CloudStreams connector service or the connection alias passed at runtime exists, but is disabled.
Action	Ensure that the associated or specified connection exists and that the connection is enabled.

0503.0116	**Unable to retrieve virtual service runtime instance while executing CloudStreams connector service "{0}"**
Explanation	Internal error while executing the cloud connector service.
Action	Contact Software AG Global Support.

0503.0120	**Error occurred while invoking CloudStreams connector service "{0}" using virtual service "{1}". Details: {2}**
Explanation	Internal error while executing the cloud connector service.
Action	Contact Software AG Global Support.

0503.0121	**Error occurred while registering CloudStreams connector service "{0}" with cloud virtual service "{1}".**
Explanation	A CloudStreams connector service is registered with a connector virtual service whenever the connector service is created or updated. The registration is required for generating Analytics information.
Action	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.

0503.0122	**Error occurred while unregistering CloudStreams connector service "{0}" with cloud virtual service "{1}".**
Explanation	A CloudStreams connector service is un-registered with a connector virtual service whenever the connector service is deleted. This is required for generating Analytics information.
Action	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.

0503.0123	**Error while retrieving the default virtual service name for "{0}" based connector service. Details: {1}**
Explanation	The error occurred while retrieving the connector virtual services list because of an internal error.
Action	Ensure that WmCloudStreams package is loaded without any warnings. If the problem persists, contact Software AG Global Support.

0503.0124	**Error retrieving business object list. Connection name "{0}". Details: {1}**
Explanation	The error occurs because of one of the following reasons: 1/ The connection does not exists or is disabled. 2/ The session ID for the connection has expired. 3/ The backend is not available or it cannot be reached to retrive the metadata from the backend SaaS provider.
Action	To resolve this error, ensure that: 1/ The connection exists and is enabled. 2/ The connection is enabled and has a valid session ID. You can turn on the session management connection option. 3/ Ensure that the backend is reachable and metadata is retrieved successfully from the backend SaaS provider.

0503.0125	**Error retrieving business object description. Connection name "{0}". Details: {1}**
Explanation	The error occurs because of one of the following reasons: 1/ The connection does not exists or is disabled. 2/ The session ID for the connection has expired. 3/ The backend is not available or cannot be reached to retrieve metadata from the backend SaaS provider.
Action	To resolve the error, ensure that: 1/ The connection exists and is enabled. 2/ The connection is enabled and has a valid session ID. You can turn on the session management connection option. 3/ The backend is reachable and metadata is retrieved successfully from the backend SaaS provider.

0503.0126	**Invalid lookup service "{0}" specified.**
Explanation	Lookup services are invoked during the cloud connector service definition. The lookup services should exist in the Integration Server namespace.
Action	Ensure that the lookup service specified in the error message exists in the Integration Server namespace and it is accessible.

0503.0127	**Invalid service specification "{0}". The lookup service "{1}" must use the specification "{2}".**
Explanation	Every lookup service must implement the specified service specification.
Action	Ensure that the specified lookup service implements the required service specification.

0503.0128	**Unable to invoke CloudStreams connector service "{0}".**
Explanation	Cloud connector services access the connection from a connection pool during service invocation. The error occures when the CloudStreams framework cannot obtain a connection from a connection pool.
Action	Analyze the cloud service usage and ensure that the connection is properly configured. Also, the connection pool should have a free available connection whenever a CloudStreams connector service is invoked.

0503.0210	**Unable to load the REST service node model for "{0}".**

0503.0212	**Invalid REST resource end point:** "{0}"
Explanation	The REST resource end point is not resolved correctly. It may have entries in brackets({}) that should be resolved.
Action	Check if the required Parameters are passed during the cloud connector service execution. You can also set any default values on the "Parameter" tab in Designer.

0503.0213	**Error in ServiceDispatcher, invalid input.**
Explanation	One of the key inputs for service execution is missing, such as a connection that is enabled or a virtual service.
Action	Check if the connection exists and is enabled. In Designer, check if the virtual service is available. Also, check that the values you specified for the inputs are correct.

0503.0217	**Unable to apply mapping on CloudStreams connector service ''{0}'', for operation "{1}". Details: ''{2}''**
Explanation	Error while reading or applying the mappings.
Action	Check the mappings available in the Cloud Provider Descriptor.

0503.0233	**Could not execute the map service ''{0}''. Exception: {1}**
Explanation	The map service associated with the mapping could not be executed.
Action	Check the server log for more details.

0503.0297	**Parameter ''{0}'' is not supported for mapping because the Data Type is Record.**

0503.0513	**Unable to identify the connectorID or it is not specified.**
Explanation	ConnectorID is not specified or empty while creating the cloud connector service.
Action	Provide a valid connectorID.

0503.0514	**Unable to identify the providerName or it is not specified.**
Explanation	Provider Name is not specified or empty while creating the cloud connector service.
Action	Provide a valid provider name.

0503.0519	**Invalid InteractionHandler implementation {0} specified for the interaction name {1}. Note that if the interaction type is {2} then InteractionHandler must implement the abstract class {3}.**
Explanation	Interaction implementation can be externalised to Java based implementation. If the interaction is involved with multiple business objects, then the connector developer should leverage the built in abstract implementation class. This abstract implementation can generate the input and output cloud service based on various property configurations. Internally CloudStreams server generates the signature based on various templates. These internal templates read the multiple properties and generates the signatures.
Action	Ensure that the implementation class specified, extends the mentioned abstract InteractionHandler class.

0504.0039	**Subscription details are not available. Update the subscription from the Service Development perspective in Software AG Designer before enabling the CloudStreams connector listener.**
Action	Update the listener node and select a subscriber from the available list of subscribers.

0550.0001	**Error while creating Connection "{0}".**
0550.0002	**Error while deleting Connection "{0}".**
0550.0003	**Error while retrieving details for Connection "{0}".**
0550.0004	**Error while updating Connection "{0}".**
0550.0005	**Error while checking for Connection "{0}".**
0550.0006	**Error while fetching list of Connections.**
0550.0007	**Error while creating Connector "{0}".**
0550.0008	**Error while deleting Connector "{0}".**
0550.0009	**Error while retrieving details for Connector "{0}".**
0550.0010	**Error while updating Connector "{0}".**
0550.0011	**Error while fetching manifest content for Connector "{0}".**
0550.0012	**Error while fetching list of Connectors.**
0550.0013	**Error while loading model for Connector "{0}".**
0550.0014	**Error while creating REST Resource "{0}".**

0550.0015	**Error while deleting REST Resource "{0}".**
0550.0016	**Error while updating REST Resource "{0}".**
0550.0017	**Error while retrieving details for REST Resource "{0}".**
0550.0018	**Error while checking for REST Resource "{0}".**
0550.0019	**Error while fetching list of REST Resources.**
0550.0020	**Error while creating Provider "{0}".**
0550.0021	**Error while updating Provider "{0}".**
0550.0022	**Error while deleting Provider "{0}".**
0550.0023	**Error while retrieving details for Provider "{0}".**
0550.0024	**Error while fetching list of Providers.**
0550.0025	**Error while creating Service "{0}".**
0550.0026	**Error while deleting Service "{0}".**
0550.0027	**Error while retrieving details for Service "{0}".**
0550.0028	**Error while updating Service "{0}".**

0550.0029	**Error while checking for Service "{0}".**
0550.0030	**Error while fetching list of Services.**
0550.0031	**{0} "{1}" already exists.**
0550.0032	**{0} "{1}" not found.**
0550.0033	**Error during {0} operation for {1} "{2}".**
0550.0034	**Error during {0} operation for {1}.**
0550.0035	**Error loading {0} "{1}".**
0550.0036	**"{0}" is a required input.**
0550.0037	**"{0}" is a required input when {1}.**
0550.0038	**Invalid input "{0}" for "{1}". Valid values are {2}.**
0550.0039	**Creating Connection "{0}".**
0550.0040	**Created Connection "{0}".**
0550.0041	**Deleting Connection "{0}".**
0550.0042	**Deleted Connection "{0}".**

0550.0043	**Retrieving details for Connection "{0}".**
0550.0044	**Updating Connection "{0}".**
0550.0045	**Updated Connection "{0}".**
0550.0046	**Checking for Connection "{0}".**
0550.0047	**Listing Connections.**
0550.0048	**Creating Connector "{0}".**
0550.0049	**Created Connector "{0}".**
0550.0050	**Deleting Connector "{0}".**
0550.0051	**Deleted Connector "{0}".**
0550.0052	**Retrieving details for Connector "{0}".**
0550.0053	**Updating Connector "{0}".**
0550.0054	**Updated Connector "{0}".**
0550.0055	**Checking for Connector "{0}".**
0550.0056	**Listing Connectors.**

0550.0057	**Creating REST Resource "{0}".**
0550.0058	**Created REST Resource "{0}".**
0550.0059	**Deleting REST Resource "{0}".**
0550.0060	**Deleted REST Resource "{0}".**
0550.0061	**Retrieving details for REST Resource "{0}".**
0550.0062	**Updating REST Resource "{0}".**
0550.0063	**Updated REST Resource "{0}".**
0550.0064	**Checking for REST Resource "{0}".**
0550.0065	**Listing REST Resources.**
0550.0066	**Creating Provider "{0}".**
0550.0067	**Created Provider "{0}".**
0550.0068	**Deleting Provider "{0}".**
0550.0069	**Deleted Provider "{0}".**
0550.0070	**Retrieving details for Provider "{0}".**

0550.0071	**Updating Provider ''{0}''.**
0550.0072	**Updated Provider ''{0}''.**
0550.0073	**Checking for Provider ''{0}''.**
0550.0074	**Listing Providers.**
0550.0075	**Creating Service ''{0}''.**
0550.0076	**Created Service ''{0}''.**
0550.0077	**Deleting Service ''{0}''.**
0550.0078	**Deleted Service ''{0}''.**
0550.0079	**Retrieving details for Service ''{0}''.**
0550.0080	**Updating Service ''{0}''.**
0550.0081	**Updated Service ''{0}''.**
0550.0082	**Checking for Service ''{0}''.**
0550.0083	**Listing Services.**
0550.0084	**Unable to load connection manager factory: {0}.**

0550.0085	**''{0}'' is not a supported Connector type.**
0550.0086	**Error while publishing provider ''{0}''.**
0550.0087	**Error while installing provider ''{0}''.**
0550.0088	**Enter a valid Package Name.**
0550.0089	**Development package for provider ''{0}'' does not exist.**
0550.0090	**Could not create the Provider package under ''{0}''.**
0550.0091	**Publishing the package for Provider ''{0}''...**
0550.0092	**Package published for Provider ''{0}''.**
0550.0093	**Installing Provider ''{0}''...**
0550.0094	**Installed Provider ''{0}''.**
0550.0095	**Creating a temporary folder for provider ''{0}'' under ''{1}''...**
0550.0096	**Moving the Provider artifacts under ''{0}''...**
0550.0097	**Copying the file ''{0}'' under ''{1}''...**
0550.0098	**Creating the package zip file for provider ''{0}''...**

0550.0099 **Moving the provider package ''{0}'' to ''{1}''...**

0601.0002 **Error:{0}**

Explanation An exception occurred while parsing the fetched data from database

Action Check whether CloudStreams 'JDBC Pool alias ' is configured properly

Add_Group **Add Group...**

AuditLogger_Editor_Name – Logged Fields

Bundle-Name **CloudStreams Service Editors**

Bundle-Vendor **Software AG**

BusinessObjectPage_Available_Obj_Label – Available Business Objects

BusinessObjectPage_FIlter_Text – type filter text

CLS.0010.0014E **PolicyGateway.shutdownMyService - Unable to remove service:{0}. Error:{1}**

Explanation A virtual service was not completely removed during CloudStreams package unload.

Action No action is necessary if the error occurred while the Integration Server was shutting down.

CLS.0010.0020W **Consumer file [{0}] could not be found! Could not load Consumer information into CloudStreams.**

Explanation Consumer definitions defined in the CloudStreams admin are persisted in an XML file in a directory under the WmCloudStreams package.

Action No action is necessary if no consumers have been defined; otherwise, please contact support.

CLS.0010.0062E	**Unable to get the password for callback identifier: {0}**
Explanation	Error while retrieving the cleartext password from the encrypted passman file store.
Action	Review the CloudStreams STS configuration, else this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the Integration Server Administrator's package management menu > WmCloudStreams package's list of services, if available.

CLS.0010.0083W	**Non-fatal CloudStreams package initialization error. {0}, {1}**
Explanation	CloudStreams encountered an error during an upgrade processing step, after the package initialization has completed.
Action	Verify whether the overinstall upgrade steps were followed as defined in the documentation, else this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0010.0085E	**CloudStreams - Unable to find ClusterStateCache**
Explanation	CloudStreams defines a cache for this information even when the product is not clustered.
Action	Contact support.

CLS.0010.0190E	**Error initializing CloudStreams keystore manager's keystore. Path:{0}, Cause: {1}**
Action	Verify whether a valid keystore file exists for this path and the file permissions allow for the Integration Server to read the file.

CLS.0010.0212E	**Endpoint connection timeout duration expected as a number but was not a number ({0})**
Explanation	A virtual service was deployed with an invalid connection timeout specified for its native provider endpoint.
Action	Review the advanced endpoint configuration in CentraSite and redeploy the service if necessary.

CLS.0010.0214E	**Either both keystore and key alias must be specified or none for the SSL configuration; KeyStore alias = [{0}]; Key alias = [{0}]**
Explanation	A virtual service with a native provider SSL endpoint was deployed with an invalid advanced endpoint configuration. The endpoint must have a valid alias for both the keystore file and the keystore entry aliases as defined in the Integration Server, or it can have no aliases defined at all.
Action	Update the advanced endpoint configuration and redeploy the virtual service to CloudStreams.

CLS.0010.0217E	**Error occurred while getting the password for handle {0} from the passman.**
Explanation	An attempt to retrieve a cleartext password from a passman encrypted file store failed.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0010.0218E	**Error occurred when storing the password for handle {0} in the passman.**
Explanation	An attempt to save a password in a passman encrypted file store failed during CloudStreams STS configuration.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloustreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0010.0220E	**Error while converting the given WS-Policy component to string.**
Explanation	Cloudstreams was unable to parse policy elements used in producing request security tokens (RST) to a configured security token service (STS).
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0010.0702E	**CloudStreams upgrade/migration has been interrupted due to an error. Details: {0}**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. It indicates that the upgrade was not successful and further actions are required.
Action	Depending on the error message, the following options are available: 1) Resolve the issue which is causing the upgrade to fail and then restart the Integration Server to see if the upgrade completes successfully. 2) Delete the cloudstreamsUpgrade.xml file from the installation path: ${IS_HOME}/packages/WmCloudStreams/ directory. This is the file that causes CloudStreams to perform its upgrade step. If this action is taken, the CloudStreams configuration will have to be re-entered manually through the Integration Server Administrator's UI. 3) Contact Support. Whenever the Integration Server is restarted, CloudStreams will attempt to perform an upgrade as long as its cloudstreamsUpgrade.xml file is present in the package directory.

CLS.0010.0706E	**CloudStreams Upgrade, unable to read required file. {0}**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. This message implies that the OS user running the Integration Server does not have adequate permissions to read the file referenced in the error message.
Action	Review user and file permissions and make necessary adjustments to ensure the file can be read.

CLS.0010.0707E	**During CloudStreams upgrade, a configuration file is missing a required entry element key attribute. {0}, File path: {1}**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The cloudstreamsUpgrade.xml file used to control a CloudStreams overinstall upgrade is corrupted. It is missing a reference to an attribute containing a path to an archive of the previous CloudStreams version, prior to the overinstall.
Action	Contact Support.

CLS.0010.0708E	**During CloudStreams upgrade, a configuration file entry element key attribute is not as expected: {0}, expected this value: {1}, but found: {2}, File path: {3}**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The cloudstreamsUpgrade.xml file used to control a CloudStreams overinstall upgrade is corrupted.
Action	Contact Support.

CLS.0010.0709E	**CloudStreams Upgrade, unable to find the required file. Expected location: {0}**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The backup file archive containing the CloudStreams package prior to the overinstall upgrade cannot be found.
Action	Contact support.

CLS.0010.0711E	**CloudStreams Upgrade, unable to delete configuration file. CloudStreams upgrade task will continue to execute after each Integration Server startup until this file is removed. Path: {0}**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. Verify that the OS user account running the Integration Server has the necessary permissions to delete the file.
Action	If the log messages suggest the upgrade ran successfully, this file can be deleted; otherwise, contact support.

CLS.0010.0712E	**During CloudStreams upgrade, a configuration file is not a valid xml. Unable to parse it. {0}, Details: {1}**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The cloudstreamsUpgrade.xml file is corrupted.
Action	Contact Support.

CLS.0010.0717W	**CloudStreams Upgrade, Could not find Default STS configuration file: {0} in archived zip file**
Explanation	The default STS configuration file was not found when performing an overinstall upgrade.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the CloudStreams package's list of services in IS Admin's package management menu if available.

CLS.0010.0718E	**During CloudStreams upgrade, a configuration file has an unexpected element key attribute, {0}, with value. {1}. The configuration file path is: {2}**
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The cloudstreamsUpgrade.xml file is corrupted.
Action	Contact Support.

CLS.0010.0719E	**CloudStreams Upgrade, Could not find Default STS configuration file: {0} following upgrade; Skipping migrating configuration data!**
Explanation	CloudStreams was unable to locate the default STS configuration file during an overinstall upgrade.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in IS Admin's package management menu if available.

CLS.0010.0720W	**CloudStreams Upgrade, Could not load Default STS client configuration; Skipping migrating configuration data**
Explanation	The default STS configuration file was not found when performing an overinstall upgrade.
Action	This is an internal error. Contact Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in IS Admin's package management menu if available.

CLS.0050.0279D	**Callback not removed for message id, "{0}". Receiver: {1}, Properties: {2}**
Explanation	When a service is invoked, the state for the invocation is stored in a callbackStore map until the response is returned. The callback object was not found in the map for the given message id.
Action	No action is necessary unless memory runs low. In that event, please contact support.

CLS.0050.0280D	**Message receiver not found for message id: "{0}", Properties: {1}**
Explanation	Synapse callback receiver used to process the provider response is not found.
Action	Please contact support.

CLS.0050.0281D	**Outbound message id not found. "{0}", Properties: {1}**
Explanation	The message id used to correlate a native provider request was not found.
Action	Please contact support.

CLS.0050.0408E	**Authentication failed for user {0}**
Explanation	Invalid basic authentication credentials were included in the Authorization header sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
Action	The web service consumer should include proper credentials and resend the service request.

CLS.0050.0608E	**Error occurred when adding Timestamp to SOAP Envelope: {0}**
Explanation	CloudStreams was unable to insert a WS security timestamp element to the request's security header sent to the native provider.
Action	Review the configured ESB "AddTimestamp" service call for virtual service and redeploy if incorrect, else this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0070.0010E	**Incoming SOAP request does not contain the 'Authorization' header. This service requires the HTTP Basic Authentication token to be present!**
Explanation	No Authorization header was sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
Action	The web service consumer should include proper credentials and resend the service request.

CLS.0070.0032E	**Unable to create Schema for this service ''{0}''. Schema validation may not succeed.**
Explanation	CloudStreams was unable to initialize the schema parser for a virtual service with a "Validate Schema" runtime policy. This error occurs when a consumer sends CloudStreams a service request.
Action	Review the schemas defined in the virtual service, make corrections, and then redeploy the virtual service if necessary; otherwise, this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0070.0071W	**The ESB service name specified for InvokeESB cloudstreams cannot be empty.**
Explanation	A virtual service was deployed containing an ESB service invocation step containing an invalid or missing service name.
Action	Review all service invocations from the "Processing steps" configuration for the virtual service, and redeploy if necessary.

CLS.0070.0072E	**The 'service' attribute is required for the InvokeESB cloudstreams definition.**
Explanation	The deployed virtual service configuration is corrupted.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0070.0073W	**Did not invoke ESB service, because the service name was either empty or invalid (must be of the form folder1.folder2:service)**
Explanation	A virtual service was deployed containing an ESB service invocation step with an invalid or missing service name.
Action	This warning is logged when a virtual service request is executed. See the action defined for CLS.0070.0071.

CLS.0070.0074E	**Unknown mediator : {0}**
Explanation	Synapse mediators are used in the "In Sequence", "Out Sequence", and "Error Sequence" steps defined for virtual services. These Mediators are predefined and registered in CloudStreams.
Action	Contact Support.

CLS.0101.0099D	**Unable to remove session context for connector service with this session token. "{0}"**
Explanation	The CloudStreams transport listener should remove the session context for a connector service when it is no longer needed.
Action	Please contact support if available IS heap memory runs low.

CLS.0102.0056E	**Package name and service name must be specified for deploying service(s).**
Action	Verify whether the service has an associated package and then redeploy; otherwise, contact Support.

CLS.0102.0057E	**Unable to deploy. A virtual service with the name "{0}" already exists in the package "{1}".**
Action	Confirm whether the package association is correct and consider undeploying previous virtual services before deployment. Otherwise, contact Support.

CLS.0200.0045E	**Error saving EhCache configuration file: {0}**
Explanation	CloudStreams was unable to save its configuration file used for the Terracotta cache component.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0200.0046E	**Could not find the specified EhCache configuration file: {0}**
Explanation	The Terracotta cache configuration file for CloudStreams caches could not be found during package startup.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0201.0003E	**PgMen incoming handler found no sie event for {0}, mep: {1}**
Explanation	A service invoke event (sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.
Action	The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.

CLS.0201.0004E	**Exception in Outgoing fault handler while creating sie. serviceName: {0} cause: {1}**
Explanation	An error occurred while trying to create a service invoke event (sie) in a policy engine's Axis2 fault handler.
Action	The original service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.

CLS.0201.0005E	**Unable to create an sie event in outgoing fault handler. serviceName: {0}**
Explanation	A service invoke event (sie) contains basic attributes of a service invocation. The sie should have been created by this or another Axis2 handler, but it was not or is no longer accessible.
Action	The original service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.

CLS.0201.0006E	**PgMen incomingHandler found an event with unexpected state {0}**
Explanation	The policy engine relies on Axis2 handlers executing during specific phases in order to capture all the attributes of a service invocation. These attributes are stored in a service invoke event (sie) for each inbound or outbound phase.
Action	The sie data for this specific service invocation may be corrupted. The data contained in dependent policy engine events may be affected. Contact support.

CLS.0201.0007E	**Exception in incomingHandler. msgId: {0} details {1}**
Explanation	An error occurred while executing a policy engine Axis2 handler.
Action	A service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.

CLS.0201.0008E	**PgMen incoming handler had no service name in message context for this msgId {0}**
Explanation	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.

CLS.0201.0011E	**PgMen incoming handler could not find service operation in axis2 message context. Service name: {0}**
Explanation	The inbound policy engine Axis2 handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service operation was not identified for this service request, the invocation will not be tracked by the policy engine.

CLS.0201.0013E	**PgMen outgoing handler found an event with unexpected state {0}, sie Dump: {1}**
Explanation	The policy engine relies on Axis2 handlers executing during specific phases in order to capture all the attributes of a service invocation. These attributes are stored in a service invoke event (sie) for each inbound or outbound phase.
Action	The sie data for this specific service invocation may be corrupted. The data contained in dependent policy engine events may be affected. Contact support.

CLS.0201.0015E	**Policy {0} forbids invocation of service {1} for scope {2}**
Explanation	This service invocation was rejected because a policy rule was breached in the policy engine.
Action	No action is necessary.

CLS.0201.0016E	**PgMen outgoing handler expected service {0} and invokeId: {1}, but cached event had {2} and {3}**
Explanation	The invocation id for this execution thread's handler does not match the id that is stored on the current service invocation event (sie).
Action	This error suggests that data corruption may have occurred. Please contact support.

CLS.0201.0017E	**PgMen outgoing handler had no service name in message context for this msgId {0}**
Explanation	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.

CLS.0201.0018E	**Axis service object not found in message context.**
Explanation	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.

CLS.0201.0023W	**No native service provider endpoint for {0}.**
Explanation	The policy engine's Axis2 outbound handlers found no endpoint reference in message context.
Action	No further action is necessary if an endpoint was located at a later point during execution and the service was invoked.

CLS.0201.0024E	**Exception caught while constructing the reason expression: {0}**
Explanation	An error occurred while processing a virtual service's error sequence step.
Action	No further action is necessary. The soap fault will be returned without the fault's reason content.

CLS.0201.0034W	**BaseHandler - No PolicyViolationDetector found, skipping analysis**
Explanation	The spring component for detecting policy violations is missing.
Action	Verify the WmCloudStreams package loaded successfully; otherwise please contact support to verify the CloudStreams spring configuration is not corrupted.

CLS.0201.0040E	**PgMen incoming event handler encountered an error executing PgMen outgoing FAULT handler. Cause: {0}**
Explanation	An error occurred while processing one of the Axis2 fault handlers used by the policy engine during a service invocation.
Action	A service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.

CLS.0201.0041E	**PgMen outgoing handler could not find service operation in axis2 message context. Service name: {0}**
Explanation	The outbound policy engine Axis2 handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service operation was not identified for this service request, the invocation will not be tracked by the policy engine.

CLS.0201.0042E	**PgMen outgoing FAULT handler could not find service operation in axis2 message context. Service name: {0}**
Explanation	The outbound policy engine Axis2 fault handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service operation was not identified for this service request, the invocation may not be accurately tracked by the policy engine.

CLS.0201.0043E	**PgMen outgoing handler encountered error publishing an event. Missing sie event.**
Explanation	A service invoke event (i.e. sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.
Action	The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.

CLS.0201.0044E	**PgMen outgoing handler encountered error publishing an event. sie event is missing service name.**
Explanation	A service invoke event (i.e. sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.
Action	The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.

CLS.0201.0046E	**No UUID generator bean (bean id={0}) configured, using java.util.UUID**
Explanation	The spring configuration is missing an expected component for UUID generation.
Action	CloudStreams is falling back to an alternate UUID factory; however, this error suggests the configuration may be corrupted. Verify the WmCloudStreams package loaded successfully; otherwise, please contact support to verify.

CLS.0202.0003E	**Cannot create a PolicyEnforcer using a null/empty service name {0}**
Explanation	A virtual service must be associated to a policy before it may be applied at runtime.
Action	Verify the policy configuration filter is correct, the policy is active, and redeploy the affected virtual services.

CLS.0202.0004E	**Cannot create a PolicyEnforcer using a null PolicyInfo reference**
Explanation	The policy enforcer is a runtime object that requires a policy info configuration element.
Action	This should not happen under normal circumstances. Please contact support.

CLS.0203.0062E	**ControllingNodeLocker.run, thread id({0}), expected Ehcache, found ({1})**
Explanation	Unexpected content was returned in the Terracotta cluster status cache.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0065E	**ControllingNodeLocker.run, thread id({0}), caught ({1}/{2}) attempting to get a lock, thread dies.**
Explanation	CloudStreams encountered an error trying to obtain a lock on the controlling node in a Terracotta cluster.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0070I	**ClusterStatusCache - cache manager for {0} returned null CacheCluster reference. Not clustered.**
Explanation	CloudStreams was unable to obtain a reference to the configured Terracotta cluster.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0071I	**{0} - getCluster(ClusterScheme.TERRACOTTA) threw exception {1}, using schema NONE**
Explanation	An attempt to get Terracotta cluster configuration details failed.
Action	If CloudStreams is configured for a Terracotta cluster, this is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0072E	**ClusterStatusCache - thread id({0}) attempts to release {1} lock, but does not hold it.**
Explanation	An attempt to release the lock on the node controller in a Terracotta cluster failed.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0073E	**Error initializing JAXB Context: {0}**
Explanation	Initialization for the cached global or registered consumers deployed to CloudStreams has failed.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0075E	**ControllingNodeLocker.run, thread id({0}), caught {1} attempting to ask about lock status, thread dies.**
Explanation	The thread defining the controlling node in a CloudStreams cluster encountered an error.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0076E	**Unable to get the cache named {0} from the cache manager {1}**
Explanation	CloudStreams encountered an error while accessing one of the Terracotta caches.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0081E	**{0}, thread id({1}), caught {2}/{3} attempting to release lock. Thread dies.**
Explanation	CloudStreams encountered an error while releasing the lock on the controlling node in the Terracotta cluster.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0082E	**EhcacheClusterStatusCache, thread id({0}), caught {1}/{2} attempting to update the controlling lock in the cache.**
Explanation	CloudStreams encountered an error while updating the controlling node in a Terracotta cluster.
Action	This is an internal error. Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0203.0100W	**Thread interrupted when trying to obtain {0} lock for the cache {1}**
Explanation	While CloudStreams was attempting to obtain a lock on a cache entry key, its thread was interrupted.
Action	No action is necessary if CloudStreams is functioning normally.

CLS.0203.0101E	**Unable to {0} lock the {1} cache for key {2} after waiting {3} ms**
Explanation	CloudStreams failed to lock a cache key in the expected time period.
Action	No action is necessary if CloudStreams is functioning normally

CLS.0203.0103E	**{0} task in thread {1} threw this: {2}**
Explanation	During CloudStreams shutdown, an error occurred in the controlling node of a Terracotta cluster.
Action	Contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0204.0008E	**Unable to access spring bean config bean : {0}. Is there a problem with CloudStreams spring config file?**
Explanation	The interval manager thread pool is missing from its spring configuration file.
Action	Contact support.

CLS.0204.0013W	**No value defined in {0} cache for this key: {1}**
Explanation	The policy engine's interval manager component creates and updates a global interval counter that is used for both clustered and non-clustered installations.
Action	It is normal for this warning to appear once or twice when the WmCloudStreams package is reloaded or during Integration Server startup. If this warning message continues to occur, verify the WmCloudStreams package loaded successfully; otherwise, please contact support.

CLS.0205.0062E	**UddiPerformanceMetricsSender - unable to publish metrics over UDDI for service: {0}, message: {1}**
Explanation	This log message is produced when CloudStreams is unable to publish performance metrics results to CloudStreams. When reviewing the content, note that some exception details may have originated from the CentraSite product hosting the UDDI server. Errors can range from improper CloudStreams configuration, OS resource issues, network connectivity, or issues with the CentraSite installation.
Action	Depending on the errors logged in the CloudStreams UI, one of the following actions may prove more relevant: (1) Verify whether the CentraSite configuration information regarding UDDI is correct for the CloudStreams UI. (2) Verify whether the hostname or IP address is reachable from the computer running the CloudStreams instance. (3) Verify whether the CentraSite instance and its repository is up and accessible.

CLS.0205.0063E	**Unable to initialize UddiClientAdapter due to a missing password for username: {0}.**
Explanation	This log message is produced when CloudStreams is unable to publish performance metrics results to CloudStreams. A password was not found in the encrypted store for the user, configured in the CentraSite panel of the CloudStreams UI.
Action	Verify whether the password is entered and the configuration was successfully saved for the CentraSite configuration screen in the CloudStreams UI.

CLS.0205.0064E	**Error connecting to the CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}**
Explanation	This log message may be produced under the following situations: (1) During CloudStreams package startup. (2) CentraSite configuration entered in the CloudStreams UI is saved, but a connection to the UDDI server fails for these settings. (3) CloudStreams attempts to publish performance metrics but fails during its regular scheduled interval.
Action	Verify whether CentraSite configuration values in the CloudStreams UI are correct and CentraSite is up and running.

CLS.0205.0067E	**Error disconnecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}**
Explanation	This log message may be seen during the following situations: (1) During CloudStreams package shutdown. (2) While CloudStreams is initializing communications with the CentraSite UDDI server after encountering an error during runtime or saving configuration values in the CloudStreams UI.
Action	Refer the "Action" text for 0205.0064.

CLS.0205.0602E	**Missing ''{0}'' JDBC destination pool from spring configuration.**
Explanation	A CloudStreams configuration file may be corrupted and a necessary configuration element may be missing.
Action	Contact Support.

CLS.0205.0603E	**Jdbc destination sender expected a JdbcEvent object but received: ''{0}''**
Explanation	The JDBC destination sender event component received an unexpected event type.
Action	Contact Support.

CLS.0205.0604E	**JDBC destination sender encountered an SQL Exception while generating ''{0}'' events. Error Code: {1} Cause: {2}**
Explanation	The CloudStreams JDBC destination sender component encountered an SQL exception while sending a runtime event.
Action	Verify whether the CloudStreams functional alias in the Integration Server Administrator is configured for a JDBC pool. Verfiy whether the database is operational and then restart the functional alias pool. Verify whether the CloudStreamsEvents database component tables installed using the Common Database Component are still defined, and the JDBC pool credentials and URL defined in the Integration Server are correct. If it still fails, contact Support.

CLS.0205.0605D	**JDBC destination sender took {0} ms to get a connection out of the data source.**
Explanation	If the '0205 MEN - Events' CloudStreams logging component is set to 'DEBUG', CloudStreams issues a log message if the time it takes to get a JDBC connection exceeds a predefined threshold as defined in the CloudStreams pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.

CLS.0205.0606D	**JDBC destination sender took {0} ms to get a prepared statement out of connection with this SQL: {1}.**
Explanation	If the '0205 MEN - Events' CloudStreams logging component is set to 'DEBUG', then CloudStreams issues a log message if the time it takes to get a JDBC prepared statement exceeds a predefined threshold as defined in the CloudStreams pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.

CLS.0205.0609D	**JDBC destination sender took {0} ms to close the prepared statement and connection.**
Explanation	If the '0205 MEN - Events' CloudStreams logging component is set to 'DEBUG', then CloudStreams issues a log message if the time it takes to close a JDBC connection exceeds a predefined threshold as defined in the CloudStreams pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.

CLS.0205.0610E	**JDBC event requires at least one SQL clause to be valid.**
Explanation	The CloudStreams JDBC component is in an invalid state.
Action	Contact Support.

CLS.0205.0611D	**JDBC destination sender took {0} ms to insert a batch of {1} "{2}" events. AutoCommit enabled on driver? {3}, Transaction Isolation level? {4}**
Explanation	If the '0205 MEN - Events' CloudStreams logging component is set to 'DEBUG', then CloudStreams issues a log message if the time it takes to execute a batch of runtime event inserts into the database, exceeds a predefined threshold as defined in the CloudStreams pg-jdbc.xml file. The current default is 500 milliseconds.
Action	No action is necessary unless the time is extremely large. In that case, consider reducing the 'pg.jdbc.batchSize' property in the CloudStreams pg-config.properties file. This will cause the JDBC destination sender to send updates to the database server in smaller batches.

CLS.0205.0612E	**The JDBC event formatter expected {0} but received: {1}**
Explanation	The CloudStreams JDBC component received an unexpected event type, so it was unable to produce the event.
Action	Contact Support.

CLS.0205.0614E	**The JDBC event SQL range should be between 0 and {0}, {1} is out of range.**
Explanation	The CloudStreams JDBC component is in an invalid state.
Action	Contact Support.

CLS.0205.0615E	**The JDBC performance metrics processor expected only one return key, but "{0}" were found.**
Explanation	The CloudStreams JDBC component is in an invalid state.
Action	Contact Support.

CLS.0205.0616E	**The JDBC performance metrics processor expected two SQL statements, but "{0}" were found.**
Explanation	The CloudStreams JDBC component is in an invalid state.
Action	Contact Support.

CLS.0205.0617E	**The JDBC performance metrics processor is missing the returned primary key upon SQL insert.**
Explanation	The database did not return the 'event_pk' primary key column for the event inserted into the cloudstreams_metrics_event table.
Action	Verify whether the database is functioning properly; otherwise, contact Support.

CLS.0205.0618E	**Jdbc event is in a bad state. Data type count "{0}" does not equal column value count "{1}"**
Explanation	The Jdbc event destination component is in an invalid state.
Action	Contact Support.

CLS.0205.0619W	**Jdbc driver doesn't support returned named SQL columns from Insert statement. Trying "Statement.RETURN_GENERATED_KEYS" mode.**
Explanation	The Jdbc event destination component will attempt to use named columns for returning the database-generated primary key after inserting a row. If the database driver does not support this feature, this log message is raised, and the component will use another method to return the inserted primary key.
Action	No action required unless other SQLException errors are raised.

CLS.0206.0035W	**MAC cache update {0} operation took {1} ms to complete for {2} SIEs. This could cause lock attempts for tallying metrics statistics in MAC cache to fail.**
Explanation	An update to the policy engine metrics data took longer than expected. When the duration of this task is longer than the configured lock request timeout, tasks can be lost when they fail to obtain exclusive locks.
Action	Review the Integration Server performance, increase the advanced property for lock timeout pg.PgMenSharedCacheManager.lockTimeOut, and the restart Integration Server. Otherwise, if this happens very frequently, contact Support. Produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in the Integration Server Administrator's package management menu, if available.

CLS.0207.0002E	**DCPool spring configuration {0} missing a workQueue property? No workQueue was instantiated.**
Explanation	The referenced policy engine thread pool is missing its in-memory work queue configuration.
Action	Possibly the *-pgmen.xml spring configuration file is corrupted. Contact support.

CLS.0207.0003E	**Work queue capacity must be greater than 0. Value {0} is invalid.**
Explanation	One of the advanced configuration properties in the *-config.properties file has an invalid queue size.
Action	These values are not exposed in the admin UI. Review the values in the pg-config.properties or wst-config.properties file and verify the policy engine work queue sizes are greater than 0.

CLS.0207.0009W	**{0} thread pool shutdown - caught {1} while awaiting pool termination.**
Explanation	A policy engine pool's thread was interrupted while waiting for graceful shutdown to complete.
Action	No action is needed.

CLS.0300.0001E	**"{0}" is an unknown connection factory alias**
Explanation	The classname specified in wst-core.xml spring bean configuration for the implementation map of the 'clientConnectionFactoryManager' bean is not in the classpath.
Action	Contact support.

CLS.0300.0002E **Class "{0}" for alias "{1}" does not implement the IConnectionManager interface.**

Action Contact Support.

CLS.0300.0003E **"{0}" is an unknown connection pool alias.**

Action Contact Support.

CLS.0300.0004E **Unknown configuration group alias, "{0}"**

Explanation A CloudStreams connector descriptor has a configurable group in its connection configuration that is not valid for the connection manager.

Action Contact support.

CLS.0300.0007E **Error creating connection alias "{0}".**

Explanation A CloudStreams connection manager had an error during its initialization phase.

Action Contact support.

CLS.0300.0010E **Unknown field key "{0}" from connection factory alias "{1}"**

Explanation All managed connection configuration fields must have a unique key name including custom configuration fields. 'cn.providerURL' is an example.

Action Review CloudStreams connector configuration to locate source of the unknown field name.

CLS.0300.0011E **Attempt to unregister an unregistered connection configuration instance, "{0}"**

Action Contact Support.

CLS.0300.0012E **Attempt to reference an unregistered connection configuration instance, "{0}"**

Action Contact Support.

CLS.0300.0013T **Duplicate field "{0}" exists in configurable group "{1}" of connection factory**

Explanation Each managed connection configuration field may only exist once for the select configurable groups.

Action In normal cases, some common fields are shared across groups intended to be mutually exclusive (e.g. Amazon Web Service groups) when used with service configurations.

CLS.0300.0014E	**Duplicate custom field "{0}" exists in configurable group "{1}" of connection factory**
Explanation	Each managed connection configuration custom field must have a unique key name associated with it.
Action	Review all custom configuration fields created in CloudStreams and verify each name is unique.

CLS.0300.0016E	**Unexpected connection configuration implementation type, {0}**
Action	Contact Support.

CLS.0300.0017W	**Error {0}, while releasing resources for connection configuration "{0}"**
Explanation	An error was encountered while releasing a managed connection pool instance during connection manager shutdown.
Action	No action is necessary.

CLS.0300.0019E	**Invalid HTTP method selected, "{0}"**
Explanation	An invalid HTTP method was referenced.
Action	Locate the source of the invalid method and change it to a valid HTTP method.

CLS.0300.0020E	**Unknown service method implementation: {0}**
Action	Contact Support.

CLS.0300.0021E	**Missing connection configuration alias is required.**
Explanation	CloudStreams connector services must have a configured managed connection alias.
Action	Configure or recreate the connector service so it has a managed connection pool alias.

CLS.0300.0022E	**Connection configuration alias "{0}" requires at least one configurable group.**
Action	Review CloudStreams connectors and locate the connector that does not have at least one configurable group for all of its connections.

CLS.0300.0025E	**Unknown service request implementation: {0}**
Action	Contact Support.

CLS.0300.0026E	**Error getting property value for "{0}" from class {1}, Error: {2}**
Explanation	CloudStreams was unable to access the value for one of its managed connection's configurable fields.
Action	Inspect the configuration value and verify it is valid for the specified field.

CLS.0300.0027E	**Error setting property value "{0}" for "{1}" from class {2}, Error: {3}**
Explanation	CloudStreams was unable to access the value for one of its managed connection's configurable fields.
Action	Inspect the configuration value and verify it is valid for the specified field.

CLS.0300.0028E	**Error introspecting class {0}, Error: {1}**
Action	Contact Support.

CLS.0300.0029E	**Custom config field "{0}" expected group alias "{1}" instead of "{2}"**
Action	Contact Support.

CLS.0300.0030E	**Custom config field is missing required key property.**
Explanation	All managed connection custom configuration fields must have a unique key name.
Action	Review CloudStreams connector configuration to locate source of the missing field key.

CLS.0300.0031E	**Illegal attempt to binding or register a connection configuration "{0}". It is already registered.**
Explanation	When a connection configuration (e.g. a managed connection pool) is enabled, its alias name must be unique.
Action	Change the connection configuration alias name so it will be unique.

CLS.0300.0032E	**Attempt to create a connection configuration instance "{0}" with missing required groups. Required groups: {1}**
Action	Review the affected CloudStreams connection configuration and ensure that it includes the required configurable group.

CLS.0300.0033W	**Error unloading connection manager alias "{0}" from factory. Details: {1}**
Explanation	An error was encountered while releasing a managed connection pool instance during connection manager shutdown.
Action	No action is necessary.

CLS.0300.0034E	**Connection factory manager overwrote key "{0}" for implementation. Old value: {1}, New value: {2}**
Action	Contact Support.

CLS.0300.0035E	**Missing connection configuration instance for the alias "{0}"**
Explanation	An error occurred while attempting to obtain a socket connection for an unknown connection configuration instance.
Action	Confirm a connection configuration exists and is enabled with this alias name.

CLS.0300.0036E	**The config value "{0}" for field "{1}" is not supported.**
Action	Contact Support.

CLS.0300.0038E	**Configuration value missing for required field "{0}" in connection configuration "{1}"**
Action	Provide a value for the connection configuration's required field and then enable it again.

CLS.0300.0039E	**Configuration value for field "{0}" is not serializable. Value: {1}**
Action	Contact Support.

CLS.0300.0040E	**Error creating native service provider endpoint, {0} with service context, {1} Error: {2}**
Explanation	The native provider endpoint could not be defined as a valid URI.
Action	Review the configured value and ensure it is properly formatted as a URI.

CLS.0300.0041E	**An IO or timeout exception is encountered for invoke "{0}" method for connection alias "{1}". Check the network connectivity/proxy setting. Details: {2}**
Explanation	A service invocation error occurred due to a network IO exception on the socket.
Action	Verify whether the connection configuration is correct, the endpoint is valid, the service is running, the connect and read timeouts are not too short, including the network connectivity and proxy settings.

CLS.0300.0042E	**Unexpected exception encountered for invoke "{0}" method for connection alias "{1}". Details: {2}**
Explanation	An unexpected service invocation error occurred that is not caused by an IO socket exception.
Action	Verify connection configuration is correct.

CLS.0300.0044E	**Error while activating Authentication scheme, "{0}" for connection alias, "{1}". Details: {2}**
Explanation	An error occurred activating an authentication scheme (e.g. OAuth, Basic Auth, etc.).
Action	Review configuration details if the authentication scheme has its own configuration; otherwise, please contact support.

CLS.0300.0045E	**HTTP version "{0}" is not supported. Must be HTTP/0.9, HTTP/1.0 or HTTP/1.1**
Action	Ensure that the connection configuration specifes the correct HTTP version.

CLS.0300.0046E	**Error in request headers configuration for "{0}" alias. Names: {1}, Values: {2}, Details: {3}**
Explanation	Error validating request headers encountered while enabling a connection configuration.
Action	Verify the comma-delimited list of request headers and values are valid.

CLS.0300.0047E	**Error in request headers configuration for "{0}" alias. Names: {1}, Values: {2}, Names and values are required.**
Action	Verify whether the comma-delimited list of header names and values have non-whitespace characters for each entry.

CLS.0300.0051E	**Error invoking connection from connection configuration instance "{0}". It is configured for an unknown web proxy alias "{1}"**
Explanation	A connection configuration has a configuration field for an unknown IS proxy server.
Action	Confirm the proxy alias entered for the connection configuration exists in the Integration Server 'Proxy Server' configuration.

CLS.0300.0052W	**Unable to register scheme for web proxy alias, "{0}", in connection configuration: "{1}"**
Explanation	A connection configuration's web proxy alias could not be initialized when it was enabled, so the configuration is enabled with no proxy server support.
Action	Verify the Integration Server proxy server configuration identified by the alias is valid.

CLS.0300.0054E	**Cannot create OAuthCredentials for OAuth version {0}**
Action	Contact Support.

CLS.0300.0055E	**Cannot create SchemeFactory for OAuth version {0}**
Action	Contact Support.

CLS.0300.0056E	**OAuthAliasHelperFactory cannot work with null token alias name**
Explanation	A connection configuration instance requires a valid OAuth alias.
Action	Verify the oauth token configuration in the CloudStreams admin has a proper alias.

CLS.0300.0057E	**OAuthAliasHelperFactory cannot find token alias name {0}**
Explanation	A connection configuration instance references an unknown OAuth token alias.
Action	Verify the connection configuration references the correct alias as defined in the oauth token configuration in the CloudStreams admin.

CLS.0300.0058E	**OAuthAliasHelperFactory cannot work with null OauthAccessDetailsManager bean. Not configured.**
Action	Contact Support.

CLS.0300.0059I	**CloudStreams outbound connector "{0}" encountered an IO exception while reading the native provider response. Consider setting the advanced connection configuration, increasing timeout values for 'Connection TimeOut' and 'Socket Read Timeout' properties. Also, optionally change 'Retry on Response Failure' to true while 'Connection Retry Count ' is greater than 0 if it is safe to send requests more than once.**
Explanation	The default timeout value for 'Connection TimeOut' and 'Socket Read Timeout' property may not be enough.The default settings for the default connector outbound connection factory will not attempt to resend a request if it believes it was received by the provider. If there is no harm to send a request more than once to a provider, enable the 'Retry on Response Failure' advanced property (cn.retryIfRequestSentOk).
Action	In case the network is slow or the backend processing takes longer than usual, increase the 'Connection Timeout' and the 'Socket Read Timeout' values. Also, optionally change 'Retry on Response Failure' to true while 'Connection Retry Count ' is greater than 0 if it is safe to send requests more than once.

CLS.0300.0061E	**Error instantiating object for hostname verifier: "{0}", Details: {1}**
Explanation	This configuration field must be set to a fully qualified classname that implements the Apache HttpClient interface: org.apache.http.conn.ssl.X509HostnameVerifier. This field is used to perform validation checks between a native provider host and its server SSL certificate.
Action	Specify "org.apache.http.conn.ssl.AllowAllHostnameVerifier" to accept all hosts or "org.apache.http.conn.ssl.StrictHostnameVerifier" for strict enforcement. Leaving this field blank implies using the "AllowAllHostnameVerifier" option.

CLS.0300.0062E	**Hostname verifier class, "{0}", must implement org.apache.http.conn.ssl.X509HostnameVerifier interface.**
Action	Specify a valid fully qualified classname in the CloudStream package's java classpath that implements the interface or leave the field blank to disable hostname verification. See CLS.0300.0061 for more details.

CLS.0300.0063E	**Error initializing registered provider's SSL context for the "{0}" algorithm. Details: {1}**
Action	Contact Support.

CLS.0300.0064E	**Error reading a key store for this file: {0}, Details: {1}**
Action	Verify whether the file path exists, the file is a valid keystore file, and Integration Server has privileges to read the file.

CLS.0300.0065E	**Error reading a trust store for this file: {0}, Details: {1}**
Action	Verify whether the file path exists, is a valid trust store file, and the Integration Server has OS privileges to read the file; otherwise, contact Support.

CLS.0300.0066E	**Error initializing entrust security provider's socket factory "{0}" algorithm. Details: {1}**
Action	Unless this is a correctable error with one of the keystore files, contact Support.

CLS.0300.0069E	**Unable to verify hostname. unknown SSL socket type: {0}**
Explanation	Unable to perform hostname verification on a native provide endpoint.
Action	Contact support.

CLS.0300.0070E	**Unknown HCAdapter event type: {0}**
Explanation	An enabled connection configuration instance has received a notification event from an unknown origin. (These events are used to keep configuration instances in synch with related Integration Server configuration changes when possible.)
Action	Contact support.

CLS.0300.0072E	**Error creating socket factory, "{0}". Details: {1}**
Explanation	Unable to create the SSL socket factory for use with a connection configuration.
Action	Review the configuration and make corrections if possible; otherwise, please contact support.

CLS.0300.0073D	**Error during onCleanup for socket factory for "{0}". Details: {1)**
Explanation	Nonfatal error encountered while release resources associated with a connection configuration's SSL socket factory.
Action	No action should be necessary for this debug message.

CLS.0300.0075E	**Unable to initialize the key store for file: {0}, Details: {1}**
Action	Ensure that the file path exists, is a valid keystore file, and the Integration Server has OS privileges to read the file; otherwise, contact Support.

CLS.0300.0076E	**Unable to create key store object from this file. {0}, exists? {1}, readable? {2}**
Action	Ensure that the file path exists, is a valid keystore file, and the Integration Server has OS privileges to read the file; otherwise, contact Support.

CLS.0300.0077E	**Unable to access client's private key and certificate for this key alias: {0}, in this keystore file: {1}, Details: {2}**
Action	Ensure that the configuration alias used to access the client key is correct for the specified keystore; otherwise, contact Support.

CLS.0300.0081E	**Unable to register or unregister connfactory event subscriber instance, {0}. Event type: {1} Details: {2}**
Explanation	An error occurred while the connection factory registered its event listener used to receive notfications for some Integration Server configuration changes.
Action	Contact support.

CLS.0300.0082E	**Error during onInit for socket factory, "{0}". Details: {1}**
Explanation	Error during SSL socket factory initialization.
Action	Contact support.

CLS.0300.0083E	**Error initializing security provider"s socket factory. Key store alias: {0}, trust store alias: {1}, details: {2}**
Explanation	Error during SSL socket factory initialization.
Action	Contact support.

CLS.0300.0093E	**Error initializing connfactory cert chain verifier for trust store file: {0}, Details: {1}**
Explanation	Error occurred while building the list of certificates that the connection configuration will trust.
Action	Contact support.

CLS.0300.0096E	**Error while attempting to verify trust for this cert: {0}, Cert will not be trusted. Details: {1}**
Action	No action is necessary unless this certificate is trusted; otherwise, contact Support.

CLS.0300.0099E	**Credentials configurable group failed to bind configuration field "{0}", with an illegal value "{1}".**
Explanation	The "cr.authSchemeType" configuration field is limited to a closed set of possible values.
Action	It should not be possible to specify an unknown value through the CloudStreams connection admin UI, so please contact support.

CLS.0300.0100E	**Protocol configurable group failed to bind configuration field "{0}", with an illegal value "{1}".**
Explanation	The "pr.protocolVersion" configuration field is limited to a closed set of possible values.
Action	It should not be possible to specify an unknown value through the CloudStreams connection admin UI, so please contact support.

CLS.0300.0105E	**Error creating buffered entity for request message. Details: {0}**
Action	If problem persists, contact Support.

CLS.0300.0106E	**Connection configuration instance "{0}" contains a custom key "{1}" with no prefix. Suggest "cx.{1}"**
Explanation	All connection fields including custom fields must have a key name that may be used to identify the field. A dot-separated prefix must be prepended to the field name's key. 'cx.' is the suggested convention for custom fields.
Action	Change the specified key forthe custom configuration field so it contains a valid prefix.

CLS.0300.0107E	**AWSActivator called with wrong token instance. {0}**
Explanation	The Amazon web service auth scheme requires auth tokens to produce the content necessary to invoke an AWS service.
Action	Please contact support.

CLS.0300.0108E	**Missing auth token required field for Amazon Web Service authentication. {0}**
Explanation	The Amazon web services require auth tokens to build a proper service request that can be authenticated.
Action	Review configuration and ensure all token fields are provided.

CLS.0300.0110E	**AWS v2 signature auth scheme requires application/x-www-form-urlencoded content.**
Explanation	Amazon web service signature version 2 cannot be used unless request message is using the required Content-Type.
Action	Correct service configuration to use the appropriate content type for the request.

CLS.0300.0111E	**Unable to update native provider URI for AWS {0} signature auth scheme.**
Explanation	The Amazon signature auth scheme appends additional security tokens as query parameters on the native provider endpoint.
Action	Please contact support.

CLS.0300.0112E	**Unexpected request type received in AWS {0} auth scheme. {1}**
Action	Contact Support.

CLS.0300.0114E	**Unsupported algorithm. {0} AWS {1} signature scheme must be one of these. {2}**
Explanation	The service must be configured to use one of the valid algorithms for signing the request.
Action	Review connection configuration.

CLS.0300.0115E	**"{0}" header is missing from {1} AWS signature auth sceheme.**
Explanation	The AWS authentication scheme requires this header.
Action	Verify the service configuration is correct.

CLS.0300.0117D	**Expected one value for AWS Param key: {0}, Found: {1}**
Explanation	This AWS auth scheme parameter was expected to have only one value.
Action	Please contact support.

CLS.0300.0118T	**Provider endpoint: {0}, AWS Canonical Request: {1}**
Explanation	AWS signature calculations require requests to be in a specific format.
Action	Use this message to debug AWS signature authentication failures.

CLS.0300.0119T	**Provider endpoint: {0}, AWS String to sign: {1}**
Explanation	AWS signature calculations create a specific string to sign when generating signatures for the request.
Action	Use this message to debug AWS signature authentication failures.

CLS.0300.0120T	**Provider endpoint: {0}, AWS Canonical Request: {1}**
Explanation	AWS v2 signatures calculations require requests to be in a specific format.
Action	Use this message to debug AWS signature authentication failures.

CLS.0300.0122T	**Added 'Host' header: {0}**
Explanation	Amazon v4 signature requests require a "Host" header be sent with request.
Action	Use this message to debug AWS signature authentication failures.

CLS.0300.0123E	**Unknown AWS auth scheme type.**
Explanation	The AuthSchemeActivatorFactory received auth tokens for an unsupported signature scheme. type: {0}
Action	Please contact support.

CLS.0300.0124E	**Unsupported AWS auth scheme type. {0}**
Explanation	An auth scheme must be declared for the service, so it can be properly authenticated by the AWS server.
Action	Verify the connector configuration is correct.

CLS.0300.0125E	**Unexpected error binding configuration authTokens to AWS configuration. Details: {1}**
Explanation	Unable to enable a connection configuration with AWS configuration group because of an unexpected error.
Action	Please contact support.

CLS.0301.0001E	**This IData request is missing NSRecord metadata. Namespace details may be impacted.**
Explanation	NSRecord metada (document types) are used to marshal between IData and Axiom (XML) data models.
Action	Contact support.

CLS.0301.0002E	**IdataBuilder error translating IData message into an Axiom element. Details: {0}**
Explanation	An error occurred while translating a message from IData to the Axiom (XML) data model.
Action	Verify the IData content is valid.

CLS.0301.0003E	**IDataBuilder missing required parameters. Either an input stream or an IData object is needed to process a message.**
Explanation	The component that translates IData to Axiom (XML) data model is missing a required value.
Action	Review service that produced this error and verify a reference to either an input stream or IData content was provided.

CLS.0301.0005E	**IDataMessageFormatter error translating Axiom element to IData for service: {0} and operation: {1}. Details: {2}**
Explanation	An error occurred while translating a message from Axiom (XML) to the IData data model.
Action	Review service that produced this error and verify the message content is valid.

CLS.0301.0006E	**IDataMessageFormatter error encoding IData message to stream for service: {0} and operation: {1}. Details: {2}**
Explanation	An error occurred while serializing a message.
Action	Review service that produced this error and verify the message content is valid.

CLS.0301.0008E	**IDataMessageFormatter is unable to resolve provider targetAddress as a valid URL. {0}**
Action	Verify whether the target address endpoint is a valid URL.

CLS.0301.0009E	**CloudStreams message mappings for CloudStreams virtual service invocation "{0}" is invalid. Details: {1}**
Explanation	A CloudStreams service has one or more message mapping steps which are invalid.
Action	Review the errors and correct the message mapping statements for this connector.

CLS.0301.0010D	**CloudStreams mapping step, Error applying map step to message. Service invocation aborted? {0}. Source: {1}, Target: {2}, Details: {3}**
Explanation	Debug message showing an exception that occurred while executing a mapping step.
Action	If the mapping step is not required, then no additional action is necessary.

CLS.0301.0011E	**CloudStreams mapping step, Unknown map type "{0}".**
Explanation	There are various categories of mapping steps. (e.g. HEADER, COOKIE, XPATH, IDATA, etc.).
Action	Review the connector configuration and fix the invalid mapping step.

CLS.0301.0012E	**CloudStreams mapping step, Illegal attempt to set a value on a LITERAL mapping step named, "{0}"**
Explanation	A mapping step cannot have a 'LITERAL' target. In other words, a LITERAL cannot have a value assigned to it; it can only be used as a source value in mapping expressions.
Action	Review the connector configuration and fix the invalid mapping step.

CLS.0301.0013E	**CloudStreams mapping step, mapping step is missing "{0}" map value.**
Explanation	The mapping step is not properly configured. It is missing required elements.
Action	Review the connector configuration and fix the invalid mapping step.

CLS.0301.0014E	**CloudStreams mapping step, mapping step is missing "context" for map value. Must be IN or OUT.**
Explanation	A mapping step has a specific context depending on where it is used during service invocations. The 'IN' context implies the expression executes before the service invocation. The 'OUT' context implies the expression executes after the service invocation.
Action	Review the connector configuration and fix the invalid mapping step.

CLS.0301.0016E	**CloudStreams mapping step, XPath map value expression contains namespace prefix, but no namespaces were provided with map. {0}**
Explanation	An XPATH mapping step must include a namespace prefix and URI declaration(s) if the XPath expression contains a colon-delimited prefix reference.
Action	Review the connector configuration and fix the invalid mapping step.

CLS.0301.0017E	**CloudStreams mapping step, XPath map step unable to set value on node. "{0}" did not find any nodes in message.**
Explanation	An XPATH mapping step executed but the expression returned no matching nodes from the Axiom (XML) message.
Action	Review the connector configuration and verify the expression is valid if matches were expected.

CLS.0301.0019E	**CloudStreams mapping step, Error executing XPath map step to set value for this XPath: "{0}" and this value: {1}, Details: {2}**
Explanation	An error occurred while executing an XPath expression meant to set a value on an Axiom (XML) message.
Action	Review the connector configuration and fix the invalid mapping step if this error was unexpected.

CLS.0301.0020E	**CloudStreams mapping step, XPath map step unable to set value on node. "{0}" found {1} nodes in message.**
Explanation	An XPATH mapping step's XPath expression against an Axiom (XML) message did not resolve to a single node.
Action	Review the connector configuration and fix the invalid mapping step if this error was unexpected.

CLS.0301.0021E	**CloudStreams mapping step, Error executing XPath map step to get value for this XPath: "{0}", Details: {1}**
Explanation	An error occurred while executing an XPath expression meant to get a value from a message.
Action	Review the connector configuration and fix the invalid mapping step if this error was unexpected.

CLS.0301.0023E	**CloudStreams mapping step. Error executing validation for mappings. Details: {0}**
Action	Review the connector configuration and then fix the invalid mapping step(s).

CLS.0301.0025E	**CloudStreams mapping step, XPath "{0}" expression returned unsupported XML element type, "{1}". Expressions must resolve to a single element or attributes only.**
Explanation	CloudStreams XPATH mapping expressions may only reference text or attributes nodes in the XML message.
Action	Review the connector configuration and fix the invalid mapping step.

CLS.0301.0031E	**No validator instance to validate CloudStreams message content using IS doc type validation.**
Explanation	CloudStreams was unable to create a validator for a message against its associated doc type(s).
Action	Review the doctypes for the affected request or response message.

CLS.0301.0032E	**Error while validating CloudStreams message content using IS doc type validation. Details: {0}**
Explanation	An unexpected error occurred while validating a message against its associated doctype(s).
Action	Review the doctypes for the affected request or response message.

CLS.0301.0033E	**Cloudstreams message is not valid based on expected doc type. Details: {0}**
Explanation	A CloudStreams request or response message did not have the expected structure as defined by its associated doctype(s).
Action	Review the connector service configuration and state of the native provider to resolve the underlying error with the unexpected message structure.

CLS.0301.0034E	**The configured translator service "{0}" is missing "static" method declaration for its "translate" method.**
Explanation	A mapping statement may have an optional attribute that defines a fully qualified classname for a java class. This class must contain a public static method named 'translate'.
Action	Verify the connector configuration's mapping statement is correct and the class has the expected 'translate' public static method and is in the CloudStreams class loader.

CLS.0301.0035E	**Error resolving configured translate service "{0}", Details: {1}**
Action	Verify whether the connector configuration's mapping statement is correct and the class is in the CloudStreams class loader. See CLS.0301.0034 for more details.

CLS.0301.0037E	**Unknown builder type "{0}" for message data handler.**
Explanation	No Axis2 message Builder implementation is registered for this builder type (key).
Action	Contact support.

CLS.0301.0038E	**Unknown message formatter type "{0}" for message data handler.**
Explanation	No Axis2 MessageFormatter implementation is registered for this message type (key).
Action	Contact support.

CLS.0301.0042E	**No response code and method mapping found for connector "{0}" and response code "{1}" and httpMethod "{2}"**
Explanation	The invoked connector service has returned an unexpected response code for the httpMethod used to execute the request. So it is considered to be a fault condition regardless of the proivder response code.
Action	A fault message will be returned to the pipeline. If the virtual service is configured to return the native provider fault, then this provider response will be included.

CLS.0301.0045E	**Unknown message handler phase. {0}**
Explanation	CloudStreams message handlers have predefined inbound and outbound phases for both request and response message processing.
Action	Contact support.

CLS.0301.0046E	**Unknown message builder content type, "{0}" for "{1}" message phase**
Explanation	The message mapping in CloudStreams wst-transport.xml configuration file is incorrect.
Action	Contact support.

CLS.0301.0047E	**Unknown message formatter content type, "{0}" for "{1}" message phase**
Explanation	The message mapping in CloudStreams wst-transport.xml configuration file is incorrect.
Action	Contact support.

CLS.0301.0062E	**Error instantiating builder class: {0} for content type: {1}. Details: {2}**
Explanation	The message mapping in CloudStreams wst-transport.xml or Integration Server's axis2.xml configuration file is incorrect.
Action	Contact support.

CLS.0301.0063E	**Error instantiating message formatter class: {0} for content type: {1}. Details: {2}**
Explanation	The message mapping in CloudStreams wst-transport.xml or Integration Server's axis2.xml configuration file is incorrect.
Action	Contact support.

CSHeaderTreeTable_Active_Label – Active

CSHeaderTreeTable_Add_Header_Label – Add Header

CSHeaderTreeTable_Add_Label – Add

CSHeaderTreeTable_Add_Row_Label – Add Row

CSHeaderTreeTable_Default_Value_Label – Default Value

CSHeaderTreeTable_Delete_Header_Label – Delete Header

CSHeaderTreeTable_Delete_Row_Label – Delete Row

CSHeaderTreeTable_Headers_Label – Header(s)

CSHeaderTreeTable_Headers_Not_Available_Message – No headers are available to select because no operation is selected on the Operation tab.

CSHeaderTreeTable_Headers_Not_Available_Title – Headers Not Available

CSHeaderTreeTable_Headers_Not_Found_Title – Headers Not Found

CSHeaderTreeTable_Insert_Row_Label – Insert Row

CloudServiceCreationPage_Error – Error

CloudServiceCreationPage_Page_Description – Specify the location and name for the new cloud connector service.

CloudServiceCreationPage_Page_Title – Create a New Cloud Connector Service

CloudServiceCreationPage_Warning – Warning

CloudStreams_Provider_Project_Label – CloudStreams Provider Project

Explanation Menu item label for creating a new CloudStreams Provider Project.

ConnectionAliasSelectionPage_No_Connections_Error_Message – No connection pools have been created for the selected cloud application provider.

ConnectionAliasSelectionPage_Page_Description – Select the connection pool that the cloud connector service "{0}" will use to connect to the cloud provider.

ConnectionAliasSelectionPage_Search_Message_Text – Search Connections

ConnectionAliasSelectionPage_Text_Available_Connection_Pool – Available Connection Pools

ConnectionAliasSelectionPage_Text_Name – Name

ConnectorParameterTable_6 – Add Parameter

ConnectorParameterTable_8 – Delete Parameter

ConnectorParameterTable_Add_Parameter_Label – Add Parameter

ConnectorParameterTable_Data_Type_Label – Data Type

ConnectorParameterTable_Default_Value_Label – Default Value

ConnectorParameterTable_Delete_Parameter_Label – Delete Parameter

ConnectorParameterTable_Name_Label – Name

ConnectorParameterTable_Shift_Down – Shift Down

ConnectorParameterTable_Shift_Down_Label – Shift Down

ConnectorParameterTable_Shift_Up – Shift Up

ConnectorParameterTable_Shift_Up_Label – Shift Up

ConnectorParameterTable_Type_Label – Type

ConnectorServiceWizard_Wizard_Title – New Cloud Connector Service

DUPLICATE_DOC_SELECTION_ERR_MSG – The document reference "{0}" has already been referred by an existing parameter. Select a different document reference and try again.

Explanation Selected a document reference that has already been referred by an existing parameter.

Action Select a different document reference.

Deploylog_Table_ServerHost – CloudStreams Server Host

Deploylog_Table_ServerVersion – CloudStreams Server Version

Deploylog_table_serverColumn – CloudStreams Server Alias

Description	**Description:**
ECLS.0300.0008	**Connection configuration alias "{0}" already registered. Original config was replaced with alias "{1}"**
Explanation	Managed connection pool aliases must be unique across all CloudStreams connectors.
Action	Locate the duplicate alias name and change its name to ensure no two pool configurations share the same alias.

Error_Generic_Message – Operation failed because of the following reason, please check the log files for more details.

Error_Unable_To_Reach_Destination – Unable to reach the Resource Destination. Check your Network connection and Hostname.

Group_Column_Connection_Description – Connection Description

Group_Column_Connection_Name – Connection Name

Group_Column_Connection_Type – Connection Type

HeaderPage_Page_Name – Headers

HeaderPage_Section_Input – Input

HeaderPage_Section_Output – Output

HeaderSelectionPage_Available_Headers_Label – Available Headers

HeaderSelectionPage_Description – Select Header

HeaderSelectionPage_Filter_Text_Message – type filter text

HeaderSelectionPage_Header_Label – Header

HeaderSelectionPage_Title – Header

HeaderSelectionWizard_Title – Select Header

IOEditor_Editor_Name – Input/Output

ISCloudConnectionNode_Node_Name – Cloud Connection

Info_Configure_Login_Operation – Configure a Login Operation under Services.

Info_Configure_Logout_Operation – Configure a Logout Operation under Services.

Is_Hidden Hide

Lookup_SODescribe soDescribe

Lookup_Selection_Dialog – Lookup Selection Dialog

Lookup_Selection_Dialog_Mesage – Select a Lookup.

Lookup_Selection_Dialog_Title – Lookup Selection

New_Group_Wizard_Description – Select a group.

New_Group_Wizard_Title – New Group

OperationPage_Business_Object_Label – Business Object:

OperationPage_Con_Pool_Label – Connection Pool:

OperationPage_Name Operation

OperationPage_Operation_Change_Title – Operation change confirmation

OperationPage_Provider_Type_Label – Connector Type:

OperationPage_Virtual_Svc_Label – Connector Virtual Service:

OperationPage_operation_Label – Operation:

ParameterPage_Form_Text_Parameters – Parameters

ParameterPage_Page_Name – Parameters

ParameterWizardPage_Field_Column – Field

ParameterWizardPage_Field_Label_Column – Field Label

ParameterWizardPage_Native_Column – Native

ParameterWizardPage_SOAP_TYPE_Column – SOAP Type

ProviderSelectionPage_Name – Name

ProviderSelectionPage_No_Providers_Error_Message – No CloudStreams connectors are installed.

ProviderSelectionPage_Page_Description – Select a CloudStreams Connector instance to use for the cloud connector service "{0}".

ProviderSelectionPage_Page_title – Select the Connector

ProviderSelectionPage_SearchLabel – Available Connectors

ProviderSelectionPage_Search_Message_Text – Search Connectors

ProviderSelectionPage_Type – Type

ProviderSelectionPage_Version – Version

Publisher Publisher:

RetrieveBusinessObjs_Operation_Cancelled – Business Objects retrieval operation was canceled.

RetrieveBusinessObjs_TaskName – Getting Business Objects...

ServiceSelectionPage_No_Services_Error_Message – No services exist for the selected cloud application provider.

ServiceSelectionPage_Page_Description – Select the service that will be used for the cloud connector service "{0}".

ServiceSelectionPage_Page_Title – Select the Service

ServiceSelectionPage_Search_Label – Available Services

ServiceSelectionPage_Search_Message_Text – Search Services

ServiceSelectionPage_Text_Name – Name

SummaryPage_Business_Object – Business Object:

SummaryPage_ConnectionPool – Connection Pool:

SummaryPage_Name Name:

SummaryPage_Namespace – Namespace:

SummaryPage_Operation – Operation:

SummaryPage_Package_Name – Package:

SummaryPage_Page_Name – Summary

SummaryPage_Provider – Connector:

SummaryPage_Provider_Type – Connector Type:

SummaryPage_Service_Name – Service Name:

SummaryPage_Version_Number – Version Number:

TCLS.0300.0121	**Added 'X-Amz-Date' header: {0}**
Explanation	Amazon v4 signature requests require a 'Date' or 'X-Amz-Date' header be sent with request.
Action	Use this message to debug AWS signature authentication failures.

WST-2360	**Updated CloudStreams Connector service "{0}" of package "{1}".**
Explanation	Cloud connector service updation has failed. See the server/error logs for details.
Action	Ensure that the cloud service which you are updating is not locked or in readonly mode. If the problem still persists, restart the Integration Server. If the problem still remains, contact Support.

category.name ESB

confirm.listener.enable – Do you want to enable the '{0}' listener? When a listener is enabled, you will not be able to change the listener's subscription and event actions from webMethods Designer Service Development.

content-type.name CloudService

g11ndsp_run_as_user – Run As User

service.editor.name – CloudStreams Service Multi-page Editor

wizard.name Cloud Connector Service

9 Command Central Messages

CCEADME0000 **Unknown node alias.**

Explanation A node with the specified alias is not found.

Action Provide a valid node alias.

CCECAME0000 **The specified flatfile location does not exist.**

Explanation The flatfile repository was not located at the specified location on the file system.

Action Specify a valid location for the flatfile repository.

CCECAME0001 **A repository already exists at the same location.**

Explanation Two or more repositories cannot point to the same location.

Action Specify a unique location for the new repository.

CCECAME0002 **A repository with this name already exists.**

Explanation The name of the repository is not unique.

Action Check the repository name and provide a unique name for the repository.

CCECAME0003 **Repository name, type and location cannot be empty or missing.**

Explanation The name, type, and location are required parameters when creating asset type repositories.

Action Specify values for all required parameters.

CCECAME0004 **Name and type cannot be empty or missing.**

Explanation All parameters are required.

Action Specify values for all parameters.

CCECAME0005 **Update failed.Trying to update {0} asset repository when the cached repository is of type {1}.**

Explanation The specified asset repository type is incorrect.

Action Specify the correct repository type.

CCECCBE0000 **File with path {} can not be deleted.**

Explanation The file can not be deleted.

Action Make sure the file is not used by any process.

CCECCUI0143 **No ports configured for the specified runtime.**

Explanation There are no ports configured for the specified runtime.

Action Configure a port.

CCECCUI0288 **No rows were selected. You are about to download all Log Sources.**

Explanation No rows were selected in the Log Sources table before clicking the Download Selected Files menu option.

Action No action required.

CCECCUI0822 **Copy**

CCECCUI0823 **Copy to clipboard**

CCECCUI0824 **Fix Name and Version**

CCECCUI0825 **Product Version**

CCECCUI0826 **Asset ID**

CCECCUI0827 **License Key Alias**

CCECCUI0828 **Repository Name**

CCECCUI0829 **Copy fix identifiers to use in templates and sagcc commands**

CCECCUI0830 **Can use for 10.3 or later managed installations**

CCECCUI0831 **Can use for 9.7 or later managed installations**

CCECCUI0832 **Use for any managed installation to get the latest release of the selected type of fix**

CCECCUI0833 **Copy composite asset identifiers to use in sagcc commands**

CCECCUI0834 **Copy product identifiers to use in templates and sagcc commands**

CCECCUI0835 **Show Fixes**

CCECCUI0836 **Show Support Patches**

CCECCUI0837 **Location URL**

CCECFRE0000 **The content of the response is not acceptable according to the accept headers**

Explanation The response content cannot be converted into the requested media type that is specified in the HTTP Accept header. For example, the response is in text format and cannot be converted into XML or JSON format.

Action Try to load the configuration again and specify a supported media type.

CCECFRE0001	**The ConfigurationTypeId "{1}" does not exist for RuntimeComponentId "{0}".**
Explanation	One or more configuration types specified do not match or are not valid for the specified properties.
Action	Provide valid configuration types for the specified properties. You can determine the valid configuration types using the following command:cc list configuration types

CCECFRE0002	**The ConfigurationTypeId "{0}" does not exist for RuntimeComponentId "{1}".**
Explanation	There is no registered ConfigurationType with the provided ID for the specified runtime component.
Action	Provide a valid ConfigurationTypeId for the specified runtime component. You can determine the IDs for configuration typesusing the following command:cc list configuration types

CCECFRE0005	**LandscapeConfigurationUiBindingService is not available.**
Explanation	The LandscapeConfigurationUiBindingService is not registered.
Action	Ensure that the bundle that contains this service is active.

CCECFRE0006	**Configuration instance {0} cannot store license keys.**
Explanation	The specified configuration instance {0} cannot store license keys.
Action	Specify a configuration instances that is able to store license keys. Such configuration instances always start with the COMMON-LICENSE prefix.

CCECFRE0007	**Getting the content of an input stream as string fails**
Explanation	Command Central cannot convert the input stream as string.
Action	Check the logs for more information.

CCECLTE0001	**The expected values expression could not be parsed correctly.**
Explanation	The expected values expression could not be parsed correctly.
Action	Check the expected values expression for errors.

CCECLTE0012	**A resource was not specified.**
Explanation	The REST call failed because a remote resource location was not specified in the REST service.
Action	Specify a valid resource in the REST service, for example, spm/inventory/components.

CCECLTE0013	**A URL was not specified.**
Explanation	The REST call to the remote host failed because the URL was not specified.
Action	Specify a valid URL, for example, http://localhost:8092.

CCECNFE0000	**LandscapeDefinition service is not available.**
Explanation	The LandscapeDefinition service is not registered.
Action	Ensure that the bundle that contains this service is active and the service is properly configured.

CCECNFE0001	**Landscape inventory service not available.**
Explanation	The landscape inventory service was not configured.
Action	Ensure that the bundle that contains this service is active.

CCECNFE0002	**Configuration service factory not available.**
Explanation	A configuration service factory is not configured.
Action	Ensure that the bundle that contains the configuration service factory is active and that the component definition is correct.

CCECNFE0003	**The configuration service encountered a remote request failure.**
Explanation	The remote request for a configuration item failed.
Action	Ensure that the node in the request is active.

CCECNFE0004	**The remote request encountered a concurrency error.**
Explanation	The system could not execute parallel remote requests.
Action	Contact Software AG Global Support.

CCECNFE0005	**Can not update credentials.**
Explanation	The user credentials on Command Central can not be updated.
Action	Ensure that the runtimeComponentId and nodeAlias parameters are valid.

CCECNFE0006	**Can not process JSON configuration.**
Explanation	The JSON format of an old configuration is incorrect.
Action	Verify that the configuration uses proper JSON format.

CCECNFE0008	**Can not update configurations cache because of failure during retrieval of remote configurations.**
Explanation	The remote request for configuration items failed and the configurations cache can not be updated.
Action	Ensure that the node in the request is active.

CCECNFE0009	**The configuration service encountered a remote request failure while retrieving configuration data for runtime component {0}, configuration instance {1}.**
Explanation	The remote request for the specified configuration item failed.
Action	Ensure that the node in the request is active and check the Platform Manager logs.

CCECOME0000	**Cannot perform an operation on nodes that are not accessible. The offline nodes are {0}.**
Explanation	The specified nodes cannot be accessed because they are offline.
Action	Check the status of the specified nodes. Command Central can only access nodes that are online.

CCECOME0002	**{0} on {1} ({2}) became unresponsive. Component restart may help to resolve this quickly.**
Explanation	Specified components became unresponsive.
Action	Component restart may help to resolve this quickly.

CCECOME0003	**{0} on {1} ({2}) crashed. You will need to start it again and investigate the cause of the failure.**
Explanation	Specified components crashed.
Action	You will need to start it again and investigate the cause of the failure.

CCECOME0007	**{0} of {1} on {2} ({3}) spiked into critical zone. The component may become overloaded!**
Explanation	The specified component becomes overloaded.
Action	Try to release the load on the specified component.

CCECOME0015	**Node {0} was not found.**
Explanation	The specified node was not found.
Action	Check if the correct alias is used. If the node is not present in the landscape it can be added using the landscape service. If the node has been added but is still not accessible, contact Software AG Global Support.

CCECOME0016	**Node {0} could not be created.**
Explanation	A node with alias {0} could not be created because another node with alias {1} already exists.
Action	Provide a different alias for the new node.

CCECOME0017	**Environment {0} could not be created.**
Explanation	An environment with alias {0} could not be created because another environment with alias {1} already exists.
Action	Provide a different alias for the new environment.

CCECOME0018	**Generation of checksum for license metering report failed**
Explanation	The generation of the checksum for the license metering report failed.
Action	Contact Software AG Global Support.

CCECOME0019	**Generation of report id for license metering report failed**
Explanation	The generation of the report ID for the license metering report failed.
Action	Contact Software AG Global Support.

CCECOME0020	**Cannot convert XML report to string**
Explanation	The convertion of the XML report failed.
Action	Contact Software AG Global Support.

CCECOME0025	**Generation of XML string for object instance of class {0} failed**
Explanation	The generation of the XML string for object instance of class {0} failed.
Action	Provide a valid object instance.

CCECOME0029	**License key {0} not found.**
Explanation	The license key with the specified alias {0} is not found.
Action	Upload and assign a valid license key for this alias or use a different existing license key alias.

CCECOME0030	**Checksum verification of report {0} failed!**
Explanation	The checksum verification of report {0} failed.
Action	Contact Software AG Global Support.

CCECOME0033	**Unable to parse this date string({0}).**
Explanation	Unable to parse this date string({0}).
Action	Contact Software AG support.

CCECOME0034	**Unexpected exception occurred: {0}.**
Explanation	An unexpected exception occurred: {0}.
Action	Contact Software AG support.

CCECOME0038	**The remote Platform Manager job with id {0} was not found.**
Explanation	A job with the specified id was not found on Platform Manager.
Action	Specify an existing job id.

CCECOME0041	**The embedded license key {0} cannot be deleted.**
Explanation	The license key {0} was implicitly added with license manifest {1} and it cannot be deleted individually.
Action	Delete the license key {0} by deleting the corresponding license manifest {1}.

CCECOMI0040	**Product Usage Report**

CCECORE0001	**Exceeded the maximum nodes allowed as per the configured license.**
Explanation	You have exceeded the nodes allowed to you as per the license configured for Command Central.
Action	Contact Software AG support to upgrade the license.

CCECORE0002	**Invalid License found. The system is going to shutdown in 30 minutes.**
Explanation	The configured license is invalid. You need to configure a valid license immediately else the system will shutdown in 30 mintures.
Action	Configure a valid license immediately. If you do not have one, contact your system dministrator or Software AG support.

CCECORE0003	**Invalid License found. The system is shutting down.**
Explanation	The system is shutting down as the configured license is invalid.
Action	Contact your Administrator or Software AG support.

CCECORE0004	**The license has expired.**
Explanation	The configured license has expired.
Action	Contact your system administrator or Software AG support.

CCECORE0005	**The license is not valid for the current operating system.**
Explanation	The configured license is not valid for the current operating system.
Action	Contact your Administrator or Software AG support.

CCECORE0006	**The number of nodes has exceeded as per the configured license.**
Explanation	As per the configured license, you are not allowed to add more nodes as you have exhausted the licensed number of nodes.
Action	Contact your system administrator or Software AG support to get the license upgraded to add more nodes.

CCECORE0007	**Falied to get the node count from the license.**
Explanation	This issue may occur when your license file is corrupt.
Action	Contact your system administrator or Software AG support.

CCECORE0008	**The configured license is not valid for this product.**
Explanation	Either the license file is not for Command Central or it may have be a corrupt file.
Action	Contact your system administrator or Software AG support.

CCECORE0009	**Failed to read the product code from the license.**
Explanation	This issue may occur when your license file is corrupt.
Action	Contact your system administrator or Software AG support.

CCECORE0010	**The configured license is not valid for this product version.**
Explanation	This issue may occur when your license file is corrupt.
Action	Contact your system administrator or Software AG support.

CCECORE0011	**Failed to read the product version from the license.**
Explanation	Either the license file is not for current version of Command Central or teh license file may be corrupt.
Action	Contact your system administrator or Software AG support.

CCECORE0012	**Node with alias {0} is not found.**
Explanation	The specified node is not found in Command Central.
Action	Ensure that the node alias is spelled correctly. You can view a list of installations and their aliases using either the Command Central Web user interface, the cc list landscape nodes command, or the REST API.

CCECORE0013	**The specified search query is not valid. The supported search attributes are: {0}**
Explanation	One or more attributes are not supported for this type of search.
Action	Ensure that the search attributes are supported for the type of search you want to perform. Make sure that the attributes are spelled correctly. The supported search attributes are listed in the error message. Note that search attributes are case-sensitive.

CCECORE0014	**Task "{0}" for node "{1}" failed.**
Explanation	The specified task failed to execute for the specified node.
Action	Read through the details provided in the error message and the logs, then take corrective steps.

CCECORE0015	**Tasks execution has failed.**
Explanation	Some or all of the tasks failed to execute.
Action	Read through the details provided in the error message and the logs, then take corrective steps.

CCECORE0016	**The specified attribute name and the attribute name in the request are not the same.**
Explanation	The attribute name in the body and the attribute name in the path segment should be the same.
Action	Fix the request and try again.

CCECORE0017	**Specify attributes to created or updated.**
Explanation	The request does not contain search attributes to be created or updated.
Action	Fix the request and submit it again.

CCECORE0018	**{0} did not get {1} for {2} seconds!**
Explanation	The specified node did not reach the expected status in the given amount of time.
Action	Retry the operation or contact SoftwareAG Global Support.

CCECORE0019	**Key {0} is invalid.**
Explanation	The specified key {0} is invalid.
Action	Specify a valid key, followed by a valid contract item identifier (for example, item=<contractItemIdentifier>).

CCECORE0020	**Contract item identifier {0} is invalid.**
Explanation	The specified contract item identifier {0} is invalid.
Action	Specify a valid contract item identifier (for example, item=<contractItemIdentifier>). You can find the valid contract item identifiers using the following command: cc list license-tools manifests contracts basepeak <nodeAlias> <productId>

CCECORE0021	**One contract item identifier expected.**
Explanation	Command Central expects one contract item identifier.
Action	Specify one valid contract item identifier.

CCECORE0022	**Could not retrieve Version of node {0}.**
Explanation	The error usually occurs because of issues connecting to node {0}.
Action	Check the logs for details about the connectivity issues.

CCECORE0023	**Cannot add contract item identifier assignment for runtime components with base and peak license key.**
Explanation	Command Central cannot add the manual contract item identifier assignment if the runtime component has a base and peak license key.
Action	Specify contract item idenfiers only for runtime components without base and peak license key.

CCECORE0025	**{0} did not get {1} for {2} seconds!**
Explanation	The specified node did not reach the expected status in the given amount of time.
Action	Retry the operation or contact SoftwareAG Global Support.

CCECORE0026	**{0} did not get {1} for {2} seconds!**
Explanation	The specified node did not reach the expected status in the given amount of time.
Action	Retry the operation or contact SoftwareAG Global Support.

CCECORE0027	**A node with the specified alias does not exist.**
Explanation	An installation (node) with the specified alias name does not exist.
Action	Specify a valid alias name for an existing installation (node).

CCECORE0028	**A runtime component with the specified id does not exist.**
Explanation	A runtime component with the specified ID does not exist on the node(s).
Action	Specify an ID of an existing runtime component.

CCECORE0029	**Cache update operation failed.**
Explanation	One of the automatic cache update operations failed to complete.
Action	Check the logs for details.

CCECORE0030	**Unknown cahce type: {0}. EventListener was not added because the required cache could not be created.**
Explanation	Ehcache is not configured properly.
Action	Contact Software AG global support.

CCECORE0031	**Unknown cahce type: {0}. EventListener was not removed because the required cache could not be created.**
Explanation	Ehcache is not configured properly.
Action	Contact Software AG global support.

CCECORE0032	**Invalid settings format: {0}**
Explanation	The format of the settings is as follows: key:value[;key:value]...
Action	Make sure that the settings comply with the specified format.

CCECORE0033	**Invalid value for period: {0}**
Explanation	The value for period must match the following pattern \d+h|m. Examples: 9m, 3h, 45m, 12h
Action	Make sure the period value complies with the specified format.

CCECPTE0000	**Invalid composite template alias: {0}**
Explanation	The composite template alias is not present or contains special characters.
Action	Specify a composite template alias. The template alias can include the following characters: letters, digits, hyphen and dot.

CCECPTE0001	**A composite template with alias {0} already exists.**
Explanation	A composite template with the specidied alias already exists.
Action	Change the alias of the composite template that is being imported or delete the existing composite template that has the same alias.

CCECPTE0002	**Missing property {0}.**
Explanation	A property is missing from the composite template definition.
Action	Add the missing property with a proper value.

CCECPTE0003	**Invalid value {0} for property {1}.**
Explanation	A property has an invalid value.
Action	Provide a proper value as described in the Command Central documentation.

CCECPTE0004	**A composite template with alias {0} does not exist.**
Explanation	A composite template with the specified alias does not exist.
Action	Import a composite template with the specified alias or use the alias of an existing composite template.

CCECPTE0005	**The requested repository version {0} was not found.**
Explanation	The requested repository version was not found.
Action	Provide an existing repository version or specify an image file location if the repository is of type image.

CCECPTE0006	**Invalid repository definition.**
Explanation	An invalid combination of properties was specified.
Action	See the Command Central documentation on how to define a repository.

CCECPTE0007	**The repository definition cannot have both version and location.**
Explanation	In the repository definition, the specified location defines that this is an image repository. However, a version cannot be specified for an image repository.
Action	Fix the repository definition. If it is an image repository, specify only a location. Otherwise, remove the location and specify proper credentials.

CCECPTE0008	**Cannot have both credentials and location in repository definition.**
Explanation	In the repository definition, location defines that this is an image repository. However, you cannot specify credentials for an image repository.
Action	Fix the repository definition. If the repository is an image repository, specify a location. If the repository is a master repository, remove the location and specify proper credentials.

CCECPTE0015	**The runtime status of runtime component {0} on node {1} is not online.**
Explanation	The runtime component has a status different than online.
Action	Check the logs on the node for issues which may cause the behavior.

CCECPTE0016	**The {0} lifecycle job of a runtime component on node {1} did not complete successfully.**
Explanation	The lifecycle job of a runtime component on a node did not complete successfully.
Action	Check the jobs on the node.

CCECPTE0017	**Define layers when there is a provisioning section.**
Explanation	Provisioning requires layers to be defined.
Action	Define a layers section.

CCECPTE0018	**Provisioning requires layer {0} however a layer is not defined.**
Explanation	All layers defined in the provisioning section should be defined in the layers section.
Action	Fix the layers section by adding the missing layers or change the provisioning section to not include layers.

CCECPTE0019	**Invalid layer alias: {0}**
Explanation	The layer alias is not present or contains special characters.
Action	Provide a layer alias. The layer alias can contain the following characters: letters, digits, hyphen and dot.

CCECPTE0020	**Invalid template alias: {0}**
Explanation	The template alias is not present or contains special characters.
Action	Provide a layer alias. The layer alias can contain the following characters: letters, digits, hyphen and dot.

CCECPTE0021	**Repository with name {0} is already defined.**
Explanation	A repository with the same name is already defined in the YAML document.
Action	Change the name of the repository, so that the name is unique in the scope of the document.

CCECPTE0022	**The maximum number of retries for applying template {0} on node {1} due to possible Platform Manager restarts is reached.**
Explanation	The maximum number of retries for applying a template on a node due to possible Platform Manager restarts is reached.
Action	Check the logs for details about previous attempts to apply the template to determine what the issues are.

CCECPTE0023	**{0} did not get {1} for {2} seconds!**
Explanation	The specified node did not reach the expected status in the given amount of time.
Action	Retry the operation or contact SoftwareAG Global Support.

CCECPTE0024	**Can not find any repository matching the provided host and name.**
Explanation	Command Central does not find a repository matching the specified host and name.
Action	Specify valid host and name.

CCECPTE0025	**Snapshot template {0} not found!**
Explanation	The snapshot template referred from the composite template cannot be found.
Action	Import a snapshot template with the specified alias and re-apply the composite template.

CCECPTE0027	**Server action {0} failed with a non-zero exit code: {1}**
Explanation	An action executing on the CommandCentral server failed.
Action	Make sure the action itself is correct and try again.

CCECPTE0032	**The jar command executable cannot be found on the source node installation.**
Explanation	The jar command executable cannot be found on the source node installation.
Action	Check the composite template logs.

CCECPTE0038	**Remote action {0} failed with a non-zero exit code: {1}**
Explanation	An action executing remotely failed.
Action	Make sure the action itself is correct and try again.

CCECPTE0039	**Neither script nor file exist for action: {0}!**
Explanation	An action must have either a script, or a file associated with it.
Action	Add a script or file and try again.

CCECPTE0040	**The runtime status of runtime component {0} on node {1} is not paused.**
Explanation	The runtime component has a status other than paused.
Action	Check the logs on the node for issues which may cause the behavior.

CCECPTE0041	**Environment {0} is not defined in 'provision'!**
Explanation	The environments in the 'provision' and 'migration' sections do not match.
Action	Make sure the same set of environments is present in both the 'provision' and 'migration' sections and try again.

CCECPTE0042	**Layer {0} referenced in 'migration' but not in 'provision'!**
Explanation	The layers referenced in the 'provision' and 'migration' sections do not match.
Action	Make sure the same set of layers are referenced from both the 'provision' and 'migration' sections and try again.

CCECPTE0043	**The number of nodes for layer {0} in 'migration' and 'provision' don't match!**
Explanation	The number of nodes for a given layer in the 'migration' section must match the number of nodes for the same layer in the 'provision' section.
Action	Make sure the number of nodes per layer is the same across the 'migration' and 'provision' sections and try again.

CCECPTE0044	**Executing more than one migration type in a single composite template is not supported: {0}, {1}. Check the source and target nodes hostnames and installation directories.**
Explanation	The composite template contains nodes that should be migrated using different migration type scenarios. This is not supported.
Action	Split or parameterize the template so that the migration is done using a single migration type.

CCECPTE0045	**Error during archiving the migration source node installation directory.**
Explanation	An error occurred during archiving the migration source node installation directory.
Action	Check the logs for the result of the executed remote archive command.

CCECPTE0046	**Runtime component with id {0} cannot be found.**
Explanation	Runtime component with the provided ID cannot be found.
Action	Check the Command Central logs for inventory service errors.

CCECPTE0047	**Cannot find node with alias {0} in the list of the bootstrapped migration source nodes: {1}.**
Explanation	Command Central cannot find the source node with the specified nodeAlias in the list of bootstrapped migration source nodes.
Action	Check the logs for previous errors.

CCECPTE0048	**Aborted because of a migration failure, see the logs for more details.**
Explanation	The entire composite template operation failed because of a migration error.
Action	Check the logs to identify the issue and try again.

CCECPTE0049	**Cannot skip run-time components stop operation when doing migration on the same host.**
Explanation	Skipping the run-time components stop operation when doing migration on the same host is not supported.
Action	To stop the run-time components, enable the migration/options/shutdown option in the composite template definition.

CCECPTE0050	**A {0} file could not be found in the imported composite template archive {1}.**
Explanation	The expected template yaml file could not be found in the imported composite template archive.
Action	Provide a valid template archive containing the expected template yaml file.

CCECPTE0051	**Source backup archive {0} was not found on the Command Central host.**
Explanation	The backup archive, created from the migration source node, was not found on the Command Central host.
Action	Check the logs for previous errors related to the backup archive creation or archive transfer from the source host to the Command Central host.

CCECPTE0052	**Source backup archive {0} was not found on host {1}.**
Explanation	The backup archive, created from the migration source node, was not found on the target host.
Action	Check the logs for previous errors related to backup archive transfer from the Command Central host to the target host. If the backup was transfered manually then check if its location is the expected by Command Central one.

CCECPTE0053	**Cygpath command returned empty result.**
Explanation	The Cygpath command returned empty result.
Action	Check the Command Central template logs.

CCECPTE0054	**Cannot skip run-time components stop operation for node {0} running on Windows when doing migration of type different hosts.**
Explanation	Skipping the run-time components stop operation when doing migration on different hosts running on Windows is not supported.
Action	To stop the run-time components, enable the migration/options/shutdown option in the composite template definition.

CCECPTE0055	**Unexpected YAML type {0} in field {1}! The correct type is integer.**
Explanation	Non-integer data was used in a field that requires integer.
Action	Use the correct integer value and try again.

CCECPTE0078	**Composite template validation for {0} completed: {1}**
Explanation	The validation detected that the compoiste template cannot be applied successfully.
Action	Read the validation report, fix the errors and try again.

CCECPTE0079	**The repository definition should not be empty.**
Explanation	A repository definition without properties is provided.
Action	Read the Command Central help on how to define a repository and provide the required properties.

CCECPTE0081	**Concrete node mapping or variable expected on {0}!**
Explanation	An unexpected value was specified.
Action	Use a concrete node mapping or variable and try again.

CCECPTE0083	**Support patches are not allowed in the "fixes" section: {0}**
Explanation	From DSL version 1.1 and above, support patches are not allowed in the "fixes" section.
Action	Move all patches to the "patches" section.

CCECPTE0084	**Node with alias {0} should be present in the landscape when alias mapping policy is EXISTING.**
Explanation	The nodes should be already registered in the landscape when alias mapping policy is "EXISTING."
Action	Add the node in the Command Central landscape.

CCECPTE0085	**Unknown node identifier type {0}**
Explanation	Command Central cannot identify the provided node identifier type.
Action	Provide a valid node identifier type.

CCECPTE0086	**The node host {0} is not part of the infrastructure layer.**
Explanation	The provided node host is not part of the infrastructure layer.
Action	Add the node host to the list of infrastructure layer hosts.

CCECPTE0087	**Illegal node index value {0}.**
Explanation	The provided node index value is not valid.
Action	Provide a value between 1 and number of nodes in the infrastructure layer.

CCECPTE0088	**Illegal node index {0} in the node alias {1}.**
Explanation	The provided node index value in the node alias is not valid.
Action	Provide an index value between 1 and the number of nodes in the infrastructure layer.

CCECPTE0089	**{0} policy cannot be used without having infrastructure layer defined.**
Explanation	The provided policy cannot be used without having an infrastructure layer defined.
Action	Provide an infrastructure layer.

CCECPTE0090	**Node with index {0} requested while the infrastructure layer has {1} nodes.**
Explanation	Invalid node index is requested.
Action	Provide a node index that corresponds to the layer nodes count.

CCECPTE0091	**DSL version 1.0 is not compatible with alias mapping policy: {0}. Allowed alias mapping policy: {1}.**
Explanation	DSL version 1.0 is not compatible with the provided alias mapping policy.
Action	Provide a compatible alias mapping policy, or use a DSL version above 1.0.

CCECPTE0092	**The "patches" section cannot be used in DSL version 1.0.**
Explanation	The "patches" section can be used in DSL version 1.1 and above.
Action	Either specify the patches in the fixes section, or change the DSL version to 1.1 or above.

CCECPTE0094	**Command Central was not able to retrieve the installation directory of the node with alias {0}.**
Explanation	Command Central was not able to retrieve the installation directory of a node.
Action	Check if the specified node is online and try again.

CCECPTI0026	**The following runtime components are started but not ready to accept client requests: {0}**
Explanation	Some runtime components have started, but are not ready to accept client requests.
Action	The components might require additional configuration.

CCECPTI0080	

CCECPTI0093	**Patches validation**

CCECPTW0030	**Source migration step {0} finished with error: {1}**
Explanation	The source node migration step finished with an error.
Action	Check the logs and identify the error root cause.

CCECPTW0031	**Skipping source node archive step. Source node installation directory is null.**
Explanation	Command Central will skip the source node archive step, because the source node installation directory is null.
Action	Start Platform Manager on the source node, retrieve the node information on Command Central when Platform Manager gets online.

CCEIMPE0004	**You cannot update the license location for the configuration type COMMON-LICLOC in Command Central.**
Explanation	You cannot update the license location for the configuration type COMMON-LICLOC in Command Central.
Action	Use the default license location.

CCEIMPE0005	**You cannot create a license location for the configuration type COMMON-LICLOC in Command Central.**
Explanation	You cannot create a license location for the configuration type COMMON-LICLOC in Command Central.
Action	Use the default license location.

CCEIMPE0006	**You cannot delete the license location for the configuration type COMMON-LICLOC in Command Central.**
Explanation	You cannot delete the license location for the configuration type COMMON-LICLOC in Command Central.
Action	Use the default license location.

CCEIMPE0007	**The product version is invalid.**
Explanation	In Command Central, when the license is created or updated for Command Central Engine, if the product version in license validation does not match the version of the product installed, this error is thrown.
Action	Provide a new license file with the product version matching the installed product.

CCEIMPE0009	**The product code is invalid.**
Explanation	In Command Central, when the license is created or updated for the Command Central Engine, if the product code does not match the Command Central Engine product code, this error is thrown.
Action	Provide a new license file with the product code matching with the Command Central Engine product code.

CCEIMPE0021	**A layer definition with the same name already exists.**
Explanation	A layer definition with the same name already exists.
Action	Specify a unique name for the layer type.

CCEIMPE0022	**A micro template with alias {0} does not exist.**
Explanation	A micro template with the specified alias does not exist.
Action	Specify the alias of an existing micro template.

CCEIMPE0023	**The provided configuration cannot be null.**
Explanation	The provided configuration cannot be null.
Action	Provide non-null layer definition configuration.

CCEIMPE0024	**Configuration of type CCE-LAYER-TYPES should have a name attribue with a valid id.**
Explanation	The name attribute of the specified configuration type should have an ID that contains only URL friendly symbols.
Action	Provide a URL-friendly ID for the name attribute.

CCEIMPE0025	**Providing micro template alias is required.**
Explanation	Specifying the micro template alias is required.
Action	Specify the alias of an existing micro template.

CCEIMPE0026	**Deleting default system layer definition {0} is not allowed.**
Explanation	Deleting default system layer definition is not allowed.
Action	Do not delete the default system layer definitions.

CCEINME0000	**Fix repository with Id {0} cannot be found.**
Explanation	The specified repository ID is not the ID of an existing repository.
Action	Check the input parameters and specify the ID of an existing repository.

CCEINME0001	**An error occurred while registering repository {0} on node {1}. Check the server logs for details.**
Explanation	The issue might occur because of a problem with the repository contents.
Action	Check the server logs for details.

CCEINRE0001	**A node with the specified alias does not exist.**
Explanation	An installation (node) with the specified alias name does not exist.
Action	Specify the valid alias name for an existing installation (node).

CCEINRE0002	**The specified runtime component is not a process!**
Explanation	The specified run-time component is not a PROCESS. Run-time components that are in the PROCESS category are components that function on their own. In contrast, run-time components that are in the ENGINE category cannot function on their own, but rather run within a PROCESS run-time component.
Action	Specify a PROCESS run-time component.

CCEJMRE0000	**A job with ID {0} cannot be found.**
Explanation	A job with the specified ID may have never existed or it may have completed long before this request.
Action	Use the following URI to list all jobs that are running or recently completed: /cce/jobmanager/jobs

CCEJMRE0001	**A node with alias {0} does not exist.**
Explanation	There is no node with the given alias in the landscape.
Action	Add the node to the landscape.

CCEJMRE0002	**A job with ID {0} on node {1} cannot be found.**
Explanation	A job with the specified ID may have never existed or it may have completed long before this request.
Action	Use the following URI to list all jobs that are running or recently completed: /cce/jobmanager/landscapejobs/local where "local" is the node alias

CCELCRE0000	**The lifecycle operation to execute is unknown.**
Explanation	You specified a lifecycle operation that is not valid. Valid lifecycle operations are start, stop, restart, pause, resume, start in debug mode, and start in safe mode. Note, however, that a run-time component might support only a subset of the valid lifecycle operations.
Action	Specify a valid lifecycle operation.

CCELCYE0003	**Error occured while executing lifecycle operation on a remote managed node with alias {0}. Remote task status is {1}**
Explanation	Error occured while executing lifecycle operation on a remote managed node.
Action	Check the Command Central and target node Platform Manager logs.

CCELCYE0004	**Error during lifecycle job execution.**
Explanation	An error occurred during the lifecycle job execution.
Action	Check the logs for details about the error.

CCELCYE0005	**At least one remote call has timed out.**
Explanation	At least one remote lifecycle execution call has timed out.
Action	Check the remote Platform Manager logs for related errors.

CCELIRE0000	**Error deleting license report with id: {0}**
Explanation	An unexpected error occurred when trying to delete the License Report with the given ID.
Action	Check the report id provided and if valid, check the server log for any exception messages.

CCELIRE0001	**Error deleting license reports.**
Explanation	At least one of the license reports was not deleted successfully.
Action	Retry the delete operation later or contact Software AG Global Support.

CCELIRE0003	**Exception while building license report Document, {0}: caught type({1}), msg({2})**
Explanation	A problem was encountered while attempting to build a License Report XML document from its string representation.
Action	Consult Software AG Global Support.

CCELIRE0004	**Invalid license manifest file.**
Explanation	The contents of the specified file is invalid for license manifest files.
Action	Specify a valid license manifest file.

CCELIRE0007	**The specified alias is not valid.**
Explanation	No additional details.
Action	Specify a valid alias. The alias can include up to 100 ASCII characters, numbers, underscore (_), hyphen (-), and period (.).

CCELIRI0008	**License manifest added.**

CCELIRI0009	**License manifest(s) removed.**

CCELIRI0010	**{0} embedded license key(s) found, {1} added, {2} replaced and {3} license key(s) removed.**

CCELIRI0011	**{0} embedded license key(s) removed.**

CCELIRW0002	**Error deleting the following reports: {0}**
Explanation	The specified reports could not be deleted successfully.
Action	Check the server log for more details and try to delete the reports individually.

CCELITE0000	**Error generating license report id!**
Explanation	An error occurred when trying to generate a unique report ID for the license report snapshot.
Action	Retry the operation or contact Software AG Global Support.

CCELITE0001	**Could not find a report with id {0}**
Explanation	No license report with the specified report ID was found in the system.
Action	Check the report ID value and try again.

CCELITE0002	**Error creating license snapshots directory {0}**
Explanation	An error occurred when trying to create a filesystem directory to store the license snapshots.
Action	Check if there is enough disk space and/or contact Software AG Global Support.

CCELITE0003	**Unable to get runtime component {0}/{1} caught: {2}**
Explanation	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
Action	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.

CCELITE0004	**Unable to get configuration types for {0}/{1} caught: {2}**
Explanation	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
Action	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.

CCELITE0005	**Unable to get configuration instances for {0}/{1} caught: {2}**
Explanation	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
Action	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.

CCELITE0006	**Unable to get configuration data for {0}/{1}/{2} caught: {3}**
Explanation	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
Action	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.

CCELITE0007	**Found null value for license configuration data for {0}/{1}/{2}**
Explanation	During license data collection, an attempt to retrieve license information about this runtime component found an invalid license.
Action	Contact Software AG Global Support.

CCELITE0008	**Expected a String value for license configuration data for {0}/{1}/{2}, found type {3}**
Explanation	During license data collection, an attempt to retrieve license information about this runtime component found an invalid license.
Action	Contact Software AG Global Support.

CCELITE0010	**Checksum verification failed for License Report with id {0} {1}.**
Explanation	The license report file may be corrupted or been tampered with, which has resulted in an integrity check failure.
Action	Regenerate the license report and/or contact Software AG Global Support with the affected license report file.

CCELITE0011	**Unable to generate and store license snapshot report; caught type: {0}, msg: {1}**
Explanation	An issue was encountered either when generating, or saving the generated license report snapshot.
Action	Check the exception and message to identify the exact cause, or contact Software AG Global Support.

CCELITE0012	**Unable to generate report, no report generator configured**
Explanation	The issue occurred because of incorrect component configuration.
Action	Check the license report configuration or contact Software AG Global Support.

CCELITE0013	**Error getting license report!**
Explanation	An error occurred when trying to retrieve the requested license report.
Action	Check the cause and retry the operation.

CCELITE0014	**Unable to parse license XML for {0}/{1} from string that follows; except msg: {2}. XML: {3}**
Explanation	The license content retrieved from the Platform Manager could not be parsed.
Action	Check the exception message for the exact cause and/or contact Software AG Global Support. The error may occur if a license file is found that is not in a standard Software AG format.

CCELITE0015	**Error generating pdf report for this reportId "{0}". Cause: {1}**
Explanation	The attempt to transform the XML data failed to produce a PDF data stream.
Action	Generate another report and verify whether the XML response is well-formed.

CCELITE0016	**Error generating pdf license report. No XML data stream available for "{0}"**
Explanation	The license reports module cannot produce a pdf report unless its canonical data is provided.
Action	Verify that the pdf generation task was executed properly using an existing report ID.

CCELITE0017	**Error generating pdf license report. Unable to locate XSLT style sheet for pdf generation. "{0}"**
Explanation	The license tools bundle could not locate the XSLT style used to produce a pdf report.
Action	Contact Software AG Global Support.

CCELITE0018	**Error applying license pdf report stylesheet "{0}" to XML data "{1}". Cause: {2}**
Explanation	Unexpected errors were encountered while generating the license pdf report.
Action	Contact Software AG Global Support.

CCELITE0019	**Unable to serialize a license report data object for "{0}". Cause: {1}**
Explanation	The license report data object could not be serialized as input for pdf report generation.
Action	Contact Software AG Global Support.

CCELITE0020	**Error verifying license report checksum.**
Explanation	An error occurred when trying to verify the license report checksum when retrieving the report.
Action	Retry request later or contact Software AG Global Support.

CCELITE0022	**Unable to open extended rights table ({0})**
Explanation	The indicated value is not available.
Action	Contact Software AG Global Support.

CCELITE0023	**Unable to load extended rights properties from {0}; caught: type({1}). message({2})**
Explanation	A problem was encountered while loading the indicated file into memory.
Action	Contact Software AG Global Support.

CCELITE0024	**Unable to close input stream from {0}; caught: type({1}). message({2})**
Explanation	A problem was encountered while cleaning up after loading the indicated file into memory.
Action	Contact Software AG Global Support.

CCELITE0026	**License manifest is already stored.**
Explanation	The license manifest is already been stored with alias {0}.
Action	Specify a different license manifest.

CCELITE0027	**Unable to store license manifest "{0}"; caught type: {1}, msg: {2}**
Explanation	An issue was encountered when storing a license manifest.
Action	Check the exception and message to identify the exact cause, or contact Software AG Global Support.

CCELITE0028	**Error creating storage location {0} for license manifests.**
Explanation	An error occurred when trying to create a filesystem directory to store license manifests.
Action	Check access rights and disk space or contact Software AG Global Support.

CCELITE0029	**Error retrieving license manifests.**
Explanation	An error occurred when trying to retrieve the list of stored license manifests.
Action	Check the cause and retry the operation.

CCELITE0030	**Could not find a license manifest with alias {0}**
Explanation	No license manifest with the specified alias was found in the system.
Action	Check the license manifest alias value and try again.

CCELITE0031	**Invalid license manifest.**
Explanation	The specified file is not a valid license manifest.
Action	Specify a valid license manifest.

CCELITE0032	**Checksum verification failed for LicenseMeteringConfiguration.xml file.**
Explanation	The LicenseMeteringConfiguration.xml file which is delivered with the CCE installation is either corrupted, or modified.
Action	Contact Software AG Global Support to get a valid LicenseMeteringConfiguration.xml file.

CCELITE0034	**Alias "{0}" already exists.**
Explanation	A license manifest with the specified alias already exists.
Action	Specify a new alias for the license manifest.

CCELITE0035	**License manifest alias missing.**
Explanation	No license manifest alias has been specified.
Action	Specify a valid license manifest alias.

CCELITE0036	**Deleting license manifest with alias "{0}" failed.**
Explanation	An error occured while trying to delete the license manifest with the specified alias.
Action	Check the exception and message to identify the exact cause, or contact Software AG Global Support.

CCELITE0037	**Deleting license manifests failed.**
Explanation	An error occured while trying to delete the license manifests.
Action	Check the exception and message to identify the exact cause, or contact Software AG Global Support.

CCELITE0042	**Invalid processor core class {0}.**
Explanation	The specified processor core class is not valid.
Action	Specify a valid processor core class.

CCELITE0046	**Checksum verification failed for the given License Manifest.**
Explanation	The license manifest file is corrupted or been tampered with, which has resulted in an integrity check failure.
Action	Use original license manifest file from Software AG and/or contact Software AG Global Support with the affected license manifest file.

CCELITE0047	**Cannot open license metering configuration file.**
Explanation	The license metering configuration file could not be read.
Action	Contact Software AG support.

CCELITE0048	**Updating {0} cache for node {1} failed.**
Explanation	Updating the cache failed. The license metering report may contain invalid data.
Action	Contact Software AG support.

CCELITE0049	**Processor core class is not available. Product cannot be checked.**
Explanation	The Platform Manager where the product is installed did not provide the processor core class the node is running on.
Action	Contact Software AG Global Support.

CCELITE0050	**Cannot find runtime status: {0}**
Explanation	The run-time status of the current landscape XML file was not found.
Action	Provide a valid landscape XML file.

CCELITE0051	**Cannot store license metering configuration data to file.**
Explanation	An error occured while writing the license metering configuration data to a new file.
Action	Contact Software AG Global Support.

CCELITE0053	**Platform Manager with version {0} is not sufficient for the license metering. Version 9.8 or higher is required.**
Explanation	The version of the Platform Manager is {0}. Platform Manager version of 9.8 or higher is required for the license metering.
Action	Update the Platform Manager with version 9.8 or higher.

CCELITE0054	**Consolidation of License Manifests failed.**
Explanation	An error occurred during the consolidation of the license manifests.
Action	Contact Software AG support.

CCELITE0055	**Collecting server details information failed.**
Explanation	An error occurred during the collection of server details information.
Action	Contact Software AG support.

CCELITE0056	**Generating license report compliance result failed.**
Explanation	An error occurred during the generation of the license report compliance result.
Action	Contact Software AG Global Support.

CCELITE0057	**License manifest for referenced location id {0} not found.**
Explanation	The license manifest for the location id {0} has been removed.
Action	Add the license manifest for the location id {0} to Command Central or assign a different location id to the installation details in the landscape overview tab.

CCELITE0058	**Unable to retrieve Command Central port number.**
Explanation	An error occured while trying to retrieve the port number of Command Central.
Action	Ensure that the Plaform Manager that belongs to this Command Central installation is running.

CCELITE0059	**The license metering cannot be stopped, because metering is required.**
Explanation	One of the active license manifests contains a product for which license metering is required, so that it is not possible to stop the metering.
Action	Remove the license manifest that requires metering or keep license metering running.

CCELITE0060	**No node alias specified.**
Explanation	The alias of a node was not specified.
Action	Specify a valid node alias. The available node aliases can be determined from the landscape configuration.

CCELITE0061	**No product id specified.**
Explanation	The ID of the product for which contracts are to be retrieved is not specified.
Action	Specify a valid product ID. The available product IDs can be determined from the landscape configuration.

CCELITE0062	**Node alias {0} is invalid.**
Explanation	A node with the specified alias {0} is not registered in Command Central.
Action	Specify a valid node alias. The available node aliases can be determined from the landscape configuration.

CCELITE0063	**No server details found for node with alias {0}.**
Explanation	The server details could not be determined for the node with the specified alias {0}.
Action	Make sure that the Platform Manager on the node with the specified alias is running.

CCELITE0064	**No product with id {0} found on node with alias {1}.**
Explanation	There is no product with the specified ID {0} installed on the node with the specified alias {1}.
Action	Specify the ID of a product that is installed on the node with the specified alias. The available product IDs can be determined from the landscape configuration.

CCELITE0065	**Platform Manager on node with alias {0} is not running.**
Explanation	The Platform Manager on the node with alias {0} is not running.
Action	Start Platform Manager on the node with alias {0} and execute the command again.

CCELITE0068	**Version {0} of license manifest is not supported. Highest supported version is {1}.**
Explanation	The version {0} of the specified license manifest is higher than the version {1} currently supported.
Action	Update Command Central to a version that supports the version of the specified license manifest.

CCELITE0069	**Version {0} of license report is not supported. Highest supported version is {1}.**
Explanation	The version {0} of the specified license report is higher than the version {1} currently supported.
Action	Update Command Central to a version that supports the version of the specified license report.

CCELITE0070	**Aggregated license report with alias {0} already exists.**
Explanation	An aggregated license report with the alias {0} already exists.
Action	Specify an aggregated license report with a different alias.

CCELITE0071	**Alias {0} already exists.**
Explanation	A license key with the specified alias {0} already exists.
Action	Specify a different alias.

CCELITE0072	**ProductCode and productId specified.**
Explanation	You must specify either productCode or productId.
Action	Remove either productCode or productId.

CCELITE0073	**Platform and OS specified.**
Explanation	You must specify either platform, or operating system.
Action	Remove either the platform or the operating system.

CCELITE0074	**Invalid platform(s) {0} specified.**
Explanation	The specified platform(s) {0} is invalid.
Action	Specify valid platform(s).

CCELITE0075	**Specified installationType {0} is invalid**
Explanation	The specified installationType {0} is invalid.
Action	Specify a valid installationType.

CCELITE0076	**Invalid productCode {0} specified.**
Explanation	The specified productCode {0} is invalid.
Action	Specify a valid productCode.

CCELITE0077	**Invalid productId {0} specified.**
Explanation	The specified productId {0} is invalid.
Action	Specify a valid productId.

CCELITE0078	**Invalid os {0} specified.**
Explanation	The specified OS {0} is invalid.
Action	Specify valid OS.

CCELITE0080	**Specified licenseKeyType {0} is invalid.**
Explanation	The specified licenseKeyType {0} is invalid.
Action	Specify a valid licenseKeyType.

CCELITE0081	**Error verifying landscape checksum.**
Explanation	An error occurred when trying to verify the landscape checksum.
Action	Contact Software AG Global Support.

CCELITE0082	**Invalid license key.**
Explanation	The specified file is not a valid license key. A valid license key must not contain binary data or be empty.
Action	Specify a valid license key.

CCELITE0083	**Invalid license key: {0}.**
Explanation	Specified file is not a valid license key.
Action	Specify a valid license key.

CCELITE0084	**A node with the specified alias does not exist.**
Explanation	An installation (node) with the specified alias name does not exist.
Action	Specify a valid alias name for an existing installation (node).

CCELITE0085	**A run-time component with the specified id does not exist.**
Explanation	A run-time component with the specified ID does not exist on the node(s).
Action	Specify an ID of an existing runtime component.

CCELITE0090	**Invalid productCode {0} and productId {1} specified.**
Explanation	The specified productCode {0} and productId {1} is invalid.
Action	Specify a valid productCode and productId.

CCELITE0091	**Unexpected exception occurred: {0}**
Explanation	An unexpected exception occurred: {0}
Action	Contact Software AG support.

CCELITE0092	**Failed to update server time stamp for server {0} : {1}**
Explanation	Failed to update server time stamp for server {0} : {1}
Action	Make sure the Platform Manager on server {0} is running.

CCELITE0093	**Error creating URL from urlString {0}.**
Explanation	Error creating URL from urlString {0}.
Action	Specifiy a valid URL.

CCELITE0094	**License key with specified alias {0} not found.**
Explanation	A license key with the specified alias {0} is not stored in the license key manager.
Action	Specify the alias of a stored license key.

CCELITE0102	**Alias must be specified for custom license keys.**
Explanation	You must specify an alias when adding a custom license key.
Action	Specify a license key alias.

CCELITE0105	**Invalid license key archive.**
Explanation	The specified file is not a valid license key archive. A valid license key archive must contain license keys.
Action	Specify a valid license key archive.

CCELITE0106	**License key already stored with alias {0}.**
Explanation	This license key is already stored with alias {0}.
Action	Specify another license key, or add the license key with a different alias.

CCELITE0107	**Licensing data is not available because the cache is not accessible.**
Explanation	All license metering data, like license keys, license reports, and license manifests, is stored in the cache, which is currently inaccessible.
Action	This problem can occur if the machine is slow. Ensure that the machine has enough resources and try it again.

CCELITI0033	**Type of installation is not defined. Product cannot be checked.**
Explanation	The Platform Manager where the product is installed does not have a type of installation (Development, Production, Test) defined.
Action	Define a type of installation for your Platform Manager.

CCELITI0038	**Product is not found in the license manifest(s).**
Explanation	You have no valid license for the installed product.
Action	Contact Software AG for licensing your product.

CCELITI0039	**Core class does not match: {0} is installed, {1} is licensed.**
Explanation	The core class of the Plarform Manager server does not match the licensed core class.
Action	Contact Software AG Global Support for licensing a higher core class.

CCELITI0040	**License capacity does not match: {0} {1} used, {2} {1} licensed.**
Explanation	The number of units used does not match the licensed number of units.
Action	Contact Software AG Global Support for licensing a higher number of units.

CCELITI0043	**Installation type does not match: {0} is installed, {1} is licensed.**
Explanation	The installation type of the Platform Manager server does not match the licensed installation type.
Action	Contact Software AG Global Support for licensing the appropriate installation type.

CCELITW0021	**Unable to translate extended rights code ({0}), not found**
Explanation	The table used to look up license Extended Rights codes does not contain the indicated value.
Action	Contact Software AG Global Support.

CCELITW0025	**LicenseReportFactory - unable to determine runtime status for component ({0}) on node ({1}); caught this: type({2}), msg({3})**
Explanation	Command Central can not determine if the identified component is up or down.
Action	This behavior could occur when the Platform Manager node is down, or because of some other communication issue. If this problem persists when the Platform Manager node is up, contact Software AG Global support.

CCELNDE0000	**The node alias is invalid.**
Explanation	An installation (node) with the specified alias name does not exist.
Action	Specify the valid alias name for an existing installation (node).

CCELNDE0001	**"{0}" Run-time component is not found on node "{1}".**
Explanation	The Landscape Inventory cache does not contain run-time component "{0}" for node "{1}".
Action	Use a combination of an existing run-time component Id and node alias or refresh the Landscape Inventory run-time component cache and try again.

CCELNDE0002	**Invalid node alias or url.**
Explanation	The specified alias name or URL for an installation (node) is not valid.
Action	Specify a valid alias name or URL.

CCELNDE0003	**Specify a valid URL.**
Explanation	The URL field in NodeInfo contains an invalid value.
Action	Check if the URL syntax of the node is valid.

CCELNDE0004	**A node with a different alias for the same host:port already exist.**
Explanation	An installation (node) with a different alias name already exists for the installation with the specified host name and port number.
Action	None.

CCELNDE0006	**Node {0} could not be created.**
Explanation	A node with alias {0} could not be created because another node with alias {1} already exists.
Action	Provide a different alias for the new node.

CCELNDE0008	**Can not retrieve node's product information for {0}**
Explanation	Command Central can not connect to Platform Manager to retrieve Platform Manager product information.
Action	Make sure the node is online.

CCELNDE0009	**Can not update inventory cache because of failure during retrieval of remote inventory items.**
Explanation	The remote request for inventory items failed and the inventory cache can not be updated.
Action	Ensure that the node in the request is active or the target node inventory is responsive.

CCELNDE0010	**The node alias cannot be empty or longer than 100 characters.**
Explanation	The specified node alias is incorrect, either because the node alias is empty, or it exceeds 100 characters.
Action	Specify a correct node alias and try again.

CCELNDE0011	**The host name should be between 2 and 253 characters long.**
Explanation	The host name is incorrect, because it is shorter or longer than the specified character length limitations.
Action	Provide a correct host name and try again.

CCELNDE0012	**The node display name should not be longer than 100 characters.**
Explanation	The node display name is incorrect, because it is longer than 100 characters.
Action	Specify a correct node display name and try again.

CCELNDE0013	**Trying to use unavailable NodeInfo element.**
Explanation	The specified element of type NodeInfo does not exist.
Action	Specify a NodeInfo element that is available.

CCELNDE0014	**Node alias is not valid. Only letters, numbers, -, _ and . are allowed.**
Explanation	The specified node alias is incorrect, because it uses special characters that are not allowed.
Action	Specify a correct node alias and try again.

CCELNDI0005	**You have exhausted the number of licensed nodes that can be configured. To add more nodes, contact your system administrator or Software AG support to get the license upgraded.**
Explanation	You have exhausted the number of licensed nodes that can be configured.
Action	To add more nodes, contact your system administrator or Software AG support to get the license upgraded.

CCELSRE0001	**The node alias cannot be updated.**
Explanation	You cannot update the alias name for an installation (node).
Action	Create a new installation or update the existing installation without changing the alias name.

CCELSRE0002	**The environment alias cannot be updated.**
Explanation	You cannot change the alias name of an environment.
Action	Create a new environment or update the existing environment without changing the alias name.

CCELSRE0004	**Node Aliases not specified!**
Explanation	To add installations (nodes) to an environment, you must specify the alias names of the installations that you want to add.
Action	Try again, this time specifying the installation (node) alias names as query parameters.

CCELSRE0005	**Alias not specified or invalid.**
Explanation	The environment could not be created or updated because the alias is invalid.
Action	Specify a valid alias. You can view a list of installations and theiraliases using the following command: cc list landscape nodes

CCELSRE0006	**Node {0} could not be created.**
Explanation	A node with alias {0} could not be created because another node with alias {1} already exists.
Action	Provide a different alias for the new node.

CCELSRE0007	**Environment {0} could not be created.**
Explanation	An environment with alias {0} could not be created because another environment with alias {1} already exists.
Action	Provide a different alias for the new environment.

CCELSRE0008	**Trying to use unavailable NodeInfo element.**
Explanation	Trying to use element of type NodeInfo that doesn't exist.
Action	Provide an available NodeInfo element.

CCELSRE0012	**Alias not specified.**
Explanation	The node could not be created because the alias is missing.
Action	Specify a valid alias.

CCELSRE0013	**Node {0} could not be created.**
Explanation	A node with alias {0} could not be created because the specified location id {1} does not exist.
Action	Provide an existing location id. Available location id(s): {2}

CCELSRE0014	**Node {0} could not be updated.**
Explanation	A node with alias {0} could not be updated because the specified location id {1} does not exist.
Action	Provide an existing location id. Available location id(s): {2}

CCELSRE0015	**Node {0} could not be created.**
Explanation	A node with alias {0} could not be created because the specified installation type {1} is invalid.
Action	Provide a valid installation type. Valid installation types are: {2}

CCELSRE0016	**Node {0} could not be updated.**
Explanation	A node with alias {0} could not be updated because the specified installation type {1} is invalid.
Action	Provide a valid installation type. Valid installation types are: {2}

CCELSRI0000	**A node with the specified alias does not exist.**
Explanation	No node alias matches {0}
Action	Provide a valid node alias.

CCELSRI0003	**The environment with the provided alias doesn't exist.**
Explanation	An environment with the specified alias name does not exist.
Action	Specify the valid alias name of an existing environment.

CCEMIGE0019	**Extracting source version failed.**
Explanation	Command Central failed to extract the source version from the bundles.info file.
Action	Ensure that the bundles.info file is at the correct location.

CCEMONE0001	**{0} on {1} ({2}) became unresponsive. Component restart may help to resolve this quickly.**
Explanation	{0} on {1} ({2}) became unresponsive.
Action	Component restart may help to resolve this quickly.

CCEMONE0002	**{0} on {1} ({2}) failed. You will need to start it again and investigate the cause of the failure.**
Explanation	RuntimeStatus of {0} went from "ONLINE" to "FAILED."
Action	Try to restart the operation. Have a look at {1} ({2}) for additional information about its status.

CCEMONE0006	**{0} of {1} on {2} ({3}) spiked into critical zone. The component may become overloaded!**
Explanation	The kpi {0} of {1} went from MARGINAL into CRITICAL status.
Action	Please have a look on {2} ({3}) to find out why this is happening.

CCEMONE0011	**Node with alias {0} does not exist.**
Explanation	There is no node with the specified alias registered with Command Central.
Action	Ensure that the node alias is spelled correctly and that it is registered with Command Central.

CCEMONE0012	**No runtime monitoring information could be found for component {0}.**
Explanation	The landscape nodes do not have monitoring information for the specified component.
Action	Check the landscape nodes for the for the specified component. Ensure that the specified component exists on the nodes and that it is spelled correctly.

CCEMONE0013	**Component {0} does not exist on node {1}.**
Explanation	The specified runtime component does not exist on the specified SPM node.
Action	Ensure that the specified component is spelled correctly and exists on the specified node.

CCEMONE0014	**Removing alert with id {0} failed.**
Explanation	The specified alert could not be found.
Action	Ensure that the alert with the specified ID exists in the Command Central landscape.

CCEMONE0015	**Error getting runtime component {0} for node {1}**
Explanation	Runtime component {0} is not available in cache.
Action	Try to update the inventory cache and make sure the node in the request is active and the target node inventory is responsive.

CCEMONE0016	**includeChildren parameter requires NodeAlias and RuntimeComponentId to be provided.**
Explanation	The <includeChildren> parameter requires the <nodeAlias> and <runtimeComponentId> parameters to be provided.
Action	Provide values for the <nodeAlias> and <runtimeComponentId> parameters.

CCEMONE0017	**Alerts filtering requires both NodeAlias and RuntimeComponentId.**
Explanation	The filtering of alerts requires both <NodeAlias> and <RuntimeComponentId> parameters to be provided.
Action	Provide values for both <NodeAlias> and <RuntimeComponentId> parameters.

CCEMONE0018	**Error while handling event [{0}].**
Explanation	There was an error while handling an event.
Action	Check the logs for previous errors.

CCEMONE0019	**Error polling SPM node [{0}].**
Explanation	The monitoring states for a runtime component on a target node could not be retrieved.
Action	Check the logs for previous errors.

CCEMONE0020	**Error during retrieving of monitoring state of {0} on node {1}.**
Explanation	The monitoring state for a runtime component on a target node could not be retrieved.
Action	Check the logs for previous errors.

CCEMONE0021	**Error polling SPM node [{0}]. Node Status will be set to {1} and the Runtime State for all instances of the node will be set to {2}.**
Explanation	The monitoring states on a target node could not be retrieved and as a result all states will be set to unknown.
Action	Check the logs for previous errors.

CCEMONE0022	**Could not retrieve Cache. Monitoring stopped.**
Explanation	The Command Central cache manager could not be retrieved.
Action	Contact Software AG Global Support.

CCEPROE0000	**No node with alias, {0}, exists in the environment.**
Explanation	The node alias specified in the request does not exist.
Action	Resubmit the request with an existing node alias.

CCEPROE0001	**No artifacts specified in uninstall request.**
Explanation	The uninstall request did not specify any artifacts.
Action	Resubmit the request with a list of valid artifacts.

CCEPROE0002	**{0} is an invalid/unsupported type for artifacts.**
Explanation	Only Product and Fix are valid artifact types.
Action	Resubmit the request with valid artifacts.

CCEPROE0003	**{0} MASTER repository configuration is invalid.**
Explanation	The repository configuration misses the location URL.
Action	Remove and add this repository again to ensure it has valid remote location URL.

CCEPROE0004	**{0} repository is not configured with user credentials.**
Explanation	The repository configuration misses username property value. Most likely the repository was not configured with the required user credentials after it was discovered.
Action	Configure the repository with valid user credentials.

CCEPROE0005	**{0} repository is not configured with user credentials.**
Explanation	The repository configuration misses the username property value. Most likely the repository was not configured with the required user credentials after it was discovered.
Action	Configure the repository with valid user credentials.

CCEPROE0006	**{0} IMAGE repository configuration is invalid.**
Explanation	The repository configuration misses the image file location.
Action	Edit this repository to ensure it has a valid image location.

CCEPROE0007	**Node {0} is already registred and reports ONLINE status.**
Explanation	The node that you are attempting to bootstrap already reports ONLINE status. Most likely you specified a node that is already setup and ready to use.
Action	Use a node alias for a Platform Manager that is not running yet. It can be a node that is already registered but does not have a backing Platform Manager, or a completely new node alias that will be added to the landscape when the Platform Manager bootstrap operation is finished.

CCEPROE0008	**Repository {0} type is not a MASTER repository.**
Explanation	Bootstrap images can be generated only from a MASTER PRODUCT repository. Other types are not supported.
Action	Specify a configured MASTER PRODUCT repository with valid user credentials and try again.

CCEPROE0009	**Repository {0} is not configured with a user password.**
Explanation	MASTER repositories require configuration of user credentials.
Action	Ensure that the selected repository is configured with a valid username and password.

CCEPROE0010	**Target machine platform is not specified.**
Explanation	The bootstrap operation requires the target platform to be explicitely defined.
Action	Select platform of the target machine that Platform Manager will be installed

CCEPROE0011	**Cannot match requested version {0} to any of the configured repositories.**
Explanation	The version you requested to install does not match the available repositories.
Action	Select a specific repository or add new repositories that will match the version you requested.

CCEPROE0012	**No PRODUCT repositories are defined to complete the operation.**
Explanation	You did not explicitly specify a repository or version to use and Command Central cannot automatically pick a repository.
Action	Ensure that you have configured a PRODUCT repository that contains the required version of Platform Manager.

CCEPROE0013	**Remote machine credentials are not provided.**
Explanation	Command Central cannot connect to a remove machine without valid user credentials.
Action	Provide user credentials for the remote machine on which you are installing Platform Manager.

CCEPROE0014	**Error while retrieving configuration.**
Explanation	Internal error while retrieving common proxy configuration.
Action	Make sure COMMON-PROXY configuration exists.

CCEPROE0015	**Remote access service returned {0} jobs while 1 was expected.**
Explanation	Only one remote operation was initiated but a different amount of jobs was returned.
Action	Contact Software AG Global Support.

CCEPROE0016	**Java not found on {0}.**
Explanation	The Java Runtime Environment is not available on the given node.
Action	Install Java Runtime Environment and try again.

CCEPROE0017	**Remote command returned a non-zero exit code: {0}**
Explanation	The remote installer command failed. Check the logs for more information.
Action	Re-try the operation. If the problem persists, contact Software AG Global Support.

CCEPROE0018	**Can not connect to Platform Manager running on host {0} and port {1} due to wrong credentials.**
Explanation	Can not connect to Platform Manager due to wrong credentials.
Action	Provide valid Platform Manager credentials.

CCEPROE0026	**The nodeAlias field is required for each node that is added.**
Explanation	Node alias is required field for each node that is added.
Action	Provide node alias.

CCEPROE0027	**The hostname field is required for each node that is added.**
Explanation	A hostname is required field for each node that is added.
Action	Provide a hostname.

CCEPROE0028	**Platform Manager port is required field for each node that is added.**
Explanation	A Platform Manager port is required field for each node that is added.
Action	Provide a port field value.

CCEPROE0029	**Platform Manager nodes are available, but the provided credentials for them are wrong: {0}**
Explanation	Platform Manager nodes are available, but the provided credentials for them are incorrect.
Action	Provide valid credentials for the Platform Manager nodes.

CCEPROE0030	**The Platform Managers are not remotely accessible: {0}**
Explanation	The specified Platform Managers are not remotely accessible.
Action	Check the connectivity and the remote accessibility to the Platform Managers.

CCEPROE0034	**Error occured while installing {2} on node {0}. Remote task status is {1}**
Explanation	The selected artifact was not installed on the remotely managed node.
Action	Check the error logs for more details about this error.

CCEPROE0038	**The maximum number of retries for installing artifacts from repository {0} on node {1} due to possible Platform Manager restarts is reached.**
Explanation	The maximum number of retries for installing artifacts from repository {0} on node {1} due to possible Platform Manager restarts is reached.
Action	Check the logs for details about previous attempts to install artifacts to determine what the issues are.

CCEPROE0042	**The maximum number of retries for uninstalling artifacts on node {0} due to possible Platform Manager restarts is reached.**
Explanation	The maximum number of retries for uninstalling artifacts on node {0} due to possible Platform Manager restarts is reached.
Action	Check the logs for details about previous attempts to install artifacts to determine what the issues are.

CCEPROE0043	**Creating an image with name {0} failed.**
Explanation	Creating an image from a mirror repository that is not on the local Platform Manager is not supported.
Action	Create a mirror repository on the local Platform Manager node and use it for bootstrapping.

CCEPROE0044	**Bootstrapping Platform Manager on installation with alias {0} failed.**
Explanation	The export of artifacts from a mirror repository with name {0} into image with name {1} failed.
Action	See the Platform Manager logs for more information.

CCEPROE0046	**Bootstrap installer {0} not found.**
Explanation	The bootstrap installer file was not found under install_dir/profiles/CCE/data/installers
Action	Make sure the specified bootstrap installer file is in the correct location.

CCEPROE0047	**unzip command not found on {0}**
Explanation	The unzip package is not present in your cygwin environment.
Action	Install unzip in your cygwin environment and try again.

CCEPROE0048	**Local bootstrap completed with exit code: {0}**
Explanation	The execution of the bootstrap operation failed unexpectedly.
Action	Check the bootstrap logs for more information.

CCEPROE0049	**The installers directory does not exist.**
Explanation	The directory containing the bootstrap installers does not exist.
Action	Create the install_dir/profiles/CCE/data/installers directory.

CCEPROE0050	**Installer platform mismatch! Expected W64 but found {0}.**
Explanation	The installation cannot be performed, because the incorrect platform is selected.
Action	Select an installer with the correct platform.

CCEPROE0051	**{0} is not a valid installer directory or it does not exist.**
Explanation	The bootstrap installer archive may not have been extracted correctly.
Action	Retry the operation or contact Software AG global support.

CCEPROE0052	**Invalid number of Windows scripts in the installer directory: {0}**
Explanation	The bootstrap installer archive must contain exactly one executable script (batch).
Action	Obtain the correct bootstrap installer.

CCEPROE0055	**Platform Manager nodes are available, but the installation directory is different than requested: {0}**
Explanation	The Platform Manager nodes are available, but the installation directory is different than requested.
Action	Change the installation directory or stop the available Platform Manager if you want to bootstrap a new instance on the same ports.

CCEPROE0056	**Error occured while uninstalling {2} on node {0}. Remote task status is {1}**
Explanation	The selected artifact was not uninstalled on the remotely managed node.
Action	Check the error logs for more details about this error.

CCEPROW0045	**The SSH server did not return the exit code of the bootstrap operation. The operation has completed but it is not clear if it was successful or not.**
Explanation	In some cases the SSH server may not return the exit code of the executed operation. This makes it unclear if the operation was successful or not.
Action	Examine the installation logs on the remote node to make sure the installation was successful.

CCERARE0000	**Not all mandatory parameters are specified.**
Explanation	Some of the parameters required for this request are missing.
Action	Check the Command Central documentation for the required parameters.

CCERARE0001	**Nothing has been scheduled for execution for this request.**
Explanation	This request should start jobs for execution, but no jobs have started.
Action	Check the logs for errors why the request has not terminated properly.

CCERARE0002	**Remote Access Service is missing.**
Explanation	A required service is missing.
Action	Check whether the remote-access bundle is started and has registered any services.

CCERARE0003	**The private key must be specified when certificate is used for authentication.**
Explanation	The selected authorization method is "certificate", however, a path to the private key is not specified.
Action	Specify the path to the private key.

CCEREAE0003	**Authentication method {0} not supported.**
Explanation	The specified authentication method is not supported.
Action	Check the Command Central documentation for the supported authentication methods.

CCEREAE0004	**The provided private key does not exist: {0}**
Explanation	The specified file that contains the private key does not exist on the file system.
Action	Make sure the private key is available.

CCEREAE0005	**Remote host should be specified.**
Explanation	Remote host is not specified and a connection cannot be established.
Action	Specify the remote host.

CCEREAE0007	**{0} not found on {1}**
Explanation	The specified path cannot be found on the target host.
Action	Make sure the specified path exists and try again.

CCEREAE0008	**Invalid output from df: {0}**
Explanation	The output of the df command does not match the POSIX standard.
Action	Make sure the target system has a POSIX compliant df command.

CCEREAE0009	**The home directory of user {0} on host {1} could not be found.**
Explanation	The home directory of the specfied user on the specfied host could not be found.
Action	Check the configuration of the remote endpoint.

CCEREAE0010	**Cannot close remote receive session.**
Explanation	The remote session for receiving files cannot be closed.
Action	Check the logs for previous erros.

CCEREMW0000	**Error producing zipped log source contents. Node alias: {0}, RuntimeComponent: {1}, Log Source Aliases: {2} Details: {3}**
Explanation	An error occurred while producing the zipped archive containing a collection of log source contents on the Command Central server.
Action	Try again. If the problem persists, contact Software AG Global Support.

CCEREMW0001	**Error attempting to close a file store used to produce zipped collection of log source contents.**
Explanation	An error occurred while closing the zip file system object containing a collection of log source file contents.
Action	No action required.

CCEREMW0002	**Error attempting to delete a temporary file used to create a zipped collection of log source contents. Filename: {0}**
Explanation	An attempt to delete the specified file has failed.
Action	Locate the file on the server hosting Command Central and delete the file if it still exists.

CCEREMW0004	**Error producing zipped log source contents. Node alias: {0} Details: {1}**
Explanation	An error occurred while producing the zipped archive containing a collection of log source contents on the Command Central server.
Action	Try again. If the problem persists, contact Software AG Global Support.

CCEREPE0000	**No repository with id, {0}, exists on managed node, {1}**
Explanation	The specified repository does not exist.
Action	Ensure the correct repository id is specified in the request, or add the desired repository to the managed node.

CCEREPE0001	**No repository with id, {0}, exists on managed node, {1}**
Explanation	The specified repository does not exist.
Action	Ensure the correct repository id is specified in the request, or add the desired repository to the managed node.

CCEREPE0002	**No such node, {0}**
Explanation	The node alias specified in the request does not exist.
Action	Specify the correct node alias, or add the relevant node to the environment.

CCEREPE0003	**The specified image location does not exist.**
Explanation	The specified location for an image repository was not found on the file system.
Action	Provide a valid location for the image repository.

CCEREPE0004	**The specified repository does not exist.**
Explanation	The specified repository was not found.
Action	Check the repository name and provide the name of an existing repository.

CCEREPE0005	**Parameters cannot be empty or missing.**
Explanation	All parameters are required.
Action	Specify values for all parameters.

CCEREPE0006	**A repository with this name already exists.**
Explanation	The name of the repository should be unique.
Action	Check the repository name and provide a unique name for the repository.

CCEREPE0007	**A repository at the same location already exists.**
Explanation	Two or more repositories cannot point to the same location.
Action	Provide a unique location for the new repository.

CCEREPE0008	**The specified repository points to an image file but the repository type is not image.**
Explanation	The specified repository cannot point to and image file, because the repository type is not image.
Action	Specify the correct repository type.

CCEREPE0009	**There is no repository to register.**
Explanation	No repository is found for the specified name.
Action	Check the repository and resubmit the request.

CCEREPE0010	**User credentials are missing.**
Explanation	No user credentials are specified for the repository.
Action	Add user credentilas for the repository.

CCEREPE0011	**Connection to node {0} failed.**
Explanation	Could not connect to node {0}.
Action	Check if the node is online.

CCEREPE0012	**Repository with type {0} does not exist.**
Explanation	The repository with the specified type does not exist.
Action	Specify an existing repository type for the repository.

CCEREPE0013	**Repository content cache invalidate failed.**
Explanation	Invalidation of the content cache for repository {0} and nodeAlias {1} failed.
Action	See the Command Central logs for more details.

CCEREPE0015	**Repository with the specified name: {0} does not exists.**
Explanation	Importing content from the repository with name: {0} failed because a repository with the specified name was not found.
Action	Check the repository name and provide the name of an existing repository.

CCEREPE0020	**Error occured while importing artifacts from repository with name: {0} to mirror repository with name: {1} for platforms: {2}**
Explanation	An error occured while importing artifacts from repository with name: {0} to mirror repository with name: {1} for platforms: {2}
Action	See the corresponding Platform Manager logs for more details.

CCEREPE0024	**Mirror repository with name: {0} is not published or registered on Command Central.**
Explanation	Command Central cannot identify the specified mirror repository.
Action	Check if a mirror repository with name: {0} is published and registered on Command Central. Note that the Refresh operation refreshes a published mirror repository immediately after it is created or at a later point in time.

CCEREPE0029	**Local mirror repository with name {0} can not be removed on target node {1}**
Explanation	The local mirror repository with name {0} can not be removed on the target node {1}
Action	See the corresponding Platform Manager logs fro more details.

CCEREPE0035	**Remote task failed: {0}**
Explanation	Remote task failed: {0}
Action	See the corresponding Platform Manager logs for more details.

CCEREPE0036	**Intiating mirror operation not from an image repository and without selecting "Product Repositories" is not supported.**
Explanation	This operation is not supported as it might be time consuming because of the size of the source repository.
Action	Either select a product repository, or change the source repository to an image repository.

CCEREPE0038	**Cannot delete Mirror repository with name: {0} because node with alias: {1} does not exists. Register node for host:{2} and port:{3}.**
Explanation	The mirror repository is physically stored on {1} node, which was deleted and is not now registered in Command Central.
Action	Add the node with alias: {1} , host: {2} and port: {3}

CCEREPE0039	**Cannot perform mirror operation because node with alias: {0} does not exists any more. Register again the node with alias: {0} for host: {1} and port: {2}.**
Explanation	The mirror repository is physically stored on {0} node, which was deleted and is not now registered in Command Central.
Action	Add the node with alias: {0} , host: {1} and port: {2}

CCEREPE0041	**Content of repository with displayName : {0} cannot be loaded.**
Explanation	The content of the repository with displayName : {0} cannot be listed.
Action	Use a different repository type or check all logs for details about the error.

CCEREPE0042	**Generation of repository status report for repository {0} will be skipped because connectivity validation failed.**
Explanation	Generating the Repository Status report will be skipped and the list content operation will not be triggered.
Action	Check if the proxy is available and if the Platform Manager proxy configuration is set correctly. Also, check if the user credentials are valid.

CCEREPE0043	**Creating a mirror repository failed because the source repository is not specified.**
Explanation	The source repository from which to create the mirror repository is not specified.
Action	Specify at least one source repository. You can specify a master, image, or another mirror repository.

CCEREPE0044	**Attempt to connect to {0} product repository from {1} installation timed out.**
Explanation	Internet access is required to connect to this repository. The error occurred either because the proxy for the local Platform Manager is not configured, or the metadata and the user credentials for the repository are not correct.
Action	Configure a proxy for the local Platform Manager and check the repository metadata.

CCEREPE0048	**Repository fix content cache update failed.**
Explanation	An explicit repository fix content cache update failed during the regular cache update.
Action	Check if the connection to the fix repository is successful.

CCEREPE0049	**Remote task failed: {0}**
Explanation	Remote task failed\: {0}
Action	Check the corresponding Platform Manager logs for more details about the error.

CCEREPE0052	**Error while retrieveing credentials with alias {0}.**
Explanation	A credentials alias is not defined.
Action	Try again using an existing credentials alias.

CCEREPE0053	**The specified repository name {0} is not valid.**
Explanation	No additional details.
Action	Specify a valid repository name. The name can include ASCII characters, numbers, underscore (_), hyphen (-), and period (.).

CCERPRE0000	**The repository name is not specified.**
Explanation	The requested operation requires a repository name.
Action	Check the input and provide a repository name.

CCERPRE0001	**Repository with the specified name {0} already exists.**
Explanation	The repository name must be unique.
Action	Check the repository name and provide a unique name for the repository.

CCERPRE0002	**Repository with the specified name {0} does not exists.**
Explanation	Editing the repository failed, because a repository with the specified name was not found.
Action	Check the repository name and provide the name of an existing repository.

CCERPRE0003	**Unknown repository type. Use one of {0}**
Explanation	The specified repository type is not supported by Command Central.
Action	Use one of the suggested repository types.

CCERPRE0004	**Destination is not specified.**
Explanation	The destination parameter is missing.
Action	Specify a value for the destination parameter. For example, dest=myfixes.zip

CCERPRE0005	**Destination parameter contains invalid characters.**
Explanation	The destination parameter cannot contain file path manipulation characters.
Action	Specify a proper destination value. For example, dest=myfixes.zip

CCERPRE0006	**Export image job is not found.**
Explanation	The job responsible for creating an image is not found on the local Platform Manager.
Action	Check the logs for indication what went wrong.

CCERPRE0007	**The specified path for the image file is not valid.**
Explanation	The path specified for the image file is not valid.
Action	Provide a valid path for the image file.

CCERPRE0008	**The specified repository content type ({0}) did not match the actual content type of the repository ({1}).**
Explanation	The specified repository content type ({0}) did not match the actual content type of the repository ({1}).
Action	Verify that the specified repository content type is correct.

CCERPRE0009	**The specified repository image file location "{0}" is not valid.**
Explanation	The specified repository image file location "{0}" is not valid.
Action	Provide a valid repository image file location.

CCERPRE0010	**The artifact : {0} is not found in the repository : {1}**
Explanation	The identifier specified for the artifact is not valid or the artifact does not exist in the repository.
Action	Provide a valid identifier for the artifact: <id>_<version>.

CCERPRE0011	**Command Central cannot find the specified image file at the specified location "{0}".**
Action	Make sure the given path and file name are correct.

CCERPRE0012	**Repository with name {0} is not found.**
Explanation	There is no registered repository with the provided name.
Action	Provide a valid name of a registered repository.

CCERPRE0013	**Repository image location URI is not valid.**
Explanation	The location you provided is empty or not a valid URI.
Action	Ensure the provided location is not empty, does not include white spaces and points to a valid image file.

CCERPRE0014	**The specified repository name {0} is not valid.**
Explanation	No additional details.
Action	Specify a valid repository name. The name can include up to 100 ASCII characters, numbers, underscore (_), hyphen (-), and period (.).

CCESREE0000	**Error occurred during retrieving user credentials**
Explanation	This error might occur due to the following reasons: - Users attempt to get credentials when the credentials data store is empty; - While setting credentials, the communication with the remote SPM failed; - While deleting credentials, the communication with the remote SPM failed.
Action	Ensure that: - If you are attempting to get the credentials, the credentials data store is not empty. - If you are setting the credentials, the remote SPM is accessible. - If you are deleting the credentials, the remote SPM is accessible.

CCESREE0001	**Specify the private key when certificate is used for authentication.**
Explanation	The selected authorization method is "certificate", however, the path to the private key is not specified or is invalid.
Action	Specify a valid path to the private key.

CCETEME0000	**A job with ID {0} cannot be found.**
Explanation	The job with the specified ID may have completed long before this request.
Action	Use the following URI to list all recently completed or runnig jobs: /cce/jobmanager/jobs

CCETEME0001	**The remote request encountered a concurrency error.**
Explanation	The system could not execute parallel remote requests.
Action	Contact Software AG Global Support.

CCETEME0002	**A job with ID {0} did not completed successfully in {1} seconds.**
Explanation	The job with the specified ID may require more time to complete.
Action	Use the following URI to list all recently completed or running jobs: /cce/jobmanager/jobs

CCETEME0003	**Template metadata cannot be empty.**
Explanation	The template metadata is required for creating a template.
Action	Ensure that you have provided metadata for the template. The metadata.Alias and nodeAlias fields are required.

CCETEME0004	**Template alias cannot be empty.**
Explanation	The template alias is a required attribute of the template metadata.
Action	Specify a value for the template alias attribute.

CCETEME0005	**Template nodeAlias cannot be empty.**
Explanation	The template nodeAlias is a required attribute of the template metadata.
Action	Specify a value for the nodeAlias attribute.

CCETEME0006	**Template options cannot be empty.**
Explanation	The template options attribute is required in the template metadata.
Action	Specify at least one option and retry.

CCETEME0007	**Error occurred during template creation {0}**
Explanation	Creating the template failed with an error.
Action	Check the error logs for more details.

CCETEME0008	**Error occurred during template creation on the remote managed node with alias : {0}. Remote task status is {1}**
Explanation	Creating a template on the remote managed node with the specified ID failed with an error.
Action	Check the job status.

CCETEME0009	**A template with alias: {0} already exists.**
Explanation	Another template with the same alias already exists.
Action	To overwrite the existing template, add the OVERWRITE_TEMPLATE option in the template metadata.To create a new template and keep the existing template, change the template alias.

CCETEME0010	**Node with alias : {0} does not exist.**
Explanation	A managed installation (node) with the specified alias name does not exist.
Action	Specify a valid alias name for an existing installation (node).

CCETEME0011	**A problem occured while downloading template with alias {0} on Command Central.**
Explanation	Command Central could not create a folder for the template on the file system.
Action	Contact the Command Central Administrator.

CCETEME0012	**A template with alias {0} could not be found.**
Explanation	Command Central could not find a template with the specified alias.
Action	Check if the specified alias for the template you want to delete is correct.

CCETEME0013	**Error occurred while creating a template on the remote managed node with alias: {0}. Remote task status is {1}**
Explanation	Creating the template fails with a "Nothing to download on Command Central" error.
Action	See the error logs for the error details.

CCETEME0014	**Template with alias {0} was not found.**
Explanation	Command Central could not find a template with the specified alias.
Action	Verify that the alias is spelt correctly and that a template with this alias is already created. If the template is not created, execute a create template operation.

CCETEME0015	**Template already exists.**
Explanation	A template with the specified alias already exists.
Action	Change the alias of the imported template or delete the existing template with the same alias.

CCETEME0016	**A problem occured while importing the template.**
Explanation	Command Central could not create a folder for the template on the file system.
Action	Contact the Command Central Administrator.

CCETEME0017	**Could not import template because a required file was not found.**
Explanation	Command Central could not find or access the file from which to import the template.
Action	Contact the Command Central Administrator.

CCETEME0018	**Template data is invalid.**
Explanation	The provided template data could not be deserialised.
Action	Check if the provided template data is corrupted.

CCETEME0019	**Template options cannot be empty.**
Explanation	The template options attribute is required in the template metadata.
Action	Specify at least one option and retry.

CCETEME0020	**The requested service temporarily not available.**
Explanation	The requested service temporarily not available. This may be due to Platform Manager (SPM) being in the process of shutting down or still loading at start up.
Action	Ensure that Platform Manager is running and Installation has ONLINE status.

CCETEME0021	**The Platform Manager (SPM) is shut down.**
Explanation	The Platform Manager (SPM) is shut down.
Action	Ensure that Platform Manager is running and Installation has ONLINE status

CCETEME0022	**Template metadata must be specified.**
Explanation	Specify metadata for the template.
Action	Check the input parameters.

CCETEME0023	**Node Alias must be specified.**
Explanation	The template input parameters must include Node Alias.
Action	Check the input parameters.

CCETEME0024	**Repository Id must be specified.**
Explanation	The template input parameters must include Repository Id.
Action	Check the input parameters.

CCETEME0025	**Repository with Id {0} cannot be found.**
Explanation	The template input parameters must include Repository Id of existing Repository.
Action	Check the input parameters.

CCETEME0026	**Template metadata in {0} cannot be unmarshalled.**
Explanation	The file containing the metadata for the template cannot be read.
Action	Make sure the file exists, can be read and contains valid XML.

CCETEME0027	**An error occurred while registering Repository {0} on Node {1}. Check the Server logs for details.**
Explanation	The issue might occur because of a problem with the Repository contents.
Action	Check the Server logs for details.

CCETEME0028	**Unable to obtain snapshot template job group id for node {0}.**
Explanation	Command Central was unable to obtain the snapshot template job group id for a node.
Action	Contact Software AG Global Support.

CCETEME0029	**Error during checking remote job status.**
Explanation	An error occurred while checking the remote job status.
Action	Check if Platform Manager is running.

CCETMRE0000	**Specify template alias, options, and target node.**
Explanation	Template alias, target node alias, and options are required parameters for this template.
Action	Specify values for all required parameters.

CCETMRE0001	**{0} option is specified but a repository for the option is not specified.**
Explanation	A repository for the option is not specified.
Action	Specify a repository for the option. For example, if the option is PRODUCTS, specify a product repository.

CCETMRE0002	**The specified repository is not applicable for this option {0}**
Explanation	The specified repository is not applicable for the specified option.
Action	Specify a proper repository. For example, if the option is PRODUCTS, specify a product repository.

CCETMRE0003	**There is no repository that supports the specified option {0}.**
Explanation	The specified option is not supported by the specified repositories. For example, the error occurs if the FIXES option is specified, but the repository for this option does not support fixes.
Action	Specify a proper repository. For example, if the specified option is FIXES, specify a repository that contains fixes.

CCETMRE0004	**No suitable option found for {0}.**
Explanation	No matching option found for the specified parameter.
Action	Specify a supported template option.

CCETMRE0005	**The alias, nodeAlias, and runtimeComponentId parameters are required for generating a composite template.**
Explanation	The alias, nodeAlias, and runtimeComponentId parameters are required for generating a composite template.
Action	Provide the required parameters with the generation request data.

CCEWCME0009	**Display name cannot be empty.**
Explanation	Display name is required.
Action	Provide the display name.

CCEWCME0010	**Alias {0} cannot be empty.**
Explanation	Environment alias and node alias cannot be empty.
Action	Provide a valid alias name.

CCEWCME0011	**{0} cannot exceed {1} characters.**
Explanation	The specified field input is incorrect.
Action	Check the error message and provide the correct input to the specified field.

CCEWCME0012	**Environment name or alias cannot be {0}.**
Explanation	Incorrect environment name/alias provided.
Action	Check the error message and provide the correct input.

CCEWCME0013	**{0} alias cannot contain {1} non-ASCII characters.**
Explanation	Environment alias cannot contain non-ASCII characters.
Action	Make sure the value of the alias field is correct.

CCEWCME0014	**Alias {0} cannot contain spaces.**
Explanation	Environment alias cannot contain spaces.
Action	Make sure the value of the alias field is correct.

CCEWCME0015	**{0} already exists.**
Explanation	The specified node/environment already exists.
Action	Specify a correct node/environment.

CCEWCME0017	**Installation name cannot be empty. It must be less than 100 characters.**
Explanation	Node name cannot be empty or contain more than 100 characters.
Action	Enter a valid node name.

CCEWCME0018	**Alias cannot be empty. It should be no more than 100 characters long. It should not have spaces. Only ASCII characters, numbers, -, _, and . are allowed.**
Explanation	The node alias cannot be empty. It should be no more than 100 characters long.
Action	Enter a valid node alias.

CCEWCME0019	**Host name cannot be empty. The host name should be between two and 253 characters characters long. Do not use any special characters, except period(.) and minus(-). Do not start or end the host name with a period(.) or minus(-).**
Explanation	The host name field cannot be empty.
Action	Provide a valid host name. The host name should be between two and 253 characters characters long. Do not use any special characters, except period(.) and minus(-). Do not start or end the host name with a period(.) or minus(-).

CCEWCME0020	**Port number cannot be empty. It must be a positive number.**
Explanation	Port number cannot be empty.
Action	Enter a valid port number.

CCEWCME0028	**Installation alias {0} already exists. Please provide a different alias for the installation.**
Explanation	Installation node already exists.
Action	Provide a different alias for the installation node you want to add.

CCEWCME0039	**Null returned while retrieving the configuration types for comparison.**
Explanation	This intermittent error occurs while retrieving the configuration types from Platform Manager.
Action	Retry configuration comparison.

CCEWCME0047	**Specify a name for the template. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and "."**
Explanation	The alias field for the template cannot be empty.
Action	Provide a valid template alias. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and "."

CCEWCME0048	**Shared secret cannot be emtpy.**
Explanation	The template shared secret cannot be emtpy.
Action	Provide a valid shared secret.

CCEWCME0049	**The shared secrets you entered do not match.**
Explanation	The shared secrets that you entered do not match.
Action	Re-enter the shared secrets.

CCEWCME0050	**Select at least one include option.**
Explanation	You cannot clear all include option check boxes.
Action	You must select at least one include option check box.

CCEWCME0051	**No license reports were selected for deletion.**
Explanation	At least one report must be selected in the view before clicking the delete button.
Action	Select one or more reports and click the delete button.

CCEWCME0053	**No repositories configured. Add at least one repository.**
Explanation	There are no central repositories configured in Command Central.
Action	Register at least one repository in Command Central.

CCEWCME0069	**Specify a name for the repository. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and "."**
Explanation	The alias field for the repository cannot be empty.
Action	Provide a valid repository alias. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and "."

CCEWCME0072	**Repository {0} creation failed.**
Explanation	Creating the repository failed.
Action	Check the server logs or contact your system administrator.

CCEWCME0073	**Repository {0} update failed.**
Explanation	Updating the specified repository failed.
Action	Check the server logs or contact your system administrator.

CCEWCME0074	**Version cannot be empty.**
Explanation	The Version field is a required field.
Action	Click the Advanced button and specify a valid server in the Enter server URL field. Leave this field empty to use the Software AG Download Center.

CCEWCME0075	**Image file path cannot be empty.**
Explanation	The Image file on server field is a required field.
Action	In the Image file on server field, provide a valid path to an image file on the Command Central server.

CCEWCME0076	**An image file should be selected.**
Explanation	Specifying an image file is required.
Action	In the Upload image file field, select an image file.

CCEWCME0077	**A repository with location {0} was not found in the Software AG Download Center.**
Explanation	The repository that you are trying to edit was not found in the Software AG Download Center.
Action	Contact your system administrator.

CCEWCME0099	**Applying template {0} on installation {1} failed.**
Explanation	The apply template operation on the target installation has failed.
Action	Check the logs and jobs on the target installation.

CCEWCME0103	**Error while creating a new license report. {0}**
Explanation	An error occurred while invoking the service action responsible for creating a new report.
Action	Check the Command Central server logs to determine the root cause for the error.

CCEWCME0104	**Error while deleting license report(s). {0}**
Explanation	An error occurred while invoking the service action responsible for deleting reports.
Action	Check the Command Central server logs to determine the root cause for the error.

CCEWCME0105	**Error while refreshing the license reports view. {0}**
Explanation	An error occurred while invoking the service action responsible for retrieving the reports from the Command Central server.
Action	Check the Command Central server logs to determine the root cause for the error.

CCEWCME0114	**Saving of template {0} from installation {1} failed.**
Explanation	The save template operation on the target installation has failed.
Action	Check the logs and jobs on the target installation.

CCEWCME0119	**You do not have enough access privileges to perform requested operation.**
Explanation	You do not have enough access privileges to perform requested operation.
Action	Contact your system administrator to help you get the required permissions.

CCEWCME0124	**Bootstrapping of Platform Manager on installation with alias {0} failed.**
Explanation	The bootstrap Platform Manager operation on the target installation has failed.
Action	Check the logs and jobs on Command Central.

CCEWCME0125	**Alias {0} already exists. Provide a unique alias.**
Explanation	Alias already exists.
Action	Provide a unique alias for the object you want to add.

CCEWCME0126	**Alias cannot be empty. It should not have spaces. Only ASCII characters, numbers, -, _, and . are allowed.**
Explanation	Alias cannot be empty.
Action	Enter a valid alias.

CCEWCME0127	**No file specified.**
Explanation	A valid file must be specified.
Action	Press the 'Browse' button and select a valid file.

CCEWCME0129	**Error while deleting license manifest(s). {0}**
Explanation	An error occurred while invoking the service action responsible for deleting license manifests.
Action	Check the Command Central server logs to determine the root cause for the error.

CCEWCME0130	**Error while refreshing the license manifests view. {0}**
Explanation	An error occurred while invoking the service action responsible for retrieving the license manifests from the Command Central server.
Action	Check the Command Central server logs to determine the root cause for the error.

CCEWCME0132	**No license manifests were selected for deletion.**
Explanation	At least one license manifest must be selected in the view before clicking the delete button.
Action	Select one or more license manifests and click the delete button.

CCEWCME0135	**The contents of the specified file has invalid format.**
Explanation	The contents of the specified file does not match the required format.
Action	Specify a file with valid format.

CCEWCME0136	**Select remote installation method.**
Explanation	A remote installation method is not selected in the web user interface.
Action	Select a remote installation method in the web user interface.

CCEWCME0137	**Distribution cannot be empty.**
Explanation	The Distribution field in the web user interface cannot be empty.
Action	Select a distribution in the Distribution field.

CCEWCME0138	**Repository cannot be empty.**
Explanation	The Repository field in the web user interface cannot be empty.
Action	Select a repository in the Repository field.

CCEWCME0140	**Installation directory cannot be empty.**
Explanation	The Installation directory field in the web user interface cannot be empty.
Action	Select an installation directory in the Installation directory field.

CCEWCME0141	**Operating System cannot be empty.**
Explanation	The Operating System field in the web user interface cannot be empty.
Action	Select an operating System in the Operating System field.

CCEWCME0142	**Bootstrapped node {0} startup timed out.**
Explanation	The status of the bootstrapped node is still OFFLINE after the required timeout.
Action	Check the Command Central bootstrap logs.

CCEWCME0143	**Bootstrap installer creation failed.**
Explanation	Bootstrap installer creation failed.
Action	Check the Command Central logs.

CCEWCME0145	**User name cannot be empty.**
Explanation	The user name field cannot be empty.
Action	Provide a value in the user name field.

CCEWCME0146	**Password cannot be empty for the selected authentication method.**
Explanation	The Password cannot be empty for the selected authentication method.
Action	Provide a value in the Password field for the selected authentication method.

CCEWCME0147	**Key file cannot be empty for the selected authentication method.**
Explanation	The Key file field cannot be empty for the selected authentication method.
Action	Provide a value in the Key file field for the selected authentication method.

CCEWCME0148	**Password cannot be empty.**
Explanation	The Password field cannot be empty.
Action	Provide a value in the Password field.

CCEWCME0149	**User name cannot be empty.**
Explanation	The user name cannot be empty.
Action	Provide a value in the user name field.

CCEWCME0151	**Navigation to the log(s) for node {0} can not be initiated.**
Explanation	A node with alias {0} does not exist in the Command Central landscape.
Action	Select an existing node different than {0}.

CCEWCME0152	**You do not have access to the requested operation(s).**
Explanation	You do not have access to the requested operation(s).
Action	Provide valid credentials to perform the requested operation(s).

CCEWCME0154	**Request to create a license report failed.**
Explanation	An error occurred during the creation of the license report.
Action	Contact Software AG Global Support.

CCEWCME0155	**Select fixes to be installed.**
Explanation	No fixes are selected for installation.
Action	Select at least one fix to be installed.

CCEWCME0156	**Duplicate fixes selected. Select only one of the fix versions to be installed.**
Explanation	Duplicate fixes with the same ID, but different versions were selected.
Action	Select only one of the possible versions.

CCEWCME0157	**The key should not be empty.**
Explanation	The Support Patch key should not be empty.
Action	Provide a Support Patch key.

CCEWCME0158	**The Platform Manager (SPM) on this installation is not online.**
Explanation	The selected fix and product installation functions are not supported when Platform Manager is not running.
Action	Start Platform Manager and try again.

CCEWCME0159	**Release 9.7 and higher supports fix installation.**
Explanation	Fix installation is supported for installations of release 9.7 and higher. See the actions suggested for your installation in the Action field.
Action	Use Software AG Update Manager to install fixes and support patches for this installation. Consider upgrading this installation to 9.10 or a later release, using Command Central.

CCEWCME0162	**This installation version ({0}) does not support this feature.**
Explanation	The selective fix uninstallation feature is supported beginning with Platform Manager 9.7.
Action	If it is not possible to upgrade the installation to the latest available release version, you should use Update Manager to uninstall fixes.

CCEWCME0163	**Select a support patch to be installed.**
Explanation	There is no support patch selected for installation.
Action	Select a support patch to install.

CCEWCME0166	**Select at least one source repository.**
Explanation	You must select at least one source repository from which to create a mirror repository.
Action	Select at least one source repository from which to create a mirror repository.

CCEWCME0167	**The provided configuration is not valid.**
Explanation	The server request can not be completed successfully.
Action	Expand this view for more details.

CCEWCME0168	**No license keys were selected for deletion.**
Explanation	You must select at least one license key in the view before clicking the delete button.
Action	Select one or more license keys and click the delete button.

CCEWCME0171	**Error while refreshing the license keys view. {0}**
Explanation	An error occurred while invoking the service action responsible for retrieving the license keys from the Command Central server.
Action	Check the Command Central server logs to determine the root cause for the error.

CCEWCME0174	**Adding/Updating a repository operation failed.**
Explanation	Adding a repository operation failed. The job status is Error.
Action	Check the logs and try again.

CCEWCME0175	**Error while deleting license key(s). {0}**
Explanation	An error occurred while invoking the service action responsible for deleting license keys.
Action	Check the Command Central server logs to determine the root cause for the error.

CCEWCME0183	**Invalid username or password.**
Explanation	Invalid username or credentials provided in the Command Central Login page.
Action	Provide valid username or credentials in the Command Central Login page.

CCEWCME0184	**To create a mirror fix repository, you need at least one product repository that will be used as a filter for the repository content.**
Explanation	To create a mirror fix repository, you need at least one product repository that will be used as a filter for the repository content.
Action	Select at least one product repository.

CCEWCME0185	**Specify a name that follows the webMethods-<major.version>.<minor.version>_<name> pattern.**
Explanation	The pattern allows to extract the version when constructing a bootstrap image for ALL SPM distribution.
Action	Name your product mirror repository after the pattern.

CCEWCME0188	**Insufficient permissions to access this resource.**
Explanation	You do not have sufficient permissions to access this resource.
Action	Contact your system administrator to get sufficient permissions.

CCEWCME0209	**Release 9.8 and higher supports product installation.**
Explanation	Product installation is supported for installations of release 9.8 and higher. See the actions suggested for your installation in the Action field.
Action	Use Software AG Installer to install products for this installation. Consider upgrading this installation to 9.10 or a later release, using Command Central.

CCEWCME0210	**Release 9.8 and higher supports support patch installation.**
Explanation	Support patch installation is supported for installations of release 9.8 and higher. See the actions suggested for your installation in the Action field.
Action	Use Software AG Update Manager to install support patches for this installation. Consider upgrading this installation to 9.10 or a later release, using Command Central.

CCEWCME0214	**Enter your user name for the Software AG Download Center.**
Explanation	The user name field cannot be epmty.
Action	Enter a valid user name for the Software AG Download Center.

CCEWCME0215	**Enter your password for the Software AG Download Center.**
Explanation	The password field cannot be epmty.
Action	Enter a valid password for the Software AG Download Center.

CCEWCME0216	**Enter your user name for the remote Platform Manager.**
Explanation	The user name field cannot be epmty.
Action	Enter a valid user name for the Platform Manager, which is specified in the repository URL.

CCEWCME0217	**Enter your password for the remote Platform Manager.**
Explanation	The password field cannot be epmty.
Action	Enter a valid password for the Platform Manager, which is specified in the repository URL.

CCEWCME0220	**Updating repository contents operation failed.**
Explanation	The repository update contents operation failed. The job status is Error.
Action	Check the logs and try again.

CCEWCME0223	**Could not transfer the file to the target destination {0}.**
Explanation	The file could not be transfered because of an error.
Action	Check if the target host has enough disk space or the specified file name is valid.

CCEWCME0228	**You are not allowed to perform the requested operation.**
Explanation	You are not allowed to perform the requested operation because of Cross Site Request Prevention.
Action	Ensure that you do not have several Command Central REST resources open in the same browser session. If you do, close all the instances of the browser and log into the Command Central web user interface again.

CCEWCME0239	**Source repositories with different versions are selected: {0}.**
Explanation	The selected source repositories have different versions.
Action	Select source repositories with the same version.

CCEWCME0240	**Connecting to asset repository {0} failed.**
Explanation	Connecting to an asset repository failed.
Action	Check the logs and try again.

CCEWCME0243	**Asset repository {0} could not be connected/edited.**

CCEWCMI0021	**Installation {0} already exists in environment {1}.**
Explanation	The selected node already exists in the environment. Drag and drop not possible.
Action	Verify if you have selected the correct nodes and the environment for drag and drop.

CCEWCMI0040	**{0} must be a non-negative integer.**
Explanation	Specified field must be a non-negative integer.
Action	Enter a valid field value.

CCEWCMI0041	**{0} cannot be empty.**
Explanation	Specified field cannot be empty.
Action	Enter a valid field value.

CCEWCMI0046	**Alias cannot be empty.**
Explanation	The port alias field cannot be empty.
Action	Provide a valid port alias name.

CCEWCMI0057	**User credentials saved successfully.**
Explanation	The provided user credentials are successfully saved.
Action	None.

CCEWCMI0058	**User credentials deleted successfully.**
Explanation	The provided user credentials are successfully deleted.
Action	None.

CCEWCMI0098	**Template {0} successfully saved from installation {1}.**
Explanation	The save template operation completed successfully.
Action	No action required.

CCEWCMI0100	**Type a keyword to display only the reports that contain the keyword in the report id, creator, create date or compliance status. The search is case-insensitive.**
Explanation	License report search filter help text.
Action	None.

CCEWCMI0101	**Do you wish to continue?**
Explanation	Part of the license report confirmation dialog for creating a new report.
Action	None.

CCEWCMI0112	**license report(s)**
Explanation	Part of 'delete license report(s)' confirmation dialog.
Action	None.

CCEWCMI0113	**Report Id(s): {0}**
Explanation	License report confirmation dialog for deleting one or more reports.
Action	None.

CCEWCMI0115	**Template {0} successfully applied on installation {1}.**
Explanation	The apply template operation completed successfully.
Action	No action required.

CCEWCMI0117	**Scheduled job did not complete within status checker''s allotted time.**
Explanation	The client job status checker stopped polling for an executing job's status before it completed. This does not necessarily mean the job did not complete successfully.
Action	Confirm if job completed via other means.

CCEWCMI0120	**Attribute {0} successfully submitted.**
Explanation	The attribute was successfully added or updated.
Action	No action required.

CCEWCMI0121	**Attribute {0} successfully deleted.**
Explanation	The attribute was successfully deleted.
Action	No action required.

CCEWCMI0123	**Platform Manager successfully bootstrapped on installation with alias {0}.**
Explanation	The bootstrap of Platform Manager was successful.
Action	No action required.

CCEWCMI0131	**Type a keyword to display only the license manifests that contain the keyword in one of the columns. The search is case-insensitive.**
Explanation	License manifest search filter help text.
Action	None.

CCEWCMI0144	**Bootstrap installer created successfully.**
Explanation	A new bootstrap installer was successfully created.
Action	None.

CCEWCMI0180	**No licenses have been registered**
Explanation	No license key aliases have been registered so that it is not possible to select a license key alias.
Action	Register a license key alias.

CCEWCMI0186	**Provided configuration is valid.**
Explanation	The server request is completed successfuly.
Action	Expand this view for more details.

CCEWCMI0245	**License manifest(s) removed.**
Explanation	The specified license manifest(s) have been removed successfully.

CCEWCMI0246	**< 1 second**

CCEWCMW0107	**No data selected for delete.**
Explanation	You must select at least one object for deletion.
Action	Select at least one object from the object list.

CCEWCMW0108	**Delete request failed, but no ErrorInfo was found.**
Explanation	A problem occurred when executing a delete request, but the server did not provide details about the problem.
Action	Check the server-side log files for details. Contact Software AG Global Support.

CCEWCMW0109	**Request to delete license reports failed for these report IDs: {0}**
Explanation	The server was not able to delete the license reports identified here. The request may have included other report IDs for which deletion was successful.
Action	Refresh the display of license reports to see which were deleted. Check the server-side error log for details about why the attempt to delete failed.

CCEWCMW0118	**Unable to determine job status due to unexpected error while checking status. {0}**
Explanation	Job status checking encountered an error. This does not necessarily mean the job did not complete successfully.
Action	Confirm if job completed via other means.

CCEWCMW0122	**The provided attribute name {0} already exists.**
Explanation	The attribute name which you are trying to add already exists.
Action	Provide a unique attribute name.

CCEWCMW0172	**Delete request failed for this alias: {0}**
Explanation	The server was not able to delete the object with the given alias.
Action	Check the server-side error log for details about why the attempt to delete failed.

CCEWCMW0187	**Provided configuration is valid, but check the warnings.**
Explanation	The server request is completed, but check the warnings.
Action	Expand this view for more details.

CCEWCMW0211	**Not all products can be installed by Command Central.**
Explanation	The number of products that you can install using Command Central increases with each Software AG release.
Action	See the Command Central release readme for a list of products that you cannot install through Command Central for each Software AG release.

CCEWCMW0212	**There are artifacts which are either not applicable for the installation or not present in the selected repository.**
Explanation	The following artifacts are either not applicable, or not present in the selected repository: {0}
Action	Either continue without the missing artifacts, or use a source repository containing those artifacts.

CCEWCMW0222	**User credentials for repository {0} are missing or invalid.**
Explanation	The user credentials for repository {0} are missing or invalid.
Action	Specify valid user credentials for repository {0}.

10 Common Monitoring Provider Messages

CMPAPIE0000	**{0}: The input parameter {1} is null or empty.**
Explanation	A required input parameter is null or empty.
Action	Please provide the required input parameter.

CMPAPIE0001	**{0}: The input parameter {1} is null.**
Explanation	A required input parameter is null.
Action	Please provide the required input parameter.

CMPAPIE0003	**{0}: Cannot load XSD file {1}**
Explanation	A required input parameter is null.
Action	Please provide the required input parameter.

CMPBKRE0000	**Error initializing Broker Attribute Values. Broker Monitoring Context cannot be null.**
Explanation	Broker Monitoring Context is required for initializing Broker Attribute Values.
Action	Verify Broker Connection parameters.

CMPBKRE0001	**Error while retrieving attribute value. MetaModel Type Name cannot be null or empty.**
Explanation	MetaModel Type Name is required for retrieving attribute value.
Action	Verify metadata model type name is provided.

CMPBKRE0002	**Error while retrieving attribute value. MetaModel instance name cannot be null or empty.**
Explanation	MetaModel instance name is required to retrieve attribute value.
Action	Verify metadata model instance name is provided.

CMPBKRE0003	**Error while retrieving attribute value. Attribute ID cannot be null or empty.**
Explanation	Attribute ID is required to retrieve attribute value.
Action	Verify Attribute ID is provided.

CMPBKRE0004	**Error while retrieving attribute values. Attribute query object cannot be null.**
Explanation	Attribute query object is required to retrieve attribute values.
Action	Verify attribute query object is provided.

CMPBKRE0005	**Error while retrieving attribute value due to invalid model type.**
Explanation	An invalid model type was provided while retrieving attribute values.
Action	Verify a valid model type is provided.

CMPBKRE0006	**Error while destroying Monitoring Context. Monitoring Context cannot be null.**
Explanation	Error while destroying Monitoring Context. Monitoring Context cannot be null.
Action	Verify Monitoring Context is provided

CMPBKRE0007	**Error while destroying Monitoring Context. Invalid Broker Monitoring Context provided.**
Explanation	Error while destroying Monitoring Context. Invalid Broker Monitoring Context provided.
Action	Verify valid Broker Monitoring Context is provided.

CMPBKRE0008	**Error while getting meta model. Model type name cannot be null.**
Explanation	Error while getting meta model. Model type name cannot be null.
Action	Verify Model type name is provided.

CMPBKRE0009	**Error while vaidating Broker Monitoring Context. Broker Monitoring Context cannot be null.**
Explanation	Error while vaidating Broker Monitoring Context. Broker Monitoring Context cannot be null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0010	**Error while vaidating Broker Monitoring Context. Invalid Broker Monitoring Context provided.**
Explanation	Error while vaidating Broker Monitoring Context. Invalid Broker Monitoring Context provided.
Action	Verify a valid Broker Monitoring Context is provided.

CMPBKRE0011	**Error while validating Broker Monitoring Context. Context object is null.**
Explanation	Error while validating Broker Monitoring Context. Context object is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0012	**Error while validating Broker Monitoring Context. Context is invalid.**
Explanation	Error while validating Broker Monitoring Context. Context is invalid.
Action	Verify valid Broker Monitoring Context is provided.

CMPBKRE0013	**Error while validating Broker Monitoring Context. Context host attribute cannot be null or empty.**
Explanation	Error while validating Broker Monitoring Context. Context host attribute cannot be null or empty.
Action	Verify host attribute is provided in Broker Monitoring Context

CMPBKRE0014	**Error while validating Broker Monitoring Context. Context port attribute is invalid.**
Explanation	Error while validating Broker Monitoring Context. Context port attribute is invalid.
Action	Verify valid port attribute is provided in Broker Monitoring Context.

CMPBKRE0015	**Error while creating Broker Server client. Host name cannot be null or empty.**
Explanation	Error while creating Broker Server client. Host name cannot be null or empty.
Action	Verify host name is provided.

CMPBKRE0016	**Error while creating Broker Server client. Port cannot be null or empty.**
Explanation	Error while creating Broker Server client. Port cannot be null or empty.
Action	Verify port is provided.

CMPBKRE0017	**Error while destroying Broker Server client. Broker Name cannot be null or empty.**
Explanation	Error while destroying Broker Server client. Broker Name cannot be null or empty.
Action	Verify Broker Name is provided.

CMPBKRE0018	**Error while creating Broker Admin client. Broker Name cannot be null.**
Explanation	Error while creating Broker Admin client. Broker Name cannot be null.
Action	Verify Broker Name is provided.

CMPBKRE0019	**Error while setting Broker Admin client. Broker Name cannot be null.**
Explanation	Error while setting Broker Admin client. Broker Name cannot be null.
Action	Verify Broker Name is provided.

CMPBKRE0020	**Error while setting Broker Admin client. Broker Admin Client cannot be null.**
Explanation	Error while setting Broker Admin client. Broker Admin Client cannot be null.
Action	Verify Broker Admin Client is specified.

CMPBKRE0021	**Error while initialzing Broker Client model. Broker Monitoring Context is null.**
Explanation	Error while initialzing Broker Client model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0022	**Error while getting Broker Client attributes. Model Instance List cannot be null.**
Explanation	Error while getting Broker Client attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.

CMPBKRE0023	**Error while getting Broker Client attributes. Attribute List cannot be null.**
Explanation	Error while getting Broker Client attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.

CMPBKRE0024	**Error while getting Broker Client attribute. Attribute ID cannot be null.**
Explanation	Error while getting Broker Client attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.

CMPBKRE0025	**Error while initialzing Broker Document Type model. Broker Monitoring Context is null.**
Explanation	Error while initialzing Broker Document Type model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0026	**Error while getting Broker Document Type attributes. Model Instance List cannot be null.**
Explanation	Error while getting Broker Document Type attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.

CMPBKRE0027	**Error while getting Broker Document Type attributes. Attribute List cannot be null.**
Explanation	Error while getting Broker Document Type attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.

CMPBKRE0028	**Error while getting Broker Document Type attribute. Attribute ID cannot be null.**
Explanation	Error while getting Broker Document Type attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.

CMPBKRE0029	**Error while initialzing Broker Gateway model. Broker Monitoring Context is null.**
Explanation	Error while initialzing Broker Gateway model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0030	**Error while initialzing Broker Gateway model. Broker Monitoring Context is null.**
Explanation	Error while initialzing Broker Gateway model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0031	**Error while getting Broker Gateway attributes. Model Instance List cannot be null.**
Explanation	Error while getting Broker Gateway attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.

CMPBKRE0032	**Error while getting Broker Gateway attributes. Attribute List cannot be null.**
Explanation	Error while getting Broker Gateway attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.

CMPBKRE0033	**Error while getting Broker Gateway attribute. Attribute ID cannot be null.**
Explanation	Error while getting Broker Gateway attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.

CMPBKRE0034	**Error while initialzing Broker model. Broker Monitoring Context is null.**
Explanation	Error while initialzing Broker model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0035	**Error while getting Broker attributes. Model Instance List cannot be null.**
Explanation	Error while getting Broker attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.

CMPBKRE0036	**Error while getting Broker attributes. Attribute List cannot be null.**
Explanation	Error while getting Broker attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.

CMPBKRE0037	**Error while getting Broker attribute. Attribute ID cannot be null.**
Explanation	Error while getting Broker attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.

CMPBKRE0038	**Error while initialzing Broker model instance. Broker Monitoring Context is null.**
Explanation	Error while initialzing Broker model instance. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0039 **Error while getting model instances. MetaModel Type name is null or empty.**
Explanation Error while getting model instances. MetaModel Type name is null or empty.
Action Verify MetaModel Type Name is provided.

CMPBKRE0040 **Error while getting model instances. Invalid MetaModel Type Name.**
Explanation Error while getting model instances. Invalid MetaModel Type Name.
Action Verify valid MetaModel Type Name is provided.

CMPBKRE0041 **Error while initialzing Broker Server model. Broker Monitoring Context is null.**
Explanation Error while initialzing Broker Server model. Broker Monitoring Context is null.
Action Verify Broker Monitoring Context is provided.

CMPBKRE0042 **Error while getting Broker Server attributes. Model Instance List cannot be null.**
Explanation Error while getting Broker Server attributes. Model Instance List cannot be null.
Action Verify Model Instance List is provided.

CMPBKRE0043 **Error while getting Broker Server attributes. Attribute List cannot be null.**
Explanation Error while getting Broker Server attributes. Attribute List cannot be null.
Action Verify Attribute List is provided.

CMPBKRE0044 **Error while getting Broker Server attribute. Attribute ID cannot be null.**
Explanation Error while getting Broker Server attribute. Attribute ID cannot be null.
Action Verify Attribute ID is provided.

CMPBKRE0045 **Error while getting Broker SSL Stats attributes. Attribute ID cannot be null.**
Explanation Error while getting Broker SSL Stats attributes. Attribute ID cannot be null.
Action Verify valid Attribute ID is provided.

CMPBKRE0046 **Error while initialzing Broker Territory model. Broker Monitoring Context is null.**
Explanation Error while initialzing Broker Territory model. Broker Monitoring Context is null.
Action Verify Broker Monitoring Context is provided.

CMPBKRE0047	**Error while getting Broker Territory attributes. Model Instance List cannot be null.**
Explanation	Error while getting Broker Territory attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.

CMPBKRE0048	**Error while getting Broker Territory attributes. Attribute List cannot be null.**
Explanation	Error while getting Broker Territory attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.

CMPBKRE0049	**Error while getting Broker Territory attribute. Attribute ID cannot be null.**
Explanation	Error while getting Broker Territory attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.

CMPBKRE0050	**Error while initialzing Territory Broker model. Broker Monitoring Context is null.**
Explanation	Error while initialzing Territory Broker model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0051	**Error while getting Territory Broker attributes. Model Instance List cannot be null.**
Explanation	Error while getting Territory Broker attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.

CMPBKRE0052	**Error while getting Territory Broker attributes. Attribute List cannot be null.**
Explanation	Error while getting Territory Broker attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.

CMPBKRE0053	**Error while getting Territory Broker attribute. Attribute ID cannot be null.**
Explanation	Error while getting Territory Broker attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.

CMPBKRE0054	**Error while getting Territory Broker Stats attribute. Could not retrieve attribute value.**
Explanation	Error while getting Territory Broker Stats attribute. Could not retrieve attribute value.

CMPBKRE0055 **Error while getting Territory Broker Stats Event attribute. Could not retrieve attribute value.**

Explanation Error while getting Territory Broker Stats Event attribute. Could not retrieve attribute value.

CMPBKRE0056 **Error during Broker ping. Invalid Ping Context.**

Explanation Error during Broker ping. Invalid Ping Context.

Action Verify valid Ping Context is provided.

CMPBKRE0057 **Error during Broker Client ping. Broker Name not set in Broker Monitoring Context.**

Explanation Error during Broker Client ping. Broker Name not set in Broker Monitoring Context.

Action Verify Broker Name is set in Broker Ping Context.

CMPDESE0001 **Error while validating DES Monitoring Context. DES Monitoring Context cannot be null.**

CMPDESE0002 **Error while validating DES Monitoring Context. DES Monitoring Context is not instance of DESMonitoringContext.**

CMPDESE0003 **Error while validating DES Monitoring Context. Context object is null.**

CMPDESE0004 **Error while validating DES Monitoring Context. Context is invalid.**

CMPDESE0005 **Error while validating DES Monitoring Context. Context host attribute cannot be null or empty.**

CMPDESE0006 **Error while validating DES Monitoring Context. Context port attribute is invalid.**

CMPDESE0007 **DES Monitoring Context cannot be null.**

CMPDESE0008 **Error while getting meta model. DES Meta model type ID cannot be null or empty.**

CMPDESE0010 **Input parameter mbean name cannot be null.**

CMPDESE0012 **Model instance list or attribute list cannot be null.**

CMPDESE0034 **Input parameter mbean name cannot be null.**

CMPDESE0036 **Invalid response from server: {0}**

CMPDESE0037 **Model instance list cannot be null.**

CMPDESE0038 **Attribute instance list cannot be null.**

CMPDESE0039 **Method Name cannot be empty or null.**

CMPDESE0040 **Attribute query string cannot be null.**

CMPDESE0042 **Attribute value is invalid or not available.**

CMPDESE0043 **DES Monitoring Context cannot be null.**

CMPDESE0044 **Input metaModelTypeID cannot be null or empty.**

CMPDESE0045 **Input modelInstanceID cannot be null or empty.**

CMPDESE0046 **Input attributeID cannot be null or empty.**

CMPDESE0047 **AttributeQuery cannot be null.**

CMPDESE0048	**unused**
CMPDESE0049	**Input context cannot be null**
CMPDESE0050	**Exception occurred while getting Object Status, {0}**
CMPDESE0051	**n/a**
CMPDESE0052	**Unknown model type: {0} During getting attribute values.**
CMPDESE0053	**Object is invalid or not available.**
CMPDESE0054	**Can't create DESMonitoringContext with null DESInputContext");**
CMPERTE0001	**Error while validating Event Routing Monitoring Context. Event Routing Monitoring Context cannot be null.**
CMPERTE0002	**Error while validating Event Routing Monitoring Context. Event Routing Monitoring Context is not instance of EventRoutingMonitoringContext.**
CMPERTE0003	**Error while validating Event Routing Monitoring Context. Context object is null.**
CMPERTE0005	**Error while validating Event Routing Monitoring Context. Context host attribute cannot be null or empty.**
CMPERTE0006	**Error while validating Event Routing Monitoring Context. Context port attribute is invalid.**
CMPERTE0007	**Event Routing Monitoring Context cannot be null.**

CMPERTE0008	**Error while getting meta model. Event Routing Meta model type ID cannot be null or empty.**
CMPERTE0010	**Input parameter mbean name cannot be null.**
CMPERTE0012	**Model instance list or attribute list cannot be null.**
CMPERTE0034	**Input parameter mbean name cannot be null.**
CMPERTE0036	**Invalid response from server: {0}**
CMPERTE0037	**Model instance list cannot be null.**
CMPERTE0038	**Attribute instance list cannot be null.**
CMPERTE0039	**Method Name cannot be empty or null.**
CMPERTE0040	**Attribute query string cannot be null.**
CMPERTE0042	**Attribute value is invalid or not available.**
CMPERTE0043	**Event Routing Monitoring Context cannot be null.**
CMPERTE0044	**Input metaModelTypeID cannot be null or empty.**
CMPERTE0045	**Input modelInstanceID cannot be null or empty.**
CMPERTE0046	**Input attributeID cannot be null or empty.**

CMPERTE0047 **AttributeQuery cannot be null.**

CMPERTE0048 **unused**

CMPERTE0049 **Input context cannot be null**

CMPERTE0050 **Exception occurred while getting Object Status, {0}**

CMPERTE0051 **n/a**

CMPERTE0052 **Unknown model type: {0} During getting attribute values.**

CMPERTE0053 **Object is invalid or not available.**

CMPERTE0054 **Can't create EventRoutingMonitoringContext with null EventRoutingInputContext");**

CMPERTW0004 **Error while validating Event Routing Monitoring Context. Context is invalid.**

CMPJBPE0000 **Presto HTTP URL Method Name cannot be empty or null.**

Explanation Presto HTTP URL Method Name cannot be empty or null.

Action Please provide Presto HTTP URL Method Name.

CMPJBPE0001 **Error while validating Presto Monitoring Context. Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0002 **Error while validating Presto Monitoring Context. Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide valid Presto Monitoring Context.

CMPJBPE0003	**Error while validating Presto Monitoring Context. Context object is null.**
Explanation	Presto Monitoring Context is required.
Action	Please provide Presto Monitoring Context.

CMPJBPE0004	**Error while validating Presto Monitoring Context. Context is invalid.**
Explanation	Presto Monitoring Context is required.
Action	Please provide valid Presto Monitoring Context.

CMPJBPE0005	**Error while validating Presto Monitoring Context. Context host attribute cannot be null or empty.**
Explanation	Presto Monitoring Context host attribute cannot be null or empty.
Action	Please provide host attribute for Presto Monitoring Context.

CMPJBPE0006	**Error while validating Presto Monitoring Context. Context port attribute is invalid.**
Explanation	Presto Monitoring Context port attribute cannot be null or empty.
Action	Please provide port attribute for Presto Monitoring Context.

CMPJBPE0007	**Presto Monitoring Context cannot be null.**
Explanation	Presto Monitoring Context is required for getting Presto model instances.
Action	Please provide Presto Monitoring Context.

CMPJBPE0008	**Error while getting meta model. Presto Meta model type ID cannot be null or empty.**
Explanation	Presto Meta model type ID cannot be null or empty.
Action	Please provide Presto meta model type ID.

CMPJBPE0009	**Presto Monitoring Context cannot be null.**
Explanation	Presto Monitoring Context cannot be null.
Action	Please provide Presto Monitoring Context.

CMPJBPE0010	**Input parameter mbean name cannot be null.**
Explanation	Input parameter mbean name is required.
Action	Please provide input parameter mbean name.

CMPJBPE0011	**Presto Monitoring Context cannot be null.**
Explanation	Presto Monitoring Context is required for getting Presto model instances.
Action	Please provide Presto Monitoring Context.

CMPJBPE0012	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPJBPE0013	**Presto Monitoring Context cannot be null.**
Explanation	Presto Monitoring Context is required for getting Presto model instances.
Action	Please provide Presto Monitoring Context.

CMPJBPE0014	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPJBPE0015	**Presto Monitoring Context cannot be null.**
Explanation	Presto Monitoring Context is required for getting Presto model instances.
Action	Please provide Presto Monitoring Context.

CMPJBPE0016	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPJBPE0017	**Presto Monitoring Context cannot be null.**
Explanation	Presto Monitoring Context is required.
Action	Please provide Presto Monitoring Context.

CMPJBPE0018	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPJBPE0019 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0020 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPJBPE0021 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0022 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPJBPE0023 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0024 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPJBPE0025 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0026 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPJBPE0027 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0028 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPJBPE0029 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0030 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0031 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPJBPE0032 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context is required.

Action Please provide Presto Monitoring Context.

CMPJBPE0033 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPJBPE0034 **Input parameter mbean name cannot be null.**

Explanation Input parameter mbean name is required.

Action Please provide input parameter mbean name.

CMPJBPE0035 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPJBPE0036 **Invalid response from server: {0}**

Explanation Invalid response from server.

Action Please resolve the issue with output.

CMPJBPE0037 **Model instance list cannot be null.**

Explanation Model instance list cannot be null.

Action Please provide model instance list.

CMPJBPE0038 **Attribute instance list cannot be null.**

Explanation Attribute instance list cannot be null.

Action Please provide attribute instance list.

CMPJBPE0039 **Method Name cannot be empty or null.**

Explanation Method Name cannot be empty or null.

Action Please provide method name.

CMPJBPE0040 **Attribute query string cannot be null.**

Explanation Attribute query string cannot be null.

Action Please provide attribute query string.

CMPJBPE0041 **Presto Monitoring Context cannot be null.**

Explanation Presto Monitoring Context cannot be null.

Action Please provide monitoring context.

CMPJBPE0042 **Attribute value is invalid or not available.**

Explanation Attribute value is invalid or not available.

Action Please provide valid attribute value.

CMPJBPE0043	**Presto Monitoring Context cannot be null.**
Explanation	Presto Monitoring Context is required.
Action	Please provide Presto Monitoring Context.

CMPJBPE0044	**Input metaModelTypeID cannot be null or empty.**
Explanation	Input metaModelTypeID cannot be null or empty.
Action	Please provide meta model type ID.

CMPJBPE0045	**Input modelInstanceID cannot be null or empty.**
Explanation	Input modelInstanceID cannot be null or empty.
Action	Please provide model instance ID.

CMPJBPE0046	**Input attributeID cannot be null or empty.**
Explanation	Input attributeID cannot be null or empty.
Action	Please provide attribute ID.

CMPJBPE0047	**AttributeQuery cannot be null.**
Explanation	AttributeQuery cannot be null.
Action	Please provide attribute query.

CMPJBPE0048	**unused**
Explanation	unused
Action	Report the error

CMPJBPE0049	**Input context cannot be null**
Explanation	Input context cannot be null

CMPJBPE0050	**Exception occurred while getting Object Status, {0}**
Explanation	Exception occurred while getting Object Status, Exception attached.
Action	Report the error

CMPJBPE0051	**n/a**
Explanation	n/a
Action	Report the error

CMPJBPE0052	**Unknown model type: {0} During getting attribute values.**
Explanation	Encountered an unknown model type when getting attribute values.
Action	Report the error

CMPJBPE0053	**Object is invalid or not available.**
Explanation	Object is invalid or not available is a default error message for a missing attribute.
Action	Report the error.

CMPJBPE0054	**Can't create PrestoMonitoringContext with null PrestoInputContext**
Explanation	There is code trying to create a PrestoMonitoringContext with null PrestoInputContext
Action	Report the error

CMPJMXE0000	**Jmx HTTP URL Method Name cannot be empty or null.**
Explanation	Jmx HTTP URL Method Name cannot be empty or null.
Action	Please provide Jmx HTTP URL Method Name.

CMPJMXE0001	**Error while validating Jmx Monitoring Context. Jmx Monitoring Context cannot be null.**
Explanation	Jmx Monitoring Context is required.
Action	Please provide Jmx Monitoring Context.

CMPJMXE0003	**Error while validating Jmx Monitoring Context. Context object is null.**
Explanation	Jmx Monitoring Context is required.
Action	Please provide Jmx Monitoring Context.

CMPJMXE0004	**Error while validating Jmx Monitoring Context. Context is invalid.**
Explanation	Jmx Monitoring Context is required.
Action	Please provide valid Jmx Monitoring Context.

CMPJMXE0005	**Error while validating Jmx Monitoring Context. Context host attribute cannot be null or empty.**
Explanation	Jmx Monitoring Context host attribute cannot be null or empty.
Action	Please provide host attribute for Jmx Monitoring Context.

CMPJMXE0006	**Error while validating Jmx Monitoring Context. Context port attribute is invalid.**
Explanation	Jmx Monitoring Context port attribute cannot be null or empty.
Action	Please provide port attribute for Jmx Monitoring Context.

CMPJMXE0007	**Jmx Monitoring Context cannot be null.**
Explanation	Jmx Monitoring Context is required for getting Jmx model instances.
Action	Please provide Jmx Monitoring Context.

CMPJMXE0020	**mBean filter can not be null or empty.**
Explanation	mBean filter can not be null or empty.
Action	Please provide mBean filter.

CMPJMXE0037	**Model instance list cannot be null.**
Explanation	Model instance list cannot be null.
Action	Please provide model instance list.

CMPJMXE0038	**Attribute instance list cannot be null.**
Explanation	Attribute instance list cannot be null.
Action	Please provide attribute instance list.

CMPJMXE0060	**SSL enabled, but there is no trustStore configured! The input context is invalid.**
Explanation	SSL enabled, but there is no trustStore configured! The input context is invalid.
Action	Please provide trustStore

CMPJMXE0061	**Jmx server is not reachable.**
Explanation	Jmx server is not reachable.
Action	Please make sure Jmx server is reachable

CMPMNGE0000	**Mashzone NextGen HTTP URL Method Name cannot be empty or null.**
Explanation	Mashzone NextGen HTTP URL Method Name cannot be empty or null.

CMPMNGE0001	**Error while validating Mashzone NextGen Monitoring Context. Mashzone NextGen Monitoring Context cannot be null.**
Explanation	Error while validating Mashzone NextGen Monitoring Context. Mashzone NextGen Monitoring Context cannot be null.

CMPMNGE0002	**Error while validating Mashzone NextGen Monitoring Context. Mashzone NextGen Monitoring Context is not instance of MZNGMonitoringContext.**
Explanation	Error while validating Mashzone NextGen Monitoring Context. Mashzone NextGen Monitoring Context is not instance of MZNGMonitoringContext.

CMPMNGE0003	**Error while validating Mashzone NextGen Monitoring Context. Context object is null.**
Explanation	Error while validating Mashzone NextGen Monitoring Context. Context object is null.

CMPMNGE0004	**Error while validating Mashzone NextGen Monitoring Context. Context is invalid.**
Explanation	Error while validating Mashzone NextGen Monitoring Context. Context is invalid.

CMPMNGE0005	**Error while validating Mashzone NextGen Monitoring Context. Context host attribute cannot be null or empty.**
Explanation	Error while validating Mashzone NextGen Monitoring Context. Context host attribute cannot be null or empty.

CMPMNGE0006	**Error while validating Mashzone NextGen Monitoring Context. Context port attribute is invalid.**
Explanation	Error while validating Mashzone NextGen Monitoring Context. Context port attribute is invalid.

CMPMNGE0007	**Mashzone NextGen Monitoring Context cannot be null.**
Explanation	Mashzone NextGen Monitoring Context cannot be null.

CMPMNGE0008 **Error while getting meta model. Mashzone NextGen Meta model type ID cannot be null or empty.**

Explanation Error while getting meta model. Mashzone NextGen Meta model type ID cannot be null or empty.

CMPMNGE0010 **Input parameter mbean name cannot be null.**

Explanation Input parameter mbean name cannot be null.

CMPMNGE0012 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

CMPMNGE0034 **Input parameter mbean name cannot be null.**

Explanation Input parameter mbean name cannot be null.

CMPMNGE0036 **Invalid response from server: {0}**

Explanation Invalid response from server: {0}

CMPMNGE0037 **Model instance list cannot be null.**

Explanation Model instance list cannot be null.

CMPMNGE0038 **Attribute instance list cannot be null.**

Explanation Attribute instance list cannot be null.

CMPMNGE0039 **Method Name cannot be empty or null.**

Explanation Method Name cannot be empty or null.

CMPMNGE0040 **Attribute query string cannot be null.**

Explanation Attribute query string cannot be null.

CMPMNGE0042 **Attribute value is invalid or not available.**

Explanation Attribute value is invalid or not available.

CMPMNGE0043 **Mashzone NextGen Monitoring Context cannot be null.**
Explanation Mashzone NextGen Monitoring Context cannot be null.

CMPMNGE0044 **Input metaModelTypeID cannot be null or empty.**
Explanation Input metaModelTypeID cannot be null or empty.

CMPMNGE0045 **Input modelInstanceID cannot be null or empty.**
Explanation Input modelInstanceID cannot be null or empty.

CMPMNGE0046 **Input attributeID cannot be null or empty.**
Explanation Input attributeID cannot be null or empty.

CMPMNGE0047 **AttributeQuery cannot be null.**
Explanation AttributeQuery cannot be null.

CMPMNGE0048 **unused**
Explanation unused

CMPMNGE0049 **Input context cannot be null**
Explanation Input context cannot be null

CMPMNGE0050 **Exception occurred while getting Object Status, {0}**
Explanation Exception occurred while getting Object Status, {0}

CMPMNGE0051 **n/a**
Explanation n/a

CMPMNGE0052 **Unknown model type: {0} During getting attribute values.**
Explanation Unknown model type: {0} During getting attribute values.

CMPMNGE0053 **Object is invalid or not available.**

Explanation Object is invalid or not available.

CMPMNGE0054 **Can't create MZNGMonitoringContext with null MZNGInputContext**

Explanation Can't create MZNGMonitoringContext with null MZNGInputContext

CMPMWSE0000 **MWS HTTP URL Method Name cannot be empty or null.**

Explanation MWS HTTP URL Method Name cannot be empty or null.

Action Please provide MWS HTTP URL Method Name.

CMPMWSE0001 **Error while vaidating MWS Monitoring Context. MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0002 **Error while vaidating MWS Monitoring Context. MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required.

Action Please provide valid MWS Monitoring Context.

CMPMWSE0003 **Error while validating Broker Monitoring Context. Context object is null.**

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0004 **Error while validating MWS Monitoring Context. Context is invalid.**

Explanation MWS Monitoring Context is required.

Action Please provide valid MWS Monitoring Context.

CMPMWSE0005 **Error while validating MWS Monitoring Context. Context host attribute cannot be null or empty.**

Explanation MWS Monitoring Context host attribute cannot be null or empty.

Action Please provide host attribute for MWS Monitoring Context.

CMPMWSE0006	**Error while validating Broker Monitoring Context. Context port attribute is invalid.**
Explanation	MWS Monitoring Context port attribute cannot be null or empty.
Action	Please provide port attribute for MWS Monitoring Context.

CMPMWSE0007	**MWS Monitoring Context cannot be null.**
Explanation	MWS Monitoring Context is required for getting MWS model instances.
Action	Please provide MWS Monitoring Context.

CMPMWSE0008	**Error while getting meta model. MWS Meta model type ID cannot be null or empty.**
Explanation	MWS Meta model type ID cannot be null or empty.
Action	Please provide MWS meta model type ID.

CMPMWSE0009	**MWS Monitoring Context cannot be null.**
Explanation	MWS Monitoring Context cannot be null.
Action	Please provide MWS Monitoring Context.

CMPMWSE0010	**Input parameter mbean name cannot be null.**
Explanation	Input parameter mbean name is required.
Action	Please provide input parameter mbean name.

CMPMWSE0011	**MWS Monitoring Context cannot be null.**
Explanation	MWS Monitoring Context is required for getting MWS model instances.
Action	Please provide MWS Monitoring Context.

CMPMWSE0012	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPMWSE0013	**MWS Monitoring Context cannot be null.**
Explanation	MWS Monitoring Context is required for getting MWS model instances.
Action	Please provide MWS Monitoring Context.

CMPMWSE0014 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0015 **MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required for getting MWS model instances.

Action Please provide MWS Monitoring Context.

CMPMWSE0016 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0017 **MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0018 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0019 **MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0020 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0021 **MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0022	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPMWSE0023	**MWS Monitoring Context cannot be null.**
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.

CMPMWSE0024	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPMWSE0025	**MWS Monitoring Context cannot be null.**
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.

CMPMWSE0026	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPMWSE0027	**MWS Monitoring Context cannot be null.**
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.

CMPMWSE0028	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPMWSE0029	**MWS Monitoring Context cannot be null.**
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.

CMPMWSE0030 **MWS Monitoring Context cannot be null.**
Explanation MWS Monitoring Context is required.
Action Please provide MWS Monitoring Context.

CMPMWSE0031 **Model instance list or attribute list cannot be null.**
Explanation Model instance list or attribute list cannot be null.
Action Please provide model instance list or attribute list.

CMPMWSE0032 **MWS Monitoring Context cannot be null.**
Explanation MWS Monitoring Context is required.
Action Please provide MWS Monitoring Context.

CMPMWSE0033 **Model instance list or attribute list cannot be null.**
Explanation Model instance list or attribute list cannot be null.
Action Please provide model instance list or attribute list.

CMPMWSE0034 **Input parameter mbean name cannot be null.**
Explanation Input parameter mbean name is required.
Action Please provide input parameter mbean name.

CMPMWSE0035 **Model instance list or attribute list cannot be null.**
Explanation Model instance list or attribute list cannot be null.
Action Please provide model instance list or attribute list.

CMPMWSE0036 **Invalid response from server: {0}**
Explanation Invalid response from server.
Action Please resolve the issue with output.

CMPMWSE0037 **Model instance list cannot be null.**
Explanation Model instance list cannot be null.
Action Please provide model instance list.

CMPMWSE0038 **Attribute instance list cannot be null.**
Explanation Attribute instance list cannot be null.
Action Please provide attribute instance list.

CMPMWSE0039 **Method Name cannot be empty or null.**
Explanation Method Name cannot be empty or null.
Action Please provide method name.

CMPMWSE0040 **Attribute query string cannot be null.**
Explanation Attribute query string cannot be null.
Action Please provide attribute query string.

CMPMWSE0041 **MWS Monitoring Context cannot be null.**
Explanation MWS Monitoring Context cannot be null.
Action Please provide monitoring context.

CMPMWSE0042 **Attribute value is invalid or not available.**
Explanation Attribute value is invalid or not available.
Action Please provide valid attribute value.

CMPMWSE0043 **MWS Monitoring Context cannot be null.**
Explanation MWS Monitoring Context is required.
Action Please provide MWS Monitoring Context.

CMPMWSE0044 **Input metaModelTypeID cannot be null or empty.**
Explanation Input metaModelTypeID cannot be null or empty.
Action Please provide meta model type ID.

CMPMWSE0045 **Input modelInstanceID cannot be null or empty.**
Explanation Input modelInstanceID cannot be null or empty.
Action Please provide model instance ID.

CMPMWSE0046 **Input attributeID cannot be null or empty.**

Explanation Input attributeID cannot be null or empty.

Action Please provide attribute ID.

CMPMWSE0047 **AttributeQuery cannot be null.**

Explanation AttributeQuery cannot be null.

Action Please provide attribute query.

CMPTCME0001 **Error while vaidating TC Monitoring Context. TC Monitoring Context cannot be null.**

CMPTCME0002 **Error while validating TC Monitoring Context. Context is not terracotta type.**

CMPTCME0003 **Error while validating TC Input Context. TC Input Context cannot be null.**

CMPTCME0004 **Error while validating TC Input Context. Context is not terracotta type.**

CMPTCME0005 **Error while validating TC Input Context. TMC host attribute cannot be null or empty.**

CMPTCME0006 **Error while validating TC Input Context. TMC port attribute is invalid.**

CMPTCME0007 **TC Input Monitoring Context cannot be null.**

CMPTCME0008 **Error while getting meta model. TC Meta model type ID cannot be null or empty.**

CMPTCME0009 **TC Monitoring Context cannot be null.**

CMPTCME0010 **Model instance list cannot be null.**

CMPTCME0011 **Attribute instance list cannot be null.**

CMPTCME0012 **Model instance list or attribute list cannot be null.**

CMPTCME0013 **Attribute query string cannot be null.**

CMPTCME0014 **Attribute value is invalid or not available.**

CMPTCME0015 **Input metaModelTypeID cannot be null or empty.**

CMPTCME0016 **Input modelInstanceID cannot be null or empty.**

CMPTCME0017 **Input attributeID cannot be null or empty.**

CMPTCME0018 **AttributeQuery cannot be null.**

CMPTCME0019 **Version not support.**

CMPTCME0020 **Could not connect to url {0}.**

CMPUMIE0000 **UM HTTP URL Method Name cannot be empty or null.**

Explanation UM HTTP URL Method Name cannot be empty or null.

Action Please provide UM HTTP URL Method Name.

CMPUMIE0001 **Error while validating UM Monitoring Context. UM Monitoring Context cannot be null.**

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0002	**Error while validating UM Monitoring Context. UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required.
Action	Please provide valid UM Monitoring Context.

CMPUMIE0003	**Error while validating UM Monitoring Context. Context object is null.**
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0004	**Error while validating UM Monitoring Context. Context is invalid.**
Explanation	UM Monitoring Context is required.
Action	Please provide valid UM Monitoring Context.

CMPUMIE0005	**Error while validating UM Monitoring Context. Context host attribute cannot be null or empty.**
Explanation	UM Monitoring Context host attribute cannot be null or empty.
Action	Please provide host attribute for UM Monitoring Context.

CMPUMIE0006	**Error while validating UM Monitoring Context. Context port attribute is invalid.**
Explanation	UM Monitoring Context port attribute cannot be null or empty.
Action	Please provide port attribute for UM Monitoring Context.

CMPUMIE0007	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required for getting UM model instances.
Action	Please provide UM Monitoring Context.

CMPUMIE0008	**Error while getting meta model. UM Meta model type ID cannot be null or empty.**
Explanation	UM Meta model type ID cannot be null or empty.
Action	Please provide UM meta model type ID.

CMPUMIE0009	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context cannot be null.
Action	Please provide UM Monitoring Context.

CMPUMIE0010	**Input parameter mbean name cannot be null.**
Explanation	Input parameter mbean name is required.
Action	Please provide input parameter mbean name.

CMPUMIE0011	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required for getting UM model instances.
Action	Please provide UM Monitoring Context.

CMPUMIE0012	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPUMIE0013	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required for getting UM model instances.
Action	Please provide UM Monitoring Context.

CMPUMIE0014	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPUMIE0015	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required for getting UM model instances.
Action	Please provide UM Monitoring Context.

CMPUMIE0016	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPUMIE0017	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0018 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0019 **UM Monitoring Context cannot be null.**

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0020 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0021 **UM Monitoring Context cannot be null.**

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0022 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0023 **UM Monitoring Context cannot be null.**

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0024 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0025 **UM Monitoring Context cannot be null.**

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0026	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPUMIE0027	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0028	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPUMIE0029	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0030	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0031	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPUMIE0032	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0033	**Model instance list or attribute list cannot be null.**
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPUMIE0034 **Input parameter mbean name cannot be null.**

Explanation Input parameter mbean name is required.

Action Please provide input parameter mbean name.

CMPUMIE0035 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0036 **Invalid response from server: {0}**

Explanation Invalid response from server.

Action Please resolve the issue with output.

CMPUMIE0037 **Model instance list cannot be null.**

Explanation Model instance list cannot be null.

Action Please provide model instance list.

CMPUMIE0038 **Attribute instance list cannot be null.**

Explanation Attribute instance list cannot be null.

Action Please provide attribute instance list.

CMPUMIE0039 **Method Name cannot be empty or null.**

Explanation Method Name cannot be empty or null.

Action Please provide method name.

CMPUMIE0040 **Attribute query string cannot be null.**

Explanation Attribute query string cannot be null.

Action Please provide attribute query string.

CMPUMIE0041 **UM Monitoring Context cannot be null.**

Explanation UM Monitoring Context cannot be null.

Action Please provide monitoring context.

CMPUMIE0042	**Attribute value is invalid or not available.**
Explanation	Attribute value is invalid or not available.
Action	Please provide valid attribute value.

CMPUMIE0043	**UM Monitoring Context cannot be null.**
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0044	**Input metaModelTypeID cannot be null or empty.**
Explanation	Input metaModelTypeID cannot be null or empty.
Action	Please provide meta model type ID.

CMPUMIE0045	**Input modelInstanceID cannot be null or empty.**
Explanation	Input modelInstanceID cannot be null or empty.
Action	Please provide model instance ID.

CMPUMIE0046	**Input attributeID cannot be null or empty.**
Explanation	Input attributeID cannot be null or empty.
Action	Please provide attribute ID.

CMPUMIE0047	**AttributeQuery cannot be null.**
Explanation	AttributeQuery cannot be null.
Action	Please provide attribute query.

CMPUMIE0048	**No such node with path {0}**
Explanation	No UM node has been found or stored with the path provided.
Action	Report the error

CMPUMIE0049	**Failed to get attribute values for instance {0}. No such node with path : {1}**
Explanation	Failed to get attribute values for instance {0}. No such node with path : {1}
Action	Report the error

CMPUMIE0050	**Failed for instance {0}. Exception message : {1}**
Explanation	Failed to get attribute values for an instance. Exception message attached.
Action	Report the error

CMPUMIE0051	**Failed for instance {0}. Can't parse path : {1}**
Explanation	Failed to get attribute values for an instance. Failed to parse the attached path.
Action	Report the error

CMPUMIE0052	**Unknown model type: {0} During getting attribute values.**
Explanation	Encountered an unknown model type when getting attribute values.
Action	Report the error

CMPUMIE0053	**Object is invalid or not available.**
Explanation	Object is invalid or not available is a default error message for a missing attribute.
Action	Report the error.

CMPUMIE0054	**Can't create UMMonitoringContext with null UMInputContext**
Explanation	There is code trying to create a UMMonitoringContext with null UMInputContext
Action	Report the error

CMPUMIE0055	**User not authorized on this node. user:{0}, sessionAttributes:{1}**
Explanation	The User specified to connect to the realm is not authorized for operations on this node. Attaches user and sessionAttributes
Action	report the error

CMPUMIE0056	**Input context cannot be null**
Explanation	Input context cannot be null

CMPUMIE0057	**Can't find interface status for {0}**
Explanation	Can't find interface status for an Interface
Action	Report the error

CMPUMIE0058	**Can't find interface name for {0}**
Explanation	Can't find interface name for a interface
Action	Report the error

CMPUMIE0059	**Not Authorized to use nRealmNode methods**
Explanation	This exception will be thrown if a user connecting to UM is Not Authorized to use nRealmNode methods
Action	Report the error

CMPUMIE0060	**Can't set node to null in UMNodeModel**
Explanation	Can't set node to null in UMNodeModel
Action	Report the error

CMPUMIE0061	**Node does not exist in NodeFactory, path:{0}**
Explanation	Node does not exist in NodeFactory, path attached.
Action	Report the error

CMPUMIE0062	**Realm Node Not connected, path:{0}**
Explanation	Realm Node Not connected, the connection has expired or couldn't be established. path attached.
Action	Report the error

CMPUMIE0063	**Realm Node Not connected**
Explanation	Realm Node Not connected
Action	Report the error

CMPUMIE0064	**Exception occurred while getting Object Status, {0}**
Explanation	Exception occurred while getting Object Status, Exception attached.
Action	Report the error

CMPUMIE0065	**Can't get realm for node, path: {0}**
Explanation	Can't get realm for node, path attached
Action	Report the error

CMPUMIE0066	**Node is null during isConnected call in class: {0}**
Explanation	Node is null during isConnected call in class: {0}
Action	Report the error

11 Database Component Configurator Messages

CAN_NOT_RUN_MIGRATE_MSG – Can not run migrate to version {0}

Explanation The user tried to migrate a database component that does not exist.

Action Make sure the database component exists using the catalog action before trying to migrate it.

CMP_STORE_INIT_ERROR – Error initializing definition store instance

Explanation The Database Component Configurator could not initialize all database component definitions.

Action Contact Software AG Global Support.

DCI_INFO_ERROR_MSG Error in getting DCI about information.

Explanation The user displayed the About information, but build information is missing.

Action Contact Software AG Global Support.

ERROR_ENCODING Error in checking database encoding

Explanation The checkEncoding action failed.

Action Make sure the the RDBMS is running.

12 Deployer Messages

1232	**Repository-based deployment does not support deployment of {0} assets when part of a project that also contains either MWS, Optimize, or Business Rules assets.**
Explanation	Deployer does not support deployment of Universal Messaging assets when part of a project that also contains MWS, Optimize, or Business Rules assets.
Action	Remove the the Universal Messaging assets from the deployment set and update the deployment map accordingly. To deploy Universal Messaging assets, you must create a separate project that contains the Universal Messaging assets.
1234	**Deployer issued the following exception while attempting to compile the package: "{0}"**
Explanation	Deployer invoked the wm.server.packages:compilePackage service, and the compilePackage service returned an error.
Action	Verify the network connectivity between the Deployer server and each target Integration Server. Also, verify that the target Integration Servers are up and running. For more information about the error that the compilePackage service returned, see the deploy or simulation report.
1240	**Error occurred while attempting to compile the package {0}. Error details : {1}**
Explanation	This error message is shown in case of compilation errors while compiling java sources present in Integration Server package.
Action	Fix the compilation issue.

185I	**Successfully stored the password entry.**
186I	**Successfully retrieved the password.**
187I	**Successfully deleted the password entry.**
188I	**Successfully retrieved the list of password handles.**
189I	**Successfully updated the password entry.**
190E	**Existing password does not match the specified old password.**
Explanation	The specified old password does not match the password handle.
Action	Supply the correct existing password.
191E	**Password handle {0} does not exist.**
Explanation	An error occurred while retrieving the password entry for the password handle.
Action	Supply a valid password handle.
192E	**An error occurred while listing password handles.**
Explanation	An error occurred while getting the list of available password handles from the password store.
Action	Check the Integration Server logs for more details.
193E	**An error occurred while storing the password entry for handle {0}.**
Explanation	An error occurred while storing the entry for the specified handle and pasword values.
Action	Check the Integration Server logs for more details.
194	**An error occurred while deleting the password entry for handle {0}.**
Explanation	An error occurred while deleting the password entry for the supplied password handle.
Action	Check the Integration Server logs for more details.

195E	**The current user is not authorized to access password store operations.**
Explanation	Only an authorized user can perform create/delete/update/fetch operations on password stores.
Action	Obtain the proper authorization.

DEP.0000.1205E	**Repository-based deployment does not support the simulate operation for the mapped target servers.**
Explanation	Repository-based projects do not support simulate operations for the mapped target servers.
Action	Perform Deploy operation.

DEP.0001.0002E	**Deployer could not connect to server aliases {0}. Make sure the server alias information is correct and the server is running.**
Explanation	Deployer could not connect to the specified server when executing the CreateBuild command-line script.
Action	Make sure the connection information specified to the script is correct and that the server is running.

DEP.0001.0003E	**You are not authorized to extract the {0} project. Ask an administrator or user that has build authorization for the project to perform this task, or ask an administrator to update the authorization for the specified project to give you build authorization.**
Explanation	You do not have build authority for the specified project.
Action	Ask an administrator or user that has build authorization for the project to perform this task or ask an administrator to update the authorization for the specified project to give you build authorization.

DEP.0001.0005E	**Error checking authorization: {0}. Make sure the service exists and the permissions for the service are adequate to allow execution of the service.**
Explanation	An error occurred while invoking the wm.deployer.authorization:isAuthorized service on the Integration Server that is running Deployer.
Action	Make sure the service exists and the permissions for the service are adequate to allow execution of the service.

DEP.0001.0006E	**Error writing project file into build file {0}. Make sure there is sufficient disk space, memory, and operating system privileges.**
Explanation	An error occurred while trying to write the project file in the build archive file.
Action	Make sure there is sufficient disk space, memory, and that you have the proper operating system privileges.

DEP.0001.0007E	**Error writing properties file into build file {0}. Ensure that the project name was correctly specified and that there is sufficient disk space, memory, and operating system privileges.**
Explanation	An error occurred while attempting to write the build properties file in the build archive file.
Action	Ensure there is sufficient disk space, memory, and operating system privileges.

DEP.0001.0008E	**Error closing build file {0}. Make sure there is sufficient disk space, memory, and operating system privileges to close the build file.**
Explanation	An error occurred while attempting to close the build file.
Action	Make sure there is sufficient disk space, memory, and operating system privileges to close the build file.

DEP.0001.0009E	**Error creating build report {0}. Make sure there is sufficient disk space, memory, and operating system privileges to create a build report.**
Explanation	An error occurred when attempting to create a build report.
Action	Make sure there is sufficient disk space, memory, and operating system privileges to create a build report.

DEP.0001.0010E	**Error during extraction: {0}**
Explanation	An error occurred while attempting to create a build for a project. The extraction error can be any error that occurred when attempting to create a build. This error can be caused by an object that is listed in the project, but does not exist on the source system.
Action	Ensure that all objects listed in the project exist on the source system.

DEP.0001.0011E	**Error extracting IS package {0}: {1}. Make sure the service exists and that the permissions are adequate to allow execution of the service.**
Explanation	An error occurred while invoking the wm.deployer.resource.extractor.is:extractPackage service.
Action	Make sure the service exists and that the permissions are adequate to allow execution of the service.

DEP.0001.0012E	**Error extracting IS ACL(s) on source system {0}: {1}. Make sure the service exists and the permissions are adequate to allow execution of the service.**
Explanation	An error occurred while invoking the wm.deployer.resource.extractor.is:extractAcls service on the specified source system.
Action	Make sure the service exists and that the permissions are adequate to allow execution of the service.

DEP.0001.0013E	**Integration Server ACL {0} does not exist on the source system.**
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0014E	**Deployer encountered the following error while extracting Integration Server users from source system {0}: {1}**
Explanation	An error occurred while invoking the wm.deployer.resource.extractor.is:extractUsers service on the specified source system.
Action	Make sure the service exists and that you have the proper permissions to execute the service.

DEP.0001.0015E	**The Integration Server user account {0} does not exist on the source system. Either remove the user account from the project or create it on the source system.**
Explanation	The identified IS user account does not exist on the source system.
Action	Either remove the user account from the project or create it on the source system.

DEP.0001.0016E	**Deployer encountered the following error while extracting Integration Server groups from source system {0}: {1}**
Explanation	An error occurred while invoking the wm.deployer.resource.extractor.is:extractGroups service on the specified source system.
Action	Make sure the service exists and that the permissions are adequate to allow execution of the service.

DEP.0001.0017E	**The Integration Server group {0} does not exist on the source system. Either remove the group from the project or create the group on the source system.**
Explanation	The identified Integration Server group does not exist on the source system.
Action	Either remove the group from the project or create the group on the source system.

DEP.0001.0018E	**Deployer encountered the following error while extracting Integration Server ports from source system {0}: {1}**
Explanation	An error occurred while invoking the wm.deployer.resource.extractor.is:extractPorts service on the specified source system.
Action	Make sure the service exists and the permissions are adequate to allow execution of the service.

DEP.0001.0020E	**Deployer encountered the following error while extracting Integration Server scheduled service {0} ({1}) from source system {2}: {3}**
Explanation	An error occurred while invoking the pub.scheduler:getTaskInfo service on the specified source system.
Action	Make sure the service exists and the permissions are adequate to allow execution of the service. If the error message indicates that the scheduled service is not on the source system, either remove the scheduled service from the project or add it to the source system.

DEP.0001.0021E	**Deployer encountered the following error while extracting assets from Trading Networks from source system {0}: {1}**
Explanation	An error occurred while invoking the wm.tn.admin:exportData service on the specified source Trading Networks system.
Action	Make sure the source Trading Networks system is running, the service exists, and the permissions are adequate to allow execution of the service.

DEP.0001.0035E	**Error invoking service "{0}".**
Explanation	An error occurred invoking a service on the Integration Server that is running Deployer.
Action	Verify that the service exists and that the permissions are adequate to execute the service. For more information, see the Integration Server error message in the Integration Server error log.

DEP.0001.0036E	**An error occurred while invoking service "{0}" on system "{1}".**
Explanation	An error occurred while invoking a service on a remote system.
Action	Verify that the service exists and that the permissions are adequate to execute the service. For more information, see the Integration Server error message in the Integration Server error log.

DEP.0001.0038E	**Project {0} is empty; it does not contain any assets to extract. Use the Deployer user interface to add assets to the project.**
Explanation	The specified project does not contain any assets to extract.
Action	Use the Deployer user interface to add assets to the project.

DEP.0001.0039E	**The following source servers are currently unavailable: {0}. Check your network connection and make sure the source servers are running.**
Explanation	The source servers are not responding to a ping. To ping a server, Deployer executes services as follows: - For an Integration Server system, Deployer uses the wm.server:ping service. - For a Trading Networks system, Deployer uses the wm.tn:ping service. - For any other system, Deployer uses the ping plug-in Web service.
Action	Check the network connection and make sure the source servers are running.

DEP.0001.0041E	**Deployment set {0} has unresolved dependencies and could result in an incomplete deployment. Use the Deployer user interface to resolve the dependencies**
Explanation	The deployment set has unresolved dependencies and could result in an incomplete deployment.
Action	Use the Deployer user interface to resolve the dependencies.

DEP.0001.0042E	**Integration Server package files {0} do not exist. Use the Deployer user interface to verify and edit the list of files for the package.**
Explanation	The list of files specified for the package do not exist.
Action	Use the Deployer user interface to verify and edit the list of files for the package.

DEP.0001.0043E	**Integration Server package {0} does not exist on the source system. Either remove the package from the project or add it to the source system.**
Explanation	The identified Integration Server package does not exist on the source system.
Action	Either remove the package from the project or add it to the source system.

DEP.0001.0044E	**Deployer encountered the following error while extracting assets from {0} on source system {1}: {2}**
Explanation	An error occurred while invoking the Deployer plug-in web service getObjects on the specified source system.
Action	Make sure the source system is running, the service exists, and the permissions are adequate to execute the service.

DEP.0001.0045E	**Build file {0} does not contain a properties file. Build cannot load because the file is incomplete. Make sure the build file is not corrupted and has not been manually updated.**
Explanation	Build cannot load because the file is incomplete.
Action	Make sure the build file is not corrupted and has not been manually updated.

DEP.0001.0053E	**Integration Server port {0} does not exist on the source system and was not extracted into the build. Make sure the port exists in the source system.**
Explanation	The Integration Server port was not extracted into the build.
Action	Make sure the port exists in the source system.

DEP.0001.0054E	**The Integration Server scheduled service does not exist on source system {0}: {1}**
Explanation	The scheduled service does not exist on the source server.
Action	Either remove the scheduled service from the project or add it to the source system.

DEP.0001.0068E	**Deployer encountered the following error while extracting Integration Server package {0} node ACLs: {1}**
Explanation	Error when executing the wm.deployer.resource.gui.IS:getTypedPackageContents service.
Action	Make sure the service exists on the Integration Server and the user has the necessary privileges to execute the service.

DEP.0001.0069E	**Error writing to the build file {0}. Make sure the build file exists, that it has read/write permission, and that the file system has adequate space.**
Explanation	An error occurred while trying to write to the build file.
Action	Read the error message to determine the possible causes. Make sure the build file exists, that it has read/write permission, and there is adequate space for it on the file system.

DEP.0001.0070E	**Trading Networks field group {0} does not exist on the specified source Trading Networks system. Either remove the profile field group from the project or add it to the source Trading Networks system.**
Explanation	The identified Trading Networks profile field group does not exist on the specified source Trading Networks system.
Action	Either remove the profile field group from the project or add it to the source Trading Networks system.

DEP.0001.0071E	**Trading Networks field definition {0} does not exist on the source Trading Networks system. Either remove the profile field definition from the project or add it to the source Trading Networks system.**
Explanation	The identified Trading Networks profile field definition does not exist on the source Trading Networks system.
Action	Either remove the profile field definition from the project or add it to the source Trading Networks system.

DEP.0001.0072E	**Trading Networks Profile {0} does not exist on the source Trading Networks system. Either remove the profile from the project or add it to the source Trading Networks system.**
Explanation	The identified Trading Networks profile does not exist on the source Trading Networks system.
Action	Either remove the profile from the project or add it to the source Trading Networks system.

DEP.0001.0073E	**Trading Networks TPA {0} does not exist on the source Trading Networks system. Either remove the TPA from the project or add it to the source Trading Networks system.**
Explanation	The identified Trading Networks trading partner agreement (TPA) does not exist on the source Trading Networks system.
Action	Either remove the TPA from the project or add it to the source Trading Networks system.

DEP.0001.0074E	**Trading Networks document attribute {0} does not exist on the source Trading Networks system. Either remove the document attribute from the project or add it to the source Trading Networks system.**
Explanation	The identified Trading Networks document attribute does not exist on the source Trading Networks system.
Action	Either remove the document attribute from the project or add it to the source Trading Networks system.

DEP.0001.0075E	**Trading Networks document type {0} does not exist on the source Trading Networks system. Either remove the Trading Networks document type from the project or add it to the source Trading Networks system.**
Explanation	The identified Trading Networks document type does not exist on the source Trading Networks system.
Action	Either remove the Trading Networks document type from the project or add it to the source Trading Networks system.

DEP.0001.0076E **Trading Networks processing rule {0} does not exist on the Trading Networks source system. Either remove the processing rule from the project or add it to the source Trading Networks system.**

Explanation The identified Trading Networks processing rule does not exist on the Trading Networks source system.

Action Either remove the processing rule from the project or add it to the source Trading Networks system.

DEP.0001.0077E **Trading Networks external ID type {0} does not exist on the source Trading Networks system. Either remove the external ID type from the project or add it to the source Trading Networks system.**

Explanation The identified Trading Networks external ID type does not exist on the source Trading Networks system.

Action Either remove the external ID type from the project or add it to the source Trading Networks system.

DEP.0001.0078E **Trading Network contact type {0} does not exist on the source Trading Networks system. Either remove the contact type from the project or add it to the source Trading Networks system.**

Explanation The identified Trading Networks contact type does not exist on the source Trading Networks system.

Action Either remove the contact type from the project or add it to the source Trading Networks system.

DEP.0001.0079E **Trading Networks binary type {0} does not exist on the source Trading Networks system. Either remove the binary type from the project or add it to the source Trading Networks system.**

Explanation The identified Trading Networks binary type does not exist on the source Trading Networks system.

Action Either remove the binary type from the project or add it to the source Trading Networks system.

DEP.0001.0080E **Trading Networks profile group {0} does not exist on the source Trading Networks system. Either remove the profile group from the project or add it to the source Trading Networks system.**

Explanation The identified Trading Networks profile group does not exist on the source Trading Networks system.

Action Either remove the profile group from the project or add it to the source Trading Networks system.

DEP.0001.0081E	**Trading Networks extended field {0} for profile {1} does not exist on the source Trading Networks system for the specified profile. Either remove the extended field from the project or add it to the appropriate profile in the source Trading Networks system.**
Explanation	The identified Trading Networks extended field does not exist on the source Trading Networks system for the specified profile.
Action	Either remove the extended field from the project or add it to the appropriate profile in the source Trading Networks system.

DEP.0001.0082E	**Trading Networks security data item {0} does not exist on the source Trading Networks system. Either remove the security data item from the project or add it to the source Trading Networks system.**
Explanation	The identifed Trading Networks security data item does not exist on the source Trading Networks system.
Action	Either remove the security data item from the project or add it to the source Trading Networks system.

DEP.0001.0085W	**Warning creating build {0}. See build report for details.**
Explanation	Deployer issued a warning while creating the build.
Action	Check the build report for details.

DEP.0001.0087E	**Deployer encountered the following error while extracting Integration Server extended settings from source system {0}: {1}**
Explanation	An error occurred while invoking the wm.deployer.resource.extractor.is:extractExtendedSettings service on the specified source system.
Action	Make sure the service exists and that the permissions are adequate to allow execution of the service.

DEP.0001.0093	**Trading Networks queue {0} does not exist on the source system. Either remove the asset from the project or add it to the source system.**
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0094E	**Integration Server extended setting {0} does not exist on the source server.**
Explanation	The indicated extended setting does not exist on the source server.
Action	Either remove the extended setting from the project or add the extended setting to the source server.

DEP.0001.0109	**TN processing rule {0} does not exist on the source system. Either remove the asset from the project or add it to the source system.**
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0114	**TN extended field {0} for profile {1} does not exist on the source system. Either remove the asset from the project or add it to the source system.**
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0117	**Cannot write to build directory: {0}. The Integration Server user does not have privileges to create or write to a file. Make sure the user has the correct privileges.**
Explanation	The Integration Server user does not have privileges to create or write to a file.
Action	Make sure the user has the correct privileges.

DEP.0001.0118	**Error writing checkpoint report: {0}. An error occurred while attempting to close the build file. Make sure there is sufficient disk space, memory, and operating system privileges.**
Explanation	An error occurred while attempting to close the build file.
Action	Make sure there is sufficient disk space, memory, and operating system privileges.

DEP.0001.0119	**IS scheduled service {0} ({1}) does not exist on the source server. Either remove the scheduled service from the project or add it to the source system.**
Explanation	The identified asset was not found on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0122	**TN Dls {0} does not exist on the source server. Either remove the asset from the project or add it to the source system.**
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0125	**TN Fp {0} does not exist on the source system.**
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0128	**TN Archival Service {0} does not exist on the source system.**
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0130	**The Target Server/Group {0} is not currently available; skipping that Target Server/Group. Check your network connection, and verify that the Target Server/Group is running.**
Explanation	Deployer cannot ping a target server or some servers in a target group. This might occur because the servers in question are not running or because of network latency.
Action	Make sure that the servers in question are running.

DEP.0001.0131	**{0} {1} {2} does not exist on the source system.**
Explanation	The identified objects do not exist on the source system.
Action	Either remove the identified objects from the project or add them to the source system.

DEP.0001.0133	**Could not rebuild project {0} because the specific build in the project could not be rebuilt. See the Integration Server logs for more information.**
Explanation	Deployer could not migrate the project because the specific build in the project could not be rebuilt.
Action	See the Integration Server logs for more information.

DEP.0001.0135	**Deployer could not migrate project {0}. Make sure all source servers specified in project {0} are running. See the Integration Server logs for more information.**
Explanation	Deployer could not migrate the project.
Action	See the Integration Server logs for more information.

DEP.0001.0136	**Could not migrate projects data. See the Integration Server logs for more information.**
Explanation	Deployer was unable to migrate the project data.
Action	See the Integration Server logs for more information.

DEP.0001.0139	**Some of the projects could not be migrated. See the Integration Server logs for more information.**
Explanation	Deployer could not migrate all projects.
Action	See the Integration Server logs for more information.

DEP.0001.0144E	**The source servers hosting the deployment sets are from different releases. Make sure all source servers are from the same release.**
Explanation	Deployer issues this message and ends the build process when you modify the version of the source server alias for existing projects.
Action	Make sure all source servers are from the same release.

DEP.0001.0145E	**Deployer did not migrate the following target groups because the alias servers were not migrated to the correct version. Change the version of the server alias or target group so that the two match.**
Explanation	You migrated a target group to a different version than that of its server alias.
Action	Change the version of the server alias or target group so that the two match.

DEP.0001.0153W	**Marked {0} {1} for deletion. The indicated server, or the network connection to that server, is not available. Alternatively, the command-line values for user and password might not be valid on the indicated server. Confirm that the server is running and reachable, and that the user/password values are valid.**
Explanation	The indicated server, or the network connection to that server, is not available. Alternatively, the command-line values for user and password might not be valid on the indicated server.
Action	Confirm that the server is running and reachable, and that the user/password values are valid.

DEP.0001.0154W	**Streamed file {0} for file {1} in deployment set {3} not found. The Integration Server, or the network connection to that server, might be shut down. Confirm that the server is running and that the network connection is up.**
Explanation	The Integration Server, or the network connection to that server, might be shut down.
Action	Confirm that the server is running and that the network connection is up.

DEP.0001.0155	**Error while reading streamed file {0} for file {1} in deployment set {3}. See the Integration Server logs for more information.**
Explanation	An error occured while reading the streamed file.
Action	See the Integration Server logs for more information.

DEP.0001.0156	**Deployer could not connect to the source server aliases specified in the project. Deployer could not rebuild and upgrade the project {0}. Make sure the server alias information is correct and the servers are running.**
Explanation	Deployer could not migrate the project because the specific build in the project could not be rebuilt.
Action	Make sure the source servers for the deployment set in the build are running.

DEP.0001.0158E	**Build name {0} contains one or more of the following invalid characters: # & @ ^ ! & * : $ / ` ' ; , ~ + = > < " Remove the invalid characters from the build name.**
Explanation	The build name contains one or more of the following invalid characters: # & @ ^ ! % * : $ /\ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the build name.

DEP.0001.0159E	**Deployer could not migrate the Deployer settings. See the Integration Server logs for more information.**
Explanation	Deployer encountered an error while migrating the Deployer settings.
Action	Check the Integration Server logs for more information.

DEP.0001.0161E	**Deployer could not migrate settings.**
Explanation	Deployer did not receive the settings during migration.
Action	Reload the Deployer package.

DEP.0002.0004E	**Project {0} does not contain a deployment set named {1}.**
Explanation	The Deployer user interface referenced a deployment set name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment set, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0006E	**Deployer did not find a dependency on component {0} was found.**
Explanation	The Deployer user interface attempted to delete a dependency that is not recognized by Deployer. Another Deployer session might have deleted the dependency, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0007E	**Deployer cannot access server alias {0} in deployment set {1}.**
Explanation	The Deployer user interface referenced a source server name that is not recognized by Deployer. Another Deployer session might have deleted the source server from the project, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0008E	**Package {0} from server alias {1} does not exist in deployment set {2}.**
Explanation	The Deployer user interface referenced a package or server name that is not recognized by Deployer. Another Deployer session might have deleted the package or server name from the project, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0009E	**Server {0} already exists in deployment set {1} as a non-Integration Server server. You cannot add Integration Server objects to it.**
Explanation	You passed an incorrect value for the parameter.
Action	Avoid executing the service outside of the Deployer user interface.

DEP.0002.0010E	**Package {0} already exists in deployment set {1} as a complete package. Cannot add package components or files to it.**
Explanation	You attempted to add package components to a deployment set that already exists on the deployment set.
Action	If you want to include the entire package in a deployment set, no action is necessary because it is already included. If you want the deployment set to contain only a partial package, first remove the entire package from the deployment set before trying to add specific package components.

DEP.0002.0011E	**Project {0} already contains a deployment set named {1}. Use a different name for the new deployment set.**
Explanation	You attempted to add a deployment set to the specified project, but the project already has a deployment set that uses the same name that you specified.
Action	Use a different name for the new deployment set.

DEP.0002.0012E	**Project name {0} contains illegal characters.**
Explanation	The project name contains spaces or one or more of the following invalid characters: # & @ ^ ! % * : $ /\ \ ` ' ; , ~ + = > < \ "
Action	Specify another name for the project that does not include the illegal characters.

DEP.0002.0013E	**Could not complete project copy due to file system error. Check your Integration Server's disk space. If you believe there is sufficient space, try the copy again. As a final option, manually recreate the project.**
Explanation	Deployer encountered an error writing the project to disk.
Action	Check your Integration Server's disk space. If you believe there is sufficient space, try the copy again. As a final option, manually recreate the project.

DEP.0002.0014E	**Project {0} already exists. Use a different, unique name for the new project.**
Explanation	A project with the name you specified already exists.
Action	Use a different, unique name for the new project.

DEP.0002.0015E	**Deployer was unable to invoke service {0}.**
Explanation	Deployer was unable to find the specified Integration Server service.
Action	Determine whether a required Integration Server package is disabled, missing, or whether parts are missing. Check for the following packages: WmDeployer, WmAdmin, WmRoot, WmDeployerResource, and WmModeler.

DEP.0002.0016E	**Unable to delete build {0}. The build file is probably in use. This file exists in the <serverDirectory>/packages/WmDeployer/persist/projects/<YourProjectName>/builds directory. Locate the process that is accessing this file and stop it. Then try to delete the build again.**
Explanation	Deployer was unable to delete the specified build file.
Action	The build file is probably in use. This file exists in the <serverDirectory>/packages/WmDeployer/persist/projects/<YourProjectName>/builds directory. Locate the process that is accessing this file and stop it. Then try to delete the build again.

DEP.0002.0017E	**Project {0} does not contain a build named {1}.**
Explanation	The Deployer user interface referenced a build name that is not recognized by Deployer. Another Deployer session might have deleted this build, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0018E	**Deployer could not load build {0}.**
Explanation	The build file is corrupted.
Action	Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\builds directory and manually remove the corrupted build file. Then use Deployer to rebuild.

DEP.0002.0019E	**Deployment map {0} already exists in project {1}.**
Explanation	You attempted to create a deployment map with the same name as an existing deployment map.
Action	Use a different name for the new deployment map.

DEP.0002.0020E	**Deployment map {0} does not exist in project {1}.**
Explanation	The Deployer user interface referenced a deployment map name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment map, or the project on the file system might be corrupted.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0021E	**Deployer could not load deployment map {0} from project {1}.**
Explanation	The deployment map file is corrupted.
Action	Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory and manually remove your deployment candidate file. Then use Deployer to recreate it.

DEP.0002.0026E	**Deployer could not save deployment map {0}.**
Explanation	Deployer encountered an error writing to disk.
Action	Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If this is not successful, try one or both of the following: Restart the server. Recreate the deployment map.

DEP.0002.0028E	**Deployment set {0} is not mapped to target {1}.**
Explanation	The Deployer user interface referenced a deployment set name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment set, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0031	**Could not invoke service {0} remotely.**
Explanation	An integration service invocation failed.
Action	Ensure that the Integration Server is running and that the service exists on that Integration Server. Also ensure that you have the proper previleges to execute the service.

DEP.0002.0032E	**Server Alias cannot be blank.**
Explanation	You left the required Server Alias field blank.
Action	Specify a value for the Server Alias field and try again.

DEP.0002.0054E	**The value specified for the task parameter is not valid.**
Explanation	You passed an incorrect value for the task parameter. The task must be either DEFINE, MAP, EXTRACT, DEPLOY, or VIEW.
Action	Avoid executing the service outside of the Deployer user interface.

DEP.0002.0058E	**Deployer cannot perform export operation because the file {0} already exists under WmDeployer/outbound**
Explanation	You attempted to export a build with the same name as an existing build.
Action	Use a different name when you export the build.

DEP.0002.0059E	**The Deployer import map file {0} is not accessible or does not exist.**
Explanation	You attempted to import a build that does not exist.
Action	Refresh the Import Build page and try again.

DEP.0002.0060E	**User is not authorized to export builds from project {0}.**
Explanation	You are not authorized to export builds for the specified project. You must have build authorization for the project.
Action	Ask an administrator or user that has build authorization for the project to perform this task or have an administrator assign you build authorization.

DEP.0002.0061E	**User is not authorized to import builds to project {0}.**
Explanation	You are not authorized to import builds for the specified project. You must have build authorization for the project.
Action	Ask an administrator or user that has build authorization for the project to perform this task or have an administrator assign you build authorization.

DEP.0002.0064E	**Deployment set {0} already exists in project {1}.**
Explanation	You attempted to create a deployment set in a project that already contains a deployment set of the same name.
Action	Use a different name for the new deployment set.

DEP.0002.0065E	**Deployer encountered an error and did not save deployment {0}.**
Explanation	Deployer encountered an error while writing to disk.
Action	Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If Deployer still cannot save the deployment, restart the server or recreate the deployment candidate.

DEP.0002.0067E	**Deployment candidate {0} does not exist in project {1}.**
Explanation	The Deployer user interface referenced a deployment candidate that is not recognized by Deployer. Another Deployer session might have deleted the deployment candidate, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0068E	**Unable to delete deployment map {0}.**
Explanation	Deployer was unable to delete the specified deployment map file.
Action	The deployment map file is probably in use. This file exists in the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory. Locate the process that is accessing this file and stop it. Then try to delete the deployment candidate again.

DEP.0002.0069E	**Unable to delete deployment candidate {0}.**
Explanation	Deployer was unable to delete the deployment candidate file.
Action	The deployment candidate file is probably in use. This file exists in the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\deployments directory. Locate the process that is accessing this file and stop it. Then try to delete the deployment candidate again.

DEP.0002.0072E	**Deployer could not load deployment {0} from project {1}.**
Explanation	The deployment candidate file is corrupted.
Action	Use Windows Explorer to locate to the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\deployments directory and manually remove the deployment candidate file. Then use Deployer to recreate it.

DEP.0002.0073E	**Deployer could not add component {0} of type {1}.**
Explanation	Deployer does not recognize the specified Integration Server component.
Action	Rather than attempting to add the component to the project, add the files that comprise the component (example, "ns" directory). You can also try adding the entire package rather than individual components of the package.

DEP.0002.0075E	**When you specify "deploymentName", you cannot specify additional arguments .**
Explanation	You specified incorrect arguments when running the deploy.bat or deploy.sh script.
Action	The deploy script can either reference an existing deployment candidate or create a new deployment candidate. When you specify the "deploymentName" argument to reference an existing deployment candidate do not supply other arguments.

DEP.0002.0076E	**When you specify "newDeploymentName", "buildName" and "deploymentMapName" are required.**
Explanation	You specified incorrect arguments for the deploy.bat or deploy.sh script.
Action	You can specify the deploy script to either reference an existing deployment candidate or to create a new deployment candidate. If you use the "newDeploymentName" argument to create a new deployment candidate, you must also specify the "buildName" and "deploymentMapName" arguments.

DEP.0002.0077E	**You are not authorized to modify the project definition.**
Explanation	You are not authorized to define a project.
Action	Ask an administrator or user that has define authorization to perform the action for you or have an administrator assign you define authorization.

DEP.0002.0078E	**You are not authorized to modify the project target mapping.**
Explanation	You are not authorized to map a project.
Action	Ask an administrator or user that has map authorization to perform the action for you or have an administrator assign you map authorization.

DEP.0002.0079E	**You are not authorized to modify project deployments.**
Explanation	You are not authorized to deploy a project.
Action	Ask an administrator or user that has deploy authorization to perform the action for you or have an administrator assign you deploy authorization.

DEP.0002.0080E	**You are not authorized to remove project builds.**
Explanation	You are not authorized to build a project.
Action	Ask an administrator or user that has build authorization to perform the action for you or have an administrator assign you build authorization.

DEP.0002.0081E	**Deployer cannot delete build {0} because it is being used by deployment candidate {1}.**
Explanation	You attempted to delete a build that is referenced by a deployment candidate.
Action	Delete or modify the deployment candidate that references the build or do not delete this build.

DEP.0002.0082E	**Deployer cannot delete deployment map {0} because it is being used by deployment candidate {1}.**
Explanation	You attempted to delete a deployment map that is referenced by another deployment candidate.
Action	Delete or modify the deployment candidate that references the deployment map.

DEP.0002.0083E	**Deployer encountered the following exception while parsing project {0}: {1}**
Explanation	An exception occurred while trying to load the project. The exception be due to an input/output error.
Action	Review the exception message to determine the cause of the error.

DEP.0002.0085E	**Deployer could not add package {0} to the deployment set.**
Explanation	Deployer was unable to determine which components in the package were available for variable substitution. The problem might be that the source Integration Server was temporarily unavailable.
Action	Check the Integration Server Error log to determine the reason that Deployer was unable to access information about the package components.

DEP.0002.0086E	**Deployment map {0} in project {1} is corrupted and must be removed. It references deployment set {2} which does not exist.**
Explanation	The deployment map file is corrupted.
Action	Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory and manually remove the deployment map file. Then use Deployer to recreate it.

DEP.0002.0087E	**Deployer cannot remove deployment set {0}. It is referenced by deployment map {1}.**
Explanation	You attempted to delete a deployment set that is being referenced by a deployment map.
Action	Perform one of the following: - Delete or modify the deployment map that references the deployment set. - Do not delete the deployment set.

DEP.0002.0089E	**Deployer could not save adapter connection metadata for project {0}**
Explanation	The project is corrupted.
Action	Retry the last action taken on the deployment project. If the action is unsuccessful, create a new project.

DEP.0002.0092E	**Deployer cannot update package {0} version in the deployment set.**
Explanation	Deployer was unable to access the specified package on the server.
Action	Retry the action. If the action is unsuccessful, investigate why Deployer is unable to locate the specified package on the remote server. If the package appears to be available on the remote server, shut down the Deployer window (as well as the window that launched Deployer) and restart the browser.

DEP.0002.0093E	**Both the {0} and the {1} Deployer plug-ins contain the Deployer plug-in type {2}.**
Explanation	More than one plug-in for the same type of deployment asset has been detected. This indicates a problem with the configuration of the Deployer.
Action	Update the configuration of the Deployer to remove extraneous plug-ins for the same type of deployment asset. Alternatively, you can uninstall, then reinstall Deployer.

DEP.0002.0096E	**Deployer is currently unable to access Trading Networks system: {0}.**
Explanation	No data was returned from the specified Trading Networks server. This indicates that the Trading Networks server is not accessible.
Action	Ensure that the Trading Networks server is accessible over the network and that you have correctly configured the server alias.

DEP.0002.0097E	**Deployer is currently unable to access target system: {0}.**
Explanation	The target Trading Networks Server is not available. The server did not respond to a server ping.
Action	Ensure that the Trading Networks Server is accessible over the network and that you have correctly configured the server alias for the Trading Networks server.

DEP.0002.0098E	**Deployer cannot check target cluster configuration. The target is missing the Deployer resource package. This can be installed from the Servers > IS & TN screen.**
Explanation	An error occurred while Deployer attempted to access a service on the target WmDeployerResource package.
Action	Install the current version of WmDeployerResource package on the target server.

DEP.0002.0099E	**Cluster node details not available.**
Explanation	An error occurred when the Deployer attempted to access a service on the target WmDeployerResource package.
Action	Install the current version of the WmDeployerResource package on the target server. Also, ensure that the target server is running and that Deployer can access it over the network.

DEP.0002.0101E	**The source servers hosting the deployment sets are different versions.**
Explanation	The source servers hosting the deployment sets are different versions.
Action	Modify the source servers to use the same versions.

DEP.0002.0102E	**The target server or target group is a different version than the project source. Select servers that use the same version.**
Explanation	Deployer issues this error message when you add a target server or target group to a deployment map and the version of the target server or group is different than that of the project source server.
Action	Use a target server or target group that is the same version as the project source server.

DEP.0002.0106E	**Dependencies may not contain the $ character.**
Explanation	You added a manual dependency that contains the $ character.
Action	Remove the $ character.

DEP.0002.0109E	**Failed to install resource package on Integration Server {0}: {1}**
Explanation	Deployer is trying to install the WmDeployerResource package on the IntegrationServer indicated by <serverName>, but the attempt failed. The <exceptionMessage> provides more information.
Action	Make sure the server is running and connected to the network, and that the system has sufficient disk space, memory, and necessary operating system privileges.

DEP.0002.0110E	**Deployer could not locate resource package {0}. Make sure the WmDeployerResource package has been installed on the Integration Server that hosts Deployer and that the system has sufficient disk space, memory, and the necessary operating system privileges.**
Explanation	An error occurred when the Deployer tried to locate the WmDeployerResource package. The <exceptionMessage> provides information about why that attempt failed. The resource package might not exist on your Integration Server or might require more memory.
Action	Make sure the WmDeployerResource package has been installed on the Integration Server that hosts Deployer and that the system has sufficient disk space, memory, and the necessary operating system privileges.

DEP.0002.0112	**Unable to import the XML document {0} nl{1}. The XML file you passed in either the import map or the import varsub flow is invalid. Correct the XML file as necessary.**
Explanation	The XML file you passed in either the import map or the import varsub flow is invalid.
Action	Correct the XML file as necessary.

DEP.0002.0114	**Input XML varsub information is not valid. It might contain an asset type for which varsub is not supported. Validate the XML file against the wm.deployer.flows:DeploymentMap_Definition or wm.deployer.flows:Varsub_Definition XSD.**
Explanation	The varsub XML file is not valid. It might contain an asset type for which varsub is not supported. The assets for which varsub is supported are AdapterConnection, ScheduledService, ExtendedSettings, Port, AdapterNotification, AdapterListener, eform, and webServiceDescriptor.
Action	Validate the XML file against the wm.deployer.flows:DeploymentMap_Definition or wm.deployer.flows:Varsub_Definition XSD.

DEP.0002.0116	**Exporting of map {0} failed; the exported map file already exists in the WmDeployer/replicate/inbound folder. Make a backup of the map file in another location, delete the map file from the inbound folder, and then export the map file again.**
Explanation	The exported map file already exists in the WmDeployer/replicate/inbound folder.
Action	Make a backup of the map file in another location, delete the map file from the inbound folder, and then export the map file again.

DEP.0002.0118	**Importing of map {0} failed. Make sure the wm.deployer.gui.UITarget:addMapSetToProject service exists and that the user has the necessary previleges for executing the service, and then try again.**
Explanation	This error might occur for no specific reason.
Action	Make sure the wm.deployer.gui.UITarget:addMapSetToProject service exists and that the user has the necessary privileges for executing the service, and then try again.

DEP.0002.0119	**Deployment map {0} already exists in project {1} and cannot be overwritten.**
Explanation	You attempted to import a map file for a map that already exists.
Action	Delete the existing map and then import the map. If you need a backup of the existing map export the map and store it in a different location.

DEP.0002.0120	**Unable to list remote server aliases.**
Explanation	This error might occur for no specific reason.
Action	Make sure the wm.deployer.Util:listAliases service exists and the user has the necessary privileges for executing the service. then try again.

DEP.0002.0121	**Unable to list target group aliases.**
Explanation	This error might occur for no specific reason.
Action	Make sure the wm.deployer.gui.UITargetGroup:listTargetGroups service exists and the user has the necessary privileges for executing the service. Then try again.

DEP.0002.0124	**Deployment set {0} is not valid for project {1}.**
Explanation	One or more deployment sets defined in the map file you are importing are not included in the project definition.
Action	Make sure the map file you are trying to import is consistent with the define step of the project.

DEP.0002.0125	**The target server {0} is not valid for plugin type {1}. Either define the target server alias on the Deployer where you are trying to import the map file or remove the target server alias from the exported map file.**
Explanation	This error is shown when you attempt to import a map file that contains a target server alias that is not defined on that Deployer.
Action	Either define the target server alias on the Deployer where you are trying to import the map file or remove the target server alias from the exported map file.

DEP.0002.0126	**The target group {0} is not valid for plugin type {1}. Define the target group on the Deployer where you are trying to import the map file or else remove the target group from the exported map file.**
Explanation	This error is shown when you try to import a map file that contains a target group not defined on that Deployer.
Action	Define the target group on the Deployer where you are trying to import the map file or else remove the target group from the exported map file.

DEP.0002.0129	**Either the number passed is not a number or is negative. Enter an integer value for the flag -id for the command --showReport.**
Explanation	This error is thrown by the Deployer comand line interface for the --showReport command. The --showReport command requires an integer value for the flag -id. If an integer is not entered for this flag then the above error is thrown.
Action	Enter an integer value for the flag -id for the command --showReport.

DEP.0002.0133	**Error exporting properties for the project {0}.**
Explanation	This error might occur for no specific reason.
Action	Make sure the wm.deployer.gui.UIProject:getFormattedProjectInfo service exists and the user has the necessary privileges for executing the service.

DEP.0002.0135	**Error retrieving properties for the project {0}.**
Explanation	This error might occur for no specific reason.
Action	Make sure the wm.deployer.gui.UIProject:getFormattedProjectInfo service exists and the user has the necessary privileges for executing the service.

DEP.0002.0136	**Unable to import zip file; zip file might be corrupt. Copy the build file from the source Deployer again. If this does not fix the problem, rebuild the original project and export the build again.**
Explanation	The build file placed in the WmDeployer/replicate/inbound is corrupted. This can occur because of error while copying the build file.
Action	Copy the build file from the source Deployer again. If this does not fix the problem, rebuild the original project and export the build again.

DEP.0002.0137	**Install of WmDeployerResource package cannot proceed. All the nodes in this cluster are not online. The following nodes are offline: {0}. Installing the package on the local node only.**
Explanation	This error occurs when you try to install the WmDeployerResource package on a cluster node and some of the nodes of the cluster are offline.
Action	Make sure all the nodes in the cluster are online.

DEP.0002.0138E	**You tried to add a target server or a target group of the same name as one that already exists in the deployment map.**
Explanation	You tried to add a target server or a target group of the same name as one that already exists in the deployment map.
Action	Rename the target server or target group alias and add it to the map.

DEP.0002.0139	**Cannot import the deployment map. Make sure the field names, values and the structure of the XML file are valid.**
Explanation	The exported map does not have the expected structure.
Action	If you modified the XML, validate the exported XML with the service wm.deployer.flows:validateXMLWithXSD. If you are exporting a map, pass the schema file as wm.deployer.flows:DeploymentMap_Definition. If you are exporting a varsub, pass the schema file as wm.deployer.flows:Varsub_Definition.

DEP.0002.0140	**Cannot import variable substitution values. Make sure the field names and values and the structure of the XML file are valid.**
Explanation	This error occurs when the exported map does not have the expected structure.
Action	If you have modified the XML, validate the exported xml with the service wm.deployer.flows:validateXMLWithXSD. If you are exporting a map then pass the schema file as wm.deployer.flows:DeploymentMap_Definition. If you are exporting a varsub then pass the schema file as wm.deployer.flows:Varsub_Definition.

DEP.0002.0142	**Project {0} already contains a deletion set named {1}. Rename the deployment or deletion set you are trying to create or delete the existing deployment or deletion set from the project. Then retry your action.**
Explanation	You tried to add a deployment or deletion set of the same name as one of the deployment or deletion sets already in the project.
Action	Rename the deployment or deletion set you are trying to create or delete the existing deployment or deletion set from the project. Then retry your action.

DEP.0002.0143	**A project can have only one deletion set for each server type. Deletion set {0} already exists for {1}. You can add assets to existing deleting sets, or delete the existing deletion set before trying to create another deletion set.**
Explanation	You attempted to create a deletion set on a project that already contains one. Only one deletion set can be created for a project.
Action	You can add assets to existing deleting sets, or delete the existing deletion set before trying to create another deletion set.

DEP.0002.0144E	**Deployer encountered an error while trying to get dependent assets for deletion set {0}. See the Integration Server logs.**
Explanation	This error might occur for no specific reason.
Action	Ensure the wm.deployer.gui.UITarget:checkTargetDependencies service exists and the user has the necessary privileges for executing the service.

DEP.0002.0146	**Deletion sets definition file {0} already exists for this project. Make a back up of the existing file in another location and then delete the file. Then export the deletion set again.**
Explanation	The exported file already exists and another export for the same deletion set would cause this error.
Action	Make a back up of the existing file in another location and then delete the file. Then export the deletion set again.

DEP.0002.0147	**Rollback on deployment candidate {0} failed. Check the rollback report for more information.**
Explanation	This error might occur for no specific reason.
Action	Check the rollback report for further information.

DEP.0002.0148	**No such deployment candidate {0} found in project {1}. Delete and recreate the deployment candidate.**
Explanation	This error might occur for no specific reason.
Action	Delete and recreate the deployment candidate.

DEP.0002.0149	**Deployment candidate {0} in project {1} is not checkpointed. Use the Deployer command-line interface to create a checkpoint for the deployment candiate. If you want to deploy without creating a checkpoint, use the -force flag.**
Explanation	This error is shown when you attempt to deploy without creating a checkpoint from the Deployer command-line interface.
Action	Use the Deployer command-line interface to create a checkpoint for the deployment candiate. If you want to deploy without creating a checkpoint, use the -force flag.

DEP.0002.0150	**The WmDeployerResource package is not installed on the target Integration Server. Install the WmDeployerResource package on the target Integration Server from the Deployer user interface on the Integration Server alias page.**
Explanation	The WmDeployerResource package is not installed on the target Integration Server.
Action	Install the WmDeployerResource package on the target Integration Server from the Deployer user interface on the Integration Server alias page.

DEP.0002.0158E	**Deployer did not save the versions for the aliases {0} because the aliases do not exist. Make sure the alias for which you specified the version is valid.**
Explanation	The alias for which you tried to update the version does not exist.
Action	Make sure the alias for which you specified the version is valid.

DEP.0002.0159E	**The deployment set contains source servers of different versions. Source servers in a deployment set must be the same version. Remove the source servers with the wrong version from the deployment set or change the versions to match.**
Explanation	The source servers in the deployment set are different versions.
Action	Remove the source servers with the wrong version from the deployment set or change the versions to match.

DEP.0002.0160E	**The deployment maps contain target servers of different versions. Target servers in deployment maps must be the same version. Remove the target servers with the wrong version from the deployment maps or change the versions to match.**
Explanation	The target servers in the deployment maps are different versions.
Action	Remove the target servers with the wrong version from the deployment maps or change the versions to match.

DEP.0002.0162E	**Repository name {0} contains illegal characters.**
Explanation	The repository name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : $ /\ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the repository alias name.

DEP.0002.0163E	**Deployment set name {0} contains illegal characters.**
Explanation	The deployment set name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : $ /\ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the deployment set name.

DEP.0002.0164E	**Deployment map name {0} contains illegal characters.**
Explanation	The deployment map name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : $ /\ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the deployment map name.

DEP.0002.0165E	**Deployment candidate name {0} contains illegal characters.**
Explanation	The deployment candidate name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : $ /\ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the deployment candidate name.

DEP.0002.0166E	**Component {0} not found in composite {1} from repository source {2}.**
Explanation	The contents of the repository have been modified.
Action	Run the build script again or recreate the repository.

DEP.0002.0167E	**There is an error in deployment candidates(s) {0} from project {1}. See the Integration Server logs for more information.**
Explanation	Deployer displays this error for various reasons.
Action	See the Integration Server logs for an explanation of the exception.

DEP.0002.0168E	**Cannot save variable substitutions. There are no servers selected.**
Explanation	Deployer requires that you select at least one server for variable substitutions.
Action	Select at least one server from the list of selected servers.

DEP.0002.0172W	**When adding a new target server to the map, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**
Explanation	Adding new target servers to the map will cause Deployer to remove any checkpoints previously created for the deployment candidates associated with this map.
Action	If you continue with the change, you must recreate any checkpoints you want to use for the associated deployment candidates.

DEP.0002.0173W	**When modifying the deployment set, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**
Explanation	Modifying the deployment set will cause Deployer to remove any checkpoints previously created for the deployment candidates associated with this project.
Action	If you continue with the change, you must recreate any checkpoints you want to use for the project.

DEP.0002.0180E	**Repository {0} is not connected. The specified flat file directory does not exist.**
Explanation	The specified repository does not exist.
Action	Ensure that the repository exists in the specified location.

DEP.0002.0183W	**When modifying the deletion set, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**
Explanation	If you modify the deletion set, Deployer will remove any checkpoints previously created for the deployment candidates associated with this project.
Action	If you continue with the change, you must recreate any checkpoints you want to use for the project.

DEP.0002.0201E	**Checkpoint for Deployment Candidate {0} failed. For more information, see the checkpoint report.**
Explanation	Possible causes for this error: 1) The project file could not be found in, or loaded from, the build. 2) The target file or deployment candidate could not be loaded from disk. 3) The user is not authorized to create a checkpoint. 4) Another reason shown in the checkpoint report.
Action	Verify that the build is available and correct and that there is sufficient disk space and memory. Also review the checkpoint report and verify that the necessary operating system privileges are set and that the user has authorization to create a checkpoint.

DEP.0002.0202W **Checkpoint for deployment candidate {0} completed with warnings. For more information, see the checkpoint report.**

Explanation Deployer encountered a warning while extracting objects from source system.

Action Review the checkpoint report to determine any further action to take. Most warnings require no action by the user.

DEP.0002.0206E **Checkpoint for deployment candidate {0} failed: {1}**

Explanation Deployer encountered an exception while extracting objects from the source system. The following are possible causes for the exception:

1) Deployer could not find project file in, or load it from, the build.

2) Deployer could not load the target file or deployment candidate from disk.

3) The user is not authorized to create a checkpoint.

4) Other reasons as shown in the checkpoint report.

Action Verify that the build is available and correct, and that there is sufficient disk space and memory. Also review the checkpoint report to verify that the necessary operating system privileges are set and that the user has authorization to create a checkpoint.

DEP.0002.0300E **User is not authorized to create variable substitution file for project {0}.**

Explanation You are not authorized to perform the action of variable substitution for the specified project. You must have map authorization for the project.

Action Ask an administrator or user that has map authorization for the project to perform this task or have an administrator assign you map authorization.

DEP.0002.0301E **Could not save variable substitution file {0}.**

Explanation Deployer encountered an error writing to disk.

Action Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If saving again is not successful, perform one or both of the following and retry the action:

Restart the server.

Recreate the variable substitution information.

DEP.0002.0302E	**Variable substitution object type {0} is invalid.**
Explanation	Deployer attempted to create a variable substitution item that is not valid. This might occur if the service that is attempting to create the variable substitution item is invoked by something other than the Deployer user interface.
Action	Contact Software AG Global Support to report this issue and request a fix.

DEP.0002.0306E	**Deployer cannot import the substitute configuration values into the deployment map. The .vs file does not exist.**
Explanation	There are no .vs files in the WmDeployer/replicate/inbound folder.
Action	Copy the variable substitution file to the WmDeployer/replicate/inbound folder and then import it into the deployment map.

DEP.0002.0309E	**Unable to export variable substitution information.**
Explanation	This error occurs when the exported map already exists in the WmDeployer/replicate/inbound folder.
Action	Backup the file to a different location and delete the original. Then export the map again.

DEP.0002.0311E	**The Deployer {0} file is not accessible or does not exist.**
Explanation	The XML file name you passed for importing the varsub is not present in the WmDeployer/replicate/inbound folder.
Action	Check and correct the file name you passed in the command-line.

DEP.0004.0001E	**Version Mismatch Error: The server alias is a different version number than the other source/target servers. Source and target servers must use the same version as the server alias.**
Explanation	The versions of the source or target servers are different than the version selected for the alias version.
Action	Remove the aliases with the wrong version from the deployment set or change the verison to match the source servers.

DEP.0004.0002W	**The target Integration Server is part of a cluster, but is not properly configured to support clustered deployment. See the product documentation for instructions on proper cluster configuration.**
Explanation	One of the target Integration Servers is not properly configured for clustering.
Action	See the webMethods Integration Server documentation for a description of the proper configuration settings for clustering.

DEP.0005.0105I	**No publishable document types needed to be synchronized in the following package(s): "{0}"**
Explanation	The packages with document types are deployed. However, there are no unsynchronized document types.
Action	Make sure that no unsynchronized document types are used for process development.

DEP.0005.0111E	**The source user has no username. Deployer cannot deploy an undefined user.**
Explanation	This error occurs when Deployer cannot deploy or roll back a target server due to an undefined user.
Action	Verify that the user exists on the source server and that configuration details are correct.

DEP.0005.0113E	**The source user "{0}" has a non-ASCII password. Deployer cannot deploy assets to an undefined user.**
Explanation	Deployer is attempting to deploy an invalid user.
Action	Verify that the selected user is valid.

DEP.0005.0115E	**An error occurred while attempting to deploy user "{0}" with the following error message follows: "{1}" **
Explanation	An error occurred while attempting to deploy a user.
Action	Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0118E	**Deployer encountered the following exception while attempting to put package "{0}" into the inbound directory: "{1}"**
Explanation	There might be network connectivity problems between Deployer and each target Integration Server. Alternatively, the target Integration Servers might not be currently running.
Action	Verify network connectivity between the Deployer server and each target server. Also, verify that the target Integration Servers are running.

DEP.0005.0131E	**Deployment completed with errors. Following is a path to the output report, followed by an error message: "{0}" Error message: "{1}" **
Explanation	Deployment completed with errors.
Action	Check the Integration Server logs, as well as error messages in the output report.

DEP.0005.0134E	**Deployer encountered an error while synchronizing documents in the following packages: "{0}"**
Explanation	This error occurs when a Broker or UM mapped with an Integration Server is unavailable.
Action	Ensure that the mapped JMS Broker or UM is available.

DEP.0005.0156E	**Deployer encountered an error during deployment. Deployer did not find package "{0}" in the build zip file "{1}".**
Explanation	Deployer invoked the wm.server.util:putPackageFile service and the service returned an error.
Action	See the deployment or simulation report to determine which error putPackageField service returned.

DEP.0005.0157E	**Deployer encountered an error during deployment. "{0}" package was not found in the build zip file: "{1}".**
Explanation	The specified package was not found in the build. Typically, this indicates that the deployment set is not current with the build.
Action	Re-create your deployment set and build files.

DEP.0005.0160E	**While attempting to install package "{0}" an exception with the following error message occurred: "{1}" **
Explanation	Deployer invoked the pub.packages:installPackage service, and the service returned an error.
Action	Verify network connectivity between the Deployer server and each target server. Verify that the target Integration Servers are running. For more information about the error returned by the installPackage service, see the deployment or simulation report. For more information about the installPackage service, see Integration Server Built-In Services Reference.

DEP.0005.0161E	**The number of bytes read from package "{0}" was not correct.**
Explanation	An I/O exception occurred while reading the specified package. As a result, all data from the package could not be read. This exception can occur for the following reasons: - The I/O operation failed or was interrupted while accessing the build file. - A security violation has occurred, which typically means that the user running Deployer does not have correct privileges to access the files.
Action	Verify that the file system and the build file that contains the source package are not corrupt. Verify that the user attempting this action has the proper authority to read files on the file system. You might need to re-create the build.

DEP.0005.0164E	**The scheduled service type "{0}" for service name "{1}" is unknown and could not be processed.**
Explanation	Your version of Deployer is out of date.
Action	Ensure that you have the latest version of the WmDeployer package.

DEP.0005.0170E	**Deployer encountered the following error while retrieving the scheduled service with service name "{0}" from target "{1}": "{2}".**
Explanation	This error occurs when Deployer fails to get details for a scheduled service for the variable substitution.
Action	Verify that the scheduled service exists under the specified name on the target server.

DEP.0005.0187E	**Deployer encountered the following exception while performing a remote invoke of the service "{0}": "{1}"**
Explanation	This error occurs when Deployer cannot invoke a service on a remote server, which indicates that the remote server might be offline.
Action	Verify that the remote server is running and available.

DEP.0005.0190E	**Deployer encountered the following error while attempting to deploy Group: "{0}": "{1}"**
Explanation	An error occurred while attempting to deploy the group.
Action	Recreate the build and deploy the group again.

DEP.0005.0193E	**Deployer encountered the following error while attempting to deploy ACL "{0}": "{1}"**
Explanation	An error occurred while attempting to deploy an ACL.
Action	Check Integration Server logs and error messages in the Deployment report.

DEP.0005.0197E	**Deployer encountered the following error while attempting to deploy Port "{0}" associated with package "{1}": "{2}".**
Explanation	An error occurred while attempting to deploy a port associated with a package.
Action	Check for error messages in the output report and Integration Server logs. Verify that the specificied port is available on the target server. Recreate the build if problems persist.

DEP.0005.0199E	**Deployment failed.**
Explanation	The deployment failed.
Action	Review the deployment report and Integration Server logs to determine the cause of the failure, and take the appropriate action.

DEP.0005.0204E	**Deployer encountered the following Trading Networks error while attempting to import "{0}" with name "{1}": "{2}", message: "{3}"**
Explanation	An error occurred attempting to import one of the following Trading Network object types: Document Attributes, Document Types, Field Groups, ID Types, Contact Types, Binary Types, or Profile Groups. Possible causes include: - A network connection error occurred between the Deployer server and the target Integration Server. - The target Integration Server is not running. - The target WmTN package on the target Integration Server is not loaded or enabled. - There could be problems with the Trading Networks object type being imported to the target.
Action	Verify the following: - There are no network connectivity errors between the Deployer server and each target Integration Server. - All target Integration Servers are running. - The WmTN package on each target Integration Server is loaded and enabled. - The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible Trading Networks object types.

DEP.0005.0231	**There are no required patches specified for the target Integration Server.**
Explanation	This message occurs when a user deploys unrequired patches into a target.
Action	See the patch details for more information.

DEP.0005.0234E	**Deployer encountered the following error while pausing the listener "{0}" associated with package "{1}": "{2}"**
Explanation	Could not pause the listener associated with the package.
Action	Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0235E	**Deployer encountered an error while disabling of port "{0}" associated with package "{1}".**
Explanation	An exception occurred while disabling the port associated with the package.
Action	Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0236E	**Deployer encountered an error while enabling the listener "{0}" associated with package "{1}": "{2}"**
Explanation	Deployer could not enable the specified listener.
Action	See the webMethods Integration Server documentation for specific instructions on how to enable a listener.

DEP.0005.0240E	**Deployer encountered the following error while suspending the triggers: "{0}"**
Explanation	Deployer could not suspend the triggers on the target Integration Server. Deployer attempts to suspend all triggers by setting the maximum percentage of document retrieval threads and the maximum percentage of trigger execution threads to zero.
Action	Verify network connectivity between Deployer and each target Integration Server. Also, verify that the target Integration Servers are running. For more information about the configuration settings for document retrieval threads and trigger execution threads, see information about configuring the server in the webMethods Integration Server documentation.

DEP.0005.0242E	**Could not resume the Integration Server triggers. Error message follows: "{0}"**
Explanation	Deployer could not resume the triggers on the target Integration Server. Deployer attempts to resume all triggers by resetting the maximum percentage of document retrieval threads and the maximum percentage of trigger execution threads to the values they had before Deployer suspended the triggers.
Action	Verify network connectivity between the Deployer server and each target Integration Server. Verify that the target Integration Servers are running. For more information about configuration settings for document retrieval threads and trigger execution threads, see information about configuring the server in the webMethods Integration Server documentation.

DEP.0005.0243E	**Deployer did not deploy deployment set "{0}" because it contains the following unsatisfied dependencies: "{1}"**
Explanation	The dependencies required by the specified deployment set are missing on the target system.
Action	Either install the necessary components on the target system, or change the Deployer project so that it no longer requires the missing dependencies.

DEP.0005.0244E	**Deployer encountered the following exception while checking dependencies on target "{0}" for deployment set "{1}": "{2}"**
Explanation	An exception occurred while checking dependencies for the deployment set at the target.
Action	Check Integration Server logs and error messages in the output report for exception details.

DEP.0005.0250E	**Simulation failed.**
Explanation	The deployment simulation failed.
Action	Refer to the simulation report and Integration Server logs to determine the cause of the failure and take the appropriate action.

DEP.0005.0256E	**There are no targets mapped for the current deployment set.**
Explanation	There are no valid target servers mapped for the deployment set.
Action	Verify that the specified target servers are mapped appropriately for the current deployment set.

DEP.0005.0257E	**Deployer cannot deploy the deployment set because there are no source servers specified.**
Explanation	There are no source servers mapped for the deployment set to define assets for deployment.
Action	Verify that source servers are defined appropriately for assets to be deployed.

DEP.0005.0263E	**The following Trading Networks error occurred while attempting to import processing rules: class: "{0}", message: "{1}"**
Explanation	An error occurred when attempting to import processing rules into Trading Networks. Possible causes include: - A network connection error between the Deployer server and the target Integration Server running Trading Networks. - The target Integration Server is not running. - The WmTN package is not loaded or enabled on the target Integration Server. - The Trading Networks object type being imported to the target might be in error.
Action	Verify the following: - There are no network connectivity errors between the Deployer server and each target Integration Server. - All target Integration Servers are running. - The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible processing rules.

DEP.0005.0265E **Deployer encountered the following Trading Networks error while attempting to import "{0}" with a group code "{1}" and name "{2}": class: "{3}", message: "{4}"**

Explanation An error occurred when attempting to import field groups into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible field groups.

DEP.0005.0266E **Deployer encountered the following Trading Networks error while attempting to import field definitions: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import field definitions into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible field definitions.

DEP.0005.0270E **Deployer encountered the following Trading Networks error while attempting to import partner profiles: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import partner profiles into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Netwoks object type is allowed. See the webMethods Trading Networks documentation for details about permissible partner profiles.

DEP.0005.0274E **Deployer encountered the following Trading Networks error while attempting to import trading partner agreements: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import trading partner agreements (TPAs) into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded and/or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The TN object type is allowed. See the webMethods Trading Networks documentation for details about permissible trading partner agreements (TPAs).

DEP.0005.0277E **Deployer encountered an error while attempting to import "{0}" with a type code "{1}" and a name "{2}". The following is the error information from Trading Networks: class: "{3}", message: "{4}"**

Explanation An error occurred when attempting to import external ID types, contact types, or binary types into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible external ID types, contact types, and binary types.

DEP.0005.0280E **Triggers were not suspended prior to package deployment. Failure to suspend a trigger during deployment could cause problems on the target server.**

Explanation Triggers were not suspended prior to package deployment.

Action Not suspending a trigger during deployment can cause problems on the target. Check the Integration Server logs for more information.

DEP.0005.0282E **Scheduled services were not suspended prior to deployment. Failure to suspend scheduled services during deployment could cause problems on the target server.**

Explanation Scheduled services were not suspended prior to deployment. Failure to suspend scheduled services during deployment can cause problems at the target.

Action Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0284E	**Scheduled services were not started after deployment.**
Explanation	Scheduled services were not started after deployment. There might be an issue with a target server.
Action	For more information, check the Integration Server logs and error messages in the output report.

DEP.0005.0286E	**Listeners were not suspended prior to deployment. Failure to suspend listeners during deployment could cause problems on the target server.**
Explanation	Listeners were not suspended prior to deployment. Failure to suspend listeners during deployment could cause problems on the target server.
Action	Check the Integration Server logs for errors in suspending the listeners.

DEP.0005.0288E	**Listeners were not started after deployment.**
Explanation	Listeners were not started after deployment. It happens when the ports are disabled or if they will be used for the first time.
Action	Check the Integration Server logs and error messages in the output report.

DEP.0005.0296E	**Deployer did not deploy the {0}, which is required for source package "{1}" and it does not already exist at the target. Although the source package would be deployed to the target, some services in that package will not run correctly until that ACL is created at the target.**
Explanation	The Read, Write, List, or Execute ACLs required for the deployed package to run correctly are not being deployed to the target Integration Server, and that ACL does not already exist on the target Integration Server. Typically, this indicates that the ACLs associated with the package were not extracted.
Action	Repeat the extraction step using Deployer to ensure that all ACLs are included.

DEP.0005.0297E	**Deployer did not deploy the {0}, which is required for source package "{1}" and it does not already exist on the target. Some services in that source package will not run correctly until that ACL is created at the target.**
Explanation	The Read, Write, List, or Execute ACLs that are necessary for the deployed package to run correctly are not being deployed to the target Integration Server, and the specified ACL does not already exist on the target Integration Server. Typically, this problem indicates that the ACLs associated with the package were not extracted.
Action	Perform the extraction step again using Deployer to ensure that all ACLs are included.

DEP.0005.0298E	**Deployer encountered the following exception while invoking of the service "{0}": "{1}"**
Explanation	This exception occurs when Deployer invokes a service on a remote server.
Action	Verify that the source or target server is available.

DEP.0005.0302E	**Deployer encountered the following exception while creating the directory "{0}": "{1}".**
Explanation	An exception occurred while attempting to create a directory.
Action	Ensure that the appropriate write permissions exist to allow for the creation of the new directory and that adequate free space is available.

DEP.0005.0303E	**Deployer encountered an exception while creating one of the temporary jar files in "{0}": "{1}"**
Explanation	An exception occurred while attempting to create one of the temporary jar files.
Action	Ensure that the appropriate write permissions exist for the new file location and that adequate free space is available.

DEP.0005.0304E	**Target Server {0} is unavailable.**
Explanation	Deployer could not connect to the specified target server.
Action	Verify the following: - Network connectivity between Deployer and each target Integration Server. - The target Integration Servers are running. - The target Integration Server alias is defined on the Deployer host server.

DEP.0005.0305E	**An exception occurred while getting a Trading Networks docType object. This is most likely caused by a user-defined extension to the Trading Networks type BizDocType. Copy the jar files containing the extensions from the webM_install_dir/IntegrationServer/packages/WmTN/code/jars directory into the WmDeployer/code/jars directory.**
Explanation	There is a user-defined extension to a Trading Networks document type and Deployer does not have access to the associated jar files.
Action	To ensure Deployer has access to the associated jar files, copy the jar files containing the extensions from the webM_install_dir/IntegrationServer/packages/WmTN/code/jars directory into the WmDeployer/code/jars directory.

DEP.0005.0306E **An error occurred while attempting to import extended field definitions; error information from Trading Networks: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import extended field definitions into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server that is running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded and/or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible extended field definitions.

DEP.0005.0307E **Deployer encountered the following Trading Networks error while attempting to import security data for profile: "{0}": class: "{1}", message: "{2}"**

Explanation Deployer encountered an error occurred while attempting to import the security data for the specified profile into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible Trading Networks Security Data.

DEP.0005.0308E **An error occurred while attempting to import queues: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import the public queues into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded and/or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible public queues.

DEP.0005.0309E **An error occurred while attempting to import profile group "{0}" with value "{1}". class: "{2}", message: "{3}"**

Explanation An error occurred when attempting to import the profile groups into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.

- The target Integration Server is not running.

- The WmTN package is not loaded and/or enabled on the target Integration Server.

- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.

- All target Integration Servers are running.

- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible profile groups.

DEP.0005.0326E	**An error occurred while deploying package "{0}". Item "{1}" could not be loaded because of reason "{2}". The package may have partially loaded; please check your target server.**
Explanation	The specified package did not load due to the reason returned from the target Integration Server.
Action	See the webMethods Integration Server documentation for the specific requirements for loading a package.

DEP.0005.0328E	**The JVM "{0}" on the target server is older than the "{1}" JVM recommended on the source for package "{2}".**
Explanation	The JVM version running on the target is older than the minimum JVM version property specified by the source.
Action	Change the minimum JVM property for the package being deployed and redeploy the package.

DEP.0005.0329E	**The "{0}" target JVM is older than the JVM recommended "{1}" on the source for package "{2}".**
Explanation	The JVM version running on the target is older that the minimum JVM version property required by the source.
Action	Change the minimum JVM property for the package being deployed, and then deploy again.

DEP.0005.0330E	**The target package version is null.**
Explanation	For partial deployment, Deployer requires that the package is present on the target server and that version of the package is not null and matches that of the source server.
Action	Verify that the package version defined on the target server is appropriate for partial package deployment.

DEP.0005.0334E	**Source package is of type Patch and package does not exist on target. The package: "{0}" will not be deployed. Re-define package to Full to deploy the package on target**
Explanation	This message indicates that the target partial mode package is undefined.
Action	Verify that the specified package exists on the target server and that it is valid for partial package deployment.

DEP.0005.0337E	**An error occurred while deploying package: "{0}"**
Explanation	Deployer invoked the pub.packages:installPackage service and the installPackage service returned an error.
Action	For more information about the error that the installPackage service returned, see the deployment or simulation report. For more information about the installPackage service and the requirements for installing packages, see the Integration Server Built-In Services Reference.

DEP.0005.0338E	**Deployer issued the following exception while attempting to activate the package: "{0}"**
Explanation	Deployer invoked the pub.packages:activatePackage service, and the activatePackage service returned an error.
Action	Verify the network connectivity between the Deployer server and each target Integration Server. Also, verify that the target Integration Servers are up and running. For more information about the error that the activatePackage service returned, see the deploy or simulation report. For more information about the activatePackage service, see the documentation for webMethods Integration Server documentation.

DEP.0005.0352E	**The package name "{0}" contains the invalid "{1}" character. For more information about illegal characters, see the webMethods Integration Server documentation.**
Explanation	The package name contains illegal characters.
Action	See the webMethods Integration Server documentation for information about how to name a package.

DEP.0005.0353E	**"{0}" is an invalid value for the Cleanup File Age parameter. Valid values are 1-9999.**
Explanation	The value specified for the Cleanup File Age parameter is invalid.
Action	Specify a valid value between 1 and 9999 for the Cleanup File Age parameter.

DEP.0005.0354E	**Invalid File Age parameter "{0}". Valid values are 0-9999.**
Explanation	The value specified for the File Age parameter is invalid.
Action	Specify a value between 0 and 9999 for the File Age parameter.

DEP.0005.0355E	**The Allow Recursive Polling parameter "{0}" is invalid. Valid values are "yes" and "no".**
Explanation	The specified Allow Recursive Polling parameter is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Allow Recursive Polling parameter.

DEP.0005.0356E	**The Run As User value "{0}" contains invalid character "{1}". For more information about illegal characters, see the webMethods Integration Server documentation.**
Explanation	The Run As User value contains illegal characters.
Action	For more information about illegal characters, see the webMethods Integration Server documentation.

DEP.0005.0357E	**No value was provided for the required Run services as user parameter.**
Explanation	The Run services as user parameter value is not specified.
Action	Specify a value for the Run services as user parameter. For more information, see the webMethods Integration Server documentation.

DEP.0005.0358E	**"{0}" is an invalid value for the File Polling Interval parameter. Valid values are 1-9999.**
Explanation	The value specified for the File Polling Interval parameter is invalid.
Action	Specify a valid value between 1 and 9999 for the File Polling Interval parameter.

DEP.0005.0359E	**No value is specified for the File Polling Interval parameter. Valid values are 1-9999.**
Explanation	No value is specified for the File Polling Interval parameter.
Action	Specify a value between 1 through 9999 for the File Polling Interval parameter.

DEP.0005.0360E	**"{0}" is an invalid value for the Cleanup Interval parameter. Valid values are 1-9999.**
Explanation	The value specified for the Cleanup Interval parameter is invalid.
Action	Specify a value between 1 and 9999 for the Cleanup Interval parameter.

DEP.0005.0361E	**"{0}" is an invalid value for the Maximum Number of Invocation Threads parameter. Valid values are 1-10.**
Explanation	The value specified for the Maximum Number of Invocation Threads parameter is invalid.
Action	Specify a value between 1 and 10 for the Maximum Number of Invocation Threads parameter.

DEP.0005.0362E	**No value provided for the required Maximum Number of Invocation Threads parameter.**
Explanation	No value was specified for the Maximum Number of Invocation Threads parameter.
Action	Specify a value between 1 and 10 for the Maximum Number of Invocation Threads parameter.

DEP.0005.0363E	**"{0}" is an invalid value for the Port parameter. The Port parameter requires an integer value.**
Explanation	The value specified for the Port parameter is not an integer.
Action	Specify a valid value for the Port parameter.

DEP.0005.0364E	**"{0}" is an invalid value for the Port parameter. The value for the Port parameter must be greater than -1.**
Explanation	The value for the Port parameter is not valid.
Action	Specify a valid value for the Port parameter.

DEP.0005.0365E	**No value was specified for the required Port parameter. Specify a value for the Port parameter.**
Explanation	No value was specified for the Port parameter.
Action	Specify a valid integer type value that is greater than -1 for the Port parameter.

DEP.0005.0366E	**The Client Authentication value: "{0}" is invalid. Valid values are 'true' and 'false'.**
Explanation	The specified Client Authentication value is neither "true" nor "false".
Action	Specify either "true" or "false" for the Client Authentication value.

DEP.0005.0367E	**The Host parameter requires a value.**
Explanation	The value for the Host parameter was not specified.
Action	Specify a value for the Host parameter.

DEP.0005.0368E	**"{0}" is an invalid value for the Type parameter. Valid values are "pop3" and "imap".**
Explanation	The value specified for the Type parameter is invalid.
Action	Specify either "pop3" or "imap" for the Type parameter.

DEP.0005.0369E	**Specify a value for the Type parameter. Valid values are "pop3" and "imap".**
Explanation	No value is specified for the required Port parameter.
Action	Specify either "pop3" or "imap" for the Port parameter.

DEP.0005.0370E	**The user name value: "{0}" contains an invalid character: "{1}". Refer to the Administering Integration Server guide for listed illegal characters.**
Explanation	The user name value contains illegal characters.
Action	For information about legal characters for user accounts, see the Administering Integration Server guide.

DEP.0005.0371E	**No value provided for user name. This field is mandatory.**
Explanation	No value is provided for user name.
Action	Specify a value for the user name. For information about the legal characters for user accounts, see the Administering Integration Server guide.

DEP.0005.0372E	**Invalid value provided for the "Log out after each mail check" parameter: "{0}". Valid values are "yes" and "no".**
Explanation	The specified value for the "Log out after each mail check" parameter is neither "yes" nor "no".
Action	Specify a valid value for the "Log out after each mail check" parameter. Valid values are "yes" and "no".

DEP.0005.0373E	**The Authorize value "{0}" is invalid. Valid values are Yes and No.**
Explanation	The specified Authorize value is neither Yes and No.
Action	Specify either Yes or No for the Authorize value.

DEP.0005.0374E	**"{0}" is an invalid value for the Time Interval parameter. Valid values are 1-9999.**
Explanation	The value specified for the Time Interval parameter is invalid.
Action	Specify a valid value between 1 and 9999 for the Time Interval parameter.

DEP.0005.0375E	**Specify a value for the required Time Interval parameter. Valid values are 1-9999.**
Explanation	The required Time Interval parameter has not been specified.
Action	Specify a value from 1 through 9999 for the Time Interval parameter.

DEP.0005.0376E	**The Reply value: "{0}" is invalid. Valid values are "yes" and "no".**
Explanation	The specified Reply value is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Reply value.

DEP.0005.0377E	**The Send reply e-mail on error value "{0}" is invalid. Valid values are Yes and No.**
Explanation	The Send reply e-mail on error value is set to a value other than Yes or No.
Action	Specify either Yes or No for the Send reply e-mail on error value.

DEP.0005.0378E	**The Remove value: "{0}" is invalid. Valid values are "yes" and "no".**
Explanation	The specified Remove value is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Remove value.

DEP.0005.0379E	**"{0}" is an invalid value for the Delete invalid messages parameter. Valid values are Yes and No.**
Explanation	The value specified for the Delete invalid messages parameter is invalid.
Action	Specify a valid value of Yes or No for the Delete invalid messages parameter.

DEP.0005.0380E	**The Multithread processing value "{0}" is invalid. Valid values are Yes and No.**
Explanation	The Multithread processing is set to a value other than Yes or No.
Action	Specify either Yes or No for the Multithread processing value.

DEP.0005.0381E	**"{0}" is an invalid value for the Number of threads if multithreading is turned on parameter. Valid values are 1-99.**
Explanation	The value specified for the Number of threads if multithreading is turned on field is invalid.
Action	Specify a value between 1 and 99 for the Number of threads if multithreading is turned on field.

DEP.0005.0382E	**Enter a value for the Number of threads if multithreading is turned on parameter. Valid values are 1-99.**
Explanation	There is no value set for the Number of threads if multithreading is turned on parameter.
Action	Specify a value between 1 and 99 for the Number of threads if multithreading is turned on parameter.

DEP.0005.0383E	**The Break Mmsg value: "{0}" is invalid. Valid values are "yes" and "no".**
Explanation	The specified Break Mmsg value is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Break Mmsg value.

DEP.0005.0384E	**The Include Headers value: "{0}" is invalid. Valid values are "yes" and "no".**
Explanation	The specified Include Headers value is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Include Headers value.

DEP.0005.0421E	**Unknown system type: "{0}".**
Explanation	The source system type is unknown, which indicates that your version of Deployer is out of date.
Action	Ensure that you have the latest version of the WmDeployer package.

DEP.0005.0422E	**Unable to invoke "{1}" because the connection object is of an unknown type. Its value is: "{0}".**
Explanation	The system type object is set to a value that is not recognized. This issue might occur if the user manually edits the project XML file.
Action	Rebuild the project file and map the steps again. Do not manually edit the project file.

DEP.0005.0423E	**Deployer encountered an exception while writing the bytes for package "{0}" to the output stream in preparation for deployment to the target "{1}".**
Explanation	An exception occurred when Deployer tried to write the package data to disk. That exception can occur for the following reasons: - The I/O operation failed or was interrupted while accessing the build file. - A security violation occurred, which typically means that the user running Deployer lacks the correct privileges to access the files.
Action	Verify that the file system is not corrupt and that adequate disk space is available for writing new files. Also verify that the user has appropriate privileges to write files on the file system.

DEP.0005.0430	**There is no logical server defined for the specified Server ID.**
Explanation	Either no logical server is defined in the WmDesigner service on the target Integration Server server, or the server is not up and running and available for process model deployment.
Action	Verify that the logical server is defined in the WmDesigner service on the target Integration Server server and that the server is available.

DEP.0005.0431	**The most-likely fix for that is to use webMethods Administrator on your target server to define a logical server with the name: "{0}".**
Explanation	This problem occurs when the logical server is not defined in the WmDesigner service on the target Integration Server server for process model deployment.
Action	Verify that the logical server is defined in the WmDesigner service on the target Integration Server server.

DEP.0005.0433E	**Cannot associate {0} ACL "{1}", with "{2}" because user "{3}" is not in the Write ACL: "{4}" .**
Explanation	Cannot associate the ACL because the user is not a member of the Write ACL.
Action	Add the user to the Write ACL.

DEP.0005.0435E	**Deployer cannot suspend selected triggers. You can suspend selected triggers only with Integration Server 6.0.1 Fix 144, Integration Server 6.1 Fix 22, or Integration Server 6.5 and later. Alternatively, you can suspend all triggers in the project properties.**
Explanation	Selected trigger suspension is supported only in the following releases: - Integration Server 6.0.1 Fix 144 - Integration Server 6.1 Fix 22. - Integration Server 6.5 and later
Action	You can suspend all triggers in the project properties.

DEP.0005.0447I	**The "{0}" file was deployed.**
Explanation	This message occurs when a user deploys files.
Action	Check whether the files are deployed or not.

DEP.0005.0449E	**Deployer could not suspend the adapter notifications. Adapter suspension is supported only with Integration Server 6.5 and later.**
Explanation	Adapter notifications could not be suspended because this functionality is only supported for Integration Server 6.5 and later.
Action	None.

DEP.0005.0457E	**Suspend adapter notifications prior to deploying packages. Failure to suspend adapter notifications during deployment can cause problems on the target.**
Explanation	Adapter notifications were not suspended prior to package deployment.
Action	Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0458E	**Deployer suspended adapter notification "{0}" but could not verify status.**
Explanation	Deployer suspended the adapter notification but was unable to verify its status after the suspension.
Action	For more information, check the Integration Server logs and error messages in the output report.

DEP.0005.0459E	**Deployer resumed adapter notification "{0}" but could not verify status.**
Explanation	Deployer resumed adapter notification but could not verify the status.
Action	Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0460E	**Suspend trigger "{0}" failed: {1}**
Explanation	Deployer could not suspend the trigger.
Action	Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0461E	**Suspend adapter notification "{0}" failed: {1}**
Explanation	Suspension of adapter notification failed.
Action	Recreate the build and deploy again. If the problem persists, check the target server adapter settings.

DEP.0005.0477E	**The source group has no name. Deployer cannot deploy an undefined group.**
Explanation	This message occurs when Deployer attempts to roll back an undefined group.
Action	Verify that the specified group is defined on the source server.

DEP.0005.0482E	**The source ACL has no name. Deployer cannot deploy an undefined ACL.**
Explanation	Deployer attempted to roll back an undefined ACL.
Action	Verify that the specified ACL exists on the source server.

DEP.0005.0492	**The Extended Setting in the source has no name. Deployer cannot deploy an undefined Extended Setting.**
Explanation	This message occurs when Deployer attempts to roll back of an undefined Extended Setting.
Action	Verify that the specified Extended Setting exists on the target server.
DEP.0005.0496E	**The Trading Networks instance is not currently available on the target server "{0}". Please check your network connection and verify that the Trading Networks instance is installed, configured, and running.**
Explanation	The target Trading Networks server is not accessible due to a network connection problem.
Action	Check your network connection. Verify that the Trading Networks instance is installed, configured, and running.
DEP.0005.0501E	**Deployer issued the following exception after it failed to load the variable substitution object {0}.**
Explanation	The map file: <serverDirectory>\packages\WmDeployer\resources\projects\<projectName>\tags\<mapName>\<deploymentSetName>_<targetServerName>.xml is either corrupt or not present.
Action	Verify that the map file exists. If it does, you might need to use Deployer to recreate your map and variable substitution actions.
DEP.0005.0505E	**ERROR: Failed to generate IData for Port. The following exception was thrown: {0}**
Explanation	The port type is unknown. This indicates that your version of Deployer is out of date.
Action	See the error log of the Deployer server.
DEP.0005.0506	**Variable {2}, in {0} "{1}" will be changed from "{3}" to "{4}" on the target system.**
Explanation	This message is displayed in the deployment report when the variable is substituted during deployment.
Action	Verify that the displayed variables are substituted.
DEP.0005.0600E	**The target server is Integration Server {0}, which does not support this feature. Deployer cannot update the following adapter connections with the variable substitution values: {1}**
Explanation	The version of the target Integration Server is a version prior to version 6.1. Versions of the Integration Server prior to 6.1 do not support the APIs that are required to update the adapter connections.
Action	Either upgrade the target Integration Server to version 6.1 or later, or manually update the Adapter connections on the target system.

DEP.0005.0615E	**Deployer encountered an error while retrieving current values for adapter connection "{0}".**
Explanation	Deployer invoked the wm.art.admin.connection:getResourceConfiguration service but was unable to get current values for the adapter connection in the varsub page.
Action	The wm.art.admin.connection:getResourceConfiguration service might not be operational or the WmART package is not installed on the target machine. Verify that both the service and the package are installed and operational.

DEP.0005.0706	**Rollback failed. For more information, see the rollback report and the Integration Server log.**
Explanation	This message occurs when a rollback operation fails.
Action	Review the rollback report and take appropriate action.

DEP.0005.0850E	**Deployer issued the following error while rolling back the contact type: "{0}"**
Explanation	Deployer issued an exception while rolling back the contact type.
Action	Contact the Trading Networks target administrator.

DEP.0005.0851E	**Deployer issued the following exception while deleting the document type during rollback: "{0}"**
Explanation	An exception occurred while deleting the document type.
Action	Contact the administrator of the target Trading Networks system for assistance.

DEP.0005.0852E	**Deployer issued the following exception while deleting the field group during rollback: "{0}"**
Explanation	An exception occurred while deleting the field group.
Action	Contact the administrator of the target server for assistance.

DEP.0005.0854E	**Deployer issued the following exception while deleting the external ID type during rollback: "{0}".**
Explanation	An exception occurred while deleting the external ID type during rollback.
Action	Verify that target server is running, then try the deleting the external ID type again.

DEP.0005.0856E	**Deployer issued the following exception while deleting the processing rule during rollback: "{0}"**
Explanation	An exception occurred while deleting the processing rule.
Action	Contact the administrator of the target server for assistance.

DEP.0005.0858E	**Deployer issued the following exception while deleting the profile during rollback: "{0}"**
Explanation	An exception occurred while deleting the profile.
Action	Verify that the target server is running. Then try the deletion again.

DEP.0005.0859E	**Deployer could not suspend the "{0}" scheduled service type with service name "{1}" because it was deployed to a clustered Integration Server.**
Explanation	The service was deployed to a clustered Integration Server and could not be suspended.
Action	Suspend the service manually at each target.

DEP.0005.0860E	**Deployer could not resume the scheduled service type "{0}" with service name "{1}". The service was deployed to a clustered Integration Server and could not be resumed. You must resume the service manually at each target.**
Explanation	The service was deployed to a clustered Integration Server and could not be resumed.
Action	Resume the service manually at each target.

DEP.0005.0861E	**Scheduled services are being deployed to a clustered Integration Server and cannot be started after deployment.**
Explanation	Scheduled services cannot be started on the clustered target.
Action	Start the services manually on each clustered target.

DEP.0005.0862E	**Scheduled services have been deployed to a clustered Integration Server and were not suspended after deployment. If suspension is required, then do so manually at each target.**
Explanation	Scheduled services could not be suspended at the clustered target after deployment
Action	Suspend the services manually at each target.

DEP.0005.0864E	**Deployer requires that scheduled services be updated at a clustered Integration Server, but this is not supported with this release. You can update the scheduled services by deploying them to each of the individual Integration Servers in the cluster.**
Explanation	This deployment candidate requires that scheduled services be updated at a clustered Integration Server, which is not supported with this release.
Action	Update the services by deploying to each of the individual Integration Servers in the cluster.

DEP.0005.0869E	**The deployment failed and Deployer is performing an automatic rollback. Please see the separate rollback report for more information about the failed deployment.**
Explanation	This message occurs when a deployment fails and an automatic rollback occurs.
Action	Please see the Rollback report and take appropriate action.

DEP.0005.1003E	**An IO exception occurred while attempting to access: "{0}". Exception details follow: "{1}".**
Explanation	An exception occurred when Deployer tried to create, write data to, or save a file. This exception can occur for the following reasons: - The I/O operation failed or was interrupted while accessing the build file. - A security violation has occurred, which typically means that the user running Deployer lacks appropriate privileges to access the files.
Action	Verify that the file system is not corrupt and that adequate disk space is available for creating, writing, and/or saving new files. Also verify that the user has proper privileges to create, write, and save files on the file system.

DEP.0005.1004E	**An exception occurred while attempting to access "{0}". Exception details follow: "{1}".**
Explanation	An exception occurred when Deployer tried to access (that is, create, save, read, or load) the indicated <object>, where <object> is one of thte following: checkpoint, deployment, build, deployReport, targetFileName, or targetServer. Possible causes of the exception include the following: - The deployment, reportFiles, or targetFile Object could not be loaded from the file system. - An I/O operation failed or was interrupted while accessing the build or checkpoint file. - A security violation has occurred, which typically means that the user running Deployer does not have privileges to access files necessary to perform the deploy operation. - A target Integration Server Adapter and/or Trigger could not be suspended/resumed.

- A variable substitution failed.

- Deployer could not obtain a connection to a target server.

Action Verify the following:

- The file system is not corrupt.

- Adequate disk space is available for creating and/or saving new files.

- The user attempting this action has the proper authority to create and save files on the file system.

- The target server is running, and is reachable on the network.

DEP.0005.1005E **You are not authorized to deploy the "{0}" project.**

Explanation The user does not have the authorization to deploy the specified project.

Action Ask an administrator or user that has deploy authorization to perform the action for you. Alternatively, have an administrator update your authorization to assign you deploy authorization for the project.

DEP.0005.1006E **You are not authorized to deploy the "{0}" project for the following reason: "{1}".**

Explanation An error occurred when invoking the service on the host Integration Server. Integration Server cannot determine whether the user is authorized to deploy the specified project.

Action Verify that the host Integration Server is still running. If you are running Deployer from a remote location, verify the network connectivity between the Deployer user interface and the server.

DEP.0005.1007E **The following exception occurred while attempting to process "{0}": "{1}"**

Explanation In the message, <subMessage> is one of the following sub-messages that Deployer displays to provide additional information about the exception: -<targetFileName> - An exception occurred while performing a [remote] invoke of the service: <ISServiceName>. Exception details follow: <exceptionInfo> - An exception occurred while attempting to XMLDecode the file: <buildFileName>. Exception details follow: <exceptionInfo>. - <errorMessageReturnedFromIS> - An exception occurred getting a Trading Networks, TN, docType object. That is most likely caused by a user-defined extension to the TN type BizDocType. Copy the jar files, which should be found in the <webM install dir>\\IntegrationServer\\packages\\WmTN\\code\\jars directory, containing those extensions into the WmDeployer/code/jars directory. - Source package is of type upgrade and required target package version is null. - Error: no Logical Server for Server ID" The most-likely fix for that is to use webMethods Administrator on your target server to define a logical server with the name: <sourceSystemName>. - An Exception occurred while attempting to IDataBinCoder the file: '<buildFileName>'. Exception details follow: <exceptionInfo> - Overwrite 'everything else' field is set to <overwriteEverythingElseString>, which is invalid. - The Port: <sourcePortName>, associated with Package: <packageName> - Disabling

of the Port: <sourcePortName>, associated with Package: <packageName> - Enabling of the Port: <sourcePortName>, associated with Package: <packageName> - Resuming the scheduled-service: " + scheduledServiceName - Suspending the scheduled-service: " + scheduledServiceName - <serviceName> - A SOAP fault occurred while performing a remote invoke of the service: <ISServiceName>.The SOAP Fault string follows: <faultString> - Getting information about the Port: <sourcePortName>, associated with Package: <packageName> The reason for the exception can be one of the following:

- There is a problem with connectivity to the target Integration Server.

- The target Integration Server is not running.

- The target Integration Server requires a Broker Server, but no Broker Server is connected to it.

- There is a user-defined extension to a Trading Networks document type, and Deployer does not have access to the associated jar files.

- You specified a partial package for deployment; however, the package does not exist on the target.

- You specified a logical server that is not defined on the target.

- The overwrite flag is invalid, which can only occur if the build file was manually edited.

Action

Based on the reason for the exception, perform one of the following:

- Verify the network connectivity between the Deployer server and each target server.

- Verify that each target server is running.

- If the target Integration Server requires that a Broker be connected to it, ensure that a Broker is connected.

- If a user-defined Trading Networks document type is in use, ensure Deployer has access to the associated jar files. To do so copy the jar files located in the <serverDirectory>\packages\WmTN\code\jars directory (which contain the Trading Networks document type extensions) to the <serverDirectory>\packages\WmDeployer\code\jars directory.

- If you specified a partial package and the package does not exist on the target, either remove the package from the deployment or specify a full package for deployment.

- If the definition of a logical server is missing, use webMethods Administrator on your target server to define a logical server with the name indicated in the error message.

- If the overwrite flag is invalid, ensure that your build file has not been manually edited.

DEP.0005.1008E	**The deploy report: "{0}" already exists. Please move it to a different directory.**
Explanation	The deploy report already exists.
Action	Move the existing deploy report file to a different directory.

DEP.0005.1010	**An error occurred interacting with server: "{0}". Exception details follow: "{1}"**
Explanation	This error occurs if the servers in a cluster are not up and running or if the cluster is invalid for some reason.
Action	Verify that the cluster is configured correctly and that all servers are up and running.

DEP.0005.1011E	**Error invoking service wm.deployer.UIAuthorization. Contact Software AG support.**
Explanation	Error invoking service wm.deployer.UIAuthorization.
Action	Contact Software AG support.

DEP.0005.1014E	**An exception occurred while attempting to close the file "{0}". This will not affect deployment, but will keep a lock on the file. Exception details follow: "{1}"**
Explanation	The build file could not be closed because an I/O exception occurred. The exception can occur for the following reasons: - The I/O operation failed or was interrupted while accessing the build file. - A security violation has occurred, which typically means that the user running Deployer does not have correct privileges to access the files.
Action	Verify that the file system is not corrupt and that adequate disk space is available for saving new files. Also verify that the user attempting this action has proper privileges to save files on the file system.

DEP.0005.1015E	**The Overwrite Existing field is set to {0}, which is invalid.**
Explanation	The overwrite flag was set to a value that the code did not recognize. This occurs when a user has manually edited the XML in the target file.
Action	Repeat the build and map steps. Do not manually edit the target file.

DEP.0005.1018E	**A null aliasValues IData was returned from the invocation of wm.server.remote:getAliasValue against remote host: {0} Cannot continue with deployment of Trading Networks. Make sure the WmTN package and the Trading Networks JDBC pool on the target server are enabled.**
Explanation	Deployer invoked the wm.server.remote:getAliasValue service while deploying Trading Networks assets, and a null value was returned.
Action	Make sure the WmTN package and the Trading Networks JDBC pool on the target server are enabled.

DEP.0005.1024E	**The target cluster {0} is not currently available. Deployer is skipping that cluster. Check your network connection and make sure all target servers ({1}) are running within the cluster.**
Explanation	Deployer cannot connect to the target cluster servers due to network connection problems.
Action	Check your network connection. You should be able to access the target server machines.

DEP.0005.1025W	**webMethods Deployer does not support deployment of certificates. Certificates for profile "{0}" will not be deployed.**
Explanation	Deployer does not support the deployment of certificates.
Action	Deployer does not support deployment of certificates. Certificates for profile "{0}" will not be deployed.

DEP.0005.1026E	**Deployer cannot enable adapter connection {0} on target {1}. Make sure the pub.art.connection:enableConnection service is operational and the WmART package is installed on the target server.**
Explanation	Deployer invoked the pub.art.connection:enableConnection service but could not enable adapter notification on the target server after deployment.
Action	Make sure the pub.art.connection:enableConnection service is operational and the WmART package is installed on the target server.

DEP.0005.1027E	**Adapter connection {0} on target {1} is not enabled. Make sure the pub.art.connection:queryConnectionState service is operational and the WmART package is installed on the target server.**
Explanation	Deployer invoked the pub.art.connection:queryConnectionState service but could not enable adapter connections on the target server after deployment.
Action	Make sure the pub.art.connection:queryConnectionState service is operational and the WmART package is installed on the target server.

DEP.0005.1028E	**Deployer cannot update adapter connection "{0}" on target "{1}".**
Explanation	Deployer invoked the wm.art.dev.connection:updateConnectionNode service but could not update adapter connections on the target server after deployment.
Action	Make sure the wm.art.dev.connection:updateConnectionNode service is operational and the WmART package is installed on the target server.

DEP.0005.1029E	**Unable to disable adapter connection {0} on target {1}. Check the Integration Server logs and error messages in the output report for more information.**
Explanation	Unable to disable adapter connection on target.
Action	Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.1030E	**Deployer encountered an error retrieving current values for adapter connection {0} on target {1}. Make sure the wm.art.admin.connection:getResourceConfiguration service is operational and the WmART package is installed on the target server.**
Explanation	Deployer invoked the wm.art.admin.connection:getResourceConfiguration service but could not get current values for the adapter connection in the varsub page.
Action	Make sure the wm.art.admin.connection:getResourceConfiguration service is operational and the WmART package is installed on the target server.

DEP.0005.1031E	**Deployer cannot set the adapter notification for {0} on target {1}. The selected adapter notification might be active on the target server. Review the project settings.**
Explanation	Deployer could not set variable substitution values for adapter notification.
Action	The selected adapter notification might be active on the target server. Review project settings to make sure they are appropriate.

DEP.0005.1032E	**The adapter notification for {0} on target {1} is not enabled.**
Explanation	Deployer invoked the pub.art.notification:queryPollingNotificationState service but could not enable adapter notification on the target server after deployment.
Action	Make sure the pub.art.notification:queryPollingNotificationState service is operational and the WmART package is installed on the target server.

DEP.0005.1033E	**Deployer cannot enable adapter notification for {0} on target {1}.**
Explanation	Deployer invoked the pub.art.notification:enablePollingNotification service, but could not enable adapter notification on the target server after deployment.
Action	Make sure the pub.art.notification:enablePollingNotification service is operational and the WmART package is installed on the target server.

DEP.0005.1034E	**Deployer cannot disable the adapter notification for {0} on target {1}. Check the Integration Server logs for more information. Re-create the build and redeploy if necessary.**
Explanation	Deployer cannot disable adapter notification.
Action	Check the Integration Server logs for more information. Re-create the build and deploy again if necessary.

DEP.0005.1039E	**Deployer cannot fine the deployment reports for deployment candidate {0}.**
Explanation	There are no reports for the deployment candidate.
Action	Try to view the reports using a simulate or deploy operation.

DEP.0005.1040E	**Invalid ID for deployment report. Please use the list command to verify your inputs.**
Explanation	This message occurs when a Deployer user attempts to view the deployment report through command line interface and the report ID does not exist.
Action	Perform simulate and deploy operations and refer to the report ID shown.

DEP.0005.1041E	**Deployer cannot read report {0}.**
Explanation	This message occurs when Deployer is unable to display reports in a browser.
Action	Ensure that the report HTML or XML files are valid and not corrupted.

DEP.0005.1045E	**An error occurred while attempting to import functional permissions: class: "{0}", message: "{1}"**
Explanation	This error occurs when Deployer is unable to deploy Trading Netowrk functional permissions, and it indicates that there might be a problem with the build.
Action	Verify that the selected functional permissions are valid on the source server, and rebuild if necessary.

DEP.0005.1049E	**An exception occurred while deleting DLS "{0}"**
Explanation	An exception occurred while deleting DLS.
Action	Contact the administrator of the target Trading Networks system for assistance.

DEP.0005.1050E	**An exception occurred while deleting the "{0}" functional permission.**
Explanation	An exception occurred while deleting the functional permission.
Action	Verify that the target server is running and try the deletion again.

DEP.0005.1055E	**An error occurred while attempting to import DLSs. The following is the error information from Trading Networks: class: "{0}", message: "{1}"**
Explanation	Deployer displays this error when it cannot deploy Trading Netowrk DLSs. It indicates that there might be a problem with the build.
Action	Verify that the selected DLSs are valid on the source server and rebuild if necessary.

DEP.0005.1057E	**Invalid ID for build report. Use the list command to verify your inputs.**
Explanation	Deployer displays this message when a Deployer user attempts to view the build report through the command line interface and the specified report ID does not exist.
Action	Perform a build operation on the deployment sets and refer to the build report ID shown.

DEP.0005.1058E	**Unable to read JMS trigger {0}.**
Explanation	Deployer is unable to read the JMS trigger files from the source server.
Action	Ensure that the JMS trigger was created properly on the source server.

DEP.0005.1059E	**Unable to read build zip file.**
Explanation	Deployer is unable to read the build zip file while deploying.
Action	Verify that the project build file is correct, and ensure that it has not been corrupted.

DEP.0005.1060E	**Error deploying to cluster. One or more of the nodes in the cluster are not running. Check the cluster configuration and the extended settings for further information.**
Explanation	Not all of the nodes in the cluster are running.
Action	Check the cluster configuration and the extended settings.

DEP.0005.1063	**Action failed: The target server is unavailable. See the Integration Server logs for more information.**
Explanation	The target server is not available.
Action	Check the Integration Server logs for any relevant errors or messages.

DEP.0005.1067E	**An error occurred while attempting to import archival services. The following is the error information from Trading Networks: class: "{0}", message: "{1}" **
Explanation	This error occurs when Deployer is unable to deploy the Trading Networks archival services and indicates that there might be a problem with the build.
Action	Verify that the selected archival services are valid on the source server and rebuild if necessary.

DEP.0005.1068E	**Automatic rollback in logical cluster group {0} failed because the connection to target server {1} was refused.**
Explanation	Deployer displays this message when an automatic rollback fails.
Action	Ensure that the specified server is online and that the network connection works. For more information, see the rollback report and take appropriate action.

DEP.0005.1069E	**Deployment in logical cluster group {0} failed. Connection to target server {1} was refused. Deployer will perform rollback on logical group {2}.**
Explanation	This error occurs when Deployer is unable to deploy assets to a logical cluster group of target servers.
Action	Verify that the servers in the logical cluster group are online and available.

DEP.0005.1074E	**Deployer cannot import Trading Networks partner profiles without a My Enterprise profile.**
Explanation	Deployer was unable to deploy the Trading Networks partner profile.
Action	Verify that a My Enterprise profile exists on the target server. If not, you must deploy the My Enterprise profile first.

DEP.0005.1076E	**Deployer encountered an exception while trying to delete {0}. Exception details follow: "{1}"**
Explanation	An exception occurred while trying to delete the node.
Action	Refresh the node list and try deleting again.

DEP.0005.1125E	**Assets in deletion set {0} have unresolved dependencies. Either add the dependent assets or remove the existing assets from the deletion set.**
Explanation	Assets in the deletion set have unresolved dependencies.
Action	Add the dependent assets, or remove the existing assets from the deletion set.

DEP.0005.1126E	**Deployment to a logical cluster failed and Deployer performed a rollback. Refer to the deployment and rollback reports for more details.**
Explanation	Deployment to a logical cluster failed and rollback has occurred.
Action	See the deployment and rollback reports for more details.

DEP.0005.1129E	**Error occured when deploying file to a Target. Please check the target Integration Server logs for details. {0}**
Explanation	This error occurs when deploying large files. It indicates that the target server WmDeployerResource package is not operational.
Action	Verify that the WmDeployerResource package is installed on the target server. If it is already installed, try re-installing.

DEP.0005.1130E	**An error occured while creating or reading the streaming file {0} corresponding to {1} in the build. Check the target Integration Server logs for details.**
Explanation	This error occurs when extracting large files from a source server. It indicates that the WmDeployerResource package is not operational.
Action	Verify that the WmDeployerResource package is installed on the target server. If it is already installed, try re-installing.

DEP.0005.1135E	**The deployment or deletion set "{0}" contains unresolved dependencies or references. Please resolve the unresolved dependencies to continue with deployment.**
Explanation	The deployment or deletion set contains unresolved dependencies or references.
Action	Resolve the unresolved dependencies or references for the deployment or deletion sets in your project.

DEP.0005.1152E	**The delivery of artifacts to the {0} target server failed. For details, check the logs of the target server.**
Explanation	The delivery of artifacts to the target server failed.
Action	For more information, check the deployment report and the Integration Server log.

DEP.0005.1153E	**The activation of artifacts on the {0} target server failed. For details, check the logs of the target server.**
Explanation	The activation of artifacts on the target server failed.
Action	For details, check the deployment report and the Integration Server log.

DEP.0005.1161E	**Deployer could not deliver artifacts to {0} because the server is unavailable.**
Explanation	The target server is unavailable.
Action	Ensure the target server is running.

DEP.0005.1167E	**Unable to delete artifacts previously delivered to {0} because the server is unavailable.**
Explanation	The target server is unavailable.
Action	Make sure the target server is running.

DEP.0005.1173E	**Skipping the activation of deployment on {0} because the target server is unavailable.**
Explanation	Target server is unavailable.
Action	Ensure target server is running.

DEP.0005.1183E	**A simulation initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the simulation in progress is complete.**
Explanation	Another user is running an operation for this project.
Action	Wait until the other operation finishes.

DEP.0005.1184E	**A deployment initiated by the user {0} for deployment candidate {1} of project {2} is in progress. Wait until the deployment in progress is complete.**
Explanation	Another user is running an operation for this project.
Action	Wait until the other operation finishes.

DEP.0005.1185E	**A rollback initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the rollback in progress is complete.**
Explanation	Another user is running an operation for this project.
Action	Wait until the other operation finishes.

DEP.0005.1186E	**A checkpoint initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the checkpoint in progress is complete.**
Explanation	Another user is running an operation for this project.
Action	Wait until the other operation finishes.

DEP.0005.1187E	**You cannot deploy the {0} project because it is not locked.**
Explanation	The project was not locked before deployment.
Action	Lock the project.

DEP.0005.1188E	**You cannot deploy the {0} project because it is locked by another user.**
Explanation	Another user has locked the project.
Action	Wait until the project is unlocked by the other user.

DEP.0005.1189E	**You cannot simulate the deployment for the {0} project because it is not locked.**
Explanation	The project was not locked before simulation.
Action	Lock the project.

DEP.0005.1190E	**You cannot simulate the deployment for the {0} project because it is locked by another user.**
Explanation	Another user has locked the project.
Action	Wait until the project is unlocked by the other user.

DEP.0005.1191E	**You cannot rollback the deployment for the {0} project because it is not locked.**
Explanation	The project was not locked before you attempted to roll back the deployment.
Action	Lock the project.

DEP.0005.1192E	**You cannot rollback the deployment for the {0} project because it is locked by another user.**
Explanation	Another user has locked the project.
Action	Wait until the project is unlocked by the other user.

DEP.0005.1193E	**You are not authorized to generate a checkpoint for the {0} project because it is not locked.**
Explanation	The project was not locked before you attempted to generate a checkpoint.
Action	Lock the project.

DEP.0005.1194E	**You are not authorized to generate a checkpoint for the {0} project because it is locked by a different user.**
Explanation	Another user has locked the project.
Action	Wait until the project is unlocked by the other user.

DEP.0005.1195E	**The deletion of delivered to the {0} target server artifacts failed. For details, check the logs of the target server.**
Explanation	The deletion of delivered to the target server artifacts failed.
Action	Check the deployment report for details. There might be additional information in the log of Integration Server.

DEP.0005.1201E	**Repository-based deployment does not support the rollback operation for the mapped target servers.**
Explanation	Repository-based projects do not support rollback operations for the mapped target servers.
Action	Only Deploy operation is supported.

DEP.0005.1203E	**There are no target servers or target groups mapped for deployment candidate {0}.**
Explanation	There are no target servers or target groups mapped to the deployment set in the map step.
Action	Map at least one deployment set to a target server or a target group in the map step.

DEP.0005.1204E	**The success flag does not match any messages returned by the target server {0}.**
Explanation	Either the target server returned the success flag of true and the messages from the target server contains error messages, or the target returned a success flag of false and the message from the target server does not contain an error message.
Action	Check the target server logs or contact Software AG Global Support.

DEP.0005.1206E	**An error ocurred while saving deployment candidate {0}.**
Explanation	An error encountered while saving the deployment candidate.
Action	Contact Software AG Global Support.

DEP.0005.1210E	**Deployer did not delete the assets from {0} because the server is unavailable.**
Explanation	The target server is unavailable.
Action	Ensure target server is running.

DEP.0005.1212E	**Deployer failed to delete the assets on the target server {0}. For more information, see the target server's logs.**
Explanation	The deletion of assets on the target server failed.
Action	Check the deployment report and the Integration Server log for details.

DEP.0005.1215E	**Deployer failed to delete the assets on the target server {0}. For more information, see the target server's logs.**
Explanation	The deletion of assets on the target server failed.
Action	Check the deployment report for details. There might be additional information in the Integration Server log.

DEP.0005.1216E	**Target server {0} did not return any messages.**
Explanation	Deployer did not receive any messages from target server {0}.
Action	Check the target server log for details.

DEP.0005.1217E	**Deletion set {0} contains unresolved dependencies. Please resolve the dependencies to proceed with deployment.**
Explanation	The deletion set contains unresolved dependencies.
Action	Resolve the unresolved dependencies for the deletion set.

DEP.0005.1218E	**Repository-based deployment does not support the rollback operation for target servers of types {0}.**
Explanation	Repository-based deployment does not support rollback operation for target servers of the given type.
Action	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.

DEP.0005.1219E	**Repository-based deployment does not support the simulate operation for target servers of types {0}.**
Explanation	Repository-based deployment does not support simulate operation for target servers of the given type.
Action	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.

DEP.0005.1220E	**Repository-based deployment does not support deletion sets for target servers of types {0}.**
Explanation	Repository-based deployment does not support deletion sets for target servers of the given type.
Action	Remove the assets of the unsupported runtimes from the deletion set and update the deployment map accordingly.

DEP.0005.1221E	**Repository-based deployment does not support deletion sets for the selected target servers.**
Explanation	Repository-based deployment does not support deletion sets for the selected target servers.
Action	Remove the deletion set from the project.

DEP.0005.1222E	**The repository is corrupted. The binary file for composite {0} of type {1} is missing from repsoitory {2}.**
Explanation	The binary file is missing from the repository.
Action	Rebuild the repository using Asset Build Environment.

DEP.0005.1227E	**Deployer issued the following exception while deleting the field definition during rollback: "{0}"**
Explanation	An exception occurred while deleting the field definition.
Action	Contact the administrator of the target server for assistance.

DEP.0005.1230	**No value was specified for the required package parameter. Specify a value for the package parameter.**
Explanation	No value was specified for the package parameter.
Action	Specify a valid package value for the package parameter.

DEP.0006.0011E	**Plugin {0} does not exist.**
Explanation	The specified plug-in is not correctly configured in the Deployer plugin configuration file. This indicates an incomplete or damaged installation, or possibly a modification to the plugin configuration file located in <serverDirectory>\packages\WmDeployer\config\plugin folder.
Action	Make sure a file named <pluginName>.cnf exists in the <serverDirectory>\packages\WmDeployer\config\plugin directory.

DEP.0006.0025E	**The versions for the aliases {0} were not persisted successfully. Verify that the specified version is valid.**
Explanation	The specified versions are not valid.
Action	Ensure that the specified versions are valid.

DEP.0006.0026E	**The version {0} reported by the {1} plugin for the server alias {2} does not match the version {3} set by the user.**
Explanation	The version reported by the plugin is different from the version set for the server alias.
Action	Set the correct version for the server alias.

DEP.0006.0028E **Plugin server name {0} contains illegal characters.**

Explanation The plugin server name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : $ /\ \ ` ' ; , ~ + = > < \ "

Action Remove the invalid characters from the plugin server name.

DEP.0006.0030E **Plugin server {0} of type {1} does not exist for the specified runtime type. Create a new plugin server or remove it from the project map.**

Explanation The plugin server does not exist for the specified runtime type.

Action Create a new plugin server or remove it from the project map.

DEP.0007.0001E **A target group with the name {0} already exists.**

Explanation You specified a name for a target group that already exists. Deployer requires that target groups be uniquely named.

Action Specify a unique name for the target group.

DEP.0007.0002E **Target group {0} does not exist.**

Explanation The specified target group does not exist

Action Verify that the target group exists in the Deployer server target groups.

DEP.0007.0005E **Error invoking service {0}. This usually indicates a problem with the Integration Server installation. On the local Deployer server, determine whether the following Integration Server packages are disabled, missing, or missing parts WmDeployer WmAdmin WmRoot WmDeployerResource WmModeler **

Explanation Deployer was unable to invoke a required Integration Server service. This usually indicates a problem with the Integration Server installation.

Action On the local Deployer server, determine whether the following Integration Server packages are disabled, missing, or missing parts:

WmDeployer

WmAdmin

WmRoot

WmDeployerResource

WmModeler

DEP.0007.0006E	**Deployer encountered the following error while invoking getConnectionInfo for system {0}: {1}**
Explanation	Deployer could not retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.
Action	Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.
DEP.0007.0007E	**The call to getConnectionInfo for system {0} returned the following exception for host name {1}: {2}**
Explanation	Deployer was unable to retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.
Action	Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.
DEP.0007.0008E	**The call to getConnectionInfo for system {0} returned the following missing data: {1} Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.**
Explanation	Deployer was unable to retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.
Action	Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.
DEP.0007.0009E	**Deployer encountered the following error while connecting to Integration Server {0}: {1}**
Explanation	Deployer was unable to connect to the specified remote Integration Server. The Integration Server might not be running, or the logon credentials might be incorrect.
Action	Make sure the Integration Server is running and that the logon credentials in the remote server configuration, including the Port value, are correct.
DEP.0007.0010E	**Deployer encountered the following error while invoking the required Integration Server service {0} on system {1}: {2} This usually indicates an incomplete or error with the installation of a plug-in on the remote server. On the specified remote server, determine whether the following required Integration Server packages are disabled, missing, or incomplete: - WmDeployer - WmAdmin - WmRoot - WmDeployerResource - WmModeler **
Explanation	Deployer was unable to invoke a required Integration Server service. This usually indicates an incomplete or error with the installation of a plug-in on the remote server.
Action	On the specified remote server, determine whether the following required Integration Server packages are disabled, missing, or incomplete:

- WmDeployer

- WmAdmin

- WmRoot

- WmDeployerResource

- WmModeler

DEP.0007.0011 **A Target Server with name {0} already exists. Rename the target server alias or use a different name for the Target Group.**

Explanation Target servers and target groups cannot have the same names.

Action Rename the target server alias or use a different name for the Target Group.

DEP.0007.0012E **Failed to load the plug-in server configuration file {0}. This indicates that the configuration file has been modified and Deployer can no longer parse the configuration file. Try to delete and then re-add the plug-in server. This should correctly recreate the configuration file. If this fails, send the contents of the server configuration file, located in "<serverDirectory>/packages/WmDeployer/config/pluginServer/<pluginName>" to Software AG Global Support.**

Explanation When Deployer started, it could not successfully load the plug-in server configuration file. This indicates the configuration file has been modified and Deployer can no longer parse the configuration file.

Action Try to delete and then re-add the plug-in server. This should correctly recreate the configuration file. If this fails, send the contents of the server configuration file, located in "<serverDirectory>/packages/WmDeployer/config/pluginServer/<pluginName>" to Software AG Global Support.

DEP.0007.0013E **Failed to save plugin server config file {0}. The plug-in configuration file provided by Software AG does not contain the entry identifying the class necessary to remotely install the communication component. The configuration file may have been altered incorrectly. Reinstall Deployer. Your project data will remain unchanged.**

Explanation The plug-in configuration file provided by Software AG does not contain the entry identifying the class necessary to remotely install the communication component. The configuration file might have been altered incorrectly.

Action Reinstall Deployer. Your project data will remain unchanged.

DEP.0007.0014E	**{0} target group {1} dependencies have been resolved. See the Integration Server error log for details. Contact webMethods Global Support if the problem cannot be resolved locally.**
Explanation	The invocation of the Communication Component Installation class has failed.
Action	See the Integration Server error log for details. Contact Software AG Global Support if the problem cannot be resolved locally.

DEP.0007.0015E	**{0} Target Group {1} validation failed. Unable to resolve some servers within the group. Your installation could be damaged or corrupt. Reinstall Deployer. Your project data will remain unchanged.**
Explanation	The remote installation of the communication component was unable to locate the component file on the file system. Your installation could be damaged or corrupt.
Action	Reinstall Deployer. Your project data will remain unchanged.

DEP.0007.0018E	**Deployer encountered the following error while pinging plug-in server {0}: {1} Deployer cannot contact the remote server hosting the identified plug-in. The host could be down or the host name could be incorrect. Verify the host name (or IP address) and ensure that the system is available.**
Explanation	Deployer cannot contact the remote server hosting the identified plug-in. The host could be down or the host name could be incorrect.
Action	Verify the host name (or IP address) and ensure that the system is available.

DEP.0007.0019E	**Plug-in {0} on target group {1} does not contain any servers.**
Explanation	You have attempted to add a target group with no servers.
Action	Add target servers in that target group.

DEP.0007.0029	**Cannot create a Target Group with same name as that of a Target Server. Either rename the target group or delete the existing target group or target server with the same name.**
Explanation	You cannot create a target group with same name as one used by a target server.
Action	Either rename the target group or delete the existing target group or target server with the same name.

DEP.0007.0030	**{0} Target Group {1} validation failed. Unable to resolve some servers within the cluster {2} in the group {3}. Make sure all nodes in the cluster are running and the WmDeployerResource package is installed on all of these nodes. If the WmDeployerResource package is not installed, install it using the Deployer user interface.**
Explanation	Deployer cannot ping some of the cluster servers.

Action	Make sure all nodes in the cluster are running and the WmDeployerResource package is installed on all of these nodes. If the WmDeployerResource package is not installed, install it using the Deployer user interface.

DEP.0007.0031E	**Validation of plug-in {0} on target group {1} failed. Deployer cannot resolve server {2} which is a part of the cluster {3}. Remove this server manually from target group.**
Explanation	A server in the cluster could not be resolved.
Action	Manually remove the server from the tagret group.

DEP.0007.0032E	**Invalid version specified for the target group {0} of type {1}. The valid versions can be {2}.**
Explanation	The version specified for the target group is not valid.
Action	Specify the correct version.

DEP.0007.0033E	**The server aliases {0} version do not match the target group {1} version. Server aliases and target groups must be of the same version. Modify either the definition of the targets within the target group or modify the version of the target group.**
Explanation	The version of the targets in the target group do not match the version of the parent target group.
Action	Modify either the definition of the targets within the target group or modify the version of the target group.

DEP.0007.0034E	**Target group name {0} contains illegal characters.**
Explanation	The target group name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : $ /\ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the target group name.

DEP.0007.0035	**Target group {0} does not exist.**
Explanation	A target group was mapped for deployement but is either not defined or was deleted.
Action	Define the target group.

DEP.0008.0001E	**You are not authorized to checkpoint the {0} project. Use the Deployer user interface to grant the user the right to deploy the project.**
Explanation	The user is not authorized to generate a checkpoint for the project.
Action	Use the Deployer user interface to grant the user the right to deploy the project.

DEP.0008.0003E	**Error invoking service "{0}".**
Explanation	An exception occurred while invoking the wm.deployer.UIAuthorization:isAuthorized service. This could mean that Integration Server is either not running or that it cannot be reached on the network.
Action	Verify that the Integration Server is running and available on the network.

DEP.0008.0004E	**Error cloning source system "{0}": {1}**
Explanation	The project contains a source system of an unknown type.
Action	Rebuild the project.

DEP.0008.0006E	**Checkpoint summary file "{0}" does not exist.**
Explanation	The checkpoint file does not exist on the disk.
Action	Use Deployer to create a checkpoint.

DEP.0008.0007E	**Cannot write to checkpoint directory "{0}".**
Explanation	You cannot create or write to the specified directory.
Action	Ensure that you have the correct privileges to create and write to the directory and that the file system has enough space for the creation of a new directory.

DEP.0008.0009E	**Error creating checkpoint "{0}": {1}**
Explanation	An exception occurred while creating the checkpoint report.
Action	Ensure that you have the correct privileges to create and write to files and that the file system has enough space for the new file.

DEP.0008.0010E	**Error saving checkpoint project {0}: {1}. Make sure you have the correct privileges to create and write to files and that the file system has enough space for the new file**
Explanation	The specified file could not be saved to disk.
Action	Make sure you have the correct privileges to create and write to files and that the file system has enough space for the new file.

DEP.0008.0013E	**Deployer cannot generate a checkpoint at {0} because the target server is unavailable**
Explanation	The target server is unavailable.
Action	Ensure that the target server is running.

DEP.0008.0015E	**Checkpoint on the target server {0} failed. Please check the target server's logs for details.**
Explanation	The checkpoint operation failed due to the reason specified in the checkpoint report.
Action	Check the checkpoint report for details. There might also be additional information in the Integration Server log.

DEP.0008.0018E	**Skipping the delete checkpoint for {0} because the server is unavailable.**
Explanation	The target server is unavailable.
Action	Ensure that the target server is running.

DEP.0008.0022E	**Failed to delete checkpoint for target server {0}.**
Explanation	Deletion of checkpoint failed.
Action	Check Deployer and Integration Server logs.

DEP.0008.0023E	**Repository-based deployment does not support the checkpoint operation for the mapped target servers.**
Explanation	Repository-based projects do not support checkpoint operations for the mapped target servers
Action	Perform Deploy operation.

DEP.0008.0024I	**Deployer does not allow you to create checkpoints for transactional deployment.**
Explanation	You cannot create a checkpoint for projects that use transactional deployment. Deployer creates checkpoints automatically for transactional deployment.
Action	See the webMethods Deployer documentation for more information.

DEP.0008.0025E	**Repository-based deployment does not support checkpoint operation for target servers of type {0}.**
Explanation	Repository-based deployment does not support checkpoint operation for target servers of the given type.
Action	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.

DEP.0100.3.42E	**The simulate, checkpoint, deploy, or rollback operation encountered an error while generating the report. Contact Software AG Global Support.**
Explanation	The simulate, checkpoint, deploy, or rollback operation encountered an error while generating the report.
Action	Contact Software AG Support.

DEP.0100.5.37	**Deployer cannot retrieve the project specified on the command. Make sure the user is authorized to view this information.**
Explanation	Deployer cannot retrieve the project specified on the command.
Action	Make sure the user is authorized to view this information.

DEP.0100.5.38	**Deployer cannot retrieve the build information specified on the command. Make sure the user is authorized to view this information.**
Explanation	Deployer cannot retrieve the build information specified on the command.
Action	Make sure the user is authorized to view this build information.

DEP.0100.5.39	**Deployer cannot retrieve the map specified on the command. Make sure the user is authorized to view this information.**
Explanation	Deployer cannot retrieve the map the user specified on the command.
Action	Make sure the user is authorized to view this information.

DEP.0100.5.40	**Deployer cannot retrieve the deployment candidates specified on the command. Make sure the user is authorized to view this information.**
Explanation	Deployer cannot retrieve the deployment candidates specified on the command.
Action	Make sure the user is authorized to view this information.

DEP.0100.5.41	**Deployer cannot retrieve the map for the user and project specified on the command. Make sure the user is authorized to view this information.**
Explanation	Deployer cannot retrieve the map for the user and project specified on the command.
Action	Make sure the user is authorized to view this information.

DEP.0100.5.42	**Deployer cannot retrieve the build information specified on the command. Make sure the user is authorized to view this information**
Explanation	Deployer cannot retrieve the build information specified on the command.
Action	Make sure the user is authorized to view this information.

DEP.0100.5.43 **There are no .map files in the IntegrationServer/packages/WmDeployer/replicate/inbound folder. Make sure the file you want to import exists in the specified folder.**

Explanation There are no .map files in the IntegrationServer/packages/WmDeployer/replicate/inbound folder.

Action Make sure the file you want to import exists in the specified folder.

DEP.0100.5.63 **The Integration Server to which you are trying to connect is configured to accept only secure connections on the UNIX platform. Use the correct digital certificates to establish the connection.**

Explanation The Integration Server to which you are trying to connect is configured to accept only secure connections on the UNIX platform.

Action Use the correct digital certificates to establish the connection.

DEP.0100.5.64E **Deployer encountered an error while invoking the service. Make sure the Integration Server to which you are trying to connect is up and running and you have properly installed all required components.**

Explanation This error is encountered when trying to invoke the service from CLI.

Action Make sure the Integration Server to which you are trying to connect is up and running and you have properly installed all required components.

InputValidationMessages.0001E – Parameter {0} cannot be null or empty

Explanation The specified parameter is either null or empty.

Action Provide a valid value for the parameter.

InputValidationMessages.0002E – Parameter {0} cannot be null.

Explanation The specified parameter is null.

Action Provide a valid value for the parameter.

InputValidationMessages.0003E – Parameter {0} cannot be a negative integer

Explanation The specified value is a negative integer.

Action Provide a positive integer value for the parameter.

InputValidationMessages.0004E – File {0} does not exist.

Explanation The specified file does not exist in the specified location.

Action Provide a valid file.

InputValidationMessages.0005E – SSL-enabled connections require that either the TrustClientCertificatesByDefault parameter be set to true or that both TrustStoreFileName and TrustStorePassword are specified.

Explanation Either the TrustClientCertificatesByDefault parameter is set to false or either the TrustStoreFileName, TrustStorePassword, or both are not specified.

Action Set the TrustClientCertificatesByDefault parameter to true or provide valid values for both the TrustStoreFileName and TrustStorePassword parameters.

OperationMessages.0002E – Failed to ping the target {0} of type {1} with following exception : {2}. Either the target is unavailable or the credentials provided are invalid.

Explanation Either the target is unavailable or the credentials provided are invalid.

Action Verify that the server is up and running, and that the specified parameters are valid.

OperationMessages.0003E – An unexpected error occurred while pinging the target {0}. Error details : {1}

Explanation An unexpected error occurred while pinging the target.

Action Check the server logs for more details.

OperationMessages.0011E – Deliver operation on the target server {0} of type {1} failed with following exception : {2}. Please check the target server's logs for details.

Explanation The Deliver operation failed due to the reason specified in the Deliver report.

Action Check the Deliver report for details. There might also be additional information in the Integration Server log.

OperationMessages.0012E – An unexpected error occurred while performing variable substitutions for the asset with ACDL file name {0}. Error details : {1}

Explanation An unexpected error occured while substituting values.

Action Check server logs for more details.

OperationMessages.0021E – An unexpected error occurred while deleting the delivered assets for the deployment with ID {0} from target {1}. Error details : {2}

Explanation An unexpected error occurred while deleting the delivered assets.

Action Check the server logs for more details.

OperationMessages.0030E – An unexpected error occurred while activating the deployment with ID {0} for target {1}. Error details : {2}

Explanation An unexpected error occurred while activating the delivered assets.

Action Check the server logs for more details.

OperationMessages.0050E – Runtime type of the artifact {0} is different from the target runtime type {1}

Explanation The runtime type of the specified artifact is different than the target runtime type.

Action Ensure that the runtime type of the asset to be deployed is same as the target server type.

WDY-4460 **The Package: "{0}" will not be activated. The dependent package "{1}" version "{2}" does not match the package version "{3}" present on the target server.**

Explanation The dependent package version does not match the package version present on the target server.

Action Ensure that the target server package version is the same as the dependent package version on the source server.

13 Designer Composite Application Framework

restconnector.name New REST UI

restconnector.projectwizardpage.description – Select a gadget from the listed projects

restconnector.projectwizardpage.loaddatafrom – Load data from

restconnector.projectwizardpage.selectgadget – Select a Gadget

restconnector.projectwizardpage.swaggerurl – Swagger URL

restconnector.projectwizardpage.title – Gadget Selection

restconnector.restresourcespage.description – Select the desired REST resources and their operations

restconnector.restresourcespage.title – REST Resources Selection

restconnector.wizard.fieldpage.description – Select the fields to be generated on UI and their configuration

restconnector.wizard.fieldpage.displaylabel – Display Label

restconnector.wizard.fieldpage.formname – Form Name

restconnector.wizard.fieldpage.incolumncount – UI Layout column count for Input Parameters

Explanation The number of columns in which Business Console displays the input and output parameters in the generated form

restconnector.wizard.fieldpage.inputparams – Input Parameters

restconnector.wizard.fieldpage.mandatory – Mandatory

restconnector.wizard.fieldpage.name – Name

restconnector.wizard.fieldpage.outcolumncount – UI Layout column count for Output Parameters

Explanation The number of columns in which Business Console displays the input and output parameters in the generated form

restconnector.wizard.fieldpage.outputparams – Output Parameters

restconnector.wizard.fieldpage.pagenumber – PageNumber

restconnector.wizard.fieldpage.pagesize – PageSize

restconnector.wizard.fieldpage.title – Field Configuration

restconnector.wizard.fieldpage.totalrecords – TotalRecords

restconnector.wizard.fieldpage.type – Type

restconnector.wizard.fieldpage.uicontrol – UIControl

restconnector.wizard.fieldpage.validation – Validation

restconnector.wizard.title – New REST Connector Wizard

14 Digital Event Services

DEVABEE0000 **The specified location "{0}" does not denote an existing directory.**

Explanation A valid event type repository is needed.

Action Check whether the specified location points to a DES event type repository.

DEVABEE0002 **Could not read content of file "{0}" in order to create zip archive "{1}"**

Explanation The file content was not available while creating zip archive.

Action See stacktrace for further explanations and actions.

DEVABEE0003 **Saving of acdl composite "{0}" failed.**

Explanation The writing of the ACDL composite to disk failed. Possible reasons are a wrong location, or missing permissions.

Action See stacktrace for further information.

DEVABEE0005 **Not a valid repository "{0}".**

Explanation The specified folder is not a valid repository folder.

Action Specify a valid repository folder.

DEVDECOE0040 **Missing configuration location.**

Explanation Required parameter for configuration location has not been set.

Action Set an existing configuration location.

DEVDECOE0041	**Configuration location "{0}" does not exist.**
Explanation	The configuration location does not exit.
Action	Provide an existing configuration location.

DEVDECOE0042	**Configuration location "{0}" is not an absolute path.**
Explanation	Configuration loaction is not an absolute path.
Action	Provide an absolute path as configuration location.

DEVDECOE0043	**Configuration location "{0}" is not a directory.**
Explanation	The configuration location must be a directory.
Action	Provide a directory as configuration location.

DEVDEEE0000	**Storing password for handle {0} failed**
Explanation	This is a failure of the Passman component.
Action	Contact your local support organization.

DEVDEEE0003	**Failed to calculate passman config location: {0}**
Explanation	Malformed URL or invalid URI provided.
Action	Verify the correct URL / URI location.

DEVDEGE0001	**Invalid command line parameter**

DEVDEGE0002	**No parameters specified**

DEVDEGE0003	**Unknown command: "{0}"**

DEVDEGE0004	**Unknown option "{0}"**

DEVDEGE0005	**Duplicate option "{0}"**

DEVDEGE0006 **Missing value for option "{0}"**

DEVDEGE0007 **Bad numeric value "{0}" for option "{1}"**

DEVDEGE0008 **Only one of the options "{0}" can be specified for "{1}"**

DEVDEGE0009 **Missing option "{0}" for "{1}"**

DEVDEGE0010 **Option "{0}" not allowed for "{1}"**

DEVDEGE0013 **Failed to find the Digital Events Type Repository**

DEVDEGE0014 **Failed to retrieve event type names**

DEVDEGE0015 **Not a bytes array value node: {0}**
Explanation An event rule of type “Bytes” should contain an array of byte values.
Action Change the value node to a bytes array in the Event Generator json document.

DEVDEGE0017 **Not a bytes value node: {0}**
Explanation An event rule of type "Bytes" should contain byte values.
Action Change the value node to bytes in the Event Generator json document

DEVDEGE0018 **Not a (textual) time value node: {0}**
Explanation An event rule of type "time" should contain a Date and a Duration value.
Action Change the value node a Date in the Event Generator json document.

DEVDEGE0019 **Not a decimal double value node: {0}**
Explanation An event rule of type "float64" should contain a double value.
Action Change the value node to a double value in the Event Generator json document.

DEVDEGE0020	**Not a (textual) Duration value node: {0}**
Explanation	An event rule of type "time" should contain a Date and a Duration value.
Action	Change the value node to a Duration in the Event Generator json document.

DEVDEGE0021	**Not a decimal float value node: {0}**
Explanation	An event rule of type "float32" should contain a decimal float value.
Action	Change the value node to a decimal float value in the Event Generator json document.

DEVDEGE0022	**Not an integer value node;: {0}**
Explanation	An event rule of type "int32" should contain an integer value.
Action	Change the value node to an integer value in the Event Generator json document.

DEVDEGE0023	**Not a long value node: {0}**
Explanation	An event rule of type "int64" should contain a long value.
Action	Change the value node to a long value in the in the Event Generator json document.

DEVDEGE0024	**Not a string value node: {0}**
Explanation	An event rule of type "string" should contain a string value.
Action	Change the value node to a string in the in the Event Generator json document.

DEVDEGE0025	**Event rate rule "{0}" not found in eventRates section of json file.**
Explanation	Event rate rules must be included in the eventRates section of the Event Generator json document.
Action	Add the event rate rule to the eventRates section of json document or remove the reference to this rule.

DEVDEGE0026	**Wrong number of object entries of json node expected: {0} sub node expected, but was {1}. (Json node: {2})**
Explanation	The event rate rule json node must have the following format: "<rate rule name>": { "fixed" | "trend" | "variation": <data> }.
Action	Make sure that the event rate rule is specified using the correct json format.

DEVDEGE0028	**Invalid configuration (null)**
Explanation	Invalid event type configuration passed as argument.
Action	Pass a valid event type configuration as argument.

DEVDEGE0029	**Could not serialize the Event Generator model into file "{0}"**
Explanation	Serialization of the Event Generator configuration failed because of an IOException. This might be caused by an incorrect file path.
Action	Make sure the destination folder is correct.

DEVDEGE0030	**Data rule "{0}" not found in rules section of json document.l**
Explanation	The data rule is missing from the rules section of json document.
Action	Add the data rule to rules section of the json document or remove reference to this data rule.

DEVDEGE0031	**Invalid DES data type specified: "{0}"; expected DES data type of kind {1} ({2})**
Explanation	The data type you specified in the Event Generator json document is not valid. For event rules of type array, map, any, and event, the rule type must match the data type.
Action	Specify a data type that matches the event rule.

DEVDEGE0032	**Event type "{0}" not found**
Explanation	The event type you specify must be available in the Digital Event Services event type repository, located in the <SoftwareAG_Directory>/common/DigitalEventServices/TypeRepository/eventtypes directory.
Action	Make sure that the event type name you specify is correct, or add the event type to the Digital Event Services event type repository.

DEVDEGE0034	**Not an array node: "{0}"**
Explanation	A json array node is expected while deserializing an event rule of type "list".
Action	Correct the Event Generator json document to include a json array node.

DEVDEGE0035	**Invalid rule type name "{0}"**
Explanation	A valid rule type must be specified in the Event Generator json document, to specify a valid data rule. Valid rule type names are: string, boolean, float32, float64, int32, int64, time, map, array, event, etc.
Action	Specify a valid rule type name.

DEVDEGE0036	**Invalid settings type name "{0}"**
Explanation	Settings type name for data rules in the Event Generator json document must be one of the following: fixed, sequencelist, random, variation, increment, simple, complex, eventCreationTime, trend according to the rule type.
Action	Specify a valid settings type name.

DEVDEGE0037	**Invalid DES data type found "{0}"**
Explanation	The Digital Event Services (DES) event field data type could not be parsed successfully.
Action	Correct the event field data type according to the valid syntax for field definition in .dx files in the event type repository.

DEVDEGE0038	**Json object key missing: "{0}" expected**
Explanation	A certain json key string is missing.
Action	Add the correct key to the json node.

DEVDEGE0039	**No event rule and no event type name for event type configuration**
Explanation	Neither the event type rule nor the event type name have been specified. You must specify at least one of them to reference an event type.
Action	Specify a valid event rule or an event type name for the corresponding event type configuration entry in the Event Generator json document.

DEVDEGE0041	**Missing event type name in case of invalid event rule for {0}.event type configuration**
Explanation	Invalid entry of the corresponding event type configuration. Either the event type name or the event rule reference must be available to define the event type.
Action	Specify a valid event type name or an event rule.

DEVDEGE0042	**Missing event type name in case of invalid event rate of {0}.event type configuration**
Explanation	Invalid entry of the corresponding event type configuration.Either the event type name or the event rate reference must be available to define the default event rate name.
Action	Specify a valid event type name or an event rate reference.

DEVDEGE0043	**Invalid event type configurations list (null)**
Explanation	The event type configuration must be valid.
Action	Make sure that the configuration of the event type is correct in the Event Generator json document.

DEVDEGE0046	**Recursion recognized for nested rule "{0}" of rule "{1}" (rules stack: "{2}")**
Explanation	Recursive references are not allowed in the Events Generator model .
Action	Remove the references that cause the recursion or change the references accordingly.

DEVDEGE0048	**Value ({0}} less than or equal to 0; expected greater than 0**
Explanation	The fixed rate value must be greater than 0.
Action	Change value of the rule to be greater than 0.

DEVDEGE0049	**Invalid object for "{0}" (null)**
Explanation	Object must be valid.
Action	Make sure that the field name value is correct.

DEVDEGE0050	**"{0}" value ({1}) must be a positive value (if {2})**
Explanation	For increment settings, the delta value must be greater than 0, if the lower value is less than the upper value.
Action	Specify a valid value.

DEVDEGE0051	**"{0}" value ({1}) must be a negative value (if {2})**
Explanation	For increment settings the delta value must be less than 0, if the lower value is greater than the upper value.
Action	Specify a valid value.

DEVDEGE0054	**"{0}" is empty.**
Explanation	You must specify at least one element in a list for a valid list setting type.
Action	Add at least one element to the list settings definition.

DEVDEGE0056	**"{0}" value ({1}) greater than "{2}" value ({3}); expected {4} less than {5}**
Explanation	For random settings type the lower value must be less than the upper value.
Action	Correct the lower and upper value that lower < upper.

DEVDEGE0058	**"{0}" value ({1}) less than 0; expected is zero or a positive value.**
Explanation	The deviation value must be greater than, or equal to 0. The unit of the deviation is the same as the mean value.
Action	Correct the deviation value so that it is greater than, or equal to 0.

DEVDEGE0060	**"{0}" value ({1}) less than or equal to 0; expected greater than 0 for a valid event rate.**
Explanation	The mean value must be greater than 0 in order to get a poitive, non-zero value for the event rate.
Action	Correct the mean value so that it is greater than 0.

DEVDEGE0065	**"{0}" event rate value ({1}) is negative; expected a positive value.**
Explanation	The trend event rate value is an incrementation value and will be added to the variation result for each new calculation. If the trend event rate value is negative, the rate might reach negative values which is not allowed for event rates.
Action	Change trend value to a positive value.

DEVDEGE0067	**Type "{0}" of nested rule "{1}" does not match the type "{2}" of rule "{3}"**
Explanation	The any, array, map, and event data rule types contain references to other nested rules. The DES data type of those rules must match the nested rules accordingly. Therefoer, for type map, array, and event the nested type is relevant: e.g. map<nestedType, nestedType>; nestedType[].
Action	Use a rule that fits in data type.

DEVDEGE0068	**Reference of rule "{0}" from rule "{1}" could not be resolved.**
Explanation	All referenced rule names must be resolvable. This means that all rules that are referenced by name must be defined.
Action	Remove the reference a to non-existings rule or create the rule accordingly.

DEVDEGE0073	**The "{0}" field is not a Duration value.**
Explanation	You have to specify a valid Duration format.
Action	Make sure that your value is in a valid Duration format.

DEVDEGE0082	**Reference of event rule "{0}" defined for event type "{1}" could not be resolved.**
Explanation	The referenced rule does not exist, it might have been deleted.
Action	If the referenced rule has been deleted, try to recreate it, or consider choosing a different rule.

DEVDEGE0083	**Type "{0}" of nested rule "{1}" does not match the event type "{2}"**
Explanation	The selected event rule must be defined for the correct event type.
Action	Choose a rule that has been created for the correct event type.

DEVDEGE0086	**Key rule must not be empty.**
Explanation	A valid map has valid key and value data. It is possible to speciffy a null value for "value", but not for "key".
Action	Select a valid key rule.

DEVDEGE0088	**Reference of event rate "{0}" defined for event type "{1}" could not be resolved.**
Explanation	The referenced rate does not exist, it might have been deleted.
Action	If the referenced rate has been deleted, try to recreate it, or consider choosing a different rate.

DEVDEGE0089	**Not a null value node;: {0}**
Explanation	Null value expected in json format.
Action	Change to expected null value.

DEVDEGE0090	**Not a null value.**
Explanation	Null may be stored as a constant.
Action	Change data to value.

DEVDEGE0091	**Invalid event type.**
Explanation	The event type is used for filtering event rules of that type.
Action	Specify a valid event type.

DEVDEGE0094	**Resource file "{0}" could not be read.**
Explanation	Input/Output problem during accessing of the file resource to be read.
Action	Make sure that the resource is not locked by other processes.

DEVDEGE0095	**Resource file "{0}" could not be deserialized.**
Explanation	The file resource could be read, but it could not be parsed using json parser. It might happen that the file resource could be parsed by json parser, but the deserializer of the Event Generator failed because of a semantic issues.
Action	Check the resouce file input for json parsing problems or semantic problems of expected Event Generator format.

DEVDEGI0012	**"{0}" was interrupted during wait**

DEVDEGW0052	**"{0}" value ({1}) is greater than the difference between the "{2}" and "{3}" values.**
Explanation	The difference between lower and upper bounds should be greater than the delta value. Otherwise only the lower and upper value are used.
Action	Use the list settings type instead of increment.

DEVDEGW0053	**"{0}" and "{1}" value ({2}) have the same value, which will cause no change in the value.**
Explanation	Lower and upper limits for increment settings should have different values. Otherwise the is no change in the value and the result is a fixed value.
Action	Change the lower and upper values to different values.

DEVDEGW0055	**"{0}" contains only one value.**
Explanation	The values list of a list settings type should have at least one element. You can use the fixed settings type.
Action	Consider using the fixed settings type.

DEVDEGW0057	**''{0}'' value ({1}) should not be equal to ''{2}'' value ({3})**
Explanation	For random settings type the lower and upper value should have different values.
Action	Consider using the fixed settings type.

DEVDEGW0059	**''{0}'' value should not be zero.**
Explanation	The deviation value is specified in the same unit as the ''meanValue'' and must be a positive value. In case of deviation = 0, there is no change in value expected and a fixed ''meanValue'' is used.
Action	Change the deviation value or consider using the fixed settings type instead.

DEVDELIE0000	**System property for license file path not specified**
Explanation	The system property that defines the location of the license file is not specified.
Action	Specify the system property.

DEVDELIE0001	**The specified license file path ''{0}'' does not exist**
Explanation	The specified license file path does not exist.
Action	Specify a valid license file.

DEVDELIE0002	**Invalid product code.**
Explanation	The product code is not valid.
Action	Provide a valid license.

DEVDELIE0003	**Invalid product version, expected major version "{0}", but found "{1}"**
Explanation	The major version in the license does not match the runtime version of the Digital Event Services product.
Action	Provide a valid license.

DEVDELIE0004	**Invalid OSGi installation directory**
Explanation	The specified value for the OSGi installation directory does not denote a valid directory.
Action	This is an internal error. Contact your support organization.

DEVDELIE0005	**The specified license file path "{0}" denotes a directory.**
Explanation	The location of the Digital Event Services license must point to the license file.
Action	Provide the proper license file location.

DEVDERCE0030	**Passed object of RunWatchdog is not valid**
Explanation	During instanciation of one of the RunWatchdog handlers, the RunWatchdog object itself is passed. However, this RunWatchdog object is not valid (null).
Action	Verify that the RunWatchdog object is valid before instanciating the handlers.

DEVDERCE0039	**The keystore name must not be empty**
Explanation	Each keystore must have a valid and unique name. The name must be unique in the namespace of all keystores. The keystore name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.
Action	Specify a valid and unique name for the keystore.

DEVDERCE0040	**Duplicate event type "{0}"**
Explanation	The specified event type appears twice in the Service Group Event Types configuration.
Action	Remove the duplicate event type from the Service Group Event Types configuration.

DEVDERCE0042	**A service group with the name "{0}" already exists.**
Explanation	Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.
Action	Specify a unique service group name.

DEVDERCE0043	**When you select "No" for "Use Local Store&Forward Queue", you can mark only one of the services in the group "{0}" as "Destination".**
Explanation	When the value you select for "Use local Store&Forward queue" is "No", the service group must contain only one destination service.
Action	Remove the other destination services from the service group.

DEVDERCE0044	**You cannot select "No" for the "Use Local Store&Forward Queue" option if the service group you are configuring contains a service of type "In-Process".**
Explanation	Services of type "In-Process" must always act as both a source and a destination service. You cannot use non-queued delivery when the service group contains an In-Process service.
Action	Use non-queued delivery for a service group that has a destination service of type Universal Messaging or Digital Event Persistence.

DEVDERCE0045	**The specified path "{0}" does not exist**
Explanation	The path must be a valid folder and it must exist on disk.
Action	Make sure the path location is an existing folder and create it if necessary.

DEVDERCE0046	**The specified path "{0}" is not a valid directory**
Explanation	The path is not an existing directory.
Action	Make sure that the specified directory exists.

DEVDERCE0047	**The specified path "{0}" is not an absolute path.**
Explanation	The path must be specified as an absolute path.
Action	Make sure that the path is specified as an absolute path.

DEVDERCE0048	**The service "{0}" is still used by the Service Group "{1}".**
Explanation	A service can only be deleted if it is not included in a service group.
Action	Remove all references to a service before deleting it.

DEVDERCE0049	**A service must not be renamed**
Explanation	A service name is used as a unique ID to reference the service.
Action	If a new name is required, delete the service and create a new one. Before deleting the service, make sure it is no longer referenced by any service group.

DEVDERCE0050	**The service name must not be empty**
Explanation	Each service must have a valid and unique name. A service name must follow the rule: <word character>+(<word character> | - | .)* where <word character> can be a digit, lower or upper case character.
Action	Specify a valid name for the service.

DEVDERCE0051	**Name "{0}" not unique considering the instance IDs. (Not allowed predefined ids: {1}).**
Explanation	Software AG Platform Manager allows only unique instance IDs to be used for the Event Routing runtime component.
Action	Change the name so that is is not identical to any other already existing service name, service group name, or the predefined {1}.

DEVDERCE0052	**A service with the name "{0}" already exists.**
Explanation	Each service must have a valid and unique name. A service name must follow the rule: <word character>+(<word character> | - | .)* where <word character> can be a digit, lower or upper case character.
Action	Specify a unique name for the service.

DEVDERCE0053	**Cannot use reserved service name "{0}"**
Explanation	This is the name of a predefined service.
Action	Choose a different service name.

DEVDERCE0054	**The service group name must not be empty**
Explanation	Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.
Action	Specify a valid and unique name for the service group.

DEVDERCE0057	**The service group "{0}" contains duplicate service entries: "{1}"**
Explanation	Each service group must contain at least one service. The list of services within a service group must contain only unique services.
Action	Use only unique services within a service group.

DEVDERCE0059	**The referenced service "{0}" does not exist**
Explanation	The specified service does not exist and cannot be assigned to a service group.
Action	Choose a valid service in order to assign it to a service group.

DEVDERCE0060	**In the group "{0}" only one service can be marked as "source"**
Explanation	Only one service within a service group can be specified as "source".
Action	Mark only one service as "source".

DEVDERCE0062	**Service type name not found for service "{0}" in group "{1}"**
Explanation	A service with invalid service type has been specified within a certain service group.
Action	Use a service with a valid service type. Only valid services may be assigned to a service group.

DEVDERCE0063	**Service type not found for service "{0}" in group "{1}"**
Explanation	A service with invalid service type has been specified within a certain service group.
Action	Use a service with a valid service type. Only valid services may be assigned to a service group.

DEVDERCE0064	**The service "{0}" is marked as "source", however the corresponding service type "{1}" cannot act as source**
Explanation	The parameters of each service depend on its service type definition. If the service type is not configured to act as source, then the services of that type cannot be configured as "source" either.
Action	Remove the "source" marker from the service definition or change the configuration of the service type in order to allow the "source" marker.

DEVDERCE0067	**The "{0}" service has to be configured as source&destination**
Explanation	This predefined service can only be used as "source and destination".
Action	Configure the service as "source and destination".

DEVDERCE0068	**A service group must not be renamed**
Explanation	A service group name is used as a unique ID to reference the service group.
Action	If a new name is required, delete the service group and create a new one. Before deleting the service group make sure that no event types are associated to it.

DEVDERCE0069	**The default service group must not be deleted**
Explanation	The default service group name is "Default". This group covers all event types which are not associated to other service groups, therefore the "Default" service group cannot be deleted.
Action	Do not delete the "Default" service group.

DEVDERCE0070	**The service group "{0}" is still referenced by an event type e.g. "{1}"**
Explanation	A service group can only be deleted if no event types are associated to it.
Action	Remove all event types associations to the service group before deleting it.

DEVDERCE0079	**Invalid name "{0}". It must follow the rule: <alpha character>+(<word character> | - | .)***
Explanation	A name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, lower or upper case character.
Action	Do not use invalid URI characters.

DEVDERCE0080	**{0} must not be null or an empty string!**
Explanation	You have entered a null or empty string for a capacity value.
Action	Enter a non-empty value for the capacity.

DEVDERCE0081	**"{0}" is not a valid capacity value**
Explanation	The capacity must consist of digits only, optionally followed by one of [K, k, M, m, G, g]. The resulting value must not be larger than 9223372036854775807.
Action	Provide a valid capacity.

DEVDERCE0082	**Cannot return a valid capacity value because the parameter "defaultCapacityValue" is missing.**
Explanation	You have specified that the capacity is the default one, but have not provided a default value.
Action	Provide a valid default capacity value.

DEVDERCE0083	**Event Type not found in type repository: {0}**
Explanation	You are trying to save event type settings in the Digital Event Services (DES) configuration for an event type which is not available in the configured DES event type repository.
Action	Add the event type in the DES event type repository.

DEVDERCE0101	**Cannot configure non-publishable event type: {0}**
Explanation	Only event types marked as publishabe can have event type settings in the Digital Event Services (DES) configuration. You tried to save event type settings in the DES configuration for a non-publishable event type.
Action	Make the event type publishable, or if the event type is nested in another event type, save the event type settings for the parent event type instead.

DEVDERCE0102	**Duplicate keystore alias {0}**
Explanation	The keystore alias has to be unique. A keystore with the given alias already exists.
Action	Provide a unique keystore alias.

DEVDERCE0111	**The truststore name must not be "{0}"**
Explanation	The given truststore name matches the reserved keyword "None".
Action	Choose a different truststore name.

DEVDERCE0112	**The keystore name must not be "{0}"**
Explanation	The given keystore name matches the reserved keyword "None".
Action	Choose a different keystore name.

DEVDERCW0061	**The predefined "{0}" service will be configured as source&destination**
Explanation	This predefined service must always be configured as "source and destination".
Action	Configure this predefined service as "source and destination".

DEVDERE0000	**Failed to look-up {0} implementation of type ''{1}''.**
Explanation	No ServiceProvider implementation for the respective type name has been found. As a result, services of this type cannot be created. Most probably this indicates that the library containing the ServiceProvider implementation is not on the application's classpath.
Action	Make sure the library containing the ServiceProvider implementation for the respective type is on the application's classpath.

DEVDERE0020	**Failed to start a receiving route for event type {0} and subscriber ID {1}.**
Explanation	A subscriber cannot be created because of an unavailable source service, an invalid durable subscriber ID, or because the durable subscruiber ID is already in use.
Action	Check if the service configured as a source is available. If you are creating a durable subscriber, make sure that its ID does not contain invalid characters, and that no durable subscriber with this ID for the same event type is currently active on the source service.

DEVDERE0100	**Cannot use non-publishable event type for pub-sub operations: {0}**
Explanation	Only event types marked as publishable can be used to emit events, or to set up a subscription.
Action	Choose a publishable event for sending/subscribing.

DEVDERE0102	**A nonpositive value of "{0}" has been specified for 'maxUnacknowledgedEvents' which is not allowed.**
Explanation	The value of 'maxUnacknowledgedEvents' must be greater than 0.
Action	Set a value of 'maxUnacknowledgedEvents' which is greater than 0.

DEVDERE0107	**Digital Event Services (DES) failed to read the last data event key for subscriber "{0}" from file "{1}".**
Explanation	When a subscriber to the In-Process service is created, DES reads the key of the last event sent to a subscriber from a configuration file. If you make changes to this file, DES might fail to read it.
Action	Contact Software AG Global Support.

DEVDERE0124	**Digital Event Services failed to remove some or all of the inactive subscriptions for event type "{0}" from source service {1}.**
Explanation	The source service is misconfigured or unreachable and Digital Event Services is not able to remove the inactive subscriptions from the service. If new events are sent to this service, the events are unnecessarily stored for the remaining subscriptions and may cause out of memory or out of disk space errors if the number of events becomes too big.
Action	Manually remove the remaining subscriptions from the source service using the appropriate tooling.

DEVDERUE0041	**The event type name "{0}" could not be decomposed, probably the event sender did not use the correct protocol.**
Explanation	When receiving an event the accompagnying type name has to follow a certain pattern , so that it can be decomposed into parts. This pattern changed between Digital Event Services 9.12 and 10.0, which means senders and receivers across these versions cannot talk to each other.
Action	Make sure all senders and receivers are either of version 9.12, or they are all of version 10.0 or greater.

DEVDERUE0043	**Failed to unsubscribe subscriber "{0}" for event type "{1}" from the Universal Messaging server, because the session is not connected.**
Explanation	Digital Event Services (DES) failed to delete the durable associated with the subscriber from the Universal Messaging server, because DES is currently not connected to the Universal Mesaaging server.
Action	When the Universal Messaging server becomes available, to avoid high number of events being stored for the durable of the subscriber, delete the durable manually.

DEVDESCE0000	**Internal error: the given "RuntimeComponent" parameter is not an instance of the "Instance" interface**
Explanation	This is an internal error.
Action	Contact Software AG Global Support.

DEVDESCE0001	**It is not allowed to create new instances of Runtime Configuration**
Explanation	Only one built-in instance of Runtime Configuration exists.
Action	In order to apply your changes, edit the built-in instance of Runtime Configuration.

DEVDESCE0002	**It is not allowed to delete the instance of Runtime Configuration**
Explanation	There is only one built-in instance of Runtime Configuration, which must not be deleted.
Action	In order to apply changes, edit the built-in instance of Runtime Configuration.

DEVDESCE0005	**It is not possible to change storage location, while instance {0} is running**
Explanation	Please ensure that the component using Digital Event Services is restarted in order to start using the new storage location.
Action	Changing the storage location requires a restart of the components using Digital Event Services.

DEVDESCE0007	**"{0}" is not a valid number**
Explanation	The value to be configured needs to be a number.
Action	Provide a valid number.

DEVDESCE0008	**It is not allowed to create new instances of Event Types Configuration**
Explanation	Only one built-in instance of Event Types Configuration exists.
Action	In order to apply your changes, edit the built-in instance of Event Types Configuration.

DEVDESCE0009	**It is not allowed to delete the instance of Event Types Configuration**
Explanation	There is only one built-in instance of Event Types Configuration, which must not be deleted.
Action	In order to apply changes, edit the built-in instance of Event Types Configuration.

DEVDESCE0010	**Configured service group ''{0}'' does not exist**
Explanation	Event types can only be assigned to existing service groups.
Action	Create the service group before assigning an event type, or choose a different service group.

DEVDESCE0011	**Unknown reliability string "{0}" as configured value string e.g. on UI**
Explanation	The string of the reliability value is unknown to the system and cannot be assigned to an internal definition. This is an internal error and should never occur.
Action	Contact Software AG Global Support.

DEVDESCE0012	**Invalid EventTypeReliability value "{0}"**
Explanation	Invalid EventTypeReliability value used for conversion into string for output on UI e.g. This is an internal error and should not occur.
Action	Contact Software AG Global Support.

DEVDESCE0013	**Invalid EventType Delivery Mode Preference value "{0}"**
Explanation	Invalid EventType Delivery Mode Preference value used for conversion into string for output on UI e.g. This is an internal error and should not occur.
Action	Contact Software AG Global Support.

DEVDESCI0006	**The storage content is not automatically copied from {0} to the new destination {1}.**
Explanation	Before starting Digital Event Services the new storage location should be prepared by copying the necessary folder and files. Events may be lost if the storage is not available at runtime.
Action	Copy the storage from the old path into the new specified path before starting Digital Event Services.

DEVDESCI0021	**com.softwareag.event.routing.configuration bundle started.**
Explanation	The Digital Event Services (DES) configuration bundle for Command Central is started.
Action	(No action required)

DEVDESCI0022	**com.softwareag.event.routing.configuration bundle stopped.**
Explanation	The Digital Event Services (DES) configuration bundle for Command Central is stopped.
Action	(No action required)

DEVDESCW0003	**It is not possible to check whether product to be configured is online. The configuration modification will take effect only after the next restart of the product.**
Explanation	The status of Digital Event Services cannot be checked using SPM tools. Please ensure that the component using Digital Event Services is restarted to use the new storage location.
Action	Changing the storage location requires a restart of the product which is using Digital Event Services.

DEVDESCW0004	**Restart "{0}" to use the storage location "{1}"**
Explanation	The running instance must be restarted to use the new storage location. SPM must be active to change the storage location.
Action	Restart SPM, otherwise the old location will be used.

DEVDRE0000	**Annotation type "{0}" contains duplicate field name "{1}"**
Explanation	Annotation type definitions must not contain duplicate field names.
Action	Correct the annotation type definition.

DEVDRE0001	**System property "{0}" not set.**
Explanation	Digital Events Repositories location is defined by a system property.
Action	Define the system property.

DEVDRE0002	**Repositories location "{0}" is not a directory.**
Explanation	The repositories location must be a directory.
Action	Define a directory as a repository location.

DEVDRE0003	**Double field name "{0}" found.**
Explanation	Event type fields with the same name are not allowed within one event type definition. E.g.\nF1 : string;F1 : boolean; <-- duplicate field name - must be renamed or deleted.
Action	Rename or delete the corresponding field.

DEVDRE0007	**Annotation type "{0}" not found in repository.**
Explanation	Each annotation specified inside the event type definition must be defined in the annotation type repository of the installation. Predefined annotation is e.g. "@Unique".
Action	Use only these annotations which are defined inside the annotation type repository of the installation.

DEVDRE0008	**Field names of annotation type "{0}" must be specified explicitly.**
Explanation	If more than one annotation field is defined for a certain annotation type you have to specify <key>="<value>" pairs in the annotation's parameter list. E.g.\n@multifield_annotation(field1="value1", field2="value2")\n\nThe number of specified parameters is arbitrary:\n@multifield_annotationOnly\n\nin case of one single defined annotation field you can specify only the "<value>" without the <key>= in front of it. E.g.\n@singlefield_annotation("value")
Action	Specify <key>="<value>" pairs as annotation parameter list instead of just "<value>". E.g.\n@multifield_annotation(field1="value1", field2="value2")

DEVDRE0009	**No field names defined for annotation type "{0}".**
Explanation	If there is no annotation field defined for a certain annotation type then it is not allowed to specifiy any <key>="<value>" pair as parameter of the annotation.
Action	Remove the whole parameter list of the annotation. Only the annotation name may be specified e.g. "@Unique".

DEVDRE0011	**No annotation field "{0}" allowed because no fields defined for annotation type "{1}".**
Explanation	There is at least one annotation field specified in the annotation's parameter list. But because no field is defined it is not allowed to specify any annotation field.
Action	Remove the whole parameter list as no annotation field is defined for the annotation type e.g. "@Unique".

DEVDRE0012	**Annotation field "{0}" not defined for annotation type "{1}".**
Explanation	The specified annotation field is invaild because it is not defined for the corresponding annotation type.
Action	Specify the correct annotation field name in the annotation parameter list. E.g. correct the <key> inside of @annotation(<key>="<value>")

DEVDRE0013	**Value "{0}" cannot be converted into annotation field type "{1}".**
Explanation	A certain annotation field type is assigned to each annotation field. The value is specified as string but it must be convertible into the corresponding annotation field type. The annotation field types are defined for each annotation field definition of a certain annotation type.\nValid types:\nSTRING: any string (corresponds to java "String" type)\nINT64: 64 bit integer value (corresponds to java "Long" type)\nFLOAT64: 64 bit floating point value (corresponds to java "Double" type)\nBOOLEAN: boolean value (corresponds to java "Boolean" type)
Action	Specify a correct value according to the correct annotation field type.

DEVDRE0015	**Event Type "{0}" is not unique.**
Explanation	Trying to access an event type as unique, that is not unique.
Action	Don't acess a non unique event type with methods for unique types.

DEVDRE0016	**Event Type "{0}" is unique, but contains more than one entry in repository.**
Explanation	There is more than one file for an unique Event Type in the repository.
Action	The repository must be repaired to contain only one variant of the unique Event Type.

DEVDRE0017	**Inconsistent file name: variant key "{0}" does not match filename "{1}"**
Explanation	The variant key, as computed based on the contents of the type definition file, does not match the type definition file name. Probably, the type definition file was manipulated directly with a text editor.
Action	Fix the type definition file.

DEVDRE0018	**Inconsistent file name: event type name "{0}" does not match filename "{1}"**
Explanation	The event type name, as extracted from the contents of the type definition file, does not match the type definition file name. Probably, the type definition file was manipulated directly with a text editor.
Action	Fix the type definition file.

DEVDRE0019	**Inconsistent file name: Annotation type name "{0}" does not match filename "{1}"**
Explanation	The annotation type name, as extracted from the contents of the type definition file, does not match the type definition file name. Probably, the type definition file was manipulated directly with a text editor.
Action	Fix the type definition file.

DEVDRE0022	**Cannot change "unique" for {0} due to broken reference of an embedded type.**
Explanation	"unique" cannot be changed, if the event type is referenced by another event type.
Action	Insert a new variant for the referenced type, change or delete the referenced types.

DEVDRE0024	**Event type info does not match for "{0}"**
Explanation	The event type info of the type being inserted does not match the existing event type info in the repository.
Action	Correct the event type info.

DEVDRE0036	**Type name to be inserted ({0}) conflicts with existing type ({1})**
Explanation	The name of any type in the repository must not be the prefix of another type name. For example, "com.company" and "com.company.type" are not allowed.
Action	Supply a non-conflicting type name.

DEVDRE0044	**"{0}" with variant "{1}" is used in "{2}" with variant "{3}" and can't be removed.**
Explanation	It is not possible to remove an event type that is embedded.
Action	First remove the parent event type and then you can remove the embedded event type. You can also use removeForced, if you can accept a broken repository.

DEVDTE0000	**Field name "{0}" has wrong format**
Explanation	The field name must follow this pattern: "[a-zA-Z_][a-zA-Z0-9_]*".
Action	Provide a valid field name.

DEVDTE0001	**A field definition requires a name**
Explanation	Each field definition has to have a name.
Action	Provide a name for the field definition.

DEVDTE0002	**A field definition requires a type**
Explanation	Each field definition has to have a type.
Action	Provide a type for the field definition.

DEVDTE0004	**Invalid field annotation**
Explanation	For field definitions, only field-applicable annotations may be specified.
Action	Provide a valid field annotation.

DEVDTE0005	**Type name "{0}" has wrong format**
Explanation	The event type name must follow this pattern: "[a-zA-Z_][a-zA-Z0-9_]*(\.[a-zA-Z_][a-zA-Z0-9_]*)*".
Action	Provide a valid event type name.

DEVDTE0006	**Invalid event annotation**
Explanation	For event types, only event-applicable annotations may be specified.
Action	Provide a valid event annotation.

DEVDTE0007	**Field name "{0}" is not defined in annotation type "{1}".**
Explanation	The field name is not defined in the corresponding annotation type.
Action	Use a differnet field name or define the field name in annotation type.

DEVDTE0008	**Field type for field "{0}" is "{1}" not matching "{2}".**
Explanation	The defined field type does not match the Java type used for an annotation value.
Action	Use a matching Java type.

DEVDTE0009	**Field type for field "{0}" is "{1}" is not matching any allowed field value.**
Explanation	AnnotationTypeDefinition only allows certain field types.
Action	Use a type which is allowed.

DEVDTE0010	**Duplicate annotation "{0}"**
Explanation	The same annotation can be applied multiple times only if the corresponding annotation type is marked as repeatable.
Action	Provide a valid annotation.

DEVDTE0011	**Java object not supported for any: "{0}"**
Explanation	Only Java objects that are supported by the Digital Event Services type system should be provided.
Action	Provide a Java instance of a supported type for an any-defined field.

DEVDTE0012	**Missing annotation type name.**
Explanation	No annotation type name was provided for the building of an annotation type.
Action	Set a name for the annotation type on the annotation type builder.

DEVDTE0013	**Recursive reference to "{0}" not allowed**
Explanation	Digital Event Types do not allow recursive type references, neither dirctly, nor indirectly.
Action	Provide a valid type reference.

DEVDTE0014	**An array must not contain another array.**
Explanation	It is not possible to define an array of arrays.
Action	An array is specified by explicitly defining the dimension.

DEVDTE0017	**The array dimension has to be a positive integer.**
Explanation	Array dimensions have to be positive integers. For example, specify dimension = 2 in order to construct a string[][].
Action	Provide a valid dimension.

DEVDTE0019	**Field "{0}" is not defined for type "{1}".**
Explanation	The type for the event does not contain the field.The type does not contain the field.
Action	Set or get a field that is defined for the type of the event.

DEVDTE0020	**Field "{0}" in event type "{1}" has field type "{2}" in event type variant "{3}", and field type "{4}" in event type variant "{5}".**
Explanation	The field types for a field are not matching.
Action	Consider using another event type variant for accessing the event.

DEVDTE0021	**The reserved package name "{0}" must not be used**
Explanation	The Digital Event Services system uses the reserved package name for internal purposes.
Action	Provide a valid package name.

DEVDTE0022	**Transmission event type "{0}" and subscribing event type "{1}" must be the same.**
Explanation	The event type used for transmission is different from the one that has been subscribed for.
Action	Contact Software AG support.

DEVDTE0024	**The path for the "{0}" annotation "{1}" does not match any field definition.**
Explanation	The paths for the annotations like "EventTime" and "EventId" must point to an existing field.
Action	Correct the path value of the annotation.

DEVDTE0025	**The field corresponding to event time path "{0}" is not a time field.**
Explanation	The event time path must point to an existing time field.
Action	Correct the path value of the EventTime annotation.

DEVDTE0028	**Field "{0}" of event type "{1}" contains an unresolved reference to event type "{2}".**
Explanation	This should not happen because only valid event type models are stored to the repository. However, the referenced type is no longer available in the repository in the case that it has been deleted from it.
Action	Correct the invalid event type or add the referenced event type to the repository.

DEVDTE0030	**The unique event type "{0}" has different variants.**
Explanation	A unique event type should only exist in one variant.
Action	Use only one variant of a unique event type.

DEVDTE0031	**Variants of Event Type "{0}" differ in "unique" setting.**
Explanation	If an event type is "unique", there cannot exist another variant of the same event type which is not "unique".
Action	Define an event type as "unique" or use it with variants.

DEVDTE0032	**The type name "{0}" does not have a package**
Explanation	Each event type name needs to be qualified with a package.
Action	Provide a valid type name.

DEVDTE0033	**The event type "{0}" and the nested event type "{1}" should have the same uniqueness setting**
Explanation	If an event type is marked as "unique", it can only refer to other "unique" event types. Vice versa, a "non-unique" event type can only refer to other "non-unique" event types.
Action	Correct the uniqueness setting.

DEVDTE0035	**Cannot access the field "{0}" of unknown type "{1}" in event type "{2}"**
Explanation	The data type of the field is not known to the current runtime, therefore the field value cannot be accessed.
Action	Specify a field with a known data type.

DEVDTE0049	**No variant key allowed for unique referenced event type "{0}".**
Explanation	In case of a uniquely defined event type, variant keys must not be specified in an event type reference:\nInvalid field definition: "F1 : event : package.unique_eventtype("<variant key>");"\nCorrect field definition: "F1 : event : package.unique_eventtype;"\n\n(* Uniquely defined event types contain a @Unique" annotation on event level.)\n(* The variant key is a hexadecimal 16-digit value, which is automatically added to the file name in the repository.)
Action	Remove the variant key and just specify the fully qualified event type name:F1 : event : package.unique_eventtype;

DEVDTE0050	**Variant key necessary for non-unique referenced event type "{0}".**
Explanation	In case of a non-uniquely defined event type, a variant key must be specified in an event type reference.\nInvalid field definition: "F1 : event : package.nonunique_eventtype;"\nCorrect field definition: "F1 : event : package.nonunique_eventtype("<variant key>");"\n\n(* Non-uniquely defined event types don't contain a "@Unique" annotation on event level.)\n(* The <variant key> is a hexadecimal 16-digit value, which is automatically added to the file name in the repository.)
Action	Add the variant key behind the fully qualified event type name:\n"F1 : event : package.nonunique_eventtype("<variant key>");"

DEVDTE0051	**Unknown type found: {0}**
Explanation	The any field contains an unknown type or type id, that cannot be read. Maybe the event has been created in a later product version.
Action	This is an internal error. Please contact your support organization.

DEVDTE0052	**Event type "{0}" cannot be resolved.**
Explanation	The event type cannot be resolved.
Action	Deploy the missing event type to the repository.

DEVDTE0053	**Event type "{0}" not sufficient for building Protobuf descriptor.**
Explanation	A required event type cannot be read from the repository.
Action	Deploy the missing event type to the repository.

DEVDTI0015	**Annotation field name "{0}" has wrong format.**
Explanation	The annotation field name must follow this pattern: "[a-zA-Z_][a-zA-Z0-9_]*".
Action	Provide a valid annotation field name.

DEVDTI0016	**Annotation type name "{0}" has wrong format.**
Explanation	The annotation type name must follow this pattern: "[a-zA-Z_][a-zA-Z0-9_]*(\.[a-zA-Z_][a-zA-Z0-9_]*)*".
Action	Provide a valid annotation type name.

15 Event-Driven Architecture Tools Messages

EDAERBCE0000 **The service group name must not be empty**

Explanation Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.

Action Specify a valid and unique name for the service group.

EDAERBCE0001 **A service group with the name "{0}" already exists.**

Explanation Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.

Action Specify a unique service group name.

EDAERBCE0002 **Invalid service group name "{0}". It must follow the rule: <alpha character>+(<word character> | - | .)***

Explanation Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, a lower or upper case character, and <alpha character> can be a lower or upper case character.

Action Specify a valid service group name which follows the rule of service group names.

EDAERBCE0003	**Invalid service group name "{0}" because it is different from the created unique instance name "{1}" which is used for the configuration persistence.**
Explanation	Each service group must have a valid and unique name. The name must be unique in the namespace of all service groups. The service group name must follow the rule: <word character>+(<word character> | - | . | _)* where <word character> can be a digit, a lower or upper case character.
Action	Specify a valid service group name where service group name must be the same as the unique instance name.

EDAERBCE0004	**The default service group must not be deleted**
Explanation	The default service group name is "Default". This group covers all event types which are not associated to other service groups, therefore the "Default" service group cannot be deleted.
Action	Do not delete the "Default" service group.

EDAERBCE0006	**The default service group must not be renamed**
Explanation	The default service group name is "Default". This group covers all event types which are not associated to other service groups, therefore the "Default" service group cannot be renamed.
Action	Do not rename the "Default" service group.

EDAERBCE0007	**The service group "{0}" is still referenced by an event type e.g. "{1}"**
Explanation	A service group can only be deleted if no event types are associated to it.
Action	Remove all event types associations to the service group before deleting it.

EDAERBCE0008	**The service group "{0}" contains duplicate service entries: "{1}"**
Explanation	Each service group must contain at least one service. The list of services within a service group must contain only unique services.
Action	Use only unique services within a service group.

EDAERBCE0009	**The service group "{0}" must contain at least one service**
Explanation	Each service group must contain at least one service. The list of services within a service group must contain only unique services.
Action	Assign at least one service to the service group.

EDAERBCE0010	**The referenced service "{0}" does not exist**
Explanation	The specified service does not exist and cannot be assigned to a service group.
Action	Choose a valid service in order to assign it to a service group.

EDAERBCE0011	**In the group "{0}" only one service can be marked as "source"**
Explanation	Only one service within a service group can be specified as "source".
Action	Mark only one service as "source".

EDAERBCE0012	**Service type name not found for service "{0}" in group "{1}"**
Explanation	A service with invalid service type has been specified within a certain service group.
Action	Use a service with a valid service type. Only valid services may be assigned to a service group.

EDAERBCE0013	**Service type not found for service "{0}" in group "{1}"**
Explanation	A service with invalid service type has been specified within a certain service group.
Action	Use a service with a valid service type. Only valid services may be assigned to a service group.

EDAERBCE0014	**The service "{0}" is marked as "source", however the corresponding service type "{1}" cannot act as source**
Explanation	The parameters of each service depend on its service type definition. If the service type is not configured to act as source, then the services of that type cannot be configured as "source" either.
Action	Remove the "source" marker from the service definition or change the configuration of the service type in order to allow the "source" marker.

EDAERBCE0015	**The service "{0}" is marked as "reliable", however the corresponding service type "{1}" does not support reliable**
Explanation	The parameters of each service depend on its service type definition. If the service type is not configured to support reliable delivery, then the services of that type cannot be configured as "reliable" either.
Action	Remove the "reliable" marker from the service definition or change the configuration of the service type in order to allow the "reliable" marker.

EDAERBCE0017	**The service name must not be empty**
Explanation	Each service must have a valid and unique name. A service name must follow the rule: <word character>+(<word character> | - | .)* where <word character> can be a digit, lower or upper character.
Action	Specify a valid name for the service.

EDAERBCE0018	**A service with the name "{0}" already exists.**
Explanation	Each service must have a valid and unique name. A service name must follow the rule: <word character>+(<word character> | - | .)* where <word character> can be a digit, lower or upper character.
Action	Specify a unique name for the service.

EDAERBCE0019	**The service "{0}" is still used by the Service Group "{1}".**
Explanation	A service can only be deleted if it is not included in a service group.
Action	Remove all references to the service before deleting it.

EDAERBCE0020	**Invalid name "{0}". It must follow the rule: <alpha character>+(<word character> | - | .)***
Explanation	A name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, lower or upper character.
Action	Do not use invalid URI characters.

EDAERBCE0021	**Name "{0}" not unique considering the instance IDs. (Not allowed predefined ids: {1}).**
Explanation	Software AG Platform Manager allows only unique instance IDs to be used for the Event Routing runtime component.
Action	Change the name so that is is not identical to any other already existing service names, service group names, or the predefined {1}.

EDAERBCE0024	**Event type "{0}" does not exist**
Explanation	The specified event type is not present in the Event Type Store, and therefore cannot be used in the Service Group Event Types configuration.
Action	Remove the event type from the Service Group Event Types.

EDAERBCE0025	**Duplicate event type "{0}"**
Explanation	The specified event type appears twice in the Service Group Event Types configuration.
Action	Remove the duplicate event type from the Service Group Event Types configuration.

EDAERBCE0026	**The service group "{0}" does not exist**
Explanation	The specified service group does not exist.
Action	Remove the service group from the Service Group Event Types configuration, or create the service group before updating the Service Group Event Types configuration.

EDAERBCE0028	**A service group must not be renamed**
Explanation	A service group name is used as a unique id to reference the service group.
Action	If a new name is required, delete the service group and create a new one. Before deleting the service group make sure that no event types are associated to it.

EDAERBCE0029	**A service must not be renamed**
Explanation	A service name is used as a unique id to reference the service.
Action	If a new name is required, delete the service and create a new one. Before deleting the service make sure it is no longer referenced by any service group.

EDAERBCE0030	**"{0}" is not a valid capacity value**
Explanation	The capacity must consist of digits only, optionally followed by one of [K, k, M, m, G, g]. The resulting value must not be larger than 9223372036854775807.
Action	Provide a valid capacity.

EDAERBCE0032	**The "{0}" service has to be configured as source&destination**
Explanation	This predefined service can only be used as "source and destination".
Action	Configure the service as "source and destination".

EDAERBCE0033	**Cannot use reserved service name "{0}"**
Explanation	This is the name of a predefined service.
Action	Choose a different service name.

EDAERBCE0038	**It is not possible to change storage location, while instance {0} is running**
Explanation	Please ensure that the component using Event Routing is restarted in order to start using the new storage location.
Action	Changing the storage location requires a restart of the components using Event Routing.

EDAERBCE0040	**The specified path "{0}" is not a valid directory**
Explanation	The path is not an existing directory.
Action	Make sure that the specified directory exists.

EDAERBCE0041	**The specified path "{0}" is not an absolute path.**
Explanation	The path must be specified as an absolute path.
Action	Make sure that the path is specified as an absolute path.

EDAERBCE0042	**The specified path "{0}" does not exist**
Explanation	The path must be a valid folder and it must exist on disk.
Action	Make sure the path location is an existing folder and create it if necessary.

EDAERCE0005	**It is not allowed to create new instances of Runtime Configuration**
Explanation	Only one built-in instance of Runtime Configuration exists.
Action	In order to apply your changes, edit the built-in instance of Runtime Configuration.

EDAERCE0021	**Invalid name "{0}". It must follow the rule: <alpha character>+(<word character> | - | .)***
Explanation	Each service must have a valid and unique name. A service name must follow the rule: <alpha character>+(<word character> | - | .)* where <word character> can be a digit, lower or upper character, and <alpha character> can be a lower or upper case character. The service name is the same as the corresponding instance ID, which is used to identify a service in the configuration persistence. This instance ID must be unique for all instances of Event Routing.
Action	Use a valid service name following the naming rules.

EDAERCE0022	**It is not allowed to create new instances of Service Group Event Types**
Explanation	Only one built-in instance of Service Group Event Types exists.
Action	In order to apply changes, edit the built-in instance of Service Group Event Types.

EDAERCE0023	**It is not allowed to delete the instance of Service Group Event Types**
Explanation	Only one built-in instance of Service Group Event Types exists, and it cannot be be deleted.
Action	In order to apply changes, edit the built-in instance of Service Group Event Types.

EDAERCE0027	**Internal error: the given "RuntimeComponent" parameter is not an instance of the "Instance" interface**
Explanation	This is an internal error.
Action	Contact your support organization.

EDAERCE0031	**It is not allowed to delete the instance of Runtime Configuration**
Explanation	There is only one built-in instance of Runtime Configuration, which must not be deleted.
Action	In order to apply changes, edit the built-in instance of Runtime Configuration.

EDAERCE0041	**Exception from getRuntimeStatus.**

EDAERCE0048	**Registration failed for service type: {0}.**

EDAERCI0043	**ui binding for {0} setup.**

EDAERCI0045	**com.softwareag.event.routing.configuration bundle stopped.**

EDAERCPE0028	**Passed object of RunWatchdog is not valid**
Explanation	During instanciation of one of the RunWatchdog handlers, the RunWatchdog object itself is passed. However, this RunWatchdog object is not valid (null).
Action	Verify that the RunWatchdog object is valid before instanciating the handlers.

EDAERCPE0029	**Default configuration not found**
Explanation	If no event routing configuration is available, all default configuration files are copied to the place where the configuration is expected. However, the zip file containing all these files could not be found. This file is created by calling the "eclipse" task of the project.
Action	Execute the "eclipse" task of the gradle build script beforehand.

EDAERCPE0030	**File {0} is empty! Service {1} is not created and no events can be handled by {1}**
Explanation	The file has no content. A service cannot be created and no events can be sent or received.
Action	Provide a file containing the desired entry or use a graphical configuration such as Software AG Command Central user interface for creating a correct service.

EDAERCPE0031	**{0} contains invalid content {1}**
Explanation	The content is not correct.
Action	Correct the content or use a graphical configuration tool such as Software AG Command Central.

EDAERCW0042	**Service group {0}: IP service set to source&destination.**

EDAERE0002	**Failed to start a subscriber route consuming from URI ''{0}''.**
Explanation	A subscriber cannot be created because of an unavailable source service or an invalid or an already used durable subscriber ID.
Action	Check if the service configured as a source is available. If you are creating a durable subscriber, make sure that its ID does not contain invalid characters, and that no durable subscriber with this ID for the same event type is currently active on the source service.

EDAERE0003	**Failed to start a subscriber route consuming from URI ''{0}'': a durable subscriber with ID ''{1}'' already exists on the IP service.**
Explanation	An IP service durable subscriber cannot be created because of an already used durable subscriber ID.
Action	Make sure that no durable subscriber with this ID for the same event type is currently active on the source IP service.

EDAERE0058	**Failed to delete the service implementation bundle for service name: "{0}".**
Explanation	Undeploying the service from the bundles folder of the configuration failed. Even if the service could not be deleted, this should not prevent the system from running normally.
Action	Delete the service jar file manually if desired.

EDAESE0000	**Failed to create an event parser.**
Explanation	The factory was not able to create an event parser.
Action	Check the log for exception stacktrace.

EDAESIE0004	**The selected Integration Server Document Type is recursive and its conversion results in a recursive Event Type which is not supported.**
Explanation	The Integration Server Document type which has been selected is recursive. After the conversion a recursive Event Type is produced. Recursive Event Types are not supported.
Action	Remove recursion from the Integration Server Document type prior to creating an event type from it.

EDAESIE0006	**Restrictions not supported for {0}**
Explanation	Union and List are not supported for restrictions.
Action	Please contact your software supplier.

EDAESIE0007	**Unsupported facet {0} with value {1}**
Explanation	The called restriction facet is not supported.
Action	Please contact your software supplier.

EDAESIE0029	**Event Types without a target namespace are not allowed outside the root "Event Types" directory.**
Explanation	An event type which does not define target namespace exists outside the root of the event types directrory.
Action	Either move this event type in the "Event Types" directory or manually create a target namespace definition for it.

EDAESIE0034	**Node {0} is not filterable because node {1} is not of cardinality 0..1 or 1..1.**
Explanation	The node is not filterable, since the node path can have several values (and not only a unique one).
Action	Set the node to not filterable, or set the cardinality of all nodes on the node path to cardinality 1..1.

EDAESIE0035	**Node {0} is not filterable because nodes {1} are not of cardinality 0..1 or 1..1.**
Explanation	The node is not filterable, since the node path can have several values (and not only a unique one).
Action	Set the node to not filterable, or set the cardinality of all nodes on the node path to cardinality 1..1.

EDAETE0211	**Event Types without a target namespace are not allowed outside the root "Event Types" directory.**
Explanation	An event type which does not define target namespace exists outside the root of the event types directrory.
Action	Either move this event type in the "Event Types" directory or manually create a target namespace definition for it.

EDAETE0213	**Cannot build editor tree.**
Explanation	A unexpected error occurred while building the editor tree.
Action	Make sure the event type schema is correctly defined.

EDAETE0214	**Cannot provide children in node tree.**
Explanation	Unexpected error while getting the child nodes in a node tree.
Action	Make sure the event type schema is correctly defined.

EDAISE0012	**The selected IS Document Type is recursive and its conversion results in a recursive Event Type which is not supported.**
Explanation	The IS Document type which has been selected is recursive. After the conversion a recursive Event Type is produced. Recursive Event Types are not supported.
Action	Remove recursion from the IS Document type prior to creating an event type from it.

16 Event Persistence Messages

EVSECM172E0000 **Invalid Event Persistence Elasticsearch URI format: {0}**

Explanation The Elasticsearch URI was specified using an invalid or unexpected format.

EVSECM172E0001 **Error creating Elasticsearch transport client for URI: {0}**

Explanation There was an error creating the Elasticsearch client and connecting to the cluster using the specified URI.

EVSECM172E0002 **Error creating Elasticsearch transport client for cluster name {0} and host(s) {1}**

Explanation There was an error creating the Elasticsearch client and connecting to the cluster using the specified URI.

EVSECM232E0000 **Invalid Event Persistence Elasticsearch URI format: {0}**

Explanation he Elasticsearch URI was specified using an invalid or unexpected format.

EVSECM232E0001 **Error creating Elasticsearch transport client for URI: {0}**

Explanation There was an error creating the Elasticsearch client and connecting to the cluster using the specified URI.

EVSECM232E0002 **Error creating Elasticsearch transport client for cluster name {0} and host(s) {1}**

Explanation There was an error creating the Elasticsearch client and connecting to the cluster using the specified URI.

EVSECM564E0000 **Invalid Event Persistence Elasticsearch URI format: {0}**

Explanation Invalid Event Persistence Elasticsearch URI format

EVSECM564E0001 **Error creating Elasticsearch transport client version 5.6.4 for URI {0}**

Explanation Error creating Elasticsearch transport client version 5.6.4 for URI {0}

Action Check your connection to the elasticsearch node and your transport client settings.

EVSECM564E0002 **Error creating Elasticsearch transport client for cluster name {0} and host {1}**

Explanation Error creating Elasticsearch transport client for cluster name {0} and host {1}

Action Check your connection to the elasticsearch node, transport client settings, and cluster name and host.

EVSECME0000 **Error creating Elasticsearch transport client for URI: {0}**

EVSECME0001 **Error creating Elasticsearch transport client for cluster name {0} and host(s) {1}**

EVSECME0002 **Invalid Event Persistence Elasticsearch URI format: {0}**

EVSEDSE0000 **Cannot get EDA event type schema parser.**

Explanation Cannot get EDA event type schema parser.

EVSEDSE0001 **Cannot get event type store at location: {0}**

Explanation Cannot get event type store at the given location.

Action Please make sure that the event type store location is valid.

EVSEDSE0002 **Non-default ETS locations are not currently supported in OSGi {0}**

EVSEDSE0003 **Timeout waiting for blueprint injection of EDA interface provider**

Explanation The timeout expired when waiting for EDA ETS/XSD services

EVSEQF232E0000	**A error occurred when trying to instantiate the Elasticsearch 2.3.2 Query Session implementation class.**
Explanation	The factory implementation could not create an instance of the query session class.
Action	Contact Global Support.

EVSEQF232E0001	**Query implementation library found in multiple locations: {0}**
Explanation	The implementation library was found in multiple locations on the server or installation directory. In this situation, the factory can not determine the proper installation directory based on the library location.
Action	Contact Global Support.

EVSEQF232E0002	**Could not find query implementation library while determining installation directory.**
Explanation	In Non-OSGi environments the factory loads its third party dependencies from a whitelist. It must first determine the installation directory. This is done by searching for the implementation jar in the Software_AG_Directory\common\EventPersistence folder. This error indicates that the library could not be found.
Action	Contact Global Support.

EVSEQF232E0003	**The property dep.common.dir is set to a non-existent directory: {0}**
Explanation	The system property dep.common.dir must be set to a valid Software_AG_Directory/common/EventPersistence directory location.
Action	Contact Global Support.

EVSEQF232E0004	**The property dep.common.dir has not been set before you use this component.**
Explanation	The system property dep.common.dir is required and must be set to the location of the Software_AG_Directory/common/EventPersistence directory.
Action	Contact Global Support.

EVSEQF564E0000	**A error occurred when trying to instantiate the Elasticsearch 5.6.4 Query Session implementation class.**
Explanation	The factory implementation could not create an instance of the query session class.
Action	Contact Global Support.

EVSEQF564E0001	**Query implementation library found in multiple locations: {0}**
Explanation	The implementation library was found in multiple locations on the server or installation directory. In this situation, the factory can not determine the proper installation directory based on the library location.
Action	Contact Global Support.

EVSEQF564E0002	**Could not find query implementation library while determining installation directory.**
Explanation	In Non-OSGi environments the factory loads its third party dependencies from a white-list. It must first determine the installation directory. This is done by searching for the implementation jar in the Software_AG_Directory/common/EventPersistence folder. This error indicates that that library could not be found.
Action	Contact Global Support.

EVSEQF564E0003	**The property dep.common.dir is set to a non-existent directory: {0}**
Explanation	The system property dep.common.dir must be set to a valid Software_AG_Directory/common/EventPersistence directory location.
Action	Contact Global Support.

EVSEQF564E0004	**The property dep.common.dir has not been set prior to using this component.**
Explanation	The system property dep.common.dir is required and must be set to the location of the Software_AG_Directory/common/EventPersistence directory.
Action	Contact Global Support.

EVSEQI172E0000	**Unsupported syntax found in aggregate function clause: {0}**
Explanation	The syntax of the aggregate expression is incorrect. This error should never occur because the grammar has already been validated. It's included for proper error handling.

EVSEQI172E0001	**Unsupported encoding exception encountered when formatting result**
Explanation	The default utf-8 encoding was not supported in this environment. The result body could not be added to the result set.

EVSEQI172E0002 **An error has occurred because the response reference has not been set in response handler**

Explanation This is a programming class usage issue. This error shouldn't be experienced once the implementation is tested and verified.

EVSEQI172E0003 **Unexpected statement type found when trying to determine query builder implementation**

Explanation The query builder examines the statement to determine if its an instance or aggregate query. In this case the implementation couldn't identify the statement type.

EVSEQI172E0004 **Error executing full text query due to invalid query filter**

Explanation The query filter could not be transformed and used in the Elasticsearch query.

EVSEQI172E0005 **An unsupported encoding exception was thrown while generating query hit.**

Explanation The default encoding of utf-8 was not available and the query hit document could not be processed.

EVSEQI172E0006 **An unsupported encoding exception was thrown while generating explain message**

Explanation The default encoding of utf-8 was not available to format the explain plan message

EVSEQI172E0007 **Error creating full text query for explain plan due to invalid query filter.**

Explanation The explain plan content could not be generated due to a parsing error in the filter syntax

EVSEQI172E0010 **Error transforming query to native Elasticsearch request!%n{0}**

Explanation The query as specified in the Common Query Syntax could not be transformed into a native Elasticsearch query.

EVSEQI172E0011 **Error executing native Elasticsearch search request!%n{0}**

Explanation An error occurred during execution of the Elastisearch query.

EVSEQI172E0012 **Error transforming query to native Elastisearch request for explain plan**

Explanation The query as expressed in the Common Query Syntax could not be transformed into an Elasticsearch request when creating the explain plan.

EVSEQI172E0013 **An unsupported encoding exception was thrown while generating explain message**

Explanation The default encoding of utf-8 is not availble and caused an exception when generating the explain plan text.

EVSEQI172E0014 **Query session has been created with invalid context for this implementation**

Explanation The context must include all of the required parameters for this query implementation.

EVSEQI172E0015 **Error creating a transport client connection to Elasticsearch cluster**

Explanation A connection to the Elasticsearch cluster could not be established.

EVSEQI172E0016 **Failed to position cursor at next event in the result stream**

Explanation An exception was thrown when trying to move the cursor to the next position in the result stream.

EVSEQI172E0017 **The method {0} is unsupported in this implementation of ResultStream**

Explanation The ResultStream inteface only requires that all implementations provide a next operation.

EVSEQI172E0018 **Error getting result at current cursor position from handler**

Explanation An exception was thrown when attempting to get the event data from the current position in the result stream.

EVSEQI172I0008 **Inbound query in common syntax form:**

EVSEQI172I0009 **Outbound query in native form:**

EVSEQI232E0000 **Unsupported syntax found in aggregate function clause: {0}**

Explanation The syntax of the aggregate expression is incorrect. This error should never occur because the grammar has already been validated. It's included for proper error handling.

EVSEQI232E0001 **Unsupported encoding exception encountered when formatting result**

Explanation The default utf-8 encoding was not supported in this environment. The result body could not be added to the result set.

EVSEQI232E0002 **An error has occurred because the response reference has not been set in response handler**

Explanation This is a programming class usage issue. This error shouldn't be experienced once the implementation is tested and verified.

EVSEQI232E0003 **Unexpected statement type found when trying to determine query builder implementation**

Explanation The query builder examines the statement to determine if its an instance or aggregate query. In this case the implementation couldn't identify the statement type.

EVSEQI232E0004 **Error executing full text query due to invalid query filter**

Explanation The query filter could not be transformed and used in the Elasticsearch query.

EVSEQI232E0005 **An unsupported encoding exception was thrown while generating query hit.**

Explanation The default encoding of utf-8 was not available and the query hit document could not be processed.

EVSEQI232E0006 **An unsupported encoding exception was thrown while generating explain message**

Explanation The default encoding of utf-8 was not available to format the explain plan message

EVSEQI232E0007 **Error creating full text query for explain plan due to invalid query filter.**

Explanation The explain plan content could not be generated due to a parsing error in the filter syntax

EVSEQI232E0010 **Error transforming query to native Elasticsearch request:%n{0}**

Explanation The query as specified in the Common Query Syntax could not be transformed into a native Elasticsearch query.

EVSEQI232E0011 **Error executing native Elasticsearch search request:%n{0}**

Explanation An error occurred during execution of the Elastisearch query.

EVSEQI232E0012 **Error transforming query to native Elastisearch request for explain plan**

Explanation The query as expressed in the Common Query Syntax could not be transformed into an Elasticsearch request when creating the explain plan.

EVSEQI232E0013 **An unsupported encoding exception was thrown while generating explain message**

Explanation The default encoding of utf-8 is not availble and caused an exception when generating the explain plan text.

EVSEQI232E0014 **Query session has been created with invalid context for this implementation**

Explanation The context must include all of the required parameters for this query implementation.

EVSEQI232E0015 **Error creating a transport client connection to Elasticsearch cluster**

Explanation A connection to the Elasticsearch cluster could not be established.

EVSEQI232E0016 **Failed to position cursor at next event in the result stream**

Explanation An exception was thrown when trying to move the cursor to the next position in the result stream.

EVSEQI232E0017 **The method {0} is unsupported in this implementation of ResultStream**

Explanation The ResultStream inteface only requires that all implementations provide a next operation.

EVSEQI232E0018 **Error getting result at current cursor position from handler**

Explanation An exception was thrown when attempting to get the event data from the current position in the result stream.

EVSEQI232I0008 **Inbound query in common syntax form:**

EVSEQI232I0009 **Outbound query in native form:**

EVSEQI564E0000 **Unsupported syntax found in aggregate function clause: {0}**

Explanation Unsupported syntax found in aggregate function clause: {0}

EVSEQI564E0001 **Unsupported encoding exception encountered when formatting result**

Explanation Unsupported encoding exception encountered when formatting result

EVSEQI564E0002 **An error has occurred because the response reference has not been set in response handler**

Explanation An error has occurred because the response reference has not been set in response handler

EVSEQI564E0003 **Unexpected statement type found when trying to determine query builder implementation**

Explanation Unexpected statement type found when trying to determine query builder implementation

EVSEQI564E0004 **Error executing full text query due to invalid query filter.**

Explanation Error executing full text query due to invalid query filter.

EVSEQI564E0005 **An unsupported encoding exception was thrown while generating query hit.**

Explanation An unsupported encoding exception was thrown while generating query hit.

EVSEQI564E0006 **An unsupported encoding exception was thrown while generating explain message**

Explanation An unsupported encoding exception was thrown while generating explain message

EVSEQI564E0007 **Error creating full text query for explain plan due to invalid query filter.**

Explanation Error creating full text query for explain plan due to invalid query filter.

EVSEQI564E0010 **Error transforming query to native Elasticsearch request!%n{0}**

Explanation Error transforming query to native Elasticsearch request!%n{0}

EVSEQI564E0011 **Error executing native Elasticsearch search request!%n{0}**
Explanation Error executing native Elasticsearch search request!%n{0}

EVSEQI564E0012 **Error transforming query to native Elastisearch request for explain plan**
Explanation Error transforming query to native Elastisearch request for explain plan

EVSEQI564E0013 **An unsupported encoding exception was thrown while generating explain message**
Explanation An unsupported encoding exception was thrown while generating explain message

EVSEQI564E0014 **Query session has been created with invalid context for this implementation**
Explanation Query session has been created with invalid context for this implementation

EVSEQI564E0015 **Error creating a transport client connection to Elasticsearch cluster**
Explanation Error creating a transport client connection to Elasticsearch cluster

EVSEQI564E0016 **Failed to position cursor at next event in the result stream**
Explanation Failed to position cursor at next event in the result stream

EVSEQI564E0017 **The method {0} is unsupported in this implementation of ResultStream**
Explanation The method {0} is unsupported in this implementation of ResultStream

EVSEQI564E0018 **Error getting result at current cursor position from handler**
Explanation Error getting result at current cursor position from handler

EVSEQIE0000 **Query session has been created with invalid context for this implementation**

EVSEQIE0001 **Error creating a transport client connection to Elasticsearch cluster**

EVSEQIE0002 **Error transforming query into native Elasticsearch request!%c{0}**

EVSEQIE0003 **Error executing native Elasticsearch search request!%c{0}**

EVSEQIE0004 **Failed to position cursor at next event in the result stream**

Explanation There was an error when moving the cursor position forward in the stream

EVSEQIE0005 **The method {0} is unsupported in this implementation of ResultStream**

Explanation The only requirement on a ResultStream implementation is that they provide a forward cursor via the next method

EVSEQIE0006 **Error getting result at current cursor position from handler**

Explanation There was an error retrieving or formating the result at the cursor position

EVSEQIE0007 **Unexpected statement type found when trying to determine query builder implementation**

Explanation The query transformation found an expression other than an instance, property list or aggregate query.

EVSEQIE0008 **Unsupported syntax found in aggregate function clause: {0}**

Explanation When processing an aggregation other than count, sum, avg, min or max was found.

EVSEQIE0009 **Unsupported encoding exception encountered when formatting result**

EVSEQIE0010 **An error has occurred because the response reference has not been set in response handler**

Explanation This is a fatal programming error; the Elasticsearch response reference was not set before invoking the handler methods.

EVSEQIE0011 **Cursor positioning error; No pending results on result stack**

Explanation The getResult method was invoked but there is no pending result item on the cursor stack.

EVSEQIE0013 **An unsupported encoding exception was thrown while generating explain message**

Explanation An error was encountered when creating a byte array with utf8 encoding

EVSEQIE0016 **Error executing full text query due to invalid query filter.**

EVSEQIE0017 **An unsupported encoding exception was thrown while generateing query hit.**

EVSEQII0014 **Inbound query in common syntax form:**

EVSEQII0015 **Outbound query in native form:**

EVSEQIW0012 **Error transforming query for explain plan**

Explanation The query transformation failed during processing of the explain plan call.

EVSEREE0001 **Event Routing Consumers are not supported by this Endpoint implementation**

Explanation Event Persistence components only support producers

EVSEREE0002 **Synchronous Event processing is not supported by this component.**

Explanation This component only supports asynchronous processing.

EVSEREE0003 **Error initializing required internal resources**

Explanation Internal resources such as the transformer or storage provider could not be initialized.

EVSEREE0004 **Error transforming event instance from native format to JSON format**

Explanation An error occurred during transformation from XML to JSON

EVSEREE0005 **Fatal exception thrown from storage provider during event processing**

Explanation An error occurred when trying to persist the current event

EVSEREE0006 **Error creating storage type definition for event type: {0}**

Explanation The event type schema could not be transformed to the storage type definition required by the storage providers.

EVSEREE0007 **Error parsing event schema with namespace {0} and event type {1}**

Explanation The EDA event type schema for the specified type could not be parsed.

EVSEREE0008 **Error creating schema parser with Event Type Store location: {0}**

Explanation A reference to the EDA schema parser class or service could not be obtained.

EVSERSE0000 **Port {0} should be a non-negative and non-zero integer value.**

Explanation Port should be a non-negative integer value.

EVSERSE0001 **{0} must be all lower case.**

Explanation Index Name must be all lower case..

EVSERSE0003 **must be a non-negative non-zero integer.**

Explanation Thread Pool Keep Alive Time must be a non-negative integer and non-zero integer.

EVSERSE0006 **must be a non-negative integer.**

Explanation Thread Pool Queue size must be a non-negative integer.

EVSERSE0009 **must be a non-negative and non-zero integer.**

Explanation Batch size must be a non-negative and non-zero integer.

EVSERSE0010 **must be a non-negative and non-zero integer.**

Explanation Batch write time must be a non-negative and non-zero integer.

EVSERSE0011 **Event Persistence does not support storage type: {0}.**

Explanation This is not supported store type for event persistence.

EVSERSE0012 **Can't create service bundle for storage type: {0}.**

Explanation The service bundle could not be created!

EVSERSE0013 **Pool size must be a non-negative integer.**

Explanation Core Thread Pool size must be a non-negative integer.

EVSERSE0014 **Not supported storage type {0}.**

EVSERSE0015 **must be a non-negative and non-zero integer.**

Explanation Hdfs maximum file size must be a non-negative and non-zero integer.

EVSERSE0016 **Pool Size must be a non-negative and non-zero integer.**

Explanation Maximum Thread Pool Size must be a non-negative and non-zero integer.

EVSERSE0017 **Elasticsearch keystore filepath is not valid.**

Explanation Elasticsearch keystore filepath is not valid.

EVSERSE0018 **Elasticsearch truststore filepath is not valid.**

Explanation Elasticsearch truststore filepath is not valid.

EVSERSE0019 **Key store should not be blank**

Explanation Key store should not be blank

EVSERSE0020 **Trust store should not be blank**

Explanation Trust store should not be blank

EVSERSE0025 **{0} must be specified using the following format: {1}.**

Explanation URI must be specified using the given format.

EVSERSE0028 **is invalid Hive Warehouse Location.**

Explanation Hive Warehouse Location is invalid, please enter a valid location name.

EVSERSI0017 **Event Persistence Configuration Validation Information**

Explanation Display Label used for Event Persistence Configuraiton Validation Information UI

EVSERSI0018 **Connection to Elasticsearch node succeeded:**

Explanation Successfully connected to the specified Elasticsearch cluster, index, host and port.

EVSERSI0026 **Connection to HDFS succeeded.**

Explanation Connection to HDFS succeeded.

EVSERSI0029 **Connection to Hive server succeeded.**

Explanation Connection to Hive server succeeded.

EVSERSW0019 **Could not connect to Elasticsearch node:**

Explanation Could not connect to the specified elasticsearch cluster node, index, host and port.

EVSERSW0020 **Could not connect to Hive server:**

Explanation Could not connect to the specified Hive server.

EVSERSW0021 **Could not connect to HDFS:**

Explanation Could not connect to the specified HDFS database, hive warehouse location,

EVSERSW0022 **Cannot get JMX MBeanServer Connector for Runtime Componenent {0}.**

Explanation Cannot get JMX MBeanServer Connector to the runtime component.

EVSERSW0023 **JMX MBeanServer invocation exception to remote runtime component {0}.**

Explanation JMX MBeanServer invocation exception to remote runtime component.

EVSERSW0024 **Cannot get JMX Connector for remote runtime component {0}.**

Explanation Cannot get JMX Connector for remote runtime component.

EVSERSW0025 **Cannot ping single SSL enabled elasticsearch node**

Explanation Cannot ping single SSL enabled elasticsearch node

EVSESEE0000 **No onfiguration passed into this service.**

EVSESEE0001 **Synchronous Event processing is not supported by this component.**

Explanation Synchronous Event processing is not supported by this component.

EVSESEE0002 **Error initializing required internal resources**

Explanation Error initializing required internal resources

EVSESEE0003 **Error stopping internal resource {0}**

EVSESEE0004 **Error transforming event instance from native format to JSON format**

Explanation Error transforming event instance from native format to JSON format

EVSESEE0005 **Cannot transforming event {0} instance from native format to JSON format and cannot persist the event into Event Persistence error table.**

Explanation Cannot transforming event {0} instance from native format to JSON format and cannot persist the event into Event Persistence error table.

EVSESEE0006 **Fatal exception thrown from storage provider during processing event {0}.**

Explanation Fatal exception thrown from storage provider during event processing.

EVSESEE0007 **Error creating storage type definition for event type: {0}**

Explanation Error creating storage type definition for the given event type.

EVSESEE0008 **DES Event Type {0} has not been registered in Digital Event Type TypeRepository.**

Explanation DES Event Type has not been registered in Digital Event Type TypeRepository.

EVSESEE0009 **Invalid Configuration class type {0}. : Expected type: {1}.**

Explanation Invalid Configuration class type.

EVSESEE0010 **'{0}' Digital Event Data Type for event field '{1}' is not supported.**

Explanation Given Digital Event Data Type is not supported.

EVSESEE0011 **Error initializing required internal resources; a restart may be required**

Explanation The required resources could not be initialized. This could be due to a wiring or classpath issue.

EVSESEE0012 **A fatal and unexpected exception was thrown when creating the generic storage event instance.**

Explanation A storage event implementation could not be instantiated from the DES event instance.

EVSESEE0013 **Event Persistence Sender is shutting down; events can't be processed in this state.**

Explanation An event was sent for processing while the sender was in the process of stopping.

Action No action. If store forward is enabled the event will be reprocessed; if not an error will be raised.

EVSESF232E0000 **A error occurred when trying to instantiate the Elasticsearch 2.3.2 Storage Provider implementation.**

Explanation The factory could not create an instance of the storage provider implementation. This error could be related to feature provisioning or a class path issue.

Action Contact Global Support.

EVSESF232E0001 **Could not find storage provider implementation library to determine installation directory.**

Explanation In Non-OSGi environments the factory loads its third party dependencies from a whitelist. It must first determine the installation directory. This is done by searching for the implementation jar in the common Software_AG_Directory\common\EventPersistence folder. This error indicates that that library could not be found.

Action Verify that the Digital Event Persistence libraries were selected during the installation.

EVSESF232E0002	**Storage provider implementation library found in multiple locations: {0}**
Explanation	The implementation library was found in multiple locations on the server or installation directory. In this situation, the factory can not determine the proper installation directory based on the library location.
Action	Check the installation directory.

EVSESF232E0003	**The property dep.common.dir is set to a non-existent directory: {0}**
Explanation	The system property dep.common.dir must be set to a valid Software_AG_Directory/common/EventPersistencet directory location.
Action	Contact Global Support.

EVSESF232E0004	**The property dep.common.dir has not been set prior to using this component.**
Explanation	The system property dep.common.dir is required and must be set to the location of the Software_AG_Directory/common/EventPersistencet directory.
Action	Contact Global Support.

EVSESF564E0000	**A error occurred when trying to instantiate the Elasticsearch 5.6.4 Storage Provider implementation.**
Explanation	A error occurred when trying to instantiate the Elasticsearch 5.6.4 Storage Provider implementation.
Action	Contact Global Support.

EVSESF564E0001	**Could not find storage provider implementation library to determine installation directory.**
Explanation	In Non-OSGi environments the factory loads its third party dependencies from a whitelist. It must first determine the installation directory. This is done by searching for the implementation jar in the Software_AG_Directory/common/EventPersistence folder. This error indicates that that library could not be found.
Action	Verify that the Digital Event Persistence libraries were selected during the installation.

EVSESF564E0002	**Storage provider implementation library found in multiple locations: {0}**
Explanation	The implementation library was found in multiple locations on the server or installation directory. In this situation, the factory can not determine the proper installation directory based on the library location.
Action	Check the installation directory.

EVSESF564E0003	**The property dep.common.dir is set to a non-existent directory: {0}**
Explanation	The system property dep.common.dir must be set to a valid Software_AG_Directory/common/EventPersistence directory location.
Action	Contact Global Support.

EVSESF564E0004	**The property dep.common.dir has not been set prior to using this component.**
Explanation	The system property dep.common.dir is required and must be set to the location of the Software_AG_Directory/common/EventPersistence directory.
Action	Contact Global Support.

EVSESFE0000	**Port {0} should be a non-negative and non-zero integer value.**
Explanation	Port should be a non-negative and non-zero integer.

EVSESFE0001	**must be a non-negative integer.**
Explanation	Thread Pool Keep Alive Time must be a non-negative integer.

EVSESFE0002	**must be a non-negative and non-zero integer.**
Explanation	Batch size must be a non-negative and non-zero integer.

EVSESFE0003	**must be a non-negative and non-zero integer.**
Explanation	Batch write time must be a non-negative and non-zero integer.

EVSESFE0004	**Event Persistence does not support storage type: {0}.**
Explanation	This is not supported storage type for Event Persistence.

EVSESFE0005	**must be a non-negative and non-zero integer.**
Explanation	Thread Pool Queue size must be a non-negative and non-zero integer.

EVSESFE0006	**must be a non-negative integer.**
Explanation	Core Thread Pool size must be a non-negative integer.

EVSESFE0007 **must be a non-negative and non-zero integer.**

Explanation Hdfs maximum file size must be a non-negative and non-zero integer.

EVSESFE0008 **Pool Size must be a non-negative and non-zero integer.**

Explanation Maximum Thread Pool Size must be a non-negative and non-zero integer.

EVSESFE0016 **{0} must be specified using the following format: {1}.**

Explanation URI must be specified using the given format.

EVSESFE0018 **{0} must be all lower case.**

Explanation Index name must be in all lower case.

EVSESFE0019 **Elasticsearch keystore filepath is not valid.**

Explanation Elasticsearch keystore filepath is not valid.

EVSESFE0020 **Elasticsearch truststore filepath is not valid.**

Explanation Elasticsearch truststore filepath is not valid.

EVSESFE0021 **is invalid Hive Warehouse Location.**

Explanation Hive Warehouse Location is invalid, please enter a valid location name.

EVSESFI0009 **Connection to HDFS succeeded.**

Explanation Connection to HDFS succeeded.

EVSESFI0017 **Connection to Hive server succeeded.**

Explanation Connection to Hive server succeeded.

EVSESFI0022 **Connection to Elasticsearch node succeeded:**

Explanation Connection to specific Elasticsearch succeeded.

EVSESFW0010 **Could not connect to Elasticsearch node:**

Explanation Could not connect to the specified elasticsearch cluster node, index, host and port.

EVSESFW0011 **Could not connect to Hive server:**

Explanation Could not connect to the specified Hive server.

EVSESFW0012 **Could not connect to HDFS:**

Explanation Could not connect to the specified HDFS database, hive warehouse location.

EVSESFW0013 **Cannot get JMX MBeanServer Connector for Runtime Componenent {0}.**

Explanation Cannot get JMX MBeanServer Connector to the runtime component.

EVSESFW0014 **JMX MBeanServer invocation exception to remote runtime component {0}.**

Explanation JMX MBeanServer invocation exception to remote runtime component.

EVSESFW0015 **Cannot get JMX Connector for remote runtime component**

Explanation Cannot get JMX Connector for remote runtime component.

EVSESI172E0000 **Process method called before provider has been started**

Explanation This is a programatic initialization error. The storage providers start method was not called during initialization.

EVSESI172E0001 **Error initializing required internal resources**

Explanation An error occurred during initialization of the various implementation classes for this storage provider.

EVSESI172E0002 **Error creating or accessing bulk indexer for event type: {0}**

Explanation A bulk indexer instance could not be accessed or created for the specified event type.

EVSESI172E0003 **Error stopping resource {0} on provider shutdown**

Explanation An internal resource threw an exception while stopping the storage provider.

EVSESI172E0005 **Failed to create Elasticsearch transport client connection to cluster {0}, index {1} on server {2} with user {3}.**

Explanation The client could not establish a connection to the Elasticsearch cluster.

EVSESI172E0006 **Elasticsearch client manager not started for cluster {0}, index {1} on server {2} with user {3}**

Explanation An attempt to get a connection was made before the client manager was started.

EVSESI172E0007 **Error stopping bulk indexer for type: {0}**

Explanation The bulk indexer instance for the specified type threw an exception on shutdown.

EVSESI172E0008 **Error creating Elasticsearch bulk indexing request**

Explanation An error occurred while formatting an Elasticsearch bulk indexing request for the current event batch

EVSESI172E0009 **Error executing Elasticsearch bulk indexing request**

Explanation The Elasticsearch bulk indexing request for the specified event batch could not be executed.

EVSESI172E0010 **Error loading metadata for persistence error type; logging to local file**

Explanation Metadata for the persistence error type couldn't be found or created. All messages will be logged to the local log file.

EVSESI172E0011 **Unable to write internal persistence error event; defaulting to log file:%n {0}**

Explanation The logger could not persist the error event data to the data store. The error will be written to the default log file.

EVSESI172E0012 **Error storing internal persistence error event to Elasticsearch index.**

Explanation The persistence error event could not be stored in elasticsearch due to an exception.

EVSESI172E0013 **Exception encountered during auto registration of event type: {0}**

Explanation Storage could not be allocated for the specified event type due to an Elasticsearch error.

EVSESI172E0014 **Error getting Elasticsearch client for auto registration**

Explanation An exception occured when trying to access the Elasticsearch transport client

EVSESI172E0015 **An event type mapping already exists for the event type: {0}**

Explanation Storage for the specified event type has already been allocated.

EVSESI172E0016 **Error checking for existing type in Elasticsearch index**

Explanation An exception was thrown while checking Elasticsearch for a registered event type

EVSESI172E0017 **No acknowledgment received from Elasticsearch cluster after create index operation**

Explanation The Elasticsearch node failed to acknowledge the status of the create index request.

EVSESI172E0018 **No acknowledgment received from Elasticsearch cluster after type mapping operation**

Explanation The Elasticsearch node failed to acknowledge the status of the put type mapping request.

EVSESI172E0019 **An Elasticsearch exception occurred while creating the type mapping**

Explanation The type mapping could not be added due to an exception thrown by the Elasticsearch client-server.

EVSESI172E0020 **Failed to initialize Elasticsearch schema parser implementation**

Explanation The event type schema parser couldn't be initialized; no event type parsing is possible.

EVSESI172E0021 **Error creating schema parser with Event Type Store location: {0}**

Explanation The EDA event type schema parser could not be initialized.

EVSESI172E0022 **Error parsing event schema with namespace {0} and event type {1}**

Explanation The event type definiition for the given namespace and event type could not be parsed.

EVSESI172E0023 **A valid namespace and event type are required to produce an Elasticsearch type mapping.**

Explanation Event type information could not be found for the specified namespace and event type.

EVSESI172E0024 **The event persistence annotation is not recognized: {0}**

Explanation An annotation specified in the event type definition is not known or supported.

EVSESI172E0027 **Error retrieving Elasticsearch client for metadata verification**

Explanation A connection couldn't be established while trying to load metadata from index

EVSESI172E0029 **Error closing transport client connection to cluster {0}, index {1} on server {2} with user {3}**

Explanation An error occurred disconnecting from the Elasticsearch cluster

EVSESI172E0030 **The event persistence annotation is not recognized: {0}**

Explanation An annotation value was specified that is not supported by event persistence

EVSESI172E0031 **Error retrieving normalized type from component for event type: {0}**

Explanation An exception was thrown by the component when generating the normalized type for the event type

EVSESI172I0004 **Elasticsearch transport client successfully connected to cluster {0}, index {1} on server {2} with user {3}**

Explanation The connection to the Elasticsearch cluster was successful.

EVSESI172I0028 **Elasticsearch transport client successfully disconnected from cluster {0}, index {1} on server {2} with user {3}**

Explanation The component has disconnected from the Elasticsearch cluster

EVSESI172W0025 **Task manager queue is full; The operation will be re-tried**

Explanation The task queue is at it's maximum size. The operation is re-tried after a slight delay.

EVSESI172W0026 **Thread interrupted while waiting for task re-submission**

Explanation The task manager thread was interrupted during re-submission delay. The operation will be re-tried immediately.

EVSESI232E0000 **Process method called before provider has been started**

Explanation This is a programatic initialization error. The storage providers start method was not called during initialization.

EVSESI232E0001 **Error initializing required internal resources**

Explanation An error occurred during initialization of the various implementation classes for this storage provider.

EVSESI232E0002 **Error creating or accessing bulk indexer for event type: {0}**

Explanation An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.

Action Check the status and healh of the cluster.

EVSESI232E0003 **Error stopping resource {0} on provider shutdown**

Explanation An internal resource threw an exception while stopping the storage provider.

EVSESI232E0005 **Failed to create Elasticsearch transport client connection to cluster {0}, index {1} on server {2} with user {3}.**

Explanation The client could not establish a connection to the Elasticsearch cluster.

EVSESI232E0006 **Elasticsearch client manager not started for cluster {0}, index {1} on server {2} with user {3}**

Explanation An attempt to get a connection was made before the client manager was started.

EVSESI232E0007 **Error stopping bulk indexer instance for type: {0}**

Explanation The bulk indexer instance for the specified type threw an exception on shutdown.

EVSESI232E0008 **Error creating Elasticsearch bulk indexing request**

Explanation An error occurred while formatting an Elasticsearch bulk indexing request for the current event batch

EVSESI232E0009 **Error executing Elasticsearch bulk indexing request**

Explanation The Elasticsearch bulk indexing request for the specified event batch could not be executed.

EVSESI232E0010 **Error loading metadata for persistence error type; logging to local file**

Explanation Metadata for the persistence error type couldn't be found or created. All messages will be logged to the local log file.

EVSESI232E0011 **Unable to write internal persistence error event; defaulting to log file:%n {0}**

Explanation The logger could not persist the error event data to the data store. The error will be written to the default log file.

EVSESI232E0012 **Error storing internal persistence error event to Elasticsearch index.**

Explanation The persistence error event could not be stored in elasticsearch due to an exception.

EVSESI232E0013 **Exception encountered during auto registration of event type: {0}**

Explanation Storage could not be allocated for the specified event type due to an Elasticsearch error.

EVSESI232E0014 **Error getting Elasticsearch client for auto registration**

Explanation An exception occured when trying to access the Elasticsearch transport client

EVSESI232E0015 **An event type mapping already exists for the event type: {0}**

Explanation Storage for the specified event type has already been allocated.

EVSESI232E0016 **Error checking for existing type in Elasticsearch index**

Explanation An exception was thrown while checking Elasticsearch for a registered event type

EVSESI232E0017 **No acknowledgment received from Elasticsearch cluster after create index operation**

Explanation The Elasticsearch node failed to acknowledge the status of the create index request.

EVSESI232E0018 **No acknowledgment received from Elasticsearch cluster after type mapping operation**

Explanation The Elasticsearch node failed to acknowledge the status of the put type mapping request.

EVSESI232E0019 **An Elasticsearch exception occurred while creating the type mapping**

Explanation The type mapping could not be added due to an exception thrown by the Elasticsearch client-server.

EVSESI232E0020 **Failed to initialize Elasticsearch schema parser implementation**

Explanation The event type definiition for the given namespace and event type could not be parsed.

EVSESI232E0021 **Error creating schema parser with Event Type Store location: {0}**

Explanation The EDA event type schema parser could not be initialized.

EVSESI232E0022 **Error parsing event schema with namespace {0} and event type {1}**

Explanation Event type information could not be found for the specified namespace and event type.

EVSESI232E0023 **A valid namespace and event type are required to produce an Elasticsearch type mapping.**

Explanation Event type information could not be found for the specified namespace and event type.

EVSESI232E0024 **The event persistence annotation is not recognized: {0}**

Explanation An annotation specified in the event type definition is not known or supported.

EVSESI232E0027 **Error retrieving Elasticsearch client for metadata verification**

Explanation A connection couldn't be established while trying to load metadata from index

EVSESI232E0029 **Error closing transport client connection to cluster {0}, index {1} on server {2} with user {3}**

Explanation An error occurred when diconnecting from the Elasticsearch cluster

EVSESI232E0030 **The event persistence annotation is not recognized: {0}**

Explanation An annotation value was specified that is not supported by event persistence

EVSESI232E0031 **Error retrieving normalized type from component for event type: {0}**

Explanation An exception was thrown by the component when generating the normalized type for the event type

EVSESI232E0032 **Error generating cache key for bulk indexer instance**

Explanation There was an error generating the cache key for the specified elasticsearch resource; verify variable values.

EVSESI232E0033 **Error creating and starting bulk indexer for event type: {0}**

Explanation The bulk indexer for the stated type could not be created or started

EVSESI232E0034 **Validation of dynamic service configuration against provided values failed**

Explanation A dynamic service configuration was provided but the variables are not present in the event.

EVSESI232E0035 **Validation of dynamic service configuration failed. Event can not be persisted: Header: {0} Body: {1}**

Explanation The values required for using a dynamic configuration were not supplied in the event being processed.

EVSESI232E0036 **Error initialising internal resources for provider; operation will be re-tried. Exception repeated {0} times**

Explanation Internal initialisation failed. The operation will be retried until successful or the component is restarted.

EVSESI232E0037 **Error creating bulk indexer for event type {0}; operation will be re-tried; Exception repeated {1} times**

Explanation An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.

EVSESI232E0038 **Error creating Elasticsearch bulk indexing request; operation will be re-tried; Exception repeated {0} times.**

Explanation There was an error while creating the indexing request most likely due to a connectivity issue between the client and the server.

Action Check the status and health of the cluster.

EVSESI232E0039 **Error executing Elasticsearch bulk indexing request; operation will be re-tried; Exception repeated {0} times.**

Explanation There was an error while creating the indexing request most likely due to a connectivity issue between the client and the server.

Action Check the status and health of the cluster.

EVSESI232E0040 **An exception occurred while checking the cluster for the specified destination index: {0}**

Explanation When the provider invoked the index exists call to Elasticsearch, the API threw an exception.

Action Check the status of the Elasticsearch cluster.

EVSESI232E0041 **An Elasticsearch exception occurred while creating the specified destination index: {0}**

Explanation When the provider invoked the create index call to Elasticsearch, the API threw an exception.

Action Check the status of the Elasticsearch cluster

EVSESI232E0042 **An error occurred while attempting to determine if auto-registration is required for type: {0} in index: {1}**

Explanation The service could not access or process the Elasticsearch type mapping in the given index.

Action Check the health of the Elasticsearch cluster.

EVSESI232E0043	**Error creating or accessing indexer for event type: {0}**
Explanation	An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.
Action	Check the status and healh of the cluster.

EVSESI232E0044	**Error creating Elasticsearch client for bulk indexing operation.**
Explanation	A connection to the Elasticsearc cluster could not be obtained.
Action	Check the status and health of the Elasticsearch cluster

EVSESI232E0045	**Error creating Elasticsearch bulk indexing request.**
Explanation	An error occurred when creating the bulk indexing request.
Action	Check the state and health of the Elasticsearch cluster.

EVSESI232E0046	**Error executing Elasticsearch bulk indexing request.**
Explanation	An error occurred when executing the indexing operation.
Action	Check the status and health of the Elasticsearch cluster.

EVSESI232E0047	**Error creating Elasticsearch client; operation will be re-tried; Exception repeated {1} times.**
Explanation	An error occurred when trying to connect to the Elasticsearch cluster.
Action	Check the state and health of the Elasticsearch cluster.

EVSESI232E0048	**Error creating bulk indexer for event type {0}; operation will be re-tried.**
Explanation	An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.
Action	Check the status and healh of the cluster.

EVSESI232E0049	**Error creating Elasticsearch client; operation will be re-tried.**
Explanation	An error occurred when trying to connect to the Elasticsearch cluster.
Action	Check the state and health of the Elasticsearch cluster.

EVSESI232E0050	**Error creating Elasticsearch bulk indexing request; operation will be re-tried.**
Explanation	There was an error while creating the indexing request most likely due to a connectivity issue between the client and the server.
Action	Check the status and health of the cluster.

EVSESI232E0051	**Error executing Elasticsearch bulk indexing request; operation will be re-tried.**
Explanation	There was an error while creating the indexing request most likely due to a connectivity issue between the client and the server.
Action	Check the status and health of the cluster.

EVSESI232E0052	**Error storing event of type: {0}**
Explanation	The indexer could not persist the event of the specified event type. This could be due to a failure to connect to the cluster or an issue with the cluster health.
Action	Check the status and healh of the cluster.

EVSESI232E0053	**Error creating or accessing indexer for event type: {0}; operation will be re-tried.**
Explanation	An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.
Action	Check the status and healh of the cluster.

EVSESI232E0054	**Error storing event of type: {0}; operation will be re-tried.**
Explanation	The indexer could not persist the event of the specified event type. This could be due to a failure to connect to the cluster or an issue with the cluster health.
Action	Check the status and healh of the cluster.

EVSESI232E0055	**Error creating Elasticsearch client for indexing request.**
Explanation	A connection to the Elasticsearc cluster could not be obtained.
Action	Check the status and health of the Elasticsearch cluster.

EVSESI232E0056	**Error preparing indexing request or processing response - id: {0} document type: {1}**
Explanation	An error occurred when creating or processing the index request required to persist the event. This could be due to an issue with the cluster.
Action	Check the status and health of the cluster.

EVSESI232I0004 **Elasticsearch transport client successfully connected to cluster {0}, index {1} on server {2} with user {3}**

Explanation The connection to the Elasticsearch cluster was successful.

EVSESI232I0028 **Elasticsearch transport client successfully disconnected from cluster {0}, index {1} on server {2} with user {3}**

Explanation The component has disconnected from the Elasticsearch cluster

EVSESI232W0025 **Task manager queue is full; The operation will be re-tried**

Explanation The task queue is at it's maximum size. The operation is re-tried after a slight delay.

EVSESI232W0026 **Thread interrupted while waiting for task re-submission**

Explanation The task manager thread was interrupted during re-submission delay. The operation will be re-tried immediately.

EVSESI564E0000 **Process method called before provider has been started**

Explanation Process method called before provider has been started

EVSESI564E0001 **Error initializing required internal resources**

Explanation An error occurred during initialization of the various implementation classes for this storage provider.

EVSESI564E0002 **Error creating or accessing bulk indexer for event type: {0}**

Explanation A bulk indexer instance could not be accessed or created for the specified event type.

EVSESI564E0003 **Error stopping resource {0} on provider shutdown**

Explanation Error stopping resource {0} on provider shutdown

EVSESI564E0005 **Failed to create Elasticsearch transport client connection to cluster {0}, index {1} on server {2} with user {3}.**

Explanation Failed to create Elasticsearch transport client connection to cluster {0}, index {1} on server {2} with user {3}.

EVSESI564E0006	**Error creating Elasticsearch client for bulk indexing operation.**
Explanation	A connection to the Elasticsearc cluster could not be obtained.
Action	Check the status and health of the Elasticsearch cluster.

EVSESI564E0007	**Error stopping bulk indexer for type: {0}**
Explanation	Error stopping bulk indexer for type: {0}

EVSESI564E0008	**Error creating Elasticsearch bulk indexing request.**
Explanation	An error occurred when creating the bulk indexing request.
Action	Check the state and health of the Elasticsearch cluster.

EVSESI564E0009	**Error executing Elasticsearch bulk indexing request.**
Explanation	An error occurred when executing the indexing operation.
Action	Check the status and health of the Elasticsearch cluster.

EVSESI564E0010	**Error creating Elasticsearch client; operation will be re-tried; Exception repeated {1} times.**
Explanation	An error occurred when trying to connect to the Elasticsearch cluster.
Action	Check the state and health of the Elasticsearch cluster.

EVSESI564E0011	**Unable to write internal persistence error event; defaulting to log file:%n {0}**
Explanation	Unable to write internal persistence error event; defaulting to log file:%n {0}

EVSESI564E0012	**Error storing internal persistence error event to Elasticsearch index**
Explanation	Error storing internal persistence error event to Elasticsearch index

EVSESI564E0013	**Exception encountered during auto registration of event type: {0}**
Explanation	Exception encountered during auto registration of event type: {0}

EVSESI564E0014	**Error creating bulk indexer for event type {0}; operation will be re-tried.**
Explanation	An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.
Action	Check the status and healh of the cluster.

EVSESI564E0015	**Error creating Elasticsearch client; operation will be re-tried.**
Explanation	An error occurred when trying to connect to the Elasticsearch cluster.
Action	Check the state and health of the Elasticsearch cluster.

EVSESI564E0016	**Error creating Elasticsearch bulk indexing request; operation will be re-tried.**
Explanation	There was an error while creating the indexing request most likely due to a connectivity issue between the client and the server.
Action	Check the status and health of the cluster.

EVSESI564E0017	**No acknowledgment received from Elasticsearch cluster after create index operation**
Explanation	No acknowledgment received from Elasticsearch cluster after create index operation

EVSESI564E0018	**No acknowledgment received from Elasticsearch cluster after type mapping operation**
Explanation	No acknowledgment received from Elasticsearch cluster after type mapping operation

EVSESI564E0019	**An Elasticsearch exception occurred while creating the type mapping**
Explanation	An Elasticsearch exception occurred while creating the type mapping

EVSESI564E0020	**Error executing Elasticsearch bulk indexing request; operation will be re-tried.**
Explanation	There was an error while executing the indexing request most likely due to a connectivity issue between the client and the server.
Action	Check the status and health of the cluster.

EVSESI564E0021	**Error creating or accessing indexer for event type: {0}**
Explanation	An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.
Action	Check the status and healh of the cluster.

EVSESI564E0022	**Error storing event of type: {0}**
Explanation	The indexer could not persist the event of the specified event type. This could be due to a failure to connect to the cluster or an issue with the cluster health.
Action	Check the status and healh of the cluster.

EVSESI564E0023 **Error creating or accessing indexer for event type: {0}; operation will be re-tried.**

Explanation An indexer could not be created to process the specified event type. This could be due to a failure to connect to the cluster for the required metadata.

Action Check the status and healh of the cluster.

EVSESI564E0024 **Error storing event of type: {0}; operation will be re-tried.**

Explanation The indexer could not persist the event of the specified event type. This could be due to a failure to connect to the cluster or an issue with the cluster health.

Action Check the status and healh of the cluster.

EVSESI564E0027 **Error retrieving Elasticsearch client for metadata verification**

Explanation Error retrieving Elasticsearch client for metadata verification

EVSESI564E0029 **Error closing transport client connection to cluster {0}, index {1} on server {2} with user {3}**

Explanation Error closing transport client connection to cluster {0}, index {1} on server {2} with user {3}

EVSESI564E0030 **The event persistence annotation is not recognized: {0}**

Explanation The event persistence annotation is not recognized: {0}

EVSESI564E0031 **Error retrieving normalized type from component for event type: {0}**

Explanation Error retrieving normalized type from component for event type: {0}

EVSESI564E0032 **Error generating cache key for resource**

Explanation Error generating cache key for resource

EVSESI564E0033 **Error creating bulk indexer for event type: {0}**

Explanation Error creating bulk indexer for event type: {0}

EVSESI564E0034 **Error creating Elasticsearch client for indexing request.**

Explanation A connection to the Elasticsearc cluster could not be obtained.

Action Check the status and health of the Elasticsearch cluster.

EVSESI564E0035 **Validation of dynamic service configuration failed. Event can not be persisted%nHeader: %s%nBody: %s**

Explanation Validation of dynamic service configuration failed. Event can not be persisted%nHeader: %s%nBody: %s

EVSESI564E0036 **Error initialising internal resources for provider; operation will be re-tried. Exception repeated {0} times**

Explanation Error initialising internal resources for provider; operation will be re-tried. Exception repeated {0} times

EVSESI564E0037 **Error creating bulk indexer for event type {0}; operation will be re-tried; Exception repeated {1} times**

Explanation Error creating bulk indexer for event type {0}; operation will be re-tried; Exception repeated {1} times

EVSESI564E0038 **Error creating Elasticsearch bulk indexing request; operation will be re-tried; Exception repeated {1} times**

Explanation Error creating Elasticsearch bulk indexing request; operation will be re-tried; Exception repeated {1} times

EVSESI564E0039 **Error executing Elasticsearch bulk indexing request; operation will be re-tried; Exception repeated {1} times**

Explanation Error executing Elasticsearch bulk indexing request; operation will be re-tried; Exception repeated {1} times

EVSESI564E0040 **An exception occurred while checking the cluster for the specified destination index: {0}**

Explanation An exception occurred while checking the cluster for the specified destination index: {0}

EVSESI564E0041 **An Elasticsearch exception occurred while creating the specified destination index: {0}**

Explanation An Elasticsearch exception occurred while creating the specified destination index: {0}

EVSESI564E0042 **An error occurred while attempting to determine if auto-registration is required for type: {0} in index: {1}**

Explanation An error occurred while attempting to determine if auto-registration is required for type: {0} in index: {1}

EVSESI564E0043 **Error preparing indexing request or processing response - id: {0} document type: {1}**

Explanation An error occurred when creating or processing the index request required to persist the event. This could be due to an issue with the cluster.

Action Check the status and health of the cluster.

EVSESI564I0004 **Elasticsearch transport client successfully connected to cluster {0}, index {1} on server {2} with user {3}**

Explanation Elasticsearch transport client successfully connected to cluster {0}, index {1} on server {2} with user {3}

EVSESI564I0028 **Elasticsearch transport client successfully disconnected from cluster {0}, index {1} on server {2} with user {3}**

Explanation Elasticsearch transport client successfully disconnected from cluster {0}, index {1} on server {2} with user {3}

EVSESI564W0025 **Task manager queue is full; The operation will be re-tried**

Explanation Task manager queue is full; The operation will be re-tried

EVSESI564W0026 **Thread interrupted while waiting for task re-submission**

Explanation Thread interrupted while waiting for task re-submission

EVSEUPE0004 **The destination file does not exist, failed creating configuration directory: ''{0}''.**

Explanation The destination file does not exist, failed creating Digital event Persistence configuration directory.

EVSEUPE0008 **Problem occurred during unmarshalling file: ''{0}''. Aborting migration of this file.**

Explanation Problem occurred during unmarshalling given file. Aborting migration of this file.

EVSEUPE0010 **The destination file exists: ''{0}''. Migrating from source to destination.**

Explanation The destination file exists. Migrating from source to destination.

EVSEUPE0011 **Problem occurred during marshalling file: ''{0}''. Aborting migration of this file.**

Explanation Problem occurred during marshalling given file. Aborting migration of this file.

EVSEUPE0012 **Not supported Digital Event Persistence Service Type: {0}**

Explanation Not supported Digital Event Persistence Service Type.

EVSEUPI0000 **Migrating Digital Event Persistence service configurations.**

Explanation Migrating Digital Event Persistence service configurations.

EVSEUPI0001 **The source directory exists: ''{0}''.**

Explanation The given source directory exists.

EVSEUPI0002 **The source directory does not exist: ''{0}''. Nothing to migrate.**

Explanation The source directory does not exist. Nothing to migrate.

EVSEUPI0003 **The destination directory exists: ''{0}''. Migrating from source to it.**

Explanation The given destination directory exists. Migrating from source to it.

EVSEUPI0005 **No Digital Event Persistence Service json files found under source directory: ''{0}''.**

Explanation No Digital Event Persistence Service json files found under source directory.

EVSEUPI0006 **Migrating Digital Event Persistence service: ''{0}''**

Explanation Migrating Digital Event Persistence service.

EVSEUPI0007 **Migrating file: ''{0}''.**

Explanation Migrating given file.

EVSEUPI0009 **The destination file exists: "{0}". Migrating from source to destination.**

Explanation The destination file exists. Migrating from source to destination.

EVSEVCE0000 **No transformer found for type: {0}**

Explanation No transformer of the required type, for example XML could be found.

EVSEVEE0000 **Elasticsearch transport client successfully connected to cluser {0}, index {1} on server {2}, port {3} with user {4}**

EVSEVEE0001 **Failed creating Elasticsearch transport client to connect to cluser {0}, index {1} on server {2}, port {3} with user {4}**

EVSEVEE0002 **Elasticsearch transport client is not started to connect to cluser {0}, index {1} on server {2}, port {3} with user {4}.**

EVSEVEE0003 **Error retrieving Elasticsearch client from pool**

EVSEVEE0004 **Error checking for existing type in Elasticsearch index**

EVSEVEE0005 **Exception encountered auto registration of event type: {0}**

EVSEVEE0006 **Event Routing Consumers are not supported by this Endpoint implementation**

EVSEVEE0007 **Synchronous Event processing is not supported by this component.**

EVSEVEE0008 **Error transforming event instance from native format to JSON format**

EVSEVEE0009 **Error initializing required internal resources**

EVSEVEE0010 **Error retrieving Elasticsearch client from pool during bulk indexing task**

EVSEVEE0011 **Error creating Elasticsearch bulk indexing request**

EVSEVEE0012 **Error executing Elasticsearch bulk indexing request**

EVSEVEE0013 **Unable to write internal persistence error event defaulting to log file:%s {0}**

EVSEVEE0014 **Error storing internal persistence error event to Elastisearch**

EVSEVEE0015 **Error loading metadata for persistence error type; logging to local file**

EVSEVEE0017 **Elasticsearch transport client not started for cluster {0}, index {1} on server {2} with user {3}.**

EVSEVEE0019 **Elasticsearch transport client successfully connected to cluster {0}, index {1} on server {2} with user {3}**

EVSEVEE0020 **Failed to create Elasticsearch transport client connection to cluster {0}, index {1} on server {2} with user {3}**

EVSEVEE0021 **Not Compliant JMX MBean, cannot create MBean {0}.**

Explanation Failed to create Elasticsearch JMX MBean

EVSEVEE0023 **An internal error occurred during schema processing operations**

Explanation This error is most likely due to incorrect wiring of the ETS/XSD services

EVSEVEI0022

EVSEVEW0016 **Task manager queue is full; The operation will be re-tried**

Explanation The work queue has reached its maximum size.

EVSEVEW0018 **Thread interrupted while waiting for task re-submission**

EVSEVHE0000 **Hive table could not be found or created for Event Type {0}**

Explanation Hive table could not be found or created in event store instance

EVSEVHE0001 **Error loading Hive table from event store instance**

Explanation Error loading Hive table from event store instance

EVSEVHE0002 **Failed to generate HDFS URI ({0})**

Explanation Failed to generate HDFS URI based on the configuration parameters.

Action Inspect configuration parameters defined in Command Central's UI.

EVSEVHE0003 **Failed to generate Hive URI ({0})**

Explanation Failed to generate Hive URI based on the configuration parameters set.

Action Inspect the configuration parameters defined in Command Central's UI.

EVSEVHE0004 **Error creating HDFS Producer for Event Type: {0}**

Explanation Error creating HDFS Producer

EVSEVHE0005 **Event could not be processed by HDFS producer**

Explanation Event could not be processed by HDFS producer

EVSEVHE0006 **Unable to create or locate Hive persistence errors table; defaulting to log file**

Explanation Unable to create or locate Hive persistence errors table

EVSEVHE0007 **Unable to write internal persistence error event; defaulting to log file**

Explanation Unable to write internal persistence error event

EVSEVHE0008 **Synchronous Event processing is not supported by this component.**

Explanation Event Persistence components only support asynchronous event processing.

EVSEVHE0009 **Consumers are not supported by the HDFS Endpoint**

Explanation The EVP HDFS Component only supports producers for event persistence

EVSEVHE0010 **Error encountered during batch processing.**

Explanation An errror occured during batch processing. Possible network connection failure.

Action Check your network connection.

EVSEVHE0011 **Ping Hive Server {0} failed.**

Explanation Hive Server is not available.

EVSEVHE0012 **Ping NameNode {0} failed.**

Explanation Cannot access the NameNode.

EVSEVHE0013 **Not Compliant JMX MBean, cannot create MBean {0}.**

Explanation Not Compliant JMX MBean.

EVSEVHE0015 **An internal error occurred during schema processing operations**

Explanation This error is most likely due to incorrect wiring of the ETS/XSD services

EVSEVHE0016 **Error transforming event instance from native format to JSON format**

Explanation The XML event could not be transformed to JSON possibly due to invalid content

EVSEVHI0014 **Successfully created Hadoop Connectivity JMX MBean {0}.**

Explanation Hadoop Connectivity JMX MBean created.

EVSEVJE0002 **JDBC Database Type not supported: {0}**

EVSEVJE0003 **Error Starting JDBC Component ({0})**

Explanation The EVP JDBC Component could not be started

EVSEVJE0004 **Error Stopping JDBC Component ({0})**

Explanation An internal error occurred when stopping the JDBC Component

EVSEVJE0005 **Error creating JDBC Producer for event type: {0}**

Explanation The EVP JDBC Endpoint could not create a Producer for the given event type.

EVSEVJE0006 **Consumers are not supported by the JDBC Endpoint**

Explanation The EVP JDBC Component only supports producers for event persistence

EVSEVJE0007 **No metadata found for event type: {0}**

Explanation No JDBC metadata was found for the given event type.

EVSEVJE0008 **Database exception while searching for event metadata!**

Explanation The metadata lookup failed with a database exception.

EVSEVJE0009 **Unable to write internal persistence error event defaulting to log file %n%n{0}**

Explanation The PersistenceError event could not be written to the store.

EVSEVJE0011 **Unexpected error during database rollback operation**

Explanation The database system reported an exception while performing the rollback

EVSEVJE0012 **Error encountered during batch processing! Number of batched events: {0}**

Explanation An error was reported while writing the events to the persistence store.

EVSEVJE0013 **Event could not be processed by producer**

Explanation An error occurred during event processing by this producer.

EVSEVJE0014 **Synchronous Event processing is not supported by this component.**

Explanation Event Persistence components only support asynchronous event processing.

EVSEVJI0000 **JDBC Connection Pool {0}{1} started with initial size of {2} and max size of {3}**

EVSEVJI0001 **JDBC Connection Pool closed**

EVSEVJW0010 **No metadata found for persistence error logger; defaulting to local log files!**

Explanation The metadata for the internal persistence error event type was not found in the store.

EVSEVPE0000 **Error Connecting ParStream Server for host: {0}, port: {1} and user: {2}.**

Explanation Error Connecting to ParStream Streaming Server.

Action Please make sure that the database server is up and running.

EVSEVPE0001 **No metadata found for event type: {0}**

EVSEVPE0002 **AutoRegistration failed for Event Type with NameSpace {0} : EventType {1}**

Explanation Check Database status and connection

EVSEVPE0003 **Database exception while searching for event metadata!**

Explanation Database exception while searching for event metadata!

EVSEVPE0004 **Synchronous Event processing is not supported by this component.**

Explanation Synchronous Event processing is not supported by this component.

EVSEVPE0005 **Error Starting ParStream Streaming Component for host: {0} and port: {1}**

Explanation Error Starting ParStream Streaming Component for host: {0} and port: {1}

EVSEVPE0006 **Error Stopping ParStream Component for host: {0} and port: {1}**

Explanation Error Stopping ParStream Component

EVSEVPE0007 **Unexpected error during database rollback operation**

Explanation Unexpected error during database rollback operation

EVSEVPE0008 **Error encountered during batch processing! Number of batched events: {0}**

Explanation Error encountered during batch processing!

EVSEVPE0009 **Unable to write internal persistence error event, defaulting to log file %n%n{0}**

Explanation Unable to write internal persistence error event defaulting to log file.

EVSEVPE0010 **Cannot get metadata information for event namespace {0} and type {1}.**

Explanation Cannot get metadata information for the event type.

EVSEVPE0011 **Error creating ParStream Producer for event type: {0}**

Explanation Error creating ParStream Producer for event type.

EVSEVPW0000 **No metadata found for persistence error logger; defaulting to local log files!**

Explanation No metadata found for persistence error logger; defaulting to local log files!

EVSHQF530E0000 **A error occurred when trying to instantiate the Hive CDH5.3.0 Query Session implementation class.**

Explanation The factory implementation could not create an instance of the query session class.

Action Contact Global Support.

EVSHQF530E0001 **Query implementation library found in multiple locations: {0}**

Explanation The implementation library was found in multiple locations on the server or installation directory. In this situation, the factory cannot determine the proper installation directory based on the library location.

Action Contact Global Support.

EVSHQF530E0002 **Could not find query implementation library while determining installation directory.**

Explanation In Non-OSGi environments the factory loads its third-party dependencies from a whitelist. It must first determine the installation directory. This is done by searching for the implementation jar in the Software_AG_Directory/common/EventPersistence folder. This error indicates that that library could not be found.

Action Contact Global Support.

EVSHQF530E0003 **The property dep.common.dir is set to a non-existent directory: {0}**

Explanation The system property dep.common.dir must be set to a valid Software_AG_Directory/common/EventPersistence directory location.

Action Contact Global Support.

EVSHQF530E0004 **The property dep.common.dir has not been set prior to using this component.**

Explanation The system property dep.common.dir is required and must be set to the location of the Software_AG_Directory/common/EventPersistence directory.

Action Contact Global Support.

EVSHQI530E0000 **Hive query execution failed with unexpected exception**

Explanation An unexpected exception occurred during the execution of the Hive query

EVSHQI530E0001 **Error transforming common query for explain plan**

Explanation An error occurred when transforming the common query to native format for the explain plan

EVSHQI530E0002 **An unsupported encoding exception was thrown while generating explain message**

Explanation The default encoding of utf-8 is required when creating the explain plan

EVSHQI530E0003 **Failed to close hive JDBC result set**

Explanation An exception was thrown during the close method on the JDBC result set

EVSHQI530E0004 **Failed to close hive JDBC statement**

Explanation An exception was thrown when closing the JDBC statement

EVSHQI530E0007 **The context did not contain the required parameters**

Explanation The context parameters for the specified session were invalid.

EVSHQI530E0008 **Error creating Hive SQL query in the current session.**

Explanation Could not create a JDBC connection and or Hive Query using the current session.

EVSHQI530E0009 **Full text query not supported by this implementation.**

Explanation This query implementation does not support full text queries.

EVSHQI530E0010 **Error closing current Hive JDBC connection.**

Explanation An exception was thrown when the close method of the connection was invoked.

EVSHQI530E0011 **Error initializing Hive JDBC connection.**

Explanation An error occurred when creating the Hive JDBC connection

EVSHQI530E0012 **Error setting default database in Hive JDBC connection.**

Explanation An exception was thrown when issuing the use database statement

EVSHQI530E0013 **Error closing active Hive JDBC statement.**

Explanation An exception was thrown during the close invocation on the current JDBC statement.

EVSHQI530E0014 **Failed to position cursor at next event in the result stream**

Explanation An error occurred when advancing the cursor in the result set.

EVSHQI530E0015 **The method {0} is unsupported in this implementation of ResultStream**

Explanation Implementors of the result stream must implement the next method; the other positional methods are optional.

EVSHQI530E0016 **Error getting result at current cursor position from handler**

Explanation An error occurred when retrieving the event data from the current cursor position.

EVSHQI530E0017 **Error closing Hive JDBC result set on close of result stream.**

Explanation The JDBC result set could not be closed when closing the result stream.

EVSHQI530E0018 **Property '{0}' in group by expression must appear in select expression**

Explanation A property specified in the group by clause is not present in the select list

EVSHQI530E0019 **Property '{0}' in select expression must appear in group by expression**

Explanation A property in the select expression is not present in the group by clause

EVSHQI530E0020 **Property '{0}' in order by expression must appear in select and group by expression**

Explanation A property specified in the order by expression is not present in the select expression

EVSHQI530I0005 **Inbound query in common syntax form:**

Explanation Label for the explan plain

EVSHQI530I0006 **Outbound query in native form:**

Explanation Explain plan label

EVSHQIE0000 **Unsupported date time format in string literal: {0}.**

Explanation Unsupported date time format in string literal

EVSHQIE0001 **Hive query execution failed.**

Explanation Hive query execution failed.

EVSHQIE0002 **Failed to close result set.**

Explanation Failed to close result set.

EVSHQIE0003 **Failed to close statement.**

Explanation Failed to close statement.

EVSHQIE0004 **HiveQuerySession initialize JDBC Connection failed.**

Explanation HiveQuerySession initialize JDBC Connection failed.

EVSHQIE0005 **Close Connection failed.**

Explanation Close Connection failed.

EVSHQIE0007 **Result cannot be formated to JSON. format**

Explanation Result cannot be formated to JSON format.

EVSHQIE0008 **Failed get next result.**

Explanation Failed get next result.

EVSHQIE0009 **Cannot create connection statement.**

Explanation Cannot create connection statement.

EVSHQIE0010 **Failed to create {0}**

EVSHQIE0011 **Property "{0}" in group by expression must appear in select expression**

Explanation Group by property is required to appear in select expression

EVSHQIE0012 **Property "{0}" in select expression must appear in group by expression**

Explanation Property in select expression must appear in the group by expression

EVSHQIE0013 **Property "{0}" in order by expression must appear in select and group by expression**

Explanation Property in order by expression must be included in the group by and select expression

EVSHQIE0014 **Full text query not supported by this implementation**

Explanation This query implementation does provide full text search capabilities

EVSHQIE0015 **Error transforming query for explain plan**

EVSHQIE0016 **An unsupported encoding exception was thrown while generating explain message**

EVSHQII0006 **Method: {0} is not supported.**

Explanation Method is not supported.

EVSHQII0017 **Inbound query in common syntax form:**

EVSHQII0018 **Outbound query in native form:**

EVSHSF530E0000 **A error occurred when trying to instantiate the HDFS 5.3.0 Storage Provider implementation.**

Explanation The factory could not create an instance of the storage provider implementation. This error could be related to feature provisioning or a class path issue.

Action Contact Global Support.

EVSHSF530E0001 **Could not find storage provider implementation library to determine installation directory.**

Explanation In Non-OSGi environments the factory loads its third party dependencies from a white-list. It must first determine the installation directory. This is done by searching for the implementation jar in the common Event Persistence folder. This error indicates that that library could not be found.

Action Verify that the Digital Event Persistence libraries were selected during the installation.

EVSHSF530E0002 **Storage provider implementation library found in multiple locations: {0}**

Explanation The implementation library was found in multiple locations on the server or installation directory. In this situation, the factory can not determine the proper installation directory based on the library location.

Action Check the installation directory.

EVSHSF530E0003 **The property dep.common.dir is set to a non-existent directory: {0}**

Explanation The system property dep.common.dir must be set to a valid Software_AG_Directory/common/EventPersistence directory location.

Action Contact Global Support.

EVSHSF530E0004 **The property dep.common.dir has not been set prior to using this component.**

Explanation The system property dep.common.dir is required and must be set to the location of the Software_AG_Directory/common/EventPersistence directory.

Action Contact Global Support.

EVSHSI530E0000 **Process method called before storage provider was started**

Explanation The storage provider was not initialized and a call was made to process an event.

EVSHSI530E0001 **Error initializing required internal resources for provider**

Explanation The required internal resources for the storage provider couldn't be initialized.

EVSHSI530E0002 **Error creating or accessing HDFS processor for event type: {0}**

Explanation An HDFS processor for the given event type could not be accessed or instantiated.

EVSHSI530E0003 **Error stopping resource {0} on storage provider shutdown**

Explanation An exception was through when stopping an internal resource on provider shutdown.

EVSHSI530E0004 **Error closing HDFS Writer instance on processor shutdown**

Explanation The HDFS writer and stream threw an exception on close.

EVSHSI530E0005 **Unexpected error encountered during batch processing.**

Explanation There was an HDFS or Hive error encounted during the processing of an event batch.

EVSHSI530E0006 **Error processing batch during execution of auto-write task.**

Explanation An unexpected exception was thrown during batch processing.

EVSHSI530E0007 **Error processing batch during execution of on-demand task**

Explanation An expected exception was thrown during batch processing

EVSHSI530E0008 **Error starting HDFS processor resource for event type: {0}**

Explanation An error was thrown when initializing and starting the HDFS processor.

EVSHSI530E0009 **Error stopping HDFS processor for event type: {0}**

Explanation An unexpected error occurred during the shutdown of the HDFS processor

EVSHSI530E0010 **Error creating HDFS processor for event type: {0}**

Explanation An internal error occurred during the creation of the HDFS processor

EVSHSI530E0011 **Unsupported encoding error converting text event to byte stream**

Explanation The event instance was formatted in an encoding other than the default of utf-8

EVSHSI530E0012 **Error streaming event data to HDFS output stream**

Explanation An error occurred while writing the event data to the HDFS file system.

EVSHSI530E0013 **Error flushing and closing the HDFS file stream**

Explanation The HDFS I/O stream could not be flushed and closed.

EVSHSI530E0014 **Error closing HDFS file system reference**

Explanation The HDFS file system reference throw an unexpected exception during the close method call

EVSHSI530E0015 **Error creating HDFS file system reference**

Explanation An unexpected exception was thrown when closing the HDFS file system.

EVSHSI530E0016 **Hive table could not be found or created for event type: {0}**

Explanation The Hive table does not exist and or could not be created by the Hive metadata manager

EVSHSI530E0017 **Error loading Hive table data or performing auto registration for event type: {0}**

Explanation An error accessing the Hive metadata or creating the Hive metadata for the specified event type occurred.

EVSHSI530E0018 **Unable to create or find Hive persistence error table; defaulting to log file:%n {0}**

Explanation The Hive metadata table for the event persistence error type could not be found or created. Errors will be logged to the error log.

EVSHSI530E0019 **Error retrieving root schema tree element children from parser**

Explanation The child nodes of the schema element tree root could not be accessed.

EVSHSI530E0020 **Error parsing schema for event type: {0} in namespace {1}**

Explanation The event type definition for the given event type and namespace could not be parsed by the schema parser.

EVSHSI530E0021 **Generated Hive event table name exceeds 255 character size limit: {0}**

Explanation Table names in Hive are limitted to 255 characters; The unique table name generated for the event type and namespace exceeded this limit.

EVSHSI530E0022 **Error creating Hive database table field definitions**

Explanation An expected error occurred when parsing the schema tree and creating the database table and field definitions

EVSHSI530E0023 **Error creating Hive database table structure definition**

Explanation An unexpected error occurred when generating the Hive table structure

EVSHSI530E0024 **Error creating Hive database table definition**

Explanation An unexpected error occurred when generating the Hive metadata table definition.

EVSHSI530E0025 **Error filtering non-mappable nodes from root schema element tree**

Explanation There are certain binary type properties supported in events; these are filtered out of the stored event. An unexpected error occurred when trying to filter these nodes.

EVSHSI530E0027 **Ping to Apache Hive Server {0} failed.**

Explanation Could not ping an active hive server for metadata operations

EVSHSI530E0028 **Ping to Apache Hadoop Name Node {0} failed.**

Explanation Failed to connect to primary name node for file system access.

EVSHSI530E0031 **Error disconnecting from Apache Hive database: {0} at host: {1} port: {2} and user: {3}**

Explanation An error occurred when disconnecting from the hive database

EVSHSI530E0034 **Error retrieving normalized type from component for event type: {0}**

Explanation An exception was thrown by the component when generating the normalized type for the event type

EVSHSI530E0035 **An exception was thrown whilst stopping an HDFS error event writer: {0}**

Explanation During shutdown of the HDFS error logger an exception was thrown when closing the writer for the given target and event type.

EVSHSI530E0036 **Validation of dynamic service configuration against provided values failed**

Explanation A dynamic service configuration was provided but the variables are not present in the event.

EVSHSI530E0037 **Unexpected exception encountered during batch processing; operation will be re-tried. Exception repeated {0} times.**

Explanation An exception occurred while writing the events to the HDFS file system. The operation will be re-tried until successful.

Action Check the status of the HDFS cluster.

EVSHSI530E0038 **Unexpected exception on HDFS file system close call during hard reset**

Explanation An exception was thrown when closing the file system reference after write exception.

EVSHSI530E0039 **Error initialising internal resources for provider; operation will be re-tried. Exception repeated {0} times**

Explanation Internal initialisation failed. The operation will be retried until successful or the component is restarted.

EVSHSI530E0040 **Error creating processor for event type {0}; operation will be re-tried; Exception repeated {1} times.**

Explanation A processor could not be created to process the specified event type. This could be due to a failure to connect to Hive for the required metadata.

Action Check the health of the Hive server and HDFS cluster.

EVSHSI530E0041 **Validation of dynamic service configuration failed. Event can not be persisted: Header: {0} Body: {1}**

Explanation The values required for using a dynamic configuration were not supplied in the event being processed.

EVSHSI530E0042 **Error create Hive MetaData table for performing auto registration for type: {0}**

Explanation Create Hive MetaData Table error.

EVSHSI530E0043 **Error streaming event data to HDFS file system in table directory: {0}**

Explanation An error occurred when writing to the event types data file in HDFS.

Action Check the status of the Hadoop HDFS file system.

EVSHSI530E0044 **Error creating processor for event type {0}; operation will be re-tried.**

Explanation A processor could not be created to process the specified event type. This could be due to a failure to connect to Hive for the required metadata.

Action Check the health of the Hive server and HDFS cluster.

EVSHSI530E0045 **Unexpected exception was encountered during batch processing; operation will be re-tried.**

Explanation An exception occurred while writing the events to the HDFS file system. The operation will be re-tried until successful.

Action Check the status of the HDFS cluster.

EVSHSI530E0046 **Error storing event of type {0}**

Explanation The event could not be wrtten to the HDFS file system.

Action Check the health of the HDFS cluster.

EVSHSI530E0047 **Error storing event of type {0}; operation will be re-tried.**

Explanation The event could not be wrtten to the HDFS file system. The cluster could be down or unreachable. The operation will be retried until successful or until the service is shut down.

Action Check the health of the HDFS cluster.

EVSHSI530I0026 **Successfully created JMX MBean for Hadoop Connectivity: {0}**

Explanation The monitoring MBean was successfully created

EVSHSI530I0029 **Connected to Apache Hive database: {0} at host: {1} port: {2} and user: {3}**

Explanation Info message on connection to hive database

EVSHSI530I0030 **Disconnected from Apache Hive database: {0} at host: {1} port: {2} and user: {3}**

Explanation Info message on database disconnect

EVSHSI530I0032 **Connected to Apache HDFS File System specified by URI: {0}**

Explanation Info message logged on connect to HDFS file system

EVSHSI530I0033 **Disconnected from Apache HDFS File System specified by URI: {0}**

Explanation Info message logged on disconnect from HDFS file system

EVSJCOE0000 **An invalid column index was passed into the accessor method: {0}**

Explanation Column indices range from 1 to n. The client has passed an index into the accessor methods that is outside this range.

EVSJCOE0001 **An invalid column label was passed into the accessor method: {0}**

Explanation The client has passed a column label into the accessor method that does not exist in this result set.

EVSJCOE0002 **The specified feature is not supported by this driver or data source: {0}**

Explanation The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.

EVSJCOE0003 **Column data at index or specified label is not integral: (0}**

Explanation A numeric column accessor method was called but the value is not a numeric.

EVSJCOE0004 **Column data at index or for specified label is not a floating point number: {0}**

Explanation A decimal column accessor method was called but the value is not a floating point number.

EVSJDRE0000 **No driver or data source implementation found for scheme: {0}**

Explanation The driver implementation is dynamically loaded based on the scheme in the database URL. This message indicates that there is no implementation class for the specified schema.

EVSJDRE0001 **The specified feature is not supported by this driver or data source: {0}**

Explanation The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.

EVSJDRE0002 **Error loading dynamic library white list from resource:**

Explanation The resource containing a white list of dynamically loaded run-time libraries could not be loaded.

EVSJDRE0003 **Error creating class loader and loading white listed run-time libraries**

Explanation There as an error when creating the classloader and loading the classes contained in the white listed libraries.

EVSJDRE0004 **Error creating instance of the driver or data source implementation class:**

Explanation The driver implementation class could not be instantiated using the custom class loader and dynamically loaded library classes.

EVSJDRE0005 **The driver or data source installation directory is a required property but has not been set.**

Explanation The driver dynamically loads the implementation and run-time libraries based on the database URL. For this to function correctly the location of the driver installation must be provide.

EVSJDRE0006 **The databaseURL property has not been set for this data source**

Explanation An attempt was made to retrieve a connection from the data source without setting the database location.

EVSJDRE0007	**No parameters found in JDBC URL query string: {0}**
Explanation	The JDBC URL contains a query string marker "?" but has no parameters.
Action	Correct the JDBC URL and ensure that the required parameters are specified correctly.

EVSJDRE0008	**The specified query parameter has no associated value: {0}**
Explanation	The JDBC URL contains a query string that includes one or more parameters with no associated values.
Action	Correct the JDBC URL and ensure that all query parameters have valid values.

EVSJDRE0009	**The installDir property is set to a non-existent directory location.**
Explanation	The installDir property points to a directory that does not exist.
Action	Verify the location of the JDBC driver installation and update the client settings.

EVSJDRE0010	**The installDir directory location points to an invalid driver distribution.**
Explanation	The installDir property points to a directory that does not contain the driver distribution.
Action	Verify the location of the JDBC driver installation and update the client settings.

EVSJDRE0011	**Error loading dynamic library white list from resource: {0}**
Explanation	The resource containing a white list of dynamically loaded run-time libraries could not be loaded.

EVSJDRE0012	**Error creating instance of the driver or data source implementation class: {0}**
Explanation	The driver implementation class could not be instantiated using the custom class loader and dynamically loaded library classes.

EVSJDRE0013	**The installDir property is set to a non-existent directory location: {0}**
Explanation	The installDir property points to a directory that does not exist.
Action	Verify the location of the JDBC driver installation and update the client settings.

EVSJDRE0014	**The installDir directory location points to an invalid driver distribution: {0}**
Explanation	The installDir property points to a directory that does not contain the driver distribution.
Action	Verify the location of the JDBC driver installation and update the client settings.

EVSJEDI232E0000 **The specified feature is not supported by this driver or data source: {0}**

Explanation The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.

EVSJEDI232E0001 **This connection implementation provides no wrapper interfaces**

Explanation The connection implementation does not support the unwrap feature declared in the Wrapper interface.

EVSJEDI232E0002 **The required properties for this data source have not be set prior to creating the connection**

Explanation Prior to creating a connection through the data source the various setter methods should be invoked to initialize the data source.

EVSJEDI232E0003 **An error occurred when creating a connection to the Elasticsearch cluster.**

Explanation The transport client could not be created during construction of the connection.

Action Check the database URL and verify that the cluster is available

EVSJEDI232E0004 **Error converting Elasticsearch mapping metadata to JSON format**

Explanation The Elasticsearch metadata response could not be marshalled into JSON format.

EVSJEDI232E0005 **An invalid column index was passed into the accessor method: {0}**

Explanation Column indices range from 1 to n. The client has passed an index into the accessor methods that is outside this range.

EVSJEDI232E0006 **Column data at index or specified label is not integral: {0}**

Explanation A numeric column accessor method was called but the value is not a numeric.

EVSJEDI232E0007 **Column data at index or for specified label is not a floating point number: {0}**

Explanation A decimal column accessor method was called but the value is not a floating point number.

EVSJEDI232E0008 **An invalid column label was passed into the accessor method: {0}**

Explanation The client has passed a column label into the accessor method that does not exist in this result set.

EVSJEDI232E0009 **Column data at index or for specified label is not a valid timestamp: {0}**

Explanation A timestamp column accessor method was called but the value is not a valid timestamp

EVSJEDI232E0010 **Column data at index or for specified label is not a valid date: {0}**

Explanation A date column accessor method was called but the value is not a valid date

EVSJEDI232E0011 **Column data at index or for specified label is not a valid time field: {0}**

Explanation A time column accessor method was called but the value is not a valid time field

EVSJEDI232E0012 **No corresponding index exists for the specified catalog: {0}**

Explanation There is a one to one relationship between the SQL catalog and Elasticsearch index in the persistence framework. A method taking a catalog parameter was called but no such index exists in the Elasticsearch cluster.

EVSJEDI232E0013 **This driver or data source only supports SQL queries**

Explanation The JDBC driver for Event Persistence is provided for basic queries against non-SQL data stores.

EVSJEDI232E0014 **The specified column name "{0}" does not exist in table; available columns are: {1}**

Explanation The SQL query specified an invalid column name in the column list, where clause, order by clause, or group by clause.

Action Correct the SQL query statement.

EVSJEDI232E0015 **Error transforming SQL query into a native Elasticsearch request%n{0}**

Explanation The SQL query could not be turned into an Elasticsearch search request.

Action Verify the syntax of the issued query and revise as needed.

EVSJEDI232E0016	**Error executing native Elasticsearch search request%n{0}**
Explanation	An error occurred while executing the native Elasticsearch search request.
Action	Check that the cluster is available and in good health.

EVSJEDI232E0017	**The index represented by the specified catalog does not exist: {0}**
Explanation	An SQL query was issued but there is no corresponding index on the cluster
Action	Check your query and the available indices on the cluster.

EVSJEDI232E0018	**The type represented by the specified table does not exist: {0}**
Explanation	An SQL query was issued but there is no corresponding type available in the index.
Action	Check your query and the available indices on the cluster.

EVSJEDI232E0019	**Unexpected statement type found while trying to determine the appropriate query builder implementation**
Explanation	Different builder classes are used to transform the SQL query into various Elasticsearch search requests. The implementation is selected based on the presence of aggregate functions or column list expressions. In this case, neither was found.
Action	Check your SQL query syntax.

EVSJEDI232E0020	**Error incrementing result cursor or accessing query result data**
Explanation	The result cursor could not be advanced to the next position.
Action	This can occur if the cluster goes down and the client tries to access the next batch. Check the cluster health.

EVSJEDI232E0021	**Error setting fetch direction on forward only result set.**
Explanation	This jdbc driver provides foward only result sets. A client attempted to set a fetch direction other than forward.
Action	Correct the client logic.

EVSJEDI232E0022	**An error has occurred because the response reference has not been set in response handler**
Explanation	This is a programming error in the implementation logic; the response must be set before using the handler.
Action	Correct the programming error.

EVSJEDI232E0023	**No matching parameter marker found for given index: {0}**
Explanation	The client invoked a set method on the prepared statement for which there was no marker. For example, setting parameter 2 on a statement with only one marker.
Action	Correct the program logic.

EVSJEDI232E0024	**No corresponding value found for the marker at parameter index: {0}**
Explanation	A parameter marker was specified in the query but no value was set prior to executing the statement.
Action	Correct the program logic by invoking the appropriare set method on the prepared statement.

EVSJEDI232E0025	**The position {0} declared in the order by clause does not match a valid column or alias defined in the select statements column or aggregate list**
Explanation	The order by clause specifies an integer position that does not match a value in the select expressions column list.
Action	Review the statement and correct the column list expression or the order by clause.

EVSJEDI232E0026	**No column matching the specified label was found in this result set: {0}**
Explanation	The findColumn method was invoked with a non-existent column label.
Action	Specify a correct column label when invoking the method.

EVSJEDI232E0027	**Column type at index or for the specified label is not a JDBC timestamp: {0}**
Explanation	A getTimestamp, getTime or getDate accessor method was called for an incorrect column type. These methods are only valid for JDBC timestamp columns.
Action	Update the program logic to use the appropriate accessor method.

EVSJEDI232E0028	**The specified database URL is not in a valid format for this driver or datasource: {0}**
Explanation	The JDBC URL contains an invalid format for the given driver or data source.
Action	Consult the JDBC Driver documentation for the appropriate URL format.

EVSJEDI564E0000	**The specified feature is not supported by this driver or data source: {0}**
Explanation	The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.

EVSJEDI564E0001 **No corresponding index exists for the specified catalog: {0}**

Explanation There is a one to one relationship between the SQL catalog and Elasticsearch index in the persistence framework. A method taking a catalog parameter was called but no such index exists in the Elasticsearch cluster.

EVSJEDI564E0002 **The required properties for this data source have not be set prior to creating the connection**

Explanation Prior to creating a connection through the data source the various setter methods should be invoked to initialize the data source.

EVSJEDI564E0003 **An error occurred when creating a connection to the Elasticsearch cluster.**

Explanation The transport client could not be created during construction of the connection.

Action Check the database URL and verify that the cluster is available.

EVSJEDI564E0004 **Error converting Elasticsearch mapping metadata to JSON format**

Explanation The Elasticsearch metadata response could not be marshalled into JSON format.

EVSJEDI564E0005 **An invalid column index was passed into the accessor method: {0}**

Explanation Column indices range from 1 to n. The client has passed an index into the accessor methods that is outside this range.

EVSJEDI564E0006 **Column data at index or specified label is not integral: {0}**

Explanation A numeric column accessor method was called but the value is not a numeric.

EVSJEDI564E0007 **Column data at index or for specified label is not a floating point number: {0}**

Explanation A decimal column accessor method was called but the value is not a floating point number.

EVSJEDI564E0008 **An invalid column label was passed into the accessor method: {0}**

Explanation The client has passed a column label into the accessor method that does not exist in this result set.

EVSJEDI564E0009 **Column data at index or for specified label is not a valid timestamp: {0}**

Explanation A timestamp column accessor method was called but the value is not a valid timestamp

EVSJEDI564E0010 **The specified column name "{0}" does not exist in table; available columns are: {1}**

Explanation The SQL query specifies an invalid column name in the column list, where clause, order by clause, or group by clause.

Action Correct the SQL query statement.

EVSJEDI564E0011 **No corresponding value found for the marker at parameter index: {0}**

Explanation A parameter marker was specified in the query but no value was set prior to executing the statement.

Action Correct the program logic by invoking the appropriare set method on the prepared statement.

EVSJEDI564E0012 **Error transforming SQL query into a native Elasticsearch request%n{0}**

Explanation The SQL query could not be turned into an Elasticsearch search request.

Action Verify the syntax of the issued query and revise as needed.

EVSJEDI564E0013 **Error executing native Elasticsearch search request%n{0}**

Explanation An error occurred while executing the native Elasticsearch search request.

Action Make sure that the cluster is available and in good health.

EVSJEDI564E0014 **The index represented by the specified catalog does not exist: {0}**

Explanation An SQL query was issued but there is no corresponding index on the cluster.

Action Check your query and the available indices on the cluster.

EVSJEDI564E0015 **The type represented by the specified table does not exist: {0}**

Explanation An SQL query was issued but there is no corresponding type available in the index.

Action Check your query and the available indices on the cluster.

EVSJEDI564E0016 **Error incrementing result cursor or accessing query result data.**

Explanation The result cursor could not be advanced to the next position. This issue can occur if the cluster goes down and the client tries to access the next batch.

Action Check the cluster health.

EVSJEDI564E0017	**Error setting fetch direction on forward only result set.**
Explanation	This jdbc driver provides foward only result sets. A client attempted to set a fetch direction other than forward.
Action	Correct the client logic.

EVSJEDI564E0018	**An error occurred because the response reference has not been set in response handler.**
Explanation	This is a programming error in the implementation logic; the response must be set before using the handler.
Action	Correct the programming error.

EVSJEDI564E0019	**No matching parameter marker found for the given index: {0}**
Explanation	The client invoked a set method on the prepared statement for which there was no marker. For example, setting parameter 2 on a statement with only one marker.
Action	Correct the program logic.

EVSJEDI564E0020	**The position {0} declared in the order by clause does not match a valid column or alias defined in the select statements column or aggregate list.**
Explanation	The order by clause specifies an integer position that does not match a value in the select expressions column list.
Action	Review the statement and correct the column list expression or the order by clause.

EVSJEDI564E0021	**No column matching the specified label was found in this result set: {0}**
Explanation	The findColumn method was invoked with a non-existent column label.
Action	Specify a correct column label when invoking the method.

EVSJEDI564E0022	**Column type at index or for the specified label is not a JDBC timestamp: {0}**
Explanation	A getTimestamp, getTime or getDate accessor method was called for an incorrect column type. These methods are only valid for JDBC timestamp columns.
Action	Update the program logic to use the appropriate accessor method.

EVSJEDI564E0023	**The specified database URL is not in a valid format for this driver or datasource: {0}**
Explanation	The JDBC URL contains an invalid format for the given driver or data source.
Action	Consult the JDBC Driver documentation for the appropriate URL format.

EVSJHDI530E0000 **The specified feature is not supported by this driver or data source: {0}**

Explanation The invoked method is not supported by the driver or data source. Only a subset of the JDBC API are required to be supported.

EVSJHDI530E0001 **The required properties for this data source have not be set prior to creating the connection**

Explanation Prior to creating a connection through the data source the various setter methods should be invoked to initialize the data source.

EVSJQIE0000 **Unsupported format in aggregation function: {0}.**

Explanation Unsupported format in aggregation function.

EVSJQIE0001 **Unsupported date time format in string literal: {0}.**

Explanation Data and time format is invalid.

EVSJQIE0002 **Query execution failed.**

Explanation Query execution failed.

EVSJQIE0003 **Failed close query result.**

Explanation Failed close query result.

EVSJQIE0004 **Failed to close query statement.**

Explanation Failed to close query statement.

EVSJQIE0005 **Failed to close query connection.**

Explanation Failed to close query connection.

EVSJQIE0006 **Failed to close qeury result.**

Explanation Failed to close query result.

EVSJQIE0007 **Failed to format the result to JSON.**

Explanation Failed to format the result to JSON.

EVSJQIE0008 **Unsupported feature: {0}.**

Explanation Feature is not supported.

EVSJQIE0009 **Failed to get next query result.**

Explanation Failed to get next query result.

EVSJQIE0010 **Full text query not supported by this implementation**

Explanation This query implementation does provide full text search capabilities

EVSJQIE0011 **Error transforming query for explain plan**

EVSJQIE0012 **An unsupported encoding exception was thrown while generating explain message**

EVSJQII0013 **Inbound query in common syntax form:**

EVSJQII0014 **Outbound query in native form:**

EVSJQPE0000 **Test Message**

EVSJUTE0000 **Invalid JDBC scheme: {0}**

Explanation Invalid JDBC scheme.

EVSPAIE0000 **Failed to execute operations: {0}**

Explanation Failed to execute operations: {0}

EVSPAIE0001 **ParStream Admin Session has not been started.**

Explanation ParStream Admin Session has not been started.

EVSPAIE0002 **Failed to close JDBC connection statement.**

Explanation Failed to close JDBC connection statement.

EVSPAIE0003 **Event type {0} with Namespace {1} has already registered.**

Explanation Event type {0} with Namespace {1} has already registered.

EVSPAIE0004 **Not supported operation: {0}.**

Explanation Not supported operation: {0}.

EVSPAIE0005 **Not Supported Encoding {0}.**

Explanation Not Supported Encoding {0}.

EVSPQIE0000 **Metadata manager error encountered during create session call**

Explanation Metadata manager couldn't be created; possibly due to invalid event type store location

EVSPQIE0001 **Error encountered when initializing metadata manager**

Explanation Metadata manager couldn't be created; possibly due to invalid event type store location

EVSPQIE0002 **Unsupported date time format in string literal: {0}**

Explanation Date and time format is invalid - See java.sql.Timestamp format

EVSPQIE0003 **Unsupported syntax in aggregate function clause: {0}**

Explanation Unsupported syntax in aggregation function clause avg, min, max, sum or count

EVSPQIE0004 **Error creating the connection to the ParStream database**

Explanation There was an error connecting to the ParStream server(s)

EVSPQIE0005 **An open query exists for this session**

Explanation There is already a pending or active query for this session; execute or close the query

EVSPQIE0006 **Error closing the connection to the ParStream database**

Explanation There was an error closing the connection to the database

EVSPQIE0007 **An open result stream exists for this query**

Explanation There is an active result stream; process the results or close the result stream

EVSPQIE0008 **There was an error executing the current query**

Explanation This could be due to a syntax error in the query or the ParStream database may be unavailable

EVSPQIE0009 **Unexpected exception when closing the query**

Explanation An error was encountered when closing the query session

EVSPQIE0010 **Failed to position cursor at next event in the result stream**

Explanation There was an error when moving the cursor position forward in the stream

EVSPQIE0011 **The method {0} is unsupported in this implementation of ResultStream**

Explanation The only requirement on a ResultStream implementation is that they provide a forward cursor via the next method

EVSPQIE0012 **Failed to format the query result into a JSON document**

Explanation There was an error when creating the JSON result from the database query

EVSPQIE0013 **Unexpected exception encountered when closing result stream**

Explanation There was an error closing the result stream; this could be caused by a network or database issue

EVSPQIE0014 **Full text query not supported by this implementation**

Explanation This query implementation does provide full text search capabilities

EVSQUAE0000 **No provider registered for scheme: {0}**

Explanation No provider registered for scheme.

EVSQUAE0001 **EventStoreUser is not set.**

Explanation EventStoreUser is not set.

EVSQUAE0002 **Where clause contains no valid expression**

Explanation A where clause was added to the builder that contains no expression.

EVSQUAE0003 **Group by clause contains no valid properties**

Explanation A group by was added to the builder but contains no event properties.

EVSQUAE0004 **Order by clause contains no valid properties**

Explanation An order by clause was added to the builder but contains no properties

EVSQUAE0005 **An internal error occurred while loading OSGi classes and creating service tracker instance.**

Explanation An internal error occurred while loading OSGi classes and creating service tracker instance.

Action Contact Global Support.

EVSQUAE0006 **An internal error occurred while performing the OSGi service lookup.**

Explanation The OSGi service look-up could not be performed.

Action Check the run-time status of the installed query factory bundles.

EVSQUAE0007 **No registered query factory found for scheme: {0}**

Explanation As EVP query factory implementation bundles are initialized they register themselves in OSGi. This indicates that there is no registered query session factory for the given URI scheme

EVSQUAE0008 **An internal error occurred when closing the OSGi service tracker.**

Explanation The close method of the OSGi service tracker class could not be found or invoked.

Action Check the run-time status of the installed product.

EVSQUAE0009 **Error creating query session factory instance for scheme: {0}**

Explanation The implementation class for the storage provider could not be instantiated.

EVSSAPE0000 **No registered storage provider factory found for store type: {0} and version: {1}**

Explanation As EVP storage implementation bundles are initialized they register their factories with the api. This indicates that there is no registered factory for the data store type and version.

EVSSAPE0001 **Error creating storage factory instance for store type: {0} and version: {1}**

Explanation The implementation class for the storage provider could not be instantiated.

EVSSAPE0002 **Found variable {0} but no associated value was provided in the event**

Explanation The service has been configured with variables but no value was included in the emitted event.

EVSSAPE0003 **Dynamic Service Configuration validation failed; no values found in map for the following variables: {0}**

Explanation A variable was defined in the service configuration but no value was found in the event header.

EVSSAPE0004 **Error compiling regular expression for variable substitution on variable: {0}**

Explanation The regular expression for substitution of the stated variable failed.

EVSSAPE0005 **An internal error occurred while loading OSGi classes and creating service tracker instance.**

Explanation The required OSGi classes needed for service look-ups could not be found or loaded. There is a problem with the component or common run-time OSGi environment.

Action Contact Global Support.

EVSSAPE0006 **An internal error occurred while performing the OSGi service look-up.**

Explanation The OSGi service look-up could not be performed.

Action Check the run-time status of the installed product.

EVSSAPE0007	**An internal error occurred when closing the OSGi service tracker.**
Explanation	The close method of the OSGi service tracker class could not be found or invoked.
Action	Check the run-time status of the installed product.

EVSUTLE0000	**Invalid JDBC scheme: {0}**
Explanation	Invalid JDBC scheme.

EVSUTLE0001	**Invalid or unexpected Event Store URI format: {0}**
Explanation	Invalid or unexpected Event Store URI format.

17 Installer Messages

CommandLineArgs.missingMaxLogSize – You changed the default maximum log size using -maxLogSize but did not provide the new value for new log size. Provide the new value for the maximum log size, followed by either 'k' or 'm'.

Explanation You changed the default maximum log size using -maxLogSize but did not provide the new value for log size.

Action Provide the new value for the maximum log size, followed by either 'k' or 'm'.

DLInitFilesProgressPanel.cannotLoadJNI – Unable to load resource {0}. Run the installer again with a 32-bit JDK instead of a 64-bit JDK.

Explanation This message is displayed when the user uses 64-bit JDK to install an older version that did not support 64-bit JDK. The 64-bit library will be missing.

Action Run the installer again with a 32-bit JDK instead of a 64-bit JDK.

DLInitFilesProgressPanel.unsupportedPlatformInternal – The installer has requested files for {0} but no files are available for that operating system at {1}.

DLInitFilesProgressPanel.unsupportedPlatformProduction – The selected product release does not support the operating system {0} on which you are trying to install.

Explanation The user is trying to install on a platform that not supported on the current install machine.

Action The user should select a different product suite that does support the current platform.

DLJarsProgressPanel.errorImagePlatformAs400 – April 2011 and later Software AG Installers do not support creation of images for IBM AS/400 systems. The installer will now exit.

DistManInstallMain.relaunchBadJavaHome – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. You must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. You can use the -javaHome command line option to launch the uninstaller using a different JDK. The JDK located in {4} is not working; verify that the path is correct.

Explanation This message is displayed when the user gave the installer or uninstaller an alternate JDK to launch the installer or uninstaller, and the path was incorrect. See 'DistManInstallMain.relaunchNoJavaHome' for more details -- {4} is the location the user gave for the JDK installation.

Action The user should provide a proper JDK installation directory.

DistManInstallMain.relaunchJavaHomeSetText – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. However, you must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. Please provide a JDK installation directory that meets these requirements; the JDK located at {4} does not meet these requirements or does not exist.

Explanation This message displayed when the user provides an alternate JDK to execute the installer or uninstaller, and the given path is too old or is not a proper directory. {0} - the JDK that is running this client {1} - the current JDK version {2} the major.minor class version that this JDK supports {3} - the required major.minor {4} - the location the user gave as an alternate JDK to run the installer or uninstaller.

Action Supply a proper JDK directory.

DistManInstallMain.relaunchJavaHomeText – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. However, you must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. Download a JDK that meets these requirements. See the Using the Software AG Installer guide for details and instructions.

Explanation If the user tries to launch the installer or uninstaller with a JDK that is too old, this message will be shown. The user will be queried to supply an alternate location for a more recent JDK. {0} - location of the current JDK executing the installer or uninstaller {1} -- version of the current JDK {2} major.minor class version the current version of JDK supports, {3} -- the minimum that is required to execute the client classes.

Action Enter the newer JDK installation directory and the installer or uninstall will execute themselves again using that JDK.

DistManInstallMain.relaunchNoJavaHome – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. You must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. You can use the -javaHome command line option to launch the uninstaller using a different JDK.

Explanation This message is displayed when the user tries to execute the installer or uninstaller with a JDK version that is too old. This can happen, for example, if the user installs webMethods 6 (which includes JDK 1.3 or 1.3.1) and tries to run the uninstaller. The message parameters are {0} - Installation home directory for java, {2} major.minor version of the java the user used to run the installer or uninstaller {3} - the major.minor version that is required as an absolute minimum.

Action As long as the user is not using console mode and running the installer, the user can point the installer or uninstaller at a newer JDK installation; the installer or uninstaller will launch again using that JDK.

InstallDirWizardPanel.cannotFindRegistryKeys – The Software AG Uninstaller cannot find the proper registry keys for this installation and cannot continue.

LockedFilesWizardPanel.explainText – The installer has detected running processes that must be stopped before you can continue. First shut down the listed products; this might also automatically shut down other listed processes. Shut down products by stopping services or exiting applications. Do not use Task Manager. If you need shutdown instructions, see the product documentation.

SAGEnvironmentManagerUnix.configFileNotReadable – The installation user has no permissions to read the config file "{0}"! Change the permissions and try again or exit the current installation.

Explanation The message that pops up when the current installation user has no read permission for the config file '/etc/sagconf.xml' on Unix systems.

ZipManager.errorLockedFile – The process cannot access the file because another process has locked a portion of the file.

18 Integration Server Messages

0701.002E	**Mobile application "{0}" version {1} is already registered.**
Explanation	A mobile application with this name and version already exists.
Action	Provide a different application name or version.

0701.003E	**Upload service "{0}" is not available.**
Explanation	The upload service supplied during mobile sync component creation does not exist in the specified namespace.
Action	Make sure the service exists within the specified namespace and that the namespace and service name are typed correctly.

0701.004E	**Download service "{0}" is not available.**
Explanation	The download service supplied during mobile sync component creation does not exist in the specified namespace.
Action	Make sure the service exists within the specified namespace and that the namespace and service name are typed correctly.

0701.005E	**Document type "{0}" is not available.**
Explanation	The business doc type supplied during mobile sync component creation does not exist in the specified namespace.
Action	Make sure the document type exists within the specified namespace and that the namespace and document type are typed correctly.

0701.006E	**Mobile sync component "{0}" is suspended and cannot be changed.**
Explanation	An attempt was made to edit the mobile sync component, but changes cannot be made to a mobile sync component when the component is suspended.
Action	Disable the mobile sync component and try to edit the component again.

0701.007E	**Mobile sync component "{0}" is associated with mobile application "{1}" version {2}. Remove association before deleting mobile sync component.**
Explanation	An attempt was made to delete a mobile sync component that is associated with a mobile application.
Action	Remove the association between the mobile sync component and the mobile application. In the Integration Server Administrator, navigate to the Solutions > Mobile Support > Mobile Apps screen, click the name of the application to edit its associations, and deselect the mobile sync component from the Mobile Sync Component Alias list. Then, try deleting the mobile sync component again.

0701.008E	**Error: {0}**
Explanation	Mobile Support encountered an error while validating the namespaces for the download service, upload service, or business doc type supplied during creation of a mobile sync component.
Action	Make sure that the service or doc type exists within the specified namespace and that the entry is typed correctly.

0701.009E	**Mobile application "{0}" version {1} was not found.**
Explanation	Mobile Support could not find the specified mobile application and version while retrieving, updating, or deleting the mobile application or processing a synchronization request.
Action	Specify a valid mobile application and version.

0701.012E	**Mobile sync component "{0}" could not be suspended. Error: {1}**
Explanation	Mobile Support could not suspend the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.014E	**Conflict resolution rule is not valid.**
Explanation	The conflict resolution rule specified during mobile sync component creation is not valid.
Action	Specify a conflict resolution rule of either "Client wins" or "Server wins".

0701.015E	**Mobile sync component "{0}" already exists.**
Explanation	Mobile Support could not create the mobile sync component because the specified alias already exists.
Action	Specify a different alias for the mobile sync component.

0701.016E	**Mobile sync component "{0}" was not found.**
Explanation	Mobile Support could not find the specified mobile sync component while retrieving, updating, enabling or disabling, or deleting the mobile sync component or associating a mobile application with the component.
Action	Specify the alias of an existing mobile sync component.

0701.022E	**Mobile sync component "{0}" could not be created. Error: {1}**
Explanation	Mobile Support could not create the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.023E	**Mobile sync component "{0}" could not be deleted. Error: {1}**
Explanation	Mobile Support could not delete the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.024E	**Mobile sync component "{0}" could not be updated. Error: {1}**
Explanation	Mobile Support could not update the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.025E	**Mobile sync component "{0}" could not be enabled. Error: {1}**
Explanation	Mobile Support could not enable the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.026E	**Mobile sync component "{0}" could not be disabled. Error: {1}**
Explanation	Mobile Support could not disable the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.027E	**Mobile sync components could not be retrieved.**
Explanation	Mobile Support could not retrieve the list of mobile sync components.
Action	Check the server log for details about this error.

0701.028E	**Mobile sync component "{0}" could not be retrieved. Error: {1}**
Explanation	Mobile Support could not retrieve the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.029E	**Mobile sync component "{0}" could not be deleted or edited.**
Explanation	The mobile sync component cannot be deleted or edited because the component is still enabled.
Action	Disable the mobile sync component and try to edit or delete the component again.

0701.030E	**Upload service "{0}" is not implementing the "{1}" specification.**
Explanation	The upload service provided during mobile sync component creation is not implementing the Mobile Support upload specification.
Action	Edit the upload service to include a reference to the wm.mobile.datasync.specs:uploadSpec specification.

0701.031E	**Download service "{0}" is not implementing the "{1}" specification.**
Explanation	The download service provided during mobile sync component creation is not implementing the Mobile Support download specification.
Action	Edit the download service to include a reference to the wm.mobile.datasync.specs:downloadSpec specification.

0701.032E	**"{0}" is not a valid Integration Server service node.**
Explanation	The download or upload service specified during mobile sync component creation is not a valid Integration Server service node.
Action	Ensure that element specified for the download or upload service is an Integration Server flow service (that is, a node type of NSService) and not another type of element.

0701.033E	**Mobile sync component state "{0}" is not valid.**
Explanation	Mobile Support detected that an external attempt was made to invoke a mobile sync component that is in a state other than "enabled," "disabled," or "suspended." As a result, Mobile Support has rejected the request to invoke the mobile sync component.
Action	No action is necessary.

0701.034E	**Mobile application "{0}" version {1} could not be created. Error: {2}**
Explanation	Mobile Support encountered an error while associating the mobile application with a mobile sync component.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.035E	**Mobile application "{0}" version {1} could not be updated. Error: {2}**
Explanation	Mobile Support encountered an error while updating the mobile application.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.036E	**Mobile application "{0}" version {1} could not be retrieved. Error: {2}**
Explanation	Mobile Support encountered an error while retrieving details about the association between the mobile application and a mobile sync component.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.037E	**Mobile applications could not be retrieved. Error: {0}**
Explanation	Mobile Support encountered an error while retrieving details about the associations between mobile applications and mobile sync components.
Action	Check the server log for details and take appropriate corrective action.

0701.038E	**Mobile application "{0}" version {1} could not be removed. Error: {2}**
Explanation	Mobile Support encountered an error while removing the association between the mobile application and a mobile sync component.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.041E	**Row identifier "{0}" is not present in business doc type "{1}".**
Explanation	The business doc type does not contain the specified row identifier.
Action	When specifying row identifiers during mobile sync component creation, be sure the row identifiers are present in the specified business doc type.

0701.042E	**Row identifier "{0}" must be a string or an object.**
Explanation	A row identifier was provided that is not a string or an object.
Action	When specifying row identifiers during mobile sync component creation, be sure the row identifiers are strings or objects.

0701.043E	**"{0}" is not a document type node.**
Explanation	A business doc type was provided that is not of type NSRecord.
Action	When specifying a business doc type during mobile sync component creation, be sure the business doc type is of type NSRecord.

0701.044E	**Mobile application "{0}" version {1} is not associated with the mobile sync component "{2}".**
Explanation	Mobile Support could not complete the synchronization operation because the mobile application is not associated with the specified mobile sync component.
Action	In Integration Server Administrator, go to the Mobile Support > Mobile App page and associate the mobile application with the specified mobile sync component.

0701.045E	**Mobile sync component "{0}" could not be suspended. Only enabled mobile sync components can be suspended.**
Explanation	An attempt was made to suspend the mobile sync component, but the attempt failed because the mobile sync component was not enabled.
Action	Ensure that the mobile sync component is enabled before attempting to suspend it.

0701.046E	**Requested mobile sync component "{0}" is not enabled.**
Explanation	Mobile Support could not process the synchronization request because the specified mobile sync component is not enabled.
Action	In Integration Server Administrator, go to the Mobile Support > Mobile Sync Components page and enable the mobile sync component. Then, resubmit the synchronization request.

0701.047E	**No mobile sync component was specified.**
Explanation	Mobile Support could not process the synchronization request because no mobile sync component was specified.
Action	Ensure that the synchronization request includes a mobile sync component alias and a mobile application name and version.

0701.048E	**Mobile sync component "{0}" cannot be suspended because it was configured to not store business data in the sync store.**
Explanation	Mobile Support could not suspend the specified mobile sync component because the Store Business Data check box was not selected in Integration Server Administrator when the mobile sync component was configured. When business objects are not stored in the sync store, mobile sync components can be disabled but not suspended.
Action	In Integration Server Administrator, on the Solutions > Mobile Support > Mobile Sync Components screen, disable the mobile sync component.

0701.049E	**Mobile sync component "{0}" cannot be refreshed because it was configured to not store business data in the sync store.**
Explanation	Mobile Support could not refresh the specified mobile sync component because the Store Business Data check box was not selected when the mobile sync component was configured. When business objects are not stored in the sync store, mobile sync components cannot be refreshed.
Action	In Integration Server Administrator, on the Solutions > Mobile Support > Mobile Sync Components > Edit Mobile Sync Component screen, select the Store Business Data check box. Then, disable and enable the mobile sync component.

0701.057E	**Error occurred while processing record "{0}".**
Explanation	Mobile Support encountered an error while processing the specified record.
Action	Check the server log for details and take appropriate corrective action.

0701.068E	**"{0}" is not locked by thread "{1}".**
Explanation	The thread attempted to unlock the specified record, but the record is not owned by the thread.
Action	Try the request again. If the issue recurs, contact Software AG Global Support.

0701.069E	**Thread "{0}" could not unlock record "{1}" because record is already unlocked.**
Explanation	The thread attempted to unlock the specified record, but the record was not locked.
Action	Try the request again. If the issue recurs, contact Software AG Global Support.

0701.080E	**Could not refresh mobile sync component "{0}". Mobile sync component is in "{1}" state.**
Explanation	Mobile Support could not refresh the mobile sync component because the component is not suspended.
Action	Suspend the mobile sync component.

0701.093E	**Error occurred while initializing sync store.**
Explanation	Mobile Support experienced an error while initializing the sync store.
Action	Check the server log for details and take appropriate corrective action.

0701.095E	**Validation Error occurred: {0}.**
Explanation	Mobile Support could not process the data row because the data that was submitted was not valid.
Action	Correct the validation error.

0701.096E	**Message "{0}" skipped. Unique ID is missing.**
Explanation	Mobile Support could not process the data row because the data does not contain row identifier(s).
Action	Supply one or more row identifiers.

0701.097E	**Unable to synchronize the mobile device. Exception: {0}**
Explanation	Mobile Support could not synchronize the mobile device for the reason specified.
Action	Check the server log for details and take appropriate corrective action.

0701.112E	**Unable to save the record associated with unique ID and mobile sync component of "{0}". Exception: {1}**
Explanation	Mobile Support could not save the record for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.113E	**Unable to save record data. Exception: {0}**
Explanation	Mobile Support could not save the record data for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.114E	**Unable to write record data. Exception: {0}**
Explanation	Mobile Support could not write the record data for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.117E	**Unable to delete record associated with unique ID "{0}" and mobile sync component "{1}". Reason: {2}**
Explanation	Mobile Support could not delete the record for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.118E	**Unable to delete record associated with mobile sync component "{0}". Reason: {1}**
Explanation	Mobile Support could not delete the record for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.119E	**Unable to get records from sync store. Reason: {0}**
Explanation	Mobile Support could not retrieve records from the sync store for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.121E	**Unable to obtain connection from connection pool. Exception: {0}**
Explanation	Mobile Support could not obtain a connection from the connection pool for the reason indicated.
Action	In Integration Server Administrator, on the Settings > JDBC Pools screen, select the pool alias associated with the MobileSupport functional alias. On the Connection Aliases > Edit screen, increase the number of maximum connections.

0701.122E	**Unable to obtain database connection from connection pool for sync store.**
Explanation	Mobile Support could not obtain a connection to the database configured for the sync store.
Action	In Integration Server Administrator, on the Settings > JDBC Pools screen, test the connection from the MobileSupport functional alias to the database. Take appropriate corrective action to resolve any errors.

0901.001E	**Name cannot be null or empty.**
Explanation	While creating or updating an OData element, Name cannot be null or empty.
Action	Provide a valid Name for the OData element.

0901.002E	**The specified name is invalid. Ensure that the name does not exceed 480 characters, does not start with a number or "_" symbol, and that it contains no special characters other than "_".**
Explanation	Specified name is invalid because name can contain only alphanumeric characters and \"_\" symbol. Name must start with an alphabet and not with a number or \"_\" symbol.
Action	Provide a valid name that starts with an alphabet and contains only alphanumeric characters and \"_\" symbol. For information about other supported unicode characters, see SimpleIdentifier in Common Schema Definition Language (CSDL) documentation.

0901.003E	**Length of the Name cannot exceed 480 characters.**
Explanation	The Name specified contains more that 480 characters.
Action	Ensure that the length of the Name does not exceed 480 charatcters.

0901.004E	**Cannot rename Complex Type name to "{0}". Complex Type name must be unique.**
Explanation	The Complex Type name could not be renamed because a Complex Type with the same name already exists.
Action	Enter a unique Name for the Complex Type.

0901.005E	**Cannot rename Entity Type name to "{0}". Entity Type name must be unique.**
Explanation	The Entity Type name could not be renamed because an Entity Type with the same name already exists.
Action	Enter a unique Name for the Entity Type.

0901.006E	**Cannot rename Property name to "{0}". Property name must be unique.**
Explanation	The Property name could not be renamed because a Property with the same name already exists.
Action	Enter a unique Name for the Complex Type.

0901.007E	**Cannot delete Complex Type because it is referred to by "{0}".**
Explanation	The Complex Type cannot be deleted because it is referred to by a Complex property.
Action	Ensure that all references to the Complex Type is removed before deleting it.

0901.008E	**A Property with the same name already exists in the Entity Type.**
Explanation	The new Property with the specified name cannot be added because another Property with the same name already exists in the Entity Type.
Action	Enter a unique Name for the new Property that you want to add.

0901.009E	**A Property with the same name already exists in the Complex Type.**
Explanation	The new Property with the specified name cannot be added because another Property with the same name already exists in the Complex Type.
Action	Enter a unique Name for the new Property that you want to add.

0901.010E	**An Entity Type with the same name already exists in the OData Service.**
Explanation	The new Entity Type cannot be created with the specified name because another Entity Type with the same name already exists in the OData Service.
Action	Enter a unique Name for the Entity Type that you want to add.

0901.011E	**A Complex Type with the same name already exists in the OData Service**
Explanation	The new Complex Type cannot be added with the specified name because another Complex Type with the same name already exists in the OData Service.
Action	Enter a unique Name for the Complex Type that you want to add.

0901.012E	**An Association with the same name already exists in the OData Service.**
Explanation	A new Association with the specified name cannot be created because another Association with the same name already exists in the OData Service.
Action	Enter a unique name for the Association that you want to add.

0901.013E	**Invalid index position "{0}"; Unable to move the OData element.**
Explanation	Unable to move the OData element to an invalid index position.
Action	Ensure that the element is moved to an index position within the same container.

0901.014E	**Invalid property. Property "{0}" does not exist and hence, cannot be moved.**
Explanation	The specified Property cannot be moved because it does not exist.
Action	Ensure that the Property you want to move is already added to the OData service.

0901.015E	**Cannot delete Entity Type because it is referred to by one of the Associations.**
Explanation	The Entity ype cannot be deleted bacause it is referred to by one of the Associations.
Action	Ensure that all references to the Entity Type is removed before deleting it.

0901.016E	**Facet "{0}" is not applicable for Type "{1}"**
Explanation	The specified Facets property is not applicable for the selected Type.
Action	Ensure that only those Facets that apply to the selected Type are specified.

1000.0042E	**Error in parsing EDM simple type "{0}" while evaluating the filter query.**
Explanation	Error in parsing the literal value of the filter expression because the literal value is incorrect.
Action	Ensure that the correct literal value is given in the filter expression.

1000.0043E	**Error in parsing property "{0}" in the Entity Data Model (EDM) while evaluating the filter query.**
Explanation	Error in parsing the property value of the filter expression.
Action	Ensure that the correct property value is given in the Entity Data Model (EDM).

1000.0044E	**Error in evaluating the filter expression "{0}".**
Explanation	The syntax of the filter expression is incorrect.
Action	Ensure that the syntax of the filter expression is correct.

1000.0047E	**Internal server error for request "{0}" due to "{1}"**
Explanation	Validation error from Olingo.
Action	Refer to the error message text for more details and correct the URL specified.

1000.0048E	**OData request "{0}" failed with error code "{1}" reason "{2}"**
Explanation	Validation error from Olingo.
Action	Refer to the error message text for more details and correct the URL specified.

1000.0049E	**Entity type "{0}" not found in the entity data model.**
Explanation	The entity type specified in the OData request is incorrect, deleted, or not available in the entity type model.
Action	Ensure that the entity type that you specified exists in the entity data model.

1000.0050E	**Odata data request failed with the error "{0}"**
Explanation	Error in the OData handler because the request is malformed.
Action	See the information provided in the error message and correct the request URL.

1000.0052E	**Error in retrieving NSOdata service node from OData Context.**
Explanation	The OData service node in the OData context is null.
Action	Ensure that the path to the OData service node specified in the request URL is correct.

12.31	**Invalid SAML assertion. The trust/signature validation failed with exception: {0}**
Explanation	Integration Server received a SAML assertion that either failed during signature validation or it did not come from a trusted issuer.
Action	Review the request and work with the sender to correct the issues.

12.45	**Error in getting security token form SAML assertion. SAML Assertion is: {0}**

12.46	**No user mapped to this X509 certificate.**

12.47	**No X509 certificate chain found.**

12.48	**No PAM authentication module.**

12.49	**No PAM user found.**

12.50	**Basic authentication, no user found.**

12.51	**Digest authentication, no user found.**

12.52	**Default authentication, no user found.**

12.53	**Request {0} for subject {1} was rejected.**

12.54	**Using account {0} for {1} subject {2}.**

12.55	**Error initializing OpenID Provider: {0}: {1}**
12.56	**Error initializing OpenID Providers**
12.57	**Requesting delegatable kerberos token for user: {0}**
12.58	**Server logged in as user : {0} into KDC**
12.59	**Kerberos delegated credentials set for user: {0}**
12.60	**Found kerberos delegated credentials for user: {0} . Placed in Context**
12.61	**Logged in as {0} . Using delegated kerberos credentials of {1} to request for service principal**
12.62	**Obtained delegated kerberos token for user : {0}**
12.63	**Kerberos ticket is set in the HTTP header: {0}**
12.64	**Kerberos delegated credentials set for : {0}**
12.65	**Unable to initialize the set of external OAuth Authorization Servers**
12.9999...0	**{0}**
13.10	**Unable to register multipart coder {0} for service {1}. A coder is already registered with that service name.**
13.11	**Unable to deregister multipart coder for service {0}. There is no coder registered with that service name.**

13.5	**Deregistering multipart content handler for service {0}.**
13.6	**Registering multipart coder {0} for service {1}.**
13.7	**Deregistering multipart coder for service {0}.**
13.8	**Unable to register multipart content handler {0} for service {1}. A content handler is already registered with that service name.**
13.9	**Unable to deregister multipart content handler for service {0}. There is no content handler registered with that service name.**
14.59	**OutboundPasswordManager could not find package: {2}**
14.60	**Master password updated for package: {0}**
14.61	**Package {2} is not enabled.**
14.62	**Package name cannot be null.**
14.63	**The value specified for the watt.server.xml.encoding parameter is not supported by your JVM. Integration Server might not be able to process the XML files.**
14.64	**Error while sending password expiry email, error message : {0}.**
14.65	**Passwords for users {0} has expired, the current expiration interval is {1} days.**
14.66	**Passwords for users {0} will expire soon.**

147.4	**Error while executing command {0}: {1}**
149.25W	**Possible SQL injection threat for {0} database**
Explanation	Incoming request to Enterprise Gateway Server contains suspicious data (payload), which could possibly cause an SQL injection attack.
Action	Contact the Integration Server system administrator to inspect and validate the incoming request to avert an SQL injection attack.
149.26W	**Possible SQL injection threat detected with the incoming payload.**
Explanation	Incoming request to Enterprise Gateway Server contains suspicious payload, which could possibly cause an SQL injection attack.
Action	Contact the Integration Server system administrator to inspect and validate the incoming request to avert an SQL injection attack.
15.9999	**{0}**
154.1	**{0}**
155.9998	**Exception --> {0}**
163.1	**JWT Token is not present. Send a Bearer token along with the request.**
163.10	**The JWT does not contain an Issuer claim (iss).**
163.11	**The certificate used to verify the JWT signature has expired (trustStore={0}, keyStore={1}).**
163.12	**The certificate used to verify the JWT signature is not yet valid (trustStore={0}, keyStore={1}).**
163.13	**The JWT signature could not be verified by any of the certificates mapped to the JWT issuer ({0}).**

163.2	**Unable to find user corresponding to the JWT Bearer token.**
163.3	**Verifying with truststore alias "{0}" and certificate alias "{1}".**
163.4	**Verified claim : "{0}".**
163.5	**User "{0}" found in the JWT Bearer token.**
163.6	**JWT does not contain a Subject claim (sub).**
163.7	**The JWT aud claim does not contain the Audience configured for this Integration Server.**
163.8	**The JWT is not yet valid. The current time is before the nbf value.**
163.9	**The JWT has expired. The current time is after exp value.**
163.9999	**Exception --> {0}**
21.1001E	**The on-premise service signature cannot be null or empty.**
Explanation	While creating an Integration Cloud connector service, the service signature cannot be null or empty.
Action	Ensure that service signature is not null or empty while invoking the service to generate an Integration Cloud connector.
21.1002E	**Package name cannot be null or empty.**
Explanation	While creating an Integration Live connector service, the package name cannot be null or empty.
Action	Ensure that you specify the package name while invoking the service to generate an Integration Live connector.

21.1003E	**The on-premise service name cannot be null or empty.**
Explanation	While creating an Integration Live connector service, the on-premise service name cannot be null or empty.
Action	Ensure that you specify an on-premise service name while invoking the service to generate an Integration Live connector.

21.1004E	**Connector service name cannot be null or empty.**
Explanation	While creating an Integration Live connector service, the connector service name cannot be null or empty.
Action	Ensure that the connector service name is not null or empty while invoking the service to generate an Integration Live connector.

21.1005E	**An error occurred while creating the webMethods Cloud connector service. Details: {0}**
Explanation	Unknown error occurred while creating the Integration Live connector service.
Action	Contact Software AG global support.

21.1006E	**Interface name cannot be null or empty.**
Explanation	While creating the Application folder structure, the Interface name cannot be null or empty.
Action	Ensure that you specify the Interface name while invoking the service to create the Application folder structure.

21.1007E	**Application name cannot be null or empty.**
Explanation	While creating the Application folder structure, the Application name cannot be null or empty.
Action	Ensure that you specify the application name while invoking the service to create the Application folder structure.

21.1008E	**An error occurred while creating the application interface. Details: {0}**
Explanation	Unknown error occurred while creating the application interface.
Action	Contact Software AG global support.

21.2001E	**An error occurred while connecting to the Universal Messaging Realm. Error: {0}**
Explanation	Integration Server encountered the specified error while connecting to the Universal Messaging Realm.
Action	Ensure that the Realm URL and that the port identified in the URL is active on the Universal Messaging Server. In addition, take the appropriate action based on the details shown in the message.

21.2002E	**User {0} is not authorized to perform administrative functions on the Universal Messaging Realm.**
Explanation	The specified user does not have the rights required to perform administrative functions.
Action	Log on with a user name that has the proper permissions to perform administrative functions.

21.3E	**No Git credentials were found for tenant {0} (user {1}). Cannot access the remote Git repository.**
Explanation	Integration Server is not provisioned with Git credentials for the tenant.
Action	Contact the system administrator.

21.4E	**Tenant {0} has no credentials. Cannot fetch tenant's package from repository.**
Explanation	Integration Server is not provisioned with GIT credentials for the tenant.
Action	Contact the system administrator.

21.5E	**The local Git repository does not exist for package {0}.**
Explanation	The specified package is not associated with a local Git repository.
Action	Contact the system administrator.

21.6002E	**Settings could not be saved because of the following error: {0}**
Explanation	The settings could not be saved because of the specified error.
Action	Take the appropriate action based on the details shown in the message.

21.6003E	**The following error occurred while saving settings: {0}. See the error log for the full stack trace.**
Explanation	Integration Server encountered the specified error while saving the settings.
Action	Review the server log for details and take appropriate corrective action.

21.6004E	**An error occurred while loading information from the webMethods Clould environment.**
Explanation	Integration Server encountered an error while loading information from the webMethods Cloud environment.
Action	Review the server log for details and take appropriate corrective action.

21.6005E	**webMethods Cloud information was not loaded because the settings are not specified.**
Explanation	You must specify the settings on the Settings page to load webMethods Cloud information.
Action	Specify the settings on the Settings page.

21.7E	**An exception occurred during the Git operation for package {0}: {1}**
Explanation	Integration Server encountered the specified error during the Git operation.
Action	Contact the system administrator.

21.7003E	**Could not save application {0}. A service with Display Name {1} already exists**
Explanation	A service with the specified display name already exists within the application. The display name of each service in the application must be unique.
Action	Specify a unique display name for the service.

21.7004E	**Could not save application {0} because there are no services selected.**
Explanation	There are no services specified for the application. You must specify at least one service for an application to be valid.
Action	Specify one or more services for the application.

21.7007E	**The following error occurred while saving application {0}: {1}. See the error log for the full stack trace.**
Explanation	Integration Server encountered the specified error while saving the application.
Action	Review the error log and correct the error.

21.7008E	**The following error occurred while deleting application {0}: {1} See the error log for the full stack trace.**
Explanation	Integration Server encountered the specified error while deleting the application.
Action	Review the error log and correct the error.

21.7009E	**The application named {0} does not exist.**
Explanation	The application's name contains too many characters.
Action	Rename the application using no more than 32 characters.

21.7009...0E	**The application named {0} does not exist.**
Explanation	The application does not exist. It might have been deleted by another user.
Action	Retry the action. If the issue persists, contact your system administrator.

21.7010E	**An application named {0} already exists.**
Explanation	The application is not valid because another application with the specified name already exists.
Action	Specify a unique application name.

21.7011E	**Could not save application {0} because the Display Name field for one or more of the services is empty.**
Explanation	The Display Name field is not specified for one or more services selected for the application.
Action	Specify a valid Display Name for each service in the application.

21.7012E	**Application {0} could not be saved because the Name contains: {1}.**
Explanation	The application's name contains the specified illegal character, leading digit, or reserved word.
Action	Rename the application.

21.7013E	**Application {0} could not be saved because the service Display Name {1} contains: {2}**
Explanation	The Display Name field of a service in the application contains the specified illegal character, value, or reserved word.
Action	Remove the specified character, value, or word from the Display Name.

21.7014E	**The following error occurred while uploading application {0}: {1}. See the error log for the full stack trace.**
Explanation	The specified error occured while uploading the application.
Action	Review the error log and correct the error.

21.7016E	**Application {0} could not be uploaded because of the following error: {1}**
Explanation	Integration Server encountered the specified error while uploading the application.
Action	Check the server log for details and take appropriate corrective action.

21.7020E	**Applications require that at least one account be selected before they can be uploaded.**
Explanation	Applications require that at least one connection be selected before it can be uploaded.
Action	Select a connection for the application.

21.7021E	**No accounts exist. Go to webMethods Cloud > Accounts and create an account.**
Explanation	Applications require that at least one account be selected before being uploaded, but no accounts have been created.
Action	Go to webMethods Clould > Accounts and create at least one account.

21.7022E	**The on-premise Integration Server could not upload the application because the service {0} does not exist.**
Explanation	The specified service does not exist.
Action	Confirm that the service exists on the system.

21.8001E	**Account with alias name {0} does not exist.**
Explanation	There is no account with the specified alias name on Integration Server.
Action	Check the alias name of the Integration Live account that you are attempting to use to ensure you have the correct name.

21.8002E	**Account with alias name {0} already exists.**
Explanation	The account is not valid because another account already uses the specified alias name.
Action	Specify an alias name for the account that is unique for the Integration Server.

21.8003E	**The Alias Name parameter is required.**
Explanation	The Alias Name parameter is required but is either missing or is null.
Action	Make sure the Alias Name parameter is specified and that the value is not null.

21.8005E	**The Tenant ID parameter is required.**
Explanation	The Tenant ID parameter is required but is either missing or is null.
Action	Make sure the Tenant ID parameter is specified and that the value is not null.

21.8006E	**The Run As User parameter is required.**
Explanation	The Run As User parameter is required but is either missing or is null.
Action	Make sure the Run As User parameter is specified and that the value is not null.

21.8012E	**Error while enabling the listener for account {0}.**
Explanation	Integration Server encountered an error while enabling the listener for the specified account.
Action	Check the server log for details and take appropriate corrective action.

21.8013E	**Error while disabling the listener for account {0}.**
Explanation	Integration Server encountered an error while disabling the listener for the specified account.
Action	Check the server log for details and take appropriate corrective action.

21.8019E	**Error sending response for request ID {1} to execute service {0}.**
Explanation	Integration Server encountered an error while sending a response to the request received from webMethods Cloud for the specified request ID.
Action	Check the server log for details and take appropriate corrective action.

21.8021E	**Error executing service {0} for request ID {1}.**
Explanation	Integration Server encountered an error while executing the specified service.
Action	Check the server log for details and take appropriate corrective action.

21.8022E	**Test of the account failed. Confirm that the parameters are correct and tenant is registered in webMethods Cloud.**
Explanation	The test of the account failed.
Action	Make sure that the information provided is correct and that the tenant is registered in webMethods Cloud.

21.8024E	**An error was encountered while executing service {0}. The response was not received within {1} milliseconds.**
Explanation	Integration Server did not receive a response from the service within the time allowed.
Action	Ensure that the on-premise Integration Server is connected to webMethods Cloud and that the account is enabled.

21.8026E	**The information for account {0} was not uploaded successfully on stage {1}. Check the Integration Server logs for more details. Error: {2}**
Explanation	Integration Server encountered the specified error while uploading the account.
Action	Check the server log for details and take appropriate corrective action.

21.8027E	**Service {0} is not shared by on-premise for application {1}.**
Explanation	The specified service is not shared by the on-premise Integration Server.
Action	Make sure that the service is assigned to the specified application.

21.8029E	**Invalid account {0} associated with the execution of service {1}.**
Explanation	The specified account is not associated with the application that shares the service.
Action	Ensure that the application that shares the service is associated with the specified account.

21.8031E	**Account {0} was not removed from stage {1}. Check the Integration Server logs for more details. Error: {2}**
Explanation	The specified account was not deleted from the stage.
Action	Check the server error log for more detailed information and take the appropriate corrective action.

21.8032E	**Invalid value {1} specified for the stage parameter of account {0}.**
Explanation	The account settings were not retrieved correctly from webMethods Cloud.
Action	Make sure that you obtained the correct account settings from webMethods Cloud.

21.8033E	**No account information is configured for webMethods Cloud.**
Explanation	You cannot upload or enable accounts or applications without first configuring the account settings.
Action	Specify the account settings and retry the operation.

21.8034E	**The webMethods Cloud account endpoint to which the on-premise Integration Server should send responses is not valid**
Explanation	You cannot upload or enable accounts or applications without first configuring the account settings.
Action	Specify the account settings and retry the operation.

21.8035E	**Invalid account settings. Make sure that webMethods Cloud settings are configured.**
Explanation	Integration Server cannot connect to webMethods Cloud because there are no settings configured for the webMethods Cloud.
Action	Configure a valid webMethods URL on the Settings screen of the Integration Server Administrator.

21.8036E	**Stage for the account is not configured on webMethods Cloud. Contact webMethods Cloud Administrator.**
Explanation	The stage specified for the account does not exist on Integration Cloud.
Action	Contact the webMethods Cloud administrator.

21.8037E	**Stage for the application is not configured on webMethods Cloud. Contact webMethods Cloud Administrator**
Explanation	The stage specified for the application does not exist on Integration Cloud.
Action	Contact the webMethods Cloud administrator.

21.9003E	**Cannot delete account {0} because it is in use by other applications.**
Explanation	The specified account is in use by other applications and cannot be deleted.
Action	Modify the application to use a different account, or leave the account active.

21.9006E	**Unable to connect to on-premise Integration Server for account {0}.**
Explanation	The specified account cannot be tested.
Action	Ensure that the specified account is enabled on the on-premise Integration Server.

24.23	**Central User Manager queried for group "{0}" of type {1} and returned "{2}".**

24.24	**Central User Manager queried for user "{0}" and returned "{1}".**
24.25	**Central User Manager queried for membership. User "{0}" {1} a member of "{2}".**
24.26	**Central User Manager found user "{0}" in "{1}" of type {2}.**
24.27	**Central User Manager searched for group "{0}" and returned "{1}".**
24.28	**Central User Manager searched for user "{0}" and returned "{1}".**
24.39E	**Error while creating Integration Live user groups, tenantID : {0}. Error message: {1}. Stack trace: {2}**
Explanation	An unexpected error occurred while creating Integration Live user groups.
Action	Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
24.41	**Integration Live Manager addUserInGroup(), --> group "{0}" reterived from UserManager for group id "{1}".**
24.42	**Integration Live Manager addUserInGroup(), --> user "{0}" added into group "{1}".**
24.43	**Integration Live Manager updateUserInGroup(), --> before update user "{0}", saml security token "{1}".**
24.44	**Integration Live Manager updateUserInGroup(), --> after update user "{0}", saml security token "{1}".**
24.45	**Integration Live Container UserManager addUser(), SagSecurityToken --> {0}.**
24.46	**Integration Live Container UserManager addUser(), tenantID: {0}.**

24.47 **Integration Live Container UserManager addUser(), user already present--> {0} but it got updated using this Assertion.**

24.48 **Integration Live Container UserManager addUser(), user added--> {0}.**

24.49 **Integration Live Container UserManager removeUser(), user--> {0}.**

24.50 **Integration Live Container UserManager removeUser(), user removed successfully--> {0}.**

24.51 **Integration Live Container UserManager getUser(), user not found --> {0}.**

24.52 **Integration Live Container UserManager addUserInGroup(), --> group "{0}" reterived from UserManager.**

24.53 **Integration Live Container UserManager addUserInGroup(), --> user "{0}" added into group "{1}".**

24.54 **Integration Live Container UserManager addUserInGroup(), --> group "{0}" is not found so not adding to user {1}.**

24.55 **Integration Live Container UserManager addUserInGroup(), --> role "{0}" reterived from UserManager.**

24.56 **Integration Live Container UserManager addUserInGroup(), --> user "{0}" added into role "{1}".**

24.57 **Integration Live Container UserManager addUserInGroup(), --> role "{0}" is not found so not adding to user {1}**

24.58 **Integration Live Container UserManager getUser(), userID: {0}.**

24.59	**Integration Live Container UserManager getUser(), user found --> {0}.**
25.67	**Integration Server could not initialize the cluster. Stopping Integration Server initialization. Use the server log and error log to diagnose and correct the problem.**
25.71	**The JCE Unlimited Strength Jurisdiction Policy File was not found**
28.62	**Unable to load keystores and truststores for package {0}.**
28.63	**Error in un-loading keystores and truststores for package {0}**
3	**Enabled**
35.5	**Number of lines to display must be a non negative number. {0}.**
4	**Disabled**
4.9998	**Exception -> {0}**
5	**Suspended**
50.22	**ForEach failed: {0}: out-array={1}, in-array={2}**
50.23	**ForEach failed: No source data available for in-array {0}**
50.24	**ForEach failed: in-array {0} is not an array type.**
50.25	**ForEach out-array {0} is not the same length as in-array {1}.**

53.15	**The listener for the port with alias "{0}" does not exist.**
53.9999	**{0}**
64.32	**HTTP Put {0}**
64.33	**HTTP Delete {0}**
64.34	**HTTP Head {0}**
64.35	**HTTP Options {0}**
64.36	**HTTP Trace {0}**
68.29	**{0}**
68.30	**{0}**
68.31	**{0}**
7.5	**Access Denied. User "{0}" in tenant {1} does not have permissions to access assets in package {2}.**
71.12	**EPRT command refused. The EPRT address {0} does not match the original host address {1}.**
72.19	**Using default html encoding for input: "{0}"**
72.20	**Exception occurred while initializing encoder {0}. Reason: {1}**

72.21	**Initialization of encoder "{0}" failed**
72.22	**Performing "{0}" encoding for input: "{1}". Output is: "{2}"**
72.23	**Failed to initialize the bundle for encoder "{0}"**
72.24	**Initialization of encoder "{0}" completed**
72.25	**Exception occurred while getting file path of "{0}"**
75.9998	**Unable to extract the password associated with the alias: {0}**
76.35	**A valid encoding is not available in the XML header {0}. Proceeding with the encoding value specified in watt.server.xml.encoding = {1}.**
76.9999	**{0}**
88.9443	**One or more required Headers "{0}" are not present in the SOAP response.**
95.27	**The audit logging database does not populate the CHAR_OCTET_LENGTH field in its metadata. Integration Server cannot determine the maximum number of bytes for the WMSERVICEACTIVITYLOG.FULLMESSAGE and WMSERVICECUSTOMFLDS.STRINGVALUE columns. If the data inserted into these columns need to be truncated, they will be truncated based on the number of characters rather than the number of bytes. This may lead to SQLExceptions while writing to the audit log. To avoid this, use the ALTER TABLE command on your database to increase the size of these columns.**
95.28	**Audit Logging: The {0} has entered fail-fast mode.**
95.29	**Audit Logging: The {0} has exited fail-fast mode.**

95.34	**Audit Logging: Error occurred while reconnecting to session for messaging connection alias {0}; will retry after {1} seconds. Error message: {2}**
95.35	**Audit Logging: Starting monitor for creating session with messaging connection alias {0}; retry interval is {1} seconds.**
95.36	**Audit Logging: Attempting to reconnect to session for messaging connection alias {0}.**
95.41	**Skipping {0} audit log data. It is larger than {1} MB, the limit defined by watt.server.diagnostic.logFiles.maxMB.**
96.11	**The DataStoreDBListener has been notified of SQLException. The JDBC connection to {0} is still valid. Returning it to the pool.**
96.20	**creation of JDBC connection failed with exception : {0}**
96.21	**JDBC Connection pool is currently in Fail-Fast mode for pool {0}:{1}**
96.22	**{0} threads are waiting to get the JDBC Connection for pool {1}:{2}**
96.23	**Connection pool size is {0}, Available pool size is {1} for pool {2}:{3}. The Maximum connection is {4}**
96.24	**Created a new JDBC Connection for pool {0}:{1}. Connection pool size is {2}.**
96.25	**Got Exception for pool {0}:{1}. Exception details: {2}**
96.26	**The JDBC function "{0}", pool alias "{1}" has entered fail-fast mode. The exception message is: {2}**

96.27	**The JDBC function "{0}", pool alias "{1}" has exited fail-fast mode.**
96.28	**Re-initializing the pool {0}:{1}.**
96.29	**Removed the connection from pool {0}:{1}. Connection pool size is {2}. Available pool size is {3}.**
96.30	**Released the connection to pool {0}:{1}. Connection pool size is {2}. Available pool size is {3}.**
96.31	**The JDBC function "{0}", pool alias "{1}" is in fail-fast mode. The exception message is: {2}**
96.8	**JDBC Connection pool threshold {0}, {1} available for pool {2}:{3}**
96.9	**JDBC Connection pool waiting threads threshold {0}, {1} threads waiting for connection for pool {2}:{3}**
98.125	**Exception:{0} while executing trigger. Rejecting Document for TriggerStore:{1}.**
98.126	**Exception:{0} while executing trigger. Unable to mark as complete to the Document History for TriggerStore:{1}.**

ACCOUNT_LOCKED User {0} is locked.

ALREADY_MARKED_ROLLBACK – tran was rolled back because tran was marked for rollback

ANNOTATION_FIELD_DUPLICATE_NAME – {0} - {1} appears more than once in the document type

ANNOTATION_FIELD_ENV – {0} - {1} envelope field is not allowed as an annotation field

ANNOTATION_FIELD_INVALID_NAME – {0} - {1} is not a valid Digital Event Services field name

ANNOTATION_FIELD_NOT_FOUND – {0} - {1} field not found in document type

ANNOTATION_FIELD_NOT_VALID – {0} - {1} field is invalid type

ANNOTATION_NSR_NOT_PUBLISHABLE – Document type is not publishable

ANNOTATION_NSR_NOT_SPECIFIED – Document type not specified

APLog.string(APLog.AP_CONNECTION_TEST_FAILED) – Test of CentraSite connection failed.

Explanation An attempt was made to connect to CentraSite, but a connection could not be made.

Action Check the connection parameters in Integration Server Administrator. Check the error log in both Integration Server and CentraSite.

ART.0114.0002E **Unable to get adapter type information. Internal error.**

Explanation An error occurred while fetching the list of supported services for a particular adapter.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0003E **Unable to get information about adapter type {0}.**

Explanation An error occurred while retrieving a service's localized deployment values (adapter name, adapter version, adapter JCA version) from the specified adapter's metadata.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0004E **Error getting available packages.**

Explanation An error occurred while retrieving a list of packages available for node creation.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0005E	**Error(s) during Adapter Runtime startup.**
Explanation	An error occurred during the initialization of the com.wm.pkg.art.AdapterRuntimeGlobals class.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0006E	**Unable to initialize transaction manager. Transaction manager already initialized.**
Explanation	WmART has attempted to initialize the Transaction Manager twice.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0007E	**Unable to get managed connection factories for adapter type {0}.**
Explanation	WmART was unable to obtain a list of connection factories for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0008E	**Unable to get the description and display name for connection type "{0}" of adapter type "{1}".**
Explanation	An error occurred while getting the display name and description for the specified connection/listener in the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0009E	**Error(s) while registering adapter type {0}.**
Explanation	An error occurred while loading the specified adapter.
Action	This might be due to a connection that failed to initialize properly. Ensure that the adapter's connections can communicate with their respective resources. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0010E	**Error(s) while unregistering adapter type {0}.**
Explanation	An error occurred while shutting down the specified adapter's connection resources.
Action	This might be due to problems in one or more connections. Ensure that all adapter connections shut down properly when the adapter was unloaded.

ART.0114.0011E	**Error occurred while Adapter Runtime was loading an adapter type. Missing required input, "{0}".**
Explanation	The class name of an adapter was not present as the first item in the pipeline given to com.wm.pkg.art.deployment.Service.registerAdapterType.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0012E	**Error occurred while Adapter Runtime was loading an adapter type. Unexpected adapter type object "{0}" for input "{1}".**
Explanation	The class name of the object passed to com.wm.pkg.art.deployment.Service.registerAdapterType is not derived from WmAdapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0013E	**Error occurred while Adapter Runtime was loading adapter type "{0}".**
Explanation	An error occurred while loading the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0014E	**Error occurred while Adapter Runtime was unloading an adapter type. Missing required input, "{0}".**
Explanation	The class name of an adapter was not present as the first item in the pipeline given to com.wm.pkg.art.deployment.Service.unregisterAdapterType.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0015E	**Error occurred while Adapter Runtime was unloading an adapter type. Unexpected adapter type object "{0}" for input "{1}".**
Explanation	The class name of the specified object passed to com.wm.pkg.art.deployment.Service.unregisterAdapterType is not derived from WmAdapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0016E	**Error occurred while Adapter Runtime was unloading adapter type "{0}".**
Explanation	An error occurred while loading the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0017E	**Error occurred while registering XidFactory for adapter type "{0}".**
Explanation	WmART was unable to locate the Transaction Manager or Transaction ID Factory class for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0018E	**Unable to get XidFactories for adapter type "{0}".**
Explanation	WmART was unable to locate the class loader while retrieving the Transaction ID Factory map for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0019E	**Unable to get XidFactory {0} for XAResource {1} in adapter type "{2}".**
Explanation	WmART was unable to determine the corresponding XidFactory class for the specified XAResource class while loading the adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0020E	**Error occurred while loading online help system for adapter type "{0}".**
Explanation	An error occurred while WmART was attempting to fetch the path to the specified adapter's online help file.
Action	Ensure that a help page key exists in your AdapterResourceBundle for ADKGLOBAL.RESOURCEBUNDLEKEY_LISTRESOURCES, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTCONNECTIONTYPES, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTPOLLINGNOTIFICATIONS, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTPOLLINGNOTIFICATIONDETAILS, and ADKGLOBAL.RESOURCEBUNDLEKEY_ABOUT.

ART.0114.0021E	**Error occurred while loading copyright for adapter type "{0}".**
Explanation	Failed to read a third-party copyright file for the specified adapter.
Action	If you have explicitly specified ADKGLOBALS.RESOURCEBUNDLEKEY_THIRDPARTYCOPYRIGHTURL in the adapter's resource bundle, ensure that the file this key references is in the pub directory in the adapter's directory tree. Also ensure that this file is readable by Integration Server.

ART.0114.0022E	**Error in {0}. Missing or invalid parameter: {1}.**
Explanation	A value was not specified for the parameter of the specified method.
Action	If you explicitly invoked the specified method, check your parameter values and resubmit. Otherwise, look in the error log for related errors.

ART.0114.0030E	**Unable to create node {0} in the namespace.**
Explanation	WmART failed to create the specified connection or listener node in the namespace.
Action	The connection/listener information you provided in Integration Server Administrator is invalid, or perhaps duplicates an existing connection/listener in the same namespace. Refer to adjacent log entries for specifics.

ART.0114.0031E	**Unable to update node {0}. Package not found.**
Explanation	WmART attempted to save changes to the specified namespace node, but could not determine its package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0032E	**Unable to update resource {0}.**
Explanation	An error occurred when updating a value in the specified namespace.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0033E	**Invalid folder name {0}.**
Explanation	While creating a new connection node, a null folder name was passed to com.wm.pkg.art.util.ServiceHelper.checkInterfaceName.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0034E	**Unable to create folder {0}.**
Explanation	WmART was unable to create the specified folder in the adapter's namespace.
Action	Ensure that the folder name conforms to naming conventions in your server's local file system, and that Integration Server has permissions to create folders under the packages folder. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0035E	**Unable to create record for {0}.**
Explanation	An error occurred in ServiceHelper.createRecordFromBean while creating an NSRecord from the specified object. Adjacent log messages might contain additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0036E	**Unable to create folder for service {0}.**
Explanation	An error occurred in ServiceHelper.registerService while creating the file system infrastructure for the specified adapter service. Adjacent log messages might contain additional details.
Action	Ensure that the local operating system access permissions within the Integration Server packages folder will allow WmART to create folders and files dynamically.

ART.0114.0037E **Unable to create service {0}.**

Explanation An error occurred in ServiceHelper.registerService while registering the adapter service. Adjacent log messages might contain additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0038E **Unable to create flow {0}.**

Explanation An error occurred in ServiceHelper.createFlowService. Adjacent log messages might contain additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0040E **Unable to create interaction input record.**

Explanation An error occurred in RecordFactoryBridgeImpl.createInputRecord while creating a mapped Record. Adjacent log messages might contain additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0041E **Unable to create input record. createMappedRecord() returned {0}.**

Explanation A call to RecordFactory.createMappedRecord returned an object of the specified class rather than a WmRecord or IDataCodable object.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0042E **Unable to convert interaction output record into IData. Output record is {0}.**

Explanation RecordFactoryBridgeImpl.createOutputData was passed an instance of the specified class rather than a WmRecord, IData, or IDataCodable instance.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0050E	**Unable to convert string to specific data type. The data type is not specified or the string value is null.**
Explanation	While configuring a new connection or listener, WmART detected that the type or value of one of the connection's properties is null.
Action	Ensure that you enter values for all required properties. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0051E	**Unable to convert string to specific data type. Unsupported data type {0}.**
Explanation	You omitted a value when configuring a connection or listener property from Integration Server Administrator.
Action	Reconfigure the connection/listener, entering valid values for all properties on the Integration Server Administrator page.

ART.0114.0053E	**Unable to convert string array to specific data type array. The data type is not specified.**
Explanation	While configuring a new connection or listener, WmART detected that the type of a property array is null.
Action	This condition indicates a coding error in the adapter or the Adapter Runtime (WmART) itself. Ensure that the adapter is handling connection and listener properties correctly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0054E	**Unable to convert string array to specific data type array. Unsupported data type {0}.**
Explanation	The Adapter Runtime (WmART) has detected a property array in a connection or listener that has an unsupported data type.
Action	Change your connection/listener to use only supported data types for all properties.

ART.0114.0055E	**Unable to convert string array to data type {0} array.**
Explanation	An unexpected property array conversion error has occurred while configuring a connection or listener.
Action	This might be due to invalid data in a property array on the Integration Server Administrator page, such as non-numeric data in a numeric property. Reconfigure the connection/listener to ensure that the entered data matches the expected data types for all properties.

ART.0114.0056E **Unable to convert string array to primitive int array.**

Explanation A value has been entered in a connection or listener property array that cannot be converted to a Java int type.

Action Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0057E **Unable to convert string array to primitive long array.**

Explanation A value has been entered in a connection or listener property array that cannot be converted to a Java long data type.

Action Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0058E **Unable to convert string array to primitive float array.**

Explanation A value has been entered in a connection or listener property array that cannot be converted to a Java float type.

Action Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0059E **Unable to convert string array to primitive double array.**

Explanation A value has been entered in a connection or listener property array that cannot be converted to a Java double type.

Action Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0060E **Unable to convert string array to primitive boolean array.**

Explanation A value has been entered in a connection or listener property array that cannot be converted to a Java Boolean type.

Action Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0061E **Unable to convert string array to primitive short array.**

Explanation A value has been entered in a connection or listener property array that cannot be converted to a Java short type.

Action Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0062E	**Unable to convert string array to primitive char array.**
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java char type.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0063E	**Unable to convert string array to Integer array.**
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java integer instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0064E	**Unable to convert string array to Long array.**
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java long instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0065E	**Unable to convert string array to Float array.**
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java float instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0066E	**Unable to convert string array to Double array.**
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java double instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0067E	**Unable to convert string array to Boolean array.**
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java Boolean instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0068E **Unable to convert string array to Short array.**

Explanation A value has been entered in a connection or listener property array that cannot be converted to a Java short instance.

Action Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0069E **Unable to convert string array to Character array.**

Explanation A value has been entered in a connection or listener property array that cannot be converted to a Java character instance.

Action Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0072E **Unable to set JavaBean properties.**

Explanation WmART has detected an error while setting the properties on a listener or listener notification bean.

Action Ensure that the adapter's listener and listener notification implementations adhere to the JavaBean standard.

ART.0114.0073E **Unable to set property {0} to value {1} on class {1}.**

Explanation WmART failed to set the specified property on the specified (bean) class because it could not introspect the class.

Action Ensure that the adapter's service template implementations adhere to the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0074E **Property {0} not found in class {1}.**

Explanation After introspecting the specified class, WmART failed to find the specified property in that class.

Action Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0075U	**Unable to set property descriptor.**
Explanation	WmART failed to introspect an unspecified bean.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0076E	**Unable to set {0} to {1} because property is not writable.**
Explanation	WmART was unable to locate the "set" method for the specified property on a bean class. The property appears to be read only.
Action	Ensure that the adapter's service template implementations support the JavaBean standard. To make the specified property writable, implement a "set" method for it.

ART.0114.0077E	**Error while setting property {0} of class {1} to {2}.**
Explanation	An error occurred while setting the specified property on the specified class instance.
Action	Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0078E	**Unable to get JavaBean properties for {0}.**
Explanation	An error occurred while reading the properties from the specified bean class.
Action	Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0081E	**Unable to create instance of {0}.**
Explanation	WmART was unable to create a new instance of the specified class.
Action	Ensure that the adapter's service and notification template implementation classes expose a default public constructor and are not abstract. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0082E	**Unable to get JavaBean property {0} of class {1}.**
Explanation	WmART failed to determine or invoke the "get" method for the property in the specified class.
Action	Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0083E	**Exception encountered attempting to load fix information for adapter type {0}.**
Explanation	The Adapter Runtime (WmART) failed while attempting to load the installed update information for the adapter.
Action	This error is generated when an exception is caught during execution. Check the error logs for information on the original exception.

ART.0114.0084E	**Missing or invalid value. {0} is not a valid value for field {1}.**
Explanation	An error occurred while validating the common values for a connection pool. The common values are settings, such as, Minimum Pool Size, Maximum Pool Size, etc.
Action	Change the invalid value. Then attempt to save and enable your connection.

ART.0114.0201E	**Unable to introspect "{0}". This service introspects the parameters of connection only.**
Explanation	WmART failed to create a WmManagedConnectionFactory instance from the specified class name. The current WmART implementation does not allow this condition to occur.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0202E	**Failure when introspecting the connection properties.**
Explanation	An error occurred while introspecting connection properties. Additional details are logged.
Action	Check adjacent log messages for specific error details. Correct any problems with your connection metadata. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0203E	**Unable to introspect "{0}"**
Explanation	The Adapter Runtime (WmART) failed to create an instance of an adapter service, notification, or listener from the specified class name.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0204E	**Unable to introspect the parameters of service template.**
Explanation	An error occurred while attempting to introspect a template or listener. Additional details are logged.
Action	Ensure that the adapter's implementation .class files are installed properly under the packages folder. If you modify the .class files for the adapter while the Integration Server is running, you must reload that adapter.

ART.0114.0205E	**Unable to lookup the resource domain values.**
Explanation	This is a general processing error message. Details should appear in adjacent log messages.
Action	Refer to the Action column for the accompanying messages.

ART.0114.0206E	**Connection alias was not specified in "{0}".**
Explanation	The connection, adapter, or listener could not be found in the request to the specified method.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0207E	**The connection alias "{0}" does not support webMethods metadata extensions. The adapter could be a third-party adapter.**
Explanation	The specified connection alias is not derived from com.wm.adk.cci.connection.WmConnection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0208E	**The connection alias "{0}" isn't configured or failed.**
Explanation	WmART failed to create a ConnectionDataNode instance based on the specified connection alias.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0209E	**Cannot get the connection instance of connectionAlias "{0}".**
Explanation	An error occurred while creating a WmConnection instance from the specified connection alias. Additional details are provided in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0213E	**Cannot get the listener instance of listenerNode "{0}".**
Explanation	The method getListenerAdapterMetadata in com.wm.pkg.art.metadata.ConnectionMetadataService failed to locate and create a listener object for the specified listener node.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0216E	**Unable to validate the resource domain value.**
Explanation	An error occurred while validating a resource domain. This is a general processing error message. Details should appear in adjacent log messages.
Action	Refer to the Action column for the accompanying messages.

ART.0114.0218E	**Failure when introspecting the parameters of the notification listener.**
Explanation	WmART failed to lookup a resource domain. Additional details should appear in adjacent log messages.
Action	Ensure that the adapter's implementation(s) of WmNotification.fillWmTemplateDescriptor sets resource domains correctly.

ART.0114.0219E	**Failure when validating the resource domain "{0}". Null checkValues returned.**
Explanation	WmART was unable to locate internal check values for the specified resource domain.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0220E	**Error occurred when closing the connection handle.**
Explanation	An error occurred when closing a connection. Additional details are logged.
Action	Ensure that the connection is configured properly and is able to communicate with the back-end resource. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0221E	**No adapter type name specified in "{0}".**
Explanation	The specified method in com.wm.pkg.art.metadata.ConnectionMetadataService failed to retrieve connection metadata because no adapter name was provided.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0222E	**No class name of WmManagedConnectionFactory specified in "{0}".**
Explanation	The specified method in com.wm.pkg.art.metadata.ConnectionMetadataService failed to retrieve connection metadata because no connection factory class name was provided.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0225E	**Cannot get the connection handle of "{0}".**
Explanation	WmART failed to create a WmConnection instance based on the specified connection alias.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0226E	**No class name of service template specified in "{0}".**
Explanation	The specified method failed to retrieve metadata from an adapter template, notification template, or listener because no service class was provided in the request.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0227E	**No resource domain name specified in "{0}".**
Explanation	The specified method failed because no resource domain was provided in the request.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0228E **No statement specified in "{0}".**

Explanation The specified method in com.wm.pkg.art.metadata.InteractionMetadataService failed because the AdapterRuntimeGlobals.STATEMENT value was not provided in the request.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0230E **Unable to get the list of service template metadata.**

Explanation The method getInteractionAdapterMetadataList in com.wm.pkg.art.metadata.InteractionMetadataService failed because the list of service templates supported by a connection was not provided in the request.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0231E **Unable to get the list of notification template metadata.**

Explanation An error occurred in com.wm.pkg.art.metadata.InteractionMetadataService.getNotificationAdapterMetadataList. This is a general processing error message. Details should appear in adjacent log messages.

Action Refer to the Action column for the accompanying messages.

ART.0114.0232E **Unable to get the adapter type "{0}".**

Explanation The method getConnectionAdapterMetadata in com.wm.pkg.art.metadata.ConnectionMetadataService was unable to create a WmAdapterType instance using the specified adapter name.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0233E **Unable to get the connection type "{0}".**

Explanation The method getConnectionAdapterMetadata in com.wm.pkg.art.metadata.ConnectionMetadataService was unable to create a connection factory using the specified class name.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0234E	**Unable to get a connection for resource "{0}".**
Explanation	WmART failed to create a WmConnection instance based on the specified connection alias.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0235E	**Error in {0}. Missing parameter: {1}.**
Explanation	The method in com.wm.pkg.art.metadata.InteractionMetadataService failed to retrieve notification metadata because the specified request parameter was missing.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0236E	**The connectionAlias or listenerNodeName must be specified.**
Explanation	The method in com.wm.pkg.art.metadata.InteractionMetadataService failed to lookup/validate notification values because neither the connection node alias nor the listener node was provided in the request.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0237E	**Value for parameter missing: {0}.**
Explanation	The operation input requires the metadata parameter listed in the message text, but the value was not provided.
Action	Add the metadata property and a value to the operation inputs and resubmit.

ART.0114.0238E	**Value for parameter {0} does not match data type {1}.**
Explanation	The value submitted with the operation input does not match the metadata parameter listed in the message text.
Action	Change the type of the value for the operation and resubmit.

ART.0114.0239E	**Number of fields does not match number of types in a record definition.**
Explanation	The operation input requires a field type and a field name for each output field specification.
Action	Ensure that the number of entries in the array of values for the field names and field types are equal and resubmit.

ART.0114.0240E	**Parameter missing: {0}.**
Explanation	The operation input is missing the required parameter listed in the message text.
Action	Ensure that the input contains an entry for the parameter and resubmit.

ART.0114.0241E	**Unrecognized parameter {0} specified.**
Explanation	The operation input contains the parameter listed in the message text, which is not defined for this template.
Action	Remove the parameter from the operation input and resubmit.

ART.0114.0242E	**Required parameter "{0}" is missing, or has no value.**
Explanation	The operation is missing a required parameter.
Action	Provide the missing parameter value, and resubmit the operation.

ART.0114.0243E	**Failed to run {0} service. Details provided in error log.**
Explanation	An exception was caught while executing the service.
Action	Look in the error log for details on the original exception.

ART.0114.0244E	**Resource domain "{0}" is not recognized by providor "{1}".**
Explanation	The specified resource domain is not registered for the template.
Action	This error should only be encountered while using the webMethods ADK for adapter development. If you are developing an adapter, ensure that the specified resource domain is registered for your template. If you are not developing an adapter, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0245E	**Failed to update IO properties in template "{0}"**
Explanation	An exception was caught while updating IO properties in the specified template.
Action	Look in the error log for details on the original exception.

ART.0114.0300	**Unable to start transaction {0}.**
Explanation	An error occurred during the initiation of a transaction.
Action	Make sure that there is connectivity to the adapter backend, and that the connection associated with the transaction is enabled.

ART.0114.0301E	**Unable to commit transaction. A transaction name must be specified.**
Explanation	WmART failed to determine the name of a transaction.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0302E	**Error while committing transaction {0}. The transaction in progress is {1}.**
Explanation	The transaction name does not match the specified connection state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0303E	**Unable to commit transaction.**
Explanation	An error occurred while committing a transaction.
Action	If the adapter uses a connection that supports LocalTransaction, ensure that it is implemented properly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0304E	**Unable to rollback transaction. A transaction name must be specified.**
Explanation	WmART failed to determine the name of a transaction.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0305E	**Error while rolling back transaction {0}. The transaction in progress is {1}.**
Explanation	The specified transaction name does not match the specified connection state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0306E	**Unable to rollback transaction.**
Explanation	An error occurred while committing a transaction.
Action	If the adapter uses a connection that supports LocalTransaction, ensure that it is implemented properly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0307E **Retryable Error during commit transaction.**

Explanation An unexpected system error occurred while committing a transaction. The transaction can be re-tried.

Action Ensure that the back-end resource for the transaction can be reached from the server and is in a valid state. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0350E **Unable to set transaction timeout to {0} seconds.**

Explanation WmART has detected that an XAResource failed to set the transaction timeout to the specified number of seconds.

Action Verify that the back-end resource for the transaction can be reached from the server and is in a valid state. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0351E **Unable to create Transaction Manager.**

Explanation WmTransactionManagerFactory failed to create a TransactionManager.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0352E **Unable to create Transaction Manager with transaction timeout set to {0} seconds.**

Explanation WmTransactionManagerFactory failed to create a TransactionManager with the specified number of timeout seconds.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0353E **Unable to set transaction timeout. Invalid timeout value {0}.**

Explanation com.wm.pkg.art.transaction.Service.setTransactionTimeout could not cast the specified object to type Integer.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0700E	**Errors occurred in cluster coordination repository access for {0}.**
Explanation	An exception was caught during processing.
Action	Look in the error log for details on the original exception.

ART.0114.0701E	**Unable to retrieve ART instance/session ID.**
Explanation	The Adapter Runtime (ART) session ID failed to initialize.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0702E	**Errors occurred attempting to stop {0}. See error log for details.**
Explanation	An exception was caught when attempting to stop the notification.
Action	Look in the error log for details on the original exception.

ART.0114.0703E	**Errors occurred attempting to confirm cluster member. See error log for details.**
Explanation	An exception was caught trying to validate Adapter Runtime (ART) cluster members.
Action	Look in the error log for details on the original exception.

ART.0114.0704E	**Internal Error-assert failed - node: {0}, detail:{1}.**
Explanation	An unexpected exception occurred during processing.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, error logs with the stack trace exposed, and the detail in this error message.

ART.0114.0705E	**Errors occurred attempting to start {0}. See error log for details.**
Explanation	An exception was caught when attempting to start the notification.
Action	Look in the error log for details on the original exception.

ART.0114.0707E	**"{0}" is an invalid setting for the cluster coordination mode of {1}. Valid values: {2}.**
Explanation	An unsupported mode was encountered.
Action	Change the mode to one of the supported settings, and restart the notification.

ART.0114.0708E	**{0} is an invalid setting for max process time of {1}. Value must be an number between {2} and {3}.**
Explanation	An invalid maximum process time was encountered for the notification.
Action	Change the maximum process time to a value within the specified range, and restart the notification.

ART.0114.0709E	**{0} is an invalid setting for max setup time of {1}. Value must be an number between {2} and {3}.**
Explanation	An invalid maximum setup time was encountered for the notification.
Action	Change the maximum setup time to a value within the specified range, and restart the notification.

ART.0114.0710E	**Adapter cluster properties files are not the same across the cluster. Please synchronize all cluster properties files and restart servers.**
Explanation	The Adapter Runtime encountered inconsistent cluster property files.
Action	Ensure the cluster property files are the same for the adapter on each clustered Integration Server.

ART.0114.0711E	**Notification {0} was unexpectedly removed from cluster.**
Explanation	Another instance of this notification erroneously determined that this current instance failed. The current instance was removed.
Action	Check the logs on other servers in the cluster. A log on one of the servers will include message 1405, which indicates that this instance was removed. Check clock synchronization and network connectivity between the two servers.

ART.0114.0712E	**Operation failed because notification {0} was unexpectedly removed from cluster.**
Explanation	Another instance of this notification erroneously determined that this current instance failed. The current instance was removed. Note that this error is similar to ART.0114.0711E; however, in this case the node was changing states.
Action	Check the logs on other servers in the cluster. A log on one of the servers will include message 1405, which indicates that this instance was removed. Check clock synchronization and network connectivity between the two servers.

ART.0114.1004E	**Parameter parsing error.**
Explanation	WmART attempted to encrypt or decrypt a null string value.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.1005E	**Parameter parsing error.**
Explanation	WmART failed to encrypt a string value.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.1006E	**Parameter parsing error.**
Explanation	WmART failed to decrypt a string value.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.1008D	**Jar file {0} is not an update jar file. Unable to read the {1} entry.**
Explanation	This message applies to adapters that use update jar files to deliver updates. The update.cnf file is not readable in the update jar file.
Action	No action is required.

ART.0114.1009D	**Jar file {0} is not an update jar file. It does not contain the {1} entry.**
Explanation	This message applies to adapters that use update jar files to deliver updates. The update.cnf file is missing from the update jar file.
Action	No action is required.

ART.0114.1010D	**File {0} is not an update file. It is not a jar file.**
Explanation	This message applies to adapters that use update jar files to deliver updates. A file was found in the adapters update directory that is not a jar file.
Action	No action is required.

ART.0114.1011D	**Error initializing UpdateFile. Missing required parameter.**
Explanation	This message applies to adapters that use update jar files to deliver updates. A null value was supplied for the file name parameter. A value is required.
Action	No action is required.

ART.0114.1012D	**No updates found for adapter: {0}.**
Explanation	No installed updates were found for the adapter.
Action	No action is required.

ART.0114.1013E	**Unable to locate the package name for adapter: {0}.**
Explanation	The Integration Server package name for the adapter could not be determined.
Action	Ensure the adapter package depends on the WmART package, and reload the adapter package.

ART.0114.1014W	**Adapter {0} is missing required fix {1}.**
Explanation	This message applies to adapters that use update jar files to deliver updates. A fix required by the adapter was not found.
Action	Install the required fix, and reload the adapter.

ART.0114.1015E	**Error loading update jar file {0}. An exception was encountered loading the {1} file.**
Explanation	This message applies to adapters that use update jar files to deliver updates. An exception occurred trying to load the update.cnf file in the update jar.
Action	Look in the error log for details on the original exception.

ART.0114.1016E	**Error loading update jar file {0}. The {1} file is missing the required property updateName.**
Explanation	This message applies to adapters that use update jar files to deliver updates. The update.cnf file associated with the fix is missing a required value.
Action	Re-apply the fix, and reload the adapter.

ART.0114.1017E	**Error loading update jar file {0}. The update name contains the illegal character ';'.**
Explanation	This message applies to adapters that use update jar files to deliver updates. The fix name in the update.cnf file contains an illegal semicolon (;) character.
Action	Re-apply the fix, and reload the adapter.

ART.0114.1018E	**Error loading update information. The '{0}' tag is missing.**
Explanation	The fix name is missing.
Action	Re-apply the fix, and reload the adapter.

ART.0114.1019E	**Illegal value is set for page size in watt.art.page.size - "{0}".**
Explanation	An invalid value was specified for the watt.art.page.size parameter. This parameter must be a positive integer greater than or equal to 1.
Action	Set the value of watt.art.page.size to an integer greater than or equal to 1.

ART.0114.1020	**Error while storing/retrieving/removing the password for the connection "{0}".**
Explanation	An error occurred while storing, retrieving or removing the password for the connection from the Integration Server passman store. The error can occur when creating, updating, or deleting an adapter connection respectively.
Action	Make sure that the latest fix is installed on Integration Server. Try to restart Integration Server and perform the operation again. Also, make sure that the package containing the connection is imported properly into Integration Server.

ART.0114.1103E	**Facility {0} - {1} error. Log handler not found.**
Explanation	WmART failed to get a Log Handler from the Integration Server for the specified facility.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.1105E	**No LogProducer for facility {0} - {1}.**
Explanation	WmART attempted to log a message, but no Log Producer exists for the specified facility.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.1106E	**Facility {0} - {1} error. No facilities registered.**
Explanation	WmART failed to get the list of facility codes from the Log Handler.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.1112E	**Unable to instantiate class {1} in adapter {0}. See error log for details.**
Explanation	An exception occurred trying to instantiate a template for the adapter.
Action	Ensure package dependencies are set correctly, and reload the adapter

ART.0114.1113E	**Class {0} is not a Service or Notification template class.**
Explanation	An invalid class was registered as a template.
Action	If you are using the webMethods ADK to develop an adapter, ensure your class is properly registered and coded to be a template. If this message is being issued from a webMethods adapter, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.1401W	**Coordination data for {0} is invalid. Coordination will revert to a default state.**
Explanation	Coordination data in the repository was not valid. If the server was recently upgraded, this might simply represent a change in record formats, and the operation you are performing will automatically correct the data for you. If you have not recently upgraded or the problem persists, it is likely that the repository is corrupted.
Action	If you recently performed a server upgrade, no action is required. If you have not recently upgraded or the problem persists, check repository logs for errors.

ART.0114.1405W	**Processing for {0} on server {1} has timed-out or failed. Local instance will take over.**
Explanation	Remote failure detected.
Action	Check logs on indicated server for messages ART.0114.0711E or ART.0114.0712E. If the messages are in the log, refer to those error messages for a resolution. If the messages do not appear in the logs, no action is required.

ART.0114.1407W	**Illegal overlap occurred in node {0}. Please verify clock synchronization with cluster member '{1}'**
Explanation	An illegal overlap exception was detected.
Action	Ensure the clocks are synchronized for all Integration Servers in the cluster.

ART.0114.1411E	**Unable to access {0} file for adapter "{1}". Please check the file permissions. Running with default configuration.**
Explanation	The cluster property file could not be read.
Action	Ensure the cluster property file exists and is readable for the specified adapter.

ART.0114.1412E	**Unable to parse {0} file for adapter "{1}". Please correct file format. Running with default configuration.**
Explanation	The cluster property file could not be parsed.
Action	Validate the cluster property file format for the specified adapter.

ART.0114.1415E	**An internal error occurred while rendering cluster settings for adapter {0}. Updated settings will not be persisted.**
Explanation	The settings could not be saved to the cluster property file.
Action	Ensure the directory and the cluster file are writable.

ART.0114.1416E	**Error attempting to save cluster settings for adapter {0}. Error {1}**
Explanation	An exception occurred trying to save the cluster settings.
Action	Look in the error log for details on the original exception.

ART.0114.1418W	**Illegal overlap occurred in node {0}. Please increase setup timeout. Current setting: {1}, actual time: {2} seconds**
Explanation	The requested operation took longer than the allotted time; the operation had no other errors.
Action	Increase the node's timeout value as indicated by the actual time.

ART.0114.1419W	**Illegal overlap occurred in node {0}. Please increase execute timeout. Current setting: {1}, actual time: {2} seconds**
Explanation	A polling operation took longer than the allotted time; the polling operation had no other errors.
Action	Increase the node's timeout value as indicated by the actual time.

ART.0114.3139E	**EventType Definition doesnt exists in the EventTypeStore for notification : {0}.**
Explanation	Event Type Definition is not present in the same namespace for the notification in the Event Type Store.
Action	Create an event type definition for the notification and manually copy it to the Event Type Store.

ART.0115.3202E	**Listener error releasing connection for {0}. Error: {1}.**
Explanation	An error occurred while closing the connection associated with the specified listener.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3203E **Error creating listener object: Null argument on init call.**

Explanation The method WmNotificationListener.initListenerNodeProperties was passed a null ListenerNode instance.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3204E **Error creating listener object: NSName null.**

Explanation The method WmNotificationListener.initListenerNodeProperties was unable to derive the name of a listener node from the ListenerNode instance.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3207E **Illegal event type received: {0}.**

Explanation The method WmNotificationListener.doNotify was passed the specified invalid event ID.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3208E **Error during listener event. Error: {0}.**

Explanation An error occurred while processing a listener event. Refer to the error message text for more details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3209E **Error creating listener object {0}. Error: {1}.**

Explanation An error occurred creating the specified listener or initializing its properties.

Action Ensure that the listener and its properties are configured correctly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3211E	**Existing transaction rolled back before execution of {0}.**
Explanation	WmART detected an incomplete transaction for the specified listener prior to executing it. The transaction has been rolled back.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3212E	**Listener error during execution of {0}. Error: {1} rolling back existing transaction.**
Explanation	WmART detected an incomplete transaction for the specified listener prior to executing it. WmART attempted to rollback the transaction, but failed. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3213E	**Listener error during execution of {0}. Error: {1} checking transaction.**
Explanation	WmART failed to determine whether the specified listener has an open transaction. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3214E	**Listener {0} not Found.**
Explanation	WmART failed to lookup the specified listener.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3215E	**Unable to create listener {0}. Listener node already exists.**
Explanation	There was an attempt to create a duplicate listener node.
Action	Enter a new listener node name that is unique to its folder.

ART.0115.3217E	**Error creating listener object: {0}. Invalid package name: {1}.**
Explanation	ListenerManager.createListener failed to create an instance of the listener because it could not find the package name in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3218E **Error creating listener object: {0}. Invalid node name.**

Explanation ListenerManager.createListener failed to create an instance of the listener because the specified node name is missing or invalid.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3219E **Error creating listener object: {0}. Error: {1}.**

Explanation An error occurred while creating the listener. This might be due to an invalid listener node name. Refer to the error message text for more details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3220E **Unable to get list of listener types supported by node {0}.**

Explanation An error occurred in ListenerManager.queryListenerTemplatesSupported for the specified adapter. See adjacent error messages for additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3221E **Unable to get listener node properties {0}.**

Explanation An error occurred while querying the specified listener's properties. See adjacent error messages for additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3223E **Unable to update listener {0}: Error: {1}.**

Explanation An error occurred while updating the specified listener's properties. See adjacent error messages for additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3225E	**Unable to delete listener {0}: Error: {1}.**
Explanation	An error occurred while deleting the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3226E	**Unable to copy listener {0}: Error: {1}.**
Explanation	An error occurred while copying the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3227E	**Unable to copy listener. Error: Source nodeName is required.**
Explanation	The method ListenerManager.copyAdapterListener failed because the source listener node name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3228E	**Unable to copy listener {0}. Error: newNodeName is required.**
Explanation	The method ListenerManager.copyAdapterListener failed because the destination listener node name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3229E	**Unable to copy listener {0}. Error: publishableDocumentName is required.**
Explanation	The method ListenerManager.copyAdapterListener failed because the destination listener publishable document name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3230E **Unable to copy listener {0}. Error: newPkg is required.**

Explanation The method ListenerManager.copyAdapterListener failed because the destination listener node package name was not present in the pipeline.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3231E **Unable to copy listener {0} to {1}. Error: Unable to get source listener node.**

Explanation The method ListenerManager.copyAdapterListener failed because the source listener node name is invalid.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3232E **Unable to copy listener {0}. Error: New name already exists {1}.**

Explanation The method ListenerManager.copyAdapterListener failed because the specified destination listener node name already exists in the package.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3235E **Unable to rename listener {0}. Error: {1}.**

Explanation An error occurred while renaming the specified listener. See adjacent error messages for additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3236E **Unable to find listener {0}.**

Explanation The method ListenerManager.queryListenerStatistics failed because it could not locate the specified listener node.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3237E	**Unable to get listener {0}. Error: Listener class name is not specified.**
Explanation	The method ListenerNode.getListener failed because it could not locate the WmConnectedListener implementation class name.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3238E	**Error in Listener Callback:{0} notification {1}.**
Explanation	An error occurred while processing a listener notification event for the specified listener. If there is a callback name in the error message, it corresponds to the notification event.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3239E	**Missing required parameter on service: {0}**
Explanation	The specified parameter is not present in the pipeline. This is an internal error.
Action	Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3240E	**Unable to retrieve listener data. No listener name specified.**
Explanation	The method ARTAdmin.retrieveListenerData failed because no listener was present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3241E	**Error retrieving listener: {0}. Error: {1}**
Explanation	An error occurred while retrieving information about the listener. Refer to the error text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3242E **Unable to get listener properties for adapter: {0}, listener type: {1}.**

Explanation An error occurred while retrieving properties of the listener in the specified adapter.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3243E **Error retrieving listeners. Missing parameter: {0}**

Explanation The method ARTAdmin.retrieveListeners failed because the adapter name was not present in the pipeline.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3244E **Error setting listener status. Missing parameter: {0}**

Explanation The method ARTAdmin.setListenerStatus failed because the listener name was not present in the pipeline.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3245E **Error retrieving listener types. Missing parameter: {0}**

Explanation The method ARTAdmin.retrieveListenerTypes failed because the adapter name was not present in the pipeline.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3246E **Error retrieving listener types. Error: {0}**

Explanation An error occurred while retrieving the listener types supported by an adapter. Refer to the error text for more details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3247E	**Error deleting listener. Missing parameter: {0}**
Explanation	The method ARTAdmin.deleteListener failed because the listener name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3248E	**Error deleting listener: {0}. Unable to find the node.**
Explanation	The method ARTAdmin.deleteListener failed because the specified listener node name is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3249E	**Error deleting listener: {0}.**
Explanation	An error occurred while deleting the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3250E	**Error setting properties for listener: {0}.**
Explanation	An error occurred while setting the properties of the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3251E	**Invalid listener node name: {0}.**
Explanation	The specified listener name is missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3252E	**Unable to commit transaction for listener {0}. Error: {1}.**
Explanation	WmNotificationListener failed to commit a transaction for the specified listener. Refer to the error text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3253E	**Listener {0} did not process notification.**
Explanation	The listener received a notification and was unable to find a listener notification to process it.
Action	Check to ensure that the listed listener has listener notifications registered with it and that at least one of them is enabled.

ART.0115.3255E	**Unable to start listener: {0}. Cannot retrieve connection from connection node: {1}**
Explanation	The listener requires a connection to start. The startup processing could not get a connection from the listed connection node.
Action	Check to ensure that the listed connection is enabled. If the connection is pooled, increase the maximum connections allowed in the pool.

ART.0115.3256E	**Unable to start listener: {0}. Error: {1}**
Explanation	An unexpected exception occurred while trying to enable a notification.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0115.3257E	**Exceeded max retries. Shutting down listener {0}. Error: {1}**
Explanation	A retryable error occurred while attempting to execute the listener. The maximum number of retries is exceeded.
Action	Check the Integration Server error log for details on the retryable exception. Correct the error and try to enable the listener.

ART.0115.3258E	**Fatal error in listener {0}. See error log for details**
Explanation	An unexpected exception occurred during listener operation.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0115.3259E	**Unable to enlist connection transactional resource**
Explanation	An unexpected exception occurred while trying to start a transaction within the listener.
Action	Check the Integration Server error log for details on the unexpected exception. If no related exceptions are found, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3260E	**Unable to commit transaction for listener {0}. Listener disabled**
Explanation	An unexpected exception occurred while trying to commit a transaction within the listener.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0115.3261E	**Connection Node {0} not enabled.**
Explanation	An error occurred while trying to retrieve a connection for the listener.
Action	Check to ensure the connection is enabled and restart the listener.

ART.0115.3262E	**Fatal error initiating transaction in listener {0}. See error log for details**
Explanation	An unexpected exception occurred while trying to start a transaction within the listener.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0115.3263E	**Connection error while retrieving metadata in listener {0}. See error log for details**
Explanation	An error occurred while trying to retrieve a connection for the listener.
Action	Check to ensure the connection is enabled. Check the Integration Server error log for more information about the connection error.

ART.0115.3264E	**Unable to stop listener: {0}. Error: {1}**
Explanation	An unexpected exception occurred while trying to stop the listener.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0115.3265E	**Errors occurred. {0} listeners were not suspended. See error log for details.**
Explanation	While attempting to suspend all listeners, some of the listeners reported errors.
Action	Look in the error log for details on the specific exceptions.

ART.0115.3266E	**Errors occurred. {0} listeners were not enabled. See error log for details.**
Explanation	While attempting to enable all suspended listeners, some of the listeners reported errors.
Action	Look in the error log for details on the specific exceptions.

ART.0115.3267E	**Cannot update adapter-defined settings in suspended listener {0}.**
Explanation	The user attempted to update adapter-defined settings for a listener; however, the listener is currently suspended.
Action	Disable the listener, and retry the operation.

ART.0115.3268E	**{0} is in an invalid state for requested operation.**
Explanation	The user attempted an operation on a listener; however, the listener was not in the proper state for the operation.
Action	Change the state of the listener to an acceptable state, and retry the operation.

ART.0115.3269E	**Unable to complete update. Setting connection for listener {0} is not supported.**
Explanation	The user attempted to change the connection associated with a listener; however, the listener does not require a connection.
Action	This operation is not supported.

ART.0115.3270E	**Unable to create listener. Setting connection for listener type {0} is not supported.**
Explanation	The user attempted to create a listener with a connection; however the listener does not require a connection.
Action	This operation is not supported.

ART.0115.3271E	**Unable to create listener. Must specify connection for listener type {0}.**
Explanation	A user attempted to create a listener that requires a connection; however no connection was specified.
Action	Specify a connection, and retry the operation.

ART.0115.3272E	**Unable to identify adapter for listener type {0}.**
Explanation	Integration Server cannot determine the adapter associated with the specified listener type.
Action	Ensure your package dependencies are set properly. Reload the adapter package, and retry the operation.

ART.0115.3712E	**Error during listener execution.**
Explanation	Either a fatal error has occurred while executing a listener, or the maximum number of non-fatal errors has been exceeded while executing a listener.
Action	Ensure that the connection from the listener to the back-end EIS is still valid, and that a communications path between them exists.

ART.0115.3716W	**Failed to retrieve connection for callback in listener {0}. Error: {1}**
Explanation	An error occurred while trying to retrieve a connection for the listener shutdown callback processing.
Action	Check to ensure the connection is enabled. Check the Integration Server error log for details on the unexpected exception.

ART.0115.3717W	**Failure in shutdown callback in listener {0}. Error: {1}**
Explanation	An error occurred during the listener shutdown callback processing.
Action	Details on the error are included in the message. The shutdown will attempt to continue.

ART.0116.3001E	**Notification error during execution of {0}. Error: {1}.**
Explanation	An error occurred while executing the specified notification. Refer to the text in the error message for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3002E	**Notification error releasing connection for {0}. Error: {1}.**
Explanation	WmART failed to release the specified notification's connection back to the connection pool.
Action	For custom adapters, check the connection's implementation for possible blocking situations. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3003E	**Error creating notification object: Null argument on init call.**
Explanation	The method WmNotification.initNotificationNodeProperties failed because it was passed a null NotificationNode object.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3004E **Error creating notification object: NSName null.**

Explanation The method WmNotification.initNotificationNodeProperties failed because it was unable to get the node name from the NotificationNode object.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3005E **Error creating notification object: {0}. Publishable Document name not set.**

Explanation The method WmNotification.initNotificationNodeProperties failed because it was unable to get the publishable document node name for the specified notification.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3006E **Error creating notification object: {0}. UUID not set.**

Explanation The method WmNotification.initNotificationNodeProperties failed because it was unable to get the specified notification's universal unique identifier (UUID) from the NotificationNode object.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3007E **Illegal event type received: {0}.**

Explanation The method WmNotification.notifyEvent was passed the specified invalid event ID.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3008E **Error during notification event. Error: {0}.**

Explanation An error occurred in the method WmNotification.notifyEvent. Refer to the error message text for more details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3009E	**Error creating notification object {0}. Error: {1}.**
Explanation	An error occurred in the method NotificationNode.getNotification while creating the notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3010E	**Error publishing notification {0}. Error: {1}.**
Explanation	An error occurred in the method WmAsynchronousNotification.publishToDispatcher while publishing a non-duplicate document from the specified notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3011E	**Existing transaction rolled back before execution of {0}.**
Explanation	WmART detected an incomplete transaction for the notification prior to processing a notification event. The transaction has been rolled-back.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3012E	**Notification error during execution of {0}. Error: {1} rolling back existing transaction.**
Explanation	WmART detected an incomplete transaction for the specified notification prior to processing a notification event. It attempted to rollback the transaction, but failed. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3013E	**Notification error during execution of {0}. Error: {1} checking transaction.**
Explanation	WmART failed to determine whether the specified notification has an open transaction. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3014E **Notification {0} not Found.**

Explanation WmART failed to locate the specified notification.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3015E **Unable to create notification {0}. Notification node already exists.**

Explanation WmART failed to create the specified notification because a notification with this name already exists.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3016E **Unable to create publishable document {0}. Error: {1}.**

Explanation The method NotificationFactory.createPublishableDocument failed to create a document for the specified notification. Refer to the error message text for more details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3018E **Error creating notification object: {0}. Invalid node name.**

Explanation The specified notification node name is missing or improperly formatted.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3019E **Error creating notification object: {0}. Error: {1}.**

Explanation An error occurred while creating the specified polling or listener notification. Refer to the error message text for more details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3020E **Unable to get list of notification types supported by node {0}.**

Explanation An error occurred in NotificationManager.queryNotificationTemplatesSupported for the specified adapter. See adjacent error messages for additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3021E	**Unable to get notification node properties {0}.**
Explanation	An error occurred while querying the specified notification's properties. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3022E	**Unable to update notification {0}. Error: Notification must be disabled.**
Explanation	NotifcationManager received a request to update the properties of an active notification.
Action	Disable the notification from Integration Server Administrator prior to updating it.

ART.0116.3023E	**Unable to update notification {0}.**
Explanation	An error occurred while updating the notification's properties. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3024E	**Unable to delete notification {0}. Error: Notification must be disabled.**
Explanation	NotifcationManager received a request to delete an active notification.
Action	Disable the notification from Integration Server Administrator prior to deleting it.

ART.0116.3025E	**Unable to delete notification {0}.**
Explanation	An error occurred while deleting the specified notification. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3026E	**Unable to copy notification {0}.**
Explanation	An error occurred while copying the specified notification. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3027E	**Unable to copy notification {0}. Error: nodeName is required.**
Explanation	The specified notification node name is missing or incorrectly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3031E	**Unable to copy notification {0}. Error: Invalid node name {1}.**
Explanation	Notification Manager failed to validate the specified node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3032E	**Unable to copy notification {0}. Error: New name already exists {1}.**
Explanation	The method NotificationManager.copyAdapterNotification failed because the specified destination notification node name already exists in the package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3033E	**Unable to copy notification {0}. Error: New document name already exists {1}.**
Explanation	The method NotificationManager.copyAdapterNotification failed because the specified new publishable document name already exists in the package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3034E	**Unable to rename notification {0}. Error: Notification must be disabled.**
Explanation	NotificationManager received a request to rename an active notification.
Action	Disable the notification from Integration Server Administrator prior to renaming it.

ART.0116.3035E	**Unable to rename notification {0}. Error: {1}.**
Explanation	An error occurred while renaming the notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3036E	**Unable to find notification {0}.**
Explanation	The method NotificationManager.queryNotificationStatistics failed because the specified notification could not be located in the namespace.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3037E	**Unable to get notification {0}. Error: Notification class name is not specified.**
Explanation	The method NotificationNode.getNotification failed to determine the implementation class name for the specified notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3038E	**Error in Notification Callback:{0} notification {1}.**
Explanation	An error occurred in method WmNotification.notifyEvent while processing the specified callback.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3039E	**Missing required parameter on service: {0}**
Explanation	The method NotificationManager.queryNotificationTemplatesSupported failed because the adapter name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3040E	**Error creating notification object: {0}. Missing parameter: {1}.**
Explanation	NotificationManager failed to create the notification because the specified parameter was not in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3041E	**Error creating notification object: {0}. Invalid Package Name {1}.**
Explanation	NotificationManager failed to create the notification because the specified package name is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3042E	**Error creating notification object: {0}. Invalid Service Name {1}.**
Explanation	NotificationManager failed to create the notification because the service name is missing, improperly formatted, or otherwise invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3043E	**Error deleting notification object. Invalid node name: {0}.**
Explanation	The specified notification node name is missing or incorrectly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3044E	**Error deleting notification object: {0}. Error: {1}.**
Explanation	NotificationManager failed to validate the specified node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3045E	**Error deleting notification object: {0}. The specified node is not a Listener Notification node.**
Explanation	NotificationManager.deleteListenerNotification was called to delete the specified notification, which is a polling notification, not a listener notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3046E	**Unable to create document {0}. Error: {1}.**
Explanation	An error occurred while creating a document for the specified notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3047E	**Unable to create notification {0}. Error deleting an existing record: {1}.**
Explanation	NotificationFactory failed to create the notification because it could not delete existing document records. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3048E	**Unable to create notification {0}. The specified Listener does not exist: {1}.**
Explanation	NotificationManager.createListenerNotification failed to create the notification because it could not locate the corresponding listener node. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3049E	**Unable to create notification {0}. The specified notification template is not synchronous: {1}.**
Explanation	NotificationFactory failed to create the notification because the underlying specified implementation class is not derived from WmSynchronousNotification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3050E	**Unable to create notification {0}. The specified notification template is not asynchronous: {1}.**
Explanation	NotificationFactory failed to create the specified notification because the underlying specified implementation class is not derived from WmAsynchronousNotification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3051E	**Unable to query properties for {0}. Invalid node name.**
Explanation	The specified notification node name is missing or improperly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3052E	**Unable to query properties for {0}. Error: {1}.**
Explanation	NotificationManager failed to validate the node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3053E	**Unable to update notification {0}. Invalid node name.**
Explanation	The specified notification node name is missing or incorrectly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3054E	**Unable to update notification {0}. Error: {1}.**
Explanation	NotificationManager failed to validate the node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3055E	**Error copying notification: {0}. Missing parameter: {1}.**
Explanation	NotificationManager failed to copy the notification because the specified parameter was not in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3056E	**Error copying notification: {0}. Invalid Package Name {1}.**
Explanation	NotificationManager failed to copy the notification because the specified package name is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3057E	**Error updating notification object: {0}. Missing parameter: {1}.**
Explanation	NotificationManager failed to update the notification because the specified parameter was not in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3058	**Unable to copy notification {0}. Error: New node name is invalid {1}.**
Explanation	Invalid connection name specified.
Action	Remove any unsupported special characters from the connection name.

ART.0116.3059	**Error trying to enable notification {0}. Error: Listener not found {1}.**
Explanation	The error occurs when trying to enable or disable a listener notification, and the associated listener is not available.
Action	Make sure that the associated listener is not deleted. If the associated listener is deleted, create the listener again with the same name.

ART.0116.3060E	**Error setting notification schedule property {0}**
Explanation	An unexpected exception occurred while trying to set the schedule parameter listed in the message.
Action	Check the Integration Server error log for details about the unexpected exception.

ART.0116.3061E	**Unable to move notification. Error: Invalid node name {0}.**
Explanation	The name of the notification you are trying to move is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3062E	**Unable to move notification {0}. Error: Invalid Node Name Format.**
Explanation	The name of the notification listed in the message text is not in folder:nodename format.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3063E	**Error moving notification: {0}. Error: Missing parameter: {1}.**
Explanation	The move operation is missing the required parameter listed in the message text.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3064E	**Error moving notification: {0}. Error: Invalid Package Name {1}.**
Explanation	The name of the destination package for the move operation is invalid on Integration Server.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3065E	**Unable to move notification {0}. Error: Src/Dest Node names not the same.{1}**
Explanation	The notification node name was changed during the move operation.
Action	Only the package name and folder are allowed to change during a move operation, while the actual node name is not allowed to change. This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3066E	**Unable to move notification {0}. Error: Notification must be disabled.**
Explanation	This notification cannot be moved because it is enabled. To move a notification, it first must be disabled.
Action	In Integration Server Administrator, disable the notification and retry the move operation.

ART.0116.3067E	**Unable to move notification {0}.**
Explanation	An unexpected exception occurred while trying to move a notification.
Action	Check the Integration Server error log for details about the unexpected exception.

ART.0116.3068E	**Unable to move notification {0}. Error: nodeName is required.**
Explanation	The node name specified for the move operation is either missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3069E	**Unable to move notification {0}. Error: New node name is invalid {1}.**
Explanation	The new node name specified for the move operation is either missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3100	**Unable to obtain list of polling notifications for adapter type.**
Explanation	The adapter type passed is null or invalid while retrieving, suspending, or resuming the adapter notifications.
Action	Ensure that a valid adapter type is passed.

ART.0116.3101E	**Unable to obtain detailed information for polling notification.**
Explanation	The method ARTAdmin.retrievePollingNotificationData failed because the notification name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3102E	**Unable to set status for polling notification.**
Explanation	The method ARTAdmin.forceNotificationDisable failed because the notification name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3103E	**Unable to set schedule for polling notification.**
Explanation	The method ARTAdmin.setNotificationSchedule failed because the notification name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3104E	**Unable to retrieve listener notification list. Missing parameter: {0}**
Explanation	The method ARTAdmin.retrieveListenerNotifications failed because the adapter name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3105E	**Unable to set notification status. Missing parameter: {0}**
Explanation	The method ARTAdmin.setNotificationStatus failed because the notification name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3106E	**Unable to set notification status. Notification not found: {0}**
Explanation	The method ARTAdmin.setNotificationStatus failed because it was unable to locate the node for the specified notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3107E	**Unable to set notification status for {0}. Error: {1}**
Explanation	The method ARTAdmin.setNotificationStatus failed because it was unable to enable or disable the specified listener notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3108E	**Unable to publish notification. Message ID {0} exceeds maximum length of {1}.**
Explanation	The message ID specified by the adapter is longer than the allowed maximum length.
Action	Integration Server restricts the length of the message ID for a published document. Contact Software AG Global Support to see how to increase this setting. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3115E	**Errors occurred. {0} notifications reported errors while attempting to suspend. See error log for details.**
Explanation	While attempting to suspend all notifications, some of the notifications reported errors.
Action	Look in the error log for details on the specific exceptions.

ART.0116.3116E	**Errors occurred. {0} notifications were not enabled. See error log for details.**
Explanation	While attempting to enable all suspended notifications, some of the notifications reported errors.
Action	Look in the error log for details on the specific exceptions.

ART.0116.3117E	**Non-fatal errors encounter while disabling notification {0}. Details recorded in error log.**
Explanation	An exception was encountered during the disable callback for a notification.
Action	Look in the error log for details on the specific exception.

ART.0116.3118E	**Non-fatal errors encounter while suspending notification {0}. Details recorded in error log.**
Explanation	An exception was encountered during the suspend callback for a notification.
Action	Look in the error log for details on the specific exception.

ART.0116.3119E	**Non-fatal errors encounter while stopping notification {0}. Details recorded in error log.**
Explanation	An exception was encountered during the shutdown callback for a notification.
Action	Look in the error log for details on the specific exception.

ART.0116.3120E	**{0} is not a valid node type for this operation.**
Explanation	An attempt was made to change the connection associated with a polling notification; however, the specified node is not a polling notification node.
Action	Select a polling notification node, and retry the operation.

ART.0116.3121E	**{0} is in an invalid state for the requested operation.**
Explanation	An attempt was made to perform an operation on a notification; however, the notification was not in the correct state. Typically this occurs when you attempt to perform an update type of operation when the notification is not in a disabled or suspended state.
Action	Change the state of the notification to disabled or suspended, and retry the operation.

ART.0116.3533	**Error while executing Polling Notification {0}. Check if the notification is present in all clusters.**
Explanation	The error occurs when a polling notification does not exist on all nodes in an Integration Server cluster.
Action	Make sure that all clustered Integration Server nodes have the same set of adapter polling notifications.

ART.0117.4000E **Unable to invoke adapter service {0}. Unable to establish connection to connection {1}.**

Explanation WmART failed to create or locate the connection object associated with the specified adapter service.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4001E **Unable to invoke adapter service {0}. Connection.createInteraction() returned null.**

Explanation WmART failed to create a new instance of WmInteraction for the specified adapter service.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4002E **Unable to invoke adapter service {0}.**

Explanation An error occurred while running the specified adapter service and processing its output. Additional information might appear in adjacent log messages.

Action Determine whether the implementation of the adapter's WmAdapterService.execute method is throwing an exception at run time, and correct as needed.

ART.0117.4005E **Connection not available.**

Explanation WmART failed to locate the connection data node for the specified connection and adapter service. This message will always appear in conjunction with 117.4020.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4006E **Invalid adapter type {0}.**

Explanation WmART failed to create an instance of the specified adapter service. This message will always appear in conjunction with 117.4021.

Action Ensure that the implementation class for the adapter service is installed correctly in the package. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4007E	**Unable to get record factory bridge.**
Explanation	WmART failed to create or locate an input/output record factory bridge object.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4008E	**Unable to get connection factory from connection.**
Explanation	WmART failed to locate the connection factory associated with a ConnectionResource.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4009E	**Unable to get record factory required for interaction input.**
Explanation	An error occurred while locating a RecordFactory associated with a ConnectionFactory. Additional details might appear in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4010E	**Unable to get adapter record factory. ConnectionFactory.getRecordFactory() returned null.**
Explanation	WmART failed to locate a RecordFactory associated with a ConnectionFactory.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4011E	**Unable to connect to resource {0}. The resource is already being used in a parent transaction.**
Explanation	WmART attempted to create a new connection to the specified resource, but detected that the resource is currently enrolled in an ongoing transaction.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4012E **Unable to run adapter service. Error occurred when connecting to resource {0}.**

Explanation An error occurred while creating a new connection to the specified resource. Additional details might appear in adjacent log messages.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4013E **Internal Error: Unable to nest connection states.**

Explanation WmART attempted to start a new transaction, but detected that a parent transaction already exists.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4014E **Error while starting nested transaction. The name {0} is already in use.**

Explanation WmART attempted to start a new transaction, but detected that the specified transaction ID is already in use.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4015E **Error(s) occurred while closing adapter connections.**

Explanation Error(s) occurred while closing one or more connections involved in a transaction. Separate log messages are listed for each connection.

Action Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4018E **Error while closing transactions at service completion Error:{0}.**

Explanation The specified error occurred while closing the connections involved in a successful transaction.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4019E	**Error while rolling back transaction Error:{0}.**
Explanation	The specified error occurred while closing the connections involved in a failed transaction.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4020E	**Unable to invoke adapter service {0}. Connection resource {1} not found.**
Explanation	WmART failed to locate the connection data node for the specified connection and adapter service.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4021E	**Unable to invoke adapter service {0}. Unable to get adapter service template.**
Explanation	WmART failed to create an instance of the specified adapter service.
Action	Ensure that the implementation class for the adapter service is installed correctly in the package. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4022E	**Unable to invoke adapter service {0}. Unable to get connection state.**
Explanation	WmART failed to determine the connection state for the specified adapter service. This will prevent a resource connection from being created.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4023E	**Unable to properly handle adapter connection error for connection {0}.**
Explanation	WmART was unable to successfully handle an error that occurred on the specified connection while executing a service.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4024E	**Unable to invoke adapter service {0}. An error occurred on connection {1}. Unable to recover from connection error.**
Explanation	An error occurred in the error handling logic while invoking the specified service. Additional details might appear in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4026E	**Unable to rollback transaction Error:{0}.**
Explanation	The specified error occurred while marking a failed transaction for rollback.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4027E	**Unable to create adapter service {0}. Invalid package name {1}.**
Explanation	WmART failed to create the specified adapter service because it could not locate the Package object for the specified package name.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4028E	**Unable to create adapter service {0}. Invalid service name.**
Explanation	WmART failed to create the specified adapter service because the service node name is missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4029E	**Unable to create adapter service {0} with connection {1}. Connection not found.**
Explanation	WmART AdapterServiceManager failed to create the adapter service because it could not locate the ConnectionDataNode object for the connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4030E	**Unable to create adapter service {0}.**
Explanation	An error occurred while creating the specified adapter service. Additional details should appear in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4032E	**Unable to find adapter service {0}.**
Explanation	WmART failed to locate the namespace node (NSNode) for the adapter service.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4033E	**Retryable Error while closing transactions at service completion Error:{0}.**
Explanation	The specified retryable run-time exception occurred while completing a successful service invocation.
Action	Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4034E	**Retryable Error(s) occurred while closing adapter connections.**
Explanation	One or more retryable errors have occurred while closing connections used in a transaction. Additional log messages might be listed.
Action	Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4035E	**Error while completing service listener Error:{0}.**
Explanation	An error occurred while calling method com.wm.pkg.art.transaction.ServiceListener.listenComplete.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4036E	**Unable to commit transaction. Transaction state:{0} .**
Explanation	WmART was unable to commit a transaction because the transaction was in the specified, unexpected state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4037E	**Unable to invoke adapter service {0}. Unable to create Input record.**
Explanation	An unexpected exception occurred during the adapter service execution.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0117.4038E	**Unable to delete adapter service {0}.**
Explanation	An unexpected exception occurred trying to delete the adapter service.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0117.4039E	**Unable to update adapter service {0}.**
Explanation	An unexpected exception occurred trying to update the adapter service.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0117.4040E	**Unable to create adapter service {0}. Adapter service node already exists.**
Explanation	It is illegal to create an adapter service with the same folder and node name.
Action	Use a different name for the adapter service and retry the create operation.

ART.0117.4048E	**Unable to update adapter service {0}.**
Explanation	An exception was encountered while attempting to update the adapter service.
Action	Check the Integration Server error log for details on the original exception.

ART.0117.4049E	**Unable to retrieve connection from resource {0}. See error log for details.**
Explanation	An exception was encountered while trying to retrieve a connection.
Action	Check the Integration Server error log for details on the original exception.

ART.0118.5000E	**Unable to retrieve and process connection properties from pipeline.**
Explanation	WmART failed to process a connection's properties. Additional log messages might be listed.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5001E	**Error processing connection property {0}. Unable to get property name.**
Explanation	WmART failed to locate an expected connection property in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5002E	**Error processing connection property {0}. Invalid value entered. The minimum string length is {1}.**
Explanation	The size of the specified connection property value is less than the specified minimum size.
Action	Reconfigure the connection from Integration Server Administrator using values that are within the constraints set by the connection.

ART.0118.5003E	**Error processing connection property {0}. Invalid value entered. The maximum string length is {1}.**
Explanation	The value of the specified property is not valid.
Action	Reconfigure the connection from Integration Server Administrator using values that are within the constraints set by the connection.

ART.0118.5004E	**Error processing connection property {0}.**
Explanation	An error occurred when converting a connection property value to its internal Java representation. Additional log messages might be listed.
Action	Reconfigure the connection from Integration Server Administrator ensuring that all data entered conforms to the underlying types in the connection class. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5005E	**Unable to configure connection properties. Error occurred while processing connection properties.**
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.

ART.0118.5006E	**Unable to get list of connections for adapter type: {0}.**
Explanation	An error occurred while retrieving the list of configured connections for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5007E	**Unable to get list of connection types for adapter type: {0}.**
Explanation	An error occurred while retrieving the list of connection factories for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5008E	**Unable to get properties for connection {0}.**
Explanation	An error occurred while retrieving the configuration details for a specific connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5009E	**Unable to get connection properties for adapter: {0}, connection type: {1}.**
Explanation	An error occurred while retrieving the connection properties for the specified connection factory and adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5010E	**Invalid connection name. The connection name must have a valid folder name and node name.**
Explanation	An invalid folder and/or connection name was entered on the Integration Server Administrator Configure Connection Type page.
Action	Re-enter the new connection type information making sure that the Folder Name and Connection Name fields have valid entries.

ART.0118.5011E	**Unable to create new connection {0}.**
Explanation	An error occurred while configuring a new connection type.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5012E	**Unable to update connection {0}.**
Explanation	An error occurred while editing the connection type.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5013E	**Unable to find connection {0}.**
Explanation	WmART was unable to locate the specified connection while deleting it.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5014E	**Unable to delete connection {0}.**
Explanation	An error occurred while deleting a connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5015E	**Unable to get connection manager properties.**
Explanation	An error occurred while getting a list of Connection Manager properties.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5016E	**Unable to get configured values for connection manager.**
Explanation	An error occurred while processing Connection Manager property values.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5017E	**Error occurred while getting connection manager properties.**
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.

ART.0118.5018E	**Error getting connection properties.**
Explanation	An error occurred while fetching connection property values.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5019E	**Error getting connection metadata. Missing required parameter: adapterTypeName.**
Explanation	WmART was unable to determine the adapter type name while processing a connection's metadata.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5020E	**Unable to process connection properties. Internal error.**
Explanation	WmART failed to set properties for a connection node. The expected connection form fields were not found in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5021E	**Unable to process connection properties. Internal error.**
Explanation	WmART failed to get properties for a connection node. The expected connection form fields were not found in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5022E	**Cannot create connection {0}. Adapter type {1} does not exist.**
Explanation	WmART failed to start the specified connection because it was unable to locate the specified adapter type.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5023E	**Unable to configure connection manager. No connection manager properties provided.**
Explanation	WmART was unable to validate Connection Manager properties because they were null.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5024E	**Unable set connection {0} state to {1}. Invalid state specified.**
Explanation	WmART was unable to modify the connection's state because the intended state is missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5025E	**Unable to enable connection {0}.**
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.

ART.0118.5026E	**Unable to stop connection {0}.**
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.

ART.0118.5027E	**Unable to enable connection {0}. Connection is already enabled or is being shutdown.**
Explanation	WmART is enabling a connection that is not currently in a disabled state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5028E	**Unable to shutdown connection{0}. Connection is already disabled or in the process of being shutdown.**
Explanation	WmART is attempting to shut down a connection that is not currently in an enabled state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5029E	**Unable to disable connection {0}. Connection is already disabled.**
Explanation	WmART is attempting to disable a connection that is already disabled.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5030E	**Unable to create connection {0}. Package {1} does not exist.**
Explanation	WmART was unable to create the connection node because it could not locate the specified package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5031E	**Unable to delete connection {0}. Internal error.**
Explanation	An error occurred while deleting the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5032E	**Unable to set connection resource properties. Internal error: ConnectionPropertiesBridge not found.**
Explanation	WmART failed to create a configured managed connection factory because it could not locate the WmConnectionPropertiesBridge instance needed to set its properties.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5033E	**Error disabling connection resources.**
Explanation	An error occurred while stopping the connection resources. See adjacent log messages for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5034E	**Connection type {0} does not exist in adapter {1}.**
Explanation	WmART was unable to locate the specified connection factory in the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5035E	**Unable to create connection {0}. Internal error occurred while creating connection factory of type {1}.**
Explanation	WmART was unable to create the specified connection factory for the connection. See adjacent log messages for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5036E	**Unable to configure connection manager.**
Explanation	WmART was unable to create a Connection Manager. See adjacent log messages for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5037E	**Cannot create ResourceAdapterMetaData object. CCI Connection Factory is not an instance of WmConnectionFactory.**
Explanation	The method ConnectionDataNodeManager.createCCIConnectionFactory could not get the ResourceAdapterMetaData object for a connection factory.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5040E	**Unable to get adapter service templates for connection {0}.**
Explanation	WmART failed to locate any adapter service templates for the specified connection.
Action	Do not configure an adapter service with a connection for which no adapter service templates exist. Try another connection.

ART.0118.5041E	**Unable to get connection status for connection resource {0}.**
Explanation	WmART was unable to obtain connection state information for the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5042E	**Unable to enable connection resource {0}.**
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.

ART.0118.5043E	**Unable to disable connection resource {0}.**
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.

ART.0118.5044E	**Unable to shutdown connection resource {0}.**
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.

ART.0118.5046E	**Unable to get a connection to resource {0}. Resource not available.**
Explanation	WmART could not locate a connection factory for the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5047E	**Unable to get a connection to resource {0}. Internal error occurred while restarting connection.**
Explanation	An error occurred while creating the connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5048E	**Unable to get adapter service templates for connection resource {0}.**
Explanation	WmART failed to locate any adapter service templates for the connection.
Action	Do not configure an adapter service with a connection for which no adapter service templates exist. Try another connection.

ART.0118.5049E	**Unable to reset adapter connection {0}. Connection {1} is not supported.**
Explanation	The method ConnectionResource.handleAdapterConnectionException reports that the specified connection class is not derived from WmConnection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5050E	**Unable to reset adapter connection {0}. Unable to configure connection manager.**
Explanation	The method ConnectionResource.handleAdapterConnectionException was unable to locate the ConnectionManager or ConnectionManagerPropertiesBridge for this connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5051E	**Unable to reset adapter connection {0}. Adapter type {1} does not exist.**
Explanation	The method ConnectionResource.handleAdapterConnectionException was unable to determine the adapter type for this connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5052E	**Unable to create connection. Connection resource {0} is restarting.**
Explanation	The method ConnectionResource.createConnection has been called against a connection resource in the restarting state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5053E **Unable to get a connection to resource {0}.**

Explanation WmART failed to create a connection because it could not communicate with the back-end connection resource.

Action Check independently that the target resource is communicating and that it can be reached from the connection. If the condition persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5054E **Unable to reset adapter connection {0}.**

Explanation An error occurred while trying to restart the specified connection. See adjacent log messages for additional details.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5055E **Unable to get adapter service templates for connection resource {0}.**

Explanation The method ConnectionResourceState.getInteractionSpecsSupported failed to locate the ResourceAdapterMetaData associated with specified connection.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5056E **Unable to create connection for connection resource {0}, connection type {1}.**

Explanation The method ConnectionResourceState.createConnection failed to get the Connection object for the specified connection.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5057E **Adapter Runtime was unable to initialize {0} connection resources for the adapter "{1}".**

Explanation com.wm.pkg.art.ns.ConnectionDataNodeManager.startConnectionResources detected failures in starting connection nodes for the specified adapter.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5058E	**Adapter Runtime was unable to stop {0} connection resources for the adapter "{1}".**
Explanation	com.wm.pkg.art.ns.ConnectionDataNodeManager.stopConnectionResources detected failures in shutting down connection nodes for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5059E	**Adapter Runtime was unable to stop connection resources for the {0} adapter types.**
Explanation	com.wm.pkg.art.ns.ConnectionDataNodeManager.stopAllConnectionResources detected failures in shutting down connection nodes.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5060E	**Unable get properties for connection resource {0}.**
Explanation	An error occurred while fetching the specified connection's properties.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5061E	**Unable to configure Connection Manager: Poolable property not set.**
Explanation	WmART failed to determine whether a connection should be pooled.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5062E	**Unable to find connection {0}: error {1}.**
Explanation	An error was encountered while validating the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5063E	**Unable to start connection {0}: after {1} attempt(s).**
Explanation	The startup of a connection pool has exceeded the maximum number of retries.
Action	Check the Integration Server error log for details on the retryable exception.

ART.0118.5064E	**Cannot reconfigure connection {0}: it must be disabled first.**
Explanation	To update a connection, it must be disabled.
Action	Disable the connection and retry the update operation.

ART.0118.5065E	**Cannot delete connection {0}: it must be disabled first.**
Explanation	To delete a connection, it must be disabled.
Action	Disable the connection and retry the delete operation.

ART.0118.5066E	**Exception encountered processing {0} connection callback method. The {1} operation will proceed.**
Explanation	An exception was encountered while executing the specified connection callback method.
Action	Look in the error log for details on the original exception. The callback processing did proceed even though the error was encountered.

ART.0118.5067E	**Unknown callback event type received on connection node: {0}**
Explanation	An unknown connection callback was made.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5068E	**Exception encountered processing {0} connection callback method.**
Explanation	An exception was encountered while executing the specified connection callback method.
Action	Look in the error log for details on the original exception. When this error is received, the callback processing does not continue.

ART.0118.5069E	**Cannot create connection factory for connection {0}. Adapter type {1} does not exist.**
Explanation	The adapter associated with this connection is not registered.
Action	Verify the package dependencies are set correctly. Reload the adapter package, and retry the operation.

ART.0118.5070E	**Exception encountered creating the connection factory for connection {0}.**
Explanation	An exception was encountered creating the connection factory.
Action	Look in the error log for details on the original exception.

ART.0118.5071W	**A non-fatal exception was encountered attempting to unregister {0}. The operation will proceed. See the error log for more details.**
Explanation	An exception was encountered trying to unregister the connection node.
Action	Look in the error log for details on the original exception. The unregister processing continued.

ART.0118.5072E	**Adapter service {0} cannot use connection {1}. The adapter service and connection are from different adapters.**
Explanation	The user attempted to set the connection associated with an adapter service; however, the adapter service and connection were not from the same adapter.
Action	Retry the operation using a connection from the same adapter.

ART.0118.5073E	**Adapter service {0} cannot use connection {1}. The connection is already being used by a listener.**
Explanation	The user attempted to use a connection in an adapter service; however, the connection is already being used by a listener.
Action	Retry the operation using a connection that is not already being used by a listener.

ART.0118.5074E	**"{0}" is not a valid connection name for adapter {1}**
Explanation	The user attempted to use a connection in a polling notification or listener; however, the connection was not part of the same adapter.
Action	Retry the operation using a connection from the same adapter.

ART.0118.5075E	**Listener {0} cannot use connection {1}. The connection is already being used by an adapter service or polling notification.**
Explanation	The specified listener cannot use the specified connection because the connection is already being used by a polling notification or an adapter service.
Action	Retry the operation using a connection that is not being used by a polling notification or adapter service.

ART.0118.5076E	**Polling notification {0} cannot use connection {1}. The connection is already being used by a listener.**
Explanation	The user attempted to use a connection in a polling notification; however, the connection is already being used by a listener.
Action	Retry the operation using a connection that is not already being used by a listener.

ART.0118.5077E	**Adapter service {0} cannot use connection {1}. The connection does not support this adapter service template.**
Explanation	The user attempted to use a connection for an adapter service; however, the connection does not support the adapter service.
Action	Retry the operation using a connection that supports the adapter service.

ART.0118.5078E	**Minimum pool size must not be greater than maximum pool size.**
Explanation	The user attempted to set the minimum pool size to a value that is greater than the maximum pool size.
Action	Retry the operation specifying a minimum pool size that is lower than the maximum pool size.

ART.0118.5079	**Exception encountered while removing {0} connection from Connection cache.**
Explanation	An error occurred while invalidating a failed XA transaction.
Action	Make sure that there is connectivity to the adapter backend, and that the connection associated with the transaction is enabled. Check the server logs for transaction details.

ART.0118.5080	**Exception encountered while updating connection {0}.**
Explanation	An error occurred while updating a connection node from an old version to a new one.
Action	Make sure that the connection parameters are valid. Make sure that the user updating the connection has been assigned the appropriate ACL.

ART.0118.5083	**Invalid value {0} specified for {1} property, hence using default value as {2}**
Explanation	The value of the watt.art.connection.nodeVersion watt property is invalid. Hence, when creating the connection node, the specified node version is ignored and the default value for node version is used instead.
Action	Make sure the watt.art.connection.nodeVersion property has a valid value. For details, see the Integration Server administration guide.

AUTH055	**Did not add user(s) {0}. Password was empty.**
Explanation	The Password field requires a value.
Action	Enter a valid password.

BAB.0002.0000E	**Wrapped Exception:**
Explanation	A communication failure occurred between Integration Server and a client resulting in the exception.
Action	Verify that the communication parameters are correct. Check the setup for any network issues.

BAB.0006.0001E	**CommException: LinkServer closed**
Explanation	A client sent a request to Integration Server after a previous connection between the client and Integration Server was closed.
Action	Make sure that the client is not designed to send new requests to Integration Server when communication with the server is closed.

BAD_AUDIT_DIRE	**The value supplied for watt.server.audit.logDir does not identify an existing directory that Integration Server can write to. watt.server.audit.logDir was not changed.**
Explanation	The audit log directory was not changed because the watt.server.audit.logDir parameter refers to a directory that either does not exist or Integration Server does not have permission to write to.
Action	Specify a directory that exists on the server and that Integration Server can write to. You can specify the full path name, or a relative path in relation to the Integration Server.

BAD_SESSION_ID	**Invalid or expired session identifier.**

BAF.0000.0001E	**No file or properites specified**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0000.0002E	**Illegal set_mode: {2}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0000.0003E **FSDirCursor _encode exception**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0004E **A minimum of three log segments required only {2} found**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0005E **Unsupported BlockDevice specified: {2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0006E **BlockDevice Exception:**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0007E **Unable to open FSData devices**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0008E **Wrong number of Data Extents:{2} != {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0009E **Invalid dataMaxExtents specified:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0010E **Invalid indexMaxExtents specified:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0011E **Invalid dataMaxExtents:{2} must be between 1 and {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0012E **Invalid indexMaxExtents:{2} must be between 1 and {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0013E **Invalid dataThreshold specified:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0014E **Invalid indexThreshold specified:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0015E **Invalid dataThreshold:{2} must be between 50% and 99%**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0016E **Invalid indexThreshold:{2} must be between 50% and 99%**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0017E **Log offset:{2} inside Superblock**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0018E **Log offset:{2} > Meta offset:{3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0019E **Meta offset{2} > Data offset:{3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0020E **Error during create - Data store already exists**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0021E **Exception during checkDataDevices:**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0022E **Exception during newHashCode:**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0023E **Unknown log type:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0024E **NOT RETURNABLE in finalize:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0025E **Finalizing undestroyed cursor (p={2} d={3})**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0026E **No more null entries after {2} in {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0027E **Filesystem full ({2} < {3})**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0028E **Block write failure**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0029E **Unable to locate block of sufficient size**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0030E **Cannot unlink last remaining empty**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0031E **Data Expansion required but Maximum Data Exceeded**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0032E **Index expansion requested but maximum are allocated**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0033E **CreateIndexExtent, unable to alloc block**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0034E **Mismatch:{2} {3} != {4}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0046E **Warning {2} failed**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0047E **Notify() on null ref idx={2} hc={3} : {4}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0048E **Transaction has no members:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0072E **Error during open - Log File does not exist**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0073E **Error during create - Log File already exists**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0074E **Error during create - Average Block Size or entries must be specified**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0075E **Error during create - NumEntries exceeds size of integer**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0076E **Error during open - data file segments do not match, input {2}, output {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0102E **The FSData is damaged, see the journal log for details**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0103E **FSData checker. Bad NULL entry chain**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0035E **Fatal Runtime Exception:{2}**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0036E **No open TXN for dirty entry**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0037E **Filesystem is in an invalid state**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0038E **Improper deleted type:{2}**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0039E **Can't unlink:{2}**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0040E **Can't add first empty back to empty list**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0041E **FreeBytes mismatch:{2} != {3}**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0042E **Out of order merge:{2} & {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0043E **First null entry cannot be null**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0044E **First empty entry cannot be null**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0045E **Transaction has no members:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0049E **Cannot use destroyed cursor**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0050E **EndTXN called outside of a transaction**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0051E **AbortTXN called outside of a transaction:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0052E **Log is not open**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0053E **Log is not closed**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0054E **Log is smaller than max block ({2} < {3})**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0055E **Transaction larger than total log**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0056E **Cursors already @ 0:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0057E **References negative!:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0058E **Entry is already unlinked!:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0059E **No backup to revert to:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0060E **Type mismatch: {2} != {3} on {4}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0061E **Data length ({2}) != expected length:{3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0001.0076E **Illegal state change from {2} to {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0002.0000E **Wrapped Exception:**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0003.0070E **TransactionException: Wait to start transaction interrupted**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0003.0071E **TransactionException: Resource already in a transaction**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0003.0072E **TransactionException: Wait to start transaction not allowed**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0062E **Data: Unable to get cursor lock**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0063E **Data: Cannot get key, cursor is unpositioned**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0064E **Data: Cannot get value, cursor is unpositioned**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0065E **Data: Cannot get value reference, cursor is unpositioned**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0066E **Data: Cursor is unpositioned**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0067E **Data: Unable to delete: {2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0068E **Data: Can not clone a destroyed cursor**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0069E **Data: Referenced object has been deleted**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0077E **IOException: No Properties provied to JDBCBlockDev**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0078E **IOException: No JDBC Driver provided to JDBCBlockDev**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0079E **IOException: No URL provided to JDBCBlockDev**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0080E **IOException: Unable to create table:{2}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0081E **IOException: {2} JDBCBlockDevice doesn't support Logical Devices - offset:{3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0082E **IOException: {2} Attempted to write past final segment: {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0083E **IOException: {2} Attempted to read past final segment: {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0084E **IOException: {2} Blob length: {3} != Segment size:{4}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0085E **IOException: {2} Not Found:**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0086E	**IOException: {2} Unable to Connect - Retries Exhausted**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0087E	**IOException: All component files must be the same length**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0088E	**IOException: Invalid logical position specified**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0089E	**IOException: Read error**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0090E	**IOException: Write error**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0091E	**IOException: Invalid Physical position**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0092E	**IOException: SplitExtent failed - Extent not found:{2}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0093E	**IOException: Unable to allocate new IBlockDevice in Device Group**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0094E **IOException: Invalid Log Region detected - Timestamp mismatch**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0095E **IOException: CompositeBlockDevice read error**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0096E **IOException: missing {2} properties file**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0097E **IOException: Illegal mode {2}. Must be 'rw' or 'r'**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0098E **IOException: block device has 0 length**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0099E **IOException: Unable to read {2} bytes**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0100E **IOException: Unable to allocate write buffer**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0005.0101E **IOException: Native library unavailable**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAQ.0002.0000 **Wrapped Exception:**

BAQ.0003.0001 **TransactionException: Resource already in a transaction**

BAR.0001.1401 **RuntimeException: unsupported cursor {2}**

BAR.0002.0000 **Wrapped Exception:**

BAR.0005.1600 **RepoDirCodec: DecodeParms must be called before decode**

BAR.0005.1601 **RepoDirCodec: Unserializable repo object**

BAR.0005.1602 **RepoDirCodec: Repo Must be Standalone**

BAR.0006.1700 **CommException: sendRequest() failed**

BAR.0006.1701 **CommException: ConnectionServer closed**

BAR.0006.1702 **CommException: Missing keyword:{2}**

BAR.0010.0001 **Directory: insert exception:**

BAR.0010.0002 **Directory: update exception:**

BAR.0010.0003 **Directory: rename exception:**

BAR.0010.0004 **Directory: get queue failed, invalid object type**

BAR.0010.0005	**Directory: entry version "{2}" does not exist for entry "{3}"**
BAR.0010.0007	**Directory: delete exception:**
BAR.0010.0008	**Directory: "{2}" already exists**
BAR.0010.0009	**Directory: entry "{2}" is not a symbolic link**
BAR.0010.0011	**Directory: object has been destroyed**
BAR.0010.0012	**Directory: null not allowed in compound directory path expression**
BAR.0010.0013	**Directory; key "{2}" not found**
BAR.0010.0014	**Directory: key "{2}" is not a repository directory**
BAR.0010.0015	**Directory: "{2}" can not be versioned**
BAR.0010.0016	**Directory: illegal state, directory may have been destroyed**
BAR.0010.0017	**Directory: "{2}" is an invalid symbolic link target**
BAR.0010.0018	**Directory: "{2}" is a repository directory and an invalid symbolic link target**
BAR.0010.0019	**Directory: "{2}" is a repository IData object and an invalid symbolic link target**
BAR.0010.0021	**Directory: new key {2} can not be a compound key**

BAR.0010.0022 **Directory: RepoQueue {2} can not be versioned**

BAR.0010.0023 **Directory: "{2}" is a symbolic link and is invalid as a symbolic link target**

BAR.0010.0024 **Directory: Entry {2} not versioned**

BAR.0010.0025 **Directory: reconnect attempt failed**

BAR.0010.0026 **Directory: get queue failed, object is null**

BAR.0010.0027 **Directory: can not be target of an update for entry {2}**

BAR.0010.0028 **Directory: invalid version number {2}**

BAR.0010.0029 **Directory: invalid relative version number {2}**

BAR.0010.0030 **Directory: cannot delete current version for entry {2}**

BAR.0010.0031 **Directory: illegal transaction state, {2} not allowed in active transaction**

BAR.0010.0032 **Directory: testAndSet failed for entry {2}:**

BAR.0010.0033 **Directory: testAndSet failed for entry {2} - Invalid Entry Type**

BAR.0010.0034 **Directory: key "{2}" is not a repository stream**

BAR.0010.0035 **Directory: internal error, unknown repository container type, {2}**

BAR.0011.0100	**Queue: constructor failure:**
BAR.0011.0101	**Queue: enqueue failure:**
BAR.0011.0102	**Queue: dequeue failure:**
BAR.0012.0200	**Stream: Invalid length key type: {2}**
BAR.0012.0201	**Stream: DataException: {2}**
BAR.0012.0202	**Stream: Invalid Object: {2} missing {3}**
BAR.0012.0203	**Stream: Invalid Segments key type: {2}**
BAR.0012.0204	**Stream: Segment {2} not found in {3}**
BAR.0012.0205	**Stream: Invalid Status key type: {2}**
BAR.0012.0206	**Stream: EOF - Pending stream**
BAR.0012.0207	**Stream: {2} already open for output**
BAR.0012.0208	**Stream: {2} closed**
BAR.0012.0209	**Stream: Error Writing byte[] to OutputStream: {2}**
BAR.0012.0210	**Stream: Error Flushing OutputStream: {2}**

BAR.0012.0211 **Stream: Error Closing OutputStream: {2}**

BAR.0012.0212 **Stream: Error Reading InputStream: {2}**

BAR.0012.0213 **Stream: Error Closing InputStream: {2}**

BAR.0013.0300 **NameParser: missing component key**

BAR.0013.0301 **NameParser: invalid key syntax: "{2}"**

BAR.0013.0302 **NameParser: index missing from key "{2}"**

BAR.0013.0303 **NameParser: index not numeric "{2}"**

BAR.0013.0304 **NameParser: bad array index syntax "{2}"**

BAR.0014.0400 **Illegal argument: Directory object cannot be stored**

BAR.0014.0403 **Illegal argument: Key must be specified**

BAR.0014.0404 **Illegal argument: Action must be ADD, DELETE, or CHANGE**

BAR.0015.0500 **Session: Logon required**

BAR.0015.0505 **Session: RepoStream object in use, RepoAPI calls not allowed**

BAR.0015.0510 **Session: Invalid logon URL "{2}" specified**

BAR.0015.0511 **Session: No default server specified**

BAR.0015.0515 **Session: Active repository session, logon not allowed**

BAR.0015.0516 **Session: Internal Error, invalid Transaction Resource object**

BAR.0015.0518 **Session: Duplicate logon not allowed**

BAR.0015.0519 **Session: Session not logged on**

BAR.0015.0520 **Session: Session disabled due to LUW timeout**

BAR.0015.0521 **Session: Previous LUW timeout still in progress, try again later**

BAR.0016.0600 **Internal Error: local server connection config invalid**

BAR.0016.0601 **Internal Error: during server initialization exception:**

BAR.0016.0603 **Internal Error: connection to repository server failed, missing remote refid**

BAR.0016.0604 **Internal Error: Repository server shutdown failed:**

BAR.0016.0605 **Internal Error: Repository server is not the primary server**

BAR.0017.0700 **RepoStore: Internal Error creating Repo Server object:**

BAR.0017.0701 **RepoStore: Unable to initialize Repository backing store**

BAR.0017.0702	**RepoStore: Repository server has been destroyed**
BAR.0017.0703	**RepoStore: Repository backing store not initialized**
BAR.0017.0704	**RepoStore: Missing 'persiststore' config parm**
BAR.0018.0900	**RepoConnection: Secondary server could not find primary repository server**
BAR.0018.0901	**RepoConnection: Could not find primary repository server: {2}**
BAR.0018.0904	**RepoConnection: Reconnect failed, no remote server cluster connection information available**
BAR.0019.1100	**Transaction: Resource already participating in a transaction**
BAR.0019.1101	**Transaction: Illegal transaction state, transaction destroyed**
BAR.0019.1102	**Transaction: Illegal transaction state, session mismatch**
BAR.0019.1103	**Transaction: Illegal transaction state, IDataSharedCuror Transactions not supported**
BAR.0019.1104	**Transaction: TransactionException: Cursor has been destroyed**
BAR.0020.1200	**SharedCursor: illegal state, cursor destroyed**
BAR.0020.1201	**SharedCursor: reconnect attempt failed**
BAR.0020.1202	**SharedCursor: invalid resource specified**

BAR.0020.1203	**SharedCursor: Reconnect Exception detected**
BAR.0020.1204	**SharedCursor: Can not get key, cursor is unpositioned.**
BAR.0020.1205	**SharedCursor: Can not get value, cursor is unpositioned.**
BAR.0021.1300	**Queue: reconnect attempt failed**
BAR.0021.1301	**Queue: illegal state, queue destroyed**
BAR.0021.1302	**Queue: object has been destroyed**
BAR.0021.1303	**Queue: Repository Queue entry corrupted**
BAR.0022.1400	**Data: illegal state, IData destroyed**
BAR.0023.1500	**Migration: export not implemented in RepoMigrate, use Repov2Migrate or Repov3Migrate to export your specific Repo version**
BAR.0023.1501	**Migration: exception:{2}**
BAR.0023.1502	**Migration: Error During Import, probably Coder mismatch between Export and Import utilities: exception:{2}**
BAR.0023.1503	**Migration: import not implemented in {2}, use RepoMigrate to import**
BAS.0123.0004E	**FSData checker repair attempted. Zero length file deleted. {0}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0007E	**FSData checker. {0} entrys not in any chain.**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0008E	**FSData checker repair attempted. Bad NULL list entry removed. {0}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0009E	**FSData checker. Entry in {0} list has bad prev pointer. {1}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0010E	**FSData checker. Entry in {0} list has wrong type. {1} != {2} {3}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0011E	**FSData checker. Duplicate entry in {0} list. {1}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0012E	**FSData checker. Entry in {0} list contains bad reference count. {1}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0013E	**FSData checker. Data node has wrong type. {0}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0014E	**FSData checker. Hash tree node has wrong type. {0}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0015E **FSData checker. Free byte count is wrong. {0} != {1}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0016E **FSData checker repair attempted. {0} orphaned NULLs recovered.**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0017E **FSData checker. Entry is in multiple chains. {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0018E **FSData checker. Repair attempted - full check will be run again.**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0019E **FSData checker. Attempting to recover orphaned NULL and EMPTY entries.**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0021E **FSData checker. Dir entry has bad last node pointer. {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0022E **FSData checker repair attempted. Bad EMPTY list entry removed. {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAT.0000.0001 **duplicate endpoint id {2}**

BAT.0000.0002	**endpoint {2} not found.**
BAT.0000.0003	**endpoint {2} can not be deleted it has producers/consumers with active or pending messages.**
BAT.0000.0004	**duplicate producer id {2}**
BAT.0000.0005	**producer {2} not found.**
BAT.0000.0006	**producer {2} can not deleted, it has active or pending messages.**
BAT.0000.0007	**duplicate consumer id {2}**
BAT.0000.0008	**consumer {2} not found.**
BAT.0000.0009	**consumer {2} can not deleted, it has active or pending messages.**
BAT.0000.0010	**duplicate message store id {2} for producer {3}**
BAT.0000.0011	**consumer {2} message store id {3} not found.**
BAT.0000.0012	**consumer {2} message store {3} can not deleted, it has active or pending messages.**
BAT.0000.0013	**no active transaction for message store id {2} for parent container id {3}**
BAT.0000.0014	**transactions not enabled for message store id {2} for parent container id {3}**
BAT.0000.0015	**method disabled because transactions are enabled for message store id {2} for parent container id {3}**

BAT.0000.0016	**consumer {2} message store {3} this method requires transactions to be enabled.**
BAT.0000.0017	**duplicate sequence number {2} for message id {3} in store id {4} in parent container id {5}**
BAT.0000.0018	**message id {2} not found in message store id {3} for parent container id {4}**
BAT.0000.0019	**out of sequence message seq {2}, last seq {3} id {4} in store id {5} in parent container id {6}**
BAT.0000.0020	**argument arrays must be same length, message store id {2} for parent container id {3}**
BAT.0000.0021	**invalid timeout value {2}, must be > 0**
BAT.0000.0022	**invalid message sequence number {2}, must be >= 0**
BAT.0000.0023	**invalid message acknowledge mode {2}**
BAT.0000.0024	**message id can not be null, {2}**
BAT.0000.0025	**illegal state change request from {2} to {3}**
BAT.0000.0026	**{2} {3} has been closed**
BAT.0000.0027	**thread has been interrupted**
BAT.0000.0028	**method [{2}] is not allowed from a rejected message handler.**

BAT.0000.0029 **the transient store type {2} specified could not be initialized.**

BAT.0000.0030 **IData backing store is null, required**

BAT.0000.0031 **IDATASTORE type requires a transacted IData implemenation**

BAT.0000.0032 **duplicate message for store id {2} in parent container id {3}**

BAT.0000.0033 **{2} {3} is already started.**

BAT.0000.0034 **{2} {3} has been stopped.**

BAT.0000.0035 **Invalid reference: MessageStore[{2}] is null.**

BAT.0000.0036 **A ISimpleQueueProducer has already been created for this SimpleQueue**

BAT.0000.0037 **A ISimpleQueueConsumer has already been created for this SimpleQueue**

BAT.0000.0038 **Cannot ack not allowed for a zero-or-more SimpleQueue**

BAT.0000.0039 **Cannot nack not allowed for a zero-or-more SimpleQueue**

BAT.0000.0040 **SimpleQueue {2} not found.**

BAT.0000.0041 **SimpleQueue {2} can not be deleted it is not empty.**

BAT.0002.0000 **Wrapped Exception:**

BAT.0127.0001	**Recoverable Error skipped because warnonopen = continue. Db:{0} Error:{1}**
BAT.0127.0002	**Recoverable Error encountered but warnonopen = fail. Db:{0} Error:{1}**
BAT.0127.0003	**Error deleting damaged data file. Db:{0} Error:{1}**
BAT.0127.0004	**Error renaming damaged data file. Db:{0} Error:{1}**
BAT.0127.0005	**Error re-creating damaged data file. Db:{0} Error:{1}**
BAT.0127.0006	**Damaged data file renamed. Db:{0} renamed:{1}**
BAT.0127.0007	**Damaged data file deleted. Db:{0}**
BAT.0127.0008	**Damaged data file re-created. Db:{0}**
BAT.0127.0009	**Error during checkDataDevice. Db:{0} Error:{1}**
BAT.0127.0010	**Damaged data file detected. Db:{0} Error:{1}**
BAT.0127.0011	**Data file resize required. Db:{0}**
BAT.0127.0012	**Error cleaning up resized Data file. Db:{0} Error:{1}**
BAT.0127.0013	**Error creating resized Data file. Db:{0} Error:{1}**
BAT.0127.0014	**Error copying resized Data file. Db:{0}**

BAT.0127.0015 **Error renaming original data file. Db:{0} Error:{1}**

BAT.0127.0016 **Error closing resized data file. Db:{0} Error:{1}**

BAT.0127.0017 **Error renaming resized data file. Db:{0} Error:{1}**

BAT.0127.0018 **Error restoring original data file. Db:{0} Error:{1}**

BAT.0127.0019 **Error cleaning up copied Data file. Db:{0} Error:{1}**

BAT.0127.0020 **Error closing original Data file. Db:{0} Error:{1}**

BAT.0127.0021 **Data file resize completed. Db:{0}**

BAT.0127.0022 **Resized Data file recovered. Db:{0}**

BEHAVIOUR_IS_INVALID – Behaviour should be one of client or server

BROKER_NOT_REACHABLE – Broker not connected.

CACHE_CACHE_MANAGER_NOT_INITIALIZED – Cache manager {0} is not loaded or initialized.

CACHE_CACHE_NOT_FOUND – Cache {1} for cache manager {0} not found.

CACHE_CANNOT_ACQUIRE_READ_LOCK – Could not acquire a read lock for key {0} in cache {1} contained within the cache manager {2}.

CACHE_CANNOT_ACQUIRE_WRITE_LOCK – Could not acquire a write lock for key {0} in cache {1} contained within the cache manager {2}.

CACHE_INVALID_INPUT – Invalid value for input parameter {0}. Error:{1}.

CACHE_MISSING_PARAM_NAME – Missing required parameter: {0}

CALLBACK_IS_REQD Callback is required

CALLBACK_SIGN_INVALID – Callback service input signature for flow service "{0}" should be as per "{1}"

CALLBACK_SPEC_INVALID – Callback service specification for flow service "{0}" should point to "{1}"

CALLBACK_SVC_EXISTS – Callback service "{0}" cannot be created as another node with same name exists

CANNOT_CREATE_FOREACH – Cannot make the For Each from: {0} to: {1}

CAN_NOT_RESUME can not resume due to state:

CAN_NOT_SUSPEND can not suspend due to state:

CLIENT_HTTP_EXP3 Do not use data.string, data.stream or data.mimeStream with the DELETE method.

CLIENT_HTTP_KERBEROS_DELEGATION_NO_CREDENTIALS – Kerberos delegatable credentials do not exist.

Explanation	Delegatable credentials do not exist. Delegation is set to Kerberos without requesting for a delegatable token in the previous (parent) pub.client:http call.
Action	Ensure that the delegation input in the pub.client:http is set only after the requestDelegatableToken is set to true in the previous (parent) pub.client:http call.

CLIENT_HTTP_KERBEROS_INVALID_SPN_FORMAT – Invalid Service Principal Name Format provided

CLIENT_HTTP_KERBEROS_PRINCIPALPASSWORD_DELEGATION_BOTHREQ – Either both Kerberos clientPrincipal and clientPassword must be supplied or both should be left blank.

CLIENT_HTTP_KERBEROS_SPNFORM_DELEGATION_FORMAT – Kerberos service principal name form must be either username or hostbased.

CLIENT_HTTP_KERBEROS_SPN_FORM_DELEGATION_BOTHREQ – Either both Kerberos service principal name and service principal name form must be supplied or both should be left blank.

CLIENT_INPUT_NOT_BYTE_ARRAY – Input {0} must be a byte array

CLIENT_WEBSOCKET_MISSING_INPUT – "{0}" is a required input

CLIENT_WEBSOCKET_WRONG_URL – URL is required and must begin with ws or wss

CURRENT_EVENT_IS_NOT_A_START_ELEMENT – Current event is not a START_ELEMENT

CURRENT_STATE_NOT_START_ELEMENT – Current state not START_ELEMENT

CURRENT_STATE_NOT_START_ELEMENT_END_ELEMENT_OR_ENTITY_REFERENCE – Current state not START_ELEMENT, END_ELEMENT or ENTITY_REFERENCE

CURRENT_STATE_NOT_START_ELEMENT_OR_END_ELEMENT – Current state not START_ELEMENT or END_ELEMENT

DB_IS_REQD The ISCoreAudit functional alias on the JDBC Pools page must be configured to use the Service Monitoring capabilities

DEFAULT_ILIVE_TRUSTSTORE_DESCRIPTION – Default truststore alias for webMethods Cloud.

DEPLOYER_PACKAGE_DISALLOW_INSTALL_ON_ENABLED – Package"{0}" will not be deployed because deploying to an enabled package is disallowed

DEPLOYER_PACKAGE_INSTALL_ERR_MSG – Package "{0}" did not install successfully. Messages: {1}

DEPLOYER_PACKAGE_NOT_ENABLED – The deployed package {0} is disabled. Check the Integration Server logs for any errors that may have occurred during deployment. If the package contains Adapter or .NET assets for which variable substitution parameters were specified, you must perform the variable substitutions manually on the Integration Server for the changes to take effect.

DEPLOYER_PACKAGE_SERVICE_EXECUTION_CHECK – Package"{0}" will not be deployed because at least one of the Package services is in execution

DISABLEDE	**Messaging Synchronizer has been disabled**
Explanation	The Broker Synchronizer has been disabled.
Action	Check the status of the Broker and the Broker Settings in Integration Server Administrator.

DUPE_EVENT_TYPE_NAME – Document type {0} has failed to load. Duplicate Broker document type name {1} is also referenced by {2}

DUP_XID_RESOURCE_UPDT – Failed attempt to store resource status={0} for xid={1}, resource={2}. XID not found.

DUP_XID_START	**Transaction start for xid={0} failed. Transaction for this xid has already been started.**

EDA_EID_ROOT_NODE	**Parameter xmldata must be XML with a root node element named "Event {http://namespaces.softwareag.com/EDA/Event}".**

EGDOS002E	**Error occurred while updating global Denial of Service options for Enterprise Gateway rules. Details: {0}.**
Explanation	Enterprise Gateway Server could not update the global Denial of Service options for Enterprise Gateway rules for the reason indicated.
Action	Ensure that the correct input parameters are provided to the service. Then, try to update the global Denial of Service options again.

EGDOS006E	**Error occurred while updating Denial of Service by IP address options for Enterprise Gateway rules. Details: {0}.**
Explanation	Enterprise Gateway Server could not update DoS by IP address options for Enterprise Gateway rules for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

EGMAPP02E	**Error occurred while updating device types. Details: {0}.**
Explanation	Enterprise Gateway Server could not update the list of device types. Possible reasons are: The device name is too long (exceeds 255 characters) or contains special characters; the device type was deleted by another user while the current user tried to update the list; the device type is specified in one or more Enterprise Gateway rules; or there was a problem saving the device types to the Enterprise Gateway rules configuration file.
Action	If you are adding a device type, use the correct format. If you are deleting a device type and the device type is used in one or more Enterprise Gateway rules, remove or change the condition in the mobile application protection filter where the device type is specified.

EGMAPP04E	**Error occurred while updating mobile applications. Details: {0}.**
Explanation	Enterprise Gateway Server could not update the list of mobile applications. Possible reasons are: The application name is too long (exceeds 255 characters) or contains special characters; the application was deleted by another user while the current user tried to update the list; the application is specified in one or more rules; or there was a problem saving the application to the Enterprise Gateway rules configuration file.
Action	If you are adding a mobile application, use the correct format. If you are deleting a mobile application and the application is used in one or more Enterprise Gateway rules, remove or change the condition in the mobile application protection filter where the application is specified.

EGRULE002E	**Enterprise Gateway rule could not be created. Details: {0}.**
Explanation	Enterprise Gateway Server could not create the Enterprise Gateway rule for the reason indicated.
Action	Ensure that the correct input parameters are provided to the rule creation service.

EGRULE004E	**Enterprise Gateway rule could not be updated. Details: {0}.**
Explanation	Enterprise Gateway Server could not update the Enterprise Gateway rule for the reason indicated.
Action	Ensure that the correct input parameters are provided to the rule update service.

EGRULE006E	**Enterprise Gateway rule could not be deleted. Details: {0}.**
Explanation	Enterprise Gateway Server could not delete the Enterprise Gateway rule for the reason indicated.
Action	Ensure that the correct input parameters are provided to the rule deletion service.

EGRULE007E	**A rule violation occurred for Enterprise Gateway rule "{0}". Filter: "{1}", message: "{2}", request IP: {3}, request URL: {4}, request time: {5}.**
Explanation	Enterprise Gateway Server could not process the request because an Enterprise Gateway rule violation occurred.
Action	Either change the rule filter settings or modify the request so a rule violation does not occur.

EGRULE008E	**A rule violation occurred for Enterprise Gateway rule "{0}". Request IP: {1}, request URL: {2}, request time: {3}.**
Explanation	Enterprise Gateway Server could not process the request because an Enterprise Gateway rule violation occurred.
Action	Either change the rule settings or modify the request so a rule violation does not occur.

ELEMENT_IS_NOT_A_TEXT_ONLY_ONE – Element is not a text-only one

ELEMENT_TEXT_CONTENT_MAY_NOT_CONTAIN_START_ELEMENT – element text content may not contain START_ELEMENT

EMPTY_KEYSTORE_ALIAS – Alias is not specified

EMPTY_KEYSTORE_LOCATION – Location is not specified

EMPTY_KEYSTORE_PROVIDER – Provider is not specified

EMPTY_KEYSTORE_TYPE – Type is not specified

ENABLED **Enabled**

ERROR_DRIVER_CONTAINS_INVALID_CHARSI – Driver alias definition cannot be created. Driver alias name contains one or more invalid characters.

Explanation The Alias Name contains invalid characters. The Alias Name may contain: letters (a -z, A-Z), numbers (0-9), space ( ), underscore (_), period (.), and hyphen (-). The alias name must contain at least one letter or number.

Action Revise the Alias Name so that it is valid.

ERROR_POOL_CONTAINS_INVALID_CHARSI – Pool alias cannot contain any of these characters: {0}

ER_SEND_MISSING_EVENT_PARAM – Missing required parameter: {0}

EXCEPTION_PARSING_HELP_CONTEXT_FILE – Exception occurred while parsing the file doc/OnlineHelp/context.xml from WmRoot package: {0}

EXPECTED_LOCAL_NAME_NOT_MATCHING – Expected local name '{0}'; current local name '{1}'

EXPECTED_NON_NULL_LOCAL_NAME – Expected non-null local name, but current token not a START_ELEMENT, END_ELEMENT or ENTITY_REFERENCE (was {0})

FAC+"."+AUTO_CREATE_CONNECTION_FACTORY – Automatically creating JMS Connection Factory {0} for JMS connection alias {1}.

FAC+"."+AUTO_CREATE_DESTINATION – Automatically creating JMS Destination {0} for JMS connection alias {1}.

FAC+"."+ERROR_READING_SJO_FILE_FOR_CONNECTIONFACTORY – Error occurred during lookup for SonicMQ ConnectionFactory object from "{0}".

FAC+"."+ERROR_READING_SJO_FILE_FOR_DESTINATION – Error occurred during lookup for SonicMQ Destination object from "{0}".

FAC+"."+EXCEPTION_DURING_HOT_DEPLOYMENT – Exception {0} occured while handling Hot Deployment notification for trigger {1}

FAC+"."+JMS_STARTING – JMS subsystem is starting.

FAC+"."+PRODUCER_RETRY_FAILED – Producer Retry for destination {0} alias {1} failed after {2} attempt(s): {3}

FAC+"."+PRODUCER_RETRY_FAILED_ATTEMPT – Producer Retry for destination {0} alias {1} failed retry attempt {2}: {3}

FAC+"."+PRODUCER_RETRY_INTERRUPT_DISABLED – Producer Retry for destination {0} alias {1} has been interrupted because the alias is now disabled.

FAC+"."+PRODUCER_RETRY_INTERRUPT_DISCONNECTED – Producer Retry for destination {0} alias {1} has been interrupted because the connection is closed.

FAC+"."+PRODUCER_RETRY_INTERRUPT_SHUTDOWN – Producer Retry for destination {0} alias {1} has been interrupted because the server is shutting down.

FAC+"."+PRODUCER_RETRY_NOTRUN_DISABLED – Producer Retry not attempted for destination {0} alias {1} because the alias is disabled: {2}

FAC+"."+PRODUCER_RETRY_NOTRUN_DISCONNECTED – Producer Retry not attempted for destination {0} alias {1} because the connection is closed: {2}

FAC+"."+PRODUCER_RETRY_NOTRUN_SHUTDOWN – Producer Retry not attempted for destination {0} alias {1} because the server is shutting down: {2}

FAC+"."+PRODUCER_RETRY_STARTED – Attempting Producer Retry for destination {0} alias {1}. Max Retry Attempts: {2}, Retry Interval: {3}, Error: {4}

FAC+"."+PRODUCER_RETRY_SUCCESS – Producer Retry for destination {0} alias {1} was successful after {2} attempt(s).

FAC+"."+REGISTER_TRIGGER_FOR_HOT_DEPLOYMENT – Registering trigger {0} for updates on Hot Deployment of dependent package

FAC+"."+RESUMING_TRIGGER_ON_HOT_DEPLOYMENT_CANCEL – Resuming trigger {0} as the Hot Deployment of dependent package ended

FAC+"."+RESUMING_TRIGGER_ON_HOT_DEPLOYMENT_END – Resuming trigger {0} as the Hot Deployment of dependent package ended

FAC+"."+SUSPENDING_TRIGGER_ON_HOT_DEPLOYMENT_START – Suspending trigger {0} as the dependent package is under Hot Deployment

FAC+"."+UNABLE_TO_RESTART_TRIGGER – Unable to re-start JMS Trigger {0}: {1}

FAC+"."+UNABLE_TO_START_TRIGGER_FIRST_TIME – Unable to start JMS Trigger {0}: {1}

FAC+"."+UN_REGISTER_TRIGGER_FOR_HOT_DEPLOYMENT – Unregistering trigger {0} for updates on Hot Deployment of dependent package

FAC_LISTENER+ALIS3300 – MSGPREFIX_LISTENER+"Unable to handle the state change event of the listener {0} acrosss the cluster"

Explanation An error occurred while processing a state change event for a listener in the cluster.

Action Check the details for the error in the Integration Server error log.

FAC_LISTENER+ALIS3311 – MSGPREFIX_LISTENER+"The cluster event can't be acted upon since the listener {0} is not present"

Explanation The error occurs when a listener is not available on a cluster node because of incorrect cluster setup. The correct cluster setup requires copying the same package on all cluster nodes.

Action Check if the package containing the listener is loaded properly. Verify if the WmART package dependency is set properly.

FAC_LISTENER+ALIS3312 – MSGPREFIX_LISTENER+"unable to activate the listener {0}. "

Explanation When a listener becomes disabled on an active node, another node becomes active. The system returns the exception if an unexpected error occurs during that process.

Action Check the error log and try enabling the listener manually later on the node on which the failure occurred.

FAC_LISTENER+ALIS3313 – MSGPREFIX_LISTENER+"Unable to perform the listener failover since the listener node {0} is not available."

Explanation The error occurs during failover handling of a node when the active node is down, if the corresponding listener node is not available.

Action Check whether the package with the corresponding listener node is enabled and active. If not, try enabling the package.

FAC_LISTENER+ALIS3314 – MSGPREFIX_LISTENER+"Unable to perform the listener failover due to an error while accessing the listener state cache."

Explanation This error occurs during failover handling of a node when the active node is down, if the listener state is not accessible from the Terracotta cache.

Action If all nodes throw the same exception, try enabling the listener manually on any of the nodes.

FAC_LISTENER+ALIS3315 – MSGPREFIX_LISTENER+"Unable to synchronize the listener {0} across the cluster since the shared cache isn't available."

Explanation In a clustered environment, shared cache is used to synchronize the state of the listeners. The error occurs when the shared cache is not available.

Action Check the connection of the shared cache server to the specified Integration Server node.

FAC_NOTIFICATION+ANOT3132 – MSGPREFIX_NOTIFICATION+"Unable to set Publish Event status. Missing parameter: {0}"

Explanation The Notification name input parameter is missing.

Action Specify the notification name for which you want to set the Publish Event status.

FAC_NOTIFICATION+ANOT3133 – MSGPREFIX_NOTIFICATION+"Unable to set Publish Event status. Notification not found: {0}"

Explanation The specified notification does not exist.

Action Check if the notification with the specified name exists in the system.

FAC_NOTIFICATION+ANOT3136 – MSGPREFIX_NOTIFICATION+"Notification 'Disable' request is not initiated by any user explicitly."

Explanation The polling notification is not disabled explicitly by any user. It was disabled automatically due to an error.

Action Check the stack trace in the error log to find out the point at which the notification 'disable' operation was triggered.

FAILURE_INSTANCE_NOT_EXCEPTION – FlowExit "{0}" -- failure instance object is not an Exception

FAILURE_INVALID_BRANCH_CHILD – Invalid child of FlowBranch "{0}"

FAILURE_NOT_FOUND_OR_INVALID – FlowExit "{0}" -- class for specified failure not found or invalid

FASHHASH_NOSUCHELEMENT – FastHashEnumerator

FFP.0001.9001E **Child at index [{0}] is cannot be added to this row.**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9002E **Cannot add child**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9003E **Cannot add child**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9004E	**Cannot put a record inside another record**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9005E	**Cannot add unknown type to a record**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9006E	**Fields cannot have children**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9007E	**Composites cannot contain composites**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9008E	**Cannot add record to a composite**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9009E **Cannot add unknown type to a composite**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9010E **Cannot add child**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9011E **Cannot add children to detail view**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9012E **Cannot add children to detail view**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9013E **Cannot add child of type: {0}**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9014E	**The first child of the Record Usage must be the Record Definition**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9015E	**Cannot set the children of a usage node. The only child is the used node definition**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9016E	**Node is not editable**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9017E	**Cannot modify the children of a reference**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9018E	**Cannot add child. Child must be of type: {0}**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9019E	**Cannot add node, node with name {0} already exists**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9020E	**Cannot edit a broken link**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9021E	**Server cannot be null**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0018.0001	**The mark method is not supported by the supplied InputStream.**

FFP.0018.0002	**The reset method is not supported by the supplied InputStream.**

FFP.0018.0003	**`{0}` must be greater than zero (0).**

FFP.0018.0004	**`{0}` is required and must be greater than zero (0).**

FFP.0018.0005	**`{0}` is required and must be greater than one (1).**

FFP.0018.0006	**`{0}` is required and must be zero (0) or greater.**

FFP.0018.0007	**If `{0}` is supplied, it must be zero (0) or greater.**
FFP.0018.0008	**`offset` + `length` cannot exceed the size of `buffer`.**
FFP.0018.0009	**Input parameter ffData cannot be null.**
FFP.0018.0010	**Cannot process ffData of type: {0}.**
FFP.0018.0011	**Could not find flat file Schema: {0}.**
FFP.0018.0012	**Not validating, not keeping results, invalid settings.**
FFP.0018.0013	**Encoding not supported: {0}.**
FFP.0018.0014	**Name and package are required.**
FFP.0018.0015	**Could not find dictionary: {0}.**
FFP.0018.0016	**Flat File Schema name must be specified.**
FFP.0018.0017	**No input signature presented.**
FFP.0018.0018	**Document Type `{0}` already exists. Please delete it before re-creating.**
FFP.0018.0019	**Value specified for maxErrors must be an integer. Value specified: `{0}`.**
FFP.0018.0020	**Could not find record definition `{0}` in dictionary {1}.**

FFP.0018.0021 **Could not find composite definition `{0}` in dictionary {1}.**

FFP.0018.0022 **Could not find field definition `{0}` in dictionary {1}.**

FFP.0018.0023 **Please specify a valid value for entryType.**

FFP.0018.0024 **{0} is not a flat file dictionary.**

FFP.0018.0025 **{0} is not a flat file schema.**

FFP.0018.0026 **Could not find root tag <FFSchmea>**

FFP.0018.0027 **Could not find a valid value for input parameter `EntryType`**

FFP.0018.0028 **Could not find root tag <FFDictionary>**

FFP.0018.0029 **Flat file dictionary {0} already exists in package {1}, cannot create it in package {2}.**

FFP.0018.0030 **Flat file schema {0} already exists in package {1}, cannot create it in package {2}.**

FFP.0018.0031 **Values are required for input parameters `FFDictionaryName` and `PackageName`.**

FFP.0018.0032 **Could not find entry `{0}` in dictionary `{1}`.**

FFP.0018.0033 **Could not find record entry `{0}`, in dictionary `{1}`.**

FFP.0018.0034 **Could not find composite entry `{0}` in dictionary `{1}`.**

FFP.0018.0035	**Could not find field entry `{0}` in dictionary `{1}`.**
FFP.0018.0036	**Document Type name `{0}` is not valid**
FFP.0018.0037	**The following input parameters are required:{0}**
FFP.0018.0038	**Cannot create document type. Referenced {0} {1} in flat file dictionary {2} could not be found**
FFP.0018.0042	**Please specify a value for name**
FFP.0018.0043	**Could not find {0}**
FFP.0018.0044	**Specified value {0} must be a flat file dictionary or flat file schema.**
FFP.0018.0045	**Could not find package: {0}**
FFP.0018.0046	**Package {0}, is not enabled. Please enable the package, or specify a different package**
FFP.0018.0047	**{0} was saved with the following warning(s):**
FFP.0018.0048	**{0} was saved with the following error(s):**
FFP.0018.0049	**{0} is not a flat file dictionary.**
FFP.0018.0052	**Cannot encode the delimiter character `{0}` (U+{1}) using specified encoding: {2}}. Please select a different delimiter character.**

FOUND_DUP_RECORD_NAME_UM – Cannot create field ''{0}'' in publishable document type ''{1}''; field with duplicate names are not permitted with protocol buffer encoding.

FPL.0001.0000E **Error processing Cleanup service: {0}**

Explanation An error occurred during the execution of the user-specified cleanup service.

Action Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written, cleanup service, which is identified in the message.

FPL.0001.0001E **Listener key not provided. Cleanup service not running**

Explanation Internal Error

Action Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FPL.0001.0002E **Cleanup service access denied. User {0} not allowed to run service {1}**

Explanation The user specified in the message attempted to run the service specified in the message, but the user does not have the privileges required to run the service.

Action Modify the "Run services as user" parameter on the file polling listener configuration page to specify a user that has the appropriate privileges. Make certain that the user you specify has the permissions to execute the processing service.

FPL.0001.0003E **Error processing service: {0}**

Explanation An error occurred during the execution of the user-specified cleanup service.

Action Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.

FPL.0001.0004E **Could not delete file: {0} - {1}**

Explanation An error occurred while attempting to delete the specified file.

Action Check the file system to determine why the specified file has not been deleted. It might be necessary to delete the file manually.

FPL.0001.0012E **Could not move source file {0} to working directory {1}**

Explanation The system was unable to move the file from the monitoring directory to the working directory.

Action On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.

FPL.0001.0013E	**Error processing monitoring file. {0}.**
Explanation	An error occurred during the execution of the user-specified processing service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.

FPL.0001.0014E	**Error processing cleanup. {0}.**
Explanation	An error occurred during the execution of the user-specified cleanup service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.

FPL.0001.0020E	**Could not get canonical path for monitoring directory: {0} - {1}**
Explanation	The system could not obtain the canonical path for the monitoring directory, which is identified in the message. The message also displays the reason.
Action	Take the appropriate action based on the reason for the error shown in the message.

FPL.0001.0030E	**Error processing file: {0}**
Explanation	An error occurred during the execution of the user-specified processing service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.

FPL.0001.0031E	**Listener key not provided. File polling listener not running**
Explanation	Internal Error
Action	Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FPL.0001.0032E	**File polling processing service access denied. User {0} not allowed to run service {1}**
Explanation	The specified user does not have privileges to run the specified service.
Action	Modify the "Run services as user" parameter in the file polling listener configuration page to specify a user that has the appropriate privileges. Make certain that the user you specify has the permissions to execute the processing service.

FPL.0001.0033E	**Error processing service: {0}**
Explanation	An error occurred during the execution of the user-specified processing service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.

FPL.0001.0034E	**Could not move file to finished directory. {0}**
Explanation	The system was unable to move the file from the working directory to the finished directory.
Action	On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.

FPL.0001.0035	**File polling processing service indicated error - [{0}]**
Explanation	The processing service flagged an error to indicate there is an error.
Action	No action is required.

FPL.0001.0036	**File polling processing file: {0}**
Explanation	The indicated file is being processed.
Action	No action is required.

FPL.0001.0037E	**Could not rename file {0} to {1}.**
Explanation	The system was unable to move the file from the monitoring directory to the working directory.
Action	On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.

FPL.0002.0001E **Invalid processing service: {0}**

Explanation The specified processing service does not exist.

Action Specify a service name that exists on the Integration Server.

FPL.0002.0002 **No such service: {0}**

FPL.0002.0003E **Unknown content type: {0}**

Explanation No content handler is defined for the given content type.

Action Specify a content type for which a content handler has been defined or define a content handler for the specified content type. For more details, see the Javadoc for the class com.wm.app.b2b.server.ServerAPI.

FPL.0002.0004E **Server Error: {0}**

Explanation This is an internal error.

Action Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FPL.0002.0005E **Invalid Cleanup service: {0}**

Explanation The specified processing service does not exist.

Action Specify a service name that exists on the Integration Server.

FPL.0003.0001E **Must provide Monitoring Directory**

Explanation No monitor directory was specified.

Action Specify a monitor directory.

FPL.0003.0004E **Monitoring Directory does not exist**

Explanation The monitoring directory does not exist.

Action Create the monitoring directory.

FPL.0003.0005E **Working Directory does not exist**

Explanation The working directory does not exist.

Action Create the working directory.

FPL.0003.0006E	**Must provide User Name**
Explanation	The user did not specify a value for the input "Run services as user".
Action	Specify a user to run the service as.

FPL.0003.0007E	**Must provide Processing service**
Explanation	The processing service was not specified.
Action	Specify a processing service.

FPL.0003.0008E	**Invalid processing service {0}**
Explanation	The specified processing service does not exist.
Action	Specify a service name that exists on the webMethods Integration Server.

FPL.0003.0009E	**Monitor Directory {0} does not exist**
Explanation	The monitor directory does not exist.
Action	Create the monitor directory.

FPL.0003.0010E	**Completion Directory does not exist or can not be created**
Explanation	The completion directory does not exist or cannot be created.
Action	Determine whether the server has permissions to create the indicated directory, or create the directory manually.

FPL.0003.0011E	**Error Directory does not exist or can not be created**
Explanation	The error directory does not exist or cannot be created.
Action	Determine whether the server has permissions to create the indicated directory, or create the directory manually.

FPL.0003.0012E	**Invalid Cleanup service {0}**
Explanation	The specified clean up service does not exist.
Action	Specify a clean up service that exists on the webMethods Integration Server.

FPL.0003.0013E	**Invalid Working Directory**
Explanation	The specified working directory is the same as either the monitoring directory or the completion directory.
Action	Specify a working directory that is not the same as the completion or monitoring directories.

FPL.0003.0015E	**Invalid Error Directory**
Explanation	The specified error directory is the same as either the monitoring directory or the completion directory.
Action	Specify an error directory that is not the same as the completion or monitoring directories.

FPP.0100.0001	**No condition string definied for the conditional validator.**
FPP.0100.0004	**Internal Error: Unable to handle type: {0}.**
FPP.0100.0005	**Unable to handle recordIdentifier of type: {0}.**
FPP.0100.0006	**Code list validatior contained no valid choices**
FPP.0100.0007	**Composite does not contain any subfields.**
FPP.0100.0008	**Cannot contain both a definition and a reference.**
FPP.0100.0009	**A <RecordElement> tag cannot have both a <CompositeUsage> and a <FieldUsage> tag**
FPP.0100.0010	**A field can only have one validator**
FPP.0100.0011	**A field can only have one extractor**
FPP.0100.0012	**Too many record parsers defined. A <RecordParser> tag can only contain one record parser.**
FPP.0100.0013	**Too many record identifiers defined. A <RecordIdentifier> tag can only contain one record identifier.**

FPP.0100.0014	**Flat file schema must have a record identifier defined.**
FPP.0100.0015	**Flat file schema must have a record parser defined.**
FPP.0100.0016	**Value {0} must be integer greater than or equal to zero.**
FPP.0100.0017	**<MaxOccur> value must be either "Unlimited" or a positive integer greater than zero. `{0}` is not a valid value.**
FPP.0100.0018	**<Position> value must be either "NoPosition" or an integer. `{0}` is not a valid value.**
FPP.0100.0019	**<Area> must be either "NoArea" or a positive integer greader than zero. `{0}` is not a valid value.**
FPP.0100.0020	**Value {0} must be integer greater than or equal to one.**
FPP.0100.0021	**Either <{0}> or <{1}> is required.**
FPP.0100.0022	**The end position ({1}) must be greater than the start position ({0}).**
FPP.0100.0023	**The flat file schema has no records defined.**
FPP.0100.0024	**This element contains a reference to the flat file dictionary {0}, which does not exist**
FPP.0100.0025	**The {0} entry called {1} in flat file dictionary {2} in package {3} could not be found**
FPP.0100.0026	**Record has no fields or composites defined**
FPP.0100.0027	**Must have a record delimiter defined when using delimited record parser**

FPP.0100.0028 **Must have a field delimiter defined when using Nth field extractors**

FPP.0100.0029 **Must have a subfield delimiter defined when using composite extractors**

FPP.0100.0030 **Element has no extractor defined**

FPU.0002.0001 **Unable to load resource bundle: {0}**

FTP_CMD_ERR **Command {0} failed**

HTTP_RESPONSE_HEADER_MISSING – Required HTTP Response Headers missing from response.

IDLE_TIMEOUT_SHOULD_BE_GT_ASYNC_WRITE_TIMEOUT – Idle timeout {0} should be greater than async write timeout of {1}

IMPROPER_URI_AND_XMLOBJECTID – The uri provided must be #{0} as [#idXmlObject] for an enveloping signature.

INCORRECT_SIGNATURE_TYPE – The signature cannot be both enveloped and detached.

INIT_XASTORE_NULL The XA store could not be initialized.

INVALID_ALLOW_HOSTNAME – Invalid character/s found in host name, {0}, in IP Access Allow list.

INVALID_CARDINALITY – Invalid range "{0}" specified for cardinality.

INVALID_COPY_MODE Invalid Copy Mode "{0}".

INVALID_DATA_RANGE Select a date range of up to 30 days and then try again.

INVALID_DES_TRIGGER_DUP_DETECTION – DES triggers do not support the duplicate document detection feature in this release.

INVALID_DES_TRIGGER_MULTI_DEST – DES triggers cannot specify more than one condition or more than one document type within a condition.

INVALID_DES_TRIGGER_SERIAL – DES triggers do not support serial processing mode in this release.

INVALID_EXIT FlowExit "{0}" -- invalid exit from try, catch, or finally

INVALID_FIELD_NAME_UM – Cannot create field "{0}" in publishable document type "{1}"; this field name is not valid for use with protocol buffer encoding. The Universal Messaging provider will transport the field contents, which will be visible to Integration Server clients only.

INVALID_FOR_EACH_COPY_PATH – Invalid Copy inside For Each.

INVALID_IDLE_TIMEOUT – Invalid value for idle timeout={0}

INVALID_INPUT_INT Incorrect Input

INVALID_INPUT_INT...0 – Incorrect Input : "{0}" and "{1}" must be valid int types

INVALID_INPUT_LONG Incorrect Input: "{0}" and "{1}" must be valid long types

INVALID_INPUT_STRING – Incorrect Input : "{0}" and "{1}" must be valid String types

INVALID_JOIN_TYPE Invalid Join type

INVALID_KEYSTORE_ALIAS – {0} alias is invalid. Only letters, numbers and underscores are allowed

INVALID_KEYSTORE_LOCATION – Location ({0}) does not exists

INVALID_KEYSTORE_PROVIDER – {0} is not a registered security provider

INVALID_KEYSTORE_TYPE – {0} is not a supported Keystore type

INVALID_KEY_SPECIFIED – Invalid keyStore {0} specified

INVALID_MAX_BINARY_MESSAGE_SIZE – Invalid value for maximum binary message size {0}, should be greater than -1

INVALID_MAX_TEXT_MESSAGE_SIZE – Invalid value for maximum text message size {0}, should be greater than -1

INVALID_TRIGGER_MIXED_ALIASES – webMethods Messaging trigger {0} is invalid. All document types in the trigger must use the same alias.

INVALID_XML_CHARACTER – The character {0} is not allowed in XML.

INVOKE_IFCNAME_MISSING – Service interface name required.

INVOKE_SVCNAME_MISSING – Service name required.

IS.0088.9446E	**Access denied to use the web service endpoint alias {0}.**
Explanation	User does not have permission to use the specified web service endpoint alias.
Action	Using the Integration Server Administrator, examine the Execute ACL property of the web service endpoint alias. Make sure that the current user has the proper ACL to use the web service endpoint alias.

ISC.0006.0004S	**Error in SSL setup: {0}**
Explanation	The server cannot configure SSL listener or SSL Sockets connections, most likely because of a problem with the SSL configuration settings.
Action	Review the exception message in the log and correct the configuration.

ISC.0006.0006I	**SSL listener restricted to 128 bit or better encryption.**
Explanation	Integration Server configuration properties watt.net.ssl.client.strongcipheronly or watt.net.ssl.server.strongcipheronly or both are set to "true".
Action	No action is necessary. This message indicates that Integration Server is using strong encryption.

ISC.0006.0013E	**Peer certificate chain is not present**
Explanation	Integration Server cannot retrieve the peer certificate chain from a client.
Action	Update your client program so that it provides a valid peer certificate to Integration Server.

ISC.0006.0014E	**SSL handshake failed on port {0} because peer certificate is not in IS Certificate Map, transfer is terminated**
Explanation	While trying to connect to Integration Server, a client presented a certificate that is not contained in the store of client certificates that are mapped to Integration Server users.
Action	To import the client certificate to Integration Server and map it to a valid user, go to the Integration Server Administrator and click Security>Certificates>Configure Client Certificates. For additional information about certificate mapping, refer to the webMethods Integration Server documentation.

ISC.0006.0015E	**Peer certificate chain is not trusted**
Explanation	While trying to connect to Integration Server, a client presented a certificate that is not trusted by Integration Server.
Action	Add the certificate to the trusted certificates directory for Integration Server. The name of this directory is specified on the Integration Server Administrator under Security>Certificates. For more information about trusted certificates, refer to the webMethods Integration Server documentation.

ISC.0006.0016E	**SSL handshake failed on port {0}, transfer is terminated**
Explanation	An IOException occurred during the SSL handshake portion of a client's attempt to connect to Integration Server at the indicated port.
Action	Check the server log and error log for possible causes for the error.

ISC.0006.0017S	**Error in adding trusted certificates: {0}**
Explanation	The Integration Server failed to add the specified CA certificate because it is not in the correct format. The CA certificate must be DER or PEM encoded.
Action	Check the certificate format. Configure CA certificates in DER or PEM format.

ISC.0006.0018S	**Error in initializing certificate chain verifier: {0}**
Explanation	An error occurred when Integration Server initialized the certificate chain verifier while setting up the specified secure listener.
Action	Check the server log and error log to determine the cause of the error.

ISC.0006.0019W	**Not including Cipher {0} because it is not a strong Cipher.**
Explanation	Integration Server generates this warning when either the watt.net.ssl.server.strongcipheronly or watt.net.ssl.client.strongcipheronly property is set to "true", and if any of the ciphers identified in either the watt.net.ssl.client.cipherSuiteList or watt.net.ssl.server.cipherSuiteList property are weak.
Action	To stop receiving this warning, remove the specified cipher from the watt.net.ssl.server.cipherSuiteList or watt.net.ssl.client.cipherSuiteList property.

ISC.0006.0020W	**Cipher ({0}) is not a valid CipherSuiteList.**
Explanation	A CipherSuite specified as a value to either the watt.net.ssl.client.cipherSuiteList or watt.net.ssl.server.cipherSuiteList property is not valid. The invalid CipherSuite is shown in the log message. One of the ChiperSuite that is specified as a value to either watt.net.ssl.client.cipherSuiteList or watt.net.ssl.server.cipherSuiteList property is not a valid CipherSuite. The invalid CipherSuite is shown in the log message.
Action	Remove the invalid CipherSuite.

ISC.0009.0012E	**Failed to create certificate: {0}**
Explanation	The certificate specified in the Configure Client Certificates settings has a bad X509Certificate format.
Action	Make sure that the .der file specified in Configure Client Certificates settings is valid.

ISC.0009.0014E	**A certificate with the same issuer, serial number and usage is already mapped to user {0}.**
Explanation	For a given usage type, only one user can be mapped to a certificate with the same issuer and serial number.
Action	To reassign this certificate to different user, edit the previously mapped certificate and change the user.

ISC.0009.0015E	**The certificate is already mapped to user {0}.**
Explanation	Integration Server failed to map the client certificate to the user because the client certificate is already mapped to the user specified.
Action	To reassign this certificate to different user, edit the previously mapped certificate and change the user.

ISC.0009.0016E	**The ISInternal functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.**
Explanation	Integration Server failed to initilize client certificate mappings because it could not access the ISInternal JDBC Pool.
Action	Assign a valid database pool to ISInternal JDBC funtional alias and restart the Integration Server.

ISC.0009.0017W	**Certification chain trust verification failed.**
Explanation	At least one of the certificates present in the certificate chain is not trusted by Integration Server.
Action	Check the certificate chain presented to Integration Server for trust verification.

ISC.0009.9001E	**Certificate chain broken: not linked properly**
Explanation	The certificate chain is out of order.
Action	Obtain a valid certificate chain.

ISC.0009.9003E	**Certificate contains an unsupported critical extension**
Explanation	When watt.security.cert.wmChainVerifier.enforceExtensionsChecks property is set to "true", Integration Server checks the presented certificate for unsupported critical extentions. If Integration Server finds a certificate containing unsupported critical extensions, it will reject the certificate and fail the request.
Action	If you enabled Integration Server to perform a certificate extentions check, advise your cleints to use certificates that do not contain unsupported critical extentions. Whether Integration Server enforces a certificate check is configured on the watt.security.cert.wmChainVerifier.enforceExtensionsChecks configuration property.

ISC.0009.9004E	**Certificate issued to {0} has expired**
Explanation	Unless configured to ignore expired certificates, Integration Server will reject any expired certificates. Whether Integration Server ignores expired certificates is configured on the watt.security.ssl.ignoreExpiredChains configuration property.
Action	Review the server log to see which client's certificate has expired. That client should renew their certificates and resubmit the request with the valid certificate.

ISC.0009.9102E	**User does not exist for certificate : {0}.**
Explanation	The user associated with the imported client certificate in Integration Server has been deleted.
Action	Ensure that all imported client certificates in Integration Server are associated with a user. If you have deleted the user associated with a client certificate, you can take one of the following actions: 1) Modify the certificate mapping using Security > Certificates > Client Certificates > Details > Change Mapping in the Integration Server Administrator. 2) Add a user with the same name as the deleted user that was associated with the imported client certificate.

ISC.0012.0040E	**OSGi service for SAML authentication not initialized.**
Explanation	There was a problem while attempting to access Integration Server from the Command Central user interface.
Action	Check the logs located in the Software_AG_directory/profiles/IS/logs directory and make sure that no errors were encountered during the initialization of the OSGi service specified in the error message.

ISC.0012.0041E	**Unable to initialize SAML authentication module. Cannot get reference of the OSGi service {0}.**
Explanation	There was a problem while attempting to access Integration Server from the Command Central user interface.
Action	Check the logs located in the Software_AG_directory/profiles/IS/logs directory and make sure that no errors were encountered during the initialization of the OSGi service specified in the error message.

ISC.0012.0042E	**Error while adding Integration Live user: {0}. Error message: {1}. Stack trace: {2}**
Explanation	An unexpected error occurred while adding an Integration Live user.
Action	Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ISC.0012.0044E	**Unable to get SAML assertion from REST URL {0} because of exception: {1}**
Explanation	An error occurred while retrieving the SAML assertion from REST URL. Refer to the error message text for more details.
Action	Verify the REST URL and ensure that the REST service exists to generate SAML assertion.

ISC.0018.0001U	**Unable to read MIME types file**
Explanation	During startup, Integration Server was unable to read the MIME types from the file "mime.types", which is located on the <IntegrationServer_dir>\lib directory. The most likely reason is that this file is corrupted.
Action	Contact Software AG Global Support for a copy of this file.

ISC.0018.0002	**Deleted group {0} was removed from {1} ACL lists**

ISC.0018.9301E	**Unlocking thread is not owner**

ISC.0018.9401E	**target directory does not exist**
Explanation	Directory specified to make the tar (zip) file does not exist in the file system.
Action	Ensure that the directory exists in the file system.

ISC.0018.9402E	**target is not a directory**
Explanation	Only directories can be zipped. The File name field do not contain the path to a directory.
Action	Ensure that the File name field contains the path to a directory.

ISC.0018.9403E	**extraction target is not a directory**
Explanation	File name specified to extract a tar file is not a directory. A tar file can be extracted only to a directory.
Action	Enter the directory to which the tar file is to be extracted.

ISC.0018.9404E	**field length exceeded: {0} > {1} ({2}**
Explanation	Integration Server encountered an internal error while adding a file to tar file.
Action	Contact Software AG Global Support.

ISC.0018.9405E	**expected {0} bytes but got {1}**
Explanation	While adding a file to a tar archive, the number of bytes added to the archive is less than the actual size of the file.
Action	Contact Software AG Global Support.

ISC.0018.9406E	**No Tar Entry specified**
Explanation	No directory is provided for zipping.
Action	Ensure that a directory is provided for zipping.

ISC.0018.9407E	**data length is greater than entry specification: {0}**
Explanation	Integration Server encountered an internal error while adding a file to the tar file.
Action	Contact Software AG Global Support.

ISC.0037.0001	**Unable to Initialize {0}**

ISC.0037.0002	**Unable to Shutdown {0}**

ISC.0037.0005	**Unable to reset job manager {0}**

ISC.0037.0006	**Unable to reset logfile {0}**

ISC.0037.0007	**Unable to reset logstream {0}**

ISC.0037.0012	**Unable to accept requests**

ISC.0037.9101E	**Guaranteed Delivery Disabled - Please correct error and reinitialize**

ISC.0042.0002E	**Unsupported Encoding: {0}**
Explanation	Integration Server did not recognize the encoding of the document. Therefore, the default encoding will be used.
Action	If Integration Server successfully uses the default encoding, no action is necessary. Otherwise, change the supplied document so that it has a valid encoding.

ISC.0042.9001 **Cannot uniquely identify the root element : Every element may be contained in at least one other element -- Try loading the DTD from a sample XML document having a DOCTYPE declaration.**

ISC.0042.9002 **Cannot uniquely identify the root element : Multiple elements are topmost elements ({0}) -- Try loading the DTD from a sample XML document having a DOCTYPE declaration.**

ISC.0042.9003 **<!ELEMENT {0} {1}> contains the following error at character {2} of the contentspec: {3}**

ISC.0042.9005U **URI {0} not declared at node {1}**

Explanation webMethods Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0042.9006U **Node reference is null**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0042.9007U **Node is not XML**

Explanation The pub.xml:getXMLNodeIterator service failed to execute because the node object supplied was not an XML node.

Action Examine the service input and make sure the "node" parameter represents an XML node, not an HTML node.

ISC.0042.9008U **Moving window mode is only available when iterating over XML nodes**

Explanation The pub.xml:getXMLNodeIterator service failed to execute because the XML node supplied did not represent a whole XML document.

Action Examine the service input and make sure the "node" parameter represents an entire XML document, not an element of an XML document.

ISC.0042.9009U **Moving window mode is not available with SAX parsers**

Explanation The pub.xml:getXMLNodeIterator service failed to execute because the moving window mode is not available with SAX parsers.

Action Switch to the webMethods parser instead of the SAX parser.

ISC.0042.9011U **SAX parsers do not expose enough DTD info; try selecting the expandDTD option**

Explanation The pub.xml:loadXMLNode service failed to execute because it used a SAX parser. Integration Server does not support SAX parsers because they do not expose enough DTD information.

Action Switch to the webMethods parser instead of the SAX parser.

ISC.0042.9012U **First node of region not found in node parameter**

Explanation The pub.web:createRegions service failed to execute because the "regions" parameter did not correctly specify the first node of the region.

Action Examine the service input for the "regions" parameter and check the query specified for identifying the first node. Make sure the query specified will correctly identify the first node.

ISC.0042.9013U **Last node of region not found in node parameter**

Explanation The pub.web:createRegions service failed to execute because the "regions" parameter did not correctly specify the last node of the region.

Action Examine the service input for the "regions" parameter and check the query specified for identifying the ending node. Make sure the query specified will correctly identify the ending node.

ISC.0049.0001 **Branch {0}: child {1} not found, default child not found for switch {2}**

ISC.0049.0002 **Branch {0}: child {1} not found, invoking default child {2}**

ISC.0049.0010 **Loop {0}: in-array {1} is not an array type.**

ISC.0049.0012 **Set: invalid encoding: {0}**

ISC.0049.0013E **Set: {0}**

Explanation While saving or loading a flow service, Integration Server encountered a problem with the base64 encoding of a Map operation.

Action Contact Software AG Global Support.

ISC.0049.0015 **Loop {0}: out-array is not the same length as in-array.**

ISC.0049.0016 **Flow timed-out at {0}**

ISC.0049.0018 **Branch {0}: no expressions evaluated true and no default child found**

ISC.0049.0019 **Branch {0}: no expressions evaluated true, but default child found**

ISC.0049.9001E **FlowExit "{0}" -- no valid ancestor to exit from $loop**

Explanation In a flow service, the Exit operation failed because an ancestor loop was not found.

Action Move the Exit operation to be a child of a Loop or Repeat step. Alternatively, set the exit-on property for the Exit operation to a value other than $loop.

ISC.0049.9002E **get: complex path is not supported**

Explanation A flow service tried to perform a get operation on a complex path, but Integration Server does not support complex path types. This is an internal error.

Action Contact Software AG Global Support.

ISC.0049.9003E **put: complex path is not supported**

Explanation A flow service tried to perform a put operation on a complex path type, but Integration Server does not support complex path types. This is an internal error.

Action Contact Software AG Global Support.

ISC.0049.9004E **delete: complex path is not supported**

Explanation A flow service tried to perform a delete operation on a complex path, but Integration Server does not support complex path types. This is an internal error.

Action Contact Software AG Global Support.

ISC.0049.9005E **Input validation for service "{0}" failed: "{1}"**

Explanation During service execution, Integration Server detected that the contents of the pipeline did not conform to the defined input signature of the service.

Action Ensure that the inputs in the pipeline match the input signature of the flow service, or disable input validation for this service.

ISC.0049.9006E	**Output validation for service ''{0}'' failed: ''{1}''**
Explanation	Upon completion of a service, Integration Server detected that the contents of the pipeline did not conform to the defined output signature .
Action	Ensure that the outputs in the pipeline match the defined output signature or disable output validation for this service.

ISC.0049.9007E	**Failure creating input validator for ''{0}''**
Explanation	During execution of a flow service, Integration Server determined that it could not create an input Validator from the parameters provided.
Action	Contact Software AG Global Support.

ISC.0049.9008E	**Failure creating output validator for ''{0}''**
Explanation	During execution of a Flow service, Integration Server determined that it could not create an output Validator from the parameters provided. This is an internal error.
Action	Contact Software AG Global Support.

ISC.0049.9009E	**Missing required property 'switch' at ''{0}''**
Explanation	The Branch step has no switch property value.
Action	Specify the name of an pipeline object that is to be used as the switch value for the Branch step.

ISC.0049.9010E	**Service ''{2}'' invoking unknown service ''{1}'' at ''{0}''. The service may have been renamed, moved or disabled.**
Explanation	The failing flow service attempted to execute another servcie that could not be located or could not be executed. The most likely cause is that the target service has been removed or renamed.
Action	Determine the new name or location of the target service and modify the failing flow service to correctly identify the target service.

ISC.0049.9011E	**Missing required property 'in-array' at ''{0}''**
Explanation	The Loop step has no input array property.
Action	Specify the name of a pipeline object to use as the input array.

ISC.0049.9012E	**Cannot define 'switch' and use label conditions at** "{0}"
Explanation	Integration Server tried to execute a Branch step, but the Branch properties were specified incorrectly. Specifically, the "evaluate labels" property was set to "true" while the "switch" property specified an expression. This is not a valid combination.
Action	Change the Branch step properties to either specify a switch value and set "evaluate-labels" to false, or do not specify a switch value and set "evaluate-labels" to true.

ISC.0049.9013E	**Timeout at** "{0}"
Explanation	A step in a flow service exceeded its timeout value before returning.
Action	This is desired behavior. Examine the underlying services that did not return in time to determine the cause of the timeout.

ISC.0049.9014E	**Scope** "{0}" **not found or invalid**
Explanation	At run time, Integration Server could not resolve the scope of the pipeline in a flow step. The scope resolved to an object that was not an IData.
Action	Make sure that the path in the scope property resolves to an IData object at run time.

ISC.0049.9015E	**FlowExit** "{0}" **- label not found:** "{1}"
Explanation	In a flow service, the Exit operation failed because it could not locate the label anywhere in the ancestry of the Exit step.
Action	Make sure that an ancestor flow step has a label that matches the one in the Exit step.

ISC.0049.9016E	**Invalid scope path**
Explanation	At run time, Integration Server could not resolve the pipeline scope specified for a flow step because the syntax of the scope property is not valid.
Action	Make sure that the path syntax of the scope property is valid.

ISC.0049.9017E	**(1) Illegal path from:** "{0}"
Explanation	In the pipeline, the map path for the source or destination is empty.
Action	If this error occurs while editing a flow service, save the flow service and then reload it.

ISC.0049.9018E	**The path has been used: {0}**
Explanation	More than one mapping operation is being performed on a pipeline object.
Action	Only one operation may be performed on a pipeline object in a Map step. Remove all but one of the map operations for the pipeline object, or ensure that only one operation is attempted at run time.

ISC.0049.9019I	**More than one copy into the path with different common parent(s).**
Explanation	When mapping data in the pipeline, under a single Map step, you tried to map from documents to two different document fields under a common parent. However, the source documents have different dimensions.
Action	Separate the data mapping into two different Map steps.

ISC.0049.9022E	**Data type does not match the path.**
Explanation	A pipeline mapping operation specifies a target type that does not match the source type at run time.
Action	Ensure that the source type at run time matches the target type specified by the map operation.

ISC.0049.9024E	**Cannot make the copy from: {0} to: {1}**
Explanation	While executing mapping in a flow step, Integration Server determined that it could not copy one field to another because the elements were of incompatible types.
Action	Make sure that the field types are compatible and have the same dimensions.

ISC.0049.9025E	**Invalid source path.**
Explanation	While trying to execute a map between fields, Integration Server determined that no source field was specified.
Action	In the pipeline, make sure that a source field is specified.

ISC.0049.9026E	**Invalid target path.**
Explanation	While trying to execute a map between fields, Integration Server determined that no target path was specified.
Action	In the pipeline, make sure that tha the map specifies a target destination.

ISC.0049.9027E	**Error at {0} - Transformers cannot loop over list elements**
Explanation	A Map step includes a link from an array variable in Pipeline In to a scalar input variable for a transformer.
Action	Do one of the following: - Remove the mapping between the array variable in Pipeline in and the scalar input variable for the transformer. - Change the service invoked by the transformer to accept arrays as data. - Create a flow service in which a LOOP step loops over the array variable. Then, (in the same flow service) invoke the service you originally wanted to use as a transformer, and make that Invoke step a child of the Loop. Finally, insert the resulting flow service as a transformer in the Map step.
ISC.0049.9031E	**Global Variable {0} does not exist.**
Explanation	The global variable that you assigned to a variable in the flow service does not exist in Integration Server.
Action	Ensure that global variable exists in IS, if it does not exist then contact IS Admin to add this Global Variable.
ISC.0050.0002	**Invalid pipeline mapping: Cannot map two pipeline variables into the same field.**
ISC.0050.0003	**Pipeline variable sources have different dimensions.**
ISC.0050.0004	**Copy failed: {0}: to={1}, from={2}**
ISC.0050.0005	**Set failed: {0}: field={1}**
ISC.0050.0007	**Failed size check on path {0}**
ISC.0050.0008	**No valid value objects for path {0}**
ISC.0050.0009	**Data check: data type mismatch**
ISC.0050.0013	**Copy failed: No source data available from {0}**

ISC.0050.0014 **Field {0} incorrectly declared as array type**

ISC.0050.0015 **Incomplete path: null value for {0}**

ISC.0050.0016 **Cannot create object for the class: {0}**

ISC.0050.0017E **Error encoding schema in FlowMap {0}**

Explanation While saving a flow service, Integration Server encountered an error trying to encode the input or output of a Map step.

Action Contact Software AG Global Support.

ISC.0050.0018E **Error decoding schema in FlowMap {0}**

Explanation While loading a flow service, Integration Server encountered an error trying to decode the input or output of a Map step.

Action Contact Software AG Global Support.

ISC.0050.0019 **Copy failed: No source data available: to={0}, from={1}**

ISC.0050.0020 **Copy failed: Cannot create target data: to={0}, from={1}**

ISC.0050.0021 **Copy failed: Cannot support the required class name: to={0}, from={1}**

ISC.0062.0001 **CreateRegions createNsDecls type not supported**

ISC.0062.0002E **CreateRegions createRegions type not supported**

Explanation The pub.web:createRegions service failed to execute because the input provided for the "regions" parameter was not an instance of IData[ ].

Action Examine the service input make sure the "regions" parameter specifies an instance of IData[ ].

ISC.0062.0003U **GenerateQueryString {0} setValues {1}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0062.0004E **GenerateQueryStrings createFields type not supported**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0062.0005E **GenerateQueryStrings createNodeIDs type not supported**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0062.0006E **GenerateQueryStrings the bind failed**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0062.0007U **GetDocAsTable nodeTypeToString: {0} unknown type**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0062.0008 **MakeRules.makeNSRecordFromDTD root of doc:{0} sig:{1}**

ISC.0062.0009 **MakeRules.makeNSRecordFromDTD root of doc:null**

ISC.0062.0010 **MakeRules.findElementDef name {0} not found in DTD:{1}**

ISC.0062.0011E **MakeRules.makeRecord ERROR ConnectParticleName:{0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0062.0012 **MakeRules.generateFlowFromDTD node parameter is null**

ISC.0062.0013 **MakeRules.generateFlowFromDTD no output signature**

ISC.0062.0014E **QueryDocWithIdentity createFields type not supported:{0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0062.0015 **QueryDocWithIdentity createNsDecls type not supported:{0}**

ISC.0062.0016E **queryXMLNode createFields type not supported:{0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0062.0017 **{0} createNsDecls type not supported:{1}**

ISC.0062.0018U **DocumentToXMLString boundNode argument is null**

Explanation The pub.xml:documentToXMLString service failed to execute because the required "document" parameter was missing. This parameter specifies the name of the document to be converted to XML.

Action Examine the service input and make sure it specifies a value for the "document" parameter.

ISC.0062.0019 **ERROR unsupported type:{0} !!!!**

ISC.0062.0022 **Server encountered an unknown error: {0}**

ISC.0062.0032 **Invalid number format: {0}**

ISC.0062.0033 **Illegal parameter value. {0} is too many root elements in boundNode. Number attributes:{1}.**

ISC.0062.0034 **loadXMLNode called client.http pipe: {0}**

ISC.0062.0036 **Invalid port number {2} for {3}**

ISC.0062.0037 **loadXMLNode service encountered unsupported encoding: {0}**

ISC.0062.9001U **boundNode parameter is null**

Explanation The pub.xml:documentToXMLString service failed to execute because the required "document" parameter was missing.

Action Examine the service input and make sure it contains the document to be converted in the form of an IData object.

ISC.0062.9002U **Namespace prefix name "{0}" for uri {1} is not legal XML name**

Explanation The pub.xml:documentToXMLString service failed to execute because it detected illegal characters in the namespace prefix of the document to be converted. Integration Server flags invalid characters in the namespace prefix only if the value for the "enforceLegalXML" parameter is set to "true".

Action To resolve this error, do one of the following:

(1) Set the input for the "enforceLegalXML" parameter to "false". This causes the service to produce an XML fragment.

(2) Make sure the input for the "nsDecls" parameter specifies a namespace prefix that starts with a letter or the underscore "_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "_" characters.

ISC.0062.9003U **Illegal parameter value. {0} is too many root elements in boundNode. Number attributes:{1}**

Explanation The pub.xml:documentToXMLString service failed to execute because the document to be converted contains multiple root elements. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.

Action Examine the service input and make sure the "enforceLegalXML" parameter is set to "false". This will cause the service to produce an XML fragment composed of the multiple elements that were not enclosed within a root element.

ISC.0062.9004U **Attribute name "{0}" is not legal XML name**

Explanation The pub.xml:documentToXMLString service failed to execute because the prefix that designates the keys that contain attributes contains illegal characters. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.

Action To resolve this error, do one of the following:

(1) Set the input for the "enforceLegalXML" parameter to "false" . This will cause the service to produce an XML fragment.

(2) Make sure the input for the "attrPrefix" parameter starts with a letter or underscore "_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "_" characters.

ISC.0062.9005U **Element name "{0}" is not legal XML name**

Explanation The pub.xml:documentToXMLString service failed to execute because the document being converted contains illegal XML tag names. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.

Action To resolve this error, do one of the following:

(1) Set the input for the "enforceLegalXML" parameter to "false". This causes the service to produce an XML fragment.

(2) Make sure the input for the "'document" parameter starts with a letter or underscore "_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "_" characters.

ISC.0062.9006U **Illegal parameter value. Document Type "{0}" not found.**

Explanation The pub.xml:xmlNodeToDocument service failed to execute because the "documentTypeName" was specified, but the document it represents does not exist on the Integration Server namespace.

Action Examine the service input and make sure the "documentTypeName" parameter specifies the fully qualified name of the document type. Remember that namespace element names are case-sensitive.

ISC.0062.9007E **collect parameter must be null when using recordName parameter**

ISC.0062.9008 **MakeArrays parameter must be false when using recordName parameter**

ISC.0062.9009 **Arrays parameter must be null when using recordName parameter**

ISC.0062.9010 **Records parameter must be null when using recordName parameter**

ISC.0062.9012 **Internal error: no record generated by makeNSRecord**

ISC.0062.9013 **Internal error: no NSName generated**

ISC.0062.9014 **MakeRules.recursiveCollectRecordRefs found nested ContentParticleSet**

ISC.0062.9015 **MakeRules.findElementDef no element definitions found**

ISC.0062.9016 **MakeRules.findElementDef name "{0}" not found in DTD**

ISC.0062.9017 **XML node parameter is null**

ISC.0062.9018 **No NSRecord generated for package "{0}" Document Type "{1}"**

ISC.0062.9019 **XML node is null**

ISC.0062.9020 **Document Type "{0}" already exists.**

ISC.0062.9021U **"object" is null**

Explanation The object to be validated does not exist in the pipeline.

Action Link an XML node or document variable to the object variable in Service In.

ISC.0062.9022U	**"{0}" - object does not exist**
Explanation	The document type or schema specified for the "conformsTo" parameter does not exist in the Integration Server namespace.
Action	Change the value of the "conformsTo" parameter to be a document type or schema that exists in the Integration Server namespace.

ISC.0062.9023U	**conformsTo parameter is null**
Explanation	While executing the pub.schema:validatePipeline service, the Integration Server determined that no value was specified for the "conformsTo" property, which is a required parameter. This parameter specifies the IS document or IS schema against which the Integration Server performs validation.
Action	Specify a value for the "conformsTo" parameter that is an IS document type or schema type that exists in the IS namespace.

ISC.0062.9024U	**Integration Server does not support this type of object in validation {0}**
Explanation	The object to be validated is not one of the types supported by validation.
Action	Currently, only XML, pipeline, and document (IData object) validation are supported.

ISC.0062.9025	**collect parameter must be null when using documentTypeName parameter**

ISC.0062.9026	**MakeArrays parameter must be false when using documentTypeName parameter**

ISC.0062.9027	**Arrays parameter must be null when using documentTypeName parameter**

ISC.0062.9028	**Documents parameter must be null when using documentTypeName parameter**

ISC.0062.9029	**The schema domain of the conformsTo object must match the schemaDomain parameter**

ISC.0062.9137E	**When node is an enhanced XML node, queryType must be XQL**
Explanation	The queryType input parameter is set to WQL but the node is an enhanced XML node. Only XQL can be used to query an enhanced XML node.
Action	Set queryType to XQL and rewrite the query to use XQL instead of WQL.

ISC.0063.0006 **Generate Transaction Ids {0}**

ISC.0063.0017 **Retrieve completed job tid={0}**

ISC.0063.0020 **Error (see job log) tid={0}**

ISC.0063.0027 **Error loading tid={0}; skipping ...**

ISC.0063.0036 **Can Still Retry {0}**

ISC.0063.0042 **Job Manager not initialized.**

ISC.0063.0045 **Deregister - already 0**

ISC.0063.0046 **Jobs still active on shutdown**

ISC.0063.0049 **Start for Nonexistent Tid={0}**

ISC.0063.0050 **Job Expired for Tid={0}**

ISC.0063.0052 **Retrieve on Nonexistent Tid={0}**

ISC.0063.0053 **Retrieve on new job**

ISC.0063.0054 **Retrieve on heuristic failure**

ISC.0063.0055 **Retrieve on expired job**

ISC.0063.0056 **Job Timed Out for Tid={0}**

ISC.0063.0058 **Restart for Nonexistent Tid={0}**

ISC.0063.0059 **Restart for Ended Tid={0}**

ISC.0063.0060 **Restart on active Tid={0}**

ISC.0063.0061 **Restart on non-pending Tid={0}**

ISC.0063.0062 **Status for non-existent Tid={0}**

ISC.0063.0063 **ChainedWait for non-existent Tid={0}**

ISC.0063.0064 **Get Remote TID for non-existent Tid={0}**

ISC.0063.0069 **Administrator email is not set.**

ISC.0063.0070 **Administrator email is {0}.**

ISC.0063.0071 **Logfile used:{0}. Jobdir used:{1}.**

ISC.0063.0072 **{0} broke lock for guaranteed job, tid={1}.**

ISC.0063.0073E **The IS Internal database pool is not configured properly. Assign a valid database pool for the "ISInternal" functional alias and restart the Integration Server.**

Explanation The ISInternal functional alias on the Settings > JDBC Pools page in the Integration Server Administrator is not properly configured, or the database it refers to is unavailable.

Action Configure the ISInternal functional alias on the Settings > JDBC Pools page in the Integration Server Administrator and use the "Test" button to verify that it can connect to the database. After configuring the ISInternal functional alias, restart the Integration Server.

ISC.0063.0074 **End for Nonexistent Tid={0}**

ISC.0063.0075 **Failed to obtain repository context : {0}**

ISC.0063.0078 **Unable to accept requests**

ISC.0063.0079 **End: Invalid Transaction Id**

ISC.0063.0080 **Unable to accept requests**

ISC.0063.0084 **Unable to accept requests**

ISC.0063.0086 **Unable to accept requests**

ISC.0063.0090 **No Output Writer specified**

ISC.0063.0098 **Not a custom stream**

ISC.0063.0100 **Not a custom Writer**

ISC.0063.0101 **Don't close user stream**

ISC.0063.0103 **{0} property is invalid. Using default value of {1}.**

ISC.0063.0104 **{0}:{1} did not create remote tid**

ISC.0064.0001E **HttpContext cannot clone self**

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0064.0011W	**Invalid maxRedirects setting {0}**
Explanation	The watt.net.maxRedirects property is not valid. It must be an integer.
Action	Change the value of the watt.net.maxRedirects property to an integer.

ISC.0064.0012E	**Class not found: {0}**
Explanation	Integration Server encountered an internal error because it could not find a class in the namespace.
Action	Contact Software AG Global Support.

ISC.0064.0018E	**Unable to instantiate class: {0}**
Explanation	Integration Server encountered an internal error because it could not instantiate a class in the namespace.
Action	Contact Software AG Global Support.

ISC.0064.0029D	**Could not open Socket connection to proxy={0} Exception:{1}**
Explanation	An exception was encountered while making an FTP connection through a proxy server. See the exception for details.
Action	Check that the FTP proxy you are using is correctly configured on the Settings > Proxy Servers page of Integration Server Administrator.

ISC.0064.0030W	**The {0} property is not a valid integer: {1}.**
Explanation	An invalid value was specified for the property identified in the message. The value for this property must be an integer.
Action	Change the value of the property to an integer.

ISC.0064.0031E	**Unexpected NTLM message sequence. The expected message type is not NTLM Type 1 Message.**
Explanation	The provided NTLM authentication credentials are not valid.
Action	Provide valid NTLM authentication credentials.

ISC.0064.9001E	**Could not connect to ftp server: {0}**
Explanation	FTP server is not accessible.
Action	Ensure that the FTP server and port are valid. If FTP proxy is configured in Integration Server, ensure that the proxy settings are correct.

ISC.0064.9002E	**FTP host name or port number is not specified**
Explanation	FTP hostname cannot be null and port cannot be zero.
Action	Ensure that you provide valid values for FTP host and port fields.

ISC.0064.9003	**Fail to connect to FTP proxy: {0}+ port: {1}**

ISC.0064.9004E	**Fail to connect to FTP server: {0} port: {1}**
Explanation	Integration server is unable to access the FTP server.
Action	Ensure that the FTP host and port fields contain valid values. If FTP host and port fields contain valid values and if Integration Server is still unable to access FTP server, contact Software AG Global Support.

ISC.0064.9005E	**{0}**
Explanation	Credentials of the FTP user are invalid.
Action	Ensure that the FTP user, password, and account fields have correct and valid values. Set the log level of Network Services component (64) to 'trace' to get more details.

ISC.0064.9006E	**{0}**
Explanation	FTP proxy server that you have configured does not support the SITE command.
Action	Check the FTP proxy server configuration to ensure that the FTP proxy server supports the SITE command. Set the log level of Network Services component (64) to 'trace' to get more details.

ISC.0064.9007E	**{0}**
Explanation	FTP proxy server that you have configured does not support the OPEN command.
Action	Check the FTP proxy server configuration to ensure that the FTP proxy server supports the OPEN command. Set the log level of Network Services component (64) to 'trace' to get more details.

ISC.0064.9008E	**FTP PORT command failed**
Explanation	FTP server encountered an error while sending the PORT command.
Action	The following lists the actions you can take: 1. Ensure that the FTP server implements the PORT command. 2. Ensure that the user has the permission to execute the command. 3. If the problem still persists, contact Software AG Global Support. Set the log level of Network Services component (64) to 'trace' to get more details.

ISC.0064.9009E	**Invalid Data Channel**
Explanation	FTP client is not able to create a data port for listening. In FTP Active mode, client creates a port for data connection and FTP server opens a connection to the client data port.
Action	Ensure that the data port specified in the FTP client is available. -OR- Use FTP passive transfer mode. Set the log level of Network Services component (64) to 'trace' to get more details.

ISC.0064.9010E	**{0}**
Explanation	FTP server is not able to connect to the data port of the client. The possible cause for this is that the data port might be blocked by a firewall on the client side.
Action	The following lists the actions you can take: 1. Check whether the client is behind a firewall. If yes, make sure that the firewall allows the connection from the server. 2. Use FTP passive transfer mode. 3. Increase the connection timeout of data port using watt.net.ftpClientDataConnTimeout property.

ISC.0064.9012E	**Socket close err. {0}**
Explanation	FTP server encountered an error while closing the FTP client socket.
Action	Contact Software AG support team.

ISC.0064.9013E	**{0}**
Explanation	FTP server is not accessible.
Action	Contact Software AG support team. Set the log level of Network Services component(64) to trace to get more details.

ISC.0064.9014E	**Content must be of type byte[], String or InputStream**
Explanation	The content type of the data sent to the FTP server is not of type byte array, string, or InputStream.
Action	Make sure that the data sent to the FTP server is of type byte array, string, or InputStream.

ISC.0064.9015E **FTP AUTH command failed with error code {0}**

Explanation An FTP client sent an AUTH command to establish an FTPS connection with the Integration Server, but the command failed with the indicated return code.

Action Check your FTP documentation for the possible causes of the FTP return code. In addition, check the server log and error log for possible causes for the error.

ISC.0064.9016E **FTP AUTH command failed with error {0}**

Explanation An FTP client sent an AUTH command to establish an FTPS connection with the Integration Server, but the command failed.

Action Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.

ISC.0064.9017E **FTP PBSZ command failed with error code {0}**

Explanation An FTP client sent a PBSZ command to establish a secure connection between the client and Integration Server, but the command failed with the indicated return code.

Action Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.

ISC.0064.9018E **FTP PROT command failed with error code {0}**

Explanation An FTP client sent a PROT command to establish a secure connection between the client and Integration Server, but the command failed with the indicated return code.

Action Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.

ISC.0064.9019E **FTP EPRT command failed with error {0}**

Explanation The FTP server returned an error for the EPRT command sent by the Integration Server FTP client.

Action Ensure that the FTP server implements the EPRT command. Ensure that the user has the permission to execute the command. Set the log level of Network Services facility (facility number 64) to 'trace' to get more details. If the problem persists, contact Software AG Global Support.

ISC.0072.0010 **Index {0} out of bounds for key {1}**

ISC.0072.0011 **value missing name. key={0}**

ISC.0072.0014 **LoopToken.evalArray unknown array type:{0}**

ISC.0072.0016 **Exception:{0} executing included template.**

ISC.0072.0017 **IfVarToken.processArgs value:{0} index:{1} ret:{2}**

ISC.0072.9001E **Unknown service: {0}**

Explanation Integration Server encountered an internal error because it could not find a requested service in the namespace.

Action Contact Software AG Global Support.

ISC.0072.9002E **Reporter died from IOException: {0}**

Explanation The Reporter.createTemplateFromFile() class issued an error because it could not read the template from the supplied file.

Action Examine the use of the Reporter class in your application and make sure that the application has proper Read access to the template file.

ISC.0076.0001 **BinCoder decode error creating IData {0}, using {1} instead. Excpt:{2}**

ISC.0076.0002 **BinCoder decode error creating IDataCodable {0}, using {1} instead. Excpt:{2}**

ISC.0076.0003 **BinCoder decode error creating Codable {0}. Excpt:{1}**

ISC.0076.0004 **BinCoder decode error creating as String {0}, s={1}. Excpt:{2}**

ISC.0076.0005E **BinCoder decode error creating Java serialized object. Excpt:{0}**

Explanation The java.io.ObjectInputStream.readObject() service encountered an error while trying to decode a Java serialized object. For a ClassNotFoundException, the most likely cause is that a client performing a remote invoke placed a class definition into the pipeline, but the class definition does not exist on the receiving Integration Server. For an InvalidClassException, the most likely cause is that the class definition on the Integration Server does not match the class definition placed in the pipeline by the client.

Action	Make sure that the originating client and the receiving Integration Server have the same class definitions. For other I/O exceptions, there might be corruption in the input stream; therefore, you should try the request again.

ISC.0076.0006 BinCoder decode error creating array {0}

ISC.0076.0007 XMLCoder decode invalid data type: {0}

ISC.0076.0008E XMLCoder decode exception: {0}

Explanation	Integration Server threw an exception while decoding an IDataXML encoded document.
Action	The document is corrupt. Contact Software AG Global Support.

ISC.0076.0009E RPCBinCoder2 decode error for array class: {0}

Explanation	Integration Server encountered an error while trying to decode an array of remote objects. Class definitions might be out of sync.
Action	Contact Software AG Global Support.

ISC.0076.0010E RPCBinCoder2 decode error for Codable class: {0}

Explanation	Integration Server encountered an error while trying to decode a codable class. Class definitions might be out of synch.
Action	Contact Software AG Global Support.

ISC.0076.0011E RPCBinCoder2 decode error for as_String class: {0}

Explanation	Integration Server encountered an error while trying to decode an object that was encoded as a String.
Action	Contact Software AG Global Support.

ISC.0076.0012E SOAP Encoding Registrar cannot register schema type {0}; schema type already exists.

Explanation	The SOAP Encoding Registrar could not register the indicated schema type. This is a serious internal error.
Action	Contact Software AG Global Support.

ISC.0076.0013E	**SOAP Message Coder cannot encode output data; pipeline does not match output signature**
Explanation	The SOAP message coder could not XML-encode the results of a SOAP remote procedure call because a variable appeared in the pipeline more than once.
Action	Examine the target service to determine why it is not producing output values that match the output signature. Correct the service's signature and/or logic after identifying the source of the problem.

ISC.0076.0014U	**SOAP Message Coder failure; a RuntimeException was thrown in the SOAP Coder**
Explanation	The message coder encountered a serious internal error.
Action	Contact Software AG Global Support.

ISC.0076.0015E	**SOAP Message Coder cannot encode variable {0}; variable does not have a valid XML name**
Explanation	The message coder could not XML-encode the SOAP RPC request or response because the pipeline contained the variable <varName>, whose name is not a valid name for an XML element.
Action	This error often occurs because the variable name contains a colon (:). Change the name of <varName> to one that is also valid as an XML element name (or map <varName> to a new variable, and use that variable as your SOAP RPC input or output parameter).

ISC.0076.0016	**Soap Message Coder warning; unregistered coder for variable {0}, using String**

ISC.0076.0017E	**SOAP Message Coder error; no coder is registered for encoding style {0}**
Explanation	The message coder encountered a serious internal error.
Action	Contact Software AG Global Support.

ISC.0076.0018	**Soap Message Coder warning; unregistered coder for variable {0}, using BasicData**

ISC.0076.0019E	**SOAP Message Coder cannot decode message; encoding style {0} is not a registered style**
Explanation	The message coder could not decode the submitted XML because it does not support the specified encoding style.
Action	Check the incoming XML and verify that the encodingStyle attribute is specified correctly and that it specifies a style that Integration Server supports.

ISC.0076.0020E	**Soap Message Coder warning; invalid HREF found {0}**
Explanation	The message coder could not resolve the href pointing to reference. A null value was produced instead.
Action	Examine the incoming XML and make sure that the specified reference points to an element that exists in the body of the message.

ISC.0076.0021E	**SOAP Message Coder cannot decode message; arrayType attribute value {0} is malformed**
Explanation	The message coder could not decode an XML-encoded array because it cannot understand the value of the "arrayType" attribute.
Action	Check the incoming XML and make sure that the "arrayType" attribute is using the correct syntax. For example, make sure that it is not missing a "[" symbol.

ISC.0076.0022E	**SOAP Message Coder cannot decode message; cannot determine type of element {0}**
Explanation	The message coder could not decode the XML-encoded parameters it has received, because the simple element <elementName> has an unknown data type (for example, xsi:type="myDataType").
Action	Check the incoming XML and make sure the data type has been specified correctly. Also make sure that it is using the correct namespace.

ISC.0076.0023E	**SOAP Message Coder cannot decode message; unable to create array for arrayType attribute value {0}**
Explanation	The message coder could not decode an XML-encoded array because it could not allocate an array of the specified dimensions.
Action	Check the incoming XML and make sure that the arrayType attribute is specified correctly. For example, make sure that it does not specify a negative dimension or an invalid array size (e.g., too many dimensions or dimensions that are unrealistically large). If the array is unusually large or the server is extremely very low on memory, the possibility also exists that this error was the result of an out-of-memory condition.

ISC.0076.0026E	**Broker Coder cannot encode document; the document, document type or both are null values**
Explanation	While attempting to process a document from the Broker, Integration Server determined that the document, the document type, or both are null values. This is an internal error.
Action	Contact Software AG Global Support.

ISC.0076.0027E **Broker Coder cannot encode document; Broker document type name is missing**

Explanation The subscribing Integration Server received a document from the Broker or a publishing Integration Server, but was unable to encode the document because the document type name was missing from the event subscription. There are three possible reasons: (1) the document to be encoded is corrupted (2) the document type is out of sync with the corresponding document type on the Broker (3) an internal error occurred.

Action Examine the document to be encoded and synchronize the document type with the Broker. If the error persists after the synchronization, contact Software AG Global Support.

ISC.0076.0028 **Broker Coder cannot decode document; byte[] is in wire format version {0}. Latest supported format is version {1}**

ISC.0076.0029 **Broker Coder warning; multi-reference with sequence id {0} does not exist; using null value**

ISC.0076.0030E **Broker Coder warning; cannot parse value {0}; using {1} instead**

Explanation Integration Server was not able to parse the document. There are two possible reasons: (1) the document might be corrupted (2) the document type is out of sync with the corresponding document type on the Broker.

Action Examine the document and make sure that it is not corrupted. Also, synchronize the document type with the corresponding Broker document type.

ISC.0076.0031E **Broker Coder warning; cannot create an instance of {0}**

Explanation Integration Server could not create an instance of the indicated class. This is an internal error.

Action Contact Software AG Global Support.

ISC.0076.0032 **Broker Coder cannot decode document; the document, document type or both are null values**

ISC.0076.0033E **Broker Coder cannot decode document; the document does not conform to the document type, {0}**

Explanation The subscribing Integration Server was not able to decode the incoming document from either the Broker or the publishing Integration Server because the document type on the local Integration Server is out of sync with the corresponding document types on the publishing Integration Server and the Broker.

Action Synchronize the publishable document type on the subscribing Integration Server with the corresponding Broker document type.

ISC.0076.0034 **The {0} class loader could not load class {1} while decoding. Trying next classloader.**

ISC.0076.9001U **Unsupported RPC type: {0}**

Explanation Integration Server RPC Bin Coder does not support the version specified in the input stream to be decoded. This is an internal error.

Action Contact Software AG Global Support.

ISC.0076.9002U **incorrect IDataXMLCoder file format: no element 'IDataXMLCoder' found**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0076.9003U **encoding {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0076.9004U **decoding: {0} ex:{1}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0076.9005U **decoding: boolean ex:{0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0076.9006U **decoding: {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0076.9007U **decoding: No null-arg create method in class: {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISC.0076.9008U	**Unsupported RPC type: {0}**
Explanation	Integration Server RPC Bin Coder does not support the version specified in the input stream to be decoded. This is an internal error.
Action	Contact Software AG Global Support.

ISC.0076.9009U	**Root element is null**
Explanation	The flow.xml or node.ndf file is corrupt.
Action	Contact Software AG Global Support.

ISC.0076.9010U	**Sibling root element is null rootTag:{0} localName:{1} root:{2}**
Explanation	The XMLCoder class issued an error because the supplied XML input stream cannot be decoded.
Action	Examine the use of the XMLCoder class in your application and make sure that the XML input stream has the correct format and it only contains supported object types. If the error still occurs, use the setIgnoreInvalid() class to set the flag to false so that XMLCoder ignores the unsupported object type that it decodes.

ISC.0076.9011U	**illegal file format**
Explanation	The service pub.flow:restorePipelineFromFile failed to execute because the file containing the saved pipeline was not encoded with XMLCoder or IDataXMLCoder.
Action	Examine the file containing the saved pipeline and make sure it is not corrupt. If the file was saved using the pub.flow:savePipelineToFile service, and it is not corrupt, contact Software AG Global Support.

ISC.0076.9012E	**Invalid state. JSON input stream does not start with the "{" character.**
Explanation	The input stream does not contain valid JSON content. JSON content must begin with the "{" character.
Action	Add a "{" character to the beginning of the JSON content.

ISC.0076.9013E	**Invalid state. JSON Object in the input stream does not end with "}" character.**
Explanation	The JSON object in the input stream does not contain valid JSON content. The JSON object content must end with the \"}\" character.
Action	Add a \"}\" character to the end of the JSON object.

ISC.0076.9014E	**Invalid state. JSON input stream contains incorrect syntax.**
Explanation	The JSON input stream contains incorrect JSON syntax.
Action	Correct the errors in the JSON input stream.

ISC.0076.9015E	**Invalid state. JSON Object in the input stream does not start with "{" character.**
Explanation	The JSON object in the input stream does not contain valid JSON content. The JSON object content must begin with the "{" character.
Action	Add a "{" character to the beginning of the JSON object in the input stream.

ISC.0076.9016E	**Invalid state. Array in the JSON input stream does not end with "]" character.**
Explanation	The JSON array in the input stream does not contain valid JSON content. The JSON array must end with the "]" character.
Action	Add the "]" character from the end of the JSON array.

ISC.0076.9017E	**Numeric value ({0}) for field {1} is outside the range for integer values. Integers must be within the range of -2147483648 to 2147483647. Error:{2}**
Explanation	Integration Server encountered an invalid integer value while parsing a JSON object.
Action	Correct the value before parsing the JSON object.

ISC.0076.9018E	**Numeric value ({0}) for field {1} is outside the range for long numbers. Long numbers must be within the range of -9223372036854775808 to 9223372036854775807. Error:{2}**
Explanation	Integration Server encountered an invalid long number value while parsing a JSON object.
Action	Correct the value before parsing the JSON object.

ISC.0076.9019E	**Numeric value ({0}) for field {1} is outside the range for float values. Error:{2}**
Explanation	Integration Server encountered an invalid float value while parsing a JSON object.
Action	Correct the value before parsing the JSON object.

ISC.0076.9020E	**Numeric value ({0}) for field {1} is outside of the range for double values. Error:{2}**
Explanation	Integration Server encountered an invalid double value while parsing a JSON object.
Action	Correct the value before parsing the JSON object.

ISC.0076.9101E	**SOAP Encoding Registrar cannot register encoding style {0}; encoding style already exists.**
Explanation	Integration Server cannot register the specified encoding style because the encoding style is already registered.
Action	Contact Software AG Global Support.

ISC.0076.9102E	**SOAP Encoding Registrar cannot register Java type {0}; Java type already exists.**
Explanation	Integration Server cannot register the specified Java type because it already exists in the registry.
Action	Contact Software AG Global Support.

ISC.0076.9103E	**SOAP Encoding Registrar cannot register Schema type {0}; Schema type already exists.**
Explanation	Integration Server cannot register the specified Schema type because it already exists in the registry.
Action	Contact Software AG Global Support.

ISC.0076.9104E	**SOAP Encoding Registrar cannot unregister Java type {0}; doesn't exist in the registry**
Explanation	Integration Server cannot unregister the specified Java type becaues it does not exist in the registry.
Action	Contact Software AG Global Support.

ISC.0076.9105E	**SOAP Encoding Registrar cannot unregister Schema type {0}; doesn't exist in the registry**
Explanation	Integration Server cannot unregister the specified Schema type becaues it does not exist in the registry.
Action	Contact Software AG Global Support.

ISC.0076.9202E	**SOAP Message Coder failure; a RuntimeException was thrown in the SOAP Coder**
Explanation	The SOAP message contains an element that does not have a valid QName.
Action	Make sure the elements in the SOAP message have valid QNames.

ISC.0076.9203E	**SOAP Message Coder cannot decode message; Invalid number {0}**
Explanation	The message coder could not decode an XML-encoded array because one of its dimensions is set to a nonnumeric value.
Action	Check the incoming XML and make sure that the arrayType attribute specifies a positive integer. For example, make sure it has not been inadvertently set to a nonnumeric value such as “A”.

ISC.0076.9204E	**SOAP Message Coder cannot encode output data; pipeline does not match output signature, duplicate variable {0} in pipeline**
Explanation	The message coder could not XML-encode the results of a SOAP remote procedure call because the specified variable appeared in the pipeline more than once.
Action	On the Integration Server, examine the target service to determine why it is not producing output values that match the output signature. Correct the service’s signature and/or logic after identifying the source of the problem.

ISC.0076.9205E	**SOAP Message Coder cannot encode variable {0}; variable does not have a valid XML name**
Explanation	The message coder could not XML-encode the SOAP RPC request or response because the pipeline contained the specified variable, whose name is not a valid name for an XML element.
Action	This error often occurs because the variable name contains a colon (:). Change the name of specified variable to one that is also valid as an XML element name (or map the variable to a new variable, and use the target variable as your SOAP RPC input or output parameter).

ISC.0076.9206E	**SOAP Message Coder error; no coder is registered for encoding style {0}**
Explanation	Integration Server encountered a serious internal error when encoding the SOAP message.
Action	Contact Software AG Global Support.

ISC.0076.9208E	**SOAP Message Coder cannot decode message; cannot determine type of element {0}**
Explanation	The message coder could not decode the XML-encoded parameters it has received, because the specified element has an unknown data type (for example, xsi:type="myDataType").
Action	Check the incoming XML and make sure the data type has been specified correctly. Also make sure that it is using the correct namespace.

ISC.0076.9209E	**SOAP Message Coder cannot decode message; unable to create array for arrayType attribute value {0}**
Explanation	The message coder could not decode an XML-encoded array because it could not allocate an array of the specified dimensions.
Action	Check the incoming XML and make sure that the arrayType attribute is specified correctly. For example, make sure that it does not specify a negative dimension or an invalid array size (e.g., too many dimensions or dimensions that are unrealistically large). If the array is unusually large or the server is extremely very low on memory, the possibility also exists that this error was the result of an out-of-memory condition.

ISC.0076.9210E	**SOAP Message Coder cannot decode message; arrayType attribute value {0} is malformed**
Explanation	The message coder could not decode an XML-encoded array because it cannot understand the value of the arrayType attribute.
Action	Check the incoming XML and make sure that the arrayType attribute is using the correct syntax. For example, make sure that it is not missing a "[" symbol.

ISC.0076.9211E	**SOAP Message Coder cannot encode output data; pipeline does not match output signature, required variable {0} is missing**
Explanation	The message coder could not transform the results of a SOAP remote procedure call because the required variable varName was not in the pipeline.
Action	On Integration Server, examine the target service to determine why it is not producing the required output variables. Correct the service signature and/or logic after identifying the source of the problem.

ISC.0076.9212E	**SOAP Message Coder cannot encode output data; pipeline does not match output signature, extra variable {0} in pipeline**
Explanation	Integration Server encountered an error while processing an RPC/Encoded SOAP message. Either the SOAP message does not match the output signature of the service or the contents of the output pipeline produced by the service do not match the service signature.
Action	Do one or more of the following: - Change the SOAP message response so that it matches the service output signature. - Change the service output signature so that it matches the expected SOAP message response. - Ensure that the service produces an output pipeline that matches the service signature.

ISC.0076.9220E	**{0} Coder: decoding error; illegal input parameter value(s)**
Explanation	One of the input parameters to the encode or decode method is null.
Action	Make sure that the input parameters passed to the encode or decode methods are not null.

ISC.0076.9221E	**{0} Coder: decoding error; can't get the SOAP Body from the SOAP Message**
Explanation	The SOAP body element cannot be retrieved from the SOAP message.
Action	Make sure that the SOAP message is valid and contais a SOAP body element.

ISC.0076.9222E	**{0} Coder: decoding error; can't convert SOAP Message to IS Document**
Explanation	Integration Server cannot convert a SOAP message to a document (IData) because of a decoding error.
Action	Contact Software AG Global Support.

ISC.0076.9230E	**{0} Coder: encoding error; can't create SOAP Message**
Explanation	Integration Server cannot create the SOAP message because an encoding error occurred.
Action	Contact Software AG Global Support.

ISC.0076.9231E	**{0} Coder: encoding error; can't add SOAP Body Element to SOAP Message**
Explanation	Integration Server cannot add the SOAP body element to the SOAP message because of an encoding error.
Action	Contact Software AG Global Support.

ISC.0076.9234E	**{0} Coder: encoding error; can't convert IS Document to XML String**
Explanation	Integration Server cannot convert the document (IData) to an XML String because of an encoding error.
Action	Contact Software AG Global Support.

ISC.0076.9236E	**SOAP Message Coder cannot decode message; value "{0}" doesn't match expected pattern yyyy-MM-dd**
Explanation	The date pattern is invalid.
Action	Make sure that the date value uses the pattern yyyy-MM-dd.

ISC.0077.0001E **Config set local host error. Excpt:{0}**

Explanation During startup, Integration Server was not able to set local host information from the values specified on the "watt.net.localhost" property.

Action Examine the value specified for property "watt.net.localhost". The value can either be a machine host name or a string representing the machine's IP address, such as "localhost" or "127.0.0.1".

ISC.0077.0002 **Unsupported email encoding {0} specified. Defaulting to {1}**

ISC.0077.0003S **Cannot initialize password store with null manager**

Explanation Initialization of the code that manages outbound passwords failed. The most likely cause is a problem with the outbound password configuration files.

Action Make sure that the following outbound password configuration files reside on the Integration Server:

config/txnPassStore.dat

config/empw.dat

config/configPassman.cnf

config/passman.cnf

See the webMethods Integration Server documentation for information about these files and to determine whether you can restore them. If you cannot determine the source of the problem, contact Software AG Global Support.

ISC.0077.0004S **Exception during {0}, type: {1}, msg: {2}**

Explanation A problem occurred when Integration Server tried to store or retrieve an outbound password or retrieve an encryption code from the outbound password store.

Action The outbound password data store, config/txnPassStore.dat, is probably corrupted. See the webMethods Integration Server documentation for information about this file and how to restore it and other outbound password configuration files. If you cannot determine the source of the problem, contact Software AG Global Support.

ISC.0077.0005 **Unable to {0}, password mgr is null**

ISC.0077.0006E	**System property "{0}" equals "{1}". This value is not valid. The default value of "{2}" will be used instead.**
Explanation	Integration Server detected an invalid value on the indicated configuration file property.
Action	Refer to the webMethods Integration Server documentation for a description of the property and its required or allowed values.
ISC.0077.9001	**Stream is already closed**
ISC.0077.9003	**Source directory does not exist**
ISC.0077.9004	**Source File not a directory**
ISC.0077.9006E	**Could not determine encoding of file {0}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0077.9007E	**Invalid encoding, {0}, specified for file {1}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0077.9009	**Local name cannot be null**
ISC.0077.9010	**Local name cannot be an empty string.**
ISC.0077.9011	**Namespace name cannot be an empty string.**
ISC.0077.9012	**Invalid value {0} specified for local name.**
ISC.0077.9013U	**Document to XSD error: Field {0} cannot be represented in XML Schema. The field name contains a prefix but an XML Namespace property is not assigned to the field**
Explanation	The document type being used to generate a WSDL document contains a top-level variable whose name includes a prefix (that is, the name is in the format prefix:local name). This variable is not associated with an XML namespace.
Action	Do one of the following:

(1) Associate the variable with an XML namespace by specifying a value for the variable's XML Namespace property.

(2) Remove the prefix. Note that some protocols require the use of a prefix. Before removing the prefix, check the service signature's input and output requirements as documented for each protocol in the webMethods Integration Server documentation.

ISC.0077.9014U **Document to XSD error: Field {0} cannot be represented in XML Schema. The field name does not conform to the XML NCName definition**

Explanation The document type being used to generate a WSDL document contains field names that do not conform to the XML NCName definition.

Action To resolve this error, rename the fields to conform to the QName lexical rules specified in http://www.w3.org/TR/REC-xml-names/#NT-QName and the XML namespace and local naming conventions specified in http://www.w3.org/TR/REC-xml-names/#NT-NCName.

ISC.0077.9015E **The amount of data needed is greater than the amount of data reserved.**

Explanation A service needed to write a large amount of data to tspace, but the space the service reserved is not large enough to hold the data.

Action Update your program to reserve more tspace. If your program does not reserve tspace directly, contact Software AG Global Support.

ISC.0077.9016 **Provided private key {0} is invalid.**

ISC.0077.9017 **Unable to read the key/certificate file(s) {0}.**

ISC.0077.9018 **Provided certificate(s) {0} is/are invalid.**

ISC.0077.9022E **XOPObject content cannot be read more than once.**

Explanation You attempted to read the contents from an XOPObject. However, previous logic in either the same service or a previous service has already read the XOPObject. The XOPObject instance can only be read one time.

Action Update the service logic so that it reads an XOPObject only one time.

ISC.0077.9023E	**Error while parsing the "{0} {1}" XML string. Parser error: {2}; XML: {3}**
Explanation	One of the reference parameters or metadata elements that you specified as message addressing property is not a valid XML string.
Action	Ensure that the XML string that you specify as message addressing reference parameter or metadata element is correct.

ISC.0077.9024E	**Error while parsing the "{0} {1}" XML string. The XML that you specify should be namespace qualified. XML: {2}**
Explanation	One of the reference parameters that you specified as the message addressing property is not a namespace qualified XML string.
Action	Ensure that the XML string that you specify as message addressing reference parameter element is namespace qualified.

ISC.0081.0002	**Error registering universal name {0}, already registered to {1}**

ISC.0081.0003	**Registered universal name {0} on service {1}**

ISC.0081.0004	**Duplicate universalName {0} registered to a different service {1}, not this service {2}. Unregister failed.**

ISC.0081.0005E	**Could not create a unique ID for the trigger from the trigger's name.**
Explanation	Integration Server was unable to create a unique identifier for the trigger. This is an internal error.
Action	Try to recreate the trigger. If that fails, contact Software AG Global Support. Be prepared to provide logs and the version number and patch level for Integration Server and your operating system.

ISC.0081.9001E	**Node {0} does not exist**
Explanation	The specified element cannot be locked because it does not exist. The element might have already been deleted. Alternatively, another user might have been deleted the element at the same time an attempt to lock the element was made.
Action	Make sure that the element exists.

ISC.0081.9002E	**Cannot perform operation without Write ACL privileges on {0}**
Explanation	The specified element cannot be locked because the user attempting to lock the element does not have write permissions to the element. To lock an element, a user must be a member of the Write ACL assigned to the element.
Action	Make sure that the user has write access to the element before attempting to lock it

ISC.0081.9003E	**Unable to lock: {0}. It has been locked by user {1}.**
Explanation	The specified element cannot be locked because it is already locked by another user.
Action	Before locking an element, make sure it is not locked by another user.

ISC.0081.9004E	**universalName {0} is already registered**
Explanation	The specified universal name already exists and is assigned to another element.
Action	Specify a unique universal name that is not already used by another element.

ISC.0081.9005E	**Unknown content type: {0}**
Explanation	Integration Server cannot create an instance of the specified content type because Integration Server does not recognize or does not support the spedcified content type.
Action	Specify a content type supported by Integration Server.

ISC.0081.9007E	**Node exists**
Explanation	An element with this fully qualified name already exists on the Integration Server. Integration Server uses the following format for the fully qualified name: folder.subfolder1.subfolder2:element
Action	Specify an element name whose fully qualified name will be unique to the Integration Server.

ISC.0081.9008E	**Node '{0}' does not exist**
Explanation	A node (element) in the Integration Server namespace was not specified.
Action	Specify a node (element) in the Integration Server namespace.

ISC.0081.9016E	**Search expression {0} is not well-formed. Enter a valid regular expression or element name.**
Explanation	The regular expression syntax is not valid.
Action	Ensure that specified regular expression is valid and can be complied into a valid pattern.

ISC.0081.9164E	**Exception occurred during generation of WSDL for service {0}: {1}**
Explanation	An error occurred while attempting to validate or generate WSDL for a Web service descriptor. The error text identifies the specific error details.
Action	Use the error details to correct the issue before attempting to save the Web service descriptor or request WSDL for the Web service descriptor.

ISC.0081.9165E	**Invalid WSDL. Attribute {0} must appear in element {1} at Operation: {2}, Binding: {3}**
Explanation	While creating a Web service descriptor from a WSDL document, Integration Server found an invalid WSDL attribute. Most likely it was a soap:fault definition that was missing the name attribute.
Action	Correct the WSDL document before attempting to create the Web service descriptor.

ISC.0081.9166E	**Invalid "use" detected in Operation {0} at Binding {1}**
Explanation	While consuming a WSDL document to create a Web service descriptor, Integration Server encountered an invalid value for the use= attribute. The only valid values for the use attribute are "literal" or "encoded".
Action	Correct the use attribute value in the WSDL document and then attempt to create the Web service descriptor.

ISC.0081.9167E	**Output signature of an RPC/Literal or a Document/Literal operation cannot have top-level fields that are named "*body" or that begin with the "@" symbol. Operation Name : {0}**
Explanation	The output siignature of a service used as an operation in an RPC/Literal binder cannot have top-level fields named "*body" or top-level fields that begin with "@".
Action	Change the output signature of the service before attempting to use the service as an operation in an RPC/Literal binder.

ISC.0081.9169e	**Input signature of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}**
Explanation	A service used as an operation in an RPC/Encoded binder cannot contain fields named "*body" or fields with a name that starts with "@" symbol.
Action	Before using the service as an operation in an RPC/Encoded binder, change the service signature to remove or rename the fields named "*body" or fields with a name that start with "@" symbol.

ISC.0081.9170	**Output signature of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}**
Explanation	The output signature of a service used as an operation for an RPC/Encoded binder cannot contain a field named "*body" or a field with a name that starts with "@ ".
Action	Change the output signature of the service before using the service as an operation in an RPC/Encoded binder.

ISC.0081.9171E	**Request header of an RPC/Encoded operation cannot have fields named named "*body" or that begin with the "@" symbol. Operation Name : {0}, Header : {1}**
Explanation	An attempt was made to add a Request Header to an operation used in an RPC/Encoded binder but the document type being added either has a field named "*body" or a field name starting with" @". Neither is allowed in a Header for an operation in an RPC/Encoded binder.
Action	Remove the fields named "*body" and the fields that start with "a" from the document type. Or use a document type that meets the field name requirements to define the format of the Header.

ISC.0081.9172E	**Response header of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}, Header : {1}**
Explanation	An attempt was made to add a Response Header to an operation in an RPC/Encoded binder but the document type being added either has a field named "*body" or a field name starting with "@". Neither is allowed in a Header for an operation in an RPC/Encoded binder.
Action	Change the document type to meet the field name requirements or use a different document type that meets the requierments to define the format of the Header.

ISC.0081.9173E	**Fault for an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}, Fault : {1}**
Explanation	An attempt was made to add a Fault to an RPC/Encoded operation but the document type being added either has a field named *body or a field name starting with @. Neither is allowed in a Fault for an RPC/Encoded operation.
Action	Edit the document type to remove the fields named *body or those that begin with the "@" symbol and then add the Fault to the RPC/Encoded operation. Or, select a different document type to define the format of the Fault.

ISC.0081.9174E	**Input signature of an RPC/Literal operation cannot have a List field at the top level. Operation Name : {0} Field : {1}**
Explanation	The input signature of a service used as an operation in a RPC/Literal binder contains a List field at the top level. Services used as operations in RPC/Literal binders cannot have List fields at the top level of the service input signature.
Action	Remove the List field from the service input signature before attempting to use the service as an operation in a RPC Literal Binder.

ISC.0081.9175E	**Output signature of an RPC/Literal operation cannot have a List field at the top level. Operation Name : {0} Field : {1}**
Explanation	The output signature of a service used as an operation in an RPC/Literal binder contains a List field at the top level. Services used as operations in RPC/Literal binders cannot have signatures that use List fields at the top level.
Action	Correct the service output signature before attempting to use the service as an operation in a RPC/Literal binder

ISC.0081.9176E	**Input signature of an RPC/Literal or a Document/Literal operation cannot have a String Table field. Operation Name : {0} Field : {1}**
Explanation	A service with a String table in its service signature cannot be used as an operation for an RPC/Literal or Document/Literal binder.
Action	Change the service signature before attempting to use it as an operation in a an RPC/Literal or Document/Literal binder.

ISC.0081.9177E	**Output signature of an RPC/Literal or a Document/Literal operation cannot have a String Table field. Operation Name : {0} Field : {1}**
Explanation	The output signature of a service used as an operation in an RPC/Literal or Document/Literal binder cannot contain a a String table.
Action	Change the servie output signature before attempting to use the service as an operation in an RPC/Literal or Document/Literal binder.

ISC.0081.9178E	**Input signature of an RPC/Literal operation cannot have identically named fields at the top level. Operation Name : {0} Field : {1}**
Explanation	A service used as an operation in a RPC/Literal binder has an input signature containing identically named fileds at the top level. All top-level field names must be unique for services used as operations in an RPC/Literal binder.
Action	Change the service signature before attempting to use the service as an operation in an RPC/Literal binder.

ISC.0081.9179E	**Output signature of an RPC/Literal operation cannot have identically named fields at the top level. Operation Name : {0} Field : {1}**
Explanation	A service used as an operation in an RPC/Literal binder contains fileds with duplicate names at the top level in the output signature. All top-level field names must be unique for operations in RPC/Literal binders.
Action	Change the output signature of the service before attempting to use the service as an operation in an RPC/Literal binder.

ISC.0081.9180E **Unable to find {0}, needed to generate WSDL for operation {1}**

Explanation A service first provider Web service descriptor uses an IS serivce as an operation, but that IS service no longer exists in the Integration Server namespace.

Action Edit the Web service descriptor to use an existing IS service as the operation or recreate the missing IS service.

ISC.0081.9181E **Cannot find document type {0} needed to generate WSDL**

Explanation An internal error has occurred while attempting to validate a Web service descriptor or generate WSDL for the Web service descriptor. The specified document type is used within the definition of the Web service descriptor but it cannot be found in the Integration Server namespace.

Action If the Web service descriptor was created from WSDL document, for example a consumer Web service descriptor a WSDL first provider Web service descriptor, delete the Web service descriptor and recreate it. If the Web service descriptor is a service first provider Web service descriptor, manuallly create the missing document type, or correct the references to the document type from the Web service descriptor (for example update the signatures of service used sa operations, update Header definitions, or update Fault definitions).

ISC.0081.9182E **Invalid WSDL schema generated for the service signatures or the document types referred by the WSD "{0}". To view the generated WSDL change the logging level of Namespace(0081) to Trace. Error details: {1}**

Explanation This is a generic message that Integration Server throws for all Xerces parser errors.

Action If Xerces parser throws "Unique Particle Attribute" error, then a possible workaround for this issue is to set the value of the 'Allow unspecified fields' constraint of the variables in the IS doc type referred by the Web service descriptor to 'False'.

ISC.0081.9194E **The header has a message part "{0}" defined by the type "{1}". Message parts in a header must be defined by the element attribute instead of the type attribute.**

Explanation An attempt was made to set the Pre 8.2 compatibility mode property to false for a Web service descriptor, but the WSDL document used to create the Web service descriptor has Header parts defined using the type attribute. For the Web service descriptor to have the Pre 8.2 compatibility mode property set to false, the Header parts in the WSDL document must use the element attribute.

Action If you want the Web service descriptor to have a Pre 8.2 compatibility mode property set to false, change the Header parts in WSDL document to use the element attribute and then use Designer recreate the Web service descriptor.

ISC.0081.9195E, W	**Invalid message part(s) defined in the wsdl: {0}**
Explanation	An invalid Message Part definition was found while consuming WSDL to create a Web service descriptor. The error message lists the specific error details .
Action	Use the error details in the message to correct the WSDL. Then, use the corrected WSDL document to create the Web service descriptor.

ISC.0081.9197E	**Cannot find SOAP-JMS trigger "{0}" specified in the provider Web service endpoint alias "{1}" assigned to binder "{2}" in the web service descriptor "{3}".**
Explanation	The Web service endpoint alias assigned to the provider Web service descriptor uses a SOAP-JMS trigger that cannot be found. The provider Web service endpoint alias for use with a JMS binder is not valid if the SOAP-JMS trigger specified in the alias cannot be found. The Web service descriptor cannot be saved if a valid Web service endpoint alias is not assigned to a binder that specifies JMS as the transport.
Action	Update the provider Web service endpoint alias to use a different SOAP-JMS trigger. Alternatively, assign a different valid provider Web service endpoint alias to the binder.

ISC.0081.9198E	**Cannot find provider Web service endpoint alias "{0}" assigned to binder "{1}" in the web service descriptor "{2}".**
Explanation	The Web service endpoint alias assigned to the provider Web service descriptor cannot be found. The Web service descriptor cannot be saved if a Web service endpoint alias is not assigned to a binder that specifies JMS as the transport.
Action	Assign a valid provider Web service endpoint alias to the binder.

ISC.0081.9199W	**MEP for operations {0} has changed from In-Only MEP to In-Out MEP. As a result, Integration Server will now execute the corresponding response handlers.**
Explanation	Changing the Pre-8.2 compatibility mode property of the Web service descriptor from false to true resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Out. At run time, Integration Server will execute response handler services for the specified operations.
Action	No action required.

ISC.0081.9200W	**MEP for operations {0} has changed from In-Out MEP to In-Only MEP. As a result, Integration Server will no longer execute the corresponding response handler services.**
Explanation	Because the specified operation has no defined output, changing the Pre-8.2 compatibility mode property of the Web service descriptor from true to false resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Only. At run time, Integration Server will no longer execute the response handler services for the specified operations.
Action	No action required.

ISC.0081.9201W	**MEP for operations {0} has changed from Robust In-Only MEP to In-Out MEP.**
Explanation	Changing the Pre-8.2 compatibility mode property of the Web service descriptor from false to true resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Out.
Action	No action required.

ISC.0081.9203W	**Invoke RefreshConnectors against the Web service descriptor to have the Web service connector''s signature updated to reflect the change to the compatibility mode.**
Explanation	After changing the Pre-8.2 compatibility mode property for a consumer Web service descriptor, the Web service connectors need to be refreshed. If an operation does not have any defined output, refreshing the Web service connectors will update the output signature to reflect the compatibility mode change. If you changed the Pre-8.2 compatibility mode property to false, the Web service connector will no longer have any SOAP message-related output parameters. If you changed the Pre-8.2 compatibility mode property to true, the output signature will include an output parameter for a SOAP fault.
Action	Refresh the Web service connectors for this Web service descriptor.

ISC.0081.9204E	**Web service descriptor {0} is not available because the WS-Policy file with policy ID {1} attached to the WSD is not present in the policy repository.**
Explanation	The Web service descriptor is not available because the WS-Policy file attached to the Web service descriptor is deleted or moved from the policy repository.
Action	The following lists the actions you can take: 1) Ensure that the WS-Policy that is attached to the Web service descriptor resides in the policy repository. -OR- 2) Edit the Web service descriptor so that it no longer uses the deleted or moved WS-Policy file.

ISC.0081.9207E	**Invalid WSDL. wsdl:fault element named {0} must be present in operation {1} of port type {2}**
Explanation	The WSDL document used to create the WSDL first provider or consumer Web service descriptor does not contain wsdl:fault element in the wsd:operation of the portType.
Action	Ensure that the WSDL contains the correct wsdl:fault element in the wsd:operation of the portType. Contact Software AG Global Support for further assistance.

ISC.0082.0001	**Type {0} exists in schema {1}. Set {1} as owner schema.**

ISC.0082.483E	**"fractionDigits"+STR_BASE_FACET_FIXED**
Explanation	The fractionDigits facet is fixed for the type and cannot be changed
Action	Do not attempt to change the fractionDigits value for the type.

ISC.0082.90007E	**Missing Attribute Information Item**
Explanation	The attribute is declared as required but is missing from the instance document.
Action	Correct the instance document.

ISC.0082.9001E	**Error while parsing "{0}"**
Explanation	An unexpected error occurred while valiating the instance document.
Action	Contact Software AG Global Support.

ISC.0082.9002E	**Unable to retrieve root element**
Explanation	The instance document does not have a root element and cannot be validated.
Action	Correct the instance document.

ISC.0082.9003E	**Unable to locate a matching element declaration**
Explanation	The element in the instance document does not have an element declaration.
Action	Correct the instance document. Ensure that the element name is correctly spelled.

ISC.0082.9004E	**[attributes] property must be empty**
Explanation	The element is defined to be of simple type. No attributes may be present.
Action	Remove the attributes from the element in the instance document, or use an element that permits the attribute.

ISC.0082.9005E	**EII (s) are not allowed in [children] property**
Explanation	The element type does not allow child elements to be present in the content.
Action	Remove the child elements from the instance document, or use a type definition that permits the desired child elements.

ISC.0082.9006E	**Unable to locate a matching attribute declaration**
Explanation	Integration Server could not locate an attribute declaration for the attribute.
Action	Correct the instance document to reference an attribute for which there is a declaration or remove the attribute from the instance document.

ISC.0082.9008E	**Invalid value - does not match fixed value**
Explanation	The element declaration has a fixed value. Only that value may be present in the instance document.
Action	Correct the instance document.

ISC.0082.9009E	**Child element {0} at position {1} is unexpected**
Explanation	The instance document contains an element at the specified location that does not match what is expected.
Action	Correct the instance document.

ISC.0082.9010E	**Incomplete content - one or more child elements are expected**
Explanation	The instance element does not contain the expected child elements. Content is missing.
Action	Correct the instance document to contain the missing content.

ISC.0082.9011E	**Unable to locate attribute declaration**
Explanation	Integration Server could not locate a corresponding schema definition for the attribute.
Action	Ensure that a schema for the relevant namespace has been created and that it contains a declaration for the attribute.

ISC.0082.9012E	**Unable to locate type definition**
Explanation	Integration Server could not locate a corresponding schema definition for the type.
Action	Ensure that a schema for the relevant namespace has been created and that it contains a definition for the type.

ISC.0082.9013E	**Unable to locate type definition {0}**
Explanation	Integration Server could not locate a corresponding schema definition for the type.
Action	Ensure that a schema for the relevant namespace has been created and that it contains a definition for the type.

ISC.0082.9014E	**Unable to locate element declaration**
Explanation	Integration Server could not locate a corresponding schema definition for the element.
Action	Ensure that a schema for the relevant namespace has been created and that it contains a declaration for the element.

ISC.0082.9015E	**Ambiguous content model in schema - not LL(1)**
Explanation	The content model is ambiguous. The given set of particle can validate the same instance with more than one unique set of occurrence counts.
Action	A schema must not be ambiguous. It must be possible to validate an instance without looking ahead in the content model definition. Modify the schema so that the content model is not ambiguous.

ISC.0082.9016E	**Unable to resolve QName: {0}**
Explanation	The type reference cannot be resolved to a defined type.
Action	Specify a defined type.

ISC.0082.9017E	**{0} is not validly derived from {1}**
Explanation	The type specified in the instance document is not a valid subtype of the type specified in the schema element declaration.
Action	Correct the instance document by specifying a valid subtype.

ISC.0082.9018E	**{0} is an abstract type and cannot be used directly to validate content**
Explanation	An abstract type cannot be specified in an instance document.
Action	Specify a concrete type that has been derived from the abstract type.

ISC.0082.9019E	**{0} is an abstract element and cannot appear in an instance**
Explanation	The instance document contains an element that has been declared abstract in the schema. Abstract elements may not appear in an instance document.
Action	Remove the abstract designation rfom the schema element definition or use a member of the abstract element's substitution group in the instance document.

ISC.0082.9020E	**{0} - xsi:type is used incorrectly (declared type is anonymous)**
Explanation	The element declaration does not reference a named type. It is not possible to specify a type in the instance document.
Action	Do not use a type specification for an element that has an anonymous type declaration.

ISC.0082.9022E	**The nillable value of {0} is false, hence xsi:nil cannot appear in an instance**
Explanation	The element declaration does not have the nillable attribute set to true. The element in the instance document may not have a nil attribute.
Action	Correct the instance document or modify the element declaration to have the nillable attribute set to true.

ISC.0082.9023E	**The value of xsi:nil is invalid**
Explanation	The instance document element contains a value for the nil attribute that is not valid. The nil attribute must have a value of true or false.
Action	Correct the instance document to specify a valid value for the nil attribute.

ISC.0082.9024E	**{0} cannot have content or child elements since xsi:nil is true**
Explanation	An element is marked nill in the instance document. The element cannot have any content.
Action	Correct the element in the instance document.

ISC.0082.9026E	**Undefined Object found**
Explanation	An unexpected object was found in the document.
Action	Correct the instance document by removing the unexpected object.

ISC.0082.9027E	**Dimension mismatch, List expected**
Explanation	The instance document contains a scalar value where an array is expected.
Action	Correct the input data.

ISC.0082.9028E	**Dimension mismatch, Single item expected**
Explanation	An array was encountered where a scalar item was expected.
Action	Correct the instance document to specify a scalar item instead of an array.

ISC.0082.9029E	**Dimension mismatch, Table expected**
Explanation	The instance document contained an object type other than String array of dimension two.
Action	Correct the instance document

ISC.0082.9030E	**Type mismatch, String expected**
Explanation	The instance document contained an object type other than String.
Action	Correct the instance document.

ISC.0082.9031E	**Type mismatch, Document expected**
Explanation	The document field was expected to reference another document but instead referenced some other data type.
Action	Correct the instance document.

ISC.0082.9033E	**Java type mismatch; expected {0}, got {1}**
Explanation	The field is declared to contain one of the supported Java wrapper types but the instance document contains some other data type.
Action	Correct the instance document.

ISC.0082.9034E	**Field is absent, field must exist**
Explanation	The specified element or attribute is required but is not present in the instance document.
Action	Correct the instance document to contain the required element or attribute.

ISC.0082.9035E	**Value cannot be null, allow null value is false**
Explanation	The field is declared to not contain nulls, but the instance document contains a null.
Action	Correct the instance document.

ISC.0082.9036E	**Duplicate root element {0} found**
Explanation	An instance document may contain only one root element.
Action	Correct the instance document so that it has only one root element.

ISC.0082.9037E	**Element [{0}] cannot have characters [{1}], because the type''s content type is element-only**
Explanation	The element's type declaration does not permit text nodes to be present.
Action	Remove the embeded text from the instance document, or use an element type declaration that permits text.

ISC.0082.9038E	**Tag occurs too many times**
Explanation	The element occurs more times than permitted by the element declaration's maxOccurs attribute.
Action	Correct the instance document.

ISC.0082.9039E	**Tag occurs too few time**
Explanation	The element occurs fewer times than required by the element declaration's minOccurs attribute.
Action	Correct the instance document.

ISC.0082.9101S	**Document Type generation error: {0}**
Explanation	An internal failure has occurred.
Action	Contact Software AG Global Support.

ISC.0082.9102S	**Integration Server says - {0}**
Explanation	An unexpected error has interrupted the conversion process.
Action	Retry the request. If the error recurs contact Software AG Global Support.

ISC.0082.9104S	**{0} - unable to locate the root element**
Explanation	An internal error has interrupted the conversion process.
Action	Contact Software AG Global Support.

ISC.0082.9105E	**Cannot process multi-dimensional array {0}. The maximum supported dimensionality for arrays is 2.**
Explanation	Document types may not conmtain String arrays with dimension greater than two
Action	Do not use String arrays with dimension greater than two.

ISC.0082.9106E	**Complex type {0} is recursive. Recursive types are supported only when selecting the option "Generate complex types as document types"**
Explanation	It is not possible to expand a type inline if it has a recursive reference. The expansion become infinite.
Action	Use the Generate complex types as document types option.

ISC.0082.9109E	**Nested and repeating model groups are not yet supported by strict compliance for the {0} component**
Explanation	This version of Integration Server does not support strict conversion of schema content models that have nested or repeating model groups.
Action	Do not use the Strict conversion option. Use the Lax or None option instead.

ISC.0082.9401E	**Invalid: length**
Explanation	The length facet value must be a non-negative integer.
Action	Specify a valid value for the length facet.

ISC.0082.9402E	**Invalid: minLength**
Explanation	The minLength facet value must be a non-negative integer.
Action	Specify a valid facet value.

ISC.0082.9403E	**Invalid: maxLength**
Explanation	The maxLength facet value must be a non-negative integer.
Action	Specify a valid facet value.

ISC.0082.9404E	**Invalid: totalDigits**
Explanation	The totalDigits facet value must be a posative integer.
Action	Specify a valid facet value.

ISC.0082.9405E	**Invalid: fractionDigits**
Explanation	The fractionDigits facet value must be a non-negative integer.
Action	Specify a valid value for the fractionDigits facet.

ISC.0082.9408E	**maxLength is less than minLength**
Explanation	The maxLength facet value is less than the minLength facet value.
Action	Adjust the minLength or maxLength facet so that minLength is less than or equal to maxLength.

ISC.0082.9410E	**Invalid enumerated item: {0}. Length of value is not equal to specified length**
Explanation	The enumerated item length is not equal to the length required by its type.
Action	Specify a valid value for the type.

ISC.0082.9411E	**Invalid enumerated item: {0}. Value is shorter than minimum length**
Explanation	The enumerated item is shorter than the required length of its type.
Action	Specify a valid value for the type.

ISC.0082.9412E	**Invalid enumerated item: {0}. Value is longer than maximum length**
Explanation	The enumerated value is longer than the maximum length allowed by its type.
Action	Specify a valid value for the type.

ISC.0082.9416E	**Invalid: minExclusive**
Explanation	The minExclusive facet value exceeds the values permitted by the totalDigits or factionDigits facets.
Action	Specify a valid facet value.

ISC.0082.9417E	**Invalid: maxInclusive**
Explanation	The maxInclusive facet value exceeds the values permitted by the totalDigits or factionDigits facet.
Action	Specify a valid value for the maxInclusive facet.

ISC.0082.9418E	**Invalid: maxExclusive**
Explanation	The maxExclusive facet value exceeds the values permitted by the totalDigits or factionDigits facets.
Action	Specify a valid value for the maxEclusive facet.

ISC.0082.9425E	**maxInclusive is less than minInclusive**
Explanation	The maxInclusive facet value is less than the minInclusive facet value.
Action	Change the value of the maxInclusive facet or the minInclusive facet.

ISC.0082.9427E	**maxExclusive is less than minExclusive**
Explanation	The maxExclusive facet value is less than the minExclusive facet value.
Action	Change the value of the maxEclusive facet or the minExclusive facet.

ISC.0082.9428E	**maxExclusive is less than minInclusive**
Explanation	The maxExclusive facet value is less than the minInclusive facet value.
Action	Change the value of the maxEclusive facet or the minInclusive facet.

ISC.0082.9436E	**maxInclusive is less than minExclusive**
Explanation	The maxInclusive facet value is less than the minExclusive facet value.
Action	Change the value of the maxInclusive facet or the minExclusive facet.

ISC.0082.9438E	**Invalid enumerated item: {0}**
Explanation	The enumeration is empty.
Action	Specify a value for the enumeration facet.

ISC.0082.9440E	**Invalid enumerated item (Out of range): {0}**
Explanation	The enumeration facet value is outside of the permitted value range of the type.
Action	Correct the enumeration facet value.

ISC.0082.9441E	**Invalid enumerated item (Does not match pattern): {0}**
Explanation	The enumeration value does not match the pattern facet for the type.
Action	Correct the enumeration value to match the pattern facet.

ISC.0082.9442E	**Invalid enumerated item. Length of value is not equal to specified length**
Explanation	The length of an enumeration value for a list must be equal to the length facet of the list.
Action	Specify a list enumeration facet with the correct length.

ISC.0082.9443E	**Invalid enumerated item. Value is shorter than minimum length**
Explanation	The length of an enumeration value for a list must be greater than or equal to the minLength facet of the list.
Action	Specify a list enumeration facet with the correct length.

ISC.0082.9444E	**Invalid enumerated item. Value is longer than maximum length**
Explanation	The length of an enumeration value for a list must be less than or equal to the maxLength facet of the list.
Action	Specify a list enumeration facet with the correct length.

ISC.0082.9447E	**Value does not conform to datatype**
Explanation	The value is not a valid instance of the type.
Action	If the error occurs during schema compilation, correct the value specification in the schema. If the error occurs during document validation, it indicates that validation successfully detected an invalid document.

ISC.0082.9449E	**"length"+STR_OUT_OF_BOUND**
Explanation	The length facet for the list is outside of the permissible range. It must not be less than the minLength facet and it must not be greater than the maxLength facet.
Action	Specify a valid length facet.

ISC.0082.9450E	**"minLength"+STR_OUT_OF_BOUND**
Explanation	The minLength facet value is either less than the minLength facet value or greater than the maxLength facet value of the base type
Action	Specify a minLength facet value that is within the range allowed by the base type.

ISC.0082.9451E	**"maxLength"+STR_OUT_OF_BOUND**
Explanation	The maxLength facet value is either greater than the maxLnegth facet value or less than the minLength facet value of the base type.
Action	Specify a maxLength facet value that is within the range allowed by the base type.

ISC.0082.9452E	**"minInclusive"+STR_OUT_OF_BOUND**
Explanation	The minInclusive facet value is either less than the minInclusive facet value or greater than the maxInclusive facet value of the base type.
Action	Specify a minInclusive facet value that is within the range allowed by the base type.

ISC.0082.9453E	**"minExclusive"+STR_OUT_OF_BOUND**
Explanation	The minExclusive facet value is either less than the minExclusive facet value or greater than the maxExclusive facet value of the base type.
Action	Specify a minExclsuive facet value that is within the range allowed by the base type.

ISC.0082.9454E	**"maxInclusive"+STR_OUT_OF_BOUND**
Explanation	The maxInclusive facet value is less than the minInclusive facet value or greater than the maxInclusive facet value of the base type
Action	Specify a correct maxInclusive facet or remove it.

ISC.0082.9455E	**"maxExclusive"+STR_OUT_OF_BOUND**
Explanation	The maxExclusive facet value is less than the minInclusive facet value or greater than the maxInclusive facet value of the base type.
Action	Specify a correct maxExclusive facet or remove it.

ISC.0082.9457E	**"totalDigits"+STR_OUT_OF_BOUND**
Explanation	The totalDigits facet value is greater than the totalDigits facet value of the base type.
Action	Specify a totalDigits facet value that is within the range allowed by the base type.

ISC.0082.9458E	**"fractionDigits"+STR_OUT_OF_BOUND**
Explanation	The fractionDigits facet of a derived type may not exceed the fractionDigits facet of the base type
Action	Correct the fractionDigits facet value so that it does not exceed the fractionDigits facet value of the base type.

ISC.0082.9459E	**"whiteSpace"+STR_OUT_OF_BOUND**
Explanation	The whiteSpace facet value is incompatible with the whiteSpace facet value of the base type
Action	Th whiteSpace facet value must specify white space handling that is more restrictive than the base type facet.

ISC.0082.9460E	**No matching enumeration value**
Explanation	The element value in the instance document contains a token that is not specified in the element type's enumeration facet.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9463E	**Length of value is not equal to specified length**
Explanation	The length of the element value in the instance document does not match the length specified by the element type's length facet.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9464E	**Value is shorter than minimum length**
Explanation	The instance document element value is shorter than the minLength facet for the element type, or the element contains a list with fewer items than the minLength facet of the list type.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9465E	**Value is longer than maximum length**
Explanation	The instance document element value is longer than the maxLength facet for the element type, or the element contains a list with more items than the maxLength facet of the list type.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9466E	**Datatype definition is missing**
Explanation	The list specification does not include a type definition for the items of the list.
Action	Specify an item type definition for the list.

ISC.0082.9469E	**Value does not match pattern(s)**
Explanation	The element value in the instance document does not match the element type's facet pattern.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9471E	**The year 0000 is prohibited**
Explanation	The facet value may not contain a year value of 0000.
Action	Do not use 0000.

ISC.0082.9472E	**totalDigits is less than fractionDigits**
Explanation	The factionDigits facet value must be less than or equal to the totalDigits facet value.
Action	Adjust the fractionDigits or the totalDigits facet value.

ISC.0082.9473E	**Invalid facet type**
Explanation	An invalid facet is specified.
Action	Specify a valid facet.

ISC.0082.9474E	**The input has invalid characters**
Explanation	An invalid whitespace character is present in the instance document.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9475E **"length"+STR_BASE_FACET_FIXED**

Explanation The length of the list is fixed and cannot be changed.

Action Remove the length facet.

ISC.0082.9476E **"minLength"+STR_BASE_FACET_FIXED**

Explanation The minLength facet of the base type is fixed; it cannot be customized.

Action Remove the minLength facet from the type specification.

ISC.0082.9477E **"maxLength"+STR_BASE_FACET_FIXED**

Explanation The maxLength facet of the base type is fixed; it cannot be customized.

Action Remove the maxLength facet from the type specification.

ISC.0082.9478E **"minInclusive"+STR_BASE_FACET_FIXED**

Explanation The minInclusive facet of the base type is fixed; it cannot be customized.

Action Remove the minInclusive facet from the type specification.

ISC.0082.9479E **"minExclusive"+STR_BASE_FACET_FIXED**

Explanation The minExclusive facet of the base type is fixed; it cannot be customized.

Action Remove the minExclusive facet from the type specification.

ISC.0082.9480E **"maxInclusive"+STR_BASE_FACET_FIXED**

Explanation The maxInclusive facet of the base type is fixed; it cannot be customized.

Action Remove the maxInclusive facet from the type specification.

ISC.0082.9481E **"maxExclusive"+STR_BASE_FACET_FIXED**

Explanation The maxExclusive facet of the base type is fixed; it cannot be customized.

Action Remove the maxExclusive facet from the type specification.

ISC.0082.9482E **"totalDigits"+STR_BASE_FACET_FIXED**

Explanation The totalDigits facet of the base type is fixed; it cannot be customized.

Action Remove the totalDigits facet from the type specification.

ISC.0082.9484E	**"whiteSpace"+STR_BASE_FACET_FIXED**
Explanation	The whiteSpace facet of the base type is fixed; it cannot be customized.
Action	Remove the whiteSpace facet from the type specification.

ISC.0082.9485E	**This datatype cannot have this facet**
Explanation	The specified facet is not defined for the type on which it appears.
Action	Remove the facet from the type specification where it appears.

ISC.0082.9486E	**Cannot specify length with minLength or maxLength**
Explanation	The length facet cannot be specified along with the minLength or maxLength facets.
Action	Remove the length facet or the minLength and maxLength facets.

ISC.0082.9487E	**"Invalid enumerated item: {0}. "+STR_EXCEEDS_TOTAL_DIGIT**
Explanation	The enumerated item has more total digits than allowed by its type.
Action	Specify a valid value for the type.

ISC.0082.9488E	**"Invalid enumerated item: {0}. "+STR_EXCEEDS_FRACTION_DIGIT**
Explanation	The enumerated item has more fraction digits than allowed by its type.
Action	Specify a value that is valid for the type.

ISC.0082.9489E	**STR_EXCEEDS_TOTAL_DIGIT**
Explanation	The total digits in the instance item exceeds the total digits that is valid for the type.
Action	None. Validation has successfully detected an invalid document.

ISC.0082.9490E	**STR_EXCEEDS_FRACTION_DIGIT**
Explanation	The instance item exceeds the fraction digits allowed for its type
Action	None. Validation successfully detected an invalid document.

ISC.0082.9491E	**Value is less than minInclusive**
Explanation	The element value in the instance document is less than the minInclusive facet for the element type.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9492E	**Value is less than or equal to minExclusive**
Explanation	The element value in the instance document is less than or equal to the minExclusive facet for the element type.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9493E	**Value is greater than maxInclusive**
Explanation	The element value in the instance document exceeds the value of the maxEclusive facet for the element type
Action	None. Validation successfully detected an invalid document.

ISC.0082.9494E	**Value is greater than or equal to maxExclusive**
Explanation	The element value in the instance document exceeds or equals the value of the maxEclusive facet for the element type
Action	None. Validation successfully detected an invalid document.

ISC.0082.9495E	**"Length constraint cannot be customized. "+STR_LENGTH_EXISTS**
Explanation	The base type already has a length facet; it is not possible to change the length facet.
Action	Remove the length facet from the type specification.

ISC.0082.9496E	**"Cannot specify minLength if length is specified. "+STR_LENGTH_EXISTS**
Explanation	The length and minLength facets are mutually exclusive.
Action	Remove one of the facets from the type specification.

ISC.0082.9497E	**"Cannot specify maxLength if length is specified. "+STR_LENGTH_EXISTS**
Explanation	The maxLnegth and length facets are mutually exclusive.
Action	Remove one of the facets from the type specification.

ISC.0082.9712E	**Cannot specify both {0} and {1}**
Explanation	The schema properties are mutually exclusive. Only one can be specified.
Action	Decide which property is relevant and remove the other.

ISC.0082.9723E **Xerces Java parser determined that the XML schema definition is invalid**

Explanation The Xerces Java parser determined that an XML schema definition is invalid. This can occur in the following situations:

- When creating an asset (IS schema, document type, or flow service) from an XML Schema definition.

- When creating a Web service descriptor from a WSDL document that contains a schema element or references an XML schema definition.

- When refreshing Web service connectors

- When executing a Web service connector

- When changing the IS schemas, document types, or service signatures associated with a Web service descriptor

Action Use the information returned by the Xerces Java parser to make the schema valid.

Alternatively, if you do not want the Xerces Java parser to perform schema validation, do one of the following:

- When creating the asset, clear the Validate schema using Xerces check box

- For an existing Web service descriptor, set the Validate schema using Xerces property to False.

ISC.0083.9001E **Requested type not available**

Explanation The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9002E **Tree type not supported**

Explanation The pub.xml:queryXMLNode service failed to execute because the supplied query object supplied was not a valid XML Node object.

Action Examine the service input and ensure it is a valid XML node object. You can invoke the pub.xml:xmlStringToXMLNode or pub.xml:loadXMLNode service to obtain the document and transform it to an XML node object before performing the query.

ISC.0083.9003E **Expression is empty**

Explanation The pub.xml:queryXMLNode service failed to execute because no query expression was specified.

Action Examine the logic and make sure that the query expression is not empty.

ISC.0083.9004E	**Node parameter is null**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XML Node to be queried was empty or missing.
Action	Examine the XML node object submitted for query and make sure it is not null.

ISC.0083.9005E	**"{0}" object type not currently supported.**
Explanation	The pub.xml:queryXMLNode service failed to execute because the document submitted was not an instance of an XML Node object. This service can obtain information from XML nodes only. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
Action	Examine the document submitted and make sure that you have used pub.xml:xmlStringToXMLNode or pub.xml:loadXMLNode service to convert the document to an XML Node object before performing the query.

ISC.0083.9006E	**Regions are not supported on IData objects**
Explanation	The pub.xml:queryXMLNode service failed to execute because it tried to perform a region query on an IData object; the Integration Server does not support this type of query. Currently only XML node objects are supported for region queries. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
Action	Do not attempt to query regions on IData objects.

ISC.0083.9007E	**Source not available for IData objects**
Explanation	The pub.xml:queryXMLNode service failed to execute because it tried to obtain information from a Document (an IData object) instead of an XML Node. This service can obtain information from XML Nodes only. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
Action	Do not attempt to query the source from Documents (IData objects).

ISC.0083.9008E	**Recursion detected in IData at {0}; can't have recursion when query contains | or //**
Explanation	The pub.xml:queryXMLNode service failed to execute because it tried to perform a query on a recursive IData object, but the query contained "|" (a union operator) or "//" (a path operator). These operators are not allowed when querying a recursive IData object.
Action	Do not attempt to query a recursive IData object when the query contains "|" or "//".

ISC.0083.9009 **Illegal typecast in query expression**

ISC.0083.9011 **'true()' or 'false()' expected**

ISC.0083.9012E **'(' expected**

Explanation The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax. Specifically, the left-hand parenthesis "(" was missing after the "true" or "false" Boolean function.

Action Examine the query expression and make sure it uses the correct syntax. There must be matching parentheses after any "true" or "false" functions, e.g., true(), false().

ISC.0083.9013E **')' expected**

Explanation The pub.xml:queryXMLNode service failed to execute because the right-hand parenthesis ")" was missing after the "true" or "false" Boolean function.

Action Examine the query expression and make sure it uses the correct syntax. There must be matching parentheses after any "true" or "false" functions, e.g., true(), false().

ISC.0083.9014E **Invalid boolean method: {0}**

Explanation The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9015E **Comparison requires an rvalue**

Explanation The pub.xml:queryXMLNode service failed to execute because the right-hand operand was not present in the query. Left- and right-hand operands are required for a comparison query.

Action Examine the query expression and make sure that both the left- and right-hand operands are supplied.

ISC.0083.9016E **Comparison righthand operand evaluates to more than one value**

Explanation The pub.xml:queryXMLNode service failed to execute a comparison query because the value of the right-hand operand was not a scalar.

Action Examine the query expression and make sure the value of the right-hand operand is a scalar or a value that can be cast at runtime to a scalar.

ISC.0083.9017E	**Comparison operator is missing.**
Explanation	The pub.xml:queryXMLNode service failed to execute a comparison query because the expression contained any or all, but no comparison operator. A comparison operator must be specified in an expression that contains any or all.
Action	Examine the query expression and make sure it contains a comparison operator.

ISC.0083.9018E	**Only relative queries allowed inside filters.**
Explanation	The XQL query expression contains an absolute path inside the filter. For example, "book[/author]".
Action	Make sure that the XQL query expression contains a relative path inside the filter. For example, "book[author]".

ISC.0083.9019U	**'[' is not matched by ']'**
Explanation	The pub.xml:queryXMLNode service failed to execute because the left-hand square bracket "[" was specified but the right-hand square "]" bracket was missing. An expression that uses a filter operator or a subscript operator must contain matching parentheses.
Action	Examine the query expression and make sure it contains matching brackets "[ ]" .

ISC.0083.9020E	**Filter brackets may only select nodes or attributes**
Explanation	The pub.xml:queryXMLNode service failed to execute because a subquery within the "[ ]" was not a node or attribute. A subquery must be a node or an attribute when a filter operation is used.
Action	Examine the query expression and make sure that the subquery contained within the "[ ]" is a node or attribute.

ISC.0083.9021E	**Invalid or missing term**
Explanation	The pub.xml:queryXMLNode service failed to execute because a query expression using a filter operator specified an invalid term or no terms at all.
Action	Examine the query expression and make sure it specifies a valid term. Valid terms are: dot('.'), left parenthesis('('), at('@'), and wildcard('*').

ISC.0083.9022E	**'(' is not matched by ')'. Token "{0}" found.**
Explanation	The pub.xml:queryXMLNode service failed to execute because the query expression contained a left parenthesis "(" that was not matched by a right parenthesis ")", but rather by another character. The query expression must specify matching parentheses when a filter operator is used.
Action	Examine the query expression and make sure it contains matching parentheses "()".

ISC.0083.9023E	**'(' is not matched by ')'. End of query found.**
Explanation	The pub.xml:queryXMLNode service failed to execute because the query expression contained a left parenthesis "(" but no right parenthesis ")". A query expression must specify matching parentheses when a filter operator is used.
Action	Examine the query expression and make sure it contains matching parentheses "()".

ISC.0083.9024E	**Invalid or misplaced term "{0}"**
Explanation	The pub.xml:queryXMLNode service failed to execute because an invalid character was specified in a query expression that contains a filter operator. Valid characters are dot ".", left and right parentheses "(" and ")", at "@", and wildcard "*".
Action	Examine the query expression and ensure that only valid characters are specified.

ISC.0083.9025E	**Invalid attribute name "{0}:"**
Explanation	The XQL query expression contains an invalid attribute name. This attribute belongs to a namespace. For example, "//@prefix:123".
Action	Make sure that the XQL query expression contains a valid attribute name. For example, "//@prefix:a123".

ISC.0083.9026E	**Invalid or missing attribute name**
Explanation	The XQL query expression contains an invalid or undefined attribute name. For example, "//@123" or "//@".
Action	Make sure that the XQL query expression contains a valid attribute name. For example, "//@a123".

ISC.0083.9027E	**attribute() takes a quoted string**
Explanation	The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to attribute() function was not a quoted string.
Action	Examine the query expression and make sure that it uses the correct syntax and passes a quoted string to the attribute() function.

ISC.0083.9028E	**attribute() incorrect attribute name "{0}"**
Explanation	The XQL query expression contains an invalid attribute name inside the attribute(). For example, "//book/attribute('123')".
Action	Make sure that the XQL query expression contains a valid attribute name inside the attribute(). For example, "//book/attribute('a')".

ISC.0083.9029 **Only nodes have attributes**

ISC.0083.9030E **count() takes a query parameter**

Explanation The XQL query expression contains a parameter in the count(), which is not allowed. For example, "//book/count(1)".

Action Make sure that the XQL query expression does not contain a parameter in the count(). For example, "//book/count()".

ISC.0083.9031E **Type {0} can't be cast to Date**

Explanation The pub.xml:queryXMLNode service failed to execute because the query engine returned a value that could not be cast as a date.

Action Examine the query expression and make sure it uses the correct syntax and specifies the correct query.

ISC.0083.9032E **date({0}){1}**

Explanation The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL date() function was not in a format that could be converted to a date.

Action Examine the detailed error message and make sure that the string parameter passed to the XQL date() function can be converted to a date.

ISC.0083.9033E **date(){0} Error offset:{1}**

Explanation The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL date() function could not be parsed.

Action Examine the detailed error message and the position provided in it and make sure that the string parameter passed to the date() function in the query expression can be parsed to a date.

ISC.0083.9034E **Invalid element name "{0}:"**

Explanation The XQL query expression contains an invalid element name. This element belongs to a namespace. For example, "//a:1".

Action Make sure that the XQL query expression contains a valid element name. For example, "//a:b".

ISC.0083.9035 **Invalid or missing element name**

ISC.0083.9036E **element() takes a quoted string**

Explanation The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL element() function was not a quoted string.

Action Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the element() function.

ISC.0083.9037E **element() incorrect attribute name "{0}"**

Explanation The XQL query expression contains an invalid parameter in element(). For example, "/book/element("1")".

Action Make sure that the XQL query expression contains a valid parameter name in element(). For example, "/book/element("a")".

ISC.0083.9038 **Only nodes have child elements**

ISC.0083.9039E **Type {0} can't be cast to Float**

Explanation The pub.xml:queryXMLNode service failed to execute because it expected a float, but the value it received was not a float.

Action Examine the query expression. Make sure it uses the correct syntax and specifies the query you intended.

ISC.0083.9040E **id() takes a quoted string**

Explanation The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL id() function was not a quoted string.

Action Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the XQL id() function.

ISC.0083.9041E **Type {0} can't be cast to Integer**

Explanation The pub.xml:queryXMLNode service failed to execute because it expected an integer, but the value it received could not be cast as an integer.

Action Examine the query expression. Make sure it uses the correct syntax and specifies the query you intended.

ISC.0083.9042E **name() takes a quoted string**

Explanation The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL name() function was not a quoted string.

Action Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the XQL name() function.

ISC.0083.9043E **name() requires a non-empty string**

Explanation The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL name() function was empty.

Action Examine the query expression and make sure it uses the correct syntax and passes a non-empty quoted string to the name() function.

ISC.0083.9044E **node() must be used relative to a node**

Explanation The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL node() function or tried to execute the function against a non-node object.

Action Examine the query expression and make sure it uses the correct syntax for the node() function and executes the function against a node.

ISC.0083.9045E **region() must be used relative to a node**

Explanation The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL region() function or tried to execute the function against a non-node object.

Action Examine the query expression and make sure it uses the correct syntax for the region() function and executes the function against a node.

ISC.0083.9046 **Query parameters of region() must return nodes**

ISC.0083.9047 **region() can't have more than one region start node**

ISC.0083.9048 **region() can't have more than one region end node**

ISC.0083.9049E **textnode() must be used relative to a node**

Explanation The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL textnode() function or tried to execute the function against a non-node object.

Action Examine the query expression and make sure it uses the correct syntax for the textnode() function and executes the function against a node.

ISC.0083.9050 **Function or method name expected**

ISC.0083.9051E **'(' missing after function or method name**

Explanation The pub.xml:queryXMLNode service failed to execute because a left-hand parenthesis "(" was missing after the function or method name. The correct syntax is functionname() or methodname() .

Action Examine the query expression and make sure that it uses the correct syntax for the function or method.

ISC.0083.9052E **Query contains truncated invocation**

Explanation The pub.xml:queryXMLNode service failed to execute because an incomplete expression was provided for a function call. Specifically, the expression contained a left parenthesis "(" but the invocation parameter or right parenthesis ")" was missing. Examples: function() function(parameter

Action Examine the query expression and make sure it uses the correct syntax.

ISC.0083.9053E **')' must terminate parameter list**

Explanation The pub.xml:queryXMLNode service failed to execute because the right parenthesis ")" was missing from the parameter list that was passed to the XQL function.

Action Examine the query expression and make sure it uses the correct syntax and includes the right parenthesis to terminate the parameter/parameter list.

ISC.0083.9054E **missing function parameter**

Explanation The pub.xml:queryXMLNode service failed to execute because the parameter required by the XQL function was not provided.

Action Examine the query expression and make sure it uses the correct syntax and includes the required parameter.

ISC.0083.9055E **Invalid number of parameters in function or method "{0}"**

Explanation The pub.xml:queryXMLNode service failed to execute because an invalid number of parameters were passed to the XQL function or method.

Action Examine the query expression and make sure it uses the correct syntax and passes the correct number of parameters to the XQL function. See XQL Query Language at http://www.w3.org/TandS/QL/QL98/pp/xql.html for method or function reference.

ISC.0083.9056E **"{0}" is not a recognized function name**

Explanation The pub.xml:queryXMLNode service failed to execute because an invalid XQL function name was provided.

Action Examine the query expression and make sure that it only uses the valid XQL functions. Integration Server currently supports the following pre-defined functions: attribute(), Boolean(), comment(), count(), date(), element(), float(), id(), integer(), name(), node(), not(), pi(), region(), textnode(), true(), false().

ISC.0083.9057E **"{0}" is not a recognized method name**

Explanation The pub.xml:queryXMLNode service failed to execute because an invalid XQL method name was provided.

Action Examine the query expression and make sure that it only uses the valid XQL methods. Integration Server currently supports the following pre-defined methods: basename(), count(), end(), index(), namespace(), nodename(), nodetype(), nodetypestring(), prefix(), regex(), regexinsensitive(), regexinsensitivematch(), regexmatch(), rawtext(), stringmatch(), source(), text(), value().

ISC.0083.9058E **Methods may only be applied to nodes and attributes**

Explanation The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9059 **regex() takes a quoted string**

ISC.0083.9060 **regexinsensitive() takes a quoted string**

ISC.0083.9061 **regexinsensitivematch() takes a quoted string**

ISC.0083.9062 **regexmatch() takes a quoted string**

ISC.0083.9063 **stringmatch() takes a quoted string**

ISC.0083.9064E	**Query contains extraneous terms**
Explanation	The pub.xml:queryXMLNode service failed to execute because there was a syntax error in the expression. Specifically, there were extraneous terms in the expression.
Action	Examine the query expression and make sure it uses the correct syntax.

ISC.0083.9065E	**Cannot parse queries of type {0}**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9066E	**Left operand of / must be either a node or an attribute**
Explanation	The pub.xml:queryXMLNode service failed to execute because the query expression specified the unary child operator "/" but the value specified by the left-hand operand was not a node type or an attribute type.
Action	Examine the query expression and make sure the left-hand operand is a node or attribute.

ISC.0083.9067E	**Only relative queries allowed in relative paths.**
Explanation	The XQL query expression contains an absolute path inside another absolute path. For example, "/x/(/y)".
Action	Make sure that the XQL query expression does not contain an absolute path embedded inside another absolute path.

ISC.0083.9068E	**Left operand of // must be a node**
Explanation	The pub.xml:queryXMLNode service failed to execute because the query expression specified the unary child descendant operator "//" but the value specified by the left-hand operand was not a node.
Action	Examine the query expression and make sure the left-hand operand is a node.

ISC.0083.9069E	**Invalid subscript argument**
Explanation	The pub.xml:queryXMLNode service failed to execute because no argument was supplied for the subscript operator or the argument supplied was not an integer.
Action	Examine the query expression and make sure that a valid integer is provided for the subscript operator.

ISC.0083.9070E	**Only values of the same type may be unioned**
Explanation	The pub.xml:queryXMLNode service failed to execute a union operation because the left-hand operand is not the same type as the right-hand operand.
Action	Examine the query expression and make sure that both operands are of the same type. Valid types are node, attribute, string, integer, float, and Boolean.

ISC.0083.9071E	**{0} and {1} types are not comparable**
Explanation	The pub.xml:queryXMLNode service failed to execute a comparison operation because the left-hand operand is not the same type as the right-hand operand.
Action	Examine the query expression and make sure that the left-hand operand and right-hand operand are of the same type. Valid types are node, attribute, string, integer, float, and Boolean.

ISC.0083.9072E	**The {0} relation is not defined on {1} types**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9073E	**Unrecognized expression type "{0}"**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9074	**generateQueryString Node doc is a required parameter. Must not be null.**

ISC.0083.9075	**generateQueryString String queryType is a required parameter. Must not be null.**

ISC.0083.9076E	**generateQueryString only supports WQL, XQLVALUES and XQL types. Unsupported type "{0}"**
Explanation	The pub.xml:queryXMLNode service failed to execute because an expression attempted to evaluate an unsupported type. Integration Server currently only supports WQL,XQLVALUES and XQL.
Action	Contact Software AG Global Support.

ISC.0083.9077E **Unknown TreeExpression type**

Explanation Integration Server tried to process an unsupported type. This is an internal error. Currently only the WQL, XQLVALUES and XQL types are supported.

Action Contact Software AG Global Support.

ISC.0083.9078E **Cannot cast "{0}" to boolean**

Explanation The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a Boolean type. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.

Action Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.

ISC.0083.9079E **Cannot cast "{0}" to a float**

Explanation The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a float. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.

Action Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.

ISC.0083.9080E **Cannot cast "{0}" to an integer**

Explanation The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to an integer. The possible causes are: (1) The left-hand and right-hand operands specified with a comparison operator were not of the same type. (2) The value returned by the query was of an unexpected type.

Action Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.

ISC.0083.9081E **Cannot cast "{0}" to a long**

Explanation The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a long type. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.

Action Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.

ISC.0083.9082 **IO error occurred while parsing a grove in a VARNAME expression: {0}**

ISC.0083.9083E **XqlQuery.getStringWithIdentities: Query "{0}" does not yield strings:{1}**

Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9084E **XqlQuery.getString: Query "{0}" does not yield strings:{1}**

Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9085E **XqlQuery: Query yields unknown type**

Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9086E **XqlQuery.getNodeWithIdentities: Query "{0}" does not yield nodes**

Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9087E **XqlQuery.getNode: Query "{0}" does not yield nodes**

Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9088E **XqlQuery.getNodeArrayWithIdentities: Query "{0}" does not yield nodes**

Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.

Action Contact Software AG Global Support.

ISC.0083.9089E	**XqlQuery.getNodeArray: Query "{0}" does not yield nodes**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9090E	**XqlQuery.getIData: Query "{0}" does not yield nodes**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9091E	**Query does not yield an IData instance as expected**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9092E	**XqlQuery.getIDataArray: Query "{0}" does not yield nodes**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9093E	**Query "{0}" does not yield only IData instances as expected**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9094E	**Floating point numbers must begin with a digit**
Explanation	The pub.xml:queryXMLNode service failed to execute because an invalid query expression was provided. Specifically, a floating point number was provided in an incorrect format. A digit must immediately precede and follow the dot "." term. Examples of the correct format are "1.23" and "-0.99.". Examples of incorrect formats are ".99" and "1.".
Action	Examine the query expression and make sure that it uses the correct format for floating point numbers.

ISC.0083.9095E	**Unrecognized operator '${0}**
Explanation	The pub.xml:queryXMLNode service failed to execute because an expression contained an unrecognized operator.
Action	Examine the query expression and make sure it only uses the valid operators specified in the XQL specification. For more information, see XQL Query Language at http://www.w3.org/TandS/QL/QL98/pp/xql.html.

ISC.0083.9096E	**Invalid number: "{0}"**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine could not parse a numberString to an integer or a float because the string does not represent an integer or float number.
Action	Examine the query expression and make sure that it uses the correct syntax. See XQL Query Language at http://www.w3.org/TandS/QL/QL98/pp/xql.html for more information.

ISC.0083.9097	**Missing terminal quote: {0}{1}**

ISC.0083.9098E	**"{0}" is not a recognized function or method name**
Explanation	The pub.xml:queryXMLNode service failed to execute because an invalid XQL function or method was specified in the query expression.
Action	Examine the query expression and make sure that you only use a set of pre-defined XQL function names or method names in the query. For a list of pre-defined functions and methods in XQL, see The XML Query Language (XQL) at http://www.w3.org/TandS/QL/QL98/pp/xql.html.

ISC.0083.9099E	**Method requires Node tree for query ''{0}''.**
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0083.9100	**Queries on attributes are not supported by IData trees.**

ISC.0083.9101	**nsDecls and namespaces are not supported by IData trees.**

ISC.0084.9004E	**Access Denied**
Explanation	The user does not have permission to access an Integration Server resource. Review the server log to find the resource and the user who was denied access.
Action	If the user should have access to this resource, either add the user to the group that is in the Allowed list of the execute ACL of the resource, or add one of this user's groups to the Allowed list of the execute ACL of the resource.

ISC.0084.9005E	**Invalid Session ID or Session Expired**
Explanation	Whenever a client presents a Session ID that is no longer valid, Integration Server throws this exception and sets the 401 HTTP response code to force the client to re-authenticate.
Action	No action is necessary.

ISC.0084.9006E	**Server is not accepting new requests at this time**
Explanation	A client request was submitted during Integration Server shutdown. Integration Server does not accept requests during shutdown.
Action	Resubmit the request after Integration Server becomes available again.

ISC.0084.9007E	**Server has reached client limit**
Explanation	Integration Server was not able to create a session to service a client requet. Integration Server sends this error with HTTP response code 503 to the client.
Action	Review the server log and error log to find possible causes of this error.

ISC.0084.9102E	**Resubmit data array cannot be null.**
Explanation	webMethods Monitor failed to resubmit the rejected document because the data array for resubmission was not supplied.
Action	Examine the document to be resubmitted and make sure that it is valid and not empty.

ISC.0084.9103E	**Resubmit data cannot be null.**
Explanation	webMethods Monitor failed to resubmit the rejected document because the data for resubmission was not supplied.
Action	Examine the document to be resubmitted and make sure that it is valid and not empty.

ISC.0084.9104E	**Auditcontexts cannot be null or empty.**
Explanation	webMethods Monitor failed to resubmit the rejected document because the "auditContexts" field in the data was either null or empty.
Action	Examine the document to be resubmitted and make sure that it is valid and that the "auditContexts " field is not missing.

ISC.0084.9105E	**Service name cannot be null or empty.**
Explanation	webMethods Monitor failed to resubmit the rejected document because the "serviceName" field in the data was either null or empty.
Action	Examine the document to be resubmitted and make sure that it is valid and that the "serviceName" field is not missing.

ISC.0084.9106U	**Service for resubmission does not exist on the server.**
Explanation	webMethods Monitor failed to resubmit the rejected document because the service for resubmission does not exist on Integration Server.
Action	Examine the document to be resubmitted and make sure that the name specified in the "serviceName" field is a valid service and exists on Integration Server.

ISC.0084.9107E	**Input pipeline cannot be null.**
Explanation	webMethods Monitor failed to resubmit the rejected document because the "pipeline" field in the data was either null or empty.
Action	Examine the document to be resubmitted and make sure that it is valid and that the "pipeline" field is not missing.

ISC.0084.9108E	**User name cannot be empty or null.**
Explanation	webMethods Monitor failed to resubmit the rejected document because the "userName" field in the data was either null or empty.
Action	Examine the document to be resubmitted and make sure that it is valid and that the "userName" field is not missing.

ISC.0084.9109E	**Access is denied to the user.**
Explanation	The current user does not have permission to invoke the service that is being resubmitted.
Action	To grant permission to the user, add the user to a group that is listed in the Execute ACL assigned to the service.

ISC.0084.9301E	**Not Authorized to use Server**
ISC.0086.9000	**Recipient certificate at index {0} not in recognizable format**
ISC.0086.9001	**bytes must be byte[]**
ISC.0086.9005	**URL must begin with "http:" or "https:"**
ISC.0086.9006	**HTTP method is null**
ISC.0086.9007	**Only use one of data.stream, data.bytes or data.mimeStream with the POST, PUT or PATCH method.**
ISC.0086.9008	**Do not use data.bytes, data.stream or data.mimeStream with the GET method.**
ISC.0086.9009	**{0}: input parameter required**
ISC.0086.9010	**invalid HTTP method: {0}**
ISC.0086.9012	**Invalid TO field: {0}**
ISC.0086.9013	**Invalid CC field: {0}**
ISC.0086.9014	**Invalid BCC field: {0}**
ISC.0086.9015	**files must be of type Values[]**
ISC.0086.9016	**No filename nor content included in the attachment!**

ISC.0086.9017 **mimeStream must be an InputStream**

ISC.0086.9018 **'pattern' is a required input**

ISC.0086.9020 **{0} does not exist**

ISC.0086.9021 **{0} cannot be read**

ISC.0086.9022 **{0} is a directory**

ISC.0086.9023 **Missing required parameter: '$name'**

ISC.0086.9024 **Missing required parameter: 'fileName'**

ISC.0086.9025 **Saved pipeline {0} does not exist**

ISC.0086.9026 **Missing required parameter: 'response'**

ISC.0086.9028 **getLastError invoked outside of a Flow**

ISC.0086.9029 **parameter 'key' is required when fromList is not null**

ISC.0086.9030 **input must be an InputStream**

ISC.0086.9031 **index must be a non-negative integer**

ISC.0086.9032 **{0} input parameter required**

ISC.0086.9033	**content input parameter required**
ISC.0086.9034	**Message content is not empty**
ISC.0086.9035	**Missing required value: {xmlvalues}**
ISC.0086.9036	**Missing required value: {record}**
ISC.0086.9037	**Missing one or more required values: {recordList,name}**
ISC.0086.9039	**Certificate not in recognizable format**
ISC.0086.9040	**Certificate at index {0} not in recognizable format**
ISC.0086.9041	**Invalid certificate input at index {0}**
ISC.0086.9042	**Could not create certs only SMIME object {0}**
ISC.0086.9043	**Not a valid InputStream**
ISC.0086.9044	**InputData not in recognizable format**
ISC.0086.9045	**Invalid recipient certificates information**
ISC.0086.9046	**Invalid recipient certificate input at index {0}**
ISC.0086.9047	**Incorrect keylength specified: {0}**

ISC.0086.9048 **Unsupported encryption algorithm specified: {0}**

ISC.0086.9049 **Could not create SMIME Enveloped object {0}**

ISC.0086.9050 **Invalid private key information**

ISC.0086.9052 **Invalid signer certificate file information**

ISC.0086.9053 **Certificate file not in any recognizable format**

ISC.0086.9054 **Could not create signed SMIME object {0}**

ISC.0086.9055 **Could not retrieve content from input**

ISC.0086.9056 **Encrypted Content not in recognizable format**

ISC.0086.9057 **Recipient certificate not in any recognizable format**

ISC.0086.9058 **Supplied certificate cannot decrypt content**

ISC.0086.9059 **Not a valid privateKey**

ISC.0086.9060 **Unable to decrypt symmetric key**

ISC.0086.9061 **Certs-Only data not in recognizable format**

ISC.0086.9062 **Signed Content not in recognizable format**

ISC.0086.9064	**bytes must be type byte[]**
ISC.0086.9065	**already in exclusive wait**
ISC.0086.9066	**cannot obtain exclusive wait**
ISC.0086.9068	**No string table data supplied**
ISC.0086.9069	**No column names supplied**
ISC.0086.9070	**{0} Maybe the wrong number of column names**
ISC.0086.9071	**No row data supplied**
ISC.0086.9072	**Deprecated Service: table to documentList conversion is now automatic.**
ISC.0086.9074	**Cannot process null input**
ISC.0086.9075	**Input not a byte array**
ISC.0086.9076	**Input in incorrect format, certificate cannot be loaded**
ISC.0086.9077	**No algorithm has been specified**
ISC.0086.9079	**No keys provided to sign the provided data**
ISC.0086.9080	**Data to sign not in the expected format (byte[])**

ISC.0086.9081	**An error occurred processing the signer information for {0}, {1}**
ISC.0086.9082	**An error occurred creating the signature for the data: {0}**
ISC.0086.9083	**No signature provided to verify**
ISC.0086.9084	**No data provided to verify detached signature**
ISC.0086.9085	**An error occurred attempting to reconstruct the signature: {0}**
ISC.0086.9086	**Signature provided is not PKCS#7 SignedData**
ISC.0086.9087	**Invalid data encountered when building the certificate chain, either an instance of a certificate or a byte[] expected**
ISC.0086.9088	**Invalid data provided for certificate entry {0}, expecting a byte[]**
ISC.0086.9089	**Parameter {0} is missing**
ISC.0086.9090	**Parameter {0} is of incorrect type**
ISC.0086.9091	**Parameters {0}, '$filestream' and '$filedata' are all missing. One of these must not be null.**
ISC.0086.9093	**Http Error: {0} - {1}**
ISC.0086.9094	**No LDAP URL specified**
ISC.0086.9095	**No connection key provided**

ISC.0086.9096 **Bad connection key: {0}**

ISC.0086.9097 **No lookup name provided**

ISC.0086.9098 **No search filter provided**

ISC.0086.9099 **No target name provided**

ISC.0086.9102 **No schema information available**

ISC.0086.9103 **Required parameter 'packageName' is missing**

ISC.0086.9104 **Required parameter 'publisher' is missing**

ISC.0086.9105 **The 'fileList' or 'fileNamePattern' parameter is required**

ISC.0086.9106 **Required parameter 'package' is missing**

ISC.0086.9107 **Package ''{0}'' has already been released, select a different name instead**

ISC.0086.9108 **Required parameter 'package' is missing**

ISC.0086.9109 **Required parameter 'packageFile' is missing**

ISC.0086.9113 **No such user present : {0}**

ISC.0086.9117 **Task being updated is not a one-time task**

ISC.0086.9118 **Task being updated is not a repeating task**

ISC.0086.9119 **Task being updated is not a complex task**

ISC.0086.9120 **Inputs cannot be null**

ISC.0086.9121 **Certificate file not found: {0}**

ISC.0086.9122 **Certificate file {0} not in any recognizable format**

ISC.0086.9123 **IO Exception encountered while reading file: {0}**

ISC.0086.9125 **lockMode must be "{0}" or "{1}". Supplied value was {2}.**

ISC.0086.9126 **key of entry to unlock can not be null**

ISC.0086.9127 **key of value to add can not be null**

ISC.0086.9128 **key of entry to insert or update can not be null**

ISC.0086.9129 **key of entry to get can not be null**

ISC.0086.9131 **key of entry to remove can not be null**

ISC.0086.9132 **value to insert or update can not be null**

ISC.0086.9133 **Cannot obtain entry lock for key**

ISC.0086.9134 **Missing required parameter: tid**

ISC.0086.9135 **Missing required parameter: alias**

ISC.0086.9136 **Missing required parameter: service**

ISC.0086.9138 **Not allowed to activate package "{0}"**

ISC.0086.9139 **The target name specified by {0} is {1}, not allowed to install package or patch to {1}**

ISC.0086.9140 **Not allowed to enable package "{0}"**

ISC.0086.9141 **Not allowed to disable package "{0}"**

ISC.0086.9142 **Not allowed to recover package "{0}"**

ISC.0086.9143 **Package file "{0}" does not exist in Inbound directory**

ISC.0086.9144 **Exception occurred while checking target package name**

ISC.0086.9145 **Invalid or non-existing package name "{0}" provided**

ISC.0086.9146 **A required parameter {0} was not supplied**

ISC.0086.9147 **The Universal Name {0} is unknown**

ISC.0086.9148 **The Universal Name {0} is already defined for {1} in the registry**

ISC.0086.9149 **The Universal Name {0} is already defined as a Service**

ISC.0086.9150 **The Universal Name {0} is not a valid QName**

ISC.0086.9151 **Parameter {0} is the wrong data type**

ISC.0086.9152 **Not allowed to reload package ''{0}''**

ISC.0086.9153 **Unknown package name ''{0}'' provided**

ISC.0086.9154 **Package ''{0}'' is already active**

ISC.0086.9155 **Package ''{0}'' is already enabled**

ISC.0086.9156 **Package ''{0}'' is already disabled**

ISC.0086.9157 **Not able to convert headerLines to byte array**

ISC.0086.9158 **Missing required parameter: 'headerLines'**

ISC.0086.9159 **Invalid input. 'headerLines' must be an instance of IData**

ISC.0086.9160 **Missing required parameter: 'body'**

ISC.0086.9161 **Invalid input. 'bytes' must be an instance of byte array**

ISC.0086.9162 **Invalid input. 'stream' must be an instance of InputStream**

ISC.0086.9163 **Invalid input. 'body' must be an instance of IData**

ISC.0086.9164 **Error reading inputstream: 'stream'**

ISC.0086.9165 **Both 'bytes' and 'stream' cannot be absent**

ISC.0086.9166 **bytes is a required field**

ISC.0086.9167 **stream is a required field**

ISC.0086.9168 **Could not retrieve raw data from implicitly signed message**

ISC.0086.9169 **Alias for Enterprise Gateway Proxy not specified**

ISC.0086.9170 **No of Connections to Enterprise Gateway Proxy not specified**

ISC.0086.9171 **New threshold for outstanding Requests not specified**

ISC.0086.9172 **Connection ID not specifie**

ISC.0086.9173 **Listener Type not specified**

ISC.0086.9174 **Invalid input. "{0}" is a required parameter of type IData**

ISC.0086.9175 **Invalid input. "{0}" is a required parameter of type String**

ISC.0086.9176E **Invalid input. "{0}" must be of type String**

Explanation The specified input parameter must have a value of type String, but does not.

Action Set the specified input paramater to a value that is of type String.

ISC.0086.9177 **Invalid input. ''{0}'' must be a positive integer**

Explanation The specified input paramater contains an invalid value.

Action Set the value of the specified input parameter to a positive integer.

ISC.0086.9178 **Invalid input. ''{0}'' must be true or false**

Explanation The specified parameter must be set to true or false.

Action Set the specified parameter to true or false.

ISC.0086.9179 **Missing required parameter: {0}**

ISC.0086.9180 **Invalid value for parameter: {0}. {0} is not a recognized numeric type**

ISC.0086.9181E **Missing required parameter: pattern**

Explanation The pattern input paramteter is required, but has not been provided.

Action Supply a value for the pattern input parameter.

ISC.0086.9182 **Missing required value: {document}**

ISC.0086.9183 **Missing one or more required values: {documentList,name}**

ISC.0086.9184 **Invalid or non-existing package name ''{0}'' provided**

ISC.0086.9185 **Missing required parameter: version**

ISC.0086.9186 **Missing required parameter: JVMversion**

ISC.0086.9187 **Missing required parameter: targetPkgVersion**

ISC.0086.9189 **Invalid date pattern or input**

ISC.0086.9193 **FTP session key not specified**

ISC.0086.9198 **Missing content or filename**

ISC.0086.9199 **{0} is not a valid directory!**

ISC.0086.9200 **Private key data must be in a byte array (byte[]).**

ISC.0086.9201 **Certificate chain data must be an array of byte array (byte[][]).**

ISC.0086.9202 **Certificate at position {0} in array is not in any recognizable format**

ISC.0086.9203 **Not a valid long number**

ISC.0086.9204E **''{0}'' is required.**

Explanation A required input value is missing.

Action Supply the missing input value and re-execute the service.

ISC.0086.9205E **If ''{0}'' is supplied, it must be zero (0) or greater.**

Explanation The indicated input value is a negative number, but it must be zero or a positive number.

Action For the specified parameter, enter a value of 0 or a positive integer. Alternatively, if the specified parameter is optional, delete the supplied value.

ISC.0086.9206E **''offset'' + ''length'' cannot exceed the size of ''{0}''.**

Explanation The values specified for offset and length are invalid because they will cause Integration Server to write data from the stream past the end of the supplied buffer.

Action Supply valid values for offset and length.

ISC.0086.9207E **The mark method is not supported by the supplied InputStream.**

Explanation A service invoked the pub.io:mark service to mark a location on a stream, but the supplied stream does not implement the mark and reset methods.

Action If you are invoking a user-written service, either use a different kind of InputStream that implements the mark and reset methods, or do not invoke the pub.io:mark service. Otherwise, contact Software AG Global Support.

ISC.0086.9208E	**The reset method is not supported by the supplied InputStream.**
Explanation	A service invoked the pub.io:reset service to reset to a location on a stream, but the supplied stream does not implement the mark and reset methods.
Action	If you are invoking a user-written service, either use a different kind of InputStream that implements the mark and reset methods, or do not invoke the pub.io:reset service.

ISC.0086.9209E	**"{0}" must be greater than zero (0).**
Explanation	The input variable specified is negative or zero, but the value must be a positive number.
Action	Supply a value greater than zero for the indicated input parameter.

ISC.0086.9210	**User specified encoding "{0}" does not match content encoding received from remote server.**

ISC.0086.9211	**No LDAP credentials provided**

ISC.0086.9212	**{0} is a required input**

ISC.0086.9213	**Notification for {0} is already registered**

ISC.0086.9214	**Notification for {0} does not exist**

ISC.0086.9215	**Invalid private key provided**

ISC.0086.9217	**Invalid certificate chain provided**

ISC.0086.9218	**Invalid partner certificate provided**

ISC.0086.9220	**Access to internal passwords denied**

ISC.0086.9221 **Password input is required**

ISC.0086.9222 **Password input must be WmSecureString**

ISC.0086.9223 **Old password input is required**

ISC.0086.9224 **New password input is required**

ISC.0086.9225 **Password must be of type WmSecureString**

ISC.0086.9226 **Password for key already exists**

ISC.0086.9227 **Password for key does not exist. Must add password as new entry**

ISC.0086.9228 **Key cannot be null**

ISC.0086.9229 **Key cannot be empty**

ISC.0086.9230 **Must input string, bytes, or chars**

ISC.0086.9232 **XML needs to be provided.**

ISC.0086.9233 **A set of values for nodeSelectors must be provided.**

ISC.0086.9234 **Either a recipientID or a recipientCert must be provided.**

ISC.0086.9235 **The XML could not be parsed.**

ISC.0086.9236 **Unable to set up the XPath context.**

ISC.0086.9237 **The keystore or key alias information is incorrect.**

ISC.0086.9238 **A value for baseURI must be provided for an enveloping signature.**

ISC.0086.9239 **The reference URI did not provide any content to sign.**

ISC.0086.9245 **The signatureSelector parameter must contain a value.**

ISC.0086.9248 **The signature could not be found.**

ISC.0086.9250 **Parameter [{0}] is not of type: [{1}]**

ISC.0086.9251 **Column [{0}] is missing for the parameter: [{1}]**

ISC.0086.9252 **key[{0}] does not exist in the pipeline**

ISC.0086.9253 **[{0}] could not be converted to a number**

ISC.0086.9254 **[{0}] could not be converted to a date**

ISC.0086.9255 **Invalid date pattern[{0}] specified.**

ISC.0086.9256 **File [{0}] does not exist**

ISC.0086.9257 **File [{0}] exists, but is a directory**

ISC.0086.9258	**Directory [{0}] cannot be created**
ISC.0086.9259	**File [{0}] exists, but is read-only**
ISC.0086.9260	**Directory [{0}] does not exist**
ISC.0086.9261	**[{0}] is not a directory**
ISC.0086.9262	**Failed to delete original file [{0}] after copying the [{1}]**
ISC.0086.9264	**Error reading properties file: [{0}]**
ISC.0086.9265	**originalObject parameter does not implement java.io.Serializable interface**
ISC.0086.9266	**File [{0}] already exists**
ISC.0086.9268	**PARAM_NUMLIST [{0}]: [{1}] could not be parsed**
ISC.0086.9270	**No PrivateKey entry found for key alias {0}.**
ISC.0086.9271	**Invalid index[{0}]. Value should be between {1} and {2}**
ISC.0086.9272	**{0} cannot be empty**
ISC.0086.9273	**Invalid holiday date pattern [{0}] specified in the holidays.cnf file**
ISC.0086.9274	**Could not parse the holiday date [{0}] specified in the holidays.cnf file using the pattern [{1}]**

ISC.0086.9275 **Invalid weekend [{0}]. Valid value should be one of the following: 'sunday', 'monday', 'tuesday', 'wednesday', 'thursday', 'friday', 'saturday'**

ISC.0086.9276 **'itemList' parameter should be an array**

ISC.0086.9277 **Specified command [{0}] is not on the allowedOSCommands list in the OSCommands.cnf file**

ISC.0086.9278 **[{0}] may not exist or it may not be a directory**

ISC.0086.9279 **Specified working directory [{0}] is not on the 'allowedWorkingDirectories' list in the OSCommands.cnf file**

ISC.0086.9280 **Unable to find the node corresponding to the provided signature node selector xpath {0}.**

ISC.0086.9281 **Unable to find the encryption certificate for recipient {0}.**

ISC.0086.9282 **Unable to resolve the certificate to verify the signature.**

ISC.0086.9283 **An invalid schema location pair was provided**

ISC.0086.9284 **Folder{0} is not empty**

Explanation The specified folder must be empty.

Action Delete the contents of the specified folder or specify an empty folder.

ISC.0086.9285 **Invalid folder name {0}. Error : {1}**

Explanation The specified folder name is invalid.

Action Specify a valid folder name.

ISC.0086.9286 **HSM based Keystore is not supported**

ISC.0086.9289E **Applications cannot use an HTTP Status-Code of {0}**

Explanation Only valid HTTP Status-Codes may be supplied.

Action Supply a valid HTTP Status-Code.

ISC.0086.9310E **Could not restore pipeline from file {0}.**

Explanation The pub.flow:restorePipelineFromFile service failed because the specified pipeline file could not be found in the IntegrationServer_directory\pipeline directory.

Action Make sure the specified pipeline file exists in the IntegrationServer_directory\pipeline directory, and then restore the pipeline.

ISC.0086.9311E **Could not save pipeline to file {0}.**

Explanation The pub.flow:savePipelineToFile service failed because the IntegrationServer_directory\pipeline directory could not be found or does not exist.

Action Make sure the IntegrationServer_directory\pipeline directory exists, and then save the pipeline.

ISC.0086.9318E **{0} must be "{1}" or "{2}".**

Explanation The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.

Action Enter a valid value for the input variable.

ISC.0086.9319E **{0} must be "{1}", "{2}", "{3}" or "{4}".**

Explanation The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.

Action Enter a valid value for the input variable.

ISC.0086.9320E **If {0} is supplied, {1} must also be supplied.**

Explanation The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.

Action Provide a valid combination of input variables.

ISC.0086.9321E	**If {0} is "{1}", {2} must be supplied.**
Explanation	The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.
Action	Provide a valid combination of input variables.

ISC.0086.9322E	**{0} must be "{1}", "{2}", "{3}" or "{4}" or "{5}".**
Explanation	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
Action	Enter a valid value for the input variable.

ISC.0086.9323E	**{0} must be "{1}", "{2}" or "{3}".**
Explanation	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
Action	Enter a valid value for the input variable.

ISC.0086.9324E	**If {0} is "{1}", {2} and {3} must be supplied.**
Explanation	The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.
Action	Provide a valid combination of input variables.

ISC.0088.0001U	**SOAPException: {0}**
Explanation	The SOAP message handler could not process the message because an error occurred.
Action	Examine the details element in the SOAP exception message for information about the specific failure that occurred.

ISC.0088.0002E	**Failed registering SOAP Processor, missing parameter: {0}**
Explanation	Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.
Action	Examine the service input and make sure that the fully qualified service name is specified correctly for input parameter "svcName".

ISC.0088.0003E	**Failed registering SOAP Processor {0} as directive {1}; directive already registered**
Explanation	Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.
Action	Make sure that the "directive" parameter specifies the correct directive. (Directive names are case-sensitive.) In addition, make sure that the specified directive is not already registered in the SOAP Processor registry. Often, this error occurs because the registry already contains a processor registered to the specified directive.

ISC.0088.0004E **Failed registering SOAP Processor {0} as directive {1}; unknown service {0}**

Explanation Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.

Action Examine the service input and make sure that the fully qualified service name is specified correctly for input parameter "svcName". (Service names are case-sensitive.) Often, this error occurs because the service does not exist on the Integration Server.

ISC.0088.0005E **Failed unregistering SOAP Processor, missing parameter: {0}**

Explanation The pub.soap.processor:unregisterProcessor service failed to execute because the "directive" parameter was not supplied.

Action Examine the service input and make sure that the "directive" parameter specifies the correct directive. (Directive names are case-sensitive.) Often, this error occurs because the directive is not specified.

ISC.0088.0006E **Failed unregistering SOAP Processor {0}; no such directive registered**

Explanation Integration Server failed to remove the specified processor from the SOAP Processor registry using the pub.processor:unregisterProcessor service.

Action Make sure that the "processorName" parameter specifies the correct directive. (Remember that directive names are case-sensitive.) In addition, make sure that the specified directive is currently registered in the SOAP Processor registry. It may have already been removed. Usually, this error occurs because the registry does not contain a processor registered to the specified directive.

ISC.0088.0007E **Failed registering SOAP Processor {0} as directive {1}; invalid character(s) in directive**

Explanation Integration Server failed to add the specified processor to the SOAP Processor registry using the pub.processor:registerProcessor service.

Action Examine the service input and make sure that the value for the "directive" parameter only contains characters that are part of a Unicode identifier. See the description of the Java standard for the full range of Unicode values. Usually, this error occurs because the specified directive contains characters that are not part of a Unicode identifier.

ISC.0088.0008 **Failed registering JAX Handler {0}; Handler already registered**

ISC.0088.0009 **Failed initializing JAX Handler {0}; error {1}**

ISC.0088.0010	**Failed destroying JAX Handler {0}; error {1}**
ISC.0088.0011	**Failed registering JAX Handler {0}, missing parameter {1}**
ISC.0088.0012	**Failed unregistering JAX Handler {0}; handler not registered**
ISC.0088.0013	**Failed unregistering JAX Handler {0}, missing parameter {1}**
ISC.0088.0014	**Failed listing JAX Handlers, missing parameter {0}**
ISC.0088.0015	**Failed finding JAX Handler {0}, missing parameter {1}**
ISC.0088.0016	**Failed finding JAX Handler {0}, handler not registered**
ISC.0088.0017	**Failed finding JAX Handler for header {0}:{1}**
ISC.0088.0020	**pub.client:soapClient SOAP request sent: {0}**
ISC.0088.0022	**pub.client:soapClient OutputValidationError - pipeline: {0} result: {1}**
ISC.0088.0023	**pub.client:soapClient InputValidationError - result: {0}**
ISC.0088.0024	**Encode input ({0}): {1}**
ISC.0088.0026	**Decode input ({0}): {1}**
ISC.0088.0028E	**Service handler {0} could not be registered. A service handler by that name already exists**
Explanation	A service handler with the provided name already exists.
Action	Specify a unique name for the service handler.

ISC.0088.0029E	**Error initializing handler {0}. Error {1}**
Explanation	An error occurred while initializing the JAX-RPC header handler.
Action	The init() method of the JAX-RPC handler threw an error. Correct the error in init() method.

ISC.0088.0030E	**Error destroying service handler {0}. Error:{1}**
Explanation	An error occurred while destroying the JAX-RPC handler.
Action	The destroy() method of the JAX-RPC Handler has thrown an error. Correct the error in destroy() method.

ISC.0088.0031E	**Service handler {0} could not be registered. Missing required parameter {1}**
Explanation	A parameter required to register the service handler was not provided.
Action	Provide the missing parameter.

ISC.0088.0032E	**Service handler {0} could not be unregistered. A service handler by that name is not registered**
Explanation	The specified service handler is not registered.
Action	Provide the name of a registered service handler.

ISC.0088.0033E	**Service handler {0) could not be unregistered. Missing required parameter {1}**
Explanation	The service handler could not be unregistered because a required parameter is missing.
Action	Provide the missing parameter.

ISC.0088.0034E	**Registered service handlers could not be listed. Missing required parameter {0}**
Explanation	The list of registered service handlers could not be created because a required input parameter was not provided.
Action	Provide the missing input parameter.

ISC.0088.0035E	**Service handler {0} could not be found. Missing required parameter {1}**
Explanation	Service handler could not be found because a required input parameter was not provided.
Action	Provide the missing input parameter.

ISC.0088.0036E	**Service handler {0} could not be found. Service handler is not registered**
Explanation	A service handler with the provided name does not exist.
Action	Register a service handler with the provided name or specify the name of an existing registered service handler.

ISC.0088.0037E	**Could not find service handler for header {0}:{1}**
Explanation	The QName of the header does not correspond to a registered service handler.
Action	Verify that the QName of the header corresponds to a registered service handler or register a service handler for the provided universal name.

ISC.0088.0038E	**Error while processing asynchronous SOAP response received by the consumer Web service descriptor {0}. SOAP Message : {1}**
Explanation	Integration Server failed to process the asynchronous SOAP response directed to the consumer web service descriptor specified in the message.
Action	Check the server log and error log to find possible causes of this error and take corrective steps.

ISC.0088.0039E	**Error while processing asynchronous SOAP response received by the consumer Web service descriptor {0}.**
Explanation	Integration Server failed to process the asynchronous SOAP response directed to the consumer Web service descriptor specified in the message, possibly because the SOAP response is not well formed.
Action	Check the server log and error log to find possible causes of this error and take corrective steps.

ISC.0088.0100	**WS Security processing failed : Unable to convert SOAPMessage into a Document : {0}**

ISC.0088.0101	**WS Security processing failed : Unable to convert Document into a SOAPMessage : {0}**

ISC.0088.0102	**WS Security processing failed : A valid Document was not specified. Unable to create SOAPMessage**

ISC.0088.0103	**WS Security processing failed : UsernameToken supported only with PasswordType as Text**
ISC.0088.0104	**WS Security processing failed : Invalid Credentials. User name {0}**
ISC.0088.0105	**WS Security processing failed : Authentication failed for user : {0}**
ISC.0088.0106	**WS Security processing failed : X509 Authentication failed with exception : {0}**
ISC.0088.0107	**WS Security processing failed : Unable to create Keystore**
ISC.0088.0108	**WS Security processing failed : Unable to create Crypto**
ISC.0088.0109	**WS Security processing failed : Invalid private key passed in to the Web service connector.**
ISC.0088.0110	**WS Security processing failed : Invalid certificate chain passed in to the Web service connector.**
ISC.0088.0111	**WS Security processing failed : Error while reading the private key/certificates from the Web service endpoint**
ISC.0088.0112	**WS Security processing failed : Error while operating on Keystore**
ISC.0088.0113	**WS Security processing failed : Unable to resolve partner certificate for encrypting the response**
ISC.0088.0114	**WS Security processing failed : Untrusted certificate chain**
ISC.0088.0115	**WS Security processing failed : Error during response encryption while retrieving partner certificate from the certificate mapper.**

ISC.0088.0116 **WS Security processing failed : Invalid outbound security policy. Username token assertion not supported in the response**

ISC.0088.0117 **WS Security processing failed : Invalid outbound security policy. X509Authentiction token assertion not supported in the response**

ISC.0088.0118 **WS Security processing failed : Unable to resolve private key for signing or decrypting the message**

ISC.0088.0119 **WS Security processing failed : Unexcected error occurred while accessing the Keystore/Truststore**

ISC.0088.0120 **WS Security processing failed : Unable to resolve partner certificate for encrypting the request**

ISC.0088.0200E **WS Security processing failed: Unable to retrieve {0} provider Web service endpoint alias named "{1}"**

Explanation Integration server could not find the provider Web service endpoint alias with the type and name specified in the message.

Action Create an appropriate provider Web service endpoint alias.

ISC.0088.0201E **WS Security processing failed: Decryption of encrypted key failed because the key is encrypted with an unknown certificate.**

Explanation Integration Server is unable to find a private key corresponding to the certificate used to encrypt the key.

Action Configure an appropriate keystore in the WS Security Properties section of the appropriate consumer or provider Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.

ISC.0088.0202E **WS Security processing failed: Unable to resolve the private key required for signing the SOAP request.**

Explanation Private key required for signing the SOAP request is not configured.

Action Configure a keystore by adding the values in the WS Security Properties section of the appropriate consumer Web Service endpoint alias or by using the Signing Key option under Security > Certificates in the Integration Server Administrator.

ISC.0088.0203E	**WS Security processing failed: Unable to resolve the private key required for signing the SOAP response.**
Explanation	Private key required for signing the SOAP response is not configured.
Action	Configure a keystore by adding the values in the WS Security Properties section of the appropriate provider Web Service endpoint alias or by using the Signing Key option under Security > Certificates in the Integration Server Administrator.
ISC.0088.0204E	**WS Security processing failed: Invalid partner certificate passed into the Web service connector.**
Explanation	Value provided for auth/message/partnerCert field while executing the Web service connector is invalid.
Action	Provide a valid certificate for auth/message/partnerCert.
ISC.0088.0205E	**WS Security processing failed: Invalid partner certificate provided in the endpoint alias "{0}".**
Explanation	Partner certificate file provided in the endpoint alias mentioned in the message is invalid.
Action	Specify a valid partner certificate file in the endpoint alias mentioned in the message.
ISC.0088.0206E	**WS Security processing failed: Unable to resolve the private key required for decrypting the SOAP request.**
Explanation	Private key required for decrypting the SOAP request is not configured.
Action	Configure a keystore by adding the values in the WS Security Properties section of the appropriate provider Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.
ISC.0088.0207E	**WS Security processing failed: Unable to resolve the private key required for decrypting the SOAP response.**
Explanation	Private key required for decrypting the SOAP response is not configured.
Action	Configure a keystore by adding the values in the WS Security Properties section of the appropriate consumer Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.
ISC.0088.0208E	**WS Security processing failed: Decryption failed because the SOAP message is encrypted with an unknown certificate.**
Explanation	Integration server is unable to find a private key corresponding to the certificate used to encrypt the message.
Action	Configure an appropriate keystore in the WS Security Properties section of the appropriate consumer or provider Web service endpoint alias or by using the

Decryption Key option under Security > Certificates in the Integration Server Administrator.

ISC.0088.0209E **WS Security processing failed: Signature verification failed because the certificate associated with the sigining private key is unknown.**

Explanation Integration server is unable to find a certificate corresponding to the private key used to sign the message.

Action Ensure that the certificate corresponding to the private key used to sign the message is imported into the certificate mapper using Security > Certificates > Configure Client Certificates in the Integration Server Administrator.

ISC.0088.0210E **WS Security processing failed: Error retrieving certificate from certificate mapper.**

Explanation Integration Server failed to retrieve the certificate corresponding to the private key that was used to sign the message. Integration Server encountered an unexpected error when attempting to retrieve the certificate from the certificate mapper.

Action Probable cause is that the embedded database of Integration Server that is used to store the certificates is corrupted. Contact Software AG Global Support.

ISC.0088.0211W **WS Security processing failed: Binder for the SOAP action "{0}" in the Web service descriptor "{1}" not found. Integration Server will use server private keys and certificates for handling WS-Security.**

Explanation Integration Server cannot find the binder for the specified SOAP action in the Web service descriptor. Integration Server is unable to use the private keys and certificates from the endpoint alias. As a result, Integration Server will use the server private keys and certificates.

Action Ensure that the correct SOAP action is specified in the incoming SOAP request.

ISC.0088.0212E **WS Security processing failed: HSM keystores are not supported.**

Explanation The Integration Server WS-Security functionality does not support HSM keystores.

Action Use a supported keystore type, for example, PKCS12 or JKS.

ISC.0088.0213E **WS Security processing failed: Integration server only supports Username token with password type {0}, but received with password type {1}.**

Explanation Incoming SOAP request has an unsupported password type in the Username token. Integration Server supports Username tokens with passwords of type: {http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0}#PasswordText only.

Action Ensure that the SOAP request the requester/client sends has a valid Username token.

ISC.0088.0214E	**WS Security processing failed: Unable to retrieve {0} consumer Web service endpoint alias named "{1}"**
Explanation	Integration server could not find the consumer Web service endpoint alias with the type and name specified in the message.
Action	Create an appropriate consumer Web service endpoint alias.
ISC.0088.9129E	**Invalid node: XML blocks must be in a container**
ISC.0088.9131E	**Invalid node: must be well-formed XML**
ISC.0088.9142E	**Invalid Body Entry. SOAP Body Entries must have a namespace name.**
ISC.0088.9143E	**Invalid Header Entry. SOAP Header Entries must have a namespace name.**
ISC.0088.9165E	**Soap Coder not found for a {0} SOAPMessage**
ISC.0088.9167E	**Service not found for soapAction = {0}**
ISC.0088.9168E	**SOAP Version Mismatch: SOAP Version "{0}" in request does not match the SOAP version "{1}" of the Web service.**
ISC.0088.9169E	**External WSDL URL does not exist for {0}, its a service first WSD.**
ISC.0088.9170E	**SOAP Version Mismatch: SOAP Version "{0}" in response does not match the SOAP version "{1}" of the Web service.**
ISC.0088.9256E	**Fault returned by invoked service**
ISC.0088.9300E	**Attachment Processing Failed: Can't get the size of the attachment due to an I/O Error**

ISC.0088.9301E **Attachment Processing Failed: Can't retrieve the content due to an I/O Error**

ISC.0088.9302E **Attachment Processing Failed: Attachment contains 'null' content**

ISC.0088.9303E **Attachment Processing Failed: The value for Data Handler is 'null'**

ISC.0088.9304E **Attachment Processing Failed: Data Handler contains 'null' Input Stream**

ISC.0088.9320E **MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; 'null' value for 'Web Service Descriptor'**

Explanation The Web service descriptor identified by the part of request URL (for provider) or passed Web service descriptor name (for consumer) as parameter, does not exist.

Action Correct the URL or correct the passed Web service descriptor name or create a proper Web service descriptor.

ISC.0088.9321E **MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; base64Binary encoded data is not in the Canonical Lexical form**

Explanation Base64Binary encoded data is not in Canonical Lexical form; it contains line break characters or tabs.

Action Convert the Base64Binary data into Canonical Lexical form.

ISC.0088.9322E **MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; invalid SOAP Message**

Explanation The SOAP Message is invalid; either it is not well formed or it does not contain valid namespace declarations.

Action Check the structure and content of the SOAP message.

ISC.0088.9323 **MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; I/O Error occurred**

Explanation Converting SOAP Message to XOP Package has been interrupted by another thread.

Action Retry the action that caused it.

ISC.0088.9324E	**MTOM Attachments Processing Failed: Cannot convert XOP Package to SOAP Message; 'Content-Id' header field is missing in some of the attachments**
Explanation	One or more attachments does not contain the “Content-Id” field. This field is required to put the content of the attachment back into the SOAP message.
Action	Verify that the serialization of XOP Package to MIME stream had “Content-Id” present in the corresponding MIME part.

ISC.0088.9325E	**MTOM Attachments Processing Failed: Cannot serialize the XOP Message; unable to retrieve bytes from SOAP String using the SOAP Message Content Encoding**
Explanation	The conversion of SOAP String to byte array using the encoding specified for SOAP message has failed.
Action	Correct the content encoding specified for the SOAP message.

ISC.0088.9326E	**MTOM Attachments Processing Failed: Cannot serialize the XOP Message; MIME serialization has failed**
Explanation	Serialization of XOP Package to MIME Stream has failed.
Action	Verify the structure of SOAP Message is correct. Particularly the elements which contains base64Binary data.

ISC.0088.9327E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'Content-Type' header of the MIME message is not equal to 'multipart/related'**
Explanation	Value for the “Content-Type” header field of the MIME message is not equal to “multipart/related”.
Action	Verify that you have passed the correct value for “Content-Type” while serializing the MIME message.

ISC.0088.9328E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'type' parameter of the 'Content-Type' header of the MIME message is not equal to 'application/xop+xml'**
Explanation	Value for the “type parameter” of the “Content-type” header field of the MIME message is not equal to “application+xop+xml”.
Action	Verify that you have passed the correct value for “type” parameter while serializing the MIME message.

ISC.0088.9329E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'start-info' parameter of the 'Content-Type' header of the MIME message is not equal to 'application/soap+xml'**
Explanation	Value for the “start-info” parameter of the “Content-Type” header field of the MIME message is not equal to “application/soap+xml”.
Action	Check if you have passed the correct value for “start-info” parameter while serializing the MIME message otherwise pass the correct value for it.

ISC.0088.9330E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; 'Content-Type' header of the Root MIME Part is invalid**
Explanation	Invalid content type for Root MIME part.
Action	Verify that you have passed the correct value for “Content-Type” header field of the Root MIME Part while serializing the MIME message.

ISC.0088.9331E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; 'Content-Type' header of the Root MIME Part does not match with the 'type' parameter of the MIME message**
Explanation	The value of the “Content-Type” header of the Root MIME Part is not equal to the value of the “type” parameter of the “Content-Type” header of the MIME message.
Action	Verify that you have passed the correct value for these field(s)/parameter(s) while serializing the MIME message.

ISC.0088.9332E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of 'type' parameter of the 'Content-Type' header of the Root MIME Part does not match with the value of the 'start-info' parameter of the MIME message**
Explanation	The value of the “type” parameter of the “Content-Type” header of the Root MIME Part is not equal to the value of the “start-info” parameter of the “Content-Type” header of the MIME Message.
Action	Verify that you have passed the correct value for these field(s)/parameter(s) while serializing the MIME.

ISC.0088.9333E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; SOAP Message in the Root MIME part is not of version 1.2**
Explanation	The version of the SOAP Message not equal to 1.2.
Action	Send the SOAP 1.2 message.

ISC.0088.9334E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; Root MIME Part contains invalid SOAP Message**
Explanation	The SOAP Message in the Root MIME Part is invalid; either it is not well formed or it does not contain valid namespace declarations.
Action	Check the structure and content of the SOAP message in the Root MIME Part.
ISC.0088.9335E	**MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; input stream is not a valid MIME stream**
Explanation	MIME Stream does not contain the valid data as per the MIME specifications.
Action	Verify that the MIME stream contains a valid MIME message.
ISC.0088.9336E	**Retrieving contents of the XOPObject failed: "{0}"**
Explanation	You attempted to read the contents from an XOPObject. However, previous logic in either the same service or a previous service has already read the XOPObject. The XOPObject instance can only be read one time.
Action	Update the service logic so that it reads an XOPObject only one time.
ISC.0088.9351E	**Could not find Web Service Descriptor with name {0}**
ISC.0088.9352E	**Handler {1} not associated with Web Service Descriptor {0}**
ISC.0088.9353E	**Could not find policy with name {0}**
ISC.0088.9354E	**Missing required parameter : {0}**
ISC.0088.9355E	**First element of the SOAP-ENV:Body must have a QName**
ISC.0088.9400E	**Invalid BOOLEAN value {0} for variable {1}; must be true or false**
ISC.0088.9432E	**SOAP Header data does not conform to Header Record: {0}**

ISC.0088.9433E **Access denied to Handler Service {0} in the Handler Chain**

ISC.0088.9434E **Provided header data for the header named "{0}" exceeds the number of headers expected by Web Service Descriptor "{1}"**

ISC.0088.9500E **Unable to determine SOAP version. Make sure that entry has a valid parent.**

ISC.0088.9501E **Invalid namespace: {0}**

ISC.0092.9117E **Invalid WSDL; URISyntaxException - Invalid URI found in the {0} attribute of the {1} element - BASE={2} URI={3}**

Explanation The WSDL document used to create a WSDL first provider web service descriptor or a consumer web service descriptor contains a URI with invalid characters or syntax at the specified location.

Action Correct the invalid URIs in the WSDL document and attempt to create the web service descriptor again.

ISC.0092.9118E **Port "{0}" is not unique within service "{1}"**

Explanation When creating a consumer Web service descriptor from a WSDL with the specified service, the service definition contains multiple ports that all have the same name.

Action Update the WSDL so that the port name is unique within the service definition.

ISC.0092.9119E **Schema definition not found for imported namespace(s):{0}**

Explanation While creating a consumer Web service descriptor or a WSDL first provider Web service descriptor from a WSDL document, Integration Server determined that the WSDL document contained one or more xsd:import elements that did not specify the schemaLocation attribute. Consequently, the schema processor in Integration Server cannot locate the schema definition for the imported namespace and Web service descriptor creation fails. When this message appears at run time, the {0} in the message is replaced by the list of the imported namespaces for which a schemaLocation attribute is not specified.

Action Correct the WSDL document by adding a valid schemaLocation attribute for each xsd:import element that did not specify a schemaLocation. The value of the schemaLocation attribute is a URI to the XML Schema definition for the imported namespace. Alternatively, modify the WSDL document by adding in inline schema definition for each namespace with a missing schemaLocation to the wsdl:types element in the WSDL document. Then attempt to create the Web service descriptor from the WSDL document.

ISC.0107.9001E **Cannot create element "{0}"; a document type or schema with this name already exists on the Integration Server.**

Explanation While trying to pull a document from the Broker, Integration Server determined that a record being referenced already existed on the Integration Server. As a result, synchronization could not continue.

Action When synchronizing document types, clear the "Overwrite existing elements when importing referenced elements" check box.

ISC.0107.9002 **Cannot create field "{0}" in Broker document type for "{1}"; this field name is not valid on the Broker. The Broker will transport the field contents, which will be visible to Integration Server clients only.**

ISC.0107.9003 **Cannot retrieve "{0}"; document type with this name does not exist on the Integration Server.**

ISC.0107.9004 **Cannot make "{0}" unpublishable; it is not a publishable document type.**

ISC.0107.9005 **Cannot make "{0}" publishable; it is already a publishable document type.**

ISC.0107.9006 **Cannot create field "{0}" in Broker document type for "{1}"; recursive types cannot be represented on the Broker. The Broker will transport the field contents, which will be visible to Integration Server clients only.**

ISC.0107.9007 **Cannot make "{0}" publishable; it contains the field name '_env'.**

ISC.0107.9008 **Cannot make document type "{0}" publishable; this name is not valid.**

ISC.0107.9009 **Cannot make "{0}" publishable; the referenced document type "{1}" does not exist.**

ISC.0107.9010 **Cannot create field "{0}" in Broker document type for "{1}"; field with duplicate names are not permitted on the Broker.**

ISC.0107.9011 **SimpleType with the name "{0}" does not exist on the Integration Server.**

ISC.0107.9012 **Could not lock node "{0}"{1}**

ISC.0107.9013 **Could not create node "{0}". User "{1}" does not have write permission on folder "{2}".**

ISC.0124.9017E **Document to XSD error: Field {0} cannot be represented in XML Schema. The field contains an XML Namespace property but the field name does not contain a prefix**

Explanation A service for which a service first provider web service descriptor is being created uses an IS document type that contains a field with an assigned XML namespace property value. However, the field name does not include a prefix to associate with the XML namespace. That is, the field name is not in the format prefix:localName.

Action Either add a prefix to the field name using the format prefix:localName or remove the value assigned to the XML namespace property. Important! Some protocols require the use of an XML namespace. Review the documentation for service signature requirements for service first provider web service descriptors.

ISC.0124.9019E **Document to XSD error: Document type {0} cannot be represented in XML Schema. The document type is an XML document type.**

Explanation Integration Server cannot create an XML Schema definition from an XML document type. Integration Server can create an XML Schema definition from an IS document type only. This error can appear whenever Integration Server creates an XML schema definition, such as when executing the pub.schema:createXSD service or when generating WSDL from a web service descriptor.

Action Replace the XML document type with an IS document type.

ISC.0164.01Error **Specified instance {0} is not a multiple of {1}.**

Explanation The object instance in the JSON input is not a multiple of the value specified in the schema.

Action Ensure that the object instance in the JSON input is a multiple of the value specified in the schema.

ISC.0164.02Error **Specified numeric instance: {1} is greater than the allowed maximum value: {0}.**

Explanation The value of the numeric instance in the JSON input is not less than or equal to the value specified in the schema.

Action Reduce the specified value in the JSON input to be less than or equal to the maximum value allowed in the schema.

ISC.0164.03Error	**Specified numeric instance is not strictly less than the allowed maximum value: {0}.**
Explanation	The value of the numeric instance in the JSON input is greater than the value specified in the schema.
Action	Reduce the specified value in the JSON input to be strictly less than the maximum value allowed in the schema.

ISC.0164.04Error	**Specified numeric instance: {1} is less than the required minimum value: {0}.**
Explanation	The value of the numeric instance in the JSON input is not greater than or equal to the value specified in the schema.
Action	Change the specified value in the JSON input to be greater than or equal to the minimum value required in the schema.

ISC.0164.05Error	**Specified numeric instance is not strictly greater than the required minimum value: {0}.**
Explanation	The value of the numeric instance in the JSON input is less than the value specified in the schema.
Action	Change the specified value in the JSON input to be greater than the minimum value required in the schema.

ISC.0164.06Error	**Specified string: {0} of length: {1} is longer than the allowed maximum value: {2}.**
Explanation	The length of the string provided in the JSON input is greater than the value specified in the schema.
Action	Reduce the length of the string in the JSON input to be less than or equal to the maximum length specified in the schema.

ISC.0164.07Error	**Specified string: {0} of length: {1} is shorter than the required minimum value: {2}.**
Explanation	The length of the string provided in the JSON input is less than the value specified in the schema.
Action	Increase the length of the string in the JSON input to be greater than or equal to the minimum value specified in the schema.

ISC.0164.08Error	**Specified string: {0} does not match the ECMA 242 pattern: {1}.**
Explanation	The string provided in the JSON input does not match the pattern specified in the schema.
Action	Ensure that the input string matches the pattern specified in the schema.

ISC.0164.10Error	**Schema allows only {0} elements in an array, but the specified instance has {1} elements.**
Explanation	The array has elements other than those specified in the schema.
Action	Remove additional elements from the array to include only those that are specified in the schema.

ISC.0164.11Error	**Schema allows a maximum of {0} elements in an array, but the specified instance has {1} elements.**
Explanation	The specified array has more elements than the maximum allowed in the schema.
Action	Remove additional elements from the array to ensure that the total number of elements is less than or equal to the maximum allowed in the schema.

ISC.0164.12Error	**Schema requires a minimum of {0} elements in an array, but the specified instance has {1} elements.**
Explanation	The specified array has fewer elements than the minimum required in the schema.
Action	Add more elements to the array to ensure that the total number of elements is greater than or equal to the minimum required in the schema.

ISC.0164.13Error	**Array must not contain duplicate elements.**
Explanation	The specified array has duplicate elements.
Action	Remove duplicate elements from the array to ensure that it contains only unique elements.

ISC.0164.15Error	**Schema allows a maximum of {0} properties, but the specified object instance has {1} properties.**
Explanation	The specified object instance has more properties than the maximum allowed in the schema.
Action	Remove additional properties to ensure that the number of properties in the object instance is less than or equal to the maximum allowed value in the schema.

ISC.0164.16Error	**Schema requires a minimum of {0} properties, but the specified object instance has {1} properties.**
Explanation	The specified object instance has more properties than the minimum required in the schema.
Action	Add properties to ensure that the number of properties in the object instance is greater than or equal to the minimum required value in the schema.

ISC.0164.17Error	**Specified object instance must have the following required properties: {0}. The following properties are missing: {1}.**
Explanation	The object instance must have all the required properties specified in the schema.
Action	Add the required properties that are missing to the object instance.

ISC.0164.20Error	**Specified object instance has the following additional properties that the schema does not allow: {0}.**
Explanation	The object instance has properties other than those specified in the schema.
Action	Remove the additional properties from the object instance.

ISC.0164.21Error	**Property {0} is missing the following required property dependencies: {1}.**
Explanation	The JSON input does not contain dependency details for the specified property.
Action	Add the dependency for the specified property to the JSON input.

ISC.0164.23Error	**Specified instance value: {0} not found in enumeration with the following possible values: {1}.**
Explanation	The specified value is not among the possible enumeration values given in the schema.
Action	Make the required changes so that the specified values is among the possible enumeration values given in the schema.

ISC.0164.25Error	**Specified instance type: {0} does not match any of the allowed primitive types: {1}.**
Explanation	The specified input does not match any of the primitive types allowed in the schema.
Action	Change the input type to match the primitive types allowed in the schema.

ISC.0164.26Error	**Specified instance failed to match all the required schemas. Matched only {0} out of {1}.**
Explanation	The specified instance does not match all the schema instances.
Action	Change the input content so that it matches all the specified schema instances.

ISC.0164.27Error	**Specified instance failed to match at least one required schema out of {0}.**
Explanation	The specified instance does not match at least one of the schema instances.
Action	Change the input content so that it matches at least one of the specified schema instances.

ISC.0164.28Error	**Specified instance failed to match exactly one schema. Matched {0} out of {1}.**
Explanation	The specified instance matches more than one of the schema instances.
Action	Change the input content so that it matches exactly one of the specified schema instances.

ISC.0164.29Error	**Specified instance should not have matched the schema.**
Explanation	The specified instance matches the schema.
Action	Change the input content to not match the specified schema.

ISC.81.9187W	**JAX-RPC handlers are not supported when the Pre-8.2 compatibility mode is false. The following handlers will be ignored at run time: {0}**
Explanation	Integration Server only supports JAX-RPC handlers for use with Web service descriptors that run in pre-8.2 compatibility mode (i.e., when the Pre-8.2 compatibility mode property is true).
Action	To continue using the JAX-RPC handler, change the Web service descriptor to run in pre-8.2 compatibility mode. If you do not want to run the Web service descriptor in pre-8.2 compatibility mode, replace the JAX-RPC handler with a service handler that has the same behavior.

ISC.81.9188W	**Port type names of all the binders will be changed to "{0}". As a result, all bindings in the generated WSDL will use the same port type.**
Explanation	When a Web service descriptor's Pre-8.2 compatibility mode property is set to false, Integration Server generates WSDL with all the bindings referring to same port type. As a result, when you change the Pre-8.2 compatibility mode property from true to false, Integration Server changes the port type names of all the binders to (wsdName)_PortType, where (wsdName) is the Web service descriptor name.
Action	Depending on your web service client framework, you may need to regenerate or recreate existing Web service clients from the WSDL.

ISC.81.9189E	**All binders must have the same binding style and use when Pre-8.2 compatibility mode is false.**
Explanation	When a Web service descriptor's Pre-8.2 compatibility mode property is set to false, Integration Server does not allow the Web service descriptor to have binders that have different binding styles and use. Integration Server issues this message when either you are attempting to create a new binder for a Web service descriptor and the new binder has a different binding style or use from the existing binders, or when you are trying to consume a WSDL to create a Web service descriptor and WSDL has multiple bindings with different style and use.
Action	If you are trying to create a new binder for a Web service descriptor, use the same binding style and use as the existing binders. If you are trying to consume a WSDL that contains multiple bindings with different style and use, split the WSDL into multiple WSDLs that each use the same style and use.

ISC.81.9190E **Multiple port types are not supported when Pre-8.2 compatibility mode is false.**

Explanation Tthe WSDL document used to create the Web service descriptor consists of multiple port types. When creating a Web service descriptor in Designer, Integration Server does not support multiple port types.

Action Split the WSDL document that consists of multiple port types into multiple WSDL documents that each use a single port type. Then, create Web service descriptors from each WSDL document.

ISC.81.9196W **MTOM streaming is not supported when the Pre-8.2 compatibility mode is true.**

Explanation When the Pre-8.2 compatibility mode property of a Web service descriptor is set to true, Integration Server does not support MTOM streaming of attachments. Integration Server issues this message when you change the Pre-8.2 compatibility mode property from false to true and when at least one of the operation's input or output signature contains a field of type Object and the java wrapper type is set to com.wm.util.XOPObject.

Action To continue using MTOM streaming, set the Pre-8.2 compatibility mode property of the Web service descriptor to false. If you want to run the Web service descriptor in pre-8.2 compatibility mode, ensure that the attachment size is not very large to avoid out of memory errors.

ISC.88.9171E **Operation not found for soapAction = {0}**

Explanation Integration Server could not find the operation for the SOAP action specified in the incoming SOAP request.

Action Ensure that the correct SOAP action is specified in the incoming SOAP request. For a service first provider, if needed, you can edit the SOAP action to operation map present in the binder properties.

ISC.88.9172E **Web service cannot be found for endpoint reference (EPR) = {0}**

Explanation Integration Server could not find the Web service with the specified endpoint reference.

Action Ensure that the Web service descriptor with the endpoint reference exists in the Integration Server.

ISC.88.9173E **Operation can not be found for endpoint reference (EPR) = {0} and soapAction = {1}**

Explanation Integration server could not find the operation in the Web service identified with the specified endpoint reference and SOAP action.

Action Ensure that the operation with the specified SOAP action is present in the Web service descriptor identified by the endpoint reference.

ISC.88.9357E	**You cannot use this service against the specified Web service descriptor because its Pre-8.2 compatibility mode property is set to false.**
Explanation	Either pub.soap.utils:resetWSDEffectivePolicy or pub.soap.utils.setWSDEffectivePolicy services were specified with a Web service descriptor with Pre-8.2 compatibility mode property set to false. These services can only be used with Web service descriptors that are running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to true)
Action	Change the Web service descriptor's Pre-8.2 compatibility mode property to true.

ISE.0093.9902E	**Error occurred while invoking a service : {0}**
Explanation	The Integration Server encountered an internal error while invoking a service. More information about the error is provided in the error message.
Action	Contact Software AG Global Support.

ISE.0093.9903E	**Not implemented**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISE.0093.9904E	**Unknown session: {0}**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISE.0093.9908E	**Parameter {0} specified for method is invalid**
Explanation	The parameter that you specified is not valid.
Action	Specify a valid parameter.

ISE.0093.9924E	**FAILED**
Explanation	Integration Server is unable to retrieve the status of Repository Server V2.
Action	Ensure that the port and host information that you specified to retrieve the status of Repository Server V2 is correct.

ISE.0093.9934E	**Service {0} doesn't exist or was removed.**
Explanation	The service that you are trying to execute does not exist in Integration Server.
Action	Ensure that the service exists in Integration Server.

ISE.0093.9935E	**Package {0} doesn't exist or was removed.**
Explanation	The package that you are trying to access does not exist or is deleted.
Action	Ensure that the package you want to access exists in the IntegrationServer_directory\packages directory.

ISE.0093.9936E	**Port {0} doesn't exist or was removed.**
Explanation	The e-mail port that you are trying to access is not configured or enabled.
Action	Ensure that the e-mail port you want to access is configured and enabled.

ISE.0093.9952E	**Access was denied to resource {0}**
Explanation	The Integration Server encountered an internal error due to resource access.
Action	Contact Software AG Global Support.

ISE.0093.9953E	**A Java exception occurred {0}**
Explanation	Integration Server encountered an unexpected error.
Action	Contact Software AG Global Support.

ISE.0093.9954E	**Resource {0} doesn't exist or was removed.**
Explanation	The Integration Server encountered an internal error due to resource access.
Action	Contact Software AG Global Support.

ISKeyStoreBundle.getKeyForJournalLogger(DEFAULT_ILIVE_TRUSTSTORE_CREATION_ERROR) – Error: Truststore alias "DEFAULT_INTEGRATION_LIVE_TRUSTSTORE" cannot be created. Details: {0}

ISP.0000.9101E	**Unable to register NTLM Challenge Response Authentication handler**
Explanation	A handler was registered and then re-registered without first being unregistered.
Action	Register a handler only once. If you want to re-register a handler, first unregister it.

ISP.0046.0001E	**Could not initialize {0} Listener. Invalid port specified: {1}**
Explanation	While attempting to initialize a port, Integration Server detected that the port was improperly configured. Specifically, an invalid port number was specified for the port in the server.cnf, ports.cnf, or listeners.cnf file.
Action	Edit the appropriate configuration file and specify a port number from 1 through 65534 that is not already in use.

ISP.0046.0006E	**Cannot initialize {0} Listener on port {1}. No socket available.**
Explanation	While trying to initialize an HTTP listener, Integration Server determined that the socket associated with the requested port is already in use by another application. As a result, the requested port is unavailable.
Action	Specify a port that is not already in use, or disable the application that is using the requested port.

ISP.0046.0007W	**{0} Access denied. Connection disallowed {1}**

ISP.0046.0019S	**Unable to establish connection to Enterprise Gateway Server {0}:{1}. Exception: {2}.**
Explanation	The Internal Server could not establish a connection to Enterprise Gateway Server for the reason indicated.
Action	Ensure that the Enterprise Gateway registration port is enabled.

ISP.0046.0020S	**Unable to establish connection to Enterprise Gateway Server {0}:{1}. Internal Server was not authenticated on the Enterprise Gateway.**
Explanation	Internal Server authentication failed on the Enterprise Gateway.
Action	Ensure that the registration credentials specified during the creation of the Internal Server port are correct.

ISP.0046.0024E	**Unable to establish connection to Enterprise Gateway Server {0}:{1}. Internal Server version {2} does not support Enterprise Gateway version {3}**
Explanation	The version of Enterprise Gateway Server must be equal to or higher than the versions of Integration Servers acting as the Internal Server.
Action	Use the same or higher version of Enterprise Gateway Server.

ISP.0046.0025E	**Rejected a connection from Internal Server {0} on port {1}. Enterprise Gateway version {2} does not support Internal Server version {3}**
Explanation	The version of Enterprise Gateway Server must be equal to or higher than the versions of Integration Servers acting as the Internal Server.
Action	Use the same or higher version of Enterprise Gateway Server.

ISP.0047.0001E	**47.1 obsolete**
Explanation	While attempting to initialize a port, Integration Server detected that the port was improperly configured. Specifically, an invalid port number was specified for the port in the server.cnf, ports.cnf, or listeners.cnf file.
Action	Edit the appropriate configuration file and specify a port number from 1 through 65534 that is not already in use.

ISP.0047.0002 **Resuming HTTPS Listener on port {0}**

ISP.0047.0003 **Starting HTTPS Listener on port {0}**

ISP.0047.0005 **Stopping HTTPS Listener on port {0}**

ISP.0047.0008 **Could not start HTTPS Listener on port {0}. No SSL support available.**

ISP.0047.0009 **Error in SSL setup: {0}**

ISP.0047.0010 **Certificate Authority was recognized**

ISP.0047.0011 **Certificate Authority was not recognized {0}**

ISP.0047.0012 **Client does not have a digital certificate**

ISP.0047.0013 **Access denied to host {0}**

ISP.0047.0014 **Error in SSL Setup: {0}**

ISP.0047.0015 **Error in SSL setup: Not all certificate fingerprints were loaded**

ISP.0047.0016 **The required client certificate was not provided by {0}**

ISP.0047.0017 **Could not start HTTPS listener on port {0}**

ISP.0047.0018E **Aborting connection from {0}: {1}**

Explanation Integration Server encountered a problem while trying to establish a secure connection with the client at the indicated address.

Action Make sure the client properly supports SSL connections.

ISP.0047.0019E **SSL listener restricted to 128 bit or better encryption:**

Explanation Integration Server configuration property watt.net.ssl.server.strongcipheronly is set to "true", but the list of ciphers includes weak ciphers. Integration Server displays these weak ciphers in subsequent messages.

Action Either use only strong ciphers, or set watt.net.ssl.server.strongcipheronly to "false".

ISP.0047.0020E **cipher {0} = {1} ({2} bit)**

Explanation Integration Server configuration property watt.net.ssl.server.strongcipheronly is set to "true", but the list of ciphers includes the weak ciphers displayed by this message.

Action Either use only strong ciphers, or set watt.net.ssl.server.strongcipheronly to "false".

ISP.0047.0021E **Aborting connection request on {0} port {1}, a certificate map does not exist for {2}**

Explanation A client presented a certificate to Integration Server, but the certificate has not been mapped to a user on Integration Server. For a certificate to be mapped to a user, the certificate must have been previously stored on Integration Server and associated with that user.

Action Use the Server Administrator interface to import the certificate to Integration Server and map it to the appropriate user.

ISP.0047.0022 **Access denied to host: Hostname verification failed. The CN "{0}" in the subject DN of the certificate does not match the hostname "{1}".**

ISP.0047.0023 **Aborting connection, Server Certificate purpose verification failed**

ISP.0047.9998U **Exception --> {0}**

Explanation Integration Server encountered an error. This message contains the exception produced by the server.

Action Examine the error message to determine the problem.

ISP.0057.0001I **Delete operation completed**

ISP.0061.0001 **Access denied to remote server {0} for user {1}**

ISP.0061.0002	**Expired remote connection to {0} for user {1}**
ISP.0061.0003	**Established new remote connection to {0} for user {1}**
ISP.0061.0004	**Established new remote connection to {0}**
ISP.0061.0005	**Error expiring remote connection: {0}**
ISP.0061.0006	**Error expiring remote connection for user {0}: {1}**
ISP.0061.0007	**Expired remote connection to {0}**
ISP.0061.0008	**Could not create default Remote Server Alias: {0}**
ISP.0061.0009	**The default Remote Server Alias was created.**
ISP.0068.0001	**Successfully logged in as user {0} on host {1}**
ISP.0068.0002	**Login attempt as user {0} on host {1} failed**
ISP.0068.0004	**Processed {0} new message(s)**
ISP.0068.0005	**Error processing email message. {0}.**
ISP.0068.0006	**EMAIL Access denied. Connection disallowed from host {0}**
ISP.0068.0007	**EMAIL Access denied. Invalid host in senders address: {0}**

ISP.0068.0008 **EMAIL Access denied. Could not figure out senders email address.**

ISP.0068.0009 **EMAIL Access denied. User {0} not allowed to run service {1}**

ISP.0068.0010 **Could not decode body part of email message**

ISP.0068.0011 **Could not decode message body into input parameters**

ISP.0068.0012 **Listener key not provided. Not running email listener**

ISP.0068.0013 **Error processing service: {0}**

ISP.0068.0014 **Could not get message content: {0}**

ISP.0068.0015 **Could not get body part of message: {0}**

ISP.0068.0016 **Error parsing message: {0}**

ISP.0068.0017 **Could not get message UID: {0}**

ISP.0068.0018 **Could not start listener threads: {0}**

ISP.0068.0020 **Could not get message with uid {0}**

ISP.0068.0021 **Could not process message with uid {0}**

ISP.0068.0022 **Could not send reply message to {0}. Check email address and smtp settings.**

ISP.0068.0023 **Received reply message. Not processing**

ISP.0068.0024 **The connection to the IMAP server {0} for user {1} was temporarily lost. Some messages may not have been processed.**

ISP.0068.0025 **No content handler for content type {0}. Service {1} called without content handler.**

ISP.0068.0026 **Content type: {0} Subject: {1}**

ISP.0068.0027 **{0} lost connection to {1} server {2}**

ISP.0068.0028 **{0} reconnected to {1} server {2}**

ISP.0068.9001E **Skipping processing reply email message**

Explanation The subject line of the e-mail received on the e-mail port starts with "Re:". Hence, it is treated as a reply message and its processing is skipped.

Action Investigate why the subject line of the e-mail starts with "Re:". Usually, this is an indicator of a reply message.

ISP.0068.9002E **Skipping processing returned email message**

Explanation The subject line of the e-mail received on the e-mail port starts with "Returned". Hence, it is treated as a message that is returned by the recipient and its processing is skipped.

Action Avoid the error and process the returned messages by setting the extended property "watt.server.email.processReturnedEmails" to true.

ISP.0068.9003E **Invalid service: {0}**

Explanation Integration Server received a message on the e-mail port listener, but the service specified to perform the message processing is invalid. The service that Integration Server selects to execute message processing depends on how the server is configured. Integration Server searches for the value in the locations listed below in order of precedence:

- The Global Service field on the Email Client Configuration screen on the Server Administrator.

- The e-mail message from the e-mail client.

- The Default Service field on the Email Client Configuration screen on the Server Administrator.

	The problem is often that the service name is specified in the wrong case (service names are case sensitive). Other causes could be that no service was specified at all or the service is not in its specified location.
Action	Make sure the service name is specified correctly and exists in the location specified.

ISP.0068.9004E	**No such service: {0}**
Explanation	The Integration Server FTP listener encountered an internal error.
Action	Contact Software AG Global Support.

ISP.0068.9005E	**Unknown content type: {0}**
Explanation	The Integration Server does not support the MIME type specified.
Action	Only use the MIME types supported by the Integration Server.

ISP.0068.9006E	**Server Error: {0}**
Explanation	An unexpected error occurred when invoking the service.
Action	If the exception details provided as part of the message does not give any hint, contact Software AG Global Support.

ISP.0068.9101E	**Invalid header {0}**
Explanation	The header specified is invalid.
Action	Ensure that a valid header is provided. Keep the following points in mind when specifying a header: 1. Header name should not contain spaces. 2. Header value should not be empty. 3. Header name and value should not be the same.

ISP.0068.9102E	**Invalid TO field: {0}**
Explanation	Either the recipient e-mail address is not provided in the "to" field or the address provided is invalid.
Action	Enter a valid e-mail addess in the "to" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0068.9103E	**Invalid CC field: {0}**
Explanation	The e-mail address entered in the "cc" field is invalid.
Action	Enter a valid e-mail addess in the "cc" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0068.9104E	**Invalid BCC field: {0}**
Explanation	The e-mail address entered in the "bcc" field is invalid.
Action	Enter a valid e-mail addess in the "bcc" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0068.9106E	**No filename nor content included in the attachment!**
Explanation	Content or filename is not provided in the attachments field.
Action	Provide either the content or the filename in the attachments field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0068.9108E	**charset {0} is not valid**
Explanation	Character set encoding specified for the body or attachement is invalid.
Action	Ensure that the Character set encoding specified is valid. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0068.9110E	**Invalid MAILHOST field: {0}**
Explanation	No value is provided for the mailhost parameter of the pub.client:smtp service.
Action	Provide a valid value for the mailhost parameter of the pub.client:smtp service. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0068.9111E	**Invalid Message Recipient: {0}**
Explanation	Either the recipient e-mail address is not provided in the "to" field or the address provided is invalid.
Action	Enter a valid e-mail addess in the "to" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0071.0001 **Could not initialize FTP Listener. Invalid port specified: {0}**

ISP.0071.0002 **Suspending FTP(S) Listener on port {0}**

ISP.0071.0003 **Can not build data channel, the exception is {0}, the message is {1}**

ISP.0071.0004 **The port range specified for passive data connections to FTP(S) listeners is invalid: please specify both "watt.net.ftpPassivePort.min" and "watt.net.ftpPassivePort.max" values**

ISP.0071.0005 **The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" value is not a number**

ISP.0071.0006 **The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.max" value is not a number**

ISP.0071.0007 **The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" and "watt.net.ftpPassivePort.max" values are not within 1-65534 range**

ISP.0071.0008 **The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" value is greater than "watt.net.ftpPassivePort.max" value**

ISP.0071.0009 **All ports within the port range specified for passive data connections to FTP(S) listeners are in use**

ISP.0071.0010E **PORT command refused. The PORT address {0} does not match the original host address {1}.**

Explanation In FTP active mode, the PORT command specifying the IP address does not match the client IP address in the control connection. Possible reason for this could be that your FTP client is compromised.

Action Contact your network security team to take necessary action in case your FTP client is compromised.

ISP.0071.0011E	**Cannot build data connection: client address {0} does not match the original host address {1}.**
Explanation	In FTP passive mode, the client address associated with the control port does not match the client address in the data port connection. Possible reason for this could be that your FTP client is compromised.
Action	Contact your network security team to take necessary actions in case your FTP client is compromised.

ISP.0071.9001E	**Cannot build data connection: use PORT or PASV first**
Explanation	The Integration Server failed to connect to a port on the FTP client because the FTP client did not provide valid port information.
Action	Check the Integration Server configuration and restart the server. If the problem persists, contact Software AG Global Support.

ISP.0071.9002E	**{0}: cannot create**
Explanation	An FTP client application connected to an FTP port on the Integration Server and tried to create a remote directory on the FTP server, but the "mkdir" command failed.
Action	Make sure the directory name was specified correctly. Also, examine the remote file system and make sure that you have permission to create the directory there.

ISP.0071.9003E	**{0}: cannot delete**
Explanation	An FTP client application connected to an FTP port on the Integration Server and tried to delete a file on the FTP server, but the "delete" command failed.
Action	Make sure the file name was specified correctly and that the file exists on the remote server. Also, examine the remote file system and make sure that you have permission to delete the file from the remote file system.

ISP.0071.9004E	**Cannot rename File to {0}**
Explanation	An FTP client application connected to an FTP port on the Integration Server and tried to rename a file on the FTP server, but the "rename" command failed.
Action	Make sure the old and new file names were specified correctly. Also, examine the remote file system and make sure that you have write permission to both the old and new file names.

ISP.0071.9005U **Unable to make dir {0}**

Explanation An FTP client application connected to an FTP port on the Integration Server and tried to create a remote directory on the FTP server, but the "mkdir" command failed.

Action Make sure the directory name is specified correctly. Also, examine the remote file system and make sure that you have the appropriate permissions to create the directory there.

ISP.0071.9006U **Unable to delete {0}**

Explanation An FTP client application connected to an FTP port on the Integration Server and tried to delete a file on the FTP server, but the "delete" command failed.

Action Make sure the file name is specified correctly and that the file exists. Also, examine the remote file system and make sure that you have permission to delete the file.

ISP.0071.9007U **Unable to rename to {0}**

Explanation An FTP client application connected to an FTP port on the Integration Server and tried to rename a file on the FTP server, but the "rename" command failed.

Action Make sure the old and new file names are specified correctly. Also, examine the remote file system and make sure that you have write permission to both the old and new file names.

ISP.0071.9008E **Cannot write**

Explanation Integration Server failed to put the file in the folder directory. The file must be in the service directory for processing.

Action Put the file in the service directory.

ISP.0071.9009E **Invalid transaction name. Not in the form 'tid[;mime.type][;encoding]'.**

Explanation The MIME type specified in the FTP request is incorrect. It should be in the form of 'tid[;mime.type][;encoding]'."

Action Make sure to provide the name in the correct format.

ISP.0071.9010U **Uable to determine mime type**

Explanation Integration Server does not support the MIME type specified.

Action Only use the MIME types supported by Integration Server. Refer to the webMethods Integration Server documentation for more information.

ISP.0071.9011E	**Cannot read**
Explanation	Ensure that the specified file exists in the FTP server.
Action	The Integration Server failed to read the specified file from the FTP server.

ISP.0071.9012U	**No such service: {0}**
Explanation	The Integration Server FTP listener encountered an internal error.
Action	Contact Software AG Global Support.

ISP.0071.9013U	**Unknown content type: {0}**
Explanation	The Integration Server does not support the MIME type specified.
Action	Only use the MIME types supported by the Integration Server. Refer to the webMethods Integration Server documentation for more information.

ISP.0071.9014U	**Server Error: {0}**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISP.0071.9015E	**Cannot publish STOR complete event**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISP.0071.9016E	**Cannot build data connection: client address {0} does not match the original host address {1}.**
Explanation	In FTP passive mode, the client address associated with the control port does not match the client address in the data port connection. Possible reason for this could be that your FTP client is compromised.
Action	Contact your network security team to take necessary action in case your FTP client is compromised.

ISP.0085.9001E	**Issuer DN must be provided**
Explanation	The certificate is incomplete. It must include an Issuer DN.
Action	Supply a certificate that includes an Issuer DN.

ISP.0085.9002E **Serial number must be provided**

Explanation The certificate is incomplete. It must contain a serial number.

Action Supply a certificate that includes a serial number.

ISP.0085.9004E **data provided for certificate not in expected format**

Explanation Only X509Certificates may be used to identify Integration Server clients.

Action Supply a valid X509Cerificate.

ISP.0085.9005E **No map entry exists for the specified information**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9006E **Certificate's file name is required**

Explanation Certificate Path is empty.

Action Supply the fully qualified file name for a certificate file.

ISP.0085.9007E **Specified certificate file does not exist**

Explanation The Certificate Path field refers to a non-existent file.

Action Supply the fully qualified file name of a certificate file.

ISP.0085.9008E **Specified certificate file is empty**

Explanation The Certificate Path field refers to an empty file.

Action Supply the fully qualified file name of a certificate file.

ISP.0085.9009E **Attempted to update a non-existent entry**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9010E **{0} is not a valid user**

Explanation The supplied user name does not identify a user on this Integration Server.

Action Supply a valid user.

ISP.0085.9011E **Missing input for the parameter 'oldName'**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9012E **No service/Document Type exist for: {0}**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9013E **Missing input for the parameter 'newName'**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9014E **Not a Document Type: {0}**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9015E **Not a flow service: {0}**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9016E **Missing input parameter: path**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9017E **No input for the parameter {0}**

Explanation This is an internal error.

Action Contact Software AG Global Support.

ISP.0085.9018E **Specified node {0} not found**

Explanation Internal error.

Action Contact Software AG Global Support.

ISP.0085.9019 **Missing required parameter: 'fileName'**

ISP.0085.9020 **Missing required parameter: 'pipeline'**

ISP.0085.9030 **No such folder: {0}**

ISP.0085.9032 **Invalid folder type: {0}**

ISP.0085.9033 **Provided folder name is null**

ISP.0085.9034 **Provided source is null**

ISP.0085.9035 **Provided package name is null**

ISP.0085.9038 **No such folder: {0}**

ISP.0085.9041U **No such service: {0}**

Explanation Integration Server FTP listener encountered an internal error.

Action Contact Software AG Global Support.

ISP.0085.9043 **Must specify either Specification or Signature**

ISP.0085.9047 **Failed to register {0}**

ISP.0085.9050 **no such service {0}**

ISP.0085.9051 **service {0} is not a Java IM**

ISP.0085.9052 **node is missing a name**

ISP.0085.9053E **invalid package**

Explanation An application tried to delete a service, but the package specified does not exist on the Integration Server.

Action Examine the service input and verify that a valid package name is specified.

ISP.0085.9054 **Node name was not provided**

ISP.0085.9055 **Node {0} does not exist**

ISP.0085.9057 **Target name was not provided**

ISP.0085.9059 **Target package does not exist. Create it first**

ISP.0085.9060 **IOException occurred file={0}: {1}**

ISP.0085.9061 **Similarly-named node "{0}" already in use**

ISP.0085.9062E **Package name was not provided**

Explanation An application tried to export a package, but the package name was not provided.

Action Examine the service input make sure it provides a valid package name.

ISP.0085.9063 **{0} package does not exist**

ISP.0085.9064 **Node directory does not exist**

ISP.0085.9065 **IOException occurred creating zip for {0} node**

ISP.0085.9066 **{0} package not found**

ISP.0085.9067 **{0} package directory not found**

ISP.0085.9068 **IOException occurred creating zip for {0} package**

ISP.0085.9074 **no such class {0}**

ISP.0085.9075 **Package {0} is not enabled**

ISP.0085.9076 **class not in package**

ISP.0085.9077 **node is not in a package**

ISP.0085.9078E **node belongs to invalid package**

Explanation An application tried to create a service, but the package name specified to contain the service was missing or invalid.

Action Examine the service input and make sure a valid package name is provided.

ISP.0085.9079E **not a valid folder name**

Explanation An application tried to create a new service, but the folder name was missing or invalid.

Action Examine the service input and verify that a valid folder name is provided.

ISP.0085.9080 **node name "{0}" already in use**

ISP.0085.9081 **folder node "{0}" in path "{1}" doesn't exist**

ISP.0085.9082 **folder node "{0}" exists in package**

ISP.0085.9083 **unsupported node type: {0}**

ISP.0085.9084 **Unable to lock: {0}. It has been locked by user {1}.**

ISP.0085.9085 **Unable to modify; node {0} is locked by another user.**

ISP.0085.9086 **Unable to perform the required operation. The destination folder has locked services which share a common Java source file.**

ISP.0085.9087 **Required parameter 'package' is missing**

ISP.0085.9088E **Invalid package version {0}, the accepted format is #.#.#.#.###**

Explanation The supplied package version is an invalid version number. The correct format is "x.y" or "x.y.z" (x, y, z all must be digits from 0-9, e.g. 2.0, 4.0.1 etc.).

Action Examine the service input and make sure a valid package version is provided.

ISP.0085.9089E **Not allowed to add unknown package(s) {0} to dependency list**

Explanation The package that was added to another package's dependency list does not exist on Integration Server.

Action Specify the package name again, this time specifying a package that exists on Integration Server and is enabled.

ISP.0085.9093 **Port must be numeric**

ISP.0085.9094E **Invalid Folder/Service Name**

Explanation The service, folder,or provider Web service descriptor that was added to a port's access list does not exist on Integration Server.

Action Enter the name of the service, folder, or Web service descriptor again, making sure to specify one that exists on Integration Server.

ISP.0085.9095 **Unable to add service to this port**

ISP.0085.9100E	**No password specified**
Explanation	The alias created for a remote server omitted the remote server's password.
Action	Enter a valid password in the password field.

ISP.0085.9101E	**Missing one or more required parameters: $alias, $service**
Explanation	The pub.remote:invoke service failed to execute because one or both of the required "$alias" or "$service" parameters were not supplied.
Action	Examine the service input and ensure that both the parameters are specified.

ISP.0085.9102E	**No such remote server: {0}**
Explanation	The pub.remote:invoke service failed to execute because an invalid server alias was provided.
Action	From the Settings>Remote Servers page of the Server Administrator examine the Remote Servers List and make sure an alias exists for the remote server. If not, create one before invoking the pub.remote:invoke service again.

ISP.0085.9103E	**User session required to invoke a protected remote server**
Explanation	Integration Server encountered a serious internal error because the user session object that invokes the service on the remote server is null.
Action	Contact Software AG Global Support.

ISP.0085.9104E	**Access denied to invoke on remote server {0}**
Explanation	The pub.remote:invoke service failed to invoke the service on the remote server because the current user does not have the proper ACL.
Action	Using the Integration Server Administrator, examine the remote server alias properties as well as the service's Execute ACL setting on the remote server. Make sure that the current user has the proper ACL to invoke the service.

ISP.0085.9105E	**User session required to invoke a remote server with SESSION scope**
Explanation	Integration Server encountered a serious internal error because the user session object that invokes the service on the remote server is null.
Action	Contact Software AG Global Support.

ISP.0085.9106 **Missing required parameter: $jobID**

ISP.0085.9108 **No such job: {0}**

ISP.0085.9110 **No such service is currently loaded {0}**

ISP.0085.9113E **Invalid Date format.Date must be in YYYY/MM/DD format.**

Explanation When attempting to schedule a one-time task, an invalid date or time format was specified.

Action Enter the date and/or time again, this time using the correct format.

ISP.0085.9114 **You specified a date/time in the past**

ISP.0085.9115 **Invalid Time format.Time must be in HH:MM:SS format**

ISP.0085.9116E **Interval must be a positive integer {0}**

Explanation A repeating task could not be scheduled because the specified interval is not valid.

Action Specify the interval again, this time specifying a positive integer.

ISP.0085.9117E **Invalid task type: {0}**

Explanation The WmRoot service wm.server.schedule:createUserTask failed to execute because an invalid task type was supplied. Valid task types are: "once", "repeat", and "complex".

Action Examine the service input and ensure that the "type" parameter specifies a valid task type.

ISP.0085.9118 **Unknown service type: {0}**

ISP.0085.9119 **{0} is missing or package is disabled**

ISP.0085.9120 **Templates directory for package {0} could not be created**

ISP.0085.9121 **Template file exists but is not writable**

ISP.0085.9123U **nobody to send message to**

Explanation Integration Server failed to invoke a service on the remote server using the e-mail port because the "to" parameter was not supplied.

Action Examine the logic to make sure that it passes the correct input to the "to" parameter when invoking services remotely using the e-mail listener.

ISP.0085.9124U **no attachment**

Explanation Integration Server failed to invoke a service on the remote server using the e-mail port because the "attachments" parameter was not supplied.

Action Examine the logic to make sure that it passes the correct input to the "attachments" parameter when invoking services remotely using the e-mail listener.

ISP.0085.9125U **attachments must be of type Values[]**

Explanation Integration Server failed to invoke a service on the remote server using the e-mail port because the input for the "attachments" parameter was not of Values[] type.

Action Examine the logic to make sure that it passes the correct Values[] input to the "attachments" parameter when invoking services remotely using the e-mail listener.

ISP.0085.9126E **Invalid attachment file {0}**

Explanation Integration Server failed to invoke a service on the remote server using the e-mail port because the file attachment specified in the "filename" parameter does not exist in the system.

Action Examine the logic to make sure that it passes a valid file to the "filename" parameter and make sure that it exists in the file system.

ISP.0085.9127 **No filename nor content included in the attachment!**

ISP.0085.9129 **An error was encountered removing {0}**

ISP.0085.9131E **Not allowed to add empty package version, the accepted format is *.***

Explanation The package dependency list does not specify a version for the package.

Action Enter a valid package version in the format "x.y" or "x.y.z" (x, y, z all must be digits from 0-9, e.g. 2.0, 4.0.1 etc.).

ISP.0085.9132 **Unable to perform operation. {0} has entities locked by another user. Please unlock these entities before performing this operation**

ISP.0085.9133 **A required parameter {0} was not supplied**

ISP.0085.9135 **The Universal Name {0} is already defined for {1} in the registry**

ISP.0085.9136 **The Universal Name {0} is already defined as a Service or Document**

ISP.0085.9139E **Cannot {0} changes because the file(s) representing {1} may have been changed to 'Read-Only'. To {0} changes, change the following file(s) from 'Read-Only' to 'Read/Write' either manually or through a source control system: {2}**

Explanation Integration Server could not compile the Java or C service, possibly because the files have changed to Read-Only.

Action Examine the file permissions and change the file permission from Read-Only to Read/Write, either manually or through a source control system.

ISP.0085.9140 **Unable to lock: {0}. It might be locked by another user.**

ISP.0085.9141E **The Universal Name {0} contains an invalid character**

Explanation This is an internal error.

Action Contact Software AG Global Support.

ISP.0085.9145E **Invalid input**

Explanation A WmRoot service failed to execute because the service input is not of the type required by the service.

Action Examine the error stack trace to determine the exception that was thrown and the service that threw it. For example, the service may require an IData object, but the supplied input was not an instance of IData.

ISP.0085.9146 **Cannot schedule service. Input has unsupported datatypes**

ISP.0085.9147E	**Missing required parameter: 'header'**
Explanation	Integration Server encountered an internal error.
Action	Contact wSoftware AG Global Support.

ISP.0085.9148E	**'header' must be of type IData**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISP.0085.9149	**Cannot perform operation without Read ACL privileges on {0}**

ISP.0085.9150	**Cannot perform operation without List ACL on package {0}**

ISP.0085.9151	**Cannot set Execute ACL {1} on {0}. You do not have permission to access the {1} ACL.**

ISP.0085.9152	**Cannot set List ACL {1} on {0}. You do not have permission to access the {1} ACL.**

ISP.0085.9153	**Cannot set Read ACL {1} on {0}. You do not have permission to access the {1} ACL.**

ISP.0085.9154	**Cannot set Write ACL {1} on {0}. You do not have permission to access the {1} ACL.**

ISP.0085.9155	**Cannot set List ACL {1} on package {0}. You do not have permission to access the {1} ACL.**

ISP.0085.9156E	**Cannot perform operation without List ACL privileges on {0}**
Explanation	You do not have List access to the element that you tried tried to lock for editing or the service you attempted to view.
Action	Contact the Administrator of the Integration Server to request List ACL permission for the service or element.

ISP.0085.9157	**Cannot perform operation without Write ACL privileges on {0}**

ISP.0085.9158 **Required parameter "{0}" is missing in invoke of {1}**

ISP.0085.9159 **Invalid input. "{0}" is a required parameter of type IData**

ISP.0085.9160 **Invalid input. "{0}" is a required parameter of type String**

ISP.0085.9161 **Invalid input. "{0}" must be of type String**

ISP.0085.9162 **Invalid input. "{0}" must be a positive integer**

ISP.0085.9163 **Invalid input. "{0}" must be true or false**

ISP.0085.9164 **Folder {0} not found**

ISP.0085.9165 **Unable perform the operation because Broker reports: {0}**

ISP.0085.9166E **Not a valid condition type**

Explanation An invalid condition type was provided. The condition type must be "simple" or "join."

Action Examine the service input and ensure that the condition type provided is "simple" or "join."

ISP.0085.9167E **Not a valid trigger name. Trigger name must be of type String**

Explanation An invalid trigger name was provided. The trigger name must be of type String.

Action Examine the service input and ensure that the trigger name is of type String.

ISP.0085.9168 **Specified trigger name does not exist: {0}**

ISP.0085.9169 **Could not validate data corresponding to publishable document: {0}**

ISP.0085.9170 **Trigger condition not satisfied by this document: {0}**

ISP.0085.9171E **Not a valid condition name. Condition name must be of type String**

Explanation During a trigger test, Integration Server encountered an invalid condition name. The condition name must be of type String.

Action Examine the service input and ensure that the condition name is of type String.

ISP.0085.9172E **Specified condition name does not exist: {0}**

ISP.0085.9173 **Trigger condition not satisfied. All documents must be submitted incase of ''AND'' join type**

ISP.0085.9174 **Package ''{0}'' does not exist.**

ISP.0085.9175 **Trigger condition ''{0}'' does not have a service**

ISP.0085.9176 **Trigger condition ''{0}'' does not have a document type; A trigger condition must have at least one document type**

Explanation To be considered valid, a trigger condition must identify at least one document type.

Action Edit the trigger condition to specify a document type.

ISP.0085.9177 **''{0}'' does not exist or it is not a service**

ISP.0085.9178 **Document type ''{0}'' does not exist**

ISP.0085.9179 **''{0}'' is not a publishable document type.**

ISP.0085.9184 **Node ''{0}'' is not writable.**

ISP.0085.9185 **Invalid filter ''{0}'' for document type ''{1}'': {2}**

ISP.0085.9186	**Multiple join conditions are not allowed in a single trigger.**
ISP.0085.9187	**Could not copy folder completely: {0}**
ISP.0085.9188	**Could not delete folder completely: {0}**
ISP.0085.9189	**Could not move folder completely: {0}**
ISP.0085.9200	**Reference(s) for "{0}" could not be automatically updated, because the element(s) are currently locked.**
ISP.0085.9201	**Internal reference(s) could not be automatically updated.**
ISP.0085.9202	**Target node "{0}" already exists.**
ISP.0085.9203	**Errors occurred while updating remote aliases ({0} of {1} updates failed). See server logs for more details.**
ISP.0085.9204	**Local update failed: {0} (Note: The cluster synchronization will not run until all local errors are resolved.)**
ISP.0085.9205	**Password input is required**
ISP.0085.9206	**Password input must be WmSecureString**
ISP.0085.9207	**Old password input is required**
ISP.0085.9208	**New password input is required**

ISP.0085.9210	**Host Name not specified**
ISP.0085.9211	**No WSDL specified: wsdlURL or wsdlString input is required**
ISP.0085.9212	**Provided package name is null**
ISP.0085.9213	**Provided name is null**
ISP.0085.9215	**Invalid SOAPBinding found: {0}**
ISP.0085.9216	**Cannot schedule service. Error is : {0}**
ISP.0085.9217	**Cannot schedule service. Please contact your System Administrator**
ISP.0085.9218	**The Lateness Action option that you have selected is invalid for this Schedule Type**
ISP.0085.9219	**This One time task was suspended since it was overdue. It cannot be resumed**
ISP.0085.9220	**The lateness time that you have selected is invalid for this Lateness Action. Overdue time must be 0 minutes for 'Run the task immediately' Overdue option and must be greater than 0 minutes for 'Suspend and wait for administrator action' and 'Skip and run at next scheduled time' Overdue options.**
ISP.0085.9232	**No such user present: {0}**
ISP.0085.9233	**Cannot update child task**
ISP.0085.9235	**Interval time is greater than or equal to the difference between the start time and end time.**

ISP.0085.9258 **Web Services Descriptor name not specified, or Web Services Descriptor not found**

ISP.0085.9259 **Web Services Descriptor is not a Consumer, no WSConnectors exist.**

ISP.0085.9260 **Web Services Connector {0} was not deleted. Reason= {1}.**

ISP.0085.9261 **Implicit and Explicit Universal names of the node are identical. The Universal name is registered for the node {1}**

ISP.0085.9263E **Unable to get information for user/certificate mapping: {0}**

Explanation An error was enountered while getting details for a certificate. The error may have occurred while reading from the database or while constructing an X509Certificate object. See the error message for details.

Action If it is a database error, go to the Settings > JDBC Pools page and use the Test button for the ISInternal functional alias to verify that you can still connect to the database. If you can, it may have been a transient error. Try displaying or importing this certificate again. If you cannot, contact your DBA to troubleshoot your database connection problem. If it is not a database error, contact Software AG Global Support.

ISP.0085.9264 **Cannot resume the task as the User {0} is disabled.**

ISP.0085.9265 **Cannot resume the task as the User {0} is removed.**

ISP.0085.9268E **A positive integer must be provided for the port**

ISP.0085.9269 **User Name for Transport not specified**

ISP.0085.9270 **User Name for WS Security not specified**

ISP.0085.9273 **URL must begin with "http:" or "https:"**

ISP.0085.9274	**HTTP method is null**
ISP.0085.9275	**only use one of: data.stream, data.bytes or data.mimeStream on a POST**
ISP.0085.9276	**do not use: data.stream, data.bytes or data.mimeStream on a GET**
ISP.0085.9277	**Invalid private key provided**
ISP.0085.9278	**Invalid certificate chain provided**
ISP.0085.9279	**Invalid partner certificate provided**
ISP.0085.9280	**invalid HTTP method: {0}**
ISP.0085.9281	**Http Error: {0} - {1}**
ISP.0085.9282	**Unable to modify; node {0} is system locked.**
ISP.0085.9284	**Invalid Date or Time.**
ISP.0085.9285	**Found unresolved dependent services: {0}**
ISP.0085.9289	**Remote Invoke not licensed.**
ISP.0085.9290	**Transport Type not specified**
ISP.0085.9291	**Binding with style="rpc" and use="encoded" is not supported for SOAP version 1.2. Binding {0} ignored.**
Explanation	Integration Server does not support RPC/Encoded for SOAP version 1.2. Integration Server ignores bindings that specify this style/use.
Action	No action is required.

ISP.0085.9292	**Bindings or operations with mixed "use" are not supported**
ISP.0085.9293	**Host Name must be ASCII characters**
ISP.0085.9294	**User Name for Transport must be ASCII characters**
ISP.0085.9295	**Password for Transport must be ASCII characters**
ISP.0085.9296	**User Name for WS Security must be ASCII characters**
ISP.0085.9297	**Password for WS Security must be ASCII characters**
ISP.0085.9299W	**Binding with style="document" and use="encoded" is not supported. Binding {0} ignored.**
ISP.0085.9300	**The HTTP URL alias "{0}" is already registered for the path: {1}**
ISP.0085.9301	**A required parameter {0} was not supplied**
ISP.0085.9302	**No valid bindings found in the WSDL.**
ISP.0085.9303	**No Valid services found in the WSDL. The WSConnector may not work until a valid _url is given as input.**
ISP.0085.9304	**HSM based Keystore is not supported**
ISP.0085.9305	**Unsupported ExtensibleElement ''{0}'' found in Operation ''{1}'' and SOAPBinding ''{2}''**

ISP.0085.9306 **SOAP Action "{0}" already found in Operation "{1}" and Binding "{2}". SOAP Action must be unique for Operation and or Binding for a specified SOAP Version.**

ISP.0085.9307 **"{0}" is not a valid HTTP URL Alias name. "{1}" leading character prohibited.**

ISP.0085.9308 **"{0}" is not a valid HTTP URL Alias target path. "{1}" leading character prohibited.**

ISP.0085.9309 **"{0}" is not a valid HTTP URL Alias name. "{1}" character prohibited.**

ISP.0085.9310 **"{0}" is not a valid HTTP URL Alias target path. "{1}" character prohibited.**

ISP.0085.9311 **"{0}" is not a valid HTTP URL Alias name. Space character prohibited.**

ISP.0085.9312 **"{0}" is not a valid HTTP URL Alias target path. Space character prohibited.**

ISP.0085.9313 **"{0}" is not a valid alias name. HTTP URL Alias must not start with "{1}".**

ISP.0085.9314 **"{0}" is not a valid HTTP URL Alias target path. URL path must not start with "{1}".**

ISP.0085.9343E **Deployment activation for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.**

Explanation The deployment was not activated due to the reason specified in the Integration Server logs.

Action See the Integration Server logs for more information.

ISP.0085.9344E **Artifact delivery for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.**

Explanation The artifacts relating to the specified deployment ID were not delivered due to the reason specified in the Integration Server logs.

Action See the Integration Server logs for more information.

ISP.0085.9345E **Deletion of artifacts delivered for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.**

Explanation The artifacts relating to the specified deployment ID were not deleted due to the reason specified in the Integration Server log.

Action See the Integration Server logs for more information.

ISP.0085.9346E **The deletion of artifacts for checkpoint ID {0} failed with an exception. For more information, see the Integration Server logs.**

Explanation The artifacts associated with the specified checkpoint ID could not be deleted due to the reason specified in the Integration Server log.

Action Check the Integration Server log for details.

ISP.0085.9364I **There are no assets for the specified checkpoint ID: {0}. Deployer cannot activate checkpoint.**

ISP.0085.9365E **Extraction of assets for checkpoint ID {0} failed for the composite {1}. For more information, see the Integration Server logs.**

Explanation Assets for the specified checkpoint ID could not be extracted due to the reason specified in the Integration Server log.

Action Check the Integration Server log for details.

ISP.0085.9370I **There are no assets for the specified deployment ID: {0}. Deployer cannot activate deployment.**

ISP.0085.9372E **Checkpoint operation for the checkpoint ID {0} was not successful. For more information, see the Integration Server logs.**

Explanation The checkpoint operation failed due to the reason specified in the Integration Server log.

Action Check the Integration Server log for details.

ISP.0085.9375E **Checkpoint activation for the checkpoint ID {0} was not successful. For more information, see the Integration Server logs.**

Explanation The checkpoint could not be created due to the reason specified in the Integration Server log.

Action Check the Integration Server log for details.

ISP.0085.9376E	**Checkpoint activation for the checkpoint ID {0} failed with an exception. For more information, see the Integration Server logs.**
Explanation	The checkpoint activation failed due to the reason specified in the Integration Server logs.
Action	See the Integration Server logs for more information.

ISP.0085.9384E	**Missing required parameter: {0}**
Explanation	A required parameter was not supplied.
Action	Supply a value for the missing parameter and execute the service again.

ISP.0090.0006	**recursive IData reference key:'{0}'**

ISP.0090.0007	**{0} recursive IDataCodable reference key:'{1}'**

ISP.0091.0001	**{0} in {1} minutes or as soon as idle**

ISP.0091.0002	**Pending shutdown/restart request has been canceled**

ISP.0091.0003	**Grace period has expired. Server is shutting down.**

ISP.0091.0004	**Grace period has expired. Server is restarting.**

ISP.0108.0008W	**Encryption and Signing key pairs have been updated: {0}**
Explanation	The encryption certificate in the user's profile is not synchronized with the one in the JNDI directory. In this case, the signing and encryption key pairs are updated and this warning message is displayed.
Action	Ensure that the encryption certificates are synchronized with those available in the JNDI directory.

ISP.0108.0009W	**Could not check profile "{0}" for key pair update: {1}**
Explanation	When the encryption certificates in the user's profile are not synchronized with those available in the JNDI directory, the signing and encryption key pairs are updated. This warning message is displayed when there are errors when accesing the LDAP directory while updating the key value pairs.
Action	Contact Software AG Global Support.

ISP.0147.0006E	**Error while closing sftp session: Details: {0}**
Explanation	The session key that you specified has expired.
Action	Ensure that the session corresponding to this session key exists and has not expired.

ISP.0147.0007E	**Error in sftp session sweeper thread. Details: {0}**
Explanation	Integration Server encountered an error in the SFTP session sweeper thread.
Action	Read through the details provided in the error message and take corrective steps.

ISS.0001.0001	**All licenses have been consumed.**

ISS.0001.0002	**{0} License key expired or invalid.**

ISS.0001.0003	**{0} License will expire in {1} days.**

ISS.0001.0004	**Integration Server will shutdown in 30 minutes, unless a valid license key is provided.**

ISS.0001.0005	**Unable to load package {0} due to invalid license for package {1}.**

ISS.0001.0006	**Could not add {0} as dependent package due to invalid license.**

ISS.0001.0007	**Could not load {0} because one of the dependent package is not loaded.**

ISS.0001.0008	**{0} Functionality disabled due to license restrictions.**

ISS.0001.0009	**License key file is read-only. License settings cannot take effect until you make the file read/write.**

ISS.0001.0010	**The license key is not valid with this version of Integration Server. License key is version {0} and Integration Server is version {1}.**

ISS.0001.0011U **The Integration Server is not licensed by the current license key.**

Explanation Integration Server has reached its client limit. Your license for Integration Server allows only a certain number of sessions to be used at a time. Integration Server issues this message when the number of users trying to use the server exceeds the number specified in the license.

Action Check the number of licensed sessions specified in your Integration Server license. Consider upgrading the license to obtain more user "seats" if the number of users requiring access to your Integration Server has increased.

ISS.0002.0002E **Error loading LDAP settings: {0}**

Explanation Integration Server encountered an IOException while reading the ldap.cnf file.

Action Check to make sure that the operating system user that is running Integration Server has permission to read and write to the ldap.cnf file. In addition, make sure that the ldap.cnf file is a valid XML file and has not been corrupted in some way. As a last resort, delete the ldap.cnf file and reconfigure the LDAP settings from the Server Administrator.

ISS.0002.0003E **Error saving LDAP settings: {0}**

Explanation An IOException occurred while Integration Server was writing the ldap.cnf file.

Action Check to make sure that the operating system user that is running Integration Server has permission to read and write to the ldap.cnf file and to the server config directory. In addition, make sure that there is sufficient disk space and quota space for creating and writing a new file.

ISS.0002.0005W **LDAP User Manager enabled, but no LDAP directories are configured**

Explanation The Integration Server is attempting to perform operations that require a connection to an LDAP server, but the Integration Server is only partially configured to use LDAP. Specifically, the configuration does not include a list of LDAP directories to which the Integration Server can connect.

Action Use the Integration Server Administrator to configure the Integration Server to connect to one or more LDAP directories. For more information about working with LDAP, refer to the webMethods Integration Server documentation.

ISS.0002.0007W **Query returned multiple DNs for a single user with filter ({0}={1})**

Explanation The values specified in the Query DN field on the LDAP directory settings screen are not sufficient to uniquely identify a user. Integration Server uses this field to build a query to send to the LDAP server so that the LDAP server can authenticate the user.

Action Make sure that the user root, user property, and user names specified on the Query DN field are not ambiguous.

ISS.0002.0008E **Could not get a connection from the pool in the time allowed**

Explanation Integration Server was unable to connect to the LDAP server because the request to obtain a connection timed out. This error can occur if the LDAP directory server is slow, is under high load, or is experiencing high latency, and there are insufficient connections in the connection pool to meet demand.

Action This error is probably transient. It is usually sufficient to wait a few seconds and try the operation again (for example logging in, executing a service) when the load has decreased and resources have become available. If the problem persists, then from the LDAP Directory Settings page of the Server Administrator, try increasing the size of the LDAP connection pool. Also check to make sure the LDAP directory server is properly configured and that the network is able to handle the load being placed on it by the application.

ISS.0002.0009E **Unable to open a connection to {0}**

Explanation The Integration Server was unable to open a connection to the indicated LDAP directory server.

Action To resolve this issue, do the following:

- Make sure the LDAP server is running and that the Integration Server has permission to connect to it.

- Make sure that the connection parameters specified on the LDAP Settings screen of the Server Administrator are properly configured.

- If you are using SSL, make sure that the directory URL specified on the LDAP Settings screen specifies an SSL port on the LDAP server and that both the Integration Server and LDAP server support SSL.

- If you are specifying credentials, make sure the principal specified on the LDAP Settings screen of the Server Administrator is correct and that the password matches. This error can also occur if the Integration Server cannot establish a connection to the LDAP server within the configured time limit because of a problem such as network latency. For more information about connecting the Integration Server to an LDAP server, see the webMethods Integration Server documentation.

ISS.0002.0010E **Error querying for user {0}: {1}**

Explanation During a user log in, the Integration Server encountered an error while performing a query to obtain the user's Distinguished Name.

Action In the Server Administrator, on the LDAP Settings screen for the LDAP directory, ensure that the user root and user properties are set correctly.

ISS.0002.0013W **Found group {0}, but it contained no attribute {1}**

Explanation During ACL mapping, Integration Server determined that the value specified in the group attribute field does match the attribute values of the group that Integration Server found.

Action Make sure the group name attribute field contains a valid group name attribute.

ISS.0002.0014E **Error querying for groups on {0} with root {1} and filter {2}: {3}**

Explanation Integration Server encountered an error when looking for LDAP groups to map to an Integration Server ACL.

Action If the text of the exception indicates a connection issue, try performing the mapping later. Otherwise, check the values specified for group name, filter, and group name attribute on the Map Groups to ACLs screen.

ISS.0002.0015E **Unable to create ACL mapping: LDAP User Manager not initialized**

Explanation An attempt to map an LDAP group to an ACL failed because the LDAP User Manager function of the Integration Server is not running. This error occurs when one user disables LDAP while another user is trying to perform ACL mapping.

Action Use the Integration Server Administrator to check the External User Management Configuration screens for possible configuration problems. In addition, try checking the server and error logs for messages about problems with the LDAP manager. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.

ISS.0002.0016E **Unable to create ACL mapping: ACL {0} not found**

Explanation An attempt to map an LDAP group to an ACL failed because the ACL specified on the Map Groups to ACLs screen does not exist. This error occurs if one user deletes the ACL in question when another user is trying to map an LDAP group to it.

Action Determine why the other user changed the Integration Server configuration then reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.

ISS.0002.0017E **Unable to retrieve password for handle {0}: {1}**

Explanation The Integration Server is trying to connect to an LDAP server. As part of connecting, the Integration Server needs to send a password to the LDAP server. This error occurs when the Integration Server cannot find the password it stored for this purpose. A likely cause is that the ldap.cnf file was moved from one system to another, but the stored outbound passwords were not.

Action Make sure the Outbound Password Manager is properly configured, and that its files are readable by the Integration Server process. If the Outbound Password Manager is set up correctly, and the error still occurs, go to the LDAP Configuration screen of the Server Administrator and reenter the existing password.

ISS.0002.0018E **Unable to store password for handle {0}: {1}**

Explanation The Integration Server was unable to store the password needed to connect to an LDAP server. The Integration Server must supply passwords to many of the applications it connects to. It stores these outbound passwords in encrypted form on the Integration Server. This error occurs when an administrator enters or changes the password, but the Integration Server cannot subsequently store it.

Action Check to see if the Integration Server is properly configured to handle outbound passwords. Make sure that the following outbound password configuration files reside on the Integration Server and are readable and writable: config/txnPassStore.dat, config/empw.dat, config/configPassman.cnf and config/passman.cnf. Refer to the webMethods Integration Server documentation for more information.

ISS.0002.0019E **Unable to delete password for handle {0}: {1}**

Explanation An administrator updated the Integration Server configuration so that it no longer connects to an LDAP server. As part of this process, the Integration Server tried to delete the password it uses to connect to the LDAP server, but was unable to. The Integration Serve deletes the LDAP server from the configuration, but the password remains, in encrypted form, on the Integration Server. The most likely cause is that the files used to store outbound passwords on the Integration Server are read-only.

Action Refer to the webMethods Integration Server documentation for more information about outbound passwords and the files used to store them. Then try to determine why the files are in read-only mode.

ISS.0002.0020E **Unable to check password: LDAP User Manager not initialized**

Explanation The Integration Server tried to check the password of an LDAP user but could not because the LDAP user manager is not running. This error occurs when one user updates the Integration Server configuration to disable LDAP directory use while another user is trying to perform an LDAP operation.

Action Determine why the other user changed the Integration Server configuration. Then, reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.

ISS.0002.0021E **Unable to check group membership: LDAP User Manager not initialized**

Explanation The Integration Server tried to find members of an LDAP group but could not because the LDAP user manager is not running. This error occurs when one user updates the Integration Server configuration to disable LDAP directory use while another user is trying to perform an LDAP operation.

Action Determine why the other user changed the Integration Server configuration. Then, reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.

ISS.0002.0023E	**Error initializing a connection to {0}: {1}**
Explanation	The Integration Server encountered an exception while trying to connect to the indicated LDAP server.
Action	Check the following: - Make sure the LDAP directory server is running and that the Integration Server has permission to access it. - Make sure the parameters on the External User Management Configuration screens of the Server Administrator have been properly set.

ISS.0002.0024W	**Error closing connection to {0}: {1}**
Explanation	Integration Server encountered an exception while trying to connect to the indicated LDAP server. Integration Server will clean up the connection.
Action	No action is required.

ISS.0002.0030E	**While attempting automatic LDAP configuration, some invalid settings were found. It is necessary to complete the configuration manually.**
Explanation	When you upgrade from Integration Server release 6.1 or earlier to Integration Server release 6.5 or later, the upgrade process tries to automatically configure the external user management facilities in your new Integration Server based on these settings in your old Integration Server. To determine the old configuration settings, the upgrade process looks for the following properties: watt.server.ldap.server watt.server.ldap.attr.userId watt.server.ldap.attr.member This error indicates that the upgrade process was unable to find one of these properties. The automatic configuration does not continue.
Action	Go to the Security > Users and Groups > External User Management Configuration screen of the Server Administrator and configure the Integration Server to use an external LDAP directory. For additional information, refer to the webMethods Integration Server documentation.

ISS.0002.0034E	**Invalid credentials connecting to {0} as {1}**
Explanation	The Integration Server encountered an Authentication Exception because the indicated user could not log in to the indicated LDAP server.
Action	This error can occur for a number of reasons. Make sure that the DN of the user is valid, the credentials (i.e. password) specified are valid, and the user account is enabled.

ISS.0002.0035E	**Invalid credentials connecting to {0} as {1}: {2}**
Explanation	The Integration Server encountered an Authentication Exception because the indicated user could not log in to the indicated LDAP server. The last part of the message <errorMessage> includes extra information provided by the LDAP server about the error. You can use this data to audit authentication errors when the Integration Server connects to Microsoft Active Directory.
Action	This error can occur for a number of reasons. Check to make sure that the DN of the user is valid, the credentials (i.e. password) specified are valid, and the user account is enabled. Note: The errorMessage portion of this error displays only if the watt.server.ldap.extendedMessages property in the server.cnf file is set to true. If you do not find the extended message useful, you can disable extended messaging by setting this property to false.

ISS.0002.0040E	**Error querying for users : {0}**
Explanation	Error while listing users from the LDAP server, a runtime exception occurred while querying users for the provided search criteria.
Action	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.

ISS.0002.0041E	**Error querying for users : {0}**
Explanation	Some errors occurred while searching for a particular group, or a search string in the LDAP Server.
Action	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.

ISS.0002.0042W	**Bailing out query as {0} is null or empty.**
Explanation	While listing users from the LDAP server, either the directory name suffix or directory name prefix returned from the server is null or empty.
Action	Ensure that the LDAP configuration is correct and the LDAP server is not disconnected.

ISS.0002.0044E	**Error querying for user(s) on {0} with search root {2}: {3}**
Explanation	Error while listing users from the LDAP server, a runtime exception occurred while querying users for the provided search criteria.
Action	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.

ISS.0002.0045W	**Found No Group on quering on {0} with root {1} and filter {2}**
Explanation	No group is found in the LDAP server for the search criteria.
Action	Refine the search query to get the required result.

ISS.0002.0046E	**Selected group {0} does not exist.**
Explanation	The Integration Server group associated with the LDAP configuration is deleted.
Action	Ensure that the group selected while configuring LDAP exists. If the group does not exist, you can take one of the following actions: 1) Modify the LDAP configuration to specify another group. 2) Add a group with the same name as the deleted group that was associated with the LDAP configuration.

ISS.0002.9001E	**LDAP User Manager not initialized**
Explanation	A user is trying to execute an operation on the LDAP server but LDAP user manager is not initialized.
Action	Check the LDAP settings.

ISS.0002.9002E	**Error saving new ACL Mappings: {0}**
Explanation	A runtime exception occurred while adding new mappings to the LDAP Server.
Action	Ensure that the mapping strings are correct (they should be in the following format - name; dn), the LDAP server is configured properly and it is running.

ISS.0003.9001	**Transformation: Required argument "{0}" missing.**

ISS.0003.9002	**Transformation: No XML source provided**

ISS.0003.9003	**Transformation: No result type specified**

ISS.0003.9004	**Transformation: No result filename specified**

ISS.0003.9005 **Transformation: No result system ID specified**

ISS.0003.9006 **Transformation: PipedInputStreamException - {0}**

ISS.0003.9007 **Transformation: HTTPS URL error - {0}**

ISS.0003.9008 **Transformation: HTTPS URL error - Response returned with HTTP protocol error {0}.**

ISS.0003.9009 **XSLT Samples: No XSLT input paramters provided**

ISS.0003.9010 **XSLT Service: No valid input provided**

ISS.0003.9011 **XSLT Service: No associated .xsl file for this service**

ISS.0006.0030E **Unable to set javax.net.ssl.keyStore: Keystore location could not be retrieved from {0}.**

Explanation Integration Server could not set the javax.net.ssl.keyStore system property because Integration Sever could not retrieve the keystore location from the keystore file. Integration Server looks in the keystore file associated with the specified keystore alias. At run time, the {0} in the error message is replaced with the name of the keystore alias assigned to the watt.sever.ssl.keyStoreAlias parameter.

Action Make sure the keystore alias assigned to the watt.server.ssl.keyStoreAlias parameter contains the correct keystore details including the correct location of the keystore file.

ISS.0006.0031E **Unable to set javax.net.ssl.keyStorePassword: Keystore password could not be retrieved from {0}.**

Explanation Integration Server could not set the javax.net.ssl.keyStorePassword system property because Integration Server could not retrieve the password from the keystore file. Integration Server looks in the keystore file associated with the specified keystore alias. At run time, the {0} in the error message is replaced with the name of the keystore alias assigned to the watt.server.ssl.keyStoreAlias parameter.

Action Make sure the keystore alias assigned to the watt.server.ssl.keyStoreAlias parameter contains the correct keystore details including the correct password for accessing the keystore file.

ISS.0006.0032E	**Unable to set javax.net.ssl.trustStore: Truststore location could not be retrieved from {0}.**
Explanation	Integration Server could not set the value of the javax.net.ssl.trustStore system property because Integration Server could not retrieve the truststore location from the truststore file. Integration Server looks in the truststore file associated with the specified truststore alias. At run time, the {0} in the error message is replaced with the name of the truststore alias assigned to the watt.server.ssl.trustStoreAlias parameter.
Action	Make sure the truststore alias assigned to the watt.server.ssl.trustStoreAlias parameter contains the correct truststore details including the correct location of the truststore file.

ISS.0006.0033E	**Unable to set javax.net.ssl.trustStorePassword: Truststore password could not be retrieved from {0}.**
Explanation	Integration Server could not set the javax.net.ssl.trustStorePassword system property because Integration Server could not retrieve the password for the truststore. Integration Server looks in the truststore file associated with the specified truststore alias. At run time, the {0} in the error message is replaced with the name of the truststore alias assigned to the watt.server.ssl.keyStoreAlias parameter.
Action	Make sure the truststore alias assigned to the watt.server.ssl.trustStoreAlias parameter contains the correct truststore details including the correct password for accessing the truststore file.

ISS.0006.0034E	**Error setting javax.net.ssl properties: {0}**
Explanation	The javax.net.ssl system properties cannot be set because the keystore and/or truststore is invalid.
Action	Use the exception included in the error message to determine why the javax.net.ssl properties could not be set. Actions to be taken might include the following:- Making sure the keystore or truststore file is valid and contains the correct information. - Making sure that the keystore alias assigned to watt.server.ssl.keyStoreAlias contains the correct details for the keystore. - Making sure that the truststore alias assigned to watt.server.ssl.trustStoreAlias contains the correct details for the truststore.If the keystore file is invalid, create a new keystore, kesystore alias, truststore, and truststore alias. Use the new keystore alias as the value of watt.server.ssl.keyStoreAlias. Use the new truststore alias as the value of watt.server.ssl.trustStoreAlias.If the truststore file is invalid, create a new truststore and truststore alias and use the new alias as the value of watt.server.ssl.trustStoreAlias.

ISS.0007.0001E	**Access Denied. User "{0}" does not have permissions to invoke service: {1}.**
Explanation	The user does not have permission to invoke an Integration Server resource. Read through the details provided in the server log to find the user name and the name of the service.
Action	To grant permission to the user, either add the user to a group that is listed in the Execute ACL assigned to the service, or add one of this user's groups to the Execute ACL assigned to the service.

ISS.0007.0002E	**Access Denied. No permissions to invoke service ({0}) on port "{1}".**
Explanation	The Access Mode for the specified port is configured to Deny by Default. With this configuration, the port only allows the services explicitly listed in the Allow List. The identified service is not in the Allow List of the identified port.
Action	If this service should be allowed on this port, add the service to the Allowed Services list of the port.

ISS.0010.8050	**Error while connecting to the remote authorization server using the remote server alias "{0}". Error details: {1}**
Explanation	Integration Server cannot connect to the specified remote OAuth authorization server.
Action	Edit the remote server alias and ensure that all the parameters are specified correctly. If needed, run a test of the remote server alias.

ISS.0010.9016E	**The cache manager required for OAuth operations is not available. Verify that the cache manager initialized successfully and then restart Integration Server**
Explanation	During the initialization of Cache Managers an error was encountered.
Action	Examine the Integration Server Error logs and Server logs for details about the error. Use the information in the logs to correct the error and then restart Integration Server.

ISS.0012.0014E	**Unable to initialize JAAS login context. JAAS configuration file in use: {0}. Error message: {1}. Stack trace: {2}**
Explanation	Integration Server uses IntegrationServer/config/is_jaas.cnf file for its JAAS configuration. If there is any problem loading this file, Integration Server throws this exception.
Action	The entries found in a JAAS configuration file should follow the JAAS syntax. If you made any changes to the IntegrationServer/config/is_jaas.cnf, review your changes and make sure there are no syntax errors in the file.

ISS.0012.0016E	**Initialization of X509ValidatorModule failed with exception: {0}.**
Explanation	The X509ValidatorModule defined in the IntegrationServer/config/is_jaas.cnf file is incorrect.
Action	Review the Integration Server error log for the actual exception. Refer to the webMethods Integration Server documentation for information about how to use this module and correct any errors found.

ISS.0012.0017E	**Authentication failed because the X.509 certificate path validation has failed.**
Explanation	The X509ValidatorModule is enabled in the IntegrationServer/config/is_jaas.cnf file. As a result, Integration Server performed certificate path validation using the information provided, but the client certificates failed the certificate path validation.
Action	Make sure that the truststore used by the X509ValidatorModule contains the intermediary certificates as well.

ISS.0012.0020E	**Authentication failed because the X.509 certificate has been revoked.**
Explanation	The X509ValidatorModule is enabled in the IntegrationServer/config/is_jaas.cnf file. As a result, Integration Server checked the client certificate against the Certificate Revocation List (CRL) and the client certificate was found to be revoked.
Action	Advise the client to resubmit the request using a valid certificate.

ISS.0012.0022E	**Access Denied. Authentication resolved to user "{0}". User is not defined in any of the available user stores.**
Explanation	Integration Server JAAS authentication modules return the username in the Subject. Integration Server then tries to retrieve the definition of this user either locally in its user store, or in Central Users (if configured), or LDAP (if configured). If Integration Server is not able to find the user anywhere, it rejects the client request with this error.
Action	If this user should be allowed accessing Integration Server resources, make sure this user is defined in any of the user stores accessible to Integration Server.

ISS.0012.0023E	**SAML assertion verification failed. The current time {0} violates the "Not Before" setting {1} specified in the SAML assertion.**
Explanation	Integration Server received a SAML assertion that arrived before the "Not Before" setting.
Action	Check the clock time of the issuer. If it is significantly different from the clock time on the Integration Server machine, adjust the Clock Skew value on the Security -> SAML screen.

ISS.0012.0024	**SAML assertion verification failed. The current time {0} violates the "Not On Or After" setting {1} specified in the SAML assertion.**
Explanation	Integration Server received a SAML assertion that arrived later than the "Not On Or After" setting.
Action	Check the clock time of the issuer. If it is significantly different from the clock time on the Integration Server machine, adjust the Clock Skew value on the Security -> SAML screen.

ISS.0012.0025E	**Rejecting SAML assertion from issuer "{0}" because issuer is not configured on the Security > SAML screen.**
Explanation	Integration Server received a SAML assertion from an issuer that has not been configured on the Security -> SAML screen.
Action	Configure the issuer on the Security -> SAML screen.

ISS.0012.0027W	**{0}% or more of maximum number of concurrent stateful sessions are in use. {1} sessions are available.**
Explanation	Integration Server is approaching the threshold for concurrent stateful sessions.
Action	No immediate action is required. Once the limit is reached, all new requests to create stateful sessions will be rejected. You can increase the limit using the Resources screen in the Integration Server Administrator; however, doing so could increase the server's resource requirement.

ISS.0012.0030E	**Rejecting SAML assertion because the subject identified in the SAML assertion is not the one who signed the request.**
Explanation	For security reasons, Integration Server cannot accept requests that are not signed by the subject identified in the SAML assertion.
Action	Sign the message using the subject identified in the SAML assertion.

ISS.0013.0001	**Binding XML. Service {0} was unable to bind incoming XML data**

ISS.0013.0004E	**Registering multipart content handler {0} for service {1}.**
Explanation	The syntax for the watt.server.content.type.mappings parameter is invalid.
Action	Use the correct syntax for this parameter. See Administering webMethods Integration Server for more information about using watt.server.content.type.mappings.

ISS.0014.0001E **Encountered fatal errors while starting License Manager. Shutting down server.**

Explanation Integration Server encountered a serious internal error while validating the license.

Action Contact Software AG Global Support.

ISS.0014.0004 **No listening ports were available. Shutting down server.**

ISS.0014.0009 **Server is unable to determine its own name.**

ISS.0014.0012 **watt.server.fileEncoding unsupported by JVM. Server may be unable to continue.**

ISS.0014.0013 **watt.server.netEncoding unsupported by JVM. Text may not process properly.**

ISS.0014.0014 **watt.server.logEncoding unsupported by JVM. Logging in default encoding.**

ISS.0014.0017 **Warning: {0} when initializing ACL Manager file {1}**

ISS.0014.0021E **Failed to invoke notification callback {0}: {1}**

Explanation Integration Server encountered an error while updating ACLs. Specifically, an error occurred when Integration Server invoked a service that is registered as a notification callback.

Action Make sure that the service being invoked exists and can be executed.

ISS.0014.0022E **Retrying service {0}. Retry count is {1}**

Explanation Integration Server is retrying a service that was previously unsuccessful.

Action No action is required.

ISS.0014.0023E **Available Thread Pool Threshold No Longer Exceeded: {0}% available**

Explanation Integration Server is no longer exceeding the specified threshold for thread pool usage.

Action No action is required.

ISS.0014.0024E **Server Initialization Aborted. See log messages.**

Explanation During start up, Integration Server encountered a serious internal error that caused it to shut down immediately.

Action Make sure that the machine on which Integration Server runs has sufficient disk space. In addition, make sure the operating system user that is trying to start Integration Server has a sufficient space allowance and has read/write permission to the directory on which Integration Server resides.

ISS.0014.0025 **Master password for outbound password encryption has expired. Password was last changed on {0}. The current expiration interval is {1} days**

ISS.0014.0026 **Master password for outbound password encryption expires in {0} days**

ISS.0014.0027 **Unable to remove outbound password handle {0}**

ISS.0014.0028 **Cannot initialize OutboundPasswordManager with null Password Manager**

ISS.0014.0029S **Master password failed a sanity check**

Explanation During Integration Server initialization, the sanity check of the master password for outbound passwords failed. Integration Server uses the master password to encrypt outbound passwords, which the Integration Server uses to connect to applications or systems such as remote Integration Servers, proxy servers, or databases. The outbound passwords are stored in files on Integration Server and encrypted for security purposes. During initialization, Integration Server performs a sanity check of the master password by attempting to use it to decrypt a special, internal string that it previously encrypted using the master password. If the decrypted internal string matches the clear text version of the string, Integration Server knows the correct master password was provided. This error is issued when the decrypted and clear text versions of the string do not match.

Action The sanity check of the master password can fail for a number of reasons:

- The outbound password file is corrupted.

- The master password file is corrupted.

- You mistyped the master password when you were prompted for it.

If you suspect you have mistyped the password, shut down the server and restart it, this time entering the correct password. If this does not correct the problem, refer to the webMethods Integration Server documentation.

ISS.0014.0030S	**Master password updated**
Explanation	The master password, which Integration Server uses to encrypt outbound passwords, has been successfully updated.
Action	No action is required.

ISS.0014.0035S	**OutboundPasswordManager configuration directory cannot be null**
Explanation	Integration Server cannot locate the configuration directory it uses for managing outbound passwords.
Action	Contact Software AG Global Support.

ISS.0014.0039S	**OutboundPasswordManager, {0} caught this: type {1}, msg {2}**
Explanation	The code that Integration Server uses to manage outbound passwords encountered a problem while trying to perform the indicated operation.
Action	If the exception message text does not suggest a solution, contact Software AG Global Support.

ISS.0014.0047	**com.wm.app.b2b.server.DataStore must be initialized before it can be used.**

ISS.0014.0048	**The ISInternal functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.**

ISS.0014.0051	**Cannot aquire the lock.**

ISS.0014.0054	**Error occurred while initializing server: {0}**

ISS.0014.0055	**Cannot acquire an exclusive lock. Another session is holding a shared lock on the requested item.**

ISS.0014.0056	**Cannot acquire an exclusive lock on the requested context. Another session has locked it.**

ISS.0014.0057	**Integration Server is quiesced and is not accepting new requests at this time.**
ISS.0014.0058	**Integration Server has reached the license limit for concurrent sessions.**
ISS.0014.9101	**User does not exist: {0}**
ISS.0014.9102	**No package name specified**
ISS.0014.9104	**A listener must be provided**
ISS.0014.9105	**A listener factory must be provided**
ISS.0014.9106	**A listener factory with {0} is already registered in the {1} package**
ISS.0014.9107	**Attempted to register a factory with an invalid identifying key**
ISS.0014.9108	**Attempted to register a listener with an invalid identifying key**
ISS.0014.9109	**A listener is already registered with the key {0}. The existing listener must be unregistered first**
ISS.0014.9110	**Failed to update listener configuration information**
ISS.0014.9111	**Unregistration failed, could not update the configuration**
ISS.0014.9112	**Service {0} unable to bind incoming XML data**
ISS.0014.9113	**No Valid Active Packages**

ISS.0014.9114 **Package directory for {0} does not exist**

ISS.0014.9115 **Package {0} does not exist**

ISS.0014.9116 **Unable to locate or start compiler**

ISS.0014.9117 **Unable to save file {0} for {1}**

ISS.0014.9118U **ServerReferenceManager can't get session to access object cache**

Explanation Integration Server encountered an internal error with the object cache.

Action Contact Software AG Global Support.

ISS.0014.9119U **Unable to allocate a new thread in the time specified**

Explanation Integration Server has reached the configured limit for the number of new threads it can create. After waiting unsuccessfully for resources to become available, Integration Server issued this ISRuntime exception. This exception usually indicates a transient condition in which resources are temporarily unavailable. If this error occurs during execution of a trigger, and retry is enabled, Integration Server will automatically retry the service. If, after a configured amount of time, the resources are still unavailable, Integration Server throws this exception.

Action If the problem persists, use the Resource Settings page of the Server Administrator to specify thread pool settings that are more appropriate for your environment.

ISS.0014.9120 **Can not set thread pool max to zero or less than min, max={0}, min={1}**

ISS.0014.9121 **Repository config file repository4.cnf not found.**

ISS.0014.9123E **{0} package not reloaded; missing the following assets: {1}**

Explanation An internal error occurred while using the local service development feature in Software AG Designer. An attempt to reload an updated IS asset (flow service, Java service, document type, etc.) failed because the specified IS asset does not exist in the IS namespace. At run time, the {0} in the error message is replaced with the package name and the {1} is replaced with the IS assets that do not exist in the namespace.

Action Contact Software AG Global Support.

ISS.0014.9124E **{0} package not reloaded. {1} already registered in {2}**

Explanation While using the local service development feature in Software AG Designer, an attempt to reload an updated IS asset (flow service, Java service, document type, etc.) failed because Integration Server determined that another package contains an asset with the same name. At run time, the {0} in the error message is replaced with the package name, the {1} is replaced with the IS asset name for which a reload was attempted, and the {2} is replaced with the name of the package that contains the already loaded, identically named asset.

Action Ensure that each IS asset uses a name that is unique across the Integration Server namespace. To rename one of the assets, you might need to disable the package that contains the asset whose name you do not want to change. Change the name of the IS asset in the package that you want to change. Then, re-enable both packages.

ISS.0014.9125E **Primary port change failed. The primary port must be a port associated with the WmRoot package.**

Explanation An attempt to change the primary port failed because the chosen port is associated with a package other than WmRoot.

Action Select a port associated with the WmRoot package as the primary port. Alternatively, change the chosen port to associate it with the WmRoot package and then designate the port as the primary port.

ISS.0014.9126E **Primary port change failed. The primary port must be an enabled port.**

Explanation An attempt to change the primary port failed because the chosen port is not enabled.

Action Select an enabled port as the primary port. Alternatively, enable the chosen port and then designate the port as the primary port.

ISS.0014.9127E **Primary port change failed. The primary port must be an HTTP or HTTPS port.**

Explanation An attempt to change the primary port failed because the chosen port is not an HTTP or HTTPS port.

Action Select an HTTP or HTTPS port to use as the primary port.

ISS.0014.9128E **Primary port change failed. The primary port must be a standard port.**

Explanation An attempt to change the primary port failed because the chosen port was not a standard port. Currently, the only non-standard port type is the diagnostic port.

Action Select a standard HTTP or HTTPS port to use as the primary port. Do not select a diagnostic port to be the primary port.

ISS.0015.0002E	**Error {0} initializing Invoke Manager class {1} from {2}**
Explanation	Integration Server failed to initialize InvokeManager from the configuration file located at <IntegrationServer_dir>/config/invokemanager.cnf file at startup.
Action	Contact Software AG Global Support.

ISS.0015.0003E	**Error {0} initializing Invoke Manager with {2}**
Explanation	Integration Server failed to initialize InvokeManager from the configuration file located at <IntegrationServer_dir>/config/invokemanager.cnf file at startup.
Action	Using a text editor, open the <IntegrationServer_dir>/config/invokemanager.cnf file and make sure that the content is not corrupt. If the error still occurs, consider removing the invokemanager.cnf file and restarting Integration Server.

ISS.0015.0004E	**Service {0} failed ACL access checking for user {1}**
Explanation	The client application failed to invoke the service because the current user did not have the Execute ACL privileges to execute the service.
Action	Using the Integration Server Administrator, examine the ACL settings of the service as well as the ACL group to which the current user belongs. Make sure that the user has the proper ACL settings.

ISS.0016.0006EE	**Cannot cache {0} service. The cache manager {1} is not initialized.**
Explanation	The cache manager SoftwareAG.IS.Services is not initialized.
Action	Check the configuration of the SoftwareAG.IS.Services cache manager.

ISS.0017.0001E	**An error was encountered parsing {0}: {1}. See the Integration Server error log for the full stack trace.**
Explanation	Either the format of XML in the configuration file is invalid, or a specific setting is not allowed.
Action	Read through the details provided in the error message and edit the configuration file to correct the problem.

ISS.0017.0002I	**Cache manager {0} created.**

ISS.0017.0003E	**{0} is required.**
Explanation	A value is required for the indicated parameter.
Action	Supply a value for the parameter.

ISS.0017.0004E	**There is no cache manager named {0}.**
Explanation	There is no cache manager with this name on Integration Server.
Action	Make sure the cache manager name is typed correctly and that it exists on the Integration Server.

ISS.0017.0005E	**There is no cache named {0} in the {1} cache manager.**
Explanation	Integration Server tried to connect to the indicated cache, but there is no cache with this name associated with the cache manager.
Action	Provide the name of a cache that is managed by the supplied cache manager.

ISS.0017.0006I	**Cache {0} created.**

ISS.0017.0007E	**Cache manager names starting with "SoftwareAG" are reserved.**
Explanation	The cache manager could not be created because the name is invalid.
Action	Choose a different name for the cache manager.

ISS.0017.0008I	**Successfully deleted cache manager {0}.**

ISS.0017.0009I	**All elements have been removed from cache {1} of cache manager {0}.**

ISS.0017.0010I	**Disabled cache {1} of cache manager {0}.**

ISS.0017.0011I	**Enabled cache {1} of cache manager {0}.**

ISS.0017.0012E	**Cache manager {0} is not started.**
Explanation	The service failed to execute because the specified cache manager is not available.
Action	Open Integration Server Administrator and go to the Settings > Caching page to verify that the cache manager is started and the cache the service wants to use is enabled.

ISS.0017.0013E	**Cache {1} for cache manager {0} not enabled.**
Explanation	The operation could not be completed because the indicated cache could not be found in the indicated cache manager.
Action	Make sure the cache name is typed correctly and that it is contained in the indicated cache manager.

ISS.0017.0014E	**Cache manager {0} already exists.**
Explanation	The cache manager could not be created because a cache manager with the indicated name already exists on the Integration Server. The name you specify must be unique on the Integration Server.
Action	Enter a new name for the cache manager that is unique to the Integration Server.

ISS.0017.0015E	**The {0} cache manager attempted to connect to a Terracotta Server Array, but the Integration Server license does not allow it. This cache manager will not be usable.**
Explanation	To use this feature, Integration Server must have a license that allows distributed caching.
Action	Obtain the appropriate license from Software AG Global Support and add it to the Integration Server.

ISS.0017.0016E	**If rejoin is enabled, a Terracotta Server Array URL must be supplied.**
Explanation	You selected the Rejoin check box, but did not configure the cache manager to connect to a Terracotta Server Array.
Action	Specify a Terracotta Server Array URL or clear the Rejoin check box.

ISS.0017.0017E	**Cannot use the administrative services to change a system cache manager: {0}.**
Explanation	The cache could not be created because a cache with that name already exists in the cache manager. The name you specify must be unique within the cache manager.
Action	See Administering webMethods Integration Server for more information about system cache managers.

ISS.0017.0018E	**The {0} cache already exists.**
Explanation	The cache could not be created because a cache with that name already exists in the cache manager. The name you specify must be unique within the cache manager.
Action	Enter a name for the cache that is unique within the cache manager.

ISS.0017.0019E	**Cannot delete a system cache manager: {0}.**
Explanation	The cache manager you attempted to delete is a system cache manager and cannot be deleted.
Action	See Administering webMethods Integration Server for more information about system cache managers.

ISS.0017.0020E	**Cache manager name cannot contain any of these characters: ? [ ] / = + < > : ; " , * | ^ @**
Explanation	The cache manager could not be created because the name you specified contains invalid characters.
Action	Specify a new name using valid characters.

ISS.0017.0021E	**Cache manager name cannot start with a '.' or end with a space.**
Explanation	The cache manager could not be created because the name you specified contains invalid characters.
Action	Specify a new name using valid characters.

ISS.0017.0022E	**Cache manager name cannot be an operating system device name.**
Explanation	The cache manager could not be created because the name you specified is a reserved word as specified by your operating system.
Action	Specify a new name for the cache manager. Refer to your operating system's documentation for a list of reserved words.

ISS.0017.0023E	**An error was encountered updating {0}: {1}. See the Integration Server error log for the full stack trace.**
Explanation	While attempting to enable or disable clustering for the Integration Sever, an error occurred while updating the Terracotta Cache Manager configuration files.
Action	Review the error details provided in the message and in the Integration Server error log. After correcting the issue that caused the error, use Integration Server Administrator to enable or disable clustering for the Integration Server.

ISS.0017.0024E	**When a cache is distributed, Overflow to Disk, Overflow to Off-heap and Persist to Disk cannot be selected.**
Explanation	The Overflow to Disk, Overflow to Off-heap and Persist to Disk options are not allowed with distributed caches.
Action	If you are creating a distributed cache, remove the values from the Overflow to Disk, Overflow to Off-heap and Persist to Disk fields.

ISS.0017.0026E	**Cache manager name is null in {0}. The cache manager will not be used**
Explanation	A cache manager configuration file was supplied with a null cache manager name.
Action	Edit the configuration file and provide a name for the cache manager.

ISS.0017.0027E **A cache manager named "{0}" has already been loaded from {1}. The name cannot also be used in {2}. The cache manager in {2} will be ignored.**

Explanation More than one configuration file in the Integration Server_directory\config\Caching directory contains the specified cache manager. Integration Server cannot load two instances of the same cache manager. The cache manager that is already loaded is being used. The cache manager in the second configuration file will be ignored.

Action Either remove one of the configuration files or change the cache manager name in one of the configuration files.

ISS.0017.0029I **Cache manager {0} successfully started.**

ISS.0017.0030E **Cache manager {0} successfully reloaded.**

Explanation A value is required for the indicated parameter.

Action Supply a value for the parameter.

ISS.0017.0031I **Cache manager {0} is already running.**

ISS.0017.0032I **Cache manager {0} is not running.**

ISS.0017.0033E **Cannot enable a system cache.**

Explanation The cache you attempted to enable is a system cache. System caches are used by internal processes and cannot be modified.

Action See Administering webMethods Integration Server for more information about system caches.

ISS.0017.0034E **Cannot disable a system cache.**

Explanation The cache you attempted to disable is a system cache. System caches are used by internal processes and cannot be modified.

Action See Administering webMethods Integration Server for more information about system caches.

ISS.0017.0035E **Cannot clear the contents of a system cache.**

Explanation The cache you attempted to clear is a system cache. System caches are used by internal processes and cannot be modified.

Action See Administering webMethods Integration Server for more information about system caches.

ISS.0017.0036E **Cannot start a system cache manager.**

Explanation The cache manager you attempted to start is a system cache manager. System cache managers are used by internal processes and cannot be modified.

Action See Administering webMethods Integration Server for more information about system cache managers.

ISS.0017.0037E **Cannot shutdown a system cache manager.**

Explanation The cache manager you attempted to shutdown is a system cache manager. System cache managers are used by internal processes and cannot be modified.

Action See Administering webMethods Integration Server for more information about system cache managers.

ISS.0017.0038E **Cannot reload a system cache manager.**

Explanation The cache manager you attempted to reload is a system cache manager. System cache managers are used by internal processes and cannot be modified.

Action See Administering webMethods Integration Server for more information about system caches.

ISS.0017.0039E **Attempted to create cache manager {0} that connects to a Terracotta Server Array, but the Integration Server license does not allow it. Cannot save cache manager configuration.**

Explanation To use this feature, Integration Server must have a license that allows distributed caching.

Action Obtain the appropriate license from Software AG Global Support and add it to Integration Server.

ISS.0017.0040I **Successfully evicted expired elements from the cache {0} contained in cache manager {1}.**

ISS.0017.0041I **Cleared all caches starting with name {0} contained within the cache manager {1}.**

ISS.0017.0042I **Cleared all caches contained within the cache manager {0}.**

ISS.0017.0043E	**Error occurred while clearing caches starting with name {0} contained within the cache manager {1}. Details:{2}**
Explanation	The service cannot remove the element from the cache for the reason indicated in the message.
Action	Take the appropriate action based on the details shown in the message.
ISS.0017.0044E	**Error occurred while clearing caches contained within the cache manager {0}. Details:{1}**
Explanation	The service did not clear the caches in the specified cache manager because of the specified error.
Action	Take the appropriate action based on the details shown in the message.
ISS.0017.0045I	**Added cache {0}.**
ISS.0017.0046I	**Updated cache {0}.**
ISS.0017.0047I	**Deleted cache {0}.**
ISS.0017.0048E	**{0} is not a distributed cache. Integration Server cannot synchronize with the Terracotta Server Array.**
Explanation	You can only synchronize distributed caches with a Terracotta Server Arrays.
Action	Set the Distributed option on all the caches you want to synchronize with the Terracotta Server Array.
ISS.0017.0049E	**The {0} cache manager is not running. Start the cache manager to synchronize the cache with the Terracotta Server Array.**
Explanation	You cannot synchronize caches against the Terracotta Server Array when the cache manager is not running.
Action	Start the cache manager and then synchronize the cache with the Terracotta Server Array.
ISS.0017.0050I	**The configuration for the {0} cache has been synchronized with the Terracotta Server Array.**

ISS.0017.0051I **Integration Server cannot evict expired elements for caches contained in a system cache manager.**

ISS.0017.0052I **Integration Server cannot reload the {0} cache manager because it is not running.**

ISS.0017.0053E **The {0} cache in {1} has a different local configuration than the configuration on the Terracotta Server Array. Integration Server is using the configuration from the Terracotta Server Array.**

Explanation The configuration of the local cache should match that of the associated Terracotta Server Array. If the local cache configuration does not match the configuration of the Terracotta Server Array, Integration Server ignores the local cache configuration and uses the configuration of the Terracotta Server Array.

Action Configure the local cache to match the configuration of the Terracotta Server Array.

ISS.0017.0054I **Use Integration Server Administrator to synchronize mismatched cache configurations with the Terracotta Server Array.**

ISS.0017.0055E **Integration Server has registered a cache manager, but the configuration file is not in the config/Caching directory. Integration Server cannot manage this configuration.**

Explanation Integration Server saved the configuration for a cache manager, but the configuration file is not in the IntegrationServer/config/Caching directory. If the configuration is valid, you can still use the cache manager, but you cannot use Integration Server Administrator to stop or start the cache manager or edit its configuration.

Action Copy the configuration file to the IntegrationServer/config/Caching directory and restart Integration Server.

ISS.0017.0056E **The {0} cache manager is shut down but there is no configuration file associated with it. Integration Server cannot restart this cache manager.**

Explanation The cache manager configuration file is not in the IntegrationServer/config/Caching directory.

Action Restore the missing configuration file to the IntegrationServer/config/Caching directory.

ISS.0017.0057E **The {0} cache manager is shut down but its corresponding configuration file ({1}) no longer exists. Integration Server cannot restart this cache manager.**

Explanation The cache manager configuration file is not in the IntegrationServer/config/Caching directory.

Action Restore the missing configuration file to the IntegrationServer/config/Caching directory.

ISS.0017.0058E	**Integration Server cannot remove the Terracotta Server Array URLs for this cache manager because one or more of its caches are distributed. Clear the Distributed option on all the caches.**
Explanation	Integration Server cannot remove Terracotta Server Array URLs if any of the caches contained in the cache manager are distributed.
Action	Shut down the cache manager and then change the Terracotta Server Array URLs.

ISS.0017.0059E	**Integration Server cannot modify the Terracotta Server Array URLs for a cache manager while it is running. Shut down the cache manager, then change the Terracotta Server Array URLs.**
Explanation	Integration Server cannot modify the Terracotta Server Array URLs for a cache manager while it is running.
Action	Shut down the cache manager and then change the Terracotta Server Array URLs.

ISS.0017.0060I	**Updated cache manager {0}.**

ISS.0017.0061I	**Added cache manager {0}.**

ISS.0017.0062E	**Integration Server encountered an error while parsing {0}: {1}.**
Explanation	The cache manager configuration file contains invalid syntax.
Action	Manually edit the cache manager configuration file so that it is syntactically correct.

ISS.0017.0063I	**The current Terracotta license is not valid for the BigMemory settings configured for the {0} cache manager. To use the cache manager, either remove the BigMemory settings from the configuration file or obtain a valid Terracotta license for BigMemory.**

ISS.0017.0064E	**Deployment of cache manager {0} failed because of invalid license. Check the Integration Server log for details.**
Explanation	Integration Server could not deploy the cache manager because the license for Integration Server or Terracotta is invalid.
Action	Acquire the correct license file for Terracotta, Integration Server, or both and then redeploy the cache manager.

ISS.0017.0065I **Reading cache manager configuration from file {0}.**

ISS.0017.0066I **{0} is a system cache manager.**

ISS.0017.0067I **Read cache manager {0} from file {1}.**

ISS.0017.0068I **Integration Server is running in safe mode. Cache manager {0} not initialized.**

ISS.0017.0069I **Initializing cache manager {0}.**

ISS.0017.0070I **Cache manager {0} initialized.**

ISS.0017.0072I **Shutting down cache manager {0}.**

ISS.0017.0073I **Cache manager {0} is shut down.**

ISS.0017.0074I **Shutting down cache managers.**

ISS.0017.0075I **Finished shutting down cache managers.**

ISS.0017.0076E **The value specified in the "Maximum Elements in Memory" field must be an integer no larger than 2147483647.**

Explanation An invalid value was specified in the Maximum Elements in Memory field.

Action Change the value to an integer no larger than 2147483647.

ISS.0017.0077E **Field cannot be changed while the cache manager is running: {0}**

Explanation The specified field cannot be modified while the cache manager is running.

Action Shut down the cache manager, and then update the field. To shut down the cache manager, open Integration Server Administrator and go to the Settings > Caching page, then click the "Shutdown" link for the cache's cache manager.

ISS.0019.7005E	**Unable to retrieve client_secret for {0} from the secure password store. See the error log for a full stack trace.**
Explanation	Integration Server cannot retrieve the client secret for the specified OpenID Provider.
Action	Re-enter the client_secret value in the OpenID Provider's configuration file and click the Reload OpenID Providers link on the Security > OpenID page.If none of the passwords work, the password store might be corrupt. Contact Software AG Global Support.

ISS.0019.7007E	**ID Token''s issuer claim {0} is invalid. It does not match the application''s OpenID Provider issuer ID.**
Explanation	Integration Server expected the iss field in the token to match the issuer value in the OpenID Provider's configuration file; however, the iss and issuer values do not match.
Action	Check that the issuer value in the OpenID Provider's configuration file is correct. If it is not, edit the OpenID Provider configuration file to include the correct issuer value. Then, click the Reload OpenID Providers link on the Security > OpenID page.

ISS.0019.7008E	**ID Token''s audience claim {0} does not match the application''s OpenID Provider client ID.**
Explanation	Integration Server expected the aud field in the token to match the client_id value in the OpenID Provider's configuration file.
Action	Check that the client_id value in the OpenID Provider's configuration file is correct. If it is not, edit the OpenID Provider configuration file to include the correct client_id value. Then, click the Reload OpenID Providers link on the Security > OpenID page.

ISS.0019.7009E	**ID Token''s audience claim has multiple values "{0}" but the required authorized party claim is not present.**
Explanation	The audience for an ID Token must contain the OAuth 2.0 client_id of the Relying Party as an audience value but the required client_id is missing.
Action	No action required.

ISS.0019.7010E	**ID Token''s authorized party claim {0} does not match the OpenID Provider client ID {1}.**
Explanation	The authorized party claim in the ID Token either does not contain or does not match the OAuth 2.0 client_id for the Authorized Party. The ID token must contain the authorized party claim when the ID Token has a single audience value and the audience is not the Authorized Party.
Action	No action required.

ISS.0019.7011E	**ID Token has expired. Expiration claim value is {0}, current time is {1}.**
Explanation	The ID Token issued by the OpenID Provider has expired and cannot be used for authentication.
Action	Set the prompt value in the OpenID Provider's configuration file to "login", which instructs the OpenID Provider to require the end user to log in using their credentials. Then, click the Reload OpenID Provider link on the Security > OpenID page. Have the user reissue the original request.

ISS.0019.7012E	**ID Token has expired. Issued at time value is {0}, current time is {1}, provider''s max_age limit is {2}.**
Explanation	The age of the ID Token issued by the OpenID Provider exceeds the max_age value in the OpenID Provider's configuration file. The token cannot be used for authentication.
Action	Increase the max_age value in the OpenID Provider's configuration file and click the Reload OpenID Provider link on the Security > OpenID page. Have the user reissue the original request.

ISS.0019.7013E	**ID Token''s asserted claim value(s) "{0}" do not match any of the provider''s asserted claim values "{1}".**
Explanation	The claim values in the token do not match any of the claim values for the OpenID Provider.
Action	No action required.

ISS.0019.7015E	**ID Token requires re-authentication, Maximum Authentication Age {0} has expired. Authentication time was {1}, current time is {2}**
Explanation	The user must be re-authenticated because the time elapsed since the token authentication time exceed the Maximum Authentication Age.
Action	Re-authenticate the token. Set the prompt value in the OpenID Provider's configuration file to "login" and click the Reload OpenID Provider link on the Security > OpenID page. Have the user reissue the request.

ISS.0019.7016E	**{0} is null.**
Explanation	The OpenID Provider's token endpoint or userinfo endpoint did not return a token.
Action	Check the error log for an exception related to the request. Set watt.server.oauth.custom.responseHeader to true and the server logging facility "0040 HTTP Response" to TRACE. Recreate the problem and check the server log for a response header of X-OAuth-Error. If no error is reported, contact the OpenID Provider.

ISS.0020.7020E **Timeout occurred during execution of a service {0} configured for circuit breaker.**

Explanation The service execution time exceeded the configured timeout period for the service.

Action Identify and correct the cause of the slow service execution. You can generate a thread dump of Integration Server and examine Integration Server logs to assist with identifying the source of the slow behavior. Then correct the component that exhibits the slow behavior.

ISS.0024.0001 **Could not initialize User Manager.**

ISS.0024.0002 **Error occurred while initializing User Manager: Class {0} was not found in CLASSPATH.**

ISS.0024.0003 **Error occurred while initializing User Manager: {0}**

ISS.0024.0004 **Could not access User Manager**

ISS.0024.0005E **Could not read users.cnf (the file may be corrupt)**

Explanation Integration Server could not read user and group configuration information from the users.cnf file. The file might be corrupt.

Action Examine this file in the Integration Server /config directory. Ensure that the server has read access to it. If the file is corrupted, you might need to set up the users and/or groups again through the Integration Server Administrator.

ISS.0024.0006E **Could not write users.cnf (the file may be corrupt)**

Explanation Integration Server could not write user and group configuration information to the users.cnf file. The file might be corrupt.

Action Examine this file in the Integration Server /config directory. Ensure that the server has write access to it. If the file is corrupted, you might need to set up the users and/or groups again through the Integration Server Administrator.

ISS.0024.0007 **The JDBCPool {0} associated with Central Users JDBC function is not defined so the Central User Manager is not enabled**

ISS.0024.0010 **Central User Manager initialization failed with error : {0}**

ISS.0024.0011 **Not able to load the {0} Role/Group.**

ISS.0024.0013 **Integration Server cannot add group to ACL because the required parameter "{0}" is not supplied.**

ISS.0024.0014 **Integration Server cannot add group "{0}" to ACL "{1}" because ACL "{1}" is not defined.**

ISS.0024.0015 **Integration Server cannot add group "{0}" to ACL "{1}" because group "{0}" is not found.**

ISS.0024.0018 **Integration Server failed to add group "{0}" to ACL "{1}" because of exception: {2}.**

ISS.0025.0009E **Integration Server could not initialize the cache manager. Stopping Integration Server initialization. Use the server log and error log to diagnose and correct the problem.**

Explanation This error occurs when Integration Server is configured to be in a cluster and cannot connect to the Terracotta Server Array (TSA). This could happen because the TSA URL in your cluster configuration is incorrect, the TSA is offline, or because there is a network problem.

Action (1) Verify that the Terracotta Server Array is available and accepting connections. (2) If it is, start the server in safe mode by including the "-safeboot" argument in the command line. On the Settings > Clustering page of Integration Server Administrator, check that the Terracotta Server Array URL value is correct. (3) Make sure the network configuration of the host is correct and there are no problems with your network.

ISS.0025.0034U **Dispatcher could not be shutdown: {0}**

Explanation Integration Server encountered a serious internal error while shutting down.

Action Contact Software AG Global Support.

ISS.0025.0035 **Dispatcher could not be started: {0}**

ISS.0025.0040I	**FIPS mode initialized**
Explanation	Integration Server is operating under Federal Information Processing Standards.
Action	No action is required.

ISS.0025.0041I	**FIPS mode not initialized**
Explanation	Integration Server is not operating under Federal Information Processing Standards.
Action	No action is required.

ISS.0025.0042S	**FIPS mode could not be initialized. Shutting down server: {0}**
Explanation	An error was encountered during initialization of FIPS mode operation.
Action	Contact Software AG Global Support. Be prepared to provide configuration information related to security provider and FIPS mode.

ISS.0025.0043S	**Integration Server started in Safe Mode**
Explanation	Integration Server is operating in safe mode either because it was started using the safeboot switch or because there were problems with the master password. When running in safe mode, Integration Server is not connected to any external resources, except the server's own external repository, and you cannot update any passwords. If it is a master password problem, there will be other messages logged that indicate that there was a master password problem.
Action	If you intended to start the Integration Server in safe mode, then no action is required. If the Integration Server automatically started in safe mode due to a master password problem, see the webMethods Integration Server Administrator documentation.

ISS.0025.0046	**Monitoring API could not be initialized. JmsUrl = {0}. Value must be supplied for JmsUrl.**

ISS.0025.0047	**Monitoring API could not be initialized because of following exception. Check JMS Provider. {0}**

ISS.0025.0048	**Monitoring API could not be initialized. Check JMS Provider.**

ISS.0025.0050	**The JCE Unlimited Strength Jurisdiction Policy File was not found. Please install it.**

ISS.0025.0053 **Error encountered while disabling Monitoring API.**

ISS.0025.0054 **Fabric Agent initialization failed.**

ISS.0025.0056 **FIPS could not be initialized because the JCE Unlimited Strength Jurisdiction Policy File was not found. Shutting down Integration Server.**

ISS.0025.0058 **Error reading system level information: {0}**

ISS.0025.0059W **Error initializing cluster node name: {0}**

Explanation The specified cluster node name is an empty node name.

Action Specify a non-empty cluster node name.

ISS.0025.0060W **Falling back on the fully qualified domain name as the cluster node name, cluster node name is :{0}**

Explanation Integration Server is using the default cluster node name for the machine because the cluster node name is empty or not provided.

Action No action is required.

ISS.0025.0061E **The logical name for the cluster node is not correct: {0}**

Explanation The name for the cluster node is not valid. The logical host name you specify must be unique within the cluster and cannot contain a semicolon (;).

Action Specify a unique logical name to identify the Integration Server instance in the cluster.

ISS.0025.0062CC **Web services stack could not be initialized. Shutting down server: {0}**

Explanation Integration Server encountered an error while initializing the Web services stack. Typical reasons are:

1) Loading of axis2.xml file located in Integration Server_directory/config/wss or Integration Server_directory/config/wssClient/conf folders failed because the file has been modified.

2) Integration Server failed to initialize the policy manager for the Web service.

Action If you have modified the axis2.xml file located in Integration Server_directory/config/wss or Integration Server_directory/config/wssClient/conf folders, make sure that the changes made are correct. For all other reasons, refer to the details listed in the error message and respond accordingly.

ISS.0025.0063E	**EDA Manager initialization failed: {0}**
Explanation	The EDA Manager did not initialize during Integration Server start up.
Action	Review the exception returned with the error message to determine why the EDA Manager did not initialize.

ISS.0025.0064E	**EDA Manager initialized.**
Explanation	The EDA Manager initialized successfully.
Action	No action required.

ISS.0025.0065W	**Encountered an error while disabling listeners. Proceeding with server shutdown.**
Explanation	An error occurred while shutting down Integration Server. If the logging level for logging facility 0025, Initialization, is set to Debug or higher, the server log will include a stack trace with more details about the error.
Action	No action is required. Integration Server will shut down as requested.

ISS.0025.0066W	**Encountered an error while suspending triggers. Proceeding with server shutdown.**
Explanation	An error occurred while shutting down Integration Server. If the logging level for logging facility "0025 Initialization" is set to Debug or higher, the server log will include a stack trace with more details about the error.
Action	No action is required. Integration Server will shut down as requested.

ISS.0025.0070C	**Integration Server detected files in config/work directory which suggests unapplied configuration changes.**
Explanation	When saving changes to configuration files, Integration Server first saves the configuration changes in a temporary file in the IntegrationServer_directory/instances/instanceName/config/work directory. After saving the changes in a temporary file, Integration Server moves the temporary file to the actual configuration file. This ensures that if unexpected behavior occurs before the configuration changes are initially saved to the temporary file, only the temporary file is impacted. The actual configuration file is not corrupted. If Integration Server detects files in in the IntegrationServer_directory/instances/instanceName/config/work, it suggests that changes to a configuration file were not saved to the temporary file and that, therefore, the changes were not made to the actual configuration file.
Action	Use the contents of the IntegrationServer_directory/instances/instanceName/config/work directory to determine which configuration files were in the process of being changed. Decide whether or not you want to redo the changes to the configuration files. Delete the files under the directory and redo the configuration change if you so choose.

ISS.0026.0002E	**Failure while loading service {0}: {1}**
Explanation	Integration Server failed to install, enable, or reload the package because it could not load a service in the package into its namespace.
Action	Examine the error message to determine the problem service. Usually this error occurs when a Java service was not compiled before loading the package.
ISS.0026.0005	**Flow service could not be registered with the server: folder.servicename may already exist.**
ISS.0026.0006	**Warning missing type name while loading service {0}**
ISS.0026.0007	**Warning missing type name in operation {0} while loading service {1}**
ISS.0026.0008E	**Error: Exception serializing Flow Service {0}**
Explanation	Integration Server encountered an internal error with a flow service.
Action	Contact Software AG Global Support.
ISS.0026.0009E	**Error: unknown flow operation type for node:{0} in file:{1}**
Explanation	Integration Server encountered an internal error with a flow service.
Action	Contact Software AG Global Support.
ISS.0026.0010	**Warning: {0} Operation with no body in service {1}**
ISS.0026.0011	**Warning: {0} Operation missing service name in {1}**
ISS.0026.0012W	**Warning: Flow Branch Operation must have switch name or use conditional labels in {0}**
ISS.0026.0013	**Warning: Flow Branch Operation cannot have switch name and use conditional labels in {0}**

ISS.0026.0014 **Warning: {0} Operation missing target path in {1}**

ISS.0026.0015 **Warning: {0} Operation missing source path name in {1}**

ISS.0026.0016 **Warning: Flow Map Delete Operation missing field name in {0}**

ISS.0026.0017 **The HTTP URL alias could not be registered by the service {0}. "{1}" is already registered as an alias for the path: {2}**

ISS.0026.9101E **Missing flow.xml**

Explanation The flow.xml file does not exist. When a flow service is created, Integration Server creates a flow.xml file and a node.ndf file in the IntegrationServer\packages\packageName\ns\folderName directory that corresponds to the package and folder in which the flow service was created.

Action Contact Software AG Global Support.

ISS.0026.9102E **Read only {0}**

Explanation The flow.xml file cannot be updated because it is read-only.

Action Navigate to the directory of the flow.xml file and make it a writable file.

ISS.0026.9103E **Unable to write to flow.xml**

Explanation An exception occurred while writing to the flow.xml file.

Action Contact Software AG Global Support.

ISS.0026.9104E **Missing class {0}**

Explanation The specified Java class cannot be found. This error is returned by the JVM.

Action Contact Software AG Global Support.

ISS.0026.9105E **Method {0} is not defined with the proper signature**

Explanation The signature of the Java service does not have a return type of void.

Action Contact Software AG Global Support.

ISS.0026.9106E	**No method {0} in class {1}**
Explanation	The service is to be supported by a specific method in a class. However, the loaded class does not contain the specified method.
Action	Make sure the class contains the method that you want to use to support the service.

ISS.0026.9107E	**Method {0} is unexpectedly null**
Explanation	Method defined to support the invoked service is null.
Action	Contact Software AG Global Support.

ISS.0026.9108E	**Unable to create service; Service name missing**
Explanation	The service cannnot be created because the service name is missing. Integration Server can only create and register services that have a name.
Action	Make sure to specify a name for the service.

ISS.0026.9109E	**Already registered in {0}**
Explanation	An identically named element already exists in another package. The fully qualified element name must be unique across Integration Server. Fully qualified element names use the format: folder.subfolder.subfolder:elementName
Action	Provide a different name for the element.

ISS.0026.9110E	**{0} : Name already used by another service type in {1} package**
Explanation	Integration Server cannot save or register the service because a service with that name already exists in the package.
Action	Specify a different name for the service.

ISS.0026.9111E	**Unable to register service; Package {0} is not enabled**
Explanation	An attempt was made to register a service in a disabled package. A service can be registered in an enabled package only.
Action	Enable the package and then attempt to register the service.

ISS.0026.9201E	**Unknown service: {0}**

ISS.0027.0001W	**nCipher Hardware accelerator not available**
Explanation	An error occurred while accessing the nCipher hardware.
Action	Turn the "0027 Server Configuration" logging facility up to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator and try again. See the details of the error in the server log.

ISS.0028.0002	**Packages directory missing or corrupted**
ISS.0028.0003	**Unable to copy the original package manifest file: {0}**
ISS.0028.0006	**Unable to load {0} package (possibly due to circular dependencies)**
ISS.0028.0007	**This package requires {0} package (Version {1}) to load**
ISS.0028.0008	**Warning! Loading package from backup manifest file**
ISS.0028.0009	**Unable to read manifest file for {0} package**
ISS.0028.0010	**Unknown service type ({0}) in {1} package**
ISS.0028.0011	**Unable to write package manifest file: {0}**
ISS.0028.0013	**Startup service exited with the following error: {0}**
ISS.0028.0014	**Startup service {1} was not found in {0} package**
ISS.0028.0016	**Shutdown service exited with the following error: {0}**
ISS.0028.0017	**Shutdown service {1} was not found in {0} package**

ISS.0028.0018 **Server could not update the node definition file. Changes to the package were not saved.**

ISS.0028.0020 **Unable to read node definition file**

ISS.0028.0021 **Server could not update the node subdirectory. Changes to the package were not saved.**

ISS.0028.0022 **Unable to locate class: {0}**

ISS.0028.0023 **Could not delete service**

ISS.0028.0024 **Invalid Package License key for Package: {0}**

ISS.0028.0025 **Unable to save Package Key for Package: {0}**

ISS.0028.0026E **Invalid or corrupt namespace plug-in configuration found in {0} package**

Explanation Integration Server could not read plug-in configuration information from the nsplugins.cnf file associated with the indicated package.

Action Contact Software AG Global Support.

ISS.0028.0027 **Namespace plug-in type name {0} in package {1} conflicts with existing type**

ISS.0028.0028 **Cannot create namespace factory class {0} in package {1}: {2}**

ISS.0028.0029 **Namespace factory class invalid type {0} in package {1}**

ISS.0028.0030 **Error: Will not load deprecated service type ({0}) in service {1} in package {2}**

ISS.0028.0035 **Package {0} has failed to load.**

ISS.0028.0036 **Document type {0} has failed to load. Duplicate Broker document type name {1} is also referenced by {2}**

ISS.0028.0038 **Error loading {0} : Name already used by another item in package {1}**

ISS.0028.0039E **Failure while loading document type {0}: {1}**

Explanation Integration Server failed to load the document type into the namespace because another document type with the same name was already being loaded into the Integration Server namespace.

Action Examine the error message to determine the problem document types. Check both document types to make sure they have different names. If they have the same name and both need to be loaded into the namespace, rename one and try again.

ISS.0028.0040E **Failure while loading schema {0}: {1}**

Explanation Integration Server failed to load the schema into the namespace because another schema with the same name was already being loaded into the Integration Server namespace.

Action Examine the error message to determine the problem schemas. Check both schemas to make sure they have different names. If both need to be loaded into the namespace, rename one and try again.

ISS.0028.0041E **Failure while loading element {0}: {1}**

Explanation Integration Server failed to load the element into the namespace because another element with the same name was already being loaded into the Integration Server namespace.

Action Examine the error message to determine the problem elements. Check both elements to make sure they have different names. If both need to be loaded into the namespace, rename one and try again.

ISS.0028.0043 **Error unregistering node {0}: {1}**

ISS.0028.0044W	**Invalid classpath entry: {0}**
Explanation	An I/O error occurred when Integration Server tried to access the file system to resolve the canonical name of the directory in which the file exists.
Action	Check the file system for errors, such as problems with permissions and cyclical links.

ISS.0028.0045E	**Failed to install package {0}. Another package exists with the name {1}**
Explanation	Integration Server was unable to install a package because a package with the same name already exists on the Integration Server.
Action	Rename one of the packages, either the existing package or the one you are trying to install. Note that case does not matter; Integration Server considers "ABC" the same name as "abc".

ISS.0028.0046E	**Unable to load package replication passwords from {0}**
Explanation	Integration Server encountered an error while loading the indicated class.
Action	Check the audit log for messages about the underlying cause of the exception.

ISS.0028.0047E	**Unable to save package replication passwords to {0}**
Explanation	Integration Server encountered an error while loading the indicated resource.
Action	Check the Audit log for messages about the underlying cause of the exception.

ISS.0028.0048	**Failed to read class {0} from input stream**

ISS.0028.0049	**Unable to locate resource {0}**

ISS.0028.0051E	**Task Scheduler startup service exited with the following error: {0}**
Explanation	Integration Server encountered an error while executing the scheduler startup service task.
Action	Contact Software AG Global Support.

ISS.0028.0052E	**Task Scheduler startup service {1} was not found in {0} package**
Explanation	The package startup process could not locate the service named in the message.
Action	Contact Software AG Global Support.

ISS.0028.0055 **Caching of package classes is disabled due to the following error for file [{0}]: {1}**

ISS.0028.0056 **The post-initialization startup service {0} threw an exception: {1}. See the error log for the full stack trace.**

ISS.0028.0057 **Failure while registering HTTP URL alias "{0}" for the package {1}. Already registered as an alias for the path: {2}**

ISS.0028.0058 **Failure while registering HTTP URL alias "{0}" for the package {1}. Already registered by package {2} as an alias for the path: {3}**

ISS.0028.0059 **Failure while registering HTTP URL alias "{0}". Already registered as an alias for the path: {1}**

ISS.0028.0060 **Failure while registering HTTP URL alias "{0}". Already registered by package {1} as an alias for the path: {2}**

ISS.0028.0061E **Unable to load system package {0} due to dependency on non-system packages.**

Explanation Integration Server cannot load the specified system package because it depends on a non-system package. System packages are pre-defined packages that are part of the Integration Server product (for example, WmPublic). A system package can have dependencies on other system package(s) only.

Action Using Designer, edit the package dependencies for the specified system package to remove the dependency on the non-system package.

ISS.0028.9999WError message – Unable to load the REST resource with URL template {0}, HTTP method(s) {1}, and service {2} because the URL template contains either illegal or unsupported characters.

Explanation The information you have specified for configuring the REST resource contains either illegal or unsupported characters.

Action Update the REST resource configuration to not include illegal or unsupported characters.

ISS.0033.0001 **Inactive server {0} was removed from cluster {1}**

ISS.0033.0100 **If any multicast setting is supplied (Discovery Address, Discovery Port, Time To Live), they must all be supplied.**

ISS.0033.0103E **Could not open the session cache. {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISS.0033.0104E **Could not add server to the cluster. {0}**

Explanation Integration Server failed to add a server to the cluster.

Action Make sure that the server repository is running and that the connection to other servers is valid.

ISS.0033.0108 **Could not remove server from cluster. {0}**

ISS.0033.0114E **Failed to add server statistics to the cluster cache. {0}.**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISS.0033.0124E **Local Address**

Explanation Integration Server failed to remove expired sessions from the Repository. This is an internal error.

Action Contact Software AG Global Support.

ISS.0033.0128 **Unable to save settings to the server's configuration file.**

ISS.0033.0143 **Please restart the server to make the new settings take effect.**

ISS.0033.0144 **Changes not saved: {0} is required.**

ISS.0033.0146 **Evaluating host {0} to receive Session Document.**

ISS.0033.0147 **Register Session Document handler with host {0}.**

ISS.0033.0148 **Received unknown special document. Body = <<{0}>>.**

ISS.0033.0149 **Changes not saved. Invalid value. {0} must be an integer.**

ISS.0033.0150 **Changes not saved. Invalid Well Known Address. If either host or port is supplied, both must be supplied. host={0}, port={1}.**

ISS.0033.0151U **Communication with Terracotta Server Array has been lost.**

Explanation During server startup, Integration Server detected a problem with its configuration that will prevent it from being part of a cluster.

Action Check the Clustering and Repository settings for your Integration Server. Refer to the webMethods Integration Server documentation for more information about clustering. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0033.0153E **Could not obtain a handle to ConnectionManager.**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISS.0033.0154E **Could not save session {0} to the session cache. {1}.**

Explanation Integration Server failed to persist the indicated session to the Repository. This is an internal error.

Action Contact Software AG Global Support.

ISS.0033.0155E **Could not create local session {0} from the cached session values. {1}.**

Explanation An Integration Server in a cluster tried to update a session object, but was unable to find it. This in an internal error.

Action Contact Software AG Global Support.

ISS.0033.0156E **Cluster Invoke did not complete successfully. Cluster Synchronization feature is not configured.**

Explanation After a trigger configuration update, Integration Server attempted to apply the change to other Integration Servers in the cluster, but was unable to. The most likely reason is that the Cluster Synchronization feature has not been properly configured.

Action Review the cluster synchronization for rrigger management text in the webMethods Integration Server documentation for instructions on configuring your cluster to propagate trigger changes to other Integration Servers in the cluster.

ISS.0033.0159 **The TSA URL must be specified on the Settings > Clustering page in order to join a cluster. Clustering has been disabled. This server is running in stand-alone mode.**

ISS.0033.0161 **CLUSTERING DISABLED: Could not create or join distributed clustering cache "{0}". This server is NOT a member of a cluster.**

ISS.0033.0162 **The Cluster Name can contain only the following characters: alphanumerics, dashes, underscores, and colons.**

ISS.0033.0163 **Cache configuration is invalid. Settings were not saved: {0}**

ISS.0033.0164 **The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to enable clustering.**

ISS.0033.0167 **The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to join a cluster. Clustering has been disabled. This server is running in stand-alone mode.**

ISS.0033.0169 **Logical cluster node name, {0}, is not valid.**

Explanation A cluster node name is either empty or null. Integration Server detects invalid cluster node names at server initialization or when someone attempts to pin a scheduled task to cluster node with an invalid name.

Action Provide a non-empty cluster node name for the cluster node.

ISS.0033.0181I **Cluster name cannot contain any of these characters: ? [ ] / = + < > : ; " , * | ^ @**

ISS.0033.0182I **Cluster name cannot start with a '.' or end with a space.**

ISS.0033.0183I **Cluster name cannot be an operating system device name.**

ISS.0033.0184I **Cluster name cannot be null or empty.**

ISS.0033.0186W	**Statsitics polling time set to 60 seconds because clustering is configured.**
Explanation	Integration Server uses a value of 60 for the statistics polling time because the watt.server.stats.pollTime server configuration parameter is set to a value less than or equal to 0 (zero) or greater than 60. When clustering is configured, watt.server.stats.pollTIme must be greater than 0 and less than or equal to 60.
Action	Set watt.server.stats.pollTime to value greater than 0 (zero) but less than or equal to 60.
ISS.0035.0002	**Initial log rotation interval could not be set: {0} ms in not valid**
ISS.0035.0004	**Returned {0} lines while requested for {1} number of lines for error logs.**
ISS.0036.0002E	**Errors occurred invoking URL {0}**
Explanation	A client application using the Java API did one of the following: 1) Tried to invoke the indicated folder or service name, but specified the wrong folder/service name. 2) Specified invalid certificates when setting up the SSL connection to the Integration Server.
Action	Examine the error stack trace to determine which exception was thrown. If it is a MalformedURLException, check the folder/service name provided in the API call and make sure that you specified the fully qualified service name. If it is a CertificateException, an IOException, or an InvalidKeyException, check the certificates provided and make sure that they are valid.
ISS.0036.0004	**Error occurred while pinging server: {0}**
ISS.0036.0005	**Error occurred while disconnecting from server: {0}**
ISS.0036.0009E	**Ping Failed to server: {0} Exception: {1}**
Explanation	A client application performed a periodic ping of a remote Integration Server. The ping resulted in an exception.
Action	Verify that the remote Integration Server is up and running. In addition, verify that there is network connectivity between the two servers.

ISS.0051.0002E	**Error: {0}**
Explanation	Integration Server failed to add a port, remove a port, or edit an existing port because it could not save ports properties to <IntegrationServer_dir>/config/port.cnf.
Action	Examine the port.cnf file to make sure that it is not corrupt and not Read-Only. If the file is corrupt, you may need to remove the file and restart Integration Server. After you do this, you can re-add ports to the Integration Server.
ISS.0051.0003	**Port {0} already registered**
ISS.0051.0005	**Unable to unregister port {0}**
ISS.0051.0008	**Listener {0} was denied access to service {1}**
ISS.0053.0002	**Access denied for user {0} on port {1} from {2}.**
ISS.0053.0003	**Dispatch caught exception in run loop: {0}**
ISS.0053.0005	**Dispatch caught exception while trying to send response: {0}**
ISS.0053.0006S	**(tid={0}) Enterprise Gateway Server encountered the error "{1}" while handling a request from client "{2}" at request URL "{3}".**
Explanation	Enterprise Gateway Server experienced an internal error while handling the request.
Action	If the issue persists, contact the system administrator.
ISS.0053.0008I	**(tid={0}) Attempting to forward the request to the Internal Server again because the original attempt failed with exception "{1}". The retry count is {2} and the request URL is "{3}". Internal Server Host is "{4}" and Port is "{5}"**
Explanation	Enterprise Gateway Server failed to transmit the client request to the Internal Server due to the indicated network exception. The server will automatically try to send the request again. If the retry attempts fail, the server will log a message and fail the client request.
Action	The action you take depends on the exception issued. Look at the exception message for specific information.

ISS.0053.0009W	**(tid={0}) Enterprise Gateway Server encountered an I/O error while writing the Internal Server''s response back to the client at "{1}". The request URL is "{2}".**
Explanation	An input/output error occurred between Enterprise Gateway Server and the Internal Server.
Action	If the issue persists, contact the system administrator.

ISS.0053.0010E	**(tid={0}) Enterprise Gateway Server encountered error "{1}" while handling the request. The server is unable to retry the request at this time. The retry count is {2}.**
Explanation	Enterprise Gateway Server experienced an internal error while handling the request.
Action	If the issue persists, contact the system administrator.

ISS.0053.0011W	**(tid={0}) Enterprise Gateway Server is stopping attempts to retry the request because the content length "{1}" of the retry request does not match the content length "{2}" of the original request. The retry count is {3}.**
Explanation	Enterprise Gateway Server could not complete the request for the reason indicated.
Action	If the issue persists, contact the system administrator.

ISS.0053.0012S	**Access is denied for user "{0}" on port {1} from client "{2}" through Enterprise Gateway "{3}".**
Explanation	Incorrect credentials were specified while connecting to the Internal Server through the Enterprise Gateway.
Action	Supply valid credentials.

ISS.0053.0013	**(tid={0}) API Gateway encountered an I/O error while responding to a request from the client at "{1}". The request URL is "{2}".**
Explanation	API Gateway cannot respond to the specified client request because of an I/O error.
Action	Retry the request. If the issue persists, contact your system administrator.

ISS.0053.0014	**(tid={0}) API Gateway encountered the error "{1}" while handling a request from the client. The server is unable to retry the request at this time. The retry count is {2}.**
Explanation	The server is unable to retry the request after the retry count exceeded the predefined threshold.
Action	Contact your system administrator.

ISS.0053.0016	**(tid={0}) API Gateway encountered an error while handling a request from client "{1}" at the request URL "{2}".**
Explanation	API Gateway encountered an error while handling the specified client request.
Action	Retry the request. If the issue persists, contact your system administrator.

ISS.0053.0017	**Access denied for user "{0}" on port {1} from client "{2}" through API Gateway "{3}".**
Explanation	The current user cannot access API Gateway on the specified port because of not having the proper ACLs.
Action	Check the ACLs for the current user. Ensure that the user has the correct ACLs to access API Gateway on the specified port.

ISS.0054.0002E	**CSRF attack detected. CSRF token is not present in the request URL: {0}**
Explanation	CSRF secure token is missing in the request URL, possibly due to a CSRF attack.
Action	If the request is valid, provide a valid CSRF secure token for the request.

ISS.0055.0001E	**Critical Java Service error**
Explanation	Integration Server encountered a serious internal error.
Action	Contact Software AG Global Support.

ISS.0055.0002	**Service setup {0} uses old-style signature**

ISS.0055.0003	**Initialization of Java Service {0} failed due to error: {1}**

ISS.0056.0001	**No SMTP server set. Cannot deliver mail**

ISS.0056.0002	**No recipient specified. Cannot deliver mail**

ISS.0056.0003	**Unable to send mail. *{0}***

ISS.0056.0004	**Invalid SMTP port specified {0}. SMTP logging turned off**

ISS.0059.0001U	**Interrupted {0}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISS.0070.0003W	**Error encountered creating {0} listener on port {1}: {2}**
Explanation	An error was encountered while creating a listener.
Action	See the excpetion message for details about the error. Use the exception message to correct the error.

ISS.0070.0004E	**Failed to load configuration information**
Explanation	An error occurred while creating a listener from the settings in a package's listeners.cnf file.
Action	Go to the Settings > Logging > Server Log page in the Integration Server Administrator and increase the logging level for the "0070 Listeners" logging facility to TRACE. Reload the package that has the affected port or restart Integration Server. If the problem recurs, capture the exception written to the server log and send it to Software AG Global Support. If you cannot connect to Integration Server because all ports are affected, contact Software AG Global Support and provide them with the listener.cnf file from the WmRoot package.

ISS.0070.0006E	**Failed to save configuration information**
Explanation	An error occurred while saving listener settings.
Action	Increase the logging level for the "0070 Listeners" logging facility to TRACE and try to save the listener settings again. If the problem recurs, capture the exception written to the server log and send it to Software AG Global Support.

ISS.0070.0008W	**Failed to bootstrap listener {0}**
Explanation	The listener could not be started from the settings in the listeners.cnf file in a package's config directory. This file may have been manually edited or corrupted.
Action	If you have a backup of the listeners.cnf file, restore it and reload the package or restart Integration Server.

ISS.0070.0013W	**Failed to start listener {0}. The following error was encountered: {1}**
Explanation	Could not start the listener.
Action	See error details in the message.

ISS.0070.0025I **Access to {0} from host {1} was denied.**

Explanation The host with the specified IP address is unable to invoke services through the specified port. Possible reason for this could be the following:- The host with the specified IP address is in the deny list of the port. - In case of an Enterprise Gateway, the host is in the Enterprise Gateway deny list.

Action The following lists the actions you can take:- If the host with the specified IP address is in the deny list of the port, delete the host from the Deny List table in the Security > Ports > IP Access > <port> page in the Integration Server Administrator.- If the host with the specified IP address is in the Enterprise Gateway deny list, delete the IP address of the host from the Denied IP Address List table in the Security > Enterprise Gateway Rules > Denial of Service Options page in the Integration Server Administrator.

ISS.0070.0027E **An I/O or Socket exception has occurred on {0}**

Explanation An error occurred while listening on a port.

Action See the exception message for details about the error.

ISS.0070.0030W **Duplicate alias {2} encountered creating {0} listener on port {1}**

Explanation When loading a package, Integration Server encountered a port alias that is the same as an existing port alias on Integration Server. The alias for a port must be unique across the Integration Server. Integration Server loads and enables the package but will not create the port with the duplicate alias.

Action If you do not want the port created, you do not need to do anything. However, if you want the port to be created when the package is loaded, delete the existing port with that alias, create a new port that has the same properties as the just deleted port, and then reload the package containing the duplicate alias. Integration Server creates the port when the package is reloaded.

ISS.0070.9001E **Invalid global service {0}**

Explanation Invalid global service name provided for message processing. An e-mail listener was started. When the Integration Server tried to determine which service to use for message processing for this listener, the Integration Server detected a problem with the name of the service specified as the Global Service. The Global Service overrides the setting for the Default Service or the service specified in the e-mail message from the e-mail client. The problem could be that the service name is specified in the wrong case (service names are case sensitive) or that the specified service does not exist in the Integration Server's namespace.

Action Examine the Global Service name provided. Make sure the name is in the correct case and that the service exists in the Integration Server's namespace.

ISS.0070.9002E **Invalid default service {0}**

Explanation An e-mail listener was started. When the Integration Server tried to determine which service to use for message processing for this listener, the Integration Server detected a problem with the name of the service specified as the Default Service. The Integration Server executes the Default Service if no service is specified in the e-mail message and no service is specified for the Global Service in the Email Client Configuration screen on the Integration Server Administrator. The problem could be that the service name is specified in the wrong case (service names are case-sensitive) or that the specified service does not exist in the Integration Server's namespace.

Action Examine the Default Service name provided. Make sure the name is in the correct case and that the service exists in the Integration Server's namespace.

ISS.0070.9003 **Enable failed: Could not log into account {0}@{1}**

ISS.0070.9005 **Must provide Server Host**

ISS.0070.9006 **Must provide Server Type**

ISS.0070.9007 **Must provide User Name**

ISS.0070.9009 **Error starting to listen: {0}**

ISS.0070.9010 **A number must be provided for the port**

ISS.0070.9011E **An invalid port number was provided**

Explanation An administrator entered an invalid port number on a port configuration screen in the Integration Server Administrator.

Action Specify a positive integer from 1 through 65534 for the port number.

ISS.0070.9012 **A port number must be provided**

ISS.0070.9013 **Private key not specified**

ISS.0070.9014	**Private key file does not exist**
ISS.0070.9015	**Listener is not enabled**
ISS.0070.9016	**A listener must be provided**
ISS.0070.9017	**Could not process certificate {0}**
ISS.0070.9018	**Peer certificate chain is not present**
ISS.0070.9019	**Peer certificate is not in IS Certificate map**
ISS.0070.9020	**Peer certificate chain is not trusted**
ISS.0070.9021	**Invalid/unsupported listener type found, {0}**
ISS.0070.9022	**Invalid value for minimum threads={0}**
ISS.0070.9023	**Invalid value for maximum threads={0}**
ISS.0070.9024	**Invalid value for thread priority={0}, minimum priority=1 and maximum priority=10**
ISS.0070.9025	**Invalid min/max threads min={0} is greater than max={1}.**
ISS.0070.9026	**Invalid thread priority={0}, minimum priority={1} and maximum priority={2}**
ISS.0070.9027	**Invalid port backlog queue value={0}**

ISS.0070.9028 **Invalid keep alive timeout value={0}**

ISS.0070.9029 **Invalid Enterprise Gateway internal port number {0}**

ISS.0070.9030 **Invalid port number {0}**

ISS.0070.9031 **Invalid maximum number of connections value {0}**

ISS.0070.9039 **Access denied to host: Hostname verification failed. The CN "{0}" in the subject DN of the certificate does not match the hostname "{1}".**

ISS.0070.9040 **Aborting connection, Server Certificate purpose verification failed**

ISS.0070.9041 **Key alias is empty. Specify a key alias for the port or a global SSL key alias on the Security > Certificates > Edit page.**

Explanation The port cannot be enabled because a key alias was not specified and there is not a default SSL key alias for the Integration Server.

Action Before enabling the port, either define a key alias or specify a default SSL key alias for the Integration Server. The default SSL key alias is the keys alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined key alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL key alias with the HTTPS port, do not supply key alias information for the create or update operations.

ISS.0070.9042 **Keystore alias is empty. Specify a keystore alias for the port or a global SSL keystore alias on the Security > Certificates > Edit page.**

Explanation The port cannot be enabled because a keystore alias was not specified and there is not a default SSL keystore alias for the Integration Server.

Action Before enabling the port, either define a keystore alias or specify a default SSL keystore alias for the Integration Server. The default SSL keystore alias is the keystore alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined keystore alias with a port, specify that keystore alias when creating or updating the port. To use the Integration Server's default SSL keystore alias with the port, do not supply keystore alias information when creating or updating the port.

ISS.0070.9043 **Invalid keypair specified. Public and private keypair moduli don't match**

ISS.0070.9044E **Unsupported key type: {0}. The HTTPS/FTPS listener supports RSA keys only. Specify a key store that contains the appropriate RSA private key.**

Explanation HTTPS or FTPS listener is configured with a keystore having DSA or EC key types. The HTTPS/ FTPS listener currently supports only RSA keys.

Action Configure the HTTPS or FTPS listener to use a keystore that contains the RSA key.

ISS.0070.9046E **Invalid character/s found in host name, {0}, in IP Access Deny list.**

Explanation The specified host in the deny list contains one or more invalid characters.

Action Correct the host name to remove the invalid characters. The host names or IP addresses can include upper and lower case alphabetic characters, digits (0-9), hyphens (-), and periods (.) and cannot include spaces. For IPv6, IP addresses can also include colons (:) and brackets ([])

ISS.0070.9048E **Integration Server cannot find the file {0} specified for the server configuration parameter {1}.**

Explanation The specified server configuration parameter uses a file to identify the allowed cipher suites; however, Integration Server cannot find the file.

Action Make sure the server configuration parameter specifies the correct location of an existing file.

ISS.0076.9021E **Error invoking the protocol buffer compiler. Error: {0}**

Explanation An error has occurred while trying to compile a message descriptor for a publishable document type. At run time, the error text from the compiler replaces the {0} placeholder in the message. This error could occur under several circumstances including: when an IS document type is made publishable for the first time, when a publishable document type is edited and then saved, or when the publishable document type is synchronized with the Universal Messaging server.

Action Use the error message to identify and correct the error. Then, repeat the action that led to the error. For example, if the error occurred when saving changes to a publishable document type, retry saving the publishable document type.

ISS.0076.9022E **Protocol buffer coder cannot find descriptor in document type: {0}**

Explanation An error occurred while encoding or decoding an instance of the specified publishable document type. Integration Server cannot find the message descriptor for the publishable document type. Integration Server creates a message descriptor for a publishable document type with an encoding type set to protocol buffers.

Action Make sure the publishable document type is synchronized with the messaging provider.

ISS.0081.9183E	**All binders must contain the same operations**
Explanation	The binders in the Web service descriptor do not contain the same operations. In a service first provider Web service descriptor with multiple binders, the binders must contain the same operations.
Action	Modify the binders to contain the same operations.

ISS.0081.9184W	**The web service descriptor does not contain any operations**
Explanation	A provider Web service descriptor cannot be saved if it does not contain any operations.
Action	Add operations to the provider Web service descriptor.

ISS.0081.9185E	**Cannot resolve operation {0} in binding {1}; operation does not have a unique SOAPAction or a unique first element name.**
Explanation	The provider Web service descriptor could not be created because the operation in the specified binding does not have a unique SOAPAction value or the first part element in the operation's input message is not unique. If neither of these values are unique, Integration Server cannot match an incoming web service request with an operation.
Action	Modify the WSDL document so that operations within a binding have unique SOAPAction values or make sure operations with duplicate SOAPAction values have an input message in which the first part element is unique.

ISS.0081.9186W	**Web service name will change from: {0} to: {1}**
Explanation	Changing the value of the Pre-8.2 compatibility mode property for a provider Web service descriptor results in a change to the value of the name attribute in the wsdl:service element in the associated WSDL document. Web service descriptors that run in pre-8.2 compatibility mode use the local name of the Web service descriptor as the service name. Web service descriptors that do not run in pre-8.2 compatibility mode use the fully qualified name of the Web service descriptor as the service name. For example, suppose that a Web service descriptor has the fully qualified name folder.myFolder:myWebService. If the Web service descriptor runs in pre-8.2 compatibility mode, in the WSDL document, the value of the name attribute in the wsdl:service element is "myWebService". If the Web service descriptor does not run in pre-8.2 compatibility mode, in the WSDL document, the value of the name attribute in the wsdl:service element is "folder.myFolder:myWebService".
Action	Existing consumer Web service descriptors and Web service connectors created from an earlier version of the WSDL document are not affected by the service name change and will execute as expected. However, web service clients created on other platforms might be affected. If a web service client is affected by the name change, regenerate the client using the updated WSDL document.

ISS.0081.9191W	**The fault has a message part "{0}" defined by the type "{1}". Message parts in a fault must be defined by the element attribute instead of the type attribute.**
Explanation	The WSDL for the Web service descriptor contains a fault message part defined by the type attribute. To be deployed to the Web services stack in version 8.2 or later of Integration Server, the fault message part must be defined using the element attribute.
Action	To enable the WSDL for the Web service descriptor to be deployed to the Web services stack, modify the fault message part in the source WSDL used to create the Web service descriptor.

ISS.0081.9192W	**WS Security Handler has no effect when the Pre-8.2 compatibility mode property is false. To enforce WS Security attach WS Policies.**
Explanation	When a Web service descriptor is not running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to false), Integration Server does not execute the WS Security Handler. As a result, the WS Security Handler has no effect and WS Security will not be enforced.
Action	If you want to enforce WS Security, create the appropriate WS Policies and attach the WS Policies to the Web service descriptor.

ISS.0081.9193W	**WS Policies has no effect when the Pre-8.2 compatibility mode property is true.**
Explanation	When a Web service descriptor is running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to true), Integration Server does not enforce WS Policies attached to the Web service descriptor.
Action	If you want to enforce WS Policies (including those with WS-Security assertions), set the Pre-8.2 compatibility mode property to false. As an alternative, if you want to keep the Pre-8.2 compatibility mode property is set to true and still enforce WS Security policies, you can use the Integration Server WS Security facility. In this case, remove all WS Policies that you have attached to the Web service descriptor and attach the WS Security Handler. For more information about the WS Security Handler, see the Designer online help.

ISS.0081.9205E	**JMS Binders are not supported when Pre-8.2 compatibility mode is true.**
Explanation	One of the following situations occurred: the Pre-8.2 compatibility mode property was changed from false to true for a Web service descriptor that contains a binder with a Transport property set to JMS, a binder that specifies the JMS transport was added to a Web service descriptor that runs in compatibility mode (the Pre-8.2 compatibility mode property is set to true), or the Transport property for an existing binder was changed to JMS for a Web service descriptor that runs in compatibility mode. A Web service descriptor for which the Pre-8.2 compatibility mode property is set to true does not support binders with a JMS transport.
Action	If you want to keep the JMS binder, change the Pre 8.2 compatibility mode property from true to false. If you want to keep the Web Service descriptor in Pre 8.2 compatibility mode, delete any binders using the JMS transport or change the binder Transport property to a supported transport (HTTP or HTTPS). Then, save the modified Web service descriptor.

ISS.0084.0001E	**Invalid credentials**
Explanation	Integration Server validates any credentials (username/password or certificates) that are supplied by the client, and if those credentials fail to match any user known to Integration Server, Integration Server will return this exception back to the client.
Action	Supply the correct credentials.

ISS.0084.9009W	**Warning: CSRF secure token is not present in the request. If you still want to complete this request, click Continue.**
Explanation	CSRF token is missing in the request URL, possibly due to a CSRF attack.
Action	If the request is valid, click Continue to complete the request.

ISS.0084.9010E	**CSRF secure token is not present in the request.**
Explanation	CSRF token is missing in the request URL, possibly due to a CSRF attack.
Action	If the request is valid, provide a valid CSRF token for the request.

ISS.0084.9101E	**Access Denied**

ISS.0085.9208E	**Service first provider Web service descriptors cannot be refreshed.**
Explanation	An attempt was made to refresh a service first provider Web service descriptor. Only WSDL first provider Web service descriptors and consumer Web service descriptors can be refreshed.
Action	None.

ISS.0085.9209E	**Cannot refresh Web service descriptor. The Web service descriptor cannot be found in the Integration Server namespace.**
Explanation	A Web service descriptor cannot be refreshed because it does not exist in the Integration Server namespace.
Action	None.

ISS.0085.9211E	**Cannot roll back Web service descriptor to previously saved version.**
Explanation	An attempt to refresh a Web service descriptor failed. However, Integration Server could not roll back to the most recently saved version of the Web service descriptor and its associated assets. This can happen if Integration Server becomes unresponsive when rolling back the Web service descriptor.
Action	Delete the Web service descriptor and recreate it using the updated WSDL document. Note that any changes made to the Web service descriptor, such as new headers or faults, will be lost. Alternatively, if the Web service descriptor was checked into a version control system, check out the last checked in version of the Web service descriptor and then refresh the Web service descriptor

ISS.0085.9212E	**Cannot Save the refreshed Web service descriptor.Integration Server will rollback to the most recently saved versions of the Web service descriptor and its associated assets.**
Explanation	The WSDL file used to refresh the Web service descriptor contains or references an invalid schema.
Action	Use the information in the server log to determine why the schema is invalid. Correct the WSDL file or the associated XML Schema definition. Then, refresh the Web service descriptor.

ISS.0085.9213E	**Cannot refresh Web service descriptor. One or more operations cannot be merged. Integration Server will roll back to the most recently saved versions of the Web service descriptor and its associated assets.**
Explanation	As part of refreshing a Web service descriptor, Integration Server merges in changes made to existing services used as operations. One of the following can prevent Integration Server from merging the changes in successfully: - The contents or properties of an existing service could not be merged into the refreshed version of the service. - The ACL information could not be set for the refreshed service. - An existing service could not be locked. Integration Server will roll back to the most recently saved versions of the Web service descriptor and its associated assets.
Action	Contact Software AG Global Support. Obtain a copy of the server log before contacting support.

ISS.0085.9214W	**The {0} docTypes folder contained one or more user-defined document types used for headers. These document types were deleted when the Web service descriptor was refreshed.**
Explanation	The specified docTypes folder contains a document type used for a header in the Web service descriptor. This document type will be deleted upon refresh. When refreshing a Web service descriptor, Integration Server deletes the WSDName_docTypes folder and all elements contained in that folder and its subfolders. Integration Server will not recreate any assets manually added to the folder or its subfolders.
Action	Do not add any assets to any of the folders created automatically by Integration Server for a Web service descriptor including the WSDName_doctypes folder. If you added any assets to the folders, move the assets to another folder before refreshing the Web service descriptor.

ISS.0085.9215W	**The {0} docTypes folder contained one or more user-defined document types used for faults. These document types were deleted when the Web service descriptor was refreshed.**
Explanation	The specified docTypes folder contained a document type used for a fault in the Web service descriptor. This document type will be deleted upon refresh. When refreshing a Web service descriptor, Integration Server deletes the WSDName_docTypes folder and all elements contained in that folder and its subfolders. Integration Server will not recreate any assets manually added to the folder or its subfolders.

Action	Do not add any assets to any of the folders created automatically by Integration Server for a Web service descriptor including the WSDName_doctypes folder. If you added any assets to the folders, move the assets to another folder before refreshing the Web service descriptor.

ISS.0085.9262	**No registered handler found for Header QName:{0}**
Explanation	The WSDL you are using to create the Web service connector has a header defined, but a matching header handler is not registered in Integration Server.
Action	Add a header handler with a QNAME matching the Document Universal Name to Integration Server, then create the Web service connector. If you do not have the appropriate header handler, you can continue the process and Developer will create the Web service connector without the header information.

ISS.0085.9283	**Unknown ExtensibleElement "{0}" found in SOAPBinding "{1}"**
Explanation	The WSDL used to create the Web service descriptor contains a binding element with a child other than SOAP 1.1 or SOAP 1.2. Integration Server does not support extensions to SOAP, such as sdk:binding (Microsoft SOAP-Toolkit extensions). Integration Server will process the valid portions of the SOAP 1.1 or SOAP 1.2 binding, but will skip processing of the unsupported extension.
Action	Verify that the WSDL contains a valid SOAP 1.1 or SOAP 1.2 binding, and is usable without the extension.

ISS.0085.9315E	**Binding {0} contains duplicate operation names {1}**
Explanation	Web service descriptor cannot be generated. A binding in the WSDL document contains more than one operation with the same name.
Action	Modify the WSDL document so that operation names are unique within a binding.

ISS.0085.9317E	**Error occurred during export of the package {0}. Details : {1}**
Explanation	Integration Server could not export the package because an error occurred during export.
Action	Read through the details provided in the error message and take corrective steps.

ISS.0085.9318E	**Invalid parameters passed. Make sure each required parameter is passed as an input to the service.**
Explanation	Integration Server cannot export the assets because the required input parameters are not specified.
Action	Specify all the required parameters.

ISS.0085.9319E	**Archive name passed "{0}" is invalid**
Explanation	The name of the archive contains illegal characters.
Action	Remove all illegal characters from the archive name.

ISS.0085.9320E	**Invalid service found; service {0} does not define any ports**
Explanation	The WSDL document contains a wsdl:service element that does not define any ports. A Web service descriptor cannot be created.
Action	Modify the WSDL document to include ports in the wsdl:service element.

ISS.0085.9321E	**Invalid port found; port {0} does not specify a binding**
Explanation	The WSDL document contains a wsdl:port element that does not specify a binding. A Web service descriptor cannot be created.
Action	Modify the WSDL document to include a binding for the port.

ISS.0085.9322E	**Invalid SOAP binding found; binding {0} does not contain all operations for corresponding portType {1}**
Explanation	The specified binding does not contain all of the operations declared in the specified portType.
Action	Modify the WSDL document so that the binding contains all of the operations declared in the specified portType.

ISS.0085.9323W	**Port alias for JMS Binder "{0}" set to "{1}". Ensure that this is the correct port alias.**
Explanation	When creating a WSDL first provider Web service descriptor, Integration Server uses the first JMS provider web service endpoint alias listed on the Settings > Web Service Endpoints page in Integration Server Administrator as the port alias.
Action	If you want to use a different JMS provider web service endpoint alias as the port alias, select the JMS binder and assign a different port alias.

ISS.0085.9324E	**Unable to create JMS Binder for binding {0}. There is not a defined JMS provider web service endpoint alias.**
Explanation	When creating a WSDL first provider Web service descriptor, Integration Server uses the first JMS provider web service endpoint alias listed on the Settings > Web Service Endpoints page in Integration Server Administrator as the port alias. If there is no defined JMS provider web service endpoint alias, Integration Server does not create the Web service descriptor.
Action	Create a JMS provider web service endpoint alias. Then create the WSDL first provider Web service descriptor.

ISS.0085.9325E	**Invalid parameter passed. {0} is a required parameter.**
Explanation	Integration Server cannot export the assets because the required input parameters are not specified.
Action	Specify all of the required parameters.

ISS.0085.9326E	**Error occurred while exporting runtime configurations: {0}. For more information, see the Integration Server logs.**
Explanation	Deployer encountered an error while exporting runtime configurations: {0}.
Action	Check Integration Server log for more information.

ISS.0085.9327E,W	**Unknown transport found in binding {0}. {1} is not a valid transport value.**
Explanation	The WSDL document used as the source for the Web service descriptor contains a binding with an invalid transport attribute. Integration Server will not create a WSDL first provider Web service descriptor when a binding transport is invalid. Integration Server will create a consumer Web service descriptor when a binding transport is invalid if the WSDL document contains other valid bindings.
Action	No action is required.

ISS.0085.9328E,W	**No transport found in binding {0}. Valid transport value is required.**
Explanation	The WSDL document used as the source for the Web service descriptor contains a binding that does not specify a transport. Integration Server will not create a WSDL first provider Web service descriptor when a binding transport is missing. Integration Server will create a consumer Web service descriptor when a binding transport is missing if the WSDL document contains other valid bindings.
Action	If possible, determine the actual transport type and then edit the WSDL document to specify that transport for the specified binding.

ISS.0085.9329E,W	**Unable to create JMS Binder for binding {0}. JMS Binders can be created using Designer only.**
Explanation	The source WSDL document for the Web service descriptor contains a SOAP JMS binding. Developer cannot be used to create a WSDL first provider Web service descriptor from a WSDL document with a SOAP JMS binding. Developer can be used create a consumer Web service descriptor from a WSDL document with a SOAP JMS binding if the WSDL document contains other valid SOAP HTTP bindings, but the resulting consumer Web service descriptor will not have a JMS binder.
Action	Use Designer to create the Web service descriptor.

ISS.0085.9331E	**Error occurred while deploying the asset: {0}. For more information, see the Integration Server logs.**
Explanation	Integration Server encountered an error while deploying the asset. Typical reasons for this error are: 1) Stream is already read. 2) An I/O error occurred. 3) Value for aclData input parameter is not provided. 4) Any other error that occurred during deployment.
Action	Read through the details provided in the error message and take corrective steps.

ISS.0085.9333W	**JVM "{0}" of the target Integration Server for installing package "{2}" is older than the recommended JVM "{1}".**
Explanation	The target Integration Server is running a JVM version that is older than the version recommended by the source package.
Action	Ensure that the target Integration Server is running the same or a later version of the JVM specified during release creation.

ISS.0085.9334E	**The version of target package cannot be null for a patch release.**
Explanation	The source package being installed is a patch release, but when the patch release was created, no version was specified for the target package.
Action	Specify a version for the target package when creating the patch release.

ISS.0085.9335W	**The target Integration Server version "{2}" and the Integration Server version "{1}" recommended by source package "{0}" are incompatible.**
Explanation	The target Integration Server version does not match the Integration Server version recommended by the source package.
Action	Ensure that the version of the target and source Integration Servers are the same.

ISS.0085.9336W	**Package "{2}" will not be deployed because the source package is a patch release and target package version: "{0}" does not match the required target package version: "{1}".**
Explanation	During installation of a patch release, Integration Server detected that the version of the target package is not the version required by the patch release.
Action	Install the correct version of the target package before applying the patch.

ISS.0085.9337W	**Package "{0}" will not be deployed because the source package is a patch release and the target package does not exist.**
Explanation	Integration Server could not install the package because the source package being installed is a patch release and the required package does not exist on the target server.
Action	The following lists the actions you can take: 1) Install the package in the target server before applying the patch. -OR- 2) Redefine the source package to a full release before deploying the package on the target server.

ISS.0085.9338W	**Package "{2}" will not be deployed because the version of source package: "{0}" is older than the version of target package: "{1}".**
Explanation	The package installed in the target server is of a later version than the source package being installed.
Action	Ensure that the version of the package on the target server is earlier than or the same as the package being installed.

ISS.0085.9341E	**Recursive invoke of wm.server.util:remoteInvoke service on a local server is not allowed.**
Explanation	You cannot invoke the wm.server.util:remoteInvoke service using the wm.server.util:remoteInvoke service recursively on a local server. Recursive invoke of wm.server.util:remoteInvoke service on a local server results in reduced thread availability and after sometime, Integration Server stops responding.
Action	Make sure that you are not invoking the wm.server.util:remoteInvoke service recursively on a local server.

ISS.0085.9377E	**Internal Error - Asset {0} does not exist**
Explanation	While using the local service development feature in Software AG Designer, an attempt to move, copy, or rename an IS asset, such as a flow service, java service, document type, or trigger, resulted in an internal error occurred. At run time, the {0} in the message is replaced with the name of the IS asset being moved, copied, or renamed.
Action	Contact Software AG Global Support.

ISS.0085.9380E	**Invalid folder name {0}. Error : {1}**
Explanation	The specified folder name is invalid.
Action	Specify a valid folder name.

ISS.0085.9381E	**Folder {0} is not empty**
Explanation	The specified folder must be empty.
Action	Delete the contents of the specified folder or specify an empty folder.

ISS.0085.9382E	**Message addressing endpoint alias "{0}" of type "{1}" does not exist.**
Explanation	The specified message addressing endpoint alias does not exist.
Action	Ensure that the message addressing endpoint alias name that you specified is correct and that this endpoint alias exists.

ISS.0085.9383E	**Cannot delete message addressing endpoint alias "{0}" because it is referred to by the following provider endpoint aliases {1}**
Explanation	A Web service endpoint alias for a provider Web service descriptor is using the message addressing endpoint alias that you attempted to delete as a part of the Response Map. Integration Server can only delete a message addressing endpoint alias if it is not in use.
Action	Before deleting a message addressing endpoint alias, ensure that the endpoint alias is not associated with the Response Map of any provider Web service endpoint alias.

ISS.0085.9385E	**Reliable messaging sequence {0} not found.**
Explanation	No reliable messaging sequence for the specified internal Sequence Id was not found.
Action	Ensure that a valid Internal Sequence Id is specified.

ISS.0085.9389E	**Host Name must be only ASCII characters.**
Explanation	Host Name contains non-ASCII characters. Host Name must consist of only ASCII characters.
Action	Specify a valid host name consisting of only ASCII characters.

ISS.0085.9390E	**User Name must be only ASCII characters.**
Explanation	User Name contains non-ASCII characters. Host Name must consist of only ASCII characters.
Action	Specify a valid User Name consisting of only ASCII characters.

ISS.0085.9391E	**Port Number must be positive integer between 0 and 65535 (inclusive).**
Explanation	Port must be a positive integer.
Action	Specify a valid integer between 0 and 65535 (inclusive) for Port.

ISS.0085.9392E	**Password must be only ASCII characters.**
Explanation	Password contains non-ASCII characters. Password must consist of only ASCII characters.
Action	Specify a valid password consisting of only ASCII characters.

ISS.0085.9393E	**Proxy server alias {0} does not exist.**
Explanation	Proxy server alias does not exist.
Action	Specify a valid configured proxy server alias.

ISS.0085.9394E	**Protocol must be either HTTP or HTTPS or FTP or SOCKS.**
Explanation	The specified protocol is not valid. Protocol must be HTTP, HTTPS, FTP or SOCKS.
Action	Specify one of the following as the protocol: HTTP, HTTPS, FTP, or SOCKS.

ISS.0085.9395E	**Invalid FTP proxy type.**
Explanation	Invalid FTP proxy type. The FTP proxy type must be an integer within the range of 0 and 7 (inclusive).
Action	Specify an interger within the range of 0 to 7 (inclusive).

ISS.0085.9396E	**Proxy server alias contains illegal characters.**
Explanation	The Proxy server alias name is invalid because it contains invalid characters such as #&@^!%*:$./\ \~;,~+=)(|}.{/\><.
Action	Specify a proxy server alias name that does not contain the following characters: #&@^!%*:$./\ \~;,~+=)(|}.

ISS.0086.9063E	**Missing required value: string**
Explanation	The string parameter is required but is either missing from the pipeline or is null.
Action	Make sure the string parameter is being supplied to the service and that the value of string is not null.

ISS.0086.9263E	**Specified path [{0}] is not on the [{1}] allowed list in the fileAccessControl configuration file**
Explanation	The specified path is not in the list of allowed directories and/or files for the specified parameter in the fileAccessControl.cnf file. For the pub.file services, Integration Server provides additional validation checks by ensuring that the paths supplied to the pub.file services are listed in the relevant parameter (allowedReadPath, allowedWritePath, or allowedDeletePath) in the fileAccessControl.cnf file. At run time, the {0} is replaced by the supplied path and the {1} is replaced with the parameter that is being checked in the fileAccessControl.cnf file.
Action	If the supplied path is listed for the specified parameter in the fileAccessControl.cnf, make sure that the supplied path does not contain any errors such as misspellings, misplaced punctuation, and so forth. Keep in mind that path names are case-sensitive on a UNIX-based system. Additionally, note that if the path includes a semicolon, the two backslashes that must precede the semicolon for a parameter in the fileAccessControl.cnf file do not need to be included in the path supplied to the input parameter of a pub.file service. If the specified path should be in the allowed list for

the specified parameter but is not, edit the parameter in the fileAccessControl.cnf file to include the path.

ISS.0086.9287E **Applications cannot set the "{0}" field in the HTTP response header.**

Explanation The input to the pub.flow:setResponseHeader service specifies a header field that cannot be set by an application.

Action Change the input to the pub.flow:setResponseHeader service so that it does not specify a header field that cannot be set by an application.

ISS.0086.9288E **Either "{0}" or "{1}" must be supplied**

Explanation A value is required for one of the two indicated parameters.

Action Supply the missing value.

ISS.0086.9290E **Invalid JMS property name "{0}"; property name must contain only Java identifier part characters.**

Explanation The property name specified as input to pub.flow:setResponseHeaders does not meet the syntax requirement for JMS properties as described in the Java Message Service standard.

Action Modify the property name to meet the syntax requirements for JMS properties. Refer to the Java Message Service standard for information about syntax requirements for message properties.

ISS.0086.9291E **Invalid JMS property name "{0}"; reserved word.**

Explanation The property name specified as input to pub.flow:setResponseHeaders contains a reserved word as described in the Java Message Service standard.

Action Modify the property name by removing the reserved word. Refer to the Java Message Service standard for information about reserved words for message properties.

ISS.0086.9292E **Applications cannot set the "{0}" field in the JMS response header.**

Explanation The input to the pub.flow:setResponseHeader service specifies a message header field that cannot be set by an application.

Action Change the input to the pub.flow:setResponseHeader service so that it does not specify a header field that cannot be set by an application.

ISS.0086.9293E	**At least one of the parameters, "generateHeaderDocumentTypes", "generateBodyDocumentTypes" or "generateFaultDocumentTypes", must be set to true.**
Explanation	The "generateHeaderDocumentTypes", "generateBodyDocumentTypes", and "generateFaultDocumentTypes" parameters are all set to false while executing the pub.soap.handler:generateDocumentTypesFromWSDL service.
Action	Set the value of any one of these parameters to true.

ISS.0086.9294E	**If convertAllPackages is set to true, packageNames cannot be specified.**
Explanation	When convertAllPackages is set to true, the pub.ws.utils:setCompatibilityModeFalse service sets the Pre-8.2 compatibility mode property to false for each Web service descriptor in an enabled package. It is invalid to specify individual packages in packageNames as well.
Action	Either remove the specified value for packageNames or set convertAllPackages to false.

ISS.0086.9295E	**If convertAllPackages is set to false, packageNames must be specified.**
Explanation	When convertAllPackages is set to false, the packageNames parameter must specify the names of the packages that contain the Web service descriptors for which to change the Pre-8.2 compatibility mode value.
Action	Either specify packages in packageNames or set convertAllPackages to true.

ISS.0086.9296E	**Package {0} not enabled.**
Explanation	The specified package is not enabled. The pub.ws.utils:setCompatibilityModeFalse service can change Web service descriptors in enabled packages only.
Action	Enable the package.

ISS.0086.9297E	**Package {0} not found.**
Explanation	The packageNames parameter specifies a package that does not exist.
Action	Ensure that the package name is spelled correctly. Additionally, verify that package exists on the Integration Server.

ISS.0086.9298E	**Unable to lock Web service descriptor for editing.**
Explanation	The Pre-8.2 compatibility mode property cannot be changed because an error occurred while attempting to lock the Web service descriptor for editing.
Action	Determine what error prevents locking of the Web service descriptor by examining the lock properties of the Web service descriptor or by attempting to lock (or check out) the Web service descriptor. Either action should provide a detailed error message that you can use to resolve the error. Then either run the pub.utils.ws:setCompatibilityModeFalse service again or lock (check out) the Web

service descriptor and change the value of the Pre-8.2 compatibility mode property manually.

ISS.0086.9299E **Web service descriptor is locked by another user.**

Explanation The Pre-8.2 compatibility mode property cannot be changed because another user has the Web service descriptor checked out or locked for editing.

Action Review the lock properties of the Web service descriptor to determine which user has it checked out or locked for editing. After the user unlocks (or checks in) the Web service descriptor, either run the pub.utils.ws:setCompatibilityModeFalse service again or lock (check out) the Web service descriptor and change the value of the Pre-8.2 compatibility mode property manually.

ISS.0086.9309E **Could not release a lock of type {0} for key {1} in cache {2} contained within the cache manager {3}. Error:{4}**

Explanation The specified lock type for the specified key, cache, and cache manager does not match the actual lock type held. This error also occurs if a release lock is called from a thread that did not lock the key.

Action Specify the correct lock type or invoke the service from the same thread that acquired the lock.

ISS.0086.9312E **Error while executing command {0}: {1}**

Explanation Integration Server encountered an error while executing the command. Typical reasons are: 1) The session is invalid. 2) The command parameter is invalid. 3) The SFTP server is not reachable.

Action Read through the details provided in the error message and take corrective steps.

ISS.0086.9313E **Invalid session {0}**

Explanation The session key that you specified is invalid.

Action Ensure that session key is correct and that the session corresponding to this session key exists.

ISS.0086.9314E **Session {0} expired.**

Explanation The session key that you specified has expired.

Action Adjust the session timeout value for this SFTP user alias according to your requirements. Once a session expires, you must create a new session.

ISS.0086.9315E	**Session {0} is in use. Integration Server does not support parallel command execution on a session.**
Explanation	You attempted to execute commands in parallel.
Action	Integration Server does not support parallel command execution on a session. Ensure that you execute the commands sequentially.

ISS.0086.9316E	**One or more required values are missing: {0}.**
Explanation	You have not provided all the mandatory input parameters that Integration Server requires to execute the SFTP put command.
Action	Ensure that you provide all the input parameters to execute the SFTP put command. For example, to execute the put command, you have the option to provide a combination of contentStream and remote file name. Integration Server throws this error if you do not provide both the input parameters in this combination.

ISS.0086.9317E	**Invalid mode: {0}.**
Explanation	The mode that you specified to execute an SFTP command is invalid.
Action	Ensure that you specify a valid value for mode. Valid values are "OVERWRITE","RESUME", and "APPEND".

ISS.0086.9334E	**The packageNames and documentTypeNames input parameters are mutually exclusive.**
Explanation	Values cannot be specified for both the packageNames and documentTypeNames input parameters.
Action	Specify either packageNames or documentTypeNames or neither. If you specify neither, Integration Server searches through all the pub.utils:messaging:migrateDocTypesTriggersToUM attempts to migrate all publishable document types contained in packages that do not start with the letters “wm” in any case combination.

ISS.0086.9335E	**Error creating package archive:{0}.**
Explanation	Integration Server could not create an archive for a package. At run time, the {0} is replaced by the error message that caused package archiving to fail.
Action	Use the error message to correct the cause of the error, then , execute the pub.utils.messaging:migrateDocTypesTriggersToUM service. Note that when using the service to migrate the contents of multiple packages, it might be hard to determine for which package Integration Server could not create an archive. If the server log facility 0153 Dispatcher (Universal Messaging) is set to the Debug level, when the pub.utils.messaging:migrateDocTypesTriggersToUM service executes, the server log will indicate which package Integration Server attempted to archive when the error occurred.

ISS.0086.9336E **Unable to lock for editing. Lock status:{0}.**

Explanation The publishable document type could not be locked and therefore cannot be updated.

Action Use the lock status to determine why the publishable document type is locked. Once the publishable document type is unlocked, execute the pub.utils.messaging:migrateDocTypesTriggersToUM service.

ISS.0086.9337E **Locked by another user:{0}.**

Explanation The publishable document type could not be locked because it is already locked by the specified user. For the publishable document type to be updated, it must be unlocked or locked by the user executing the pub.utils:messaging:migrateDocTypesTriggresToUM service.

Action Ask the user who has the publishable document type locked to unlock it. Once the publishable document type is unlocked, execute the pub.utils.messaging:migrateDocTypesTriggersToUM service.

ISS.0086.9339E **Could not find newConnectionAlias {0}.**

Explanation Integration Server cannot find the Universal Messaging connection alias specified for the newConnectionAlias parameter. It is possible the alias does not exist or there is an error in the supplied alias name.

Action Specify an Universal Messaging connection alias that exists on Integration Server as the value for newConnectionAlias. Make sure you spell the alias name properly. Universal Messaging connection alias names are case sensitive. Then, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service.

ISS.0086.9340E **Cannot find document type:{0}.**

Explanation Integration Server cannot locate the document type.

Action Make sure the document type exists on Integration Server. Then, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service.

ISS.0086.9341E **The specified element is not a document type.**

Explanation An element specified for the documentTypeNames parameter is not a document type. Valid values for the documentTypeNames parameter are names of publishable document types that exist on Integration Server.

Action Make sure the documentTypeNames parameter specifies only publishable document types that exist on Integration Server. Then, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service.

ISS.0086.9342E	**The specified element is not a publishable document type.**
Explanation	An element specified for the documentTypeNames parameter is not a publishable document type. Valid values for the documentTypeNames parameter are names of publishable document types that exist on Integration Server.
Action	Make sure the documentTypeNames parameter specifies only publishable document types that exist on Integration Server. Then, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service.

ISS.0086.9343E	**Package not found**
Explanation	The contents of the package could not be migrated because Integration Server cannot find the package. The packageNames input parameter specifies a package that does not exist on Integration Server.
Action	Make sure the packageNames parameter specifies only packages that exist on Integration Server. Then re-execute the pub.utils.messaging:migrateDocTypesTriggersToUM service.

ISS.0086.9344E	**Package disabled**
Explanation	The contents of the package could not be migrated because the package is disabled. Only the contents of enabled packages can be migrated.
Action	Enable the package and re-execute the pub.utils.messaging:migrateDocTypesTriggersToUM service.

ISS.0086.9345W	**Document type does not belong to a package or belongs to a system package.**
Explanation	The pub.utils.messaging.migrateDocTypesTriggersToUM service skipped migration for a publishable document type because the publishable document type did not belong to a package or belongs to a system package. A system package begins with the letters “wm” in an case combination. The service modifies publishable document types or webMethods messaging triggers in a system package only when the system package is specified in the packageNames input parameter or the publishable document type was specified in the documentTypeNames input parameter.
Action	To migrate the skipped publishable document type, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service and specify the publishable document type name in the documentTypeNames input parameter. Alternatively, to migrate multiple publishable document types in a system package, re-execute the pub.utils.messaging.migrateDocTypesTriggersToUM service and specify the system package in the packageNames input parameter.

ISS.0086.9346I	**Document type not changed.**
Explanation	Integration Server skipped migration for the document type because the pub.utils.messaging.migrateDocTypesTriggersToUM service did not make any changes to the publishable document type.
Action	No action required.

ISS.0086.9347I	**Package does not contain publishable document types.**
Explanation	Migration failed for the package because it does not contain any publishable document types that can be migrated.
Action	No action required.

ISS.0086.9348E	**The "serviceName" input parameter is required.**
Explanation	There is no service name specified for the serviceName input parameter.
Action	Specify a service name for the serviceName input parameter.

ISS.0086.9350E	**The "resultSetKey" input parameter is optional.**
Explanation	The pipeline key name specified for the resultSetKey input parameter does not exist in the pipeline.
Action	Specify the correct pipeline key name for the servicePipeline input parameter.

ISS.0086.9351E	**The pipeline key name "{0}" does not exist in the wrapped service pipeline.**
Explanation	The specified pipeline key name does not exist in the wrapped service.
Action	Verify the resultset key value returned by the wrapped service.

ISS.0086.9352E	**The $internal service input parameter is required.**
Explanation	The calling service must create the $internal service input parameter before calling iterator.
Action	Create the required $internal input parameter for the iterator service and rerun.

ISS.0086.9353E	**The timeToLive input parameter must be greater than 0.**
Explanation	The timeToLive input parameter must have a value of greater than 0.
Action	Specify a value that is greater than 0 for the timeToLive input parameter.

ISS.0086.9354E	**The batchSize input parameter must be greater than 0.**
Explanation	The batchSize input parameter requires a value greater than 0.
Action	Set the batchSize input parameter to a value greater than 0 and rerun the service.

ISS.0086.9355E	**The service request has expired.**
Explanation	The value specified in the timeToLive input parameter has expired and the result set has been removed from the cache.
Action	Increase the value for timeToLive and rerun the service.

ISS.0086.9356W	**Document type is not assigned to a UM connection alias.**
Explanation	Integration Server skipped the document type during migration because a value was not specified for newConnectionAlias or a newConnectionAlias specified a Broker connection alias and the document type is either associated with a Broker connection alias or is publishable locally.
Action	Specify a value for newConnectionAlias and re-execute the pub.utils.messaging:migrateDocTypesTriggersToUM service. Alternatively, use Designer to assign the document type a Universal Messaging connection alias and then re-execute the pub.utils.messaging:migrateDocTypesTriggersToUM service.

ISS.0086.9361E	**newConnectionAlias:{0} must be an existing UM connection alias.**
Explanation	The newConnectionAlias input parameter specifies an alias that does not exist or specifies a Broker connection alias. The pub.utils.messaging.migrateDocTypesTriggersToUM service can be used to migrate publishable document types to a UM connection alias only
Action	Specify the name of a Universal Messaging connection alias that exists on Integration Server and then re-execute the pub.utils.messaging:migrateDocTypesTriggersToUM service.

ISS.0086.9362I	**Trigger does not contain any filters.**
Explanation	Integration Server skipped the trigger during migration because the trigger does not contain any filters.
Action	No action required.

ISS.0086.9363W	**Trigger already specifies a value for Provider Filter (UM).**
Explanation	Migration of the filters in the trigger failed because one or more of the trigger conditions already contains a value for Provider Filter (UM). A trigger filter cannot be migrated if a value already exists in Provider Filter (UM).
Action	Manually create the needed Provider Filter. For information about creating trigger filters for use with Universal Messaging, see the documentation.

ISS.0086.9365E	**Error retrieving Broker Transport Factory.**
Explanation	Integration Server cannot connect to the Broker. Specifically, the Broker Transport Factory cannot be located. Either the connection to the Broker is unavailable or the connection to the Broker is not configured correctly. A Broker connection is required for the pub.utils.messaging:migrateDocTypesTriggersToUM service to execute successfully.
Action	Make sure the Broker connection alias is properly configured, the Broker is installed and properly configured, and that the Broker is available.

ISS.0086.9366E	**Error retrieving Broker Transport.**
Explanation	Integration Server cannot connect to the Broker. Either the connection to the Broker is unavailable or the connection to the Broker is not configured correctly. A Broker connection is required for the pub.utils.messaging:migrateDocTypesTriggersToUM service to execute successfully.
Action	Make sure the Broker connection alias is properly configured, the Broker is installed and properly configured, and that the Broker is available

ISS.0086.9367E	**Error retrieving Broker Admin Client.**
Explanation	Integration Server cannot connect to the Broker. Either the connection to the Broker is unavailable or the connection to the Broker is not configured correctly. A Broker connection is required for the pub.utils.messaging:migrateDocTypesTriggersToUM service to execute successfully.
Action	Make sure the Broker connection alias is properly configured, the Broker is installed and properly configured, and that the Broker is available.

ISS.0086.9368I	**Converted Filter:{0} to Provider Filter (UM):{1}.**
Explanation	Integration Server converted the expression in Filter to the expression in Provider Filter (UM).
Action	No action required.

ISS.0086.9369W	**Partial filter conversion - Dropped:{0}.**
Explanation	The complete filter in the Filter field could not be migrated to the Provider Filter (UM) field. Integration Server migrated some expressions in the filter successfully, but could not migrate one or more expressions in the original filter. The pub.utils.messaging:migrateDocTypesTriggersToUM service returns this message for each expression that could not be migrated. At run time, the portion of the expression that could not be migrated replaces the {0} in the message. The contents of the Filter field will not change. That is, Integration Server does not remove the filter expressions that it migrated to Provider Filter (UM) field from the Filter field.
Action	No action is required. However, you might want to edit the contents of the Filter field by removing the expressions that were migrated to Provider Filter (UM). This will eliminate duplicate filter processing.

ISS.0086.9371E	**The node specified as input for the node parameter does not exists or is not a DOM node**
Explanation	The node specified as input to the node parameter for the pub.xmldata:domNodeToXMLData service does not exist or is not a DOM node.
Action	Make sure the node specified as input for the node parameter for the pub.xmldata:domNodeToXMLData service exists and is a DOM node.

ISS.0086.9372E	**The document type specified for the conformsTo input parameter does not exist or is not an XML document type.**
Explanation	The document type specified for the conformsTo input parameter for the pub.xmldata:domNodeToXMLData service either does not exist or is not an XML document type.
Action	Make sure that the document types specified as input to the conformsTo parameter exists and is an XML document type..

ISS.0086.9373E	**The document specified as input for the xmlDataDocument parameter does not exist or is not of type XMLData.**
Explanation	Either the specified document as input for the xmlDataDocument parameter does not exist or it is not of type XMLData. The pub.xmldata.xmlDataToXMLString service requires that the input document be of type XMLData.
Action	Make sure the document specified as input for xmlDataDocument exists and is of type XMLData. Use the Document data type property for the specified document to determine if it is of type XML Data.

ISS.0086.9380E	**The servicePrincipal input parameter is required if a jaasContext is specified.**
Explanation	If the pub.client:http service specifies a value for the auth/kerberos/jaasContext input parameter, the auth/keberos/servicePrincipal input parameter must be specified as well.
Action	Specify a value for the auth/Kerberos/servicePrincipal input parameter.

ISS.0086.9381E	**A value is not supplied for the Kerberos clientPassword input parameter. The Keberos clientPassword must be specified if the Kerberos clientPrincipal is supplied.**
Explanation	The pub.client:http service specifies a value for the auth/kerberos/clientPrincipal input parameter but does not specify a value for the auth/kerberos/clientPassword input parameter. If clientPrincipal is specified, then clientPassword must be specified.
Action	Specfiy a value for the auth/kerberos/clientPassword field.

ISS.0086.9382E	**Input to {0} must be an inputstream.**
Explanation	The input must be an input stream.
Action	Specify an inputstream.

ISS.0086.9383E	**Input must be a byte array or an inputstream.**
Explanation	The input must be a byte array or an input stream.
Action	Specify a byte array or input stream.

ISS.0086.9384E	**Input to {0} must be a (byte[]).**
Explanation	If the user does not provide a byte[] type
Action	User should provide a byte[].

ISS.0086.9385E	**Error while processing the signature stream:**
Explanation	User encounters problem while reading the stream
Action	To inform the user that there is a problem in processing the stream.

ISS.0088.9108E	**SOAP Handler {0} already registered**
Explanation	While executing pub.soap.processor:registerProcessor, Integration Server could not register the custom SOAP message processor because the registry already has a SOAP message processor registered for the supplied directive.
Action	When registering a custom SOAP message processor using pub.soap.processor:registerProcessor, specify a directive for which there is not already a custom SOAP message processor. Alternatively, use pub.soap.processor:unregisterProcessor to unregister the custom SOAP message processor that is currently registered to the specified directive and then register the new SOAP message processor with that directive.

ISS.0088.9109	**SOAP is only supported using HTTP POST protocol**
Explanation	The SOAP message handler was not able to accept the request because the SOAP message was submitted to Integration Server using the HTTP GET method. The SOAP message handler only accepts requests via the POST method (per W3C specification).
Action	Modify the client to use HTTP POST to submit SOAP messages to Integration Server.

ISS.0088.9110E	**Invalid BOOLEAN value {0} for variable {1}; must be 0 or 1**
Explanation	The addHeaderEntry service failed because the mustUnderstand attribute was not set correctly.
Action	Check the logic in the process that failed to make sure that it sets the value of the specified variable to either 0 or 1. No other values are permitted when setting the mustUnderstand attribute.

ISS.0088.9111E	**Cannot load or execute the SOAP processor {0}**
Explanation	The SOAP message handler cannot process the SOAP message because the requested SOAP processor is non-operational.
Action	On the server, check the status of the service that is registered to directiveName. Make sure this service is loaded and operating successfully. (Frequently this error occurs because the processor was modified and then did not recompile successfully.)

ISS.0088.9112E	**An Exception was thrown in the server:{0}**
Explanation	Integration Server, the SOAP processor, or one of the services processing the message has thrown an exception.
Action	See the detail element in the SOAP fault to determine the exception that was thrown and which process it was thrown by.

ISS.0088.9113E	**The SOAP Envelope does not have a Body block**
Explanation	The SOAP client was given a soapRequestData that did not contain a body element.
Action	Examine the logic in the client to see whether it uses the stringToSoapData or streamToSoapData service to generate their SOAP objects. If so, determine whether the String or stream from which the SOAP object was generated represented a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as removeHeaderEntry or removeBodyEntry) and might have inadvertently removed the entire Body element.

ISS.0088.9116]E	**The server cannot execute the requested SOAP utility; required parameter {0} is missing or invalid**
Explanation	The requested SOAP utility service failed to execute because a required parameter was not supplied.
Action	Check the logic in the SOAP processor or client to make sure that it passes the correct parameters to each SOAP utility service that it invokes.

ISS.0088.9117E **One or more header entries were not understood by the SOAP processor**

Explanation The SOAP processor has rejected the SOAP message because it cannot obey a mandatory header entry (a header entry whose mustUnderstand attribute is enabled).

ISS.0088.9118E **Parameter {0} must be a valid soapData**

Explanation The requested SOAP utility service failed to execute because the value supplied to the specified parameter s not a SOAP object.

Action Examine the logic in the SOAP processor or client and make sure that it passes a SOAP object to the specified parameter.

ISS.0088.9119E **SOAP Processor did NOT return a valid SOAP Response**

Explanation The message handler did not receive a valid SOAP message from the SOAP processor.

Action Examine the logic in the SOAP processor to make sure that it composes the SOAP response message correctly. For example, check to see whether it the processor uses the stringToSoapData or streamToSoapData services to generate soapResponseData. If so, determine whether the original String or stream represents a valid SOAP message. If the SOAP processor logic seems correct, contact Software AG Global Support. This would indicate a serious internal error.

ISS.0088.9120E **Parameter {0} is not one of the valid data types: {1}**

Explanation The requested SOAP utility failed to execute because the specified parameter did not have the correct data type. The exception message identifes the data type that is expected.

Action Examine the logic in the SOAP processor or client and make sure that it passes an object of the specified data type to the specified parameter.

ISS.0088.9122E **Service {0} does not exist**

Explanation The SOAP facility could not complete the requested operation because it could not find the specified service. This error is issued by various SOAP processes (e.g., registering a SOAP processor, invoking a SOAP processor, invoking a target service).

Action Examine the process that failed and make sure that it specifies the name of the requested service correctly. For example, if you receive this error when registering a SOAP processor, check that you have specified the svcName parameter correctly. Remember that service names are case-sensitive.

ISS.0088.9123E **Requested SOAP processor {0} is not registered on this server**

Explanation The Integration Server could not process the SOAP message because it does not have the SOAP processor requested by the client.

Action On the client side, verify that the correct process directive is specified in the URL (remember that the directive is case-sensitive). If the client has specified the process directive correctly, then use pub.soap.processor:list to verify that the requested processor is registered on the Integration Server.

ISS.0088.9124E **SOAP Message does not conform to the SOAP message model**

Explanation The SOAP message passed to the validateSoapData utility failed validation (for example, it is missing the Body element or the Header element follows the body).

Action Examine the logic that produced the message and see whether it uses the stringToSoapData or streamToSoapData service to manually generate a SOAP object instead of using the message composition services (e.g., createSoapData, addHeaderEntry, addBodyEntry). If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as removeHeaderEntry or removeBodyEntry) and might have inadvertently removed required portions of the SOAP object (for example, the entire Body element).

ISS.0088.9125E **SOAP request does not conform to the SOAP message model**

Explanation The SOAP message handler could not process the SOAP request because it violates the SOAP message schema (for example, it is missing the Body element or the Header element follows the body).

Action On the client side, correct the logic that builds the message to ensure that it produces a valid SOAP message.

ISS.0088.9126E **SOAP response does not conform to the SOAP message model**

Explanation The SOAP message handler could not return the SOAP response generated by a SOAP processor on the Integration Server because the message violates the SOAP message schema.

Action Examine the logic in the SOAP processor and see whether it uses the stringToSoapData or streamToSoapData service to generate a SOAP object. If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Examine the logic that produced the message and see whether it uses the stringToSoapData or streamToSoapData service to manually generate a SOAP object instead of using the message composition services (e.g., createSoapData, addHeaderEntry, addBodyEntry). If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as removeHeaderEntry or removeBodyEntry) and might have inadvertently removed required portions of the SOAP object (for example, the entire Body element).

ISS.0088.9127E	**The server could not load the SOAP XML Validator**
Explanation	The SOAP message handler encountered a serious internal error.
Action	Contact Software AG Global Support.

ISS.0088.9128E	**Request is from namespace {0}, server requires namespace {1}**
Explanation	The SOAP message handler could not process the message because the message is not from a version of SOAP that the Integration Server supports. Integration Server supports the version indicated in the exception message.
Action	From the client side, resubmit the message using a version of SOAP that Integration Server supports.

ISS.0088.9132E	**Failed to register SOAP Handler {0}, illegal characters in directive name.**
Explanation	Integration Server was not able to successfully register the SOAP processor, because directiveName contains characters that are not allowed in a directive name.
Action	Register the SOAP processor under a name that is composed only of letters, digits, or the characters -_.!~*'( ).

ISS.0088.9133E	**Error while encoding RPC output**
Explanation	While encoding RPC output, an exception occurred which resulted in an Integration Server error.
Action	Use the underlying exception to help determine what caused the error.

ISS.0088.9134E	**Exception occurred while processing the body of the message**
Explanation	Integration Server, the SOAP processor, or one of the services processing the SOAP message has thrown an exception.
Action	See the detail element in the SOAP fault to determine the exception that was thrown and by which process it was thrown.

ISS.0088.9135E	**A WMDocument Exception was thrown in the server, usually because an XML block was not well-formed**
Explanation	The SOAP message handler, the soapHTTP service, or the soapRPC service has received a SOAP message that contains invalid XML.
Action	Check the process that submitted the SOAP message to the Integration Server and make sure that it is producing valid XML. This error usually occurs because of a basic error in the XML document, such as missing tags or overlapping elements.

ISS.0088.9137E **Invalid input parameter; {0} must be a Document (IData)**

Explanation The requested SOAP service failed to execute because the object passed into the specified parameter is not an IData object.

Action Check the logic in the SOAP processor or client to make sure that it passes an IData into the specified parameter.

ISS.0088.9138E **Input parameters do not conform to targetInputSignature: {0}**

Explanation The pub.client:soapRPC service could not submit the remote procedure call because the input parameters did not pass the data-validation process.

Action This error is thrown when a client supplies an invalid set of input parameters for a SOAP remote procedure call. Specifically, it indicates that the parameters submitted to pub.client:soapRPC in reqParms do not match the structure and constraints of the document type specified in targetInputSignature. Generally, you will want to code your client to detect this kind of error and take some type of corrective action when it occurs.

ISS.0088.9139E **Output parameters do not conform to targetOutputSignature: {0}**

Explanation The SOAP RPC client could not submit the remote procedure call because the output parameters returned by the remote server did not pass the data-validation process.

Action This error is thrown when a client receives an invalid set of output parameters (results) from a SOAP remote procedure call. Specifically, it indicates that the parameters returned to pub.client:soapRPC in respParms do not match the structure and constraints of the document type specified in targetOutputSignature. Generally, you will want to code your client to detect this kind of error and take some type of corrective action when it occurs.

ISS.0088.9140E **Invalid target signature {0}, must be a Document Type**

Explanation The SOAP RPC client could not process the remote procedure call because it was not able to validate the input or output parameters associated with the request. The signature it was given for validation is not a document type.

Action Examine the logic in the SOAP RPC client and make sure that the object it specifies in targetInputSignature and/or targetOutputSignature is a document type. That is, these parameters, if used, specify the fully qualified name of a document type that exists on Integration Server.

ISS.0088.9141E **Invalid target signature {0}, Document Type does not exist**

Explanation The SOAP RPC client could not process the remote procedure call because it was not able to validate the input or output parameters associated with the request. The specified document type does not exist on the Integration Server.

Action Examine the logic in the SOAP RPC client and make sure that targetOutputSignature and/or targetOutputSignature are correctly specified. (Remember that the names of

document types are case sensitive.). Also verify that the specified document type exists on the server and the package in which it resides is loaded and enabled.

ISS.0088.9144 **this SOAPEnvelope object already contains a valid SOAPHeader object**

Explanation An attempt was made to add a SOAPHeader object to the SOAPEnvelope of a SOAPMessage that already contains a SOAPHeader object.

Action The SOAPEnvelope object may contain a maximum of one SOAP Header.

ISS.0088.9145E **this SOAPEnvelope object does not contain a valid SOAPHeader object**

Explanation An attempt was made to access the SOAPHeader object, but the SOAPEnvelope of the SOAPMessage does not contain a SOAPHeader object.

Action Add a SOAPHeader object to the SOAPEnvelope before accessing it.

ISS.0088.9147E **this SOAPEnvelope object does not contain a valid SOAPBody object**

Explanation An attempt was made to access the SOAPBody object, but the SOAPEnvelope of the SOAPMessage does not contain a SOAPBody object.

Action Add a SOAPBody object to the SOAPEnvelope before accessing it.

ISS.0088.9148E **Exception occurred while retrieving SOAPHeader object**

Explanation The specified exception occurred while attempting to access the SOAPHeader object.

Action Correct the error and retry.

ISS.0088.9149E **Exception occurred while retrieving SOAPBody object**

Explanation The specified exception occurred while attempting to access the SOAPBody object.

Action Correct the error and retry.

ISS.0088.9150E **Exception occurred while retrieving SOAPHeaderElement objects**

Explanation The specified exception occurred while attempting to access the SOAPHeaderElement object.

Action Correct the error and retry.

ISS.0088.9151E	**Exception occurred while retrieving SOAPBodyElement objects**
Explanation	The specified exception occurred while attempting to access the SOAPBodyElement object.
Action	Correct the error and retry.

ISS.0088.9152E	**The property {0} is unknown**
Explanation	An attempt was made to either get or set a property of the specified SOAPMessage, but the property name is unknown. The only valid SOAPMessage property names are javax.xml.soap.WRITE_XML_DECLARATION and javax.xml.soap.CHARACTER_SET_ENCODING.
Action	Specify the name of a valid property.

ISS.0088.9153E	**this SOAPMessage object already contains a valid Detail object**
Explanation	An attempt was made to add a Detail object to the SOAPBody of this SOAPMessage, but the SOAPBody already contains a Detail object. The SOAPBody can contain one and only one Detail object.
Action	Remove the existing Detail object before adding the new one.

ISS.0088.9154	**this SOAPMessage object already contains a valid Fault object**
Explanation	An attempt was made to add a Fault object to the SOAPBody of this SOAPMessage, but the SOAPBody already contains a Fault object. The SOAPBody can contain one and only one Fault object.
Action	Remove the existing Fault object before adding the new one.

ISS.0088.9155E	**this SOAPMessage does not contain a valid Envelope object**
Explanation	The specified SOAPMessage does not contain a valid SOAPEnvelope object.
Action	Create a new SOAPMessage that contains a valid SOAPEnvelope object.

ISS.0088.9163E	**Could not retrieve WSDL for service {0}, WSD not found.**
Explanation	Integration Server could not retrieve the WSDL for the specified Web service descriptor because the specified Web service descriptor does not exist on Integration Server.
Action	Ensure that the specified Web service descriptor exists on Integration Server.

ISS.0088.9164E	**Access to WSDescriptor {0} denied.**
Explanation	The user is not authorized to access the specified Web service descriptor.
Action	Specify a username that is authorized to access the specified Web service descriptor.

ISS.0088.9166E	**Binder not found for soapAction = {0}**
Explanation	The Web service descriptor has more than one binder, with the same operation name. Developer cannot calculate a default soapAction attribute to identify the correct operation.
Action	Include a unique soapAction attribute in the SOAPAction HTTP Header for every request.

ISS.0088.9251E	**JAX-RPC Handler failed to process the message**
Explanation	The JAX-RPC handler was invoked to process the message. Either the handleRequest() or handleResponse() method returns false, indicating a failure.
Action	Check the webMethods Integration Server log for error messages generated by the JAX-RPC handler.

ISS.0088.9252E	**An Exception has been caught: {0}**
Explanation	An exception was caught while attempting to process a SOAP message.
Action	Correct the problem indicated by the exception message.

ISS.0088.9253E	**Could not add "Text" element to "Reason" element, locale is null**
Explanation	An attempt to add a Text element to the existing Reason element failed because the locale was not specified.
Action	Specify the locale when adding the Text element.

ISS.0088.9255I	**This element's QName cannot be changed**
Explanation	An attempt to change the QName of a SOAPEnvelope, SOAPBody, or SOAPHeader failed, because the QName cannot be changed.
Action	No action is required.

ISS.0088.9356E	**One or more required Headers "{0}" are not present in the SOAP request.**
Explanation	The SOAP request received by the provider does not contain one or more required headers. Note that Integration Server considers all headers defined in a Web service descriptor to be required.
Action	Determine why the SOAP request does not contain the required headers, which might involve contacting the client to determine why the client did not include the required headers in the request.

ISS.0088.9420E	**Required parameter {0} is missing**
Explanation	A required input parameter was not provided.
Action	Provide the required input parameter.

ISS.0088.9421E	**The service {0} does not exist**
Explanation	The specified service does not exist.
Action	Specify an existing service.

ISS.0088.9422E	**Either parameter {0} or {1} must be provided**
Explanation	The service requires either one of the specified parameters, but neither was provided.
Action	Provide one of the required parameters.

ISS.0088.9423E	**Service handler {0} is already registered**
Explanation	A service handler with that name is already registered.
Action	Specify a different name when registering the service handler.

ISS.0088.9425E	**Error destroying service handler {0}. Error:{1}**
Explanation	An error occurred while destroying the JAX-RPC handler.
Action	The destroy() method of the JAX-RPC Handler has thrown an error. Correct the error in destroy() method.

ISS.0088.9427E	**Service handler {0} could not be unregistered. A service handler by that name is not registered**
Explanation	A service handler with the provided name is not registered.
Action	Specify the name of a registered service handler.

ISS.0088.9428E	**Service handler {0} could not be found. A service handler by that name is not registered**
Explanation	The specified service handler could not be found because it is not registered.
Action	Provide the name of a registered service handler.

ISS.0088.9429E	**Could not find service handler for header {0}:{1}**
Explanation	The header QName does not correspond to a registered service handler.
Action	Verify that the QName of the header corresponds to a registered service handler or register a service handler for the provided QName.

ISS.0088.9430E	**Handler processing failed on the provider**
Explanation	A handler service failed on the provider.
Action	Examine the handler services for errors and correct any errors that are found.

ISS.0088.9431E	**Handler processing failed on the consumer: {0}**
Explanation	A handler service failed on the consumer.
Action	Examine the handler services for errors and correct any errors that are found.

ISS.0088.9443E	**One or more required Headers "{0}" are not present in the SOAP response.**
Explanation	The SOAP response received by the Web service connector does not contain one or more required headers. That is, the SOAP response does not contain a header with a QName that matches the QName of a header defined in the consumer Web service descriptor. Note that Integration Server consider all headers defined in a Web service descriptor to be required.
Action	Determine why the SOAP response does not contain the required headers, which might involve contacting the provider to determine why the provider did not include the required headers in the response.

ISS.0088.9448E	**Handler services do not support XML document type usage**
Explanation	The name of the document type supplied to the pub.soap.handler* service is an XML document type. Integration Server does not support the use of XML document types with web services. As a result, the pub.soap.handler* services will not accept the name of XML document type as input for the documentType or documentTypes names input parameters.
Action	Modify the documentType or documentTypes input parameter to specify an IS document type name instead of an XML document type name.

ISS.0092.9045E	**A WS-I compliant Web Service Descriptor cannot contain a header or fault with a different namespace. Source: {0}**
Explanation	The supplied WSDL document is not WS-I compliant because it contains a header or a fault with a different namespace.
Action	Edit the WSDL document to be WS-I compliant.

ISS.0092.9101E	**Cannot specify both 'element' and 'type'.**
Explanation	The supplied WSDL document is invalid because element and type are both used to define a message part.
Action	Edit the WSDL document so that either element or type is used to define the message part.

ISS.0092.9102E	**{0}: not a valid web service description document**
Explanation	The file identified as the source for creating the Web service descriptor is not a .wsdl or .wsd file. A consumer Web service descriptor or a WSDL first provider Web service descriptor can be generated from a .wsdl or .wsd file only.
Action	Provide a .wsdl or .wsd file to use as the source for the Web service descriptor.

ISS.0092.9103E	**{0}: invalid file, unable to parse root element**
Explanation	The WSDL document does not contain a proper root element. Integration Server is unable to determine which element is the root element and cannot parse the root element.
Action	Ensure that the WSDL document contains a proper root element.

ISS.0092.9105E	**Cannot find the specified Document Type or input/output parameter.**
Explanation	While creating an XML Schema definition, Integration Server cannot find the specified document type or the Input/Output parameters are not mentioned.
Action	When creating an XML Schema definition from an document type, service (input/output parameters), or specification, ensure that the chosen source exists and is not null.

ISS.0092.9106E	**Field {0} is multi-dimensional which cannot be converted to xsd without using SOAP_ARRAY**
Explanation	The specified field is a table (multi-dimensional) and cannot be represented in XML Schema.
Action	A multi-dimensional field such as a table can be represented as a nested fields in an array.

ISS.0092.9107E	**Port {0} is missing required extended element.**
Explanation	The WSDL document is invalid because the specified port is missing a required element. Integration Server cannot create a Web service descriptor.
Action	Edit the WSDL document to include a valid port.

ISS.0092.9108E	**SimpleType {0} does not have base type.**
Explanation	In the WSDL or WSD document the specified simple type definition does not have a base type.
Action	Edit the simple type definition in the WSDL document to include a base data type.

ISS.0092.9109E	**The system cannot find {0}**
Explanation	The Web service descriptor cannot be created because the specified WSDL file cannot be found on the file system.
Action	Make sure that the specified WSDL file exists on the file system or that the provided URL for the WSDL file is correct.

ISS.0092.9111E	**Element must be a document type, service, or specification**
Explanation	The specified source from which Integration Server is to create an XML Schema definition is not a document type, service, or specification.
Action	Make sure the specified source is a document type, service, or specification.

ISS.0092.9112E	**The service does not have a valid signature**
Explanation	The service signature from which Integration Server is to create the XML Schema definition is not valid.
Action	Make sure the specified service has a valid signature that describes the expected names and data types for the inputs and outputs to the service.

ISS.0092.9113E	**Unknown ExtensibleElement "{0}"**
Explanation	The portType element in the WSDL document is missing required extensions (document OR operation).
Action	Edit the WSDL document to include the required extension in the that the portType element.

ISS.0092.9114E	**Invalid WSDL; 'arrayType' attribute value {0} is malformed. Invalid QName {1}**
Explanation	The supplied WSDL document is invalid because the specified arrayType attribute value contains the specified invalid QName.
Action	Edit the WSDL document to supply a valid QName for the arrayType attribute value.

ISS.0092.9115E	**Invalid WSDL; 'arrayType' attribute value {0} is malformed. It should contain characters '[' and ']'**
Explanation	The supplied WSDL document is invalid because the specified arrayType attribute value does not contain the opening and/or closing bracket characters '[' and ']'.
Action	Edit the WSDL by correcting the arrayType attribute value so that it includes the opening and closing bracket characters '[' and ']'.

ISS.0092.9116E	**Invalid WSDL; 'arrayType' attribute value {0} is malformed. Invalid rank size {1}**
Explanation	The supplied WSDL document is invalid because the specified arrayType attribute value contains an invalid rank size. The rank size should follow the pattern: "(\\[,*\\])*\\[((\\d+,)*\\d+)?\\]" OR "(\\[,*\\])*" OR "(\\[((\\d+,)*\\d+)?\\])*")
Action	Edit the WSDL document to specify a valid rank size for the attribute. A valid rank size follows this pattern: "(\\[,*\\])*\\[((\\d+,)*\\d+)?\\]" OR "(\\[,*\\])*" OR "(\\[((\\d+,)*\\d+)?\\])*")

ISS.0094.0001E	**Repository Exception: {0}**
Explanation	During initialization, Integration Server could not initialize the Repository Manager. The most likely reason is that the repository4.cnf file is corrupted.
Action	Check the directory that contains the repository files. By default, they are located at <IntegrationServer_dir>\WmRepository4\ directory. Try renaming the repository4.cnf file manually (to something like "damagedrepository4.cnf") or deleting it, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.

ISS.0094.0003E	**RepositoryManager detected damaged data files : {0}**
Explanation	During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In a recovery attempt, Integration Server tried to open the files, but was unable to.
Action	Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Try manually renaming the files (to something like "damagedFSData00000000") or deleting them, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.

ISS.0094.0004E	**RepositoryManager Exception renaming damaged data files : {0}**
Explanation	During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In an attempt to correct the problem, Integration Server tried to rename the damaged files before creating new ones but encountered an exception when trying to rename the damaged files.
Action	Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Try manually renaming the files

(to something like "damagedFSData00000000") or deleting them, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.

ISS.0094.0006E **RepositoryManager Exception creating new data files : {0}**

Explanation During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In an attempt to correct the problem, Integration Server renamed the damaged files and tried to create new ones but encountered an exception when trying to create new files. Possible reasons for the problem are that the file system does not have enough space for the data files or that Integration Server does not have write access to the directory that contains the files.

Action Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Make sure the file system has space for the files and that Integration Server has write access to the directory.

ISS.0095.0006E **AuditLogManager: Exception auditing start of service {0}: {1}**

Explanation An error was encountered while audit logging the start of a service invocation.

Action Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.

ISS.0095.0007E **AuditLogManager: Exception auditing end of service {0}: {1}**

Explanation An error was encountered while audit logging the start of a service invocation.

Action Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.

ISS.0095.0008E **AuditLogManager: Exception auditing error for service {0}: {1}**

Explanation An error was encountered while audit logging a service invocation.

Action Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.

ISS.0095.0009E **AuditLogManager: Audit runtime interface object cannot be initialized: {0}**

Explanation The Integration Server Audit Log Manager encountered an internal error.

Action Contact Software AG Global Support.

ISS.0095.0010E	**AuditLogManager Runtime Exception: {0} publishing log entry {1}. {2}**
Explanation	An error was encountered while audit logging a service error.
Action	See the detailed error message and stack trace that follow. If audit logging to a database, you may have to work with your DBA to diagnose a database problem.

ISS.0095.0014E	**Audit Logging initialized with errors.**
Explanation	An error was encountered while starting the audit logging facility.
Action	Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, contact Software AG Global Support and provide them with the server log.

ISS.0095.0015W	**Database at URI {0} is not available.**
Explanation	An audit logger is configured to write log messages to a database, but the database is not available.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.

ISS.0095.0016W	**Changing destination of queue {0} from database {1} to file system {2}.**
Explanation	An asynchronous audit logger is configured to write log messages to a database, but the database is not available. The audit logger is being reconfigured to write audit messages to the file system.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.

ISS.0095.0017W	**Changing destination of logger {0} from database {1} to file system {2}.**
Explanation	A synchronous audit logger is configured to write log messages to a database, but the database is not available. The audit logger is being reconfigured to write audit messages to the file system.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.

ISS.0095.0018W	**Cannot change destination of logger {0} to file system.**
Explanation	An audit logger is configured to write log messages to a database, but the database is not available. It is not possible to write messages for this audit logger to the file system because the messages contain binary data. This audit logger is being disabled.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.

ISS.0095.0019W	**Disabling the logger {0}.**
Explanation	The audit logger is being disabled. This is probably happening because the logger's database is not available.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.

ISS.0095.0020W	**Audit Logging Initialization: The {0} JDBC Pool Alias was not configured with enough connections. The Maximum Connections have been increased to {1}.**
Explanation	The auditing system needed more database connections than were provided in the JDBC Pools configuration. The configuration was changed as needed.
Action	No action is required.

ISS.0095.0021E	**ERROR: Audit Logging Initialization: The {0} JDBC Pool Alias was not configured with enough connections. Unable to automatically increase the Maximum Connections setting.**
Explanation	The auditing system needed more database connections than were provided in the JDBC Pools configuration. An attempt was made to automatically increase the number of connections, but it failed.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and increase the Max Connections setting for the ISCoreAudit functional alias. Restart Integration Server.

ISS.0095.0022W	**Audit Logging Initialization: Unable to verify the Max Connections setting for the Audit Logging database.**
Explanation	Integration Server encountered an error while checking the Max Connection setting for the ISCoreAudit functional alias.
Action	If the auditing system is slow or unresponsive, go to the Settings > JDBC Pools page of the Integration Server Administrator and increase the Max Connections setting for the ISCoreAudit functional alias.

ISS.0095.0024W **The value for watt.server.audit.logDir has been changed and does not identify an existing directory that Integration Server can write to. File-based audit logs will continue to be written to the {0} directory.**

Explanation The audit log directory was not changed because the watt.server.audit.logDir parameter refers to a directory that either does not exist or Integration Server does not have permission to write to. As a result, Integration Server will write file-based audit logs to the last valid directory specified.

Action Go to the Settings > Extended page in the Integration Server Administrator and change the value for the watt.server.audit.logDir parameter. Specify a directory that exists on the server and that Integration Server can write to. You can specify the full path name, or a relative path in relation to the Integration Server.

ISS.0095.0025W **The {0} file was not found and is being created.**

Explanation Upon start up, Integration Server could not find the specified file, for which {0} is a placeholder, in the following directory: IntegrationServer/instances/instanceName/config/auditing where instanceName is the Integration Server instance that was started. Integration Server will create the file. The file specifies which database errors are considered transient.

Action If the specified file has been modified, restore the file from a backup, if possible. If the file has not been modified, no action is necessary.

ISS.0095.0026W **The {0} file was not found and is being created. The audit logging system is using default settings.**

Explanation Upon start up, Integration Server could not find the specified file, for which {0} is a placeholder, in the following directory: IntegrationServer/instances/instanceName/config/auditing where instanceName is the Integration Server instance that was started. The specified file contains the configured auditing logging settings. Integration Server will create the file, which will contain the default auditing logging settings.

Action If the specified file has been modified, restore the file from a backup or use Integration Server Administrator to restore the configured audit logging settings . If the file has not been modified (that is, you have not modified the audit logging configuration), no action is necessary.

ISS.0095.0030I **Audit Logging: The {0} has entered fail-fast mode for messaging connection alias {1}.**

Explanation The specified audit logger has entered queue fail-fast mode lost the connection to the Universal Messaging server established through indicated messaging connection alias. The audit logger will write log entries to the internal audit logging queue instead of the Universal Messaging

Action Make sure that Universal Messaging server is up and running and that there are no network related problems between Integration Server and Universal Messaging server.

ISS.0095.0031I	**Audit Logging: The {0} has exited fail-fast mode for the messaging connection alias {1}.**
Explanation	The specified audit logger has exited queue fail-fast mode because connectivity to the Universal Messaging server has been restored. The audit logger writes new log entries to the Universal Messaging queue.
Action	None.

ISS.0095.0032I	**Audit Logging: Session for messaging connection alias {0} disconnected.**
Explanation	The session on a Universal Messaging server created using the specified messaging connection alias has disconnected. Any audit loggers that use the specified messaging connection alias to write log entries to a Universal Messaging queue will enter queue fail-fast mode and begin writing log entries to the internal audit logging queue.
Action	Make sure that Universal Messaging server is up and running and that there are no network related problems between Integration Server and Universal Messaging server.

ISS.0095.0033I	**Audit Logging: Reestablished connection with session for messaging connection alias {0}.**
Explanation	The session on a Universal Messaging server created using the specified messaging connection alias has been re-established. Any audit loggers that user the specified messaging connection alias will exit queue fail-fast mode and resume writing new log entries to the Universal Messaging queue
Action	None.

ISS.0095.0037E	**Pool with messaging connection alias name {0} does not exist.**
Explanation	For an audit logger configured to use Universal Messaging as the queue provider, Integration Server requested a session from a pool for a Universal Messaging connection alias that does not exist. The Universal Messaging connection alias specified in the Connection Alias field for the logger does not exist.
Action	Make sure the logger specifies an existing Universal Messaging connection alias for the Connection Alias field.

ISS.0095.0038W	**watt.server.audit.um.sessionPool.min.value is invalid {0}. Value must be an integer greater than zero. Integration Server will use default value of 2.**
Explanation	The watt.server.audit.um.sessionPool.min value is invalid because it is not an integer greater than zero. Integration Server will use the default value of 2 until a valid value is specified.
Action	Set watt.server.audit.um.sessionPool.min to an integer greater than 0 (zero) but less than or equal to the value of watt.server.audit.um.sessionPool.max.

ISS.0095.0039W	**watt.server.audit.um.sessionPool.max.value is invalid {0}. Value must be an integer greater than zero. Integration Server will use default value of 10.**
Explanation	The watt.server.audit.um.sessionPool.max value is invalid because it is not an integer greater than zero. Integration Server will use the default value of 10 until a valid value is specified.
Action	Set watt.server.audit.um.sessionPool.max to an integer greater than 0 (zero) but greater than or equal to watt.server.audit.um.sessionPool.min.

ISS.0095.0040W	**Invalid watt.server.audit.um.sessionPool.min value {0) and watt.server.audit.um.sessionPool.max value {1}. watt.server.audit.um.sessionPool.min must be less than or equal to watt.server.audit.um.sessionPool.max. Integration Server will use the default values of 2 and 10, respectively.**
Explanation	The watt.server.audit.um.sessionPool.min value and watt.server.audit.um.sessionPool.max value are invalid because the watt.server.audit.um.sessionPool.min value is greater than the watt.server.audit.um.sessionPool.max value. Integration Server will use the default values of 2 and 10, respectively, until valid values are specified
Action	Set watt.server.audit.um.sessionPool.mim and watt.server.audit.um.sessionPool so that both are integers greater than 0 (zero) and watt.server.audit.um.sessionPool.min value is less than or equal to the watt.server.audit.um.sessionPool.max value.

ISS.0095.9998E	**AuditLogManager Exception: {0}**
Explanation	An error was encountered using the audit logging database.
Action	Try logging again. It may be a transient error. If the error persists, examine the detailed message and stack trace that follow. You may need to work with your DBA to diagnose a problem with the audit logging database.

ISS.0096.0001E	**JDBCConnectionManager: initialization failed for {0} functional alias, check configuration.**
Explanation	Unable to initialize the functional alias. Integation Server will not be able to connect to the database for this functional alias.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the functional alias settings are correct. Use the Test button to check that Integration Server can reach the configured database.

ISS.0096.0002W	**JDBCConnectionManager: creating Embedded Pool Alias for {0}.**
Explanation	The connection pool for the embedded database is being created.
Action	No action is required.

ISS.0096.0004E	**JDBCConnectionManager: embedded database objects not created: {0}**
Explanation	Unable to create tables, keys, or other database objects while initializing the embedded database.
Action	Verify that Integration Server has write access to the file system. If the problem persists, contact Software AG Global Support.

ISS.0096.0005E	**JDBCConnectionManager: initialization failed with exception {0}**
Explanation	Initialization of the JDBC Connection Manager failed.
Action	Contact Software AG Global Support.

ISS.0096.0010E	**The DataStoreDBListener has detected a bad connection for the {0} JDBC functional alias. The JDBC connection pool is being reinitialized**
Explanation	A database connection being used by the pub.storage services is no longer functional. This often indicates a network interruption has broken all existing database connections. Integration Server is reinitializing the pool of connections for the JDBC functional alias. If network connectivity has been restored, the pub.storage services may continue to be used without interruption. If network connectivity has not been restored, the pub.storage services will continue to fail until it is restored.
Action	If the network interruption is transient and connectivity to the database is restored quickly, no immediate action is required. If the network interruption persists, or if transient network interruptions continue to occur, this indicates a problem in the network or in the networking implementation of the host that Integration Server is running on. Seek assistance from a networking expert in your company to investigate and resolve this problem.

ISS.0097.0004E	**Failed to lock Repository entry {0}**
Explanation	Integration Server encountered an internal error when trying to lock the repository.
Action	If the error continues, contact Software AG Global Support.

ISS.0097.0006I	**Messaging synchronizer shutdown**
Explanation	The Broker Synchronizer has shut down.
Action	No action is required. This message is displayed when Integration Server is shutting down.

ISS.0097.0012E	**Messaging Synchronizer cannot open repository for sync-state storage**
Explanation	An error was encountered while trying to open WmRepository4.
Action	Contact Software AG Global Support.

ISS.0097.0013E	**Messaging Synchronizer cannot update sync state; cannot remove sync data from repository: {0}**
Explanation	An error occurred while removing sync state data from WmRepository4.
Action	Contact Software AG Global Support.

ISS.0097.0014E	**Messaging Synchronizer cannot update sync state; document type not specified**
Explanation	The document type to be syncrhonized was not specified; the nsName input variable is null.
Action	Specify a document type name for nsName.

ISS.0097.0015D	**Messaging Synchronizer cannot update sync state; document type {0} has no sync state**
Explanation	The requested document type has no sync state.
Action	No action is required.

ISS.0097.0016E	**Messaging Synchronizer cannot perform sync; Integration Server cannot connect to provider**
Explanation	Synchronization cannot occur because Integration Server cannot connect to the message provider.
Action	Make sure the message provider is running and that the message connection alias is enabled in Integration Server Administrator.

ISS.0098.0003U	**Exception occurred while decoding Broker Document {0} : {1}**
Explanation	Integration Server failed to decode the document received from the Broker. The document may be corrupt.
Action	Check the publisher of the document. Consider redelivering the document from the Broker.

ISS.0098.0010U	**Exception initializing Dispatcher configuration from file: {0}**
Explanation	Integration Server encountered the indicated exception while trying to initialize the Dispatcher. This is a serious internal error.
Action	Contact Software AG Global Support.

ISS.0098.0023E	**Document Router for Consumer Queue:{0} encountered error: {1}**
Explanation	Integration Server encountered an error while routing a document to a Broker.
Action	The action to take depends on the exception that occurred. Review the returned exception for more guidance.

ISS.0098.0024U	**No Trigger available for incoming Document {0}. Rejecting Document**
Explanation	Integration Server failed to deliver the incoming document to thea trigger because there is not a trigger that subscribes to the document. The intended trigger may be disabled or deleted.
Action	Examine the existing triggers. If a trigger that subscribes to the document is disabled, enable it and ask the publisher to re-publish or deliver the document.

ISS.0098.0025E	**Document {0} from store {1} exceeded Redelivery Count.**

ISS.0098.0029U	**Exception while doing Request Reply: {0}**
Explanation	Integration Server encountered an internal error while executing a request reply.
Action	Contact Software AG Global Support.

ISS.0098.0030E	**{0} received duplicate document(s). Error {1}**
Explanation	Integration Server determined that it received duplicate documents from a publisher.
Action	If you determine that the Integration Server did receive duplicate messages, check the publishing source to learn the source of the problem. In some cases, Integration Server did not really receive duplicates. For example, two documents might use the same tracking ID but have different content. If Integration Server did not receive a duplicate document, try resubmitting the document using webMethods Monitor.

ISS.0098.0031E	**Consumer:{0} unable to persist Document(s) to Document Store. Error: {1}**
Explanation	Integration Server failed to write a document to the transient store. A likely cause is that the Integration Server JVM has run out of memory.
Action	Try increasing the heap size of the JVM. The heap size indicates how much memory is allotted for server processes.

ISS.0098.0033E	**Error while shutting down Dispatcher: {0}**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISS.0098.0036U	**{0} encountered Transport Exception: {1}**
Explanation	Integration Server failed to publish the document because of one of the following: 1) The Broker is temporarily unavailable. 2) The client does not have the canPublish permission for its associate Broker document. 3) The document being published does not conform to the Broker document on the Broker. This may be because the document was not synchronized with the one on the Broker. 4) An internal error occurred.
Action	Do one of the following: 1) Check the Broker status. If the Broker or network connection is temporarily down, wait until they are up to re-publish the document. 2) Using the Broker administration tool, check the publication permissions of the client group to which the trigger client belongs. Make sure that the client is allowed to publish the document. 3)Synchronize the document and make sure that the document being published matches its associate Broker document type. 4) If the previous actions fail to correct the problem, contact Software AG Global Support.

ISS.0098.0038E	**{0} handling invalid Document. Exception: {1}**
Explanation	Integration Server encountered an error while processing a document. Specifically, the document does not have a corresponding publishable document type on the Integration Server or the publishable document type does not have a matching schema.
Action	Make sure that the appropriate document types and schemas for the document exist on the Integration Server.

ISS.0098.0041E **Unable to connect to Broker. Starting to poll**

ISS.0098.0044U **Exception while interacting with the Document Store name:{0} Problem:{1}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISS.0098.0045U **Unrecoverable Exception while initializing the Dispatcher: {0}**

Explanation Integration Server encountered the indicated exception while trying to initialize the Dispatcher. This is an internal error.

Action Contact Software AG Global Support.

ISS.0098.0047E **Connection to Broker unavailable. Unable to create transport for Trigger:{0}.**

ISS.0098.0048U **Unable to remove subscription for Publishable Document {0} from transport:{1}. If connected, please remove subscription from {2} manually.**

Explanation Integration Server failed to remove the document type subscription before unregistering the trigger. The Broker may be unavailable.

Action In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when they are back up.

ISS.0098.0049U **Exception:{0} while executing trigger. Unable to acknowledge Document for TriggerStore:{1}.**

Explanation Integration Server failed to execute the trigger. This indicates an internal error.

Action Contact Software AG Global Support.

ISS.0098.0055U **Exception during attempt to register Trigger: {0}**

Explanation Integration Server failed to register the trigger. This indicates an internal error.

Action Contact Software AG Global Support.

ISS.0098.0056U **Unable to acknowledge Document {0} to transport for Trigger {1}. Exception:{2}**

Explanation Integration Server encountered an internal error while acknowledging the document to the transport for the trigger.

Action Contact Software AG Global Support.

ISS.0098.0057U	**Unable to delete Document Store for Trigger:{0}. Exception:{1}**
Explanation	Integration Server encountered an internal error while deleting the document store associated with the trigger.
Action	Contact Software AG Global Support.

ISS.0098.0058E	**Stopping delivery of {1} to trigger {0} to prevent infinite loop.**

ISS.0098.0059U	**Exception while shutting down the Document Stores:{0}.**
Explanation	Integration Server encountered a serious internal error while shutting down.
Action	Contact Software AG Global Support.

ISS.0098.0060U	**Exception while saving Dispatcher configuration :{0}.**
Explanation	Integration Server encountered an exception while trying to save Dispatcher configuration information to the dispatch.cnf file in the <IntegrationServer_dir>/config directory.
Action	If the dispatch.cnf file is set to read-only, change it to read/write. If the file is not set to read-only, this error indicates a serious internal error and you should contact Software AG Global Support.

ISS.0098.0062E	**{0} encountered Exception: {1}**

ISS.0098.0073U	**ControlledPublishOnSuccess max exceeded while processing {0}**
Explanation	Integration Server failed to publish a document because the maximum concurrent publish-on-success value was exceeded.
Action	Do one of the following: 1) On the Integration Server, increase the "concurrent publish on success" setting by editing the "watt.server.control.maxPublishOnSuccess" property. 2) Decrease the number of concurrent publish operations in the service.

ISS.0098.0074E	**Outbound msg store max exceeded, services blocking. Start broker to drain store.**

ISS.0098.0075E **Insufficient memory while decoding event:{0} for {1}.**

Explanation Integration Server does not have sufficient memory to decode the documents being retrieved from the Broker. Integration Server will attempt to decode the documents one more time.

Action Check the size of the documents sent by the Broker and consider increasing the heap size of the Integration Server's JVM.

ISS.0098.0076U **Unable to decode events for {0}. Please check JVM Heap size and/or size of Documents on the Broker.**

Explanation Integration Server does not have sufficient memory to decode the documents from the Broker.

Action Check the document size sent by the Broker and consider increasing the heap size of the JVM used by Integration Server.

ISS.0098.0077E **Dispatcher out of memory. Retrying operation.**

Explanation Integration Server does not have sufficient memory to continue its document publishing operations. Integration Server will attempt to process this message again.

Action Consider increasing the heap size of the JVM used by Integration Server.

ISS.0098.0078E **Dispatcher out of memory. Operation failed. Check error log.**

Explanation Integration Server does not have sufficient memory to continue its document publishing operations. Integration Server has exceeded its retry count, and an exception will be thrown.

Action Consider increasing the heap size of the JVM used by Integration Server.

ISS.0098.0079E **Dispatcher out of memory. Retry succeeded.**

Explanation Integration Server successfully retried a publishing operation after an OutOfMemory error prevented the operation from working the first time.

Action If the Integration Server continues to issue this message, check the JVM Heap size and/or size of Documents on the Broker. The Trigger configuration (possibly the acknowledgment queue size) may need to be adjusted.

ISS.0098.0080U **Insufficient memory while persisting messages for Trigger: {0}.**

Explanation Integration Server does not have sufficient memory to persist the documents to the document store for the trigger.

Action Check the size of the documents being persisted and consider increasing the heap size of the JVM used by Integration Server.

ISS.0098.0081U	**Insufficient memory while persisting message: {1} for Trigger: {0}.**
Explanation	Integration Server does not have sufficient memory to persist a single document to the document store for the trigger.
Action	Check the size of the document being persisted and consider increasing the heap size of the JVM used by Integration Server.

ISS.0098.0082U	**Unable to persist Document: {0} to Document Store: {1}. Exception: {2}**
Explanation	Integration Server failed to persist the document to the document store. This indicates a serious internal error.
Action	Contact Software AG Global Support.

ISS.0098.0083U	**Unable to acknowledge Document: {0} for Trigger Store: {1}. Insufficient memory.**
Explanation	Integration Server does not have sufficient memory to acknowledge the document to the document store.
Action	Check the size of the document being persisted and consider increasing the heap size of the JVM used by Integration Server.

ISS.0098.0084U	**Exception:{0} during Trigger dispatching.**
Explanation	Integration Server encountered an internal error while which processing a document destined for an individual trigger.
Action	Contact Software AG Global Support.

ISS.0098.0085U	**Unable to remove all subscriptions for transport:{0} while unregistering trigger. If connected, please remove subscription from {1} manually.**
Explanation	Integration Server failed to remove all stale subscriptions before unregistering the trigger. The Broker may be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when they are back up.

ISS.0098.0086U	**Unable to remove all subscriptions for transport:{0} before registering trigger. If connected, please remove stale subscriptions from {1} manually.**
Explanation	Integration Server failed to remove all stale subscriptions before registering the trigger. The Broker may be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when the Broker and network are back up.

ISS.0098.0087E **Duplicate document of type:{0} with Id:{1} received for trigger:{2}.**

ISS.0098.0089U **Transaction size (no of documents * size of documents) is too large for Document Store: {0}. Please reduce capacity of Trigger and /or increase initial size of Document Stores.**

Explanation The Integration Server failed to persist documents because the document store did not contain enough space. Documents received from the Broker are persisted in the triggers' persistent stores.

Action In the Integration Server Administrator, click Settings>Resources>Document Stores. On this page, consider increasing the initial size of the document store. Also, consider reducing the number of triggers that subscribe to the document.

ISS.0098.0090U **Size of Document: {0} for Document Store: {1} is too large. Server is unable to persist. Audit logging the document.**

Explanation Integration Server failed to persist a document because the document store did not contain enough space.

Action In the Integration Server Administrator, click Settings>Resources>Document Stores. On this page, consider increasing the initial size of the document store.

ISS.0098.0096I **Integration Server is now connected to a Broker that tracks document redelivery counts. Restart the Integration Server to make use of redelivery counts in duplicate detection.**

Explanation Integration Server connects to a version of the Broker that supports redelivery count. Previously it was connected to a Broker that did not support this feature.

Action Restart Integration Server so that it can take advantage of the redelivery count feature supported by the Broker.

ISS.0098.0100 **Copying of documents to trigger store started.**

ISS.0098.0103S **{0} not initialized. Adjust document store settings and restart server.**

Explanation Integration Server was unable to create the Document Store on disk. The Document Store is essential for Integration Server functioning, therefore startup terminates.

Action Check to see if there is enough disk space on the drive where the Document Store is being created (usually under <IS_SERVER_ROOT>\DocumentStore directory). If there is sufficient disk space, then check to see if the dispatch.cnf file under <IS_SERVER_ROOT>\config directory is corrupted. If the problem persists despite a re-start, contact Software AG Global Support.

ISS.0098.0104I	**Integration Server is now connected to a Broker that does not track document redelivery counts. Restart the Integration Server so that duplicate detection does not expect document redelivery counts.**
Explanation	Integration Server connects to a version of the Broker that does not support the redelivery count. Previously it was connected to a Broker that does support this feature.
Action	Restart the Integration Server so that its duplicate detection mechanism does not expect redelivery counts to be present in documents delivered by the Broker.

ISS.0098.0105E	**Unable to fully build comparable trigger: {0}**
Explanation	During Cluster Synchronization, Integration Server was unable to compare trigger nodes across all the nodes in the cluster. The most likely cause is that one or more triggers are not completely configured. Cluster Synchronization makes sure that changes made to a trigger's configuration on one Integration Server are propagated to other servers in the cluster. If an Integration Server is configured for Cluster Synchronization, this process runs when an administrator makes a trigger configuration change through the Integration Server Administrator or when a user-written service calls one of the pub.trigger:* services.
Action	Using the development tool, check the trigger configuration. After correcting the problem, retry the task you were performing when the error occurred.

ISS.0098.0106	**Trigger comparison failed: trigger = {0}; parameter = {1}; local value = {2}; remote value = {3}.**

ISS.0098.0107E	**Error occurred during cluster invoke: Alias = {0}; Service = {1}; Exception = {2}.**
Explanation	During Cluster Synchronization, Integration Server threw an exception while invoking a service on a remote node in the cluster. Cluster Synchronization makes sure that changes made to a trigger's configuration on one Integration Server are propagated to other servers in the cluster. If an Integration Server is configured for Cluster Synchronization, this process runs when an administrator makes a trigger configuration change through the Server Administrator or when a user-written service calls one of the pub.trigger:* services.
Action	The action you take depends on the exception issued. Look at the exceptionMessage for specific information.

ISS.0098.0108	**Serial trigger {0} has been automatically suspended due to an exception: {1}.**

ISS.0098.0109	**Unable to establish secure connection to Broker. Password needed for SSL connection to Broker:{0}.**
ISS.0098.0112	**Trigger Resource Monitor now monitoring resource availability for trigger "{0}".**
ISS.0098.0113	**Trigger Resource Monitor invoked "{0}". Status of resource is "available".**
ISS.0098.0114	**Trigger Resource Monitor invoked "{0}". Status of resource is "not available".**
ISS.0098.0115	**Trigger Resource Monitor has resumed trigger "{0}".**
ISS.0098.0116	**Trigger Resource Monitor encountered an exception while attempting to resume trigger "{0}": {1}**
ISS.0098.0117	**The ISInternal functional alias is not configured properly on the JDBC Pools page. It is required in order to create and manage AND and XOR trigger joins. Assign a valid database pool and restart the Integration Server.**
ISS.0098.0118	**The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to create and manage AND and XOR trigger joins.**
ISS.0098.0119	**Trigger Retry Failure occurred for trigger "{0}" : "{1}" . This trigger is being suspended and the message is being rolled back to the Broker because the Audit Logging subsystem also failed: "{2}"**
ISS.0098.0120	**The default Broker was detected while initializing the dispatch.cnf file. Broker Settings will automatically be enabled.**
ISS.0098.0121	**The default Broker was not detected while initializing the dispatch.cnf file. Broker Settings will automatically be disabled.**

ISS.0098.0122 **The subscription for publishable document {0} will not be removed or recreated because the client prefix {1} used by the Broker connection for trigger {2} may be shared by multiple clients. If required, please remove subscription from Broker manually.**

ISS.0098.0123 **The subscription for publishable document {0} will not be removed or recreated because the client prefix {1} used by the Broker connection for trigger {2} may be shared by multiple clients. If required, please remove subscription from Broker manually.**

ISS.0098.0124E **A username and password are required for Username/Password authentication.**

Explanation Authentication credentials were not specified.

Action Provide a username and password.

ISS.0098.9002U **Required property missing for creating {0} transport: {1}**

Explanation Integration Server could not read properties from the <IntegrationServer_dir>\config\dispatch.cnf file. The file may be corrupt.

Action Examine the dispatch.cnf file to make sure that it is not corrupt and that the "clientGroupName" and "brokerHost" fields exist. If the file is corrupt, rename it and restart Integration Server. After you do this, you can re-configure the Broker Settings using the Integration Server Administrator.

ISS.0098.9005 **Invalid connections properties for creating {0}**

ISS.0098.9006U **No matching Document Type exists for {0}**

Explanation A pub.publish* service returned an error because the document specified in the "documentTypeName" parameter does not exist on the Integration Server.

Action Examine the input for the "documentTypeName" parameter. Make sure that the parameter specifies the fully qualified name of the document type for which you want to publish or deliver an instance. Keep in mind that document type names are case-sensitive. Additionally, ensure that the specified document type exists on Integration Server.

ISS.0098.9007E **Data does not conform to the Publishable Document Type {0} errors: {1}**

Explanation A pub.publish* service issued an error because the IData input for the "document" parameter does not conform to the document type specified in the "documentTypeName" parameter.

Action Examine the validation error message and the IData object passed to the "document" parameter. Make sure that it conforms to the document type specified in the "documentTypeName" parameter.

ISS.0098.9008U **No registered Transport for the given id: {0}**

Explanation Integration Server failed to create a subscription to the publishable document type specified in a trigger. The transport information does not exist, which indicates an internal error.

Action Contact Software AG Global Support.

ISS.0098.9009 **Certificate file require for using SSL encryption**

ISS.0098.9010E **No waiting thread for Document Id: {0}. Requestor might have timed out.**

Explanation Integration Server encountered an internal error while publishing the document and waiting for a reply.

Action Contact Software AG Global Support.

ISS.0098.9011U **{0} is not a Publishable Document Type.**

Explanation A pub.publish* service returned an error because the document type specified in the "documentTypeName" parameter was not publishable.

Action Ensure that the Publishable property is set to "true" for the document type."

ISS.0098.9013U **Dispatcher is not initialized**

Explanation Integration Server was not able to publish, deliver, or reply to a document because the dispatcher that is responsible for performing these operations was not initialized.

Action Log on to the Integration Server Administrator and make sure that you have correctly configured Integration Server for document publishing.

ISS.0098.9014U **BrokerException: {0}**

Explanation Integration Server was unable to publish or retrieve documents from the Broker because the operation failed on the Broker.

Action Examine the error message provided by the Broker. Refer to the webMethods Broker API documentation for the Java Client for a detailed description of the error.

ISS.0098.9015 **Rejected document because Dispatcher was unable to deliver document after {0} attempts**

ISS.0098.9016U	**Broker Transport unable to subscribe to Publishable Document Type:{0} BrokerEvent Type:{1}**
Explanation	Integration Server failed to create a subscription to the publishable document type specified in a trigger. The client is not allowed to subscribe to the Broker document type associated with the publishable document type.
Action	In the Broker Administrator, check the subscription permissions of the client group to which the trigger belongs. Make sure that the client is allowed to subscribe to the Broker document type associated with the publishable document type.

ISS.0098.9017	**Rejecting document as there is no enabled Trigger registered:**

ISS.0098.9018E	**Unrecoverable Error while initializing the webMethods Messaging Subsystem (Dispatcher): {0}. No webMethods Messaging features will be available until this issue is resolved and the server is restarted.**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISS.0098.9019U	**Request timed out while waiting for reply**
Explanation	Integration Server encountered an internal error while publishing or delivering the document and waiting for a reply.
Action	Contact Software AG Global Support.

ISS.0098.9021U	**Received incorrect document as Reply. Expecting {0} and received {1}**
Explanation	Integration Server failed to receive the expected reply document while publishing or delivering the document and waiting for a reply.
Action	Check the subscriber of the publisher document. Make sure that the subscriber delivers a correct reply document.

ISS.0098.9022E	**Invalid DispatcherMessage {0}**
Explanation	Integration Server failed to deliver the document to the subscribing triggers. The document is null, which indicates an internal error.
Action	Contact Software AG Global Support.

ISS.0098.9023U	**Transport Factory: {0} not found.**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISS.0098.9024U	**{0} Unknown Transport Type specified. Unable to create transport.**
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISS.0098.9025U	**{0} not configured. {1} operation can only be done after a {0} is configured.**
Explanation	The pub.publish:deliver or pub.publish:deliverAndWait service failed to execute because Integration Server is not configured to connect to the Broker.
Action	Use Integration Server Administrator to configure the server to connect to a Broker.

ISS.0098.9027U	**Unknown broker version.**
Explanation	Integration Server failed to connect to the Broker because the version of the Broker is not supported.
Action	Do not attempt to set up such an environment. See the "Installing webMethods Products" for supported configurations.

ISS.0098.9028	**Incompatible Broker version. The minimum Broker version required is 6.0.**

ISS.0098.9033E	**Duplicate condition name "{1}" in Trigger "{0}"**
Explanation	Integration Server could not save the condition settings of a trigger because the trigger has duplicate condition names.
Action	Edit the trigger so that each condition has a unique name.

ISS.0098.9034E	**Condition name "{0}" - Cannot have duplicate document types in AND join.**
Explanation	Integration Server could not save a trigger because a condition has duplicate document types in an "AND" join.
Action	Edit the trigger condition to make sure that unique document types are specified in the "AND" join.

ISS.0098.9035E	**Cannot specify different filters for document type ''{0}'' within a single trigger**
Explanation	Integration Server could not save the condition settings of a trigger because more than one filter is specified for a document type in the trigger.
Action	If multiple conditions in the trigger specify the same document type, make sure that the filter applied to the document type is the same for each condition.

ISS.0098.9036U	**Unable to ack**
Explanation	Integration Server failed to acknowledge the document to the trigger document store. This indicates an internal error.
Action	Contact Software AG Global Support.

ISS.0098.9050U	**Unable to publish volatile Document: {0}. Broker not connected.**
Explanation	Integration Server published a volatile document while the Broker was down. A service exception occurred for the publishing service and the volatile document was lost.
Action	Make sure the Brroker is available and re-publish the document.

ISS.0098.9051U	**No activation specified for Join Document:{0}.**
Explanation	The published document cannot be processed in a join because it is missing an activation ID.
Action	The publisher of the document needs to set an activation ID for the document.

ISS.0098.9056U	**cmd for msgs all not the same or null**
Explanation	A flow service mixed the pub.publish:deliver and pub.publish:publish steps when the "delayUntilServiceSuccess" parameter is set to "true".
Action	Use separate flow services to deliver and publish a message when the "delayUntilServiceSuccess" parameter is set to "true".

ISS.0098.9057U	**destination for msgs all not the same or null**
Explanation	A flow service contains multiple pub.publish:deliver steps where the "delayUntilServiceSuccess" parameter is set to "true", but the destination IDs are not identical.
Action	Use separate flow services to deliver a message to different destination IDs when the "delayUntilServiceSuccess" parameter is set to "true".

ISS.0098.9058E	**publish-on-success is suspended**
Explanation	The publish-on-success facility has been programmatically suspended. Therefore, the publish-on-success operation will not work.
Action	Restart the Integration Server.

ISS.0098.9059E	**max concurrent publish-on-success is exceeded**
Explanation	The watt.server.control.maxPublishOnSuccess parameter was exceeded by a publishing flow. The maxPublishOnSuccess parameter controls the maximum number of documents that Integration Server publishes on success at one time.
Action	Decrease the number of documents published by a flow service that uses publish-on-success, or increase the value of the maxPublishOnSuccess parameter.

ISS.0098.9061	**Document store runtime capacity**

ISS.0098.9062U	**Document store is missing for {2}**
Explanation	Integration Server encountered an internal error in the document store.
Action	Contact Software AG Global Support.

ISS.0098.9063	**Step size for {2} must be positive and no greater than 100: {3}**

ISS.0098.9064	**Unable to mark as complete to the Document History**

ISS.0098.9065E	**Error reply {0} received. adapterType:{1}, errorCategory:{2},errorText:{3},eventId:{4}**
Explanation	A client, typically an Integration Server but possibly a Broker client or Adapter, sent a request document to an Integration Server, but received an error reply (a document of type pub.publish.notification:error) in response. This happens when the service executing the request document on the target server encounters an error. Instead of sending the expected reply document type, it sends an error document indicating it could not process the request document correctly.
Action	Check the Error log of the target Integration Server, that is, the Integration Server to which the request document was sent. If the error occurred when a document was being published to a single subscriber, you will know which target server issued the error reply. However, if the error occurred during a publish to multiple Integration Servers, you will have to determine which target server issued the error.

ISS.0098.9066E	**Missing required parameter: "{0}".**
Explanation	A client tried to invoke a service, but did not specify a required parameter.
Action	Supply the missing required parameter.

ISS.0098.9067E	**Trigger not found for triggerName: "{0}".**
Explanation	Integration Server tried to suspend or fetch metadata for the indicated trigger, but there is no trigger with this name enabled on Integration Server.
Action	Make sure the trigger name is typed correctly and that the trigger is enabled.

ISS.0098.9068E	**Unable to get status for Trigger "{0}": No IControlObject found.**
Explanation	Integration Server encountered an error while trying to perform an action against a trigger, but the trigger was not completely configured, and as a result, not fully initialized.
Action	Verify that the trigger is properly configured and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.

ISS.0098.9069E	**Unable to get status for Trigger "{0}": {1}**
Explanation	Integration Server encountered an error while trying to perform an action against a trigger. - For trigger retrieval, the status indicates whether the trigger is active or suspended. - For trigger processing, the status indicates whether the trigger is active or suspended and shows the current threads being used, the current volatile queue size, and the current persisted queue size.
Action	The action you take depends on the exception issued. Look at the exception message and the server log for additional details.

ISS.0098.9072E	**Trigger "{0}" is locked. Change not permitted.**
Explanation	A user tried to modify the indicated trigger using the Trigger Management screens in Integration Server Administrator or the built-in services, but the trigger is locked.
Action	Unlock the trigger and try again.

ISS.0098.9073E	**Unable to suspend document {0} for Trigger "{1}": No IControlObject found.**
Explanation	A request to suspend document processing failed. The most likely cause is that the trigger was not completely configured, and as a result, not fully initialized.
Action	Make sure the trigger is configured properly and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.

ISS.0098.9074E **Unable to suspend document {0} for Trigger "{1}": {2}**

Explanation A request to suspend document processing failed due to the indicated exception.

Action The action you take depends on the exception issued. Look at the exception message value in the message for specific information.

ISS.0098.9075E **Unable to resume document {0} for Trigger "{1}": No IControlObject found.**

Explanation A request to resume document processing failed. The most likely cause is that the trigger was not completely configured, and as a result, not fully initialized.

Action Make sure the trigger is properly configured and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.

ISS.0098.9076E **Unable to resume document {0} for Trigger "{1}": {2}**

Explanation A request to resume document processing failed due to an exception.

Action The action you take depends on the exception issued. Look at the exception message value in the message for specific information.

ISS.0098.9077E **Unable to persist the change made to Trigger "{0}": {1}**

Explanation The configuration change for a trigger was not saved to file. As a result, the change will revert back to its original value after Integration Server restarts or someone reloads the package.

Action The action you take depends on the exception issued. Look at the exception message value in the message for specific information.

ISS.0098.9078E **maxExecutionThreads cannot exceed queueCapacity**

Explanation The value specified for the number of maximum execution threads exceeds the queue capacity. This is not permitted because the number of documents the Integration Server can process concurrently (maxExecutionThreads) cannot exceed the maximum number of documents that can be in the trigger's queue (queueCapacity).

Action Change the maximum execution threads value to be less than or equal to the queue capacity. Alternatively, change the queue capacity value so that it is greater than or equal to the maximum execution threads.

ISS.0098.9079E **queueRefillLevel cannot exceed queueCapacity**

Explanation The value specified for the queue refill level exceeds the queue capacity. The queue refill level is the number of unprocessed documents that must remain in the trigger queue before Integration Server retrieves more documents for the queue from the Broker. This level cannot exceed the maximum number of documents that can be in the trigger's queue (queueCapacity).

Action	Change the queue refill level value so that it is less than or equal to the queue capacity. Alternatively, change the queue capacity value so that it is greater than or equal to the queue refill level.

ISS.0098.9080E **{0} must be a positive number.**

Explanation	The value specified for the indicated parameter was zero or a negative number. This value must be positive number.
Action	Supply a positive number for the indicated parameter.

ISS.0098.9081 **Unable to publish Document: {0}. Broker not connected.**

ISS.0098.9082 **Unable to create trigger "{0}": {1}**

ISS.0098.9083 **Unable to create trigger "{0}". Invalid Trigger Name.**

ISS.0098.9084 **Unable to create trigger "{0}". Invalid NSName.**

ISS.0098.9085 **Unable to create trigger "{0}". Package "{1}" does not exist.**

ISS.0098.9086 **Unable to create trigger "{0}": Insufficient Write ACL privileges.**

ISS.0098.9087 **Unable to create trigger "{0}". A trigger with this name already exists.**

ISS.0098.9088 **{0} must me greater than 0 or -1.**

ISS.0098.9089 **{0} must me greater than or equal to 0.**

ISS.0098.9090 **Unable to publish to the broker the Document: {0}. Sync the document with the broker.**

ISS.0098.9092W **Filter cannot be migrated to UM Povider Filter, it uses an unsupported construct:{0}.**

Explanation The contents of the Filter field could not be migrated to the Provider Filter (UM) field because the filter contains the specified unsupported constructs. At run time, the unsupported constructs replace {0}, {1}, and {2}.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9093W **Filter cannot be completely migrated to Provider Filter (UM). Contains duplicate field name:{0}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains the specified duplicate field name. Universal Messaging cannot filter on duplicate field names because duplicate field names cannot be encoded as protocol buffers.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9094W **Filter cannot be completely migrated to Provider Filter (UM). Contains field with an invalid name:{0}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains a name considered to be invalid by Universal Messaging or a field name that cannot be encoded as protocol buffers.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9095W **Filter cannot be completely migrated to Provider Filter (UM). Contains an Object or Object List field:{0}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains a field of type Objects and Object Lists which is defined to be an unknown Java wrapper type. Object and Object Lists defined to be an unknown Java wrapper type cannot be encoded with protocol buffers.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9096W **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid AND condition:{0} - {1}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an AND condition that specifies a null value. Because a null value cannot be included in a protocol buffer message, a filter that checks for a null value is invalid.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9097W **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid FUNCTION.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an invalid FUNCTION.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9098W **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid comparator value:{0} - {1}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains a comparison considered invalid by Universal Messaging or protocol buffers. At run time, the {0} in the message is replaced the contents of the left side of the expression and {1} is replaced by the contents of the right side of the expression.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9099W **Filter cannot be completely migrated to Provider Filter (UM). Contains a NULL comparator value:{0} - {1}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter compares a field to a NULL value. Because a null value cannot be included in a protocol buffer message, a filter that checks for a null value is invalid.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9100W **Filter cannot be completely migrated to Provider Filter (UM). Contains a REGEX value:{0} {1}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains a regular expression. Universal Messaging filtering syntax does not support the use of regular expressions.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9101W **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid Boolean value:{0}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an invalid value for a field or type Boolean.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9102W **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid OR condition:{0} - {1}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an OR condition that specifies a null value. Because a null value cannot be included in a protocol buffer message, a filter that checks for a null value is invalid. At run time, the {0} in the message is replaced the contents of the left side of the expression and {1} is replaced by the contents of the right side of the expression.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9103W **Filter cannot be completely migrated to Provider Filter (UM). Contains an invalid NOT condition:{0}.**

Explanation The contents of Filter could not be migrated to Provider Filter (UM) because the filter contains an invalid value in a NOT condition.

Action No action is required. The contents of the Filter field will not change. The trigger will apply the filter to any messages that it receives. Note that while Broker might have applied portions of the filter to received messages before routing the message to the trigger, once the trigger and it's document types have been updated to work with Universal Messaging, the contents of the Filter field become a local filter only. If you want the filter to become a provider filter applied by Universal Messaging, you must specify a filter in the Provider Filter (UM) field.

ISS.0098.9104E **{0} operation is not supported when connection alias type is Local.**

Explanation The documentTypeName input parameter specifies a publishable document type that uses the IS_LOCAL_CONNECTION alias. Instances of publishable document types that use the IS_LOCAL_CONNECTION messaging connection alias cannot be delivered.

Action Change the documentTypeName input parameter value to be a publishable document type associated with a Universal Messaging connection alias or a Broker connection alias and then re-execute the service. If you want to publish a document locally, use the pub.publish:publish service or the pub.publish:publishAndWait service.

ISS.0098.9105E **Cannot specify different provider filters for document type ''{0}'' within a single UM trigger**

Explanation If a webMethods messaging trigger that receives messages from Universal Messaging specifies the same publishable document type in more than one condition, the conditions must specify the same provider filter. That is, the contents of the Provide Filter (UM) column must be the same for each condition that subscribes to the same publishable document type.

Action Revise the contents of the Provider Filter (UM) column to be the same for each condition that subscribes to the same publishable document type.

ISS.0099.0001U **Broker Transport:{0} unable to subscribe to Broker Document {1}. Exception {2}**

Explanation The Integration Server failed to create the subscription for the trigger on the Broker. The Broker may be unavailable.

Action In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.

ISS.0099.0002U **Broker Transport:{0} unable to unsubscribe to Broker Document {1}. Exception {2}**

Explanation The Integration Server failed to cancel the subscription for the trigger from the Broker after removing the trigger from the Integration Server. The Broker might be unavailable.

Action In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.

ISS.0099.0003U **Unable to create Broker Transport {0}. Exception {1}**

Explanation The Integration Server failed to create the Broker transport for the Broker client because the client could not reconnect to the Broker. The Broker might be temporarily unavailable.

Action In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.

ISS.0099.0005E	**Creating subscription on Broker without invalid filter: {0}**
Explanation	A trigger contains an invalid filter. The subscription was created on the Broker without the invalid filter.
Action	Change the filter in the trigger to a valid trigger.

ISS.0099.0006U	**Unable to disconnect Broker Transport. Exception: {0}**
Explanation	Integration Server failed to disconnect from the Broker during shutdown. This indicates an internal error.
Action	Contact Software AG Global Support.

ISS.0099.0007U	**BrokerTransport:{0} got Exception: {1}**
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISS.0099.0008U	**Insufficient memory while retrieving events for BrokerTransport:{0}**
Explanation	The Integration Server does not have sufficient memory to retrieve even one document from the Broker.
Action	From the Broker, check the size of the document. Consider increasing the heap size of the JVM used by Integration Server.

ISS.0099.0009U	**Unable to retrieve events from the Broker for BrokerTransport:{0}. Insufficient JVM memory. Please check Heap size/ size of Documents on the Broker.**
Explanation	The Integration Server does not have sufficient memory to retrieve documents from the Broker.
Action	From the Broker, check the size of the documents. Consider increasing the heap size of the JVM used by Integration Server.

ISS.0099.0010U	**Broker Transport:{0} failed to unsubscribe to all Broker Documents. Exception {1}**
Explanation	The Integration Server failed to cancel the subscriptions from the Broker while removing the trigger from the Integration Server. The Broker might be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.

ISS.0099.0011E	**Broker Transport Factory unable to retrieve password for handle {0}**
Explanation	An internal error occurred.
Action	Contact Software AG Global Support.

ISS.0099.0012E	**{0} failed to retrieve password for handle {1}. Exception {2}**
Explanation	An internal error occurred.
Action	Contact Software AG Global Support.

ISS.0099.0013E	**{0} failed to save password for handle {1}. Exception {2}**
Explanation	An internal error occurred.
Action	Contact Software AG Global Support.

ISS.0099.0014E	**{0} failed to refresh broker settings. Exception type {1}, msg {2}**
Explanation	An error occurred while saving broker settings to disk.
Action	Read through the details provided in the exception and take corrective steps. If you are not able to resolve the problem, contact Software AG Global Support.

ISS.0099.0015E	**BrokerTransport : Broker Timing out repetitively. New subscriptions won't get created and if subscriptions are already existing,this might lead to the client queue growing on the broker**
Explanation	An attempt to create a new subscription has timed out multiple times.
Action	Contact Software AG Global Support.

ISS.0100.0036E	**{0} getReader() has already been called for this request**
Explanation	A servlet or JSP called the ServletRequest.getInputStream() method after it had already called the ServletRequest.getReader() method. The servlet or JSP can call one method or the other, not both.
Action	Check the servlet or JSP and ensure that only one of these methods is called.

ISS.0100.9900U	**The {0} action is not enclosed by a {1} action.**
Explanation	Integration Server was not able to execute a Web application because there are syntax errors in the JSP file.
Action	Examine the error message to determine which tag name caused the exception to be thrown. Then check the JSP file that contains the tags and look for syntax errors. See the "Web Applications Developer's Guide" for the correct usage. After you fix the problem, re-deploy the Web application on Integration Server.

ISS.0100.9901U **The {0} action is not enclosed by a {1} action at {2}.**

Explanation Integration Server was not able to execute a web application because there was a syntax error in the <webm:ifvar> and <webm:else> tags in the JSP file.

Action Examine the JSP file that contains the <webm:ifvar> and <webm:else> tags. See the "webMethods Applications Developer's Guide" for the correct usage of these tags. After you fix the problem, re-deploy the Web application on Integration Server.

ISS.0105.0003E **Cannot get canonicalKey: {0}**

Explanation The pub.synchronization.xref:getCanonicalKey service failed to execute because an exception was thrown when Integration Server tried to retrieve the corresponding canonical key for the specified native ID from the repository.

Action Examine the exception message and stack trace for details. Verify that you have provided correct input for the "appID", "nativeID", and "objectID" parameters. If you cannot find the cause for the problem, contact Software AG Global Support.

ISS.0105.0005E **Cannot insert into database this record, appId="{0}", nativeId="{1}", canonicalKey="{2}", objId="{3}", error: {4}**

Explanation The pub.synchronization.xref:createXReference service or pub.synchronization.xref:insertXReference service failed to execute because an exception was thrown when Integration Server tried to insert or create the cross-reference record in the repository.

Action Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0105.0006E **Cannot close latch: {0}**

Explanation The "pub.synchronization.latch:closeLatch" service failed to execute because an exception was thrown when Integration Server tried to close the latch for a given application ID, canonical Key, and object ID.

Action Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0105.0007E **Cannot open latch: {0}**

Explanation The "pub.synchronization.latch:closeLatch" service failed to execute because an exception was thrown when the Integration Server tried to open the latch for a given application ID, canonical Key, and object ID.

Action Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set

up your JDBC Pool correctly.If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0105.0008E **Cannot get nativeId: {0}**

Explanation The "pub.synchronization.xref:getNativeId" service failed to execute because an exception was thrown when the Integration Server tried to retrieve the native ID for a given canonical key, application ID, and object ID.

Action Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0105.0009E **Cannot obtain a JDBC connection: {0}**

Explanation The Integration Server was not able to obtain a connection to the JDBC database where cross-reference keys and echo suppression status are stored. A likely cause is that the pool alias for this database was specified incorrectly on the Settings>JDBC Pools page of the Server Administrator.

Action From the Settings>JDBC Pools page of the Server Administrator, examine the pool alias properties for the Xref and make sure it specifies the correct Database URL, User Id, Password, and Database driver. Then, restart the Integration Server.

ISS.0105.0010E **No JDBC connection available**

Explanation The Integration Server was not able to obtain a connection to the JDBC database where the cross-reference keys and echo suppression status are stored. A likely cause is that no JDBC pool connections are available.

Action From the Settings > JDBC Pools page of the Integration Server Administrator, examine the pool alias properties for the Xref and consider increasing the number of connections. Then, restart Integration Server.

ISS.0105.0011E **Release JDBC connection error: {0}**

Explanation Integration Server tried to perform a database operation, but the "pub.synchronization*" service failed to release its connection to the database. This indicates an internal error.

Action Contact Software AG Global Support.

ISS.0105.0012E	**Get preparedStatement error: {0}**
Explanation	While trying to perform a database operation, a "pub.synchronization*" service encountered an SQLException.
Action	Examine the error stack trace to determine which SQL exception was thrown. Make sure you followed the instructions in the "webMethods Integration Server documentation and set up the Database correctly. If you cannot determine the cause of the error, contact the database vendor.

ISS.0105.0013E	**Check isLatchClosed error: {0}**
Explanation	The pub.synchronization.latch:isLatchClosed service threw an exception when it tried to check the latch status for a given canonical key, application ID, and object ID.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set up your JDBC Pool correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0105.0014E	**Drop all records with objId="{0}", error: {1}**
Explanation	The "pub.synchronization.xref:deleteByObjectId" service threw an exception when it tried to remove all cross-reference records associated with a particular process or synchronization.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0105.0024E	**Delete xref record: appId="{0}", canonicalKey="{1}", objId="{2}", error: {3}**
Explanation	The pub.synchronization.xref:deleteXReference service threw an exception when it tried to remove all cross-reference records associated with a particular process or synchronization.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.012.0026E	**The certificate in the SAML assertion signature does not match the certificate on file for the issuer; Rejecting SAML assertion.**
Explanation	The certificate in the SAML assertion signature does not match the certificate on file for the issuer.
Action	Check the issuer configuration on Security -> SAML screen and make sure that the identified truststore contains the correct certificate for the issuer.

ISS.0125.0015W **The trigger input control parameters, watt.server.control.triggerInputControl.delaysIncrementInterval and watt.server.control.triggerInputControl.delays, were set to their default values because an exception occurred when parsing the supplied values.**

Explanation Integration Server could not set the trigger input control configuration parameter watt.server.control.triggerInputControl.delaysIncrementInterval and/or watt.server.control.triggerInputControl.delays to the new value because an exception occurred when parsing a new value for one of the parameters. Integration Server reset both configuration parameters to the default values.

Action Use a valid value for the watt.server.control.triggerInputControl.delaysIncrementInterval or watt.server.control.triggerInputControl.delays parameter.

ISS.0128.0001E **Unable to get JDBC connection. Exception:{0}**

Explanation Integration Server was unable to connect to the database defined by the DocumentHistory functional alias. This alias defines the database that the Integration Server uses to detect duplicate documents.

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.

ISS.0128.0002E **Exception while {1}: {0}**

Explanation An exception occurred when Integration Server tried to perform a task using the In Doubt Resolver component.

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.

ISS.0128.0003E **SQLException:{0} while {1}**

Explanation An exception occurred when Integration Server tried to perform a SQL operation using the JDBC connection pool for the functional alias DocumentHistory.

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.

ISS.0128.0004E	**Exception while loading the Decision Tree: {0}**
Explanation	An exception occurred when Integration Server tried to create the decision tree for resolving duplicate documents. The decision is based on multiple criteria, but Integration Server was not able to load these criteria into memory.
Action	Contact webMethods Customer Care. Be prepared to provide logs and the version number and patch level for Integration Server and your operating system.

ISS.0128.0005E	**Exception:{0} while resolving Document of type: {1} and Id: {2} for trigger: {3}. Document is being deemed as In Doubt.**
Explanation	An exception occurred when Integration Server tried to resolve a document it received. The exception might be due to a problem with the database connection for the alias DocumentHistory or with the Resolver Service associated with the trigger.
Action	Examine the Server log for error messages that indicate the cause of the problem. If the error was a database/SQL exception, check to see if the functional alias DocumentHistory is working properly. If a problem occurred with the Resolver Service, verify that the service is properly coded.

ISS.0128.0006E	**Trigger: {0} encountered exception while executing resolver service: {1}. Exception: {2}**
Explanation	Integration Server received a document, but the document resolver service associated with the trigger encountered an exception.
Action	Check the Error log to see if the Document Resolver Service associated with the trigger has logged any error messages. If no messages have been logged, change the auditing properties for the service to enable the Log on Error property. In addition, because this is a user-written service, check it to make sure it has been coded properly.

ISS.0128.0007E	**In Doubt document of type:{0} with Id:{1} received for trigger:{2}. Document is being Audit Logged.**
Explanation	Integration Server received a document, but the document resolver service associated with the rrigger could not resolve the document and therefore considers it to be "In Doubt".
Action	Check the document's id to see if it is a duplicate. If there is an document resolver service associated with the trigger, determine why the service was not able to resolve the document. Integration Server records occurrences of In Doubt Documents in the Audit log. You can view In Doubt documents through WmMonitor.

ISS.0128.0008E **Unable to Audit Log document of type:{0} with id:{1} as it can't be decoded. Exception:{2}.**

Explanation An error occurred when Integration Server tried to resolve a document. As part of the resolution process, a document first goes to the In Doubt Resolver component. If that component successfully resolves the document, Integration Server decodes the document and sends it to the trigger. However, if the In Doubt Resolver cannot resolve the document, the Integration Server decodes the document and sends it to the In Doubt Resolver service associated with the trigger. This error is issued if there is an error when decoding the document before sending it to the In Doubt Resolver service associated with the trigger.

Action Make sure the document type on Integration Server matches the associated Broker document type on the Broker. Re-sync the document types by pushing the IS document type to the Broker ("Push to Broker"). If all the document type fields and data types match and the problem still persists, contact webMethods Customer Care.

ISS.0128.0009E **Unable to get JDBC Connection to the database.**

Explanation As part of storing history for the document being processed, the Integration Server's In Doubt Resolver component add/deletes rows to a database. While performing one of these actions, the connection to the database was lost.

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a functional alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.

ISS.0128.0010 **Detected expired UUID:{0} for trigger:{1}. Deleting all expired UUIDs.**

ISS.0128.0011 **Unable to resolve processing state for UUID:{0} for trigger:{1}. Exception:{2}**

ISS.0128.0012 **Unable to mark UUID:{0} for trigger:{1} as complete in the database. A non-expired UUID already exists.**

ISS.0128.0014E **Unable to insert UUID:{0}. Exception:{1}**

Explanation As part of storing history for the document or message being processed, Integration Server's In Doubt Resolver component stores the UUID (universally unique ID) of the document (message) in a database. An exception occurred during this process.

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when

you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.

ISS.0128.0015E **Document history initialization failed. Please verify database connection is available.Exception {0}.**

Explanation No valid JDBC connection Pool is available for the In Doubt Resolver Alias "DocumentHistory". Detection of duplicate documents depends on the availability of a database where document history is defined.

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.

ISS.0128.9002E **Unable to get Connection**

Explanation No valid JDBC connection Pool is available for the In Doubt Resolver Alias "DocumentHistory".

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.

ISS.0128.9006E **Invalid argument supplied for:{0}**

Explanation Integration Server stores document history information in a database so that it can detect when duplicate documents are received. This error occurs when a process tries to insert an entry that specifies an invalid argument into the database.

Action Check to see if the name of the trigger and the UUID of the document satisfy the constraints specified on the columns of the Table WM_IDR_MSG_HST in your database. This error can occur if the Trigger Name or UUID exceeds the column length of the database column.

ISS.0128.9013E **Exception while executing in doubt resolver service:{0}**

Explanation Integration Server received a document, but an exception occurred during execution of the document resolver service associated with the trigger.

Action Check the Integration Serverse error log to see if the document resolver service has logged any error messages. If no errors were logged, configure the document resolver service's auditing properties to Log on Error. In addition, verify that the document resolver service has been coded properly.

ISS.0128.9015E	**The DocumentHistory functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.**
Explanation	Integration Server stores document history information in a Document History database so that it can detect when duplicate documents are received. Integration Server throws this exception whenever it does not find a JDBC Pool for the Document History functional alias.
Action	Configure a JDBC Pool for Document History functional alias.

ISS.0131.0001E	**No threads available. All diagnostic listener threads are in use.**
Explanation	Integration Server has detected that all threads allocated to the diagnostic thread pool are in use.
Action	Wait for one or more of these threads to finish. If this problem persists, contact webMethods Customer Care.

ISS.0131.0002	**DOMString size error. Details:{0}**

ISS.0131.0003	**Hierarchy request error. Details:{0}**

ISS.0131.0004	**Wrong document error. Details:{0}**

ISS.0131.0005	**Invalid character error. Details:{0}**

ISS.0131.0006	**No data allowed error. Details:{0}**

ISS.0131.0007	**No modification allowed error. Details:{0}**

ISS.0131.0008	**Not found error. Details:{0}**

ISS.0131.0009	**Not supported error. Details:{0}**

ISS.0131.0010	**Inuse attribute error. Details:{0}**

ISS.0131.0011 **Invalid state error. Details:{0}**

ISS.0131.0013 **Invalid modification error. Details:{0}**

ISS.0131.0015 **Invalid access error. Details:{0}**

ISS.0131.0017 **Type mismatch error. Details:{0}**

ISS.0131.9998 **Cannot set attribute name or value to null**

ISS.0131.9999 **Cannot get null attribute**

ISS.0134.0002 **JMS Runtime Configuration Internal Error. Unable to set thread pool max: {0}**

ISS.0134.0003 **An error occurred while loading JMS configuration file: {0}**

ISS.0134.0004 **Unable to start JMS connection alias {0}: {1}**

ISS.0134.0005E **Unable to start JMS connection alias {0}. The alias is now disabled: {1}**

Explanation The specified JMS connection alias could not be started because it is disabled. Only enabled JMS connection aliases can be started.

Action Enable the JMS connection alias.

ISS.0134.0006 **JNDI Propery "{0}" not found. Setting JMS connection alias {1} to disabled.**

ISS.0134.0009 **JMS configuration file not found: {0}**

ISS.0134.0010 **JMS subsystem is not configured. The default JMS connection alias is being created.**

ISS.0134.0011	**Unable to load JMS configuration file "{0}": {1}**
ISS.0134.0012	**Unable to load JMS configuration file "{0}": File not found.**
ISS.0134.0014	**"jms.cnf" file contains no configuration data.**
ISS.0134.0015	**Unable to load configuration for JMS connection alias {0}: {1}**
ISS.0134.0016	**JMS Connection Error on connection "{0}": {1}**
ISS.0134.0017	**Unable to destroy CSQ for connection "{0}": {1}**
ISS.0134.0018	**Unable to ping JNDI provider "{0}": {1}**
ISS.0134.0019	**Unable to start CSQ Factory. The CSQ feature will not be functional for any JMS connection aliases: {0}**
ISS.0134.0020	**Exception occured while pinging JMS provider "{0}": {1}**
ISS.0134.0021	**Error delisting resource from transaction: {0}**
ISS.0134.0022	**Error closing JMSSession: {0}**
ISS.0134.0023	**Error shutting down CSQ Factory: {0}**
ISS.0134.0024	**CSQ Dispatcher "{0}" unable to retrieve producer. CSQ Dispatcher is now stopping: {1}**
ISS.0134.0025	**CSQ Dispatcher "{0}" is stopping because of exception: {1}**

ISS.0134.0026	**CSQ Dispatcher "{0}" was unable to send message to "{1}" after {2} retries: {3}**
ISS.0134.0027	**CSQ Dispatcher "{0}" was unable to send message to "{1}": {2}**
ISS.0134.0028	**Out of memory error while acking message from CSQ "{0}". Attempting two retries**
ISS.0134.0030	**CSQ Dispatcher "{0}" was unable to acknowledge message: {1}**
ISS.0134.0031	**Out of memory error while sending message from CSQ. Attempting two retries**
ISS.0134.0033	**No metadata found for JMS connection alias {0}**
ISS.0134.0034	**No metadata found for JMS connection alias {0}: {1}**
ISS.0134.0035	**The JMS provider and version associated with JMS connection alias {0} is not officially supported.**
ISS.0134.0039	**IllegalStateException occured in Consumer {0}: {1}**
ISS.0134.0040	**OutOfMemoryError occured in Consumer {0}**
ISS.0134.0041	**JMS Trigger {0} failed preprocessing: {1}**
ISS.0134.0042	**JMS Trigger {0} failed: {1}**
ISS.0134.0043	**JMS Trigger {0} failed post-processing: {1}**
ISS.0134.0044	**JMS trigger {0} was unable to set JMS Reply To Context: {1}**

ISS.0134.0045I	**JMS Trigger {0} has acknowledged the message(s).**
Explanation	The specified JMS trigger has acknowledged the message(s) to the JMS provider.
Action	No action required.

ISS.0134.0046	**JMS Trigger {0} has recovered the message(s).**

ISS.0134.0051	**Created JMS Trigger Thread Pool with a maximum of {0} threads.**

ISS.0134.0053	**Unable to start JMS trigger {0}: {1}**

ISS.0134.0056	**Error closing Connection Handle: {0}.**

ISS.0134.0057	**JMS trigger {0} did not shutdown in the allotted time ({1} seconds). It is now being forced to shutdown.**

ISS.0134.0058	**JMS trigger {0} is shutting down because of exception: {1}**

ISS.0134.0059	**Error destroying Consumer Context: {0}.**

ISS.0134.0060	**Unable to refill Shared Session Pool after release: {0}**

ISS.0134.0061	**Consumer Context Pool shutodwn timeout: Freeing up active entries.**

ISS.0134.0062	**Internal Error: returning unused object to Consumer Context Pool!**

ISS.0134.0063	**JMS transaction failed with $errorType {0}.**

ISS.0134.0064	**Unable to register JMS trigger {0}: {1}**

ISS.0134.0065	**Unable to unregister JMS trigger {0}: {1}**
ISS.0134.0066	**JMS trigger {0} has started**
ISS.0134.0072	**JMS Trigger Resource Monitor scheduled new system task.**
ISS.0134.0073	**JMS Trigger Resource Monitor has resumed the last trigger. Its system task will now be canceled.**
ISS.0134.0074	**JMS Trigger Resource Monitor is now monitoring the resource availability of trigger {0}.**
ISS.0134.0075	**JMS Trigger Resource Monitor invoked service {0}. Status of resource is "{1}".**
ISS.0134.0076	**JMS Trigger Resource Monitor received an exception while invoking service {0}: {1}**
ISS.0134.0077	**JMSTrigger Resource Monitor has resumed trigger {0}.**
ISS.0134.0078	**JMS Trigger Resource Monitor received an exception while attempting to resume trigger {0}: {1}**
ISS.0134.0081	**No suitable data type was found in the message body so an empty Message is being created.**
ISS.0134.0082	**Not starting JMS connection alias {0} because package {1} is not loaded/enabled yet.**
ISS.0134.0083	**Trigger {0} cannot receive messages in a batch while using a transacted connection. The "max batch messages" size will be set to 1.**

ISS.0134.0084 **Unable to acknowledge InDoubtResolver: {0}**

ISS.0134.0085 **Unable to remove InDoubtResolver entry: {0}**

ISS.0134.0086 **Trigger Preprocessing Failure occurred for trigger {0}: {1}. The DocumentHistory JDBC alias may not be configured correctly. The trigger will be automatically suspended. You must restart it manually.**

ISS.0134.0087 **Trigger Preprocessing Failure occurred for trigger {0}: {1}. The trigger will be automatically suspended and IS will monitor the DocumentHistory JDBC resource.**

ISS.0134.0088 **Rejecting incoming message for trigger: {0}, documentID: {1}. Delivery Count has exceeded {2} attempts.**

ISS.0134.0089 **JMS Trigger {0} failed decoding: {1}**

ISS.0134.0090 **Unable to retrieve password from Password Manager with key {0}: {1}**

ISS.0134.0091 **Unable to set password in Password Manager with key {0}: {1}**

ISS.0134.0094 **Unable to start JMS connection alias {0}. The server will attempt to reconnect every {1} seconds: {2}**

ISS.0134.0096 **Could not create Destination to Ping Connection Alias :{0}.**

ISS.0134.0098 **JMS connection alias {0} is unable to check the JNDI namespace for updates to the ConnectionFactory "{1}": {2}**

ISS.0134.0099 **JMS connection alias "{0}" is updating because of changes made to ConnectionFactory "{1}" in the JNDI namespace.**

ISS.0134.0100	**Unable to restart JMS connection alias {0} after updating ConnectionFactory {1}: {2}**
ISS.0134.0102	**Unable to register event listener. Update functionality not available for this JNDI provider: {0}**
ISS.0134.0103	**The JNDI event listener for JMS connection alias {0} has been disconnected. The system will try to reconnect.**
ISS.0134.0104	**JMS connection alias {0} is dynamically setting polling interval to {1} milliseconds.**
ISS.0134.0105	**JMS connection alias {0} is unable to retrieve polling interval, so the default value of {1} minutes will be used instead: {2}**
ISS.0134.0106	**Starting JMS connection alias with Guaranteed Multisend policy. Broker list = {0}; Multisend Broker count = {1}.**
ISS.0134.0114D	**Refreshed Consumer Context: sessionId={0}, trigger={1}**
Explanation	Integration Server refreshed the session for the specified message consumer.
Action	None.
ISS.0134.0115D	**Initialized default Session pool for alias "{0}"; max size "{1}"**
Explanation	Integration Server created a default Session Pool for the specified JMS connection alias.
Action	No action required.
ISS.0134.0116D	**Initialized MessageProducer pool for alias "{0}"; destination "{1}"; max size "{2}"**
Explanation	For the specified JMS connection alias, Integration Server created a MessageProducer Pool for the specified destination.
Action	No action required.
ISS.0134.0117E	**Unable to initialize MessageProducer pool for alias "{0}"; destination "{1}": {2}**
Explanation	An error occurred while initializing the MessageProducer Pool for the specified JMS connection alias and destination. The error most likely occurred because the destination does not exist or cannot be accessed.
Action	Verify that the specified destination exists and that you have sufficient privileges to access the destination. If the JMS connection alias uses a JNDI provider for administered objects, verify that the JNDI provider is available.

ISS.0134.0999 **JMS subsystem unexpected error: {0}**

ISS.0134.9045E **Unable to create trigger "{0}". Invalid or non-ascii characters in NSName.**

Explanation The WS endpoint trigger could not be created because the Web service endpoint alias name includes characters that are not valid for an element name.

Action Change the name of the alias so that it does not include any characters that Integration Server considers to be reserved or invalid for element names. Refer to the Designer or webMethods Developer documentation for a list of reserved or invalid characters.

ISS.0134.9082E **The client side queue cannot be used with a send and wait request if the reply destination is a temporary queue.**

Explanation The useCSQ parameter is set to true and the replyToDestinationName is blank or specifies a temporary queue.

Action If you want Integration Server to route messages to the client side queue when the JMS provider is not available leave useCSQ set to true and specify a queue that is not temporary. That is, specify values for the destinationNameReplyTo and destinationTypeReplyTo input parameters.

ISS.0134.9083E **The pub.jms:sendBatch service is not supported with this provider.**

Explanation The connecationAliasName parameter specifies a JMS connection alias that uses a JMS provider that is not supported with the pub.jms:sendBatch service.

Action Change the value of the connectionAliasName parameter to specify a JMS connection alias that uses a supported JMS provider.

ISS.0134.9084E **The pub.jms:sendBatch service is not supported with connection factories that use the multisend guaranteed or multisend best effort Broker cluster policies.**

Explanation The connectionAliasName parameter specifies a JMS connection alias that uses a connection factory to which the multisend guaranteed or multisend best effort Broker cluster policy is applied. The pub.jms:sendBatch service cannot be used with connection factories that have these policies.

Action Change the value of the connectionAliasName parameter to specify a JMS connection alias that does not use a connection factory to which the multisend guaranteed or multisend best effort Broker cluster policy is applied.

ISS.0134.9350E **UM admin operation failed [{0}]: {1}**

Explanation The specified admin operation could not be completed on Universal Messaging due to the listed error. Integration Server will perform admin operations on Universal Messaging when Designer is being used to manage destinations and durable subscribers on Universal Messaging.

Action Use the provided error message to determine why the admin operation could not be completed.

ISS.0135.0001E **No properties found for JNDI alias {0}**

Explanation Integration Server could not find the JNDI properties file for the specified JNDI provider alias.

Action Ensure that the properties file associated with the JNDI provider alias exists and is not empty. The JNDI properties file is stored in the following directory: IntegrationServer_directory\instances\instanceName\config\jndi

ISS.0135.0002E **JNDI configuration file already exists: {0}**

Explanation Integration Server cannot create the JNDI provider alias because a JNDI properties file already exists for an alias with that name.

Action Ensure that the JNDI provider alias is not a duplicate of one that already exists. Specify a different name for the JNDI provider alias.

ISS.0135.0003E **JNDI configuration file does not exist: {0}**

Explanation When deleting the JNDI provider alias, Integration Server encountered an error when attempting to dlete the assoiated properties file as the asssociated JNDI properties file does not exist.

Action Ensure that the properties file associated with the JNDI provider alias exists in the following directory: IntegrationServer_directory\instances\instanceName\config\jndi

ISS.0135.0004E **Unable to delete JNDI configuration file: {0}**

Explanation When deleting the JNDI provider alias, Integration Server could not delete the associated JNDI properties file.

Action Ensure that another user is not currently accessing the properties file for the JNDI provider alias that you are attempting to delete. The JNDI properties files are located in the following directory IntegrationServer_directory\instances\instanceName\config\jndi

ISS.0135.0005E **Unable to load JNDI Properties. File not found: {0}**

Explanation Integratio Server cannot load the properties file associated with the JNDI provider alais.

Action Ensure that a valid properties file exists for the JNDI provider alias in the following directory: IntegrationServer_directory\instances\instanceName\config\jndi

ISS.0135.0006E	**Unable to load JNDI Properties. Invalid properties file: {0}**
Explanation	Integration Server could not load the properties file for the JNDI provider alias becaues the file is invalid.
Action	Ensure that the properties file associated with the JNDI provider alias exists and is not empty. The JNDI properties file is stored in the following directory: IntegrationServer_directory\instances\instanceName\config\jndi

ISS.0137.0002W	**Scheduler: Unable to get pool for ISInternal**
Explanation	Integration Server was unable to get the ISInternal JDBC connection pool.
Action	Configure the ISInternal functional alias (specified on the Settings > JDBC Pools screen in Integration Server Administrator) and assign a valid JDBC connection pool to it.

ISS.0137.0006E	**Scheduler: Error initializing scheduler: {0}**
Explanation	Integration Server encountered an error while initilizing the database in which information about scheduled jobs is stored.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0007E	**Scheduler: Unable to get a connection to the database.**
Explanation	Integration Server was unable to get a connection from the JDBC connection pool.
Action	Use Integration Server Administrator to increase the maximum number of connections available in the JDBC connection pool that is assigned to the ISInternal functional alias.

ISS.0137.0010E	**Scheduler: Resources unavailable: {0}**
Explanation	Scheduler thread throttle, which is the percentage of server threads the scheduler function is permitted to use, is reached. Integration Server cannot execute a scheduled task because there are no threads available.
Action	Use Server Administrator to increase the maximum number of connections available in the JDBC pool that is assigned to the ISInternal functional alias.

ISS.0137.0011E	**Scheduler: Exception: {0}**
Explanation	Integration Server encountered an error while retrieving a scheduled task from the database and executing it.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0012E	**Scheduler: Error inserting task into database: {0}**
Explanation	Integration Server encountered an error while adding a new scheduled task to the database.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0013E	**Scheduler: Error updating task in database: {0}**
Explanation	Integration Server encountered an error while updating the information of a scheduled task in the database.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0014E	**Scheduler: Error updating status in database: {0}**
Explanation	Integration Server encountered an error while updating the status of a scheduled task in the database.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0016E	**Scheduler: Exception getting task IDs from database: {0}**
Explanation	Integration Server encountered an error while retrieving the IDs of scheduled tasks associated with a user.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0017E	**Scheduler: Exception getting tasks from database: {0}**
Explanation	Integration Server encountered an unexcepted SQLException while retrieving the scheduled tasks from the database.
Action	Ensure that the database is available and configured to execute scheduled tasks.

ISS.0137.0018E	**Scheduler: Exception while invoking "{0}": {1}**
Explanation	Integration Server encountered a runtime exception while invoking a scheduled task.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0021E	**Invalid database vendor type: {0}**
Explanation	The database driver for the ISInternal functional alias is not valid.
Action	Go to the Settings > JDBC Pools page in Integration Server Administrator and set ISInternal's pool alias to use one of the listed database drivers.

ISS.0137.0022E	**No ISInternal JDBC Pool**
Explanation	The ISInternal functional alias is not configured.
Action	Configure the ISInternal functional alias (specified on the Settings > JDBC Pools screen in Integration Server Administrator) and assign a valid JDBC connection pool to it.

ISS.0137.0023E	**Could not get connection for pool {0}**
Explanation	Integration Server attempted to acquire a JDBC connection, but no connections are available in the pool assigned to the ISInternal functional alias.
Action	Use Server Administrator to increase the maximum number of connections available in the JDBC pool that is assigned to the ISInternal functional alias.

ISS.0137.0024E	**Namespace Dependency Manager is disabled**
Explanation	Unable to determine if the service executed by a scheduled task refers to other services that are unavailable.
Action	Contact Software AG Global Support.

ISS.0137.0025E	**Found unresolved dependent services: {0}**
Explanation	Integration Server was unable to create or run the scheduled task because the service scheduled to run contains a reference to a service that cannot be located.
Action	Update the scheduled task to specify a correct reference to the dependent service. Note: Integration Server performs reference validation for services only when the watt.server.scheduler.ignoreReferenceValidation configuration parameter is set to true. The default is false.

ISS.0137.0026E	**User {0} is disabled**
Explanation	The user a scheduled task is set to run as is disabled. The task will not run.
Action	Enable the user or modify the task to run as a different user.

ISS.0137.0027E	**User {0} is removed**
Explanation	The user associated with a scheduled task has been removed.
Action	Add the user or change the scheduled task to execute with an enabled user.

ISS.0137.0028W	**Could not complete last run at node {0}**

ISS.0137.0029E	**Rolling back due to scheduler thread throttle reached: {0}**
Explanation	A scheduled task attempted to use more threads than the maximum number allowed by the Scheduler thread throttle limit. Any scheduled tasks that attempt to execute under these circumstances will fail.
Action	Use Integration Server Administrator to increase the Scheduler thread throttle under Settings > Resources > Edit Resource Settings > Server Thread Pool.

ISS.0137.0030E	**...<truncated>**
Explanation	Integration Server encountered an error during the execution of a scheduled task.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0031E	**Invalid Target {0}**
Explanation	A scheduled task is set to run on a host that is not currently a member of the Integration Server cluster.
Action	Modify the scheduled task to run on a member of the cluster.

ISS.0137.0032E	**Invalid task ID {0}**
Explanation	Internal error.
Action	Contact Software AG Global Support.

ISS.0137.0033E	**Errors encountered while initializing Scheduler. Scheduled tasks will not run. Check the logs for more information.**
Explanation	Integration Server encountered an error either while initializing the scheduler or while connecting to the database in which information about scheduled jobs is stored. As a result, scheduled tasks will not run.
Action	Read through the contents of the error logs and take corrective steps. After correcting the issue that caused the error, restart the Integration Server.

ISS.0137.0034E	**Unknown Service: {0}. Scheduled task will not run.**
Explanation	The service configured to execute for a scheduler does not exist in the Integration Server.
Action	Ensure that the service is available in the Integration Server.

ISS.0138.0350E	**Test of CentraSite connection failed.**
Explanation	Integration Server encountered an exception while connecting to CentraSite.
Action	Ensure the parameters that Integration Server uses to connect to CentraSite are correct. Specifically, check the URL pointing to CentraSite (including the port), the user name, and password.

ISS.0139.0056W	**Error: Default keystore alias "DEFAULT_IS_KEYSTORE" cannot be created. Details: {0}**
Explanation	Error while creating DEFAULT_IS_KEYSTORE alias at the first startup of Integration Server.
Action	The following lists the actions you can take: 1. Ensure that the keystore file 'keystore.jks' is present in the Integration Server_directory\common\conf directory. 2. Ensure that the keystore has not expired. 3. Contact Software AG Global Support.

ISS.0139.0057W	**Error: Default truststore alias "DEFAULT_IS_TRUSTSTORE" cannot be created. Details: {0}**
Explanation	Error while creating DEFAULT_IS_TRUSTSTORE alias at the first start up of Integration Server.
Action	The following lists the actions you can take: 1. Ensure that the truststore file platform_truststore.jks is present in the Integration Server_directory\common\conf\ directory. 2. Ensure that the truststore has not expired. 3. Contact Software AG Global Support.

ISS.0139.9002E	**Error: invalid keystore or truststore configuration file "{0}".**
Explanation	Configuration file related to keystore is corrupted.
Action	Create a keystore alias.

ISS.0139.9003I	**Keystore alias "{0}" saved successfully.**

ISS.0139.9004W	**Keystore alias "{0}" saved successfully. Warning: before using the keystore, you must create a password for at least one of its key aliases. Please edit the keystore alias configuration and add one or more valid key alias passwords.**
Explanation	The key aliases are not configured. Before using the keystore, you must create a password for at least one of its key aliases.
Action	Edit the keystore alias configuration and add at least one valid key alias passwords.

ISS.0139.9005E	**Keystore alias "{0}" saved successfully. An error occurred while loading the keystore in memory, please edit the keystore alias configuration. Details: {1}**
Explanation	An error occurred while loading the keystore in memory.
Action	Edit the keystore alias configuration. Make sure that the keystore location is correct and keystore exists on the file system. Then, make sure that the configuration file related to the keystore is valid.

ISS.0139.9006W	**Keystore alias "{0}" saved successfully. Warning: the following key aliases "{1}" cannot be used because they do not have passwords. Please edit the keystore alias configuration and add password(s) for the appropriate key alias(es).**
Explanation	Some key aliases are not configured.
Action	Edit the keystore alias configuration and add passwords for the corresponding key aliases.

ISS.0139.9007W	**Keystore alias "{0}" saved successfully. Warning: the following key aliases "{1}" have been removed from the keystore alias configuration.**
Explanation	Few key aliases were removed from the keystore alias configuration.
Action	Refresh the keystore alias.

ISS.0139.9012E	**Error: cannot save the keystore alias "{0}".**
Explanation	Either the keystore location is invalid, or the key aliases passwords do not consist of ASCII characters.
Action	Make sure that the keystore location is valid and the key aliases passwords consist of valid ASCII characters.

ISS.0139.9013E	**Error: keystore "{0}" not found.**
Explanation	The configuration file related to keystore alias is unavailable.
Action	Make sure that the configuration file related to the keystore alias exists in the directory ../config/security/keystore.

ISS.0139.9014E	**Error: keystore "{0}" not found. Details: {1}.**
Explanation	Invalid keystore location.
Action	Make sure that the location of the keystore is correct; the key aliases passwords are valid; and the configuration file exists, and it is not corrupted.

ISS.0139.9016W	**Keystore "{0}" was reloaded successfully. Warning: you must provide the password for at least one key alias in the keystore before using it. Please edit the keystore alias configuration and add at least one valid key alias password.**
Explanation	Either the keystore does not contain any key aliases, or a key alias password is not provided. You must provide the password for at least one key alias in the keystore before using it.
Action	Check whether the keystore has any key aliases. If not, then add key alias in the keystore. If there are key aliases in the keystore, then edit the keystore alias configuration and add at least one valid key alias password.

ISS.0139.9017W	**Keystore "{0}" reloaded successfully. Warning: the following key aliases "{1}" cannot be used because they do not have a password. Please edit the keystore alias configuration and add one or more valid key alias passwords.**
Explanation	Key alias must be configured in advance.
Action	Edit the keystore alias configuration and add one or more valid key alias passwords.

ISS.0139.9018W	**Keystore "{0}" reloaded successfully. Warning: the following key aliases "{1}" have been removed from the alias configuration.**
Explanation	Key alias must be configured in advance.
Action	Edit the keystore alias configuration and add one or more valid key alias passwords.

ISS.0139.9019E	**Error: cannot reload keystore "{0}". Details: {1}.**
Explanation	Keystore alias does not map to a valid keystore.
Action	Make sure that the keystore location is correct and keystore exists on the file system. Make sure that the configuration file related to the keystore is valid.

ISS.0139.9020E	**Error: cannot reload keystore "{0}".**
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.

ISS.0139.9022E	**Error: unable to delete the keystore alias "{0}".**
Explanation	Keystore does not exist.
Action	Make sure that the keystore location is correct and the keystore exists on the file system.

ISS.0139.9023E	**Error: invalid keystore alias name "{0}".**
Explanation	Keystore alias is null or empty.
Action	Make sure that the keystore alias is not null or empty.

ISS.0139.9024E	**Error: cannot load the keystore pointed to by keystore alias "{0}", because of invalid password(s) for key alias(es) "{1}".**
Explanation	Invalid key alias password.
Action	Make sure that the key aliases passwords are correct.

ISS.0139.9025E	**Error: invalid key alias "{0}".**
Explanation	The key alias is invalid.
Action	Make sure that the key alias exists in the keystore.

ISS.0139.9026E	**Error: unable to look up the password for the key alias "{1}" in the keystore '{0}".**
Explanation	Invalid key alias password.
Action	Make sure that the key alias password is correct.

ISS.0139.9028E	**Truststore alias "{0}" saved successfully. An error occurred while loading the truststore in memory, please edit the truststore alias configuration. Details: {1}.**
Explanation	Configuration file is corrupted.
Action	Make sure that the configuration file, which corresponds to the truststore alias is valid.

ISS.0139.9029E	**Error: cannot save the truststore alias "{0}".**
Explanation	Truststore location is invalid.
Action	Make sure that the truststore location is valid.

ISS.0139.9030E	**Error: truststore "{0}" not found.**
Explanation	The configuration file related to truststore alias is unavailable.
Action	Make sure that the configuration file related to the truststore alias exists in the directory ../config/security/keystore.

ISS.0139.9031E	**Error: truststore "{0}" not found. Error: {1}.**
Explanation	Either the truststore location, or the configuration file is invalid.
Action	Make sure that the location of the truststore is correct; the truststore alias password is correct; and the configuration file exists, and it is not corrupted.

ISS.0139.9033E	**Error: cannot reload truststore "{0}". Details: {1}.**
Explanation	Either the keystore location is invalid, or the key aliases are modified.
Action	Make sure that the keystore location is valid and the key alias is not modified.

ISS.0139.9034E	**Error: cannot reload truststore "{0}".**
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.

ISS.0139.9036E	**Error: unable to delete the truststore alias "{0}".**
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file for the truststore alias exists in the directory ../config/security/keystore.

ISS.0139.9037E	**Error: invalid truststore alias name "{0}".**
Explanation	Invalid truststore name.
Action	Make sure that the truststore name is not null or empty.

ISS.0139.9038E	**Error: cannot retrieve data for the truststore "{0}".**
Explanation	Keystore is not loaded or initialized properly.
Action	Make sure that keystore is valid and the alias refers to the valid keystore location.

ISS.0139.9039E	**Error: cannot retrieve trusted certificates from the truststore pointed to by truststore alias "{0}". Details: {1}.**
Explanation	Truststore is not initialized or loaded properly.
Action	Reload the truststore alias and then make sure that the configuration file exists for the truststore alias.

ISS.0139.9041E	**Error: cannot retrieve the key for alias "{0}" from the keystore pointed to by keystore alias "{1}". Details: {2}.**
Explanation	Key alias entry in the keystore is not valid.
Action	Make sure that the key alias entry in the keystore is valid. For example, the certificate chain is available or the algorithm of the private key matches to the algorithm of the PublicKey in the end entity Certificate (at index 0).

ISS.0139.9043E	**Error: cannot retrieve the certificate for alias "{0}" from the truststore pointed to by truststore alias "{1}". Unsupported certificate type "{2}".**
Explanation	Invalid certificate type.
Action	Make sure that the certificate configured by the key alias is X509 Certificate.

ISS.0139.9044E	**Error: the alias has been modified from "{0}" to "{1}".**
Explanation	Keystore alias does not map to a valid keystore.
Action	Make sure that the keystore alias refers to a valid keystore.

ISS.0139.9045E	**Error: either the alias name"{0}" or the configuration file name "{1}" is incorrect.**
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file exists for the alias in the directory ../config/securoty/keystore.

ISS.0139.9047E	**Password for following key aliases must be ASCII characters: {0}**
Explanation	The key alias password consists of non-ASCII characters.
Action	Make sure that the key alias password consists of valid ASCII characters.

ISS.0139.9051E	**Error: cannot load the keystore/truststore configuration file "{0}". Details:{1}.**
Explanation	Failed to load the keystore file. Possible reasons: a. Corrupt keystore file b. Incorrect password c. No read permission for keystore file
Action	Ensure that: a. The Keystore file is not corrupted. Try opening it using another keystore tool. b. Provide a correct password c. Check file permissions

ISS.0139.9052E	**Error: invalid keystore/truststore configuration file "{0}".**
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
ISS.0139.9053E	**Error: ISKeyStoreManager initialization failed. Cannot create the keystore configuration directory "{1}".**
Explanation	Keystore directory does not exist.
Action	Keystore location is invalid. Make sure that the keystore directory exists.
ISS.0139.9054E	**Error: alias has been modified from "{0}" to "{1}".**
Explanation	Keystore alias does not map to a valid keystore .
Action	Make sure that the keystore alias refers to a valid keystore.
ISS.0139.9055E	**Error: either the alias name "{0}" or the configuration file name "{1}" is incorrect.**
Explanation	Configuration file is corrupted.
Action	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
ISS.0139.9058I	**Default keystore alias for Integration Server.**
ISS.0139.9059I	**Default truststore alias for Integration Server.**
ISS.0141.0001E	**Unable to create JMS URI for WS Endpoint Alias "{0}": {1}**
Explanation	The Web service endpoint alias does not contain the information needed to construct a JMS URI.
Action	Use the information in the exception to update the alias. For example, you may need to make changes to the provider Web service endpoint alias or edit the SOAP-JMS trigger used with the alias.
ISS.0141.0002E	**Unable to create WS Endpoint Trigger: {0}**
Explanation	Integration Server could not create a WS endpoint trigger using the information in the provider Web service endpoint alias.
Action	In Integration Server Administrator, use the information provided in the exception to edit the provider Web service endpoint alias

ISS.0141.0101W	**WS-Policy file {0} with policy ID {1} is invalid. Details: {2}**
Explanation	The WS-Policy file added to the policy repository is not valid. Integration Server has moved the policy file to the IntegrationServer/config/wss/policies/invalid folder.
Action	Correct the invalid WS-Policy file in the IntegrationServer/config/wss/policies/invalid folder to make it valid and move it back into the main policy repository directory.

ISS.0141.0103W	**Web service descriptor {0} is not available because the WS-Policy file {1} with policy ID {2} attached to the WSD is deleted.**
Explanation	The Web service descriptor is not available because the WS-Policy file attached to the Web service descriptor is deleted or moved from the policy repository.
Action	The following lists the actions you can take: 1) Ensure that the WS-Policy that is attached to the Web service descriptor resides in the policy repository. -OR- 2) Edit the Web service descriptor so that it no longer uses the deleted WS-Policy file.

ISS.0141.0107W	**Web service descriptor {0} is not available because the policy ID in WS-Policy file {1} is changed from {2} to {3}.**
Explanation	The Web service descriptor is not available because the policy ID of the WS-Policy file attached to the Web service descriptor has changed.
Action	The following lists the actions you can take: 1) Change the policy id of the WS-Policy that is attached to the Web service descriptor to what it was previously. 2) Edit the Web service descriptor by re-attaching the WS-Policy file with the updated policy ID.

ISS.0141.0108E	**Transport header "{0}" is invalid and will not be added to the message. Transport headers must be Strings.**
Explanation	In the name/value pair supplied as a transport header, the name and the value must be of type String. If a transport header has a name or value that is not of type String, the header will not be included in the message.
Action	Change the transport header so that the name and value are both of type String.

ISS.0141.0109W	**Could not deploy consumer Web service descriptor {0} for handling asynchronous responses. Connectors generated for this consumer Web service descriptor can only be used for handling responses synchronously. Cause: {1}.**
Explanation	The consumer Web service descriptor specified in the message could not be deployed to handle asynchronous responses. See the error message for more details about the cause of the failure.
Action	If the error message indicates that the error can be resolved by changing the WSDL, change or correct the WSDL used for creating the consumer Web service descriptor and recreate the consumer. If the error still occurs, contact Software AG Global Support.

ISS.0141.9106E	**Received a null response.**
Explanation	An internal error occurred while processing the Web service request.
Action	Contact Software AG Global Support.

ISS.0141.9107E	**Received unsupported content-encoding: {0}**
Explanation	The Web service response used the specified content-encoding, which is not supported.
Action	Ensure that the Web service request specifies a supported content-encoding for the response.

ISS.0141.9108E	**An HTTP transport error occured. Error Code: {0}, Error Message: {1}**
Explanation	An error occurred while sending a Web service response. The error code and message portions of the error contain details about the error.
Action	Contact Software AG Global Support.

ISS.0141.9109E	**Access Denied**
Explanation	A Web service request has arrived over an HTTP or HTTPS port, but the port access check has failed for the Web service descriptor. This means that the provider Web service descriptor name is either missing from the Allow list or is present in the Deny List, depending on how access to the port is defined.
Action	If access to this Web service is to be allowed over this port, ensure that the provider Web service descriptor name is either removed from the port's deny list or added to the port's allow list.

ISS.0141.9208E	**Could not deploy the Web service descriptor {0}. Cause: {1}**
Explanation	Integration Server could not deploy the Web service descriptor. Typical reasons are: 1) The WS-Policy that is attached to the provider Web service descriptor does not exist. 2) The module required to handle the attached WS-Policy does not exist.

3) The "rampartConfigProperties" parameter, which is in the axis2.xml file, is locked. If it is not one of these reasons, refer to the error message, which lists the cause.

Action The following lists the actions you can take for one of the typical causes:

1) Ensure the WS-Policy that is attached to the Web service descriptor resides in the policy repository: (webMethods_directory)/IntegrationServer/config/wss

2) Ensure the module required to handle the attached WS-Policy resides in the (webMethods_directory)/IntegrationServer/config/wss/modules subdirectory.

3) Ensure the "rampartConfigProperties" parameter in the axis2.xml file is not locked. The axis2.xml file resides (webMethods_directory)/IntegrationServer/config/wss/modules subdirectory. For all other reasons, refer to the cause listed in the error message and respond accordingly.

ISS.0141.9211E **Received a plain text response: {0}**

Explanation A Web service call expected a SOAP Response but instead received a plain text response. The actual responseText is returned within a SOAP fault.

Action Determine why the Web service provider did not return a SOAP response. It is possible that an incorrect endpoint address was used or an error occurred on the Web service provider.

ISS.0141.9213E **Unknown web services reliable messaging sequence {0} specified for endpoint URI {1}.**

Explanation A reliable messaging sequence with the specified sequence key corresponding to the specified endpoint URI does not exist.

Action Specify a valid sequence key for the specified endpoint URI.

ISS.0141.9214E **A duplicate web services reliable messaging sequence {0} specified for endpoint URI {1}.**

Explanation A reliable messaging sequence with the specified sequence key and endpoint URI already exists.

Action Specify a valid sequence key for the specified endpoint URI.

ISS.0141.9215E **A closed web services reliable messaging sequence {0} specified for endpoint URI {1}.**

Explanation The reliable messaging sequence with the specified sequence key and endpoint URI is closed.

Action Specify a valid sequence key for the specified endpoint URI.

ISS.0141.9216E	**A terminated web services reliable messaging sequence {0} specified for endpoint URI {1}.**
Explanation	The reliable messaging sequence with the specified key and endpoint URI is terminated.
Action	Specify a valid sequence key for the specified endpoint URI.

ISS.0141.9217E	**Web services reliable messaging is not enabled for consumer web Services Descriptor {0}.**
Explanation	Reliable messaging is not enabled for the specified consumer web service descriptor.
Action	Specify a valid consumer web service descriptor for which reliable messaging is enabled or enable reliable messaging for the specified consumer web service descriptor.

ISS.0142.0003W	**User {0} issued request to cancel the thread. Thread id - {1}**
Explanation	Integration Server received a request to cancel an executing thread.
Action	No action is required.

ISS.0142.0004W	**User {0} issued request to kill the thread. Thread id - {1}**
Explanation	Integration Server received a request to kill an executing thread.
Action	No action is required.

ISS.0142.0018E	**The watt.server.threadKill.timeout.enabled parameter is set to true; however, the property that enables the thread kill facility, watt.server.threadKill.enabled, is set to false.**
Explanation	The ability to cancel or kill service threads is controlled by the watt.server.threadKill.enabled property. If you want to be able to cancel or kill threads, this property must be set to true, which is the default setting.
Action	Set watt.server.threadKill.enabled to true so that a flow step will not run beyond its specified timeout period.

ISS.0145.0000E	**Unable to start Integration Server in quiesce mode. No quiesce port was specified.**
Explanation	Integration Server cannot be started from the command line with the -quiesce switch unless a quiesce port is specified.
Action	Start Integration Server using either the Start menu (on Windows) or the startup.sh script (on UNIX). Then, specify the quiesce port that Integration Server should use to enter and exit quiesce mode.

ISS.0145.0009E	**Unable to quiesce this Integration Server. Exception: {0}**
Explanation	An error occurred while switching this server to quiesce mode.
Action	Check the Integration Server server and error logs. Take appropriate corrective action for the reported asset type. Then, try switching to quiesce mode again.

ISS.0145.0012W	**Handler "{0}" cannot disable asset type "{1}". Exception: {2}**
Explanation	While entering quiesce mode, Integration Server encountered an error when attempting to disable the specified asset type.
Action	In the Integration Server Administrator, manually disable the assets of the reported asset type.

ISS.0145.0015E	**Unable to return Integration Server to active mode. Exception: {0}**
Explanation	An error occurred while switching this Integration Server to active mode.
Action	Check the Integration Server server and error logs. Then, take the appropriate corrective action.

ISS.0145.0018W	**Handler "{0}" was unable to restore state of "{1}" asset type. Exception: {2}**
Explanation	While exiting quiesce mode, Integration Server could not restore the state of the specified asset type.
Action	In the Integration Server Administrator, manually enable the assets of the reported asset type.

ISS.0145.0020W	**Unable to shut down the quiesce mode manager. Exception: {0}.**
Explanation	Integration Server could not save the quiesce properties in the quiesce configuration file. The quiesce.cnf file either does not exist or is corrupt.
Action	Delete the quiesce.cnf file from the Integration Server_directory\config directory. Then, restart the server and specify the quiesce port again.

ISS.0145.0022E	**Unable to save the configuration after setting quiesce port to {0}. Exception: {1}**
Explanation	An error occurred when the quiesce port was changed and Integration Server attempted to save the changes.
Action	Set the quiesce port to a valid port. If the error recurs, contact Software AG Global Support.

ISS.0145.0023E	**Unable to validate quiesce port {0}. Port does not exist.**
Explanation	The quiesce port has been deleted.
Action	Specify the port alias of an existing valid port.

ISS.0145.0024E	**Unable to validate quiesce port {0}. Port is not enabled.**
Explanation	The quiesce port is disabled.
Action	Enable the quiesce port.

ISS.0145.0025E	**Unable to validate quiesce port {0}. Port is not associated with WmRoot or WmPublic package.**
Explanation	The quiesce port does not reside in either the WmRoot or the WmPublic package.
Action	Specify the port alias of a valid quiesce port that resides in either the WmRoot package or the WmPublic package.

ISS.0145.0027E	**Unable to validate quiesce port {0}. Port type is incorrect.**
Explanation	The specified quiesce port does not belong to the HTTP or HTTPS protocol.
Action	Specify the port alias of a valid quiesce port of type HTTP or HTTPS.

ISS.0145.0028E	**Unable to validate quiesce port {0}. Port is suspended.**
Explanation	The quiesce port is suspended.
Action	Resume the quiesce port.

ISS.0145.0029E	**Unable to validate quiesce port {0}. Port does not have the necessary access mode.**
Explanation	The quiesce port's access mode is set to Deny+.
Action	Change the quiesce port's access mode to Allow.

ISS.0145.0202E	**Integration Server that is configured to be a member of a cluster did not join the cluster when exiting quiesce mode.**
Explanation	When exiting quiesce mode, Integration Server did not join the cluster.
Action	Use the Integration Server server log and error log to determine why Integration Server did not join the cluster and take the necessary actions to correct the error. Then, do one of the following for Integration Server to join the cluster: either restart Integration Server or enter and exit quiesce mode.

ISS.0145.0206E	**Integration Server is not configured for clustering. Errors occurred during initialization of cache managers. Exception: {0}**
Explanation	When exiting quiesce mode, Integration Server failed to initialize cache managers.
Action	Check Integration Server Server and Error logs and take required actions to correct the clustering error. Once this is done, you can either restart Integration Server or Enter and Exit Quiesce Mode to enable the cluster.

ISS.0145.0207E	**Integration Server is not configured for clustering. Errors occurred during initialization of cache managers.**
Explanation	When exiting quiesce mode, Integration Server failed to initialize cache managers.
Action	Check Integration Server Server and Error logs and take required actions to correct the clustering error. Once this is done, you can either restart Integration Server or Enter and Exit Quiesce Mode.

ISS.0145.0302W	**Unable to suspend {0}. Reason: {1}**
Explanation	While entering quiesce mode, Integration Server could not suspend the specified trigger.
Action	Check the server log for details and manually suspend the trigger.

ISS.0145.0306W	**Unable to resume {0}. Reason: {1}**
Explanation	While entering quiesce mode, Integration Server could not resume the specified trigger, even though the package containing trigger is enabled.
Action	Check the server log for details and manually enable the trigger.

ISS.0145.0315W	**Quiesce timeout limit of {0} minutes has expired. {1} services are running. Proceeding with disabling the packages.**
Explanation	Integration Server is proceeding with disabling packages even though some long-running services are still running. One or more of these services might fail.
Action	In the Integration Server Administrator, check which services are still running and make sure those services have completed before attempting to quiesce this server again. Alternatively, increase the quiesce timeout limit.

ISS.0145.0504E	**Cannot disable packages. Exception: {0}**
Explanation	While entering quiesce mode, Integration Server could not disable packages.
Action	Check the Integration Server server log for details. Then, in the Integration Server Administrator, manually disable the packages.

ISS.0145.0506E	**Package "{0}" is not loaded.**
Explanation	While starting in quiesce mode, Integration Server could not load the WmRoot or WmPublic package.
Action	Start the server in active mode, and then enter quiesce mode.

ISS.0145.0509E	**Unable to restore state of packages. Exception: {0}**
Explanation	While exiting quiesce mode, Integration Server could not restore the state of packages.
Action	Check the Integration Server server log for details. Then, in the Integration Server Administrator, manually enable or disable the packages as necessary.

ISS.0145.0511E	**Cannot enable package "{0}".**
Explanation	While exiting quiesce mode, Integration Server could not enable the specified package.
Action	In the Integration Server Administrator, manually enable the specified package.

ISS.0145.0603E	**Cannot enable listener "{0}" in quiesce mode. Exception: {1}**
Explanation	Integration Server could not start the quiesce listener.
Action	Ensure that the listener is enabled in the listener.cnf configuration file.

ISS.0145.0604E	**Cannot disable listener "{0}" in quiesce mode. Exception: {1}**
Explanation	Integration Server could not stop the quiesce listener.
Action	Ensure that the listener is disabled in the listener.cnf configuration file.

ISS.0145.0700E	**Unable to process scheduled task. Exception: {0}**
Explanation	Integration Server encountered a runtime error of unknown cause while attempting to quiesce a scheduled task.
Action	Check the server log for details and take the appropriate corrective steps.

ISS.0145.0701E	**Unable to retrieve scheduled task "{0}" from database. Exception: {1}**
Explanation	Either the database server is down or Integration Server is no longer connected to the database.
Action	Make sure the connection between Integration Server and the database is active.

ISS.0145.0702E	**Unable to retrieve scheduled task from database. Exception: {0}**
Explanation	Either the database server is down or Integration Server is no longer connected to the database.
Action	Make sure the connection between Integration Server and the database is active.

ISS.0145.0705E	**Unable to resume scheduled task "{0}" in quiesce mode. Exception: {1}**
Explanation	The state of the scheduled task may be inconsistent between the database and Integration Server. This can occur when changes are made to the database outside of Integration Server.
Action	Check the state of the task in the database. In the Integration Server Administrator, change the state of the task to match the state reported in the database.

ISS.0145.0711E	**Unable to retrieve host name. Exception: {0}**
Explanation	The Integration Server you are attempting to quiesce is part of a cluster, and there is an issue with the cluster's configuration.
Action	Verify your clustering environment and cache configuration according to the guidelines in the webMethods Integration Server documentation.

ISS.0145.0803W	**Cannot disable JMS connection alias "{0}". Reason: {1}**
Explanation	While entering quiesce mode, Integration Server could not disable the specified JMS connection alias.
Action	In the Integration Server Administrator, manually disable the JMS connection alias.

ISS.0145.0805W	**Cannot enable JMS connection alias "{0}". Reason: {1}**
Explanation	While exiting quiesce mode, Integration Server could not enable the specified JMS connection alias.
Action	In the Integration Server Administrator, manually enable the JMS connection alias.

ISS.0145.0902E	**Unable to shut down the guaranteed delivery outbound Job Manager. Exception: {0}**
Explanation	While entering quiesce mode, Integration Server could not shut down the outbound Job Manager.
Action	In the Integration Server Administrator, manually disable the guaranteed delivery outbound Job Manager.

ISS.0145.0905E	**Unable to initialize the guaranteed delivery inbound Job Manager. Exception: {0}**
Explanation	While exiting quiesce mode, Integration Server could not initialize the guaranteed delivery inbound Job Manager.
Action	In the Integration Server Administrator, manually enable the guaranteed delivery inbound Job Manager.

ISS.0145.0906E	**Unable to initialize the guaranteed delivery outbound Job Manager. Exception: {0}**
Explanation	While exiting quiesce mode, Integration Server could not initialize the guaranteed delivery outbound Job Manager.
Action	In the Integration Server Administrator, manually enable the guaranteed delivery outbound Job Manager.

ISS.0146.9001E	**Key cannot be empty.**
Explanation	The Key field must not be empty while adding a global variable.
Action	Provide a vaild Key for the global variable.

ISS.0146.9002E	**Value cannot be empty.**
Explanation	The Value field must not be empty while adding a global variable.
Action	Provide a valid value for global variable.

ISS.0146.9003E	**Global variable {0} already exists.**
Explanation	Global variable key must be unique.
Action	Provide a unique key for the global variable.

ISS.0146.9004E	**Global variable {0} does not exist.**
Explanation	You attempted to delete or edit a global variable that does not exist.
Action	Ensure that the global variable exists before attempting to edit or delete it.

ISS.0146.9005	**Global Variable key cannot contain any of these characters:{0}**
Explanation	The global variable key that you specified contains special characters other than period (.) or underscore(_).
Action	Ensure that the global variable key does not contain any special characters other than period or underscore(_).

ISS.0146.9006E	**Global variable key cannot exceed 255 characters.**
Explanation	The global variable key that you specified contains more than 255 characters.
Action	Ensure that length of the global variable key is less than or equal to 255.

ISS.0146.9007E	**Global variable value cannot exceed 255 characters.**
Explanation	The global variable value that you specified contains more than 255 characters.
Action	Ensure that length of the global variable value is less than or equal to 255.

ISS.0146.9008E	**The value of the 'isSecure' field of a global variable cannot be edited.**
Explanation	You attempted to edit the value of the ‘isSecure’ field of a global variable.
Action	Ensure that you do not edit the value of the ‘isSecure’ field of a global variable.

ISS.0147.9001E	**SFTP server alias {0} already exists.**
Explanation	The SFTP server alias name that you specified already exists in Integration Server.
Action	Specify an SFTP server alias name that does not exist in Integration Server.

ISS.0147.9002E	**SFTP server alias {0} does not exist.**
Explanation	The specified SFTP server alias does not exist in Integration Server.
Action	Ensure that the SFTP server alias name you specified is correct and that this SFTP server alias exists in Integration Server.

ISS.0147.9003E	**Cannot retrieve the host key from location {0}. Details: Corrupt or unknown public key file format.**
Explanation	The specified host key file contains the public key of the SFTP server in an unsupported format.
Action	Ensure that the host key file contains the public key in the supported (openssh) format.

ISS.0147.9004E	**Cannot find the private key file {0}.**
Explanation	Integration Server is unable to find the private key file at specified location.
Action	Ensure that the private key file exists at the specified location.

ISS.0147.9005E	**Private key file {0} already exists in Integration Server.**
Explanation	The specified private key file already exists in Integration Server.
Action	Specify a different private key file.

ISS.0147.9006E	**User alias {0} does not exist.**
Explanation	The specified SFTP user alias does not exist in Integration Server.
Action	Ensure that the SFTP user alias name you specified is correct and that this SFTP user alias exists in Integration Server.

ISS.0147.9007E	**User alias {0} already exists.**
Explanation	The SFTP user alias name that you specified already exists in Integration Server.
Action	Specify an SFTP user alias name that does not exist in Integration Server.

ISS.0147.9008E	**Cannot read host key from location {0}.**
Explanation	Integration Server is unable to read the host key file from the location you specified.
Action	Specify a valid host key file location to which Integration Server has the required permission for reading.

ISS.0147.9009E	**Cannot write the public key to file {0}.**
Explanation	Integration Server is unable to write the host key file to the specified location.
Action	Ensure that Integration Server has the required permission and enough disk space to write the host key to the specified location.

ISS.0147.9010E	**Cannot get host key from server {0}. Details: {1}**
Explanation	Integration Server is unable to retrieve the host key from the specified (arg0) SFTP server.
Action	Ensure that the SFTP server is configured and running on the specified host-port.

ISS.0147.9011E	**Test of user alias {0} Fail. Details: {1}**
Explanation	Testing of SFTP user alias (arg0) failed due to error (arg1).
Action	Ensure that the SFTP user alias information is correct and that the SFTP server is running on the specified host and port.

ISS.0147.9012E	**Cannot delete SFTP server alias {0} because the following SFTP user alias(es) are using it : {1}.**
Explanation	Integration Server cannot delete the SFTP server alias (arg0) because the SFTP user alias(es) [arg1] are using it.
Action	Ensure that the SFTP server alias that you want to delete is not included in any SFTP user alias definition.

ISS.0148.9010E	**A valid short value must be specified for "{0}".**
Explanation	The value of short data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid short value.

ISS.0148.9011E	**A valid boolean value must be specified for "{0}".**
Explanation	The value of boolean data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid boolean value.

ISS.0148.9012E	**A valid double value must be specified for "{0}".**
Explanation	The value of double data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid double value.

ISS.0148.9013E	**A valid float value must be specified for "{0}".**
Explanation	The value of float data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid float value.

ISS.0148.9014E	**A valid character value must be specified for "{0}".**
Explanation	The value of character data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid charater value.

ISS.0148.9015E	**A valid byte value must be specified for "{0}".**
Explanation	The value of byte data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid byte value.

ISS.0148.9016E	**A valid long value must be specified for "{0}".**
Explanation	The value of long data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid long value.

ISS.0148.9017E	**{1} is not a valid value for {0}. Allowed values are {2}**
Explanation	The value {1} specified for field {0} while calling a service is not available in the pick list {2}.
Action	Ensure that the value specified for the field {0} is in the pick list {2}.

ISS.0149.0001E	**Message size exceeded the limit of {0} MB.**
Explanation	Enterprise Gateway Server could not process the request because the message associated with the request is larger than the size allowed in the Enterprise Gateway rule.
Action	Either reduce the message size of the request or increase the message size limit in the filter for the rule.

ISS.0149.0002D	**Enterprise Gateway rules processing has started on URL {0} and IP address {1} at time {2}.**
Explanation	Enterprise Gateway Server has started processing rules.
Action	No action is needed.

ISS.0149.0003D	**Processing Enterprise Gateway rule "{0}".**
Explanation	Enterprise Gateway Server has started processing the specified rule.
Action	No action is needed.

ISS.0149.0004D	**Processing Enterprise Gateway rule filter "{0}".**
Explanation	Enterprise Gateway Server has started processing the specified rule filter.
Action	No action is needed.

ISS.0149.0005E **A rule violation occurred for Enterprise Gateway rule "{0}" for filter "{1}": {2}.**

Explanation Enterprise Gateway Server could not process the request because the request met a filter condition defined in the Enterprise Gateway rule.

Action Check the filter conditions for the specified rule and either change the conditions or modify the request so a rule violation does not occur.

ISS.0149.0006E **A rule violation occurred for Enterprise Gateway rule "{0}".**

Explanation Enterprise Gateway Server could not process the request because its type did not match the request type configured in the Enterprise Gateway rule.

Action Modify the request so it matches one of the configured request types.

ISS.0149.0007E **Denial of Service by IP address limit was reached for IP address {0}.**

Explanation Enterprise Gateway Server could not process the request because an Enterprise Gateway Denial of Service limit was reached for this IP address.

Action Delete the IP address from the Enterprise Gateway deny list.

ISS.0149.0008W **IP address {0} is unblocked.**

Explanation Enterprise Gateway Server is again accepting requests from this IP address because the Enterprise Gateway Denial of Service block interval has elapsed.

Action No action is needed.

ISS.0149.0009W **IP address {0} is blocked for a duration of {1} minutes.**

Explanation Enterprise Gateway Server has blocked incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limits.

Action Wait for the IP address to become unblocked when the block interval elapses. If an IP address is blocked too often, reevaluate the "maximum requests" and "maximum requests in progress" limits.

ISS.0149.0011E **Requests from IP address {0} have exceeded the maximum in-progress limit of {1}.**

Explanation Enterprise Gateway Server will deny or block incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limit for in-progress requests.

Action Delete the IP address from the Enterprise Gateway deny list.

ISS.0149.0012D	**Denial of Service clean-up task has executed.**
Explanation	Periodically, Enterprise Gateway Server starts a task to clear old Denial of Service entries from the queue.
Action	No action is needed.

ISS.0149.0013E	**Global Denial of Service limits were reached: {0}.**
Explanation	Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limits.
Action	Wait for the block interval to elapse.

ISS.0149.0014E	**Requests from IP address {0} have exceeded the maximum request limit of {1} in {2} seconds.**
Explanation	Enterprise Gateway Server will deny or block incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limit for requests allowed in a specified time period.
Action	Delete the IP address from the Enterprise Gateway deny list.

ISS.0149.0015S	**Requests from all IP addresses will be blocked for a duration of {0} minutes.**
Explanation	Enterprise Gateway Server will block incoming requests received from all IP addresses for the indicated interval because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limits.
Action	Wait for the block interval to elapse.

ISS.0149.0016E	**OAuth token is not present in the request header.**
Explanation	Enterprise Gateway Server could not process the request because the OAuth token is not present in the request header.
Action	Either disable the OAuth filter or ensure that the request contains the OAuth token.

ISS.0149.0017E	**Maximum in-progress limit of {0} has been exceeded.**
Explanation	Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limit for in-progress requests.
Action	Wait for the block interval to elapse.

ISS.0149.0018E **Maximum requests limit of {0} in {1} seconds has been exceeded.**

Explanation Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limit for requests allowed in a specified time period.

Action Wait for the block interval to elapse.

ISS.0149.0019E **The header "{0}" is not present in the request header.**

Explanation Enterprise Gateway Server could not process the request because the indicated header is not present in the request header.

Action Either disable the mobile application protection filter or ensure that the request has the required mobile device type, application name, and application version request headers.

ISS.0149.0020E **Mobile application version {0} is {1} {2} for application "{3}" and device type "{4}".**

Explanation Enterprise Gateway Server could not process the request because the request matches the indicated mobile application protection filter condition. As a result, the request is in violation of the Enterprise Gateway rule.

Action Reevaluate the mobile application protection filter conditions if desired.

ISS.0149.0501CS **Exception occurred while sending a notification for Enterprise Gateway rule "{0}": {1}.**

Explanation Enterprise Gateway Server could not send an alert notification indicating that a rule violation occurred for the reason indicated in the exception.

Action Check the server error logs and take corrective steps.

ISS.0149.0502CS **Exception occurred while invoking "{0}": {1}.**

Explanation Enterprise Gateway Server could not invoke the flow service to notify users that a rule violation occurred for the reason indicated in the exception.

Action Check the server error logs and take corrective steps.

ISS.0149.0503W **Alert notification for Enterprise Gateway rule "{0}" was not sent. No alert options were found for the rule.**

Explanation Enterprise Gateway Server could not send an alert notification indicating that a rule violation occurred because no alert options were specified for the rule to indicate how to handle the alert.

Action Check the server error logs and take corrective steps.

ISS.0149.0504W **Alert notification for Enterprise Gateway rule "{0}" was not sent. SMTP server configuration is not valid.**

Explanation Enterprise Gateway Server could not send an alert notification for the Enterprise Gateway rule because the server is not configured to send emails.

Action Check the settings on the Settings > Resources screen under Email Notification. If your server is not configured to send emails, use Integration Server Administrator to configure an SMTP port.

ISS.0149.9001E **Enterprise Gateway rule "{0}" already exists.**

Explanation Enterprise Gateway Server could not create the rule because an Enterprise Gateway rule with this name already exists.

Action Specify a unique name for the Enterprise Gateway rule.

ISS.0149.9002E **Enterprise Gateway rule "{0}" was not found**

Explanation Enterprise Gateway Server could not find the specified Enterprise Gateway rule. Either the rule does not exist on this server or the specified rule name is incorrect.

Action Ensure that the Enterprise Gateway rule exists on this Enterprise Gateway Server and that the name specified for the rule is correct.

ISS.0149.9003E **Mobile application protection filter conditions were not specified.**

Explanation Enterprise Gateway Server failed to create or update an Enterprise Gateway rule that has a mobile application protection filter enabled because no filter conditions were specified.

Action Either specify one or more conditions or disable this filter.

ISS.0149.9004E **Mobile application "{0}" was not found.**

Explanation Enterprise Gateway Server did not recognize the application name provided in the mobile application protection filter because the application is not in the Mobile Applications list.

Action Either specify a different mobile application or use the Mobile Application Protection Options screen in Integration Server Administrator to add the application.

ISS.0149.9005E **Mobile device type "{0}" was not found.**

Explanation Enterprise Gateway Server did not recognize the device type provided in the mobile application protection filter because the device is not in the Device Types list.

Action Specify a different device type or use the Mobile Application Protection Options screen in Integration Server Administrator to add the device type.

ISS.0149.9006E	**Condition "{0}" is not supported.**
Explanation	Enterprise Gateway Server failed to apply the condition to this Enterprise Gateway rule because the condition character specified in the mobile application protection filter is not valid.
Action	Ensure that the condition is one of the following characters: =,<,>,<=,>=,<>

ISS.0149.9007E	**Mobile application version "{0}" is not valid.**
Explanation	Enterprise Gateway Server failed to apply the condition to this Enterprise Gateway rule because the application version specified in the mobile application protection filter is not formatted correctly.
Action	Ensure that the application version is in the following format: <major-version>.<minor-version>.<sub-minor-version>.<patch>

ISS.0149.9008E	**Mobile applications list was not updated. The following applications are specified in one or more rules: {0}.**
Explanation	Enterprise Gateway Server failed to remove mobile applications from the application list because the applications are specified in a filter condition for one or more rules.
Action	Before you attempt to remove a mobile application from the list, make sure the application is not specified in a filter condition in any rules.

ISS.0149.9009E	**Device types list was not updated. The following device types are specified in one or more rules: {0}.**
Explanation	Enterprise Gateway Server failed to remove device types from the device types list because the device types are specified in a filter condition for one or more rules.
Action	Before you attempt to remove a device type from the list, make sure the device type is not specified in a filter condition in any rules.

ISS.0149.9010E	**Service name "{0}" is not valid.**
Explanation	A flow service was specified for Enterprise Gateway Server to invoke when an Enterprise Gateway rule violation occurs, but the service name is not valid.
Action	Specify a valid, fully qualified service name.

ISS.0150.9001	**Missing required parameter: "{0}".**
Explanation	A required parameter was not supplied.
Action	Supply the specified required parameter.

ISS.0150.9002	**Unable to create port: "{0}".**
Explanation	Integration Server cannot create the port because an exception occurred.
Action	Use the specified exception to determine why the port could not be created.

ISS.0150.9003	**Unable to set the IP access mode for the port: {0}**
Explanation	An error occurred during an attempt to set the IP access mode for the port.
Action	Use the exception returned by the error message to determine the cause of the error.

ISS.0150.9004	**Unable to set the IP access list for the port: {0}**
Explanation	An error occurred while attempting to set the IP access list for the port.
Action	Use the exception returned by the error message to determine the cause of the error.

ISS.0150.9005	**Unable to set the URL access mode for the port: {0}**
Explanation	An error occurred during an attempt to set the URL access mode for the port.
Action	Use the exception returned by the error message to determine the cause of the error.

ISS.0150.9006	**Unable to set the URL access list for the port: {0}**
Explanation	An error occurred during an attempt to set the URL access list for the port.
Action	Use the exception returned by the error message to determine the cause of the error.

ISS.0150.9008	**The primary port cannot be changed.**
Explanation	An update operation attempted to make changes to the primary port of the Integration Server. The primary port cannot be updated.
Action	To make changes to the port that is assigned to be the primary port, specify another port as the primary port. Then make changes to the port that was previously the primary port.

ISS.0150.9009	**Invalid protocol. The webMethods Platform Manager subsystem does not support the protocol "{0}".**
Explanation	A create or update operation for port settings specified an protocol that is not supported by the webMethods Platform Manager subsystem in Integration Server.
Action	Specify a protocol supported by the webMethods Platform Manager subsystem in Integration Server.

ISS.0150.9010	**Cannot change port protocol [from {0} to {1}].**
Explanation	An update operation attempted to change the protocol for the port. Once a port is created, the protocol cannot be changed.
Action	To change the protocol used with a particular port, first delete the port. Then, recreate the port with the new protocol.

ISS.0150.9011	**Package "{0}" is not loaded or is not enabled.**
Explanation	A create or update port operation attempted to create or change a port in a package that either does not exist or is not enabled.
Action	Make sure the package exists and is enabled before performing the create or update port operation.

ISS.0150.9012	**Unable to disable port: {0}**
Explanation	An exception occurred during an attempt to disable the port
Action	Review the exception to determine why the port could not be disabled.

ISS.0150.9013	**No port found with unique ID {0}.**
Explanation	A read, update, or delete port operation supplied a port ID that does not exist.
Action	Verify the instance ID that the Software AG Platform Manager associates with the port. To do this, refresh the port list on the Software AG Platform Manager.

ISS.0150.9014	**The port was created. However, the access configuration was not set: {0}**
Explanation	A create port operation was partially successful. The port was created and some configuration settings were established. However, establishing some or all of the access configuration settings failed. The port will be disabled if it is not already.
Action	Review the exception to determine why the access configuration could not be set.

ISS.0150.9015	**The port was partially updated. However, the access configuration was not set: {0}**
Explanation	An update port operation was partially successful. Some settings were updated. However, updates to some or all of the access configuration settings failed. The port will be disabled if it is not already.
Action	Review the exception to determine why the access configuration settings could not be updated.

ISS.0150.9020	**The diagnostic port must be associated with the WmRoot package. Package {0} is invalid.**
Explanation	A create or update operation for the diagnostic port attempted to assign a package other than WmRoot to the diagnostic port. This is not allowed. The diagnostic port must be associated with the WmRoot package.
Action	Specify the WmRoot package when creating or updating the diagnostic port.

ISS.0150.9021	**Cannot create diagnostic port. A diagnostic port with port number {0} and ID {1} already exists. Each Integration Server can have one diagnostic port only.**
Explanation	An operation attempted to create a diagnostic port. However, the Integration Server already has a diagnostic port. Each Integration Server can have one diagnostic port only.
Action	To create a new diagnostic port, delete the existing diagnostic port first.

ISS.0150.9022	**Unable to update port. The diagnostic port cannot be changed to a standard port.**
Explanation	An operation attempted to change a diagnostic port to a standard port. A diagnostic port cannot be created in this way because the type of port may not be changed.
Action	To create a standard port on an assigned diagnostic port, first delete the existing diagnostic port and then create a standard port.

ISS.0150.9023	**Unable to update port. The standard port cannot be changed to a diagnostic port.**
Explanation	An operation attempted to change a standard port to a diagnostic port. A diagnostic port cannot be created in this way because the type of port may not be changed.
Action	To create a diagnostic port on an assigned port, first delete the existing port and then create a diagnostic port.

ISS.0150.9024	**Invalid keystore alias {0}**
Explanation	A create or update port operation specified a keystore alias that does not exist.
Action	Make sure to specify the name of an existing keystore alias. Verify that the name of the keystore alias is spelled correctly.

ISS.0150.9025	**Invalid key alias {0}**
Explanation	A create or update port operation specified a key alias that does not exist.
Action	Make sure to specify the name of an existing key alias. Verify that the name of the key alias is spelled correctly

ISS.0150.9026	**Invalid truststore alias {0}**
Explanation	A create or update port operation specified a truststore alias that does not exist.
Action	Make sure to specify the name of an existing truststore alias. Verify that the name of the truststorealias is spelled correctly.

ISS.0150.9027	**Cannot enable port. Keystore alias is empty. Specify a keystore alias for the port or a define a default SSL keystore alias for the Integration Server.**
Explanation	A create or update port operation did not specify a keystore alias and there is not a default SSL keystore alias for the Integration Server. An HTTPS port requires a keystore alias.
Action	Either define a keystore alias or specify a default SSL keystore alias for the Integration Server. The default SSL keystore alias is the keystore alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined keystore alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL keystore alias with the HTTPS port, do not supply keystore alias information for the create or update operations.

ISS.0150.9028	**Cannot enable port. Keystore alias is empty. Specify a key alias for the port or a define a default SSL key alias for the Integration Server.**
Explanation	A create or update port operation did not specify a key alias and there is not a default SSL key alias for the Integration Server. An HTTPS port requires a key alias.
Action	Either define a key alias or specify a default SSL key alias for the Integration Server. The default SSL key alias is the keys alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined key alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL key alias with the HTTPS port, do not supply key alias information for the create or update operations.

ISS.0150.9030	**Unable to assign primary port: "{0}".**
Explanation	An attempt to change the primary port failed because the selected port does not meet the primary port criteria mentioned in the wrapped exception.
Action	Select a port that meets the primary port requirements. Alternatively, change the chosen port to meet the primary port requirements mentioned in the wrapped exception.

ISS.0150.9037E	**Unable to assign quiesce port: "{0}".**
Explanation	An attempt to change the quiesce port failed because the selected port does not meet the quiesce port criteria mentioned in the wrapped exception.
Action	Select a port that meets the quiesce port requirements. Alternatively, change the chosen port to meet the quiesce port requirements mentioned in the wrapped exception.

ISS.0150.9999	**The webMethods Platform Manager subsystem experienced an unexpected error: {0}**
Explanation	An error occurred in the webMethods Platform Manager subsystem that runs in Integration Server.
Action	Contact Software AG Global Support.

ISS.0151.9001	**Missing required parameter: "{0}".**
Explanation	A required parameter is missing.
Action	Contact Software AG Global Support.

ISS.0153.0089C	**Trigger {0} failed because of message decoding exception: {1}. Message has been acknowledged to messaging provider.**
Explanation	The specified trigger could not decode a received document.
Action	Review the provided exception to determine why decoding failed.

ISS.0153.0401EE	**{0} failed to save password for handle {1}. Exception: {2}**
Explanation	Integration Server was unable to save the password in the password store. This can occur if there is an issue with either the messaging.cnf file, which contains details about the connection alias, or the password store.
Action	Take appropriate action to resolve the problem described in the exception.

ISS.0153.0402EE	**{0} failed to retrieve password for handle {1}. Exception: {2}**
Explanation	Integration Server was unable to retrieve the password from the password store. This can occur if there is an issue with either the messaging.cnf file, which contains details about the connection alias, or the password store.
Action	Take appropriate action to resolve the problem described in the exception.

ISS.0153.0404WW	**Client authentication type for Universal Messaging connection alias {0} is not valid. Therefore, no authentication will be performed for this connection. Supported types: basic, none.**
Explanation	The client authentication type provided for the specified Universal Messaging connection alias is not valid. As a result, Universal Messaging will use the default authentication type (“none”) and no authentication will be performed.
Action	Supply a valid authentication type (“none” or “basic”).

ISS.0155.0003E	**Unable to perform hot deployment of packages. Hot deployment timeout limit has expired while waiting for in-flight tasks to complete.**
Explanation	Hot deployment of packages can happen only if the in-flight tasks are complete within the specified hot deployment timeout period.
Action	Increase the hot deployment timeout limit in the Settings > Hot Deployment page of the Integration Server Administrator. Alternatively, ensure that Integration Server is handling less load or requests.

ISS.0155.0005E	**Hot deployment of the system package {0} is not supported.**
Explanation	You attempted to hot deploy a system package. Hot deployment can be performed only for custom packages.
Action	Ensure that the packages that you are attempting to hot deploy are not system packages.

ISS.0155.0008E	**Invalid input. Provide a valid positive integer as the hot deployment timeout value.**
Explanation	The hot deployment timeout value must be a positive integer.
Action	Provide a valid positive integer as the hot deployment timeout value.

ISS.0155.0010E	**Cannot cancel the hot deployment operation. The installation of package has already started.**
Explanation	You attempted to cancel the hot deployment operation after the installation of the package started. You can cancel the hot deployment operation only before the package installation starts.
Action	If you attempted to cancel the hot deployment because of the delay in the completion of in-flight tasks, this message indicates that the in-flight processes are now complete and Integration Server has started the hot deployment operation. No action required. If the hot deployment operation is canceled because the new version of the package has issues, perform hot deployment of the previous version of the package from the salvage directory or perform hot deployment of a newer version of the package after correcting the issues.

ISS.0157.0001E **Package "{0}" is not loaded**

Explanation The specified package exists on Integration Server but is not enabled.

Action Make sure the specified package is enabled. Then, re-execute the pub.assets:getChecksums service. Note that the service gets checksums only for assets that are loaded. If the specified package is partially loaded, the service gets checksums for the loaded assets only.

ISS.0157.0002E **Package "{0}" does not exist**

Explanation The specified package does not exist on Integration Server .

Action Make sure the specified package exists and is loaded. Then, re-execute the pub.assets:getChecksums service.

ISS.0157.0003E **A value must be specified for either 'packages' or 'assets'**

Explanation A value was not specified for either the packages or assets input parameters. The pub.assets:getChecksums service requires a value for either packages or assets.

Action Specify a value for the packages input parameter or the assets input parameter. Then, re-execute the pub.assets:getChecksums service.

ISS.134.9215E **Connection Count must be a positive integer, and it must not exceed {0}.**

Explanation The value of the Maximum execution threads property is less than the value of the Connection count property. The Maximum execution threads value must be greater than or equal to the Connection count value.

Action Change the value of the Maximum execution threads property to be greater than or equal to the Connection count property. Alternatively, change the value of the Connection count property to be less than or equal to the Maximum execution threads property.

ISS.134.9216E **The Multiple Connection feature is not supported when using non-durable Topics.**

Explanation Only JMS triggers that subscribe to queues and/or topics (durable subscribers) can use multiple connections to receive messages from the JMS provider. A JMS trigger that subscribes to a topic that is a non-durable subscriber cannot use multiple connections to receive messages from the JMS provider. That is, only a JMS trigger that subscribes to queues and/or topics that are durable subscribers can have a connection count greater than 1.

Action Set Connection count to 1. Alternatively, remove any topics that are non-durable subscribers from the list of destinations to which the JMS trigger subscribes.

ISS.141.9102E	**No transport info in MessageContext**
Explanation	An internal error occurred while processing the Web service request.
Action	Contact Software AG Global Support.

ISS.141.9103E	**No MessageFormatter in MessageContext**
Explanation	An internal error has occurred while processing the Web service request.
Action	Contact Software AG Global Support.

ISS.141.9209E	**Could not deploy the Web service descriptor {0} as policy with id {1} is not found.**
Explanation	Integration Server was unable to execute the Web service connector because the WS-Policy attached to the Web service connector is either missing or invalid. Valid policies should be in the policy repository, that is, saved in the following directory: (webMethods_directory)/IntegrationServer/config/wss
Action	If you want to secure the Web service with the policy, locate the WS-Policy and add it to the policy repository. You can check the policy repository's invalid subdirectory to see whether the policy was moved because it is invalid. If the policy is in the invalid directory, correct it to make it valid, and move it back into the main policy repository directory. If the WS-Policy does not exist, detach the WS-Policy from the Web service descriptor. If you still need to secure the Web service, create a WS-Policy that provides the security you want, add it to the policy repository, and attach it to the Web service descriptor.

ISS.150.9036E	**Port Alias cannot be edited.**
Explanation	Once a port is created, the port alias cannot be changed.
Action	None. However, if you want an existing port to use a different port alias, you must delete the port and then recreate it using the new port alias.

ISS.153.9302E	**Protocol buffer coder cannot find descriptor in document type: {0}**
Explanation	An error occurred while encoding or decoding an instance of the specified publishable document type. Integration Server cannot find the message descriptor for the publishable document type. Integration Server creates a message descriptor for a publishable document type with an encoding type set to protocol buffers.
Action	Make sure the publishable document type is synchronized with the messaging provider.

ISS.156.10E	**Failed to unsubscribe because subscription does not exist for unique key "{0}".**
Explanation	Subscription not found for the unique key \"{0}\".
ISS.156.11E	**Provided options "{0}" are not valid.**
Action	Provide valid options.
ISS.156.13E	**Unable to invoke service "{0}" because of the exception: "{1}" .**
Explanation	The exception message describes the cause.
Action	Check the exception message and take appropriate action.
ISS.156.14E	**An error occured because the service name is not provided when the isAsync flag is set to true.**
Explanation	An error occurs when service name is not provided and the isAsync flag is set to true.
Action	Provide a service name when isAsync flag is set to true.
ISS.156.15E	**An error occured because the user "{0}" is invalid or does not have the ACL permission to execute the service: "{1}".**
Explanation	You have entered an invalid username or the user does not have necessary permissions to invoke the callback service.
Action	Enter a valid user name and check if the user has the necessary permissions to invoke the callback sevice.
ISS.156.16E	**An error occured because the service name is provided and the isAsync flag is set to false.**
Explanation	An error occurs when service name is provided and the isAsync flag is set to false.
Action	Do not provide a service name when isAsync is set to false.
ISS.156.6E	**Could not unsubscribe the subscription. The exception message is: "{0}".**
Explanation	The exception message describes the cause.
Action	Check the exception message and take appropriate action.

ISS.156.7E	**Event routing service is unavailable.**
Explanation	An error occurred when initializing event routing service.
ISS.156.8E	**Invalid Callback Service "{0}". Service should be invokable and should have reference to "{1}" document type as the only input.**
Explanation	Callback service cannot be invoked and does not have reference to \"{1}\" document type.
Action	Ensure that the callback service can be invoked and has reference to \"{1}\" document type as the only input.
ISS.156.9E	**Subscription failed because subscription already exists for unique key "{0}"**
ISS.88.9435E	**The specified document type {0} does not exist.**
Explanation	The document type that you supplied as input to the service does not exist.
Action	Check the name of the document type that you are attempting to use to ensure you have the correct name. Then, specify a document type name that exists and re-invoke the service.
ISS.88.9436E	**The structure of the document instance does not match the specified document type, {0}; validation failed.**
Explanation	The service validates a document instance using the IS document type you supplied. However, the document instance does not have the structure specified by the IS document type. Validation of the document instance failed.
Action	Check the IS document type you are attempting to use to ensure you specifying the correct one. Then, re-invoke the service specifying the correct IS document type for the document instance.
ISS.88.9437E	**Unexpected exception occurred: {0}**
Explanation	The Web services stack, which is Integration Server code that performs Web service functionality, encountered an unexpected error.
Action	Read through the contents of the messages, and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.88.9438E **Unexpected exception occurred while creating a fault message.**

Explanation Integration Server encountered an unexpected error. It was attempting to add a child fault element to a non-existing parent fault element.

Action Contact Software AG Global Support.

ISS.88.9439E **The query for the fault element failed because its corresponding parent element is absent from the SOAP message.**

Explanation You attempted to query a SOAP message for SOAPFault elements. However, there is no parent element in the SOAP message for the queried item. For example, Integration Server will issue this error if you attempt to query for a fault code when there is no SOAPFault in the SOAP message.

Action Ensure the SOAP message that you are attempting to process is valid. If the SOAP message is valid, contact Software AG Global Support.

ISS.88.9440E **The structure of the SOAP fault detail Document is not valid, resulting in the invalid attribute name: {0}; validation failed.**

Explanation A document representing the SOAP fault detail was passed to a service that handles SOAP faults, for example, the pub.soap.handler:addFaultBlock. The fault detail Document that was passed to the service has an invalid structure. An example of an invalid structure would be if the name in the Document instance that corresponds to an attribute is "@ns1:", but there is no local name for the attribute. In this example, there should have been additional text after the ":" that corresponds to a valid local name.

Action Ensure that IS document instance for the SOAP fault detail is a proper representation of valid XML structure. Correct the SOAP fault detail Document and execute the service again.

ISS.88.9441E **Validation requested, but no IS document type specified; validation failed.**

Explanation You specified that you want an input Document to be validated. However, you have not provided the document type that the service should use for validation. As a result, the validation failed.

Action Invoke the service again. This time pass the document type to use for validation in the appropriate input parameter.

ISS.88.9442E **Service executed with invalid input parameter {0} : {1}**

Explanation Execution of the service failed because the specified input parameter was passed an invalid value. The invalid value is displayed in the message.

Action Invoke the service again, this time specifying a valid value for the input parameter.

IS_RUNTIME_EXCEPTION – runtime exception occured. see error log for details.

JBS.0122.0006 **Package ''{0}'' has deploy directory contents, but does not have a dependency on 'WmJBoss'**

JNDI_CONTEXT_NOT_INITIALIZED – Cannot perform JNDI operation: JNDI context is not initialized.

JSONCODER_INVALID_DECODE_FOR_REAL – Both decodeRealAsString and decodeRealAsDouble cannot be set to true.

JSONCODER_UNSUPPORTED_TOKEN – Invalid state. Unsupported token found in the JSON input stream.

Explanation The input stream does not contain valid JSON content.

Action Provide valid JSON content in the input stream.

JSON_INVALID_INPUTS_REAL_AS_STRING_AND_DOUBLE – Both decodeRealAsString and decodeRealAsDouble cannot be set to true.

JSON_INVALID_INPUT_REAL_AS_STRING – Field decodeRealAsString if set , can only be true or false.

JournalLogger.FAC_SCHED+"."+DATABASE_VERSION_CHECK_FAILED – Check of internal database failed: the current version {0} should be at least {1}

LDAP_URL_INVALID_CHAR – Directory url contain invalid charactors. {0}

LVLCHNG_COMP_CODE_INVALID – Supplied "componentCode" is not valid.

LVLCHNG_COMP_CODE_NULL – Parameter "componentCode" is required and it cannot be null.

LVLCHNG_LISTENER_NULL – Parameter "listener" is required and it cannot be null.

NESTED_TRANS_NOT_SUPPORTED – another tran active. nested tran disabled in settings

NODE_NS_NAME_EXISTS – node_nsName already exists

NODE_NS_NAME_IS_INVALID – node_nsName "{0}" is invalid

NODE_NS_NAME_IS_REQUIRED – node_nsName is required

NODE_PKG_IS_INVALID – node_pkg "{0}" is invalid

NODE_PKG_IS_REQUIRED – node_pkg is required

NODE_TYPE_IS_INVALID – Node "{0}" is not of type 'webMethods/WebSocket'

NOT_NSWEBSOCKETENDPOINTCLIENT_TYPE – Provided NSWebSocketEndpointDescriptor is not of type Client

NOT_NSWEBSOCKETENDPOINTDESC_TYPE – Provided NSName "{0}" is not a type of NSWebSocketEndpointDescriptor. Please provide the NSWebSocketEndpointDescriptor' NSName

NOT_NS_WEBSOCKET_ENDPOINT_CLIENT_TYPE – Provided NSWebSocketEndpoint is not of type Client

NOT_NS_WEBSOCKET_ENDPOINT_TYPE – Provided NSName "{0}" is not a type of NSWebSocketEndpoint. Please provide the NSWebSocketEndpoint' NSName

NO_LOADERS_FOUND Loader is not configured for the cache {1} contained within the cache manager {0}.

NO_MORE_EVENTS_AVAILABLE – No more xml events avaiable

NO_OUTPUT_SIGNATURE – no output signature

NO_TRANS_FOR_THREAD – current thread not with any transaction

NO_WRITERS_FOUND Writer is not configured for the cache {1} contained within the cache manager {0}.

OAUTH_ONE_PREVENTS_OTHERE – {0} may not be specified if {1} is "{2}".

Explanation The service failed because the specified input variable contains an invalid value combination. The invalid combination is listed in the message text.

Action Enter a valid value combination for the input variable.

ON_BINARY_IS_INVALID – onBinary "{0}" is invalid

ON_CLOSE_IS_INVALID – onClose "{0}" is invalid

ON_CONNECT_IS_INVALID – onConnect "{0}" is invalid

ON_ERROR_IS_INVALID – onError "{0}" is invalid

ON_TEXT_IS_INVALID onText "{0}" is invalid

OPERATION_NOT_SUPPORTED_WITH_DES_ALIAS – {0} operation is not supported when connection alias type is DES.

OTHER_THAN_SPACE_CHARACTERS_ENCOUNTERED – Other than space characters encountered

PACKAGE_HOTDEPLOY_ACTIVATION_FAILED_ON_RECOVERYE – Package recovered but not activated.

Explanation Hot deployment of the specified package failed. Integration Server recovered the package from the salvage directory, but was unable to activate the package.

Action Check the logs for hot deployment failure messages or contact Software AG Global Support.

PACKAGE_HOTDEPLOY_AUTORECOVER_ERRORE – Package cannot be recovered, check server logs for details.

Explanation Hot deployment of the specified package failed.

Action Check the logs for hot deployment failure messages or contact Software AG Global Support.

PACKAGE_HOTDEPLOY_AUTORECOVER_FAILEDE – Error during hot deployment of package {0}. Package cannot be recovered.

Explanation Hot deployment of the specified package failed. Integration Server attempted to recover the package from the salvage directory but was unable to do so.

Action Check the logs for hot deployment failure messages or contact Software AG Global Support.

PACKAGE_HOTDEPLOY_AUTORECOVER_SUCCESSI – Package recovered and activated.

PACKAGE_HOTDEPLOY_IN_PROGRESSE – Cannot hot deploy package {0}. Hot deployment of package {1} is already in progress.

Explanation You attempted to hot deploy multiple packages in parallel. Integration Server does not support parallel hot deployment of packages.

Action Integration Server does not support parallel hot deployment of packages. Ensure that you perform hot deployment of packages sequentially.

PACKAGE_HOTDEPLOY_TIMEOUTE – Cannot hot deploy package {0} due to error: {1}

Explanation Hot deployment of the package failed due to the listed error.

Action Review the error details provided in the message to determine the cause of the failure and take appropriate action, and then retry hot deploying the packages.

PARSER_MUST_BE_ON_START_ELEMENT_TO_READ_NEXT_TEXT – parser must be on START_ELEMENT to read next text

PASSWORDBADOLDPASSWORDE – Invalid user name or password.

Explanation The specified user credentials are not valid.

Action Provide a valid user name and password.

PASSWORD_EMPTY Password is empty. User(s) {0} not added.

Explanation The Password field requires a value.

Action Enter a valid password.

PASSWORD_EXPIRED Password expired.

PASSWORD_UPDT_EMPTY – Password is empty. Password was not changed.

Explanation The Password field requires a value.

Action Enter a valid password.

PDT_OUT_OF_SYNC Document type "{0}" is out of sync with Provider

PIECMNE0000 Error initializing ISAttributeValues. ISMonitoringContext cannot be null.

Explanation The ISAttributeValues cannot be initialized because ISMonitoringContext is null.

Action This is an internal error. Contact Software AG Global Support.

PIECMNE0001 Error retrieving AttributeValue. The metaModelTypeID cannot be null or empty.

Explanation The AttributeValue cannot be retrieved because metaModelTypeID is null or empty.

Action This is an internal error. Contact Software AG Global Support.

PIECMNE0002 Error retrieving AttributeValue. The attributeID cannot be null or empty.

Explanation The AttributeValue cannot be retrieved because metaModelTypeInstanceID is null or empty.

Action This is an internal error. Contact Software AG Global Support.

PIECMNE0003 Error retrieving AttributeValue. The attributeID cannot be null or empty.

Explanation The AttributeValue cannot be retrieved because attributeID is null or empty.

Action This is an internal error. Contact Software AG Global Support.

PIECMNE0004 Error retrieving attribute values. The attributeQuery object cannot be null.

Explanation The attribute values cannot be retrieved because the attributeQuery object is null.

Action This is an internal error. Contact Software AG Global Support.

PIECMNE0005	**Error retrieving attribute values. The modelType is invalid.**
Explanation	The attribute values cannot be retrieved because the modelType is invalid.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0006	**Error while destroying ISMonitoringContext. The ISMonitoringContext cannot be null.**
Explanation	The ISMonitoringContext could not be destroyed because it is null.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0007	**Error destroying ISMonitoringContext. Invalid ISMonitoringContext provided.**
Explanation	The ISMonitoringContext could not be destroyed because it is not a valid instance of ISMonitoringContext.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0008	**Error getting meta model. The metaModelTypeId cannot be null.**
Explanation	The meta model could not be retrieved because the metaModelTypeID is null or empty.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0009	**Error validating ISMonitoringContext. ISMonitoringContext cannot be null.**
Explanation	The ISMonitoringContext could not be validated because it is null.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0010	**Error validating ISMonitoring Context. Invalid ISMonitoringContext provided.**
Explanation	The ISMonitoringContext could not be validated because it is not an instance of MonitoringContext.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0011	**Error validating ISMonitoringContext. ISInputContext object is null.**
Explanation	The ISMonitoringContext cannot be validated because the supplied ISInputContext object is null.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0012	**Error validating ISMonitoringContext. ISInputContext is invalid.**
Explanation	The ISMonitoringContext cannot be validated because the supplied ISInputContext object is invalid.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0013	**Error validating ISMonitoringContext. Context host attribute cannot be null or empty.**
Explanation	The ISMonitoringContext cannot be validated because the context has a host attribute that is null or empty.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0014	**Error validating ISMonitoringContext. Context port attribute is invalid.**
Explanation	The ISMonitoringContext cannot be validated because the context has an invalid port attribute.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0015	**Error initializing ISModelInstance. ISMonitoringContext is null.**
Explanation	An ISModelInstance cannot be initialized because the ISMonitoringContext is null.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0016	**Error getting model instances. The metaModelTypeName is null or empty.**
Explanation	The model instances cannot be retrieved because a metaModelTypeName is null or empty.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0017	**Error getting model instances. Invalid metaModelTypeName.**
Explanation	The model instances cannot be retrieved because a valid metaModelTypeName was not supplied.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0018	**Error while initializing ISServerModel. ISMonitoringContext is null.**
Explanation	The ISServerModel cannot be initialized because ISMonitoringContext is null.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0019	**Error getting attributes for Integration Server. The modelInstanceListToQuery cannot be null.**
Explanation	Integration Server attributes cannot be retrieved because the modelInstanceListToQuery was null .
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0020	**Error getting Integration Server attributes. The attributeListToQuery cannot be null.**
Explanation	The Integration Server attributes cannot be retrieved because the attributeListToQuery was null.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0021	**Error getting attributeID. The attributeID cannot be null.**
Explanation	The Integration Server attribute cannot be retrieved because the attributeID was null.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0022	**Error while pinging Integration Server. Invalid ISMonitoringContext.**
Explanation	The ping of Integration Server failed because the provided ISMonitoringContext is invalid.
Action	This is an internal error. Contact Software AG Global Support.

PIESIME0000	**Unable to access Integration Server:{0}**
Explanation	An error occurred while attempting to access Integration Server. The details of the error will replace the {0} in the message text.
Action	Use the details of the error to resolve the error preventing a connection to Integration Server.

PIESIME0001	**Integration Server is unavailable:{0}**
Explanation	An error occurred while attempting to access Integration Server. The details of the error will replace the {0} in the message text.
Action	Use the provided error information to correct the issue and try again.

PIESIME0002	**An error occurred while invoking a service on Integration Server:{0}**
Explanation	An error occurred while invoking a service on Integration Server. The details of the error will replace the {0} in the message text.
Action	Use the supplied error information to correct the condition causing the error. Then, reissue the service request.

PIESIME0004	**Port object cannot be null.**
Explanation	ISContext cannot be created because the Port object is null.
Action	Provide a valid Port object that is not null.

PIESIME0005	**UserCredentials username/password cannot be null.**
Explanation	ISContext cannot be created because the username/password is null.
Action	Make sure that the username/password has a valid value and is not null.

PIESIME0006	**Missing required ClientAuthType for SSL.**
Explanation	ISContext cannot be created because the ClientAuthType required for SSL is null.
Action	Make sure the ClientAuthType has a valid value and is not null.

PIESIME0007	**Invalid protocol. The webMethods Platform Manager subsystem does not support the protocol "{0}".**
Explanation	A create or update operation for port settings specified a protocol that is not supported by the webMethods Platform Manager subsystem in Integration Server.
Action	Specify a protocol supported by the webMethods Platform Manager subsystem in Integration Server.

PIESIME0008	**Unable to connect Integration Server:{0}**
Explanation	An error occurred while attempting to connect Integration Server. The details of the error will replace the {0} in the message text.
Action	Use the error details to resolve the error that is preventing a connection to Integration Server.

PIESIME0009E	**Port Validation Error :{0}**
Explanation	The port configuration is not valid.
Action	Make sure the port configuration is valid.

PIESIME0010	**Port Validation Error, Invalid URLAccess Service :{0}**
Explanation	The port is not valid because the supplied URLAccess does not have a valid service name.
Action	Specify a valid service name for URLAccess.

PIESIME0011	**Port Validation Error, Invalid IPAccess Hostname :{0}**
Explanation	The port is not valid because the IPAccess Hostname is not valid.
Action	Specify a valid value for the IPAccess Hostname.

PIESIME0012	**Port Validation Error, Port Alias already exists : {0}**
Explanation	The port is not valid because the port alias is used by another port on Integration Server.
Action	Specify a port alias that is unique for the Integration Server.

PIESIME0013	**Port Validation Error, Primary port may not be disabled in an update.**
Explanation	A primary port cannot be disabled as part of an update.
Action	Do not attempt to disable the primary port as part of updating a port. If you want to disable the port acting as the primary port, you must first designate another port as the primary port. Then you can disable the port that was previously the primary port.

PIESIME0014	**Port Validation Error, Primary port package name must be WmRoot. Invalid Package Name : {0}**
Explanation	The primary port must be associated with the WmRoot package.
Action	Make sure the primary port is associated with the WmRoot package.

PIESIME0015	**Invalid server configuration parameter names: {0}**
Explanation	The server configuration parameter names must begin with “watt.”
Action	Rename the server configuration parameter names so that they begin with “watt.”

PIESIME0016	**A required configuration parameter is missing: {0}**
Explanation	A required configuration parameter is missing.
Action	Check the logs.

PIESIME0017	**Configuration details for COMMON-JDBC cannot be null.**
Explanation	While creating a JDBC pool alias, the configuration details for COMMON-JDBC cannot be null.
Action	Provide valid JDBC pool alias configuration details.

PIESIME0018	**JDBC pool alias cannot be null or empty.**
Explanation	While creating or updating a JDBC pool, the pool alias cannot be null or empty.
Action	Provide a valid value for the JDBC pool alias.

PIESIME0019	**Invalid configuration type.**
Explanation	The configuration type provided while creating the JDBC pool alias must be of type COMMON-JDBC.
Action	Provide a valid configuration of type COMMON-JDBC.

PIESIME0020	**Invalid configuration type.**
Explanation	The configuration type provided while updating the JDBC pool alias must be of type COMMON-JDBC.
Action	Provide a valid configuration of type COMMON-JDBC.

PIESIME0021	**JDBC pool cannot be null.**
Explanation	While creating a JDBC pool alias,the pool configuration details cannot be null.
Action	Provide valid configuration details while creating or updating a JDBC pool.

PIESIME0022	**{0} cannot be null or empty.**
Explanation	The specified value must not be null or empty
Action	Provide a valid value.

PIESIME0023	**Enter a positive number for {0}**
Explanation	The specified value must not be a negative number.
Action	Specify a positive number.

PIESIME0024 **JDBC configuration instance id is missing.**

Explanation JDBC configuration instance id is required and must be specified.

Action Provide a valid JDBC configuration instance id.

PIESIME0025 **MaxSize must be greater than 0.**

Explanation The value provided for MaxSize must be greater than 0.

Action Ensure that the value provided for MaxSize is greater than 0.

PIESIME0026 **Configuration details for COMMON-JDBC cannot be null.**

Explanation While updating a JDBC pool alias, the configuration details for COMMON-JDBC cannot be null.

Action Provide valid JDBC pool alias configuration details.

PIESIME0027 **JDBC pool cannot be null.**

Explanation While updating a JDBC pool alias,the pool configuration details cannot be null.

Action Provide valid configuration details while creating or updating a JDBC pool.

PIESIME0028 **MinSize must be less than or equal to MaxSize.**

Explanation Minimum connections must be less than or equal to maximum connections.

Action Ensure that the value provided for MinSize is less than or equal to MaxSize.

PIESIME0029 **Invalid SMTP port.**

Explanation SMTP port should be greater than 0.

Action Change the SMTP port to a valid value greater than 0.

PIESIME0030 **Unable to retrieve truststores.**

Explanation Integration server is unable to retrieve the truststores.

Action Ensure that there are truststores installed in Integration server.

PIESIME0031 **SMTP settings are already defined.**

Explanation Unable to define new SMTP settings because the SMTP settings are already defined.

Action To specify new SMTP settings, update the existing SMTP configuration.

PIESIME0032	**The truststore {0} does not exist.**
Explanation	The specified truststore alias cannot be found.
Action	Ensure that the specified truststore exists in Integration Server.

PIESIME0033	**Configuration details for COMMON-DBFUNCTION cannot be null.**
Explanation	While updating a functional alias, the configuration details for COMMON-DBFUNCTION cannot be null.
Action	Provide valid functional alias configuration details.

PIESIME0034	**Invalid configuration type.**
Explanation	The configuration type provided while updating the functional alias must be of type COMMON-DBFUNCTION.
Action	Provide a valid configuration of type COMMON-DBFUNCTION.

PIESIME0035	**Functional alias cannot be null**
Explanation	While updating a functional alias,the functional alias configuration details cannot be null.
Action	Provide valid configuration details while updating a functional alias.

PIESIME0037	**Configuration details for COMMON-JNDI cannot be null.**
Explanation	While configuring a JNDI provider alias, the configuration details for COMMON-JNDI cannot be null.
Action	Provide valid JNDI provider alias configuration details.

PIESIME0038	**Invalid configuration type.**
Explanation	The configuration type provided while configuring a JNDI provider alias must be of type COMMON-JNDI.
Action	Provide a valid configuration of type COMMON-JNDI.

PIESIME0039	**SMTP server not configured.**
Explanation	SMTP server is not configured in Integration Server.
Action	Configure SMTP server in Integration Server.

PIESIME0040	**Functional alias specified is not valid.**
Explanation	The functional alias specified in the input must be valid.
Action	Ensure that the functional alias specified in the input is valid.

PIESIME0041	**Functional alias description cannot be modified.**
Explanation	The functional alias description specified in the input cannot be modified.
Action	Ensure that the functional alias description specified in the input is not modified.

PIESIME0042	**The functional alias {0} cannot be associated with the embedded database pool.**
Explanation	The embedded database pool can only be used with IS Internal and Cross Reference database components.
Action	Associate the functional alias with any JDBC connection pool other than the embedded database pool.

PIESIME0043	**Invalid configuration details for COMMON-JMS. Invalid value for {0}.**
Explanation	The value specified for COMMON-JMS configuration {0} is not valid.
Action	Specify valid values for all the mandatory attributes in COMMON-JMS configuration.

PIESIME0045	**Configuration details for COMMON-JMS cannot be null.**
Explanation	The configuration details for COMMON-JMS cannot be null.
Action	Provide valid JMS configuration details.

PIESIME0046	**Invalid configuration provided while updating the COMMON-JMS configuration.**
Explanation	The JMS alias configuration provided while updating the COMMON-JMS configuration does not match the existing JMS alias configuration.
Action	Provide a valid JMS configuration that matches the JMS configuration to be updated.

PIESIME0047	**An error occurred while invoking a service in Integration Server : {0}**
Explanation	An error occurred while invoking a service in Integration Server. Error {0} occurred.
Action	Use the supplied error information to correct the condition causing the error. Then, reissue the service request.

PIESIME0048	**JMS alias {0} should be disabled before {1} operation.**
Explanation	The JMS alias {0} should be disabled before performing the {1} operation.
Action	Ensure that the JMS alias is disabled.

PIESIME0049	**Messaging connection alias {0} should be disabled before {1} operation.**
Explanation	The messaging connection alias {0} should be disabled before performing the {1} operation.
Action	Ensure that the messaging connection alias is disabled.

PIESIME0050	**Messaging connection alias description cannot be null or empty.**
Explanation	While creating a messaging connection alias, the description field cannot be null or empty.
Action	Provide a valid description for messaging connection alias.

PIESIME0051	**Messaging connection alias name cannot be updated.**
Explanation	You attempted to update the messaging connection alias. Messaging connection alias name is not editable.
Action	To change the name of a messaging connection alias, delete the existing messaging connection alias and create a new alias.

PIESIME0052	**Default messaging connection alias cannot be deleted.**
Explanation	The messaging connection alias that you attempted to delete is the default messaging connection alias, which cannot be deleted.
Action	To delete a default messaging connection alias, configure another messaging connection alias as the default.

PIESIME0053	**Cannot create a new messaging connection alias for Broker.**
Explanation	Only one messaging connection aliases for Broker can exist at a time in Integration Server.
Action	Delete the existing messaging connection aliases for Broker before creating a new messaging connection aliases for Broker.

PIESIME0057 **Logger name for COMMON-LOGGERS configuration type is invalid.**

Explanation Valid values of logger name for COMMON-LOGGERS configuration type are {0}.

Action Ensure that you specify a valid logger name when updating the COMMON-LOGGERS configuration type.

PIESIME0058 **Server logger cannot be disabled.**

Explanation You attempted to disable the server logger. Server logger cannot be disabled.

Action Ensure that the server logger is enabled.

PIESIME0059 **Destination for server log entries must be a file.**

Explanation The destination for server log entries can only be a file.

Action Ensure that you specify a file as the destination for server log entries.

PIESIME0060 **Mode for writing server log entries must be synchronous.**

Explanation The server logger writes log entries synchronously to the specified destination file. Therefore, the mode for writing server log entries must be specified as synchronous.

Action Ensure that the mode for writing server log entries is specified as synchronous.

PIESIME0062 **The destination for writing Integration Server log entries must be database or file.**

Explanation Integration Server logger writes log entries to database or file only. You attempted to specify a destination other than database or file.

Action Ensure that you specify database or file as the destination for writing Integration Server log entries.

PIESIME0063 **Configuration details for COMMON-VARS cannot be null.**

Explanation While creating a global variable, the configuration details for COMMON-VARS cannot be null.

Action Provide valid global variable configuration details.

PIESIME0064 **Invalid configuration type.**

Explanation The configuration type provided while creating the global variable must be of type COMMON-VARS.

Action Provide a valid configuration of type COMMON-VARS.

PIESIME0065	**Global variable validation error: Variable Setting cannot be empty.**
Explanation	The global variable configuration is not valid.
Action	Make sure that Variable Setting is not empty and that the global variable configuration is valid.

PIESIME0066	**Global variable validation error: Integration Server accepts only Strings as global variable values.**
Explanation	The global variable value specified is not of type String.
Action	Provide a valid value of type String for the global variable.

PIESIME0067	**Global variable validation error: Global variable value cannot be empty.**
Explanation	The global variable value must not be empty.
Action	Provide a valid value for the global variable.

PIESIME0068	**Global variable validation error: Global variable value cannot exceed 255 characters.**
Explanation	The global variable value that you specified contains more than 255 characters.
Action	Ensure that length of the global variable value is less than or equal to 255.

PIESIME0069	**Global variable validation error: Global variable key cannot be empty.**
Explanation	The global variable key must not be empty.
Action	Provide a valid key for the global variable.

PIESIME0070	**Global variable validation error: Global variable key cannot exceed 255 characters.**
Explanation	The global variable key that you specified contains more than 255 characters.
Action	Ensure that length of the global variable key is less than or equal to 255.

PIESIME0071	**Global variable validation error: Global variable key contains special characters other than "." and "_".**
Explanation	The global variable key that you specified contains special characters other than period (.) or underscore(_).
Action	Ensure that the global variable key does not contain any special characters other than period or underscore(_).

PIESIME0072	**Invalid value for ServiceLogLevel in Service Logger.**
Explanation	The value specified for ServiceLogLevel in Service Logger is not valid. Valid values for ServiceLogLevel are perSvc, brief, and verbose.
Action	Ensure that you specify a valid value for ServiceLogLevel in Service Logger.

PIESIME0073	**Invalid value for GenerateAuditingDataOnStartup in Security Logger.**
Explanation	The value specified for GenerateAuditingDataOnStartup in Security Logger is not valid. The GenerateAuditingDataOnStartup value must be a valid Boolean value (true/false).
Action	Ensure that you specify a valid value for GenerateAuditingDataOnStartup in Security Logger.

PIESIME0074	**Invalid value for GenerateAuditingDataOnEvent in Security Logger.**
Explanation	The value specified for GenerateAuditingDataOnEvent in Security Logger is not valid. Valid values for GenerateAuditingDataOnEvent are Success or Failure, Success, and Failure.
Action	Ensure that you specify a valid value for GenerateAuditingDataOnEvent in Security Logger.

PIESIME0075	**Invalid value for SecurityAreasToAudit in Security Logger.**
Explanation	The value specified for SecurityAreasToAudit in Security Logger is not valid. Valid values for SecurityAreasToAudit are {0}.
Action	Ensure that you specify a valid value for SecurityAreasToAudit in Security Logger.

PIESIME0076	**Unable to disable messaging connection alias.**
Explanation	An operation to disable messaging connection alias failed.
Action	Check the Integration Server logs for more information.

PIESIME0077	**Configuration details for COMMON-CLUSTER cannot be null.**
Explanation	When updating cluster settings, the configuration details for COMMON-CLUSTER cannot be null.
Action	Provide valid cluster configuration details.

PIESIME0078	**Invalid configuration type.**
Explanation	When updating the cluster settings, the provided configuration type must be COMMON-CLUSTER.
Action	Specify a configuration type of COMMON-CLUSTER when updating the cluster settings.

PIESIME0079	**{0} is required.**
Explanation	The required field value cannot be empty.
Action	Specify a value for the required field.

PIESIME0082	**Session timeout must be a positive integer.**
Explanation	The provided session timeout is not a positive integer.
Action	Specify a positive integer for session timeout.

PIESIME0083E	**Configuration details for {0} cannot be null.**
Explanation	While creating a {0} web service endpoint alias, the configuration details for {1} cannot be null.
Action	Provide valid web service endpoint alias configuration details.

PIESIME0084	**Invalid configuration type.**
Explanation	The configuration type provided while creating {0} web service endpoint alias must be of type {1}.
Action	Provide a valid configuration type.

PIESIME0085	**{0} Web service endpoint alias is not specified.**
Explanation	{0} Web service endpoint alias is not specified.
Action	Specify a valid web service endpoint alias configured in Integration Server.

PIESIME0086	**{0} Web service endpoint alias contains invalid characters.**
Explanation	{0} Web service endpoint alias contains invalid characters.
Action	Specify a valid web service endpoint alias.

PIESIME0087	**Host or port is not specified for {0} web service endpoint alias.**
Explanation	Host or port is not specified for {0} web service endpoint alias.
Action	Specify a valid host and port for the web service endpoint alias.

PIESIME0088	**Keystore alias or key alias is not valid.**
Explanation	Keystore alias or key alias must be a valid alias configured in Integration Server.
Action	Specify a valid configured keystore alias or key alias.

PIESIME0089	**Truststore alias is not valid.**
Explanation	Truststore alias must be a valid alias configured in Integration Server.
Action	Specify a valid configured truststore alias.

PIESIME0090	**{0} cannot be edited.**
Explanation	You attempted to edit {0}, which cannot be edited.
Action	Ensure that the specified field is not edited.

PIESIME0092	**Execute ACL is not valid.**
Explanation	The specified Execute ACL does not exist.
Action	Specify a valid ACL.

PIESIME0093	**Proxy server alias is not valid.**
Explanation	Proxy server alias must be a valid alias configured in Integration Server.
Action	Specify a valid proxy server alias.

PIESIME0094E	**The proxy-bypass alias cannot be deleted.**
Explanation	The default proxy alias, proxy-bypass, contains the proxy bypass addresses list and cannot be deleted.
Action	You cannot create or delete the proxy-bypass alias.

PIESIME0095E	**Invalid protocol specified. Protocol must be HTTP, HTTPS, FTP, or SOCKS.**
Explanation	Protocol must be HTTP, HTTPS, FTP, or SOCKS.
Action	Specify HTTP, HTTPS, FTP, or SOCKS as the protocol.

PIESIME0096E	**Invalid FTP proxy type. The FTP proxy type must be an integer within the range of 0 and 7 (inclusive).**
Explanation	FTP proxy type must be an integer within the range of 0 and 7 (inclusive).
Action	Specify an integer within the range of 0 and 7 (inclusive).

PIESIME0097E	**Only the NonProxyHosts field can be edited in the proxy-bypass alias.**
Explanation	You attempted to edit the fields other than the NonProxyHosts field in the proxy-bypass alias.
Action	Ensure that you edit only the NonProxyHosts field in the proxy-bypass alias.

PIESIME0098E	**License key location cannot be updated.**
Explanation	License key location cannot be updated.
Action	License key location cannot be updated.

PIESIME0099E	**The proxy server alias element for the existing configuration of type COMMON-PROXY cannot be updated.**
Explanation	You attempted to update the alias element for the existing configuration of type COMMON-PROXY.
Action	The proxy server alias element is not editable.

PIESIME0102	**File Access Permission configuration instance id cannot be null.**
Explanation	File Access Permission configuration instance id is required and must be specified.
Action	Provide a valid File Access Permission configuration instance id.

PIESIME0103	**Configuration details for IS-FILEPERMISSION cannot be null.**
Explanation	While updating a file permission instance, the configuration details for IS-FILEPERMISSION cannot be null.
Action	Provide valid file permission configuration details.

PIESIME0104	**Invalid configuration type.**
Explanation	The configuration type provided while updating the file permission configuration must be of type IS-FILEPERMISSION.
Action	Provide a valid configuration of type IS-FILEPERMISSION.

PIESIME0105	**Configuration details for IS-FILEPERMISSION cannot be null.**
Explanation	While updating the file access control configuration, the configuration details for IS-FILEPERMISSION cannot be null.
Action	Provide valid file access control configuration details.

PIESIME0106	**File permission type cannot be modified.**
Explanation	While updating file access control configuration, the file permission type cannot be modified.
Action	Provide valid configuration details while updating the file access control configuration.

PIESIME0107	**Logger Levels specified for Server Logger cannot be modified.**
Explanation	You attempted to add or delete the Logger Levels specified for Server Logger.
Action	You cannot add or delete the Logger Levels specified for Server Logger.

PIESIME0108	**Logger Level names and descriptions specified for Server Logger cannot be modified.**
Explanation	You attempted to modify the Logger Level names or descriptions specified for Server Logger.
Action	You can modify only the Logger Level value for Server Logger.

PIESIME0109E	**Specify an {0} proxy server alias.**
Explanation	Protocol of the proxy server alias that you specified and the transport type of the consumer web service endpoint alias must match.
Action	Specify an {0} proxy server alias.

PIESIME0110	**Value of {0} must be a positive integer between 0 and {1} (inclusive).**
Explanation	You specified an invalid value for {0}. Value of {1} must be a positive integer between 0 and {2} (inclusive).
Action	Ensure that you specify a positive integer between 0 and {1} (inclusive) as the value of {0}.

PIESIME0111	**Alias of an Integration Server logger cannot be modified.**
Explanation	You attempted to modify the alias of an Integration Server logger.
Action	You cannot modify the alias of an Integration Server logger.

PIESIME0112	**Invalid timestamp format.**
Explanation	The timestamp format must be supported by the Java class java.text.SimpleDateFormat.
Action	Specify any timestamp format that is supported by the Java class java.text.SimpleDateFormat.

PIESIME0113	**Alias of a {0} cannot be modified.**
Explanation	You attempted to modify the alias of a {0}.
Action	You cannot modify the alias of a {0}.

PIESIME0114E	**Remote server endpoint configuration details are not valid for {0}.**
Explanation	The value specified for remote server endpoint {0} is missing or is not valid.
Action	Specify valid values for all mandatory remote server endpoint attributes.

PIESIME0115E	**Remote server endpoint configuration details cannot be null.**
Explanation	Configuration details for a remote server endpoint cannot be null.
Action	Provide valid remote server endpoint details.

PIESIME0116E	**Remote server endpoint configuration could not be updated because the configuration details provided are not valid.**
Explanation	The remote server endpoint configuration could not be updated because the provided configuration details are not valid.
Action	Specify valid values for all mandatory remote server endpoint attributes.

PIESIME0117E	**An error occurred while invoking a service in Integration Server: {0}**
Explanation	Integration Server could not execute the service for the reason indicated.
Action	Check the reason detailed in the message, take appropriate corrective action, and reissue the service request.

PIESIME0118E	**Connection attempts to the remote server endpoint {0} failed.**
Explanation	A connection error occurred while trying to connect to the remote Integration Server from the target server on which the remote server endpoint was created. Either the remote server is not available or the provided host name, port, or authentication credentials are not valid.
Action	Check the status of the remote server and restart the server if necessary. Ensure the configuration of the remote server endpoint is valid.

PIESIME0119E	**Invalid SOCKS protocol version.**
Explanation	Supported SOCKS protocol versions are 4 and 5.
Action	Specify the SOCKS protocol version as either 4 or 5.

PIESIME0120E	**SOCKS protocol version 4 does not support authentication.**
Explanation	You specified authentication credentials (i.e. username and password) for SOCKS protocol version 4.
Action	Do not specify authentication credentials (i.e. username and password) for SOCKS protocol version 4.

PIESIME0121	**Messaging connection alias client prefix cannot be null or empty.**
Explanation	While creating a messaging connection alias, the client prefix field cannot be null or empty.
Action	Provide a valid client prefix for messaging connection alias.

PIESIME0122	**JAAS Context cannot be null or empty.**
Explanation	You did not specify a valid JAAS login context for Kerberos authentication. The JAAS Context field must not be null or empty.
Action	Provide a valid JAAS login context for Kerberos authentication.

PIESIME0123	**Service Principal Name Format cannot be null or empty.**
Explanation	You did not specify a valid Service Principal Name Format. Service Principal Name Format must not be null or empty.
Action	Provide a valid Service Principal Name Format.

PIESIME0124	**Proxy server alias contains invalid characters.**
Explanation	The Proxy server alias name can contain only alphanumeric characters.
Action	Specify a proxy server alias name that contains only alphanumeric characters.

PIESIME0125	**No LDAP server configuration is available in the target Integration Server or more than one LDAP servers are configured in the target Integration Server.**
Explanation	Only one LDAP server must be configured in the target Integration Server.
Action	Add or remove LDAP server configurations to ensure that there is only one LDAP server configured in the target Integration Server.

PIESIME0126	**An LDAP server is already configured in the target Integration Server.**
Explanation	Only one LDAP server must be configured in the target Integration Server. There is already one or more than one LDAP servers configured in the target Integration Server.
Action	Ensure that there is only one LDAP server configured in the target Integration Server. Retain one LDAP server configuration and delete the rest.

PIESIME0127	**The Maximum Connection Pool Size must be greater than the Minimum Connection Pool Size.**
Explanation	The value specified for Maximum Connection Pool Size is lesser than the Minimum Connection Pool Size.
Action	Ensure that you provide a Maximum Connection Pool Size greater than the Minimum Connection Pool Size.

PIESIME0128	**LDAP server configuration must contain either a default group or a group member attribute.**
Explanation	While configuring the LDAP server, either a default group or a group member attribute must be specified.
Action	Ensure that you specify a default group or a group member attribute while configuring the LDAP server.

PIESIME0129	**Invalid LDAP URL! Specify a LDAP URL that starts with ldap:// or ldaps:// and try again.**
Explanation	Invalid LDAP URL specified in the Server configuration type for LDAP.
Action	Specify a valid URL in the Server configuration type for LDAP.

PIESIME0130	**The Group Id attribute in the Server configuration type for LDAP cannot be null.**
Explanation	The Group Id attribute is not provided in the Server configuration type for LDAP.
Action	Specify a Group Id attribute in the Server configuration type for LDAP.

PIESIME0131	**Default JAAS Realm alias cannot be deleted.**
Explanation	The JAAS Realm alias that you attempted to delete is the default Integartion server JAAS Realm, which cannot be deleted.
Action	Do not delete the default Integration Server JAAS Realm.

PIESIME0132	**Specified JAAS Realm is already defined.**
Explanation	Unable to define new JAAS Realm because the specified JAAS Realm is already defined.
Action	Specify new JAAS Realm.

PIESIME0133	**Configuration details for COMMON-JAAS-Realm cannot be empty.**
Explanation	The configuration details for COMMON-JAAS-Realm cannot be empty.
Action	Provide valid JAAS Realm details.

PIESIME0134	**Provided JAAS Realm name is not same as the existing JAAS Realm name.**
Explanation	Unable to update as provided JAAS Realm name does not match with the existing JAAS Realm name.
Action	To update a current JAAS Realm provide the same name as the existing one.

PIESIME0141	**JMS Trigger State must be specified**
Explanation	JMS Trigger State must be specified
Action	Provide the JMS Trigger state

PIESIME0142	**JMS Trigger State must be Enabled or Disabled or Suspended**
Explanation	JMS Trigger State must be Enabled or Disabled or Suspended
Action	Provide the JMS Trigger State

PIESIME0143	**JMS Trigger Type must be specified**
Explanation	JMS Trigger Type must be specified
Action	Provide the JMS Trigger Type

PIESIME0144	**JMS Trigger Type must be All or Standard or SOAP**
Explanation	Provided JMS Trigger Type must be All or Standard or SOAP
Action	Provide JMS Trigger Type

PIESIME0145	**Thread Pool Throttle must be specified**
Explanation	Thread Pool Throttle must be specified
Action	Provide value to the Thread Pool Throttle

PIESIME0146 **Thread Pool Throttle must be an integer between 1 and 100**

Explanation Thread Pool Throttle must be an integer between 1 and 100

Action Provide value to the Thread Pool Throttle between 1 and 100

PIESIME0147 **Processing Throttle must be specified**

Explanation Processing Throttle must be specified

Action Provide a value to the Processing Throttle

PIESIME0148 **Processing Throttle must be an integer between 1 and 100**

Explanation Processing Throttle must be an integer between 1 and 100

Action Provide a value to the Processing Throttle between 1 and 100

PIESIME0180 **User {0} cannot be deleted.**

Explanation The predefined user {0} cannot be deleted.

Action Provide a valid user name while deleting a User configuration.

PIESIME0181 **User id cannot be empty.**

Explanation User id cannot be empty while adding / updating / deleting a User configuration.

Action Provide a valid user name while adding / updating / deleting a User configuration.

PIESIME0182 **User ID cannot be edited.**

Explanation You attempted to edit ID, which cannot be edited.

Action Ensure that the specified field is not edited.

PIESIME0183 **User {0} cannot be removed from the Group {1}.**

Explanation User {0} cannot be removed from the Group {1}.

Action Provide a valid list of Groups while updating a User configuration.

PIESIME0184 **User configuration instance id cannot be null.**

Explanation User configuration instance id is required and must be specified.

Action Provide a valid User configuration instance id.

PIESIME0185	**Missing required configuration : User**
Explanation	Missing required configuration : User
Action	Provide the required User configuration

PIESIME0186	**Invalid property {0}.**
Explanation	Invalid property {0}.
Action	Provide a valid property.

PIESIME0187	**Invalid configuration type.**
Explanation	The configuration type provided must be of type COMMON-LOCAL-USERS.
Action	Provide a valid configuration type.

PIESIME0188	**Invalid configuration type.**
Explanation	The configuration type provided must be of type IS-GROUPS.
Action	Provide a valid configuration type.

PIESIME0189	**Group configuration instance id cannot be null.**
Explanation	Group configuration instance id is required and must be specified.
Action	Provide a valid Group configuration instance id.

PIESIME0190	**Group name cannot be empty.**
Explanation	Group name cannot be empty while adding / updating / deleting a Group configuration.
Action	Provide a valid group name while adding / updating / deleting a Group configuration.

PIESIME0191	**Group {0} cannot be deleted.**
Explanation	The predefined Group {0} cannot be deleted.
Action	Provide a valid Group name while deleting a Group configuration.

PIESIME0192	**Group {0} cannot be edited**
Explanation	The predefined Group {0} cannot be edited
Action	Provide a valid Group name while updating a Group configuration

PIESIME0193 **Group name cannot be edited.**

Explanation You attempted to edit Group name, which cannot be edited.

Action Ensure that the specified field is not edited.

PIESIME0194 **User {0} cannot be added to Group {1}.**

Explanation User {0} cannot be added to Group {1}.

Action Provide a valid list of Groups while updating a User configuration

PIESIME0195 **Group {0} already exists.**

Explanation Group {0} already exists.

Action Provide a valid Group name while creating a Group configuration.

PIESIME0196 **Missing required configuration : Group**

Explanation Missing required configuration : Group

Action Missing required configuration : Group

PIESIME0197 **Group configuration instance id cannot be null.**

Explanation Group configuration instance id is required and must be specified.

Action Provide a valid Group configuration instance id.

PIESIME0198 **The Group {0} does not exist.**

Explanation The specified Group cannot be found.

Action Provide a valid name for Group configuration.

PIESIME0199 **Missing required configuration : ACL**

Explanation Missing required configuration : ACL

Action Missing required configuration : ACL

PIESIME0200 **ACL configuration instance id cannot be null.**

Explanation ACL configuration instance id is required and must be specified.

Action Provide a valid ACL configuration instance id.

PIESIME0201 **The ACL {0} does not exist.**

Explanation The specified ACL cannot be found.

Action Provide a valid name for ACL configuration.

PIESIME0202 **Invalid configuration type.**

Explanation The configuration type provided must be of type IS-ACLS.

Action Provide a valid configuration type.

PIESIME0203 **ACL name cannot be empty.**

Explanation ACL name cannot be empty while adding / updating / deleting an ACL configuration.

Action Provide a valid ACL name while adding / updating / deleting an ACL configuration.

PIESIME0204 **ACL {0} cannot be deleted.**

Explanation The predefined ACL {0} cannot be deleted.

Action Provide a valid ACL name while deleting an ACL configuration.

PIESIME0205 **ACL name cannot be edited.**

Explanation You attempted to edit ACL name, which cannot be edited.

Action Ensure that the specified field is not edited.

PIESIME0206 **ACL {0} already exists.**

Explanation ACL {0} already exists.

Action Provide a valid ACL name while creating an ACL configuration.

PIESIME0207 **Group {0} cannot be removed from {1} list of {2} ACL.**

Explanation Group {0} cannot be removed from {1} list of {2} ACL.

Action Provide valid Group names for Allow and Deny list of an ACL configuration.

PIESIME0208 **Group {0} cannot be added to {1} list of {2} ACL.**

Explanation Group {0} cannot be added to {1} list of {2} ACL.

Action Provide valid Group names for Allow and Deny list of an ACL configuration.

PIESIME0209	**Group created but User names are not valid.**
Explanation	Group created but provided User names are not valid.
Action	Provide valid User names for the group.

PIESIME0210	**Group name is not valid.**
Explanation	Group name contains non-ASCII characters.
Action	Provide a valid group name.

PIESIME0211	**User id is not valid.**
Explanation	User id contains non-ASCII characters.
Action	Provide a valid user id.

PIESIME0212	**ACL name is not valid.**
Explanation	ACL name contains non-ASCII characters.
Action	Provide a valid ACL name.

PIESIME0213	**ACL created but Allow or Deny Group names are not valid.**
Explanation	ACL created but provided Allow or Deny Group names are not valid.
Action	Provide valid Allow or Deny Group names for the ACL.

PIESIME0214	**Allow or Deny Group names are not valid.**
Explanation	Allow or Deny Group names provided are not valid.
Action	Provide valid Allow or Deny Group names while updating an ACL configuration.

PIESIME0215	**User names are not valid.**
Explanation	User names provided are not valid.
Action	Provide valid User names while updating a Group configuration.

PIESIME0217	**Provided value for 'Action On Startup Error' is not valid.**
Explanation	Provided value for 'Action On Startup Error' is not valid. Supported values are 'standalone', 'shutdown', 'quiesce'
Action	Provide a valid value for 'Action On Startup Error'. Supported values are 'standalone', 'shutdown', 'quiesce'

PIESIMI0150 **IS System Properties**

Explanation Java System Properties

PIESIMI0151 **General Properties**

Explanation General Properties

PIESIMI0160 **IS Groups**

Explanation IS Groups Configuration Type

PIESIMI0161 **Groups**

Explanation Groups

PIESIMI0170 **IS ACLs**

Explanation IS ACLs Configuration Type

PIESIMI0171 **ACLs**

Explanation ACLs

PIESIMW0036 **Unable to establish a connection using the specified JNDI provider alias.**

Explanation Integration Server is unable to establish a connection using the specified JNDI provider alias. For possible causes, check the server logs.

Action Ensure that the JNDI provider is running and that the JNDI provider-specific libraries are used in Integration server.

PIESIMW0044 **JMS alias {0} created successfully, but an error occurred while enabling the JMS alias.**

Explanation An error occurred while enabling JMS alias {0}. Check logs of integration server. Exception : {1}

Action Check the Integration Server log to handle the exception manually.

PIESIMW0055 **IS Resource settings updated successfully. If Broker is not configured, Broker-related settings will be ignored.**

Explanation IS Resource settings updated successfully. If Broker is not configured on Integration Server, all the Broker-related settings that you specified will be ignored.

Action Ensure that Broker is configured if you want the Broker-related settings to be updated.

PIESIMW0056 **Unable to read listeners.cnf file from package {0}.**

Explanation Unable to read the listeners.cnf configuration file while attempting to locate the port number for the specified port alias.

Action No action is required. If the issue persists, contact Software AG Global Support.

PIPELINE_SAVE_ACCESSDENIED – Save pipeline to file {0}, Access denied

POOL_NOT_EXISTI Pool alias {0} does not exist.

PREFIX+String.valueOf(NEG_TIMEOUT_ERROR) – Pool {0} cannot be initialized. The pool timeouts must not be negative.

PROPERTIES_CAN_NOT_BE_NULL – properties can not be null

PROTOBUF_CODER_UNSUPPORTED_DATATYPE – Protocol buffer coder cannot handle data type {0} for field {1} in document type: {2}. Error: {3}

PROXY_INVALID_SOCKS_AUTH – SOCKS protocol version 4 does not support authentication.

PROXY_INVALID_SOCKS_VERSION – Invalid SOCKS protocol version.

REMOTE_NO_REGISTRY_TYPE – No Registry type specifed

RESOURCE_CAN_NOT_BE_NULL – resource can not be null

RESPONSE_ONE_OF_THREE_REQD – "{0}" or "{1}" or "{2}" must be supplied

REVERSE_GATEWAY_NO_LICENSE – Could not find a valid license for Enterprise Gateway.

Explanation The Enterprise Gateway Server instance does not have a valid license for webMethods Enterprise Gateway.

Action Check the terms of the license file.

ROLLBACK_FAILED_BAD_STATE – Rollback failed due to status

RUN_AS_USER_IS_REQUIRED – runAsUser is required

SCC.0121.0004 **enlist failed: {0} xid = {1} rxid = {2}**

SCC.0121.0007 **delist failed: {0} xid = {1} rxid = {2}**

SCC.0121.0010E **commit failed: {0} xid = {1} resource = {2}**

Explanation Integration Server transaction manager was unable to commit a two-phase commit (2PC) transaction to the backend XA resource.

Action Check to see if the backend resource is connected to Integration Server. Then, if necessary, re-initiate the transaction.

SCC.0121.0013 **prepare failed: {0} xid = {1} rxid = {2} vote = {3}**

SCC.0121.0017E **rollback failed: {0} xid = {1} resource = {2}**

Explanation The Integration Server transaction manager was unable to roll back a two-phase commit (2PC) transaction, most likely due to a resource issue.

Action Check to see if the backend resource is connected to Integration Server. Then, if necessary, re-initiate the transaction.

SCC.0121.0020 **end failed: {0} xid = {1} rxid = {2}**

SCC.0121.0026 **delisted transaction commit failed: {0} xid = {1}**

SCC.0121.0029 **one phase commit failed: {0} xid = {1} resource = {2}**

SCC.0121.0031 **sync beforeCompletion ran: {0} error: {1}**

SCC.0121.0033 **sync afterCompletion ran: {0} error: {1}**

SCC.0121.0034 **commit failed: more than 1 local trans enlisted. xid = {1} rxid = {2}**

SCC.0121.0035 **resource delisted with TMFAIL flag, transaction marked for rollback. xid = {0} rxid = {1}**

SCC.0121.0036 **transaction timeout. xid = {0}**

SCC.0121.0052E **Unable to persist transaction status for xid = {0}: Exception: {1}**

Explanation The transaction recovery manager in Integration Server was unable to write the status of a two-phase commit (2PC) transaction to the disk-based XA recovery store.

Action Investigate the following possible causes for the problem:

1) The operating system userid under which the Integration Server is running does not have write privileges to the XAStore directory.

2) There is not sufficient disk space for the directory.

3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XA recovery store directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart Integration Server.

SCC.0121.0055E **Unable to get unrecovered transactions from persistent store. Exception:{0}**

Explanation The transaction recovery manager in Integration Server was unable to obtain a list of incomplete transactions from the XA recovery store. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.

Action Investigate the following possible causes for the problem:

1) The operating system userid under which Integration Server is running does not have write privileges to the XAStore directory.

2) There is not sufficient disk space for the directory.

3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XA recovery store directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart the Integration Server.

SCC.0121.0056 **RecoveryManager found {0} unrecovered Transactions. Starting recovery.**

SCC.0121.0057 **Recovery process started for Transaction Xid:{0}, Status: {1}.**

SCC.0121.0062E **Unable to rollback Xid:{0} during recovery for resource:{1}, transaction might been heuristically rolled back/commited by resource. Manual intervention might be required. Exception:{2}: Error Code:{3}.**

Explanation The transaction recovery manager in Integration Server detected a transaction whose status in Integration Server is different from the status stored in the back-end resource (for example, a database). This situation occurs when the transaction recovery manager tries to rollback a transaction that the back-end XA resource has already rolled back or committed.

Action Check to see if the back-end resource administrator (for example a database administrator) manually issued a rollback/commit for the incomplete transaction. If so, ensure that the other back-end XA resources do the same.

SCC.0121.0067E **Unable to commit Xid:{0} during recovery for resource:{1}, transaction might been heuristically rolled back/commited by resource. Manual intervention might be required. Exception:{2}.**

Explanation The transaction recovery manager of the Integration Server detected a transaction whose status in the Integration Server is different from the status stored in the back-end resource (for example, a database). This situation occurs when the transaction recovery manager tries to commit a transaction that the back-end XA resource has already rolled back or committed.

Action Check to see if the back-end resource administrator (for example a database administrator) manually issued a rollback/commit for the incomplete transaction. If so, ensure that the other back-end XA resources do the same.

SCC.0121.0070 **XARecoveryStore: Error during checkDataDevice. Db:{0} Error:{1}**

SCC.0121.0071 **XARecoveryStore: Resized Data file recovered. Db:{0}**

SCC.0121.0072 **XARecoveryStore: Error restoring original data file. Db:{0} Error:{1}**

SCC.0121.0073	**XARecoveryStore: Recoverable Error Skipped - warnonopen = continue. Db:{0} Error:{1}**
SCC.0121.0074	**XARecoveryStore: Recoverable Error Encountered but warnonopen = fail. Db:{0} Error:{1}**
SCC.0121.0075	**XARecoveryStore: Damaged data file detected. Db:{0} Error:{1}**
SCC.0121.0076	**XARecoveryStore: Data file resize required. Db:{0}**
SCC.0121.0077	**XARecoveryStore: Error cleaning up resized Data file. Db:{0} Error:{1}**
SCC.0121.0078	**XARecoveryStore: Error creating resized Data file. Db:{0} Error:{1}**
SCC.0121.0079	**XARecoveryStore: Error closing original Data file. Db:{0} Error:{1}**
SCC.0121.0080	**XARecoveryStore: Error closing resized data file. Db:{0} Error:{1}**
SCC.0121.0081	**XARecoveryStore: Error cleaning up copied Data file. Db:{0} Error:{1}**
SCC.0121.0082	**XARecoveryStore: Error renaming original data file. Db:{0} Error:{1}**
SCC.0121.0083	**XARecoveryStore: Data file resize completed. Db:{0}**
SCC.0121.0084	**XARecoveryStore: Error renaming resized data file. Db:{0} Error:{1}**
SCC.0121.0086	**XARecoveryStore: Error copying resized Data file. Db:{0}**
SCC.0121.0087	**XARecoveryStore: Damaged data file renamed. Db:{0} renamed:{1}**

SCC.0121.0088 **XARecoveryStore: Error renaming damaged data file. Db:{0} Error:{1}**

SCC.0121.0089 **XARecoveryStore: Damaged data file deleted. Db:{0}**

SCC.0121.0090 **XARecoveryStore: Error deleting damaged data file. Db:{0} Error:{1}**

SCC.0121.0091 **XARecoveryStore: Error re-creating damaged data file. Db:{0} Error:{1}**

SCC.0121.0092 **XARecoveryStore: Damaged data file re-created. Db:{0}**

SCC.0121.0094S **Unrecoverable Exception while initializing the XA Recovery Store: {0}**

Explanation Integration Server was unable to create a persistent XA recovery store on disk. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.

Action Investigate the following possible causes for the problem:

1) The operating system userid under which the Integration Server is running does not have write privileges to the XA recovery store directory.

2) There is not sufficient disk space for the directory.

3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XAStore directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart the Integration Server.

SCC.0121.0095 **XA Recovery Store could not be created.**

SCC.0121.0104 **Unable to gain access to resource:{0} Error:{1}. Please verify that the Connection exists and is correctly configured.**

SCC.0121.0106 **No transaction record found for Xid:{0} in resource:{1}. Transaction might have been commited or erased on resource:{1}. Unable to resolve as transaction might be in mixed state, requires manual intervention.**

SCC.0121.0107 **Invalid global transaction state for Xid:{0}. Unable to auto-resolve transaction, aborting recovery.**

SCC.0121.0108 **Transaction Xid:{0} exceeded abandon timeout setting, aborting recovery.**

SCC.0121.0112E **Error while shutting down XA Recovery Store:{0}.**

Explanation The Integration Server XA recovery store did not shut down cleanly. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.

Action Restart Integration Server and examine the Server log for any error messages regarding the XARecovery Store. If the problem is a file permission or out of storage issue, correct the problem and restart the Integration Server. If the problem is not a file permission or out of storage issue, archive the contents of the XAStore directory and contact Software AG Global Support.

SCC.0121.0113E **Recover call on XAResource:{0} failed. Exception:{1}, Error Code:{2}**

Explanation The transaction recovery manager on Integration Server encountered an error when it tried to obtain a list of all incomplete XIDs known to the back-end resource. The error occurred because the back-end resource threw an exception.

Action Check to see if the back-end resource is available and connected to Integration Server. The name of the resource will be the name of the connection defined in the adapter for the resource.

SCC.0121.0116 **Active transaction detected while completing service {0}. Rolling back pending operations.**

SCC.0121.0118 **Active resource detected while cleaning Top Transaction for service {0}. Rolling back pending operations.**

SCC.0121.0120 **Active transaction found with the thread after cleanup while completing service {0}. Check the cleanup process.**

SCC.0121.0990 **XA Transaction Logging: {0}**

SCC.0126.0100 **An error occurred while attempting to clean up transaction resources on connection {0}**

SCC.0126.0101 **An error occurred while attempting to release connection {0}**

SCC.0126.0102 **An error occurred while attempting to close connection pool {0}**

SCC.0126.0103E **Assertion error during creation of connection pool {0}**

Explanation An error occurred while allocating the managed connection because either the connection pool does not exist or the connection pool is empty for the managed connection factory.

Action Ensure that the connection pool settings contain valid values. If the values are valid and if Integration Server is still unable create the connection pool, contact Software AG Global Support.

SCC.0126.0104 **Assertion error during reset of connection pool {0}**

SCC.0126.0105E **Assertion error during connection request from pool {0}**

Explanation An error occurred while allocating a connection to a request from the connection pool. This can happen if there are no available connections in the pool, if the managed connection factory does not exist, or if the conditions provided by the basic connection pool properties (such as pool size, minimum number of connections or maximum number of connections) are not met.

Action Ensure the connection pool settings are valid. If the connection pool settings are valid and Integration Server is still unable to allocate a connection from the connection pool, contact Software AG Global Support.

SCC.0126.0106 **An error occurred while attempting to retrieve a connection from {0}**

SCC.0126.0107 **A connection was not available for request in pool {0}**

SCC.0126.0110 **Failed to retrieve handle for connection {0}**

SCC.0126.0111 **A duplicate connection returned from managed connection factory {0}**

SCC.0126.0112 **A data level assertion occurred while managing connections for pool {0}**

SCC.0126.0113 **Pool {0} cannot be initialized. The pool sizes (min, max, increment) must not be negative.**

SCC.0126.0115E **Pool {0} cannot be initialized. The minimum pool size must be <= the maximum pool size.**

Explanation An error occurred while initializing the connection pool because the minimum number of connections is greater than the maximum number of connections allowed or the maximum number of connections is set to zero.

Action Check the adapter connection pool settings to ensure the values for the minimum number of connections and maximum number of connections are valid. If the adapter connection pool settings are valid and the pool is still unable to initialize, contact Software AG Global Support.

SCC.0126.0116E **Pool {0} cannot be initialized. A valid ManagedConnectionFactory was not provided.**

Explanation An error occurred while checking basic properties for a connection pool because the managed connection factory for this pool is null.

Action Check the connection pool settings to ensure that a valid connection factory is provided. If the settings are valid and the problem still exists, contact Software AG Global Support.

SCC.0126.0117E **An error occurred while attempting to destroy connection {0}**

Explanation An error occurred while closing the database connection from the connection pool.

Action This is an internal error. Contact Software AG Global Support.

SCC.0126.0118E **Pool state error in {0}. Cannot process request.**

Explanation The next available connection cannot be obtained from the connection pool because the connection pool is disabled.

Action Check the connection pool settings to ensure that the connection pool is enabled. If the connection pool is enabled and if Integration Server is still unable to obtain the next available connection from the connection pool, contact Software AG Global Support.

SCC.0126.0119E	**An error occurred while attempting to create connections for {0}**
Explanation	An error occurred while creating a new connection for the connection pool.
Action	Ensure that the resource database is running and the connection pool settings are valid. If the resource database is running and the connection pool settings are valid, contact Software AG Global Support.

SCC.0126.0120E	**{0} Threads are already waiting to get connection. The pool {1} doesn't have a connection available for the request.**
Explanation	This error occurs when a thread holds a connection and stops responding or is in an infinite loop. In either case, the connection pool management capabilities to grant, release, or close connections do not work. Meanwhile, if the pool is flooded with many connection requests, all of the requesting threads are held in a waiting state. Under a heavy load, Integration Server might stop responding. If there are a large number of threads already waiting for a connection, ResourceAllocationException will be thrown to the new threads.
Action	Check the adapter connection pool settings to ensure the values for the minimum number of connections and maximum number of connections are valid. If the adapter connection pool settings are valid and the pool is still unable to initialize, contact Software AG Global Support.

SCHEDU_ACL_DENIED	**User {0} doesn't have permission to execute the service {1}.**

SESSION_EXPIRED	**Session has expired.**

SS.0088.9424E	**Error initializing service handler {0}. Error: {1}**
Explanation	An error occurred while initializing the JAX-RPC header handler.
Action	The init() method of JAX-RPC handler threw an error. Correct the error in init() method.

STATUS_ACTIVE	**Transaction is active**

STATUS_COMMITTED	**Transaction is committed**

STATUS_COMMITTING Transaction is committing

STATUS_MARKED_ROLLBACK – Transaction is marked for rollback

STATUS_NO_TRANSACTION – No Transaction

STATUS_PREPARED Transaction is prepared

STATUS_PREPARING Transaction is preparing

STATUS_ROLLEDBACK Transaction is rolled back

STATUS_ROLLING_BACK – Transaction is rolling back

STATUS_TWO_LOCAL_TX – commit failed. more than one local transaction enlisted.

STATUS_UNKNOWN Transaction status is unknown

STRINGSET_NOSUCHELMENT – StringSetEnumerator

SUSPENDED Suspended

TEST_INVALID_ALIASE – Associated pool alias for the functional alias {0} does not exist.

Explanation Integration Server cannot establish a connection to the pool. A connection pool alias is not associated with the specified functional alias.

Action Make sure a connection pool is associated with the functional alias.

THREAD_ALREADY_WITH_THIS_TX – thread already associated with this transaction

THREAD_WITH_ANOTHER_TX – thread already associated with another transaction

TRAN_NOT_ACTIVE transaction is not active

TRAN_NOT_FOR_THREAD – transaction is not with current thread

TRAN_NOT_WMTRAN transaction not a Tran instance

TRUST_STORE_EMPTY Truststore alias is empty. Specify a Truststore alias for the port or a global truststore alias on the Security > Certificates > Edit page.

UM_MIGRATE_CONNECTION_ALIAS_NOT_FOUND...0 – conectionAlias was not found:{0}.

UM_MIGRATE_CONNECTION_ALIAS_NOT_UM...0 – conectionAlias:{0} MUST be a Universal Messaging Connection Alias.

UM_MIGRATE_NOT_MIGRATABLE_FILTER – Filter cannot be completely migrated to Provider Filter (UM). Contains an unsupported construct:{0} {1} {2}.

UNABLE_TO_INIT_XASTORE – Unrecoverable Error while initializing XA Store: {0}

UNEXPECTED_END_OF_DOCUMENT_WHEN_READING_ELEMENT_TEXT_CONTENT – unexpected end of document when reading element text content

UNEXPECTED_EVENT_TYPE – Unexpected event type {0}

UNSUPPORTED_ACTION_DELETE_DEST_NULL – Cannot delete durable subscriber {0} for alias {1}. The durable subscriber cannot be accessed. You may need to delete the durable subscriber from the JMS provider manually.

URI_IS_INVALID URI "{0}" is invalid

URI_IS_NOT_UNIQUE URI "{0}" is already being used

URI_IS_REQUIRED URI is required

URLALIAS_ALREADY_REGISTERED – The HTTP URL alias could not be registered by the service {0}. "{1}" is already registered as an alias for the path: {2}

URLALIAS_ALREADY_REGISTERED2 – HTTP URL alias "{0}" could not be registered. It is already registered as an alias for the path: {1}

URLALIAS_ALREADY_REGISTERED3 – HTTP URL alias "{0}" could not be registered. It is already registered by package {1} as an alias for the path: {2}

URL_IS_INVALID URL "{0}" is invalid

URL_IS_NOT_UNIQUE URL "{0}" is already being used

URL_IS_REQUIRED URL is required

VCS.0132.0051 VCS package shutting down

VCS.0132.0052 loading configuration file: {0}

VCS.0132.0054 error loading configuration file: {0}

VCS.0132.0057 loading users file: {0}

VCS.0132.0059 **error loading users file: {0}**

VCS.0132.0060 **saving users file: {0}**

VCS.0132.0061 **error saving users file: {0}**

VCS.0132.0062 **retrieving information from VCS server**

VCS.0132.0063 **no configuration file read for package: {0}; expecting: {1}**

VCS.0132.0064 **overwriting existing property: {0}; new value: {1}**

VCS.0132.0100 **file not checked out: {0}**

VCS.0132.0101 **file checked out: {0}**

VCS.0132.0102 **file out of date: {0}**

VCS.0132.0103 **file checked out by another user: {0}**

VCS.0132.0150 **setting VCS client as {0}**

VCS.0132.0151 **no current VCS client**

VCS.0132.0152 **invalid VCS client: {0}**

VCS.0132.0153 **no VCS client type set**

VCS.0132.0202	**files to delete: {0}**
VCS.0132.0252	**Deleted by %value dev_user% on %value is_host% at %value is_time%**
VCS.0132.0253	**%value usercomment%%nl%dev_user : %value dev_user%%nl%is_host : %value is_host%%nl%dev_host: %value dev_host%%nl%is_time : %value is_time%**
VCS.0132.0254	**delete failed; attempting to revert from opened list**
VCS.0132.0302	**not locking in build mode (no package specified)**
VCS.0132.0303	**not locking in delete mode**
VCS.0132.0304	**running checkout from VCS**
VCS.0132.0353	**Checked in by %value dev_user% on %value is_host% at %value is_time%**
VCS.0132.0354	**%value usercomment%%nl%dev_user : %value dev_user%%nl%is_host : %value is_host%%nl%dev_host: %value dev_host%%nl%is_time : %value is_time%**
VCS.0132.0355	**running checkin to VCS**
VCS.0132.0502	**not deleting files during preDelete**
VCS.0132.0651	**No entries to submit**
VCS.0132.0700	**loading directories: {0}; version: {1}**
VCS.0132.0800	**Perforce client not found**

VCS.0132.0801 **Perforce user not found**

VCS.0132.0850 **For {0}, command: {1}**

VCS.0132.0951 **Parent does not exist: {0}**

VCS.0132.1000 **Node not found for version**

WEBSOCKET_NO_CALLBACK – Values for callback is required

WEBSOCKET_NO_VALUE Callback "{0}" is required

WEBSOCKET_REQ_FIELD – "{0}" is a required field.

WEBSOCKET_REQ_STR_OR_BYTE – Message field should be either string or byte object

WEBSOCKET_RUASUSER runAsUser is a required field.

WEBSOCKET_RUN_AS_USER – runAsUser is a required field.

WEBSOCKET_SESSION_NOTFOUND – Could not find session with sessionId: "{0}"

WS_ALIAS_EXISTING_MESSAGE_ADDRESSINGE – Could not add the Web service endpoint alias because the message addressing endpoint alias {0} for transport type {1} already exists. Provide a different alias name.

Explanation The message addressing endpoint alias name you specified already exists for a transport type (HTTP, HTTPS, JMS).

Action Specify a message addressing endpoint alias name that does not already exist.

WS_INVALID_ASC_CLIENT_KEYTAB_FILE – Client Keytab Filename must be ASCII characters

WS_INVALID_ASC_CLIENT_PASSWORD – Password for Client Principal must be ASCII characters

WS_INVALID_ASC_CLIENT_PRINCIPAL – Client Prinicipal name must be ASCII characters

WS_INVALID_ASC_CLIENT_PWD_INPUT_MODE – Client Password Input Mode must be ASCII characters

WS_INVALID_ASC_JAAS_CONTEXT – JAAS Context name must be ASCII characters

WS_INVALID_ASC_SERVICE_PRINCIPAL – Service Principal Name must be ASCII characters

WS_INVALID_ASC_SERVICE_PRINCIPAL_FORM – Service Principal Name Form must be ASCII characters

WS_NO_MSG_KRB_JAAS_CONTEXT – JAAS Context for WS Security not specified

WS_NO_MSG_KRB_SERVICE_PRINCIPAL – Service Principal for WS Security not specified

WS_NO_MSG_KRB_SERVICE_PRINCIPAL_FORM – Service Principal Name Form for WS Security not specified

XID_NOT_FOUND Failed attempt to store global status={0} for xid={1}. XID not found.

XML_NOT_WELLFORMED XML provided is not well-formed or external references encountered while parsing XML - {0}

XML_SOURCE_SHOULD_BE_OF_CORRECT_TYPE – xmlSource should be of type 'java.io.InputStream', 'java.io.Reader', 'org.w3c.dom.Node', 'javax.xml.stream.XMLStreamReader' or 'java.lang.String'

XML_TARGET_SHOULD_BE_OF_CORRECT_TYPE – xmlTarget should be of type 'java.io.OutputStream', 'java.io.Writer' or 'javax.xml.stream.XMLEventWriter'

XSL.0002.0014E **new Object[][]{{Integer.valueOf(1),Integer.valueOf(2),"JAXP: Error - {0}"},{Integer.valueOf(2),Integer.valueOf(3),"JAXP: Warning - {0}"},{Integer.valueOf(3),Integer.valueOf(5),"JAXP: Properties file is {0}."},{Integer.valueOf(4),Integer.valueOf(5),"JAXP: DocumentBuilderFactory = {0}"},{Integer.valueOf(5),Integer.valueOf(5),"JAXP: SAXParserFactory = {0}"},{Integer.valueOf(6),Integer.valueOf(5),"JAXP: TransformerFactory = {0}"},{Integer.valueOf(7),Integer.valueOf(5),"JAXP: Stylesheet template {0} cached."},{Integer.valueOf(8),Integer.valueOf(5),"JAXP: Stylesheet templates cache cleared."},{Integer.valueOf(9),Integer.valueOf(3),"JAXP: Required argument 'stylesheet' not specified; no value removed from stylesheet cache."},{Integer.valueOf(10),Integer.valueOf(5),"JAXP: Stylesheet template {0} removed from cache."},{Integer.valueOf(11),Integer.valueOf(3),"JAXP: Stylesheet template {0} was not found in cache."},{Integer.valueOf(12),Integer.valueOf(5),"JAXP: Stylesheet {0} was successfully compiled."},{Integer.valueOf(13),Integer.valueOf(5),"JAXP: Compiling TransformerFactory = {0}"},{Integer.valueOf(14),Integer.valueOf(2),"JAXP: Error - External entity attack detected. Entity name is {0}"},,}**

Explanation An external entity was detected in the XML that the pub.xslt.Transformations:transformSerialXML service received or in the XSLT stylesheet the service used to transform the XML.

Action Check the XML file or the XSLT stylesheet for external entities. If the external entity is a trusted entity, add the entity to the server parameter watt.core.xml.allowedExternalEntities.

19 Mediator Messages

0010.0345Debug **AliasesController.updateAliases - Deployment request for runtime alias is null**

Explanation Mediator received an alias deployment request with null values.

Action Check the deployment request and specify valid information in the request.

0010.0715E **Mediator Upgrade, did not complete successfully.**

Explanation This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. This message indicates the upgrade was not successful. There should be a previous error message in the server log that indicates the problem.

Action See actions for message ID '0010.0702'

0010.0753 **Successfully migrated Mediator cache configuration file**

0010.0786Error **Error initializing runtime aliases. {0}**

Explanation Mediator could not initialize the XML data for the runtime alias.

0010.0811Debug Error – AliasesController.removeAliases - Cannot delete alias. Null values found in the request field(s).

Explanation Mediator received an alias undeployment request with null values in one or more fields.

Action Verify the request and resend the request with valid values in the fields.

0010.0814Error	**Error retrieving the secure alias: {0}. {1}**
Explanation	Error while retrieving the secure string for the alias from the Integration Server password manager.
Action	Check the Integration Server password manager for details on the secure alias string.

0010.0815Error	**Error saving the secure alias: {0}. {1}**
Explanation	Error while saving the secure string for the alias to the Integration Server password manager.
Action	Check the Integration Server password manager for the secure alias string.

0010.0816Error	**Secure alias does not contain a secure string. Secure alias: {0}**
Explanation	The secure alias does not have a secure string associated with it.
Action	Enter a valid secure string for the secure alias and try again.

0010.0817Error	**Secure alias has invalid secure string encoding. Secure alias: {0}**
Explanation	The secure string assigned to the secure alias is not valid.
Action	Check if the secure string is properly encoded.

0010.0852	**Mediator could not deploy the service, {0}. {1}**
Explanation	An error occurred while parsing the default content type values for the service. Hence, the service could not be deployed.
Action	Check the Integration server logs for more details.

0010.0853	**Service failed because of an incorrect value for the default content type. Service: {0}; default content type: {1}**
Explanation	The default content type you provided for the service is either not valid or not supported by Mediator.
Action	Check the default content type provided to the service. A list of the content types support by Mediator is available in the product documentation.

0010.0855	**Mediator cannot deploy the service because the SOAP action in the REST request received is not suitable.**
Explanation	Mediator could not find a suitable SOAP action for the REST request received from the consumer.
Action	Redeploy the service with the correct SOAP action.

0010.0868	**Mediator is performing start-up tasks, please wait ...**
Explanation	User trying to attempt deployment while loading service(s) from cache/disk at start-up.
Action	Please wait to trigger deployment task until complete the Mediator start-up tasks

0030.0092	**PublisherPropsObserver - Unknown sender data type ({0})**
Explanation	The properties observer received an invalid sender type.
Action	This indicates a coding error. Non-Mediator code should never call this method.

0030.0094	**PublisherPropsObserver - Unknown parameters data type ({0})**
Explanation	The properties observer received an invalid update object type.
Action	This indicates a coding error. Non-Mediator code should never call this method.

0030.0099	**PublisherPropsObserver - Unknown wrapper factory data type ({0})**
Explanation	This message has incorrect text. It should indicate an invalid data type for UDDP publisher bean.
Action	Update the pg configuration file to use a proper UDDI publisher data type.

0030.0100	**PublisherPropsObserver - Unable to find wrapper factory**
Explanation	There is no UDDI publisher configured, but its properties are being changed.
Action	Update the configuration file. Either configure a UDDI publisher or unregister the UDDI properties observer.

0030.0104	**Exception encountered initializing logging resource: {0}**
Explanation	A problem was encountered while setting up a logger for Mediator to use. There should be an exception message with more details.
Action	Fix the problem identified by the exception message.

0030.0109	**PublisherPropsObserver - Can't convert string ({0}) to integer for publishing interval, ignoring input**
Explanation	The value received for performance data reporting interval was not a valid numeric string.
Action	Make sure a numeric value is input.

0030.0113	**PublisherPropsObserver - Unknown pg service deployer data type ({0})**
Explanation	The data typi of the PG Service Deployer bean is invalid.
Action	Update the pg configuration file to use a proper PG Service Deployer data type.

0030.0301	**ConsumerApplicationManager.convert - cannot handle null request**
Explanation	Unable to create Consumer deployment object for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0302	**ConsumerApplicationManager.convert - cannot convert consumer with null {0}**
Explanation	Invalid Consumer deployment object was found.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0303	**VirtualServiceDeployer.{0} - cannot handle null {1}**
Explanation	A null reference was found during a deployment activity. The object and activity are identified in the message.
Action	Probably bad SOAP request for deployment, fix request.

0030.0304	**VirtualServiceDeployer.deploy - service ({0}) already deployed, undeploying**
Action	Info level message, no action required.

0030.0305	**VirtualServiceDeployer.undeploy - cannot undeploy service ({0}), not deployed**
Explanation	Attempt to undeploy virtual service failed.
Action	Verify that Mediator and CentraSite agree that the service is no longer deployed. If not, try undeploying this service again, or restarting Mediator/IS.

0030.0306	**VirtualServiceDeployer.{0} - caught this: type({1}) message({2})**
Explanation	Unable to deploy virtual service. See exception message for more details.
Action	Address the problem indicated by exception and try to deploy again.

0030.0309	**ClusteredServiceDeployer{0} - cannot handle null {1}**
Explanation	Unable to create VS deployment object for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0315	**ClusteredConsumerManager.updateConsumer - cannot handle null consumer**
Explanation	Unable to create Consumer object for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0318	**ClusteredServiceDeployer - cannot deploy null info to cache**
Explanation	A problem occurred while attempting to convert a PGService for deployment to shared cache. There should be another message describing the conversion or deployment issue.
Action	Fix the conversion or deployment problem.

0030.0319	**ClusteredServiceDeployer - cannot undeploy null service name from cache**
Explanation	Virtual service undeployment requires a non-empty service name. This is problem with undeployment request payload.
Action	Fix the undeployment request payload.

0030.0328	**ConsumerApplicationManager.{0} - cannot handle null update request**
Explanation	Invalid Consumer deployment request for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0330	**ConsumerApplicationManager - not updating consumer ({0}), modification date, ({1}), is no more recent**
Action	Info level message, no action required.

0030.0333	**ConsumerApplicationManager.{0} - caught this: type({1}) message({2})**
Explanation	Unable to create and persist Consumer object for update.
Action	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.

0030.0336	**Consumer Application Update Failed; requested update has invalid {0} field**
Explanation	Invalid consumer name or key in remove request.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0337	**Consumer Application Remove Failed; consumer ({0}) does not exist**
Explanation	Attempt to remove consumer failed.
Action	Reply to CentraSite Deployment attemp should indicate error. Try redeploying this consumer or resynchronizing all consumers.

0030.0343	**RegisteredConsumerNamesManager.{0} - cannot handle null update request**
Explanation	Invalid RegisteredConsumerNames deployment request for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0344	**Registered Consumer Names Update Failed; requested update has invalid {0} field**
Explanation	Invalid service name or consumer names in registered consumer names update request.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0346	**RegisteredConsumerNamesManager - not updating consumer names registered to ({0}), modification date, ({1}), is no more recent**
Action	Info level message, no action required.

0030.0347	**RegisteredConsumerNamesManager.{0} - cannot handle null update request**
Explanation	Invalid RegisteredConsumerNames deployment request for remove.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0348	**Registered Consumer Names Remove Failed; requested update has invalid {0} field**
Explanation	Invalid service consumer name in remove request.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0350	**Registered Consumer Names Remove Failed; service ({0}) has no registered consumers**
Explanation	Invalid request to remove RegisteredConsumerNames, must include at least one consumer name.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0352	**RegisteredConsumerNamesManager.{0} - caught this: type({1}) message({2})**
Explanation	Unable to create and persist RegisteredConsumerNames object for update.
Action	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.

0030.0356	**VirtualServiceDeployer - unable to get endpoints for {0}, caught this: type({1}), msg({2})**
Explanation	Unable to obtain endpoint for deployed service.
Action	Probably bad SOAP request to Deployer or bad VSD, fix one or both.

0030.0357	**ClusteredRegisteredConsumerNamesDeployer.updateConsumerNames - cannot handle null reg names object**
Explanation	Unable to create RegisteredConsumerNames object for update.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0358	**Consumer Application Remove Failed; requested update has invalid name and key fields, both are empty**
Explanation	Consumer remove request must have either name or key to identify consumer; both were null or empty.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0359	**ConsumerApplicationManager - Consumer update request has invalid IP range; from ({0}) to ({1})**
Explanation	Consumer update request had invalid IP address range.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0361	**VirtualServiceDeployer - redeploying undeployed service ({0}), deployment failed for newer version**
Action	Info level message, no action required.

0030.0362	**VirtualServiceDeployer - a problem was encountered during deployment, ({0}) will be undeployed and replaced if necessary**
Action	Info level message, no action required.

0030.0363	**VirtualServiceDeployer.{0} - service({1}) caught this: type({2}) message({3})**
Explanation	Message context encountered an exception while attempting to redeploy or undeploy a virtual service. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0030.0364	**Deployment request for service: {0}. Registered consumer name element was processed, but the existing modification date is the same as the request. {1}**
Action	Info level message, no action required.

0030.0366	**UddiPropertiesObserver - Password lookup failed; type ({0}), message ({1})**
Explanation	A problem was encoutnered by attempting to retrieve stored password. There should be an exception with more specific trouble description.
Action	Fix the problem identified by the exception message.

0030.0367	**UddiPropertiesObserver - Unable to activate performance date policies; type ({0}), message ({1})**
Explanation	The performance data deployer was unable to run. This message should include more details regarding the reason.
Action	Fix the problem identified by the exception message.

0030.0370	**Unable to connect to UDDI: ({0}); property updates saved, but data collection is OFF.**
Explanation	A problem was encountered during publisher test.
Action	This is probably a bad configuration parameter, fix it.

0030.0371	**UddiPropertiesObserver - Unable to convert port string ({0}) to integer, using default port {1}**
Explanation	The value input for 'UDDI port' number is non-numeric.
Action	Input an numeric port value.

0030.0396Debug	**Exception in AliasesController.{0}. Alias type: {1}, message: {2}**
Explanation	Mediator is unable to create and persist an alias during an update.
Action	Verify the access permissions in the file system. See the Mediator error logs for details.

0030.0398Error	**Runtime alias update failed. The update request contains an invalid field: {0}**
Explanation	The SOAP request sent to the Deployer contains an invalid field.
Action	Resend the request with a valid value for the field.

0030.0399Debug	**SimpleAliasDeploymentManager.convert - Cannot deploy simple alias: {0}. Null value in field(s)**
Explanation	Mediator found an invalid simple alias during deployment.
Action	Resend the request with a valid value for the field(s).

0030.0410Error	**Error undeploying alias. Alias is associated with services. Alias: {0}, services: {1}**
Explanation	You are trying to undeploy an alias which is already deployed to a service. If you continue with undeploy, the associated services will not be usable.
Action	Remove the association between the alias and the service that you want to delete, or undeploy the associated services before you undeploy the alias.

0030.0412Debug error – EndpointAliasDeploymentManager.convert - Cannot deploy endpoint alias: {0}. Null value in field(s)

Explanation	Mediator found an invalid endpoint alias during deployment.
Action	Resend the request with a valid value for the field(s)

0030.0419	**AliasesDeploymentManager.convert - Cannot deploy alias: {0} of type {1}. Null value in field: {2}**
Explanation	Mediator found an invalid alias of type {1} during deployment. Alias Name: {0} Reason - Null value in field: {2}
Action	Resend the request with valid value for the field : {2}

0030.0420	**Deployment of webMethods IS Alias {0} failed because no webMethods IS service exists with the given service name {1} in Mediator.**
Explanation	Cannot deploy webMethods IS Alias with alias name : {0} and service name : {1}. No webMethods IS Service exists with given service name {1} in Mediator.
Action	Resend the deploy request with valid webMethods IS service name.

0050.0001	**Unable to find Policy Element in the VSD:{0}**
Explanation	An exception was encountered while attempting to extract a policy element from VSD. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0002	**Unable to create Rampart properties:{0}**
Explanation	An exception was encountered while attempting to assemble Rampart keystore properties. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0003	**Unable to replace static Rampart configuration with configured properties:{0}**
Explanation	An exception was encountered while attempting to re-configure Rampart keystore properties. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0004	**Unable to create Rampart Configuration Element:{0}**
Explanation	An exception was encountered while attempting to convert Rampart configuration string to XML. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0005	**Unable to create XPath to select first Policy Alternative:{0}**
Explanation	An exception was encountered while attempting to create an Xpath object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0006	**Error while removing existing RampartConfig elements:{0}**
Explanation	An exception was encountered while attempting to remove configuration elements. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0007	**Required configuration information to enable WS-Security processing is missing. Unable to process service: {0}. Please ensure Keystore/Truststore information is configured**
Explanation	Service could not be initialized due to a problem with keystore/trustore configuration.
Action	Fix the security configuration.

0050.0011	**Exception while determining hostname or IP address of the server:{0}**
Explanation	An exception was encountered while attempting to resolve a host name or IP address. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0013	**Mediator needs the repository location of the SOAP Stack**
Explanation	Configuration does not include a valid location for Axis2 repositoryconfiguration.
Action	Fix the axis2 configuration.

0050.0016	**ServerManager ready for processing**
Action	Info level message, no action required.

0050.0017	**Mediator encountered exception while starting ServerManager:{0}**
Explanation	An exception was encountered during configuration of Axis2 listeners. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0018	**Invalid Port specified. Using default configuration: {0}**
Explanation	The 'port' property has a non-numeric string value, the value configured in Axis is used.
Action	Make sure the property value to numeric.

0050.0019	**Port {0} is already in use. Trying alternate**
Explanation	The port indicated in the message is not available to use with a new socket.
Action	Specify another port value in the system 'port' property or Axis configuration.

0050.0020	**Exception while creating "id" selection XPath: {0}**
Explanation	Message context encountered an exception while attempting to create an XPath object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0021	**Found Element within Resources element with id: {0}**
Action	Info level message, no action required.

0050.0022	**Exception while selecting element with id:{0} in Resources Element: {1}**
Explanation	Message context encountered an exception while attempting to extract the indicated element from XML. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0023	**Mediator received a response for the request with message Id :{0} But a callback is not registered (anymore) to process this response**
Explanation	No callback was registered at the time this response was processed.
Action	This is probably a VS configuration problem.

0050.0024	**Mediator received a response message without a message Id**
Explanation	There was a problem relating the native service response to a virtual service request.
Action	Look for previously logged message indicating that message Id was not used.

0050.0025	**Mediator encountered an exception: {0}. No error handlers found - [Message Dropped]**
Explanation	This could be a configuration problem. An exception was encountered while attempting to handle a fault. The associated exception message should include more details regarding the problem.
Action	Fix the configuration, or other problem identified by the exception message.

0050.0029	**VSD with incorrect Namespace:{0}. Unable to create PGService.**
Explanation	The namespace found in the VSD is unknown.
Action	This is a virtual service configuration problem.

0050.0031	**The {0} element is required for a Mediator Service**
Explanation	Some element used during service deployment was found to be null. The specific element should be identified in the message text.
Action	This is a virtual service configuration problem.

0050.0032	**The {0} sequence element is required for a Mediator Service**
Explanation	The VSD is missing the sequence element identified in the message.
Action	This is a virtual service configuration problem.

0050.0033	**The inSequence for VSD:{0} is invalid.**
Explanation	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
Action	This is a virtual service configuration problem.

0050.0034	**The outSequence for VSD:{0} is invalid.**
Explanation	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
Action	This is a virtual service configuration problem.

0050.0035	**Exception while parsing Virtual Service String Definition:{0}**
Explanation	An exception was encountered while attempting to parse the virtual service description. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0036	**Unable to create Virtual Service Definition**
Explanation	Unable to create XML object from the VSD string.
Action	This is a virtual service configuration or deployment problem.

0050.0037	**PGServiceFactory encountered and exception while creating the PGService: {0}**
Explanation	An exception was encountered while attempting to validate input or output sequence or during WSDL URI processing. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0038	**Invalid parameter specified for PGService: {0}**
Explanation	The attribute named in the message has no value in the VSD.
Action	This is a virtual service configuration problem.

0050.0039	**Exception {0} for PGService: {1}**
Explanation	An exception was encountered while attempting during service creation. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0040	**No PGService found with name: {0}**
Explanation	Attempting to undeploy or get endpoints for a service that does not exist.
Action	Make sure the virtual service exists before operating on it.

0050.0041	**WSStack exception processing service: {0} Cause: {1}**
Explanation	An AxisFault was encountered while attempting to either undeploy or get endpoints for the virtual service named in the message. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0042	**Unable to locate the WSStack configuration. Can't deploy Virtual Service:{0}**
Explanation	The Synapse configuration cannot supply an Axis configuration.
Action	This is an Axis2/Synapse/WS-Stack configuration problem.

0050.0043	**A Virtual Service with name:{0} already exists. Unable to deploy.**
Explanation	Cannot deploy an Axis service when one already exists with the same name.
Action	Undeploy the existing service before attempting to redeploy or use the same name.

0050.0044	**Unable to locate WSStack configuration. Please check if WSStack is enabled/correctly configured.**
Explanation	Unable to retrieve the configuration context supplier bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.

0050.0045	**Invalid parameter passed for Virtual Service creation:{0}**
Explanation	An attempt to persist the VSD for a service found a null element. The VSD is not allowed to be null.
Action	This may be the result of invalid deployment payload; fix the VSD.

0050.0046	**Unable to persist VSD:{0} to disk. Encountered error:{1}**
Explanation	An exception was encountered while attempting to serialize the VSD for the service identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0047	**Unable to {0} VSD:{1}. Error:{2}**
Explanation	This message is used in several different error conditions, as indicated by the object of 'unable to...'.
Action	Fix the 'unable to...' problem for the service identified by 'VSD:'.

0050.0048	**Error getting endpoints for service:{0}, Cause: {1}**
Explanation	An exception was encountered while attempting to get endpoints. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0049	**Exception while creating PGService: {0}, Cause: {1}**
Explanation	An AxisFault was encountered while checking if deploying service already exists or while attempting to register service with Axis2. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0050	**Error while engaging module: {0}**
Explanation	An AxisFault was encountered while attempting to engage the Axis2 module indicated in the message. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0052	**Axis was unable to load module {0}**
Explanation	An exception was encountered while attempting to load and engage module identified in message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0053	**Loading the WSDL : {0}**
Action	Info level message, no action required.

0050.0055	**PGService {0} encountered error while converting wsdl element to a StreamSource:{0}**
Explanation	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0057	**Unknown WSDL format for PGService:{0}, neither WSDL 1.1 nor WSDL 2.0**
Explanation	The current WSDL element has unknown or no namespace associated.
Action	This is a virtual service configuration problem.

0050.0060	**Populating SOAP service using WSDL**
Action	Info level message, no action required.

0050.0061	**Unable to find a WSDL for the PGService:{0}. Assuming a POX or Legacy service**
Action	Info level message, no action required.

0050.0062	**PGService: {0} is available on transports {1}**
Action	Info level message, no action required.

0050.0063	**Adding PGService:{0} to the SOAP Stack**
Action	Info level message, no action required.

0050.0064	**Removing PGService:{0} due to error: axisFault.getMessage()**
Action	Info level message, no action required.

0050.0065	**Exception while setting policy on PGService:{0}**
Explanation	An exception was encountered while attempting to engage WS-Policy module. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0066	**Setting Policy with id:{0} on Mediator Service:{1}**
Action	Info level message, no action required.
0050.0068	**Successfully created service in SOAP Stack for PGService:{0} containing {1} endpoint(s).**
Action	Info level message, no action required.
0050.0069	**Error{1} on setting parameter :{0} on Mediator Service**
Explanation	An exception was encountered while attempting to set a parameter into an Axis service. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0070	**creating new Mediator Service: {0}**
Action	Info level message, no action required.
0050.0071	**Unable to find service directory for service {0}**
Explanation	Unable to persist WSDL assets because the virtual service directory does not exist.
Action	Redeploying the virtual service should create the service directory.
0050.0074	**Error: {0} while reading from file {1}**
Explanation	An exception was encountered while attempting to read the proxy file identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0076	**Scheduled task[{0}] with startup delay of {1} ms and interval of {2} ms**
Action	Info level message, no action required.

0050.0077	**Error initializing JMS transport listener. Cause: {0}**
Explanation	An exception was encountered while attempting to register JMS listener. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0078	**Unable to stop TransportListener called:{0}. Exception:{1}**
Explanation	An AxisFault was encountered while attempting to stop the JMS transport listener during bean initialization. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0083	**Error {0} occurred while updating the load balancer properties**
Explanation	An AxisFault was encountered while attempting to add load balancer URL to an Axis transport description. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0084	**Loadbalanced Endpoint: [{0}] failed!**
Explanation	A mediation operation to a load balanced endpoint has failed. The endpoint indicated in the message is not available. This usually indicates a communication problem with the targeted server.
Action	Fix the targeted server.

0050.0086	**Unable to get the IS keystore manager - please check your configuration!**
Explanation	Unable to retrieve the keystore manager bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.

0050.0087	**Keystore initialization failed! Please check the server log for more details**
Explanation	Unable to load the keystore file.
Action	This is a Mediator security configuration problem.

0050.0088	**Truststore initialization failed! Please check the server log for more details**
Explanation	Unable to load the truststore file.
Action	This is a Mediator security configuration problem.

0050.0089	**Unable to get the Rampart Configuration Handler - please check your configuration!**
Explanation	Unable to retrieve the Rampart creation handler bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.

0050.0099	**VSD proxy loader, Unable to delete file: {0}**
Explanation	The file or directory indicated in the message could not be deleted.
Action	Determine why the file or directory could not be deleted and make it deletable.

0050.0100	**VSD proxy loader, Unable to delete directory: {0}**
Explanation	The directory indicated in the message could not be deleted.
Action	Determine why the directory could not be deleted and make it deletable.

0050.0101	**VSD proxy loader, Unable to create directory: {0}**
Explanation	The file or directory indicated in the message could not be created.
Action	Delete the directory so that Mediator can create it again.

0050.0105	**Unable to determine fault cause. Please check the log file for more information!**
Explanation	This error indicates that Mediator could not determine the cause for the error when trying to extract the soap fault message from the response. Additional errors if any would be present in the IS log file (server.log)

0050.0208	**Error resolving WSDL URI. Cause {0}**
Explanation	An exception was encountered while attempting to resolve URI elements into XML source. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0209	**Error initializing virtual service factory. Cause: {0}**
Explanation	An exception was encountered while attempting to initialize XPath elements. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0210	**Error setting location of virtual service proxies directory. Path: {0} Cause: {1}**
Explanation	An exception was encountered while attempting to use the directory identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0211	**Unable to determine service endpoint URI for this service: {0} No transport listener defined for the virtual service's transport protocol.**
Explanation	The configuration context's listener manager cannot find an endpoint for the current service. This may indicate that the hosting IS does not have an appropriate listener registered.
Action	This is a configuration problem, either in IS ports or VSD

0050.0212	**Unknown exception deploying virtual service: {0} Cause: {1}**
Explanation	An exception was encountered while attempting to get an endpoint reference from the context listener manager. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0214	**Error {0} manifest from external resources associated with virtual service: {1}. Cause: {2}**
Explanation	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0215	**Error initializing virtual service transformation bean with this xslt: {0} Cause: {1}**
Explanation	An exception was encountered while attempting to read the transformation file. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0216	**Error transforming raw virutal service string. Cause: {0} virtual service xml: {1}**
Explanation	An exception was encountered while attempting to read the Mediator's transformation file. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0221	**Mediator has an internal configuration error. It's deploy-time xslt transformation file path does not exist. Path: {0}**
Explanation	An exception was encountered while attempting to read the file identified in the message. The associated exception message should include more details regarding the problem.
Action	This is a configuration problem; make sure the file identified in the message exists and contains the transformation.

0050.0250	**Could not find user-specified value for HTTP method! Defaulting to inbound request HTTP method {0}**
Explanation	The 'routing method' context variable has an invalid value.
Action	If the value indicated in the message is acceptable, no action is required. Otherwise virtual service configuration must be changed.

0050.0252	**Could not set HTTP method for outgoing request for endpoint: {0}**
Explanation	The outgoing request's message context is null.
Action	This is a virtual service/policy configuration problem.

0050.0300	**Context variable name "{0}" is already declared. Multiple declarations in the same context is not allowed.**
Explanation	Context variable names must be unique for a service.
Action	This is a service configuration problem.

0050.0303	**Attempt to reference context variable without providing a message context. Custom context variables may only be declared with a 'session' scope at this time. Other scopes are not supported.**
Explanation	Attempting to get context variable or context variable map, but the message context (or session) is null.
Action	Earlier error messages should provide clues to help determine why a valid message context is null.

0050.0306	**Context variable name is required for variable declaration.**
Explanation	Variable name validation failed, QName is null or is missing a local part.
Action	This is a context variable configuration problem.

0050.0307	**Namespace URI and prefix is required for custom variable declaration. varName: {0}**
Explanation	Variable name validation failed, Namespace URI and prefix must both be neither null nor empty.
Action	This is a context variable configuration problem.

0050.0308	**Context variable name must be a valid identifer (alpha-numeric, $, or _ permitted) Found: {0}**
Explanation	Variable name validation failed, name has invalid characters.
Action	This is a context variable configuration problem.

0050.0309	**Core Context variables cannot have a namespace or prefix as part of its declaration. varName: {0}**
Explanation	Variable name validation failed, prefix for core variables must be empty.
Action	This is a context variable configuration problem.

0050.0310	**Either a Message context or axis service name is required when creating a custom context variable. varName: {0}**
Explanation	Both service name and Axis2 message context are null, this is not acceptable. This is probably the result of attempting to deploy a service with no service name.
Action	Verify that service configuration is correct.

0050.0311	**Attempt to create a custom variable using a message context with no AxisService. varName: {0}**
Explanation	The axis2 message context is corrupted, it should identify a service.
Action	Earlier error messages should provide clues to help determine why a valid message context could not be created.

0050.0312	**Unexpected error creating custom Mediator context variable. varName: {0} reason: {1}**
Explanation	An exception was encountered while attempting to create a custom context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0313	**Unexpected error removing custom Mediator context variable for service: {0} reason: {1}**
Explanation	An exception was encountered while attempting to remove or inject a custom context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0314	**Unexpected error initializing core Mediator context variables. reason: {0}**
Explanation	An exception was encountered while attempting to create a context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0316	**Unexpected error getting Mediator context variable value. varName: {0} reason: {1}**
Explanation	An exception was encountered while attempting to get the valuue of the context variable named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0317	**Unexpected error setting Mediator context variable value. varName: {0}, value:{1}, reason: {2}**
Explanation	An exception was encountered while attempting to set the context variable value named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0318	**Expected a virtual service name for this method operation, but none was provided.**
Explanation	Attempting to get context variable map for a null service name.
Action	Earlier error messages should provide clues to help determine why a valid service name is null.

0050.0321	**Mediator context variable adapter unable to locate this type: {0}**
Explanation	The context variable type indicated in the message is unknown.
Action	This is a context variable configuration problem.

0050.0322	**Unexpected error getting core Mediator context variable value from adapter. type: {0}**
Explanation	An exception was encountered while attempting to get the context variable value named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0323	**Only string and int schema types are supported at this time. Type: {0}, declared with "{1}" context variable is not supported.**
Explanation	The context variable schema type is not among the accepted types.
Action	This is a service configuration problem.
0050.0324	**Context variable name declarations cannot contain $ sign symbols in the name since that is used as a reference operator. varName: {0}**
Explanation	Variable name validation failed, name must include substitution character, (dollar sign).
Action	This is a context variable configuration problem.
0050.0325	**Unable to return list of context variables declared for this service: {0} Reason: {1}**
Explanation	An AxisFault was encountered while attempting to retrieve a list of context variable names. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0326	**Unable to return list of context variables declared for this message context: {0} Reason: {1}**
Explanation	An AxisFault was encountered while attempting to get a list of context variables or list of variable keys. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0327	**Context variable name deployed with virtual service {0} references an unknown namespace prefix. name attribute: {1}**
Explanation	Context variable identified in message has invalid namespace.
Action	This is a context variable configuration problem.

0050.0328	**Exception while copying context variables from request to response message context. Reason: {0}**
Explanation	An AxisFault was encountered while attempting to copy context variable names between contexts. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0329	**Could not create backup directory for failed services! Dir tried = {0}**
Explanation	An attempt to create the 'failed services' directory has failed.
Action	Determine why the directory could not be created. Either fix the creation problem or specify a different directory.

0050.0331	**Error occurred when getting backup directory for path {0}**
Explanation	An exception was encountered while attempting to determine directory for backing up failed services. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0333	**Error occurred while resolving URI; message = {0}**
Explanation	An exception was encountered during URI resolution. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0337	**Previously selected {0} port {1} is no longer enabled or available!**
Explanation	The message indicates port number and type. The requested port is not available.
Action	Select a new port number for the indicated port type.

0050.0343	**Context variable API expected an IData object for ctx variable, {0}, but received this: {1}**
Explanation	The data element from which a context variable is to be extracted has an unknown data type.
Action	This is probably a flow configuration problem; where the pipeline was populated with an invalid value.

0050.0344	**Attempt to insert {0} core ctx variable with invalid value type: {1}. Expected a collection of this type: {2}**
Explanation	.The allowable data type for a core context variable is restricted, depending on variable type.
Action	.This is a context variable configuration problem.
0050.0345	**Unable to access array element [{0}] in SOAP_HEADERS core ctx variable. Cause: {1}**
Explanation	The index value indicated in the message must be numeric.
Action	This is a context variable configuration problem.
0050.0346	**Invalid array or key reference for core ctx variable. This substitution string has mismatched braces: {0}**
Explanation	The context variable substitution string is invalid, mismatched brace characters were found.
Action	This is a context variable configuration problem.
0050.0347	**Attempt to create an IData value for a ctx variable from an unsupported class type. CtxVar: {0} Bad type: {1}**
Explanation	The context variable to be converted to IData has an unknown data type.
Action	This is a context variable configuration problem.
0050.0348	**Unable to append header block to the end of the soap header. Cause: {0}, soapHeader element: {1}**
Explanation	An exception was encountered while attempting to add append new SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0349	**Unable to prepend header block to the beginning of the soap header. Cause: {0}, soapHeader element: {1}**
Explanation	An exception was encountered while attempting to add prepend new SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0350	**Unable to remove header block from the soap header. Cause: {0}, soapHeader: {1}**
Explanation	An exception was encountered while attempting to remove a SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0351	**Unable to set header block at position {0} of the soap header. Cause: {1}, soapHeader element: {2}**
Explanation	An exception was encountered while attempting to replace a SOAP header block with a new one. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0355	**Could not create STS configuration directory! Dir tried = {0}**
Explanation	The file or directory indicated in the message could not be created.
Action	Delete the directory so that Mediator can create it next time it is required.

0050.0357	**Error occurred when getting STS configurations directory for path {0}**
Explanation	An exception was encountered while attempting to create the directory indicated in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0362	**Error occurred when creating STS client**
Explanation	An exception was encountered while attempting to create an STS client object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0364	**Error occurred when initializing default STS configuration store**
Explanation	An exception was encountered while attempting to create JAXB marshaller/unmarshaller pair. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0365	**Could not find STS configuration file with path {0}**
Explanation	An attempt to delete the file indicated in the message failed because the file does not exist.
Action	Check this directory [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] to make sure there is an xml file with the STS config name being deleted. For e.g. if the STS config being deleted is MySTS, then there should be an XML file called MySTS.xml in the mentioned directory

0050.0366	**Could not delete STS configuration file with path {0}**
Explanation	An attempt to delete the file indicated in the message returned 'false'. The file was not deleted.
Action	Make sure the STS config file present under [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] is present and not locked by any other application (e.g. opened in an editor like Windows Notepad). Check the log file to see if there is any java IOException related to disk errors.

0050.0367	**Error occurred when saving STS configuration to disk**
Explanation	An exception was encountered while attempting to marshal configuration object into file. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0368	**Error occurred when reading STS configuration from file {0}**
Explanation	An exception was encountered while attempting to unmarshal configuration file indicated in the message into JAXB object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0371	**Error getting IS keystore manager instance!**
Explanation	An exception was encountered while attempting to get a reference to the keystore manager. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0373	**Error occurred when adding rampart configuration to STS policy**
Explanation	An exception was encountered while attempting to configure the STS policy. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0379	**Error occurred when adding assertion to STS policy**
Explanation	An exception was encountered while attempting to add an assertion to a WS-Policy artifact. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0382	**Error occurred when adding OnBehalfOf element to WS-Trust request element**
Explanation	An exception was encountered while attempting to add the WS-Trust element to a request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0383	**Error occurred when sending WS-Trust request to STS to obtain SAML assertion**
Explanation	An exception was encountered while attempting to add SAML assertion to pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0384	**Could not find required property {0} for SAML sender-vouches action!**
Explanation	The pub.mediator.security.ws.AddSamlSenderVouchesToken ESB service is missing the required 'ConfigName' input value
Action	Make sure that the 'ConfigName' service input has a valid STS config name (must match one of the configured STS names)

0050.0386	**Could not find any STS client configuration with name {0}. Check to see if such an STS configuration exists!**
Explanation	This error occurs if the configured ESB service that calls the pub.mediator.security.ws.AddSamlSenderVouchesToken specifies the STS config name incorrectly.
Action	Check if the specified STS config name matches one of the configured STSs in Mediator. The "ConfigName" service input value should be the same name (case-sensitive) as the STS name specified in Mediator Admin configuration page

0050.0388	**Could not get SAML assertion from STS!**
Explanation	A null assertion element was found in the STS client.
Action	Mediator sent a request to the configured STS to obtain a SAML assertion, but no valid assertion was obtained by the client. Please check the log file for any errors related to sending the WS-Trust request to the STS to obtain the token.
0050.0389	**Adding OnBehalfOf element in WS-Trust request for IS user {0}**
Action	Info level message, no action required.
0050.0390	**Could not find base STS policy file: {0} !**
Explanation	An exception was encountered while attempting to load a WS-Policy artifact from the file indicated in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0391	**Error occurred when getting STS configurations! Check to see if the ISTSClientConfigManager bean is configured!**
Explanation	The STS configuration manager bean could not be found.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0392	**Could not find any STS configuration with the name {0}**
Explanation	The STS client configuration identified in the message to be loaded or deleted could not be found.
Action	Verify that the STS configuration being loaded or deleted has an equivalent configuration file present under [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] directory. E.g. if the configuration being deleted is called MySTS, then there should be a file with name MySTS.xml in the mentioned directory
0050.0394	**Error occurred when getting key aliases for keystore {0}: Error: {1}**
Explanation	An exception was encountered while attempting to add a list of certificate aliases to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0395 **Error occurred when getting keystore handles {0}**

Explanation An exception was encountered while attempting to add a list of keystore handles to the pipeline. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0396 **Error when signing SAML assertion and SOAP request body**

Explanation An exception was encountered while attempting to sign a SAML assertion and request body. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0397 **Error occurred when adding ws-addressing headers to outbound soap request; Error: {0}**

Explanation An exception was encountered while attempting to add WS-Addressing headers. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0400 **Using default timestamp value of 300s, because input TTL {0} is invalid (-ve or too big)**

Explanation The input value was not valid, a default was used.

Action If the default is acceptable, no action is required. Otherwise update the configuration.

0050.0507 **ScaDeploymentPayload.extractParts found no virtual service requests**

Action Info level message, no action required.

0050.0508 **Unexpected exception, attempting to {0}, caught: type({1}), msg({2})**

Explanation An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0509 **ScaDeploymentPayload.extractParts - Unable to find consumer file {0}, for component {1})**

Explanation The SCA deployment package was expected to contain a file to define the consumer identified in the message. The file was not found.

Action This is a deployment payload construction problem.

0050.0510	**Unexpected exception, attempting to process {0} request, caught: type({1}), msg({2})**
Explanation	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0515	**ScaCompositeConfiguration found component with implementation type ({0})**
Action	Info level message, no action required.
0050.0516	**{0} - unable to convert string ({1}) to XMLGregorianDate: exception message ({2})**
Explanation	The date element from the deployment payload has an unexpected format.
Action	This is problem with the contents of the deployment payload.
0050.0517	**DeploymentPayload.{0} - input pipeline does not contain expected key ({1})**
Explanation	The deployment payload must include an element with the key indicated in the message.
Action	This is problem with the contents of the deployment payload.
0050.0519	**ScaDeploymentPayload - unable to delete temporary zip file: ({0})**
Explanation	The file indicated in the message could not be deleted.
Action	Determine why the file could not be deleted and make it deletable.
0050.0520	**DeploymentPayload - invalid request type: {0}**
Explanation	The deployment payload type is unknown.
Action	This is a deployment payload construction problem.
0050.0528	**DeploymentPayload - found null/empty virtual service descriptor for service {0}**
Explanation	The deployment payload must contain a VSD. The VSD for the service identified in the message was not found.
Action	This is a deployment payload construction problem.
0050.0603	**Error occurred when adding UsernameToken to SOAP Envelope: {0}**
Explanation	An exception was encountered while attempting to add username token to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0605	**Error occurred when adding X.509 token to SOAP Envelope: {0}**
Explanation	An exception was encountered while attempting to add X509 token to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0630Debug	**DeploymentPayload - No update requests for the runtime aliases being deployed**
Explanation	Mediator did not receive any update requests for the runtime aliases being deployed.
Action	Check the update request for runtime aliases.

0050.0632Error	**Mediator does not support the runtime alias. Alias type: {0}**
Explanation	Mediator was not able to find a runtime alias of the specified type.
Action	Check the alias type assigned to the runtime alias.

0050.0670Error	**Resources for the endpoint URI not found. Endpoint URI: {0}**
Explanation	Mediator does not have REST resources configured with the specified URI.
Action	Check the configuration of the virtual REST service to ensure that the required resources are configured.

0050.0677	**Error while processing the REST to SOAP transformation in Mediator. The JSON string in the request is empty.**
Explanation	Mediator expects a non-empty JSON string in the request message.
Action	Check if the JSON request string is valid, and try again. Contact your system administrator for details if the issue persists.

0050.0678	**Mediator could not complete the transformation of a REST request received from the consumer to a SOAP request because of an error. JSON string:{0}. {1}**
Explanation	Mediator encountered an error while converting the JSON request to a SOAP request as part of the conversion of the REST request to a SOAP request.
Action	Check if the JSON request string is valid and try again. Contact your system administrator for details if the issue persists.

0050.0679	**Mediator could not complete the transformation of a REST request received from the consumer to a SOAP request because of an error. {0}**
Explanation	Mediator encountered an error while converting the multi-part REST request to SOAP request as part of the conversion of the REST request to SOAP request.
Action	Check if the attachments in the multi-part request are valid.

0050.0680	**Mediator could not complete the transformation of a REST request received from the consumer to a SOAP request because of an error. JSON string: {0}. {1}**
Explanation	Mediator encountered an error while converting the JSON string sent as an attachment to a SOAP request as part of the conversion of the REST request to a SOAP request.
Action	Check if the JSON string in the attachment to the SOAP request is valid.

0050.0681	**Mediator could not complete the transformation of a REST request received from the consumer to a SOAP request because of an error. {0}**
Explanation	Mediator encountered an error while parsing the schema in WSDL file, which leads to namespaces not being placed properly in the SOAP request when the REST to SOAP transformations are processed.
Action	Check the schema of the WSDL file provided in the native SOAP service.

0070.0081	**[{0}] Removing the Content-Encoding header in response as the Accept-encoding is null**

0070.0094	**[{0}] --> Incoming Request Header does not contain a valid OAuth token.**
Explanation	User has configured OAuth authenticaton scheme but OAuth token is not present in the request.
Action	Ensure that the request has an authorization header with OAuth token in it.

0070.0172	**Found duplicate target namespace [{0}], enabling namespace-growth for schema validation**
Explanation	This flag will be auto enabled when duplicate target namespaces found in the schema definition otherwise it will be false by default.
Action	User can enable/disable this flag by setting true/false to pg.schema.validation.namespacegrowth property.

010.0787Error	**Could not load information on runtime aliases to Mediator. File not found {0}**
Explanation	Mediator could not find the file containing information on the runtime aliases.
Action	Check if the file is present in the specified location.

010.0788Error	**Error loading aliases from file store :{0}, {1}**
Explanation	Mediator encountered an error while loading the aliases from the file store.
Action	Check if the file store exists in Mediator and is valid.

010.0790	**Error saving runtime aliases to the file store: {0}. {1}**
Explanation	Mediator encountered an error while saving the aliases from the file store.
Action	Check if the file store exists in Mediator and is a valid file store.

010.0792Error	**Runtime alias not added to the file store: {0}**
Explanation	Mediator is not able to add the runtime alias to the file store.
Action	Check the Integration Server log for more details

0201.0049	**No Certificate was sent over HTTPS transport**

0203.0323Error	**Error parsing alias service names file. {0}**
Explanation	Mediator cannot parse the alias service names file.
Action	Check the Integration Server log for details. Redeploy the aliases and the associated services after you have fixed the issues in the alias service names file.

0203.0324Error	**Error loading the service names associated with the alias to memory. {0}**
Explanation	Mediator cannot parse the alias service names file.
Action	Check the Integration Server log for details.

0203.0325Error	**Error saving the service names associated with the alias to the file store. {0}**
Explanation	User may not have permission to write to the file, or the file may not be in the disk.
Action	Check the Integration Server log for details.

0203.0326Debug error – RuntimeAliasesCache - Null references to aliases found. Could not load the runtime alias cache.

Explanation	Mediator found null references to aliases.
Action	Check the cluster configuration in Integration Server and also ensure that there are no null elements in the cache.

MED.0010.0062E	**Unable to get password for callback identifier: {0}**
Explanation	Error while retrieving cleartext password from encrypted passman file store.
Action	Review Mediator STS configuration; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0010.0083W	**Non-fatal Mediator package initialization error. {0}, {1}**
Explanation	Mediator encountered an error during an upgrade processing step after the package initialization completed.
Action	Verify the overinstall upgrade steps were followed as defined in the documentation; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0010.0212E	**Endpoint connection timeout duration expected as a number but was not a number ({0})**
Explanation	A virtual service was deployed with an invalid connection timeout specified for its native provider endpoint.
Action	Review the advanced endpoint configuration in CentraSite and redeploy the service if necessary.

MED.0010.0214E	**Both keystore and key alias must be specified or none at all for SSL configuration; KeyStore alias = [{0}]; Key alias = [{0}]**
Explanation	A virtual service with a native provider SSL endpoint was deployed with an invalid advanced endpoint configuration. The endpoint must have a valid alias for both the keystore file and the keystore entry aliases as defined in the Integration Server or it can have no aliases defined at all.
Action	Update the advanced endpoint configuration and redeploy the virtual service to Mediator.

MED.0010.0217E	**Error occurred when getting the password for handle {0} from passman!**
Explanation	An attempt to retrieve a cleartext password from a passman encrypted file store failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0010.0218E	**Error occurred when storing the password for handle {0} in passman!**
Explanation	An attempt to save a password in a passman encrypted file store failed during Mediator STS configuration.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0010.0220E **Error converting given WS-Policy component to string**

Explanation Mediator was unable to parse policy elements used in producing request security tokens (RST) to a configured security token service (STS).

Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0010.0228E **Endpoint read timeout duration expected as a number but was not a number ({0})**

Explanation A virtual service was deployed with an invalid read timeout specified for its native provider endpoint.

Action Review the advanced read configuration in CentraSite and redeploy the service if necessary.

MED.0010.0702E **Mediator Upgrade, Mediator migration interrupted due to error. Details: {0}**

Explanation This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. It indicates the upgrade was not successful and further actions are required.

Action Depending on the error message, one of the three options are available. 1) Resolve the issue causing the upgrade to fail, and restart the Integration Server again to see if the upgrade completes successfully. 2) Delete the mediatorUpgrade.xml file from installation path: ${IS_HOME}/packages/WmMediator/ directory. This is the file that causes Mediator to perform its upgrade step. If this action is taken, the Mediator configuration will have to be re-entered manually through the IS admin UI. 3) Contact support. Everytime the Integration Server is restarted, Mediator will attempt to perform an upgrade as long as its mediatorUpgrade.xml file is present in the package directory.

MED.0010.0705E **Mediator Upgrade, mediatorUpgrade.xml file is corrupted. Expected 'properties' root element but none found.**

Explanation This message indicates the mediatorUpgrade.xml file included after the installer completes a Mediator overinstall is corrupted. This file is normally installed into the ${IS_HOME}/packages/WmMediator/ directory path when the overinstall completes. Its presence causes Mediator to run its upgrade tasks during the next Integration Server restart. Once the upgrade task has completed, this file is removed ensuring the upgrade is run only once.

Action Contact customer support or remove the mediatorUpgrade.xml file. The mediator package should load without error during the next Integration Server restart if this file is removed, but Mediator configuration must be set up manually through the IS admin UI.

MED.0010.0706E	**Mediator Upgrade, unable to read required file. {0}**
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. This message implies that the OS user running the Integration Server does not have adequate permissions to read the file referenced in the error message.
Action	Review user and file permissions and make necessary adjustments to ensure the file can be read.

MED.0010.0707E	**Mediator Upgrade, configuration file is missing a required entry element key attribute. {0}, File path: {1}**
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file used to control a Mediator overinstall upgrade is corrupted. It is missing a reference to an attribute containing a path to an archive of the previous Mediator version prior to the overinstall.
Action	Contact support.

MED.0010.0708E	**Mediator Upgrade, configuration file entry element key attribute: {0}, expected this value: {1}, but found: {2}, File path: {3}**
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file used to control a Mediator overinstall upgrade is corrupted.
Action	Contact support.

MED.0010.0709E	**Mediator Upgrade, unable to find the required file. Expected location: {0}**
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The backup file archive containing the Mediator package prior to the overinstall upgrade cannot be found.
Action	Contact support.

MED.0010.0711E	**Mediator Upgrade, unable to delete configuration file. Mediator upgrade task will continue to execute after each Integration Server startup until this file is removed. Path: {0}**
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. Verify that the OS user account running the Integration Server has the necessary permissions to delete the file.
Action	If the log messages suggest the upgrade ran successfully, this file can be deleted; otherwise, contact support.

MED.0010.0712E	**Mediator Upgrade, configuration file is not valid xml. Unable to parse it. {0}, Details: {1}**
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file is corrupted.
Action	Contact support.

MED.0010.0717W	**Mediator Upgrade, Could not find Default STS configuration file: {0} in archived zip file**
Explanation	The default STS configuration file was not found when performing an overinstall upgrade.
Action	No action is necessary if migrating from Mediator 8.0; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0010.0718E	**Mediator Upgrade, configuration file has unexpected element key attribute, {0}, with value. {1}, and configuration file path: {2}**
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file is corrupted.
Action	Contact support.

MED.0010.0719E	**Mediator Upgrade, Could not find Default STS configuration file: {0} following upgrade; Skipping migrating configuration data!**
Explanation	Mediator was unable to locate the default STS configuration file during an overinstall upgrade.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0010.0720W	**Mediator Upgrade, Could not load Default STS client configuration; Skipping migrating configuration data**
Explanation	The default STS configuration file was not found when performing an overinstall upgrade.
Action	No action is necessary if migrating from Mediator 8.0; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0050.0408E	**Authentication failed for user {0}**
Explanation	Invalid basic authentication credentials were included in the Authorization header sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
Action	The web service consumer should include proper credentials and resend the service request.

MED.0050.0608E	**Error occurred when adding Timestamp to SOAP Envelope: {0}**
Explanation	Mediator was unable to insert a WS security timestamp element to the request's security header sent to the native provider.
Action	Review the configured ESB "AddTimestamp" service call for virtual service and redeploy if incorrect. Otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0070.0010E	**Incoming request does not contain the 'Authorization' header. This service requires the HTTP Basic Authentication token to be present.**
Explanation	Authorization header was not sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
Action	The web service consumer must include valid credentials and resend the service request.

MED.0070.0032E	**Unable to create Schema for this service "{0}" Schema validation may not succeed!**
Explanation	Mediator was unable to initialize the schema parser for a virtual service with a "Validate Schema" runtime policy. This error occurs when a consumer sends Mediator a service request.
Action	Review the schemas defined in the virtual service, make corrections, and redeploy the virtual service if necessary; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0070.0071W	**The ESB service name specified for InvokeESB mediator cannot be empty!**
Explanation	A virtual service was deployed containing an ESB service invocation step containing an invalid or missing service name.
Action	Review all service invocations from the "Processing steps" configuration for the virtual service and redeploy if necessary.

MED.0070.0072E **The 'service' attribute is required for the InvokeESB mediator definition**

Explanation The deployed virtual service configuration is corrupted.

Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0200.0045E **Error saving EhCache configuration file: {0}**

Explanation Mediator was unable to save its configuration file used for the Terracotta cache component.

Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0200.0046E **Could not find specified EhCache configuration file: {0}**

Explanation The Terracotta cache configuration file for Mediator's caches could not be found during package startup.

Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0062E **ControllingNodeLocker.run, thread id({0}), expected Ehcache, found ({1})**

Explanation Unexpected content was returned in the Terracotta cluster status cache.

Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0065E **ControllingNodeLocker.run, thread id({0}), caught ({1}/{2}) attempting to get a lock, thread dies**

Explanation Mediator encountered an error trying to obtain a lock on the controlling node in a Terracotta cluster.

Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0070I	**ClusterStatusCache - cache manager for {0} returned null CacheCluster reference, not clustered?**
Explanation	Mediator was unable to obtain a reference to the configured Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0071I	**{0} - getCluster(ClusterScheme.TERRACOTTA) threw exception {1}, using schema NONE**
Explanation	An attempt to get Terracotta cluster configuration details failed.
Action	If Mediator is configured for a Terracotta cluster, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0072E	**ClusterStatusCache - thread id({0}) attempts to release {1} lock, but does not hold it**
Explanation	An attempt to release the lock on the node controller in a Terracotta cluster failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0073E	**Error initializating JAXB Context: {0}**
Explanation	Initialization for the cached global or registered consumers deployed to Mediator has failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0075E	**ControllingNodeLocker.run, thread id({0}), caught {1} attempting to ask about lock status, thread dies**
Explanation	The thread defining the controlling node in a Mediator cluster encountered an error.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0076E	**Unable to get cache named {0} from cache manager {1}**
Explanation	Mediator encountered an error accessing one of the Terracotta caches.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0081E	**{0}, thread id({1}), caught {2}/{3} attempting to release lock, thread dies**
Explanation	Mediator encountered an error releasing the lock on the controlling node in the Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0082E	**EhcacheClusterStatusCache, thread id({0}), caught {1}/{2} attempting to update controlling lock in cache**
Explanation	Mediator encountered an error updating the controlling node in a Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0100W	**Thread interrupted when trying to obtain {0} lock for cache {1}**
Explanation	While Mediator was attempting to obtain a lock on a cache entry key, its thread was interrupted.
Action	No action may be necessary if Mediator is functioning normally.

MED.0203.0101E	**Unable to {0} lock the {1} cache for key {2} after waiting {3} mSecs**
Explanation	Mediator failed to lock a cache key in the expected period of time.
Action	No action may be necessary if Mediator is functioning normally

MED.0203.0103E	**{0} task in thread {1} threw this: {2}**
Explanation	An error occurred in the controlling node of a Terracotta cluster during Mediator shutdown.
Action	Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0205.0062E	**UddiPerformanceMetricsSender - unable to publish metrics over UDDI for service: {0}, message: {1}**
Explanation	This log message is produced when Mediator is unable to publish performance metrics results to Mediator. When revieiwng the content, please be aware that some exception details may have originated from the CentraSite product hosting the UDDI server. Errors can range from improper Mediator configuration, OS resource issues, network connectivity, or issues with the CentraSite installation.
Action	Depending on the errors logged in the Mediator UI, one of the following actions may prove more relevant. Verify CentraSite configuration information regarding UDDI is correct for the Mediator UI. Verify the hostname or IP address is reachable from the computer running the Mediator instance. Verify the CentraSite instance and its repository is up and accessible.

MED.0205.0063E	**Unable to initialize UddiClientAdapter due to a missing password for username: {0}.**
Explanation	This log message is produced when Mediator is unable to publish performance metrics results to Mediator. A password was not found in the encrypted store for the user configured in the CentraSite panel of the Mediator UI.
Action	Verify the password is entered and the configuration was successfully saved for the CentraSite configuration screen in the Mediator UI.

MED.0205.0064E	**Error connecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}**
Explanation	This log message may be produced under the following situations: During Mediator package startup. CentraSite configuration entered in Mediator UI is saved, but a connection to the UDDI server fails for these settings. Mediator attempts to publish performance metrics but fails during its regularly scheduled interval.
Action	Verify the CentraSite configuration values in the Mediator UI are correct and CentraSite is up and running.

MED.0205.0067E	**Error disconnecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}**
Explanation	This log message may be produced during the following situations: During Mediator package shutdown. While Mediator is initializing communications with the CentraSite UDDI server after encountering an error during runtime or saving configuration values in the Mediator UI.
Action	Please see the Action for 0205.0064

MED.0205.0602E	**Missing "{0}" Jdbc destination pool from spring configuration**
Explanation	One of the Mediator configuration files is corrupted and a necessary configuration element is missing.
Action	Contact support.

MED.0205.0603E	**Jdbc destination sender expected a JdbcEvent object but received: "{0}"**
Explanation	The JDBC destination sender event component received an unexpected event type.
Action	Contact Support.

MED.0205.0604E	**Jdbc destination sender encountered a Sql Exception while generating "{0}" events. Error Code: {1} Cause: {2}**
Explanation	The Mediator Jdbc destination sender component encountered a SQL exception while sending a runtime event.
Action	Verfiy the database is operational and restart the functional alias pool. Verify the MediatorEvents database component tables installed using the Common Database Component are still defined, and the Jdbc pool credentials defined in Integration Server are correct. If all else fails, please contact Support.

MED.0205.0605D	**Jdbc destination sender took {0} msecs to get a connection out of data source.**
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to get a Jdbc connection exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.

MED.0205.0606D	**Jdbc destination sender took {0} msecs to get a prepared statement out of connection with this SQL: {1}.**
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to get a Jdbc prepared statement exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.

MED.0205.0609D	**Jdbc destination sender took {0} msecs to close the prepared statement and connection.**
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to close a Jdbc connection exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.

MED.0205.0610E	**Jdbc event requires at least one sql clause to be valid.**
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.

MED.0205.0611D	**Jdbc destination sender took {0} msecs to insert a batch of {1} ''{2}'' events. AutoCommit enabled on driver? {3}, Transaction Isolation level? {4}**
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to execute a batch of runtime event inserts into the database exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 500 milliseconds.
Action	No action is necessary unless the time is extremely large. In that case, consider reducing the 'pg.jdbc.batchSize' property in Mediator's pg-config.properties file. This will cause the Jdbc destination sender to send updates to the database server in smaller batches.

MED.0205.0612E	**Jdbc destination sender cannot use a read-only connection object to insert events.**
Explanation	The functional alias used by Mediator's Jdbc destination sender is configured for a read-only transaction model in the Integration Server admin.
Action	Change the configured transaction model so it supports updates to the database.

MED.0205.0614E	**Jdbc event sql range should be between 0 and {0}, {1} is out of range.**
Explanation	Mediator Jdbc component is in an invalid state.
Action	Contact Support.

MED.0205.0615E	**Jdbc performance metrics processor expected only one return key, but ''{0}'' were found.**
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.

MED.0205.0616E	**Jdbc performance metrics processor expected two SQL statements, but ''{0}'' were found.**
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.

MED.0205.0617E	**Jdbc performance metrics processor is missing returned primary key upon SQL insert**
Explanation	Database did not return the 'event_pk' primary key column for the event inserted into the mediator_metrics_event table.
Action	Verify database is functioning properly; otherwise, contact Support.

MED.0205.0618E	**Jdbc event is in a bad state. Data type count "{0}" does not equal column value count "{1}"**
Explanation	The Jdbc event destination component is in an invalid state.
Action	Contact Support.

MED.0205.0619W	**Jdbc driver doesn't support returned named SQL columns from Insert statement. Trying "Statement.RETURN_GENERATED_KEYS" mode.**
Explanation	The Jdbc event destination component will attempt to use named columns for returning the database-generated primary key after inserting a row. If the database driver does not support this feature, this log message is raised, and the component will use another method to return the inserted primary key.
Action	No action required unless other SQLException errors are raised.

MED.0206.0035W	**MAC cache update {0} operation took {1} milliseconds to complete for {2} SIEs. This could cause lock attempts for tallying metrics statistics in MAC cache to fail.**
Explanation	An update to the policy engine metrics data took longer than expected. When the duration of this task is longer than the configured lock request timeout, tasks can be lost when they fail to obtain exclusive locks.
Action	Review Integration Server performance and increase the advanced property for lock timeout pg.PgMenSharedCacheManager.lockTimeOut and restart IS. Otherwise, if this happens very frequently, contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

20 My webMethods Server Messages

ClassPathComponentsMapper.folder.cannot.read – Cannot read from folder.

Explanation Cannot read from file. The file was deleted with no read rights.

Action Check to see if the file exists and if you have read rights.

ClassPathComponentsMapper.folder.not.exists – The folder does not exist:

Explanation The provided folder does not exist.

Action You must specify an existing folder.

ClassPathComponentsMapper.folder.not.valid – The specified path is not a valid folder.

Explanation The specified path is not valid folder; it might be a file and not a folder.

Action Specify a valid folder path.

Error.POP.0.0.001 **Error sending mail**

Explanation When a forum message is retracted, an e-mail notification is sent to the configured forum administrator. This error occurs if there are any problems sending this e-mail to the administrator.

Action Check the My webMethods Server logs for additional information about the specific e-mail failure. It may be caused by the e-mail server not being available, or because of an invalid forum administrator e-mail address. See Check the My webMethods Server logs for more details. See ..\MWS\server\<serverName>\logs

POP.001.0002E	**A "{0}" occurred with the Message "{1}"**
Explanation	An unexpected error occurred during deployment.
Action	Examine the install.log, and optionally try again. In the log file, look for any information specific to the deployed component.

POP.002.0004E	**Context is in an invalid state.**
Explanation	The server attempted to use an invalid context object. This error is the result of attempting to use a context object before it has been initialized or after it has been uninitialized.
Action	Always use the provider com.webmethods.portal.bizPolicy.IContextProvider (available through the com.webmethods.portal.system.PortalSystem) to acquire a context object.

POP.002.0005E	**Unable to locate command: {0}**
Explanation	The requested command is not deployed on the server.
Action	Log in to My webMethods Server and use the Install Administration portlet to deploy the command to the server.

POP.002.0006E	**Unable to locate biz policy for resource: {0}**
Explanation	The server cannot resolve the business policy for the specified resource because no policy has been registered for the resource type.
Action	Create and register a business policy for the resource type. Consult the My webMethods Server documentation to learn more about business policies.

POP.002.0007E	**Unknown error encountered while trying to resolve business policy for uri {0}**
Explanation	The server cannot resolve a business policy for specified resource because of an internal error.
Action	Check the _problems_.log in the ..\MWS\server\default\logs directory for more specific error information.

POP.002.0008E	**Uri is not a valid thingID: {0}**
Explanation	The server cannot invoke the RemoveAcess command on a resource that is not a metadata resource.
Action	Correct the command-invoking source code to specify a metadata resource using either the 'resourceURI' parameter or the context's current resource.

POP.002.0009	**Invalid arguments to create Alias command**
Explanation	You cannot invoke this command without the required arguments: key and target.
Action	If you invoked this command programatically, review the Javadocs and make the required changes to the invoking code.

POP.002.0010	**The arguments are not valid**
Explanation	When invoking the alias commands you must supply valid arguments.
Action	If you invoked this command programatically, review the Javadocs and make the required changes to the invoking code.

POP.002.0011	**You cannot flush another user's cache**
Explanation	Only an Administrator can flush another user's cache.
Action	You must log in to My webMethods Server with Administrator credentials to be able to flush another user's cache.

POP.002.0012E	**Class group name is not specified**
Explanation	You must specify the groupName parameter when invoking the ReloadClasses command.
Action	Correct the command-invoking code to specify the 'groupName' parameter. The parameter value should be the name of the group's class-loader bundle.

POP.002.0014E	**Unable to authenticate user: {0}**
Explanation	The server cannot authenticate the user either because the user does not exist or because the user's password is incorrect.
Action	Try again with correct username and password. If necessary, log in to My webMethods or My webMethods Server and use the User Management feature to add the user to the server

POP.002.0016E	**Error listing directory groups**
Explanation	The server cannot list the groups of a particular directory service, most likely because of a problem connecting to the directory service.
Action	If the directory service is a newly configured directory service, log in to the My webMethods Server and double-check the configuration using the Folders > System > Portlets > Administration > Directory Services Administration portlet. If the directory service is an existing directory service for which groups could be listed previously, validate that the LDAP or ADSI server to which the directory service is connected is up and running properly. Also check that the machine which hosts My webMethods Server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.

POP.002.0017E	**Error retrieving template list**
Explanation	The server cannot list directory service templates, because an error occurred loading the templates.
Action	Check the ..\MWS\server\default\logs_problems_.log file for more specific error information.

POP.002.0018E	**Error listing users**
Explanation	The server cannot list the users of a particular directory service, most likely because of a problem connecting to the directory service.
Action	If the directory service is a freshly configured directory service, go back to the Portal Admin Dashboard, and double-check the configuration using the Directory Service Administration portlet (in the Portal Configuration category). If the directory service is an existing directory service for which groups could be listed previously, validate that the LDAP or ADSI server to which the directory service is connected is up and running properly. Also check that the machine which hosts the Portal server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.

POP.002.0019E	**Error updating directory**
Explanation	The server cannot update the directory service configuration because an error occurred in validating or storing the configuration settings.
Action	Check the ..\MWS\server\default\logs_problems_.log file for more specific error information.

POP.002.0020	**Invalid command ID: {0}**
Explanation	The requested command is not found.
Action	Verify that the command has been properly installed. This can be done by logging in to My webMethods Server as sysadmin and viewing the commands in the folder Folders > System > Manager > Commands directory.

POP.002.0021E	**Cannot resolve install mechanics for: {0}**
Explanation	An error occurred during the installation of a server component.
Action	Look in the ..\MWS\server\default\logs_problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to say why the error was thrown, but it will show where the error originated.

POP.002.0022	**Location is not a folder: {0}**
Explanation	When the Install Services commands are instructed to deploy all of the components of a folder, the resource must be a folder and cannot be a file.
Action	Ensure that either the Autodeploy folder is properly configured or that the object passed to the InstallComponents command is a folder.

POP.002.0023	**Cannot find folder: {0}**
Explanation	When the Install Services commands are instructed to deploy all of the components of a folder, the folder must be available.
Action	Ensure that either the Autodeploy folder is properly configured or that the objecgt passed to the InstallComponents command is an available folder.

POP.002.0025E	**Command name is not specified**
Explanation	The Ant build file does not contain the command name needed to invoke the ExecuteCommand ant task.
Action	Correct the Ant build file to provide the command name with the 'name' attribute of the ExecuteCommand task.

POP.002.0026E	**Cannot resolve command [name, type] [{0}, {1}]**
Explanation	The server cannot execute the command by means of an Ant task because the specified command has not been deployed to the server.
Action	Deploy the command specified by the error message.

POP.002.0027E	**Attribute target is required**
Explanation	The target for invoking the ExecuteTargetLoop Ant task has not been specified.
Action	This error can occur if a developer modifies an Ant build file used to deploy comments to the server. Correct the Ant build file to add a 'target' attribute to the ExecuteTargetLoop task invocation.

POP.002.0028E	**Cannot create IInitializableComponentData from: {0}**
Explanation	The component configuration data is not one of the following types: xml (serialized XML document), xmlLocation (URL specifying an XML document), properties (serialized properties map), propertiesLocation (URL specifying a properties file location).
Action	Correct the component configuration in the phaseProvider.xml configuration file to specify component configuration data as either xml, xmlLocation, properties, or propertiesLocation.

POP.002.0029E	**Attribute source is required**
Explanation	The server cannot execute an Ant task because the task requires a source attribute to be specified.
Action	Correct the Ant build file to add a 'src' attribute to RunJavaScript and RunSQLScript tasks. The 'src' attribute must specify the file path to the script to be run.

POP.002.0030E	**Cannot create IInitializableComponentData from {0} for provider {1}**
Explanation	The server cannot unregister the specified component. The component's configuration data has become corrupted.
Action	Reinstall the component with the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet, and then re-try uninstalling the component.

POP.002.0031	**Cannot find IComponent using IComponentData {0} in provider {1}**
Explanation	An attempt was made to unregister a component that is not currently registered.
Action	No further action is required.

POP.002.0032E	**Cannot get IComponentData for component {0} from provider {1}**
Explanation	An error occurred during the unregistration of a server component.
Action	Look in the ..\MWS\server\default\logs_problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to say why the error was thrown, but it will show where the error originated. It is likely that you need to restart the server.

POP.002.0033E	**Component Provider not found: {0}**
Explanation	The server cannot unregister the component because component data has become corrupted.
Action	Re-install the component with the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet, then re-try uninstalling.

POP.002.0034E	**Attribute descriptorSrc is required**
Explanation	The Ant task does not have skin descriptor content.
Action	Correct the Ant build file to provide skin descriptor content using the 'descriptorSrc' attribute to CreateSkinInstance, GetSkinInfo, and RemoveSkinInstance Ant tasks.

POP.002.0035E	**Skin name is empty**
Explanation	The server cannot determine the skin name because the skin descriptor does not contain the skin name or because the skin descriptor is improperly structured.
Action	Correct the skin descriptor to include the skin name in the 'name' attribute value of the 'wm_xt_skin' element.

POP.002.0036E	**Portlet info is not specified**
Explanation	Portlet descriptor content is not included in the GetPortletInfo Ant task.
Action	Correct the Ant build file to provide portlet descriptor content using the 'descriptorSrc' attribute.

POP.002.0037E	**Portlet name is empty**
Explanation	The server cannot determine the portlet name because the portlet descriptor does not contain the portlet name or because the portlet descriptor is improperly structured.
Action	Correct the portlet descriptor to include the portlet name as the content of the 'name' element.

POP.002.0038E	**Portlet is not available: {0}**
Explanation	The specified portlet is not deployed on the server.
Action	Use the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet to deploy the portlet specified by the error message.

POP.002.0040E	**Cannot find system folder for the portlet: {0}**
Explanation	An error occurred during installation of a portlet.
Action	Look in the ..\MWS\server\default\logs_problems_.log file for the stack trace of the error. It may be necessary to reinstall the component.

POP.002.0041	**Page have to be a folder type**
Explanation	When cloning pages, the source of the cloning operation must be of the appropriate type
Action	Ensure that an appropriate source is used for the cloning operation.

POP.002.0042E **Destination container is not a valid thing: {0}**

Explanation The server cannot clone a remote resource; the resource must be cloned to a metadata destination container.

Action Correct the command-invoking source code to specify a metadata destination container using the 'destContainerURI' parameter.

POP.002.0043E **Source item container is not a valid thing: {0}**

Explanation The server cannot clone the remote resource; only metadata resources can be cloned.

Action Correct the command-invoking source code to specify a metadata resource using either the 'resourceURI' parameter or the server context's current resource.

POP.002.0044E **Invalid XType: {0}**

Explanation The server cannot resolve the DBO type of the remote item to be cloned. The most likely reason is that the DBO type has been uninstalled from the system.

Action Normally, a DBO type cannot be uninstalled from the system until all instances of the type have been deleted. This message may also indicate that a damaged instance of the remote item is still present but cannot be cloned or recovered. No further action can be taken.

POP.002.0046E **Item is not a valid thing: {0}**

Explanation The server cannot invoke the metadata command because the command must be invoked against a metadata resource.

Action Correct the command-invoking source code to specify a metadata resource using either the 'resourceURI' parameter or the server context's current resource.

POP.002.0047 **Can not create an item with an empty name**

Explanation When creating a new resource, a 'name' property is required.

Action When creating the resource, ensure that a name is supplied.

POP.002.0048E **Delete operation failed**

Explanation The container cannot be deleted because at least one of the items in the container cannot be deleted. Refer to the the list of contained items that cannot be deleted, displayed in the user interface along with this message.

Action Manually delete the specified undeletable contained items individually. This may result in more detailed information as to why the items cannot be deleted.

POP.002.0049E **Error obtaining owned folder**

Explanation The server cannot obtain the owned folder because of an internal server error.

Action Check the ..\MWS\server\default\logs_problems_.log file for more specific error information.

POP.002.0050E **Cannot get current resource uri**

Explanation Cannot invoke the portlet command because a target portlet for the command is not specified.

Action Correct the command-invoking code to specify the portlet with the 'resourceURI' parameter or with the server context's current resource.

POP.002.0051E **ResourceURI is not specified**

Explanation The server cannot invoke the portlet command because a target portlet for the command is not specified.

Action Correct the command-invoking source code to specify the portlet with the 'resourceURI' parameter or with the server context's current resource.

POP.002.0052E **PortletBean is not ICommandBean**

Explanation The command cannot be invoked against the portlet because the portlet's portlet-bean does not implement the com.webmethods.portal.bizPolicy.command.ICommandBean interface.

Action Modify portlet's portlet-bean source code to make the portlet-bean implement ICommandBean. Rebuild and redeploy the portlet.

POP.002.0053E **UserID is not of type IThingID or String**

Explanation The command was invoked using RMI with an inappropriate userID data type. This error is usually a result of a bug in the command-invoking code.

Action Correct the command-invoking code to ensure it invokes the command with a userID specified either as a java.lang.String or a com.portal.webmethods.meta2.thing.IThingID object.

POP.002.0054E **Search library not found: {0}.**

Explanation An attempt was made to delete a search library that does not exist.

Action Log in to My webMethods Server and use the Search Administration portlet to check the name of the search library against the available libraries.

POP.002.0056E	**Saved Searches folder not found.**
Explanation	The server cannot save a search because the user's saved-searches folder does not exist.
Action	User folders such as the user's saved-searches folder are created automatically for users when they login to My webMethods Server. Try logging out as the user, and then logging in again.

POP.002.0057E	**No name parameter found**
Explanation	The server cannot invoke the save-search command name; the command does not specify a name parameter.
Action	Correct the command-invoking source code to specify a 'name' parameter.

POP.002.0058E	**Not a valid skin: {0}**
Explanation	The server cannot invoke the ReloadSkin command; the specified skin identifier does not identify a valid skin.
Action	Correct the command-invoking source code to specify a valid skin resource using the 'skin' parameter.

POP.002.0059E	**Default xmlimport requires an IThingID for the parent: {0}**
Explanation	The server cannot import a metadata resource using xmlImport unless the parent of the resource is also a metadata resource.
Action	Correct the xmlImport file to move or remove elements contained by the element specified by the error message.

POP.002.0060	**Default xmlimport requires the parent to be a container: {0}**
Explanation	When executing an XML import script, every new child must be created within a valid container.
Action	Check the script to ensure that each created item has a valid parent.

POP.002.0061E	**Unable to locate acl for aclName: {0}**
Explanation	The server cannot modify the access control list (ACL) for a resource specified in xmlImport because the access control list was referenced by an alias that does not exist.
Action	Correct the xmlImport file to replace the 'aclName' attribute value specified by the error message with a valid value.

POP.002.0062E **Unable to find value for acl**

Explanation The server cannot create an access control entry using xmlImport because the ACL element requires a value attribute.

Action Correct the xmlImport file to add a 'value' attribute to the 'acl' elements. The 'value' attribute values must contain one of the following My webMethods Server access right names (comma separated): READ, CREATE_ITEM, CREATE_CONTAINER, MODIFY, DELETE, PORTLET_MODIFY_PROPERTIES_INSTANCE, PORTLET_MODIFY_PROPERTIES_USER, ALL.

POP.002.0063E **Unable to find ace value for: {0}**

Explanation The server cannot create access an control entry using xmlImport because the xmlImport entry references an unknown right value.

Action Correct the xmlImport file to add a 'value' attribute to the 'acl' elements. The 'value' attribute values must contain one of the following My webMethods Server access right names (comma separated): READ, CREATE_ITEM, CREATE_CONTAINER, MODIFY, DELETE, PORTLET_MODIFY_PROPERTIES_INSTANCE, PORTLET_MODIFY_PROPERTIES_USER, ALL.

POP.002.0064 **Unable to find alias name to set the acl**

Explanation The required argument 'value' was not set on this xmlimport element.

Action Ensure that the ACL element has a 'value' attribute

POP.002.0065E **Alias attribute missing on context node**

Explanation The server cannot establish the resource context during xmlImport because the context element requires an alias attribute.

Action Correct the xmlImport file to add an 'alias' attribute to 'context' elements. The alias attribute value must contain the name of a valid alias; elements enclosed by the context apply to the resource identified by this alias.

POP.002.0069S **Root users folder not found**

Explanation The server cannot create the user's home folder because the server users folder does not exist.

Action Create a new server folder, and set its alias to 'folder.users'.

POP.002.0076E **The basic update properties requires a thingID: {0}**

Explanation The server cannot invoke the ImportFiles command because it does not specify a target folder for the import.

Action Correct the command-invoking source code to specify a folder using either the 'resourceURI' parameter or the server context's current resource.

POP.002.0077E **Adding to version control requires a thingID: {0}**

Explanation The server cannot invoke the version-control command without specifying a versionable resource.

Action Correct the command-invoking source code to specify a versionable resource using either the 'resourceURI' parameter or the server context's current resource.

POP.002.0078E **The resource does not support IVersionableMechanics: {0}**

Explanation The server cannot invoke the version-control command on the resource because the resource is not versionable.

Action Do not invoke the AddToVersion command against resources that are not versionable. Only server folders and server content items are versionable.

POP.002.0079E **Command requires a thingID: {0}**

Explanation The server cannot invoke the version-control command without specifying a versionable resource.

Action Correct the command-invoking source code to specify a versionable resource using either the 'resourceURI' parameter or the server context's current resource.

POP.002.0080E **Invalid version Uri: {0}**

Explanation The server cannot display the server version information of an item because the identifier used to specify the version is not a valid version identifier.

Action Correct the source code that invokes the ViewVersion command to provide a valid version identifier.

POP.002.0081E **Invalid thing ID: {0}**

Explanation The server cannot display the server version information of an item because the identifier used to specify the item does not identify a valid resource

Action Correct the command-invoking source code to provide a valid versioned-item identifier for the 'targetURI' parameter.

POP.002.0082	**User {0} don't have rights to view {1}**
Explanation	The current user failed the permissions check to see a particular version of an item.
Action	Check the permissions on that item.

POP.002.0083E	**Could not acquire context, principal data not found on session**
Explanation	The server cannot create a server context for the specified javax.servlet.http.HttpSession because the HttpSession has not been initialized with the necessary server session data.
Action	Restart My webMethods Server.

POP.002.0085E	**Can't create subscription for non Thing: {0}**
Explanation	The server cannot create a subscription from xmlImport data because subscriptions are supported only for metadata resources.
Action	Correct the xmlImport file to remove 'subscription' elements from non-metadata resource contexts. The best way to determine specifically which subscription elements in the xmlImport file are causing this error is the trial-and-error approach: remove each subscription element in the xmlImport file one by one and then try re-importing from the xmlImport file.

POP.002.0086E	**Unable to import xml. No uid.**
Explanation	An attempt to create an access control entry or subscription using xmlimport did not specify the user ID of the My webMethods Server user or group.
Action	Correct the xmlImport file to add a 'uid' attribute to 'subscription' and 'ace' elements. The 'uid' attribute value must contain the user ID (LDAP user ID) of a valid My webMethods Server user or the cn (LDAP group ID) of a valid My webMethods Server group.

POP.002.0087W	**Unable to import xml. Could not acquire uri for uid: {0}**
Explanation	The user referenced in the xmlImport file does not exist on My webMethods Server.
Action	Log in to My webMethods or My webMethods Server with appropriate permissions and add the user, or change the xmlImport file.

POP.002.0089E	**Unable to import subscription. No value specified for 'deliveryMode'.**
Explanation	The server cannot create a subscription from xmlImport data because the subscription element requires a deliveryMode attribute. This error is caused by importing from an improperly constructed xmlImport file.
Action	Correct the xmlImport file by adding a 'deliveryMode' attribute to 'subscription' elements. The valid value for 'deliveryMode' attribute is "email", indicating notifications for this subscription are to be delivered to the user's e-mail address.

POP.002.0090E **Unable to import subscription. No value specified for 'criteria'.**

Explanation The server cannot create the subscription from xmlImport data because the subscription element requires a criteria attribute that contains the name of at least one criterion valid for the type of resource subscribed to.

Action Correct the 'subscription' elements in the xmlImport file so that they all contain valid 'criteria' attribute values. Valid values are not empty; they must contain a comma-separated list of criterion names. The criterion names for basic folders are: 'added', 'removed', 'modified', 'deleted', and 'moved'. The criterion names for basic links, forms, portlets, and content items are 'modified', 'deleted', and 'moved'. Custom DBO types may have additional criteria.

POP.002.0091E **No matching criteria found for type: {0} and for criteria: {1}.**

Explanation The server cannot create a subscription from xmlImport data because the subscription element requires a criteria attribute that contains the name of at least one criterion valid for the type of resource subscribed to.

Action Correct the xmlImport file so that 'subscription' elements contained by any element of the type specified by the error message's resource-typeName have valid 'criteria' attribute values. Valid values are not empty; they must contain a comma-separated list of criterion names. The criterion names for basic folders are: 'added', 'removed', 'modified', 'deleted', and 'moved'. The criterion names for basic links, forms, portlets, and content items are 'modified', 'deleted', and 'moved'. Custom DBO types may have additional criteria.

POP.002.0092E **Can't set ace for non Thing: {0}**

Explanation The server cannot modify the access control entry (ACE) for a resource specified in xmlImport because the resource does not support My webMethods Server access control entries.

Action Correct the xmlImport file to remove the 'ace' element for the resource specified by the error message.

POP.002.0093E **Unable to locate alias for: {0}**

Explanation The server cannot establish the resource context during xmlImport because the alias specified for the context does not exist.

Action Log in to My webMethods Server and use the Alias Management portlet to create the alias specified by the error ,message or fix the xmlImport file to use an alias that does exist. To fix the xmlImport file, locate the alias attribute with the value specified by the error message and replace that value with the name of an existing alias.

POP.002.0095	**Unable to create alias: {0} because it already exists.**
Explanation	The command failed because an alias of the same name has already been registered.
Action	Either apply a different name to the new alias or modify the existing alias that uses the same name.

POP.002.0096E	**Mechanics is not an IBasicMechanics**
Explanation	The server cannot use xmlImport to update the properties of a resource that is not a metadata resource.
Action	Correct the xmlImport file to not update the properties of non-metadata resources. The best way to determine the element in the xmlImport file that is causing this error is the trial-and-error approach: remove each element in the xmlImport file one-by-one and then try re-importing from the xmlImport file.

POP.002.0097E	**Unable to complete import because type: {0} doesn't exist.**
Explanation	The server cannot import a resource specified in xmlImport because the resource is an instance of a DBO that is not currently deployed in My webMethods Server.
Action	Deploy the DBO specified by the error message and then rerun the xmlImport.

POP.002.0098	**Role xmlimport requires attributes of 'roleProvider' and 'name'**
Explanation	When creating a new role using an xmlImport script, the attributes must be available.
Action	Modify the xmlimport script to include the required 'roleProvider' and 'name' properties.

POP.002.0099	**Role xmlimport unable to locate roleProvider: {0}**
Explanation	The type of role is not registered on the current system.
Action	Check the 'roleProvider' attribute to make sure it is correct.

POP.002.0103	**Failed to set Alias {0} for resource {1}.**
Explanation	The system failed to correctly set an alias during the xmlimport.
Action	Check the server logs at ..\MWS\server\default\logs for any additional exceptions that occurred during the import.

POP.002.0105	**Failed to load xml document from {0}**
Explanation	The XML file specified for the xmlimport script is either not found or not well-formed.
Action	Verify that the XML file exists in the specified location and that the contents of the file are valid XML.

POP.002.0107	**Failed to invoke remote command: {0}. Original error message: {1}**
Explanation	A problem occured when executing a command on a remote server.
Action	Check the logs on the remote server for additional information.

POP.002.0108	**User UID can not be found in MWS directories: {0}**
Explanation	No user is found with the specific user ID.
Action	Specify a valid user ID.

POP.002.0110	**You have insuffient privileges to impersonate other users.**
Explanation	You have insufficient privileges to impersonate other users.
Action	The log file indicates how to grant user impersonate privileges. Contact a system administrator if you need such privileges.

POP.002.0111	**Illegal Argument: Command result may not be serialized.**
Explanation	The command result cannot be serialized.
Action	Make sure the command result can be serialized.

POP.002.0113	**The parent of the task is already completed**
Explanation	You cannot create a new child task if its parent task has been completed.
Action	Contact the parent task owner to determine how to handle the additional work.

POP.002.0114	**User {0} does not have the functional privilege to delegate task {1}**
Explanation	The user has not been granted the functional privilege to delegate the task.
Action	Please contact the system administrator if you need such privileges.

POP.002.0118	**Thing with name "{0}" for locale "{1}" already exists in "{2}". Unable to rename "{3}"**

POP.003.0003S	**No access model specified in property "{0}".**
Explanation	The framework.access.model system property does not specify an access model.
Action	Update the portal.properties file to specify framework.access.model property value. The choices are permissive or restrictive.

POP.003.0004S	**Unable to register principal types: "{0}".**
Explanation	The system directory is corrupted.
Action	Restore the underlying system user directory content from a backup or manually restore the user directory. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

POP.003.0005S	**Unable to register search service: "{0}".**
Explanation	An error occurred in registering a new search service.
Action	You might need to reinstall My webMethods Server.

POP.003.0006S	**Error initializing content service: "{0}".**
Explanation	The content service cannot be initialized.
Action	Check the Content Service Administration portlet to verify that the content service is properly configured.

POP.003.0007E	**Cannot list roles, directory service "{0}" not found.**
Explanation	The directory service cannot be found.
Action	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.

POP.003.0008E	**Could not locate system directory: "{0}".**
Explanation	The server cannot find the system user directory.
Action	Verify that the system directory is present in Directory Services Administration portlet, and that it is configured and functional.

POP.003.0009E	**Error setting system directory: "{0}".**
Explanation	The command failed to change the system directory service.
Action	Do not attempt to change the system directory.

POP.003.0012W	**"{0}" does not have permission to modify the Administrators group.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu to open the Permissions portlet to give the user access rights.

POP.003.0013W	**"{0}" does not have permission to modify the directory configuration.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu to open the Permissions portlet to give the user access rights.

POP.003.0014E	**Cannot update directory config, domain not found: "{0}".**
Explanation	An attempt was mademto update the config information for a directory service using an invalid domain name.
Action	Use a valid domain name.

POP.003.0015S	**Cannot update directory config, Administrator user not found: "{0}".**
Explanation	The system directory or the database is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. If LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

POP.003.0016E	**Cannot update directory config, Everyone group not found: "{0}".**
Explanation	The system directory does not have an everyone group or the directory is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

POP.003.0017S	**Cannot update directory config, Guest user not found: "{0}".**
Explanation	The system directory is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

POP.003.0018E	**Cannot remove the system directory.**
Explanation	The system directory services cannot be removed.
Action	Do not try to remove the system directory.

POP.003.0021E	**System directory does not have Administrator user.**
Explanation	The LDAP user store is missing the administrator user.
Action	Add a user to the system LDAP user store whose UID matches the Portal Administrator UID. This should only be necessary if the LDAP user store has become corrupted or the PortalAdmin user has been removed.

POP.003.0022S	**System directory does not have Everyone group. Everyone group access will not be available.**
Explanation	The system directory is corrupted.
Action	Restore or create the everyone group in the system directory. Use the directory's administration UI or tools for that purpose.

POP.003.0023E	**System directory does not have Guest user. Guest access will not be available.**
Explanation	The system directory does not have a guest user or it is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

POP.003.0024W	**The type "{0}" is either 'disabled' or not deployed to this MWS cluster node. Please contact the My webMethods Server Administrator.**
Explanation	An attempt was made to view a portlet for which the status has been set to disabled.
Action	Use the Manage Components portlet in the Administration Dashboard to change the status of the portlet type.

POP.003.0025W	**{0} cannot view the content of {1}.**
Explanation	The user is denied access to view a portlet item
Action	Use the Permissions page to set the authentication scheme for the item to one of the installed authentication schemes.

POP.003.0026W	**{0} cannot list the shortcuts to {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0027W	**{0} cannot list the notes for {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0028W	**{0} cannot view the access list for {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0029W	**{0} cannot view the authentication scheme for {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0030W	**{0} cannot create an item of type {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open up the Permissions portlet to give the user access rights.

POP.003.0031W	**{0} cannot update the content of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0032W	**{0} cannot add the note for {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0033W	**{0} cannot remove the note for {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0034W	**{0} cannot update the properties of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0035W	**{0} cannot delete {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0037W	**{0} cannot destroy {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0038	**{0} cannot store content {1}.**
Explanation	An attempt was made to store a document on a type that does not support document storage
Action	Ensure that content is stored on document types

POP.003.0039W	**{0} cannot contain a duplicate reference to {1}.**
Explanation	You cannot create items with the same name under the same folder.
Action	When naming items in a folder, make sure each item uses a name that is unique within the folder.

POP.003.0040W	**Cannot uninstall "{0}" because it has "{1}" published instances. Please delete them first and try again.**
Explanation	The DBO cannot be uninstalled because it has published instances.
Action	Manually delete all published instances of this DBO and try to uninstall it again. You can use Publish History portlet to help you find all published instances.

POP.003.0044W	**{0} is checked out.**
Explanation	The item cannot be checked out because it is already checked out.
Action	Wait until the item is checked in and try again.

POP.003.0045W	**{0} is not versioned.**
Explanation	The item is not versioned.
Action	Add the item to version control using the item's local menu.

POP.003.0046	**{0} cannot view version number of {1}.**
Explanation	An attempt was made to view a version of a document that failed a permissions check
Action	Verify that the current user has sufficient permissions

POP.003.0047W	**{0} cannot list the versions of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0048W	**{0} cannot add to versioning {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0049	**{0} cannot remove from versioning {1}.**
Explanation	An attempt was made to remove a version from version control that failed a permissions check
Action	Verify that the current user has sufficient permissions

POP.003.0050W	**{0} is checked out by {1}.**
Explanation	The item is already checked out.
Action	Wait until the item is checked in and before trying to check out.

POP.003.0051W	**{0} cannot set the current version of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0052W	**{0} cannot publish a version of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0053W	**{0} cannot check out {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0054W	**{0} is not checked out.**
Explanation	You cannot check the item in because it is not checked out.
Action	Do not attempt to check in an item that was not checked out.

POP.003.0055W	**{0} cannot check in {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0056W	**{0} cannot undo the check out of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's 'rmissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0057E	**Source branch is not found: "{0}".**
Explanation	The server cannot find a source version branch for this object.
Action	Do not try to add this object to version control.

POP.003.0058	**Destination branch is not found: "{0}".**
Explanation	Version control system was unable to create a new branch required to complete the add to versioning command.
Action	Check the logs for additional information such as out of disk space.

POP.003.0059W	**{0} cannot be added to versioning because parent is null.**
Explanation	The item is invalid because it does not have a parent.
Action	Use the local item menu to delete the item.

POP.003.0060W	**Not initialized: call init(PageData) first.**
Explanation	An internal error has occurred.
Action	Try the operation again.

POP.003.0061W	**Column must be contained by a row.**
Explanation	The page data xml is not valid. The column element must reside inside a row element.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try editing and then saving the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

POP.003.0062E	**Property must be contained by a portlet.**
Explanation	The page data xml is not valid. The property element must be inside portlet element.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

POP.003.0063E	**Portlet must contain 'uri' attribute.**
Explanation	The page data xml file is not valid. The portlet definition does not have an URI attribute.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

POP.003.0064W **Property must contain 'name' attribute.**

Explanation The page data xml is not valid. The property element must have a name attribute.

Action If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

POP.003.0065E **Wiring must be contained by a portlet.**

Explanation The page data xml is not valid. The property element must reside inside the portlet element.

Action If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

POP.003.0066W **Wiring must contain 'name' attribute.**

Explanation The page data xml is not valid. The wiring element must have a name attribute.

Action If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

POP.003.0067E **Wiring must contain 'portlet' attribute.**

Explanation The page data xml file is not valid. The wiring definition does not have a portlet attribute.

Action If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

POP.003.0069E **The content service "{0}" is not available. Please contact the My webMethods Server Administrator.**

Explanation The server failed to update the contents of a file that was saved to My webMethods Server.

Action Verify that the location for the My webMethods Server content repository exists.

POP.003.0070	**"{0}" is not editable as it does not exist in a sandbox.**
Explanation	An invalid attempt to check in a versioned item was made.
Action	Check out a new version and the the item check in.

POP.003.0071E	**Cannot lookup install service: "{0}".**
Explanation	The server cannot find the install service for this component.
Action	The component is not supported.

POP.003.0072E	**ComponentUri is not a thingID: "{0}".**
Explanation	The server cannot determine the location of the installed component based on the passed URI.
Action	Correct the calling code to specify a thingID as the componentUri parameter of the uninstallComponent command.

POP.003.0073E	**{0} cannot install component.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0074W	**{0} cannot read search service.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0075	**{0} cannot set access entries on {1}.**
Explanation	An attempt was made to set permissions which failed a permissions check
Action	Ensure the current user has sufficient permissions to edit the permissions on the current object

POP.003.0076W	**{0} cannot remove access entries from {1}.**
Explanation	The specified user cannot remove entries from the access control list of the specified item.
Action	Grant the user the rights to perform the operation, or have the operation performed by a different user with permission to change the access control list of the target item.

POP.003.0077W	**{0} cannot set the authentication scheme of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0078W	**{0} cannot set the owner of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0079E	**Internal error. Access right lengths do not match.**
Explanation	Internal error. A database API inconsistency exists.
Action	Use the Manage Components portlet to edit permissions for this My webMethods Server object.

POP.003.0080W	**No auth scheme for auth Level: "{0}".**
Explanation	The authentication scheme might not be installed yet, or the specified authentication level is not valid.
Action	Install the missing authentication scheme wm_<schema>Auth.cdp component or correct the authLevel attribute value of your custom xmlImport.xml file.

POP.003.0081E	**No implementation for auth scheme: "{0}".**
Explanation	The authentication scheme for the target My webMethods Server item is invalid.
Action	Use the Permissions page to set the authentication scheme for the item to one of the installed authentication schemes.

POP.003.0082W	**{0} cannot list the contents of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0083W	**{0} cannot add an item to {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0084W	**{0} cannot add a shortcut to {1}.**
Explanation	Most likely user does not have appropriate access rights.E145
Action	Give the user access rights.

POP.003.0085W	**{0} cannot remove an item from {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open Permissions portlet to give the user access rights.

POP.003.0086W	**{0} cannot remove a shortcut from {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0087	**You cannot copy this container into a descendant of itself.**
Explanation	A paste operation was attempted inside the source container.
Action	Paste the clipboard contents into an external container.

POP.003.0088W	**You cannot move this container into a descendant of itself.**
Explanation	The folder cannot move into one of its subfolders.
Action	If you need to move the folder, do not attempt to move it into a subfolder of itself.

POP.003.0090W	**{0} cannot contain a duplicate name.**
Explanation	The folder or page cannot have items with duplicate names.
Action	When naming items in a folder, make sure each item has a name that is unique within the folder.

POP.003.0091E	**Unable to create xtype with null name: "{0}".**
Explanation	The xtype id passed into the createChild command is not valid.
Action	Pass a valid xtype id parameter value. The valid values are listed in the tblXTypes tables.

POP.003.0092W	**{0} is a reserved folder and cannot be modified.**
Explanation	The folder is a system folder and cannot be modified.
Action	Do not try to modify a system folder.

POP.003.0093W	**You cannot move a reserved item.**
Explanation	The item is reserved and cannot be moved.
Action	Do not attempt to move reserved items.

POP.003.0094W	**{0} is a reserved folder and can not be versioned.**
Explanation	The folder cannot be added to the version control because it is a special folder type.
Action	Do not try to add this folder to version control.

POP.003.0095W	**{0} cannot change the columns of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0096	**{0} cannot move portlet {1}.**
Explanation	An attempt to move a portlet failed a permissions check
Action	Verify that the current user has sufficient permissions

POP.003.0097W	**{0} cannot minimize portlet {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0099W	**{0} cannot view this item.**
Explanation	The user attempted to view an item but does not have permission to see it.
Action	The My webMethods Server administrator should use the Manage Components portlet to edit permissions for this My webMethods Server object.

POP.003.0102W	**Unable to locate: "{0}".**
Explanation	The server cannot find the user in the directory.
Action	The user might have been removed from the directory. Determine if this user belongs in the directory.

POP.003.0103W	**Unable to locate: "{0}" invalid type.**
Explanation	The directory might be corrupted or improperly configured.
Action	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.

POP.003.0104W	**{0} cannot modify user.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0105W	**Cannot modify attribute on principal, {0} not found.**
Explanation	The server cannot find the user in the directory.
Action	The user might have been removed from the directory. Determine if this user belongs in the directory.

POP.003.0106W	**Cannot set email address on principal, email address attribute not configured properly.**
Explanation	The email attribute is not configured for this user directory.
Action	Update the directory configuration in Directory Service Administration portlet to specify an email attribute name and try again.

POP.003.0107W	**{0} cannot create an alias.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0108W	**Alias not found: "{0}".**
Explanation	An attempt was made to remove an alias that does not exist.
Action	Verify that the remove alias call uses an existing alias name.

POP.003.0109W	**{0} cannot delete the "{2}" alias.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0110E	**Internal ScheduleMechanics error.**
Explanation	The paging cookie is invalid.
Action	Close the browser, then open it again, and retry the action.

POP.003.0111W	**{0} cannot view the subscription of {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0112W	**{0} cannot list the subscriptions to {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0113W	**{0} cannot edit the subscription to {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0115W	**Cannot create cookie for URI: "{0}".**
Explanation	The system directory or the database is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

POP.003.0116W	**User page size must be >= 0 (zero indicates default).**
Explanation	The page size cannot be negative.
Action	Correct the calling code to pass the pageSize parameter as a positive number.

POP.003.0117W	**Cannot set password on user, user not found: "{0}".**
Explanation	The system directory or the database is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

POP.003.0118E	**Cannot get roles for user, user not found: "{0}".**
Explanation	The server cannot find the user in the directory.
Action	The user might have been removed from the directory. Determine if this user belongs in the directory.

POP.003.0119E	**Unable to locate mechanics: "{0}".**
Explanation	Mechanics were not found for the given name or URI.
Action	If the error is related to a standard portlet, try to redeploy the portlet using the Install Administration portlet. If you have created a custom portlet, you need to correct the calling code in CAF and redeploy the portlet.

POP.003.0120W	**{0} cannot cut {1}.**
Explanation	The user does not have appropriate access rights.
Action	Use the item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0121W	**{0} cannot cut {1}.**
Explanation	The user does not have the appropriate access rights.
Action	Use the item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0122W	**A datasource named "{0}" already exists.**
Explanation	An attempt was made to register a SQL datasource with a datasource name that has already been used for another datasource.
Action	Use a different name for the new datasource.

POP.003.0123W	**You cannot copy a reserved item.**
Explanation	The item is reserved.
Action	Do not attempt to copy a reserved item.

POP.003.0124	**{0} cannot access datasource.**
Explanation	An attempt to issue a SQL statement was made with an invalid argument for the datasource
Action	Ensure that the datasource is registered

POP.003.0126W	**compression not allowed.**
Explanation	The presentation cache content cannot be compressed.
Action	Correct the calling code to not call PresentationCacheContent.setCompressed(true).

POP.003.0129W	**Cannot initialize principal, invalid type: "{0}".**
Explanation	The directory might be corrupted or improperly configured
Action	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.

POP.003.0130E	**Error in thread resyncing group properties [domain]: "{0}".**
Explanation	The server failed to refresh the metadata for a Group from the LDAP server.
Action	Validate the connectivity to the LDAP server using an LDAP browser tool, the directory native Administration UI, or other tools.

POP.003.0132	**"{0}" depends on "{1}".**
Explanation	During the wiring resolution phase an error occurred
Action	Check the wiring configuration for the portlets on the current page.

POP.003.0134W	**{0}'s account has been disabled.**
Explanation	The user account has been disabled.
Action	Enable the user account in the underlying user directory. Use the directory Administration UI or other tools for that purpose.

POP.003.0135W	**Unable to find the content location for: "{0}". Content service is not available or out of sync with the database. Please try again. If the problem persists, contact the My webMethods Server Administrator.**
Explanation	The content store is corrupted.
Action	Delete the item and try again.

POP.003.0136W	**Cannot install component "{0}" because it requires "{1}" to be installed first.**
Explanation	The component being installed depends on another component that is not yet installed and not listed in the items to install list.
Action	Install the required components before attempting to install the component that raised the error.

POP.003.0137W	**Unable to create with unknown type: "{0}".**
Explanation	Cannot create an item because the xtype is invalid.
Action	Pass a valid xtype parameter to createChild command. All valid xtypes are found in the XTypes system folder in the My webMethods Server UI.

POP.003.0139W	**Component "{0}" installation failed. System state is recovered by uninstalling the component. Original error: {1}**
Explanation	The installation of the component failed.
Action	Uninstall the component to recover the system state. Look at the install.log file for details of why the installation failed.

POP.003.0140E	**Component "{0}" installation failed. System state is recovered by reinstalling the previous version of the component. Original error: {1}"**
Explanation	The installation of the component failed.
Action	Uninstall the component to recover the system state. Look at the install.log file for details of why the installation failed.

POP.003.0141	**The username/password you entered is invalid.**
Explanation	The login attempt failed.
Action	Verify that the username and password are correct.

POP.003.0142	**Invalid principal type: "{0}".**
Explanation	An attempt to modify a group's membership failed.
Action	Verify that the group exists prior to attempting to modify the group.

POP.003.0143	**{0} cannot set policy on {1}.**
Explanation	An attempt was made to add an item to a Security Realm failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0144	**{0} cannot remove policy from {1}.**
Explanation	An attempt to remove an item from a Security Realm failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0146	**{0} cannot modify the members of group: {1}**
Explanation	An attempt to modify the members of group failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0147	**{0} cannot modify the membership of principal: {1}**
Explanation	An attempt to modify the groups and roles a principal belongs to failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0148	**Command Error, Parent is not a container. Class= {0}**
Explanation	An attempt was made to create a new item inside a parent that is not a valid container.
Action	Ensure that the attempt is made to create a child inside a valid container.

POP.003.0150	**{0} cannot create users or groups in the "{1}" directory service."**
Explanation	An attempt was made to create a user or group failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0151	**{0} cannot modify the members of role: {1}**
Explanation	An attempt to modify the members of a role failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0153	**{0} cannot add a {2} to {1}.**
Explanation	An attempt to create a new child failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0154	**{0} cannot remove a {2} from {1}.**
Explanation	An attempt to remove a child from a folder failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0155	**My webMethods Server webspace {0} should have an valid alias**
Explanation	Webspaces must have a valid name in order to be created.
Action	Ensure that a valid alias name is supplied.

POP.003.0156	**Unclosed skin property: "{1}". Please close with "].**
Explanation	During the dynamic skin property resolution, a malformed skin property was referenced.
Action	Ensure that the javaScript file with the dynamic skin property is properly formed.

POP.003.0160E	**Failed to resolve wiring for property "{0}"**
Explanation	Wiring cannot be resolved for the <propertyName> property of a portlet instance.
Action	Open the Wiring settings for this portlet, make sure the source portlet and its property are still available. Adjust the wiring settings if necessary.

POP.003.0162	**A group cannot be a member of itself.**
Explanation	A malformed attempt to modify a group was made.
Action	Do not set a group as a member of itself.

POP.003.0163	**Invalid username or Password.**
Explanation	The username or password is invalid.
Action	Specify a valid username and password.

POP.003.0164	**{0} cannot copy {1}.**
Explanation	The user does not have the privilege to copy.
Action	Please contact the system administrator if you need this privilege.

POP.003.0165	**{0} cannot clone {1}.**
Explanation	The user does not have the privilege to clone.
Action	Please contact the system administrator if you need this privilege.

POP.003.0166	**{0} is a system component. And will not be uninstalled.**
Explanation	System components cannot be uninstalled.
Action	Do not attempt to uninstall a system component.

POP.003.0167	**Too many failed login attempts for: "{0}". You may try to login again in {1} minutes.**
Explanation	The user is not allowed to login because of too many failed login attempts. The user must wait a specified amount of time before trying again.
Action	Make sure you are using a valid username and password. Contact the system administrator if your existing credentials are not working.

POP.003.0168	**Password has expired for: "{0}". Please contact an administrator to reset your password.**
Explanation	The user's password has expired.
Action	Contact an administrator to reset your password.

POP.003.0169	**{0} is reserved and cannot be used for an alias.**
Explanation	The specified name is reserved by the system and cannot be used for an alias name.
Action	Specify a differnt name as an alias.

POP.003.0171	**The uploaded file type is not allowed. The allowed file extensions are: {0}**
Explanation	The uploaded file type is not supported by the system.
Action	Be sure to upload only supported file types.

POP.004.0001E	**The Resource Bundle for "{0}" was not found.**
Explanation	The server cannot load the specified resource bundle class. The bundle is a portlet class that has not been deployed or was deployed in a different portlet.
Action	Use the Portlet Developer to add the resource bundle class to the invoking portlet. Redeploy the portlet.

POP.004.0002E	**The Message Key "{0}" was not found in the Resource Bundle "{1}".**
Explanation	The resource bundle message key is missing.
Action	Correct the resource bundle to include a resource for the key specified by the error message.

POP.004.0003	**There was no Object found for Message Key "{0}".**
Explanation	No object was found for the specified message key.
Action	Specify a valid message key.

POP.004.0004E	**An error occurred while formatting the Message Key "{0}".**
Explanation	The resource bundle message key is missing or the message could not be formatted because its content is invalid.
Action	Correct the resource bundle to include the key specified by the error message, or correct the resource content identified by the key.

POP.004.0005S	**Error creating search pools "{0}".**
Explanation	The server cannot initialize some search service data structures because an internal portal error occurred.
Action	Use the specific error message details to diagnose the problem.

POP.004.0006S	**Invalid cache ID: "{0}".**
Explanation	The server cannot initialize an invalid cache.
Action	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/>

POP.004.0008E	**Unable to initialize content service component: "{0}".**
Explanation	Cannot initialize the content service.
Action	If you cannot reconfigure the offending content service. Call Software AG Global Support for a reset directive.

POP.004.0010E	**No provider for directory [name, type] : [{0}, {1}]**
Explanation	The server cannot initialize the specified directory service because the directory service is an unknown type.
Action	Correct the directoryConfig.xml My webMethods Server configuration file to remove the Service element with the name attribute value specified by the error message.

POP.004.0011E	**Invalid XML for directory, no DirectoryConfig element found: "{0}".**
Explanation	The server cannot initialize the directory service because its configuration data is corrupt.
Action	Correct the directoryConfig.xml My webMethods Server configuration file to remove the Service element with the name attribute value specified by the error message.

POP.004.0012S	**Unable to construct component data for directory: "{0}".**
Explanation	The server cannot initialize the directory service.
Action	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.

POP.004.0013S	**Alias Cache not found.**
Explanation	The server cannot initialize the alias service because the alias cache is not configured.
Action	Add the following entry to the cache.xml My webMethods Server configuration file: <cache name="AliasCache" class="com.webmethods.portal.service.cache.impl.AliasCache" maxSize="5000" isClustered="true" ID="2" enabled="true"/>

POP.004.0014E	**Can't create alias cache.**
Explanation	The server cannot initialize the metadata service because the required cache was not located.
Action	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/>

POP.004.0015E	**Unable to create MetaContext: "{0}".**
Explanation	The server cannot create a connection to metadata datasource because the configuration information for the datasource was not retrieved.
Action	Correct the metaContext.xml My webMethods Server configuration file to remove the Context element with the connection attribute value specified by the error message.

POP.004.0016S	**Can't get schedule list: "{0}".**
Explanation	The server was unable to list all of the My webMethods Server schedules.
Action	Verify that the database has been properly configured and that the My webMethods Server schema was properly installed by paying close attention to the installation process.

POP.004.0017S	**Thing Cache not found.**
Explanation	The server cannot initialize the metadata service because the required cache was not located.
Action	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/>

POP.004.0018S	**Can't create thing cache.**
Explanation	The server cannot initialize the metadata service because the thing cache configuration is invalid.
Action	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/>

POP.004.0019S	**No queue specified.**
Explanation	The server cannot initialize the e-mail notification deliverer because the notification queue name was not specified in the deliverer's configuration.
Action	Specify the queue name in the queue attribute of the delivery initializers in the phaseProvider.xml My webMethods Server configuration file.

POP.004.0020S	**Unexpected exception: "{0}".**
Explanation	The server cannot initialize the e-mail notification deliverer because an unexpected error occurred.
Action	Check the _problems_.log in the My webMethods Server current logging directory for more specific error information.

POP.004.0021S	**Invalid ConnectionManager config file.**
Explanation	The server cannot initialize the datasource connection manager because it cannot acquire its configuration file.
Action	Validate that the portal.properties My webMethods Server configuration file contains the following entry: 'sled.connectionmanager.config=config:/db.xml'.

POP.004.0022E	**Could not acquire meta context : version service name: "{0}".**
Explanation	The server cannot acquire the metadata datasource by name because the specified name is unrecognized.
Action	Restart the server where My webMethods Server is installed.

POP.004.0023E	**Could not find root folder of version services.**
Explanation	The root folder of the version service does not exist.
Action	Reinstall the version service using the My webMethods Server Configurator.

POP.004.0024S	**Could not create service thing : version service name: "{0}".**
Explanation	The server cannot initialize the version service.
Action	Verify that all of the versioning components have been deployed. This includes the version service and version portlet which can be located in the system portal folders.

POP.004.0027E	**Ftp login failed for user [{0}] : {1}.**
Explanation	The server cannot login to the remote FTP server.
Action	Verify that the credentials are valid for the FTP connection service, and that the network connectivity is valid.

POP.004.0028E	**Ftp Connection Error: Access Denied**
Explanation	The server cannot connect to the remote FTP server.
Action	Validate that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.

POP.004.0029E	**Ftp Connection Error: "{0}".**
Explanation	The server cannot connect to the remote FTP server.
Action	Validate that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.

POP.004.0032E	**Invalid ID's in createThing.**
Explanation	The server was unable to publish a new My webMethods Server object.
Action	Correct the invoking method to pass in a valid owner and parent ID parameters.

POP.004.0033E	**Database is busy or unavailable.**
Explanation	The server cannot execute the SQL command because the database is not responding to My webMethods Server in a timely fashion. The database could be experiencing too much load preventing it from responding to My webMethods Server and the server might not be able to access the database's server or port. In addition, the database might not be running.
Action	Verify that the database is running, and is not experiencing heavy load. Verify that the database has an adequate number of connection threads available. Verify that the machine on which the My webMethods Server is running can access the datasource's configured host name and port.

POP.004.0034E	**Datasource Mismatch, passed ({0}) to API on ({1}).**
Explanation	The metadata datasource cannot operate on a resource from a different datasource.
Action	Correct the invoking source code to use a metadata service to operate on a resource that belongs to the service's datasource. Consult the API documentation for more information.

POP.004.0035E	**Invalid URI**
Explanation	The server cannot resolve the datasource for a metadata My webMethods Server identifier.
Action	The identifier that caused this error does not identify a resource, do not use it to identify a resource.

POP.004.0036E	**Invalid schedule info: interval "{0}", timeAt "{1}": Unable to parse 'timeAt' and/or 'interval'**
Explanation	An attempt to create or modify a schedule has failed because of invalid schedule parameters.
Action	Correct the invoking code to pass valid schedule parameters. Valid interval and timeAt parameter values are the time values formatted according to the ISO 8601 date/time format.

POP.004.0037E	**Invalid schedule info: interval "{0}", timeAt "{1}": 'timeAt' overlaps with 'interval'**
Explanation	The server cannot execute the scheduled event because the time to wait (timeAt), after the interval setting but before executing the event, is approximately as long as the interval itself.
Action	Edit the schedule using the Event Administration portlet, in the Portal Configuration category in the My webMethods Server Admin Dashboard, so the interval is longer than the On/At time-to-wait, such that weeks instead of days, hours instead of minutes.

POP.004.0038E	**Unknown thing type: {0}**
Explanation	The server was unable to identify the base type of the metadata service object.
Action	Verify that the portlet was built using the My webMethods Server.

POP.004.0039E	**Unable to unregister XType: {0}**
Explanation	The xtype was not registered or there are published instances of that xtype.
Action	Ensure that all instances of that xtype have been deleted prior to unregistering. These types are found by using the Publish History reporting portlet.

POP.004.0040E	**Can't convert to xtype of different base type**
Explanation	Xtype conversion is unsupported.
Action	Correct the invoking method and do not attempt to modify the xtype parameter.

POP.004.0041E	**Invalid Principal.**
Explanation	The server cannot modify the access control entry.
Action	Correct the invoking method to specify a principal parameter.

POP.004.0042E	**Invalid Ace. Cannot set both granted and denied on the same right.**
Explanation	The server cannot set a single access control entry to grant and deny the same access right.
Action	Correct the invoking source code. Consult the API documentation for more information.

POP.004.0043E	**Invalid Ace. Unknown right.**
Explanation	The server cannot set access control entry with the right bit outside of the defined right bit range, as defined by the access service API.
Action	Correct the invoking source code. Consult the API documentation for more information.

POP.004.0045E	**Invalid Ace. Cannot delegate a right not granted.**
Explanation	The server cannot modify the access control entry.
Action	Correct the invoking method to include the proper right set parameter.

POP.004.0046	**Setting user name is not supported.**
Explanation	Internal group and user objects cannot have their name set
Action	Check and correct directory API usage

POP.004.0047E	**Cookie is not set in this view.**
Explanation	The server cannot display the inbox notifications because a paging cookie was not set.
Action	Log out, log in, and try again.

POP.004.0048E	**Unable to load Subscription object. Subscription no longer exists.**
Explanation	The server cannot locate the subscription information that triggered the notification.
Action	Delete the notification by locating the offending notification in the My webMethods Server inbox and deleting it.

POP.004.0049E	**Unable to load Event.**
Explanation	The server cannot load event data because an error occurred in querying the database.
Action	Check the _problems_.log in My webMethods Server current logging directory for more specific error information.

POP.004.0050E	**Unable to remove Notification.**
Explanation	The server was unable to locate the notification in order to delete it.
Action	Correct the invoking method to specify a valid notification parameter.

POP.004.0051E	**Unable to remove Event.**
Explanation	The server cannot remove the event item from the database due to a SQL error while executing the stored procedure that performs the removal.
Action	Check the _problems_.log in My webMethods Server current logging directory for more specific error information.

POP.004.0052E **Start index beyond end of list.**

Explanation The server cannot list a page of metadata resources because the specified start index of the page is greater than the total number of resources in the list.

Action Correct the source code that executes the query. Specify a start index that is less than the total number of resources in the list by modifying the start property of the com.webmethods.portal.service.view.IPagingCookie.

POP.004.0053E **Paged before first item.**

Explanation The server cannot list a page of metadata resources because the specified start or end index of the page is less than one.

Action Correct the source code that executes the query. Specify a start index that is less than the total number of resources in the list by modifying the start or end properties of the com.webmethods.portal.service.view.IPagingCookie.

POP.004.0054E **Invalid end index.**

Explanation The server cannot execute a paged container query because the page-start index is greater than the page-end index.

Action Correct the source code that executes the query. Specify a start index that is less than the end index by modifying the start and end properties of the com.webmethods.portal.service.view.IPagingCookie.

POP.004.0055E **Invalid sort order for getTreeView.**

Explanation The server cannot sort the tree view's results with the supplied sort parameter.

Action Correct the invoking code to pass valid sort parameters.

POP.004.0056E **Error saving subscription. No subscription or source information.**

Explanation The server cannot add the subscription because the subscription information is corrupted.

Action Correct the invoking method to specify a valid subscription parameter.

POP.004.0057E **Error adding subscription. No subscription or source information.**

Explanation The server cannot add the subscription because the subscription information is corrupted.

Action Correct the invoking method and ensure that the proper parameters are passed.

POP.004.0059	**Can't create an archived thing, use deactivate or delete.**
Explanation	The archived thing type cannot be created directly. It is created automatically when object is deleted
Action	Check and correct MWS API used when creating new object instance

POP.004.0060	**Unable to save Role.**
Explanation	A database error occurred when saving role information
Action	Check logs for additional exception details

POP.004.0061E	**Unable to load Role.**
Explanation	The server cannot load the metadata information for a registered role.
Action	Using the Role Administration portlet, regenerate and configure the role.

POP.004.0062E	**Missing results from the database.**
Explanation	The server has received invalid results from a stored procedure.
Action	Verify that the database has been properly configured and that the schema was properly installed by paying close attention to the installation process.

POP.004.0063E	**Access model not set.**
Explanation	The access service cannot evaluate access rights for a user until its access model has been specified.
Action	Correct the portal.properties file in the My webMethods Server config directory so that it has the following line: framework.access.model=restrictive.

POP.004.0064E	**Access model is not valid.**
Explanation	The server cannot set the access model because the specified model is unknown. The valid model values are 1 (permissive) and 2 (restrictive).
Action	Correct the portal.properties file in the My webMethods Server config directory so that it has the following line: framework.access.model=restrictive.

POP.004.0065E	**Serialized object version is different then current version: [version, currentVersion] [{0},{1}]**
Explanation	The server cannot read the alias stored in the database because its serialized object version is out of date.
Action	Revert to the previous version of wm-caf-server.jar, and restart the My webMethods Server.

POP.004.0066E	**Unknown type: {0}**
Explanation	The server cannot initialize the directory search control because the specified query type is unknown.
Action	Correct the code invoking directory search to specify a type of 1 (users) or 2 (groups).

POP.004.0067E	**Attempted to set subkey on primary-key only key.**
Explanation	The server cannot create the cache key.
Action	Correct the invoking method to include appropriate cache key parameter.

POP.004.0068E	**Can't find or create valid cache.**
Explanation	The cache update stored procedure cannot resolve the cache identifier.
Action	Correct the invoking source code to provide a cache-key with a valid cacheID. Consult the API documentation for more information.

POP.004.0069E	**Cache error: data is not a serializable object**
Explanation	The server attempted to cache an object that is not serializable.
Action	Correct the source code that invokes the com.webmethods.portal.service.cache.impl.DBCache.getBytesFromObject() method to pass serializable object.

POP.004.0070E	**Invalid connection parameters.**
Explanation	The server cannot connect to the remote FTP server.
Action	Verify that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.

POP.004.0071E	**Error persisting directory config.**
Explanation	The server cannot store the directory configuration modifications.
Action	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.

POP.004.0072E	**Cannot lookup non user or group thing based objects : {0}**
Explanation	The server cannot look up directory service resources using metadata identifiers unless the resource is a user, group, or role.
Action	The identifier specified by the error message does not identify a directory resource, do not try to use it to identify a directory resource.

POP.004.0073E	**Invalid URI, no directory service specified for URI -** "{0}"
Explanation	The server cannot locate an invalid directory user.
Action	Use the Directory Service Administration portlet to verify that the directory service is properly configured.

POP.004.0074E	**Specified domain in URI not found [domain, uri] -- [{0}, {1}]. This can be due to directory service being disabled or removed**
Explanation	The server cannot look up the directory service based on a Portal identifier because the identified directory service does not exist.
Action	This error may have happened because the specified directory service configuration was deleted. Try re-adding the directory service using the Directory Services Administration portlet (in the Portal Configuration category of the Portal Admin Dashboard).

POP.004.0075	**Cannot add directory service, service already exists: {0}**
Explanation	Directory service name must be unique.
Action	Check and correct directory service name being created.

POP.004.0076E	**Error adding new directory service: {0}**
Explanation	The server cannot add or update a directory service because of an error in validating or storing the directory service configuration.
Action	Check the _problems_.log in the My webMethods Server current logging directory for more specific error information.

POP.004.0077E	**Cannot build URI, unknown type 0**
Explanation	The server cannot construct a My webMethods Server identifier for the directory service object because the specified type is not one of user, group, or role.
Action	Correct the source code that invokes the com.webmethods.portal.server.directory.impl.DirectoryTools.constructDirectoryURI() method to specify only either user, group, or role.

POP.004.0078E	**Invalid escape character in {0} at position {1}**
Explanation	The server was unable to normalize the LDAP DN.
Action	Investigate the original DN and try to remove offending characters if possible.

POP.004.0079E	**Cannot retrieve most significant attribute; invalid DN: "{0}"**
Explanation	The server cannot parse a directory service object DN (the object's LDAP ID), because the DN is invalid.
Action	Supply a valid DN to the com.webmethods.portal.service.directory.impl.jndi.JNDITools class's getMostSignificantAttr() and getMostSignificantAttrSet() methods.

POP.004.0080E	**Unable to connect to: {0}**
Explanation	The server cannot connect to the remote LDAP directory store.
Action	Verify that the Directory configuration is valid by using the Directory Service Administration portlet.

POP.004.0081E	**No user class specified in directory factory config**
Explanation	The server cannot store the directory configuration modifications.
Action	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.

POP.004.0082E	**No group class specified in directory factory config**
Explanation	The server cannot initialize the directory service.
Action	Verify that the Directory service is properly configured by using the Directory Service Administration portlet.

POP.004.0083E	**Unable to wrap object. Unkown type: {0}**
Explanation	The server was unable to read an LDAP entry.
Action	Use the Directory Services Administration portlet to verify that the Directory configuration is valid.

POP.004.0084	**Unable to wrap LDAP object: {0}**
Explanation	There was an error fetching LDAP object properties
Action	Check MWS logs for additional exception details

POP.004.0085E	**Error setting attribute [name, value, action, message] - [{0}, {1}, {2}, {3}]**
Explanation	The server cannot modify the LDAP attribute.
Action	Verify that the connection to the LDAP directory store has adequate privileges to modify LDAP entries. Use your LDAP vendor's administration tool.

POP.004.0086E	**No response controls for directory: {0}**
Explanation	The server cannot update the directory search control.
Action	Start a new search.

POP.004.0087E	**Cannot page backward**
Explanation	The server cannot page directory search control backwards because the control is at the first page of results.
Action	Correct the source code invoking the directory search to check if the search has previous results before trying to page back to previous results. You can determine if a search has previous results by inspecting the value of the hasPrevious property of the com.webmethods.portal.service.view.IPagingCookie that you used to perform the search.

POP.004.0088E	**Cannot page forward**
Explanation	The server cannot page the directory search control forward because the search has no more results.
Action	Correct the source code invoking the directory search to check if the search has more results before trying to page forward. You can determine if a search has more results by inspecting the value of the hasNext property of the com.webmethods.portal.service.view.IPagingCookie that you used to perform the search.

POP.004.0089E	**Unable to retrieve user list**
Explanation	The server cannot list the users of a directory service, there might be a problem connecting to the directory service.
Action	If the directory service was recently configured directory service, go back to the My webMethods Server Admin Dashboard, and double-check the configuration using the Directory Service Administration portlet. Verify that the LDAP or ADSI server that connects to the directory service is up and running properly. Verify that the server the hosts My webMethods Server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.

POP.004.0090E	**Unable to lookup user {0}**
Explanation	The server cannot locate the specified user.
Action	Use the User and Group Management portlet to verify that the group exists in the LDAP directory store.

POP.004.0091E	**Invalid username or password**
Explanation	You have supplied invalid credentials.
Action	Try authenticating again with proper user name and password.

POP.004.0092E	**Could not lookup DN {0}**
Explanation	The server cannot look up a user or group by directory DN, the user or group's LDAP ID, because an error occurred while querying the directory store.
Action	Check the _problems_.log in My webMethods Server current logging directory for more specific error information.

POP.004.0093E	**Error looking up group {0}**
Explanation	The server cannot locate the specified group.
Action	Verify that the Directory service is configured by using the Directory Service Administration portlet.

POP.004.0094E	**Unable to perform search : {0}**
Explanation	An unknown error occurred while performing an LDAP directory search.
Action	Correct the invoking method to specify a valid query parameter.

POP.004.0095E	**Error getting memberships**
Explanation	The server cannot get membership information from the LDAP directory store.
Action	Verify that the Directory configuration is valid by using the Directory Service Administration portlet.

POP.004.0096E	**Unable to modify password of user {0} because the supplied old password is incorrect.**
Explanation	An attempt was made to change a user's password without supplying the user's existing password.
Action	Supply the correct existing password.

POP.004.0097E	**INSTALL is not supported operation for: {0}**
Explanation	Installation of the deployable object has failed.
Action	The deployable object does not have any installation code associated with its file extension. Do not attempt to deploy an unsupported type to the My webMethods Server.

POP.004.0098E	**UNINSTALL is not supported operation for: {0}**
Explanation	The server cannot uninstall the specified type of component.
Action	The specified component was not uninstalled; try again.

POP.004.0100E	**Component file not found: {0}**
Explanation	The server cannot install the component the component was not found at the specified location.
Action	Specify the correct location. If you are installing a component using the Install Administration portlet, select a valid location using the portlet's Browse button.

POP.004.0101E	**Cannot set properties for installer: {0}**
Explanation	The server cannot set install services because an internal error occurred.
Action	Check the _problems_.log in My webMethods Server current logging directory for more specific error information.

POP.004.0102E	**Script file not found: {0}**
Explanation	The server cannot execute a portlet deployment script.
Action	Using My webMethods Server, rebuild and redeploy the portlet.

POP.004.0103E	**Install script finished with {0} error(s). Please look at the install.log for details**
Explanation	An error occurred while installing or uninstalling a deployable component.
Action	Examine the logs, and try again. Look for the information specific to the deployed component in the install.log file.

POP.004.0104E	**Error installing/uninstalling component**
Explanation	An error occurred while installing or uninstalling a deployable component.
Action	Examine the logs, and optionally try again. Look for the information specific to the deployed component in the install.log file.

POP.004.0105E	**Failed to initialize LoggingCollector: {0}**
Explanation	The server cannot initialize logging over the JMS provider.
Action	Verify that the JMS server is running and configured.

POP.004.0106E	**PortletInfo is not available for uri [{0}]. Probably the portlet is not properly installed. Try to uninstall and then install it again.**
Explanation	Portlet is not currently available.
Action	Try to uninstall and then re-install the portlet again.

POP.004.0107E	**Invalid portlet descriptor. Portlet/DBO name is not defined**
Explanation	The server cannot load portlet information from the portlet descriptor because the portlet descriptor does not contain the portlet's name, or the portlet descriptor is incorrectly structured.
Action	Using the My webMethods Server to correct the portlet descriptor and redeploy it to the My webMethods Server.

POP.004.0109E	**Portlet URI is not published instance of the portlet or type. Unable to persist properties**
Explanation	The server cannot persist the properties of a portlet type without a valid portlet or portlet type identifier.
Action	Supply a valid portlet or portlet type identifier to the com.webmethods.portal.service.portlet.impl.PortletType.setProperties() method.

POP.004.0110E	**Portlet bean class is invalid: {0}**
Explanation	The server cannot initialize the portlet because the portlet does not implement the required interface.
Action	Using My webMethods Server to correct the portlet's deployment descriptor or regenerate the portlet, and then redeploy it.

POP.004.0111E	**Portlet bean is not poolable: {0}**
Explanation	The server cannot instantiate the portlet bean because the bean does not implement the com.webmethods.portal.system.pool.IPooledObject interface.
Action	Use My webMethods Server to correct the portlet bean source code to implement IPooledObject.

POP.004.0112E	**Portlet title bar class is invalid: {0}**
Explanation	The server cannot initialize portlet type information because the portlet titlebar class specified by the portlet's descriptor was not found.
Action	Using the Portlet Developer, remove the titlebar class specification from the portlet descriptor and then redeploy the portlet.

POP.004.0113E	**Invalid URI, no search service specified: {0}**
Explanation	The server cannot locate search provider because of an invalid URI.
Action	Correct the invoking code to use a valid URI.

POP.004.0114E	**Invalid datasource name: {0}**
Explanation	The server cannot execute a SQL statement against an invalid datasource.
Action	Correct the invoking method to pass the correct parameters. One of the critical parameters is the handle of the datasource, which can be obtained from the DataManager's API.

POP.004.0115S	**Can't find data service folder: {0}**
Explanation	The server cannot locate the system folder.
Action	It is possible that a system administrator has deleted a critical system folder. If so, you might need to reinstall My webMethods Server.

POP.004.0116E	**Cannot obtain database connection from pool: {0}**
Explanation	The server cannot obtain a database connection because all connections allocated for My webMethods Server are already in use or My webMethods Server cannot connect to the database.
Action	Verify that the database is running and is not experiencing a heavy load. Verify that the database has an adequate number of connection threads available. Verify that the machine on which the My webMethods Server is running can access the datasource's configured host name and port.

POP.004.0117E	**Database connection is closed.**
Explanation	The server cannot execute the SQL query because the database connection is closed.
Action	Execute the statement again. If problems persist, shut down and restart My webMethods Server.

POP.004.0118E	**Error updating Clob field**
Explanation	An error occurred while updating an unbounded size database field at the database level.
Action	Try the operation again.

POP.004.0119E	**Error updating Blob field**
Explanation	An error occurred in updating an unbounded size database field at the database level.
Action	Try the operation again.

POP.004.0120E	**Could not find content service for: {0}**
Explanation	The server cannot store versioned content for a resource because the content service for the resource was not found.
Action	Delete the resource.

POP.004.0121E	**Versioned content uri is null or empty: {0}**
Explanation	The server cannot access the versioning information.
Action	The version information is corrupted. Try to obtain a different version and recreate the changes.

POP.004.0122E	**Content doesn't exist: {0}**
Explanation	The server cannot read a resource's versioned content because the resource has no content.
Action	Delete the resource using the UI.

POP.004.0123E	**User ID is invalid: {0}**
Explanation	The server cannot locate the user's information about the versioned object.
Action	The version information is corrupted. Use the Publish portlet to publish a new instance of the item, and add the item to versioning. Consult the My webMethods Server documentation.

POP.004.0124E	**Could not find user: {0}**
Explanation	Cannot locate the user's information about the versioned object.
Action	The version information is corrupt. Publish a new instance of the item, and add the item to versioning.

POP.004.0125E	**Could not find thing: {0}**
Explanation	Cannot resolve metadata resource identifier from string.
Action	The resource specified by the identifier does not exist; do not use the identifier.

POP.004.0126E	**Cookie is not set on the List View**
Explanation	The server cannot sort or slice the list without a paging cookie.
Action	Correct the invoking source code to associate the paging cookie with the list by setting the cookie property of the list.

POP.004.0127E	**Unable to initialize directory service {0}: {1}**
Explanation	The server cannot initialize the directory service due to an error.
Action	Verify the connection information to the directory service using the Directory Service Administration portlet. Verify that the login credentials are accurate. Verify that there is network connectivity to the directory service from My webMethods Server.

POP.004.0128E	**Invalid directory Uri: "{0}"**
Explanation	The URI is malformed.
Action	Correct the invoking method to specify a valid URI parameter.

POP.004.0129	**Uri "{0}" should resolve to principal object, but was found: {1}**
Explanation	Attempting to look up a directory principal by a URL that does not resolve to a valid directory object.
Action	Check and correct directory API usage. Verify that the URI value used to look up directory object is valid.

POP.004.0130E	**Unidentified Clob implementation class: {0}**
Explanation	The server cannot retrieve an unbounded-length field from the database because the database driver is incompatible with My webMethods Server.
Action	Modify the datasource driver settings in the db.xml My webMethods Server configuration file to use approved driver.

POP.004.0131S	**Unidentified Blob implementation class: {0}**
Explanation	The server cannot retrieve result set data because of an incompatible database implementation.
Action	Verify that the correct version of Oracle is installed and that you are using the My webMethods Server supplied database drivers. You can consult your Oracle installation documentation to verify the version of Oracle and ensure that you have nt added any custom Oracle drivers in the class path.

POP.004.0132E	**Xtype not found: {0}**
Explanation	The server cannot locate the portlet xtype in the metadata store.
Action	Most likely the portlet has been undeployed. Use the Install Administration portlet to redeploy the portlet.

POP.004.0133	**XType already registered: {0}**
Explanation	Every XType (Portlet Name, Dynamic Business Object) must have a unique name. An attempt was made to install a new portlet or application that contains a portlet or Dynamic Business Object which is already registered in MWS.
Action	Check to see if an application or portlet was renamed. It is also possible that a component un-install was not fully successfull, in this case use /compnonent/development/tools/wm_remove_portlet to clean up and delete component registration in MWS.

POP.004.0134E	**Error loading class group: {0}**
Explanation	The server cannot load all the classes for the specified class loader group.
Action	Check the _problems_.log in My webMethods Server current logging directory for more specific error information.

POP.004.0135E	**Error setting config on directory, rolling back to previous config.**
Explanation	The server cannot store the directory configuration modifications.
Action	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.

POP.004.0136E	**Unable to retrieve group list.**
Explanation	The server cannot get group information from the LDAP directory store.
Action	Verify that the directory configuration is valid by using the Directory Service Administration portlet.

POP.004.0141E	**No configuration information found for content service, not initializing: {0}.**
Explanation	The server cannot initialize the content service.
Action	If you cannot reconfigure the offending content service by using the Content Service Admin portlet call Software AG Global Support for a reset directive.

POP.004.0144I	**FTPconnection connect to {0}.**
Explanation	A connection was initiated with the remote FTP server.
Action	This is an informative statement. No action is necessary.

POP.004.0152E	**No Query Parameters specified.**
Explanation	The server cannot execute the search because there is no search query.
Action	Navigate to the Search portlet and try again.

POP.004.0153E	**Search Server is unavailable or not properly configured**
Explanation	The server cannot access the search service.
Action	Verify that the search service is properly configured by using the Search Admin portlet.

POP.004.0155E	**Error adding file to search index: {0}**
Explanation	The server was unable to properly index a My webMethods Server component object.
Action	Determine if the document is in an unknown format or is malformed. Examine the Lucene Search Admin portlet for details on formats.

POP.004.0156E	**content stream is null**
Explanation	The server cannot locate the content file in the content repository.
Action	Verify that the existence of the content repository and network connectivity. The content repository has some configuration information in the storageConfig.xml. If a custom content service has been mounted, then verify that connectivity between the My webMethods Server process and the network file system is intact. Verify that you can browse to the content using My webMethods Server. Purge all items pending deletion with the Manage Deleted Items Admin Portlet.

POP.004.0157E	**Error getting resync list for library: {0}**
Explanation	The server cannot resynchronize the search library index because an error occurred in querying the database for the list of resources to index.
Action	Restart the My webMethods Server.

POP.004.0158E	**Malformed Language Pack: {0}**
Explanation	The server cannot use the language pack because its name is malformed. The name should be one of [language], [language]_[country], or [language]_[country]_[variant], where [language] is a language code such as en or ja, [country] is a country code such as US or JP, and [variant] is a variant code.
Action	Correct the language pack name and re-install language pack.

POP.004.0187	**Could not lookup URI {0}**
Explanation	If the URI points to an invalid directory object (user or group) an error occurs.
Action	Check and correct directory API usage. Check what URI value was used. This error might also occur if the user was deleted immediately before logging in. The error will go away when MWS caches are updated, usually within seconds.

POP.004.0196	**Role Modification is not supported for: {0}.**
Explanation	Only static roles support modification of role membership. This error is thrown when attempting to modify membership using the directory APIs for non-static roles
Action	Check and correct directory API usage. Check to see if the role being modified is static role

POP.004.0197	**Failed to set property "{0}". Reason: {1}**
Explanation	Error has occurred when setting the thing object properties. This might happen when attempting to set the property of a specific java type, but passing in an incompatible value.
Action	Check MWS logs for additional error information. Check the values the code attempted to update and determine if the actual property types are valid.

POP.004.0198E	**Cannot create a user with a duplicate id: {0}**
Explanation	An attempt was made to create a new user with a duplicate ID of an existing user.
Action	Use a unique identifier when creating a new user, group or role.

POP.004.0199E	**Cannot create a group with a duplicate id: {0}**
Explanation	An attempt was made to create a new user with a duplicate ID of an existing user.
Action	Use a unique identifier when creating a new user, group or role.

POP.004.0200	**Cannot create database connection to default MWS datasource.**
Explanation	Unable to create database connection to MWS database schema.
Action	Check MWS database connection configuration in MWS/server/default/config/mws.db.xml config file.

POP.004.0201	**Cannot initialize MWS, invalid database schema is specified**
Explanation	MWS validates if database schema contains correct tables and then throws this error if it is not configured.
Action	Check if MWS database schema was correctly created by dbConfigurator tool. You might need to drop and re-create MWS schema.

POP.004.0202	**Cannot create database connection to default MWS datasource. Please verify database connection parameters in the MWS/server/{0}/config/mws.db.xml configuration file**
Explanation	An issue has occurred with the database connection configuration file such as invalid XML or an incorrect JDBC driver name.
Action	Verify the database connection parameters in the MWS/server/default/config/mws.db.xml configuration file.

POP.004.0203	**User {0} can not set access on {1}**
Explanation	User does not have access rights to set or update permissions.
Action	See if the user or groups and roles, the user is a member of has access rights to set permissions on a given object.

POP.004.0204	**Failed to search business data with the "taskTypeID" query term specified.**
Explanation	The taskTypeID is not specified in task search term.
Action	Provide a valid taskTypeID as a task search term.

POP.004.0205	**Unable to locate whitelist storage object**
Explanation	The required whitelist storage object cannot be located.
Action	Contact the system administrator to make sure that whitelist storage has been configured.

POP.004.0206 **Failed to connect to database at {0}. Verify hostname/port and connection credentials.**

Explanation Failed to connect to database.

Action Make sure the database is running and has a network connection, and that the proper credentials are in use. Otherwise, contact the system administrator to make sure database has been configured correctly.

POP.004.0207 **Unable to update whitelist storage object**

Explanation Your user account has not been granted the privilege for updating a whitelist storage object.

Action Contact the system administrator if you need this privilege.

POP.004.0209 **Role name is empty.**

POP.005.0002E **Can Not Re-initialize CDS library**

Explanation An attempt was made to initialize the system twice.

Action After My webMethods Server is initialized, do not attempt to do so again.

POP.005.0003E **Error parsing segment urls: "{0}"**

Explanation One of the My webMethods Servers in the cluster has an incorrect URL.

Action Determine the correct URL for the My webMethods Server, then log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to correct the error.

POP.005.0004E **Unable to register component: "{0}" due to "{1}"**

Explanation My webMethods Server could not register the specified component.

Action Look in the _problems_.log file for the stack trace of the error. It might be necessary to reinstall the component.

POP.005.0005 **Unable to reload component: "{0}" due to "{1}"**

Explanation During dynamic reloading of a component (for example, a portlet), an error occurred.

Action Check the logs to investigate what component failed to be reloaded. If the component is a portlet, then try uninstalling the portlet and reinstalling it, or try to revert to a previous version of the portlet.

POP.005.0006E	**This server node is not defined in the MWS cluster configuration: "{0}"**
Explanation	The specified My webMethods Server is not included in the cluster configuration.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to add the specified My webMethods Server to the cluster.

POP.005.0007	**Front End URL is not specified in the MWS cluster configuration**
Explanation	The cluster doesn't have a valid configuration.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.

POP.005.0008E	**internal cache error**
Explanation	An internal error occurred while removing an item from a cache.
Action	Inspect the _problems_.log for details of the failure. This error could indicate that there is invalid data in a cache. Restart My webMethods Server to address the problem.

POP.005.0009E	**Unable to loadComponent: "{0}"**
Explanation	A failure occurred while loading a My webMethods Server component.
Action	Look in the _problems_.log file for the stack trace of the error. It may be necessary to reinstall the component.

POP.005.0010E	**Unknown object: "{0}"**
Explanation	The ComponentData object for a component is of an unknown type.
Action	The componentData must be one of the handled object types. This error means that a My webMethods Server component could not initialize because it is invalid. Check the component for a valid configuration.

POP.005.0013	**Command not found: "{0}"**
Explanation	A request to obtain a registered command failed. The command does not exist.
Action	Check the custom portlet invoking the command and ensure that it is specifying a deployed command.

POP.005.0014	**Unbalanced "{1}" in value expression: "{0}"**
Explanation	A legacy portlet has created an illegal dynamic expression.
Action	Review the custom portlet for proper syntax of any dynamic expressions.

POP.005.0021	**Attempting to use non empty My webMethods Server database for fresh deployment. Please make sure to create new empty My webMethods Server database**
Explanation	A first time startup check determined that the configured database is not a new database. A new database is required for a new installation.
Action	You must create new (empty) My webMethods Server database and configure My webMethods Server to connect to it. Please refer to the Software AG documentation for installing webMethods products.

POP.005.0022	**Wrong version of My webMethods Server database: {0} but expected: {1}**
Explanation	A first time startup check determined that the configured database does not match the schema required by My webMethods Server.
Action	Verify that the specified database is properly configured. The database is likely configured with an old or incomplete schema. Please refer to the Software AG documentation for installing webMethods products.

POP.005.0026	**Must have at least one server node defined**
Explanation	The cluster does not have a valid configuration. No server nodes are defined.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.

POP.005.0028	**"{0}" server node must have at least one web stack listener enabled**
Explanation	Each node in the cluster is required to have at least one port enabled for accepting web requests.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.

POP.005.0029	**server node name must not be empty**
Explanation	The cluster does not have a valid configuration. A server node name is not defined.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.

POP.005.0030	**Credentials required.**
Explanation	Credentials of a valid My webMethods Server user are required.
Action	Provide the user name and password of a valid My webMethods Server user account.

POP.005.0031	**Credentials should be String[].**
Explanation	Credentials must be supplied in a string array format.
Action	Configure the JMX client to provide credentials in a string array format.

POP.005.0032	**Credentials should have 2 elements.**
Explanation	Two credential elements (user name and password) were expected, but a non-matching number of elements were provided.
Action	Provide only the user name and password.

POP.005.0033	**JMX Authentication failed!**
Explanation	The user cannot be authenticated within My webMethods Server.
Action	Provide a valid My webMethods Server user.

POP.005.0034	**JMX Authorization failed!**
Explanation	The provided user does not have sufficient privileges for connecting via JMX.
Action	Provide a user with the "Connect to JMX" privilege.

POP.005.0035	**Insufficient privileges for establishing JMX communication!**
Explanation	The provided user does not have sufficient privileges for connecting via JMX.
Action	Provide a user with the "Connect to JMX" privilege.

POP.005.0036	**JMX Server Port number cannot be parsed. Port parameter value "{0}".**
Explanation	The provided JMX port number is not an available port number.
Action	Change the JMX port configuration property to an available port number.

POP.005.0037	**JDK 1.6 or higher is required to run JMX over SSL.**
Explanation	My webMethods Server is currently started with JDK 1.5.
Action	Update the My webMethods Server JDK to JDK 1.6.

POP.005.0039	**Cannot start CDS library because MWS did not initialize yet**
Explanation	The CDS library cannot start because My webMethods Server has not initialized yet.
Action	Wait for My webMethods Server to initialize before starting the CDS library.

POP.005.0040	**Cannot start common directory service because IS was started before MWS. Complete the MWS upgrade, which includes starting MWS, before performing the IS upgrade, which includes starting IS. See the upgrade guide for correct order.**
Explanation	The CDS library cannot start because the My webMethods Server upgrade has not completed yet.
Action	Complete the My webMethods Server upgrade before starting the CDS library.

POP.005.0041	**Unable to start server at port number {0} on host {1} (for: {2}) , reason : {3}. Perhaps another MWS process is already running?**
Explanation	The server cannot be started at the specified port on the specified host due to the specified reason.
Action	Make sure that no other My webMethods Server instance is running on the same host using the same port.

POP.005.0042	**Unable to start. The server name {0} could not be found in the cluster definition**
Explanation	The server cannot start because the specified server name cannot be found in the cluster definition.
Action	Make sure that the server name matches the name specified in the cluster definition.

POP.005.0043	**The JMS communication layer for common directory services (CDS) failed to initialize, which causes CDS assets to be out of sync. To enable JMS communication, specify a valid JNDI Provider URL on the Cluster Administration page in My webMethods and restart Integration Server.**

POP.006.0003E	**portlet bean URI not specified**
Explanation	The portlet:bean JSP tag does not contain a uri attribute to identify a valid portlet instance.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'uri' attribute. The attribute value must identify a valid portlet instance. Also, ensure that the portlet type referenced by the 'uri' attribute has been deployed and that all instances referenced by the attribute exist.

POP.006.0004E	**cannot create portlet bean for the URI "{0}"**
Explanation	The portlet:bean JSP tag does not contain a uri attribute that identifies a valid portlet instance.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'uri' attribute. The attribute value must identify a valid portlet instance. Also, ensure that the portlet type referenced by the 'uri' attribute has been deployed, and that all instances referenced by the attribute exist.

POP.006.0005	**parent "{0}" not found**
Explanation	The JSP page is invalid, because a JSP tag that is only valid when it is inside of a parent JSP tag is not inside the expected parent.
Action	Locate the error in the JSP page and correct the problem.

POP.006.0006E	**cannot find portlet bean named "{0}" in the current page context**
Explanation	The portlet:portletController JSP tag does not contain a portlet attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.IPortletBean object is stored.
Action	Ensure that all instances of the 'portlet:portletController' JSP tag include a 'portlet' attribute that references a valid IPortletBean.

POP.006.0007E	**cannot obtain portlet info**
Explanation	The portlet:info JSP tag does not contain an info attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletInfo object is stored.
Action	Ensure that all instances of the 'portlet:info' JSP tag include an 'info' attribute that references a valid IPortletInfo object.

POP.006.0008E	**cannot find portlet info named "{0}" in the current page context**
Explanation	The portlet:propertyGroups, portlet:propertyGroup, or portlet:propertyLine JSP tag does not contain an info attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletInfo object is stored.
Action	Ensure that all instances of the 'portlet:propertyGroups', 'portlet:propertyGroup', and 'portlet:propertyLine' JSP tags include an 'info' attribute that references a valid IPortletInfo object.

POP.006.0015	**cannot obtain portlet property info**
Explanation	The portlet configuration information could not be found. This problem could result from an invalid JSP page or a portlet installation that has been corrupted.
Action	Review the JSP page and ensure the portlet:propertyLine JSP tag is contained within a portlet:bean tag. If the JSP is correct and the problem persists, try re-installing the broken portlet.

POP.006.0016E	**cannot find portlet property info named "{0}" in the current page context**
Explanation	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletPropertyInfo object is stored.
Action	Ensure that all instances of the 'portlet:propertyLine' JSP tag include a 'propertyInfo' attribute that references a valid IPortletPropertyInfo.

POP.006.0017	**portlet property name not specified**
Explanation	The JSP page contains a portlet:propertyLine tag that is missing the required "name" property.
Action	Review the JSP page and correct any missing "name" properties.

POP.006.0018E	**cannot obtain portlet property bag**
Explanation	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.

POP.006.0019E	**cannot find portlet property bag named "{0}" in the current page context**
Explanation	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.

POP.006.0020E	**object named "{0}" in the current page context is not a portlet property bag**
Explanation	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.

POP.006.0021	**"{0}" requires body content**
Explanation	A JSP page contains an sql:query tag with missing SQL query text in the tag body.
Action	The JSP page must be edited to either remove the tag or add the SQL query text as the tag body.

POP.006.0022	**skin property not found**
Explanation	In a JSP page, the ui:img tag is trying to render an image from the skin, but the image was not defined in the skin.
Action	Edit the skin to add the missing image, or change the JSP page to reference an image that does exist.

POP.006.0024E	**'IterateTag' container is null**
Explanation	The util:iterate JSP tag does not contain a container attribute. The value of this attribute is the key to the pageContext entry in which a java.util.Collection, java.util.Iterator, or java.lang.Object[] object is stored.
Action	Ensure that all instances of the 'util:iterate' JSP tag include a 'container' attribute that references a valid container object.

POP.006.0025	**"{0}" class not supported as an 'IterateTag' container**
Explanation	A JSP page uses the util:iterate tag, but the value of the 'container' property is not one of the supported data types.
Action	The JSP page must be edited to correct the problem.

POP.006.0026	**"{0}" requires "{1}" attribute**
Explanation	A JSP page uses the util:iterate tag, but the "indexVar" tag attribute was not supplied.
Action	The JSP page must be edited to add the missing tag attribute.

POP.006.0027	**cannot find 'PerfStartTag' token named "{0}"**
Explanation	A JSP page uses the util:perfEnd tag, but the perf token supplied in the "name" tag attribute does not exist.
Action	This problem most likely results from a malformed JSP page. The JSP developer should review the JSP page for any mismatched util:perfStart/util:perfEnd pairs.

POP.006.0028E	**cannot find XML DOM node named "{0}" in the current page context**
Explanation	Use of the xml:valueOf JSP tag causes this exception.
Action	Remove all instances of the 'xml:valueOf' JSP tag.

POP.006.0029E	**cannot create XML DOM document from given XML stream**
Explanation	The XML stream specified for the xml:xml JSP tag does not contain well-formed XML.
Action	Check the _problems_.log in the Portal's current logging directory for more specific error information.

POP.006.0030E	**cannot load XML DOM document for the specified location "{0}"**
Explanation	The xml:xml JSP tag could not load a file from the location specified by the 'location' attribute.
Action	Edit instances of the 'xml:xml' JSP tag to include a 'location' attribute that correctly specifies the url to an XML document.

POP.006.0031	**Required Property Editor parameter "{0}" not specified.**
Explanation	A JSP page is rendering a property editor, but a required parameter has not been supplied.
Action	The JSP developer should edit the JSP page to supply the missing required parameter.

POP.006.0032	**Property Editor "{0}" not deployed.**
Explanation	A JSP page is trying to render a property editor that is not deployed to My webMethods Server.
Action	Deploy the missing property editor to My webMethods Server, or change the JSP page to use a property editor that is deployed to My webMethods Server.

POP.006.0033	**invalid portlet bean URI: {0}**
Explanation	A JSP page is using either the portlet:bean or the portlet:controller tag in which the supplied portlet URI does not match an existing portlet instance.
Action	Deploy the missing portlet instance. Or, edit the JSP page to change the URI to match an exisitng portlet instance.

POP.007.0002	**Error getting directory mechanics: "{0}"**
Explanation	The My webMethods Server instance was not properly installed.
Action	Re-create the My webMethods Server database schema and the My webMethods Server server instance.

POP.007.0003	**Error rendering layout "{0}" due to "{1}"**
Explanation	There was an error either compiling or executing the application *.JSP page.
Action	You may need to run My webMethods Server with a full JDK which includes the Java compiler. Or, if you have modified any system JSP or NBSP pages, there may have been a syntax error.

POP.007.0006	**Requested content was not found: "{0}"**
Explanation	An error occurred when attempting to browse to a page or file; the page or file does not exist in My webMethods Server.
Action	Verify that the URL being browsed to is correctly formed and specifies a valid URL.

POP.007.0007E	**Command not Found: "{0}"**
Explanation	An attempt was made to execute a server command that is not deployed.
Action	Log in to My webMethods Server and use the Install Administration portlet to deploy the missing portlet.

POP.007.0008	**The requested resource is not a webservice: "{0}"**
Explanation	An attempt was made to obtain a WSDL for a resource that is not a web service.
Action	Modify the request to specify a resource that is a web service.

POP.007.0009	**You are not authorized to view the resource.**
Explanation	The current user does not have permission to view the specified object or page.
Action	Check the permissions for the object or page to ensure that the user has read rights

POP.007.0010E	**This renderer is unable to render: "{0}"**
Explanation	An attempt was made to use the FolderRenderer to render an item that is not a folder.
Action	You cannot use the FolderRenderer for non-folders; specify a valid folder.

POP.007.0011E	**Unknown response: "{0}"**
Explanation	The dispatch handler returned an unknown return code.
Action	Correct the dispatch handler to return a valid return code.

POP.007.0012	**Cannot redirect to an invalid data type: "{0}"**
Explanation	An incorrect API was called when redirecting to new URL. This error is most likely to occur with a custom portlet.
Action	Verify that the portlet specifies the correct API for redirection.

POP.007.0013	**Unable to find adequate authentication information to instantiate an http session**
Explanation	My webMethods Server is unable to authenticate an HTTP session.
Action	This error can occur because of incorrect implementation of custom authentication (such as, agent based authentication). Review the custom authentication scheme and verify that it is correctly implemented.

POP.007.0023	**getWriter() has already been called on this response.**
Explanation	This error indicates an incorrect usage of the HttpResponse.getWriter() API and most likely occurred in a custom CAF application.
Action	Review the CAF application and check the implementation of the HttpResponse APIs.

POP.007.0024	**getOutputStream() has already been called on this response.**
Explanation	This error indicates an incorrect usage of the HttpRespose.getOutputStream() API and most likely occurred in a custom CAF application.
Action	Review the CAF application and check the implementation of the HttpResponse APIs.

POP.007.0026	**Response body content already written.**
Explanation	This error occurs when attempting to set the HttpResponse header when the response has been already partially or fully committed. This most likely occurred in a custom CAF application.
Action	Review the CAF application and check the implementation of the HttpResponse APIs.

POP.007.0027	**Internal Error! Portlet Controller Bean is null.**
Explanation	The system cannot serve as the internal controller bean for the portlet.
Action	This error occurs only for non-CAF portlets. Log out and log back in to resolve this problem.

POP.007.0028	**User not found: "{0}"**
Explanation	This error occurs when a user ID passed into My webMethods Server by a custom authentication handler cannot be matched.
Action	Verify that the specified user exists in the My webMethods Server directories, and check the custom authentication handler logic.

POP.007.0029	**No authentication information was found.**
Explanation	No user name was supplied to My webMethods Server when authenticating a user. This error can occur with a custom authentication handler.
Action	Check the implementation of the custom authentication handler. Verify the proper operation of any custom login forms.

POP.007.0033	**No portlet found to render "{0}" view.**
Explanation	This error can occur if there is a registered portlet renderer, but the portlet defined in the renderer is not found.
Action	Renderers are used internally by My webMethods Server to define certain system pages. If this error occurs, check to see if any of the My webMethods Server system components have been un-installed.

POP.007.0035	**The value {0} can not be changed**
Explanation	An attempt has been made to change the value of an invalid portlet preference.
Action	Verify that the correct portlet preference name is used.

POP.007.0036	**The store() method can not be called from a render method**
Explanation	An attempt was made to change and persist portlet preferences from the render() method.
Action	Portlet preferences can be changed only with the portlet action method. Correct the code which updates portlet preferences to use the proper method.

POP.007.0037	**The state of the portlet can not be changed**
Explanation	Portlet preferences can be updated only during the action() request.
Action	Correct the usage of the portlet preferences APIs to change preferences during the action() request.

POP.007.0038 **The key given is null.**

Explanation An attempt was made to use the portlet preferences API with a NULL preference name.

Action Correct the portlet preferences API implementation to specify a valid preference name.

POP.007.0044 **The map given is null**

Explanation This error indicates an incorrect usage of the portlet URL APIs; the parameter map setting is NULL.

Action Correct the portlet URL APIs implementation to specify a valid parameter map.

POP.007.0045 **The map given contains a null key**

Explanation This error indicates an incorrect usage of the portlet URL APIs; the parameters map setting contains a NULL key.

Action Correct the portlet URL APIs implementation to specify a valid parameter map key.

POP.007.0046 **The map contains a non String key**

Explanation This error indicates an incorrect usage of the portlet URL APIs; the parameters map setting contains non-String values.

Action Correct the portlet URL APIs implementation to pass in only String type parameters.

POP.007.0047 **Namespace prefix defined more than once for {0}**

Explanation An incorrect URL was passed into My webMethods Server; more than one namespace prefix is provided.

Action Check that the URL passed into My webMethods Server contains only one single value for the namespace prefix.

POP.007.0048 **Namespace prefix is not defined for {0} and the prefix id is not a valid thingID**

Explanation An incorrect URL was passed into My webMethods Server; no namespace prefix is provided.

Action Modify the URL passed into My webMethods Server to define the missing namespace prefix.

POP.007.0049	**The portlet mode {0} is not supported for the {1} markup language.**
Explanation	The requested mode is not implemented in the portlet or is not supported.
Action	Check the portlet URL API usage if attempting to set the mode with APIs. If this is a custom portlet, check to see if the portlet implements this mode.

POP.007.0051	**Output generated because of an exception**
Explanation	An exception occurred while rendering portlet content.
Action	Refer to the server logs at ..\MWS\server\default\logs for additional exception details.

POP.007.0052	**sendRedirect was already called**
Explanation	An attempt was made to change the portlet window state, mode, or parameters after a redirect request was sent.
Action	Examine and correct the usage of the redirect request in the portlet code.

POP.007.0053	**The portlet mode is null**
Explanation	An attempt was made to set a NULL portlet mode.
Action	Examine and correct the usage of the Portlet URL API.

POP.007.0054	**The window state {0} is not supported by the portlet container**
Explanation	An attempt was made to set an invalid window state.
Action	Examine and correct the window state being set by the Portlet URL APIs.

POP.007.0055	**The window state is null**
Explanation	An attempt was made to set a NULL window state.
Action	Examine and correct the window state being set by the Portlet URL APIs.

POP.007.0056	**The portlet mode {0} is not supported by the portlet container**
Explanation	An attempt was made to set an invalid portlet mode.
Action	Examine and correct the portlet mode being set by the Portlet URL APIs.

POP.007.0057	**The map contains a non String[] value**
Explanation	An attempt was made to set a parameter with a value that is not of the type String[].
Action	Examine and correct parameters being by the Portlet URL API; these values must be String or String[] types only.

POP.007.0058	**The key given is null**
Explanation	An attempt was made to pass in a NULL key value.
Action	Examine and correct the key value that is being passed in by the Portlet URL AP1.

POP.007.0059	**The value given is null**
Explanation	An attempt was made to pass in a NULL value.
Action	Examine and correct the value being passed in by the Portlet URL API.

POP.007.0060	**The sendRedirect method can not be invoked after any of the following methods of the ActionResponse interface has been called: setPortletMode, setWindowState, setRenderParameter, setRenderParameters**
Explanation	The sendRedirect method can not be invoked after any of the following methods of the ActionResponse interface has been called: setPortletMode, setWindowState, setRenderParameter, setRenderParameters
Action	Correct the code to ensure that the sendRedirect() method does not occur after these calls during the same action request.

POP.007.0061	**A relative or incorrect path URL is given**
Explanation	An attempt was made to redirect to an invalid URL.
Action	Check the URL that is the target of the redirect. It must start with "http://", "https://", or "/".

POP.007.0062	**You cannot have null as a parameter**
Explanation	An attempt was made to pass in a NULL parameter name.
Action	Examine and correct the parameter name used in the PortletContext and PortletRequest APIs.

POP.007.0063	**Content type cannot be application/x-www-form-urlencoded**
Explanation	Incorrect API usage. The ServletRequest.getReader() and getInputStream() methods are not available for requests where a form is submitted.
Action	Examine and correct the ServletRequest.getReader() and getInputStream() API usage.

POP.007.0064	**This method cannot be called, when getReader() method has been called**
Explanation	The ServletResponse method cannot be used when the getReader() method has been called.
Action	Examine and correct the ServletResponse API usage.

POP.007.0065	**The attribute name cannot be null**
Explanation	An attempt was made to get or set an attribute using a NULL name.
Action	Examine and correct the attribute name being passed to the API.

POP.007.0066	**Path must start with /**
Explanation	An attempt was made to get a resource using an invalid path. The path of the resource must start with "/".
Action	Examine and correct the path name set by the PortletContext API.

POP.007.0069	**The content type {0} is not supported.**
Explanation	An attempt was made to set an invalid content type.
Action	Check and correct the content type being set by the PortletResponse API.

POP.007.0070	**The content type has not been set before calling the getPortletOutputStream() method.**
Explanation	The response content type must be set before obtaining the output stream.
Action	Examine and correct the API calls.

POP.007.0071	**the output stream has already been called**
Explanation	A Writer cannot be obtained for the response after obtaining the output stream.
Action	Examine and correct the API usage.

POP.007.0072	**the PrintWriter object has already been called**
Explanation	A Writer cannot be obtained for the response because the output stream has already been obtained.
Action	Examine and correct the API usage.

POP.007.0073	**Can not serialize Portlet Preferences**
Explanation	There was error when serializing portlet preferences. Portlet preferences cannot contain non-serializable objects.
Action	Check the server log for more details. Examine and correct any portlet preferences being set to ensure only serializable objects are used.

POP.007.0074	**Portlet Application "{0}" is not properly installed or unavailable.**
Explanation	The system cannot load the specified portlet application. It is either not installed or is disabled in the cluster partition.
Action	Re-install the portlet application. Check the server logs for errors during installation. Verify that the application is enabled in the cluster partition.

POP.007.0075	**Portlet "{0}" is not found**
Explanation	The specified portlet is not installed or is disabled in the cluster partition.
Action	Verify that the portlet application is installed; install if necessary. Check the server logs for any installation errors. Verify that the portlet is enabled in the cluster partition.

POP.007.0076	**PortletContainer Servlet "{0}" is not found. Check default web application configuration file (defaultPortletAppWeb.xml)**
Explanation	System servlet is not found.
Action	Determine if any changes were made to system configuration files in ../MWS/server/default/deploy/portal.war. Re-install My webMethods Server.

POP.007.0077	**You are not authorized to view the resource. {0}**
Explanation	The current user does not have permission to read the specified object or resource.
Action	Examine and correct the user account permissions.

POP.007.0078	**This action requires an anti-cross-site-request-forgery token.**
Explanation	The executed command or action did not specify an anti-cross-site-request-forgery token.
Action	Check if the given command or action does require an AXRF token. If it does require a token, the token must be explicitly generated and passed in as a URL parameter. For example, when calling a CAF action from a portlet URL, the action must either be configured to not require a token (which lessens security), or a token must be generated when calling this action from a direct URL.

POP.007.0101	**Illegal Property Editor name: "{0}".**
Explanation	A legacy portlet property uses an invalid property-editor name.
Action	Examine and correct the property-editor name in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

POP.007.0102	**Illegal Property Editor parameter value for "{0}": "{1}".**
Explanation	An incorrect parameter value was passed to the property editor.
Action	Check the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

POP.007.0103	**Property Editor requires DHTML.**
Explanation	The property editor "dhtml" property configuration is invalid. The property editor requires DHTML to be enabled.
Action	Examine the property editor configuration in the wm-portlet.xml file. Set dhtml=true (this applies only to legacy non-CAF portlets).

POP.007.0105	**Property editor "{0}" parameter "{1}" of type "choice" defined without choices.**
Explanation	An invalid 'choice' parameter value was supplied to the property editor.
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

POP.007.0106	**Illegal property editor "{0}" attribute: "{1}" value: "{2}".**
Explanation	An invalid property editor attribute was encountered.
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

POP.007.0107	**Illegal property editor "{0}" parameter "{1}" attribute "{2}" value: "{3}".**
Explanation	An invalid property editor attribute was encountered.
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

POP.007.0108	**Illegal property editor "{0}" parameter "{1}" choice "{2}" attribute "{3}" value: "{4}".**
Explanation	An invalid property editor attribute was encountered.
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

POP.007.0109	**Property Editor not deployed: "{0}".**
Explanation	An incorrect property editor was specified for use
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

POP.007.0110	**Illegal Redirect URL: "{0}".**
Explanation	An invalid redirect URL was provided.
Action	Check and correct the redirect URL used in the API calls.

POP.009.0001	**WebService invocation is disabled for the requested command**
Explanation	An attempt was made to invoke a My webMethods Server command as a web service, but the command does not allow invocation as a web service.
Action	1. Enable the command if it is disabled. 2. For some commands it is not possible to execute them with a web service. If this is one of those commands, no other action can be taken.

POP.009.0002	**No WebService type mapping found for java class: {0}**
Explanation	For a My webMethods Server command being invoked as a web service, one or more of the command bean (input) fields to the command does not have a SOAP serializer (or deserializer) defined. Therefore, the My webMethods Server framework cannot convert the data to a SOAP message.
Action	The command developer must either mark the command as not enabled for web service invocation, or write the custom serializer/deserialzer code for the data type and register it in the type mapping registry by overriding the "initializeSOAPMappingRegistry" method of the command Java class.

POP.009.0003	**The CommandBean must implement ISoapComplexTypeBean to be used as a WebService**
Explanation	For a My webMethods Server command being invoked as a web service, the command bean Java class does not implement the interface that is required to be used as a web service.
Action	The command developer must either mark the command as not enabled for web service invocation, or change the command bean Java class to have it implement the interface.

POP.009.0004	**Error initializing ServiceDesc for WebService: {0}**
Explanation	An unexpected exception was detected while preparing a My webMethods Server command to be invoked as a web service.
Action	Inspect the stack trace in the My webMethods Server server log files to determine the cause of the exception.

POP.009.0005	**No WebService marshalling factories are defined for type {0}, and the type can not be treated as a javabean because it does not contain a public no-arg constructor**
Explanation	For a My webMethods Server command being invoked as web service, one of the inputs or outputs is a complex Java class that does not have a no-arg constructor. Therefore, it cannot be automatically marshalled into a SOAP message.
Action	The command developer must either mark the command as not enabled for web service invocation, or add a no-arg constructor to the Java class.

POP.009.0006	**SAML or Hybrid authentication can not be used. Please deploy SAML Security Service component or use Basic authentication instead**
Explanation	The SAML security service is not available.
Action	Deploy the SAML security service component or use basic authentication instead.

POP.009.0007	**Could not find a user context.**
Explanation	Cannot find UID for the user.
Action	Specify a correct UID.

POP.009.0008	**The SAML service you are trying to access is not available right now.**
Explanation	The SAML service is currently unavailable.
Action	Inspect the stack trace in the My webMethods Server log files to determine the cause of the exception.

POP.009.0009	**Failed to initialize WS-Stack clients within {0} milliseconds. They will be disabled.**
Explanation	The Web Services Stack client failed to initialize in the specified period.
Action	Check the OSGi configuration at com.softwareag.platform.config.propsloader or restart My webMethods Server to re-initialize Web Services Stack.

POP.009.0102	**{0}: {1} is not a IThingIDList**
Explanation	The SOAP serializer that is intended to marshall a IThingIDList object into a SOAP message was passed the wrong type of object.
Action	This is most likely a defect in the way the type mapping registry was initialized. Examine the related code to determine the problem and correct as required.

POP.011.0001	**The method "{0}" has not been implemented.**
Explanation	An attempt was made to improperly invoke a Dynamic API.
Action	Examine the logs for an indication of what component and user action caused this error.

POP.011.0002	**must specifiy both 'prefix' and 'uri' parmeters for 'taglib' directive**
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.

POP.011.0003	**expected "{0}" end tag but found "{1}" end tag**
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.

POP.011.0005	**"{0}" tag declared invalid by TagExtraInfo**
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.

POP.011.0006	**"{0}" tag requires "{1}" attribute**
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.

POP.011.0007	**specified attribute "{0}" for "{1}" tag not declared in tld**
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.

POP.011.0008	**specified attribute "{0}" value for "{1}" tag cannot be request-time expression**
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.

POP.011.0009	**request cannot be null**
Explanation	An error occurred while uploading a file.
Action	Check the logs for additional information.

POP.011.0010	**saveDirectory cannot be null**
Explanation	An error occurred while uploading a file.
Action	Use the Content Service page to ensure that a directory is configured to store the uploaded files.

POP.011.0011	**maxPostSize must be positive**
Explanation	An error occurred while uploading a file.
Action	Use the Content Service page to ensure that a maximum size for uploaded fixes is configured.

POP.011.0012E	**"{0}" is not a directory.**
Explanation	The temporary location for for saving a file upload is not valid.
Action	Delete all files in the Portal/server/default/temp folder.

POP.011.0013W	**"{0}" is not writable directory.**
Explanation	The temporary location for saving a file upload is not writable.
Action	Make sure My webMethods Server was started by a user who has rights to the portal temp folder.

POP.011.0014E **Posted content type "{0}" isn't multipart/form-data.**

Explanation My webMethods Server expects to upload a multipart portlet, but the specified content type does not match.

Action Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0015E **Posted content length of "{0}" MB exceeds limit of "{1}" MB.**

Explanation An uploaded file is larger than the size allowed by the system administrator.

Action Upload a smaller file or have the system administrator use the Content Service Administration portlet to increase the maximum allowed file size.

POP.011.0016E **Separation boundary was not specified.**

Explanation The specified file was corrupted before or during the upload process.

Action Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0017E **Corrupt form data. No leading boundary was found.**

Explanation The specified file was corrupted before or during the upload process.

Action Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0018E **Malformed line after disposition "{0}"**

Explanation The specified file was corrupted before or during the upload process.

Action Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0019E **The published file was empty or invalid.**

Explanation The specified file was corrupted before or during the upload process.

Action Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0020E **Content disposition "{0}" is corrupt.**

Explanation The specified file was corrupted before or during the upload process.

Action Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0021	**Invalid content disposition "{0}".**
Explanation	An error occurred while processing the uploaded file.
Action	Investigate the contents of the HTTP POST to see if the data was corrupted.

POP.011.0022E	**Content type corrupt "{0}".**
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0023E	**Malformed line after disposition "{0}".**
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0024	**No file name available.**
Explanation	An error occurred while uploading a file.
Action	Examine the contents of the HTTP POST to see if the data was corrupted.

POP.011.0025E	**Failed to create a DocumentBuilderFactory.**
Explanation	The XML parser appears to be missing.
Action	Check for the xercesImpl.jar file in the portal class path. If the file is missing, reinstall My webMethods Server.

POP.011.0026E	**Failed to create a TransformerFactory.**
Explanation	The Xalan XSTL processor could not be loaded.
Action	Check for the xalan.jar file in the portal classpath. If the file is missing, reinstall My webMethods Server.

POP.011.0027	**JMS already initialized with "{0}".**
Explanation	An error occurred during startup.
Action	Ensure that startup routines are invoked only once.

POP.011.0028E	**JMSProvider: failed to get configuration file.**
Explanation	The JMS provider appears to be disconnected.
Action	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.

POP.011.0029E	**JMSProvider: failed to get configuration file "{0}", due to "{1}".**
Explanation	The JMS provider appears to be disconnected.
Action	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.

POP.011.0030E	**JNDI name not found: "{0}".**
Explanation	The JMS provider appears to be disconnected.
Action	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.

POP.011.0031	**Can't initialize perf service: "{0}".**
Explanation	The specified Performance Service failed to initialize.
Action	Check the perfUtils.properties configuration file for spelling errors.

POP.011.0032	**Perf Service Not Initialized.**
Explanation	An attempt was made to use the Performance Service before it was initialized.
Action	The Performance Service might be disabled. Check the contents of the perfUtils.properties configuration file.

POP.011.0033	**Cannot open stream. Location: "{0}".**
Explanation	An attempt to access a file failed.
Action	Ensure that the file exists at the specified location.

POP.011.0034E	**Size read mismatch "{0}" vs "{1}"**
Explanation	An InputStream corruption error occurred.
Action	Examine the _problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.

POP.011.0035	**Cannot create temporary folder:** "{0}"
Explanation	Folder creation failed.
Action	Most likely, the current process lacks Write access to the configured temporary folder.

POP.011.0036E	**Unable to delete file:** "{0}"
Explanation	An error occurred while removing a temporary file.
Action	Find the specified file and remove it manually.

POP.011.0037E	**Unable to delete directory:** "{0}"
Explanation	An error occurred while cleaning up temporary files.
Action	Find the specified directory and manually remove the temporary files.

POP.011.0039E	**ObjectUtil: illegal arguments.**
Explanation	An error occurred while setting a property on an object, because the target object is null or the property name is null or empty.
Action	Examine the _problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to expalin why the error was thrown, but it will show where the error originated.

POP.011.0044E	**Error obtaining JMS topic for name:** "{0}"
Explanation	The requested JMS topic is not available.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0045E	**no JMS provider, requesting topic name:** "{0}"
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0046E	**JMSTopic.createTopicSession(), no JMS provider.**
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0047E	**Unable to connect to registry.**
Explanation	The My webMethods Server configuration registry is unavailable.
Action	In a cluster deployment, make sure the Master server is started before starting the other cluster nodes.

POP.011.0048	**no protocol defined for: "{0}"**
Explanation	The system tried to load a file from an unknown protocol.
Action	Check the protocol string spelling.

POP.011.0053E	**Error obtaining JMS queue for name: "{0}"**
Explanation	The requested JMS queue is unavailable.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0054E	**no JMS provider, requesting queue name: "{0}"**
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0055E	**JMSTopic.createQueueSession(), no JMS provider.**
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0056E	**Invalid line: "{0}"**
Explanation	An error occurred in parsing a .properties file.
Action	Look in the _problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.

POP.011.0057E	**JMSDestination.Subscriber, unable to create consumer on: "{0}"**
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0058E **JMSDestination.Subscriber, unable to create session for: "{0}"**

Explanation The JMS provider appears to be disconnected.

Action Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0062E **Stream exhausted.**

Explanation An error occurred in decoding a BASE64 String.

Action Examine the _problems_.log file for the error stack trace. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.

POP.011.0063E **BASE64Encoder: Bad Padding byte.**

Explanation An error occurred in decoding a BASE64 String.

Action Examine the _problems_.log file for the error stack trace. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.

POP.011.0065 **There must be a default entry --> default=icon_def.gif.**

Explanation The iconMap.properties file is corrupted.

Action Revert any changes made to this file.

POP.011.0068 **Output stream not set for: "{0}"**

Explanation An error occurred during page rendering.

Action Check the logs for problems that result in this situation.

POP.011.0076 **Unable to convert data type "{0}" to "{1}"**

Explanation The system failed in the attempted type coercion.

Action If possible, check the input value to ensure that it can be properly coerced to the target data type.

POP.012.0001.tagname_error – Not a valid value!Tag Name cannot contain spaces.

Explanation The Tag Name cannot contain spaces.

Action Make sure the value of the Tag Name field is correct.

POP.012.0001.wm_axsrftconfig – This action requires a custom anti-cross-site-request-forgery token.

Explanation An invalid custom token is provided during portlet configuration.

Action Check and, if needed, re-configure the New Secret Interval and Oldest Secret preferences in wm_axsrftconfig.

POP.012.0001.wm_caf_task – Cannot upload this file as it is empty.Uploading empty files is not allowed.

Explanation Content cannot contain an empty file, therefore uploading is not allowed

Action Make sure that the file contains content.

POP.012.0001.wm_calendar – Illegal "{0}" parameter value: "{1}".

Explanation The start date of an entry in the calendar is missing.

Action Specify the start date of the entry in the calendar.

POP.012.0001.wm_cforms_layout – Recursive use of Composite Form for "{0}".

Explanation The composite form for "{0}" is attempting to display an item that displays the same composite form for "{0}". For instance, the composite form for "{0}" is displaying a form containing the same composite form for "{0}").

Action Change the composite form for "{0}" "view" property to a different item.

POP.012.0001.wm_commonsearchbar – Search Context Portlet URI is not valid: {0}

Explanation Search context portlet URI is not valid.

Action Specify a valid search context portlet.

POP.012.0001.wm_commonsearchresults – Search Context Portlet URI is not valid: {0}

Explanation The search context portlet URI is not valid.

Action Specify a valid search context portlet.

POP.012.0001.wm_contentrendererE – Unable to parse regexps: {0}

Explanation The My webMethods Server installation is missing RegEx support jars.

Action Reinstall My webMethods Server.

POP.012.0001.wm_dirsearchcontext – This portlet is not intended to be viewed standalone

Explanation This portlet is not intended to be viewed as standalone.

Action Do not view this portlet as a standalone portlet.

POP.012.0001.wm_discotres_forumview – Forum or category not specified.

Explanation The forum or category should not be null.

Action Specify the forum or category for the forum view.

POP.012.0001.wm_discotres_forumwizard – Must specify "parent" property.

Explanation The "parent" property must not be empty.

Action Enter a valid "parent" property.

POP.012.0001.wm_discotres_messageview – Forum message not specified.

Explanation The forum requires some messages for proper notification.

Action Provide the messages needed for the message view resources.

POP.012.0001.wm_discotres_topicview – Forum topic not specified.

Explanation Specify the correct forum topic.

Action Specify a valid forum topic.

POP.012.0001.wm_fabric_addtostart – You already have an instance of this portlet on the target page.

Explanation You already have an instance of this portlet on the target page.

Action Choose another portlet to add.

POP.012.0001.wm_formattedxml – No content available for {0}.

Explanation No content can be retrieved from the specified style sheet.

Action Make sure that the style sheet has content.

POP.012.0001.wm_inlinecontent – No content available for {0}.

Explanation No content can be retrieved.

Action Make sure the resource has content.

POP.012.0001.wm_jazzy – Not a valid dictionary identifier: "{0}".

Explanation The dictionary ID provided is not valid.

Action Provide a valid dictionary ID.

POP.012.0001.wm_mws_diagnostics – No Performance Service is currently available. To enable the Service, please go to the properties page of this portlet.

Explanation No performance service is currently enabled.

Action To enable a service, go to the properties page of the Performance Analysis portlet.

POP.012.0001.wm_noodle – Cannot load page content.

Explanation The page fails to load the content.

Action Check if the file exists and if the path of the file is correct.

POP.012.0001.wm_noodle_context_wiring – This portlet has no UI.

Explanation The specified portlet deployed on the server has no user interface.

Action Go to Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration and re-install the portlet.

POP.012.0001.wm_ntlmv2authadmin – NTLM autentication failed because login has been disabled for the {0} user.

Explanation The Directory Service reports that the 'Diisabled' attribute for the user record is set to true. This user cannot authenticate with My webMethods Server.

Action To enable this user to authenticate with My webMethods Server, set the 'Diisabled' attribute to false in the appropriate directory server.

POP.012.0001.wm_portletinportletE – Recursive use of Portlet-in-Portlet for "{0}".

Explanation Portlet-in-Portlet is attempting to display an item that displays the same Portlet-in-Portlet (for instance, the Portlet-in-Portlet is displaying a portal page containing the same Portlet-in-Portlet).

Action Change the Portlet-in-Portlet's "Portal Page" property to a different item.

POP.012.0001.wm_principalprofileadmin – You don't have rights to modify the properties of this item.

Explanation The current user does not have sufficient privileges to make changes to this portlet

Action Contact a My webMethods Server system administrator to modify the current user's permissions.

POP.012.0001.wm_propertiesE – {0} is not specified.

Explanation The Properties portlet could not locate the object to show its properties.

Action Close and reopen the internet browser window.

POP.012.0001.wm_publish.NotLicensed – The "Publish" feature is disabled because this deployment is not licensed.

Explanation The requested feature is not part of the used license.

Action If you want to use this feature, you should buy and install the appropriate license.

POP.012.0001.wm_publish.ToEnable – To enable the "Publish" feature please contact webMethods to obtain a Portal license.

Explanation The requested feature is not part of the used license. Contact Software AG to obtain the Portal license to enable the "Publish" feature.

Action To use the "Publish" feature, you should buy and install the appropriate Portal license.

POP.012.0001.wm_sessionmonitor – The view "{0}" is not available.

Explanation Unable to fetch the view context from the server.

Action Try republishing the portlet to the server.

POP.012.0001.wm_shelladmin – A shell with the system name "{0}" already exists.

Explanation The same system name is not allowed for two different shells. This error occurs when an attempt is made to save a shell with a system name that already exists.

Action Specify a unique system name for the shell.

POP.012.0001.wm_shelleditorE – Cannot clone parent''s shell section because it is not a Portal Page.

Explanation Some legacy shells created before Portal 6.2 or customer-created shells may have a raw JSP page assigned to a shell section. Such shells cannot be cloned.

Action Rework the legacy shell to use portal pages instead of JSP pages.

POP.012.0001.wm_skinadmin – A skin with the system name "{0}" already exists.

Explanation The same system name is not allowed for two different skins. This error occurs when an attempt is made to save a skin with a system name that already exists.

Action Specify a unique system name for the skin.

POP.012.0001.wm_skineditorE – {0} is not a valid skin.

Explanation The specified skin object is not a valid portal skin.

Action Log off from My webMethods and log back in.

POP.012.0001.wm_spm_commandex – "{0}" does not identify a user or group.

Explanation The supplied URI is not a valid user or group.

Action Specify a correct URI.

POP.012.0001.wm_sysdirsvc – Unable to locate principal: {0}

Explanation The principal cannot be retrieved using the provided principal URI.

Action Check the server log for the principal URI that was used and make sure the principal URI is valid. Contact an administrator if the principal URI is valid but the issue persists.

POP.012.0001.wm_table – Illegal "{0}" property value: "{1}".

Explanation An invalid value is specified for the property.

Action Check the log for information about the value that was specified for the property. Specify a valid value for the property.

POP.012.0001.wm_tabs – Illegal "{0}" property value: "{1}".

Explanation An invalid value is specified for the property.

Action Check the log for information about the value that was specified for the property. Specify a valid value for the property.

POP.012.0001.wm_thumbnailagentE – Error executing external process

Explanation The Thumbnail agent has failed to execute an external process to prepare thumbnails.

Action Use the Install Administration portlet to reinstall the wm_thumbnailagent portlet.

POP.012.0001.wm_tree – Illegal "{0}" property value: "{1}".

Explanation An invalid value is used for the specified property.

Action Check the server log for the value used for the property. Make sure a valid value is used.

POP.012.0001.wm_universalpicker – Cannot resolve portlet ID for "{0}".

Explanation Cannot retrieve the thing using the specified ID.

Action Check the server log for the ID that cannot be retrieved and make sure that the ID is valid. Contact an administrator if you think that the ID is valid but the error persists.

POP.012.0001.wm_userhomefolderE – Empty "{0}" property.

Explanation The user ID is either invalid or was not found.

Action Use the User Home folder portlet to refresh the page.

POP.012.0001.wm_userprofilewiring – This portlet has no UI.

Explanation The specified portlet deployed on the server has no user interface.

Action Go to Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration and re-install the portlet.

POP.012.0001.wm_versionE – Unable to acquire publish portlet controller bean.

Explanation An internal portlet error has occurred.

Action Log off from My webMethods and log back in.

POP.012.0001.wm_webclipE – Cannot clip from "{0}" because it is not an HTTP resource.

Explanation The Webclip portlet has failed to connect to the specified URL and get its HTML content.

Action Check the URL specified for the Webclip portlet.

POP.012.0001.wm_wiringE – Can only wire portlets

Explanation An attempt was made to wire a non-portlet.

Action You can only wire portlets.

POP.012.0001.wm_xt_dbdirsvc – Directory could not authenticate this user

Explanation The user cannot be authenticated with the specified credentials.

Action Make sure the user credentials are valid.

POP.012.0001.wm_xt_dbrole – An error occured executing the SQL query: "{0}". Please type a valid query and try again.

Explanation The SQL query is invalid.

Action The server log contains the invalid SQL query. Use a valid SQL query.

POP.012.0001.wm_xt_extdirsvc – Directory could not authenticate this user

Explanation The user cannot be authenticated with the specified credentials.

Action Make sure the user credentials are valid.

POP.012.0001.wm_xt_ldapdirsvc – This directory service does not support creating Users or Groups

Explanation The LDAP directory service does not support creating users or groups.

Action Contact an administrator if you want to create users or groups.

POP.012.0001.wm_xt_oauthsvc – Verification of the IdToken failed!

Explanation Verification of the ID Token (security token) that contains claims about the authentication of a user by an authorization server failed. The failure may occur due to the following reasons: 1.The issuer identifier for the OpenID Provider obtained during discovery does not match the value of the iss (issuer) claim.2. The ID Token does not list the client (client_id) as a valid audience (aud).

Action Check the OAuth configuration 'OAuth 2.0 Client Identifier' parameter.

POP.012.0001.wm_xt_portalrules – Unknown rule thing: {0}

Explanation The type of rule cannot be determined.

Action Check the server log for the rule ID that cannot be determined and make sure that the ID is valid. Contact an administrator if you think that the ID is valid but the error persists.

POP.012.0001.wm_xt_rssfeed – age not found: {0}

Explanation The specified RSS Feed Resource age "{0}"does not exist.

Action Examine the warning message and confirm that the age {0} exists.

POP.012.0001.wm_xt_ruleE – The current IDirectoryUser is null.

Explanation Rule matching has failed to load the user.

Action Log off from My webMethods and log back in.

POP.012.0001.wm_xt_samlsecurityservice – The input document contains no elements.

Explanation The input document contains no elements.

Action Make sure that a valid document that is not empty is passed.

POP.012.0001.wm_xt_shell – Cannot delete "{0}" because it is the default system shell.

Explanation The default system shell cannot be deleted.

Action Do not attempt to delete the default system shell.

POP.012.0001.wm_xt_shortcutE – Unhandled object type found for the wm_xt_shortcut URL property: {0}

Explanation An invalid object type was referenced by a shortcut.

Action Delete the specified object and start over.

POP.012.0001.wm_xt_skinE – Cannot delete "{0}" because it is the default system skin.

Explanation The portal skin specificed as the default skin cannot be deleted.

Action Before deleting the skin, use the Skin Administration portlet to specify another skin as the default.

POP.012.0001.wm_xt_ssolink – Failed to generate SAML artifact, artifact is null

Explanation The SAML artifact cannot be generated.

Action Make sure that the item thing ID and user ID are valid, and that the SAML service is running.

POP.012.0001.wm_xtypeviewE – You have not specified an object to display in this portlet.

Explanation The Xtype View portlet does not have a valid target object to display.

Action Update the Xtype View portlet properties and specify a valid DBO to display.

POP.012.0002.wm_caf_task – Cannot connect to webMethods Content Service Platform Server on {0} : {1} . Please make sure the server is available.

Explanation webMethods Content Service Platform is either not running, disconnected, or the environment configuration defined in My webMethods is incorrect.

Action Make sure the CSP server is running; ensure that network connectivity is available; check the CSP environment configuration in My webMethods and verify the connection values.

POP.012.0002.wm_commonsearchbar – Search Context Portlet does not implement ISearchContext interface

Explanation The search context portlet does not implement the ISearchContext interface.

Action Make sure the search context portlet implements the ISearchContext interface.

POP.012.0002.wm_commonsearchresults – Search Context Portlet does not implement ISearchContext interface

Explanation The search context portlet does not implement the ISearchContext interface.

Action Make sure the search context portlet implements the ISearchContext interface.

POP.012.0002.wm_contentrendererE – Requested content was not found: "{0}"

Explanation The server attempted to download invalid content.

Action Verify that valild content is present at the source location and can be downloaded.

POP.012.0002.wm_dirsearchcontext – Failed to move to next principal in directory services, service={0}, error={1}

Explanation The directory search cannot continue because an exception was thrown when attempting to go to the next page search. No search results are returned.

Action Check the My webMethods Server log for the directory service used for the search and the exception that was thrown. Provide the log details to an administrator.

POP.012.0002.wm_discotres_forumview – Can display listing for forum or category only.

Explanation Only the listing for forum or category is displayed successfully.

Action No action required.

POP.012.0002.wm_discotres_forumwizard – Must specify "target" property.

Explanation The "target" property must not be empty.

Action Enter a valid "target" property.

POP.012.0002.wm_discotres_messageview – Can display forum message only.

Explanation Only forum messages are displayed successfully.

Action No action is required.

POP.012.0002.wm_discotres_topicview – Can display listing for forum topic only.

Explanation Only the listing for forum topic is displayed successfully.

Action No action required.

POP.012.0002.wm_jazzy – Not a valid dictionary: "{0}".

Explanation The dictionary specified is not valid.

Action Provide a valid dictionary.

POP.012.0002.wm_publish – Please select a type to publish.

Explanation The 'type' input parameter must be set to 'publish'.

Action Provide an allowed value. The 'type' input parameter must be set to 'publish'.

POP.012.0002.wm_sessionmonitor – Use this portlet to monitor real-time user activity and send status messages to user(s) via e-mail. Click the appropriate column heading to sort by User Name, Location (Host ID), or Administrator status.

Explanation Use this portlet to monitor real-time user activity and to send status messages to users by e-mail. Click the appropriate column heading to sort by User Name, Location (Host ID), or Administrator status.

Action For more information, see the PDF publication, "My webMethods Server Portlet Reference."

POP.012.0002.wm_shelladmin – A shell with the display name "{0}" already exists.

Explanation The same display name is not allowed for two different shells. This error occurs when an attempt is made to save a shell with a display name that already exists.

Action Specify a unique system name for the shell.

POP.012.0002.wm_skinadmin – A skin with the display name "{0}" already exists.

Explanation The same display name is not allowed for two different skins. This error occurs when an attempt is made to save a skin with a display name that already exists.

Action Specify a unique display name for the skin.

POP.012.0002.wm_skineditor – feature not recognized: {0}

Explanation The feature is not recognized.

Action Contact Software AG Global Support. For contact information, log in to https://empower.softwareag.com/.

POP.012.0002.wm_spm_commandex – Invalid argument supplied.

Explanation An invalid argument was supplied as a parameter in the request map.

Action Check the arguments for the command request.

POP.012.0002.wm_sysdirsvc – Password attribute is missing

Explanation No password information is provided when creating a new principal.

Action Provide a password attribute when creating a new principal.

**POP.012.0002.wm_systemcontent – <h3>Attempted redirect to a restricted host. </h3> **

Explanation My webMethods Server does not allow redirects to arbitrary URLs. In this case the URL was not configured as an acceptable redirect host.

Action Ask the My webMethods Server administrator to modify the Server Redirect WhiteList to allow redirects to this foreign URL.

POP.012.0002.wm_userhomefolder – This user does not have a home folder. Note that the Portal typically does not create a home folder for a user until the user logs in for the first time.

Explanation The user does not have a home folder.

Action Note that the Portal typically does not create a home folder for a user until the user logs in for the first time. Contact an administrator if this problem persists after the user logs in.

POP.012.0002.wm_versionE – Unable to acquire target resource: {0}

Explanation An internal portlet error has occurred.

Action Log off from My webMethods and log back in.

POP.012.0002.wm_wiringE – {0} is not a normal thing

Explanation An attempt was made to wire an invalid portlet instance.

Action Delete the specified portlet and locate the correct portlet.

POP.012.0002.wm_xt_extdirsvc – This directory service does not support creating Users or Groups

Explanation This external directory service does not support creating users or groups.

Action Create an administrator if you want to create users or groups.

POP.012.0002.wm_xt_ldapdirsvc – This directory service does not support deleting Users or Groups

Explanation The LDAP directory service does not support deleting users or groups.

Action Contact an administrator if you want to delete users or groups.

POP.012.0002.wm_xt_oauthsvc – The discovery document response is not valid.

Explanation Unable to obtain configuration information about the OpenID provider, including information about all the necessary endpoints and public key location.

Action Check the OAuth configuration 'Discovery Document URL' parameter.

POP.012.0002.wm_xt_portalrules – Unable to resolve user id: {0}

Explanation The principal information cannot be retrieved using the specified ID.

Action Check the server log for the principal ID that cannot be retrieved and make sure that the ID is valid. Contact an administrator if you think that the ID is valid but the error persists.

POP.012.0002.wm_xt_rssfeed – refresh interval not found: {0}

Explanation The specified RSS Feed Resource refresh interval "{0}"does not exist.

Action Provide a valid value for the input variable refresh interval :{0}.

POP.012.0002.wm_xt_samlsecurityservice – The SAML artifact is invalid or has expired.

Explanation The SAML artifact is invalid because it provides wrong information for the cluster index.

Action Make sure the SAML artifact has the correct information.

POP.012.0002.wm_xt_shell – Cannot delete "{0}" because it is the base system shell.

Explanation The base system shell cannot be deleted.

Action Do not attempt to delete the base system shell.

POP.012.0002.wm_xt_skinE – Cannot delete "{0}" because it is the base system skin.

Explanation The portal skin specified as the base system skin cannot be deleted.

Action The base portal skin cannot be deleted because it is used as a parent for all other portal skins.

POP.012.0002.wm_xt_wikiobject – Wiki with such name already exists

Explanation A wiki with such a name already exists.

Action Use a unique name for the wiki.

POP.012.0003.wm_commonsearchbar – None of the portlet tabs are visible

Explanation None of the portlet tabs are visible for the search bar.

Action Make sure that the search options are set.

POP.012.0003.wm_commonsearchresultsE – Failed to parse the max search results setting of "{0}", using default of "{1}"

Explanation The common search code is attempting to build a search query object from a query string that was passed into it. The query string supplied contains an invalid value for the 'maxResults' setting. The warning message is written to the logs and the process continues with the default maxResults value.

Action Make sure the portlet that invokes the API supplies a valid number for the 'maxResults' setting in the search query string. Typically, the end user would not cause this scenario because the wm_commonsearchbar portlet that usually builds the query string validates the maxResults field before allowing the submission of the search form.

POP.012.0003.wm_contentserviceadmin – Cannot start a new content import process because another content import process is currently running.

Explanation You cannot start a new content import process because another content import process is currently running.

Action Wait until the content import in progress completes.

POP.012.0003.wm_dirsearchcontext – Failed to convert short move to next principal in directory services, service={0}, error={1}

Explanation The internal ID is not a valid integer.

Action Check the My webMethods Server log for the directory service used for the search and the exception that was thrown. Provide the log details to an administrator.

POP.012.0003.wm_discotres_topicview – Must specify "target" property.

Explanation The "target" property must not be empty.

Action Enter a valid "target" property.

POP.012.0003.wm_jazzy – Cannot load dictionary "{0}" because an I/O error occurred.

Explanation The specified dictionary cannot be loaded.

Action Make sure that the dictionary is accessible.

POP.012.0003.wm_noodle – Cannot load portlet content.

Explanation The portlet fails to load the content.

Action Check if the portlet has content and if the path of the portlet is correct.

POP.012.0003.wm_ntlmv2authadmin – Field [{0}] is required.

Explanation A necessary form field was not provided.

Action Review the form and fill out all required fields, then resubmit.

POP.012.0003.wm_sessionmonitor – No sessions are available for this Portal Node.

Explanation No sessions are available for this portal node.

Action Try republishing the portlet to the server.

POP.012.0003.wm_shelladminE – The URI "{0}" does not identify a valid shell.

Explanation The shell instance is not a valid portal shell object type.

Action Restart the My webMethods Server to flush the internal caches.

POP.012.0003.wm_skinadminE – The URI "{0}" does not identify a valid skin.

Explanation The skin instance is not a valid portal skin type.

Action Restart My webMethods Server to flush the internal caches.

POP.012.0003.wm_skineditor – property not recognized: {0}

Explanation The property is not recognized.

Action Make sure this particular editor resource is declared correctly.

POP.012.0003.wm_spm_commandex – Cannot create env entry. Entry already exsists.

Explanation There is a duplicate entry with that name.

Action Specify a different name for the entry.

POP.012.0003.wm_tree – The "{0}" property value must begin with a '{' character.

Explanation The property value should begin with a "{" character.

Action Make sure that the property value begins with a "{" character.

POP.012.0003.wm_wiring – You don't have rights to modify the wiring of this item.

Explanation The current user does not have sufficient permissions to modify the wiring properties of this portlet.

Action Contact your My webMethods Server administrator to modify your user permissions.

POP.012.0003.wm_xt_dbdirsvc – This directory service does not support deleting Users or Groups

Explanation The database directory service does not support deleting users or groups.

Action Contact an administrator if you want to delete users or groups.

POP.012.0003.wm_xt_extdirsvc – This directory service does not support deleting Users or Groups

Explanation This external directory service does not support deleting users or groups.

Action Contact an administrator if you want to delete users or groups.

POP.012.0003.wm_xt_ldapdirsvc – This directory service does not support modifying User or Group memberships

Explanation The LDAP directory service does not support modifying users or groups.

Action Contact an administrator if you want to modify users or groups.

POP.012.0003.wm_xt_oauthsvc – Unable to obtain OSGI service reference: {0}

Explanation The lookup for the OAuth user service failed.

Action If a user service application is defined in the OAuth configuration, check if the user service application is deployed correctly.

POP.012.0003.wm_xt_portalrules – Deprecated method {0} is not valid on wm_xt_portalrules

Explanation The method is deprecated and should not be invoked.

Action Use only supported methods.

POP.012.0003.wm_xt_rssfeedE – Unable to find suitable factory for: {0}

Explanation An RSS feed has failed to parse RSS content.

Action Choose another RSS feed.

POP.012.0003.wm_xt_samlsecurityservice – Unable to locate principal "{0}".

Explanation Directory principal information cannot be retrieved.

Action Make sure the SAML artifact contains correct directory principal information.

POP.012.0004.wm_commonsearchbar – Saved Search Name has already been used.

Explanation The saved search name has already been used.

Action Specify a different search name.

POP.012.0004.wm_commonsearchresults – Failed to retrieve data from : {0} LDAPs

Explanation The specified directory services failed to return a result due to an error.

Action Check the My webMethods Server logs for errors related to the specified directory services.

POP.012.0004.wm_contentserviceadminE – Content service not found: "{0}".

Explanation The content service is no longer valid.

Action If you cannot reconfigure the offending content service by using the Content Service Admin portlet, contact Software AG Global Support for a reset directive.

POP.012.0004.wm_dirsearchcontext – Failed to evaluate expression for object, exp={0}, obj={1}, error={2}

Explanation The expression cannot be evaluated.

Action Check the My webMethods Server log to determine the expression and the exception that was thrown. Provide the log details to an administrator.

POP.012.0004.wm_mws_diagnostics – Performance Service does not support serialization.

Explanation The currently running performance service does not support data serialization, therefore a snapshot cannot be exported.

Action Switch to a performance service that supports serialization.

POP.012.0004.wm_ntlmv2authadmin – Jespa library is required.

Explanation NTLMV2 will not function without the Jespa library.

Action Contact Software AG Global Support for information about downloading the Jespa library from jespa.org.

POP.012.0004.wm_portalaliassearchcontext – One or more of the requested aliases can not be removed

Explanation One or more of the requested aliases can not be removed.

Action Before deleting an alias, verify that it exists and that it is not a system alias.

POP.012.0004.wm_shelladminE – Cannot delete "{0}" because it is the default system shell.

Explanation The default portal shell cannot be deleted.

Action Use the Shell Administration portlet to specify another shell as the default, and then delete the first shell.

POP.012.0004.wm_skineditor – can't resolve input source: {0}

Explanation The input resource provided is incorrect.

Action Provide the correct input resource.

POP.012.0004.wm_spm_commandex – "{0}" argument not supplied.

Explanation The required argument is not provided.

Action Check the provided arguments.

POP.012.0004.wm_tree – Cannot render resource as tree fragment.

Explanation The resource content is empty.

Action Make sure that the resource has content.

POP.012.0004.wm_wiki_createnew – Please provide the container for wiki

Explanation The container is not provided for the wiki.

Action Provide the container for the wiki.

POP.012.0004.wm_xt_dbdirsvc – This directory service does not support modifying User or Group memberships

Explanation The database directory service does not support modifying users or groups.

Action Contact an administrator if you want to modify users or groups.

POP.012.0004.wm_xt_extdirsvc – This directory service does not support modifying User or Group memberships

Explanation This external directory service does not support modifying users or groups.

Action Contact an administrator if you want to modify users or groups.

POP.012.0004.wm_xt_ldapdirsvc – No valid "{0}" found for the principal "{1}" from "{2}" directory service. Please check if ID attribute is valid in the Directory Services Configuration

Explanation No principal is found in the LDAP directory service using the specified name.

Action Use a valid name when searching for the principal in the LDAP directory service.

POP.012.0004.wm_xt_portalrules – Web application is not deployed or available {0}. Cannot evaluate {1}

Explanation The specified web application is not deployed or available. As a result, My webMethods Server cannot evaluate the specified function.

Action Make sure that the specified web application is deployed and available.

POP.012.0005.wm_contentserviceadminE – Cannot remove default content service.

Explanation The default content service cannot be deleted.

Action My webMethods Server disallows the deletion of the default content service.

POP.012.0005.wm_dirsearchcontext – Failed to create a directory service iterator, dirService={0}, error={1)

Explanation A problem was encountered while trying to iterate through a directory service.

Action Check the server log for information about the directory service and the exception that was thrown. Provide the log details to an administrator.

POP.012.0005.wm_jazzy – Please specify text to check.

Explanation The specified text is empty.

Action Specify the text to check.

POP.012.0005.wm_mws_diagnostics – Wrong Import File format.

Explanation The file you are trying to import was exported from a performance service that is different from the one currently running.

Action Check the portlet preferences and make sure the correct performance service is running.

POP.012.0005.wm_ntlmv2authadmin – Configuration test failed. Please double check all the required parameters.

Explanation The specified configuration is not valid. NTLMv2 authentication will not succeed until the parameters are corrected.

Action Review the NTLMv2 configuration and modify parameters as required.

POP.012.0005.wm_portalaliassearchcontext – Unable to add alias "{0}" because an alias with that name already exists.

Explanation Unable to add alias because an alias with that name already exists.

Action Create a unique alias name.

POP.012.0005.wm_shelladminE – Cannot delete "{0}" because it is the base system shell.

Explanation The shell could not be deleted because it is a parent shell for other deployed shells.

Action My webMethods Server explicitly disallows deletion of the base shell.

POP.012.0005.wm_skineditor – cannot rename "{0}" to "{1}"

Explanation The field name "{1}" already exists.

Action Specify a unique field name.

POP.012.0005.wm_spm_commandex – Neither "{0}" or "{1}" arguments are supplied.

Explanation Neither the first nor the second argument was provided.

Action Provide at least one argument.

POP.012.0005.wm_sysdirsvc – User ID can not contain non alphanumeric characters.

Explanation The provided user ID contains characters, different than numbers and letters.

Action Provide a user ID that contains only alphanumeric characters and retry the operation.

POP.012.0005.wm_xt_dbdirsvc – Directory could not load principal data, "{0}" attribute is missing

Explanation The principal data cannot be loaded because the specified attribute is missing.

Action Check the log file for the missing attribute. Contact an administrator to make sure the specific principal is valid and has the specified attribute.

POP.012.0005.wm_xt_extdirsvc – No data service defined

Explanation The OSGi external directory service could not be found.

Action Check if the external directory service is defined correctly.

POP.012.0005.wm_xt_ldapdirsvc – Unable to locate "{0}" directory service. It might have been disabled.

Explanation The LDAP directory service cannot be located.

Action Make sure the LDAP directory service is enabled.

POP.012.0006.wm_contentserviceadmin – You do not have sufficient rights to modify content service "{1}".

Explanation You do not have sufficient rights to modify this content service.

Action An administrator must assign modify permission to the current user. Otherwise, modify the content service as an Administrator user.

POP.012.0006.wm_dirsearchcontext – Not a valid attribute filter string, string={0}

Explanation The attribute filter string specified is not valid.

Action Provide a valid attribute filter string. The server log file contains information about the invalid value.

POP.012.0006.wm_portalaliassearchcontext – Unable to update alias "{0}" because an existing alias with that name could not be found.

Explanation Unable to update alias because an existing alias with that name could not be found.

Action Select an existing alias to update, or create a new alias.

POP.012.0006.wm_shelladmin – "{0}" does not identify a legacy shell.

Explanation The shell instance is not a valid legacy shell object type.

Action Restart the My webMethods Server to flush the internal caches.

POP.012.0006.wm_spm_commandex – Could not modify environment variable. Variable not found

Explanation The variable was not found.

Action Check and refresh the environment variables list.

POP.012.0006.wm_xt_dbdirsvc – An error occurred executing the SQL query: "{0}". Please type a valid query and try again.

Explanation The SQL query is invalid.

Action Make sure that the SQL query is valid. Contact an administrator if you are sure your SQL is valid.

POP.012.0006.wm_xt_extdirsvc – Unable to instantiate class: {0}

Explanation The OSGi external directory service is not defined or exposed correctly.

Action Check if the external directory service is defined correctly.

POP.012.0006.wm_xt_samlsecurityservice – Unable to locate server within cluster to validate the SAML artifact, index={0}

Explanation The server specified in the SAML artifact cannot be located within the cluster.

Action Make sure the SAML artifact contains the correct server index information.

POP.012.0007.wm_contentserviceadmin – A content service with a name of "{0}" already exists.

Explanation A content service with the same name already exists.

Action Define a unique name when adding a new content service,

POP.012.0007.wm_dirsearchcontext – Not a valid attribute filter string, missing separator, string={0}

Explanation The specified string does not have a valid attribute filter separator.

Action Provide a valid attribute filter separator. You can find the invalid value in the server log file.

POP.012.0007.wm_mws_diagnostics – Performance Service is not running. No data is available.

Explanation No performance service currently is running, so there is no data to display.

Action Enable a performance service and allow time for it to collect some data, then retry.

POP.012.0007.wm_portalaliassearchcontext – This portlet is not intended to be viewed standalone

Explanation This portlet is not intended to be viewed as an individual portlet, outside of another portlet.

Action Avoid using this portlet as a single stand-alone portlet.

POP.012.0007.wm_shelladmin – Cannot convert legacy shell because it uses JSP pages instead of Portal pages.

Explanation	My webMethods Server cannot convert a legacy shell because it uses JSP pages instead of Portal pages.
Action	Contact Software AG Global Support. For contact information, log in to https://empower.softwareag.com/.

POP.012.0007.wm_xt_dbdirsvc – {0} is required

Explanation	The SQL query is invalid because the required property is missing.
Action	Make sure the SQL query includes the required property.

POP.012.0007.wm_xt_extdirsvc – Unable to get the OSGI service: {0}

Explanation	The OSGi external directory service is not defined or exposed correctly.
Action	Check if the external directory service is defined correctly.

POP.012.0008.wm_contentserviceadmin – A content service with a root of "{0}" already exists.

Explanation	A content service with the same root already exists.
Action	Verify that no other service uses the same root location.

POP.012.0008.wm_dirsearchcontext – Unable to locate the attribute provider for URI={0}

Explanation	The principal attribute provider for the specific directory service cannot be found.
Action	Find the directory service in the server log and contact an administrator with the log information.

POP.012.0008.wm_migration – Your download should begin shortly.

Explanation	Informational message indicating that the download to begin shortly.
Action	No action required.

POP.012.0008.wm_portalaliassearchcontext – Unable to remove alias "{0}" because it is a system alias

Explanation	Unable to remove the alias because it is a system alias.
Action	No action available. You cannot delete a system alias.

POP.012.0008.wm_xt_dbdirsvc – {0} "{1}" is invalid. It is missing required field "{2}"

Explanation The SQL query is invalid because the required property is missing.

Action Make sure the SQL query includes the required property.

POP.012.0009.wm_portalaliassearchcontext – Unable to remove alias "{0}" because it does not exist

Explanation Unable to remove the alias because it does not exist.

Action Before attempting to delete an alias, verify that it exists.

POP.012.0009.wm_xt_dbdirsvc – {0} "{1}" is invalid. It does not implement case-insensitive lookup for uid attribute

Explanation The database directory service does not support case-insensitive lookup for the UID attribute.

Action Check the server log for information about the UID attribute and the query. Contact an administrator to make sure that the database directory service supports case-insensitive lookup for the UID attribute.

POP.012.0010.wm_spm_commandex – LDAP directory service not found: {0}

Explanation An LDAP directory service with the specified name does not exist or is not available.

Action Verify that: 1. The name of the LDAP directory service is correct. 2. The LDAP directory service is enabled.

POP.012.0010.wm_xt_dbdirsvc – Directory could not load principal "{0}"

Explanation No principal is found in the database directory service using the specified name.

Action Use a valid name when searching the principal in the database directory service.

POP.012.0011.wm_spm_commandex – LDAP directory service already exists: {0}

Explanation An LDAP directory service with the specified name already exists.

Action Specify a unique name for the LDAP directory service.

POP.012.0012.wm_skineditor – You can not set skin parent to itself

Explanation The skin parent cannot be set to itself.

Action The skin parent cannot be set to itself because it is used as a parent for all others.

POP.012.0015.wm_migration – May not export resource which does not have a parent

Explanation You cannot export a resource that does not have a parent.

Action Ensure that the resource has a valid parent.

POP.012.0019.wm_migration – Export failed : Calender Id/Name Invalid

Explanation An invalid Calendar ID or Name is specified for Task Definition export.

Action Specify a valid Calendar ID or Name for export. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0020.wm_migration – Export failed : Shell Id/Name Invalid

Explanation An invalid Shell ID or Name is specified for Task Definition export.

Action Specify a valid Shell ID or Name for export. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0020.wm_securityrealmadmin – Warning: Selecting 'OK' will permanently remove the SecurityRealm from the system.

Explanation Before proceeding, verify that permanent deletion of the security realm will not affect your application or solution.

Action Clcik OK to permanently remove the security realm from the system.

POP.012.0021.wm_migration – Export failed : Skin Id/Name Invalid

Explanation An invalid Skin ID or Name is specified for Task Definition export.

Action Specify a valid Skin ID or Name for export. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0021.wm_securityrealmadmin – Warning: Selecting 'OK' will permanently remove this Container and all its contents from the system.

Explanation Before proceeding, verify that permanent deletion of the container will not affect your application or solution.

Action Clcik OK to permanently remove this container and all its contents from the system.

POP.012.0022.wm_migration – Export failed : Security Realm Id/Name Invalid

Explanation An invalid Security Realm ID or Name is specified for Task Definition export.

Action Specify a valid Security Realm ID or Name for export. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0023.wm_migration – Exception Closing Stream continuing with processing

Explanation An exception occurred during resource migration.

Action Check the detailed error message and take appropriate action.

POP.012.0024.wm_migration – Export failed : Certificate Id/Name Invalid

Explanation An invalid Shell ID or Name was specified for Task Definition export.

Action Specify a valid Shell ID or Name for export. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0025.wm_migration – Export failed : Invalid depth specified {0}

Explanation An invalid depth is specified for Task Definition export.

Action Specify the valid path for Task Definition export. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0026.wm_migration – Export failed : Invalid URI/alias specified for Export

Explanation An invalid URL or alias has been specified for Task Definition export.

Action Specify a valid URL or alias for export. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0027.wm_migration – Export did not containing any DLS Objects

Explanation The DLS object specified for export is not found.

Action Specify the correct object for export. Consult the logs at ..\MWS\server\<instanceName>\logs for more details.

POP.012.0028.wm_migration – Export failed : Invalid ID/URI/alias/Name specified for Task Definition Export

Explanation An invalid ID, URL, alias, or Name is specified for Task Definition export.

Action Specify a valid ID, URL, aliias, or Name for export. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0029.wm_migration – Export failed : Unable to get the skin archive content for {0}

Explanation Unable to get the field value using the specified path.

Action Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0032.wm_migration – The Descriptor file specified is invalid

Explanation An invalid Descriptor file is specified.

Action Specify a valid Descriptor file for export. See the log files in <Software AG_directory>\MWS\server\<instance_name>\logs for further information.

POP.012.0033.wm_migration – Please specify valid target folder path

Explanation An invalid target folder path was encountered while trying to execute migration.

Action Specify a valid target folder path.

POP.012.0034.wm_migration – Import failed for entry :--> {0}

Explanation An invalid entry is specified for Task Definition export.

Action See the log files in <Software AG_directory>\MWS\server\<instance_name>\logs for further information.

POP.012.0035.wm_migration – No Task Instances found for Task application name {0} and task_type_id {1}

Explanation No task instances are found that match the specified search criteria.

Action Verify that the task application name and task type ID specified for the task instance search are valid. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0036.wm_migration – Export failed : Invalid ID/URI/alias/Name specified for Task Rules Export

Explanation An invalid ID, URL, alias, or Name is specified for Task Rules export.

Action Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0037.wm_migration – Export successful for :--> {0}

Explanation The specified export completed successfully.

Action No action required.

POP.012.0038.wm_migration – Failed to get bizPolicy for :--> {0}

Explanation An invalid bizpolicy is specified.

Action Specify a vaild bizPolicy. Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0039.wm_migration – Failed to get view details for thingID:--> {0}

Explanation The view details for the specified object could not be retrieved.

Action Consult the log file at ..\MWS\server\<instanceName>\logs for further information.

POP.012.0041.wm_migration – Import functionality is not supported.

Explanation The import function is not supported.

Action No action required.

POP.012.0055.wm_migration – Import info file {0} is invalid

Explanation The migration portlet was unable to find the control file that lists the My webMethods Server assets to be imported.

Action The user has specified an invalid path and file for the import control file. Check that the specified file exists and has read permission for the current user.

POP.012.0056.wm_migration – Failed to list principals from directory service {0}

Explanation My webMethods Server failed to build a list of principals from the specified directory service. This can happen if the directory service is non-functional and cannot access the underlying directory privider, such as an LDAP server or database.

Action Check the Directory Services Administration portlet to verify that the directory service provider is correctly configured and is enabled. Also check the error logs for directory service provider connection failures.

POP.012.0058.wm_migration – WARNING:Command not found: {0}

Explanation My webMethods Server was unable to locate an internal command by name.

Action This is an internal failure and cannot be remedied by the end-user.

POP.012.0059.wm_migration – Error applying ACL for {0}

Explanation A general error occured applying an import ACL to a principal.

Action This is a system error that cannot be remedied by the end-user.

POP.012.0060.wm_migration – WARNING: Profile Attribute Import failed: {0}

Explanation A general error occured when applying the profile attributes to a user during import. The details of the failure will be appended to the error message.

Action This is a system error that cannot be remedied by the end-user.

POP.012.0061.wm_migration – Error importing skin {0}

Explanation A general error occured when importing a skin. The details of the failure are appended to this message.

Action This is a general message meant to capture any errors that occur during skin import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0062.wm_migration – Error occurred post-processing ACLs

Explanation A general error occurred applying ACLs to imported users, groups, or roles.

Action This is a general message meant to capture any errors that occur when applying ACLs. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0063.wm_migration – Rule target not found for {0}.

Explanation The target of a My webMethods Server rule could not be resolved to a specific My webMethods Server object. For example, a shell rule would display this error if it referenced a shell that did not exist.

Action Examine the rule that is reporting the warning to determine the rule target, then confirm that the rule target exists.

POP.012.0065.wm_migration – Unable to register datasource {0}

Explanation A general failure occured importing a datasource.

Action This is a general message meant to capture any errors that occur during datasource import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0067.wm_migration – Unable to import saved search for {0}

Explanation A general error occured when importing a set of saved searches for the specified resource (for example, Task List Management or My Inbox).

Action This is a general message meant to capture any errors that occur during a saved search import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0068.wm_migration – Unable to locate principal for applying saved searches to {0}

Explanation The import includes private saved searches for a user that does not exist in the target My webMethods Server.

Action Import or create the missing user and then import the saved searches. Otherwise, this error can be ignored, and the private saved searches will not be imported.

POP.012.0069.wm_migration – Unable to locate principal for {0}

Explanation A general warning message that the import references a user, group, or role that could not be located in the target My webMethods Server.

Action Make sure any users, groups, or roles used by the asset that generates this warning are imported or created prior to the import.

POP.012.0070.wm_migration – Unable to apply members to {0}

Explanation A general error occurred importing the role or group membership.

Action This is a general message meant to capture any errors that occur during import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0073.wm_migration – Attempting to import deprecated XType {0}

Explanation The import contained a My webMethods Server asset that is no longer supported in My webMethods Server. For example, older versions of wm_xt_savedsearch are no longer supported in 8.0 and generate this warning.

Action Because the My webMethods Server asset that generated this error is no longer supported, the message is for informational purposes only.

POP.012.0107.wm_portalcontent – This is not meant to be viewed

Explanation An attempt was made to view a portal content resource that does not have a user interface.

Action Do not attempt to view the portal content resource directly. If the resource must be viewed, you must create a renderer that is capable of displaying a user interface for the object.

POP.012.1001.wm_mws_diagnostics – Cannot find file to parse.

Explanation Unable to load the file for analysis.

Action Select a file to upload for analysis.

POP.012.1002.wm_mws_diagnostics – Unable to parse the log file; possible wrong log file format.

Explanation The selected log file cannot be parsed. It is possible that the log file is in an incorrect format.

Action Make sure the selected log file is in the appropriate format.

POP.012.1003.wm_mws_diagnostics – Error during XML marshalling. Possible wrong log file format.

Explanation My webMethods Server was unable to parse the xml log file.

Action Select a log file generated by My webMethods Server and upload again.

POP.012.1004.wm_mws_diagnostics – Unable to locate default {0}

Explanation Unable to locate default {0}

Action Check the My webMethods Server instance configuration.

POP.012.1005.wm_mws_diagnostics – The given host: {0} does not exist

Explanation My webMethods Server was not able to reach the remote host.

Action Check the connection settings for the remote host, verify that My webMethods Server has network access to the host, then try again.

POP.012.1006.wm_mws_diagnostics – An error has occurred while downloading the file: {0}

Explanation There was a problem when parsing the file.

Action Check the My webMethods Server logs for more details. See ..\MWS\server\<serverName>\logs

POP.012.1007.wm_mws_diagnostics – An error has occurred while processing the downloaded file: {0}

Explanation There was a problem processing the file.

Action Check the My webMethods Server logs for more details. See ..\MWS\server\<serverName>\logs

POP.012.wm_httpheaderauth.userDisabled – HTTP header autentication failed because login has been disabled for the {0} user.

Explanation A My webMethods Administrator disabled the user.

Action Contact your My webMethods Administrator. If the user is not disabled, but this message still appears, contact Software AG.

POP.013.0005E **This item is either inactive or deleted and can not be viewed.**

Explanation The item is deleted but has not yet been purged.

Action Use the Deleted Items Administration portlet to remove the deleted items completely from the user interface.

POP.013.0096	**This was not meant to be viewed**
Explanation	An attempt was made to view a My webMethods DBO that does not have a user interface.
Action	Do not attempt to view the resource directly. If the resource must be viewed, you must create a renderer that is capable of displaying a user interface for the object.

POP.013.0097	**Datasource {0} not found**
Explanation	A portlet is attempting to open a database connection to a data source that is not available on the My webMethods Server.
Action	The My webMethods Server administrator should add the missing database connection information using the "Data Sources" portlet.

POP.013.0099	**Unable to construct a secure URL because the MWS secure front end URL is not available**
Explanation	Constructing a secure URL is not possible because the My webMethods Server secure front-end URL is not available.
Action	Make sure that the front-end URL has been specified.

POP.013.0100	**You must enable JavaScript to use this site.**
Explanation	You must enable JavaScript to use this site.
Action	Make sure that JavaScript is enabled.

POP.015.0001	**No constant was specified for {0}.**
Explanation	When the system attempted to parse a My webMethods Server rule, the syntax expected a number and none was found.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0002	**Incorrect number of children. Expected {0} and found {1}.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find another term and none was found. For instance, the rule might have been a comparison, and only one term was found to compare.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0003	**Both child terms must be numbers.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find a numeric value or a value that can be converted into a number. None was found.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0006	**Unknown types for comparison: {0} and {1}.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find valid terms that can be compared to each other but was unable to do so.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0007	**Unable to find object Reference: {0}.**
Explanation	When the system attempted to evaluate a My webMethods Server rule, the rule referred to an object reference which could not be located.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0008	**No object Reference name is set.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find an object identifier and none was found.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0009	**Incorrect number of children. Expected 0 or 1 and found {0}.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser found an unexpected term in the sequence.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0010	**Incorrect number of children. Expected 2 or more and found {0}.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find additional terms and no more were found. For instance, the rule might have been a comparison, and only one term was found to compare.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0011	**Unable to find method to invoke: {0}.**
Explanation	When the system attempted to evaluate a My webMethods Server rule, it was unable to invoke the specified method.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0012	**Incorrect number of children. Expected 1 or more and found {0}.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find additional terms and no more were found. For instance, the rule might have been a comparison, and only one term was found to compare.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0013	**XML Parse Exception. Expected {0} tag and found {1} tag.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser was unable to find the correct XML schema.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0014	**XML Parse Exception while parasing tag {0}.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser was unable to find the correct XML schema.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0015	**Parse Exception at char: {0} {1}.**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser encountered a syntax error at the specified position.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0029	**Expected to find matching char "{0}"**
Explanation	When the system attempted to parse a My webMethods Server rule, the parser encountered a syntax error at the specified position.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.016.0001	**unbalanced end element: expected "{0}" but was "{1}"**
Explanation	The optional PrettyPrintingResponseWriter that was enabled manually by the developer to tidy up the rendered html for a page in the web.xml of the webapp, has detected html that was not well-formed.
Action	This should never happen. If this happens a defect in one of the JSF component renderers has not properly closed one of the html tags that was written to the response writer.

POP.016.0002	**Portlet Preferences are only available inside the Portlet Context**
Explanation	This error message is not used in the current trunk code anymore.
Action	N/A

POP.016.0003	**Else control must be preceded directly by If control**
Explanation	The CAF view contains an "Else" control without a sibling "If" control.
Action	The developer should change the "Else" control to an "If" control or remove it from the CAF view.

POP.016.0004	**Duplicate component ID: {0} (IDs must be unique within naming-container)**
Explanation	In a CAF view two controls have the same ID value.
Action	The developer must change the ID of all the controls that are using the same ID to make the control's ID unique.

POP.016.0005	**Resource bundle is not available: {0}**
Explanation	The specified resource bundle could not be loaded.
Action	The developer should check the resource bundle name to make sure it is correct and make sure the resource bundle file is included in the war file.

POP.016.0006	**View source is not found: {0}**
Explanation	When attempting to load a CAF .view file, the file was not found.
Action	The developer should inspect the deployed war file to make sure the missing view file exists.

POP.016.0007	**Can only switch portlet modes within an action request**
Explanation	A portlet attempted to change the portlet mode outside of an action request which is not allowed per the JSR-168 specification.
Action	The developer should change the portlet source code and not attempt to change the portlet mode from a code path that does not originate in a portlet action handler.

POP.016.0008	**Unable to locate control ID {0} in view: {1}**
Explanation	There was no control in the view that had the specified control id.
Action	The developer should review their application code to make sure the correct control ID is used for the lookup.

POP.016.0009	**Connection failed to datasource {0}. Caused by: {1}**
Explanation	A SQLException was caught while retrieving the data for a RowSetTableContentProvider.
Action	Review the server log file to inspect the stack trace of the exception to try to determine the cause of the error.

POP.016.0010	**Search Results Table Control could not be located**
Explanation	The Export Table Button control could not find the table control to use for exporting data.
Action	The developer should check the Export For property of the Export Table Button control to make sure it matches the ID of the table control.

POP.016.0011	**DateInput component value must be a java.util.Date instance**
Explanation	The value bound to a Date Input control is not the expected data type.
Action	The developer should review the binding expression of the Date Input control to make sure it resolves to a java.util.Date object.

POP.016.0012	**DateRangeInput component value must be a com.webmethods.caf.faces.data.object.DateRange instance**
Explanation	The value bound to a Date Range Input control is not the expected data type.
Action	The developer should review the binding expression of the Date Range Input control to make sure it resolves to a com.webmethods.caf.faces.data.object.DateRange object.

POP.016.0013	**managed-bean-scope value "pageflow" should be changed to "session" for managed-bean "{0}" in application "{1}".**
Explanation	A managed-bean declaration in the faces-config.xml is using the deprecated pageflow managed-bean-scope.
Action	The application developer should change the managed-bean-scope value pageflow to session for the managed-bean and then rebuild and redeploy the application.

POP.016.0014	**ScheduleInput component value must be a com.webmethods.caf.faces.data.object.Schedule instance**
Explanation	The value bound to a Schedule Input control is not the expected data type.
Action	The developer should review the binding expression of the Schedule Input control to make sure it resolves to a com.webmethods.caf.faces.data.object.Schedule object.

POP.016.0015	**Interval must be set to calculate previous or next date**
Explanation	The Schedule.nextDate(..) or Schedule.previousDate(..) api was called but the schedule does not have an interval configured.
Action	Set the interval on the Schedule object before attempting to calculate the next or previous date.

POP.016.0016	**Source table provider does not expose currentRow data and thus cannot be used with PageableTableContentProvider.**
Explanation	Source table provider does not expose currentRow data and cannot be used with the PageableTableContentProvider.
Action	Review the configuration of the table content provider to ensure that it is configured properly.

POP.016.0017	**Cannot find value for script parameter: {0}**
Explanation	The value of a script parameter is null.
Action	The developer should review the source of the script parameter value to determine why it has no value.

POP.016.0018	**Cannot find control with id "{1}" for script parameter: {0}**
Explanation	The control id specified as the value of a script parameter did not match a control in the view.
Action	The developer should review the script paramater value to ensure it matches an exisitng control in the view.

POP.016.0019	**Cannot create null method binding.**
Explanation	An attempt was made to create a method binding object without supplying an expression string.
Action	The developer should review the application code to determine why the expression is null.

POP.016.0020	**Cannot create null value binding.**
Explanation	An attempt was made to create a value binding object without supplying an expression string.
Action	The developer should review the application code to determine why the expression is null.

POP.016.0021	**Cannot convert null locale string.**
Explanation	The com.webmethods.caf.faces.convert.ConvertUtils.getLocalFromToString API was called with a null string.
Action	The developer should review the application code to determine why the supplied locale string is null.

POP.016.0022	**Portlet control can only be used within a portlet request**
Explanation	The Portlet Include control is used in a non-portlet environment.
Action	Do not use the Portlet Include control in a standalone CAF web application.

POP.016.0023	**Cannot export from this context or phase**
Explanation	An attempt was made to export a file, but a compatible export handler was not found.
Action	You should not get this error.

POP.016.0024	**Cannot export control of specified type (id={0},type={1})**
Explanation	An attempt was made to export a control but the control specified was not an UIData based control so it cannot be exported.
Action	The developer should review the configuration of the export button to make sure the correct control is being exported.

POP.016.0027	**Cannot parse string "{0}" as date (using pattern "{1}").**
Explanation	A Date Import control value was a string but it could not be converted to a Date object.
Action	The developer should verify that the value pattern matches the format of the string bound to the control.

POP.016.0029	**The "rowVariable" property must be set to use BoundPropertiesSelectItemGroupProvider.**
Explanation	The rowVariable property must be set to use BoundPropertiesSelectItemGroupProvider.
Action	The developer should review the application code to ensure that the rowVariable property was set.

POP.016.0030	**The "rowType" property must be set to use as an IUpdateableTableContentProvider.**
Explanation	An attempt was made to add a new row to an updatable table content provider but the row type was not specified.
Action	The developer should review the application code to ensure that the rowType property was set.

POP.016.0031	**Cannot create response for {0}.**
Explanation	The CAF view handler was unable to get a response writer to render the output.
Action	This should not occur. If this error occured, there is a catastrophic problem with the server instance. Other errors in the server logs might provide some guidance.

POP.016.0032	**AutoRefresh is not supported**
Explanation	An attempt was made to autorefresh a LazyNodeTreeContentProvider instance that does not support autorefresh.
Action	The developer should review the application code to remove any calls to the autorefresh API.

POP.016.0033	**NeedRefresh is not supported**
Explanation	An attempt was made to mark a LazyNodeTreeContentProvider instance as needing a refresh that does not support autorefresh.
Action	The developer should review the application code to remove any calls to the setNeedRefresh API.

POP.016.0034	**Child not in parent's children list**
Explanation	There is a problem building the structure of a LazyNodeTreeContentProvider instance.
Action	The developer should review the application code that is providing the values to the tree content provider to make sure that the parent/child relationships of the tree data are correct.

POP.016.0035	**The "rowIdBinding" property must be set to add or remove rows to or from a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.**
Explanation	The rowIdBinding property must be set to add or remove rows to or from a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.
Action	Set the rowIdBinding property for a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.

POP.016.0036	**The "rowIdBinding" property must be set to move rows within a SelectableListTableContentProvider.**
Explanation	The rowIdBinding property must be set to move rows within a SelectableListTableContentProvider.
Action	This error message is no longer used.

POP.016.0037	**Saved Search Not Found: {0}**
Explanation	An attempt was made to change the active saved search for a SearchBar control but the target saved search no longer exists.
Action	The end user should refresh the page and select a saved search.

POP.016.0039	**cannot load external resource: {0}**
Explanation	When loading an app-nav.xml file, there was a reference to an external resource which is not allowed.
Action	The developer should review the app-nav.xml and remove the references to external resources.

POP.016.0040	**cannot have more than one root page**
Explanation	When loading an app-nav.xml file more than one root page element was detected.
Action	The developer should review the app-nav.xml file to ensure that there is only one root page declared.

POP.016.0042	**Error updating control value ("{1}" property of "{0}" control).**
Explanation	An error was detected updating a control value. The cause of the error is contain within the message details displayed to the user.
Action	Review the error message details displayed to the user to determine the cause of the error.

POP.016.0043	**Toggle target control "{0}" could not be located.**
Explanation	The For property in a Toggle control does not resolve to a control.
Action	The application developer should review the application code to ensure that the For property of the toggle control matches the expected target control.

POP.016.0043.details – Check the configuration of the control with this id: {0}

Explanation	Provides additional details for the "POP.016.0043" error.
Action	See action for the "POP.016.0043" error.

POP.016.0044	**Calendar StartDay is not set**
Explanation	A calendar control is being rendered but the start day has not been set.
Action	The developer should review the application code to ensure that the calendar has a start day.

POP.016.0045	**Invalid value for height property of the "{0}" control.**
Explanation	The value of the height property of a Static Row or Static Cell control is not a valid height.
Action	The developer should review the application code to ensure that the height value is a valid unit of measure.

POP.016.0046	**Invalid value for width property of the "{0}" control.**
Explanation	The value of the width property of a Static Row or Static Cell control is not a valid width.
Action	The developer should review the application code to ensure that the width value is a valid unit of unit of measure.

POP.016.0047	**Can only reset portlet navigation state within an action request**
Explanation	Portlet navigation state such as if portlet maximized or minimized can only be changed from an ActionRequest
Action	Do not attempt to change the portlet navigate state from the RenderRequest. Use ActionRequest.

POP.016.0048	**The target action was invalid**
Explanation	Request portlet action in PortletUrl is invalid and cannot be found
Action	Check the name action being requested and determine if it is defined in the portlet Java code

POP.016.0048.detail – The target action was: {0}

Explanation	The request portlet action in PortletUrl is invalid and cannot be found
Action	Check the name action being request and determine if it is defined in the portlet Java code

POP.016.0049	**The target action was invalid**
Explanation	It is possible to invoke actions on the designated portlet via PortletURL. To prevent a malicious user from invoking an arbitrarily action on the portlet, each action defined must be annotated in Java code with @PortletAction annotation which instructs MWS runtime that a given action code is allowed when invoked from a url.
Action	Check portlet action definition code, and determine if it has the @PortletAction annotation defined.

POP.016.0049.detail – The target action requires a @PortletAction annotation: {0}

Explanation	It is possible to invoke actions on the designated portlet via PortletURL. To prevent malicious user to invoke an arbitrarily action on the portlet, each action defined must be annotated in Java code with @PortletAction annotation which instructs MWS runtime that a given action code is allowed from a url.
Action	Check portlet action definition code if it has @PortletAction annotation defined

POP.016.0050	**The target action was invalid**
Explanation	To prevent cross-site scripting attacks when malicious script might invoke a porlet action using a URL, the URL used to call a portlet action must obtain and use AXSRF token.
Action	When producing a Portlet URL, make sure that the AXSRF token is included in the URL using com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true) API.

POP.016.0050.detail – The target action "{0}" requires an anti-xsrf token.

Explanation	To prevent cross-site scripting attacks when malicious script might invoke a porlet action using an URL, the URL used to call a portlet action must obtain and use an AXSRF token.
Action	When producing a Portlet URL, make sure that an AXSRF token is included in the URL using com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true) API.

POP.016.0051 **The target action was invalid**

Explanation To prevent cross-site scripting attacks when malicious script might invoke a porlet action using an URL, the URL used to call a portlet action must obtain and use a valid AXSRF token.

Action When producing a Portlet Url, make sure that AXSRF token is included in the URL using com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true) API.

POP.016.0052 **The target action was invalid**

Explanation The Portlet Url can invoke portlet actions from a URL. If the CAF application does not force use of Annotated Portlet Actions, see CAF documentation for more details, then it is possible to use a JSF binding expression to specify the action to invoke. This error is thrown if binding expression does not resolve to a valid method.

Action Check and correct the binding expression used for portlet action because it does not resolve to a valid action method.

POP.016.0052.detail – The target action was: {0}

Explanation The Portlet Url can invoke portlet actions from a URL. If the CAF application does not force the use of Annotated Portlet Actions, see the CAF documentation for more details, then it is possible to use a JSF binding expression to specify the action to invoke. This error is thrown if binding expression does not resolve to a valid action method.

Action Check and correct binding expression used for portlet action because it does not resolve to a valid action method.

POP.016.0053 **Invalid content type. The allowed content types are: {0}**

Explanation An attempt was made to upload a file of an unsupported type to an Attachment Panel control.

Action Upload a file of a supported type for attachments.

POP.016.0054 **Invalid file extension. The allowed file extensions are: {0}**

Explanation An attempt was made to upload a file of an unsupported type to an Attachment Panel control.

Action Upload a file type that is supported as an attachment.

POP.016.0055 **Invalid file size. The maximum file size is: {0}**

Explanation The file uploaded to an Attachment Panel control is larger than the allowed size of an attachment.

Action Upload a smaller file.

POP.017.0001 **Task is locked and you may not update it at this time. Please wait till task is unlocked**

Explanation Task instance is locked in following cases: when a task is being updated, or when task events and assignments are being processed. To ensure state consistency when a task is locked, no other updates to the task are possible (though the task can still be read and searched on). Typically lock time is very short (similar to database transaction).

Action Enable MWS "task" logging category Debug logging and investigate timing and duration of task locks.

POP.017.0003 **Task auditing level is not sufficient to rollback task state**

Explanation Task state should be kept in task audit in order for task rollback to function. If task state is not present in the audit, rollback is not possible

Action Make sure to audit full task state. Task audit options can be controlled as properties on task definition object. You must login as sysadmin, browse to /task.storage, navigate to "Task Definitions" and open properties of task type, then change audit settings.

POP.017.0004 **You don't have permissions to queue new task**

Explanation User does not have a task functional priviliege to queue task of specific task type.

Action Configure Permissions on the user to enable "Queue Task" functional privilege.

POP.017.0007 **You don't have permissions to view this task**

Explanation The current user does not have permission to view task information.

Prior to MWS_7.1.3_Fix9, the mechanism to determine if a user had permission to view a task required the user to hold "view task data" permission. With the introduction of MWS_7.1.3_Fix9, the user/role must have this permission and also must be present in the "assigned to" or "delegated to" lists. Under these conditions, if the user holds only "view task data" permission, permission to view the task is denied and this error occurs.

A task client option, task.base.permission, is available to apply the simpler "view task data" permission even if MWS_7.1.3_Fix9 is applied. For more information, see the Task Engine Optional Settings section in the PDF publication, Task Engine User's Guide.

Action If your system does not have MWS_7.1.3_Fix9 applied, make sure that the user holds "view task data" permission.

If your system has MWS_7.1.3_Fix9 applied, make sure the user holds "view task data" permission and is also present on the "assigned to" or "delegated to" lists. Also, see the explanatory text above concerning the task.base.permission option.

POP.017.0008 **You don't have permissions to view task data**

Explanation Current User does not have permissions to view task business data.

Action Configure Permissions on the user to enable "View Task Data" functional privilege.

POP.017.0009 **You don't have permissions to view audit log**

Explanation Current user does not have permissions to view task audit.

Action Configure Permissions on the user to enable "View Task Audit" functional privilege.

POP.017.0010 **You don't have permissions to accept this task**

Explanation Current user does not have permissions to accept task instance.

Action Configure Permissions on the user to enable "Accept Task" functional privilege.

POP.017.0011 **You don't have permissions to accept other users on this task**

Explanation Current user does not have permissions to accept task instance.

Action Configure Permissions on the user to enable "Accept Task" functional privilege.

POP.017.0012 **You don't have permissions to assign this task**

Explanation Current user does not have permissions to assign task instance.

Action Configure Permissions on the user to enable "Assign Task" functional privilege.

POP.017.0013 **You don't have permissions to rollback this task**

Explanation Current user does not have permissions to rollback task instance.

Action Configure Permissions on the user to enable "Rollback Task" functional privilege.

POP.017.0014 **You don't have permissions to modify task data**

Explanation Current user does not have permissions to update task business data.

Action Configure Permissions on the user to enable "Modify Task Data" functional privilege.

POP.017.0015	**You don't have permissions to modify task info**
Explanation	Current user does not have permissions to update generic task info properties.
Action	Configure Permissions on the user to enable "Modify Task Info" functional privilege.

POP.017.0016	**Task Type ID is not valid {0}**
Explanation	This error is reported when attempting to queue a task and specifying an invalid task type ID (from APIs).
Action	Check if the specified Task Type is deployed to MWS.

POP.017.0017	**Task ID is not valid {0}**
Explanation	This error is reported when attempting to operate on invalid task.
Action	Check if the specified task is still available in MWS, it may already be deleted.

POP.017.0018	**Unable to find task client bean: {0}**
Explanation	During task searches, assignments and events evaluation, Task Engine needs access to task generated beans which are part of task application. This error is reported when it fails to instantiate these beans.
Action	Check if task application was deployed properly, and if there are any errors in the install.log, re-install task application.

POP.017.0020	**Cannot obtain FacesContext for Task application: {0}**
Explanation	Indicates that task application was not properly deployed.
Action	Investigate any possible errors during task application installation. Re-install task application.

POP.017.0022	**You don't have permissions to delegate this task**
Explanation	Current user does not have permissions to delegate task instance.
Action	Configure Permissions on the user to enable "Delegate Task" functional privilege.

POP.017.0024	**You don't have permissions to complete this task**
Explanation	Current user does not have permissions to complete task instance.
Action	Configure Permissions on the user to enable "Complete Task" functional privilege.

POP.017.0025	**You don't have permissions to cancel this task**
Explanation	Current user does not have permissions to cancel task instance.
Action	Configure Permissions on the user to enable "Cancel Task" functional privilege.

POP.017.0026	**You don't have permissions to suspend this task**
Explanation	Current user does not have permissions to suspend task instance.
Action	Configure Permissions on the user to enable "Suspend Task" functional privilege.

POP.017.0027	**You don't have permissions to resume this task**
Explanation	Current user does not have permissions to resume task instance.
Action	Configure Permissions on the user to enable "Resume Task" functional privilege.

POP.017.0028	**User {0} not found**
Explanation	This error is reported when using Task Engine API from WmTaskClient IS package and "impersonated" user name is not valid.
Action	Check the name of the "impersonated" user in the Task Engine API calls.

POP.017.0029	**You can not rollback non-Active task**
Explanation	Only tasks in "Active" state can be rolled back.
Action	Set the status of the task to "Active".

POP.017.0030	**You can not queue new task. Task type is not enabled**
Explanation	Task Type, which the task is about to be queued for, is disabled.
Action	Enable the Task Type from the Task Engine Administration.

POP.017.0032	**Connecting user does not have Impersonate Users privilege**
Explanation	When using remote Task Engine API (from WmTaskClient IS package or web services), the API allows to impersonate user so task operations are performed on behalf of a different user. This is useful because typically passwords of end user are not known, so 'sysadmin' account should be used for remote APIs invocation. It is possible to connect to remote API using a non-sysadmin account, but in this case the user account needs to have "Impersonate Users for Remote Clients" Task Engine privilege.
Action	Grant the user the "Impersonate Users for Remote Clients" Task Engine privilege.

POP.017.0033	**You can not update non-Active task: {1}**
Explanation	Tasks whose status is "Completed", "Cancelled" or "Expired" cannot be updated.
Action	Administrator can set task status back to "Active".

POP.017.0034	**You can not rollback non-Active task**
Explanation	Tasks whose status is "Completed", "Cancelled" or "Expired" cannot be rolled back.
Action	Administrator can set task status back to "Active".

POP.017.0037	**Task is out of date, please refresh**
Explanation	Task Engine updates from UI or API implement "optimistic locking" to ensure that data being updated is up-to-date. This error is reported if task data being passed in from UI or API call is not the latest.
Action	UI needs to be refreshed to reload up-to-date task data. When using Task Engine APIs task data needs to be re-loaded.

POP.017.0039	**You don't have permissions to add task comments**
Explanation	Current user does not have permissions to add comments to task instance.
Action	Configure Permissions on the user to enable "Add Comment" functional privilege.

POP.017.0040	**You don't have permissions to delete task comments**
Explanation	Current user does not have permissions to delete comments from task instance.
Action	Configure Permissions on the user to enable "Delete Comments" functional privilege.

POP.017.0041	**You don't have permissions to delete other user's task comments**
Explanation	Current user does not have permissions to delete comments from task instance which were created by other people.
Action	Configure Permissions on the user to enable "Delete Other People's Comment" functional privilege.

POP.017.0042	**You don't have permissions to create new collaboration tasks**
Explanation	Current user does not have permissions to queue collaboration task of another task.
Action	Configure Permissions on the user to enable "Queue Collaboration Tasks" functional privilege.

POP.017.0045	**You can not update suspended task**
Explanation	If current task status is "Suspended", it can only be updated back to "Active" status. No other updates are allowed.
Action	Administrator can set task status back to "Active".

POP.017.0051	**You can not set the parent task ID using the self task ID**
Explanation	This error is reported when attempting to update an existing task via APIs and set its "parentTaskID" property to the ID of the task itself.
Action	Check "parentTaskID" being set.

POP.017.0052	**You can not set the parent task ID using non integer value**
Explanation	This error is reported when updating or queuing a new task via API and "parentTaskID" property is not a valid task ID value.
Action	Check value of "parentTaskID" being used.

POP.017.0053	**You can not set the parent task ID using invalid task ID**
Explanation	This error is reported when updating or queuing a new task via API and "parentTaskID" property is not a valid task ID value.
Action	Check "parentTaskID" value used.

POP.017.0061	**You can not set the delegated to or delegated from list if their size does not match**
Explanation	When updating task delegation via APIs both "delegatedFromList" and "delegatedToList" list values should contain the same number of items.
Action	Check "delegatedFromList" and "delegatedToList" values used.

POP.017.0071	**Task indexTableDis is null or emptys**
Explanation	Invalid task index configuration is provided from taskDefinition.xml file.
Action	Re-create task index configuration by re-configuring task index fields in Designer.

POP.017.0072	**Task indexTableDis format is invalid: {0}**
Explanation	Invalid task index configuration is supplied in taskDefinition.xml file.
Action	Re-create task index configuration by re-configuring task index fields in Designer.

POP.017.0090 **Failed to invoke IS service: {0}**

Explanation Failed to invoke IS service when executing task decision table assignment. The reason could be that related rule project is not deployed on the corresponding IS server, or that IS service parameters, such as project name, rule set name, etc. are invalid.

Action Please make sure the related rule project is deployed and correct IS service parameters are used when configuring task decision table assigment.

POP.017.0091 **You can not change status of scheduled task**

Explanation If the current status of the task is "scheduled", no other status updates are allowed.

POP.017.0092 **You can not update task schedule date if task not in scheduled status**

Explanation The task schedule date field cannot be updated if the task is not in a "scheduled" status.

POP.017.0093 **Task Schedule Date cannot be before current date**

Explanation The Task Schedule Date attribute specifies the start time of the schedule. However, the value specified in the Task Schedule Date element is for a start time that is before the current time.

Action Specify a date/time value for the Task Schedule Date attribute that is after the current time.

POP.017.0094 **Task Schedule Date cannot be after Expire date**

Explanation The Task Schedule Date attribute specifies the start time of the schedule. However, the value specified in the Task Schedule Date element is for starting the schedule after the Expire date of the schedule.

Action Specify a date/time value for the Task Schedule Date attribute that is before the Expire date.

POP.017.0095 **You can not change status of active/suspended task to scheduled**

Explanation Tasks with an "active" or "suspended" status cannot be updated to “scheduled”.

POP.017.0096 **You can not accept a scheduled task**

Explanation Tasks with a “scheduled” status cannot be accepted.

POP.017.0097	**Child task schedule date cannot be before parent task schedule date**
Explanation	A child task should be scheduled to start after its parent task started.
Action	Reschedule the child task for a date after the parent task's start date. Alternatively, move back the parent task schedule date.

POP.017.0098	**Child task schedule date cannot be after parent task expiredate**
Explanation	A child task should be scheduled for a date before its parent task expires.
Action	Reschedule the child task for a date before the parent task's expiration date. Alternatively, extend the parent task's expiration date.

POP.017.0100	**Task has reached maximum number of modifications**
Explanation	The task has reached the maximum number of modifications set by the Infinite Loop task rule.
Action	Keep a smaller number of modifications to avoid such an error.

POP.017.0101	**Unhandled Exception during rule processing. Rule [{0}]**
Explanation	An exception was caught during processing Task Rules.
Action	Check the My webMethods Server logs at ..\MWS\server\<instancename>\logs for additional exception details to determine the cause.

POP.017.0102	**Unhandled Exception during task change processing**
Explanation	An exception was thrown while publishing a new notification or processing task events.
Action	Check the My webMethods Server logs at ...\MWS\server\<instanceName>\logs for additional exception details to determine the cause.

POP.017.0103	**Unable to deliver task completion to Process runtime (PRT)**
Explanation	Task completion cannot be delivered to the Process runtime.
Action	Check the My webMethods Server logs at ..\MWS\server\<instanceName>\logs for additional exception details to determine the cause.

POP.017.0104	**Process runtime (PRT) task step failed**
Explanation	An exception was thrown while processing the task completion. Most likely the time for redelivery was exceeded.
Action	Check the My webMethods Server logs at ..\MWS\server\<instanceName>\logs for additional exception details to determine the cause.

POP.017.0106	**Indexed task searches are not available in Preview Server. Please use standalone MWS server instead**
Explanation	Indexed task searches are not available when the portal system is running in a preview server mode.
Action	Use a standalone My webMethods Server instead.

POP.017.0107	**Cannot process rule [{0}] for Task [{1}] due to [{2}]**
Explanation	An exception was thrown while processing the task rule, which may mean that the task cannot be found.
Action	Check the My webMethods Server logs at ..\MWS\server\<instanceName>\logs for additional exception details to determine the cause.

POP.017.0108	**Failed to acquire lock for [{0}] in {1} milliseconds**
Explanation	The exception occurs when a timeout occurs while waiting to acquire a task lock in the task locking service.
Action	Internally used. Some handlers may re-send an event to be re-delivered later.

POP.017.0120	**RuleName is null or empty**
Explanation	The RuleName attribute of the schedule rule to be added or updated cannot be null.
Action	Specify a valid non-null RuleName attribute.

POP.017.0121	**TaskTypeID is null or empty**
Explanation	The TaskTypeID attribute of the schedule rule to be added or updated cannot be null.
Action	Specify a valid non-null TaskTypeID attribute.

POP.017.0122	**StartDate is null or empty**
Explanation	The StartDate attribute of the schedule rule to be added or updated cannot be null.
Action	Specify a valid non-null StartDate attribute.

POP.017.0123	**Failed to obtain a task index engine manager for: {0}.**
Explanation	Task Engine cannot obtain a task index engine manager of the specified type.
Action	Verify whether: 1. The specified task index manager is registered as an OSGi service. 2. The OSGi service id for the task index manager is correct. 3. The service is running without errors in the My webMethods Server OSGi runtime.

POP.018.0001 **IView object does not support indexed properties**

Explanation A binding expression attempted to resolve a property of an IView object by index. This operation is not supported.

Action The ViewPropertyResolver does not support lookup of a property by index. Change the application code so that it does not attempt an unsupported operation.

POP.018.0002 **IView object is readonly**

Explanation A binding expression attempted to update a property of an IView object which is not supported.

Action The ViewPropertyResolver does not support update of an IView property. Change the application code so that it does not attempt an unsupported operation.

POP.018.0003.DirSearchProvider – Failed to move to next principal in directory services, service={0}, error={1}

Explanation An unexpected exception occurred during the directory service search API call.

Action Review the server log files for the stack trace of the cause.

POP.018.0004.DirSearchProvider – Failed to evaluate expression for object, exp={0}, obj={1}, error={2}

Explanation An unexpected error was caught while evaluating the value of the property used to sort the principal.

Action Review the server log files for the stack trace of the cause.

POP.018.0005.DirSearchProvider – Failed to create a directory service iterator, dirService={0}, error={1}

Explanation An unexpected error was caught while creating a directory service iterator.

Action Review the server log files for the stack trace of the cause.

POP.018.0006.DirSearchProvider – Unable to locate the attribute provider for URI={0}

Explanation While filtering a principal by an attribute, the provider of the attribute was not located.

Action Check the server to make sure the logged provider URI resolves to a attribute provider.

POP.018.0007.AttachmentsProvider – Attachments container id is not valid: {0}

Explanation The attachements provider for an Attachment Panel control does not have a valid container id for read/write of attachment files.

Action The developer should review the application code to ensure the attachment provider container id is a valid folder id or alias.

POP.018.0008.AttachmentsProvider – Specified attachments container id is not a container: {0}

Explanation The attachements provider for an Attachment Panel control does not have a valid container id for read/write of attachment files.

Action The developer should review the application code to verify that the attachment provider container id is a valid folder id or alias.

POP.018.0009.AttachmentsProvider – Attachment id has not been specified

Explanation The attachements provider updateAttachment or removeAttachment API was called but the attachment id parameter was null.

Action The developer should review the application code to verify that the API calls are passing an attachment id value that is not null.

POP.018.0010.AttachmentsProvider – FileItem has not been specified

Explanation The attachements provider addAttachment or updateAttachment API was called but the fileItem parameter was null.

Action The developer should review the application code to verify that the API calls are passing a a fileItem value that is not null.

POP.018.0011.AttachmentsProvider – The specified attachment id is not a child of the attachment container: {0}

Explanation The attachments provider updateAttachment or removeAttachment API was called with an attachment id that is not a child of the attachments container.

Action The developer should review the application code to verify that the API calls are passing an attachment id value that is a child of the attachments folder.

POP.019.0001 **Unable to convert data type "{0}" to "{1}"**

Explanation The system failed to convert an object from the source data type to the destination data type.

Action Review the error stack trace in the My webMethods Server server logs to determine the cause.

POP.019.0002 **Cannot load "{0}" because it is not an HTTP resource**

Explanation The html parser failed to load the resource.

Action Inspect the error stack trace in the My webMethods Server server logs to determine the cause.

POP.023.0001	**Failed to start HPSTRA engine**
Explanation	An error occurred and the HPSTRA engine failed to start.
Action	Check the HPSTRA configuration and restart My webMethods Server.

POP.023.0002	**Failed to save HPSTRA configuration**
Explanation	An internal error occurred when saving the specified HPSTRA configuration.
Action	Gather error information from the logs and contact Software AG Global Support.

POP.023.0003	**Failed to configure HPSTRA engine**
Explanation	An error occurred when configuring the HPSTRA engine.
Action	Gather error information from the logs and contact Software AG Global Support.

POP.023.0004	**Error occurred while stopping HPSTRA**
Explanation	An internal error occurred when stopping the HPSTRA engine.
Action	Gather error information from the logs and contact Software AG Global Support.

POP.023.0005	**Invalid HPSTRA configuration specified. Details: {0}**
Explanation	The specified HPSTRA congfiguration is invalid or incomplete.
Action	Check the HPSTRA configuration and retry the previous operation.

POP.023.0006	**Failed to perform operation, HPSTRA engine is not enabled. Please configure it properly**
Explanation	The HPSTRA engine is disabled and cannot perform the requested operation.
Action	Enable the HPSTRA engine and retry the operation.

POP.023.0007	**HPSTRA action execution failed, Reason:**
Explanation	An internal error occurred and the HPSTRA engine failed to execute the requested operation.
Action	Gather error information from the server logs and contact Software AG Global Support.

POP.023.0009	**Failed to authenticate against an Elasticsearch instance, please check your credentials**
Explanation	The user name and/or password, specified in the HPSTRA configuration are not valid.
Action	Check your credentials in the Authentication section of the HPSTRA configuration and retry the operation.

POP.023.0010 **An Elasticsearch exception occurred. Details: {0}**

Explanation The Elasticsearch server returned an error message in response to the request from the HPSTRA engine.

Action Gather error information from the logs and contact Software AG Global Support.

POP.101.0001.com.softwareag.caf.shared.diagnostics – The directory does not exist

Explanation The specified directory is not found.

Action Provide a valid directory location as a parameter.

POP.101.0002.com.softwareag.caf.shared.diagnostics – The specified path is not a valid directory

Explanation The specified location is not a directory.

Action Provide a valid directory location as a parameter.

POP.101.0006.com.softwareag.caf.shared.diagnostics – Unsupported report type

Explanation A report was generated by an AeventProcessor which is not supported.

Action Use an existing report or add the new one to the list of supported reports in LogAnlyzer.java

POP.101.0007.com.softwareag.caf.shared.diagnostics – An error occurs while adding a root element to the analyzed log file

Explanation A root element cannot be added to the analyzed log file.

Action Check the log file for any discrepancies.

POP.101.0010.com.softwareag.caf.shared.diagnostics – Either one or both of the provided documents are null

Explanation The method load() was not invoked beforehand or it was invoked using incorrect parameters.

Action You need to call the load() method before you continue using EnvDiff API.

POP.101.0011.com.softwareag.caf.shared.diagnostics – At least one argument has to differ from null

Explanation This invocation is not supported.

Action Contact Software AG Global Support.

POP.101.0012.com.softwareag.caf.shared.diagnostics – Cannot read the following file: {0}

Explanation The file cannot be read.

Action Check file and directory permissions; if the file is accessed over a network, check network connectivity.

POP.101.0013.com.softwareag.caf.shared.diagnostics – No output channel found

Explanation This behavior is not supported.

Action Contact Software AG Global Support.

POP.101.0014.com.softwareag.caf.shared.diagnostics – Input directory or file does not exist: {0}

Explanation The specified directory or file does not exist.

Action Specify an existing directory or file.

POP.101.0015.com.softwareag.caf.shared.diagnostics – The system variable %1$s and the %2$s parameter are not set

Explanation The required system properties are incorrect or are not set.

Action Set the system variables using proper values. For more information, see the product documentation.

POP.101.0016.com.softwareag.caf.shared.diagnostics – Similarity level must be in the following range: 0-100

Explanation Similarity level is not set to a valid value.

Action Set a similarity level between 0 and 100.

POP.101.0017.com.softwareag.caf.shared.diagnostics – Java artifact mapping file does not exist in: {0}; cannot generate {1} report.

Explanation A Java artifact mapping file cannot be found. The report cannot be generated.

Action Specify a valid Java artifact mapping XML file. Use the --java-artifact-mapping parameter to specify the path.

POP.101.0018.com.softwareag.caf.shared.diagnostics – File not found in: {0}

Explanation The specified file does not exist.

Action Specify an existing file.

POP.101.0019.com.softwareag.caf.shared.diagnostics – File name is null

Explanation The name of the file was not set in java artifact mapping XML file and this is a unsupported scenario.

Action Contact Software AG Global Support.

POP.101.0020.com.softwareag.caf.shared.diagnostics – Product ID is null.

Explanation The product ID was not set in a Java artifact mapping XML file; this is a unsupported scenario.

Action Contact Software AG Global Support.

POP.101.0021.com.softwareag.caf.shared.diagnostics – Database configuration is not specified

Explanation This error occurs when the file mws.db.xml is not specified or cannot be found.

Action Specify a valid mws.db.xml file.

POP.102.0001.com.webmethods.caf.shared.bpm.common – This configuration is missing important parameters! Session and node id are mandatory!

Explanation This error occurs: 1) when a node id is not provided when trying to search for a content type, or 2) when a session is not opened.

Action For 1), select a node that the searched content is associated with.For 2), verify that the CSP server is running, properly configured, and connected.

POP.102.0002.com.webmethods.caf.shared.bpm.common – Illegal connection parameters

Explanation An attempt has been made to connect to the CSP server without providing username/password values.

Action In My webMethods, check the Environment entries for the "wm_csp_task" portlet. If they are empty, next check the Global Environment entries. If no values are provided, specify a value for "csp/default/username" and "csp/default/password" entries. In general, the user name and password are specified in the Global Environment entries, except in cases when you have multiple CSP servers and want different portlets to connect to different servers. Otherwise, the Global Environment values are inherited by all portlets.

POP.102.0003.com.webmethods.caf.shared.bpm.common – The provided session is null!

Explanation The session which is the client primary access point to the CSP server is not instantiated.

Action Verify that the username and password are correct in the CSP configuration in My webMethods Server.

POP.102.0005.com.webmethods.caf.shared.bpm.common – Error while marshalling!

Explanation This error indicates that a low-level communication problem exists between Task Engine and webMethods Content Service Platform.

Action Stop and restart the Task Engine and the CSP server and try again. If the problem persists, contact Software AG Global Support.

POP.102.0006.com.webmethods.caf.shared.bpm.common – Error while unmarshaling result!

Explanation This error indicates that a low-level communication problem exists between Task Engine and webMethods Content Service Platform.

Action Stop and restart the Task Engine and the CSP server and try again. If the problem persists, contact Software AG Global Support.

POP.102.0008.com.webmethods.caf.shared.bpm.common – This configuration is missing important parameters! Content id is mandatory!

Explanation The Content ID value is not set.

Action Verify that a Content ID is set for this provider; ensure that the binding expression is correctly configured.

POP.102.0009.com.webmethods.caf.shared.bpm.common – No retrieval module initiated! Please set proper session!

Explanation The CSP session is not set for the provider; the retrieval module cannot be initiated.

Action Verify that a session is set for this provider; ensure that the binding expression is correctly configured.

PerformanceMonitorDefaultviewView.errorMessage.unsupportedPerfServiceImpl – Currently enabled performance service implementation {0} does not support analysis. Cannot proceed.

Explanation The performance service implementation specified for support analysis is not supported. Without these mandatory parameters, the execution cannot proceed.

Action Provide the supported parameters required for the currently enabled performance service.

WSC.001.0002 Failed to bind to endPoint: {0} and interface: {1}

Explanation The error occurs at binding to the WS-Stack registry.

Action Inspect the stack trace in the My webMethods Server log files to determine the cause of the exception.

WSC.001.0004	**Context instance does not allow access of inbound SOAP request interceptors**
Explanation	An exception occurred while registering the interceptor with a context at the WS Server service provider.
Action	Inspect the stack trace in the My webMethods Server log files to determine the cause of the exception.

WSC.001.0005	**Context instance does not allow access of outbound SOAP request interceptors**
Explanation	An exception occurred while registering the request interceptor with the context.
Action	Verify that the context is an instance of ProxyContext.

WSC.001.0006	**Exception occurred while invoking webservice: {0}. Details: {1}**
Explanation	An exception occurred while invoking the specified web service.
Action	Inspect the stack trace in the My webMethods Server log files to determine the cause of the exception.

WSC.001.0007	**Unable to connect to web service at {0}**
Explanation	The reason for the web service connection failure is specified in the error message.
Action	Check the detailed error message and take the appropriate action.

WSC.002.0002	**SAML artifact not found in request**
Explanation	The exception occurs when SAML authentication has to be performed, and indicates that the SAML artifact was not found within the SOAP headers of the incoming SOAP request.
Action	Check the SOAP request regarding the SAML artifact.

WSC.002.0009	**SAML Assertion is missing the subject name**
Explanation	An exception was thrown during the verification of the SAML Assertion showing that the subject name is missing.
Action	Check the subject name.

WSC.002.0010	**SAML Assertion has an invalid authentication method, method: {0}**
Explanation	The SAML Assertion passed is not valid.
Action	Specify a valid authentication method.

WSC.002.0012 **SAML Assertion has an invalid statement format**

Explanation While validating the SAML Assertion the format of the statement is invalid.

Action Specify a valid statement format.

WSC.002.0013 **SAML Assertion has an invalid assertion id.**

Explanation The SAML Assertion has an invalid assertion ID.

Action Check the assertion ID.

WSC.002.0014 **The credential type is not supported: {0}**

Explanation An exception occurred during realm authentication.

Action Supply a correct credential type.

WSC.002.0015 **User failed to authenticate with basic auth: {0}**

Explanation An exception occurred during realm authentication.

Action Check the username and password supplied.

ascii.only.name.validation.msg – Name cannot contain non ASCII characters!

Explanation The Name field can contain only ASCII charachters.

Action Remove the non-ASCII characters from the Name field.

config.connection.authentication.password.value – 'Password' cannot be null or empty

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "password" key under connection > authentication does not exist, or has a null or empty value.

Action Check the HPSTRA configuration file, supply a valid password for connecting to the Elasticsearch server, and restart My webMethods Server.

config.connection.authentication.username.value – 'Username' cannot be null or empty

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "username" key under connection > authentication does not exist, or has a null or empty value.

Action Check the HPSTRA configuration file, supply a valid user name for connecting to the Elasticsearch server, and restart My webMethods Server.

config.connection.autoDiscovery.pollingInterval.value – Autodiscovery 'polling interval' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "pollingInterval" key under connection > autoDiscovery has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "pollingInterval" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.connection.connectTimeout.value – The 'connect timeout' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "connectTimeout" key under connection has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "connectTimeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.connection.connectionPool.maxConnections.value – The 'maximum pool connections' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "maxConnections" key under connection has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "maxConnections" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.connection.requestTimeout.value – The 'request timeout' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "requestTimeout" key under connection has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "requestTimeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.connection.servers.size.value – The 'servers' parameter should contains at least one server URL (http, https)

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "servers" key under connection is empty, or has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "servers" key, and restart My webMethods Server. Valid values are unique http or https URLs.

config.connection.servers.type.value – All entries of the 'servers' parameter should be unique and valid server URLs (http, https)

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "servers" key under connection has one or more invalid values.

Action Check the HPSTRA configuration file, supply valid values for the "servers" key, and restart My webMethods Server. Valid values are unique http or https URLs.

config.connection.value – Configuration's connection information cannot be null

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "connection" key does not exist.

Action Check the HPSTRA configuration file, supply a valid configuration under the "connection" key, and restart My webMethods Server.

config.persistence.consistency.value – Index operation 'consistency' parameter should be either null (use default settings) or one of the values: 'one' | 'quorum' | 'all'

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "consistency" key under "persistence" has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "consistency" key, and restart My webMethods Server. Valid values are null (default), "one", "quorum", and "all".

config.persistence.createIndex.numberOfReplicas.value – The parameter 'number_of_replicas' for the index should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "numberOfReplicas" key under connection > createIndex has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "numberOfReplicas" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.persistence.createIndex.numberOfShards.value – The parameter 'number_of_shards' for the index should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "numberOfShards" key under connection > createIndex has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "numberOfShards" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.persistence.timeout.value – Index operation 'timeout' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "timeout" key under "persistence" has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "timeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.search.searchType.value – Search operation 'search_type' parameter should be either null (use default settings) or one of the values: 'query_then_fetch' | 'dfs_query_then_fetch'

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "searchType" key under "search" has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "searchType" key, and restart My webMethods Server. Valid values are null (default), "query_then_fetch", and "dfs_query_then_fetch".

config.search.timeout.value – Search operation 'timeout' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "timeout" key under "search" has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "timeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.synchronization.batchSize.value – Synchronization's 'batch size' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "batchSize" key under "synchronization" has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "batchSize" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.synchronization.lockTimeout.value – Synchronization's 'lock timeout' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "lockTimeout" key under "synchronization" has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "lockTimeout" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

config.synchronization.pollingInterval.value – Synchronization's 'polling interval' parameter should be greater or equal to 1

Explanation My webMethods Server stores the configuration for the HPSTRA engine in the hpstra_config.json file. This exception occurs when the configuration file was modified manually, and the "pollingInterval" key under "synchronization" has an invalid value.

Action Check the HPSTRA configuration file, supply a valid value for the "pollingInterval" key, and restart My webMethods Server. Valid values are positive integers from 1 to 2147483647.

error.msg.noDebug The requested URL {0} resulted in an error.

Explanation An error occurred while processing the URL.

Action Verify that the URL is correct.

error.msg.withDebug – The requested URL {0} resulted in an error in {1}.

Explanation An error occurred while processing the URL.

Action Verify that the URL is correct.

g11n.Spregistration.propertygroup.customErrMsg6 – SAML Attribute Name cannot be empty

Explanation You did not provide a value in the reqired field SAML Attribute Name.

Action Provide a valid value in the SAML Attribute Name field.

g11n.Spregistration.propertyline.non-ascii – Only alphabet, numbers and underscores allowed and Length should not be more than 25

Explanation The Attributes field can contain up to 25 symbols. Only alphanumerical characters and underscores are allowed.

Action Remove any illegal or excess characters from the field.

g11n.UmConnectionConfiguration.service.unavailiable – Configuration store service unavailiable

Explanation	The OSGI service that stores the SSL configuration in the platform secure store is not available.
Action	Retry saving the SSL configuration. If the issue persist, contact your system administrator.

g11n.UmConnectionConfiguration.validation.path – Invalid path specified

Explanation	The location of the truststore/keystore for CA/client certificates is not a valid file path.
Action	Check the specified path and supply a valid entry.

http.status.401	**Unauthorized**
Explanation	Invalid basic authentication credentials.
Action	Contact the security officer/web master for this resource and obtain the proper authorization for your credentials.

http.status.403	**Forbidden**
Explanation	The action is prohibited.
Action	The owner of this resource does not allow access to the resource. Contact the security officer/web master for this resource and obtain the proper authorization for your credentials.

http.status.404	**Not Found**
Explanation	The specified value was not found.
Action	Verify that the URL is correct. This error most often occurs when the resource has been removed from the server. It can also be caused by a DNS failure, if the server has been assigned a new IP address, or if the server no longer exists.

http.status.405	**Method Not Allowed**
Explanation	This HTTP method (GET, PUT, etc.) is not allowed on this server for the specified URL.
Action	Use only supported methods. Contact the security officer/web master for this resource for more information.

http.status.406	**Not Acceptable**
Explanation	The content returned from the server is not specified as acceptable by the client.
Action	Investigate the problem by looking at the Accept headers generated by the client system and the data stream returned by the web server.

http.status.407	**Proxy Authentication Required**
Explanation	Access to the URL resource requires the prior use of a proxy server that needs authentication which has not been provided.
Action	Log in to the proxy server with valid credentials and retry.

http.status.408	**Request Time-out**
Explanation	The interval of time between the establishment of an IP connection (socket) between the client and the server and the receipt of any data on that socket is too long. The server has dropped the connection.
Action	Attempt reconnecting to the resource. This error is typically caused by high server loads or network traffic. Contact the web master for this resource if the problem persists.

http.status.409	**Conflict**
Explanation	The request submitted by the client cannot be completed because it conflicts with an existing condition or rule. For example, a file on the server cannot be replaced with a file that has an older timestamp.
Action	Examine the client action and consult with the web master for this resource.

http.status.413	**Request Entity Too Large**
Explanation	The HTTP data stream sent by the client is too large to be accepted by the server.
Action	Attempt sending data in smaller batches. Otherwise, consult with the web master for this resource.

http.status.415	**Unsupported Media Type**
Explanation	The HTTP data stream sent by the client identifies a URL resource with a media type that does not agree with the media type specified on the request, is incompatible with the current data for the resource, or is incompatible with the HTTP method specified on the request.
Action	Examine the request and correct the media type if possible. Otherwise, consult with the web master for this resource.

http.status.422	**Unprocessable Entity (WebDAV)**
Explanation	The request was well-formed but was unable to be processed due to semantic errors.[
Action	Examine and correct the entity definition.

http.status.423	**Locked (WebDAV)**
Explanation	The resource that is being accessed is locked.
Action	Unlock the resource if possible. Otherwise, contact the web master for this resource.

http.status.424	**Failed Dependency (WebDAV)**
Explanation	The method could not be performed on the resource because the requested action depended on another action and that action failed (for example, a PROPPATCH).
Action	Examine the action request, correct as necessary, and perform again.

http.status.500	**Internal Server Error**
Explanation	The server encountered an unexpected condition that prevented it from fulfilling the request by the client.
Action	Make sure that the required services are running, communication channels are accessible, and parameters are valid. Examine the server logs for more information if possible. Otherwise, contact the server administrator.

http.status.501	**Not Implemented**
Explanation	The server does not understand or does not support the HTTP method it finds in the HTTP data stream sent to it by the client.
Action	Make sure the request contains a vallid HTTP method.

http.status.507	**Insufficient Storage (WebDAV)**
Explanation	The method could not be performed on the resource because the server is unable to store the representation needed to successfully complete the request.
Action	This condition is usually temporary. If persisten, verify that sufficient storage is available on the server, or contact the system administrator. If the request that received this status code was the result of a user action, the request must not be repeated until it is requested by a separate user action.

install.fixes.1	**Installing update XML component {0}**
Explanation	The update XML file must be in the proper format and an installation location must be specified.
Action	Make sure the file contains the correct XML format and specify the correct location.

install.fixes.2	**Failed to install update XML component {0}**
Explanation	Update manager has attempted to install the update XML component but the attempt has failed.
Action	Make sure that My webMethods Server is running and is connected to the network, and that network connectivity exists to the server. Retry the installation. Otherwise, contact the system administrator.

install.fixes.3	**Failed to delete update XML component {0}**
Explanation	Update Manager attempted to delete the XML component but was not successfull.
Action	Make sure that My webMethods Server is running and is connected to the network, and that network connectivity exists to the server. Retry the deletin. Check the server log file for more information. Otherwise, contact the system administrator.

install.fixes.4	**Failed to process all update XML components**
Explanation	The update XML components operation could not be processed.
Action	Verify that the parameters are appropriately specified in the request. Otherwise, contact the system administrator.

install.fixes.5Not Used – Completed processing of update XML components

Explanation	XML components were updated successfully.
Action	No actiion required.

ldap.exceptions	**Unable to retrieve data from {0} ldaps**
Explanation	The specified directory services failed to return a result due to an error.
Action	Check the My webMethods Server logs for errors related to the specified directory services.

message.um.remoteupdate.fail – MWS node with name "{0}" failed to update with new Universal Messaging URL.

Explanation During an update of the cluster configuration, the specified node failed to be updated.

Action Log into the specified node, and on the Cluster Administration page, click Reload to manually update the node.

message.um.remoteupdate.fail.ctx – MWS failed to acquire user context, before notifying other nodes about UM URL change.

Explanation During an update of the cluster configuration, the specified node failed to be updated.

Action Log into the specified node, and on the Cluster Administration page, click Reload to manually update the node.

message.um.update.fail – Current MWS node failed to update with new Universal Messaging URL.

Explanation While updating the JNDI URL of the specified node, the JMS system of that node failed to reload.

Action Restart the node. If My webMethods Server cannot connect to Universal Messaging, check the logs for errors. If the errors are not related to network connectivity, contact Software AG.

message.um.url.invalid – The specified JNDI URL "{0}" is not valid.

Explanation The specified JNDI URL does not conform to the Universal Messaging standards.

Action The URL must start with a valid UM protocol, such as nsp, nsps, nhp, or nhps, for example: nsp://myurl:9000.

21 OSGi Messages

OGICRE0003	**Expected String [2] but its length is ''{0}''**
Explanation	There is a problem with the user-defined credentials that are passed to the server in order to authenticate the user before creating MBeanServerConnection.
Action	The expected user-defined credentials are a username and password. Provide these security credentials only.

OGICRE0004	**Authentication fails with user ''{0}''**
Explanation	There is a problem with authentication of the current user.
Action	Check the provided username and password.

OGICRE0015	**''{0}'' property is not set, cannot proceed.**
Explanation	JMX authentication configuration property '"com.softwareag.platform.startup.jmx.auth.config"' is not set, cannot proceed.
Action	Set the JMX authentication configuration property '"com.softwareag.platform.startup.jmx.auth.config"' and provide a valid value to it.

OGICRE0016	**JAAS login configuration property ''{0}'' is not set, cannot proceed.**
Explanation	During the startup routine, the OSGi platform attempts to prepare JAAS configuration. The platform expects that the "com.softwareag.platform.startup.jaas.login.config" property is set and points to a valid JAAS configuration file. The error message is displayed when the property is not available at platform startup.
Action	Ensure that the "com.softwareag.platform.startup.jaas.login.config" is set and points to a valid JAAS configuration file.

OGICRE0019	**System property "java.io.tmpdir" is not set or empty, cannot ensure that the directory exists.**
Explanation	The 'java.io.tmpdir' property is expected to be set by the JVM. The platform startup cannot ensure that the directory pointed by this property is available if the property is empry or undefined.
Action	If you want to use a temporary file directory, make sure that it exists and is set to the JVM.

OGICRE0021	**Java temporary directory pointed by "java.io.tmpdir" system property: "{0}" does not exist and cannot be created.**
Explanation	The java temporary directory pointed by the "java.io.tmpdir" JVM property does not exist and automatic creation of this directory failed.
Action	Ensure that the directory pointed by the "java.io.tmpdir" JVM property exists.

OGICRI0008	**Standard JMX Management is used.**
Explanation	Custom authentication is not enabled. The standard JMX Management is used.
Action	If you want to enable custom authentication, set a System property with name "com.softwareag.jmx.noCustomAuthentication" and set it to "false".

OGICRI0013	**Using JMX authentication configuration: "{0}"**
Explanation	Information about the value of "com.softwareag.platform.startup.jmx.auth.config" JMX authentication configuration parameter.
Action	None.

OGICRI0014	**Using JAAS login configuration: "{0}".**
Explanation	Information about the value of "java.security.auth.login.config" JAAS configuration parameter.
Action	None.

OGICRI0022	**Successfully created Java temporary directory: {0}**
Explanation	Directory pointed by "java.io.tmpdir" system property did not exist and the OSGi platform startup bundle created it automatically.
Action	None.

OGICRW0017	**Configured JMX RMI Agent port: ''{0}'' is not valid; default port ''{1}'' will be used instead.**
Explanation	The platform startup routine is attempting to initialize the JMX RMI Agent using the port configured in the "com.softwareag.platform.startup.jmx.rmi.agent.port" key. The property is not a valid number.
Action	Set a valid port number in the "com.softwareag.platform.startup.jmx.rmi.agent.port" key.

OGICRW0020	**The parent directory of the Java temporary directory ({0}) is not write enabled.**
Explanation	Cannot write into the parent directory of the temporary directory pointed by the ''java.io.tmpdir'' system property. Automatic creation of the temporary directory will fail.
Action	Ensure that the user who started the platform has permissions to write into the parent directory of the temporary files directory.

OGICRW0023	**The parent directory of the Java temporary directory pointed by ''java.io.tmpdir'' system property: ''{0}'' does not exist and cannot be created.**
Explanation	When the OSGi platform is started it attempts to ensure that the temporary files directory (denoted by the "java.io.tmpdir" system property) exists. If the directory does not exist on the file system, the OSGi platform startup bundle attempts to create it. This message is displayed when the OSGi platform startup bundle fails to create the parent directory of the temporary files directory.
Action	Ensure that the directory pointed by the ''java.io.tmpdir'' JVM property exists.

OGIMIGE0002	**ERROR: Missing file in source installation - {0}**
Explanation	This message is displayed when no source file is found.
Action	Check if the file exists and is readable for the user.

OGIMIGE0003	**ERROR: Missing file in destination installation - {0}**
Explanation	This message is displayed when no destination file is found under path: <installdir_new_version>/profiles/<some_profile>/configuration/com.softwareag.platform.config.propsloader/
Action	Check if the file exists and is readable for the user.

OGIMIGE0004	**ERROR: Backup failed for destination file - {0}**
Explanation	The file is backed up before merging . Losing this file might be crucial.
Action	Make sure that the file can be written in the parent directory.

OGIMIGE0006	**ERROR: Error while opening file - {0}**
Explanation	In order to migrate a file its content should be read. This error occurs because the file could not be opened properly.
Action	Make sure the file is not locked (for example, the file may be already opened by another program).

OGIMIGE0007	**ERROR: Result configuration file in destination installation was not found - {0}**
Explanation	After merging, the result is either a new file, or an updated overwritten destination file.
Action	Please make sure the file exists and is readable for the user.

OGIMIGE0010	**ERROR: More than one in the destination installation - {0} were found under {1}**
Explanation	This message is displayed when more than one destination file is found. This is not expected if a clean destination installation is done.
Action	Check the log file to see where are the files. Remove the unneeded files and leave only one file - the default one.

OGIMIGE0013	**ERROR: Loading source properties layout configuration failed. The source file is: from file {0}**
Explanation	When we load our properties we also load the comments and blank lines the file contains.
Action	Make sure that you source file is a valid java poprerty file and it is not corrupted.

OGIMIGE0014	**ERROR: Cannot identify version of product {0}. Cannot find any locally installed products in the specified installation directory: {1}**
Explanation	The migration application attempted to identify the version of a locally installed product with the given product prop file name (without the .prop suffix), but no locally installed products were found in the specified installation directory.
Action	Specify the source version of the product when prompted to.

OGIMIGE0015	**ERROR: Cannot identify version of product {0}. Cannot find this product in the list of locally installed products in the specified installation directory: {1}**
Explanation	The migration application attempted to identify the version of a locally installed product with the given product prop file name (without the .prop suffix), but such locally installed product was not found in the specified installation directory.
Action	Specify the source version of the product when prompted to.

OGIMIGE0018	**ERROR: Storing result properties configuration layout failed.**
Explanation	The property file with all the properties and their comments failed on the saving step.
Action	Check the file access permisions of your taget installation.

OGIMIGE0019	**ERROR: JAAS configuration {0} does not exist.**
Explanation	The JAAS configuration file is missing and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0020	**ERROR: JAAS configuration {0} is not a file.**
Explanation	The JAAS configuration file is not a valid file and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0021	**ERROR: Destination JAAS configuration {0} does not exist.**
Explanation	The JAAS configuration file is missing and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0022	**ERROR: Destination JAAS configuration {0} is not a file.**
Explanation	The destination JAAS configuration file is not a valid file and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0023	**ERROR: Backup failed for destination JAAS configuration file.**
Explanation	Creating a backup of the original file was not successful and it is unsafe for the migration to continue.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0024	**ERROR: Error parsing source JAAS configuration**
Explanation	An error is found in the source JAAS configuration and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0025	**ERROR: Error parsing destination JAAS configuration**
Explanation	Migration of the JAAS configuration was not successful. An error was found in the destination JAAS configuration and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0026	**ERROR: Error saving destination JAAS configuration.**
Explanation	An error occured while storing the migrated JAAS configuration and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0028	**ERROR: Source server.xml configuration {0} does not exist.**
Explanation	The server.xml file could not be migrated because the file does not exist.
Action	Check if the source server.xml file exists and is readable for the user.

OGIMIGE0029	**ERROR: Source server.xml configuration {0} is not a file.**
Explanation	The server.xml is not a proper file.
Action	Check the server.xml file.

OGIMIGE0030	**ERROR: Parsing server.xml file {0}.**
Explanation	The server.xml file is not a valid XML file.
Action	Check the server.xml file.

OGIMIGE0031	**ERROR: Reading server.xml file {0}.**
Explanation	The server.xml file could not be read properly.
Action	Check the server.xml file.

OGIMIGE0032	**ERROR: Parser Configuration server.xml file {0}.**
Explanation	Parser error occurs when parsing the server.xml file.
Action	Check the server.xml file.

OGIMIGE0033	**ERROR: Backup file {0}.**
Explanation	The file could not be backed up successfully.
Action	Check the source location and target location paths and files.

OGIMIGE0034	**ERROR: Reading file {0}.**
Explanation	The error occurs because the file could not be read properly.
Action	Check the source location and target location paths,files, and permissions.

OGIMIGE0035	**ERROR: Writing file {0}.**
Explanation	The error occurs because the file could not be written properly.
Action	Check the source location and target location paths,files, and permissions.

OGIMIGE0036	**ERROR: Create/Update file {0}.**
Explanation	The error occurs because the file could not be created or updated properly.
Action	Check the source location and target location paths,files, and permissions.

OGIMIGE0042	**ERROR: Configuration migration finished with failure(s).**
Explanation	Migration failed for the server.xml, web.xml, and config.xml, *.jks files.
Action	Check the detailed error messages displayed by the migration tool.

OGIMIGE0048	**ERROR: Cannot identify version of product {0}. The product installation under {1} does not contain any build modules for the current installer platform: {0}**
Explanation	The migration application attempted to identify the version of a locally installed product, but the local product is targeting a different installer platform (operating system and architecture) and the product information could not be loaded.
Action	Specify the source version of the product when prompted to.

OGIMIGE0049	**ERROR: Cannot parse version of product {0}. The product version of {1} does not have valid syntax. Expecting a version in the format <major>.<minor>.<micro>.<fixnum>.<buildnum>.**
Explanation	The migration application attempted to identify the source version of a locally installed product but the product version did not have the expected format.
Action	Specify the source version of the product when prompted to.

OGIMIGE0052	**ERROR: User repository file does not exist in the expected location: {0}**
Explanation	Migration for common/conf entries was not successful.The users.txt file was not found in the expected location.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0053	**ERROR: Error reading user repository file: {0}**
Explanation	Migration for common/conf entries was not successful. The users.txt file could not be read from the expected location.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0054	**ERROR: User repository file version cannot be retrieved: {0}**
Explanation	Migration for common/conf entries was not successful. The users.txt file was not migrated. An unexpected error occurred during the retrieval of the users.txt file version.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0055	**ERROR: User repository version is not compatible. Required minimal version is: {0}, found version is: {1}. Manual steps are required.**
Explanation	Migration for common/conf entries was not successful. The users.txt file cannot be migrated if the files in both locations are not with compatible versions.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0056	**ERROR: User repository version could not be retrieved: {0}**
Explanation	Migration for common/conf entries was not successful. An unexpected error occurred during the compatibility check of the users.txt file. The users.txt file must be migrated manually.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0058	**ERROR: Source user repository file does not exist: {0}**
Explanation	Migration for common/conf entries was not successful. The source user repository file users.txt cannot be found in the specified location.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0059	**ERROR: Destination user repository file does not exist: {0}**
Explanation	Migration for common/conf entries was not successful. The destination user repository file users.txt cannot be found in the specified location.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0060	**ERROR: Source user repository file could not be copied to destination.**
Explanation	Migration for common/conf entries was not successful. The source user repository file users.txt cannot be copied to destination due to an unexpected error.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0066	**ERROR: Missing source SSH configuration file {0}**
Explanation	Migration of the SSH configuration was not successful. The source file with the SSH configuration is not found and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0067	**ERROR: Error reading source SSH configuration file {0}**
Explanation	Migration of the SSH configuration was not successful. An error occurred while reading the source SSH configuration file and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0068	**ERROR: Missing destination SSH configuration file {0}**
Explanation	Migration for SSH configuration was not successful. The destination configuration file for the SSH configuration cannot be found and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0069	**ERROR: Error backing up destination SSH configuration file {0}**
Explanation	Migration of the SSH configuration was not successful. An error occurred while trying to backup the original destination SSH configuration file and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0071	**ERROR: Destination SSH config file not found {0}**
Explanation	Migration for the SSH configuration was not successful. The destination SSH config file was not found and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0072	**ERROR: Error storing migrated SSH configuration {0}**
Explanation	Migration of the SSH configuration was not successful. An error occurred while storing the migrated SSH configuration and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0073	**Invalid source installation directory specified: {0}. No {1} subdirectory is present, this directory is required for the {2} migration to proceed.**
Explanation	The migration application requires the specified product subdirectory to be available in the source installation in order to proceed, but the directory was not found. This can happen if the product, for which the migration is executed is not available in the source installation directory.
Action	Make sure that the specified source installation contains the product that is being migrated.

OGIMIGE0081	**In file {0} Keystore/Truststore file referenced from HTTPS Connector in attribute {1} that can not be found, creating a valid HTTPS configuration not possible.**
Explanation	The server.xml file contains a Keystore/Truststore configuration (keystoreFile= truststoreFile=), pointing to a file that cannot be found. Migrating this would lead in an unusable HTTPS configuration.
Action	In your profile check the file /tomcat/conf/server.xml and the properties keystoreFile="TheKeystoreFilename" truststoreFile="TheTrustStoreFileName". Also check that the file(s) TheKeystoreFilename/TheTrustStoreFileName are existing and valid keystore/truststore files or reference the delivered default one: keystoreFile="C:\SAG822\profiles\CTP\configuration\tomcat\conf\localhost_dont_use_in_production.jks" and start the migration again.

OGIMIGE0083	**ERROR: Backup file cannot be created - invalid value for destination file passed.**
Explanation	While trying to create a backup of the original file, an invalid original file was passed.
Action	Check the log for more details.

OGIMIGE0084	**Cannot identfy installer platform for specified installation directory: {0}. Reason: Cannot read installation metadata file: {1}**
Explanation	The migration application needs to verify that the source installation is created for the same operating system and architecture as the destination installation. This is done by inspecting the installation metadata located under install/products directory in the installation. If the installation metadata is missing or corrupt, or the process does not have read permissions for the specified file, the platform identification will fail and the migration cannot proceed.
Action	Make sure that the specified installation directory contains proper installation metadata (install/products directory containing installer property files for installed products) and the process has the correct privileges to read it.

OGIMIGE0086	**Failed to read file "{0}".**
Explanation	The platform migration utility could not read the specified file.
Action	Make sure the file exists and the user executing the migration is authorized to read it.

OGIMIGE0087	**Failed to close file stream "{0}".**
Explanation	An I/O error occurred while closing the file stream.
Action	Make sure the file exists and the user executing the migration is authorized to read it.

OGIMIGE0089	**An invalid path property "{0}" was found in file "{1}". Path should not be null or empty.**
Explanation	A path property sent for transformation has a null or empty value. Transformation cannot proceed with an invalid argument.
Action	Ensure that the property referenced in the given file has a valid path value.

OGIMIGE0092	**The path "{0}" is referenced in file "{1}"; it should be available as "{2}", but could not be found. Hence the path cannot be migrated.**
Explanation	The path transformer has discovered that a path referenced in a file in the source installation points to a file inside the source installation. The file does not exist and the configuration is invalid.
Action	Ensure that the path referenced in the specified file points to a valid file on the file system.

OGIMIGE0095	**The absolute path "{0}" referenced in file "{1}" does not exist on the file system.**
Explanation	The path transformer has discovered that a path referenced in a file in the source installation points to a file outside the source installation. The file does not exist and the configuration is invalid.
Action	Ensure that the path referenced in the specified file points to a valid file on the file system.

OGIMIGE0097	**Could not determine original installation location for "{0}".**
Explanation	The path transformer failed to determine the original source installation root directory, which is required in order for the transformer to function properly.
Action	Make sure the migration source directory contains a "profiles" folder with at least one valid profile inside.

OGIMIGE0098	**The original source directory "{0}" exists on this file system but the current migration is using "{1}" as a source. Path transformation is not supported.**
Explanation	Path transformer determined that the migration source directory is different from the original source installation root directory (which could be the case when you are migrating from a zip file or from a mapped/mounted directory). However, the original source installation root directory exists on this file system but it is not used as a migration source directory. This is not a supported path transformation scenario as the system may not reliably validate the transformed paths.
Action	If the original source installation directory is available on the same file system it should be used directly as a migration source directory.

OGIMIGE0099	**The target directory "{0}" must be the same as the installation root directory "{1}".**
Explanation	The target directory in the migrated profile config.ini file is different from the migration target directory. The target installation is corrupted.
Action	Make sure that the migration target directory is not moved or tampered with.

OGIMIGE0102	**Failed to copy transformed file path from "{0}" to "{1}".**
Explanation	Path transformer transformed a file path from the migration source directory to the migration target directory. The file copy operation failed.
Action	Make sure that the user executing the migration is able to physically copy the source file to the destination.

OGIMIGE0103	**An invalid URL property "{0}" was found in file "{1}". URL should not be null or empty.**
Explanation	A URL property sent for transformation has a null or empty value. Transformation cannot proceed with an invalid argument.
Action	Ensure that the property referenced in the given file has a valid URL value.

OGIMIGE0107	**Source installation directory ({0}) uses "{1}" platform, while destination installation directory ({2}) uses "{3}".**
Explanation	The migration cannot proceed if the source and destination installation platforms are different.
Action	Make sure the source and destination directories contain installations of one and the same platform.

OGIMIGE0111	**ERROR: copy file{0}.**
Explanation	Copy file operation failed.
Action	Make sure the file exists and is not used or opened by an application.

OGIMIGE0113	**Error occurred while merging the properties from '{0}' to '{1}'.**
Explanation	Merging the .properties files failed with an error.
Action	Check the logs for more information.

OGIMIGE0115	**ERROR: Error during finilization of the JAAS configuration.**
Explanation	An error occured while finilizing the migrated JAAS configuration and the migration could not proceed.
Action	Contact Software AG Global support.

OGIMIGE0116	**Abort migration due to errors while evaluating source installation {0}**
Explanation	Migration of roles.txt entries was not successful due to problems with the source SAG product installation.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0117	**Abort migration due to errors while evaluating destination installation {0}**
Explanation	Migration of roles.txt entries was not successful due to problems with the source SAG product installation.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0118	**Error while reading source 'roles.txt': {0}**
Explanation	Unexpected error occured while reading the 'roles.txt' file from the source SAG product installation.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0119	**Error while reading destination 'roles.txt': {0}**
Explanation	Unexpected error occured while reading the 'roles.txt' file from the destination SAG product installation.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0121	**Cannot backup {0}. Migration is not safe. Proceeding with next migration.**
Explanation	Cannot create backup copy of the 'roles.txt' file. Migration might be successful but if it fails the previous content of the 'roles.txt file can't be restored. Therefore, we skip the migration for this particular 'roles.txt' file.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0122	**Error while merging {0} and {1}**
Explanation	Unexpected error occured while merging the content of source and destination installation 'roles.txt' files. The current migration will be skipped and the original 'roles.txt' content will be restored.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0123	**'config.ini' doesn't exist or is not file: {0}**
Explanation	Cannot proceed with the migration since the required configuration file 'config.ini' doesn't exist.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0126	**Configuration location {0} doesn't exist or is not file.**
Explanation	The specified configuration location doesn't exist and therefore the migration process will be skipped.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0127	**Configuration location {0} does not exist.**
Explanation	The specified configuration location doesn't exist and therefore the migration process will be skipped.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0128	**Configuration location {0} is not a file.**
Explanation	The specified configuration location doesn't exist and therefore the migration process will be skipped.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0129	**Cannot create backup file: {0}**
Explanation	The migration is not able to create a backup file for the JAAS configuration.
Action	Check the source location and target location paths, files, and permissions.

OGIMIGE0130	**This is not a valid destination backup file location: null**
Explanation	Missing destination backup file location.
Action	Check the source location and target location paths, files, and permissions.

OGIMIGE0131	**The destination backup file location '{0}' does not exist**
Explanation	The destination backup file location does not exist.
Action	Check the source location and target location paths, files, and permissions.

OGIMIGE0134	**JKS '{0}' with file {1} is missing manadtory property for password from the configuration file.**
Explanation	If truststoreFile property is present in configuration there should be truststorePass property. The same rule applies for keystoreFile and keystorePass.
Action	Check the properties of HTTPS connectors.

OGIMIGE0135	**The backup of '{0}' failed.**
Explanation	The problem might be that the pointed file cannot be copied or deleted after backup.
Action	Check for permisions on the file.

OGIMIGE0136	**The migration of key/certificates from '{0}' to '{1}' failed.**
Explanation	The migration of certificates and\or keys is failing for the pointed Java Key Stores. The following keystores are migrated as a part of the HTTPS configuration migration.
Action	Check if property files are poinnting to the correct locations of trustore and keystore in the source installation. Check if password given in the configuration is correct. Check if the given configuration is actually operational.

OGIMIGI0133	**This login context is skipped by migration, because it contained SSX login module, but In version 10.x SSX is no longer available and migration is not possible**

OGIMIGW0005	**WARNING: File could not be deleted - {0}.**
Explanation	An error occured while deleting incompatible destination file. This is a warning message because deleting this file should not be crucial for the finctionality of the application.
Action	Delete this file manually as it may cause future conflicts.

OGIMIGW0008	**WARNING: Referenced file was found in the source installation but was not found in the destination installation: "{0}" . Check if the file was migrated and if not migrate it manually.**
Explanation	Configurations could have properties with values that contain paths to files. During migration these paths could become invalid. To prevent the migration of such paths that make the configurations unusable, a check is done if the file exists in the new installation. This warning shows that the file was successfully located in the source installation, but was missing from the destination.
Action	Check if the path from the configuration is valid after the migration. If the path is not valid, migrate the file manually and edit the path if needed.

OGIMIGW0009	**WARNING: Referenced file was not found in the destination system: "{0}"**
Explanation	Configurations could have properties with values that contain paths to files. During migration these paths could become unvalid. To prevent the migration of such paths that make the configurations unusable, a check is done if the file exists in the new installation.
Action	Check if the path from the configuration is valid after the migration.If the path is not valid, migrate the file manually and edit the path if needed.

OGIMIGW0011	**WARNING: Property value could not be transformed properly.**
Explanation	When a migration is done, some properties require special transformation for their values. For this reason special transformer classes are used. This message is shown when there is a problem with finding the class, the class could not be instantiated or the class is not a valid Transformer class. This could lead to invalid property values.
Action	Check the value of the migrated property.

OGIMIGW0012	**WARNING: Installer client jar not available, falling back on custom installer metadata parser.**
Explanation	Migration framework did not find a required jar for reading the installation metadata, it will attempt to read the metadata by parsing the prop file instead.
Action	No action is required.

OGIMIGW0016	**WARNING: Properties for transformation were not loaded.This might make your configuration unusable.**
Explanation	We are using special files that map properties which need some kind of transformation for their value or key. In order to use them we have to load them from a file. This step has failed.
Action	Contact Software AG global support.

OGIMIGW0017	**WARNING: Transformer class was not found for the following property:**
Explanation	We allow custom property transformation which is done via a class. The loading of this class has failed. One or more properties were not transformed correctly.
Action	Contact Software AG global support.

OGIMIGW0027	**WARNING: Some runtime componets were not enabled in the source configuration - {0}. Migration exits successfully.**
Explanation	Some runtime componets like JMX, SSH are not enabled in the source configuration. The migartion will not migrate any data from these source configurations.
Action	If you want to disable the component explicitly please do so by changing the port property in the connector in the destination installation.

OGIMIGW0037	**WARNING: Error on read file {0}.**
Explanation	The error occurs because the file could not be read properly.
Action	Check the source location and target location paths,files, and permissions.

OGIMIGW0038	**WARNING: Error on write file {0}.**
Explanation	The error occurs because the file could not be written properly.
Action	Check the source location and target location paths,files, and permissions.

OGIMIGW0051	**WARNING: Using the default 'localhost_dont_use_in_production.jks' file in file {0} property name {1}, because the file referenced in the older version could not be found. Change the file specified in the property.**
Explanation	The specified property in the specified properties file points to the default .jks keystore file, because the keystore file referenced in the older version could not be found.
Action	Change the property to point to a valid existing production .jks keystore file.

OGIMIGW0065	**WARNING: SSH port is not set in source configuration {0}. Migration exits successfully.**
Explanation	SSH port is not set in source configuration so there is nothing to migrate.
Action	SSH port is not set in configuration and nothing is done. If this is not the case, refer to the upgrade documentation and execute the required manual steps.

OGIMIGW0104	**Value for JAAS configuration in config.ini could not be processed.**
Explanation	The JAAS configuration modifications will be made to the original JAAS configuration located in the profile folder.
Action	Define an absolute path to the current location of the JAAS configuration to be migrated or move it in the profile configuration folder.

OGIMIGW0108	**WARNING: source internal user repository file users.txt not present : "{0}" Skip the migration of users.txt; groups.txt, roles.txt.**
Explanation	The users.txt internal user repository file is not present in common/conf directory. The file(s) could not be migrated.
Action	Check the profiles/TheProfile/configuration/jaas.config for the following entry: internalRepository="ADirectory/users.txt"and check if this is migrated by the jaas config migration. Do the same for the groups.txt and roles.txt files. If there is no such entry, a migration of that file is not nesecessary, because no internal user repository for authentication is enabled or configured.

OGIMIGW0112	**WARNING: security configuration source file scPassMan.config.xml missing. File is mandatory! Skipping migration of all passman files.**
Explanation	Passman security configuration files are normally 3 files : scPassMan.config.xml ; defaultPassStore.dat and mpw.dat . The .dat files are optional, but the .xml is important and without it migration cannot be done.
Action	Check whether the scPassMan.config.xml file is present in the following location: installdir/profiles/TheProfile/configuration/security. With the xml file present, retry migration or migrate manually.

OGIMIGW0132	**Found SSX login module {2} in source {0}. SSX is removed in 10.0, so login context {1} will not be migrated.**
Explanation	SSX login module is found in source installation, but SSX is removed in version 10.0, so we can't migrate it properly
Action	Migrate login context by hand as it is not possible not migrate it automatically.

22 Platform Manager Messages

SPMADME0000	**Administration SPI for "{0}" and namespace "{1}" not found.**
Explanation	The Administration SPI for the specified entity and namespace should be registered beforehand.
Action	Check if the correct entity ID and namespace are provided or if the product plug-in is available.

SPMADME0001	**Error while invoking "{0}" Administration function with arguments "{2},{3}" of "{1}" and namespace "{4}".**
Explanation	The specified administration function is either not available, the arguments used to invoke the function are incorrect, or unchecked exception has been thrown.
Action	Check the functions supported by the Administration SPI.

SPMADME0002	**Administration function "{0}" with arguments "{2},{3}" of "{1}" and namespace "{4}" not found.**
Explanation	The specified administration function is not defined for the entity with the specified arguments.
Action	Check the functions supported by the Administration SPI.

SPMADME0003	**{0} process finished with error code {1}. Requested command: {2} Output: {3}**
Explanation	The requested command could not be executed successfully.
Action	Check the upgrade and migration help for the product.

SPMCCPEMIE0001	**An error occurred during a call to wm.monitor.util:configSettings. The error reported is: {0}.**
Explanation	An error occurred during the service call to write the configuration settings to WmMonitor. A probable cause for the error is failing to access the IntegrationServer\packages\WmMonitor\config\monitor.cnf file. The error could also occur when the monitor.cnf file is not present initially and the service call to write the configuration settings creates and populates the file with default values.
Action	Ensure that the IntegrationServer\packages\WmMonitor\config\monitor.cnf file is present, contains name=value pairs, and the name=value pairs are valid. Also, ensure that the name-value pairs are acceptable for your configuration.

SPMCCPEMIE0002	**Only BASIC authentication is supported.**
Explanation	The specified authentication is not supported.
Action	Change authentication to BASIC.

SPMCCPEMIE0003	**The My webMethods Server URL is not valid.**
Explanation	The URL for pinging My webMethods Server is not valid.
Action	Check that your WmMonitor configuration values for host, port, username and password are valid.

SPMCCPEMIE0009	**No My webMethods Server credentials were provided.**
Explanation	The connection to My webMethods Server cannot be validated without proper credentials.
Action	Specify values for username and password.

SPMCCPEMIE0014	**The My webMethods Server host, port, and/or connection protocol were not provided.**
Explanation	You must specify values for the My webMethods Server host, port, and connection protocol.
Action	Specify values for host, port, and connection protocol.

SPMCCPEMIE0015	**The values are required.**
Explanation	You must specify values in the fields.
Action	Specify values for these fields.

SPMCCPEMIW0000 **My webMethods Server password was not provided.**

Explanation The password is a required field.

Action Provide a password for My webMethods Server.

SPMCCPEMIW0004 **The My webMethods Server URL is not accessible. Click Show Details for more information.**

Explanation The URL for pinging My webMethods Server is not accessible.

Action Check that your WmMonitor configuration values for host, port, username and password are valid, and also confirm that My webMethods Server is reachable on the network.

SPMCCPEMIW0005 **My webMethods Server credentials are not valid.**

Explanation The username or password are incorrect.

Action Check that the username and password are correct.

SPMCCPEMIW0011 **The password is required.**

Explanation You must specify a password.

Action Specify a password.

SPMCCPEMIW0012 **No value was provided for 'Data Level Security Administrator'**

Explanation A value for the Data Level Security, DLS, super user was not provided.

Action No action is required if the default value of \'Administrator\' is acceptable.

SPMCCPEMIW0013 **A default value of 'Administrator' was provided; it will be displayed upon Save.**

Explanation Because no value was provided for the Data Level Security super user, the default value of \'Administrator\' is used.

Action Set a value for Data Level Security Administrator.

SPMCFCE0012 **Properties serializer supports only instances of java.util.Properties**

Explanation The user is trying to use a Properties serializer on an inapropriate object type.

Action Use proper serializer for your object.

SPMCFCE0023	**There is no registered ConfigurationSerializer under runtimeComponentId {0} and configurationTypeId {1}**
Explanation	No registered ConfigurationSerializer exists under the entered runtimeComponentId and configurationTypeId.
Action	Register a ConfigurationSerializer under the entered runtimeComponentId and configurationTypeId.

SPMCFCE0026	**ConfigurationManager should be registered with the runtimeComponentId and configurationTypeId properties.**
Explanation	ConfigurationManager should be registered with the runtimeComponentId and configurationTypeId properties. They cannot be null.
Action	Register ConfigurationManager and set values for the runtimeComponentId and configurationTypeId properties.

SPMCFCE0030	**Error ocurred during serialization/deserialization.**
Explanation	Error ocurred during serialization/deserialization.
Action	Check for user permissions and hardware failures and try again.

SPMCFCE0049	**Configuration is not available for this component.**
Explanation	The component requires a configuration to function properly.
Action	Set the configuration for this component.

SPMCFCI0000	**Port Settings**
Explanation	PortSettingsConfigurationType Display Name
Action	None.

SPMCFCI0001	**Listener ports configuration**
Explanation	PortSettingsConfigurationType description.
Action	None.

SPMCFCI0019	**The keystore truststore settings cannot be null.**
Explanation	The keystore truststore settings cannot be set to null.
Action	Provide a valid keystore truststore setting.

SPMCFCI0028	**There can be only one primary pool defined in the JDBC configuration.**
Explanation	There can be only one primary pool defined in the JDBC configuration.
Action	Specify only one pool with the primary as true.

SPMCFCI0080	**Configuration Type Metadata**
Explanation	Metadata describing specific configuration type

SPMCFGE0000	**The configuration type argument is not set.**
Explanation	The configuration type argument is not set.
Action	Set the configuration type argument.

SPMCFGE0001	**Configuration type {0} cannot be found.**
Explanation	A Configuration Manager that can handle configuration type {0} cannot be found.
Action	Make sure that configuration type {0} is supported, for example check if there is a Configuration Manager registered for it.

SPMCFGE0002	**A Configuration instance with ID = {0} does not exist.**
Explanation	A Configuration instance with the provided ID does not exist.
Action	Use the ID of an existing Configuration instance.

SPMCFGE0003	**Loaded configuration cannot be null.**
Explanation	The requested configuration cannot be null.
Action	Provide valid runtimeComponent, configurationInstance, and configurationStatus.

SPMCFGE0004	**The Configuration Manager Service is not set.**
Explanation	The Configuration Manager Service is not set.
Action	Set the Configuration Manager Service.

SPMCFGE0005	**The component ID or configurationType ID is wrong.**
Explanation	The component ID or configurationType argument ID is wrong.
Action	Use an appropriate component ID or configurationType ID.

SPMCFGE0006	**Configuration is not available for this component.**
Explanation	This component needs configuration in order to function.
Action	Set the configuration for this component.

SPMCFGE0007	**ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .**
Explanation	Platform Manager did not find registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
Action	Register ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.

SPMCFGE0008	**Id cannot be null.**
Explanation	When creating a configuration instance, the id argument cannot be null.
Action	Provide a non-null id argument.

SPMCFGE0009	**ConfigurationTypeId cannot be null.**
Explanation	When creating a configuration instance, the ConfigurationTypeId argument cannot be null.
Action	Provide a non-null id argument.

SPMCFGE0010	**DisplayName cannot be null.**
Explanation	When creating a configuration instance, the displayName argument cannot be null.
Action	Provide a non-null id argument.

SPMCFGE0011	**The component to be updated is null.**
Explanation	The runtime component to be updated cannot be null.
Action	Provide a non-null runtime component.

SPMCFGE0012	**Protocol value cannot be changed.**
Explanation	The protocol value for an existing port configuration cannot be changed.
Action	Retry the operation without changing the protocol.

SPMCFGE0013 **Create command is not supported.**

Explanation Create configuration command is not supported by this configuration manager.

Action Check the logs.

SPMCFGE0020 **ConfigurationService is not set.**

Explanation ConfigurationService is not set.

Action Register a ConfigurationService.

SPMCFGE0021 **New configuration is null.**

Explanation The configuration sent for validation is null.

Action Send a valid configuration that is not null.

SPMCFGE0022 **Delete command is not supported**

Explanation Delete configuration command is not supported by this configuration manager.

Action Check the logs.

SPMCFGE0023 **The new configuration to be validated can not be null.**

Explanation The new configuration to be validated can not be null.

Action Send a valid configuration that is not null for validation.

SPMCFGE0024 **Duplicate truststore aliases in the existing instances.**

Explanation Duplicate truststore aliases are present in the existing instances.

Action Use a unique truststore alias.

SPMCFGE0025 **Duplicate truststore aliases are present in the existing instances.**

Explanation Duplicate truststore aliases are present in the existing instances.

Action Use a unique truststore alias.

SPMCFGE0026 **Duplicate keystore aliases in existing instances.**

Explanation Duplicate keystore alias is present in the existing instances.

Action Use a unique keystore alias.

SPMCFGE0027	**Duplicate keystore alias is present in existing instances.**
Explanation	Duplicate keystore alias is present in the existing instances.
Action	Use a unique keystore alias.

SPMCFGE0028	**The file location provided in the keystore could not be found.**
Explanation	The file location provided in the keystore could not be found.
Action	The file location provided in the keystore configuration must point to an existing file. Use an existing file location.

SPMCFGE0040	**The keystore location information is missing.**
Explanation	The keystore location information is missing in the new configuration.
Action	Use a valid keystore location that points to an existing file.

SPMCFGE0041	**The keystore location information is either null or empty. It should point to an existing file.**
Explanation	The keystore location information is either null or empty. It should point to an existing file.
Action	The keystore location should point to an existing file.

SPMCFGE0042	**An exception occurred when trying to get the existing aliases.**
Explanation	The PlatformManagerException exception occured when trying to get the existing aliases.
Action	You need to correct the existing configuration instances with valid aliases.

SPMCFGE0043	**An exception occurred when trying to get the existing aliases.**
Explanation	The IOException exception occurred when trying to get the existing aliases.
Action	Provide a valid runtime ID and configuration type ID to the validator.

SPMCFGE0049	**Configuration of type Common-JDBC is null.**
Explanation	Configuration object for Common-JDBC is null.
Action	Specify the valid configuration object for Common-JDBC.

SPMCFGE0051	**Duplicate alias for Jdbc Pool is found.**
Explanation	Alias for Jdbc Pool is not unique. This is not a valid configuration.
Action	Specify a unique Jdbc Pool alias.

SPMCFGE0053	**There can be only one pool with primary as true.**
Explanation	There is more than one pool defined as primary. This is not valid.
Action	Specify only one pool with primary as true.

SPMCFGE0055	**JDBC Pool information is not available. Specify valid JDBC Pool Settings.**
Explanation	JDBC Pool information is not available in the JDBC Settings Configuration Object. This is not valid.
Action	Specify valid JDBC Pool Settings.

SPMCFGE0058	**An exception occurred when trying to get the existing aliases.**
Explanation	The PlatformManagerException exception occured when trying to get the existing aliases.
Action	You need to correct the existing configuration instances with valid JDBC pool aliases.

SPMCFGE0059	**The JDBC connection failed.**
Explanation	The JDBC connection failed because it was invalid.
Action	Specify valid JDBC connection data.

SPMCFGE0060	**Failed to close a valid JDBC connection.**
Explanation	Failed to close a valid JDBC connection.
Action	Contact your system administrator.

SPMCFGE0061	**Password verification failed.**
Explanation	The password provided to load the certificate is incorrect.
Action	You need to provide a valid password and try again.

SPMCFGE0065	**Configuration Instance "{0}" does not exist.**
Explanation	Configuration Instances should be backed up by existing source.
Action	Make sure this particular Configuration Instance is declared correctly.

SPMCFGE0066	**Configuration Instance "{0}" is not a valid URL.**
Explanation	Configuration Instance "{0}" should be backed up by valid URL source.
Action	Make sure this particular Configuration Instance is declared correctly.

SPMCFGE0067	**Unknown property name "{0}".**
Explanation	The property is not recognized.
Action	Make sure this particular Configuration Instance is declared correctly.

SPMCFGE0068	**The specified port number is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.**
Explanation	The specified port number is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.
Action	Specify a different port number or shut down the component that is running on this port.

SPMCFGE0071	**The value {0} cannot be used. A non-negative number is expected.**
Explanation	The specified value must not be a negative number.
Action	Specify a non-negative number.

SPMCFGE0073	**The value of the Threadpool Min parameter cannot be equal to or more than the value for the Threadpool Max parameter.**
Explanation	The value of the Threadpool Min parameter cannot be equal to or more than the value of the Threadpool Max parameter.
Action	Change the configuration to make the value of the Threadpool Max parameter more than the value of the Threadpool Min parameter.

SPMCFGE0078	**The configuration contains duplicate log file name entries.**
Explanation	Duplicate log file names exist in the log configuration appendices.
Action	Make sure each log file name in the log configuration is unique.

SPMCFGE0079	**Log file name {0} already exists.**
Explanation	The specified log file name exists in another runtime component's log configuration.
Action	Make sure each file name is unique across runtime components.

SPMCFGE0080	**Not enough disk space.**
Explanation	The disk partition free space is less that 10Mb.
Action	Make sure the disk partition has enough free space.

SPMCFGE0081	**The user does not have privileges to perform file operations. Check the current security policy.**
Explanation	The user performing the file operation does not have the proper privileges necessary to create or write to a log file.
Action	Make sure the user has adequate privileges to perform the operation.

SPMCFGE0082	**Error creating temp file in {0}. Make sure the specified directory is valid.**
Explanation	The log configuration validation failed because the specified log directory is not valid or does not exist.
Action	Make sure the specified log directory is valid.

SPMCFGE0084	**The "from" or "to" email address is not correct.**
Explanation	In Platform Manager, during validation of sending a test email, if the "from" or "to" email address is not correct, this error is thrown.
Action	Ensure that the "from" or "to" email address is correct, and try again.

SPMCFGE0086	**Not able to connect to the SMTP server {0}.**
Explanation	In Platform Manager, the socket connection is not able to connect to the SMTP server with the given credentials.
Action	Ensure the server is running and the specified credentials are correct.

SPMCFGE0088	**Unable to send a test mail to the recipient {1} using the SMTP server {0}.**
Explanation	In Platform Manager, an error occurs when sending an email to the recipient.
Action	The email ID is non-existent. Enter a valid email ID and try again.

SPMCFGE0090	**An exception occurred when trying to get the existing aliases.**
Explanation	The IOException exception occurred when trying to get the existing aliases.
Action	Provide a valid runtime ID and configuration type ID to the validator.

SPMCFGE0091	**An exception occurred when trying to get the existing JDBC pools defined as primary.**
Explanation	The PlatformManagerException exception occured when trying to get the existing JDBC pools defined as primary.
Action	You need to correct the existing configuration instances with only one JDBC pool as primary.

SPMCFGE0092	**An exception occurred when trying to get the existing JDBC pools defined as primary.**
Explanation	The IOException exception occurred when trying to get the existing JDBC pools defined as primary.
Action	Provide a valid runtime ID and configuration type ID to the validator.

SPMCFGE0093	**No value was specified for the Protocol parameter.**
Explanation	No value was specified for the Protocol parameter.
Action	Specify a value for the Protocol parameter.

SPMCFGE0094	**The keystore truststore setting is empty.**
Explanation	The keystore truststore setting does not contain any fields.
Action	Provide either the keystore, truststore or extended properties.

SPMCFGE0095	**The keystore truststore setting does not contain any element.**
Explanation	The keystore truststore setting should either have the keystore, the truststore, or the extended properties, which is missing.
Action	Add the keystore, the truststore, or the extended properties to the keystore truststore setting.

SPMCFGE0096	**There can be only one primary pool defined in the JDBC configuration.**
Explanation	There can be only one primary pool defined in the JDBC configuration.
Action	Specify only one pool with the primary as true.

SPMCFGE0097	**The JDBC Pool name is not unique.**
Explanation	The JDBC Pool name is not unique.
Action	Specify a unique JDBC Pool name.

SPMCFGE0098	**The JDBC driver class should not be null when the database server type is Custom.**
Explanation	The JDBC driver class should not be null when the database server type is Custom.
Action	Specify the JDBC Driver class if the database server type is Custom.

SPMCFGE0099	**The database server host should not be null when the database server type is non-custom and the URL is not specified.**
Explanation	The database server host should not be null when the database server type is non-custom and the URL is not specified.
Action	Specify the hostname for the database server when the server type is non-custom and the database URL is not specified.

SPMCFGE0100	**The database server port number should not be null when the database server type is non-custom and the URL is not specified.**
Explanation	The database server port number should not be null when the database server type is non-custom and the URL is not specified.
Action	Specify the port number for the database server when the server type is non-custom and the database URL is not specified.

SPMCFGE0101	**The database server SID should not be null when the database server type is Oracle and the URL is not specified.**
Explanation	The database server SID should not be null when the database server type is Oracle and the URL is not specified.
Action	Specify the Oracle SID when the database server type is Oracle and the database URL is not specified.

SPMCFGE0102	**The database server's database name should not be null when the database server type is non-Oracle and the URL is not specified.**
Explanation	The database server's database name should not be null when the database server type is non-Oracle and the URL is not specified.
Action	Specify the database name when the database server type is non-Oracle and the URL is not specified.

SPMCFGE0103	**An error occured while getting either the runtime components or configuration instances using the configuration or inventory service.**
Explanation	An error occured while getting either the runtime components or configuration instances using the configuration or inventory service.
Action	Retry the action.

SPMCFGE0105	**Configuration instance and its configuration manager must have the same configuration type.**
Explanation	Configuration instance and its configuration manager must have the same configuration type.
Action	Check the type of the provided configuration instance.

SPMCFGE0106	**Not able to connect to the SMTP server(s) {0} with the given credentials and also not able to send a test mail to the recipient using the SMTP server(s) {1}.**
Explanation	In Platform Manager, the socket connection is not able to connect to the SMTP server with the given credentials (if provided). Also, a test mail to the recipient using the SMTP server is also not sent.
Action	Ensure the server is running and the server credentials entered are correct. Also, enter the correct email address and try again.

SPMCFGE0109	**The license file can not be empty.**
Explanation	In Platform Manager, when an empty license file is uploaded, this message is seen.
Action	You need to ensure to upload a license file that is not empty.

SPMCFGE0110	**The truststore location information is missing.**
Explanation	The truststore location information is missing in the new configuration.
Action	Use a valid truststore location that points to an existing file.

SPMCFGE0111	**The truststore location information is either null or empty. It should point to an existing file.**
Explanation	The truststore location information is either null or empty. It should point to an existing file.
Action	The truststore location should point to an existing file.

SPMCFGE0112	**The specified port is already bound by configuration instance {0} of runtime {1} and is enabled.**
Explanation	The specified port is already bound by configuration instance {0} of runtime {1} and is enabled.
Action	Change the port number and retry.

SPMCFGE0114	**The specified Bind Address value of {0} is invalid.**
Explanation	The value of {0} is invalid for Bind Address.
Action	Specify a valid bind address and retry.

SPMCFGE0115	**The specified port {0} is already in use by another configuration instance.**
Explanation	The specified port {0} is already in use by configuration instance {1} of runtime {2}.
Action	Change the port number and retry.

SPMCFGE0117	**The specified port number {0} is already in use.**
Explanation	The specified port number {0} is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.
Action	Specify a different port number or shut down the component that is running on this port.

SPMCFGE0120	**License file location is not specified in License Location Manager.**
Explanation	The location of the license file is not specified in the License Location Manager.
Action	Specify a valid license file location in License Location Manger before loading the License instance.

SPMCFGE0121	**The configured license is not valid for this product : {0}**
Explanation	The product code in the license file does not match with the product installed.
Action	Contact your system administrator or Software AG Global Support.

SPMCFGE0122	**The configured license is not valid for this version : {0}**
Explanation	The product version in the license file does not match with the product installed version.
Action	Contact your system administrator or Software AG Support.

SPMCFGE0125	**The provided port alias {0} already exists.**
Explanation	The provided port alias {0} already exists for this runtime component.
Action	Provide a unique port alias for the runtime component.

SPMCFGE0126	**The specified port alias {0} differs from the existing port alias {1}**
Explanation	The specified port alias {0} differs from the existing port alias {1}
Action	Do not change the port alias when you execute an update operation.

SPMCFGE0127	**The JDBC Pool alias cannot be changed once it is created.**
Explanation	While updating a JDBC Pool, the alias was modified. The alias for the JDBC Pool must not change after creating the pool.
Action	Specify the same JDBC Pool alias in the request, or remove it.

SPMCFGE0128	**Configuration of type COMMON-JNDI is null.**
Explanation	The configuration object for COMMON-JNDI is null.
Action	Specify the valid configuration object for COMMON-JNDI.

SPMCFGE0129	**Configuration of type COMMON-JNDI should have one JNDI element.**
Explanation	A configuration of type COMMON-JNDI should have one JNDI element.
Action	Provide one JNDI element for this configuration.

SPMCFGE0130	**Configuration of type COMMON-JNDI should have JNDI element with valid alias.**
Explanation	A configuration of type COMMON-JNDI should have a JNDI element with a valid alias.
Action	Provide URL friendly alias for the JNDI element.

SPMCFGE0131	**Configuration of type COMMON-JNDI should have JNDI element with unique alias.**
Explanation	A configuration of type COMMON-JNDI should have a JNDI element with a unique alias.
Action	Provide a unique alias for the JNDI element.

SPMCFGE0132	**Error occurred while retrieving the JNDI configuration instances.**
Explanation	An error occurred while retrieving the JNDI configuration instances.
Action	See the Platform Manager logs for mode details.

SPMCFGE0133	**Provide a URL for the specified JNDI provider type.**
Explanation	The URL for the specified JNDI provider type is missing.
Action	Specify the URL for the specified JNDI provider type.

SPMCFGE0134	**Provide Initial Context Factory for the specified JNDI provider type.**
Explanation	The specified JNDI provider type does not have an Initial Context Factory.
Action	Specify the Initial Context Factory for the specified JNDI provider type.

SPMCFGE0135	**DbFunctional alias was not found.**
Explanation	A DbFunctional alias with the specified alias value could not be found.
Action	Check if a DbFunctional alias with the provided alias value is available.

SPMCFGE0136	**Element value is not set.**
Explanation	The value of an integral element has not been set.
Action	Ensure that the specified data contains valid values for all required elements.

SPMCFGE0137	**Invalid DbFunctional alias.**
Explanation	The provided DbFunctional alias is invalid.
Action	Check the provided DbFunctional alias for invalid characters.

SPMCFGE0138	**Duplicate DbFunctional alias.**
Explanation	The provided alias already exists.
Action	Provide a new alias.

SPMCFGE0139	**Invalid Pool alias.**
Explanation	The provided Pool alias is invalid.
Action	Provide a new Pool alias.

SPMCFGE0140	**Problem detected while trying to read/write DbFunctional alias data.**
Explanation	The read/write operation failed.
Action	Check if the DbFunctional alias data file is available.

SPMCFGE0141	**Configuration of type COMMON-JMS should have JMS element with valid alias.**
Explanation	A configuration of type COMMON-JMS should have a JMS element with a valid alias.
Action	Specify a URL friendly alias for the JMS element.

SPMCFGE0142	**Configuration of type COMMON-JMS is null.**
Explanation	Configuration object for COMMON-JMS is null.
Action	Specify the valid configuration object for COMMON-JMS.

SPMCFGE0143	**Configuration of type COMMON-JMS should have a JMS element.**
Explanation	A configuration of type COMMON-JMS should have a JMS element.
Action	Specify a JMS element for this configuration.

SPMCFGE0144	**Provide URL for the specified JMS provider type.**
Explanation	The URL for the specified JMS provider type is missing.
Action	Provide a URL for the specified JMS provider type.

SPMCFGE0145	**Provide an existing JNDI alias for the specified JMS provider type.**
Explanation	The JNDI alias provided for the specified JMS provider type does not exist.
Action	Provide an existing JNDI alias for the specified JMS provider type.

SPMCFGE0146	**The provided JNDI alias does not exist. Provide an existing JNDI alias for the specified JMS provider type.**
Explanation	The JNDI alias provided for the specified JMS provider type does not exist.
Action	Provide an existing JNDI alias for the specified JMS provider type.

SPMCFGE0147	**Configuration of type COMMON-JMS should have JMS element with unique alias.**
Explanation	A configuration of type COMMON-JMS should have a JMS element with a unique alias.
Action	Provide unique alias for the JMS element.

SPMCFGE0148	**Error occurred while retrieving the JMS configuration instances.**
Explanation	An error occurred while retrieving the JMS configuration instances.
Action	See the Platform Manager logs for mode details.

SPMCFGE0149	**ConfigurationUiBindingService is not set.**
Explanation	The ConfigurationUiBindingService is not set.
Action	Register the ConfigurationUiBindingService.

SPMCFGE0150	**Configuration ui binding for {0} runtimeComponent and {1} configurationType cannot be retrieved.**
Explanation	The configuration user interface binding cannot be retrieved because of incorrect search parameters or incorrect SPI implementation.
Action	Provide a valid runtimeComponent ID and configurationType ID or check the SPI implementation.

SPMCFGE0151	**Error occured while trying to unmarshal ui binding XML data.**
Explanation	An error occured while trying to unmarhall the user interface binding XML data.
Action	Check if the XML file is well-formed and valid.

SPMCFGE0152	**Error occurred while trying to parse XSD Schema.**
Explanation	An error occurred while trying to parse the XSD Schema.
Action	Check if the XSD schema is valid.

SPMCFGE0153	**Client group for webMethods Messaging alias is invalid or not specified.**
Explanation	While configuring webMethods Messaging alias, if provider type is Broker, Client Group cannot be empty.
Action	Provide a valid Client Group while configuring webMethods Messaging alias.

SPMCFGE0154	**Broker messaging alias must have valid authentication configuration.**
Explanation	If the webMethods Messaging alias provider is Broker, you must specify valid authentication configuration.
Action	Provide a valid authentication while configuring webMethods Messaging alias.

SPMCFGE0155	**Broker Messaging alias must have a valid user.**
Explanation	While configuring webMethods Messaging alias, if provider type is Broker, you must specify a valid user.
Action	Provide a valid user while configuring webMethods Messaging alias.

SPMCFGE0156	**Broker Messaging alias must have a valid password.**
Explanation	When the messaging alias provider is Broker, the alias should have a valid password.
Action	Provide a valid password for a messaging alias with provider type Broker.

SPMCFGE0157	**Broker Messaging alias must have a valid keystore definition.**
Explanation	When the messaging alias provider is Broker, it should have valid keystore definition.
Action	Provide a valid keystore for a messaging alias with provider type Broker.

SPMCFGE0158	**Broker Messaging alias must have a valid encryption definition.**
Explanation	When the messaging alias provider is Broker, the alias should have a valid encryption definition.
Action	Provide a valid encryption definition for a messaging alias with provider type Broker.

SPMCFGE0159	**Specify at least one server log facility to be updated.**
Explanation	When updating the server logger, you must specify at least one server log facility.
Action	Ensure that you specify a server log facility.

SPMCFGE0160	**While updating a global variable, you can modify only the value for the global variable.**
Explanation	You attempted to modify the key while updating a global variable. You can modify only the value for the global variable.
Action	Ensure that you modify only the value for the global variable.

SPMCFGE0161	**Configuration of type COMMON-LOCAL-USERS should have User element with a valid id.**
Explanation	The User element should have an ID that contains only URL friendly symbols.
Action	Provide URL friendly ID for the User element.

SPMCFGE0162	**Configuration of type COMMON-LOCAL-USERS should have one User instance.**
Explanation	Configuration of type COMMON-LOCAL-USERS should have one User instance.
Action	Provide one User element for this configuration.

SPMCFGE0163	**Configuration of type COMMON-LOCAL-USERS should have User element with unique id.**
Explanation	The ID should be unique among all configurations of type COMMON-LOCAL-USERS.
Action	Provide a unique ID for the User element.

SPMCFGE0164	**Retrieving COMMON-LOCAL-USERS configuration instances failed.**
Explanation	An error occurred while retrieving the configuration instances of type COMMON-LOCAL-USERS.
Action	Check the error logs for more information.

SPMCFGE0165	**Configuration of type COMMON-LOCAL-USERS should have password.**
Explanation	A password is required for the User element, but it is missing.
Action	Provide a password for the User.

SPMCFGE0166	**The User element id for existing configuration of type COMMON-LOCAL-USERS cannot be updated.**
Explanation	User ID cannot be changed on update operation.
Action	Use the the same User ID from the existing configuration.

SPMCFGE0167	**Configuration of type COMMON-CLUSTER is null.**
Explanation	The configuration object for COMMON-CLUSTER is null.
Action	Specify the valid configuration object for COMMON-CLUSTER.

SPMCFGE0168	**The provided server name should be unique within the landscape.**
Explanation	The provided server name already exists in the landscape.
Action	Provide a server name that is unique within the landscape.

SPMCFGE0169	**Error occurred while retrieving the COMMON-CLUSTER configuration instances.**
Explanation	An error occurred while retrieving the COMMON-CLUSTER configuration instances.
Action	See the Platform Manager logs for mode details.

SPMCFGE0170	**Path to the internal user repository file cannot be found.**
Explanation	File {0} does not exist.
Action	Specify a valid path to the user.txt file relative to profile or product suite directories.

SPMCFGE0171	**User does not exist.**
Explanation	User with id {0} is not found in the User repository file.
Action	Try to refresh the configuration metadata.

SPMCFGE0172	**One of the existing servers has changed name.**
Explanation	One of the existing servers has a changed name.
Action	The names of existing servers should not change.

SPMCFGE0173	**Invalid value of Init Size.**
Explanation	Only positive integers are allowed.
Action	Provide Init Size greater than zero.

SPMCFGE0174	**Path to users.txt not specified.**
Explanation	The path to the users.txt file is not specified in the component XML data.
Action	Specify a property named "usersRepoPath" with a value relative to profile or Software AG installation directories.

SPMCFGE0175	**Missing or invalid ProxyServer alias.**
Explanation	The ProxyServer alias is missing or invalid.
Action	Provide a valid ProxyServer alias.

SPMCFGE0176	**Protocol or Host value is not set.**
Explanation	The value of a required element (Host or Protocol) has not been set.
Action	Ensure that the specified data contains valid values for Host and Protocol.

SPMCFGE0177 **Duplicate ProxyServer alias.**

Explanation The provided alias already exists.

Action Provide a new alias.

SPMCFGE0178 **Invalid Protocol value.**

Explanation The provided Protocol value is invalid.

Action Provide a valid Protocol value.

SPMCFGE0179 **Invalid Host value.**

Explanation The provided Host value is invalid.

Action Provide a valid Host value.

SPMCFGE0180 **Problem detected while trying to read/write Proxy data.**

Explanation The read/write operation failed.

Action Check if the Proxy data file is available.

SPMCFGE0181 **Invalid value of Max Size.**

Explanation Only positive integers greater than Init Size are allowed.

Action Provide Max Size greater than zero and greater than Init Size.

SPMCFGE0182 **Error in configuration changed event handler for run-time component {0}.**

Explanation An event was raised but most likely this run-time component does not exist anymore.

Action Change the configuration for existing run-time components.

SPMCFGE0183 **Missing or invalid Component Endpoint alias.**

Explanation The Component Endpoint alias is missing or invalid.

Action Provide a valid Component Endpoint alias.

SPMCFGE0184 **Duplicate Component Endpoint alias.**

Explanation The provided alias already exists.

Action Provide a new unique alias.

SPMCFGE0185	**Problem detected while trying to read/write configuration data.**
Explanation	The read/write operation failed.
Action	Check if the configuration data file is available.

SPMCFGE0186	**There is no existing ProxySettings configuration instance with the provided ProxyAlias.**
Explanation	The provided ProxyAlias was not found in the existing ProxySettings aliases.
Action	Provide existing ProxyAlias.

SPMCFGE0187	**There is no existing Keystore configuration instance with the provided KeystoreAlias.**
Explanation	The provided KeystoreAlias was not found in the existing Keystore aliases.
Action	Provide existing KeystoreAlias.

SPMCFGE0188	**There is no existing Truststore configuration instance with the provided TruststoreAlias.**
Explanation	The provided TruststoreAlias was not found in the existing Truststore aliases.
Action	Provide existing TruststoreAlias.

SPMCFGE0189	**Missing or empty BASIC authentication user.**
Explanation	The BASIC authentication user is missing or empty.
Action	Provide BASIC authentication user.

SPMCFGE0190	**Either KeystoreAlias or KeystoreDefinition can be specified, but not both.**
Explanation	Either KeystoreAlias or KeystoreDefinition can be specified, but not both at the same time.
Action	Provide either KeystoreAlias or KeystoreDefinition.

SPMCFGE0191	**Either TrustoreDefinition or TruststoreAlias can be used, but not both.**
Explanation	Either TrustoreDefinition or TruststoreAlias can be used, but not both at the same time.
Action	Provide either TrustoreDefinition or TruststoreAlias.

SPMCFGE0193	**The "configuration" property is not set.**
Explanation	The "configuration" property defines where the proxy settings are stored.
Action	Set the "configuration" property.

SPMCFGE0194	**This configuration instance is not intended to be deleted.**
Explanation	This configuration can only be modified.
Action	Modify the configuration instead of deleting it.

SPMCFGE0195	**Configuration password decryption failed. The provided value for shared secret is incorrect.**
Explanation	Decrypting the configuration password has failed. The value specified for the shared secret is incorrect.
Action	Check if the values for shared secret on Command Central and Platform Manager are the same.

SPMCFGE0196	**The server cannot be null.**
Explanation	The creation of a cluster configuration requires servers.
Action	Specify at least one server.

SPMCFGE0197	**Wrong configuration ID.**
Explanation	The configuration ID is not recognized.
Action	Re-try using a valid configuration ID.

SPMCFGE0198	**LDAP configuration file not found.**
Explanation	An LDAP configuration file with the specified alias is not found.
Action	Specify a valid configuration instance ID.

SPMCFGE0199	**Configuration {0} can not be deleted.**
Explanation	The configuration file can not be deleted.
Action	Make sure that a configuration with the specified alias exists.

SPMCFGE0201	**Error while processing jaas.config entries.**
Explanation	Cannot store the JAAS configuration file.
Action	Check the wrapper log for details about the error.

SPMCFGE0202	**{0} process finished with error code "{1}".**
Explanation	CMD: {2}, OUTPUT: {3}
Action	Check the upgrade and migration help for the product.

SPMCFGE0204	**There is no existing Credentials configuration instance with the provided alias {0}.**
Explanation	The specified alias {0} was not found in the existing credentials configuration instances.
Action	Specify an existing credentials alias.

SPMCFGE0205	**Credentials configuration file not found.**
Explanation	A credentials configuration file with the specified alias is not found.
Action	Specify a valid configuration instance ID.

SPMCFGE0206	**Specified alias is reserved for default credentials and cannot be used.**
Explanation	The default credentials have reserved aliases, such as NONE, TRUSTED or DEFAULT_ADMINISTRATOR.
Action	Specify a valid alias.

SPMCFGE0207	**Configuration instance with alias {0} does not exist.**
Explanation	The specified configuration instance does not exist.
Action	Specify a valid alias of an existing configuration instance.

SPMCFGE0209	**Proxy configuration file not found.**
Explanation	The configuration instance ID is not valid.
Action	Specify a valid configuration instance ID.

SPMCFGE0210	**A realm with the same name already exists.**
Explanation	A JAAS realm with the same name already exists.
Action	Specify a unique realm name.

SPMCFGE0212	**Installation name {0} may not contain "{1}".**
Explanation	The specified installation name {0} contains the reserved character sequence "{1}".
Action	Remove the character sequence "{1}" from the installation name.

SPMCFGE0213	**Missing or invalid port number. A positive number is expected.**
Explanation	The specified value must be a positive number.
Action	Specify a positive number.

SPMCFGE0214	**A configuration of type COMMON-CREDENTIALS should have a CommonCredentials element with a valid alias.**
Explanation	A configuration of type COMMON-CREDENTIALS should have a CommonCredentials element with a valid alias.
Action	Provide a URL-friendly alias for the CommonCredentials element.

SPMCFGE0215	**ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .**
Explanation	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with the specified properties.
Action	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with the specified properties.

SPMCFGE0216	**Shared secret is not configured.**
Explanation	Shared secret is required for encryption of sensitive information.
Action	Configure shared secret for each of Command Central's environments.

SPMCFGI0108	**No primary or HTTPS ports are found for {0} component and its parent/child relations.**
Explanation	No primary or HTTPS ports were found for {0} component and its parent/child relations.
Action	Check configured and available ports for availability and collisions.

SPMCFGW0029	**The validator with the given type is not able to instantiate a KeyStore.**
Explanation	The validator with the given type is not able to instantiate a KeyStore.
Action	Provide the correct certificate information.

SPMCFGW0030	**An exception occurred when trying to load the keystore certificate.**
Explanation	The NoSuchAlgorithmException exception occurred when trying to load the keystore certificate.
Action	Provide the correct certificate information.

SPMCFGW0031	**An exception occurred while trying to load the keystore certificate.**
Explanation	The CertificateException exception occurred while trying to load the keystore certificate.
Action	Provide the correct certificate information.

SPMCFGW0032	**An exception occurred when trying to load the keystore certificate.**
Explanation	The IOException exception occurred when trying to load the keystore certificate.
Action	Provide the correct certificate information.

SPMCFGW0033	**An exception occurred when trying to load the keystore certificate.**
Explanation	The URISyntaxException exception occurred when trying to load the keystore certificate.
Action	Provide the correct certificate information.

SPMCFGW0034	**The file location provided in the truststore could not be found.**
Explanation	The file location provided in the truststore could not be found.
Action	Provide the correct certificate information.

SPMCFGW0035	**An exception occurred when trying to load the truststore certificate.**
Explanation	The KeyStoreException exception occurred when trying to load the truststore certificate.
Action	Provide the correct certificate information.

SPMCFGW0036	**An exception occurred when trying to load the certificate.**
Explanation	The NoSuchAlgorithmException exception occurred when trying to load the certificate.
Action	Provide the correct certificate information.

SPMCFGW0037	**An exception occurred when trying to load the certificate.**
Explanation	The CertificateException exception occurred when trying to load the certificate.
Action	Provide the correct certificate information.

SPMCFGW0038	**The validator could not load the certificate because of an exception.**
Explanation	The validator could not load the certificate when trying to load the certificate because of the IOException exception.
Action	Provide the correct certificate information.

SPMCFGW0039	**URI syntax provided is incorrect.**
Explanation	The URISyntaxException occurred when trying to load the certificate.
Action	Provide the correct certificate information.

SPMCFGW0057	**JDBC Driver cannot be loaded.**
Explanation	JDBC Driver is not installed.
Action	Verify that the specified JDBC Driver is installed. For more information, see the Command Central documentation.

SPMCFGW0083	**The path of the log file {0} is not fully qualified.**
Explanation	The specified log file path is not fully qualified.
Action	Provide the absolute path for the log file.

SPMCFGW0104	**Could not perform configuration validation for {0} because {1} error was encountered.**
Explanation	Could not perform configuration validation for {0} because {1} error was encountered.
Action	Retry the action.

SPMCFGW0113	**The specified port is already bound by configuration instance {0} of runtime {1} and is not enabled.**
Explanation	The specified port is already bound by configuration instance {0} of runtime {1} and is not enabled.
Action	Change the port number and retry.

SPMCFGW0116	**The specified port {0} is already in use by another configuration instance.**
Explanation	The specified port {0} is already in use by configuration instance {1} of runtime {2}, but is not enabled or it is on different bind address.
Action	Specify a different port number.

SPMCFGW0203	**Advanced Memory settings are deprecated.**
Explanation	Using the COMMON-MEMORY configuration type to set up advanced memory settings is deprecated.
Action	Use the COMMON-JVM-OPTIONS configuration type to configure the advanced memory settings.

SPMCFGW0211	**JDBC Driver Class is required for validation.**
Explanation	Default JDBC Driver not found for Database Server Type {0}. JDBC Driver Class is required for performing validation.
Action	Please specify the JDBC Driver in your JDBC Settings configuration and make sure that the specified Driver is installed. For more information, see the Command Central documentation.

SPMCFRE0000	**The content of the response is not acceptable according to the accept headers**
Explanation	The content of the response is not acceptable according to the accept headers.
Action	Check the response and the accept headers.

SPMCFRE0001	**Unexpected exception occured.**
Explanation	Unexpected exception occured.
Action	Check the logs.

SPMCFRE0002	**Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:**
Explanation	Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:
Action	Check the logs.

SPMCFRE0003	**ConfigurationSerializersRegistry is not available.**
Explanation	ConfigurationSerializersRegistry is not available.
Action	Contact Software AG Global Support.

SPMCFRE0004	**ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .**
Explanation	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
Action	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.

SPMCFRE0005	**A ConfigurationTypeId "{0}" doesn't exist for RuntimeComponentId "{1}" .**
Explanation	There is not registered ConfigurationType with the provided ID for the required RuntimeComponent.
Action	Provide valid ConfigurationTypeId for the required RuntimeComponent.

SPMCFRE0006	**Configuration Service cannot handle Configuration Model "{0}". Supported models are: {1}. Check Configuration Type "{2}" definition.**
Explanation	Most likely there is an error in the definition of the Configuration Type SPI in the respective product plug-in.
Action	Check the Configuration Type "{2}" definition.

SPMCLTE0014	**ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .**
Explanation	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
Action	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.

SPMCLTE0015	**Authentication call to SPM failed to execute.**
Explanation	Authentication call to SPM failed to execute.
Action	Make sure that the user has valid access rights to the service.

SPMCLTE0016	**Cannot retrieve the delegated assertion for the current user.**
Explanation	Cannot retrieve the delegated assertion for the current user.
Action	Check if the user has valid delegated rights.

SPMCLTE0017	**Internal Error processing Platform Manager request**
Explanation	The server encountered an error and it cannot complete the request.
Action	Contact your system administrator.

SPMCLTE0018	**The specified runtime component {0} could not be found on node {1}.**
Explanation	There is no component called {0} registered for node {1}. The data could not be retrieved.
Action	Check the components for Platform Manager node {1}.

SPMCLTE0020	**{0} is not a valid type for the runscript request**
Explanation	The type for the runscript request is not valid. Valid types are fix or product.
Action	Resubmit the request with a valid type.

SPMCLTE0021	**No artifacts specified in uninstall request**
Explanation	The unistall request does not specify any products or fixes.
Action	Resubmit the request with a valid list of products and fixes.

SPMCLTE0022	**Invalid artifact type for uninstall**
Explanation	The artifact type must be product or fix.
Action	Specify valid artifacts in the request.

SPMCLTE0023	**Invalid repository type: {0}**
Explanation	The specified repository type is not supported.
Action	Use fix or product as the repository type.

SPMCLTE0024	**No such repository: {0}**
Explanation	The repository does not exist.
Action	Specify a valid repository.

SPMCLTE0025	**Unsupported repository type: {0}**
Explanation	Fix and product are the only supported repository types.
Action	Use fix or product as the repository type.

SPMCLTE0026	**Unsupported repository type: {0}**
Explanation	Fix and product are the only supported repository types.
Action	Specify a valid repository type.

SPMCLTE0027	**The response cannot be converted to java.util.Properties: {0}**
Explanation	The response does not comply with the java.util.Properties text or XML format.
Action	Make sure the format is correct or contact Software AG Global Support.

SPMCLTE0028	**{0} is not a valid type for the install request.**
Explanation	The type for the install request is not valid. Valid types are fix or product.
Action	Resubmit the request with a valid type.

SPMCLTE0030	**Failed to store license metering time stamp.**
Explanation	The products on the platform {0} were metered by the license metering tool of Command Central, but the time stamp when this metering was performed by node {1} could not be stored.
Action	Make sure that the harddisc on the specified server is not full or contact Software AG Global Support.

SPMCLTE0031	**Remote task failed: {0}**
Explanation	Remote task failed: {0}
Action	Check the corresponding Platform Manager logs for more details about the error.

SPMCLTI0009	**Internal Server Error**
Explanation	Internal server error.
Action	Make sure that the required services are running, communication channels are accessible, and parameters are valid.

SPMCLTI0010	**Unknown Error**
Explanation	An unspecified error occured during communication.
Action	Make sure that the required services are running, communication channels are accessible, and parameters are valid.

SPMCLTI0011	**Error occurred during execution of the command!**
Explanation	An error occured during communication.
Action	Make sure that the required services are running, communication channels are accessible, and parameters are valid.

SPMCLTW0001	**An exception has occured while retrieving remotely RuntimeStatus from: {0}**
Explanation	This might be happenning due to a number of reasons, such as missing monitoring implementation in the product plugin, network interference, and others.
Action	See detailed stack trace in order to define the actual reason for this exception.

SPMCOME0000	**{0} is unknown runtime component.**
Explanation	This component ID does not exist.
Action	Use runtimeComponentId that already exists.

SPMCOME0001	**{0} is an unknown product.**
Explanation	The required productId does not exist in the list of InventoryService.getInstalledProducts()
Action	Use a productId of a product that is already installed.

SPMCOME0002	**No available implementation for {0}.**
Explanation	Displayed status of a product plug-in after calling a specific operation that is not available.
Action	Use an available operation.

SPMCOME0003	**The PortSettings XML cannot be empty.**
Explanation	The PortSettings XML response cannot be empty.
Action	Add data in the PortSettings XML response.

SPMCOME0004	**PortSettings contains property keys that do not match properties in the config.ini file.**
Explanation	PortSettings contains property keys that do not match properties in the config.ini file.
Action	Check the property keys and try to find the matching one or fix the config.ini file.

SPMCOME0005	**Load configuration error.**
Explanation	Indicates issues with reading/writing a configuration.
Action	Fix any issues related to reading or writing the configuration.

SPMCOME0006	**Unexpected exception.**
Explanation	An unexpected exception occurred while reading/writing a configuration.
Action	Fix the unexpected exception.

SPMCOME0007	**Un-handled internal server error. {0}**
Explanation	A Platform Manager Exception occurred.
Action	Resolve the exception.

SPMCOME0010	**Error:**
Explanation	This is most likely an error that is not expected.
Action	None.

SPMCOME0017	**Provided configuration is not valid.**
Explanation	The provided configuration does not conform with the rules for the specified configuration type.
Action	Check the provided configuration for errors and rule breaches.

SPMCOME0018	**Unexpected component status: {0} but should have one of {1}**
Explanation	The requested operation cannot be completed because the component cannot do the operation in its current runtime status.
Action	Ensure that the component is in one of the expected statuses to complete this operation. For ONLINE status, start the parent runtime instance.

SPMCOME0020	**A Configuration instance with ID = {0} does not exist.**
Explanation	A Configuration instance with the provided ID does not exist.
Action	Use the ID of an existing Configuration instance.

SPMCOME0029	**Server did not find anything matching the request URI.**
Explanation	There is no resource for this URI.
Action	Check if the URI is correct. Check if the resource IDs are valid.

SPMCOME0030	**The request cannot be understood by the server.**
Explanation	Inconsistent or empty body.
Action	Do not retry without modifications of the request.

SPMCOME0031	**The request is not acceptable as stated in the accept headers.**
Explanation	Platform Manager cannot return the response in the desired format.
Action	Either change the accept headers, or the data format of the response.

SPMCOME0033	**The KPI {0} contains invalid data and cannot be created.**
Explanation	The error occurs when the RuntimeStateZone can not be calculated. Possible reasons for this issue are that the given values for max, marginal, and normal are null or in the wrong format.
Action	Check the content of the KPI and provide correct data.

SPMCOME0043	**Node version is not supported.**
Explanation	Command Central connects to an old Platform Manager node.
Action	Remove the old Platform Manager node.

SPMCOME0045	**Failed provisioning operation. Status is {0}.**
Explanation	The failed operation status is {0}.
Action	Try to correct the issue and retry the operation.

SPMCOME0046	**Operation failed due to unsatisfied dependencies: {0}**
Explanation	There are missing dependencies.
Action	Try to correct the situation. Retry the operation.

SPMCOME0047	**The specified repository does not exist.**
Explanation	The specified repository was not found.
Action	Check the repository name and provide the name of an existing repository.

SPMCOME0048	**Configuration password decryption failed. The provided value for shared secret is incorrect.**
Explanation	Decrypting the configuration password has failed. The value specified for the shared secret is incorrect.
Action	Check if the values for shared secret on Command Central and Platform Manager are the same.

SPMCOME0049	**Un-handled internal server error.**
Explanation	A Platform Manager Exception occurred.
Action	Resolve the exception.

SPMCOME0051	**Cannot connect to the repository due to {0}.**
Explanation	Internet access is required to connect to this repository. The error occurred either because the proxy for the local Platform Manager is not configured, or the metadata and the URL for the repository are not correct.
Action	Make sure the proxy for the local Platform Manager is configured and the given repository URL is valid. To find the URL, run 'sagcc list repository products properties=*.

SPMCOME0053	**Service {0} is not available.**
Explanation	The service did not start in time.
Action	Retry the operation or refresh.

SPMCOME0055	**Cannot connect to the repository. {0}**
Explanation	The selected release is an innovation release to which you do not currently have access.
Action	For more information about the innovation release and how to get access, visit http://empower.softwareag.com/innovationrelease/

SPMCOME0057	**Cannot connect to the repository.**
Explanation	The supplied credentials are not valid.
Action	See the Command Central documentation for information on troubleshooting credentials.

SPMCOME0058	**Cannot connect to the repository {0}.**
Explanation	The proxy for the local Platform Manager is not configured.
Action	See the Command Central documentation for information on configuring proxies.

SPMCOME0061	**Error reading metering data cache file.**
Explanation	The metering data cache file could not be read.
Action	Check the access rights to the metering folder.

SPMCOME0062	**Error writing to metering data cache file.**
Explanation	Writing to the metering data cache file failed.
Action	Check the access rights to the metering folder.

SPMCOMI0008	**The command is disabled.**
Explanation	Most probably an important OSGi service is not registered.
Action	None.

SPMCOMI0009	**No help available.**
Explanation	This command does not provide a help message.
Action	None.

SPMCOMI0011	**[DISABLED]**
Explanation	A command with this info line prefix cannot be executed.
Action	None.

SPMCOMI0032	**Unsupported operation.**
Explanation	The attempted operation is currently not supported by the Platform Manager server.
Action	Contact you administrator.

SPMCONE0001 **Error while loading configuration.**

Explanation An error occurred while loading configuration.

Action Provide valid arguments.

SPMCONE0006 **Error while getting a configuration type.**

Explanation An error occurred while getting a configuration type.

Action Resubmit the request.

SPMCONE0007 **Error during serialization**

Explanation An error occurred during the serialization step.

Action Resubmit the serialization step.

SPMCONE0013 **Error while updating configuration.**

Explanation An error occurred while updating the configuration.

Action Resubmit the configuration.

SPMCONE0015 **Error while getting configuration status.**

Explanation Error while getting configuration status.

Action Get the configuration status correctly.

SPMCONE0024 **Error while getting configuration instances.**

Explanation An error occurred while getting configuration instances.

Action Resubmit the configuration instances get operation.

SPMCONI0000 **The command is not recognized. Type {0} for help.**

Explanation The typed command is not recognized.

Action Type spm for help.

SPMCONI0002 **{0} - get configuration values for the given configuration type**

Explanation Missing configuration values for the given configuration type.

Action Get configuration values for the given configuration type.

SPMCONI0003	**Configuration (JavaModel): {0}**
Explanation	Configuration (JavaModel) information.
Action	None.

SPMCONI0004	**Configuration (Text): {0}**
Explanation	Configuration (Text) information.
Action	None.

SPMCONI0005	**No load configuration.**
Explanation	No load configuration.
Action	None.

SPMCONI0008	**Configuration status: {0}**
Explanation	Information about the configuration status.
Action	None.

SPMCONI0009	**No configuration status.**
Explanation	No configuration status.
Action	None.

SPMCONI0010	**The specified resource doesn't exist.**
Explanation	The specified resource doesn't exist.
Action	None.

SPMCONI0011	**There is no configuration type found for this runtime component.**
Explanation	There is no configuration type found for this runtime component.
Action	None.

SPMCONI0012	**{0} - Submit configuration and get the configuration status**
Explanation	The configuration status is missing or the configuration is not submitted.
Action	Submit the configuration and get the configuration status.

SPMCONI0014 **Bad URI - {0}**

Explanation Bad URI is submitted.

Action None.

SPMCONI0016 **Configuration status: {0}**

Explanation Information about the configuration status.

Action None.

SPMCONI0017 **No configuration status.**

Explanation No configuration status.

Action None.

SPMCONI0018 **{0} - query for the current configuration status.**

Explanation A query for the current configuration status.

Action None.

SPMCONI0019 **No configuration instance.**

Explanation No configuration instance.

Action None.

SPMCONI0020 **No configuration instances.**

Explanation No configuration instances.

Action None.

SPMCONI0021 **Configuration Instance description: {0}**

Explanation Configuration Instance description.

Action None.

SPMCONI0022 **Configuration Instance ID: {0}**

Explanation Information about the Configuration Instance ID.

Action None.

SPMCONI0023 **Configuration Instance name: {0}**

Explanation Information about the Configuration Instance name.

Action None.

SPMCONI0025 **{0} - list of the configuration instances for a given runtime component**

Explanation List of the configuration instances for a given runtime component.

Action None.

SPMCONI0026 **JobManagerService is not available.**

Explanation JobManagerService is not available.

Action None.

SPMCONI0027 **Invalid job ID: {0}**

Explanation Information about an invalid job ID.

Action None.

SPMCONI0028 **Number of jobs: {0}**

Explanation Information about the number of jobs.

Action None.

SPMCONI0029 **Job ID: {0}**

Explanation Information about the job ID.

Action None.

SPMCONI0030 **The status of the job with ID ({0}) is {1}.**

Explanation Information about the job status.

Action None.

SPMCONI0031 **The job started at {0}.**

Explanation Information about when the job started.

Action None.

SPMCONI0032 **The job ended at {0}.**

Explanation Information about when the job ended.

Action None.

SPMCONI0033 **The job is still running.**

Explanation The job is still running.

Action None.

SPMCONI0034 **The duration of the job so far is {0} seconds.**

Explanation Information about the duration of the job.

Action None.

SPMCONI0035 **{0} - lists all (not done) jobs or status of a specific job**

Explanation Lists all (not done) jobs or status of a specific job.

Action None.

SPMCONI0036 **{0} - runtime status of the component identified by this ID.**

Explanation Runtime status of the component identified by this ID.

Action None.

SPMCONI0037 **No RuntimeState found for {0}.**

Explanation No RuntimeState found.

Action None.

SPMCONI0038 **{0} - list of the runtime components**

Explanation List of the runtime components.

Action None.

SPMCONI0039 **{0} - list of the installed products**

Explanation List of the installed products.

Action None.

SPMCONI0040 **{0} - starts the runtime component with this ID with safe mode enabled.**

Explanation Starts the runtime component with this ID with safe mode enabled.

Action None.

SPMCONI0041 **{0} - starts the runtime component with this ID with debug mode enabled.**

Explanation Starts the runtime component with this ID with debug mode enabled.

Action None.

SPMCONI0042 **{0} - stops the runtime component with this ID.**

Explanation Stops the runtime component with this ID.

Action None.

SPMCONI0043 **{0} - starts the runtime component with this ID.**

Explanation Starts the runtime component with this ID.

Action None.

SPMCONI0044 **{0} - resumes the runtime component with this ID.**

Explanation Resumes the runtime component with this ID.

Action None.

SPMCONI0045 **{0} - restarts the runtime component with this ID.**

Explanation Restarts the runtime component with this ID.

Action None.

SPMCONI0046 **{0} - pauses the runtime component with this ID.**

Explanation Pauses the runtime component with this ID.

Action None.

SPMCONI0047 **{0} - creates a new configuration instance for a given runtime component and a given configuration type.**

Explanation Creates a new configuration instance for a given runtime component and a given configuration type.

Action None.

SPMCONI0048	**Error during creating configuration**
Explanation	Error during creating configuration
Action	None.

SPMCONI0049	**{0} - Delete configuration and get the configuration status.**
Explanation	Delete configuration and get the configuration status.
Action	Delete configuration and get the configuration status.

SPMCONI0050	**ConfigurationSerializer is not found for runtimeComponent with ID: {0} and configurationType with ID: {1}**
Explanation	ConfigurationSerializer is not found for runtimeComponent with ID: {0} and configurationType with ID: {1}.
Action	None.

SPMCONI0051	**{0} - runtime state of the comonent identified by this ID**
Explanation	Runtime state of the comonent identified by this ID
Action	None

SPMCORE0001	**Exception handling directory change events.**
Explanation	An exception occurred when handling directory change events.
Action	Contact your Command Central Administrator.

SPMCORE0002	**Exception processing directory change events.**
Explanation	An exception occurred when processing directory change events.
Action	Contact your Command Central Administrator.

SPMCORE0003	**The provided observer should not be null.**
Explanation	The provided observer should not be null.
Action	Provide a non-null observer to the Directory Watcher infrastructure.

SPMCORE0004	**The provided observed directory should not be null.**
Explanation	The provided observed directory should not be null.
Action	Provide a non-null observed directory to the Directory Watcher infrastructure.

SPMCORE0005	**The provided observed directory change types should not be null or empty.**
Explanation	The provided observed directory change types should not be null or empty.
Action	Provide valid observed directory change types to the Directory Watcher infrastructure.

SPMCORE0007	**Could not get JMXConnector for runtime component with id {0}**
Explanation	The runtime component does not have a configured JMX port, or there was a problem obtaining the configuration.
Action	Check if the runtime component is online and verify that at least one enabled JMX port configuration is available.

SPMCORE0008	**Repository configuration under {0} cannot be deleted. Try to delete the file manually.**
Explanation	The repository configuration file cannot be deleted.
Action	Delete the file manually and restart Platform Manager

SPMCORE0009	**Configuration for repository under {0} is corrupted. Retry the operation.**
Explanation	Repository configuration file got corrupted while being stored on disk.
Action	Retry the repository operation.

SPMCORI0000	**TestMessage**
Explanation	Test message to be removed.
Action	None.

SPMCTCE0000	**Unexpected YAML type {0} in field {1}! The correct type is integer.**
Explanation	Non-integer data was used in a field that requires integer.
Action	Use the correct integer value and try again.

SPMDBCE0000	**Unsupported parameter name: {0}**
Explanation	The parameter name is not supported.
Action	See the Command Central documentation for a list of supported parameters.

SPMDIAE0000	**Log source not found: {0}**
Explanation	The requested log source does not exist.
Action	Use getLogSources() prior to retrieveLog().

SPMDIAE0001	**{0} does not exist or is not a directory.**
Explanation	The specified location does not exist or is not a directory.
Action	Provide a location that exists and is a directory.

SPMDIAW0002	**Missing 'logDirs' configuration property for DefaultLogAccess service component configuration.**
Explanation	An SPM bundle has a LogAccess service component that is missing its 'logDirs' configuraiton property.
Action	The OSGI service configuration must include this property if log files are to be collected.

SPMDIAW0003	**{0} cannot be evaluated.**
Explanation	The path expression {0} cannot be evaluated.
Action	Make sure the component definition has the correct path expression.

SPMDIAW0004	**The instance management service did not return a proper instance name.**
Explanation	The default log access component defintion did not provide an instance name regular expression and the instance management service did not return a proper instance name.
Action	Provide an instance name regular expression or a proper implementation of the instance management service.

SPMDIRE0000	**{0} not found!**
Explanation	A runtime component or a log was not found.
Action	Verify the requested item is really present in the system.

SPMIMGE0000	**Product {0} does not support instance management.**
Explanation	The Platform Manager plugin for product {0} does not support instance management.
Action	See the Software AG Platform Manager documentation to double check if product {0} supports instance management. If the product supports instance management, contact Software AG Global Support.

SPMIMGE0002	**Properties for {0} cannot be returned.**
Explanation	A server error occured during properties extraction.
Action	Contact Software AG Global Support.

SPMIMGE0003	**{0} cannot be matched against {1}**
Explanation	The specified regular expression in the component definition does not match the run-time component ID.
Action	Revise the regular expression in the component definition or contact Software AG Global Support.

SPMIMGE0004	**Mandatory property {0} is not specified.**
Explanation	A required property in the component definition is missing.
Action	Specify the required property in the component definition.

SPMIMGE0005	**Instance management script {0} cannot be resolved.**
Explanation	The instance management script was not found on the file system or there is another I\O error.
Action	Make sure the instance management script has the correct name and is in the correct location.

SPMIMGE0007	**This instance management command cannot be performed because the following input properites are missing: {0}**
Explanation	The input properties are insufficient for performing the requested instance management operation.
Action	Provide the input properties that are missing or contact Software AG Global Support.

SPMIMGE0008	**Instance management operation failed with exit code: {0}**
Explanation	The execution of the instance management operation failed.
Action	Check the logs for more details or contact SoftwareAG Global Support.

SPMIMGE0009	**Instance Management process finished with error code "{0}".**
Explanation	CMD: {1}, OUTPUT: {2}
Action	Check the administration documentation for the specified product instance.

SPMIMGE0010	**Property [{0}] has an invalid value [{1}].**
Explanation	Null or empty values are not allowed.
Action	Provide a valid value and try again.

SPMIMPE0000	**Unable to locate configuration source property for persistent ID: {0}; configuration properties for this PID are: {1}.**
Explanation	Most probably the persistent ID configuration is not provided by Dynamic Configurator.
Action	Provide the persistent ID using Dynamic Configurator.

SPMIMPE0001	**The configuration source location for the persistent ID {0} is not a valid URL: {1}**
Explanation	The configuration source location is not a valid URL.
Action	Dynamic Configurator should point to a valid URL for the given persistent ID.

SPMIMPE0020	**The CC asset {0} does not contain the required {1} file.**
Explanation	The asset does not contain file that is requied for the install asset operation.
Action	Check if the asset was built correctly.

SPMINRI0000	**Nothing found for ID = {0}**
Explanation	Nothing found for this ID.
Action	None.

SPMINRI0001	**Inventory Service is not set.**
Explanation	Inventory Service is not set.
Action	None.

SPMINVI0000	**Product cannot be null.**
Explanation	Product cannot be null.
Action	None.

SPMINVI0001	**Category cannot be null.**
Explanation	Category cannot be null.
Action	None.

SPMINVI0002	**ID must start with productId.**
Explanation	ID must start with productId.
Action	None.

SPMJBRE0000	**A job with ID {0} cannot be found.**
Explanation	A job with the specified ID may have never existed or it may have completed long before this request.
Action	Use the following URI to list all jobs that are running or recently completed: /spm/jobmanager/jobs

SPMJOBE0001	**Maximum number of non-done jobs reached. Try again later or increase {2}. Current jobs: {0} max jobs: {1}.**
Explanation	The job manager queue is full and new jobs cannot be scheduled.
Action	Wait a few moments or increase com.softwareag.platform.management.jobmanager.impl.Configuration.SYS_PROP_MAX_JOBS.

SPMJOBE0002	**Job sequence exhausted. Try again later or set a bigger {0}**
Explanation	All job sequence IDs have been consumed.
Action	Wait a few moments or set a bigger com.softwareag.platform.management.jobmanager.impl.Configuration.SYS_PROP_JOB_SEQUENCE_MAX_SIZE.

SPMJOBE0003	**Job {0} failed!**
Explanation	The task being carried out by this job has failed.
Action	Inspect the logs to troubleshoot the problem or contact SoftwareAG Global Support.

SPMJOBI0000	**This job is done or not available due to a problem.**
Explanation	The Null Job status.
Action	None.

SPMLCCE0000	**runtimeComponentId for productId {0} is null.**
Explanation	The AdvancedLifecycleOperations service is registered in with productID that does not contain the given runtimeComponentId.
Action	Make sure that your product plugin has correct productId and runtimeComponentId IDs.

SPMLCCE0001	**Runtime component "{0}" does not support life cycle operation "{1}".**
Explanation	This Runtime component does not support the specified life cycle operation.
Action	Make sure you execute life cycle operations supported by this run-time component.

SPMLCCE0015	**The run-time status of runtimeComponent {0} is not {1}.**
Explanation	The lifecycle operation did not complete as expected.
Action	Check the logs for details about the error.

SPMLCCE0016	**Runtime status of component with id: {0} can not be retrieved or component is not stopped on time.**
Explanation	The run-time status of the component with id: {0} can not be retrieved on time.
Action	Check the logs for details about the error.

SPMLCCE0032	**The runtimeComponent with id: {0} does not have LifeCycleOperations SPI registered.**
Explanation	A LifeCycleOperations SPI has not been found for runtimeComponent : {0}
Action	Check the component definition, used for registering the SPI.

SPMLCCE0041	**Runtime component {0} did not become online.**
Explanation	The runtime component did not become online.
Action	Check the runtime component logs.

SPMLCCE0042	**Restart job having id {0} finished with status error.**
Explanation	The restart job finished with status error.
Action	Check the logs for details.

SPMLCCE0043	**The thread was interrupted while waiting for runtime status.**
Explanation	The checking of the runtime status of a component was interrupted.
Action	Check the logs for JVM errors.

SPMLCCE0044	**Exception occurred while getting runtime status.**
Explanation	An exception occured when checking the runtime status of a component.
Action	Check the SPM logs for system errors

SPMLCCE0045	**The thread was interrupted while setting runtime status.**
Explanation	The checking of the runtime status of a component was interrupted.
Action	Check the logs for JVM errors

SPMLCRE0000	**The lifecycle operation to execute is unknown.**
Explanation	The operation is not a part of the predefined list of lifecycle operations that can be executed: start, stop, restart, pause, resume, start in debug, and start in safe mode.
Action	Specify an operation from the predefined list.

SPMMICE0000	**Extracting source version failed.**
Explanation	Failed to extract the source version from the bundles.info file.
Action	Ensure that the bundles.info file is at the correct location.

SPMMONE0000	**Could not get JMXConnector for runtime component with id {0} because JMX port configuration was not found.**
Explanation	This particular run-time component does not have a configured JMX port or there was a problem obtaining the configuration.
Action	Check if the run-time component is online and that at least one enabled JMX port configuration is available.

SPMMWSE0000	**Provide "sysadmin" credentials in CCE for "{0}"**
Explanation	When BASIC authentication is used, credentials for the "sysadmin" user must be supplied in Command Central for the My webMethods Server component.
Action	Verify that BASIC authentication for the My webMethods component uses credentials for "sysadmin" user.

SPMMWSE0002	**Primary port not set for {0}**
Explanation	A primary port is required to connect to My webMethods Server.
Action	Provide primary port value for {0}.

SPMMWSE0003	**Invalid URI**
Explanation	The supplied URI for connection to My webMethods Server does not have a valid syntax according to RFC 3986.
Action	Verify that the correct hostname and port are provided.

SPMMWSE0004	**An error occurred while constructing the URL**
Explanation	The connection URL to My webMethods Server is malformed.
Action	Verify that the correct hostname and port are provided.

SPMMWSE0005	**Root context path ''{0}'' is invalid.**
Explanation	The context path may start with a slash and can contain only the following characters: uppercase or lowercase letters, decimal digits, hyphen, period, and underscore.
Action	Verify that the root context path contains only valid characters.

SPMMWSE0006	**Invalid credentials set for user "sysadmin"**
Explanation	The password supplied for the "sysadmin" user is not correct.
Action	Provide the correct password for the "sysadmin" user in the authentication information in Command Central.

SPMMWSE0007	**First Name is required**
Explanation	The First Name field must not be empty.
Action	Enter a first name.

SPMMWSE0008	**Last Name is required**
Explanation	The Last Name field must not be empty.
Action	Enter a last name.

SPMMWSE0009	**Unable to find server log directory: {0}**
Explanation	Unable to read the server log directory path from systemPaths.properties
Action	Check if there is a connection to the My webMethods Server database.

SPMMWSE0010	**Encryption failed for: {0}**
Explanation	The encryption of a value failed.
Action	Contact Software AG Global Support. Provide the logs for Platform Manager and My webMethods Server and the reproduction steps for the issue.

SPMMWSE0011	**Decryption failed for: {0}**
Explanation	The decryption of a value failed.
Action	Contact Software AG Global Support. Provide the Platform Manager and My webMethods Server logs and the reproduction steps of the issue.

SPMMWSE0012	**Primary datasource cannot be deleted**
Explanation	You cannot delete the primary My webMethods Server database connection datasource.
Action	None required.

SPMMWSE0013	**Adding a Derby data source is not supported**
Explanation	My webMethods Server does not support additional Derby data sources.
Action	Add a datasource of one of the supported database types.

SPMMWSE0014	**Missing or invalid db.xml**
Explanation	A My webMethods Server system configuration file is either missing or invalid.
Action	Contact the My webMethods Server system administrator.

SPMMWSE0015	**Only TRUSTED and BASIC authentication are supported**
Explanation	The specified authentication is not supported.
Action	Change authentication to TRUSTED or BASIC.

SPMMWSE0030	**Please enter a valid email address.**
Explanation	An invalid email address was entered.
Action	Enter a new email address.

SPMOGIE0000	**Could not obtain the runtime component id from "cplm" file: {0}**
Explanation	There was a problem obtaining metadata information about a specific profile.
Action	Check the profile folder structure and if cplm.xml contains any errors.

SPMOGIE0002	**Following exception occured "{0}" while parsing "{1}".**
Explanation	One of the profiles contains wrong metadata.
Action	Check listed file for errors.

SPMOGIE0003	**The Common Platform Lifecycle Management (cplm-v.xml) file is malformed.**
Explanation	The profile metadata file contains errors.
Action	Try to check cplm.xml file for errors in the specific profile.

SPMOGIE0005	**Operation "{0}" is not defined in the "cplm" file.**
Explanation	There was lifecycle operation for the specific component that is not defined inside cplm.xml.
Action	Try to repair cplm.xml file in the component profile folder.

SPMOGIE0008	**Common Platform Lifecycle Management (cplm-v.xml) file not found!**
Explanation	A file called cplm.xml is expected inside the profile folder.
Action	Try to create cplm.xml file for the component.

SPMOGIE0009	**Configuration with version "{0}" was not found in the metadata file.**
Explanation	No configuration with the specified version exists inside the cplm.xml file.
Action	Check the profile folder for cplm.xml and make sure it is up to date.

SPMOGIE0010	**Recursive actions not allowed.**
Explanation	A recursive action exists inside cplm.xml file.
Action	Check the cplm.xml file in the profile and remove any recursive actions.

SPMOGIE0011	**Malformed action "{0}".**
Explanation	Wrong metadata information exists inside the profile cplm.xml file.
Action	Check the cplm.xml file for the profile and correct errors.

SPMOGIE0012	**Action "{0}" not found.**
Explanation	Unknown action definied inside cplm.xml.
Action	Correct the cplm.xml file for the profile.

SPMOGIE0013	**Script "{0}" does not exist.**
Explanation	The specified script cannot be found in cplm.xml.
Action	Specify valid script/path inside the profile cplm.xml file.

SPMOGIE0014	**Failed executing: {0}**
Explanation	A problem occurred while executing the specified script.
Action	Check the specified script for errors.

SPMOGIE0015	**Missing value data for element "argument".**
Explanation	Wrong data format inside the profile cplm.xml file.
Action	Provide valid data inside cplm.xml.

SPMOGIE0016	**More than one "action" element with the same name exist.**
Explanation	A naming conflict exists inside cplm.xml.
Action	Provide different action names.

SPMOGIE0017	**Two "configuration" elements have the same version.**
Explanation	A conflict exists inside cplm.xml file.
Action	Provide different versions for "configuration" elements.

SPMOGIE0018	**Missing attribue "path" or "actionReference" for element "execute".**
Explanation	Wrong data exists inside the profile cplm.xml.
Action	Provide the missing data.

SPMOGIE0019	**Cannot specify both "path" and "actionReference" attributes in one "execute" element.**
Explanation	Wrong data exists inside cplm.xml.
Action	Correct cplm.xml file inside the profile folder.

SPMOGIE0026	**Unable to find configuration instances for the runtime component with ID: "{0}". The '"{1}"' system property is not set.**
Explanation	Such a property should be available in the config.ini file located under the configuration folder of this runtime component.
Action	Add the property by hand. The value must be the absolute path to the folder that contains the configuration properties files.

SPMOGIE0027	**Unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is either not existing or is not a directory.**
Explanation	This folder should contain the configuration properties files.
Action	Check if the location is configured properly in the config.ini file.

SPMOGIE0029	**Unable to load the configuration instance with ID "{0}" for the "{1}" runtime component.**
Explanation	None of the available configuration handlers can load the configuration instance. The configuration instance type might not be supported.
Action	Check the supported configuration instance types.

SPMOGIE0030	**Unable to update the configuration instance with ID "{0}" for the "{1}" runtime component.**
Explanation	None of the available configuration handlers can update the configuration instance. The configuration instance type might not be supported.
Action	Check the supported configuration instance types.

SPMOGIE0031	**Unable to load the configuration instance with ID: "{0}" for the "{1}" runtime component. The "{2}" property is not available but is required.**
Explanation	Unable to load the instance because of invalid set of configuration properties. The required properties must be available.
Action	Add the required property and report the invalid configuration instance.

SPMOGIE0032	**Unsupported protocol for configuration instance {0}.**
Explanation	Unknown protocol for the specified configuration instance.
Action	Check documentation for supported protocols.

SPMOGIE0033	**The update of the "{0}" configuration instance for the "{1}" runtime component failed. The port settings are empty.**
Explanation	The incoming configuration is empty. No port settings data is available.
Action	Port settings data should be present inside incoming configuration.

SPMOGIE0034	**No port available in configuration instance {0}.**
Explanation	Port number cannot be found inside the configuration instance.
Action	Provide port number inside the configuration instance.

SPMOGIE0035	**The update of the "{0}" configuration instance for the "{1}" runtime component failed. The available port configurations are more than one.**
Explanation	The configuration instance should contain only one port configuration.
Action	Remove obsolete port configurations.

SPMOGIE0036	**The update of the "{0}" configuration instance for the "{1}" runtime component failed. The port is null.**
Explanation	The port settings do not contain any port configuration.
Action	Provide port configuration.

SPMOGIE0037	**Invalid or missing port number: "{0}"**
Explanation	The validation of the port number failed. The port number should be greater than 1024 and smaller than 65535.
Action	Check the source of the port number and provide a value in the specified range.

SPMOGIE0038	**Error writing the new configuration. An attempt was made to overwrite an existing configuration file "{0}" with the new configuration.**
Explanation	The port number is a part of the configuration file name. Therefore, if the user sets a port that is already used in another configuration, a collision in the file names occurs. In such case the write operation is aborted because configuration data might be lost.
Action	Check if the port number set in the configuration that is being written is not used in another configuration of the same type.

SPMOGIE0039	**The new configuration could not be written. Unable to delete the original configuration instance file: "{0}"**
Explanation	A problem occurred while deleting the configuration instance file.
Action	For more details, check the I/O exceptions in the log file.

SPMOGIE0040	**ConfigurationService not found!**
Explanation	Most probably spm configuration bundle was not started.
Action	Try to start spm the configuration bundle.

SPMOGIE0042	**No connector configurations or connector port found for component: {0}**
Explanation	Expected data is missing for the specified component.
Action	Provide configuration for the specified component.

SPMOGIE0045	**Cannot start "{0}" profile in debug mode without debug port configuration.**
Explanation	It is possible that wrong data exists inside the cplm.xml file.
Action	Escape single quote with another single quote.

SPMOGIE0046	**Cannot start "{0}" profile in debug mode because the debug port configuration is disabled.**
Explanation	It is possible that wrong data exists inside the cplm.xml file.
Action	Escape single quote with another single quote.

SPMOGIE0048	**Exception occurred while obtaining port configurations for profile "{0}".**
Explanation	A problem occurred while reading profile port configurations.
Action	Check profile port configurations for errors.

SPMOGIE0050	**{0} cannot be null.**
Explanation	{0} cannot be null.
Action	Make sure the parameter is not null.

SPMOGIE0051	**{0} must begin with {1}**
Explanation	{0} must begin with {1}
Action	Make sure {0} begins with {1}.

SPMOGIE0055	**A log configuration not found: {0}**
Explanation	A log configuration was not found.
Action	Check your configuration instance path.

SPMOGIE0056	**Could not retrieve parent runtime component with id {0} for child runtime component with id {1}.**
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.

SPMOGIE0057	**Could not get JMXConnector for a runtime component of category {0}. Runtime component id is {1}.**
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.

SPMOGIE0058	**Could not get JMXConnector because no JMX port configuration is available for runtime component with id {0}.**
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.

SPMOGIE0059	**Could not get JMXConnector for runtime component with id {0} because none of the configured JMX ports is open.**
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.

SPMOGIE0060	**Could not get SubsystemMBean for a runtime component of a type different than ENGINE. Category : {0}, runtime component id : {1}**
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.

SPMOGIE0061	**No subsystem with id {0} is found for runtime component with id {1}.**
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.

SPMOGIE0062	**Exactly one subsystem is expected for runtime component with id {0}.**
Explanation	Exactly one subsystem is expected for the given runtime component.
Action	Make sure there is exactly one subsystem specified for runtime component.

SPMOGIE0064	**Executing "{0}" lifecycle operation shell script "{1}" returned non-zero exit code: {2}.**
Explanation	Non-zero exit code indicates an error.
Action	Check the product and Platform Manager logs for more details. Try to execute the script from the command line.

SPMOGIE0065	**Cannot start "{0}" profile in debug mode because the configured debug port is already in use.**
Explanation	Another application is started using the same port number.
Action	Stop the other product using the same port for debug mode.

SPMOGIE0066	**Platform Manager is unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is either not existing or is not a directory.**
Explanation	No configuration instances were found in the listed location.
Action	Check if the location is configured correctly in the config.ini file.

SPMOGIE0067	**Platform Manager is unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is empty.**
Explanation	Platform Manager is unable to find configuration instances for the runtime component. This folder should contain the profile-related folders and files for the specified runtime component. The path is configured in the config.ini file.
Action	Check if this folder is empty.

SPMOGIE0070	**Error while getting runtime status.**
Explanation	A problem occurred while obtaining data from an Engine.
Action	Check if the connection and credentials are OK.

SPMOGIE0081	**"{0}" operation failed for runtime component with id {1}. Reason:{2}**
Explanation	Executing operation against engine failed.
Action	Check JMX credentials and properties for this engine.

SPMOGIE0090	**No alias provided for the port configuration.**
Explanation	Providing a value for the alias during the creation of the port configuration is required.
Action	Specify an alias for the port configuration.

SPMOGIE0091	**The provided port alias is not URL friendly.**
Explanation	The provided port alias contains symbols that are not URL friendly.
Action	Provide only URL friendly symbols for the port alias.

SPMOGIE0092	**Failed to construct the Configuration Instance ID.**
Explanation	Platform Manager failed to construct the Configuration Instance ID.
Action	Check the configuration file for this instance.

SPMOGIE0093	**Missing common port alias. This configuration will be ignored.**
Explanation	The common port alias is missing and the configuration will be ignored.
Action	Provide an alias for this port configuration.

SPMOGIE0094	**Failed to construct the configuration instance.**
Explanation	Platform Manager failed to construct the configuration instance.
Action	Provide valid configuration data.

SPMOGIE0096	**Cannot read config.ini file for RuntimeComponent with ID {0}. Fall back on default product: {1}.**
Explanation	Cannot retrieve the parent product for the specified run-time component because an error occured while reading the corresponding config.ini file. The default product will be used instead.
Action	Check if the config.ini is a valid properties file.

SPMOGIW0001	**Could not pass the validating schema. The "cplm" file will not be validated.**
Explanation	File called cplm.xml does not contain expected metadata.
Action	Check profile folder files called cplm.xml for errors.

SPMOGIW0028	**Unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is empty.**
Explanation	This folder should contain the configuration properties files for the specified runtime component. The path is configured in the config.ini file.
Action	Check if this folder should be empty.

SPMOGIW0054	**Could not retrieve engines for runtime component with id : {0}.**
Explanation	Most likely the component with the specified ID was offline.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.

SPMPROE0003	**Script failed with status {0}**
Explanation	A fix script job failed with indicated status.
Action	Refer to the Software AG Update Manager log for more information.

SPMPROE0004	**Install fixes is not supported.**
Explanation	The requested feature is not supported yet.
Action	Use the runscript method to install fixes.

SPMPROE0005	**Nothing to install.**
Explanation	None of the artifacts exist in the specified repository.
Action	Use different artifacts or install from a different repository.

SPMPROE0006	**Install from local repository not supported.**
Explanation	The feature is not yet supported.
Action	Export artifacts from the repository into an image archive and install from the archive.

SPMPROE0007	**No repository found for {0}**
Explanation	The specified repository does not exist.
Action	Create the repository or use a different one.

SPMPROE0008	**Install from remote repository is not supported.**
Explanation	Installing from a remote repoitory is not supported.
Action	Create an image archive using installer client, and install from the archive.

SPMPROE0009	**Unable to process fix script.**
Explanation	Failures occurred processing a fix script.
Action	See the Software AG Update Manager logs and exception for failure details.

SPMPROE0010	**Invalid Type: {0}**
Explanation	The type of script is unrecognized. Valid types are either product, or fix.
Action	Use product or fix as the script type.

SPMPROE0011	**Uninstall of fixes is not supported by the uninstall method.**
Explanation	The operation is not supported.
Action	Use runscript to remove fixes.

SPMPROE0012	**Invalid artifact type: {0}**
Explanation	The artifact was not a product or fix artifact.
Action	Use a valid artifact.

SPMPROE0013	**Script failed with exit code {0}. See log at {1} for more information.**
Explanation	An installation script failed.
Action	Refer to the log for more details on the failure.

SPMPROE0014	**The provided configuration does not include the com.softwareag.plm.spm.provisioning.pathtosum property.**
Explanation	The property must be specifried in the configuration.
Action	Include a com.softwareag.plm.spm.provisioning.pathtosum property setting that references the Software AG Update Manager installation directory.

SPMPROE0016	**The com.softwareag.plm.spm.provisioning.pathtosum property does not reference an existing directory.**
Explanation	The property must reference the installation directory of Software AG Update Manager.
Action	Specify a valid directory.

SPMPROE0018 **Removal of ProvisioningService configuration is not supported.**

Explanation The ProvisioningService requires a configuration.

Action None required.

SPMPROE0020 **No such repository, {0}**

Explanation The install request specified a nonexistant repository.

Action Specify a valid repository ID.

SPMPROE0021 **No matching products to uninstall.**

Explanation The uninstall request specified products that are not installed.

Action Ensure that the correct product list or managed node is included in the request.

SPMPROE0022 **{0} is not in repository {1} or the required products {2} are not installed.**

Explanation The fix cannot be installed because it does not reside in the source repository or required products are not installed.

Action Specify a different fix repository. Verify with Update Manager if the fix can be resolved.

SPMPROE0023 **Multple fixes with id, {0}, reside in the repository {1}**

Explanation Platform Manager cannot determine which fix version to install.

Action Specify a complete version number for the fix (<fixname>_<version>).

SPMPROE0024 **Script failed with exit code {0}:{1}. See log at {2} for more details.**

Explanation The execution of the script failed.

Action Rerun script after resolving the errors listed in the log.

SPMPROE0025 **Script failed with status {0}: {1}**

Explanation The execution of the fix script failed.

Action Rerun the script after resolving the errors.

SPMPROE0026 **Unrecognized repository type: {0}**

Explanation The repository is not a supported type.

Action Use a valid repository type.

SPMPROE0027	**Unsupported repository. Use P2 enabled repository for provisioning artifacts.**
Explanation	Only P2 enabled repositories are supported.
Action	Use a P2 enabled repository for provisioning artifacts.

SPMPROE0028	**Artifact with id "{0}" and version "{1}" not found in the repositories {2}**
Explanation	The repositories do not contain any of the desired artifacts.
Action	Check the template and repository definitions.

SPMPROE0030	**Platform Manager restart failed.**
Explanation	The attempt at restarting Platform Manager failed.
Action	Check the Platform Manager logs.

SPMPROE0031	**Failed detecting Platform Manager Components.**
Explanation	The attempt to identify whether Platform Manager components (for example, the product plug-ins) are about to be provisioned has failed.
Action	Check the Platform Manager logs.

SPMPROE0032	**Platform Manager will be restarted.**
Explanation	Platform Manager will be restarted because Platform Manager components have been installed.
Action	Wait for Platform Manager to start. Check the logs for more details.

SPMPROE0048	**Could not uninstall products {0}. See sd-provisioning.log for details.**
Explanation	Could not uninstall products {0}.
Action	See sd-provisioning.log for more details.

SPMPROE0049	**Fixes {0} provided for uninstallation are not installed.**
Explanation	The fixes, provided for uninstallation are not found on the target installation.
Action	Provide only installed fixes for uninstallation.

SPMPROE0050	**The following fixes provided for uninstallation are not uninstallable: {0}**
Explanation	Some of the fixes, provided for uninstallation are not uninstallable.
Action	Provide only installed fixes which are uninstallable.

SPMPROI0000	**Fix installation completed with exit code: {0}**
Explanation	The fix script has completed with the indicated exit status.
Action	If status is nonzero, review the Software AG Update Manager logs for possible problems.

SPMPROI0001	**Launching: {0}**
Explanation	A fix script is being started in a separate process. The specific shell command is included in the message.
Action	None required.

SPMPROI0002	**Failed to launch fix script.**
Explanation	A scipt could not be launched. The associated job will be given an error status.
Action	Refer to the exception included in the message to resolve the problem.

SPMPROW0029	**{0} is not in repository {1} or the required products are not installed.**
Explanation	The fix cannot be installed because it does not reside in the source repository or required products are not installed.
Action	Specify a different fix repository. Verify with Update Manager if the fix can be resolved.

SPMREPE0000	**Unsupported operation.**
Explanation	The getContent operation is not supported for fix images.
Action	Use UpdateManager to view fixes.

SPMREPE0001	**Unsupported operation.**
Explanation	The import operation is only supported on local product repositories.
Action	None required.

SPMREPE0002	**Invalid configuration detected for repository, {0}**
Explanation	The location property of the repository is invalid. The configuration refers to a fix image, which must be a local file.
Action	Delete the configuration.

SPMREPE0003	**Repository not found at {0} for configuration, {1}**
Explanation	A configuration was found for a fix image repository that does not exist.
Action	Remove the configuration.

SPMREPE0004	**Unsupported operation.**
Explanation	The export operation is not supported for this artifact type or repository.
Action	None required.

SPMREPE0005	**Unsupported operation.**
Explanation	The repository type does not support dependencies.
Action	None required.

SPMREPE0006	**Unsupported operations.**
Explanation	Publishing is not supported for this repository type.
Action	None required.

SPMREPE0007	**Unable to parse canonical in {1}: {0}**
Explanation	The product properties could not be processed. The file is not a valid image archive.
Action	Use a valid image archive.

SPMREPE0008	**Importing of artifacts into an image archive is not supported.**
Explanation	Importing artifacts into an image archive is not supported.
Action	To create an image archive, use the export feature.

SPMREPE0009	**URI scheme for image archive repository, {0}, must be file**
Explanation	The repository configuration is invalid.
Action	Specify a local file as the archive location.

SPMREPE0010	**Repository not found at {0}**
Explanation	There is no archive at the specified location.
Action	Specify a valid location for the archive.

SPMREPE0011	**Exporting from images is not supported.**
Explanation	The function is not supported.
Action	None required.

SPMREPE0012	**Dependencies not available for image archives.**
Explanation	The function is not supported.
Action	Non required.

SPMREPE0013	**Publish feature is not supported for image archives.**
Explanation	Only local repositories may be published.
Action	None required.

SPMREPE0016	**Platform Manager cannot list product or fix repositories of release 9.7 or earlier.**
Explanation	The listing of product or fix repositories is not supported for releases 9.7 or earlier.
Action	Start the Software AG Installer and select the release that includes the products you want to see, or start the Software AG Update Manager and select the release and products that include the fixes you want to see.

SPMREPE0017	**Sandboxes are not modifiable.**
Explanation	Importing into sandboxes is not supported.
Action	None required.

SPMREPE0018	**Exporting from sandboxes is not supported.**
Explanation	The function is not supported.
Action	Use the installer client to export images from legacy sandboxes.

SPMREPE0019	**Dependencies not available for sandboxes.**
Explanation	The function is not supported.
Action	Use installer client to interact with legacy sandboxes.

SPMREPE0020	**Only local repositories can be published.**
Explanation	Sandboxes cannot be published.
Action	None required.

SPMREPE0021	**Unable to load/create repository at {0}**
Explanation	Platform Manager was not able to read the repository content.
Action	See to logs for more information. The repository may have been corrupted.

SPMREPE0024	**Unable to verify archive: {0} due to {1}**
Explanation	The file could not be verified as a ZIP archive.
Action	Ensure the path to the archive is correct.

SPMREPE0025	**The specified file {0} is not a valid image file.**
Action	To validate a product image, open the Software AG Installer and go to Advanced Options > Images. If necessary, re-create the {product | fix} image using the instructions in Using the Software AG Installer (product image) or Using the Software AG Update Manager (fix image), and then try again.

SPMREPE0026	**Local repository, {0}, has an invalid location: {1}**
Explanation	The repository configuration is invalid.
Action	Delete the configuration.

SPMREPE0027	**Unable to create repository at {0}**
Explanation	The repository could not be created.
Action	See the logs for more information.

SPMREPE0028	**Exporting of fixes is not supported.**
Explanation	The function is not supported.
Action	Use Software AG Update Manager to export fixes.

SPMREPE0037	**Unsupported operation.**
Explanation	getContent is not supported for remote fix repositories.
Action	Use Software AG Update Manager to view repository content.

SPMREPE0038	**Unsupported operation.**
Explanation	Import is not supported for remote fix repositories.
Action	Use Software AG Update Manager to manage fix repositories.

SPMREPE0039	**Unsupported operation.**
Explanation	Export is not supported for remote fix repositories.
Action	Use Software AGUpdate Manager to manage fix repositories.

SPMREPE0040	**Unsupported operation.**
Explanation	Dependencies not supported for remote fix repositories.
Action	Use Software AG Update Manager to manage fix repositories.

SPMREPE0041	**Unsupported operation.**
Explanation	Publish is not supported for remote fix repositories.
Action	Use Software AG Update Manager to manage fix repositories.

SPMREPE0042	**Unable to access SD Security Service.**
Explanation	The security service used to access remote repositories is not available.
Action	Try to restart the security service.

SPMREPE0043	**Unable to obtain security token for user, {0}, for the {1} repository.**
Explanation	The attempt to login to the SD security service failed.
Action	Ensure correct credentials are set for the repository.

SPMREPE0044	**Unable to load remote repository, {0}, due to {1}**
Explanation	A failure was detected attempting to access the repository.
Action	See the logs for more information.

SPMREPE0045	**Unsupported operation.**
Explanation	Importing into a remote repository is not supported.
Action	None required.

SPMREPE0047	**Unsupported operation.**
Explanation	Exporting from a remote repository is not supported.
Action	Import the artifacts into a local repository, then export from the local repository.

SPMREPE0048 **Unsupported operation.**

Explanation Publish is not supported for remote repositories. They are already published.

Action None required.

SPMREPE0049 **{0} not found in repository.**

Explanation The specifed artifact does not exist in the repository.

Action Verify that the correct artifact is used.

SPMREPE0050 **Unable to list repositories.**

Explanation Failures occurred while reading repository configuration.

Action Ensure read access is provided for repositories defined in the SPM profile.

SPMREPE0051 **Unable to list repositories.**

Explanation Failures occurred while reading repository configuration.

Action Ensure read access is provided for the repositories defined in the SPM profile.

SPMREPE0053 **Location can not be null.**

Explanation When adding a new repository configuration, the location property must be provided.

Action Provide a location for the repository being configured.

SPMREPE0054 **Invalid content type: {0}**

Explanation The type of a repository must be either product or fix.

Action Provide a valid repository type.

SPMREPE0055 **Repository already configured for {0}**

Explanation A repository at this location is already configured.

Action None required.

SPMREPE0057 **{0} is an invalid path.**

Explanation The location cannot be represented as a valid URI.

Action Use a valid path.

SPMREPE0058 **Location does not exist: {0}**

Explanation There is no fix image archive at the specified location.

Action Provide the location of an existing fix image archive.

SPMREPE0062 **Unable to delete configuration properties: {0}**

Explanation The configuration properties for a repository could not be deleted.

Action Manually delete the property file.

SPMREPE0064 **Must specify repository type.**

Explanation The type argument for listing repositories cannot be null.

Action Specify the repository type, either product or fix.

SPMREPE0065 **No such repository - {0}**

Explanation There is no repository with the given ID.

Action Use a known repository configuration.

SPMREPE0066 **Source and destination arguments cannot be null.**

Explanation Both source and destination arguments must be specified for the import operation.

Action Provide valid source and destination repository arguments.

SPMREPE0067 **No such repository registered, {0}**

Explanation The source repository for the import operation does not exist.

Action Provide a valid source repository argument.

SPMREPE0068 **No such repository registered, {0}**

Explanation The destination repository for the import operation does not exist.

Action Provide a valide destination repository.

SPMREPE0069 **Incompatable repositories.**

Explanation The source and destination repositories must have the same content type.

Action Ensure that both repositories are either product, or fix repositories.

SPMREPE0070	**Cannot import into remote repository, {0}**
Explanation	Importing into remote repositories is not supported.
Action	Specify a local repository as the destination.

SPMREPE0071	**Unable to create path to provisioning configuration: {0}**
Explanation	Unable to create provisioning configuration directory.
Action	Ensure that the Platform Manager configuration directory is writable.

SPMREPE0072	**Invalid repository type: {0}**
Explanation	The repository type must be product or fix.
Action	Specify a valid repository type.

SPMREPE0073	**No repository name provided.**
Explanation	A repository name must be provided for discovering fix repositories.
Action	Provide the repository name.

SPMREPE0074	**Invalid server or repository name: {0}**
Explanation	The server or name arguments contain invalid characters for a URL.
Action	Specify valid server and names for the fix repository.

SPMREPE0075	**Repository discovery failed: No ProductRepositoryManagementService available**
Explanation	Unable to discover product repositories as the necessary services are not active.
Action	See the logs to determine why the repository manager service is inactive.

SPMREPE0076	**Cannot connect to Software AG repository: {0}**
Action	Make sure the Platform Manager has Internet access and the proxy configuration is present and correct. You can also check the logs for the Platform Manager. Then try again to connect.

SPMREPE0077	**Source repository cannot be null.**
Explanation	A source repository must be specified for the export operation.
Action	Specify the local repository to use for export.

SPMREPE0078	**Path cannot be null.**
Explanation	The path to the destination archive must be specified for the export operation.
Action	Provide a path where the archive should be created.

SPMREPE0079	**No such repository registered, {0}**
Explanation	There is no repository with the given ID.
Action	Specify a valid source repository.

SPMREPE0080	**Unsupported operation.**
Explanation	Platform Manager cannot export from archive.
Action	Specify a local repository from which to export.

SPMREPE0081	**Cannot export into existing file: {0}**
Explanation	Exporting cannot be used to add to an existing archive.
Action	Specify the location to create a new archive.

SPMREPE0082	**Artifact must be specified.**
Explanation	An artifact argument for get dependencies was null.
Action	Specify the artifact for its list of dependecnies.

SPMREPE0083	**Source repository cannot be null.**
Explanation	The source repository for get dependencies cannot be null.
Action	Specify a valid repository in which to search for dependencies.

SPMREPE0084	**No such repository registered, {0}**
Explanation	The specified repository does not exist.
Action	Specify a valid repository in which to search for dependencies.

SPMREPE0085	**No such repository: {0}**
Explanation	The specified repository does not exist.
Action	Specify a valid local repository to publish.

SPMREPE0086	**Source and destination repositories are the same.**
Explanation	The source and destination repositories must refer to different repositories.
Action	Specify valid repositories.

SPMREPE0087	**{0} not found in repository.**
Explanation	The specifed artifact does not exist in the repository.
Action	Verify that the correct artifact is used.

SPMREPE0088	**Unsupported operation.**
Explanation	The publishing of local repositories is not supported in this release.
Action	None required.

SPMREPE0089	**Unsupported operation.**
Explanation	The unpublish operation is not supported for repository type.
Action	None required.

SPMREPE0090	**No such repository registered, {0}**
Explanation	The specified repository is not registered.
Action	Specify a valid repository, or add the repository.

SPMREPE0091	**Failures occurred attempting to publish a repository: {0}**
Explanation	Internal errors prevented the publish operation from completing.
Action	Depends on the specific error. Check the logs for the error details.

SPMREPE0092	**The repository, {0}, is already published with context, {1}**
Explanation	Specify the correct repository or republish to use a different context.
Action	To change context, unpublish, then republish with new context.

SPMREPE0093	**Web publishing service is unavailable.**
Explanation	The necessary service to publish repositories is not active.
Action	None required.

SPMREPE0094	**Invalid context: {0}**
Explanation	The context in the publish request may not be null and must start with /
Action	Check if the context of the publish request is null and verify that it starts with /

SPMREPE0095	**Invalid context: {0}**
Explanation	The context must not be null and start with /
Action	Use a valid context.

SPMREPE0096	**Repository {0}, is not published.**
Explanation	The request assumes the repository has been published.
Action	None required.

SPMREPE0097	**Failures detected while unpublishing repository: {0}**
Explanation	The unpublishing operation failed.
Action	Depends on the type of failure. Check the logs for the error details.

SPMREPE0098	**No credentials for accessing the remote fix repository, {0}, have been configured.**
Explanation	You must provide user credentials to access remote repositories.
Action	Specify the user and password properties for the repository.

SPMREPE0099	**The location of a repository is invalid: {0}**
Explanation	The URI of a repository does not have a valid path.
Action	Specify a valid location when registering repositories.

SPMREPE0100	**No repository found at the specified location: {0}**
Explanation	The location specified did not match any known repository.
Action	Specify a valid location.

SPMREPE0101	**No fix service available.**
Explanation	A required service for managing fix repositories is unavailable.
Action	Review the Platform Manager logs for indications of fix service failures.

SPMREPE0103	**{0} is an invalid path. It must be relative.**
Explanation	To create a new local repository, you must use only relative paths.
Action	Specify a relative path.

SPMREPE0104	**Login to repository, {1}, failed for user, {0},**
Explanation	Repository configured with incorrect credentials.
Action	Reconfigure the repository credentials.

SPMREPE0105	**Only one platform may be specified in the provided filter .**
Explanation	The repository operation included a filter with multiple platforms.
Action	Specify only one platform in the filter and retry the operation.

SPMREPE0106	**The repository, {0}, is currently in use.**
Explanation	The operation cannot be processed until the specified repository becomes available.
Action	Retry when all provisioning operations are completed.

SPMREPE0107	**Failed to load repository, {0}**
Explanation	An error occurred while attempting to access the repository.
Action	Check the logs for the error details.

SPMREPE0108	**Publish with non-default realm or roles is not supported.**
Explanation	The requested operation is not supported.
Action	Retry the request without specifying a realm or roles.

SPMREPE0109	**{0} is not in repository {1}**
Explanation	Unable to export the specified fix into the archive because the fix does not reside in the source repository.
Action	Specify a different fix or repository.

SPMREPE0110	**Invalid SDC installer properties.**
Explanation	The servers/production/versions property in the server.properties file is missing.
Action	This is an internal error and should be reported. Contact Software AG Global Support.

SPMREPE0111 **No such repository, {0}**

Explanation The specified repository is not registered.

Action Specify an valid repository, or create one.

SPMREPE0112 **Unsupported operation.**

Explanation The getReadme operation is not supported by the repository.

Action Specify an appropriate repository.

SPMREPE0113 **Unable to load remote repository {0}. The server returned null result.**

Explanation The attempt to load to the specified remote repository failed.

Action Ensure that the correct repository metadata is provided and try again.

SPMREPE0114 **Update Manager threw unexpected exception: {0}.**

Explanation Update Manager threw unexpected exception: {0}.

Action Check the Update Manager installation.

SPMREPE0115 **Login failed for user: {0} and location: {1}**

Explanation The login operation failed for user: {0} and location: {1}

Action Provide valid credentials and valid repository location.

SPMREPE0116 **The Repository Validation parameter should not be null.**

Explanation The Repository Validation parameter should not be null.

Action Provide a valid (not null) Repository Validation parameter.

SPMREPE0117 **The repository path should not be empty.**

Explanation The repository path should not be empty.

Action Provide a valid non-empty repository path.

SPMREPE0118 **The provided username or password should not be empty.**

Explanation The username or password should not be empty.

Action Provide non-empty valid username or password.

SPMREPE0119	**Fixes repository validation failed.**
Explanation	The fixes repository validation failed.
Action	Analyze the error and provide valid input.

SPMREPE0120	**Products repository validation failed.**
Explanation	The products repository validation failed.
Action	Analyze the error and provide valid input.

SPMREPE0121	**Trusted authentication failed while trying to log in {0} repository.**
Explanation	Connecting to the specified repository using trusted authenticaion failed.
Action	See the Platform Manager wrapper log for more details.

SPMREPE0122	**Repository {0} not found.**
Explanation	The specified repository is not registered.
Action	Check the repository name or register a repository with the same name.

SPMREPE0123	**Dependencies resolution failed. {0}**
Explanation	The dependencies resolution of the selected products failed.
Action	Try to correct the issue and retry the operation.

SPMREPE0124	**Artifact with id "{0}" and version "{1}" not found in the repositories {2}.**
Explanation	The repositories do not contain any of the required artifacts.
Action	Check the template and the repository definitions.

SPMREPE0125	**Dependencies resolution failed. {0} Possible runtimes are {1}.**
Explanation	The dependencies resolution of the selected products failed because a product can be installed on multiple runtimes.
Action	Choose the runtime you would like to use and discard the others.

SPMREPE0126	**The specified products {0} are not found in the product repository {1}.**
Explanation	The specified products {0} are not found in the product repository {1}.
Action	Verify that the correct product codes are used.

SPMREPE0127	**Product mirror operation into {0} repository failed with status : {1}**
Explanation	Importing products into the mirror repository failed.
Action	See the products' sd-provisioning.log for more information.

SPMREPE0128	**Failing Fix Mirror Repository operation: {0}**
Explanation	{0}
Action	For more details check the Update Manager logs.

SPMREPE0129	**Failed to obtain fix dependencies. {0}**
Explanation	No additional information.
Action	Check if the specified fix dependency is a valid fix and if it exists in the repository.

SPMREPE0130	**The mirror repository with name {0} is not found.**
Explanation	The repository with name {0} either does not exists, or is not a mirror repository.
Action	Use an existing mirror repository, or create a new one with the specified name.

SPMREPE0131	**Mirror repository validation failed. {0}**
Explanation	The mirror repository checksum validation failed. The repository is corrupted.
Action	Remove the mirror repository and create it again.

SPMREPI0014	**Importing into {0}**
Explanation	Importing of artifacts is starting.
Action	None required.

SPMREPI0015	**Import failed: {0}**
Explanation	An import operation failed.
Action	See the installation log for more information.

SPMREPI0023	**Creating local repository at {0}**
Explanation	A new local repository is being created.
Action	None required.

SPMREPI0029	**No matching products found in {0} repository**
Explanation	The request to mirror a repository is ignored as none of the specified artifacts reside in the repository.
Action	None required.

SPMREPI0030	**Import from {0} to {1} failed.**
Explanation	The import operation failed.
Action	See the logs for more information.

SPMREPI0031	**Importing all products from {0} to {1}**
Explanation	All products in the source repository will be imported.
Action	None required.

SPMREPI0032	**Importing products fro {0} to {1}**
Explanation	A subset of products is being imported. The specific products are listed as subsequent log entries.
Action	None required.

SPMREPI0033	**{0}**
Explanation	The id of a product being imported.
Action	None required.

SPMREPI0034	**Import from {0} to {1} was successful.**
Explanation	The import operation completed successfully..
Action	None required.

SPMREPI0035	**Exporting artifacts from {0} to {1}**
Explanation	An export operation is starting.
Action	None required.

SPMREPI0036	**Export from {0} to {1} failed due to {2}**
Explanation	The export operation failed.
Action	See the logs for more information.

SPMREPI0056 **The configuration of repository {0} has an invalid location property: {0}**

Explanation The location property is not a valid URI.

Action Remove the repository.

SPMREPI0059 **Unable to add repository {0}.**

Explanation The location is an invalid URL.

Action Noe required.

SPMREPI0060 **Unable to add repoistory {0}.**

Explanation The attempt to configure the remote repository failed.

Action See the logs for more information.

SPMREPI0061 **Failures occurred during removal of repository {0}.**

Explanation The repository configuration may not have been completely removed.

Action See the logs for further information.

SPMREPI0063 **Removed repository configuration, {0}**

Explanation The repository was successfully removed.

Action None required.

SPMREPW0022 **Unable to delete {0}**

Explanation The directory of the local repository to be created was not empty.

Action None required.

SPMREPW0046 **Failed to remove password handle for repository, {0}**

Explanation Cleanup of passman data was incomplete while removing the repository.

Action None required.

SPMREPW0052 **Unable to initialze repository {0}.**

Explanation The repository could not be validated.

Action Remove the repository configuration.

SPMREPW0102	**Failed to remove password handle for repository, {0}**
Explanation	The passman cleanup was incomplete.
Action	None required.

SPMRMCE0001	**Invalid input data.**
Explanation	The submitted data failed to un-marshal or validate against the schema.
Action	Correct the reported problem in the input data and retry the request.

SPMRMCE0002	**Internal Error processing the request.**
Explanation	The server encountered an error and cannot execute the request.
Action	Contact your system administrator.

SPMRMCE0003	**Invalid client request.**
Explanation	The submitted client request is rejected by the server.
Action	Check the status code for more details or consult the Software AG Platform Manager documentation. Correct the problem and resubmit the request.

SPMRMCE0005	**The requested functionality is not supported.**
Explanation	Platform Manager does not support the requested functionality.
Action	See the Software AG Platform Manager documentation for the supported requests for this resource.

SPMRMCI0000	**Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:**
Explanation	The configuration operation for the specified run-time component, instance, and type failed with the specified exception.
Action	Check the logs for the error details.

SPMRPIE0000	**Use RepositoryService to create new repository configurations.**
Explanation	The ConfigurationService cannot be used to add repository configurations.
Action	Use the RepositoryService to configure new repositories.

SPMRPRE0000	**Invalid filter specification.**
Explanation	A request was made that included a product filter and the useInventory option.
Action	Resubmit with the appropriate filter. Use either a product list or the useInventory option, not both at the same time.

SPMRPRE0001	**No repository with id, {0}, and type, {1} exists**
Explanation	The request references a non-existant repository.
Action	Specify the correct repository ID and/or type.

SPMSCOE0000	**No Credentials in Data Store for handle: {0}**
Explanation	Searching for exact credentials match does not return results.
Action	Search again for existing credentials.

SPMSCOE0001	**No Credentials available in Secured Store for handle: {0}**
Explanation	Searching for exact credentials match does not return results.
Action	Search again for existing credentials.

SPMSURE0000	**Some of the required properties for retrieving a UiBinding are not provided. Please provide values for {0} and a value for one of {1}.**
Explanation	Some of the required properties for retrieving a UiBinding are not provided.
Action	Provide the full set of required properties.

SPMSURE0002	**Could not transfer the file to the target destionation {0}. Reason: {1}.**
Explanation	The file could not be transfered due to an error.
Action	Check if the target host has enough disk space or the provided file name is valid.

SPMSURW0001	**Some of the required properties for retrieving a UiBinding are not provided. Provide values for {0}.**
Explanation	Some of the properties required for retrieving a UiBinding are not provided.
Action	Provide the full set of required properties.

SPMTEME0000	**Error occurred while reading the configuration instances for {0}**
Explanation	The error occurred while creating a template that includes configuration information.
Action	Check whether the configuration instances for the specified runtime component are available by querying them explicitly. Check the logs for errors if the query fails.

SPMTEME0001	**Error occurred while applying template {0}**
Explanation	The error occurred when applying the specified template.
Action	Check the logs for more details.

SPMTEME0006	**Error occurred during template creation {0}**
Explanation	The error occurred when creating a template.
Action	Check the logs for more details about the error.

SPMTEME0012	**Error occured while executing a task with id: {0} and status: {1}**
Explanation	Executing the specified task failed.
Action	Check the Platform Manager logs for more information.

SPMTEME0014	**Deleting configuration instance with type {0} is not supported operation.**
Explanation	Platform Manager does not support deleting the configuration instance with the specified type.
Action	Check the warning to determine if any damage to the system will occur.

SPMTEME0015	**Skipping deleting configuration instance ({0}) for runtime component - {1}. Reason: {2}**
Explanation	The error occurred because either the runtime component, or a configuration manager for the configuration instance is missing in the Platform Manager.
Action	Check if the specified runtime component is present or that the appropriate SPM plugin is installed. Check the warning to determine if any damage to the system will occur.

SPMTEME0016	**Skipping deleting configuration instance ({0}) for the missing runtime component - {1}**
Explanation	The specified runtime component is missing in the Platform Manager.
Action	Check if the specified runtime component is present in the Platform Manager. Check the warning to determine if any damage to the system will occur.

SPMTEME0017	**Task with id: {0} and status {1} did not finish in the expected period of time.**
Explanation	The timeout period, configured through a system property, is not sufficient to complete the task.
Action	Try to execute the operation again or increase the timeout value.

SPMTEME0018	**Task with id: {0} and status: {1} was canceled.**
Explanation	The execution of the operation is interrupted.
Action	Try to execute the operation again.

SPMTEME0019	**Error occurred during execution of operation {0} on template {1}**
Explanation	The error occurred when executing the specified operation.
Action	Check the logs for more details about the error.

SPMTEME0020	**The repository cannot be empty.**
Explanation	A repository should be specified in order to apply the template.
Action	Specify a repository to be used for applying the template.

SPMTEME0021	**The required services are not initialized.**
Explanation	The services required for applying are template are not initialized.
Action	Check whether all required bundles are started.

SPMTEME0022	**Template alias cannot be empty.**
Explanation	Template alias must be specified when creating or applying a template.
Action	Specify a template alias.

SPMTEME0023	**Template metadata cannot be empty.**
Explanation	Template metadata must be specified when creating or applying a template.
Action	Specify template metadata.

SPMTEME0024	**Template options cannot be empty.**
Explanation	Template options should be specified when creating or applying a template.
Action	Specify template options.

SPMTEME0025	**The provided template or template metadata does not contain any products.**
Explanation	A request to install products is made, however, the template or the template metadata does not contain any products.
Action	Check whether the template operation request is correct.

SPMTEME0026	**Fix Installation properties cannot be empty.**
Explanation	Fix Installation properties cannot be empty.
Action	Specify fix installation properties.

SPMTEME0027	**Arguments can not be null.**
Explanation	Neither of the arguments can be null.
Action	Specify proper arguments.

SPMTEME0028	**The script for this template is empty.**
Explanation	The script that is used for provisioning of this template is empty.
Action	Provide proper arguments to ensure successful generation of the script.

SPMTEME0029	**The provided template does not have a script for the specified type.**
Explanation	The template does not support the specified provisioning operation.
Action	Check the template metadata for discrepancy.

SPMTEME0030	**Job cannot be null.**
Explanation	An issue occurred during a template operation.
Action	Contact Software AG Global Support.

SPMTEME0031	**Configuration instance {0} threw unexpected exception during processing.**
Explanation	The composite template encountered and error while processing configuration instance {0}. This behavior is to be expected in some cases, for example when the run-time component on which the configuration is applied is not up and running.
Action	No action required. The composite template retries the configuration operation automatically. Check the final job log after the last retry.

SPMTEME0032	**The thread was interrupted while waiting for runtime status.**
Explanation	During the apply template configuration operation, the checking of the runtime status of a component was interrupted.
Action	Check the logs for JVM errors.

SPMTEME0033	**Exception occurred while getting runtime status.**
Explanation	An exception occured during the apply template configuration operation, when checking the runtime status of a component.
Action	Check the SPM logs for system errors

SPMTEME0034	**The thread was interrupted while setting runtime status.**
Explanation	During the apply template configuration operation, the checking of the runtime status of a component was interrupted.
Action	Check the logs for JVM errors

SPMTEME0035	**Applying template was interrupted.**
Explanation	The thread applying the template was interrupted.
Action	Check the logs for more details.

SPMTEME0036	**Can not retrieve the imported template: {0}**
Explanation	Platform Manager can not retrieve the imported template: {0}
Action	Check the imported template metadata for inconsistent entries.

SPMTEME0037	**The template file can not be deleted.**
Explanation	The template file can not be deleted.
Action	Ensure that the template file is not locked on the file system.

SPMTEME0038	**The provided template alias should not be null.**
Explanation	The provided template alias should not be null.
Action	Provide a valid, non-null template alias.

SPMTEME0039	**Can not retrieve the imported template metadata: {0}**
Explanation	Can not retrieve the imported template metadata: {0}
Action	Check the imported template metadata for inconsistent entries.

SPMTEME0040	**Waiting for product with Id: {0} is interrupted.**
Explanation	Waiting for product with Id: {0} is interrupted.
Action	Double-check the logs for more details related to this error.

SPMTEME0047	**Configuration Type {0} does not support "text/plain" representation. Use JSON or XML.**
Explanation	The configuration data contained in the template is not in the expected format.
Action	Change the configuration definition in the template.

SPMTEME0048	**Could not deserialize Configuration Instance {0} for Runtime Component {1} having Configuration Type {2}.**
Explanation	The Configuration Data contained in the Template is not in the expected format.
Action	Change the Configuration definition in the Template.

SPMTEMW0002	**Applying the template completed with the following warnings: {0}**
Explanation	When applying a template, unexpected events occurred, but they did not prevent the process from executing.
Action	Check the warnings with extra caution to determine whether any damage to the system will occur.

SPMTEMW0003	**Skipping creating configuration instance ({0}) for the missing runtime component - {1}**
Explanation	The specified runtime component is missing in the specified Platform Manager.
Action	Check if the specified runtime component is present. Check the warning to determine if any damage to the system will occur.

SPMTEMW0004	**Skipping creating configuration instance ({0}) for runtime component - {1}. Reason: {2}**
Explanation	The error occured because either the runtime component, or a configuration manager for the configuration instance is missing in the specified Platform Manager.
Action	Check if the specified runtime component is present and that the appropriate Platform Manager plugin is installed. Check the warning to determine if any damage to the system will occur.

SPMTEMW0005	**Creating configuration instance with type {0} is not supported operation.**
Explanation	Platform Manager does not support the create operation for the configuration instance with the specified type.
Action	Check the warning to determine if any damage to the system will occur.

SPMTEMW0007	**Skipping updating configuration instance ({0}) for the missing runtime component - {1}**
Explanation	The specified runtime component is missing in the Platform Manager.
Action	Check if the specified runtime component is present. Check the warning to determine if any damage to the system will occur.

SPMTEMW0008	**Template operation "{1}" completed with the following warnings: {0}**
Explanation	During template operation "{1}" unexpected events occurred but they did not prevent the operation from completing.
Action	Check the warnings to figure out what was successfully processed as part of operation "{1}".

SPMTEMW0009	**Skipping updating configuration instance ({0}) for runtime component - {1}. Reason: {2}**
Explanation	The error occurred because either the runtime component, or a configuration manager for the configuration instance is missing in the Platform Manager.
Action	Check if the specified runtime component is present or that the appropriate Platform Manager plugin is installed. Check the warning to determine if any damage to the system will occur.

SPMTEMW0010	**Skipping storage of item with id : {0} . Reason : {1}**
Explanation	The issue occured during item serialization.
Action	Check the Platform Manager logs for more information about the error.

SPMTEMW0011	**Updating configuration instance with type {0} is not supported operation.**
Explanation	Platform Manager does not support updating the configuration instance with the specified type.
Action	Check the warning to determine if any damage to the system will occur.

SPMTEMW0013	**Skipping storage of configuration instance ({0}) for runtime component - {1}. Reason: {2}**
Explanation	An error occurred while loading the configuration instance and it will not be included in the template that will be created.
Action	Check the logs for more details about the error.

SPMTEMW0046	**Reserved instance name {0}.**
Explanation	Instance name {0} is reserved for internal use only.
Action	Use a different instance name.

SPMTERE0000	**Template log file not available.**
Explanation	The Platform Manager log access service was unable to locate the template log file.
Action	Contact Software AG Global Support.

SPMTERE0001	**Installer and Update Manager logs unavailable.**
Explanation	The Installer or Update Manager logs cannot be located.
Action	Contact Software AG Global Support.

SPMUTLE0000	**Invalid URL.**
Explanation	The URL does not fit the specification.
Action	Specify a valid URL.

SPMUTLE0001	**URL string cannot be parsed as a URI reference**
Explanation	The URL does not fit the specification.
Action	Specify a valid URL.

SPMUTLE0002	**Problem with saglicutil execution.**
Explanation	The saglicutil utility cannot be started.
Action	Contact Software AG Global Support.

SPMUTLE0003	**Error occurred: Saglicutil verifier tool is missing!**
Explanation	The saglicutil verifier tool is not found at the expected location.
Action	Contact Software AG Global Support.

SPMUTLE0004	**Unable to collect NetworkInterface details; caught this: type({0}), msg({1})**
Explanation	An attempt to use java.lang.NetworkInterface to collect MAC address information failed.
Action	Determine whether the current user has permission to collect this information.

SPMUTLE0005	**Collected {0} MAC addresses before failure.**
Explanation	This message will always be logged with SPMULTLE0004
Action	No action required.

SPMUTLE0006	**Error occurred: Execution of saglicutil verifier tool failed!**
Explanation	The execution of the saglicutil verifier tool may fail due to the latest Windows patches not being installed or due to a corrupted installation environment.
Action	Ensure that the latest Windows patches are installed or contact Software AG Global Support.

SPMUTLE0007	**Error occurred: Processor core type information is missing!**
Explanation	The saglicutil verifier tool does not provide the processor core type information.
Action	Contact Software AG Global Support.

SPMUTLE0008	**Error occurred: Processor core count information is missing!**
Explanation	The saglicutil verifier tool does not provide the processor core count information.
Action	Contact Software AG Global Support.

SPMUTLW0009	**Abnormal termination of command {0} with result {1}**
Explanation	The internal command execution returned non-zero exit code.
Action	No user action is required.

SPMWTNE0000	**Integration Server password was not provided**
Explanation	The password is a required field.
Action	Provide an Integration Server password.

SPMWTNE0001	**Integration Server URL is not valid**
Explanation	The Integration Server URL is malformed
Action	Check that your Task Engine configuration values for host, port, username and password are valid.

SPMWTNE0002	**Only BASIC authentication is supported**
Explanation	The provided authentication is not supported.
Action	Change authentication to BASIC.

SPMWTNE0009	**No Integration Server credentials were provided**
Explanation	The connection to Integration Server cannot be validated without proper credentials.
Action	Provide values for username and password.

SPMWTNE0014	**Integration Server host, port, and/or connection protocol were not provided**
Explanation	The Integration Server host, port, and connection protocol are required values.
Action	Provide values for host, port, and connection protocol.

SPMWTNISE0000	**My webMethods Server password was not provided.**
Explanation	The password is a required field.
Action	Provide a password for My webMethods Server.

SPMWTNISE0001	**An error occurred during a call to wm.task.taskclient:getConfig. The error reported is: {0}.**
Explanation	An error occurred during the service call to write the configuration settings to WmTaskClient. The error might be caused by accessing the IntegrationServer\\packages\\WmTaskClient\\config\\tascklient.properties file. This message will also occur if the file was initially not present and the service call to write the configuration settings created the file and populated it with default values.
Action	Make sure that the IntegrationServer\\packages\\WmTaskClient\\config\\tascklient.properties file is present, contains name\=value pairs, and the name\=value pairs are valid. Note: This message will also occur if the file was initially not present and the service call to write the configuration settings created the file and populated it with default values. Check that the name-value pairs are acceptable for your configuration.

SPMWTNISE0002	**Only BASIC authentication is supported**
Explanation	The specified authentication is not supported.
Action	Change authentication to BASIC.

SPMWTNISE0003	**The My webMethods Server URL is not valid.**
Explanation	The URL for pinging My webMethods Server is not valid.
Action	Check that your WmTaskClient configuration values for host, port, username and password are valid.

SPMWTNISE0009	**No My webMethods Server credentials were provided.**
Explanation	The connection to My webMethods Server cannot be validated without proper credentials.
Action	Specify values for username and password.

SPMWTNISE0011	**The password is required.**
Explanation	You must specify a password.
Action	Specify a password.

SPMWTNISE0014	**The My webMethods Server host, port, and/or connection protocol were not provided.**
Explanation	You must specify values for the My webMethods Server host, port, and connection protocol.
Action	Specify values for host, port, and connection protocol.

23 Process Engine Messages

JL.execution(PRTMessageConstants.AA_CASE_CREATE) – {1}, {2}: Created Case with id {0}

JL.execution(PRTMessageConstants.AA_CASE_ERROR) – {1}, {2}: Failed to create case: {0}

JL.execution(PRTMessageConstants.AA_CASE_RESPONSE) – Received message from AgileApps: {0}

JL.execution(PRTMessageConstants.AA_CASE_UNK_STATUS) – {1}, {2}: Received status from AgileApps: {0}

JL.execution(PRTMessageConstants.AA_NO_CASE_RECORD_ID) – {0}: Case creation was unsuccessful. AgileApps returned status: {1} and error message: {2}

JL.execution(PRTMessageConstants.AA_PROCESS_RESPONSE) – {1}: Sending message to AgileApps: {0}

JL.execution(PRTMessageConstants.AL_ERRPUB_OPTIMIZE) – {1}: exception publishing Optimize log event {2}: {0}

JL.execution(PRTMessageConstants.AL_ERRPUB_OPTIMIZE_STEP) – {1}, {2}: exception publishing Optimize log event {3}: {0}

JL.execution(PRTMessageConstants.AL_ERR_GET_AUDIT_RUNTIME) – {1}: exception getting audit runtime: {0}

JL.execution(PRTMessageConstants.AL_ERR_GET_STACK) – {1}, {2}: exception retrieving process stack: {0}

JL.execution(PRTMessageConstants.AL_NO_MID_FOR_PID) – {1}: exception getting model identifier: {0}

JL.execution(PRTMessageConstants.AL_PIPEERR_STEP0) – {1}, {2}: exception trying to encode step pipeline: {0}

JL.execution(PRTMessageConstants.DUPLICATE_TASK_CALLBACK) – {0}, {1}: ignoring duplicate callback from Task Engine for TaskId {2}.

JL.execution(PRTMessageConstants.EP_ERRPUB_EDA) – {1}, {2}: exception publishing EDA Event: {0}

JL.execution(PRTMessageConstants.EP_PIPEERR0) – {1}, {2}: exception encoding transition pipeline to {3}: {0}

JL.execution(PRTMessageConstants.EP_SENDTX0) – {0}, {1}: sending live transition to {2}

JL.execution(PRTMessageConstants.EP_SENDTX0_DEADPATH) – {0}, {1}: sending dead transition to {2}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_CASE_CONTROL) – {0}: publishing case control event to AgileApps with control "{1}"

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_CHANGE) – {0}: sending process instance change EDA Event: {1}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_ERROR) – {0}: sending process error EDA Event: {1}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_LOG_CUSTOM_ID) – {0}: sending process log custom id EDA Event: {1}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_LOG_MESSAGE) – {0}: sending process log message EDA Event: {1}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_STEP_CHANGE) – {0}, {1}: sending process step instance change EDA Event: {2}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_STEP_ERROR) – {0}, {1}: sending process step error EDA Event: {2}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_STEP_LOOP_CHANGE) – {0}, {1}: sending process step loop instance change EDA Event: {2}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_STEP_TRANSITION) – {0}, {1}: sending process step instance transition EDA Event: {2}

JL.execution(PRTMessageConstants.IL_ERR_CREATE_LOGGER) – {1}: exception creating instance logger: {0}

JL.execution(PRTMessageConstants.IM_CANCELLEDOK) – {0}, MID={1}, MVer={2}: process cancelled

JL.execution(PRTMessageConstants.IM_CREATEOK) – {0}, MID={1}, MVer={2}: process started

JL.execution(PRTMessageConstants.IM_FAILEDOK) – {0}, MID={1}, MVer={2}: process failed

JL.execution(PRTMessageConstants.IM_FINISHOK) – {0}, MID={1}, MVer={2}: process completed

JL.execution(PRTMessageConstants.IM_RECREATE) – {0}, MID={1}, MVer={2}: process restarting

JL.execution(PRTMessageConstants.IM_SVC_CANCEL_TX) – {0}, {1}: transitioning to cancel step

JL.execution(PRTMessageConstants.IM_TRYCREATE0) – {0}, {1}: new process instance created on {2}

JL.execution(PRTMessageConstants.IM_TRYCREATE2) – {0}, {1}: using existing pid on {2}

JL.execution(PRTMessageConstants.IM_UPDATE_TRACK) – {0}: updated track count by {1} to {2}

JL.execution(PRTMessageConstants.IS_RETRYLIMIT) – {0}, {1}: step level retry count exceeded for service: {2}

JL.execution(PRTMessageConstants.IS_SVC_RETRY) – {1}, {2}: step level retry {3} of {4} in {5} ms: {0}

JL.execution(PRTMessageConstants.IS_THRESHOLD) – {0}, {1}: thread threshold detected; retry abandoned

JL.execution(PRTMessageConstants.PRT_EXCEPTION) – Exception: {0}

JL.execution(PRTMessageConstants.SDA_AFTER_STEP_PIPE) – {0}, {1}: after step pipeline: {2}

JL.execution(PRTMessageConstants.SDA_BEFORE_STEP_PIPE) – {0}, {1}: before step pipeline: {2}

JL.execution(PRTMessageConstants.SDA_BEFORE_STEP_PIPE)...0 – {0}, {1}: before step pipeline: {2}

JL.execution(PRTMessageConstants.SDA_CHANGE_VERSION) – {0}, {1}: process version changed from {2} to {3}

JL.execution(PRTMessageConstants.SDA_DEAD_INGORED) – {0}, {1}: synchronization point ignoring dead path from {2}

JL.execution(PRTMessageConstants.SDA_DYNAMIC_CALL_ACTIVITY_STARTED) – {0}, {1}: Dynamic call activity step instantiated the following models:{2}

JL.execution(PRTMessageConstants.SDA_DYNAMIC_CALL_ACTIVITY_STARTED_MODEL_NOT_WAITING) – {0} {1} instance(s) (not waiting for return)

JL.execution(PRTMessageConstants.SDA_DYNAMIC_CALL_ACTIVITY_STARTED_MODEL_WAITING) – {0} {1} instance(s) (waiting for return)

JL.execution(PRTMessageConstants.SDA_DYNAMIC_CALL_ACTIVITY_WAIT) – {0}, {1}: {2} of {3} callable instances completed

JL.execution(PRTMessageConstants.SDA_ERR_GENERAL) – {1}, {2}: exception executing step: {0}

JL.execution(PRTMessageConstants.SDA_ERR_HANDLEEVT_CHANGE) – {1}: exception failing the process: {0}

JL.execution(PRTMessageConstants.SDA_ERR_OUT) – {1}, {2}: exception sending output {3} of {4}: {0}

JL.execution(PRTMessageConstants.SDA_ERR_SAVECTX) – {1}, {2}: exception saving step context: {0}

JL.execution(PRTMessageConstants.SDA_ERR_TX) – {1}, {2}: exception updating track count: {0}

JL.execution(PRTMessageConstants.SDA_EVAL0) – {0}, {1}: transition condition {2} evaluated to {3}

JL.execution(PRTMessageConstants.SDA_EVALF) – {0}, {1}: transition condition {2} is False

JL.execution(PRTMessageConstants.SDA_EVALT) – {0}, {1}: transition condition {2} is True

JL.execution(PRTMessageConstants.SDA_EXC_SEND_DEAD_PATH) – {1}, {2}: unable to send dead path transition with the following exception: {0}

JL.execution(PRTMessageConstants.SDA_INVALID_STEP) – {1}, {2}: deprecated step found: {0}

JL.execution(PRTMessageConstants.SDA_LOGCUST) – {0}, {1}: logging custom audit data

JL.execution(PRTMessageConstants.SDA_LOG_STEP_INPUT_DATA) – {0}, {1}: logging step input data

JL.execution(PRTMessageConstants.SDA_LOG_STEP_LOOP_INPUT_DATA) – {0}, {1}: logging step loop input data

JL.execution(PRTMessageConstants.SDA_LOG_STEP_LOOP_OUTPUT_DATA) – {0}, {1}: logging step loop output data

JL.execution(PRTMessageConstants.SDA_LOG_STEP_OUTPUT_DATA) – {0}, {1}: logging step output data

JL.execution(PRTMessageConstants.SDA_NOPIPE) – {0}, {1}: step not executed, enquueing event

JL.execution(PRTMessageConstants.SDA_PROCSTATS) – {0}, {1}: pushing step on suspended list

JL.execution(PRTMessageConstants.SDA_PUBLISH1) – {0}, {1}: published output document {2}

JL.execution(PRTMessageConstants.SDA_RETRIES) – {0}, {1}: step iteration count exceeded

JL.execution(PRTMessageConstants.SDA_SVC) – {0}, {1}: executing {2} in package {3}

JL.execution(PRTMessageConstants.SDA_SVC_ERR_MSG) – {1}, {2}: exception invoking service {3}: {0}

JL.execution(PRTMessageConstants.SDA_SVC_ERR_TX) – {0}, {1}: transitioning to error step {2}

JL.execution(PRTMessageConstants.SDA_SVC_SENDOUT) – {0}, {1}: sent {2} output events

JL.execution(PRTMessageConstants.SDA_SYNCHBEG) – {0}, {1}: start step execution

JL.execution(PRTMessageConstants.SDA_SYNCHEND) – {0}, {1}: end step execution

JL.execution(PRTMessageConstants.SDA_TDELTA0) – {0}, {1}: no track count change

JL.execution(PRTMessageConstants.SDA_TXASYNCH) – {0}, {1}: publishing transition to {2} on {3}

JL.execution(PRTMessageConstants.SDA_TXASYNCH_DEADPATH) – {0}, {1}: sending Dead Path PTE to {2} on {3}

JL.execution(PRTMessageConstants.SDA_TXNOCOND) – {0}, {1}: sending dead transition to {2}

JL.execution(PRTMessageConstants.SDA_TXSEND) – {0}, {1}: sending live transition to {2}

JL.execution(PRTMessageConstants.SDA_UNABLE_INVOKE_ERROR_STEP_LOCALLY) – {1}, {2}: unable to invoke error step locally with the following exception: {0}

JL.execution(PRTMessageConstants.SDA_UNSATISFIED_JOIN) – {0}, {1}: taking unsatisfied join transition {2}

JL.execution(PRTMessageConstants.SDC_ABSOLUTE_TIME_INVALID) – {0}, {1}: absolute timeout type is invalid

JL.execution(PRTMessageConstants.SDC_DROPQ0) – {0}, {1}: dropping {2} events

JL.execution(PRTMessageConstants.SDC_HANDLEJOINTIMER) – {0}, {1}: handling join timeout

JL.execution(PRTMessageConstants.SDC_HANDLEPROCTIMER) – {0}: handling process timeout

JL.execution(PRTMessageConstants.SDC_HANDLESTEPTIMER) – {0}, {1}: handling step timeout

JL.execution(PRTMessageConstants.SDC_JOINTIME) – {0}, {1}: starting join timeout

JL.execution(PRTMessageConstants.SDC_JOIN_RSLT) – {0}, {1}: join evaluates to {2}

JL.execution(PRTMessageConstants.SDC_PROCTIME) – {0}: starting process timeout

JL.execution(PRTMessageConstants.SDC_QUEUE_SZ) – {0}, {1}: {2} events in the queue. Event names: {3}. Join string: {4}. Join state: {5}

JL.execution(PRTMessageConstants.SDC_STEPTIME) – {0}, {1}: starting step timeout

JL.execution(PRTMessageConstants.SDC_TOHANDLE) – {0}, {1}: transitioning to timeout handler

JL.execution(PRTMessageConstants.SDC_TOPIPEERR) – {1}, {2}: exception assembling pipeline: {0}

JL.execution(PRTMessageConstants.SD_ACTIVITY_NOT_RUNNING) – {0}, {1}: boundary event {2} ignored because activity is not running

JL.execution(PRTMessageConstants.SD_CORRELATE) – {0}, {1}: using correlation service {2}

JL.execution(PRTMessageConstants.SD_CORRELATE_DISABLED) – {0}, {1}: correlated to disabled model {2} version {3}

JL.execution(PRTMessageConstants.SD_CORRELATE_ERR) – {1}, {2}: exception invoking correlation svc {3}: {0}

JL.execution(PRTMessageConstants.SD_CORRELATE_FIELD) – {0}, {1}: using correlation field {2}

JL.execution(PRTMessageConstants.SD_CORRELATE_NEW) – {0}, {1}: correlated to process id

JL.execution(PRTMessageConstants.SD_CORRELATE_TN) – {0}, {1}: correlating to TN conversation id

JL.execution(PRTMessageConstants.SD_CORRELBADMID) – {0}, {1}: correlated to {2}, expected {3}

JL.execution(PRTMessageConstants.SD_ERR_DISPATCH) – {1}, {2}: exception dispatching step: {0}

JL.execution(PRTMessageConstants.SD_ERR_HANDLEEVT) – {1}, {2}: exception handling transition event: {0}

JL.execution(PRTMessageConstants.SD_INPUTMATCH) – {0}, {1}, document {3} is a valid published input

JL.execution(PRTMessageConstants.SD_INVOKEDISPATCH) – {0}, {1}: dispatching step on new execution thread

JL.execution(PRTMessageConstants.SD_NOINPUT1) – {0}, {1}: document {3} is NOT a valid published input

JL.execution(PRTMessageConstants.SD_NOSTEPDEF) – {0}, {1}: no process fragment contains this step

JL.execution(PRTMessageConstants.SD_PTE) – {0}, {1}: handling transition event from {2}

JL.execution(PRTMessageConstants.SD_PUBLISH) – {0}, {1}: handling native document {3} on {2}

JL.execution(PRTMessageConstants.SD_STARTSTEP) – {0}, {1}: starting step execution

JL.execution(PRTMessageConstants.SD_STEPSYNCH) – {0}, {1}: running step on same execution thread

JL.execution(PRTMessageConstants.SM_ACTDONE) – {0}: process status changed to {1}

JL.execution(PRTMessageConstants.SM_RESTARTPROC) – {0}: restarting process at step {1}

JL.execution(PRTMessageConstants.SM_RESUMEPROC) – {0}: resuming process at {1}

JL.execution(PRTMessageConstants.SM_START) – {0}: processing {1} request

JL.execution(PRTMessageConstants.ST_DB_CONNECT_ERR1) – {1}: exception connecting to database: {0}

JL.execution(PRTMessageConstants.ST_DB_CONNECT_ERR2) – {1}, {2}: exception connecting to database: {0}

JL.execution(PRTMessageConstants.ST_LOCK_FAIL) – {0}, {1}: step lock FAILED

JL.execution(PRTMessageConstants.ST_LOCK_SUCCESS) – {0}, {1}: step locked

JL.execution(PRTMessageConstants.ST_LOCK_TRY) – {0}, {1}: attempting step lock

JL.execution(PRTMessageConstants.TC_INVOKE_CONTROL_TASKS) – {0}: invoking wm.task.taskclient:controlTasks with control "{1}"

JL.execution(PRTMessageConstants.TC_INVOKE_CONTROL_TASKS_ERR) – {1}: exception invoking wm.task.taskclient:controlTasks service: {0}

JL.execution(PRTMessageConstants.TN_ERR_PROFIELD) – {1}: exception fetching data for field {2}: {0}

JL.execution(PRTMessageConstants.TN_ERR_PROSTORE) – {1}: exception fetching data from TN profile store: {0}

JL.execution(PRTMessageConstants.TO_CANCEL_JOIN) – {0}, {1}: cancelling join timeout

JL.execution(PRTMessageConstants.TO_CANCEL_PROCESS) – {0}: cancelling process timeout

JL.execution(PRTMessageConstants.TO_CANCEL_STEP) – {0}, {1}: cancelling step timeout

JL.execution(PRTMessageConstants.TO_ERR_INVOKE) – {1}, {2}: exception invoking timeout: {0}

JL.execution(PRTMessageConstants.TO_KILLSTEPTHR) – {0}, {1}: killing step execution thread

JL.execution(PRTMessageConstants.TO_MISSING_JOIN_TIMER_TYPE) – {0}, {1}: cannot start Join timeout -- type not specified

JL.execution(PRTMessageConstants.TO_MISSING_PROCESS_TIMER_TYPE) – {0}: cannot start Process timeout -- type not specified

JL.execution(PRTMessageConstants.TO_MISSING_STEP_TIMER_TYPE) – {0}, {1}: cannot start Step timeout -- type not specified

JL.execution(PRTMessageConstants.TO_NO_TRANSITION) – {1}, {2}: no transition to handle timeout: {0}

JL.execution(PRTMessageConstants.TO_STRT_NO_DURATION) – {0}, {1}: did not start timer, no end time specified.

JL.execution(PRTMessageConstants.TO_STRT_TIMER) – {0}, {1}: starting timeout: {2}

JL.execution(PRTMessageConstants.TO_TIMEOUT_JOIN) – {0}, {1}: join timer has expired

JL.execution(PRTMessageConstants.TO_TIMEOUT_PROCESS) – {0}: process timer has expired

JL.execution(PRTMessageConstants.TO_TIMEOUT_STEP) – {0}, {1}: step timer has expired

JL.general(PRTMessageConstants.ADM_BPM_ONLY_USAGE) – This service cannot be invoked outside of an executing Business Process instance.

JL.general(PRTMessageConstants.ADM_MWS_INIT_ERROR) – Unable to initialize MWS library. Business calendar based timeouts will not be able to be evaluated.

JL.general(PRTMessageConstants.ADM_MWS_INIT_ERROR2) – Exception trying to initialize MWS library: {0}

JL.general(PRTMessageConstants.ADM_MWS_INIT_ERROR_GET_POOL) – Error trying to get JDBC pool configuration using functional alias {0}. Business calendar based timeouts will not be able to be evaluated.

JL.general(PRTMessageConstants.ADM_MWS_INIT_ERROR_GET_POOL2) – Exception trying to get JDBC pool configuration: {0}

JL.general(PRTMessageConstants.AL_CANTPOP) – Exception trying to pop audit log context: {0}

JL.general(PRTMessageConstants.AL_CANTPUSH) – Exception trying to push audit log context: {0}

JL.general(PRTMessageConstants.AL_CUSTNOT) – Custom logging: cannot convert {0} to logging type {1} (value {2})

JL.general(PRTMessageConstants.AL_CUSTNOU0) – Custom logging: cannot find value for {0}.{1} on path {2}

JL.general(PRTMessageConstants.AL_ERRPUB1) – Exception publishing Audit Log Event {1}: {0}

JL.general(PRTMessageConstants.AL_ERRPUB_OPTIMIZE) – Exception publishing Optimize Log Event {1}: {0}

JL.general(PRTMessageConstants.AL_ERR_GET_AUDIT_RUNTIME2) – Exception getting audit runtime: {0}

JL.general(PRTMessageConstants.AL_ERR_LOG) – Exception logging audit entry: {0}

JL.general(PRTMessageConstants.AL_ERR_REG_LOGGER) – Exception registering Process Logger: {0}

JL.general(PRTMessageConstants.AL_FAILED_AUDIT_CACHE_ADD) – Adding audit entry to failed process audit cache: {0}

JL.general(PRTMessageConstants.AL_FAILED_AUDIT_CACHE_ADD_ERR) – Could not add audit entry to failed process audit cache: {0}

JL.general(PRTMessageConstants.AL_FAILED_AUDIT_CACHE_EMPTY) – All entries in the failed audit cache have been stored in the process audit database

JL.general(PRTMessageConstants.AL_FAILED_AUDIT_CACHE_STORED) – Stored {0} entries from the failed audit cache in the process audit database

JL.general(PRTMessageConstants.AL_FAILED_AUDIT_CACHE_STORE_ERR) – Exception when trying to store entries from the failed audit cache in the process audit database: {0}

JL.general(PRTMessageConstants.AL_NO_MID_FOR_PID) – {1}: exception getting model identifier: {0}

JL.general(PRTMessageConstants.AL_PIPEERR_STEP0) – Exception trying to encode step pipeline for {1}: {0}

JL.general(PRTMessageConstants.BT_CFG_ERROR) – [MID={1}] Problem reading BrainTribe config file: "{2}". {0}

JL.general(PRTMessageConstants.DASHBOARD) – Dashboard

JL.general(PRTMessageConstants.DASHBOARD_DIAGNOSTIC) – Diagnostic

JL.general(PRTMessageConstants.DASHBOARD_ENVIRONMENT) – Environment

JL.general(PRTMessageConstants.DASHBOARD_ENV_AUDIT_SETTINGS) – Audit Logging Settings

JL.general(PRTMessageConstants.DASHBOARD_ENV_CONTROL_TRIGGER) – Standard Control Triggers

JL.general(PRTMessageConstants.DASHBOARD_ENV_CR) – Content Repository View

JL.general(PRTMessageConstants.DASHBOARD_ENV_JDBC) – JDBC Connections

JL.general(PRTMessageConstants.DASHBOARD_ENV_JMS_TRIGGER) – JMS Control Trigger

JL.general(PRTMessageConstants.DASHBOARD_ENV_SETTINGS) – Process Engine Settings

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_AUDITLOG) – Audit Logging Status

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_AUDIT_LOGGING) – Audit Logging

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_BROKER_PUSH) – Broker Push

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_BUSINESS_CALENDAR) – Business Calendars

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_BUSINESS_CALENDARS) – Business Calendars

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_CHECK) – Health Check

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_CONTROL) – Control Triggers

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_DBMS) – DBMS Status

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_DB_SCHEMA) – Database Schema Compatibility

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_EFORM_LISTENER) – E-form Listener

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_JMS) – JMS Control Status

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_JMS_MSG) – JMS

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_MESSAGING_PUSH) – webMethods Messaging Push

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_OPTIMIZE) – Optimize Subsystem

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_OPTIMIZE_MSG) – Optimize Logging

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_PA_DB) – Process Auditing

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_PE_DB) – Process Engine Database

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_RESTART_TIMERS) – Restart Timers

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_STARTUP_MESSAGES) – Startup Messages

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_STORAGE) – Storage

JL.general(PRTMessageConstants.DASHBOARD_PROCESS) – Process

JL.general(PRTMessageConstants.DASHBOARD_PROCESS)...0 – Process Engine

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_ALL_EVENTS) – 5 - Process and All Events and Activities

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_ERRORS) – 2 - Errors only

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_NONE) – 1 - None

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_PROCESS) – 3 - Process only

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_START) – 4 - Process and Start Events

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_UNKNOWN) – Unknown

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_AUDIT_ASYNC) – Asynchronous

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_AUDIT_DB) – Database

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_AUDIT_FILE) – File

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_AUDIT_SYNC) – Synchronous

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_SETTINGS) – Settings

JL.general(PRTMessageConstants.DASHBOARD_RESTART_EFORM_FAIL) – Failed to restart e-form listener for {0}.

JL.general(PRTMessageConstants.DASHBOARD_RESTART_EFORM_SUCCESS) – Restart of e-form listener: {0} successful.

JL.general(PRTMessageConstants.DASHBOARD_STATUS_NO) – No

JL.general(PRTMessageConstants.DASHBOARD_STATUS_SUSPENDED) – Suspended

JL.general(PRTMessageConstants.DASHBOARD_STATUS_YES) – Yes

JL.general(PRTMessageConstants.DUP_CHK_BEGIN) – CheckDuplicates processing {0}, uuid, {1}

JL.general(PRTMessageConstants.DUP_CHK_END) – CheckDuplicates processed {0}, uuid, {1}, status, {2}

JL.general(PRTMessageConstants.DUP_CHK_ISEXP) – CheckDuplicates throwing ISRuntimeException {0}, uuid, {1}

JL.general(PRTMessageConstants.EF_CFG_ERROR) – [MID={1}] Problem reading E-form config file: "{2}". {0}

JL.general(PRTMessageConstants.EF_LISTENER_ADDED) – [MID={0}] Now listening to path: "{1}" for e-Forms on jcr "{2}"

JL.general(PRTMessageConstants.EF_LISTENER_ADD_ERROR) – [MID={1}] Error adding listener to Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF_LISTENER_ALREADY_EXISTS) – [MID={0}] Content Repository currently has a listener listening in that location. No new listener added to listening path: "{1}" for e-Forms on jcr "{2}".

JL.general(PRTMessageConstants.EF_LISTENER_CHANGE_NOTALLOWED) – [MID={0}] Unable to change listener please disable all other models currently using this listener: "{1}"

JL.general(PRTMessageConstants.EF_LISTENER_DOCNOTFOUND) – [MID={0}] Cannot start e-form process because doc type: "{1}" does not exist. For e-form instance at: "{2}". Please recreate the e-form doc or rebuild the model(s).

JL.general(PRTMessageConstants.EF_LISTENER_ERROR) – [MID={1}] Error with Content Repository "{2}". Check if the repo is running, login credentials and repo connection information is correct. {0}

JL.general(PRTMessageConstants.EF_LISTENER_FIRED) – [MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}

JL.general(PRTMessageConstants.EF_LISTENER_FIRED)...0 – [MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}

JL.general(PRTMessageConstants.EF_LISTENER_NOTCONFIGURED) – [MID={0}] Content Repository "{1}" not configured.

JL.general(PRTMessageConstants.EF_LISTENER_NO_DOCS) – Content Repository currently has no models associated to it. No reason to restart the repository at this time.

JL.general(PRTMessageConstants.EF_LISTENER_PORTS_NOTADDED) – [MID={0}] Cannot edit access for PORT 15006. Please ensure to manually add access for "wm.prt.eforms:update" "wm.server:connect" "wm.server:disconnect" "wm.server:ping".

JL.general(PRTMessageConstants.EF_LISTENER_REMOVED) – [MID={0}] Listener for e-Forms at path: "{1}" has been disabled from jcr "{2}"

JL.general(PRTMessageConstants.EF_LISTENER_REMOVE_ERROR) – [MID={1}] Error disabling/removing listener from Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF_LISTENER_RESTART_ERROR) – [MID={1}] Error restarting listener(s) to Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF_LISTENER_RESTART_MODEL_NOTENABLED) – No model(s) enabled using this listener "{0}". Listener will not be restarted.

JL.general(PRTMessageConstants.EF_METHOD_SUCCEEDED) – The method succeeded.

JL.general(PRTMessageConstants.EF_PASS_ERROR) – [MID={1}] Cannot retrive password: "{2}". {0}

JL.general(PRTMessageConstants.EF_PUBLISH_COULD_NOT_CREATE_DOC) – Could not create the IS document type "{0}" from e-form instance "{1}"; make sure the e-form instance contents matches the IS document type.

JL.general(PRTMessageConstants.EF_PUBLISH_DOCNOTFOUND) – Cannot publish the e-form as an IS document because the IS document type "{0}" does not exist. Please create the IS document type from your e-form template.

JL.general(PRTMessageConstants.EF_PUBLISH_DOC_PUBLISH_FAILED) – Error publishing e-form instance: {0}

JL.general(PRTMessageConstants.EF_PUBLISH_FILENOTFOUND) – Cannot publish the e-form as an IS document because the e-form instance file "{0}" does not exist.

JL.general(PRTMessageConstants.EF_PUBLISH_INPUTS_NOT_PROVIDED) – The required input values were not provided; for this service though some inputs are optional you must provide either (instanceName and instanceByteStream) or (instanceFilePath). If both sets are provided, then (instanceName and instanceByteStream), takes precedence.

JL.general(PRTMessageConstants.EF_PUBLISH_PUBLISH_ATTEMPT) – Trying to publish e-form instance "{0}" as IS document type "{1}". If any associated processes do not start, then please check the error log for any pub.publish:publish errors.

JL.general(PRTMessageConstants.EF_PUBLISH_TEMPLATE_NOT_PROVIDED) – The required input value, templateName, was not provided.

JL.general(PRTMessageConstants.EP_PIPEERR0) – Exception encoding transition pipeline: {0}

JL.general(PRTMessageConstants.EP_SENDERR) – Exception during send: {0}

JL.general(PRTMessageConstants.HEALTHCHECK_AUDITLOG_DB_RED) – Process audit database could not be accessed

JL.general(PRTMessageConstants.HEALTHCHECK_AUDITLOG_INIT_RED) – Error initializing audit logging

JL.general(PRTMessageConstants.HEALTHCHECK_AUDITLOG_RED) – Process Logger is either not enabled or not configured for the database

JL.general(PRTMessageConstants.HEALTHCHECK_BC_RED) – MWS library is not initialized

JL.general(PRTMessageConstants.HEALTHCHECK_BC_YELLOW) – JDBC pool functional alias "CentralUsers" is not configured

JL.general(PRTMessageConstants.HEALTHCHECK_BROKER_RED) – ControlTrigger is not enabled

JL.general(PRTMessageConstants.HEALTHCHECK_BROKER_YELLOW) – Broker is not configured

JL.general(PRTMessageConstants.HEALTHCHECK_JMS_RED) – JMSControlTrigger is not enabled

JL.general(PRTMessageConstants.HEALTHCHECK_MESSAGING_YELLOW) – webMethods Messaging is not configured

JL.general(PRTMessageConstants.HEALTHCHECK_OPTIMIZE_NOT_CONFIGURED) – JMS Server URL is not configured

JL.general(PRTMessageConstants.HEALTHCHECK_OPTIMIZE_NOT_INIT) – Unable to initialize Optimize interface

JL.general(PRTMessageConstants.HEALTHCHECK_PADB_RED) – Process audit database could not be accessed

JL.general(PRTMessageConstants.HEALTHCHECK_PADB_VERSION_RED) – Process audit database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

JL.general(PRTMessageConstants.HEALTHCHECK_PA_FAILED_AUDIT_CACHE_NOT_EMPTY_RED) – Failed process audit cache contains records that need to be inserted into the process audit database

JL.general(PRTMessageConstants.HEALTHCHECK_PA_FAILED_AUDIT_CACHE_NO_EXIST_RED) – Failed process audit cache does not exist

JL.general(PRTMessageConstants.HEALTHCHECK_PEDB_RED) – Process engine database could not be accessed

JL.general(PRTMessageConstants.HEALTHCHECK_PEDB_VERSION_RED) – Process engine database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

JL.general(PRTMessageConstants.HEALTHCHECK_TRIGGER_RED) – Trigger {0} is not enabled.

JL.general(PRTMessageConstants.IL_ERR_CREATE_LOGGER) – Exception creating instance logger: {0}

JL.general(PRTMessageConstants.IL_ERR_LOG_ENABLED) – Exception determining if model is enabled for instance logging: {0}

JL.general(PRTMessageConstants.IM_CLEANUPEVERY) – Cache cleanup running every {0} seconds and every {1} instances

JL.general(PRTMessageConstants.IM_MODINACTIVE0) – Warning. Process model {0} is inactive

JL.general(PRTMessageConstants.IM_MODINACTIVE1) – Cannot suspend/resume {0}. Fragment for model {1} is missing

JL.general(PRTMessageConstants.IM_NOCLEANUP) – Instance cleanup disabled.

JL.general(PRTMessageConstants.IS_RETRYLIMIT) – Step Level Retry count exceeded for service: {0}

JL.general(PRTMessageConstants.IS_SVC_RETRY) – Exception: {0}. Step Level Retry configured for service: {1}. Retry {2} of {3} in {4} ms

JL.general(PRTMessageConstants.IS_THRESHOLD) – Thread Threshold detected. Retry abandoned for {0}.

JL.general(PRTMessageConstants.JMS_ALIAS_ERROR) – JMS Connection Alias for PE 'PE_NONTRANSACTIONAL_ALIAS' has not been configured.

JL.general(PRTMessageConstants.JMS_CREATE_CONNECTION_ERROR) – Error creating JMS connection alias: {0}

JL.general(PRTMessageConstants.JMS_CREATE_TOPIC_ERROR) – Error creating PE internal JMS topic: {0}

JL.general(PRTMessageConstants.JMS_UPDATE_CG_PERMISSIONS_ERROR) – Error updating client group permissions: {0}

JL.general(PRTMessageConstants.MM_BADFRAGERR) – Exception loading model fragment {1}: {0}

JL.general(PRTMessageConstants.MM_CANTMAKEDIR) – Unable to create directory: {0}

JL.general(PRTMessageConstants.MM_DELETING) – Deleting {0} old fragments from {1}

JL.general(PRTMessageConstants.MM_DELFILE) – Deleting XML file {0}

JL.general(PRTMessageConstants.MM_DELFRAG) – Deleting model fragment: {0}

JL.general(PRTMessageConstants.MM_FILEERR) – Exception reading fragment file {1}: {0}

JL.general(PRTMessageConstants.MM_NEWFRAG) – Adding new process fragment (pkg={0}, file={1})

JL.general(PRTMessageConstants.MM_READMOD) – Loading model fragment {0}

JL.general(PRTMessageConstants.MM_READPKG) – Loading process models in package {0}

JL.general(PRTMessageConstants.MON_INVALID_ENABLE_RESUBMISSION) – Enable Resubmission value must be either "True" or "False"

JL.general(PRTMessageConstants.MON_INVALID_LOGGING_LEVEL) – Invalid Logging Level

JL.general(PRTMessageConstants.MON_INVALID_LOG_TRANSITIONS) – Log Transitions value must be either "True" or "False"

JL.general(PRTMessageConstants.MON_INVALID_MODEL) – [MID={0}, MVers={1}] Model does not exist.

JL.general(PRTMessageConstants.MON_INVALID_PID) – Process instance {0} is not running or does not exist.

JL.general(PRTMessageConstants.MON_LOGGING_LEVEL_TOO_LOW) – [MID={0}] Logging level for Model cannot be set below minimum value of {1}.

JL.general(PRTMessageConstants.MON_OLD_MODEL_VERSION) – [MID={0}] QoS cannot be changed because it was generated from a pre-7.0 version of Modeler.

JL.general(PRTMessageConstants.OL_OPTIMIZE_INIT_ERROR) – Unable to get Optimize process data collector. Tracking enabled models will not be logged to Optimize.

JL.general(PRTMessageConstants.OL_OPTIMIZE_INIT_ERROR2) – Exception trying to get Optimize process data collector: {0}

JL.general(PRTMessageConstants.OL_OPTIMIZE_SHUTDOWN_ERROR) – Exception trying to shut down Optimize data collector: {0}

JL.general(PRTMessageConstants.PRT_EXCEPTION) – Exception: {0}

JL.general(PRTMessageConstants.PRT_MESSAGE) – {0}

JL.general(PRTMessageConstants.REPO_DEFAULT_ROOT_PATH) – (optional)

JL.general(PRTMessageConstants.REPO_EXE) – A RepositoryException occurred while trying to read data from the Content Repository: "{0}"

JL.general(PRTMessageConstants.REPO_FILE_DOES_NOT_EXIST) – File does not exist in repository

JL.general(PRTMessageConstants.REPO_IO_EXE) – An IOException occurred while trying to read data from the Content Repository: "{0}"

JL.general(PRTMessageConstants.REPO_PATH_NOT_FOUND_EXE) – A PathNotFoundException occurred while trying to read data from the Content Repository: "{0}"

JL.general(PRTMessageConstants.REPO_READ_NODE_ERROR) – An exception occurred while trying to read data from the Content Repository at: "{0}". Please check log for details.

JL.general(PRTMessageConstants.SDA_ERR_GENERAL) – Exception executing step {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA_ERR_HANDLEEVT_CHANGE) – Exception trying to fail the process *{1}: {0}

JL.general(PRTMessageConstants.SDA_ERR_OUT) – Exception sending output {1} of {2} for PID {3} SID {4}: {0}

JL.general(PRTMessageConstants.SDA_ERR_SAVECTX) – Exception saving step context {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA_ERR_TX) – Exception updating track count {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA_INVALID_STEP) – Exception: Deprecated step found {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA_SVC_ERR_MSG) – Exception invoking service {1}, {2}, Svc={3}: {0}

JL.general(PRTMessageConstants.SDC_TOPIPEERR) – Exception assembling pipeline {1}, {2}: {0}

JL.general(PRTMessageConstants.SD_CORRELATE_ERR) – Error invoking correlation svc {1}: {0}

JL.general(PRTMessageConstants.SD_ERR_DISPATCH) – Exception dispatching step: {0}

JL.general(PRTMessageConstants.SD_ERR_HANDLEEVT) – Exception handling transition event: {0}

JL.general(PRTMessageConstants.SD_INPUTMATCH) – Document {0} is a valid published input

JL.general(PRTMessageConstants.SD_NOINPUT1) – Document {0} is NOT a valid published input

JL.general(PRTMessageConstants.SD_NOSTEP1) – Document {2} does not match to any step in process {0} on {1}

JL.general(PRTMessageConstants.SD_PUBLISH) – Handling native document {0} on {1}

JL.general(PRTMessageConstants.SD_STEPMATCH) – Document {2} matches step in process {0} on {1}

JL.general(PRTMessageConstants.SM_BAD_ACTION) – {0} is not a valid Action.

JL.general(PRTMessageConstants.ST_CACHE_CONNECT_ERR) – Exception: Unable to connect to cache!

JL.general(PRTMessageConstants.ST_CACHE_MGR_NOT_INITIALIZED) – Could not initialize cache manager

JL.general(PRTMessageConstants.ST_CACHE_NOT_INITIALIZED) – Could not initialize cache: {0}

JL.general(PRTMessageConstants.ST_CLEAN_DURATION) – Storage cleaner: Duration {0} ms

JL.general(PRTMessageConstants.ST_CLEAN_EVERY) – Storage cleaner: will run every {0} seconds

JL.general(PRTMessageConstants.ST_CLEAN_JDBC) – Storage cleaner: executing embedded SQL

JL.general(PRTMessageConstants.ST_CLEAN_PROC) – Storage cleaner: executing stored procedure

JL.general(PRTMessageConstants.ST_DB_CONNECT_ERR) – Exception: Unable to connect to database!

JL.general(PRTMessageConstants.ST_DB_ERR) – Storage exception: {0}

JL.general(PRTMessageConstants.ST_FAILED_PROC_EXPIRE) – Storage cleaner: expiration for failed processes: {0} seconds

JL.general(PRTMessageConstants.ST_LOCK_INSERT_FAIL) – Failed to insert Lock ID: {0} -- attempt {1} of {2}

JL.general(PRTMessageConstants.ST_NO_CLEAN) – Storage cleaner: Disabled

JL.general(PRTMessageConstants.ST_NO_CLEAN_FAILED_PROC) – Storage cleaner: clean up for completed processes is disabled

JL.general(PRTMessageConstants.ST_NO_LOCK) – Storage cleaner: cannot acquire lock. Exception: {0}

JL.general(PRTMessageConstants.ST_PROC_EXPIRE) – Storage cleaner: expiration for completed processes: {0} seconds

JL.general(PRTMessageConstants.TM_DFLTXPORT) – Default PE transport is {0}

JL.general(PRTMessageConstants.TM_DFLTXPORT_DEF) – Default PE transport is {0}; deferred

JL.general(PRTMessageConstants.TM_PUSH_ATTEMPT) – Pushing doctypes to webMethods Messaging

JL.general(PRTMessageConstants.TM_PUSH_ERROR) – webMethods Messaging push error: {0}

JL.general(PRTMessageConstants.TM_PUSH_NOCONN) – Not performing webMethods Messaging push (not connected)

JL.general(PRTMessageConstants.TM_SEND) – Sending {2} over {0} to {1}

JL.general(PRTMessageConstants.TM_SENDABBR) – Sending {1} over {0}

JL.general(PRTMessageConstants.TN_DISPATCH0) – DocID={0}, DocType={1}, ConvId={2}: processing incoming TN document

JL.general(PRTMessageConstants.TN_ERR_BADFILTER) – Exception evaluating TN document filter: {0}

JL.general(PRTMessageConstants.TN_ERR_PROFIELD) – Exception fetching data for field {1}: {0}

JL.general(PRTMessageConstants.TN_ERR_PROSTORE) – Exception fetching data from TN profile store: {0}

JL.general(PRTMessageConstants.TN_NOMATCH) – DocID={0}, DocType={1}, ConvId={2}: no Model match for TN document

JL.general(PRTMessageConstants.TN_NOSTEPMATCH) – DocID={0}, DocType={1}, ConvId={2}, MID={3}: no Step match for TN document

JL.general(PRTMessageConstants.TN_STARTORJOIN) – ConvId={0}, PID={1}: starting/joining TN process

JL.general(PRTMessageConstants.TOU_INVALID_BIZ_CAL_ALIAS) – Business calendar alias {0} does not exist

JL.general(PRTMessageConstants.TOU_INVALID_BIZ_CAL_EVALUATOR) – Business calendar evaluator does not exist

JL.general(PRTMessageConstants.TOU_INVALID_BIZ_TIMEOUT) – Business timeout is invalid: {0}

JL.general(PRTMessageConstants.TO_ERR_INVOKE) – Exception invoking timeout for {1}, {2}: {0}

JL.general(PRTMessageConstants.TO_TIMER_THREAD_INTERRUPTED) – Timer thread interrupted: {0}

JL.string(PRTMessageConstants.BT_CFG_ERROR) – [MID={1}] Problem reading BrainTribe config file: "{2}". {0}

JL.string(PRTMessageConstants.DASHBOARD_PROCESSLOG_ALL_EVENTS) – 5 - Process and All Events and Activities

JL.string(PRTMessageConstants.EF_METHOD_SUCCEEDED) – The method succeeded.

JL.string(PRTMessageConstants.EF_PUBLISH_COULD_NOT_CREATE_DOC) – Could not create the IS document type "{0}" from e-form instance "{1}"; make sure the e-form instance contents matches the IS document type.

JL.string(PRTMessageConstants.EF_PUBLISH_DOCNOTFOUND) – Cannot publish the e-form as an IS document because the IS document type "{0}" does not exist. Please create the IS document type from your e-form template.

JL.string(PRTMessageConstants.EF_PUBLISH_DOC_PUBLISH_FAILED) – Error publishing e-form instance: {0}

JL.string(PRTMessageConstants.EF_PUBLISH_FILENOTFOUND) – Cannot publish the e-form as an IS document because the e-form instance file "{0}" does not exist.

JL.string(PRTMessageConstants.EF_PUBLISH_INPUTS_NOT_PROVIDED) – The required input values were not provided; for this service though some inputs are optional you must provide either (instanceName and instanceByteStream) or (instanceFilePath). If both sets are provided, then (instanceName and instanceByteStream), takes precedence.

JL.string(PRTMessageConstants.EF_PUBLISH_PUBLISH_ATTEMPT) – Trying to publish e-form instance "{0}" as IS document type "{1}". If any associated processes do not start, then please check the error log for any pub.publish:publish errors.

JL.string(PRTMessageConstants.EF_PUBLISH_TEMPLATE_NOT_PROVIDED) – The required input value, templateName, was not provided.

JL.string(PRTMessageConstants.HEALTHCHECK_PADB_VERSION_RED) – Process audit database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

JL.string(PRTMessageConstants.HEALTHCHECK_PEDB_VERSION_RED) – Process engine database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

JL.string(PRTMessageConstants.IM_CANCELLEDOK) – *PID={0}, MID={1}, MVer={2}: process cancelled

JL.string(PRTMessageConstants.IM_FAILEDOK) – *PID={0}, MID={1}, MVer={2}: process failed

JL.string(PRTMessageConstants.IM_UPDATE_TRACK) – *{0}, {1}: updated track count by {2} to {3}

JL.string(PRTMessageConstants.REPO_DEFAULT_ROOT_PATH) – (optional)

JL.string(PRTMessageConstants.REPO_EXE) – A RepositoryException occurred while trying to read data from the Content Repository: "{0}"

JL.string(PRTMessageConstants.REPO_FILE_DOES_NOT_EXIST) – File does not exist in repository

JL.string(PRTMessageConstants.REPO_IO_EXE) – An IOException occurred while trying to read data from the Content Repository: "{0}"

JL.string(PRTMessageConstants.REPO_PATH_NOT_FOUND_EXE) – A PathNotFoundException occurred while trying to read data from the Content Repository: "{0}"

JL.string(PRTMessageConstants.REPO_READ_NODE_ERROR) – An exception occurred while trying to read data from the Content Repository at: "{0}". Please check log for details.

JL.string(PRTMessageConstants.RULE_SVC_PIPEI) – Prepared pipeline to invoke Rule as: "{0}"

JL.string(PRTMessageConstants.SDA_BEFORE_STEP_PIPE) – *{0}, {1}: after step pipeline: {2}

JL.string(PRTMessageConstants.SDA_BEFORE_STEP_PIPE)...0 – *{0}, {1}: before step pipeline: {2}

JL.string(PRTMessageConstants.SDA_DEAD_INGORED) – *{0}, {1}: synchronization point ignoring dead path from {2}

JL.string(PRTMessageConstants.SD_ACTIVITY_IN_DEBUG) – Boundary event ignored because process was started in Debugger [PID={0}, ACTIVITY_SID={1}, BOUNDARY_SID={2}]

JL.string(PRTMessageConstants.SD_ACTIVITY_NOT_RUNNING) – *{0}, {1}: boundary event {2} ignored because activity is not running

JL.string(PRTMessageConstants.ST_CACHE_CONNECT_ERR) – Exception: Unable to connect to cache!

JL.string(PRTMessageConstants.ST_CACHE_MGR_NOT_INITIALIZED) – Could not initialize cache manager

JL.string(PRTMessageConstants.ST_CACHE_NOT_CONFIGURED) – Could not configure Shared Cache for Join locks

JL.string(PRTMessageConstants.ST_CACHE_NOT_INITIALIZED) – Could not initialize cache: {0}

JL.string(PRTMessageConstants.ST_LOCK_INSERT_FAIL) – Failed to insert Lock ID: {0} -- attempt {1} of {2}

JL.string(PRTMessageConstants.TU_DELTHR_CACHE) – Deleting thread from cluster cache, thread id={0}

JL.string(PRTMessageConstants.TU_SETTHR_CACHE_ALIVE) – Marking thread alive in cluster cache, thread id={0}

JL.string(PRTMessageConstants.TU_SETTHR_CACHE_KILLED) – Marking thread killed in cluster cache, thread id={0}

PRT.0101.0024E	**Exception trying to encode step pipeline for {1}: {0}**
Explanation	Unable to encode the pipeline for audit logging.
Action	Check the exception message for details.

PRT.0101.0025	**Failed to encode pipeline for step {0}: {1}**

PRT.0101.0026E	**Custom logging: cannot find value for {0}.{1} on path {2}**
Explanation	Unable to get the field value using the specified path.
Action	Make sure the field name and the path are correct.

PRT.0101.0028E	**Custom logging: cannot convert {0} to logging type {1} (value {2})**
Explanation	Failed to execute custom fields logging because the type of the field value cannot be determined.
Action	Verify that the custom field value is the correct field type.

PRT.0101.0029E **Exception trying to push audit log context: {0}**

Explanation Unable to add audit log context.

Action Check the exception message for details.

PRT.0101.0030E **Exception trying to pop audit log context: {0}**

Explanation Unable to remove audit log context.

Action Check the exception message for details.

PRT.0101.0031E **Exception publishing Audit Log Event {1}: {0}**

Explanation Unable to publish the log document for audit logging.

Action Check the exception message for details.

PRT.0101.0034E **Exception publishing Optimize Log Event {1}: {0}**

Explanation Unable to perform the task because an audit runtime storage is not found.

Action Make sure the audit runtime storage is properly set up and running.

PRT.0101.0035 **Exception registering Process Logger: {0}**

PRT.0101.0055 ***{0}, {1}: sending live transition to {2}**

PRT.0101.0057E **Exception encoding transition pipeline: {0}**

Explanation Unable to send an output transition using the specified transport.

Action Check the exception message for details.

PRT.0101.0059E **Exception during send: {0}**

Explanation Cannot publish the document over the transport.

Action Check the exception message in the Integration Server error logs for details.

PRT.0101.0060 ***{0}, {1}: sending dead transition to {2}**

PRT.0101.0080 **Loading process models in package {0}**

PRT.0101.0082 **Found PE model files in {0}**

PRT.0101.0083 **Loading model fragment {0}**

PRT.0101.0084E **Exception loading model fragment {1}: {0}**
Explanation Error while reading the process model file.
Action Check the exception message for details.

PRT.0101.0085 **Skipping model fragment {0}**

PRT.0101.0086 **Deleting {0} old fragments from {1}**

PRT.0101.0087E **Exception reading fragment file {1}: {0}**
Explanation Error while reading the process model file.
Action Check the process exception message in the Integration Server error logs for details.

PRT.0101.0088 **Deleting model fragment: {0}**

PRT.0101.0089 **Deleting XML file {0}**

PRT.0101.0090 **Adding new process fragment (pkg={0}, file={1})**

PRT.0101.0091 **Unable to create directory: {0}**

PRT.0101.0118 **[MID={0}, MVers={1}] has timed out**

PRT.0101.0122E **Exception invoking timeout for {1}, {2}: {0}**
Explanation Failed to invoke timeout.
Action Check the exception message for details.

PRT.0101.0124E ***{0}, {1}: starting timeout: {2}**

Explanation Starting absolute timeout.

Action This is an informative message only, indicating that an absolute timeout is being started for the process and step with the displayed IDs.

PRT.0101.0140E ***{0}, {1}: killing step execution thread**

Explanation Error while saving the process model file.

Action Make sure you have write permission and network access to the file system.

PRT.0101.0143I **{0} session**

Explanation Timeout accessed an Integration Server service session to get the service thread.

Action Informative message only: indicates that an IS service session has been accessed to get the service thread.

PRT.0101.0145 **[SID={0}] Creating timer entry for join timeout**

PRT.0101.0147 ***{0} cannot start Process timeout -- type not specified**

PRT.0101.0148 ***{0}, {1}: cannot start Join timeout -- type not specified**

PRT.0101.0149 ***{0}, {1}: cannot start Step timeout -- type not specified**

PRT.0101.0150E **Registering PE transport {0}**

Explanation Unable to sync documents with the Broker.

Action Check the error message for details.

PRT.0101.0151 **Using new PE transport {0} as default**

PRT.0101.0152 **Removing PE transport {0}**

PRT.0101.0153 **Default PE transport is {0}**

PRT.0101.0154 **Default PE transport is {0}; deferred**

PRT.0101.0155 **Not performing Broker push (not connected)**

PRT.0101.0156 **Pushing doctypes to Broker**

PRT.0101.0157 **Broker push error: {0}**

PRT.0101.0158 **Sending {2} over {0} to {1}**

PRT.0101.0160 **Broadcasting {1} over {0}**

PRT.0101.0162 **Sending {1} over {0}**

PRT.0101.0175 ***{0}, {1}: new process instance created on {2}**

PRT.0101.0178 **Warning. Process model {0} is inactive**

PRT.0101.0180 **NON-START STEP. Step {1} of model {0} is a non-start step**

PRT.0101.0182 **[MID={0}, MVer={1}, fragment={2}] using newly-created pid**

PRT.0101.0183 **checking out process stack**

PRT.0101.0184 **using pre-existing stack. Parent process ID = {0}**

PRT.0101.0186 **creating brand new process stack**

PRT.0101.0195 **setting process status to RUNNING**

PRT.0101.0196 ***PID={0}, MID={1}, MVer={2}: process started**

PRT.0101.0197 ***{0}, MID={1}, MVer={2}: process restarting**

PRT.0101.0199 **[PID={0}, Delta={1}] updating Track Count**

PRT.0101.0202 ***PID={0}, MID={1}, MVer={2}: process completed**

PRT.0101.0206 **Cache cleanup running every {0} seconds and every {1} instances**

PRT.0101.0207 ***{0}, {1}: transitioning to cancel step**

PRT.0101.0223 **looking for PID for CID {0}**

PRT.0101.0224 **[MID={1}] matching bizdoc to model. Type name = {0}. Require start = {2}**

PRT.0101.0228 **{0} index entries found for doctype {1}**

PRT.0101.0229 **entry({0}) ==> {1}@{2}, filter={3}**

PRT.0101.0230 **evaluateFilter(): filter = {0}**

PRT.0101.0231 **evaluateFilter(): pipe = {0}**

PRT.0101.0235 **DocID={0}, DocType={1}, ConvId={2}: processing incoming TN document**

PRT.0101.0236 **({0}) doc internal ID: {1}**

PRT.0101.0237 **({0}) doctype name: {1}**

PRT.0101.0238 **({0}) conversation ID: {1}**

PRT.0101.0240 **joining existing conversation {1}**

PRT.0101.0241 **using model ID {0}**

PRT.0101.0242E **DocID={0}, DocType={1}, ConvId={2}: no Model match for TN document**

Explanation Not starting a process instance because no process model is found that matches the business document (bizdoc).

Action Make sure there is a process model that subscribes to this business document (bizdoc).

PRT.0101.0243E **DocID={0}, DocType={1}, ConvId={2}, MID={3}: no Step match for TN document**

Explanation Unable to match a step to the business document (bizdoc).

Action Make sure at least one step in the process model subscribes to this business document (bizdoc).

PRT.0101.0244 **ConvId={0}, PID={1}: starting/joining TN process**

PRT.0101.0247 **joining process (status {0})**

PRT.0101.0248 **PROCESS DONE, CANNOT JOIN**

PRT.0101.0249 **joining at step {1} (frag {0})**

PRT.0101.0251E	**IM failed: model is disabled or non-start step**
Explanation	Unable to create a process instance because it is a non-start step or the process model is inactive.
Action	If joining a running process, make sure it has the correct conversation ID. Otherwise, make sure the process model is enabled in webMethods Monitor.

PRT.0101.0252	**Attribute {0} = {1}**

PRT.0101.0253	**BizDocAttribute {0} is required in a process, but no definition is available on this server**

PRT.0101.0254E	**Exception fetching data from TN profile store: {0}**
Explanation	Unable to get the Trading Networks partner profile summary.
Action	Check the Trading Networks partner profile.

PRT.0101.0255	**Profile Field {0} = {1}**

PRT.0101.0256E	**Extended profile field {0} is required in a process, but no definition is available on this server**
Explanation	Unable to get the extended profile field.
Action	Make sure the extended profile field is populated.

PRT.0101.0257E	**Exception fetching data for field {1}: {0}**
Explanation	Unable to get the Trading Networks extended profile field.
Action	Check the Trading Networks extended profile field.

PRT.0101.0258	**Duplicate document: {0}. Document rejected**

PRT.0101.0278	***{0}, {1}: handling transition event to {2}**

PRT.0101.0284	***{0}, {1}: handling native document {3} on {2}**

PRT.0101.0289E	**NO MATCHING STEP**
Explanation	Unable to find the step that subscribes to this document.
Action	Make sure a step in the process model subscribes to this document.

PRT.0101.0290E	**Document {2} does not match to any step in process {0} on {1}**
Explanation	Unable to find the step that subscribes to this document.
Action	Make sure a step in the process model subscribes to this document.

PRT.0101.0292	**Document {2} matches step in process {0} on {1}**

PRT.0101.0294E	**NO MATCHING INPUT for pid**
Explanation	Unable to get the input definition for this document.
Action	Make sure the document exists and is synced to the Broker.

PRT.0101.0295E	***{0}, {1}: document {3} is NOT a valid published input**
Explanation	Unable to get the input definition for this document.
Action	Make sure the document exists and is synced to the Broker.

PRT.0101.0297	***{0}, {1}, document {3} is a valid published input**

PRT.0101.0300E	***{0}, {1}: using correlation service {2}**
Explanation	An error occurred while accessing the ProcessAudit database.
Action	Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.

PRT.0101.0301E	**pipe: {0}**
Explanation	An error occurred while accessing the ProcessAudit database.
Action	Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.

PRT.0101.0303 ***{0}, {1}: correlating to TN conversation id**

PRT.0101.0305E ***{0}, {1}: correlated to process id**

Explanation An error occurred while accessing the ProcessAudit database.

Action Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.

PRT.0101.0306 **correlation ID mapped to existing PID**

PRT.0101.0307E **Error invoking correlation svc {1}: {0}**

Explanation Failed to invoke the specified correlation service.

Action Check the process exception in the Integration Server error logs for details.

PRT.0101.0309 **dispatching event : {0}**

PRT.0101.0310 ***{0}, {1}: starting step execution**

PRT.0101.0311E ***{0}, {1}: no process fragment contains this step**

Explanation Unable to find the step in the process model fragment file.

Action Make sure generated model fragment file contains this step.

PRT.0101.0314 **Exception dispatching step: {0}**

PRT.0101.0315E **Exception handling transition event: {0}**

Explanation Failed to handle a process transition document.

Action Check the exception message for details.

PRT.0101.0317W **Error joining because it is terminated already**

Explanation Cannot join a process that is not running.

Action Check the exception message for details.

PRT.0101.0318 ***{0}, {1}: using correlation field {2}**

PRT.0101.0319 ***{0}, {1}: correlated to disabled model {2} version {3}**

PRT.0101.0320 ***{0}, {1}: correlated to {2}, expected {3}**

PRT.0101.0335 ***{0}, {1}: start step execution**

PRT.0101.0336 ***{0}, {1}: end step execution**

PRT.0101.0337 **continuing synchronous execution at step {0}**

PRT.0101.0341 ***{0}, {1}: executing step**

PRT.0101.0343 **fragment and step validated**

PRT.0101.0347 ***{0}, {1}: pushing step on suspended list**

PRT.0101.0349 **step iteration = {0}**

PRT.0101.0356 ***{0}, {1}: step not executed, enqueueing event**

PRT.0101.0357 ***{0}, {1}: step iteration count exceeded**

PRT.0101.0358 ***{0}, {1}: setting try count to {2}**

PRT.0101.0359E **Exception executing step {1}, {2}: {0}**

Explanation The XPath expression cannot be parsed.

Action Verify that the XPath expression is valid.

PRT.0101.0360E	**Exception saving step context {1}, {2}: {0}**
Explanation	Failed to save the context of the step.
Action	Check the exception message in the Integration Server error logs for details.
PRT.0101.0361	**done preparing step for execution**
PRT.0101.0362	***{0}, {1}: logging custom audit data**
PRT.0101.0366	**no service to execute**
PRT.0101.0370	**merging pre-defined service inputs**
PRT.0101.0372	**service executed OK. After step invoke outPipe={0}**
PRT.0101.0373	***{0}, {1}: sent {2} output events**
PRT.0101.0374E	**SERVICE EXECUTION FAILED ({0}) {1}**
Explanation	Caught a service exception. If an error handler is defined, the appropriate error action will be taken. Otherwise, the process will be marked as failed.
Action	Check webMethods Monitor for details about the failure.
PRT.0101.0376E	**Exception invoking service {1}, {2}, Svc={3}: {0}**
Explanation	Failed while executing the step. Service throws an error.
Action	If an error handler is defined, the appropriate error action will be taken. Otherwise, the process will be marked as failed.
PRT.0101.0377	***{0}, {1}: transitioning to error step {2}**
PRT.0101.0378E	***{0}, {1}: terminated abnormally**
Explanation	Failure during process execution. No error handler defined for the step.
Action	Define an error handler for the failed step so that appropriate error action can be taken.

PRT.0101.0383 **considering published output {0} (doctype {1})**

PRT.0101.0385 **document: {0}. Publishing with stack {1}**

PRT.0101.0387E **missing content for document {0}**

Explanation Unable to get the document from the publish output because of a missing or corrupted document object.

Action Make sure the document is in the publish output pipeline.

PRT.0101.0388 ***{0}, {1}: published output document {2}**

PRT.0101.0389 **considering bizdoc output {0}**

PRT.0101.0390 **done with bizdoc output {0}**

PRT.0101.0391E **Exception sending output {1} of {2} for PID {3} SID {4}: {0}**

Explanation Error while sending output documents.

Action Check the exception message for details.

PRT.0101.0392 **ERROR on output {0} of {1}. Output isa {2}. Output: {3}**

PRT.0101.0395 **considering transition to step {0} on {1}**

PRT.0101.0396 ***{0}, {1}: adding dead transition to {2}**

PRT.0101.0397 ***{0}, {1}: adding live transition to {2}**

PRT.0101.0398 **synchronously following transition to {0}**

PRT.0101.0399 ***{0}, {1}: publishing transition to {2} on {3}**

PRT.0101.0400E **Exception updating track count {1}, {2}: {0}**

Explanation Failed to evaluate the condition associated with this output, possibly because of an invalid condition parameter.

Action Check the process exception message in the Integration Server error logs for details.

PRT.0101.0401 ***{0}, {1}: no track count change**

PRT.0101.0402 ***{0}, {1}: updated track count by {2} to {3}**

PRT.0101.0403 ***{0}, {1}: transition condition {2} evaluated to {3}**

PRT.0101.0412W **Cannot execute step {0} because the process was terminated already**

Explanation Cannot execute a step because the process was terminated.

Action Check for incorrect use of the correlation service.

PRT.0101.0428E **PE queue processing for step {0}**

Explanation An error occurred while executing a step.

Action See the detailed error message for specific information.

PRT.0101.0430 **event queue empty, nothing to do**

PRT.0101.0432 ***{0}, {1}: transitioning to timeout handler**

PRT.0101.0434E **Exception assembling pipeline {1}, {2}: {0}**

Explanation Cannot create a transition pipeline for the specified step.

Action Check the exception in the Integration Server error logs for details.

PRT.0101.0435 ***{0}, {1}: {2} events in the queue. Join state: {3}**

PRT.0101.0441 **dropping {0} (id {1})**

PRT.0101.0442 **update track count ({0}) as a result of dropping events after the join**

PRT.0101.0444 **returning positive join result**

PRT.0101.0445 **these events will be in the pipeline:**

PRT.0101.0447 **applying thread count DELTA of {0}**

PRT.0101.0448I ***{0}, {1}: starting join timeout**

Explanation Starting join timeout.

Action This is an informative message only, indicating that a join timeout has been started.

PRT.0101.0449I ***{0}, {1}: starting step timeout**

Explanation Starting step timeout.

Action This is an informative message only, indicating that a step has been started.

PRT.0101.0451 ***{0}, {1}: absolute timeout type is invalid**

PRT.0101.0452 **Exception: Deprecated step found {1}, {2}: {0}**

PRT.0101.0455 **Error cloning IData {0}.**

PRT.0101.0468E **Something just tried to dequeue an event with a null ID**

Explanation Unable to remove metadata from the queue.

Action Check the IllegalArgumentException message in the Integration Server error logs for details.

PRT.0101.0469E	**Document with duplicate correlation ID submitted.**
Explanation	An error occurred when a document with a duplicate correlation ID was found.
Action	Make sure each correlation ID is unique.
PRT.0101.0489	**PRTX: INSERT {0}.{1} --> p.{2}**
PRT.0101.0494	**PRTX: mapping {0}.{1} (insert={2})**
PRT.0101.0509	**Using Shared Cache for Join locks**
PRT.0101.0511E	**Can not initialize jdbc runtime storage for PE. Make sure ProcessAudit or ProcessEngine runtime pool is configured properly**
Explanation	Failed to establish a database for Process Engine storage; using repository instead.
Action	Check the Process Audit and PRT Associated Pool Alias configurations.
PRT.0101.0512E	**Storage exception: {0}**
Explanation	Exception executing an SQL statement.
Action	Check for incorrect database configuration.
PRT.0101.0513	**Storage cleaner: will run every {0} seconds**
PRT.0101.0514E	**Storage cleaner: executing stored procedure**
Explanation	An error occurred while saving the web service binding file. The user may not have the correct access to the directory.
Action	Make sure that the user has proper read/write access to the directory.
PRT.0101.0515E	**Storage cleaner: executing embedded SQL**
Explanation	An error occurred while saving the web service binding file. The user may not have the correct access to the directory.
Action	Make sure that the user has proper read/write access to the directory.

PRT.0101.0517E	**Storage cleaner: Duration {0} ms**
Explanation	An error occurred while saving the Web service binding file. The user may not have the correct access to the directory.
Action	Make sure that the user has proper read/write access to the directory.

PRT.0101.0518E	**Exception: Unable to connect to database!**
Explanation	The Web service binding file does not exist. The user may not have the correct access to the directory.
Action	Make sure that the user has proper read/write access to the directory.

PRT.0101.0519	**Storage cleaner: expiration for completed processes: {0} seconds**

PRT.0101.0521	**Storage cleaner: cannot acquire lock. Exception: {0}**

PRT.0101.0522	**Storage cleaner: expiration for failed processes: {0} seconds**

PRT.0101.0523E	**Storage cleaner: clean up for completed processes is disabled**
Explanation	The WSDL file for the web service could not be accessed. The file may not exist or it may be in the wrong directory location.
Action	Make sure that this file exists and has been deployed to the correct directory location.

PRT.0101.0531	**Exception: {0}. Step Level Retry configured for service: {1}. Retry {2} of {3} in {4} ms**

PRT.0101.0532E	**No Step Level Retry configured for step service: {0}**
Explanation	The WSDL file for the Web service could not be accessed.
Action	Make sure that the WSDL file exists and has been deployed to the generated package.

PRT.0101.0533E	**Step Level Retry count exceeded for service: {0}**
Explanation	An error occurred while accessing the process model package.
Action	Make sure that the process model has been generated and the corresponding namespace package has been created.

PRT.0101.0534	**Thread Threshold detected. Retry abandoned for {0}.**
PRT.0101.0535	**Error querying process {0} version {1} from {2}. Make sure the process is deployed for monitoring.**
PRT.0101.0550	**[MID={0}] StatusManager processing {1} request**
PRT.0101.0551	***{0}: process status changed to {1}**
PRT.0101.0552	***{0}: resuming process at {1}**
PRT.0101.0553	***{0}: restarting process at step {0}**
PRT.0101.0554	**Running process at step {0}**
PRT.0101.0601I	**web service request/reply {0}**
Explanation	Performing Web service request/reply.
Action	Informative message only: indicates that the PRT dispatcher is processing a Web service request/reply.
PRT.0101.0700I	**Adding thread to thread table, thread id={0}**
Explanation	Added a thread with the following thread ID to the Process Engine's internal thread table.
Action	Informative message only: indicates the thread ID for a thread added to the Process Engine's internal table.
PRT.0101.0701I	**Getting thread from thread table, thread id={0}**
Explanation	Retrieved a thread with the following thread ID from the Process Engine's internal thread table.
Action	Informative message only: indicates the thread ID for a thread retrieved from the Process Engine's internal table.

PRT.0101.0702 **Deleting thread from thread table, thread id={0}**

PRT.0101.0830 **JMS Connection Alias for PE 'PE_NONTRANSACTIONAL_ALIAS' has not been configured.**

PRT.0101.0831 **Error creating JMS internal topic: {0}**

PRT.0101.0832 **Error updating client group permissions: {0}**

PRT.0101.0833 **Error creating JMS connection alias: {0}**

PRT.0101.0850E **[MID={0}] Now listening to path: "{1}" for e-Forms on jcr "{2}"**

Explanation This is an informative message. The e-form configuration is now listening for events.

Action To generate an event, place an e-form into the My webMethods Server folder location that the listener is monitoring.

PRT.0101.0851 **[MID={1}] Error with Content Repository "{2}". Check if the repo is running, login credentials and repo connection information is correct. {0}**

PRT.0101.0852E **[MID={1}] Error disabling/removing listener from Content Repository "{2}". {0}**

Explanation Listener cannot be removed because the repository is down or does not exist.

Action Make sure the repository is still running and connected, and that the listener is valid.

PRT.0101.0853 **[MID={0}] Content Repository "{1}" not configured.**

PRT.0101.0854 **[MID={0}] Listener for e-Forms at path: "{1}" has been disabled from jcr "{2}"**

PRT.0101.0855 **[MID={1}] Error adding listener to Content Repository "{2}". {0}**

PRT.0101.0856E **[MID={1}] Problem reading E-form config file: "{2}". {0}**

Explanation An invalid e-form configuration file or unknown file type using the CSP or JCR file name extension was found in WmPRT\config\.

Action Log in to My webMethods and delete and then re-create the e-form configuration in the Define Environments application page.

PRT.0101.0857E	**[MID={0}] Unable to change listener please disable all other models currently using this listener: "{1}"**
Explanation	The SOAP processor aborted processing of the SOAP message because of a problem with the message header.
Action	Make sure the header entries of the SOAP message are valid.
PRT.0101.0858E	**[MID={0}] Cannot edit access for PORT 15006. Please ensure to manually add access for "wm.prt.eforms:update" "wm.server:connect" "wm.server:disconnect" "wm.server:ping".**
Explanation	E-forms requires the specified port to be open.
Action	Make sure that that port 15006 is open and has access for "wm.prt.eforms:update", "wm.server:connect", "wm.server:disconnect", and "wm.server:ping".
PRT.0101.0859E	**[MID={0}] Cannot start e-form process because doc type: "{1}" does not exist. For e-form instance at: "{2}". Please recreate the e-form doc or rebuild the model(s).**
Explanation	The document type related to this listener does not exist on the Integration Server.
Action	Re-create the e-form document type and rebuild the affected process model(s).
PRT.0101.0860	**[MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}**
PRT.0101.0861	**[MID={1}] Error restarting listener(s) to Content Repository "{2}". {0}**
PRT.0101.0862	**Content Repository currently has no models associated to it. No reason to restart the repository at this time.**
PRT.0101.0863	**[MID={1}] Cannot retrive password: "{2}". {0}**
PRT.0101.0864	**No model(s) enabled using this listener "{0}". Listener will not be restarted.**
PRT.0101.0865	**[MID={0}] Content Repository currently has a listener listening in that location. No new listener added to listening path: "{1}" for e-Forms on jcr "{2}".**

PRT.0101.0900E	**Monitor: {0}**
Explanation	Type mismatch in BPEL assign.
Action	Check that the mapping performed in the assign step is valid. Mapping is not typesafe.

PRT.0101.0902E	**Invalid Logging Level**
Explanation	Unable to find type of the field for the record using the specified part and Xpath query.
Action	Check that the type used in the part and XPath query is defined in your Integration Server instance. This can occur when the field or record are not defined in the Integration Server instance to which the corresponding process has been deployed.

PRT.0101.0903E	**Log Transitions value must be either "True" or "False"**
Explanation	Unable to find type of the field for the record using the specified part and Xpath query.
Action	Check that the type used in the part and XPath query is defined in your Integration Server instance. This can occur when the field or record are not defined in the Integration Server instance to which the corresponding process has been deployed.

PRT.0101.0907	**Enable Resubmission value must be either "True" or "False"**

PRT.0101.0908	**[MID={0}, MVers={1}] Model does not exist.**

PRT.0101.0909	**[MID={0}] QoS cannot be changed because it was generated from a pre-7.0 version of Modeler.**

PRT.0101.0910	**[MID={0}] Logging level for Model cannot be set below minimum value of {1}.**

PRT.0101.1001	**CheckDuplicates processing {0}, uuid, {1}**

PRT.0101.1002	**CheckDuplicates processed {0}, uuid, {1}, status, {2}**

PRT.0101.1003	**CheckDuplicates throwing ISRuntimeException {0}, uuid, {1}**

PRT.0101.1100 **Error trying to get JDBC pool configuration using functional alias {0}. Business calendar based timeouts will not be able to be evaluated.**

PRT.0101.1101 **Exception trying to get JDBC pool configuration: {0}**

PRT.0101.1102 **Unable to initialize MWS library. Business calendar based timeouts will not be able to be evaluated.**

PRT.0101.1103 **Exception trying to initialize MWS library: {0}**

PRT.0101.1200 **Business timeout is invalid: {0}**

PRT.0101.1201 **Business calendar alias {0} does not exist**

PRT.0101.1202 **Business calendar evaluator does not exist**

PRT.0101.1300 ***{0}, {1}: did not start timer, no end time specified.**

PRT.0101.1301 ***{0}: executing Process Timeout**

PRT.0101.1302 ***{0}, {1}: executing Step Timeout**

PRT.0101.1303 ***{0}, {1}: executing Join Timeout**

PRT.0101.1304 **[MID={0}, SID={1}] Error killing step thread**

PRT.0101.1305 **[MID={0}] Constructing process timeout**

PRT.0101.1306 **[MID={0}, SID={1}] Constructing step timeout**

PRT.0101.1307 **[MID={0}, SID={1}] Constructing join timeout**

PRT.0101.1309 ***{0}, {1}: cancelling step timeout**

PRT.0101.1310 ***{0}, {1}: cancelling join timeout**

PRT.0101.1400 **Exception trying to fail the process *{1}: {0}**

PRT.0101.1401 ***{0}, {1}: sending Dead Path PTE to {2} on {3}**

PRT.0101.1402 ***{0}, {1}: process version changed from {2} to {3}**

PRT.0101.1403 ***{0}, {1}: taking unsatisfied join transition {2}**

PRT.0101.1500 **made input pipe from {0} events**

PRT.0101.1600 **Unable to get Optimize process data collector. Tracking enabled models will not be logged to Optimize.**

PRT.0101.1601 **Exception trying to get Optimize process data collector: {0}**

PRT.0101.1602 **Exception trying to shut down Optimize data collector: {0}**

PRT.0101.1742 **Failed to restart e-form listener for {0}.**

PRT.0101.1743 **Restart of e-form listener: {0} successful.**

PRT.0101.9123E **No value was supplied for the required parameter {0}.**

Explanation A parameter is missing or corrupted.

Action Make sure that the parameter object exists.

PRT.0101.9124E	**An invalid value was supplied for the required parameter {0}. The bad value was {1}.**
Explanation	The value of the specified key is invalid.
Action	Make sure the value is the specified type.

PRT.0101.9125E	**Service {0} failed.**
Explanation	Caught a service exception.
Action	Check the service exception message in the Integration Server error logs for details.

PRT.0101.9135E	**Cannot read frag file {0}: the file does not exist.**
Explanation	An error occurred while reading the process model file: the file does not exist.
Action	Make sure the model has been generated correctly.

PRT.0101.9136E	**Cannot read frag file {0}: the file is not readable.**
Explanation	An error occurred while reading the process model file: the file is not readable.
Action	Check the file permissions.

PRT.0101.9137E	**Malformed frag file {0}: the file does not contain the 'fragment' key.**
Explanation	Unable to read the process model file; the file may be corrupted.
Action	Regenerate the process model.

PRT.0101.9138E	**IOException reading frag file {0}**
Explanation	An error occurred while reading the process model file.
Action	REfer to the process exception in the Integration Server error logs for details.

PRT.0101.9139E	**Cannot write frag file {0}: the file already exists and is not writeable.**
Explanation	An error occurred while saving the process model file: the file already exists.
Action	Check the file permissions.

PRT.0101.9151E	**Cannot rebind role {0} from partner ID {1} to partner ID {2}**
Explanation	Unable to add a TN sender or receiver role because the current public role information indicates a different partner ID.
Action	Make sure the sender or receiver matches the partner ID, then restart the process.

PRT.0101.9195E	**Could not enable model "{0}" version "{1}" for {2}**
Explanation	Cannot get a lock for global data.
Action	Determine whether another step in the process currently has a lock on global data.

PRT.0101.9196E	**Could not disable model "{0}" version "{1}" for {2}**
Explanation	Cannot get a lock for global data.
Action	Determine whether another step in the process currently has a lock on global data.

PRT.0101.9197E	**Could not acquire lock "{0}"**
Explanation	A field is not present in global data when using BPEL assign.
Action	Make sure the data exists.

PRT.0101.9201	**Correlated process ID {0} is incorrect; a process already exists with that process ID and a different model ID**

PRT.0101.9204E	**The CID returned from {0} is too long. CID length is {1}; maximum allowed is {2}**
Explanation	The conversation ID has exceeded the maximum allowed length.
Action	Shorten the conversation ID and rerun the process.

PRT.0101.9205E	**Correlation ID joins to a process instance that is no longer running. PID: {0}**
Explanation	Joins are not allowed on process instances that are not in running status.
Action	Change the state to running or start a new process instance.

PRT.0101.9206	**Intermediate Receive Step {2} of model {0} version {1} does not correlate to existing Process ID**

PRT.0101.9215E	**Cannot start process {0}: unable to determine the appropriate model**
Explanation	The process model ID has not been properly stored in the Process Engine DB.
Action	Check that the DB is working properly and rerun the process.

PRT.0101.9216E	**Cannot start process {0} with model {1} at step {2}: there is no fragment defined that contains that step**
Explanation	The process model fragment file does not contain the definition for the specified step.
Action	Check that the step is properly generated in the fragment file. If not, regenerate the process.

PRT.0101.9217E	**Cannot start process {0} at step {1}: there is no such step defined in fragment {2}**
Explanation	The process model fragment file does not contain the definition for the specified step.
Action	Check that the step is properly generated in the fragment file. If not, regenerate the process.

PRT.0101.9218	**Error changing version for process {0} with model {1} at step {2} from version {3} to {4}: there is no fragment defined that contains that step**

PRT.0101.9228E	**Missing ConversationID for call to getInstanceId()**
Explanation	Cannot start a process because a conversion ID was not present in the Trading Networks document envelope.
Action	Make sure that the conversation ID is properly defined and extracted.

PRT.0101.9229E	**Model {0} was specified, but there is no step in this model for a bizdoc of type {1}**
Explanation	Cannot find any step in the model that subscribes to this document.
Action	Make sure the model has a step that subscribes to this document.

PRT.0101.9230E	**Couldn't start process. Either the model is disabled or this document targets a non-start step.**
Explanation	The process cannot be started either because the model is disabled or the step subscribing to this document is not a start step.
Action	Make sure the model is enabled and that the step that subscribes to this document is a start step.

PRT.0101.9231E	**No ConversationID available; PE bizdoc processing fails**
Explanation	Cannot start a new process or join an existing process because a conversation ID was not present in the TN document envelope.
Action	Make sure that conversation ID is properly defined and extracted.

PRT.0101.9244E	**PID {0}: Cannot {1} process; status is {2}**
Explanation	The process instance has one of the following statuses: STAT_UNKNOWN, STAT_RUNNING, STAT_SUSPENDED, STAT_FAILED, STAT_CANCELLED, or STAT_DONE. Because the process instance is in one of these states, it cannot run the requested action. The requested action will be one of the following: START, SUSPEND, RESUME, CANCEL, FAIL, RESTART, QUIET, or DONE.
Action	Make sure the action is allowed on processes with the specified status.

PRT.0101.9245E	**PID {0}: Bad command RESTART; target step is missing**
Explanation	Unable to restart the process because of a missing or corrupted target step ID in the pipeline.
Action	Check the pipeline then restart the process.

PRT.0101.9246E	**PID {0}: Bad command RESTART; pipeline is missing**
Explanation	Unable to restart the process because of a missing or corrupted pipeline.
Action	Check the pipeline then restart the process.

PRT.0101.9248E	**PID {0}: Bad command RESTART; pipeline is missing /ProcessData**
Explanation	Unable to restart the process because of a missing or corrupted ProcessData object in pipeline.
Action	Check the pipeline then restart the process.

PRT.0101.9249E	**PID {0}: Bad command RESTART; pipeline is missing /ProcessData/LastEvents**
Explanation	The process instance was not restarted because the pipeline is missing.
Action	Make sure that the pipeline is properly logged.

PRT.0101.9250E	**PID {0}: Bad command RESTART; RestartParameters is missing**
Explanation	Cannot restart the process instance because some or all of the restart parameters are missing.
Action	Make sure that all of the restart parameters are present in the pipeline.

PRT.0101.9251E	**PID {0}: restart failed because the supplied pipeline contains an invalid ProcessInstanceID {1}**
Explanation	Unable to restart due to a invalid process instance ID.
Action	Check the pipeline then restart the process.

PRT.0101.9253E	**MID {0}: Cannot restart process; frag {1} step {2} does not define bizdoc {3} as input**
Explanation	Process cannot be restarted because the target step does not define the document as an input.
Action	Make sure that the target step specifies the document as an input.
PRT.0101.9254E	**PID {0}: failed to restart at step {1} because at least one valid event is needed in path /ProcessData/LastEvents/ of the supplied pipeline {2}**
Explanation	The process cannot be restarted because all documents in the pipeline have been removed.
Action	Start a new instance of the process.
PRT.0101.9255E	**MID {0} Failed to restart the process because Model {0} is not enabled**
Explanation	The process cannot be restarted because the model is disabled.
Action	Enable the model and restart again.
PRT.0101.9256	**PID {0} Failed to execute process instance status change**
PRT.0101.9262E	**PID {0}: Could not get a connection in {1}**
Explanation	An error occurred while trying to connect to Process Engine DB storage.
Action	Make sure that Process Engine DB storage is properly configured and running.
PRT.0101.9263E	**PID {0}: Update thread count failed**
Explanation	An error occurred while communicating with the Process Engine DB.
Action	Make sure that the Process Engine DB is properly configured and running.
PRT.0101.9264	**Cannot create new instance of model {0} version {1}, it is not enabled**
PRT.0101.9265	**Step {2} of model {0} version {1} is not a start step**
PRT.0101.9285E	**Could not create TN facade**
Explanation	Unable to create a Trading Networks implementation.
Action	Check the process exception message in the Integration Server error logs for details.

PRT.0101.9286E	**Could not handle doc output**
Explanation	Error while handling the output of a business document (bizdoc).
Action	Check the process exception message in the Integration Server error logs for details.

PRT.0101.9287E	**bizdoc_output() failed because pipeline object {0} is not a TN bizdoc object**
Explanation	The specified document is the wrong type.
Action	Make sure the document is a Trading Networks document.

PRT.0101.9301E	**Exception occurred during correlation or cross-reference operation**
Explanation	Unable to perform ID correlation because an error occurred while connecting to Process Engine DB storage.
Action	Refer to the process exception in the Integration Server error logs for details.

PRT.0101.9306	**Correlation field {0} does not exist in published document {1}**
Explanation	A correlation field is specified for the document starting this step, but the correlation field does not exist in the document at run time.
Action	Ensure that the correlation field is specified in the published document to establish correlation.

PRT.0101.9316	**Could not get process ID from conversation ID**

PRT.0101.9321	**Thread sleep wait interrupted: {0}**

PRT.0101.9322	**Variable "{0}" does not exist in the pipeline**

PRT.0101.9340E	**Bad join expression; invalid character {0}**
Explanation	The specified character is not allowed in the join expression.
Action	Verify that the join expression is valid.

PRT.0101.9341E	**Bad XOR join specification {0}; id required**
Explanation	The XOR join expression does not contain an unique ID.
Action	Make sure that a unique ID is present for the XOR join expression.

PRT.0101.9342E **Bad XOR join specification; unparseable timeout {0}**

Explanation The timeout value of the XOR join expression is not in a valid format.

Action Make sure the timeout value for the XOR join expression is in milliseconds.

PRT.0101.9343E **Bad join expression; one or more unmatched)**

Explanation Missing parenthesis in a join expression.

Action Make sure the join expression is valid.

PRT.0101.9344E **Bad join expression; one or more unmatched (**

Explanation Missing parenthesis in a join expression.

Action Make sure the join expression is valid.

PRT.0101.9345E **Bad join expression; bad standalone join spec {0}**

Explanation Invalid standalone in a join expression.

Action Make sure the join expression is valid.

PRT.0101.9346 **Global data is no longer supported. Model {0} : SID {1}**

PRT.0101.9356E **Can not set track count to {0}; only 1 allowed for TransitionMetaData**

Explanation The track count is not 0 or 1.

Action Make sure the track count is 0 or 1.

PRT.0101.9358E **Exception while executing SQL statement**

Explanation The SQL processor failed to execute this statement because there is an error in the statement itself - a reference to a non-existent table, a non-existent (misspelled) field, or an incorrect SQL keyword.

Action Check the process exception message in the Integration Server error logs for details.

PRT.0101.9360 **XPath data is no longer supported. Model {0} : SID {1}**

PRT.0101.9412 **PID {0}: Cannot execute step {1} because the process was terminated already**

PRT.0101.9417E **Cannot publish {0}. Document is not in pipeline.**

Explanation Cannot publish document; the document is not in the pipeline.

Action Check for improper or missing mapping in the Integration Server flow service.

PRT.0101.9432 **Task execution was unsuccessful. The task engine returned status: {0} and error message: {1}**

Explanation The Task Engine has returned an error to the Process Engine

Action Check the My webMethods Server logs in ..\MWS\server\instances\<instanceName>\logs.

PRT.0101.9467 **Cannot enqueue an event with a null ID**

PRT.0101.9469 **Error encountered: Document with duplicate correlation ID submitted.**

PRT.0101.9613 **There are no enabled Processes matching this trigger: {0}**

Explanation A document has arrived on a subscriptionTrigger but there are no enabled processes associated with this trigger. Therefore, the document is ignored.

Action In most cases this means your process is not enabled. Log in to My webMethods and use webMethods Monitor to select the process and enable it for execution, then try again.

PRT.0101.9862 **This service has been deprecated and is no longer supported.**

Explanation The service executed is no longer supported in the current release.

Action Consult the release readme file and the Process Engine Administrator's guide for deprecated and removed services to determine if there is a replacement service.

PRTExceptionConstants.EXC_AA_CASE_ERROR – AgileApps returned status: {0} and error message: {1}

PRTExceptionConstants.EXC_AA_CASE_NOCREATE – Case type {0} has circular dependency on Model {1}

PRTExceptionConstants.EXC_EFORM_DUP_FRIENDLYNAME – Friendly name: {0} already in use please choose another.

PRTExceptionConstants.EXC_FILE_UTILS_FILE_EXISTS – File "{0}" already exists.

PRTExceptionConstants.EXC_FILE_UTILS_VALIDATE_DIR – File or directory "{0}" is not in the "{1}" directory.

PRTExceptionConstants.EXC_PT_JOINTIMEOUT – The step "{2}" of model "{0}" with process id of "{1}" has join timed out, with no timeout step or error step to process.

PRTExceptionConstants.EXC_SDA_CA_DYNAMIC_DUPLICATE_FIELD_ERR – Dynamic Call Activity document list contains duplicate values for {0} field.

PRTExceptionConstants.EXC_SDA_CA_DYNAMIC_MISSING_FIELD_ERR – Dynamic Call Activity document does not contain {0} field.

PRTExceptionConstants.EXC_SDA_CA_DYNAMIC_MISSING_ROOT_DOC_ERR – Dynamic Call Activity CallActivityModels document list does not exist.

PRTExceptionConstants.EXC_SD_CIDLONG2 – The Correlation ID is too long. The length is {0}; maximum allowed is {1}

PRTExceptionConstants.EXC_SM_FORBID – PID {0} Cannot restart process; It was initiated from AgileApps

PRTExceptionConstants.EXC_SM_NOACTFORSTAT...0 – PID {0}: Cannot {1} a process instance with a status of {2}.

PRTExceptionConstants.EXC_TRANSITION_NOT_FOUND – Transition Key {0} could not be found for Process ID {1}.

24 Realtime Monitoring Messages

WEPRME0001 **The user name must not be null.**

WEPRME0002 **The SQL statement must not be null.**

WEPRME0003 **The temporal validity approach must not be null.**

WEPRME0005 **The class of the user-defined function must not be null.**

WEPRME0007 **The database source builder must not be null.**

WEPRME0008 **Persistency for a database source is currently not supported.**

WEPRME0009 **The class of the database source builder must not be null.**

WEPRME0010 **Persistency for tables is currently not supported.**

WEPRME0011 **The source adapter must not be null.**

WEPRME0012 **The authorization module does not currently support persistency.**

WEPRME0013 **The source adapter class must not be null.**

WEPRME0014 **The subscription mode must not be null.**

WEPRME0015 **The sink adapter must not be null.**

WEPRME0016 **The unsubscription mode must not be null.**

WEPRME0017 **The sink adapter class must not be null.**

WEPRME0018 **The authorization privilege must not be null.**

WEPRME0019 **{0} because the connection has already been closed.**

WEPRME0020 **{0} because the connection has been shut down by the server.**

WEPRME0021 **Unable to close the connection; it has already been shut down by the server.**

WEPRME0022 **The batch job cannot be started because the connection has been already closed.**

WEPRME0023 **The batch job is already active.**

WEPRME0024 **The temporal validity approach {0} requires the use of an instance of SourceAdapter.**

WEPRME0025 **Unsupported approach: {0}.**

WEPRME0026	**The temporal validity approach {0} requires the use of an instance of SinkAdapter.**
WEPRME0027	**The temporal validity approach {0} requires the use of an instance of PnSinkAdapter.**
WEPRME0028	**The temporal validity approach {0} requires the use of a subclass of SourceAdapter.**
WEPRME0029	**The temporal validity approach {0} requires the use of a subclass of PnSourceAdapter.**
WEPRME0030	**The temporal validity approach {0} requires the use of a subclass of SinkAdapter.**
WEPRME0031	**The temporal validity approach {0} requires the use of a subclass of PnSinkAdapter.**
WEPRME0032	**The user {0} does not have the privilege to add the query.**
WEPRME0033	**A user can only add a query to his/her own schema.**
WEPRME0034	**The user {0} does not have the privilege to use the query.**
WEPRME0035	**The user {0} does not have the privilege to add the user-defined function.**
WEPRME0036	**Current system configuration does not support persistency.**
WEPRME0037	**The user {0} does not have the privilege to remove the user-defined function.**
WEPRME0038	**The user {0} does not have the privilege to add the database source.**
WEPRME0039	**The user {0} does not have the privilege to remove the database source.**

WEPRME0040 **The user {0} does not have the privilege to use the database source.**

WEPRME0041 **The user {0} does not have the privilege to add the table.**

WEPRME0042 **The user {0} does not have the privilege to remove the table.**

WEPRME0045 **The user {0} does not have the privilege to remove the query.**

WEPRME0046 **The user {0} does not have the privilege to add the subscription.**

WEPRME0047 **A user can only add a subscription to his/her own schema.**

WEPRME0048 **The user {0} does not have the privilege to remove the subscription.**

WEPRME0049 **The user {0} does not have the privilege to use the subscription.**

WEPRME0050 **The user {0} does not have the privilege to grant the privilege.**

WEPRME0051 **The user {0} does not have the privilege to revoke the privilege.**

WEPRME0052 **The user {0} does not have the privilege to check the privilege.**

WEPRME0053 **The batch job cannot be executed because the connection has been closed.**

WEPRME0054 **The batch job cannot be executed because the connection has been shut down by the server.**

WEPRME0055 **No active batch job to execute.**

WEPRME0056 **The event engine has already been shut down.**

WEPRME0057 **An unexpected interrupt has occurred.**

WEPRME0059 **Calling the push method is not allowed after calling the done method.**

WEPRME0060 **Calling the heartBeat method is not allowed after calling the done method.**

WEPRME0067 **Init must be called before opening the adapter.**

WEPRME0068 **The following command is unknown: {0}.**

WEPRME0069 **The temporal validity approach {0} requires the use of an instance of PnSourceAdapter.**

WEPRME0070 **A user can only add a source to his/her own schema.**

WEPRME0071 **The artefact must not be null.**

WEPRME0072 **The query identifiers cannot be delivered.**

WEPRME0073 **The query cannot be prepared.**

WEPRME0074 **The query cannot be checked.**

WEPRME0075 **The query properties cannot be retrieved.**

WEPRME0076 **The server function cannot be registered.**

WEPRME0077 **The function cannot be deregistered.**

WEPRME0078 **The server data source cannot be registered.**

WEPRME0079 **The data source cannot be deregistered.**

WEPRME0080 **The server table cannot be registered.**

WEPRME0081 **The table cannot be deregistered.**

WEPRME0082 **The source cannot be prepared.**

WEPRME0083 **The query cannot be started.**

WEPRME0084 **The query cannot be stopped.**

WEPRME0085 **The sink cannot be subscribed.**

WEPRME0086 **The sink cannot be unsubscribed.**

WEPRME0087 **The earliest possible subscription time cannot be determined.**

WEPRME0088 **The earliest possible unsubscription time cannot be determined.**

WEPRME0089 **The server sink cannot be subscribed.**

WEPRME0090 **The server sink cannot be unsubscribed.**

WEPRME0091 **The privilege cannot be granted.**

WEPRME0092 **The privilege cannot be revoked.**

WEPRME0093 **The privilege cannot be checked.**

WEPRME0094 **The identifiers cannot be retrieved.**

WEPRME0095 **The registration cannot be checked.**

WEPRME0096 **The query metadata cannot be delivered.**

WEPRME0097 **Version mismatch between client and server. Cannot connect to server version {0} using client version {1}. Use a client version between {2} and {3} instead. Your current client version can only connect to server versions between {4} and {5}.**

WEPRME0098 **Unable to connect to any of the provided servers: {0}.**

WEPRME0099 **This operation is currently not supported in high availability mode.**

WEPRME0100 **The query head cannot be retrieved.**

WEPRME0101 **In high availability mode, this operation is currently only supported using a remote connection.**

WEPRME0102 **The SQL statement contains syntactical errors.**

WEPRME0104 **Unrecognized semantic exception. Please report the SQL statement to your software supplier.**

WEPRME0105 **The {0} argument of the {1} aggregation must be numeric.**

WEPRME0106 **The types of the arguments of the aggregation do not match the required argument types.**

WEPRME0107 **The field {0} is unknown or not visible.**

WEPRME0108 **The argument of the ABS function must be numeric.**

WEPRME0109 **In the case function, the type of the {0} result expression does not match the types of the previous result expressions ({1}, {2}).**

WEPRME0110 **The signature of the user-defined function {0} does not match the specified types ({1}).**

WEPRME0111 **The user-defined function {0} is unknown or not visible.**

WEPRME0112 **The {0} argument of the {1} must be numeric.**

WEPRME0113 **The {0} argument of the {1} must be of character/string type.**

WEPRME0114 **The types of the arguments of the operation do not match the required argument types.**

WEPRME0115 **The arguments of the {0} comparison cannot be compared ({1}, {2}).**

WEPRME0116 **The expression list contains constants of different types.**

WEPRME0117 **The types of the expression and the constants in the expression list cannot be compared ({0}, {1}).**

WEPRME0118 **Only expressions and star selections are permitted in a selection list.**

WEPRME0119 **An aggregate is not allowed inside a WHERE clause.**

WEPRME0120 **Only expressions are permitted in a GROUP BY clause.**

Explanation The GROUP BY clause contains an entry that is not an expression.

Action Replace the entry by a valid expression.

WEPRME0121 **The {0} constant listed in the set condition must have the same size as the specified field list.**

WEPRME0122 **The types of the field and the constants in the constant list cannot be compared ({0}, {1}).**

WEPRME0123 **The source {0} is unknown or not visible.**

WEPRME0124 **The size of a count-based window must be greater than zero.**

Explanation The query contains an invalid size. This refers to the ROWS argument in an SQL query, or the size attribute of a window element in an XML query.

Action Specify a valid size.

WEPRME0125 **The sliding size specification of a count-based window must be greater than zero.**

Explanation The query contains an invalid sliding size. This refers to the SLIDE argument in an SQL query, or the increment attribute of a window element in an XML query.

Action Specify a valid sliding size.

WEPRME0126 **The duration of a time-based window must be greater than zero.**

Explanation The query contains an invalid duration. This refers to the RANGE argument in an SQL query, or the size attribute of a window element in an XML query.

Action Specify a valid duration.

WEPRME0127	**The sliding size specification of a time-based window must be greater than zero.**
Explanation	The query contains an invalid sliding size. This refers to the SLIDE argument in an SQL query, or the increment attribute of a window element in an XML query.
Action	Specify a valid sliding size.
WEPRME0128	**The DURATION argument of a MATCHING clause must be greater than zero.**
WEPRME0129	**The WITHIN argument of a MATCHING clause must be greater than zero.**
WEPRME0130	**Duplicate definition for the pattern state ''{0}''.**
WEPRME0131	**The DEFINE clause does not define all the pattern states required by the specified pattern.**
WEPRME0132	**The field {0} is already defined by the input query.**
WEPRME0133	**The type of the defined field and the type of its default value do not match ({0}, {1}).**
WEPRME0134	**The type of the defined field and the type of the assigned value do not match ({0}, {1}).**
WEPRME0135	**The field names ''START_TIMESTAMP'' and ''END_TIMESTAMP'' are reserved for additional information provided by pattern matching.**
WEPRME0136	**The identifier for a pattern state must be a single character.**
WEPRME0137	**An aggregate is not allowed inside the condition in an action definition.**
WEPRME0138	**The condition of an action definition must be a predicate.**

WEPRME0139 **An aggregate is not allowed inside an action definition in a MATCHING clause.**

WEPRME0140 **The right-hand side of an action definition must be an expression.**

WEPRME0143 **Only predicates are permitted in the ON clause of a join.**

WEPRME0144 **Only predicates are permitted in a WHERE clause.**

WEPRME0145 **The {0} operation requires identical output format of the involved subqueries.**

WEPRME0146 **Only predicates are permitted in a disjunction.**

WEPRME0147 **Only predicates are permitted in a conjunction.**

WEPRME0148 **Only predicates are permitted in a negation.**

WEPRME0149 **The EXISTS clause is currently not supported.**

WEPRME0150 **An SQL expression list in a relational expression is currently not supported.**

WEPRME0152 **Only an expression is permitted as the first argument of a comparison.**

WEPRME0153 **Only an expression is permitted as the second argument of a comparison.**

WEPRME0154 **Only constants are allowed in the set of an IN clause.**

WEPRME0155 **A subquery in an IN clause is currently not supported.**

WEPRME0156 **Only expressions are permitted as the first argument of a BETWEEN clause.**

WEPRME0157 **Only expressions are permitted as the second argument of a BETWEEN clause.**

WEPRME0158 **The arguments of the BETWEEN clause cannot be compared ({0}, {1}).**

WEPRME0159 **The first argument of the BETWEEN clause is greater than the second argument.**

WEPRME0160 **Only expressions are permitted in the IS NULL clause.**

WEPRME0161 **Only expressions are permitted in {0}.**

WEPRME0162 **Only expressions are permitted in an exponentiation.**

WEPRME0163 **Only expressions are permitted in a unary operation.**

WEPRME0164 **Only expressions are permitted in the WHEN clause of a simple CASE statement.**

WEPRME0165 **Only expressions are permitted in the THEN clause of a simple CASE statement.**

WEPRME0166 **Only expressions are permitted in the ELSE clause of a simple CASE statement.**

WEPRME0167 **Only predicates are permitted in the WHEN clause of a boolean CASE statement.**

WEPRME0168 **Only expressions are permitted in the THEN clause of a boolean CASE statement.**

WEPRME0169 **Only expressions are permitted in the ELSE clause of a boolean CASE statement.**

WEPRME0170 **Duplicate field definition in recursive query.**

WEPRME0171 **The number of defined fields in the recursive query does not match the number of fields in the subquery.**

WEPRME0172 **The defined field name does not match the field name in the subquery.**

WEPRME0173 **The defined field type does not match the field type in the subquery.**

WEPRME0174 **Check the specified aggregation.**

WEPRME0175 **Check the specified SELECT item.**

WEPRME0176 **Check the specified DEFINE condition.**

WEPRME0177 **Check the specified action.**

WEPRME0178 **Check the specified part of the join predicate.**

WEPRME0179 **Check the specified part of the WHERE clause.**

WEPRME0180 **The operator type {0} is currently not allowed within a recursive query.**

WEPRME0181 **The operator type {0} is not allowed within a recursive query.**

WEPRME0182 **The type {0} is unexpected.**

WEPRME0183 **The defined field is not null but the field in the subquery is nullable.**

WEPRME0184 **The input of a window has to be a chronon stream.**

WEPRME0185 **The pattern of a MATCHING clause must not be empty.**

WEPRME0189 **The base time specification does not represent a valid date/time.**

Explanation The query contains an invalid base time. This refers to the RELATIVE TO clause in an SQL query, or the relative-to attribute of a window element in an XML query.

Action Specify a valid base time.

WEPRME0191 **The LIKE clause requires a constant string pattern.**

WEPRME0192 **Only predicates are permitted in a HAVING clause.**

WEPRME0194 **Arrays of type {0} are currently not supported.**

WEPRME0195 **Only expressions of type BOOLEAN are allowed in this context but the present type is {0}.**

WEPRME0196 **The {0} function only supports FLOAT and DOUBLE values as arguments.**

WEPRME0197 **The argument of the CHAR_LENGTH function must be of string type.**

WEPRME0198 **Casting from {0} to {1} is currently not supported.**

WEPRME0199 **The argument of the {0} function must be numeric.**

WEPRME0200 **The {0} argument of the {1} function must be numeric.**

WEPRME0201 **Windows can only be applied to input streams or (sub)queries.**

WEPRME0202 **Tried to configure DataSource with unknown connection type {0} in RTM system.**

WEPRME0203 **Tried to configure unknown database table {0} in RTM system.**

WEPRME0204 **Cannot find builder class for DataSource configured in RTM system.**

WEPRME0205 **Cannot call builder class constructor for DataSource configured in RTM system.**

WEPRME0206 **Cannot access specified database table for DataSource configured in RTM system.**

WEPRME0207 **Initialization of CONNECT right failed.**

WEPRME0208 **Unable to initialize privileges for super user.**

WEPRME0209 **Unable to initialize privileges for monitoring user.**

WEPRME0211 **Unable to initialize privileges for pre-loaded data sources.**

WEPRME0212 **Unable to retrieve localhost name.**

WEPRME0213 **The system is already started.**

WEPRME0214 **Unable to prepare communication servers.**

WEPRME0215 **The user cannot be connected as direct connections to this system are currently not allowed.**

WEPRME0216 **The user cannot be connected as the system is not started.**

WEPRME0217 **The user cannot be connected as the system is already shut down.**

WEPRME0218 **The user cannot be connected as the username is unknown or the password is wrong.**

WEPRME0219 **The user cannot be connected as the connect right is missing.**

WEPRME0220 **The connection cannot be removed from the system as it is unknown.**

WEPRME0221 **The system was already shut down.**

WEPRME0222 **Setting the class loader is only allowed before system start.**

WEPRME0223 **System is not running in high availability mode.**

WEPRME0224 **The system does not allow remote connections.**

WEPRME0225 **Create database allowed only before the system start.**

WEPRME0226 **Drop database allowed only after system is already shut down.**

WEPRME0228 **Unable to send synchronous command.**

WEPRME0229 **Internal error: CallBack of class {0} provided to {1} is not an instance of {2}.**

WEPRME0230 **Status of health check monitor of local system is not OK; shutting down!**

WEPRME0231 **Unexpected exception in HA ServerConnectionHandler.**

WEPRME0232 **Unexpected error occurred when master was driving recovery of slave.**

WEPRME0233 **Unexpected error occurred when handling recovery request from master.**

WEPRME0239 **Exception when aborting connection process.**

WEPRME0240 **Unsupported protocol.**

WEPRME0241 **No handler registered for protocol {0}.**

WEPRME0242 **Handshake failed due to an exception.**

WEPRME0243 **Missing basic properties ({0}) needed to compute composed property.**

WEPRME0246 **Unexpected role {0}.**

WEPRME0247 **Received unknown command {0}.**

WEPRME0248 **The adapter must not be null.**

WEPRME0249 **The query {0} cannot be stopped as it is still in use by a subquery.**

WEPRME0250 **The query {0} cannot be stopped as it is still in use by a subscriber.**

WEPRME0251 **The subscription identifier {0} is already in use for user {1}.**

WEPRME0252 **The approach ({0}) does not match approach of the query ({1}).**

WEPRME0253 **The sink cannot be subscribed as the query {0} has not been started.**

WEPRME0254 **Unable to compute starting point for snapshot-reducible results.**

WEPRME0255 **Unable to start subscription {0} from {1}.**

WEPRME0256 **The connection to all servers has been lost.**

WEPRME0257 **At least one server address has to be provided.**

WEPRME0259 **Unable to connect to {0} due to incompatible server version.**

WEPRME0260 **Authentication with remote system failed.**

WEPRME0261 **Inconsistent high availability mode of servers.**

WEPRME0262 **The source cannot be prepared as the query identifier {0}.{1} is already in use.**

WEPRME0263 **Unable to parse the given SQL statement: {0}.**

WEPRME0264 **Unable to compute property: {0}.**

WEPRME0265 **The query cannot be prepared as the query identifier {0} is already in use.**

WEPRME0266 **The query {0} cannot be started as it is already closed.**

WEPRME0267 **The query {0} cannot be started as it is not yet initialized.**

WEPRME0268 **The mode {0} is not allowed for server subscriptions.**

WEPRME0269 **Persistent server subscriptions are only allowed with start time Long.MIN_VALUE.**

WEPRME0270 **Client subscription may not be unsubscribed using serverUnsubscribe - use unsubscribe.**

WEPRME0271 **Server subscription may not be unsubscribed using unsubscribe - use serverUnsubscribe.**

WEPRME0272 **Unable to stop subscription {0} from {1}.**

WEPRME0273 **A user-defined function factory is already registered for {0}.{1}.**

WEPRME0274 **No user-defined function is registered for {0}.{1}.**

WEPRME0275 **A data source is already registered for {0}.{1}.**

WEPRME0276 **A table is already registered for {0}.{1}.**

WEPRME0277 **No data source is registered for {0}.{1}.**

WEPRME0278 **No table is registered for {0}.{1}.**

WEPRME0279 **Subscription start point may only be computed for running queries.**

WEPRME0280 **The query identifier {0} is unknown.**

WEPRME0281 **Only numeric, string and date/time values can be used with {0} aggregation.**

WEPRME0282 **Only numeric values can be used with {0} aggregation.**

WEPRME0285 **Unknown aggregation type {0}.**

WEPRME0286 **A {0} aggregate must have exactly one sub-expression.**

WEPRME0287 **A {0} aggregate must not have more than one sub-expression.**

WEPRME0288 **Only numeric, string and date/time values can be used with maximum/minimum aggregation.**

WEPRME0289 **Only numeric values can be used with sum aggregation.**

WEPRME0292 **An exception occurred during batch execution.**

WEPRME0293 **Client did not provide valid number of supported stream protocols.**

WEPRME0294 **No stream protocol requested by the client is supported.**

WEPRME0295 **None of the proposed stream protocols is supported by the server.**

WEPRME0296 **The stream protocol requested by the server is not supported.**

WEPRME0297 **An exception occurred while sending a command.**

WEPRME0298 **Registration of new protocol mappings is only allowed before starting.**

WEPRME0299 **Starting may be done only once.**

WEPRME0300 **A yet unknown version.**

WEPRME0301 **An error occurred while parsing {0} and converting it to the target date format.**

WEPRME0302 **Unable to determine own address.**

WEPRME0303 **The protocol {0} requires a serializer for complex {1} which is not available at the server.**

WEPRME0304 **The protocol {0} requires a serializer for complex {1} which is not available at the client.**

WEPRME0305 **Unknown protocol {0}.**

WEPRME0306 **There is no handler registered under identifier {0} for protocol {1}.**

WEPRME0307 **A subscription to query {0} cannot be established as it has been configured to be non-subscribable.**

WEPRME0308 **The query with identifier {0}.{1} is not a connectable source.**

WEPRME0309 **Wrong approach: {0} (expected {1}).**

WEPRME0310 **Unknown command for system operation:{0}.**

WEPRME0311 **Unable to execute lock command on slave.**

WEPRME0312 **Execution of command on slave causes exception.**

WEPRME0313 **Unable to sync command with slave.**

WEPRME0314 **Only the owner of a source may disconnect from it.**

WEPRME0315 **Only the owner of a source may connect to it.**

WEPRME0316 **The dynamic protocol handler could not be connected.**

WEPRME0317 **The dynamic protocol adapter must not be null.**

WEPRME0318 **Master result to slave communicators may only be added before the system is started.**

WEPRME0319 **Unable to grant rights to subscribe to HA difference to user.**

WEPRME0320 **Unable to execute recover command on slave.**

WEPRME0321 **Unable to retrieve health information from master.**

WEPRME0322 **Unable to retrieve health information from client.**

WEPRME0323 **Connection to HA partner system timed out.**

WEPRME0324 **There is already a class {0} bound.**

WEPRME0325 **This callback is already disconnected.**

WEPRME0326 **Unable to store entry of class {0} in repository.**

WEPRME0327 **The repository already contains an artefact of type {0} for {1}.{2}.**

WEPRME0328 **Repository error: the entry to retrieve is unknown.**

WEPRME0329 **Repository error: the entry to remove is unknown.**

WEPRME0330 **Repository error: unknown subscription.**

WEPRME0331 **Repository does not contain an artefact of type {0} with owner {1} and identifier {2} or it might not be accessed.**

WEPRME0332 **Loading repository from database failed.**

WEPRME0333 **Unable to access notification dispatcher of underlying local connection as remote connection is not yet authenticated.**

WEPRME0334 **The user-defined aggregation function must not be null.**

WEPRME0335 **The class of the user-defined aggregation function adapter must not be null.**

WEPRME0337 **The server user-defined aggregation function cannot be registered.**

WEPRME0338 **The user-defined aggregation function cannot be registered.**

WEPRME0339 **The user-defined aggregation function cannot be deregistered.**

WEPRME0340 **The user-defined operator adapter factory must not be null.**

WEPRME0341 **The class of the user-defined operator adapter factory must not be null.**

WEPRME0342 **Persistency for user-defined operators is currently not supported.**

WEPRME0343 **The server user-defined operator cannot be registered.**

WEPRME0344 **The user-defined operator cannot be registered.**

WEPRME0345 **The user-defined operator cannot be deregistered.**

WEPRME0346 **The user {0} does not have the privilege to add the user-defined aggregation function.**

WEPRME0347 **The user {0} does not have the privilege to remove the user-defined aggregation function.**

WEPRME0348 **The user {0} does not have the privilege to add the user-defined operator.**

WEPRME0349 **The user {0} does not have the privilege to remove the user-defined operator.**

WEPRME0350 **An user-defined aggregation function is already registered for {0}.{1}.**

WEPRME0351 **No user-defined aggregation function is registered for {0}.{1}.**

WEPRME0352 **A user-defined operator is already registered for {0}.{1}.**

WEPRME0353 **No user-defined operator is registered for {0}.{1}.**

WEPRME0354 **Only expressions are permitted as argument of {0} functions.**

WEPRME0355 **Only expressions are permitted as {0} argument of {1} functions.**

WEPRME0356	**The connected system does not support the registration of user-defined aggregation functions.**
WEPRME0357	**The connected system does not support the deregistration of user-defined aggregation functions.**
WEPRME0358	**The connected system does not support the registration of user-defined operators.**
WEPRME0359	**The connected system does not support the deregistration of user-defined operators.**
WEPRME0361	**Unable to create instance of {0}.**
WEPRME0367	**The parameter type number {0} of a user-defined operator adapter factory for {1}.{2} must not be null.**
WEPRME0370	**Unable to find class {0}.**
WEPRME0371	**The method name {0} is not unique in class {1}.**
WEPRME0372	**The method {0} is not declared in class {1}.**
WEPRME0373	**Methods using varargs are not supported.**
WEPRME0374	**The method {0} is not static.**
WEPRME0375	**The method {0} is not public.**
WEPRME0376	**The return type {0} of method {1} is not supported.**

WEPRME0377 **The parameter type {0} of method {1} is not supported.**

WEPRME0378 **The method has been called with wrong parameters.**

WEPRME0379 **The method is not accessible.**

WEPRME0380 **The method cannot be invoked.**

WEPRME0381 **Wrong number of parameters.**

WEPRME0383 **Unable to invoke {0}.**

WEPRME0385 **Unable to determine parameter types.**

WEPRME0386 **Unable to determine output metadata.**

WEPRME0387 **Unable to access {0}.**

WEPRME0388 **No such method available: {0}.**

WEPRME0389 **Return type of method {0} must be StreamMetaData.**

WEPRME0390 **Return type of method {0} must be JavaTypes.Type.**

WEPRME0391 **Unable to access constructor.**

WEPRME0392 **No valid constructor available.**

WEPRME0393 **Wrong parameters: use class name and method names.**

WEPRME0394 **The {0} method must have at least two parameters.**

WEPRME0400 **The user-defined operator {0} is unknown or not visible.**

WEPRME0401 **The parameter type {0} must be the same as value parameter type of {1}.**

WEPRME0406 **The statements are not initialized.**

WEPRME0407 **The statements have to be initialized first.**

WEPRME0408 **This statement is not available.**

WEPRME0409 **The operation removeAll is not supported.**

WEPRME0410 **The operation removeAndReturn is currently not supported.**

WEPRME0411 **Elements are already removed by next.**

WEPRME0412 **{0} is not contained.**

WEPRME0413 **Calling the method getMinTimeStamp only supported in ordered remove mode.**

WEPRME0414 **Structure is empty.**

WEPRME0415 **The only supported key is key 0.**

WEPRME0416 **Not possible as heap is consuming.**

WEPRME0417 **Remove is always done.**

WEPRME0418 **The initial list has to be empty.**

WEPRME0419 **The length of the specified byte array does not match the length of the serialized byte array.**

WEPRME0420 **The given text node does not contain a single character.**

WEPRME0421 **The given node cannot be read.**

WEPRME0422 **The end of file has been reached before record metadata could be read completely.**

WEPRME0423 **The number of column names and column types differ.**

WEPRME0424 **The value contains more than one character.**

WEPRME0425 **The value is not in JDBC time escape format or null.**

WEPRME0426 **The value is not in JDBC date escape format or null.**

WEPRME0427 **The character encoding {0} is not supported.**

WEPRME0428 **The class of the serialized object was not found.**

WEPRME0429 **The class used by serialization is invalid.**

WEPRME0430 **The input stream is corrupt.**

WEPRME0431 **The input stream consists of primitive data instead of objects.**

WEPRME0432 **An input/output error has occurred.**

WEPRME0433 **Writing a serializable object to a string failed due to I/O error.**

WEPRME0434 **Writing a serializable object to a string failed due to security problems.**

WEPRME0435 **Writing a serializable object to a string failed due to output stream being null.**

WEPRME0436 **NULL as null code is not allowed.**

WEPRME0437 **The end of file has been reached before record could be read completely.**

WEPRME0438 **The number of values differs from record metadata definition (expecting {0} but found {1}).**

WEPRME0439 **The index referring to the local error array is out of bounds.**

WEPRME0440 **The value for column {0} ({1}) must not be null.**

WEPRME0442 **No error at index {0} in the local error array.**

WEPRME0443 **The length of the specified byte array does not match the length of the serialized double array.**

WEPRME0444 **The length of the specified byte array does not match the length of the serialized long array.**

WEPRME0445 **The class of the object to be read cannot be found ({0}).**

WEPRME0446 **The length of the specified byte array does not match the length of the serialized String array.**

WEPRME0447 **This serializer does not support the restoring of objects.**

WEPRME0448 **Unsupported type code: {0}.**

WEPRME0449 **Unsupported type name: {0}.**

WEPRME0450 **Unsupported type: {0}.**

WEPRME0451 **Types may not be null.**

WEPRME0452 **Unsupported Java type: {0} ({1}).**

WEPRME0453 **Unsupported SQL type: {0}.**

WEPRME0454 **Negative iterator only supported if negative counts are not.**

WEPRME0455 **Call to next while not hasNext.**

WEPRME0456 **The distinctIterator is not supported if negative counts are allowed.**

WEPRME0457 **Queue is empty.**

WEPRME0458 **Pos={0}, size={1}.**

WEPRME0459 **Operation results in negative value.**

WEPRME0460 **Negative value.**

WEPRME0461 **The argument is not an array.**

WEPRME0462 **The argument is not a wrapper array.**

WEPRME0463 **SingleObjectList already contains an object.**

WEPRME0464 **SingleObjectList only supports index 0.**

WEPRME0465 **SingleObjectList already may only contain one object.**

WEPRME0466 **This list is empty.**

WEPRME0467 **SingleObjectList does not support subList.**

WEPRME0468 **A time period with non-constant time unit (day, week, month and year) must not be greater than {0}.**

WEPRME0469 **The size in milliseconds of the time period can only be calculated for constant time periods.**

WEPRME0470 **Composite metadata already contains specified metadata fragment ''{0}''.**

WEPRME0471 **Some metadata fragments cannot be added to composite metadata:{0}.**

WEPRME0472 **Composite metadata does not contain specified metadata ''{0}''.**

WEPRME0473 **User {0} is already subscribed to {1}.**

WEPRME0474 **Identifier {0} is not supported.**

WEPRME0475 **Unable to subscribe to {0} due to failed subscription to dependent metadata: {1}.**

WEPRME0476 **User {0} is not subscribed to {1}.**

WEPRME0477 **Unexpected parameter {0}=>{1}.**

WEPRME0478 **Illegal parameter type! Expected {0}, found {1}.**

WEPRME0479 **Missing parameter(s): {0}.**

WEPRME0480 **Double metadata update - this should not appear in current update mechanism.**

WEPRME0481 **Transparent composite metadata does not contain specified metadata ''{0}'' as a direct fragment, hence it cannot be removed.**

WEPRME0482 **Requested point is not part of the domain.**

WEPRME0483 **Empty domain.**

WEPRME0484 **New domain ({0},{1}) has to be contained in old one ({2},{3}).**

WEPRME0485 **Range out of domain.**

WEPRME0486 **From==to but fromFactor != toFactor.**

WEPRME0487 **New domain has to be contained in old one.**

WEPRME0488 **Bound out of domain.**

WEPRME0489 **A weight has to be given for each function.**

WEPRME0490 **Functions do not have a common domain.**

WEPRME0491 **Parse error at position {0}, cause: {1}.**

WEPRME0492 **Syntax not supported.**

WEPRME0493 **Unexpected end of regular expression.**

WEPRME0494 **Missing number in count expression.**

WEPRME0495 **Non-digit in count expression.**

WEPRME0496 **Empty (sub) expression.**

WEPRME0497 **Range error.**

WEPRME0498 **Count value is 0.**

WEPRME0499 **Right parenthesis without matching left parenthesis.**

WEPRME0500 **Left parenthesis without matching right parenthesis.**

WEPRME0501 **Negative call on empty state.**

WEPRME0502 **Wrong number of parameters.**

WEPRME0503 **Empty state.**

WEPRME0504 **The switch function does not contain a function for the given identifier and no default function is specified.**

WEPRME0505 **Too many parameters fixed.**

WEPRME0506 **Inconsistent length of arguments.**

WEPRME0507 **Indices have to be in ascending order.**

WEPRME0508 **{0} cannot be used as result type for conversion.**

WEPRME0509 **This UserDefinedOperator has too many inputs. Maximum expected: {0}. Found: {1}.{2}**

WEPRME0510 **This UserDefinedOperator is missing inputs. Minimum expected: {0}. Found: {1}.{2}**

WEPRME0511 **TableName has to be provided.**

WEPRME0512 **Map has to be provided.**

WEPRME0513 **Error reading file.**

WEPRME0514 **Read line does not match the expected format (check number of rows and row delimiter).**

WEPRME0515 **A method responsible for updating a structure was called in a class which does not support updates.**

WEPRME0516 **ResultSet does not provide row {0}.**

WEPRME0517 **File {0} cannot be written.**

WEPRME0518 **Row names must not be null.**

WEPRME0519 **Error parsing date {0}.**

WEPRME0520 **No update necessary after delete.**

WEPRME0521 **At least one row has to be mapped.**

WEPRME0522 **A required value is missing in the given line.**

WEPRME0523 **Between line {0} and {1} : {2}.**

WEPRME0524 **Line {0} : {1}.**

WEPRME0525 **Number of successful commands must not be negative.**

WEPRME0526 **At least one supported stream protocol has to be provided.**

WEPRME0527 **CreateArray only works for complex array types, not for {0}.**

WEPRME0528 **Unsupported type {0}.**

WEPRME0529 **[This Error replaces a {0} which is not available to the class loader.] {1}.**

WEPRME0530 **[This RuntimeException replaces a {0} which is not available to the class loader.] {1}.**

WEPRME0531 **Unable to serialize Object.**

WEPRME0532 **Unsupported modifier.**

WEPRME0533 **Unable to deserialize Object.**

WEPRME0534 **Channel is already closed!**

WEPRME0535 **The null communication type should not be sent.**

WEPRME0536 **Java serialization is not supported. Use ObjectStreamCommunication if needed.**

WEPRME0537 **Unsupported type {0}.**

WEPRME0538 **Unsupported type.**

WEPRME0539 **Exception while receiving {0}.**

WEPRME0540 **Communication type must not be null.**

WEPRME0541 **Factory parameters must not be null.**

WEPRME0542 **Unable to create server on address other than local address.**

WEPRME0543 **Unable to resolve {0}.**

WEPRME0544 **Unsupported CommunicationType: {0}.**

WEPRME0545 **Could not receive answer as receiving was interrupted.**

WEPRME0546 **Could not receive answer as connection was closed due to an exception.**

WEPRME0547 **Requests must not use ResponseStatus.**

WEPRME0548 **Exception while handling async command ({0}).**

WEPRME0549 **More than one ID is not supported yet.**

WEPRME0550 **No command handler registered for ID {0}.**

WEPRME0551 **Command {0} sent by wrong side of communication.**

WEPRME0552 **Command {0} is asynchronous.**

WEPRME0553 **Command {0} is synchronous.**

WEPRME0554 **Wrong protocol, expected {0} but received unknown protocol ID {1}.**

WEPRME0555 **Wrong protocol, expected {0} but received {1}.**

WEPRME0556 **Wrong magic value for protocol {0}.**

WEPRME0557 **Protocol must not be null.**

WEPRME0558 **Uninitialized composite serializer for {0}.**

WEPRME0559 **Registration not possible after shutdown.**

WEPRME0560 **There is no address registered for handling protocol {0}.**

WEPRME0561 **There is already a handler registered for protocol {0}.**

WEPRME0562 **There is no handler registered for protocol {0}.**

WEPRME0563 **Unable to shut down server at {0}.**

WEPRME0564 **Unable to shut down {0} communication servers.**

WEPRME0565 **Compatibility matrix has to be provided.**

WEPRME0566 **Duplicate ID{0}.**

WEPRME0567 **No request types provided for {0}.**

WEPRME0568 **No respond types provided for {0}.**

WEPRME0569 **Unknown command ID: {0}.**

WEPRME0570 **Missing serializer for complex {0}.**

WEPRME0571 **Parameter has to specify a directory.**

WEPRME0572 **Channel is already closed!**

WEPRME0573 **Unable to read communication server index file {0}.**

WEPRME0574 **Unable to start communication server on directory {0}.**

WEPRME0575 **Unable to create communication server index file {0}.**

WEPRME0576 **The stream protocol requested by the client is not supported.**

WEPRME0577 **The stream protocol {0} requested by the client is not supported.**

WEPRME0578 **Exception while closing streams.**

WEPRME0579 **Unable to accept a new connection in the specified time.**

WEPRME0580 **No server present at {0} .**

WEPRME0581 **File instead of directory found at server address {0}.**

WEPRME0582 **Unknown stream protocol: {0}.**

WEPRME0583 **Unable to connect to {0}.**

WEPRME0584 **Unable to close socket.**

WEPRME0585 **Protocol handler must not be null.**

WEPRME0586 **There was already a handler registered for protocol {0}.**

WEPRME0587 **There was already a handler registered.**

WEPRME0588 **The handler to register does not handle the correct protocol {0}.**

WEPRME0589 **This server does not support protocol type {0}.**

WEPRME0590 **Unable to start communication server on port {0}.**

WEPRME0591 **Unable to close server socket.**

WEPRME0592 **Unable to connect to {0}:{1}.**

WEPRME0593 **Unable to initialize cache.**

WEPRME0594 **Cache already exists but with another end timestamp.**

WEPRME0595 **Unable to remove the specified cache.**

WEPRME0596 **New SerialBlob(..) threw SerialException.**

WEPRME0597 **New SerialBlob(..) threw SQLException.**

WEPRME0598 **Write(Element,Node) needs operator, expression or predicate.**

WEPRME0599 **Node conversion not implemented for type {0} and sub-type {1}.**

WEPRME0600 **Unsupported constant type: {0}.**

WEPRME0601 **Outer semi join.**

WEPRME0602 **Non-constant unit in time shift.**

WEPRME0603 **Expression wrapped by this predicate is not of type BOOLEAN.**

WEPRME0604 **Only expressions can be used as boolean expressions.**

WEPRME0605 **A boolean expression must not have any sub-predicates.**

WEPRME0606 **Argument types cannot be compared with {0}.**

WEPRME0607 **Only expressions can be used as arguments of a comparison predicate.**

WEPRME0608 **Second parameter of LIKE has to be a constant.**

WEPRME0609 **Second parameter of LIKE has to be a String.**

WEPRME0610 **Invalid operator [{0}].**

WEPRME0611 **A comparison predicate must not have any sub-predicates.**

WEPRME0612 **The comparison predicate's arguments are not comparable.**

WEPRME0613 **Incomparable Java type {0}.**

WEPRME0614 **The state of the logical constant is unknown.**

WEPRME0615 **A logical constant must not have any sub-predicates.**

WEPRME0616 **Unknown logical constant type {0}.**

WEPRME0617 **The logical operation type {0} is currently not supported.**

WEPRME0618 **Illegal member specification.**

WEPRME0619 **Illegal set specification.**

WEPRME0620 **Types of member and set are not comparable.**

WEPRME0621 **Illegal subpredicate.**

WEPRME0622 **Unknown logical operation type {0}.**

WEPRME0623 **Only predicates can be used as child nodes of a logical operation predicate.**

WEPRME0624 **Only operators can be used as sets of an exists predicate.**

WEPRME0625 **Only expressions can be used as expression of an in predicate.**

WEPRME0626 **Only operators can be used as sets of an in predicate.**

WEPRME0627 **A logical (boolean) IN operator must not have any sub-predicates.**

WEPRME0628 **A logical (boolean) IN operator does not yet support subqueries.**

WEPRME0629 **A logical (boolean) NOT must have exactly one sub-predicate.**

WEPRME0630 **A logical (boolean) NOT must not have more than one sub-predicate.**

WEPRME0631 **Unknown logical operation type {0}.**

WEPRME0632 **Unknown aggregation operator mode {0}.**

WEPRME0633 **Only predicates can be used as filter predicate nodes of an aggregation operator.**

WEPRME0634 **Only operators can be used as child nodes of an aggregation operator.**

WEPRME0635 **An aggregation operator must have exactly one input operator.**

WEPRME0636 **An aggregation operator must not have more than one input operator.**

WEPRME0637 **Aggregation is currently not supported within recursive PN queries.**

WEPRME0638 **Unsupported target approach: {0}.**

WEPRME0640 **Unknown aggregation operator mode {0}.**

WEPRME0641 **A distinct operator must have exactly one operator.**

WEPRME0642 **A distinct operator must not have more than one input operator.**

WEPRME0643 **Unknown distinct operator mode {0}.**

WEPRME0644 **Empty enumeration.**

WEPRME0645 **Enumeration contains constants of different types.**

WEPRME0646 **An enumeration operator must not have any input operators.**

WEPRME0647 **An enumeration operator provides a set of constants as subquery-replacement for the use in IN-predicates, hence no active enumeration operators are possible.**

WEPRME0649 **The specified object is not of the expected type; {0}.**

WEPRME0650 **ActionMapFormat.parseActionMap(String) failed.**

WEPRME0651 **Only operators can be used as child nodes of an equivalence operator.**

WEPRME0652 **The chosen query plan (operator at index {0}) does not exist.**

WEPRME0653 **The relational metadata of the operator node''s children does not fit.**

WEPRME0654 **The operator node has no children.**

WEPRME0655 **Only operators can be used as child nodes of an except/minus operator.**

Explanation An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.

Action Connect exactly two operators as input of the except/minus operator.

WEPRME0656 **An except/minus operator must have exactly two input operators.**

Explanation An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.

Action Connect exactly two operators as input of the except/minus operator.

WEPRME0657 **An except/minus operator must not have more than two input operators.**

Explanation An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.

Action Connect exactly two operators as input of the except/minus operator.

WEPRME0658 **Unknown except/minus operator mode {0}.**

WEPRME0659 **Passive operators does not have chronon stream properties.**

WEPRME0660 **I/O exception occurred during metadata construction: ''{0}''.**

WEPRME0661 **Only column expressions specified by a single column name can be used as timestamp columns of a file operator.**

WEPRME0662 **Only operators can be used as child nodes of an output file operator.**

WEPRME0663 **An input-file operator must not have any input operators.**

WEPRME0664 **File not found: {0}.**

WEPRME0665 **Unable to read file header.**

WEPRME0666 **Time information must have a reference timestamp.**

WEPRME0667 **Time information must not have any additional timestamps.**

WEPRME0668 **Unknown file operator mode {0}.**

WEPRME0669 **An output-file operator must have exactly one input operator.**

WEPRME0670 **An output-file operator must not have more than one input operator.**

WEPRME0671 **For storing time intervals the names of the columns storing the start and an end timestamp are required.**

WEPRME0672 **File writing currently unsupported.**

WEPRME0673 **Unknown file operator type {0}.**

WEPRME0674 **Only operators can be used as child nodes of a selection operator.**

WEPRME0675 **A selection operator must have exactly one input operator.**

WEPRME0676 **A selection operator must not have more than one input operator.**

WEPRME0677 **Unknown identity operator mode {0}.**

WEPRME0678 **Only operators can be used as child nodes of an intersection operator.**

WEPRME0679 **An intersect operator must have exactly two input operators.**

WEPRME0680 **An intersect operator must not have more than two input operators.**

WEPRME0681 **Unknown target approach {0}.**

WEPRME0682 **Unknown intersect operator mode {0}.**

WEPRME0683 **Only operators can be used as child nodes of a join operator.**

WEPRME0684 **Only predicates can be used as condition of a theta join operator.**

WEPRME0685 **A join operator must have at least two input operators.**

WEPRME0686 **Implementations of multiway join are currently not supported, i.e., they must be transformed to join plans of binary joins using the query optimizer.**

WEPRME0687 **Implementations of outer joins are currently not supported.**

WEPRME0688 **Implementations of semi joins are currently not supported.**

WEPRME0689 **Implementations of joins between active and passive source are currently not supported.**

WEPRME0690 **Unknown join type {0}.**

WEPRME0693 **Unknown join mode {0}.**

WEPRME0694 **Implementations of natural joins without common attributes between active and passive sources are currently not supported.**

WEPRME0695 **Columns named by {0} cannot be unified because of different types.**

WEPRME0696 **Column failure.**

WEPRME0697 **Only operators can be used as child nodes of a mapping operator.**

WEPRME0698 **A mapping operator must have exactly one input operator.**

WEPRME0699 **A mapping operator must not have more than one input operator.**

WEPRME0700 **Unknown mapping operator mode {0}.**

WEPRME0701 **Some pattern variables are undefined.**

WEPRME0702 **Only constants can be used as initial values of a matching operator''s MEASURE clause.**

WEPRME0703 **Only columns can be used in a matching operator''s PARTITION BY part.**

WEPRME0704 **Only predicates can be used in the AS part of a matching operator''s DEFINE clause.**

WEPRME0705 **Only columns can be used on the left side of a DO part of a matching operator''s DEFINE clause.**

WEPRME0706 **Only expressions can be used on the right side of a DO part of a matching operator''s DEFINE clause.**

WEPRME0707 **Only operators can be used as child nodes of a matching operator.**

WEPRME0708 **A pattern matcher must have exactly one input operator.**

WEPRME0709 **A pattern matcher must have a synthetic input representing the underlying NFA''s state.**

WEPRME0710 **A pattern matcher must not have more than two input operators.**

WEPRME0712 **{0} mode not supported.**

WEPRME0713 **Unknown selection operator mode {0}.**

WEPRME0714 **The relational metadata of the operator node''s children does not fit.**

WEPRME0715 **The operator node has no children.**

WEPRME0716 **Only operators can be used as child nodes of a projection operator.**

WEPRME0717 **A projection operator must have exactly one input operator.**

WEPRME0718 **A projection operator must not have more than one input operator.**

WEPRME0719 **Unknown projection operator mode {0}.**

WEPRME0720 **Unsupported data type.**

WEPRME0721 **A random operator must not have any input operators.**

WEPRME0722 **Random sources are currently not supported for target approach: {0}.**

WEPRME0723 **Unknown random operator mode {0}.**

WEPRME0724 **Unknown content.**

WEPRME0725 **Ambiguous content.**

WEPRME0726 **Only operators can be used as child nodes of a recursion operator.**

WEPRME0727 **A recursion operator must have exactly one input operator.**

WEPRME0728 **A recursion operator must not have more than one input operator.**

WEPRME0729 **The use of recursion operators inside the cursor algebra is currently not supported.**

WEPRME0730 **Unknown recursion operator mode {0}.**

WEPRME0731 **Only operators can be used as child nodes of a renaming operator.**

WEPRME0732 **A renaming operator must have exactly one input operator.**

WEPRME0733 **A renaming operator must not have more than one input operator.**

WEPRME0734 **Unknown renaming operator mode {0}.**

WEPRME0735 **A repository entry operator must not have any input operators.**

WEPRME0736 **A repository entry operator with name {0} for user {1} is unknown.**

WEPRME0737	**A subquery using the approach {0} cannot be used in a query compiled for the approach {1}.**
WEPRME0738	**Only predicates can be used as condition of a selection operator.**
WEPRME0739	**Only operators can be used as child nodes of a selection operator.**
WEPRME0740	**A selection operator must have exactly one input operator.**
WEPRME0741	**A selection operator must not have more than one input operator.**
WEPRME0742	**Unknown selection operator mode {0}.**
WEPRME0743	**No value columns specified.**
WEPRME0744	**Wrong number of fields in value {0} (expected {1}, found {2}).**
WEPRME0745	**For exact matches exactly one count argument must be specified.**
WEPRME0746	**For maximum matches exactly one count argument must be specified.**
WEPRME0747	**For minimum matches exactly one count argument must be specified.**
WEPRME0748	**For range matches exactly two count arguments must be specified.**
WEPRME0749	**Only operators can be used as child nodes of a set operator.**
WEPRME0750	**A set operator must have exactly one input operator.**

WEPRME0751 **A set operator must not have more than one input operator.**

WEPRME0752 **The defined field list and the specified values are not comparable.**

WEPRME0753 **Unknown mode {0}.**

WEPRME0755 **Unknown selection operator mode {0}.**

WEPRME0756 **Only operators can be used as child nodes of an output socket operator.**

WEPRME0757 **A input-socket operator must not have any input operators.**

WEPRME0758 **At this point a source reading its data from a socket channel to {0}@{1}:{2} should be returned.**

WEPRME0759 **An output-socket operator must have exactly one input operator.**

WEPRME0760 **An output-socket operator must not have more than one input operator.**

WEPRME0761 **At this point a sink writing the data received from {0} to a socket channel available at {1}@{2}:{3} should be returned.**

WEPRME0762 **Unknown socket type {0}.**

WEPRME0763 **The use of sockets inside the cursor algebra is currently not supported.**

WEPRME0764 **Unknown socket operator mode {0}.**

WEPRME0765 **Local metadata fragment identified by {0} cannot be created because of multiple fields matching the field name pattern.**

WEPRME0766 **Local metadata fragment identified by {0} cannot be created because no available field matches the field name pattern.**

WEPRME0767 **This exception is thrown to avoid the creation of a new metadata fragment.**

WEPRME0768 **Initialization is only available for source operators.**

WEPRME0769 **Recursive query not contained.**

WEPRME0770 **Source operators are internally used for identifying data sources, hence the occurrence of this exception is a signal of a misuse of a source operator.**

WEPRME0771 **Only operators can be used as child nodes of a stream operator.**

WEPRME0772 **A stream operator must have exactly one input operator.**

WEPRME0773 **A stream operator must not have more than one input operator.**

WEPRME0774 **The use of stream operators inside the pipes algebra is currently not supported.**

WEPRME0775 **The target of a stream operator is to transform a passive query into an active one, hence no passive stream operators are possible.**

WEPRME0776 **Unknown stream operator mode {0}.**

WEPRME0777 **Only operators can be used as child nodes of a time shift.**

WEPRME0778 **A time shifter must have exactly one input operator.**

WEPRME0779 **A time shifter must not have more than one input operator.**

WEPRME0780 **A time shifter must have a constant time shift.**

WEPRME0781 **Unknown selection operator mode {0}.**

WEPRME0782 **{0} mode not supported.**

WEPRME0783 **Only operators can be used as child nodes of an union operator.**

WEPRME0784 **A union operator must have at least two input operators.**

WEPRME0785 **A union operator must have at least two input operators.**

WEPRME0786 **Unknown union operator mode {0}.**

WEPRME0787 **Only an operator can be used as child node of a window operator.**

WEPRME0788 **A window operator must have exactly one input operator.**

WEPRME0789 **A window operator must not have more than one input operator.**

WEPRME0790 **A window operator on a non-chronon stream is currently not supported.**

WEPRME0791 **Unknown window operator type {0}.**

WEPRME0792 **The use of a window operator inside the cursor algebra is currently not supported.**

WEPRME0793 **Unknown window operator mode: {0}.**

WEPRME0794 **Only expressions can be used as child nodes of an aggregate expression.**

WEPRME0796 **User-defined aggregation function does not support PN approach.**

WEPRME0797 **A constant expression must not have any sub-expressions.**

WEPRME0798 **Local metadata fragment identified by {0} cannot be created.**

WEPRME0799 **Local metadata fragment identified by {0} cannot be created because of multiple fields matching the field name pattern.**

WEPRME0800 **Local metadata fragment identified by {0} cannot be created because no available field matches the field name pattern.**

WEPRME0801 **A column expression must not have any sub-expressions.**

WEPRME0802 **Unable to identify field {0}.**

WEPRME0803 **Only numeric values can be used with ABS function.**

WEPRME0804 **The decimal place parameter has to be of type Integer.**

WEPRME0805 **Illegal condition.**

WEPRME0806 **Case does not provide FieldMetaData.**

WEPRME0807 **Inconsistent types in case.**

WEPRME0810 **Only String values can be used with CHAR_LENGTH function.**

WEPRME0811 **Casting from {0} to {1} is currently not supported.**

WEPRME0812 **Unknown function type {0}.**

WEPRME0813 **Only expressions can be used as child nodes of a function expression.**

WEPRME0814 **Initialization is only available for user-defined functions.**

WEPRME0815 **A {0} operation must have exactly two sub-expressions.**

WEPRME0816 **A {0} operation must not have more than two sub-expressions.**

WEPRME0817 **Only numeric values can be used with ABS function.**

WEPRME0818 **FLOOR function only supports Double and Float values.**

WEPRME0819 **CEILING function only supports Double and Float values.**

WEPRME0820 **The result type of a CHAR_LENGTH function has to be Integer.**

WEPRME0821 **ROUND function only supports numeric values.**

WEPRME0822 **TRUNCATE function only supports numeric values.**

WEPRME0823 **Currently casting between these types is not allowed.**

WEPRME0824	**Currently only casting between numeric types and casting to String type is supported.**
WEPRME0825	**A {0} function must not have any sub-expressions.**
WEPRME0826	**Unexpected undefined case.**
WEPRME0827	**Parameters missing for user-defined function {0}.**
WEPRME0828	**Too many parameters for user-defined function {0}.**
WEPRME0829	**Unknown function expression type {0}.**
WEPRME0830	**Only numeric values can be negated.**
WEPRME0831	**Only numeric values can be mathematically subsumed.**
WEPRME0832	**Exponentiation with base type {0} is only allowed for exponent types {1}, {2} and {3}.**
WEPRME0833	**Exponent type cannot be {0}.**
WEPRME0834	**Only textual values can be concatenated.**
WEPRME0835	**Unknown operation type {0}.**
WEPRME0836	**Recognized a numeric constant without a numeric data type.**
WEPRME0837	**Only expressions can be used as child nodes of an operation expression.**

WEPRME0838 **A {0} operation must have exactly one sub-expression.**

WEPRME0839 **A {0} operation must not have more than one sub-expression.**

WEPRME0840 **A {0} operation must have exactly two sub-expressions.**

WEPRME0841 **A {0} operation must not have more than two sub-expressions.**

WEPRME0842 **Unknown operation expression type {0}.**

WEPRME0843 **Only numeric values can be negated.**

WEPRME0844 **Only numeric values can be mathematically subsumed.**

WEPRME0845 **Unknown operation expression type {0}.**

WEPRME0847 **Only expressions can be used as child nodes of a renamed field expression.**

WEPRME0848 **A renamed field expression must have exactly one sub-expression.**

WEPRME0849 **A renamed field expression must not have more than one sub-expression.**

WEPRME0850 **Child at index {0} cannot be accessed because the given index is not assigned so far.**

WEPRME0851 **Index {0} cannot be accessed ({1} children are allowed).**

WEPRME0852 **Index {0} cannot be accessed ({1} parents are allowed).**

WEPRME0853	**New child has reached its maximum number of parents (number of allowed parents: {0}).**
WEPRME0854	**New parent has reached its maximum number of children (number of allowed children: {0}).**
WEPRME0855	**Node has reached its maximum number of children (number of allowed children: {0}).**
WEPRME0856	**Node has reached its maximum number of parents (number of allowed parents: {0}).**
WEPRME0857	**Only use this method on nodes without a fixed number of children.**
WEPRME0858	**Only use this method on nodes without a fixed number of parents.**
WEPRME0859	**Parent at index {0} cannot be accessed because the given index is not assigned so far.**
WEPRME0860	**A node of the specified iteration cannot be added to the given node''s global metadata because it does not hold the specified precondition.**
WEPRME0861	**This exception is thrown to avoid the creation of a new metadata fragment after resetting.**
WEPRME0862	**Not contained.**
WEPRME0863	**Entry already contained.**
WEPRME0864	**Entry not contained.**

WEPRME0865 **SpeedUp <0 is not allowed.**

WEPRME0866 **Unsupported SQL data type.**

WEPRME0867 **Period has to be equal to or greater than 0.**

WEPRME0868 **This period worker thread cannot be woken up, because wait time is zero.**

WEPRME0869 **For this factory, getSignature() may not be called with instantiation parameter types as the adapter is already instantiated.**

WEPRME0870 **For this factory, createInstance() may not be called with instantiation parameters as the adapter is already instantiated.**

WEPRME0872 **Class not found.**

WEPRME0873 **The function adapter class for the user-defined function must not be null.**

WEPRME0877 **Unable to create instance of {0}.**

WEPRME0878 **{0} does not provide a constructor with signature String[], which is obligatory.**

WEPRME0884 **Query already reconstructed.**

WEPRME0885 **Could not instantiate adapter class of sink adapter.**

WEPRME0886 **The {0} already exists in the database.**

WEPRME0887 **The removal of {0} from the database failed.**

WEPRME0889 **Repository error: The query graph to be sorted must have at least one node without an input.**

WEPRME0890 **The input queries differ from the sorted output queries.**

WEPRME0891 **Query properties may only be retrieved after the query is built.**

WEPRME0892 **Unsupported approach.**

WEPRME0893 **Could not instantiate adapter class of source adapter.**

WEPRME0896 **Unable to access class {0}.**

WEPRME0897 **Unable to create instance of {0}.**

WEPRME0898 **Update in the database failed.**

WEPRME0899 **The given SQL statement {0} does not provide streaming data.**

WEPRME0900 **Unable to parse the given SQL statement: {0}.**

WEPRME0901 **Unable to translate the given SQL statement ({0}): {1}.**

WEPRME0902 **Unable to translate the given SQL statement (problem with at least one specified column name): {0}.**

WEPRME0903 **Configuration could not been loaded, check XML config URL.**

WEPRME0904 **Could not locate resource!**

WEPRME0905 **Provided class not found!**

WEPRME0906 **Unable to read configuration file.**

WEPRME0907 **XML parsing problem.**

WEPRME0908 **BOT failed.**

WEPRME0909 **Check whether the persistent ID of the object is null!**

WEPRME0910 **COMMIT failed.**

WEPRME0911 **Initializing transaction failed.**

WEPRME0912 **Obtaining entity manager failed.**

WEPRME0913 **Persistence factory shutdown failed.**

WEPRME0914 **ROLLBACK failed.**

WEPRME0915 **The removal of {0} query from the database failed.**

WEPRME0916 **The saving of {0} to the database failed.**

WEPRME0918 **Unknown approach.**

WEPRME0920 **Unsupported approach {0}.**

WEPRME0921 **Unable to access database with given data source specification.**

WEPRME0923 **Unable to access database with given data source and table specification.**

WEPRME0924 **Unable to reconstruct refresh time.**

WEPRME0925 **Please provide connection URL property "rtmsystem.datasource.connection_url" in order to connect to database.**

WEPRME0926 **Please provide JDBC driver name property "rtmsystem.datasource.jdbc_drivername" in order to initalize the data source.**

WEPRME0927 **Problem with basic data source configuration.**

WEPRME0928 **Problem with JDBC driver, please verify that the library is attached, library classpath is correct and driver name is correct.**

WEPRME0929 **The classpath of the JDBC driver is malformed.**

WEPRME0930 **Obtaining Connection to JDBC Source {0} has failed!**

WEPRME0931 **This method is not supported by this version.**

WEPRME0932 **Could not instantiate builder class of ServerDataSourceEntry.**

WEPRME0933 **Load of tables failed!**

WEPRME0934 **The builder class for the data source must not be null.**

WEPRME0938	**Illegal HA state - slaves ({0}) are already locked before starting command execution.**
WEPRME0939	**Setting the remote ID is only allowed if the local connection is a remote stub.**
WEPRME0940	**Using High Availability, commands may only be given to the master.**
WEPRME0941	**An unexpected exception occurred while executing a remote command from the client.**
WEPRME0942	**No async commands supported yet.**
WEPRME0943	**No sync commands expected by {0}.**
WEPRME0944	**Only master can deliver list of active servers in HA cluster.**
WEPRME0945	**Only the master may broadcast update of cluster topology.**
WEPRME0946	**Remote connection handler is already removed or unknown.**
WEPRME0947	**Sink currently does not have to handle any commands.**
WEPRME0948	**System already shut down.**
WEPRME0949	**The class {0} cannot be instantiated on the server.**
WEPRME0950	**The system is already shut down.**
WEPRME0951	**This API is only to be used in HA mode.**

WEPRME0952	**Unable to close channel {0}.**
WEPRME0953	**Unexpected command {0}.**
WEPRME0954	**Unexpected command: {0}.**
WEPRME0955	**Unknown command: {0}.**
WEPRME0956	**Unsupported approach.**
WEPRME0957	**An exception occurred while connecting.**
WEPRME0959	**Connection to server has been lost.**
WEPRME0960	**Slave trying to initialize metadata after master failed to do so.**
WEPRME0961	**Unexpected approach {0}.**
WEPRME0962	**{0} does not provide a constructor with signature String[], which is obligatory when passing a non-empty String array with parameters.**
WEPRME0963	**Builder class constructor not usable.**
WEPRME0964	**Builder class for DataSource not found.**
WEPRME0965	**Builder properties should contain at least one property e.g. connection URL.**
WEPRME0966	**Check if the schema file available.**

WEPRME0967 **Specified database table cannot be accessed.**

WEPRME0968 **System could not be configured, check XML config URL.**

WEPRME0969 **Unable to configure JPA Provider.**

WEPRME0970 **Unable to read configuration file.**

WEPRME0971 **Unable to read configuration file.**

WEPRME0972 **Unable to validate configuration file.**

WEPRME0973 **Unknown connection type purpose {0}.**

WEPRME0974 **Unknown database table {0}.**

WEPRME0975 **Unknown LoginModuleControlFlag: {0}.**

WEPRME0976 **Provided resource name is null!**

WEPRME0977 **Resource could not be located, please verify resource name ({0})!**

WEPRME0978 **Inconsistent stream metadata.**

WEPRME0979 **Unable to connect communication client.**

WEPRME0980 **Unable to connect due to incompatible protocols.**

WEPRME0981 **Unknown command.**

WEPRME0982 **Unsupported appraoch {0}.**

WEPRME0983 **Wrong command for being handled here: {0}.**

WEPRME0984 **Connection lost while not expecting a valid connection.**

WEPRME0985 **Disaster case, as other server has role {0}.**

WEPRME0986 **Inconsistent number of master result to slave communicators.**

WEPRME0987 **Master result to slave communicator which claims to support punctuations does not.**

WEPRME0988 **Multiple high availability partners are registered in cluster status ({0}).**

WEPRME0989 **No connection to slave which should be recovered.**

WEPRME0990 **No responsible master result sender found for query {0}.{1}.**

WEPRME0991 **Only the master can provide a list of active slaves.**

WEPRME0992 **Other server in unexpected role {0}.**

WEPRME0993 **PN approach currently not supported here.**

WEPRME0994 **Setting the cluster status provider is only allowed before start of high availability!**

WEPRME0995	**Setting the health check provider is only allowed before start of high availability!**
WEPRME0996	**Setting the system shutdown manager is only allowed before start of high availability!**
WEPRME0997	**Status of health check monitor of local system is not OK; shutting down!**
WEPRME0998	**Unable to connect to high availiability partner due to incompatible versions.**
WEPRME0999	**Unable to create client connection handler because cluster status provider is not yet set.**
WEPRME1000	**Unable to do handshake with HA partner.**
WEPRME1001	**Unable to grant all artefact privileges to HA user.**
WEPRME1002	**Unable to initialize master mode because the cluster''s master lock could not be acquired.**
WEPRME1003	**Unable to request communication parameters of master.**
WEPRME1004	**Unable to request role of HA partner.**
WEPRME1005	**Unable to retrieve high availability partner from cluster status.**
WEPRME1006	**Unable to shut down HA communication client of master.**
WEPRME1007	**Unable to take over master mode because the cluster''s master lock could not be acquired.**

WEPRME1008 **Unsupported approach: {0}.**

WEPRME1009 **The specified HA server address {0} is not yet registered.**

WEPRME1010 **This command should not be used by the HA protocol.**

WEPRME1012 **No sync commands expected.**

WEPRME1013 **Break-off of input stream must only occur on input 1.**

WEPRME1014 **Action must not be null.**

WEPRME1015 **Add privilege on concrete and already existing artefact makes no sense.**

WEPRME1016 **Artefact must not be null.**

WEPRME1017 **Identifier must not be null.**

WEPRME1018 **Null argument.**

WEPRME1019 **Owner must not be null.**

WEPRME1020 **Wrong privilege type.**

WEPRME1021 **Grants load failed.**

WEPRME1022 **Grants remove failed.**

WEPRME1023 **No actual artefact known.**

WEPRME1024 **Privilege {0} for user {1} granted by {2} not found.**

WEPRME1025 **Privilege {0} for user {1} not found.**

WEPRME1026 **Privilege cannot be persistent as the referenced artefact is not persistent.**

WEPRME1027 **The user {0} does not have the privilege {1}.**

WEPRME1028 **The user {0} does not have the privilege to grant the privilege {1}.**

WEPRME1029 **Privilege must not be null.**

WEPRME1030 **The delete failed.**

WEPRME1031 **The granted privilege to be serialized has no grants specified.**

WEPRME1032 **The remove of granter {0} to the database failed.**

WEPRME1033 **The saving of granter {0} to the database failed.**

WEPRME1034 **User must not be null.**

WEPRME1035 **Unsupported privilege type in serialization.**

WEPRME1036 **Unsupported privilege type.**

WEPRME1037	**Wrong privilege type.**
WEPRME1038	**Granting privileges is not supported by this authorization module.**
WEPRME1039	**Persistence is not supported by this authorization module.**
WEPRME1040	**Revoking privileges is not supported by this authorization module.**
WEPRME1041	**Check argument, xmlConfig path is wrong, file could not be located.**
WEPRME1042	**Check argument, xmlSchema path is wrong, file could not be located.**
WEPRME1043	**Check arguments, either xmlConfig path or xmlSchema path is wrong, files could not be located.**
WEPRME1044	**Check arguments, either xmlConfig path or xmlSchema were null.**
WEPRME1045	**Clearing the system is only allowed before calling createSystem.**
WEPRME1046	**System could not be configured, check XML config URL.**
WEPRME1047	**Class for schema manager not found.**
WEPRME1048	**Current system configuration does not support persistence.**
WEPRME1049	**No schema manager provided!**
WEPRME1050	**Object of the schema manager cannot be instantiated!**

WEPRME1051 **Only client commands can be sent using this callback.**

WEPRME1052 **Problem with access to class of schema manager.**

WEPRME1053 **Registering protocol handlers is only allowed before system start!**

WEPRME1054 **Registering protocols is only allowed before system start!**

WEPRME1055 **Setting the cache provider is only allowed before system start!**

WEPRME1056 **The protocol handler must not be null.**

WEPRME1057 **The protocol must not be null.**

WEPRME1058 **There is already a protocol handler registered using identifier {0}.**

WEPRME1059 **There is already a protocol registered using identifier {0}.**

WEPRME1060 **Unknown protocol {0}.**

WEPRME1061 **The identifier "{0}" is not allowed for a {1}.**

WEPRME1062 **The identifier "{0}" is too long (maximum of {1} characters allowed).**

WEPRME1063 **The identifier of type {0} must not be null.**

WEPRME1064 **Unsupported artefact {0}.**

WEPRME1065	**Minimum supported client version must not be greater than maximum one.**
WEPRME1066	**Server must not support older maximum client versions than the previous one.**
WEPRME1067	**Server must not support older minimum client versions than the previous one.**
WEPRME1068	**Server must support clients with same version.**
WEPRME1069	**Server versions have to be provided in ascending order.**
WEPRME1070	**The operator is not processing.**
WEPRME1071	**The timestamps have to be provided in ascending order.**
WEPRME1072	**Sources must not have inputs.**
WEPRME1073	**The method (compute)Done must not be called on sources.**
WEPRME1074	**The method (compute)HeartBeat must not be called on sources.**
WEPRME1075	**The method (compute)Punctuate must not be called on sources.**
WEPRME1076	**The method (compute)Push must not be called on sources.**
WEPRME1077	**No additional outputs allowed.**
WEPRME1078	**A SourceAdapter providing a chronon stream must not use end timestamps other than start timestamp +1.**

WEPRME1079 **The operator is not processing ({0}).**

WEPRME1080 **The timestamps have to be provided in ascending order.**

WEPRME1081 **Source has to have at least one output.**

WEPRME1082 **Extra start time must be smaller than start time.**

WEPRME1083 **No extra work function specified for this source.**

WEPRME1084 **Sequence may not start before the logical start time.**

WEPRME1085 **Sequence produced wrong start timestamp.**

WEPRME1086 **HeartBeatPeriod has to be a divisor of elementPeriod.**

WEPRME1087 **Time {0} already past ({1}).**

WEPRME1088 **The specified label must not be null.**

WEPRME1089 **Lower bound of 1st range does not match with specified minimum.**

WEPRME1090 **Number of ranges and colors differ.**

WEPRME1091 **Upper bound of {0} range does not match with lower bound of {1} range.**

WEPRME1092 **Upper bound of last range does not match with specified maximum.**

WEPRME1093 **Legend for time series number {0} is not specified!**

WEPRME1094 **Sinks may not have outputs.**

WEPRME1095 **An ID has to be provided for each source.**

WEPRME1096 **Unable to provide metadata.**

WEPRME1097 **Illegal input index {0}.**

WEPRME1098 **Input data validity may not overlap more than one day.**

WEPRME1099 **Output already exists.**

WEPRME1100 **Output creation must take place before init.**

WEPRME1101 **Missing negative element for group {0}.**

WEPRME1102 **The length of minimal splits cannot be less than one millisecond.**

WEPRME1103 **An ID has to be provided for each cache input.**

WEPRME1104 **An ID has to be provided for each input.**

WEPRME1105 **Unexpected number of cache inputs!**

WEPRME1106 **Unexpected number of stream inputs!**

WEPRME1107 **Duplicate scope limited heartbeat for input {0}.**

WEPRME1108 **Scope limited heartbeats with different timestamps.**

WEPRME1109 **Window advance <= 0 not allowed.**

WEPRME1110 **Window size <= 0 not allowed.**

WEPRME1111 **Missing negative input elements.**

WEPRME1112 **Not all positive elements matched.**

WEPRME1113 **Negative call on empty state.**

WEPRME1115 **The window advance must not be smaller than or equal to 0.**

WEPRME1116 **Negative element not matching any previous positive one.**

WEPRME1117 **An ID has to be provided for each input.**

WEPRME1118 **Not all positive elements were matched by a negative one.**

WEPRME1119 **Adding status is only allowed before open.**

WEPRME1120 **Additional status elements have to be consecutive.**

WEPRME1121 **The length of minimal splits cannot be less one millisecond.**

WEPRME1125 **Error on both streams !**

WEPRME1126 **Inconsistent streams.**

WEPRME1127 **No additional outputs allowed.**

WEPRME1128 **Minimum split length <= 0 not allowed.**

WEPRME1129 **Ambiguous next edge.**

WEPRME1130 **Graph has to be packed before sequences can be generated.**

WEPRME1131 **Graph is already packed.**

WEPRME1132 **No node with ID {0}.**

WEPRME1133 **Reserved ID.**

WEPRME1134 **Wrong temporal event order.**

WEPRME1135 **The checked graph has the following errors: {0}**

WEPRME1136 **Duplicate scope limited heartbeat for input {0} (old: {1}, new: {2}).**

WEPRME1137 **Scope limited heartbeats with different timestamps.**

WEPRME1138 **Maximum size must only be given if blockIfFull is set.**

WEPRME1139 **Duplicate scope limited heartbeat for input {0}.**

WEPRME1140 **Start timestamp series is not monotonous.**

WEPRME1141 **Scope limited heartbeat for recursive input {0} was not processed within the whole recursive query plan.**

WEPRME1142 **Scope limited heartbeats are not supported for non-recursive inputs of recursion base.**

WEPRME1143 **The window advance must not be smaller than or equal to 0.**

WEPRME1144 **The window size must not be smaller than or equal to 0.**

WEPRME1145 **Execution has already been assigned.**

WEPRME1146 **Sink has to belong to this graph.**

WEPRME1147 **Source has to belong to this graph.**

WEPRME1148 **No corresponding connection found.**

WEPRME1149 **Punctuation type {0} is not supported by default serializer.**

WEPRME1150 **Data must not be null.**

WEPRME1151 **Invalid element (empty time interval).**

WEPRME1152 **Check internal queue resources/state.**

WEPRME1153 **Operator won''t produce any result in this state: {0}.**

WEPRME1154 **Method must not be called inside a connection''s batch run.**

WEPRME1155 **Input record does not comply with the schema: expected {0}, but received {1}.**

WEPRME1156 **The record size ({0}) of {1} does not comply with metadata {2}.**

WEPRME1157 **The row {0} does not support null values.**

WEPRME1158 **RequiredDatabaseSources must not be null.**

WEPRME1159 **RequiredQueries must not be null.**

WEPRME1160 **RequiredUserDefinedFunctions must not be null.**

WEPRME1161 **Null properties are not allowed.**

WEPRME1162 **Property {0} has to be of type {1}.**

WEPRME1163 **RecordMetaData must not be null.**

WEPRME1164 **Subscriptions must not be null.**

WEPRME1165 **The given notification callback is already registered.**

WEPRME1166 **The given notification callback is not registered.**

WEPRME1167 **A timestamp for each input has to be specified.**

WEPRME1168 **All inputs have to be provided before init.**

WEPRME1169 **An operator may not publish elements in state {0}.**

WEPRME1170 **An operator may not publish punctuations in state {0}.**

WEPRME1171 **Cannot determine periodically updated metadata fragments! Execution is unavailable!**

WEPRME1172 **Cannot determine periodically updated metadata fragments! PeriodicMetaDataUpdateWorkerThread is unavailable!**

WEPRME1173 **Complete from is already set for output ID {0}.**

WEPRME1174 **Complete from must not change (Was {0} for output {1} and tried to change to {2}).**

WEPRME1175 **Graph must not be null!**

WEPRME1176 **Graph Wlock needed.**

WEPRME1177 **Identifier {0} is not supported.**

WEPRME1178 **Illegal Operator State: {0} (State.INITIALIZED or State.PROCESSING expected).**

WEPRME1179 **Index out of bounds.**

WEPRME1180 **Input {0} already set.**

WEPRME1181 **Input {0} not set.**

WEPRME1182 **Input {0} was not set.**

WEPRME1183 **MetaData-object must not be null!**

WEPRME1184 **Minimum heartbeat distance must not be smaller than one.**

WEPRME1185 **Not enough inputs provided.**

WEPRME1186 **Operator already closed.**

WEPRME1187 **Operator already closed.**

WEPRME1188 **Operator is already initialized.**

WEPRME1189 **Operator is already opened.**

WEPRME1190 **Operator is working.**

WEPRME1192 **Operator may not use tellDone method in state {0}.**

Explanation The tellDone method of an operator announces to downstream operators that the operator will no longer send events. Calling this method is restricted to certain states of the lifecycle of the operator.

Action Restrict the use of this method to the permitted lifecycle states.

WEPRME1193 **Operator was already closed.**

WEPRME1194 **Operator was already closed - use reset.**

WEPRME1195 **Output already exists.**

WEPRME1196 **Output already set.**

WEPRME1197 **Output creation must take place before init.**

WEPRME1198 **Output ID out of bounds.**

WEPRME1199 **Output not found.**

WEPRME1200 **Output not set.**

WEPRME1201 **Punctuations of type {0} are not supported by operator {1}.**

WEPRME1202 **Setting complete from for operators with optional inputs is only possible if no inputs present.**

WEPRME1203 **Setting complete from for operators with optional inputs is only possible when initialized.**

WEPRME1204 **Setting complete from is only possible for sources.**

WEPRME1205 **Too many inputs provided.**

WEPRME1206 **Nullary operators have no sources.**

WEPRME1207 **Input not set.**

WEPRME1208 **Unable to read from input.**

WEPRME1209 **From must not be null.**

WEPRME1210 **Unable to close input stream.**

WEPRME1211 **Unable to read file.**

WEPRME1212 **Reset is not supported for a queue while it is consuming.**

WEPRME1213 **Min must not be greater than max.**

WEPRME1214 **Only positive numbers of elements are supported.**

WEPRME1215 **Times must not be negative.**

WEPRME1216 **Right input has to support reset.**

WEPRME1217 **Not enough sources provided.**

WEPRME1218 **Sources not yet provided.**

WEPRME1219 **Wrong input type.**

WEPRME1220 **Cannot determine supportsReset before init.**

WEPRME1221 **No source provided.**

WEPRME1222 **Source not yet provided.**

WEPRME1223 **Wrong input type.**

WEPRME1224 **Initally empty map required.**

WEPRME1225 **This queue is limited.**

WEPRME1226 **Buffer must have a capacity of at least one element.**

WEPRME1227 **No additional run can be obtained before consuming the last one.**

WEPRME1228 **No new cursors can be requested after all previously requested cursors were closed.**

WEPRME1229 **Only one additional cursor supported due to consuming TeeBuffer.**

WEPRME1230 **This is a consuming TeeBuffer.**

WEPRME1231 **This is not a consuming TeeBuffer.**

WEPRME1232 **Iterator is empty.**

WEPRME1233 **Underlying iterator has to support remove.**

WEPRME1234 **Init not allowed after open{0}{1}.**

WEPRME1235 **Iterator is already closed.**

WEPRME1236 **Iterator is already initialized.**

WEPRME1237 **Iterator is already open.**

WEPRME1238 **Iterator is not initialized.**

WEPRME1239 **Iterator was already closed - use reset.**

WEPRME1240 **Iterator was not opened.**

WEPRME1241 **No more elements left.**

WEPRME1242 **Remove is not supported by this iterator.**

WEPRME1243 **Reset is only allowed after open and before close.**

WEPRME1244 **Update may only be used after next().**

WEPRME1245 **Not all required sources set.**

WEPRME1246 **Operator was already initialized.**

WEPRME1247 **Operators do not supported remove.**

WEPRME1248 **Sources {0} not set.**

WEPRME1249 **Update may only be used after next().**

WEPRME1250 **Exception during close.**

WEPRME1251 **Exception during init.**

WEPRME1252 **Exception during query processing.**

WEPRME1253 **Unable to handle {0} due to {1}.**

WEPRME1254 **Unknown device.**

WEPRME1255 **Wrong data format: missing header element.**

WEPRME1256 **Wrong data format: missing header end.**

WEPRME1257 **Wrong data format: missing header start.**

WEPRME1258 **Wrong data format: missing packet end.**

WEPRME1259 **Wrong data format: unable to parse parameter.**

WEPRME1260 **Wrong data format: unable to parse parameter count.**

WEPRME1261 **Wrong data format: unable to parse timestamp.**

WEPRME1262 **Wrong data format: wrong number of parameters.**

WEPRME1263 **Wrong data format: wrong parameter format.**

WEPRME1264 **Bytes message cannot be read because of the following reason: {0}.**

WEPRME1265 **Bytes messages do not support reading lines of data.**

WEPRME1266 **Bytes message cannot be written because of the following reason: {0}.**

WEPRME1267 **Connection cannot be created. Check associated properties (e.g. authentication properties)! {0}.**

WEPRME1268 **Connection cannot be listened to because of the following reason: {0}.**

WEPRME1269 **Connection factory cannot be retrieved via JNDI. Check associated ID! {0}.**

WEPRME1270 **Destination cannot be retrieved via JNDI. Check associated ID! {0}.**

WEPRME1271 **JNDI context cannot be created. Check connection properties! {0}.**

WEPRME1272 **Message cannot be sent because of the following reason: {0}.**

WEPRME1273 **Receiver cannot be created because of the following reason: {0}.**

WEPRME1274 **Sender cannot be created because of the following reason: {0}.**

WEPRME1275 **Session cannot be created because of the following reason: {0}.**

WEPRME1276 **Connection cannot be created because of the following reason: {0}.**

WEPRME1277 **Input has to support reset.**

WEPRME1278 **This class must not be reinitialized.**

WEPRME1279 **Unexpected reinitialization.**

WEPRME1280 **Only operators can be used as child nodes of a distinct operator.**

WEPRME1281 **Database sources using direct access cannot be used in user-defined operators.**

WEPRME1282 **Incompatible parameter type for user-defined operator {0} (expected {1}, found {2}).**

WEPRME1283 **Initialization is only available for user-defined operators.**

WEPRME1284 **Input of user-defined operator has unknown mode {0}.**

WEPRME1285 **Inputs of a user-defined operator have to be ordered (first input streams, second database sources).**

WEPRME1286 **Only user-defined operators and sources can be used as child nodes of a user-defined operator (found {0}).**

WEPRME1288 **Unable to compute stream metadata for user-defined operator.**

WEPRME1289 **Unable to retrieve specified source input.**

WEPRME1290 **Unknown user-defined operator mode {0}.**

WEPRME1291 **Wrong number of instantiation parameters for user-defined operator {0} (expected {1}, found {2}).**

WEPRME1292 **List caches cannot be indexed!**

WEPRME1293	**Missing key indices!**
WEPRME1294	**Missing key!**
WEPRME1295	**Unsupported communication type.**
WEPRME1296	**Attempt to inconsistently initialize serializers for complex {0}.**
WEPRME1297	**Wrong serialization initialization - Missing: {0}, unused: {1}.**
WEPRME1298	**Wrong alternative.**
WEPRME1299	**File has to be empty.**
WEPRME1300	**Update ist not permitted.**
WEPRME1301	**Iterator always removes elements.**
WEPRME1302	**Remove is currently not supported.**
WEPRME1303	**Unsupported type code: {0}.**
WEPRME1304	**Unsupported RTM exception type.**
WEPRME1305	**Inputs of an user-defined operator have to be ordered (first input streams, second database sources).**
WEPRME1306	**Only user-defined operators and sources can be used as child nodes of an user-defined operator (found {0}).**

WEPRME1307 **Wrong number of instantiation parameters for user-defined operator {0} (expected {1}, found {2}).**

WEPRME1308 **Incompatible parameter type for user-defined operator {0} (expected {1}, found {2}).**

WEPRME1309 **Input metadata mismatch for user-defined operator {0}. {1}**

WEPRME1310 **Missing inputs for user-defined operator {0}. {1}**

WEPRME1311 **Too may inputs for user-defined operator {0}. {1}**

WEPRME1312 **Unable to use user-defined operator {0}. {1}.**

WEPRME1313 **RequiredUserDefinedOperators must not be null.**

WEPRME1314 **An input stream is to be connected to an operator at index {0}, but the index must not be negative or exceed the maximum allowed number of inputs, which is {1}.**

WEPRME1315 **Inconsistent output stream metadata.**

WEPRME1317 **The entry to insert does not provide the list of required entries.**

WEPRME1318 **A list of required repository entries has to be provided.**

WEPRME1319 **An initialization reason has to be provided. Use other constructor if no reinitialization takes place.**

WEPRME1320 **JPA initialization is only allowed using the parameterless constructor.**

WEPRME1322 **The entry is not yet initialized.**

WEPRME1323 **The timestamps have to be provided in increasing order.**

WEPRME1324 **The end timestamp has to be greater than the start timestamp.**

WEPRME1325 **First snapshot-reducible event has been sent for the following query: Owner: {0} Identifier: {1} Event: {2}**

WEPRME1326 **The entry {0} required by {1} is not in the repository.**

WEPRME1327 **The entry {0} can not be removed as it is still in use.**

WEPRME1328 **The left-hand side of an action must be a field declared in the measure clause.**

WEPRME1335 **This UserDefinedOperator is missing cache inputs. Minimum expected: {0}. Found: {1}.{2}**

WEPRME1336 **This UserDefinedOperator is missing stream inputs. Minimum expected: {0}. Found: {1}.{2}**

WEPRME1337 **This UserDefinedOperator has too many cache inputs. Maximum expected: {0}. Found: {1}.{2}**

WEPRME1338 **This UserDefinedOperator has too many stream inputs. Maximum expected: {0}. Found: {1}.{2}**

WEPRME1340 **Invalid range of exponent.**

WEPRME1341 **Error occurred when evaluating function {0}. {1}**

WEPRME1342 **Error occurred when evaluating operation {0}. {1}**

WEPRME1343 **Cast to {0} is illegal due to precision loss.**

WEPRME1344 **Illegal real exponent for negative base. Integer required.**

WEPRME1345 **Invalid negative exponent for base zero.**

WEPRME1346 **Undefined for x <= 0.**

WEPRME1347 **Undefined for negative values.**

WEPRME1348 **The query {0} cannot be stopped as it is still in use.**

WEPRME1349 **Unexpected problem caused by usage of a subscription.**

WEPRME1350 **The user-defined function {0}.{1} cannot be deregistered as it is still in use.**

WEPRME1351 **The user-defined aggregation function {0}.{1} cannot be deregistered as it is still in use.**

WEPRME1352 **The user-defined operator {0}.{1} cannot be deregistered as it is still in use.**

WEPRME1353 **The data source {0}.{1} cannot be deregistered as it is still in use.**

WEPRME1354 **The table {0}.{1} cannot be deregistered as it is still in use.**

WEPRME1355 **The number of inputs returned by the user-defined operator adapter''s getNumberOfInputs() method ({0}) is not consistent with the the number of inputs the user-defined operator adapter factory is called with ({1}).**

WEPRME1356	**The number of cache inputs returned by the user-defined operator adapter''s getNumberOfInputs() method ({0}) is not consistent with the the number of cache inputs the user-defined operator adapter factory is called with ({1}).**
WEPRME1357	**Division by zero.**
WEPRME1358	**Column ''{0}''not found in metadata object.**
WEPRME1359	**Unexpected number of field metadata entries. Found {0}, expected {1}.**
WEPRME1360	**Objects of type {0} do not match. {1} <> {2}.**
WEPRME1361	**Unexpected number of columns. Found {0}, expected {1}.**
WEPRME1362	**Argument may not be null!**
WEPRME1363	**Column {0} has an unexpected type. Found {1}, expected {2}.**
WEPRME1365	**Column is expected to be nullable: {1}.**
WEPRME1366	**Column is expected to be case sensitive: {0}.**
WEPRME1368	**Parameter is not within range [{0}, {1}]: {2}.**
WEPRME1369	**Stream is expected to be a chronon stream!**
WEPRME1370	**Stream is not expected to be a chronon stream!**
WEPRME1371	**Parameter does not match expected value. Found {0}, expected {1}.**

WEPRME1372 **The address given in config parameter {0} must not be empty.**

WEPRME1373 **The deprecated property {0} is used although the new property {1} is present.**

WEPRME1374 **Wrong number of factory parameters (was {0} but expected {1}).**

WEPRME1375 **Invalid port number: {0}.**

WEPRME1378 **Error evaluating aggregate function {0}. {1}**

WEPRME1379 **Error occurred in method {0}.**

WEPRME1380 **The signature of the user-defined aggregation function {0} does not match the specified types ({1}).**

WEPRME1381 **The user-defined aggregation function {0} is unknown or not visible.**

WEPRME1383 **Error occurred when evaluating function {0}.**

WEPRME1384 **Error occurred when evaluating operation {0}.**

WEPRME1385 **The field {0} is ambiguous. Check if fields and sources are properly renamed and no duplicate aliases are introduced.**

WEPRME1386 **The provided source parameters should not be null.**

Explanation The input parameter source parameters is null. A valid source parameters object should be provided.

WEPRME1387 **The provided server source parameters should not be null.**

Explanation The input parameter server source parameters is null. A valid server source parameters object should be provided.

WEPRME1388 **The provided query parameters should not be null.**

Explanation The input parameter query parameters is null. A valid query parameters object should be provided.

WEPRME1389 **The provided query language should not be null.**

Explanation The input parameter query language is null. A valid query language object should be provided.

WEPRME1390 **The provided query string should not be null.**

Explanation The input parameter query string is null. A valid query string object should be provided.

WEPRME1391 **The command prepareQuery2 is not supported by the server.**

Explanation The client tried to send the command prepareQuery2 to the server. The current server version does not support handling of this command. There is a mismatch between client version and server version.

WEPRME1392 **The query {0} cannot be subscribed to using subscription mode {1} as subscriptions to this query were restricted to times when no element is valid.**

Explanation The query was prepared using the query parameter 'isSubscribableOnlyWhenNoElementValid'. Subscriptions to such queries may not use other subscription modes than 'ALL'.

Action Use subscription mode 'ALL'.

WEPRME1393 **The query {0} can currently not be subscribed to as subscriptions to this query were restricted to times when no element is valid.**

WEPRME1394 **The query {0} cannot be unsubscribed from using subscription mode {1} as subscriptions to this query were restricted to times when no element is valid.**

Explanation The query was prepared using the query parameter 'isSubscribableOnlyWhenNoElementValid'. Unsubscriptions to such queries may not use other subscription modes than 'ALL'.

Action Use subscription mode 'ALL'.

WEPRME1395 **An exception related to {0} occurred in the underlying connection.**

WEPRME1396 **Creation of empty arrays is not supported.**

WEPRME1397 **All values in an array value construction must have the same type.**

WEPRME1398 **Only field expressions can be used as child nodes of an array element reference expression.**

WEPRME1399 **Limiting subscriptions to times when no element is valid is currently not supported in HA mode.**

WEPRME1400 **The field {0} is not of type ARRAY.**

WEPRME1401 **The method {0} is not yet supported in class {1}.**

WEPRME1402 **The XML query is not a valid XML document.**

WEPRME1404 **The XML query contains semantical errors.**

WEPRME1405 **An operator providing a chronon stream must not use end timestamps other than start timestamp +1.**

WEPRME1406 **Unknown timezone: {0}.**

WEPRME1407 **The time unit ''{0}'' is unknown.**

WEPRME1408 **Connection to {0} system lost.**

WEPRME1409 **Client lost connection to server with address {0}.**

WEPRME1425 **The Positive-Negative approach is currently not supported when running in high availability mode.**

WEPRME1427 **NullPointerException occurred while accepting new connection on address {0}.**

WEPRME1428 **CommunicationException occurred while accepting new connection on address {0}.**

WEPRME1429 **Exception occurred while accepting new connection on address {0}.**

WEPRME1431 **The pattern contains illegal characters. Supported characters are letters and the meta characters '*', '+', '?', '.', '|', '(', ')', '[', ']', '^', '{', '}', '' and digits.**

WEPRME1432 **An aggregate is not allowed in this context.**

Explanation The query contains an aggregate, but in a context that does not permit aggregates. Aggregates are only allowed in the SELECT and HAVING clauses of an SQL query, or inside an aggregate operator of an XML query.

Action Correct the query and resubmit.

WEPRME1433 **An Ehcache with the name {0} already exists.**

Explanation The system has tried to create a new Ehcache but it already existed in the CacheManager.

Action Make sure the existing Ehcache is removed from the CacheManager.

WEPRME1434 **Ehcache configuration error: {0}.**

Explanation The provided ehcache configuration file is not valid.

Action Make sure the provided ehcache configuration file is valid.

WEPRME1435 **Problem creating new Ehcache: {0}.**

Explanation The system tried to create a new Ehcache but encountered problems.

Action See detailed message for further information.

WEPRME1436 **Invalid value of join attribute ''{0}''.**

Explanation Join attributes refer to the input operators of a join by specifying their 0-based index. They are thus composed of a list of indexes, where only 0 and 1 are valid indexes. As an additional constraint, the list must not contain duplicates.

Action Correct the specified join attribute.

WEPRME1437 **The child nodes with the UIDs ''{0}'' and ''{1}'' are not equivalent in the equivalence node.**

Explanation Two of the child nodes in the equivalence node have different record metadata. All direct children of an equivalence node in a query graph must have the same record metadata (resulting schema).

Action Adapt the equivalence node so that all child nodes have the same record metadata.

WEPRME1438 **Regular expression is invalid at offset {0}.**

Explanation The query contains a PATTERN clause, but its regular expression has invalid syntax. The offset contained in the message is the 0-based offset within the regular expression where the failure was detected.

Action Correct the regular expression syntax and resubmit the query.

WEPRME1439 **Barrier can only await one single set of connections.**

WEPRME1440 **The connection barrier has not been passed yet.**

WEPRME1441 **Connection for ID {0} could not be used as it connected too late.**

WEPRME1442 **Unexpected incoming recovery connection for ID {0}.**

WEPRME1443 **Duplicate incoming recovery connection for ID {0}.**

WEPRME1444 **Wrong user or password for recovery connection for ID {0}.**

WEPRME1445 **The connection is already authenticated.**

WEPRME1447 **Unable to cast the {0} value {1} to {2}.**

Explanation The specified CAST function tries to cast the specified value to the shown type, but this is not possible.

Action Either change the value in a way that it can be casted to the specified type or change the type accordingly.

WEPRME1449 **Unable to read the given event.**

WEPRME1450 **Unable to write the given event.**

WEPRME1451 **Percentage of delays must be in [0,1].**

Explanation Percentage of delays must be in [0,1].

Action Configure delay to be in [0,1].

WEPRME1452 **Exclusion threshold for delays must be greater than or equal zero.**

Explanation Exclusion threshold for delays must be greater than or equal zero.

Action Set exclusion threshold for delays to be greater than or equal zero.

WEPRME1453 **The weighting factor alpha must be in [0,1].**

Explanation The weighting factor alpha must be in [0,1].

Action Set the weighting factor alpha to be in [0,1].

WEPRME1454 **Size for the queue must be greater 1.**

Explanation Size for the queue must be greater 1.

Action Set size for the queue to be greater 1.

WEPRME1455 **Missing Ehcache configuration.**

Explanation The useEhcache query parameter was set, but there was no Ehcache configuration present in the RTM system confuration.

Action Either remove the useEhcache query parameter, or extend the RTM system configuration to include an Ehcache configuration.

WEPRME1456	**Element must not be null.**
Explanation	Element must not be null.
Action	Insert only elements not being null.

WEPRME1458	**Only one overload detector can be registered at a time.**
Explanation	Only one overload detector can be registered at a time.
Action	Register only one overload detector.

WEPRME1459	**The DURATION expression of a MATCHING clause must be evaluable to a numeric type.**
Explanation	The specified DURATION expression evaluates to a type that is not numeric, e.g., STRING. But DURATION expressions must be numeric.
Action	Change the DURATION expression such taht is evaluates to a numeric type.

WEPRME1460	**The WITHIN expression of a MATCHING clause must be evaluable to a numeric type.**
Explanation	The specified WITHIN expression evaluates to a type that is not numeric, e.g., STRING. But WITHIN expressions must be numeric.
Action	Change the WITHIN expression such taht is evaluates to a numeric type.

WEPRME1461	**Check the DURATION expression.**
Explanation	The DURATION expression contains an unspecific error.
Action	Check the DURATION expression.

WEPRME1462	**Check the WITHIN expression.**
Explanation	The WITHIN expression contains an unspecific error.
Action	Check the WITHIN expression.

WEPRME1469	**The maximum window size must not be smaller than or equal to 0.**
Explanation	The maximum windo size specifies the maximum validity an event can get applied by the window operator. As validities are always greater than zero the maximum window size also has to be.
Action	Specify a maximum window size that is greater than 0.

WEPRME1471	**The size of a count-based window can only be specified using a numeric constant.**
Explanation	Count-based windows does not support window size specification using numeric expressions.
Action	Replace the window size expression by a numeric constant.

WEPRME1472	**Check the window size expression.**
Explanation	The window size expression contains an unspecific error.
Action	Check the window size expression.

WEPRME1473	**Only constant maximum windows sizes, i.e., milliseconds, seconds, minutes or hours, are allowed for time-based windows.**
Explanation	The maximum window size must be evaluable to a constant amount of milliseconds. For this reason only constant time units are supported.
Action	Use a constant unit, i.e., millisecond, second, minute or hour, when specifying a maximum window size.

WEPRME1474	**The size of a time-based window can''t be specified using a non-numeric constant.**
Explanation	The window size is specified by a non-numeric constant.
Action	Replace the non-numeric constant window size specification by a numeric constant or an expression that can be evaluated to a numeric type.

WEPRME1475	**The window size must not be greater than the specified maximum window size.**
Explanation	The computed window size was greater than the specified maximum window size.
Action	Check the window size expression if it could be limited to results that are less than or equal to the specified maximum window size or adapt (or remove) the specified maximum window size.

WEPRME1476	**The user {0} does not have the privilege to refresh the table.**

WEPRME1477	**The table {0} does not support triggered cache refresh!**
Explanation	The table is configured with no support for a a-periodic, triggered cached refreshed.
Action	Change the AccessProperties of the table and enable supportsTriggeredRefresh option to enable a-periodic triggering of table refreshes.

WEPRME1479 **The required complete-from timestamp cannot be guaranteed by the source.**

Explanation The source operator cannot guarantee the semantic subscription time requested when preparing the query.

Action Change or remove the requested semantic subscription time when preparing the query.

WEPRME1480 **The required complete-from timestamp cannot be guaranteed by the source adapter (not an intra source adapter).**

Explanation Only intra source adapters are able to guarantee semantic subscription time requests when preparing a query.

Action Use registered intra source adapters or remove the requested semantic subscription time when preparing the query.

WEPRME1481 **The required complete-from timestamp cannot be guaranteed by the source adapter (intra source adapter does not support requesting semantic subscription times).**

Explanation The used intra source adapter does not support guaranteed semantic subscription time requests when preparing a query.

Action Use intra source adapters supporting this feature or remove the requested semantic subscription time when preparing the query.

WEPRME1482 **The required complete-from timestamp cannot be guaranteed by the source adapter (intra source adapter is not able to provide the requested semantic subscription time).**

Explanation The used intra source adapter is not able to guarantee the semantic subscription time requested when preparing the query.

Action Change or remove the semantic subscription time requested when preparing the query.

WEPRME1483 **The required complete-from timestamp cannot be guaranteed by the operator.**

Explanation The operator is already opened and the requested semantic subscription time cannot be guaranteed anymore.

Action Modify or remove the semantic subscription time requested when preparing the query.

WEPRME1484	**The required complete-from timestamp cannot be guaranteed by the count-based window.**
Explanation	Count-based windows does not support requesting semantic subscription times when preparing a query.
Action	Remove the count-based window from the query or remove the semantic subscription time request when preparing the query.

WEPRME1485	**The duration must not be NULL.**
Explanation	The duration expression was evaluated to NULL.
Action	The duration expression must not return NULL as it cannot be interpreted as a duration value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.

WEPRME1486	**The within must not be NULL.**
Explanation	The within expression was evaluated to NULL.
Action	The within expression must not return NULL as it cannot be interpreted as a within value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.

WEPRME1487	**The window size must not be NULL.**
Explanation	The window size expression was evaluated to NULL.
Action	The window size expression must not return NULL as it cannot be interpreted as a window size value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.

WEPRME1488	**Execution is already started.**

WEPRME1489	**Execution is already stopped and may not be restarted.**

WEPRME1490	**Execution is not started, yet.**

WEPRME1491	**Execution is already stopped.**

WEPRME1492 **Error unregistering mBean ''{0}''.**

WEPRME1493 **Failed to invoke setter on class ''{0}''.**

WEPRME1494 **Failed to invoke action ''{0}'' on class ''{1}''.**

WEPRME1495 **Failed to invoke getter ''{0}'' on class ''{1}''.**

WEPRME1496 **Attribute name cannot be null.**

WEPRME1498 **Getter must not be invoked as long as metadata is not activated.**

WEPRME1499 **Attribute ''{0}'' not found in class ''{1}''.**

WEPRME1500 **Setters is not supported.**

WEPRME1501 **Action name cannot be null.**

WEPRME1502 **No parameters allowed.**

WEPRME1503 **No Signature allowed.**

WEPRME1504 **Action name has to start with either {0}, {1} or {2}.**

WEPRME1505 **No such metaDataIdentifier found: {0}.**

WEPRME1506 **Unsupported parameter type: {0}.**

WEPRME1508	**Aggregates are not allowed in the GROUP BY clause.**
Explanation	As the grouping is applied before the aggregates are computed on the groups it is not allowed to use aggregates in the GROUP BY clause.
Action	Remove the aggregate from the GROUP BY clause.

WEPRME1509	**Check the specified group expression.**
Explanation	The group expression contains an unspecific error.
Action	Check the group expression for errors.

WEPRME1510	**Check the specified predicate (having clause).**
Explanation	The predicate contains an unspecific error.
Action	Check the predicate for errors.

WEPRME1511	**Only operators can be used as child nodes of a limit operator.**
Explanation	A non-operator node was passed as the input node of a limit operator, where only an operator node is allowed.
Action	Supply an operator node as the child of a limit operator.

WEPRME1512	**Only operators can be used as child nodes of an order operator.**
Explanation	A non-operator node was passed as the input node of an order operator, where only an operator node is allowed.
Action	Supply an operator node as the child of an order operator.

WEPRME1513	**Translation mode does not support operators of type {0}.**
Explanation	An unsupported operator was found during the translation of an SQL statement. The operator may be invalid for the current mode , but valid in other translation mode.
Action	Avoid SQL statements using the offending operator, or use a translation mode that supports it.

WEPRME1514	**Invalid aggregate in ORDER BY clause.**
Explanation	An ORDER BY clause was found to contain an aggregate function, which was not specified earlier in the same query. This is not allowed, an ORDER BY clause must not introduce new aggregate functions.
Action	Correct SQL statement, e.g. by adding the aggregate in question to the SELECT list.

WEPRME1515	**Check the specified part of the ORDER BY clause.**
Explanation	The ORDER BY clause was found to contain some invalid construct.
Action	Inspect ORDER BY clause and remove any invalid expressions.

WEPRME1516	**Subquery not allowed in this context.**
Explanation	A subquery was found in a context, where it is not supported.
Action	Correct statement according to the language specification.

WEPRME1517	**Subquery results in more than one column, where it must be a single column.**
Explanation	A subquery in a comparison of the where clause must result in a single column.
Action	Correct SQL statement.

WEPRME1518	**Invalid frame bound.**
Explanation	A window definition contained an invalid frame bound. A frame bound of UNBOUNDED FOLLOWING is not allowed on the left hand side of a window frame BETWEEN definition, and a frame bound of UNBOUNDED PRECEDING is not allowed on the right hand side.
Action	Correct SQL statement.

WEPRME1519	**Window function not allowed in this context.**
Explanation	A window function was found in a context, where it is not supported.
Action	Correct statement according to the language specification.

WEPRME1520	**Check the specified part of the window specification.**
Explanation	A window specification was found to contain some invalid construct.
Action	Inspect window specification and remove any invalid expressions.

WEPRME1521	**Only operators can be used as child nodes of a window aggregation operator.**
Explanation	A non-operator node was passed as the input node of a window aggregation operator, where only an operator node is allowed.
Action	Supply an operator node as the child of a window aggregation operator.

WEPRME1524	**Invalid nested aggregate function reference.**
Explanation	The argument of a set function invocation cannot be another set function.
Action	Correct SQL statement.

WEPRME1535	**The 2nd argument of the ROUND function must be of type integer.**
Explanation	The 2nd argument of the given ROUND function call is not of type integer which is mandatory.
Action	Change the expression specifying the 2nd argument of ROUND function such that it is of type integer.

WEPRME1536	**Unable to parse long value due to wrong number format. {0}**
Explanation	The given literal does not comply with the structure of an integral number, i.e. it contains characters other than 0-9,+,-.
Action	Please remove any invalid characters from your integer literal.

WEPRME1537	**Unable to parse integer value due to wrong number format. {0}**
Explanation	The given literal does not comply with the structure of an integral number, i.e. it contains characters other than 0-9,+,-.
Action	Please remove any invalid characters from your integer literal.

WEPRME1538	**If FROM is specified in the TRIM function,either the trim specification (LEADING, TRAILING, or BOTH) or the trim character or both have to be specified.**
Explanation	If FROM is specified in the TRIM function,either the trim specification (LEADING, TRAILING, or BOTH) or the trim character or both have to be specified.
Action	Either add the trim specification, the trim character or both. Alternatively remove the FROM clause.

WEPRME1539	**Only expressions are permitted for the trim source argument of the TRIM function.**
Explanation	Only expressions are permitted for the trim source argument of the TRIM function.
Action	Use an expression for the trim source argument.

WEPRME1540	**Only expressions are permitted for the trim character argument of the TRIM function.**
Explanation	Only expressions are permitted for the trim character argument of the TRIM function.
Action	Use an expression for the trim character argument.

WEPRME1541	**The {1} function only supports STRING values as argument for the substring source.**
Explanation	The {1} function only supports STRING values as argument for the substring source.
Action	Use a STRING value as argument for the substring source.

WEPRME1542	**The {1} function only supports INTEGER values as argument for the start position.**
Explanation	The {1} function only supports INTEGER values as argument for the start position.
Action	Use an INTEGER value as argument for the start position.

WEPRME1543	**The {1} function only supports INTEGER values as argument for the string length.**
Explanation	The {1} function only supports INTEGER values as argument for the string length.
Action	Use and INTEGER value as argument for the string length.

WEPRME1544	**The {1} function only supports STRING values as argument for the trim character.**
Explanation	The {1} function only supports STRING values as argument for the trim character.
Action	Use a STRING value as argument for the trim character.

WEPRME1545	**The {1} function only supports STRING values as argument for the trim source.**
Explanation	The {1} function only supports STRING values as argument for the trim source.
Action	Use a STRING value as argument for the trim source.

WEPRME1546	**The argument of the {0} function must be of type STRING or CHARACTER.**
Explanation	The argument of the LOWER and the UPPER function must be of type STRING or CHARACTER.
Action	Use a STRING or CHARACTER value as argument for the LOWER and the UPPER function.

WEPRME1547	**For the SUBSTRING function the substring source must be of type STRING and the start position and string length must be of type INTEGER.**
Explanation	For the SUBSTRING function the substring source must be of type STRING and the start position and string length must be of type INTEGER.
Action	Use a STRING value for the substring source and an INTEGER value for the start poistion and the string length.

WEPRME1548	**For the TRIM function the trim source must be of type STRING and the trim character must be of type STRING or CHARACTER.**
Explanation	For the TRIM function the trim source must be of type STRING and the trim character must be of type STRING or CHARACTER.
Action	Use a STRING value for the trim source and a STRING or CHARACTER value for the trim character.

WEPRME1549	**A {0} operation must have exactly three sub-expressions.**
Explanation	A {0} operation must have exactly three sub-expressions.
Action	Ensure that the {0} operation has exactly three sub-expressions.

WEPRME1550	**The LOWER and the UPPER function only support STRING and CHARACTER values.**
Explanation	The LOWER and the UPPER function only support STRING and CHARACTER values.
Action	Ensure that only STRING and CHARACTER values are used.

WEPRME1551	**The trim character for the TRIM function must have exactly one character.**
Explanation	The trim character for the TRIM function must have exactly one character.
Action	Use a single character as trim character for the TRIM function.

WEPRME1552	**The values for start position and start length of the SUBSTRING function are not valid.**
Explanation	The values for start position and start length of the SUBSTRING function are not valid.
Action	Use correct values for start position and start length of the SUBSTRING function.

WEPRME1555	**The return type of method {0} needs to be assignable to {1}. Found: {2}.**

WEPRME1556	**The first parameter of method {0} needs to be the same class or a super-class of {1}. Found: {2}.**

WEPRME1557	**Mmethod {0} is expected to have return type {1}. Found: {2}.**

WEPRME1558 **Method {0} is expected to have {1,choice,0#no parameters| 1#exactly one parameter| 1<exactly {1,number} parameters}.**

WEPRME1559 **The function cannot be registered.**

WEPRME1560 **The function factory cannot be registered.**

WEPRME1561 **The class of the user-defined function adapter factory must not be null.**

WEPRME1562 **The class of the user-defined aggregation function adapter factory must not be null.**

WEPRME1565 **Receiver version is to old to handle serialized user defined aggregation function adapter factory.**

WEPRME1567 **Failed to instantiate user defined window function for call "{0}". {1}**

WEPRME1568 **The signature {0} of the retrieved user defined window function for call "{1}" is invalid. {2}**

WEPRME1569 **Failed to instantiate user defined aggregation function for call "{0}". {1}**

WEPRME1570 **The signature {0} of the retrieved user defined aggregation function for call "{1}" is invalid. {2}**

WEPRME1571 **Failed to instantiate user defined function for call "{0}". {1}**

WEPRME1572 **The signature {0} of the retrieved user defined function for call "{1}" is invalid. {2}**

WEPRME1573 **Unknown window function type {0}.**

WEPRME1574 **Parameter number {0} of method {1} is expected to be serializable.**

WEPRME1575 **The mask "{0}" defining the temporal format is not valid.**
Explanation The mask "{0}" defining the temporal format is not valid.
Action Select a valid temporal format.

WEPRME1576 **Date conversion error for value "{0}".**
Explanation Date conversion error for value "{0}".
Action Enter a valid date.

WEPRME1577 **Unsupported date field "{0}".**
Explanation Unsupported date field "{0}".
Action Select a valid date field.

WEPRME1578 **Conversion to date failed for input string "{0}".**
Explanation Conversion to date failed for input string "{0}".
Action Enter a valid input string.

WEPRME1582 **RequiredUserDefinedAggregationFunctions may not be null.**

WEPRME1583 **The aggregation function adapter may not be null.**

WEPRME1584 **The function adapter may not be null.**

WEPRME1585 **The window function adapter may not be null.**

WEPRME1586 **The connected system does not support the registration of user-defined window functions.**

WEPRME1587 **The connected system does not support the de-registration of user-defined window functions.**

WEPRME1588 **The class of the user-defined window function adapter must not be null.**

WEPRME1589 **The server user-defined window function cannot be registered.**

WEPRME1590 **The class of the user-defined window function adapter factory must not be null.**

WEPRME1591 **The class of the user-defined aggregation function adapter factory must not be null.**

WEPRME1592 **The user-defined window function cannot be deregistered.**

WEPRME1593 **The user-defined window function cannot be registered.**

WEPRME1594 **The user-defined window function adapter factory must not be null.**

WEPRME1595 **The user {0} does not have the privilege to add the user-defined window function.**

WEPRME1596 **A user-defined window function factory is already registered for {0}.{1}.**

WEPRME1597 **No user-defined window function is registered for {0}.{1}.**

WEPRME1598 **The user-defined window function {0}.{1} cannot be deregistered as it is still in use.**

WEPRME1599 **A window function is not allowed in this context.**

WEPRME1600 **The signature of the user-defined window function {0} does not match the specified types ({1}).**

WEPRME1601 **The user-defined window function {0} is unknown or not visible.**

WEPRME1602	**DISTINCT mode is not allowed for user-defined aggregates.**
WEPRME1603	**The window function {0} is expected to have exactly {1} sub-expression(s).**
WEPRME1604	**Unknown window function type {0}.**
WEPRME1605	**Window functions are not supported in ACTIVE mode.**
WEPRME1606	**Unknown window function operator mode {0}.**
WEPRME1607	**Unexpected sub-expression type {0}. Aggregate or window function expected.**
WEPRME1608	**Invalid aggregation function adapter factory: Resolved a valid signature for the call ''{0}'', but failed to instantiate an adapter.**
WEPRME1609	**Invalid usage of aggregation function adapter factory. The signature for the call ''{0}'' had not been resolved before attempting to instantiate the adapter.**
WEPRME1610	**Invalid function adapter factory: Resolved a valid signature for the call ''{0}'', but failed to instantiate an adapter.**
WEPRME1611	**Invalid usage of function adapter factory. The signature for the call ''{0}'' had not been resolved before attempting to instantiate the adapter.**
WEPRME1612	**Invalid window function adapter factory: Resolved a valid signature for the call ''{0}'', but failed to instantiate an adapter.**
WEPRME1613	**Invalid usage of window function adapter factory. The signature for the call ''{0}'' had not been resolved before attempting to instantiate the adapter.**

WEPRME1614 **Only expressions can be used as child nodes of a window function expression.**

WEPRME1615 **Window function {0} is only applicaple over ordered windows.**

WEPRME1616 **Window function {0} is only applicaple over unbounded windows.**

WEPRME1617 **The user {0} does not have the privilege to remove the user-defined window function.**

WEPRME1618 **The signature's return type may not be null.**

WEPRME1619 **The signature's parameter types may not be null.**

WEPRME1620 **Only expressions are permitted in a PARTITION BY clause.**

WEPRME1621 **The {0,choice,0#parameter|1#instantiation parameter} types may not be null.**

WEPRME1622 **Expected at least {1} {0,choice,0#parameter|1# instantiation parameter} type(s), found {2}.**

WEPRME1623 **Expected at most {1} {0,choice,0#parameter|1# instantiation parameter} type(s), found {2}.**

WEPRME1624 **The {1}-th {0,choice,0#parameter|1#instantiation parameter} type is expected to be numeric, but is {2}.**

WEPRME1625 **{0,choice,0#Parameter|1#Instantiation parameter} types may not be null (found null at index {1}).**

WEPRME1626 **{0,choice,0#Parameter|1#Instantiation parameter} type {1} is expected to be compatible with type {2}. Found {3}.**

WEPRME1627 **The number of input parameter types differs. Expected {0}, but was {1}.**

WEPRME1628 **The {0}-th input parameter type may not be null.**

WEPRME1629 **The {0}-th parameter type is exepected to be assignable to type {1}. Was: {2}.**

WEPRME1630 **The Return type may not be null.**

WEPRME1631 **Incompatible return types. Expected {0}, but was {1}.**

WEPRME1632 **The number of instantiation parameter types differs. Expected {0}, but was {1}.**

WEPRME1633 **The {0}-th instantiation parameter may not be null.**

WEPRME1634 **The {0}-th instantiation parameter is exepected to be equal to or a sub-type of {1}. Was: {2}.**

WEPRME1635 **No {0,choice,0#parameter|1#instantiation parameter} types expected. Found {1}.**

WEPRME1636 **The given window function requires an ORDER BY clause in the window specification.**

WEPRME1637 **The given window function does not accept a bounded frame given in the window specification.**

WEPRME1638 **Unable to cast the given object to the specified type ''{0}''.**

WEPRME1639 **Unable to convert the given date ''{0}''.**

WEPRME1640 **Unable to convert the given date of class {0}.**

WEPRME1641 **Unable to read next record.**

WEPRME1642 **Unable to convert the next record.**

WEPRME1643 **Remove not supported.**

WEPRME1644 **Reset not supported.**

WEPRME1645 **Unable to initialize JSON parser on given reader.**

WEPRME1646 **The field {0} is neither a group column nor part of an exact match of a group expression or an aggregate call.**

Explanation Queries including grouping and/or aggregates are only able to use group columns/expressions and aggregate calls in the select list.

Action Either add the missing column to the group columns or remove the grouping/aggregation from the query.

WEPRME1647 **The combination of grouping and/or aggregation and (qualified) star expressions in the select list is not allowed.**

Explanation Since (qualified) star expressions are matching input/subquery columns and these columns are usually not preserved by grouping/aggregation the combination of both is not allowed.

Action Explicitely enumerate the columns in the select list that should be contained in the result.

WEPRME1648 **Unable to extract RecordMetaData. Reason: {0}.**

Explanation The schema (RecordMetaData) extraction for a BigMemory Data Source terminated with an error.

Action Investigate the 'Reason' specified in the message.

WEPRME1649	**Measure must be either euclidean, manhattan, cosine, tanimoto, or squaredeuclidean.**
WEPRME1650	**Only operators can be used as child nodes of an external subquery operator.**
WEPRME1651	**An external subquery operator must have exactly one input operator.**
WEPRME1652	**Invalid record found in cache {0} while fetching value of {1}.**
WEPRME1653	**Unknown outer join type "{0}".**
WEPRME1654	**Unknown semi join type "{0}".**
WEPRME1656	**I/O exception while reading XML input.**
WEPRME1657	**Record conversion exception while reading XML input.**
WEPRME1658	**An exception occured while processing XQuery: {0}**
WEPRME1659	**PN approach is not supported for geometric mean.**
WEPRME1660	**Unable to create an aggregation factory instance for input types {0}.**
WEPRME1661	**The parameter "k" needs to be an integer greater than 0.**
WEPRME1662	**The parameter "iterations" needs to be an integer greater than 0.**
WEPRME1663	**The parameter "measureId" needs to match one of: euclidean, manhattan, cosine, tanimoto or squaredeuclidean.**

WEPRME1664 **Unknown cross join type ''{0}''.**

WEPRME1665 **The source this scalar has to provide exactly one result.**

WEPRME1666 **The source of scalar has to provide at most one result.**

WEPRME1667 **No matching adapter found for signature {0}.**

WEPRME1668 **Ambiguous adapters: {0}**

WEPRME1669 **Unable to create instance.**

WEPRME1670 **The given list of adapters contains adapters with identical parameter types.**

WEPRME1671 **The given adapter classes must not be null.**

WEPRME1672 **The given adapter parameters must not be null.**

WEPRME1673 **The number of given adapter classes and parameter type lists does not match.**

WEPRME1674 **Unable to instantiate adapter {0}.**

WEPRME1675 **Wrong parameters - use at least class name and method name and if ambiguous add parameter class names.**

WEPRME1676 **The method {0} is not declared in class {1} with the given parameter types {3}.**

WEPRME1677 **Wrapping given operator of approach {0} to approach {1} is not supported.**

WEPRME1678 **Violation of push-scalar operator rules.**

WEPRME1679 **Left status structure has to support temporal queries.**

WEPRME1680 **Right status structure has to support temporal queries.**

WEPRME1681 **Unknown authentication type ''{0}''.**

WEPRME1682 **Requesting required complete-from is not supported by this intra source adapter.**

WEPRME1683 **Property {0} is unknown! Please check the property name.**

WEPRME1684 **Value {1} is not in defined domain ({2}) of property {0}! Please check the property value.**

WEPRME1685 **Value {1} of property {0} is not in the defined range! Please check the property value.**

WEPRME1686 **The mandatory property {0} is not provided (level {1})!**

WEPRME1688 **The given system propeties must not be null.**

WEPRME1689 **The class of the pull source cannot be found.**

WEPRME1690 **The IS comparison is only allowed with a NULL constant as second argument.**

WEPRME1691 **Only established connections can be marked as broken.**

WEPRME1692 **Only established connections can be marked as shutting down.**

WEPRME1693 **Unable to connect to cluster within {0} seconds.**

WEPRME1696 **An exception occurred while recovering connection to {0}.**

WEPRME1702 **The pull result is already closed.**

WEPRME1703 **The pull result has run out of data.**

WEPRME1704 **This handler is not handling any synchronous command.**

WEPRME1705 **This handler is not handling any asynchronous command.**

WEPRME1706 **The server user-defined aggregation function factory cannot be registered.**

WEPRME1707 **The pull source adapter must not be null.**

WEPRME1708 **The pull source cannot be prepared.**

WEPRME1709 **The parameters for the server pull source must not be null.**

WEPRME1710 **The class for the server pull source must not be null.**

WEPRME1711 **The server function factory cannot be registered.**

WEPRME1712 **The server user-defined window function factory cannot be registered.**

WEPRME1713 **The server pull source cannot be prepared.**

WEPRME1714 **The query parameters must not be null.**

WEPRME1715 **The query cannot be removed.**

WEPRME1716 **The query cannot be executed.**

WEPRME1717 **The batch job cannot be started because the connection has already been shut down by the server.**

WEPRME1718 **The data source cannot be registered.**

WEPRME1719 **The table cannot be registered.**

WEPRME1720 **The parameters for the pull source must not be null.**

WEPRME1721 **The pull source must not be null.**

WEPRME1722 **The pull source cannot be prepared.**

WEPRME1723 **Not supported in HA mode.**

WEPRME1725 **Unable to add a node that is not the root of a logical query graph.**

WEPRME1726 **Unable to remove a node that is not the root of a logical query graph.**

WEPRME1727 **Only operators can be used as child nodes of a scalar operator.**

WEPRME1728 **A scalar operator must have exactly one input operator.**

WEPRME1729 **A scalar operator must not have more than one input operator.**

WEPRME1730 **Scalar is not supported for BA approach.**

WEPRME1731 **Incompatible approach.**

WEPRME1735 **Server shutting down.**

WEPRME1736 **Unexpected type: Tried to receive {0} but got {1}.**

WEPRME1737 **There is no server running with id {0}, {1}.**

WEPRME1738 **There is already a server running with id {0}, {1}.**

WEPRME1739 **Invalid ID {0} (must be numeric).**

WEPRME1740 **IndexedStorage should be initialized with an empty cache.**

WEPRME1741 **Unable to create temporary file for buffering the content of the reader.**

WEPRME1742 **Unable to read from temporary file.**

WEPRME1743 **Error during execution of Pull Query {0}.**

Explanation A severe runtime error has occured.

Action Analyze detailed log information and the cause of the exception.

WEPRME1744 **Window specification using ROWS requires frame bounds to be of type LONG.**

WEPRME1745 **Window specification using RANGE requires the order-by column to be of numeric type. Found: {0}.**

WEPRME1746 **Window specification using RANGE requires at least one numeric order-by expression.**

WEPRME1747 **Window specification using RANGE and custom frame bounds requires exactly one numeric order-by expression.**

WEPRME1748 **Unable to prefetch data.**

WEPRME1749 **An error occured during subscription handling.**

WEPRME1750 **Partition/Window entries are not comparable as the OVER clause did not contain an order-by expression.**

WEPRME1751 **Only expressions can be used as child nodes of window function {0}.**

WEPRME1752 **The user-defined function {0} cannot be used as a window function.**

Explanation Only (user-defined) window functions and (user-defined) aggregate functions can be used as window functions. But the specified function is an user-defined function.

Action Either replace the user-defined function by a (user-defined) window function or by an (user-defined) aggregate function or remove the window specification.

WEPRME1753 **The source {0} is ambiguous. Check if sources are properly renamed and no duplicate aliases are introduced.**

WEPRME1754 **The given window function does not allow the specification of a window frame.**

WEPRME1755 **The subquery used in WHERE clause produced a non-scalar result.**

Explanation When neither ALL or ANY is specified only scalar subqueries can be used with a relational operator in a WHERE clause.

Action Change the subquery such that it produces a scalar result.

WEPRME1756 **Unsupported XML entity: {0}**

WEPRME1757 **Unable to handle the JSON token ''{0}''.**

WEPRME1758 **Unable to parse the given JSON input: {0}**

WEPRME1759 **Unable to read the given JSON input.**

WEPRME1760 **Error converting value ''{0}'' of column ''{1}'' to type {2} due to the following issue: {3}**

WEPRME1761 **The JSON input contains an unmatched END-ARRAY token.**

Explanation The underlying JSON parser produced an END-ARRAY token without an according START-ARRAY token.

Action Check the processed JSON input.

WEPRME1762 **The JSON input contains an unexpected {0} token.**

Explanation The JSON parser produced an unexpected token.

Action Check the processed JSON input.

WEPRME1763 **The JSON input contains an unmatched START-OBJECT token.**

Explanation The JSON parser produced a START-OBJECT token without an according END-Object token.

Action Check the processed JSON input.

WEPRME1764 **Unable to read JSON input.**

Explanation An I/O exception occurred while reading the JSON input.

Action Check the processed JSON input.

WEPRME1765 **The connection locale may not be null.**

WEPRME1766 **Unable to open the specified file {0}.**

WEPRME1767 **Unable to reset buffered reader.**

WEPRME1769 **The following error has been reported {0} times and any recurrences will be suppressed: {1}**

WEPRME1770 **Unable to compute stream metadata for user-defined source factory.**

WEPRME1771 **Exception occurred while inferring schema.**

WEPRME1772 **Super column value is incompatible with defined type. Configured "{0}" but actually was "{1}".**

WEPRME1773 **Super column metadata differs among source factories for the same pull source. Expected "{0}", but was "{1}".**

WEPRME1774 **SearchAttribute name at index {0} must not be null.**

WEPRME1775 **The given search attribute {0} cannot be found.**

WEPRME1776 **Dynamic indexing is not supported for search attribute {0} as it is of type {1}.**

WEPRME1778 **Return type of UDX {0} does not comply with the schema: expected {1} but found {2}.**

WEPRME1779 **Null not allowed as return value of UDX {0}.**

WEPRME1780 **Method getComputedNext() may only be used after next().**

WEPRME1781 **Could not find a source node in external subquery graph.**

WEPRME1782 **Error closing communication: {0}.**

WEPRME1784 **Failed to create directory {0}.**

WEPRME1786 **Repository contains an artefact of unexpected type {0} with owner {1} and identifier {2} that is using a pull query.**

WEPRME1787 **Unable to parse the given XML document: {0}.**

Explanation An error occurred while parsing the given XML document.

Action Check the underlying exception's message

WEPRME1788 **The query language {0} is not supported.**

Explanation The specified query language parameter is not supported by this method.

Action Change the query language parameter to one of the supported query languages, e.g., SQL or XML.

WEPRME1789 **The constructor of RemotePullSourceFactory requires two to four parameters ([host [port]] user password).**

Explanation The constructor was called with the wrong number of String arguments.

Action Call the constructor with the parameters (host, port, user, password) or (host, user, password) or (user, password).

WEPRME1790 **Unable to prepare the XML representation of the external subquery for the remote RTM system.**

Explanation An error occurred when preparing the external subquery that should be executed by the remote RTM system.

WEPRME1791 **The external subquery does not have any registered source.**

WEPRME1792 **The external subquery does have more than one registered source.**

WEPRME1793 **Grouping set(s) not supported in this context.**

Explanation A query contained a group by clause that specifies any of GROUPING SETS, ROLLUP, or CUBE, or an empty grouping set. This is not supported with either a SetCondition, nor with push processing mode.

Action Modify query in order to obey the restriction on grouping sets.

WEPRME1794 **Grouping operation argument must be a group expression.**

Explanation The query contains a grouping operation with an invalid argument. The arguments of a grouping operation must be grouping expressions.

Action Modify query to contain only group expressions as arguments of a grouping operation.

WEPRME1795 **Grouping-set bit index may not be larger than number of group expressions. Was {0} > {1}.**

WEPRME1796 **Grouping-set multiplicity may not be less than 1. Was {0}.**

WEPRME1797 **Grouping-sets do not cover all group expressions. Uncovered indices: {0}.**

WEPRME1798 **The GROUPING function currently supports only up to 64 arguments. Found {0}.**

WEPRME1799 **Parallel computation of GROUPING-SETS operator was interrupted.**

WEPRME1800 **Exactly one parameter expected.**

WEPRME1801 **Parameter type not supported by wrapped Aggregator.**

WEPRME1802 **The given node does not provide a field name.**

WEPRME1803 **The group expression does not provide a field name.**

WEPRME1804 **Unsupported aggregation type {0}.**

WEPRME1805 **The aggregates attribute does not provide a field name.**

WEPRME1806 **Predicate is neither a logical operation, comparison nor boolean expression.**

WEPRME1807 **Neither attribute of the comparison is a field.**

WEPRME1808 **The sort specification does not provide a field name.**

WEPRME1809 **Mapping has a Field with childIndex > 0**

WEPRME1810 **The given attribute {0} is not contained in search attributes.**

WEPRME1811 **The given node is no constant.**

WEPRME1812 **Unable to extract record metadata.**

WEPRME1813 **Number of clusters (k) has to be greater than 0.**

WEPRME1814 **Number of iterations needs to be greater than 0.**

WEPRME1815 **Unknown measure {0}. Valid measures are: {1}.**

WEPRME1816 **Invalid or missing delimiter.**

WEPRME1817 **Invalid or missing field index.**

WEPRME1818 **Getting an adapter factory for {0} was not successful.**

WEPRME1819 **Unknown raql window function type: {0}**

WEPRME1820 **SupportsReset is only allowed after init.**

WEPRME1821 **SupportsPeek is only allowed after init.**

WEPRME1822 **SupportsRemove is only allowed after init.**

WEPRME1823 **The SinglePullSourcePullSourceFactory only supports parameterless usage.**

WEPRME1824 **Left bounds other than UNBOUNDED PRECEDING or CURRENT ROW are not supported in this context.**

WEPRME1825 **Right bounds other than UNBOUNDED FOLLOWING or CURRENT ROW are not supported in this context.**

WEPRME1826 **Illegal frame bounds: {0} > {1}.**

WEPRME1827 **Operation type is unknown or can not be processed.**

WEPRME1828 **At least three items have to be allowed.**

WEPRME1829 **Legend must not be null!**

WEPRME1830 **Number of legends must be equal to number of chart types!**

WEPRME1831 **Start and/or end does not fit actual day.**

WEPRME1832 **Unsupported message type: {0}.**

WEPRME1833 **Unsupported callback type.**

WEPRME1834 **Login only allowed for initialized login module.**

WEPRME1835 **Commit only allowed for login module after successful login.**

WEPRME1836 **Could not create login context.**

WEPRME1837 **Unknown Callback.**

WEPRME1838 **The GROUPING-SET operator's search lattice is expected to have only one single entry with key 'null' on its root level.**

WEPRME1839 **Master and slave produce different results.**

WEPRME1840 **The buffer must not be smaller than 1: {0}**

WEPRME1841 **The pre-fetching number must not be smaller than 1: {0}.**

WEPRME1842 **The pre-computing number must not be smaller than 1: {0}.**

WEPRME1843 **The result block size number must not be smaller than 1: {0}.**

WEPRME1844 **The pull result adapter must not be null.**

WEPRME1845 **The pull query could not be executed.**

WEPRME1846 **A subscription to a pull query was not possible.**

WEPRME1847 **The pull result adapter class must not be null.**

WEPRME1848 **Could not unsubscribe from pull query.**

WEPRME1849 **Unable to subscribe to pull query.**

WEPRME1850 **Subscriptions to pull queries are currently not supported in HA mode.**

WEPRME1851 **Users may only remove subscriptions from their own schema.**

WEPRME1852 **The pull result could not be closed.**

WEPRME1853 **Cannot change to existing remote connection id {0}.**

WEPRME1854 **Remote connection id does not match the Id defined by the current master.**

WEPRME1855 **The class could not be found.**

WEPRME1856 **ServerConnectionHandler may not be null.**

WEPRME1857 **Detected second master: {0} <-> {1}**

WEPRME1858 **The result adapter was already closed.**

WEPRME1859 **No adapter found for handling.**

WEPRME1860 **Error in handling remote subscription.**

WEPRME1861 **Class {0} does not provide a default constructor, which is obligatory.**

WEPRME1862 **A subscription with this name exists already.**

WEPRME1863 **Cannot make a persistent subscription to a non-persistent query.**

WEPRME1864 **Cannot unsubscribe from a subscription, which does not exist.**

WEPRME1865 **The provided subscription parameter should not be null.**

WEPRME1866 **The execution time must not be null.**

WEPRME1867 **A non-server subscription cannot be made persistent.**

WEPRME1868 **Logical Constant is not a boolean.**

WEPRME1869 **Child does not have REFERENCED_FIELDS metadata.**

WEPRME1870 **Not implemented.**

WEPRME1871 **Unknown Predicate Type.**

WEPRME1872 **Could not find source of expression: {0}.**

WEPRME1873 **Mapping has a Field with childIndex > 0.**

WEPRME1874 **Parent grouping-set has not been set yet.**

WEPRME1875 **Rule broken: inverse map does not contain the source of a referenced field.**

WEPRME1876 **Mappings are not supposed to have ANCHOR->CHILD_INDEX != 0.**

WEPRME1877 **Query Graph broken: Found a Field with child != 0 at Order Node: ({0}, {1}).**

WEPRME1878 **Field does not contain field index.**

WEPRME1879 **Found EQUI-Join with 0 equi-fields.**

WEPRME1880 **Cannot handle multiway NATURAL JOIN.**

WEPRME1881 **Columns named by {0} cannot be unified because of different types.**

WEPRME1882 **Found NATURAL-Join with 0 join-candidates.**

WEPRME1883 **Optimizer cannot handle IN(subquery), yet.**

WEPRME1884 **Unknown Node type encountered: {0}.**

WEPRME1885 **Argument is not a predicate.**

WEPRME1886 **Found NOT with {0} child nodes.**

WEPRME1887 **Found NOT with a child that's no predicate (is {0}).**

WEPRME1888 **getAnd() called with less than 1 node.**

WEPRME1889 **Argument is not an expression.**

WEPRME1890 **Non-String Signature Key found: {0}.**

WEPRME1891 **Unknown Node-Type: {0}.**

WEPRME1892 **Unhandled enum entry: {0}.**

WEPRME1893 **Aggregate is configured to have{0} arguments, but has actually {1} arguments.**

WEPRME1894 **WindowFunction is configured to have {0} arguments, but has actually {1} arguments.**

WEPRME1895 **Aggregate is configured to have {0} arguments, but has actually {1} arguments.**

WEPRME1896 **UNEXPECTED.**

WEPRME1897 **Function {0} only supports Double and Float values.**

WEPRME1898 **Function {0} only supports numeric values.**

WEPRME1899 **Offset must not be negative.**

WEPRME1900 **Unknown frame unit: {0}.**

WEPRME1901	**Function {0} must have exactly one sub-expression.**
WEPRME1902	**Function {0} must not have more than one sub-expression.**
WEPRME1903	**Unsupported method.**
WEPRME1904	**Communication is already closed.**
WEPRME1905	**Unhandled communication type: {0}.**
WEPRME1906	**EhcacheBasedLinkedList should be initialized with an empty cache.**
WEPRME1907	**Index: {0}, Size: {1}.**
WEPRME1908	**Not feasible to copy the whole OffHeap list into the Java heap.**
WEPRME1909	**fromIndex = {0}**
WEPRME1910	**toIndex = {0}**
WEPRME1911	**fromIndex({0}) > toIndex({1})**
WEPRME1912	**next() has been called at all or after remove() has been called.**
WEPRME1913	**nextPos() has been called, or remove() has been called after the last call to nextPos().**
WEPRME1914	**At least one feature toggle did not satisfy the given assertions. {0}**

WEPRME1915 **AttributeName unknown: {0}.**

WEPRME1916 **No standard filter: {0}.**

WEPRME1917 **Unknown type: {0}.**

WEPRME1918 **Failed to activate metadata handler for metadata identifier {0}.**

WEPRME1919 **The DynamicMetaDataManager is not registered.**

WEPRME1920 **This XmlPullSourceFactory accepts at most 2 instantiation parameters. Got {0}.**

WEPRME1921 **The number of instantiation parameters does not match the number of instantiation parameter types ({0} <> {1}).**

WEPRME1922 **Expected STRING instantiation parameter type at index {0}, found {1}.**

WEPRME1923 **Unhandled sink adapter type/approach: {0}.**

WEPRME1924 **Parent grouping-set has already been set and cannot be overriden.**

WEPRME1925 **Graph node is already defined: {0}.**

WEPRME1926 **Unknown graph node: {0}.**

WEPRME1927 **BigMemory does not support consecutive aggregations and applying criterias after aggregating.**

WEPRME1928 **BigMemory does not support limiting the number of elements that are aggregated, ordered and applied criterias to.**

WEPRME1929 **This aggregation function does not support merging multiple aggregation states into one.**

WEPRME1931 **The value {0} cannot be rounded to a {1} value since it is greater than the maximum or less than the minimum {1} value.**

WEPRME1932 **Argument is not a field.**

WEPRME1933 **The parameter n must be greater than 0.**

WEPRME1934 **Target array is to short. Required array size is: {0}.**

WEPRME1935 **Chunksize must be greater than 0.**

WEPRME1936 **The parameter "times" must be greater than 0.**

WEPRME1937 **Unable to close JSON parser.**

WEPRME1938 **Namespace with index {0} does not exist.**

WEPRME1941 **Result of operation was not a number.**

WEPRME1942 **Result of operation was infinite.**

WEPRME1943 **An overflow occured in aggregation {0} of type {1}.**

WEPRME1944 **An overflow occured in function {0} of type {1}.**

WEPRME1947 **DISTINCT aggregates cannot be pushed-down: {0}.**

WEPRME1948 **Aggregates on constant values cannot be pushed-down: {0}.**

WEPRME1949 **Expressions on constant values cannot be pushed-down: {0}.**

WEPRME1950 **Comparisons on two variables cannot be pushed-down: {0}.**

WEPRME1951 **Comparisons of type {0} cannot be pushed-down.**

WEPRME1952 **Cannot cast from {0} to {1}: {2}.**

WEPRME1953 **The expression of type {0} cannot be pushed down: {1}.**

WEPRME1954 **Unexpected data type {0} for expression {1}.**

WEPRME1955 **Illegal constant expression '*'.**

WEPRME1956 **The aggregate of type {0} cannot be pushed-down: {1}.**

WEPRME1957 **Unknown cell definition: {0} (type {1}).**

WEPRME1958 **Operation {0} on two cells cannot be pushed-down.**

WEPRME1959 **DIVISION with constant dividend is not supported in TC Store.**

WEPRME1960 **Integer DIVISION cannot be pushed-down.**

WEPRME1961 **Error parsing string {0} to XML document: {1}**

WEPRME1962 **Order expression cannot be pushed down to TC Store, as it may yield null values, which cannot be sorted properly.**

WEPRME1963 **AGGREGATION with HAVING predicate cannot be pushed down.**

WEPRME1964 **GROUP BY on constant expression cannot be pushed-down.**

WEPRME1965 **GROUP BY on complex {0} expression cannot be pushed down.**

WEPRME1966 **No aggregates to push-down.**

WEPRME1967 **OPERATOR of type {0} cannot be pushed-down.**

WEPRME1968 **ORDER BY on a constant expression cannot be pushed down.**

WEPRME1969 **The data type {0} is not supported: {1}.**

WEPRME1970 **The IN predicate's list may only contain constant expressions.**

WEPRME1971 **The IN predicate's 'member' expression may not be constant: {0}.**

WEPRME1972 **Operator {0} may not operate on a derived/non-record stream.**

WEPRME1973 **Unsupported predicate type {0}.**

WEPRME1974 **Wrong parameter type {0}. Expected STRING.**

WEPRME1975 **Unsupported type in ORDER BY clause: {0}.**

WEPRME1976 **CellDefinition is expected to have type {0}. Found {1}.**

WEPRME1977 **Complex GROUPING SETS cannot be pushed down.**

WEPRME1978 **GROUPING expressions cannot be pushed down.**

WEPRME1979 **Unexpected number of child nodes. Expected {0}, but was {1}.**

WEPRME1980 **The MAPPING is not a plain projection and cannot be pushed down.**

WEPRME1981 **The projection mapping is a parent of non-schema preserving operator and cannot be pushed down.**

WEPRME1982 **The projection mapping is a child of a DISTINCT operator and cannot be pushed down.**

WEPRME1983 **Missing XML element: {0}.**

WEPRME1984 **The TCStore type {0} cannot be mapped to a corresponding RTM type.**

WEPRME1985 **RTM type {0} cannot be mapped to corresponding TC Store type.**

WEPRME1986 **Wrong parameter ''{0}''. Expected {1}.**

WEPRME1987 **Wrong number of instantiation parameters: Expected 0 or 1, but was {0}.**

WEPRME1988 **CellCollection has no value for field {0}, but field must not be nullable.**

WEPRME1989 **Conversion of RTM record to TC record failed, as value for not-nullable field {0} is NULL.**

WEPRME1990	**RTM type {0} is not supported when converting RTM record to TC record using match mode {1}.**
WEPRME1992	**Column name "{0}" is not unique within the given schema and needs to be renamed.**
WEPRME1993	**Case insensitive String or Character comparisons are not supported by TC Store.**
WEPRME1994	**Cannot group on case insensitive STRING/CHARACTER in TC Store.**
WEPRME1995	**The user-defined data type {0} is not supported for serialization to a DES event.**
WEPRME1996	**The data type {0} is not supported for perfect serialization to a DES event.**
WEPRME1997	**The DES data type {0} is not supported for perfect serialization to a record.**
WEPRME1998	**The record's key cannot be referenced in arbitrary expressions.**
WEPRME1999	**The field to translate is not a key field: {0}.**
WEPRME2000	**Key column "{0}" could not found in schema.**
WEPRME2001	**Key column name "{0}" is not unique within the given schema.**
WEPRME2002	**The {0} data type cannot be compared or sorted.**
WEPRME2003	**The key alias {0} is not unique.**
WEPRME2004	**The following cell definitions lead to ambiguous columns: {0}**

WEPRME2005 **Key field {0} is ambiguous in the schema {1}.**

WEPRME2006 **The key field {0} could not be found in the schema {1}.**

WEPRME2007 **Unexpected duplicate fieldName {0}.**

WEPRME2008 **There are no search attributes defined for cache {0}.**

WEPRME2009 **Cannot sort on case insensitive STRING/CHARACTER in TC Store.**

WEPRME2010 **Cannot determine MIN or MAX on case insensitive STRING/CHARACTER in TC Store.**

WEPRME2011 **The provided server source factory parameters must not be null.**

Explanation The input parameter server source factory parameters is null. A valid server source factory parameters object must be provided.

WEPRME2012 **The classpath entries of the provided server source factory parameter must not be null.**

Explanation The input parameter classpath entries is null. A valid array, either containing classpath entries or empty, must be provided.

WEPRME2013 **The classloading strategy of the provided server source factory parameter must not be null.**

Explanation The input classloading strategy is null. A valid classloading strategy object must be provided.

WEPRME2014 **User can not be added.**

WEPRME2015 **User can not be removed.**

WEPRME2016 **Insufficient permissions to add user account.**

WEPRME2017 **Insufficient permissions to remove user account.**

WEPRME2018 **User must not be null.**

WEPRME2019 **User {0} does not exist.**

WEPRME2020 **User {0} already exists.**

WEPRME2021 **Password does not stand the predicate-test.**

WEPRME2022 **System Authentication doesn't support User Management.**

WEPRMI0001 **Initializing RTM system.**

WEPRMI0002 **Configuring persistent RTM system.**

WEPRMI0003 **Initialization of RTM system finished.**

WEPRMI0004 **Starting RTM system.**

WEPRMI0005 **Start of RTM system finished.**

WEPRMI0006 **Shutting down RTM system.**

WEPRMI0007 **Shutdown of RTM system is finished.**

WEPRMI0008 **User {0} trying to locally connect to RTM system.**

WEPRMI0009 **User {0} connected to RTM system.**

WEPRMI0010 **Current HA role is {0}.**

WEPRMI0013 **HA role has been set to {0}.**

WEPRMI0015 **Slave is preparing recovery.**

WEPRMI0016 **Slave requesting recovery from master.**

WEPRMI0017 **Master has started sending recovery data to slave.**

WEPRMI0018 **Master finished sending recovery data to slave.**

WEPRMI0019 **Slave has started processing recovery request from master.**

WEPRMI0020 **Slave successfully finished processing recovery request from master.**

WEPRMI0021 **Server with newer build number {0} connected as slave.**

WEPRMI0025 **Aborted handshake due to shutdown.**

WEPRMI0026 **Handshake with remote RTM system successfully finished.**

WEPRMI0027 **Snapshot reducibility has been determined for the following query; Owner:{0}; Identifier:{1}; SQL:{2}; Snapshot reducible from:{3};**

WEPRMI0028	**Could not connect to a running high-availability peer, now attempting to acquire master lock.**
WEPRMI1376	**Properties of RTM system: {0}**
WEPRMI1377	**Properties of JPA : {0}**
WEPRMI1412	**Remote connection server is shutting down.**
WEPRMI1413	**Client starts close procedure.**
WEPRMI1414	**Client finishes close procedure.**
WEPRMI1415	**Client marks connection as broken for address {0}.**
WEPRMI1416	**Client shuts down broken connection to address {0}.**
WEPRMI1417	**Local connection is closed due to {0}.**
WEPRMI1419	**Closing HA result transmission query {0}.**
WEPRMI1420	**Shutting down remote connection handler with remote connection id {0}.**
WEPRMI1426	**Starting to accept new connections on address {0}.**
WEPRMI1430	**Stopped accepting new connections on address {0}.**
WEPRMI1446	**Re-authentication at remote RTM system finished successfully.**

WEPRMI1697 **Client marks connection as shutting down: {0}**

WEPRMI1698 **Client shuts down connection: {0}, isClosing={1}.**

WEPRMI1699 **Client starts recovering connection to {0}.**

WEPRMI1700 **Client is successfully connected to {0}.**

WEPRMI1701 **Ignored NPE when sending {0} to {1}.**

WEPRMI1724 **{0} (connectable source {1})**

WEPRMI1733 **Nested exceptions:**

WEPRMI1734 **Combined exceptions**

WEPRMI1785 **Starting RTM system (version={0} built at {1}).**

WEPRMI1945 **TCP/IP communication server is listening on local port {0}.**

WEPRMW0001 **Unable to shut down RTM system's persistence manager.**

WEPRMW0002 **Unable to shut down communication servers.**

WEPRMW0003 **Unable to stop communication server.**

WEPRMW0004 **Unable to stop communication client.**

WEPRMW0005 **Unable to shut down client connection handler.**

WEPRMW0006 **Unable to shut down server connection handler.**

WEPRMW0007 **Unable to connect to high availability partner.**

WEPRMW0008 **Unable to shut down master connection handler.**

WEPRMW0009 **Unable to send for slave health request.**

WEPRMW0010 **Server with older build number {0} connected as slave.**

WEPRMW0011 **Unable to shut down slave connection handler.**

WEPRMW0012 **Unable to send for master health request.**

WEPRMW0017 **Unable to call a task on the decoupled sink adapter.**

WEPRMW0018 **Authentication with remote RTM system contains illegal commands.**

WEPRMW1329 **Caught exception during operator initialization.**

WEPRMW1330 **Caught exception during heartbeat processing from input {0}.**

WEPRMW1331 **Caught exception while closing operator.**

WEPRMW1332 **Caught exception processing done signal from input {0}.**

WEPRMW1333 **Error processing element of index {0}.**

WEPRMW1334 **Caught exception while opening operator.**

WEPRMW1410 **Status of local system is not OK; shutting down!**

WEPRMW1411 **Status of cluster is not OK; shutting down!**

WEPRMW1421 **Received a shutdown notification from HA {0} with HA communication address {1}.**

WEPRMW1422 **Server ({0}) lost connection to HA partner system.**

WEPRMW1423 **Server is shutting down broken connection for address {0} as communication to master has been lost.**

Explanation This message appears in the log of an HA slave when it loses its connection to a master that supports remote connections. It indicates why clients will lose their connection to that address.

Action Check other messages to see if the reason for the lost connection can be found.

WEPRMW1522 **Aborting authentication with remote RTM system.**

WEPRMW1687 **Rule-based optimization failed due to: {0}**

Explanation The optimizer has failed optimizing the query and falled back to a non-optimized query.

WEPRMW1694 **Master identifies himself with different address. Is {0}, not {1}.**

WEPRMW1695 **Still connected to old slave.**

WEPRMW1768	**External Subquery Translation failed. Reason was: {0}**
Explanation	The user query was optimized but the external subquery translation has failed to translate the logical query graph. This could under the circumstances result in a slower query performance.
Action	Try to rewrite the query or contact your local software supplier.
WEPRMW1777	**Search attribute {0} has been skipped as dynamic indexing is not supported for type {1}.**
WEPRMW1783	**Buffer file ''{0}''could not be deleted: {1}.**
WEPRMW1939	**Unable to expand the explicit sub-query {0} for non-incremental query optimization.**
WEPRMW1940	**BigMemory was not able to execute the Search API query against a cache.**
WEPRMW1946	**Exact average value {0} is not accuratly representable as a double. The BigDecimal representation is {1}.**
WEPRMW1991	**{0} push-down failed as there already is an Aggregation being pushed-down.**

25 Security Messages

SINAZE0000	**FileBasedAuthzStoreImpl: Storage cannot be loaded: {0}**
Explanation	Role storage (roles.txt) can not be loaded.
Action	Check the existance of the roles.txt file or the relevant storage.

SINAZE0001	**FileBasedAuthzStoreImpl: Storage location {0} is missing.**
Explanation	Role storage (roles.txt) is missing.
Action	The location passed to the service does not point to the existing file/storage. Check the availablity to the file.

SINAZE0002	**Cannot open storage file {0}**
Explanation	Role storage (roles.txt) cannot be opened.
Action	Check if the storage (file) is available and accessible.

SINAZE0003	**{0} is not readable!**
Explanation	Role storage (roles.txt) cannot be read.
Action	Check if the storage (file) has proper access rights, and whether it is not locked.

SINAZE0004	**Invalid entry in storage file. Invalid line in the storage file.**
Explanation	Role storage (roles.txt) syntax is not correct. Invalide entry is found.
Action	Check the storage (file) and validate the syntax.

SINAZE0005	**cannot open {0}**
Explanation	Role storage (roles.txt) cannot be opened/accessed.
Action	Check the storage (file).

SINAZE0006	**Cannot write to storage file {0}. File does not exist.**
Explanation	Cannot write to storage file. File does not exist.
Action	Chech the availability of the storage/file.

SINAZE0007	**{0} is not writable!**
Explanation	Role storage (roles.txt) is not editable.
Action	Check access rights for the storage file.

SINESE0000	**/{0} not found.**
Explanation	Internal error. A file used by the product is missing.
Action	Contact SoftwareAG global support.

SINESE0001	**Error loading /{0}**
Explanation	Internal error. A file used by the product cannot be processed.
Action	Contact SoftwareAG global support.

SINESE0002	**/{0} not found.**
Explanation	Internal error. A validation properties file used by the product is missing.
Action	Contact SoftwareAG global support.

SINESE0003	**Error loading /{0}**
Explanation	Internal error. A validation properties file used by the product cannot be processed.
Action	Contact SoftwareAG global support.

SINESE0004	**Unknown System Type!**
Explanation	System type cannot be recognized.
Action	Contact SoftwareAG global support.

SINESE0005	**System property {0} is set, but file '{1}' doesn't exist**
Explanation	System property com.softwareag.sin.esapi.resources has a value that points to an invalid file or a file that doesn't have proper rights.
Action	Check the value of the system property com.softwareag.sin.esapi.resources and update it to point to a valid readable ESAPI.properties file.

SINJCE0003	**Initialize: JAAS property not set: {0}**
Explanation	The login module requires a 'DUMMY_USER_PROPERTY_URL' option representing a URL to the user properties file to load, but such option is not configured.
Action	Configure a 'DUMMY_USER_PROPERTY_URL' option for the DummyLoginModule. The option value must be a URL to a standard Java properties file containing users, groups and roles information.

SINLDE0048	**Authentication failed**
Explanation	LDAPLoginModule - authentication against LDAP failed. User name or password are wrong.
Action	Re-enter the user name and password. Check if their values are correct.

SINLDE0056	**No configured servers.**
Explanation	No configured servers were found.
Action	Ensure that the servers are configured properly.

SINLDE0057	**No configured servers.**
Explanation	No configured servers were found.
Action	Ensure that the servers are configured properly.

SINLDE0058	**No configured servers.**
Explanation	No configured servers were found.
Action	Ensure that the servers are configured properly.

SINLDE0059	**No configured servers.**
Explanation	No configured servers were found.
Action	Ensure that the servers are configured properly.

SINLDE0060	**LDAP keystore load error**
Explanation	An error occurred during extraction of a keystore. Possible causes are invalid URL, invalid algorithm, invalid certificate, invalid argument, etc.
Action	Ensure that the requested keystore and its URL are valid.

SINLDE0061	**LDAP truststore load error.**
Explanation	An error occurred during extraction of a truststore. Possible causes are invalid URL, invalid algorithm, invalid certificate, invalid argument, etc.
Action	Ensure that the requested truststore and its URL are valid.

SINLDE0062	**This principal {0} is with wrong type. Should be {1}**
Explanation	An error occurred while checking principal type. The principal type must be GROUP_TYPE.
Action	Change the principal type to GROUP_TYPE.

SINLDE0085	**keystore is null**
Explanation	There was an error opening keystore.
Action	Please check keystore/trustore properties

SINLDE0086	**keyAlias is null**
Explanation	You added keystore url, but you did not provide keyAlias to use.
Action	Please check keystore properties

SINLDE0087	**keyPass is null**
Explanation	You provided keystore url, but you did not provide keystorePassword and keyPassword.
Action	Please check keystore properties

SINLDW0063	**More than one result returned uidprop: {0} uid: {1}**
Explanation	A single result is expected when getting DN from UID.
Action	Ensure that the UID contains a single DN corresponding to the search filter.

SINLDW0064	**More than one result returned gidprop: {0} gid: {1}**
Explanation	A single result is expected when getting DN from GID.
Action	Ensure that the GID contains a single DN corresponding to the search filter.

SINLDW0066	**Problem listing group properties.**
Explanation	An issue has occurred while listing group properties.
Action	Ensure that the group properties are valid.

SINLDW0067	**Empty [DN Prefix/Sufix]**
Explanation	Empty DN Prefix and DN Sufix were found when listing users during an LDAP configuration.
Action	Ensure that the DN Prefix and/or DN Sufix are present.

SINLDW0070	**Problem checking if DN is a group.**
Explanation	There was an issue while checking if the DN is a group when trying to get the group ID.
Action	Ensure that the DN is a group.

SINLDW0071	**Problem checking if dn is a user**
Explanation	There was an issue while checking if the DN is a user when trying to get the user ID
Action	Ensure that the DN is a user.

SINLDW0081	**Property {0} is unknown, but is found in server configuraion. Please check spelling of the properties.**
Explanation	A wrong property was found in the server configuration. Properties are case sensitive.
Action	Check the spelling and capitalization of the properties in the server configuration.

SINLME0012	**Initialize: failed to create X509CRL from the CRL URL: {0} {1}**
Explanation	CRLException was thrown during the initialization of the CRL. Possible reasons: the CRL file is broken or it is not in CRL format - http://docs.oracle.com/javase/7/docs/api/java/security/cert/X509CRL.html.
Action	Double check in the JAAS configuration the value of the "crl_url" property and verify if the defined CRL file is a valid CRL file.

SINLME0013	**Initialize: failed to create URL or InputStream from the CRL URL: {0} {1}**
Explanation	IOException exception diring initialization of the CRL. Possible reasons: the URL is broken or the file is not found.
Action	Double check in the JAAS configuration the value of the "crl_url" property and verify if this is a valid URL. If the CRL is on the file system, make sure the value for the "crl_url" begins with "file://".

SINLME0014	**Initialize: failed to create CRL - CRL location: {0} {1}**
Explanation	Unknown exception diring initialization of the CRL.
Action	Double check the log files about the exception type and the explanation.

SINLME0015	**Initialize: CRL location is not specified.**
Explanation	The "check_crl_status" property is set to true but the "crl_url" property is not set up.
Action	1. Disable CRL check by setting up the "check_crl_status" property to false or by removing it; 2. Specify the "crl_url" property correctly.

SINLME0190	**login: unsupported callback {0}**
Explanation	Supplied CallBack is not supported. Software AG Security Infrastructure supports only SagCredentialCallback, PasswordCallback and NameCallback.
Action	Check which Callback is used.

SINLME0191	**Engine failed to load with options: {0}**
Explanation	Authentication failed in RoleLoginModule. Storage is not loaded properly.
Action	Check logs for more details about the reasons.

SINLME0192	**Provider class cannot be found {0}**
Explanation	Role storage implementation provider is not found.
Action	Check the value of the "provider_class" property in the JAAS configuration file.

SINLME0193	**Provider class cannot be instantiated {0}**
Explanation	Role storage implementation provider cannot be instantiated.
Action	Check the value of the "provider_class" property in the JAAS configuration file.

SINLME0194	**Provider class cannot be accessible {0}**
Explanation	Role storage implementation provider class is not accessible.
Action	Check the value of the "provider_class" property in JAAS configuration file. Check classloaders, if the requested provider class is available.

SINLME0195	**resolveArtifact: ArtifactParseException {0}**
Explanation	An error occurred while parsing the artifact.
Action	Check the JAAS configuration.

SINLME0197	**resolveArtifact: ArtifactParserException {0}**
Explanation	An error occurred while parsing the artifact.
Action	Check the JAAS configuration.

SINLME0198	**resolveArtifact: Exception {0}**
Explanation	An error occurred while parsing the artifact.
Action	Check the JAAS configuration.

SINLME0199	**resolveArtifact: no name could be found in the SAML response. Returning NULL.**
Explanation	No name was found in the parsed artifact and the resolving failed.
Action	Check the JAAS configuration and the artifact creator.

SINLME0204	**authenticate() failed. Principal not available in the servlet request.**
Explanation	The configuration requires a principal, but the HTTP request does not contain one.
Action	Check the JAAS configuration.

SINLME0205	**authenticate() failed. X509Certificate Chain is not available in the servlet request.**
Explanation	The configuration requires a certificate, but the HTTP request does not contain one.
Action	Check the JAAS configuration.

SINLME0206	**authenticate() failed. SAML Artifact is not available in the servlet request.**
Explanation	The configuration requires a SAML artifact, but the HTTP request does not contain one.
Action	Check the JAAS configuration.

SINLME0207	**authenticate() failed. SAML Artifact header field name is not set in the JAAS configuration.**
Explanation	The configuration expects to find the HTTP header field used to search for a SAML Artifact, but the HTTP header is not set.
Action	Check the JAAS configuration.

SINLME0208	**authenticate() failed. Netegrity SiteMinder is not available in the servlet request.**
Explanation	The configuration requires a Netegrity SiteMinder, but the HTTP request does not contain one.
Action	Check the JAAS configuration.

SINLME0209	**authenticate() failed. Netegrity SiteMinder header field name is not set in the JAAS configuration.**
Explanation	The configuration expects to find the HTTP header field used to search for a Netegrity SiteMinder, but the HTTP header is not set.
Action	Check the JAAS configuration.

SINLME0210	**authenticate() failed.'{0}' custom header is not available in the servlet request.**
Explanation	The configuration requires a custom header name, but the HTTP request does not contain one.
Action	Check the JAAS configuration.

SINLME0211	**authenticate() failed. Custom header name property is not set in the JAAS configuration.**
Explanation	The configuration expects to find the HTTP header field used to search for a custom header, but the HTTP header is not set.
Action	Check the JAAS configuration.

SINLME0212	**authenticate: SAML Assertion identity provider key not available. Authentication failed.**
Explanation	The SAML Assertion identity provider key is not available.
Action	Check the JAAS configuration.

SINLME0213	**authenticate: SAML Assertion validation process failed. Authentication failed.**
Explanation	The SAML Assertion validation process failed.
Action	Check the JAAS configuration.

SINLME0214	**authenticate: no username returned. Authentication failed.**
Explanation	The SAML assertion does not contain a username.
Action	Check the JAAS configuration.

SINLME0215	**initConfiguration: failed!**
Explanation	An error was found in the LoginModule configuration.
Action	Check the JAAS configuration.

SINLME0216	**Initialize: trust store location is not specified. The default one will be used: {0}; trust store type: {1}**
Explanation	The trust store location is not specified and the default one will be used.
Action	Check the JAAS configuration.

SINLME0217	**Initialize: failed to create KeyStore from the trust store URL: {0}, keystore type: {1}**
Explanation	Failed to create a KeyStore from the trust store url.
Action	Check the JAAS configuration.

SINLME0218	**Failed to read certificate from trust store!**
Explanation	Failed to read the certificate from the trust store.
Action	Check the JAAS configuration.

SINLME0219	**validateAssertion: no name could be found in the SAML assertion**
Explanation	The SAML assertion does not contain a username.
Action	Check the JAAS configuration.

SINLME0220	**authenticate() failed. Basic authentication information is not available in the servlet request.**
Explanation	The configuration requires Basic authentication information, but the HTTP request does not contain it.
Action	Check the JAAS configuration.

SINLME0221	**authenticate() failed. The Authorization header required for Basic authentication is not available in the servlet request.**
Explanation	The configuration expects to find the Authorization HTTP header, but the HTTP header is not set.
Action	Check the JAAS configuration.

SINLME0222	**initConfiguration: failed! Can not load the key store {0}**
Explanation	Failed to initiate the configuration on the AppleDSLoginModule. Cannot load truststore.
Action	Verify that the location of the truststore is valid, the file is not corrupted and password is not missing or invalid.

SINLME0223	**Error in parsing the HTTP header cookie: {0}**
Explanation	An error occurred while authenticating with the AppleDSLoginModule.
Action	Make sure that the HTTP request is valid and contains all required headers.

SINLME0224	**authenticate: There is no cookie header in the HttpServletRequest.**
Explanation	While trying to authenticate with AppleDSLoginModule, the cookie header could not be found in the HttpServletRequest.
Action	Make sure that the HTTP request is valid and contains all required headers.

SINLME0225	**Cookie is not found in cookie header.**
Explanation	While trying to authenticate with AppleDSLoginModule, the cookie could not be found in the cookie header.
Action	Make sure that the HTTP request is valid and contains all required headers.

SINLME0226	**Cannot read response data**
Explanation	A read error occured while trying to parse the input content.
Action	Make sure that the HTTP response does not contain corrupted data.

SINLME0227	**The personal id - {0}, is not returned by the server**
Explanation	The user principal does not contain a name attribute. The name attribute is expected from the HTTP response.
Action	Make sure that HTTP request is present and contains all necessary data. Check whether the login module is configured with the proper personal ID.

SINLME0228	**AppleUrlCreator could not be created. Invalid parameters.**
Explanation	An error has occurred while trying to create an instance of AppleUrlCreator. The input parameters are NULL.
Action	Make sure that HTTP request is present and contains all necessary data. Check whether the login module is configured with the proper cookie header.

SINLME0229	**constructURL: Neither URL ({0}), nor URL without query ({1}) is specified**
Explanation	An error occurred when trying to construct a URL, because the URL is not specified in the configuration.
Action	Make sure you correctly specify an URL in the configuration.

SINLME0230	**constructURL: Application admin password ({0}) is required!**
Explanation	An error occurred when trying to construct a URL, because the application administrator password is not specified in the configuration.
Action	Make sure you correctly specify the application administrator password in the configuration.

SINLME0231	**Application ID ({0}) is not specified as config property.**
Explanation	If the auth URL contains an <appId> placeholder, the application ID be must also be specified as a property.
Action	Set the application ID property.

SINLME0232	**Application ID ({0}) is not specified in the URL**
Explanation	The application ID must be contained in the authentication URL.
Action	Make sure that the application ID is contained in the URL.

SINLME0233	**The IP placeholder - {0}, could not be found in the URL**
Explanation	The auth URL must contain the IP placeholder.
Action	Make sure that the machine IP is contained in the URL.

SINLME0234	**The application admin password placeholder - {0}, could not be found in the URL**
Explanation	The auth URL must contain the application admin password placeholder.
Action	Make sure that the application admin password placeholder is contained in the URL.

SINLME0235	**The cookie placeholder - {0}, could not be found in the URL**
Explanation	The auth URL must contain the cookie placeholder.
Action	Make sure that the cookie placeholder is present in the URL.

SINLME0236	**Cannot create URL from {0}**
Explanation	An error occurred while trying to create a URL from the auth URL.
Action	Make sure that the authentication URL is valid and does not contain any restricted characters.

SINLME0237	**CookieValidator: Validation failed while reading URL data.**
Explanation	The URL validation failed while reading URL data.
Action	Make sure that the response from the URL does not contains corrupted data.

SINLME0238	**Validation failed! The URL is not specified.**
Explanation	The URL validation failed - the URL is NULL.
Action	Make sure that the provided authentication URL is valid.

SINLME0241	**Validation failed! Invalid line in the HTTP response.**
Explanation	Content validation failed due to an invalid line in the HTTP response.
Action	Make sure that the HTTP response does not contain invalid data.

SINLME0242	**Validation failed! Status code is {0}**
Explanation	Content validation has failed.
Action	Make sure that the HTTP response is successful and has SUCCESS status code.

SINLME0243	**Required func and returned values are different**
Explanation	The check of the required principal fails due to inconsistency between the required func and the returned values.
Action	Make sure that the property attributes of the principal are not null.

SINLME0244	**login: username not found: {0}**
Explanation	The configured properties file that represents the user store of the login module does not contain an entry for the specified user.
Action	The properties file that represents the user store of the login module must contain a 'userids' property with a comma-separated list of user identifiers. For each identifier, a separate <identifier>.name property must be configured which represents the human-readable user name. If the username is not found, this means that respective

configuration (user identifier and/or name) is not present in the properties file. If the user should be allowed to log in, then this user information must be added to the properties file.

SINLME0245 **login: passwords don't match for user {0}**

Explanation The specified password does not match the configured password for the user.

Action Double-check the specified password. The password for the user is configured via the "<userid>.passhash" property in the properties file configured for the login module. The value of the property is the SHA-1 digest of the plain text password encoded as a hexadecimal number.

SINLME0246 **login: SHA-1 hashing algorithm not found**

Explanation The Java virtual machine does not contain a security provider which supports the SHA-1 hashing algorithm.

Action Make sure you use a Java version which supports SHA-1 hashing algorithm or configure a Java security provider which supports this algorithm.

SINLME0247 **Resource not found: {0}**

Explanation The specified resource file cannot be found in the classpath.

Action Please check if the security infrastructure java archives are not corrupted and whether they contain the mentioned resource.

SINRME0139 **Wrong password format.**

Explanation Password entry for the user is not correct. It must start with "$6a$" or "6".

Action Check users.txt file.

SINRME0140 **Duplicates in user name.**

Explanation User names are duplicated in the users.txt.

Action Check the users.txt file that is used.

SINRME0141 **Duplicates in user name.**

Explanation User names are duplicated in the users.txt.

Action Check the users.txt file that is used.

SINRME0142	**Failed to initialize CipherUtil.**
Explanation	CipherUtil cannot be initialized due to some of following reasons: missing or invalid algorithm or key; invalid padding scheme; provider doesn't support a CipherSpi implementation for the specified algorithm; provider doesn't support a MacSpi implementation for the specified algorithm; provider doesn't support a SecretKeyFactorySpi implementation for the specified algorithm; the given key specification is inappropriate for this secret-key factory to produce a secret key; the given key is inappropriate for initializing MAC.
Action	General security error. Contact SoftwareAG global support.

SINSCE0000	**URL is missing in configuration!**
Explanation	Store cannot be added due to missing URL in the configuration.
Action	Ensure that a valid URL is specified.

SINSOE0000	**Cannot initialize Web SSO config context.**
Explanation	The Web SSO configuration could not be properly initialized.
Action	Make sure that your configuration is valid.

SINSOE0001	**Cannot initialize Web SSO config context.**
Explanation	The Web SSO configuration could not be properly initialized.
Action	Make sure that your configuration is valid.

SINSOE0002	**Failed to initialize Saml2 engine - all SAML operations will fail.**
Explanation	Internal error. The Saml2 engine failed to initialize properly. All SAML operations will fail.
Action	Contact SoftwareAG global support.

SINSOE0003	**Error initializing keystore.**
Explanation	Keystore cannot be found or the credentials are wrong.
Action	Ensure that the keystore exists and you have provided valid credentials.

SINSOE0004	**Error initializing keystore.**
Explanation	Keystore cannot be found or the credentials are wrong.
Action	Ensure that the keystore exists and you have provided valid credentials.

SINSOE0005	**Cannot load IDPSSODescriptor from metadata.**
Explanation	The error occured because of invalid IDP metadata.
Action	Make sure that the provided IDP metadata is correct and has the SSO services defined.

SINSOE0006	**Cannot load SPSSODescriptor from metadata.**
Explanation	The error occured because of invalid SP metadata.
Action	Make sure that the provided SP metadata is correct and has the consumer services defined.

SINSOE0007	**IDP cannot be determined.**
Explanation	IDP is missing in the metadata.
Action	Ensure that you have provided IDP metadata.

SINSOE0008	**Cannot get dynamic configuration.**
Explanation	Internal error. The service that provides configurations cannot be obtained.
Action	Contact SoftwareAG global support.

SINSOE0009	**The configuration could not be found.**
Explanation	Internal error. The service that provides configurations cannot be obtained.
Action	Contact SoftwareAG global support.

SINSOE0010	**The configuration could not be found.**
Explanation	Internal error. The service that provides configurations cannot be obtained.
Action	Contact SoftwareAG global support.

SINSOE0011	**Configuration Admin service is not available.**
Explanation	Internal error. The service that provides configurations cannot be obtained.
Action	Contact SoftwareAG global support.

SINSOE0012	**Can't obtain key from the keystore or generate key info for credential: {0}, {1}**
Explanation	A key cannot be obtained from the keystore with the provided crednetials.
Action	Make sure the provided credentials are valid.

SINSOW0013	**Password for key alias: '{0}' is missing. This might lead to failure to load the respective key from key store**
Explanation	A password is not provided for the given alias.
Action	Check your configuration and add a password for the specified alias.

SINSOW0014	**Cannot obtain SPSSODescriptor. Default Web SSO profile will be used.**
Explanation	Cannot fetch metadata for the given provider (SPSSODescriptor).
Action	Check whether the Service Provider metadata contains the required data if the usage of the default value is not desired.

SINSSE0022	**SSOS properties could not be updated after sso properties file creation. Restart may be needed.**
Explanation	SSO Service properties could not be updated after sso properties file creation.
Action	Restart of the SSO service may be needed.

SINSSE0023	**CacheManager cannot be instantiated. {0}**
Explanation	CacheManager cannot be instantiated. The service will work without cache. This could cause some performance degradation.
Action	Check the value of the "com.softwareag.security.idp.ehcache.location" property in the com.softwareag.sso.pid.properties dynamic configuration file.

SINSSE0024	**Ehcache cannot be initialized. cacheManager = {0}**
Explanation	Ehcache cannot be initialized. The cachemanager in not available.
Action	Switch logging to debug and check the log file for more details.

SINSSE0025	**Ehcache in null**
Explanation	Ehcache in null.
Action	Switch logging to debug and check the log file for more details.

SINSSE0026	**Return NULL. Missing user ID in the assertion.**
Explanation	Wrong SAML assertion format. The required ID attribute is missing.
Action	Check the SAML assertion syntax.

SINSSE0027	**parseAssertion(String) throws SAMLException {0}**
Explanation	Parsing of the SAML assertion failed.
Action	Activate debug logging and check log file for more details.

SINSSE0028	**Return NULL. Missing user ID in the assertion.**
Explanation	Wrong SAML assertion format. The required ID attribute is missing.
Action	Check the SAML assertion syntax.

SINSSE0029	**{0}**
Explanation	Parsing of the SAML assertion failed.
Action	Activate debug logging and check log file for more details.

SINSSE0030	**generateAssertion() throws GeneralSecurityException {0}**
Explanation	Generation of the SAML assertion failed with GeneralSecurityException.
Action	Activate debug logging and check log file for more details.

SINSSE0031	**generateAssertion() throws XMLSignatureException {0}**
Explanation	Generation of the SAML assertion failed with XMLSignatureException.
Action	Activate debug logging and check log file for more details.

SINSSE0032	**generateAssertion() throws MarshalException {0}**
Explanation	Generation of the SAML assertion failed with MarshalException.
Action	Activate debug logging and check log file for more details.

SINSSE0033	**generateAssertion() throws MarshallingException {0}**
Explanation	Generation of the SAML assertion failed with MarshallingException.
Action	Activate debug logging and check log file for more details.

SINSSE0034	**Error loading truststore or keystore. Services will be unregistered.**
Explanation	Keystore or truststore cannot be found or the credentials are missing.
Action	Ensure that the keystore/truststore exists and you have provided valid credentials.

SINSSE0035	**Error loading truststore. Services will be unregistered.**
Explanation	Truststore cannot be found or the credentials are missing.
Action	Ensure that the truststore exists and you have provided valid credentials.

SINSSE0036	**Error during STS API initialization: {0}**
Explanation	An algorithm is not supported by the JVM.
Action	Ensure that unlimited strength JCE (Java Cryptographic Extension) is available on the system.f If it is available, contact Software AG Global Support.

SINSSE0037	**Error during AuthResponse generation: {0}**
Explanation	A signature cannot be created or the element being signed cannot be marshalled.
Action	Ensure that the identity provider keystore is available and contains a signing key with the configured alias and credentials.

SINSSE0038	**Unsupported request type - expected AuthnRequest but was {0}**
Explanation	The received request is not a SAML AuthnRequest.
Action	Ensure the received SAML message is a valid SAML AuthnRequest.

SINSSE0039	**Error during request parsing: {0}**
Explanation	The received SAML AuthRequest cannot be parsed.
Action	Ensure the received XML message is a valid SAML AuthnRequest message.

SINSSE0040	**Missing signature in the request, ID: {0}**
Explanation	The received SAML AuthnRequest does not contain a signature.
Action	Ensure the received SAML AuthnRequest is signed by the respective relying party issuing the request.

SINSSE0041	**Insufficient input data: destination not provided!**
Explanation	A SAML response cannot be generated due to missing destination URL.
Action	Ensure a valid destination URL is provided when generating the SAML Response message.

SINSSE0042	**Insufficient input data: userId not provided!**
Explanation	A SAML response cannot be generated due to missing user ID.
Action	Ensure valid user ID is provided when generating SAML Response. The user ID is required to generate the SAML assertion's subject information.

SINSSE0044	**Missing request ID**
Explanation	Validation of SAML AuthRequest message is failing due to missing ID attribute.
Action	Ensure the SAML AuthnRequest message contains a valid ID attribute.

SINSSE0045	**Missing request issue instant**
Explanation	Validation of SAML AuthRequest fails due to missing IssueInstant attribute.
Action	Ensure the SAML AuthnRequest message contains a valid IssueInstant attribute, which represents the time instant of issue for the request.

SINSSE0046	**SAML AuthnRequest version is not SAML 2.0**
Explanation	The SAML AuthnRequest has invalid Version attribute, the only supported version is SAML 2.0
Action	Ensure SAML AuthnRequest message uses SAML 2.0 version.

SINSSE0047	**Missing issuer in the request.**
Explanation	SAML AuthRequest message does not specify an issuer.
Action	Ensure the SAML AuthnRequest message specifies an issuer, which identifies the entity that generated the request message.

SINSSE0048	**No relying party configuration found for entityId {0}**
Explanation	The identity provider is not configured with a relying party for the given entity identifier.
Action	Check if the relying party identified by the specified entityId is trusted, and if so, configure a relying party with this identifier in the identity provider configuration.

SINSSE0049	**Unexpected signature algorithm: {0}**
Explanation	The signature algorithm of the received SAML AuthnRequest message does not match the signature algorithm configured for the respective relying party in the identity provider configuration.
Action	The expected relying party signature algorithm must be specified in the relying party configuration. To disable checking the signature algorithm, do not configure a signature algorithm for the relying party.

SINSXE0000	**Initialize: keystore password is not specified.**
Explanation	Keystore password is missing.
Action	Make sure that the keystore password is specified.

SINSXE0001	**No token returned from IAF.**
Explanation	Internal error.
Action	Contact SoftwareAG global support.

SINSXE0002	**Signature creation failed.**
Explanation	Certificate cannot be found or error occurred during signing operation.
Action	Make sure that the provided certificate is valid.

SINSXE0003	**Unsupported encoding.**
Explanation	Internal error. Encoding with not supported charset.
Action	Contact SoftwareAG global support.

SINSXE0004	**verifySignature: Given certificate is NULL**
Explanation	Cannot verify given signature. The certificate is missing.
Action	Set certificate for verification of the signature.

SINSXE0005	**Utility path is not specified**
Explanation	The utility path is not specified in the JAAS configuration.
Action	Make sure that the utility path is specified in the JAAS configuration.

SINSXE0006	**RMI Port must be a valid integer.**
Explanation	The specified RMI port is invalid.
Action	Set a valid RMI port in the configuration.

SINSXE0007	**Remote classes are not currently bound**
Explanation	Internal error.
Action	Contact Software AG global support.

SINSXE0008	**Problem with clearing credentials**
Explanation	Internal error. User credentials cannot be cleared. Logout operation failed.
Action	Contact Software AG global support.

SINSXE0009	**Problem creating repository manager**
Explanation	Internal error. RMI registry function was not found or could not obtain remote reference to the repository.
Action	Contact Software AG global support.

SINSXE0010	**TEMPLATE_SECTION must not be null or empty.**
Explanation	Template section option is not specified in the JAAS configuration.
Action	Make sure that the template section option is specified in the JAAS condiguration.

SINSXE0011	**Error opening SSX Repository**
Explanation	The error is thrown by the SSX repository during opening operation.
Action	Make sure that the provided SSX parameters are valid.

SINSXE0012	**Cannot obtain lock**
Explanation	Internal error. An interruption ocurred when obtaining the remote registry.
Action	Contact Software AG global support.

SINSXE0013	**Cannot obtain lock**
Explanation	Internal error. An interruption ocurred when obtaining the remote registry.
Action	Contact Software AG global support.

SINSXE0014	**Cannot obtain lock**
Explanation	Internal error. An interruption ocurred when obtaining groups from the repository.
Action	Contact Software AG global support.

SINSXE0015	**Cannot obtain lock**
Explanation	Internal error. An interruption ocurred when obtaining users from the repository.
Action	Contact Software AG global support.

SINSXE0016 **Cannot obtain lock**

Explanation Internal error. An interruption ocurred when obtaining user groups from the repository.

Action Contact Software AG global support.

SINSXE0017 **Cannot obtain lock**

Explanation Internal error. An interruption ocurred when obtaining the users in a group from the repository.

Action Contact Software AG global support.

SINSXE0018 **Cannot obtain lock**

Explanation Internal error. An interruption ocurred when obtaining the principles in a group from the repository.

Action Contact Software AG global support.

SINSXE0019 **Cannot obtain lock**

Explanation Internal error. An interruption ocurred when checking if a group exists in the repository.

Action Contact Software AG global support.

SINSXE0020 **Cannot obtain lock**

Explanation Internal error. An interruption ocurred when checking if a user exists in the repository.

Action Contact Software AG global support.

SINSXE0021 **Cannot obtain lock**

Explanation Internal error. An interruption ocurred when obtaining user principals from the repository.

Action Contact Software AG global support.

SINSXE0022 **Cannot obtain lock**

Explanation Internal error. An interruption ocurred when obtaining group principals from the repository.

Action Contact Software AG global support.

SINSXE0023	**Cannot obtain lock**
Explanation	Internal error. An interruption ocurred when obtaining the repository type.
Action	Contact Software AG global support.

SINSXE0024	**Cannot obtain lock**
Explanation	Internal error. An interruption ocurred when specifying page size.
Action	Contact Software AG global support.

SINSXE0025	**Cannot obtain lock**
Explanation	Internal error. An interruption ocurred when specifying principals data to IAF.
Action	Contact Software AG global support.

SINSXE0026	**LoadAccessList: Cannot read file {0} {1}**
Explanation	The URL of the load access list is not provided.
Action	Make sure that the "load access list" command line option is present.

SINSXE0027	**This client has no permissions for authentication. Please contact with your RMI server administrator.**
Explanation	The client has no permissions for authentication.
Action	Contact your RMI server administrator.

SINSXE0028	**authenticate: could not logout.**
Explanation	Internal error. Logout operation failed.
Action	Contact Software AG global support.

SINSXE0029	**authenticate: could not login the user with credentials: {0} {1}**
Explanation	Logon failed.
Action	Make sure the used credentials are valid.

SINSXE0030	**logout: user data parameter is null during the remote logout!**
Explanation	Internal error. Logout operaiton failed. User doesn't exist.
Action	Try again later, if that doesn't solve the issue, contact Software AG global support.

SINSXE0031	**logoutUser: could not logout the user: {0} {1}**
Explanation	Internal error. Logout operation failed.
Action	Contact Software AG global support.

SINSXE0032	**logoutUser: this context could not be fund in the cache. User data: {0}**
Explanation	Internal error. Context is missing from the cache.
Action	Contact Software AG global support.

SINSXE0033	**Could not obtain lock**
Explanation	Internal error. An interruption occured when obtaining the remote registry.
Action	Contact Software AG global support.

SINSXE0034	**Could not obtain lock**
Explanation	Internal error. An interruption occured when obtaining an acess token frim the remote token manager.
Action	Contact Software AG global support.

SINSXE0035	**Invalid parameter!**
Explanation	Passed arguments during initialization of the remote SSX server are not registry port or configuration file.
Action	Make sure that either URL configuration or port number is present in the command line options.

SINSXE0036	**key store password parameter is missing**
Explanation	Keystore password is missing.
Action	Provide valid keystore password.

SINSXE0037	**Error starting the server**
Explanation	Error occurred during initialization/start of the server.
Action	Contact Software AG global support.

SINSXE0038	**Error running the server**
Explanation	Internal error.
Action	Contact global Software AG support.

SINSXE0039	**Error unbinding services**
Explanation	Error occurred during shutdown of the server.
Action	Contact Software AG global support.

SINSXE0040	**Can't get all groups: {0}**
Explanation	Groups cannot be obtained. The SSX repository cannot be opened.
Action	Make sure that the provided SSX repository parameters are valid. If the parameters are correct, contact global Software AG support.

SINSXE0041	**This principal {0} is with wrong.**
Explanation	Internal error. The principal has wrong user type.
Action	Contact global Software AG support.

SINSXE0042	**This {0} has wrong type**
Explanation	This {0} has wrong user type.
Action	Contact global Software AG support.

SINSXE0043	**This {0} is not user.**
Explanation	Error when verifying user.
Action	Contact global Software AG support.

SINSXE0044	**This principal: {0} has wrong type**
Explanation	Wrong principal type.
Action	Contact global Software AG support.

SINSXE0045	**This {0} is not group.**
Explanation	Error when verifying group.
Action	Contact global Software AG support.

SINSXE0046 **This method is not supported!**

Explanation Specifying page size is not yet supported.

Action Do not use this method.

SINSXE0047 **Input data cannot be null**

Explanation Input data (password) is missing or incorrect.

Action Make sure that the input data (password) is correct.

SINSXE0048 **Token type is not IAF token or artifact.**

Explanation Access token is invalid, it does not contain a IAF token or artifact.

Action Contact global Software AG support.

SINSXE0049 **Cannot retrieve access token {0}**

Explanation Internal error. Repository cannot be opened.

Action Contact global Software AG support.

SINSXE0050 **Can not get manifest file.**

Explanation Cannot obtain the manifest of the SSX jar file.

Action Contact Software AG global support.

SINSXE0051 **Can not receive user groups properties.**

Explanation Internal error. Native code exceuted. Cannot receive user groups properties.

Action Contact global Software AG support.

SINSXE0052 **Can not receive user properties.**

Explanation Internal error. Native code exceuted. Cannot receive user properties.

Action Contact global Software AG support.

SINSXE0053 **Can not receive group properties.**

Explanation Internal error. Native code exceuted. Cannot receive group properties.

Action Contact global Software AG support.

SINSXE0054	**Server not responding for a long time.**
Explanation	Connectivity issues.
Action	Contact global Software AG support.

SINSXE0055	**There is no SAG User Database Module in the manifest file.**
Explanation	The manifest file of the Software AG security extension java archive does not contain a 'SAG User Database Module' attribute section.
Action	Contact Software AG Global Support.

26 Tamino Messages

INOAAE0001 **Function not selected : name**

Explanation The server extension function is not selected so that the parameter cannot be modified.

Action Select the server extension function first.

INOAAE0004 **Cannot modify journal space**

Explanation The journal space of the specified database cannot be modified.

Action Check whether the data space is already in use. Check the database location for remaining disk space.

INOAAE0018 **Port number 'port' for 'name' indication**

Explanation The port number cannot be used.

Action Change the port parameter value.

INOAAE0019 **fail - delete database dbname read only parameter is set**

Explanation The database parameter "read only" must be cleared before the database can deleted.

Action Remove the read only flag in the database parameters.

INOAAE0020 **Modify Email notification properties failed**

Explanation The modification of Email notification properties failed.

Action Look at the detailed error message and action.

INOAAE0022 **mvcount spaces successfully moved from oldloc to newloc, one or more spaces couldn't be moved because of errors/warnings**

Explanation The given number of spaces were moved successfully but one or more spaces could not be moved because an error or a warning occurred during the execution of the command.

Action Find out why spaces were not moved and try to move them via the 'Move' command of the database spaces entry.

INOAAE0024 **Change License file failed**

Explanation Change license file failed.

Action Check the license file.

INOAAE0026 **The parallel option is not supported for incremental backups**

Explanation Options "parallel" and "incremental" are mutually exclusive.

Action Select only one of the options.

INOAAE0032 **Cannot activate dynamic property 'name'**

Explanation The property cannot be updated in the current server session, but will be active after a restart of the database.

Action Restart the database to activate the property.

INOAAE0038 **Cannot open file path, file does not exist or is opened by another one or not enough access rights**

Explanation The file does not exist or is already open.

Action Check the filename.

INOAAE0039 **Unknown database space number**

Explanation The database space number is not valid for this database.

Action Use a valid database space number.

INOAAE0040 **This command is valid for journal space only**

Explanation The database space type is not valid for this command.

Action Use the journal space.

INOAAE0042 **CD database information file not found**

Explanation The error message information file for the CD database not found.

Action Check the path and filename.

INOAAE0043 **CD database information file doesn't contain all necessary data or was created on a different platform**

Explanation The content of the information file is not complete or the file is not the required information file is from a different operating system.

Action Check the content of the information file.

INOAAE0044 **CD database from different operating system cannot be registered**

Explanation Only CD databases from the same operating system can be registered.

Action Use a CD database that was created on the same operating system.

INOAAE0045 **Operation not allowed on CD database or read only database**

Explanation The operation is not allowed on a CD database or read only database.

Action No action required.

INOAAE0054 **The "Add database space" function has failed**

Explanation The attempt to add one or more of the database spaces failed.

Action Check the database locations for remaining disk space. The server property "read only" may be set to "yes".

INOAAE0055 **More than one replication database is not yet supported**

Explanation Only one replication database is allowed.

Action No action required.

INOAAE0056 **Re-invert of database dbName has failed**

Explanation The re-invert operation failed. Possible reasons are that the database is not active or, if active, one or more indices could not be repaired.

Action Check your database status.

INOAAE0058 **Invalid Access Control Element name**

Explanation Function names cannot be part of paths.

Action Use either a function name or a path but not both.

INOAAE0059 **Invalid master database name**

Explanation The master database name specified is invalid.

Action Specify another database name for the master database.

INOAAE0060 **Specification of key parameter is mandatory**

Explanation The parameter must be specified.

Action Specify the parameter and try again.

INOAAE0065 **Server extension 'name' not defined**

Explanation The specified server extension does not exist.

Action No action required.

INOAAE0066 **Internal configuration store key _default not found**

Explanation The default internal configuration store key could not be found.

Action Please contact your software supplier.

INOAAE0067 **File 'path' not found**

Explanation The specified file could not be found.

Action Specify a valid filename.

INOAAE0068 **Different server extension names: name1 is different from name2**

Explanation The server extension names differ.

Action No action required.

INOAAE0069 **File 'path' not extracted**

Explanation The server extension installation file was not extracted.

Action No action required.

INOAAE0070 **File 'path' already installed**

Explanation The server extension installation file was previously installed.

Action No action required.

INOAAE0072 **Document 'path' not installed**

Explanation The server extension installation document was not installed.

Action The action depends on previous error messages. Please check the previous messages for more information.

INOAAE0073 **File 'path' not created**

Explanation The server extension installation file was not created.

Action Correct the access rights for the directory and retry the operation.

INOAAE0074 **Server extension name 'name' not defined**

Explanation The name of the server extension is not defined.

Action Specify the name of the server extension and retry the operation.

INOAAE0075 **Server extension name 'name' already defined**

Explanation The name of the server extension already exists.

Action Change the name of the server extension and retry the operation.

INOAAE0076 **Directory 'path' already exists**

Explanation The server extension installation directory already exists.

Action Remove the directory and retry the operation.

INOAAE0077 **Document 'path' already installed**

Explanation The server extension installation document is already installed.

Action Remove the server extension installation document.

INOAAE0078 **Execution failed: command**

Explanation The specified operating system command failed.

Action The action depends on previous error messages. Please check the previous messages for more information.

INOAAE0079 **Database name not defined**

Explanation The required database name was not specified.

Action Please contact your software supplier.

INOAAE0080 **No functions defined: name**

Explanation There are no functions defined in the server extension.

Action Add functions to the server extension and retry the installation.

INOAAE0081 **The Tamino server returned an invalid server extension response document**

Explanation The server extension response document does not correspond to the agreed protocol with the Tamino server.

Action Please contact your software supplier.

INOAAE0082 **Server extension 'name' does not exist**

Explanation The specified server extension does not exist.

Action Correct the name of the server extension and retry the operation.

INOAAE0083 **File 'path' already open**

Explanation The server extension installation package is already open.

Action Wait until the package is not being used and retry the operation.

INOAAE0084 **File 'path' not open**

Explanation The server extension installation package is not open.

Action Wait until the package is not being used and retry the operation.

INOAAE0085 **File 'path' not previously closed**

Explanation The server extension installation package is not closed.

Action Wait until the package is not being used and retry the operation.

INOAAE0086 **Operation 'type' not implemented**

Explanation The requested operation is not implemented.

Action No action required.

INOAAE0087 **Command 'type' not allowed**

Explanation This command is not allowed for the requested server extension.

Action Ensure that you use one of the commands allowed for the server extension.

INOAAE0088 **message**

Explanation This is a generic container for Tamino error messages.

Action See the content of the message during online Tamino operation for further information.

INOAAE0089 **Not an installation package: path**

Explanation The provided file is not a server extension installation package.

Action Use a valid installation package.

INOAAE0092 **Error during write to inodmn, write interrupted or socket closed by inodmn**

Explanation This is an internal error. It could be caused by not fully compatible versions of Tamino and System Management Hub.

Action Please contact your software supplier.

INOAAE0093 **Error during read from inodmn, read interrupted or socket closed by inodmn**

Explanation This is an internal error. It could be caused by not fully compatible versions of Tamino and System Management Hub.

Action Please contact your software supplier.

INOAAE0094 **Command is an illegal number**

Explanation This is an internal error in the event logging protocol.

Action Please contact your software supplier.

INOAAE0095 **This command requires a different database state**

Explanation An attempt was made to execute a command that either requires an active database, but the database is inactive, or the command can be executed only in inactive mode, but the database is active.

Action Start or stop the database to bring it into the appropriate mode (active or inactive) and retry the command.

INOAAE0096 **The command requested cannot be executed because it is already running**

Explanation The command you wish to execute is already being executed by someone else, but the command cannot be executed in parallel.

Action Wait until the running command has completed. The argevsrv process keeps track of running commands. If the command is blocked although it is obviously not running, try restarting the argevsrv process.

INOAAE0097 **Insufficient resources to complete the command**

Explanation This is an internal error in the event logging protocol. Some resource (usually disk or main storage) is exhausted and the function failed to complete.

Action Check if there is enough free disk space. Delete temporary and otherwise expandable files, then try again.

INOAAE0098 **Path 'path/name' not created**

Explanation The specified path name is too long.

Action Choose another file structure with shorter path names.

INOAAE0099 **Path 'path' not converted**

Explanation The specified path name was not converted to a URL or vice versa. Either the path name or the URL is too long.

Action Choose another file structure with shorter path names.

INOAAE0110 **Internal error with database startup by changing replication database to a normal database**

Explanation An internal error occurred when starting the database.

Action Please contact your software supplier.

INOAAE0111 **No valid destination directory for backup files given.**

Explanation No valid destination directory was given.

Action Specify at least one valid directory with write access for Tamino and enough space for the backups.

INOAAE0113 **Path 'path' not extracted**

Explanation The specified path was not extracted from the internal configuration store. This is an internal error.

Action Please contact your software supplier.

INOAAE0114 **Execution mode 'name' not extracted**

Explanation This is an internal error.

Action Please contact your software supplier.

INOAAE0115 **Execution mode not compatible: mode1 != mode2**

Explanation The specified execution modes are not compatible.

Action Select a compatible execution mode.

INOAAE0116 **GUID not extracted**

Explanation The GUID was not extracted from the internal configuration store. This is an internal error.

Action Please contact your software supplier.

INOAAE0117 **DLL 'path' is not registered**

Explanation The specified DLL cannot be used.

Action Specify another DLL.

INOAAE0118 **DLL 'path' not unregistered**

Explanation The specified DLL cannot be used.

Action Specify another DLL.

INOAAE0119 **Remove of all server extensions failed**

Explanation The server extensions could not be removed.

Action Check the extensions.

INOAAE0120 **XML port not defined for database 'name'**

Explanation The XML port value is missing in the internal configuration store.

Action Please contact your software supplier.

INOAAE0121	**Not enough memory**
Explanation	There is not enough memory for an http request.
Action	Close some of your applications.

INOAAE0122	**XML template processing failed, template template missing or incorrect**
Explanation	This is an internal error of the Tamino Manager browser interface.
Action	Check if the quoted template file exists and if it is intact. If not, either reinstall or contact your software supplier.

INOAAE0123	**No package name defined: name**
Explanation	For a server extension the Java package name is required.
Action	If you generated the Java package yourself, use a unique name for your Java package. If it is a third-party product, get a new package from your software vendor.

INOAAE0124	**Unknown database dbname : rename failed or no information from Software AG XTS Directory Server**
Explanation	The database to be renamed could not be found.
Action	Check if the specified database exists and if the Software AG XTS Directory Server is running.

INOAAE0125	**Directory 'path' not deleted**
Explanation	The directory is in use. Therefore it cannot be deleted.
Action	Wait until the directory is no longer in use and try again.

INOAAE0126	**No valid location type found**
Explanation	The location type parameter is missing.
Action	Specify the location type parameter.

INOAAE0127	**Location type 'type' is unknown**
Explanation	An unknown location type is specified.
Action	Specify a valid location type.

INOAAE0128 **File 'path' not copied**

Explanation The specified file was not copied to the target file.

Action Check your permissions or check your disk space.

INOAAE0129 **Please specify at least the location path**

Explanation The path parameter is missing.

Action Specify the path parameter.

INOAAE0130 **Path path exceeds the maximum path length of maxpathlen characters**

Explanation The length of the specified path exceeds the allowed maximum length of a directory path.

Action Specify a shorter directory path.

INOAAE0131 **Location path path includes no valid directory**

Explanation The root of the specified directory path is invalid. A possible cause is that the specified directory path could be on a removable drive or RAM disk.

Action Specify a valid directory path.

INOAAE0132 **Location path path is located on a remote drive. Please choose a local drive.**

Explanation A remote drive is not allowed for a location path.

Action Specify the location path on a local drive.

INOAAE0133 **Name name exceeds the maximum name length of maxnamelen characters**

Explanation The length of the specified name exceeds the allowed maximum length.

Action Specify a shorter name.

INOAAE0134 **Name name already exists as database location name**

Explanation The specified location name is the name of an existing database location.

Action Change the location name.

INOAAE0135 **Path path already exists as database location path**

Explanation The specified location path is the path of an existing database location.

Action Change the location path specification.

INOAAE0136	**Database location name not found**
Explanation	The specified location name was not found in the internal configuration store.
Action	Specify an existing location name.

INOAAE0137	**Location name is the current default location**
Explanation	Deleting the current default location is not allowed.
Action	Change the default location.

INOAAE0138	**Location name is the current default backup location**
Explanation	Deleting the current default backup location is not allowed.
Action	Change the default backup location.

INOAAE0140	**Database dbname uses database location name with location path path as 'category'. If you still want to delete the location, all spaces from that location must be moved to another location before you can delete it.**
Explanation	The specified location is defined as a category location for a database, so deleting is not allowed. Move the database spaces on that location to another one.
Action	Change the default database location category specification.

INOAAE0141	**No response document received**
Explanation	There was no response document received from the server.
Action	Check if the network communication is established.

INOAAE0142	**Value for property 'name' too small - minimum is minval**
Explanation	The value for the given property is smaller than the minimum allowed.
Action	Specify a larger value.

INOAAE0143	**Value for property 'name' too large - maximum is maxval**
Explanation	The value is larger than the maximum allowed.
Action	Specify a smaller value.

INOAAE0144 **Invalid numeric value for property 'name'**

Explanation The property is a numeric property and the value has the wrong type.

Action Change the property value to numeric.

INOAAE0145 **Property 'name' must be 'yes' or 'no'**

Explanation The property is a boolean property and the value has the wrong type.

Action Change the property value to 'yes' or 'no'.

INOAAE0146 **The sequence of backup spaces is not complete.**

Explanation One or more streams or extents are missing in the selected backup spaces. Only complete backups can be restored. Spaces missing at the end of the sequence will be only detected at runtime when data is loaded into the new database.

Action Check the stream or extent numbers of the selected backup spaces and add missing spaces. Check if the sequence of backup spaces (Extent 1, Extent 2, ..) is correct.

INOAAE0149 **Web server wsname already assigned**

Explanation The web server is already assigned to the specified database.

Action Check the specified web servers and the web server assignments.

INOAAE0153 **Web server wsname not assigned**

Explanation The specified web server is not assigned to the specified database, therefore the assignment cannot be deleted.

Action Check the web server assignments to the specified database.

INOAAE0154 **Error retrieving collection/doctype information: the requested document(s) could not be locked**

Explanation The document is already locked or cannot be locked. A possible reason can also be an unclosed session.

Action Wait for a short time and try this command again.

INOAAE0155 **Unknown location location name**

Explanation The given location does not exist.

Action Choose a valid location.

INOAAE0157 **Parameter parameter name missing**

Explanation The parameter with the given name is not specified.

Action Specify the required parameter.

INOAAE0158 **parameter name: invalid path, directory does not exist or is not writable**

Explanation The given path does not exist or is not writeable.

Action Use a path that exists and is writable.

INOAAE0159 **Database dbname already exists**

Explanation The "rename database" command failed because the database name already exists.

Action Use a different name or remove the database.

INOAAE0162 **Cannot delete database space spaceNo**

Explanation The specified database space cannot be deleted from the location.

Action Check whether the database space is already in use.

INOAAE0165 **Cannot expand database space spaceNo**

Explanation The specified database space cannot be expanded.

Action Check whether the database space is already in use. Check the database location for remaining disk space. If the database is read-only it cannot be expanded.

INOAAE0169 **Database database name exists**

Explanation A database with the same name exists either on the local computer, or in the scope of XTS Directory Service (which may know databases on multiple computers).

Action Choose a different name. On Windows platforms, it is not sufficient to have two names differ only in upper/lowercase.

INOAAE0170 **Configuration 'configuration' already exists for external backup method 'method'**

Explanation The configuration name already exists for this external backup method.

Action Specify a new configuration name which does not exist already.

INOAAE0174 **Could not initialize TCP stack**

Explanation This is an internal error in the event logging protocol. The communication between a logging client and the logging server could not be established. Basic functions and commands may be unaffected by this failure but messages will not be stored permanently or displayed in the Tamino Manager browser interface.

Action This failure is most likely due to extreme shortage of resources, or missing operating system components. Check the disk space. Check the integrity of the installation. Contact you software supplier to check if there is a software update.

INOAAE0175 **Error in inodmn conversation: unexpected response buffer**

Explanation This is an internal error of the event logging protocol.

Action Please contact your software supplier.

INOAAE0177 **Error in inodmn conversation: invalid number**

Explanation This is an internal error in the event logging protocol.

Action Please contact your software supplier.

INOAAE0178 **Function not implemented**

Explanation This is an internal error of the event logging protocol, a feature is not implemented in the version installed. Basic functions and commands are probably not affected.

Action No action necessary. Please contact your software supplier for a possible software update.

INOAAE0179 **Error in inodmn conversation: request failed**

Explanation This is an internal error in the event logging protocol. It could be caused by not fully compatible Tamino and System Management Hub versions.

Action Please contact your software supplier for a possible software update.

INOAAE0180 **Too many parameters**

Explanation A parameter has been specified repeatedly, but is only allowed once.

Action Change the command and retry.

INOAAE0181 **Database does not exist**

Explanation There is no database with the given name.

Action Choose a valid database name.

INOAAE0182 **Space space is not a valid backup space**

Explanation The file or tape specified has not been recognized as a valid Tamino backup. The file or tape could be damaged or access to the medium could be denied.

Action Use a valid backup space.

INOAAE0183 **Backup spaces have not been specified in the sequence determined by their extent or stream numbers**

Explanation The spaces are not ordered by their extent or stream number. The first space does not have the extent number 1.

Action Specify backup spaces in the order of the extent or stream number.

INOAAE0184 **Creation of directory path failed**

Explanation The directory at the given path could not be created.

Action Check the permissions for the given path.

INOAAE0186 **Unknown command**

Explanation The command is unknown in this context.

Action Specify a valid command for this context.

INOAAE0187 **Missing parameter**

Explanation A parameter specification is missing.

Action Specify the needed parameter.

INOAAE0188 **Not allowed to set a location of type 'type' as default location**

Explanation The location represents a type which is not allowed to be set as the default location.

Action Set another location as the default location.

INOAAE0189	**No valid location category specified**
Explanation	The specified category is not a valid location category.
Action	Specify a valid location category.

INOAAE0190	**Memory fault**
Explanation	An error has occurred while allocating memory storage.
Action	Reboot the system.

INOAAE0191	**database space spaceNo at location oldLoc not found**
Explanation	A database space cannot be moved from one location to another, because the space does not exist at the source location.
Action	Search for the space at another location.

INOAAE0192	**database space spaceNo at location newLoc already exists**
Explanation	The database space cannot be moved to the new location. The space already exists.
Action	Delete the space from the new location.

INOAAE0193	**Cannot remove database space spaceNo from location oldLoc**
Explanation	A database space cannot be removed from the source location.
Action	Check the permissions for the database space. The database space could be in use by a running database. Do a shutdown of the database and try again.

INOAAE0194	**Cannot write internal configuration store**
Explanation	The write operation into the internal configuration store failed.
Action	Check the permissions.

INOAAE0195	**Unknown database dbname or no information from Software AG XTS Directory Server**
Explanation	The database is unknown or there is no information from the Software AG XTS Directory Server.
Action	Check the database name, and check if the Software AG XTS Directory Server is running.

INOAAE0196 **Database dbname ID or port not found**

Explanation The database ID or port was not found in the internal configuration store.

Action Please contact your software supplier.

INOAAE0197 **Database dbname already active**

Explanation The database is already active.

Action Stop the database and re-execute the operation.

INOAAE0198 **Database dbname not active**

Explanation The database is not active.

Action Start the database and re-execute the operation.

INOAAE0203 **Function 'name' not found**

Explanation The function was deleted, but the display has not been refreshed.

Action Refresh your display.

INOAAE0204 **Invalid function type 'type'**

Explanation The type of a server extension function was invalid. This is an internal error.

Action Please contact your software supplier.

INOAAE0205 **File 'path' not added**

Explanation The file was not added to the server extension package. This is an internal error.

Action Please contact your software supplier.

INOAAE0208 **Not allowed to specify a recoverydate with recoveryoption=no**

Explanation If a recoverydate is specified, recoveryoption=no is not allowed.

Action Specify recoveryoption=yes or do not use the recoveryoption parameter.

INOAAE0209 **Access Violation - You are not allowed to access the requested database**

Explanation You are not authorized to access the database.

Action Get authorization from the database administrator.

INOAAE0210 **Min Port must be lower than Max Port and Port Ranges cannot overlap**

Explanation An invalid port range was specified. Min Port must be lower than Max Port and Port Ranges cannot overlap.

Action Change the ports and retry the operation.

INOAAE0212 **Error reading database locations**

Explanation An error occurred while reading database locations from the internal configuration store.

Action Please contact your software supplier.

INOAAE0215 **Unknown category**

Explanation The agent was called with an invalid category.

Action Use a valid category for this agent.

INOAAE0216 **Missing database name**

Explanation The database name is missing in the object ID.

Action Use a valid object ID.

INOAAE0217 **Missing Object ID**

Explanation The object ID is missing in the agent call parameter.

Action Use a valid object ID.

INOAAE0218 **Missing database space type**

Explanation The database space type is missing in the agent call parameter.

Action Use a valid database space type.

INOAAE0219 **Unknown database space category**

Explanation The database space category in the agent call parameter is unknown.

Action Use a valid database space category .

INOAAE0220 **The database dbname does not exist**

Explanation One of the following errors may have occurred: - XTS not configured in the "hosts" file - the XTS service not running - the database is not specified in the XTS configuration file xtsurl.cfg.

Action Choose another database name, check XTS configuration.

INOAAE0222 **The database dbname must be offline**

Explanation The database must be stopped for this operation.

Action Shut down the database.

INOAAE0225 **Leave command request on Event Service failed**

Explanation This request is part of the command synchronization scheme. This scheme synchronizes the execution of commands that might interfere otherwise and it prevents parallel execution of commands that should be executed only once per database at a time (like a backup).

Action Check if the Event Service is running. If it is running, stop and re-start the service to initialize command synchronization

INOAAE0226 **Database status request on event demon failed**

Explanation The status of a database could not be received from the event demon.

Action Check if the event demon is running.

INOAAE0229 **Tape path does not exist**

Explanation The tape with the specified path does not exist.

Action Specify an existing tape path.

INOAAE0230 **Device path does not exist**

Explanation The device with the specified path does not exist.

Action Specify an existing device path.

INOAAE0231 **Could not create location name at path**

Explanation Creating the location failed because of an internal configuration store error.

Action Check access rights (privileges) of the connected user; the user must be a power user (administrator).

INOAAE0232 **Could not delete location name**

Explanation Deleting the location failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0233 **Could not rename location name to newname**

Explanation Renaming the location failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0234 **Could not set location name as default database location**

Explanation Setting the location as the default location failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0235 **Could not set location name as default backup database location**

Explanation Setting the location as the default backup location failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0236 **Could not modify default of database location category 'category'**

Explanation Modifying the default database location category failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0238 **Archive path is empty**

Explanation The archive is empty or corrupt. Try with a correct archive.

Action Correct the archive you want to work with.

INOAAE0242 **No database name specified**

Explanation The database name must be specified.

Action Specify the database name.

INOAAE0243 **database registration failed**

Explanation The registration of a read only database failed.

Action Check the source file/path and database name.

INOAAE0268 **Move command for location type 'type' not supported**

Explanation The move command is not supported for some location types, especially tape.

Action Specify a valid location type as the target of the move command.

INOAAE0272 **Backup date 'bckDate' specifies no valid backup set for database dbName**

Explanation The given date was not found as a savepoint entry in the internal configuration store.

Action Specify a valid date which corresponds to a valid savepoint entry in the internal configuration store.

INOAAE0274 **No collection name specified**

Explanation The collection name must be specified for this operation.

Action Specify the collection name.

INOAAE0284 **Unregister is not allowed for normal databases; use "delete" command**

Explanation Use the "delete" command to remove a normal database.

Action Use the batch command "delete" instead of "unregister".

INOAAE0285 **Delete is not allowed for CD databases; use "unregister" command**

Explanation Use the "unregister" command to remove a CD database.

Action Use the batch command "unregister" instead of "delete".

INOAAE0287 **External function name exceeds 80 characters**

Explanation The length of the external function name may not exceed 80 characters.

Action Specify a shorter function name.

INOAAE0294 **No file restored : name**

Explanation No file was restored. Maybe there are no server extensions installed.

Action If there are server extensions installed check your database.

INOAAE0295 **Directory not created : path**

Explanation The specified directory was not created.

Action Check the permissions of your file system.

INOAAE0296 **Directory not found : path**

Explanation The specified directory was not found.

Action Check the permissions of your file system.

INOAAE0297 **Database not running : name**

Explanation The specified database is not running.

Action Start the database.

INOAAE0298 **Server returned error code : type**

Explanation The Tamino server returned an error code.

Action Please contact your software supplier.

INOAAE0304 **Fail - command log switch to mode buffers buffers**

Explanation This is a result message for a batch command.

Action Check the database.

INOAAE0305 **Parameter not defined : name**

Explanation No value given for a mandatory parameter.

Action Retry the command with the specified parameter value.

INOAAE0306 **Invalid object identification : name**

Explanation The given object identification is invalid.

Action Retry the command with a correct object identification.

INOAAE0307 **Update of settings failed : name**

Explanation The update of the given settings parameter failed.

Action Check the job log for further information.

INOAAE0310 **Path exists; please remove it or use another one**

Explanation This is an error message for creating a CD database in batch mode. A specified pathname exists already, so a different pathname must be supplied or the existing path must be removed.

Action Remove the path or use another one.

INOAAE0311 **Invalid character used in the specified location name at position position**

Explanation An invalid character has been specified in the location name. This can be a non-ASCII character or one of the special characters " %&,;!\=#[]\"\<>`'".

Action Change the character.

INOAAE0312 **Invalid character used in the specified path at position position**

Explanation An invalid character has been specified in the given path. This can be a non-ASCII character or one of the special characters "\/:*?\"<>|&`" for Windows or ":*? \"<>|;,&!\`'" for all other operating systems.

Action Change the character.

INOAAE0313 **Mapped documents exist : name**

Explanation Mapped XML documents exist for the server extension.

Action Delete the XML documents before uninstalling the server extension.

INOAAE0314 **Command not allowed if no function is selected**

Explanation The server extension must contain at least one selected function.

Action Select some functions from the object being packed.

INOAAE0315 **Database name contains invalid character "&" (ampersand)**

Explanation A database name can't contain the "&" character.

Action Remove the "&" from the database name.

INOAAE0347 **Database could not be connected**

Explanation The security manager could not connect to Tamino.

Action Check if the database has been started.

INOAAE0355 **The first and last character of a name should not be a blank**

Explanation Blanks are not allowed at the beginning and end of a name.

Action Change the first/last character.

INOAAE0356 **ACL name contains invalid character:**

Explanation Special characters are not allowed.

Action Remove special characters from ACL name.

INOAAE0359 **Group name contains invalid allowed character:**

Explanation Special characters are not allowed.

Action Remove special characters from the group name.

INOAAE0361 **User ID contains invalid character:**

Explanation Special characters are not allowed.

Action Remove special characters from the user ID.

INOAAE0362 **User created with escaped XML special characters in description**

Explanation XML special characters are not allowed.

Action Remove special characters from the description.

INOAAE0363 **Special characters are not allowed in an ACE name:**

Explanation Special characters are not allowed in an ACE name.

Action Remove special character from ACE name.

INOAAE0370 **TSM@DLL PARSE_ERR**

Explanation The retrieved XML-document is invalid or the XML parser could not retrieve data.

Action Shut down the database and restart it.

INOAAE0372 **TSM@DLL UNKNOWN ACL OR ACL NOT RETRIEVABLE**

Explanation The mentioned ACL is no longer available. Maybe another concurrent session deleted it.

Action Refresh the data within the Tamino Manager and try again.

INOAAE0373 **TSM@DLL UNKNOWN GROUP**

Explanation The mentioned GROUP is no longer available. Maybe another concurrent session deleted it.

Action Refresh the data within the Tamino Manager and try again

INOAAE0377 **Access control element 'name' already exists in access control list**

Explanation The access control element already exists in an access control list.

Action Change the name of the access control element.

INOAAE0378 **Version with compatibility level level of Tamino not found**

Explanation For reading the backup, a Tamino version of the same compatibility level is required.

Action Install a Tamino version of the required compatibility level.

INOAAE0381 **No container size information in backup file filename found**

Explanation The backup file does not contain important information for restoring.

Action Check the backup file or generate a new one.

INOAAE0382 **Not enough free memory**

Explanation Not enough free memory.

Action try closing other applications to free memory.

INOAAE0386 **Access Control List 'name' already exists**

Explanation An access control list with the specified name already exists.

Action Change the name of the access control list.

INOAAE0387 **User 'name' already exists**

Explanation The given user already exists in the ino:user doctype.

Action Supply a new user ID.

INOAAE0388 **User 'name' does not exist**

Explanation The user ID has not been found in the ino:user doctype.

Action Create the required user ID.

INOAAE0389 **Access control list 'name' does not exist**

Explanation The access control list has not been found in the ino:acl doctype.

Action Create the required access control list.

INOAAE0390 **User group 'name' does not exist**

Explanation A user group with the given name has not been found in the ino:group doctype.

Action Create the required group.

INOAAE0391 **Acename has not been defined**

Explanation The command line parameter "acename" has not been provided.

Action Provide the "acename" parameter.

INOAAE0392 **Permission has not been defined**

Explanation The command line parameter "permission" has not been provided.

Action Provide the parameter "permission".

INOAAE0393 **Aclname has not been defined**

Explanation The command line parameter "aclname" has not been provided.

Action Provide the parameter "aclname".

INOAAE0394 **Database is readonly**

Explanation The database is readonly, updates are not possible.

Action No action required.

INOAAE0395 **UserID has not been defined**

Explanation The command line parameter "userid" has not been provided.

Action Provide the parameter "userid".

INOAAE0396 **Groupname has not been defined**

Explanation The command line parameter "groupname" has not been provided.

Action Provide the parameter "groupname".

INOAAE0397 **Ace permission is not defined**

Explanation The permission for the access control element is not defined.

Action Provide the permission for the access control element.

INOAAE0398 **Permission has to be set to an allowed value**

Explanation Permission has not been set to an allowed value.

Action Set permission to an allowed value.

INOAAE0399 **Description has not been defined**

Explanation Description has not been provided.

Action Provide description.

INOAAE0400 **User group 'name' already exists**

Explanation The usr group already exists in the ino:group doctype.

Action Change the group name to one that does not already exist.

INOAAE0401 **Missing compatibility level : type**

Explanation The source or target compatibility level was not specified.

Action Specify the compatibility level and execute the command again.

INOAAE0402 **Set database version failed**

Explanation The "set database" action failed. Read the error messages to get more information.

Action Check the error messages that are generated before this message at runtime to get the reason.

INOAAE0408 **Some databases may be still active at system shutdown**

Explanation An error occurred while all active databases were stopped.

Action Shut down manually all active databases prior to the system shutdown; get assistance from your software supplier to fix the problems that were reported.

INOAAE0412 **This request is in conflict with another request that is currently being executed**

Explanation Some commands that access the same resources are mutually exclusive. This message can also appear if a process has been killed with operating system means or has crashed while the crash held the critical section locked.

Action Retry later. If no other command is active and no one else is currently executing administrative commands, shut down and restart the System Management Hub Event Layer Service.

INOAAE0413 **The request cannot be executed because a condition is missing**

Explanation The request requires another command to be active.

Action No action possible. Please contact your software supplier.

INOAAE0414 **Restore of database dbName failed**

Explanation An error occurred while restoring the specified database.

Action Try to detect the error, otherwise contact your software supplier.

INOAAE0417 **Web server 'wsname' does not exist**

Explanation The IP address and/or port of web server cannot be changed; the specified web server does not exist.

Action Use an existing web server.

INOAAE0418 **IP address of web server 'wsname' is invalid**

Explanation The IP address of the web server is invalid.

Action Specify the IP address in a valid format.

INOAAE0419 **File 'path' already exists**

Explanation The server extension installation file already exists.

Action Select another path name.

INOAAE0423 **Unable to execute command with version 'argbatchversion' for database from version 'version'. Please use 'version=version' parameter for argbatch command, or change your environment : 'argbatch set environment version=version'.**

Explanation A Tamino agent was called from the wrong version.

Action Use the "version" parameter for the argbatch command or change your environment with: "argbatch set environment version=...".

INOAAE0428 **Web server 'wsname' not defined**

Explanation The specified web server is not defined in the web server management.

Action Add the specified web server in the web server management.

INOAAE0439 **Tamino plug-in for argevsrv not installed or not properly initialized**

Explanation The Tamino plug-in was not installed, or the System Management Hub Event Service was unable to load it. Tamino will work without it but some administrative commands will not be be synchronized. This will cause problems only in rare conditions when multiple databases are created at the same time on the same computer.

Action Avoid creating multiple databases at the same time on the same computer; please contact your software supplier to find out why the Tamino plug-in was not loaded by the System Management Hub Event Service.

INOAAE0441 **version of database not found**

Explanation The database was found but not the version of Tamino that it requires.

Action Check if the correct Tamino version for database is installed or set the version to one installed on the machine.

INOAAE0442 **Tamino version not found**

Explanation The specified Tamino version was not found.

Action Check if the Tamino version is installed on the machine.

INOAAE0443 **highest Tamino version not found**

Explanation The highest Tamino version was not found.

Action Check if Tamino is installed on the machine

INOAAE0444 **Max and/or Min port not found or RGS error**

Explanation The Max and/or Min port was not found, or there was an RGS error.

Action Please contact your software supplier.

INOAAE0456 **The "Move database space" function failed**

Explanation An attempt to move a database space failed. Additional information is supplied in error messages that have occurred earlier.

Action Please follow the actions of the error messages displayed earlier in the same job log.

INOAAE0459 **The "Create Database" function failed**

Explanation An attempt to create a database failed. Additional information is supplied in error messages that have occurred earlier.

Action Please follow the actions of the error messages displayed earlier in the same job log.

INOAAE0462 **The "Delete Database" function failed**

Explanation An attempt to delete a database failed. Additional information is supplied in error messages that have occurred earlier.

Action No action required. Please follow the actions of the error messages displayed earlier in the same job log.

INOAAE0463 **The database information is available in ONLINE mode only**

Explanation The information can only determined when the database is started.

Action Start the database and call the information function again.

INOAAE0472 **Backup of database dbName failed**

Explanation Errors occurred while backing up the specified database. A possible reason could be low system memory.

Action Try to detect the error, otherwise contact your software supplier.

INOAAE0474 **Start of database dbName failed**

Explanation Errors occurred while starting the database.

Action Try to detect the error, otherwise contact your software supplier.

INOAAE0475 **Stop of database dbName failed**

Explanation Errors occurred while stopping the specified database.

Action If you cannot identify the error from a previous error message, please contact your software supplier.

INOAAE0480 **Add database space spaceNo to location newLoc failed**

Explanation An attempt to add database spaces to the specified location failed.

Action No action required.

INOAAE0481 **Not enough space on location newLoc**

Explanation The new location to which the database space should be moved is not big enough.

Action Choose a larger location for moving the database space.

INOAAE0491 **Error(s) occurred during modify of database properties**

Explanation An error occurred while attempting to modify database properties. Only the properties with an error message or a warning were not modified. All other properties are changed.

Action Please contact your software supplier.

INOAAE0509 **External function name already used : name**

Explanation The external name of a server extension function is already in use.

Action Change the external function name and retry the operation.

INOAAE0510 **Java classpath not modified : text**

Explanation The Java classpath was not modified according to the modification rules.

Action Correct the modification parameters and retry the operation.

INOAAE0534 **File 'path' not deleted**

Explanation The server extension DLL file could not be deleted.

Action Delete the DLL manually.

INOAAE0547 **Directory path does not exist**

Explanation The directory with the specified path does not exist.

Action Specify an existing path.

INOAAE0548 **No location name specified**

Explanation No location name was specified.

Action Specify a location name.

INOAAE0549 **Character '' not allowed as part of location name**

Explanation The character '\' is not allowed as part of the location name, because this name is used as internal configuration store key, and the '\' is the internal configuration store key delimiter.

Action Replace this character by another one.

INOAAE0567 **There is currently only one location defined. Please create at least one more file system location using the Location Management 'Add' command.**

Explanation No second location is defined that can be used as destination location for the move command .

Action Create a second location and then start this command again.

INOAAE0605 **Wrong date or date format. Format 'datepattern' required.**

Explanation An invalid date is specified or an invalid date format is used.

Action Specify a valid date (use same format as used in 'argbatch show backups').

INOAAE0608 **No other Tamino version installed, set version not possible**

Explanation Because there is no other Tamino version installed, it makes no sense to change the version.

Action No action required.

INOAAE0611 **Named pipe path does not exist**

Explanation The named pipe with the specified path does not exist.

Action Specify an existing named pipe path.

INOAAE0619 **Device path is not a named pipe**

Explanation The specified path is not a named pipe.

Action Specify an existing named pipe path.

INOAAE0637 **Directory name 'path' not compatible with object identification 'name'**

Explanation The directory name must consist of the first part of the object identification.

Action Create a new server extension package with the correct directory name.

INOAAE0638 **Server extension function 'name' does not exist**

Explanation The specified server extension function does not exist.

Action Correct the function name.

INOAAE0639 **Server extension function parameter 'name' does not exist**

Explanation The specified server extension function parameter does not exist.

Action Correct the parameter name.

INOAAE0641 **Internal error from DSIF interface name returncode returncode error number errornr**

Explanation This is an internal error message.

Action Please contact your software supplier.

INOAAE0645 **Stop of XML session 'session' failed**

Explanation Errors occurred while stopping the specified XML session.

Action Try to detect the error, otherwise contact your software supplier.

INOAAE0646 **Error reading backup methods for database dbname**

Explanation No backup methods were found in the internal configuration store for the database.

Action Please contact your software supplier.

INOAAE0648 **Error reading parameters of backup method 'method'**

Explanation No parameters were found for the backup method in the internal configuration store.

Action Please contact your software supplier.

INOAAE0651 **Could not set global parameters for external backup method 'method' of database dbname**

Explanation Setting of global parameters failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0653 **Could not set configuration parameters for external backup method 'method' of database dbname**

Explanation Setting of configuration parameters failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0656 **Could not delete configuration 'configuration' of method 'method' of database dbname**

Explanation The deletion of the configuration failed.

Action Please contact your software supplier.

INOAAE0658 **Error reading configurations for database dbname of backup method 'method'**

Explanation An error occurred while reading the configuration data.

Action Please contact your software supplier.

INOAAE0659 **No configuration found for database dbname of backup method 'method'**

Explanation No configuration data was specified for this method and database.

Action Specify configuration data for this method and database using the 'External Backup Environment' dialog.

INOAAE0660 **Replication database name expected**

Explanation The replication database name must be specified for this function.

Action Specify the replication database name

INOAAE0662 **The database replication_db cannot be added into the permission list**

Explanation An error occurred while adding the replication database name to the permission list.

Action Check the subsequent error messages for more details.

INOAAE0665 **Database database cannot be set as replication database**

Explanation An error occurred during the type change. The database cannot be set to a replication database. Possible reason: This database is a master database.

Action Check for related additional messages.

INOAAE0667 **Replication database database cannot be reset to normal type**

Explanation The database cannot be reset to a normal database.

Action See the subsequent error messages.

INOAAE0668	**Database master_database is not active or is not a master database**
Explanation	The master database must be in the active state or permit this database to be replicated.
Action	Start up the master database and check the permission list for replication databases.

INOAAE0669	**Replication of master database master_database is not permitted**
Explanation	Permission to replicate the master database was denied.
Action	Ask the administrator to permit replication access to the master database.

INOAAE0672	**Not enough space at location newLoc for additional newsize MB - maximum free is freesize MB**
Explanation	The new location to which the database space should be moved or added is not big enough.
Action	Choose a larger location for the database space operation.

INOAAE0680	**Backup(s) not found wrongbackups please use one of the following backups**
Explanation	Wrong backups were specified.
Action	Use only valid backups of the database. You can see all backups with the command "argbatch show backups database=mydatabase".

INOAAE0681	**At least one backup must be given or don't use keepbackups**
Explanation	For the option keepbackups, at least one backup must be given/selected.
Action	Give/select at least one backup.

INOAAE0683	**Switching log space for database dbName has failed**
Explanation	Errors occurred while switching log space for the database.
Action	Try to detect the error, otherwise contact your software supplier.

INOAAE0684	**At least one destination directory must be given with parameter "destinationdirectory_0"**
Explanation	the option "keep backup files" needs at least one destination directory.
Action	Specify a destination directory with the parameter "destinationdirectory_0".

INOAAE0685 **For option "keepbackups=selected" at least one backup date and at least one destination directory must be given with parameter "destinationdirectory_0", "backupdate_0"**

Explanation Give at least one backup date and one destination directory in the parameter list.

Action Use the parameter "backupdate_0" to specify a backup to be kept and "destinationdirectory_0" for the destination directory.

INOAAE0691 **Could not add backup method 'method' for database dbname**

Explanation Adding the backup method failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0694 **Could not delete method 'method' of database dbname**

Explanation Deleting the backup method failed because of an internal configuration store error.

Action Please contact your software supplier.

INOAAE0696 **Internal error errno during modify property 'name' to 'value'**

Explanation An error occurred while setting a new property value.

Action Please contact your software supplier.

INOAAE0699 **Deletion of backup 'bckDate' of database dbName failed**

Explanation An error occurred while deleting the specified backup.

Action Check the additional messages.

INOAAE0707 **No permission to modify the type of the database**

Explanation To change the type of a database to a replication database or to set it back to a normal one, the user needs to have administrator rights. Other possible reason: The database is not allowed to replicate the master database.

Action Log in as administrator and try the operation again and check whether this database is in the permission list of the master database.

INOAAE0708 **Update server sessions exist**

Explanation The database has already update sessions so that it cannot be used to replicate another database.

Action Use a newly created database and retry this operation.

INOAAE0709 **Passwords not matched**

Explanation The passwords entered do not match.

Action Please ensure the passwords match.

INOAAE0725 **Error while changing port ranges**

Explanation An error occurred while changing the port ranges.

Action Please contact you software supplier.

INOAAE0727 **path is not a raw section**

Explanation The specified path must be a raw section.

Action Ensure that the path specifies a raw section.

INOAAE0728 **Unable to load data for CD databases**

Explanation This database is a CD database. Data load not possible.

Action No action required.

INOAAE0731 **Rename web server failed**

Explanation The web server could not be renamed, the operation failed.

Action The reason why the web server could not be renamed is in the job log. Check it and retry.

INOAAE0733 **Add web server failed**

Explanation The web server could not be added, the operation failed.

Action The reason why the web server could not be added is in the job log. Check it and retry.

INOAAE0737 **Delete web server failed**

Explanation The web server could not be deleted, the operation failed.

Action The reason why the web server could not be deleted is in the job log. Check it and retry.

INOAAE0740	**Modify web server failed**
Explanation	The web server could not be modified, the operation failed.
Action	The reason why the web server could not be modified is in the job log. Check it and retry.

INOAAE0741	**Domain 'name' does not exist**
Explanation	Domain has not been defined.
Action	Please check the defined domains list in Tamino and create the domain if necessary.

INOAAE0744	**parameter name: must not be a location on a raw section, is only allowed on DATA, INDEX, JOURNAL and RESERVED location**
Explanation	A location on raw section is only allowed as DATA, INDEX, JOURNAL and RESERVED location.
Action	Use a location that is not located on a raw section.

INOAAE0745	**All reserved locations are located on raw section(s), at least one location must not be located on a raw section**
Explanation	At least one reserved location for a database must not be on a raw section.
Action	Use at lease one location not located on a raw section.

INOAAE0746	**Location locname is of type type, this type is not allowed for loctype**
Explanation	Some location types are only allowed for special locations. For example locations on a tape are only allowed for backup locations.
Action	Use a location which is allowed for the current location type.

INOAAE0747	**Not allowed to set a location of type 'type' as default backup location**
Explanation	The default backup location cannot be in a location of type "raw".
Action	Use a location of a type that is allowed for a backup location.

INOAAE0749	**This command is deprecated. Please use the new command "show acls".**
Explanation	The command has been replaced by a new command.
Action	Please use the new command.

INOAAE0750 **This command is deprecated. Please use the new command "show groups".**

Explanation The command is deprecated.

Action Please use the new command.

INOAAE0753 **Query internal configuration store key key failed**

Explanation An error occurred when querying the given internal configuration store key.

Action Please contact your software supplier.

INOAAE0754 **This command is deprecated. Please use the new command "show users".**

Explanation The command is deprecated.

Action Please use the new command.

INOAAE0755 **Access to internal configuration store value value key key failed**

Explanation An error occurred when getting the given internal configuration store key value.

Action Please contact your software supplier.

INOAAE0761 **parameter name: must be the logical name of an existing location**

Explanation The parameter must specify the short, "logical" name of a location (not its entire path), and the location must exist.

Action Display the the "Locations" tree node in the System Management Hub (under the "Tamino" node) to display a list of existing locations or to add a new location.

INOAAE0762 **parameter name: must contain only digits 0 to 9**

Explanation The value for this parameter must be an integer number with no fractional parts.

Action Re-enter the parameter using only digits 0-9.

INOAAE0763 **parameter name: must be "yes" or "no"**

Explanation This parameter must have either the value "yes" or "no", all lowercase characters.

Action Re-enter either "yes" or "no" (without the double quotes).

INOAAE0764 **parameter name: must only contain digits 0-9, comma, dot, "E" or "e" for exponentiation**

Explanation The value for this parameter must be a valid floating point number, or a number with an exponent.

Action Re-enter he parameter value as floating point number, or with an exponent. Depending on the locale settings on the local computer, the decimal sign may be expected either as "," or as a ".".

INOAAE0766 **Size for space type extent extend is missing and no default size available**

Explanation No default size could be obtained for this space type.

Action A size must be specified, and it must be above the minimum value for this space type.

INOAAE0767 **The size specified for space type extent extend is under the minimum (minimum size Mb)**

Explanation The given size for the extent is too small.

Action A size of at least the given minimum must be specified.

INOAAE0768 **At least one backup location must be in the filesystem if no tape is supplied as initial backup**

Explanation If no tape is supplied to create the database from (in the "Create From Backup" command) the initial backup is created at creation time as a file and requires a location that is in the file system. Before this message was issued, attempts were made to create it in one of the provided backup locations, in the default backup location and in the default location.

Action Create a location in the file system using the "Add" command the System Management Hub browser interface, tree node Tamino/DB Locations and make it the default location (by clicking the new location and executing the "Set Default" command).

INOAAE0769 **At least one backup location is required for the initial backup of the new database**

Explanation Specify one or more location where backups shall be created later on. This location is already required and used during the creation of the new database.

Action Specify one or more writable, random accessible backup locations for the database to be created

INOAAE0774 **Database version with compatibility level of CD database not installed or found**

Explanation A Tamino of the same compatibility level of CD database must be installed to use the CD database

Action Install a database of the same compatibility level.

INOAAE0775 **Database name contains invalid character "*" (asterisk)**

Explanation A database name cannot contain the "*" character.

Action Remove the "*" from the database name.

INOAAE0776 **This command is deprecated. Please use the new command "show users".**

Explanation This command is not supported as the user descriptions can be seen in the results of the new command.

Action Please do not use this command and use the new one instead.

INOAAE0778 **Database name contains invalid character "/" (slash)**

Explanation A database name cannot contain "/" character.

Action Remove the "/" from database name.

INOAAE0779 **Port address 'buf' is invalid. Valid range is 0 - 65535.**

Explanation The specified port address is not valid.

Action Specify a valid port address in the range 0 to 65535.

INOAAE0784 **Database name contains invalid character "<" (less than)**

Explanation A database name cannot contain the "<" character.

Action Remove the "<" from database name.

INOAAE0785 **Database name contains invalid character ">" (greater than)**

Explanation A database name cannot contain the ">" character.

Action Remove the ">" from database name

INOAAE0786 **This command is deprecated. Please use the new command "show acesofacl".**

Explanation The command is deprecated.

Action Please use the new command.

INOAAE0787 **Domain parameters missing**

Explanation Some or all of the necessary parameters for the domain creation/modification are missing.

Action Please ensure that all necessary domain parameters are defined.

INOAAE0788 **Unrecognized domain parameters**

Explanation The domain parameters defined are not valid for the domain type being created/modified.

Action Please ensure that the correct domain parameters for the domain type being created/modified are defined.

INOAAE0792	**Namespace declarations required. Please check that all namespaces are defined.**
Explanation	There are some namespace prefixes for which no namespace declarations have been defined.
Action	Please ensure namespace declarations exist for all namespace prefixes.

INOAAE0794	**Internal error occurred**
Explanation	Internal error code 41 occurred.
Action	Please contact your software supplier.

INOAAE0797	**Domain 'name' already exists**
Explanation	A domain with the same name exists.
Action	Please choose another name.

INOAAE0798	**Failed to open input file filename for data load**
Explanation	The file cannot be opened or does not exist.
Action	Check the input and start the operation again.

INOAAE0799	**Parameter 'newname' or 'new_name' missing. The 'new_name' parameter is deprecated, please use the 'newname' parameter for the new name of the database.**
Explanation	No parameter with the new name of the database was given.
Action	Provide the database name using the parameter 'newname'.

INOAAE0802	**Could not connect to inodmn. Port number not found in internal configuration store, probably not installed.**
Explanation	The Software AG EventLayer Service is not installed correctly.
Action	Try re-installing the System Management Hub. Check for a fix or an update from your software supplier.

INOAAE0803	**Could not connect to inodmn, service not running**
Explanation	The "Software AG EventLayer Service" is not running, database functions and commands are probably unaffected.
Action	Restart the service. If the problem persists, contact your software supplier for an update or fix.

INOAAE0807 **Invalid parameter name 'name' specified.**

Explanation The parameter name specified is not valid since it contains one or more space characters.

Action Specify a parameter name that does not contain space characters.

INOAAE0812 **Web server IP address 'ipAddress' is invalid**

Explanation The specified web server IP address is invalid.

Action Specify a valid IP address. The valid range is 0 - 255.

INOAAE0817 **No license for raw section support**

Explanation The use of raw sections requires an appropriate license option.

Action Contact your software supplier for a license option to support raw sections.

INOAAE0818 **No raw section support for the used platform**

Explanation There is no raw section support for the used platform.

Action Do not use raw sections.

INOAAE0819 **Raw section support internal error**

Explanation There was an internal error while processing a raw section.

Action Please contact your software supplier.

INOAAE0820 **Raw section initialization failed**

Explanation An error occurred while initializing a raw section.

Action Check the raw section.

INOAAE0825 **Master database must be restarted before a replication database can be set up**

Explanation A restart of the master database is necessary.

Action Restart the master database and try to set up the replication database again.

INOAAE0826 **Inconsistency detected while setting the database to replication type**

Explanation This database is not suitable to be set as the replication database of the specified master database. Perhaps the versions are not identical or this one was not created from the backup of the master. Also possible is that this database has its own updates after the creation.

Action Use another database to replicate the master.

INOAAE0831 **Only one location specified for parallel backup**

Explanation More than one location is required for parallel backup.

Action Please specify more than one location for the parallel backup.

INOAAE0832 **Renaming a replication database master is not allowed.**

Explanation Renaming a replication database master is not allowed, because the link between the master and replication databases would be lost.

Action No action required.

INOAAE0834 **Database is a replication database master database. Deleting the replication database master is not allowed. No replication databases can be updated from this master database if this database is deleted.**

Explanation Deleting this master database would mean that no replication databases could be updated from this master database. If you really want to delete this replication master database use the "force=yes" parameter for argbatch or check the "Force Delete of Replication Master Database" checkbox in the GUI.

Action Use the "force=yes" parameter for argbatch or check the "Force Delete of Replication Master Database" checkbox in the GUI.

INOAAE0835 **Data load for database dbName failed**

Explanation Load of data failed with error.

Action Check the other related messages for more information.

INOAAE0836 **Unload data from database dbName failed**

Explanation An error occurred while data was being unloaded from the database.

Action Check for other messages related to this error for possible reasons.

INOAAE0837 **Location path path is read only**

Explanation The location path specified is read only.

Action Specify a location path with write access.

INOAAE0838 **Server extension does not contain a function**

Explanation It was detected that no function has been defined for the server extension. Such a server extension is considered as invalid.

Action Extend your server extension by at least one function.

INOAAE0841 **Uninstall of server extension name aborted**

Explanation The uninstall operation for the server extension has not been completed due to functions that are used in some schema.

Action Restart the uninstall operation with the parameter "force" set to "yes" (batch command).

INOAAE0842 **Uninstall of server extension 'name' failed**

Explanation The uninstall operation failed.

Action Check the job log to find the reason for the failure.

INOAAE0843 **Please specify either parameter IP address or node**

Explanation The specification of the IP address or node is invalid.

Action Please specify either the IP address or the node.

INOAAE0844 **Unable to find the replication database name from the permission list**

Explanation The replication database name is not in the permission list.

Action Check the parameter.

INOAAE0845 **Please specify either parameter IP address or node**

Explanation Either the parameter IP address or node must be specified.

Action Please specify either the parameter IP address or node.

INOAAE0846 **Upgrade from this database to Vversion not possible**

Explanation This error occurs because the database cannot be upgraded directly to the target version.

Action Upgrade to the next higher version and after that try a "set version" to the target version.

INOAAE0847 **Named pipe path not allowed for the specified location type**

Explanation A named pipe is not allowed to set for the specified target location. Only the backup location type accepts named pipes.

Action Specify another location for the target location.

INOAAE0849 **Cannot open event log session**

Explanation Open event log session on argevsrv failed.

Action Check that argevsrv is running.

INOAAE0850 **parameter name: must be of type FileSystem or RAW Section**

Explanation Data, Index and Journal location must be of type FileSystem or RAW Section.

Action Use a location of type FileSystem or RAW Section.

INOAAE0852 **This command is deprecated. Please use the new command "inoload".**

Explanation This command is set to deprecated, use the new command instead.

Action Use inoload to load or unload data in batch mode.

INOAAE0855 **Output directory directory does not exist**

Explanation The output directory should exist.

Action Create the output directory or check the permission if it already exists.

INOAAE0868 **Stop request requestid failed :errortext**

Explanation Stop of a request failed.

Action Check the error text for an explanation of why the operation failed.

INOAAE0870 **Query current active requests failed : message**

Explanation A query of the current requests failed.

Action Check the error message for more information.

INOAAF0002 **Version 'version' of Tamino not found. Please use 'set version' command to change the version to the installed version.**

Explanation The specified Tamino version was not found.

Action Use the "set version" command and change the version of the database.

INOAAF0007 **Cannot create database: reason**

Explanation A database cannot be created with the parameters specified.

Action Alter specified parameter value or provide missing parameter.

INOAAF0253 **Error reading savepoints for database dbname**

Explanation An error occurred when reading database savepoint entries in the internal configuration store.

Action Please contact your software supplier.

INOAAF0254 **Could not create XML document**

Explanation An error occurred when creating an XML document.

Action Reboot and restart the system.

INOAAF0256 **Open of event log failed**

Explanation An error occurred when creating an event session.

Action Check the event demon.

INOAAF0262 **Error reading database locations for savepoint 'savepoint'**

Explanation No database locations were found in the internal configuration store for the savepoint.

Action Please contact your software supplier.

INOAAF0264 **Duplicate parameter name parameter**

Explanation The parameter appears more than once in the parameter list, but only a single value is allowed.

Action Check where the parameter given is repeated and issue the command again without it.

INOAAF0265 **Job initialization failed**

Explanation The job log could not be initialized because of insufficient resources. This could be memory or SMP resources like locks or threads.

Action Free resources and retry.

INOAAF0267 **Rename database failed**

Explanation The database could not be renamed.

Action The reason why the database could not renamed is in the job log. Check it and retry.

INOAAF0369 **TSM@DLL *** FATAL ERROR NO ROLLBACK POSSIBLE (SESSION LOST) ***

Explanation Tamino reported an invalid session ID.

Action Shut down the database and restart it.

INOAAI0000 **Change License file**

Explanation Change license file.

Action No action required.

INOAAI0003 **Modify journal space of database dbname**

Explanation The size of the journal space is being modified.

Action No action required.

INOAAI0005 **Modify journal space successfully finished**

Explanation This message indicates that the "Modify journal space" function completed successfully.

Action No action required.

INOAAI0006 **Modification and reorganization of journal space in location Location from oldsize MB to one journal space of newsize MB**

Explanation The journal space size is being modified at the given location. If more the one journal space exists, the journal space is reorganized to one of the given size.

Action No action required.

INOAAI0008 **Modify properties of Email notification**

Explanation Email notification properties are being modified.

Action No action required.

INOAAI0009 **Add location name at path**

Explanation Start of the "add location" function.

Action Information message, no action required.

INOAAI0010 **Delete location name**

Explanation Start of the "delete location" function.

Action Information message, no action required.

INOAAI0011 **Moving location oldloc to newloc**

Explanation Start of the "move location" function.

Action Information message, no action required.

INOAAI0012 **Rename location name to newname**

Explanation Start of the "rename location" function.

Action Information message, no action required.

INOAAI0013 **Set location name as default database location**

Explanation Start of the "set default location" function.

Action Information message, no action required.

INOAAI0014 **Set location name as default backup database location**

Explanation Start of the "set default backup location" function.

Action Information message, no action required.

INOAAI0015 **Modify default of database location category 'category'**

Explanation Start of the "modify default of database location category" function.

Action Information message, no action required.

INOAAI0016 **Database Version set to version**

Explanation The database was set to the specified version.

Action Information message, no action required.

INOAAI0017 **Modify Email notification properties successfully finished**

Explanation Email notification properties have been modified successfully.

Action No action required.

INOAAI0021 **Unregistering database dbName**

Explanation This is a job log identification message.

Action No action required.

INOAAI0023 **New license file sucessfully applied.**

Explanation The license file was successfully applied.

Action No action required.

INOAAI0025 **Please log in again to the web application in order to use the new product license!**

Explanation The new functionality is available after you log in again.

Action Log in again and restart your web applications.

INOAAI0028 **Confirmed all pending alerts**

Explanation All warnings, errors and fatal errors of the job records specified have been acknowledged.

Action No action required.

INOAAI0033 **New value of dynamic property 'name' is effective now**

Explanation The property value has been updated and is active from now on.

Action No action required.

INOAAI0035 **Database has been successfully unregistered**

Explanation This message indicates, that the "Unregister Database" function is completed.

Action No action required.

INOAAI0037 **Pending alerts of all jobs have been confirmed**

Explanation All warnings, errors and fatal errors have been confirmed. The job records may be deleted now.

Action No action required.

INOAAI0048 **Server extension command execution**

Explanation This is an informational message.

Action No action required.

INOAAI0049 **Command Name : name**

Explanation This message specifies the command name of a server extension.

Action No action required.

INOAAI0050 **Collection Name : name**

Explanation This message specifies the collection name of an XML document.

Action No action required.

INOAAI0051 **Master database set to masterdb**

Explanation The database named is the master database.

Action No action required.

INOAAI0063 **Tamino will close the current log space extent and open a new one when the current log space block has been filled up**

Explanation Tamino writes log information in blocks. When the currently used block has been filled up completely, Tamino will close the current log space extent and open a new one. As a consequence, you might encounter a minimal growth of the current log space before a new one is created.

Action No action required.

INOAAI0148 **The name 'location_name' is not the name of an existing location; the default location is used instead**

Explanation An invalid location name was specified or extracted from a backup. It could be a valid location on the host where the backup was created.

Action No action required. The location defined as default in the location management will be used.

INOAAI0152 **No item selected for modification**

Explanation No item was selected to be modified.

Action Select an item and retry.

INOAAI0160 **Delete database space of database dbname**

Explanation The database space with the highest extent is being deleted. The deletion will not proceed when the space is in use.

Action No action required.

INOAAI0161 **Delete database space successfully finished**

Explanation This message indicates that the "Delete database spaces" function completed successfully.

Action No action required.

INOAAI0163 **Expand database space of database dbname**

Explanation The last database space is being expanded.

Action No action required.

INOAAI0164 **Expand database space successfully finished**

Explanation This message indicates that the "Expand database spaces" function completed successfully.

Action No action required.

INOAAI0167 **Deleting database space spaceNo from location Location**

Explanation The specified database space is being deleted from the given location.

Action No action required.

INOAAI0168 **Expanding database space spaceNo in location Location from oldsize MB to newsize MB**

Explanation The specified database space is being expanded at the given location.

Action No action required.

INOAAI0176 **Restoring of database dbName without further recovery successfully completed**

Explanation The specified database has been restored successfully. Changes that occurred later than the backup time were not reapplied.

Action No action required.

INOAAI0211 **Data load in collection collectionname**

Explanation Data has been loaded into the named collection.

Action No action required.

INOAAI0227 **Data unload from collection collectionname**

Explanation Data will be unloaded into the named collection.

Action No action required.

INOAAI0237 **mvcount spaces successfully moved from oldloc to newloc**

Explanation The specified number of spaces were moved from one location to another one.

Action Information message, no action required.

INOAAI0248 **Document path : path**

Explanation This message specifies the path name of an XML document.

Action No action required.

INOAAI0249 **Query string : text**

Explanation This message specifies the query string to retrieve XML documents.

Action No action required.

INOAAI0250 **Schema name : name**

Explanation This message specifies the schema name of a XML Document.

Action No action required.

INOAAI0269 **Execution of command 'name' successful**

Explanation A server extension command was successfully executed.

Action No action required.

INOAAI0273 **Location locCount : locName**

Explanation This is an informational message for one default database location of the category.

Action Information message, no action required.

INOAAI0275 **No pending alerts found**

Explanation An attempt was made to confirm all pending alerts, but no job with pending alerts was found. Either there are no alerts in the display, or the alerts in the display have been confirmed meanwhile by someone else.

Action No action required.

INOAAI0276 **When all pending alerts are confirmed, the "Pending Alerts" folder is cleared. Each individual job is still in the "Running Jobs" or in the "Completed Jobs" folder until it is deleted by automatic cleanup; up to that point, the warning, error and alert messages are still visible in the single job view.**

Explanation No job or message is really removed when alerts are confirmed; they are just moved away from the Alerts folder.

Action No action required

INOAAI0277 **When a job record is deleted, it is removed from the job log and its disk file is deleted. Jobs that are not completed (i.e. stopped or still running) and jobs that have unconfirmed alert messages are not deleted and remain in their respective folders.**

Explanation Only finished jobs with no pending alerts are deleted.

Action No action required

INOAAI0280 **Object Identification : text**

Explanation The given text provides the object identification of the server extension.

Action No action required.

INOAAI0286 **Execution type: type**

Explanation The specified type is the selected server extension execution type.

Action No action required.

INOAAI0288 **Backing up all server extensions for database 'name'**

Explanation All server extensions in the specified database are being backed up.

Action No action required.

INOAAI0289 **Backup of all server extensions successful**

Explanation All server extensions have been backed up successfully.

Action No action required.

INOAAI0290 **Restoring server extension for database 'name'**

Explanation A server extension of the specified database is being restored.

Action No action required.

INOAAI0291 **Restore of server extension 'name' successful**

Explanation The specified server extension has been restored successfully.

Action No action required.

INOAAI0292 **Restoring all server extensions for database 'name'**

Explanation All server extensions of the specified database are being restored.

Action No action required.

INOAAI0293 **Restore of all server extensions successful**

Explanation All server extensions have been restored successfully.

Action No action required.

INOAAI0299 **Storing binary file 'path'**

Explanation A binary file is being stored in the database.

Action No action required.

INOAAI0300 **Restoring binary file 'path'**

Explanation A binary file is being restored from the database.

Action No action required.

INOAAI0301 **Removing binary file 'path'**

Explanation A binary file is being removed from the database.

Action No action required.

INOAAI0303 **Command log switched mode buffers buffers**

Explanation This is a result message for a batch command.

Action No action required.

INOAAI0308 **Update of settings successful : name**

Explanation The update of the given settings parameter value was successful.

Action No action necessary.

INOAAI0316 **Backing up server extension for database 'name'**

Explanation A server extension in the specified database is being backed up.

Action No action required.

INOAAI0317 **Backup of server extension 'name' successful**

Explanation The specified server extension has been backed up successfully.

Action No action required.

INOAAI0318 **Deleting document : name**

Explanation The XML document will be deleted.

Action No action necessary.

INOAAI0319 **No mapped document : name**

Explanation No XML document is mapped to the server extension.

Action No action necessary.

INOAAI0320 **Trace server extensions in database 'name'**

Explanation The server extension trace mode is changed in the specified database.

Action No action required.

INOAAI0321 **Trace switched on successfully**

Explanation The server extension trace is switched on.

Action No action required.

INOAAI0322 **Trace switched off successfully**

Explanation The server extension trace is switched off.

Action No action required.

INOAAI0323 **Store server extensions in database 'name'**

Explanation The storing of server extension files is changed to the specified database.

Action No action required.

INOAAI0324 **Store server extension files switched on successfully**

Explanation The storing of server extension files is switched on.

Action No action required.

INOAAI0325 **Store server extension files switched off successfully**

Explanation The storing of server extension files is switched off.

Action No action required.

INOAAI0326 **Analyze object for a new server extension**

Explanation The object for a new server extension will be analyzed.

Action No action required.

INOAAI0327 **Object File : path**

Explanation This specifies the object file for the new server extension.

Action No action required.

INOAAI0328 **Analysis of new server extension object successful**

Explanation The analysis of the object for the new server extension was successful.

Action No action required.

INOAAI0329 **Remove server extension object**

Explanation The object of a new server extension will be removed.

Action No action required.

INOAAI0330 **Select function for a new server extension**

Explanation The function for a new server extension will be selected.

Action No action required.

INOAAI0331 **Select function for a new server extension successful**

Explanation The function for a new server extension was successfully selected.

Action No action required.

INOAAI0332 **Display trace state successful**

Explanation The server extension trace state is displayed successfully.

Action No action required.

INOAAI0333 **Create Database from Backup**

Explanation Button Create Database from Backup

Action none

INOAAI0357 **Access Control List 'name' created**

Explanation A new access control list has been created. Details are generally provided in other messages.

Action No action required.

INOAAI0358 **User group 'name' created**

Explanation A new user group has been created.

Action No action required.

INOAAI0360 **User 'name' created**

Explanation A new user has been created. Details are generally provided in other messages.

Action No action required.

INOAAI0364 **Access control list 'name' modified**

Explanation The current ACL has been modified.

Action No action required.

INOAAI0365 **User group 'name' modified**

Explanation The user group has been modified.

Action No action required.

INOAAI0366 **User 'name' modified**

Explanation The user has been modified.

Action No action required.

INOAAI0368 **Access control element 'name' added to the access control list**

Explanation An ACE has been added successfully to an ACL.

Action No action required.

INOAAI0374 **Access control list 'name' deleted**

Explanation The access control list has been deleted.

Action No action required.

INOAAI0375 **User 'name' deleted**

Explanation The user has been deleted.

Action No action required.

INOAAI0376 **User group 'name' deleted**

Explanation The user group has been deleted.

Action No action required.

INOAAI0406 **Shutdown of all active databases completed**

Explanation All active databases are about to shut down, or they are already inactive.

Action No action required.

INOAAI0407 **All autostart databases checked**

Explanation All databases with autostart parameter set have been started.

Action No action required.

INOAAI0410 **op of operation done**

Explanation This message provides information about operation progress.

Action No action required

INOAAI0424 **New value : text**

Explanation This describes a new value for a Java public or private classpath.

Action No action required.

INOAAI0425 **Starting autostart databases of version version**

Explanation Databases with the autostart parameter set to 'yes' are being started.

Action No action required.

INOAAI0426 **Stopping all active databases of version version**

Explanation Active databases are being stopped

Action No action required.

INOAAI0429 **Confirming all alerts**

Explanation Fatal error, error and warning messages are being confirmed. Once all alerts are confirmed, a job will be scheduled for cleanup (will be removed later), or it can be delete explicitly as a single job or along with all completed jobs.

Action No action required.

INOAAI0431 **Deleting all completed jobs**

Explanation All jobs without unconfirmed alerts are being deleted.

Action No action required.

INOAAI0432 **All job records of completed jobs successfully deleted by user (except jobs with pending alerts)**

Explanation Deleted job records will not appear in the job monitor list any more; the corresponding files have been deleted on disk.

Action No action required.

INOAAI0445 **Setting version for database 'dbName'**

Explanation Set the version of a specific database.

Action Data must be unloaded and loaded into a new database manually.

INOAAI0446 **No property has been modified. All properties already set to the given values.**

Explanation A property will be changed when the new property value is different from the value stored in the internal configuration store.

Action No action required.

INOAAI0448 **'param' has been changed from 'oldValue' to 'newValue'**

Explanation A database property was changed successfully by the "modify property" command.

Action No action required.

INOAAI0451 **Adding database space for database dbName**

Explanation This message indicates the beginning of the execution of the "Add database spaces" function.

Action No action required.

INOAAI0452 **Add database space successfully finished**

Explanation This message indicates that the "Add database spaces" function completed successfully.

Action No action required.

INOAAI0454 **Moving database space for database dbName**

Explanation This message indicates the beginning of the execution of the "Move database spaces" function.

Action No action required.

INOAAI0455 **Move database space successfully finished**

Explanation This message indicates that the "Move database spaces" function completed successfully.

Action No action required.

INOAAI0457 **Creating database dbName**

Explanation This message indicates the beginning of the execution of the "Create Database" function.

Action No action required.

INOAAI0458 **Create database successfully finished**

Explanation This message indicates that the database was created successfully.

Action No action required.

INOAAI0460 **Deleting database dbName**

Explanation This message indicates the beginning of the execution of the "Delete Database" function.

Action No action required.

INOAAI0461 **Database has been successfully deleted**

Explanation This message indicates that the "Delete Database" function completed successfully.

Action No action required.

INOAAI0465 **Start of database dbName successful**

Explanation This message indicates that the specified database has been started successfully.

Action No action required.

INOAAI0467 **Stop of database dbName successful**

Explanation This message indicates that the specified database has been stopped successfully.

Action No action required.

INOAAI0468 **Backup of database dbName**

Explanation This message indicates that a backup of the specified database is being created.

Action No action required.

INOAAI0469 **Restore database dbName using backup 'bckDate' with recovery**

Explanation This message indicates the beginning of the execution of a database restore function with a database recovery based on the log spaces.

Action No action required.

INOAAI0470 **Restore database dbName using backup 'bckDate' without recovery**

Explanation This message indicates the beginning of the execution of a database restore function without a database recovery based on the log spaces.

Action No action required.

INOAAI0471 **Backup of database dbName successfully completed**

Explanation This message indicates that the specified database has been backed up successfully.

Action No action required.

INOAAI0476 **Restoring and recovering of database dbName successfully completed**

Explanation The specified database has been restored and recovered successfully.

Action No action required.

INOAAI0477 **Moving database space spaceNo from location oldLoc to newLoc**

Explanation A database space is being moved from one location to another.

Action No action required.

INOAAI0479 **Adding size MB database space to location newLoc**

Explanation The specified database space is being added to the given location.

Action No action required.

INOAAI0484 **Uninstalling all server extensions in database 'name'**

Explanation All server extensions in a database are being uninstalled from the specified database and the file system. If a restore is being performed the server extensions will be recovered from the backup database.

Action No action required.

INOAAI0490 **Modify database properties successfully finished**

Explanation Database properties have been modified successfully.

Action No action required.

INOAAI0492 **Modify properties for database dbName**

Explanation Database properties are being modified.

Action No action required.

INOAAI0493 **Restore database dbName using backup 'bckDate' with partial recovery**

Explanation A database restore function with partial recovery has been started.

Action No action required.

INOAAI0494 **Checking and repairing database dbName**

Explanation A function to check and repair the database has been started.

Action No action required.

INOAAI0495 **Check and repair of database dbName finished successfully**

Explanation The check and repair function was successfully applied to the specified database, i.e. the recreation of the indices was successful.

Action No action required.

INOAAI0497 **help**

Explanation This is a standard information message to show the server version in space and property commands.

Action No action required.

INOAAI0501 **Uninstall of all server extensions successful**

Explanation All server extensions in a database have been uninstalled successfully. This is an informational message.

Action No action required.

INOAAI0502 **Registering Java class 'path'**

Explanation The installation count for the Java class is added to the internal configuration. This is an informational message.

Action No action required.

INOAAI0505 **Function name: 'name'**

Explanation This is the name of a server extension function. This is an informational message.

Action No action required.

INOAAI0506 **External name: 'name'**

Explanation This is the external name of a server extension function. This is an informational message.

Action No action required.

INOAAI0511 **Parameter 'para' not valid**

Explanation The specified parameter is not valid for the current command.

Action Check the spelling of the parameter. If the spelling is correct, check whether the parameter is valid in the current context.

INOAAI0514 **message**

Explanation This is an informational message about a server extension document that has been returned from the Tamino server.

Action No action required.

INOAAI0515 **Listing server extensions in database 'name'**

Explanation A list of all installed server extensions for the specified database is being generated.

Action No action required.

INOAAI0516 **Installing server extension in database 'name'**

Explanation A new server extension is being installed in the specified database.

Action No action required.

INOAAI0517 **Package file: path**

Explanation The specified path is the pathname of the packed server extension file.

Action No action required.

INOAAI0518 **Execution mode: mode**

Explanation The specified mode is the selected server extension execution mode.

Action No action required.

INOAAI0519 **Installation of server extension 'name' successful**

Explanation The specified server extension was installed successfully.

Action No action required.

INOAAI0520 **Uninstalling server extension from database 'name'**

Explanation A server extension is being uninstalled from the specified database.

Action No action required.

INOAAI0521 **Server extension name: 'name'**

Explanation This message specifies the name of a server extension.

Action No action required.

INOAAI0522 **Uninstall of server extension 'name' successful**

Explanation The specified server extension has been uninstalled successfully.

Action No action required.

INOAAI0523 **Modifying server extension in database 'name'**

Explanation A server extension in the specified database is being modified.

Action No action required.

INOAAI0524 **Modification of server extension 'name' successful**

Explanation The specified server extension has been modified successfully.

Action No action required.

INOAAI0525 **Deleting help URL 'path'**

Explanation The specified help file for a server extension is being deleted.

Action No action required.

INOAAI0526 **Executing command 'call'**

Explanation The specified operating system command is being executed.

Action No action required.

INOAAI0527 **De-registering server extension DLL 'path'**

Explanation The specified server extension DLL file is being de-registered.

Action No action required.

INOAAI0528 **Deleting server extension DLL 'path'**

Explanation The specified server extension DLL file is being deleted.

Action No action required.

INOAAI0529 **Deselect function of a new server extension**

Explanation A selected function for a new server extension is being deselected. This is an informational message.

Action No action required.

INOAAI0530 **Extracting entry 'name'**

Explanation An entry is being extracted from a packed file.

Action No action required.

INOAAI0531 **Inserting document 'path'**

Explanation The URL of a help file for a server extension is being inserted into the server extension's installation document.

Action No action required.

INOAAI0532 **Registering DLL 'path'**

Explanation A server extension DLL file is being registered.

Action No action required.

INOAAI0533 **DLL 'path' already registered**

Explanation The specified server extension DLL file is already registered.

Action No action required.

INOAAI0535 **Deleting file 'name'**

Explanation The specified server extension installation file is being deleted.

Action No action required.

INOAAI0536 **Deleting directory 'path'**

Explanation The specified server extension installation directory is being deleted.

Action No action required.

INOAAI0537 **Showing server extension attributes in database 'name'**

Explanation The attributes of a server extension in the specified database are being listed.

Action No action required.

INOAAI0538 **Setting access rights for server extension in database 'name'**

Explanation The access rights of a server extension are being set in the specified database.

Action No action required.

INOAAI0543 **Stopping database dbName in normal mode**

Explanation This message indicates that the specified database is being stopped in normal mode.

Action No action required.

INOAAI0544 **Stopping database dbName in abort mode**

Explanation This message indicates that the specified database is being stopped in abort mode.

Action No action required.

INOAAI0545 **Stopping database dbName in rollback mode**

Explanation This message indicates that the specified database is being stopped in rollback mode.

Action No action required.

INOAAI0568 **Unexpected messages received**

Explanation This message is the header for subsequent messages.

Action No action required.

INOAAI0569 **Edit details for a new server extension**

Explanation Details for a new server extension will be edited.

Action No action required.

INOAAI0570 **Description: text**

Explanation This is a short description of the new server extension.

Action No action required.

INOAAI0571 **Author name: name**

Explanation This is the name of the new server extension author.

Action No action required.

INOAAI0572 **Help file: name**

Explanation This is the name of a help file for the new server extension.

Action No action required.

INOAAI0573 **Editing of new server extension details successful**

Explanation The editing of the new server extension details was successful.

Action No action required.

INOAAI0574 **Starting database dbName**

Explanation A Tamino database is being started.

Action No action required.

INOAAI0577 **Unloading document 'path'**

Explanation The server extension object information document is being unloaded.

Action No action required.

INOAAI0578 **Edit details for a new server extension function**

Explanation Details for a new server extension function will be edited.

Action No action required.

INOAAI0579 **Function type: text**

Explanation This message displays the type of a server extension function.

Action No action required.

INOAAI0580 **Editing of new server extension function details successful**

Explanation The editing of the new server extension function details was successful.

Action No action required.

INOAAI0581 **Loading document 'path'**

Explanation A server extension analyzer document is being loaded.

Action No action required.

INOAAI0582 **Start Database**

Explanation This is a command for the Tamino agent dbagent.

Action No action required.

INOAAI0583 **Stop Database**

Explanation This is a command for the Tamino agent dbagent.

Action No action required.

INOAAI0584 **Delete Database**

Explanation This is a command for the Tamino agent dbagent.

Action No action required.

INOAAI0587 **Check and Repair**

Explanation This is a command for the Tamino agent dbagent.

Action No action required.

INOAAI0589 **Information**

Explanation This is a command for the Tamino agent dbagent.

Action No action required.

INOAAI0591 **Database Spaces**

Explanation This is a command for the Tamino agent dbagent.

Action No action required.

INOAAI0592 **Properties**

Explanation This is a command for the Tamino agent dbagent.

Action No action required.

INOAAI0598 **Register CD Database**

Explanation This is a command button for the Tamino agent dblist.

Action No action required.

INOAAI0599 **Prepare for CD**

Explanation This is a command for the Tamino agent dblist.

Action No action required.

INOAAI0600 **Unregister CD Database**

Explanation This is a command button for the Tamino agent dbagent.

Action No action required.

INOAAI0601 **Create a new server extension package**

Explanation This is an informational message.

Action No action required.

INOAAI0602 **Package path: path**

Explanation This is the pathname of the server extension package.

Action No action required.

INOAAI0603 **Creation of package 'name' successful**

Explanation A server extension package was created successfully.

Action No action required.

INOAAI0604 **Port range successfully changed**

Explanation The port range was successfully changed.

Action none

INOAAI0607 **inodmp return erg**

Explanation This message shows a return value of inodmp.

Action No action required.

INOAAI0612 **Deselection of function 'name' successful**

Explanation The server extension function was successfully deselected.

Action No action required.

INOAAI0613 **Modify parameter of server extension function**

Explanation The parameter name and XML type of a selected server extension function will be modified.

Action Insert the corresponding values.

INOAAI0614 **Parameter name: name**

Explanation This specifies the name of the parameter being modified.

Action No action required.

INOAAI0615 **Modified name: name**

Explanation This specifies the modified name of the parameter.

Action No action required.

INOAAI0616 **XML type: type**

Explanation This specifies the modified XML type of the parameter.

Action No action required.

INOAAI0617 **Modification of parameter 'name' successful**

Explanation A server extension function parameter was successfully modified.

Action No action required.

INOAAI0618 **Preparation of CD database successful**

Explanation This is an informational message.

Action No action required.

INOAAI0625 **Renaming database dbname to newdbname**

Explanation The database is being renamed.

Action No action required.

INOAAI0626 **Database successfully renamed**

Explanation The database was renamed successfully.

Action No action required.

INOAAI0627 **Server extension class 'name'**

Explanation This message specifies the Java class name of a server extension.

Action No action required.

INOAAI0629 **database successfully registered**

Explanation A database has been successfully registered.

Action No action required.

INOAAI0630 **Registering CD database dbname**

Explanation The CD database is being registered.

Action No action required.

INOAAI0631 **Location name at path successfully added**

Explanation The location was successfully added.

Action No action required.

INOAAI0632 **Location name successfully deleted**

Explanation The location was successfully deleted.

Action No action required.

INOAAI0633 **Location name successfully renamed to newname**

Explanation The location was successfully renamed.

Action No action required.

INOAAI0634 **Location name successfully set as default database location**

Explanation The location was successfully set as the default database location.

Action No action required.

INOAAI0635 **Location name successfully set as default backup database location**

Explanation The location was successfully set as the default backup location.

Action No action required.

INOAAI0636 **Default of database location category 'category' successfully modified**

Explanation The default database location category was successfully modified.

Action No action required.

INOAAI0642 **Stopping XML session**

Explanation The XML session is being stopped.

Action No action required.

INOAAI0649 **Setting global parameters for external backup method 'method' of database dbname**

Explanation Global parameters for external backup method are being set.

Action No action required, information message.

INOAAI0650 **Global parameters for external backup method 'method' of database dbname successfully set**

Explanation The global parameters were successfully set.

Action No action required, information message.

INOAAI0652 **Setting configuration parameters for external backup method 'method' of database dbname**

Explanation The configuration parameters for the external backup method are being set.

Action No action required, information message.

INOAAI0654 **Configuration parameters for external backup method 'method' of database dbname successfully set**

Explanation The configuration parameters were successfully set.

Action No action required, information message.

INOAAI0655 **Deleting configuration 'configuration' of method 'method' of database dbname**

Explanation The "delete configuration" function was started.

Action No action required, information message.

INOAAI0657 **Configuration 'configuration' of method 'method' of database dbname successfully deleted**

Explanation The configuration parameters were successfully deleted.

Action No action required, information message.

INOAAI0661 **Replication database name replication_db added into the permission list**

Explanation This is a status report that the replication database name has been added into the permission list.

Action No action required.

INOAAI0663 **Replication database name replication_db removed from the permission list**

Explanation The replication database name has been removed from the permission list.

Action No action required, this is an information message.

INOAAI0664 **Database database set to replication type**

Explanation The database is set to the type "replication database".

Action No action required, this is an information message.

INOAAI0666 **Replication database database has been reset to normal type**

Explanation The replication database was reset so that it is a normal database.

Action No action required, this is an information message.

INOAAI0670 **Private Classpath: path**

Explanation The displayed path is the server extension private Java classpath.

Action No action required.

INOAAI0671 **type Classpath: path**

Explanation The specified operation type is performed with the server extension private Java classpath.

Action No action required.

INOAAI0673 **Keep files from backup datetime**

Explanation This indicates that the backup files will be saved.

Action No action required, information message.

INOAAI0674 **Move backup space to "destination"**

Explanation The backup space is being moved moved to new location.

Action No action required, information message.

INOAAI0682 **Switching log space for database dbName**

Explanation A switch of the log space is initiated.

Action No action required.

INOAAI0687 **Nothing has changed: mode**

Explanation The specified server extension attribute did not change.

Action No action required.

INOAAI0688 **Attribute: mode**

Explanation This specifies a new attribute of the parameter.

Action No action required.

INOAAI0689 **Default value : text**

Explanation This specifies the default value of the parameter.

Action No action required.

INOAAI0690 **Adding backup method 'method' for database dbname**

Explanation An external backup method of the database is being added.

Action No action required, information message.

INOAAI0692 **Backup method 'method' successfully added for database dbname**

Explanation The backup method has been successfully added.

Action No action required, information message.

INOAAI0693 **Deleting method 'method' of database dbname**

Explanation An external backup method of the database is being deleted.

Action No action required, information message.

INOAAI0695 **Method 'method' of database dbname successfully deleted**

Explanation The backup method has been successfully deleted.

Action No action required, information message.

INOAAI0697 **Deleting backup 'bckDate' of database dbName**

Explanation The backup of the database is being deleted.

Action Information message, no action required.

INOAAI0698 **Deletion of backup 'bckDate' of database dbName successfully completed**

Explanation The specified database backup has been deleted successfully.

Action Information message, no action required.

INOAAI0701 **Remove permitted replication database name replicationdb from master database masterdb**

Explanation This is a title for the messages for removing a database name from the permission list.

Action No action required.

INOAAI0702 **Add permitted replication database name**

Explanation This is a title for adding database name into the permission list.

Action No action required.

INOAAI0704 **Set type to normal database**

Explanation This is a title for setting the database type to a normal one.

Action No action required.

INOAAI0705 **Create replication database list**

Explanation This is a title for create replication database list.

Action No action required.

INOAAI0706 **Retrieve replication database information**

Explanation This is a title for retrieving the information of databases.

Action No action required.

INOAAI0711 **Domain 'name' created**

Explanation The domain has been created.

Action No action required.

INOAAI0713 **Domain 'name' modified**

Explanation The domain has been modified.

Action No action required.

INOAAI0715 **Domain 'name' deleted**

Explanation The domain has been deleted.

Action No action required.

INOAAI0718 **Creating database dbName from backup dated timestamp**

Explanation A new database is created with the content of a given backup. The log spaces belonging to the backup are not recovered.

Action No action required.

INOAAI0721 **Web server assignments changed.**

Explanation The web server assignments for this database have changed.

Action No action required.

INOAAI0722 **Setting port ranges for Tamino databases**

Explanation The static and dynamic port ranges are being set.

Action No action required.

INOAAI0726 **Port ranges successfully changed**

Explanation The port ranges were successfully changed.

Action No action required.

INOAAI0729 **Renaming web server 'wbsname' to 'newwbsname'**

Explanation The web server is being renamed.

Action No action required.

INOAAI0730 **Web server successfully renamed**

Explanation The web server was successfully renamed.

Action No action required.

INOAAI0732 **Web server successfully added.**

Explanation The web server was added successfully.

Action No action required.

INOAAI0734 **Adding web server 'newwbsname'**

Explanation The web server is being added.

Action No action required.

INOAAI0735 **Deleting web server 'wbsname'**

Explanation The web server is being deleted.

Action No action required.

INOAAI0736 **Web server successfully deleted**

Explanation The web server was deleted successfully.

Action No action required.

INOAAI0738 **Modifying web server 'wbsname'. New IP address: 'ipaddress', new node: 'node', new port: 'port'.**

Explanation The web server is being modified.

Action No action required.

INOAAI0739 **Web server successfully modified**

Explanation The web server was modified successfully.

Action No action required.

INOAAI0751 **Preparing CD database dbname**

Explanation A CD database is being prepared.

Action No action required.

INOAAI0770 **Could not create database, cleaning up now**

Explanation The "Create Database" or "Create Database From Backup" command has failed. Files, internal configuration store entries and XTS entries made during this process are deleted.

Action No action required.

INOAAI0771 **Location location selected for initial backup**

Explanation The initial backup could not be created in the first backup location specified. It has been created in the location indicated in the message text instead.

Action No action required.

INOAAI0781 **The command requires an active database**

Explanation An attempt was made to execute a command that requires an active database, but the the database is inactive.

Action The database must be started before the command can be executed.

INOAAI0782 **The command requires an inactive database**

Explanation An attempt was made to execute a command but the database is active and the command requires an inactive database.

Action The database must be stopped before the command can be executed.

INOAAI0789 **Web server assignments changed. Please restart all databases which have this web server assigned to make your changes effective.**

Explanation The web server assignments for this database have changed.

Action Please restart all databases which have this web server assigned to make your changes effective.

INOAAI0795 **Set type to replication database with simultaneous query**

Explanation The flag for simultaneous query for replication is set to 'enabled'.

Action No action required.

INOAAI0796 **Set type to replication database without simultaneous query**

Explanation The flag to allow simultaneous query for replication is disabled.

Action No action required.

INOAAI0821 **Initialize raw section**

Explanation This is an event log message while the raw section is being initialized.

Action No action required.

INOAAI0822 **Raw section successfully initialized**

Explanation The raw section has been successfully initialized.

Action No action required.

INOAAI0827 **Set static min port min**

Explanation The static minimum port is being set. All Tamino database static ports must be greater than or equal to this value.

Action No action required.

INOAAI0828 **Set static max port max**

Explanation The static maximum port is being set. All Tamino database static ports must be lower than or equal to this value.

Action No action required.

INOAAI0829 **Set dynamic min port dmin**

Explanation The dynamic minimum port is being set. Tamino databases use the port range for dynamically allocated ports. This port range should not be used by any other software.

Action No action required.

INOAAI0830 **Set dynamic max port dmax**

Explanation The dynamic maximum port is being set. Tamino databases use the port range for dynamically allocated ports. This port range should not be used by any other software.

Action No action required.

INOAAI0840 **Function func is used in collection coll, schema schm, doc type doc**

Explanation The server extension to be uninstalled contains a function that is still used in the given context.

Action Typically no action is required but be aware that in the case of a forced uninstall the corresponding functions cannot be executed any longer.

INOAAI0848 **Restart parameter ignored, because only dynamic properties changed**

Explanation A restart parameter was given, but a restart is only useful if a static property is changed.

Action No action required.

INOAAI0865 **Moving database space spaceNo of database dbname from oldLoc to newLoc**

Explanation The database space of the named database is being moved from one location to another location.

Action No action required.

INOAAI0866 **Stop current request(s)**

Explanation Stop a current running request.

Action No action required.

INOAAI0867 **Request requestid successfully stopped**

Explanation A request has been successfully stopped.

Action No action required.

INOAAI0869 **No current active requests found**

Explanation No requests are running on the XML Server.

Action No action required.

INOAAW0071 **Higher server extension versions exist : name**

Explanation In other databases, higher versions of this server extension exist.

Action Back up the server extension.

INOAAW0150 **Backup spaces are copied because one or more spaces could still be part of an existing backup generation**

Explanation To protect integrity of backup generations, spaces with the Tamino backup filename extension "1B0" are always copied because they could be part of a backup generation on the local host, or another remote host.

Action Make sure that the selected backup spaces are not used in a backup generation by a local database or elsewhere, and then change their filename extension to something different from "1B0".

INOAAW0166 **Parameter 'para' unknown**

Explanation The specified database parameter name is not known by the Tamino server.

Action Check the spelling of the parameter. If the spelling is correct, check whether the parameter is valid in the current context.

INOAAW0206 **Required spacetype size could not be obtained from the backup, using minimum sizes where not specified otherwise**

Explanation Minimum sizes will be used if not specified otherwise but the new database might refuse to start with these settings.

Action Specify the effective spaces of the saved database if creating with the minimum sizes does not succeed.

INOAAW0271 **Cannot move space of database database, because the database is online**

Explanation The database of the database space to move is in an active state.

Action Stop the database.

INOAAW0411 **Show progress aborted**

Explanation The progress information process is aborted because no more progress is determined, but operation is not finished.

Action No action required.

INOAAW0422 **An error has occurred when user user attempted to remove the records of all completed jobs without pending alerts from the joblog**

Explanation One or more job records may remain in the given job log after the attempt to delete all due records.

Action Check if the service is running. If the problem persists, job records can be deleted "physically" by deleting the files with the extensions "0G0" and "0F0" in the directory were job records are stored (try the "log" directory in the Tamino or System Management Hub root directory) and restarting the service. This however will also delete records with pending alerts and records of active commands and should only be done as a last resort.

INOAAW0433 **File 'path' not deleted**

Explanation The server extension file could not be deleted.

Action No action necessary.

INOAAW0434 **File 'path' not found**

Explanation The specified file could not be found.

Action No action necessary.

INOAAW0435 **Directory 'path' not deleted**

Explanation The directory is in use. Therefore it cannot be deleted.

Action Wait until the directory is not in use, then retry the operation.

INOAAW0436 **Directory 'path' not found**

Explanation The specified directory was not found.

Action Check the permissions of your file system.

INOAAW0440 **Automatic assign of ports for the database failed, please assign the ports manually**

Explanation The database is not usable until the ports are assigned manually.

Action Assign the ports for the database manually.

INOAAW0640 **After restarting the Tamino server the server extension will be updated correctly**

Explanation The Tamino server crashed. The server extension will be usable after restart.

Action Restart the Tamino server to use this server extension .

INOAAW0676 **Please store the tape(s) from backup datetime in a safe place!**

Explanation Tapes cannot be saved, the user must store them in a safe place.

Action Keep the backup in a safe place.

INOAAW0677 **Please store the files from external backup datetime in a safe place!**

Explanation External backups cannot be saved, the user must store them in a safe place.

Action Keep the external backup in a safe place.

INOAAW0700 **Updating existing server extension 'name'**

Explanation A previous version of the server extension is already installed in the database and will be updated.

Action No action required.

INOAAW0800 **Disabling autostart for database dbName**

Explanation The parameter "autostart" of the database has been set to "false".

Action No action required.

INOAAW0804 **No property changed, property name and value is missing**

Explanation There is no property name in the command.

Action Supply the name of the property and the new value (propertyname=value) at the end of the batch command.

INOAAW0815 **Parameter 'name' is ignored for server extensions with execution type 'type'**

Explanation The parameter cannot be used for server extensions of the given execution type.

Action No action required.

INOAAW0833 **Force ignore replication database master status is set.**

Explanation Normally it is not allowed to delete a replication database master, so force ignore replication master status is set. The database will be removed.

Action No action required.

INOAAW0839 **Server extension name is used in schema**

Explanation In some node of a schema a function of the server extension name is used.

Action See the following messages for detailed information.

INOAAW0851 **No backups with user data found, please don't use option "Keep Backups"**

Explanation No backups with user data found, please don't use option "Keep Backups".

Action Do not use the option "Keep Backups".

INOAAW0853 **This command is deprecated. Please use the new command "inoload".**

Explanation This command is set to the deprecated state and will be disabled in the next version

Action Use the new command inoload instead of this command.

INOAAW0854 **COM server extension registration/deregistration suppressed**

Explanation When packaging the COM server extension, the option to suppress the registration/deregistration commands has been used.

Action It is the installer's responsibility to make sure the COM objects are correctly registered/deregistered using the methods provided by the underlying infrastructure.

INOAAW0871 **Can't connect to XTS directory server rc = xtsrc**

Explanation Can't connect to XTS directory server. This server is necessary for Tamino databases.

Action Check the XTS directory server.

INOCVE8065 **Collection collection contains non-migrated indexes**

Explanation The upgrade was rejected because there are non-migrated indexes in Tamino 4.1.4.

Action Please migrate the indexes. Refer to the migration documentation for details.

INOCVE8067 **Collection collection contains doctypes that are not namespace clean**

Explanation The upgrade was rejected because at least one doctype in the database is not namespace clean.

Action Please perform a namespace cleanup. Refer to the migration documentation for details.

INOCVE8069 **Conversion of data mapping to version version has failed with response response**

Explanation An error occurred during the conversion of data mapping for standard index and collations.

Action Please contact your software supplier.

INOCVE8070 **number TSD2 user collections exist**

Explanation TSD2 user collections exist and must be migrated to TSD3.

Action Please use the migration tool to migrate the TSD2 user collections.

INOCVE8071 **The count of existing user collections has failed with response response**

Explanation The query to count existing user collections has failed.

Action Please contact your software supplier.

INOCVE8073 **number installed COM server extensions found, conversion not allowed**

Explanation It is not possible to convert a Tamino database to this version as COM server extensions are installed.

Action Contact your software supplier for help with switching versions.

INOCVE8074	**Counting existing COM server extensions has failed with response response**
Explanation	The query to count existing COM server extensions has failed.
Action	Contact your software supplier for help with switching versions.

INOCVE8075	**Request to create indexes for doctype doctype in collection collection is pending**
Explanation	A request to create indexes is pending.
Action	Please correct the current status using the admin-command ino:repairIndex with option CONTINUE or DROP.

INOCVE8077	**The schema check for existing user collections has failed**
Explanation	The test define of existing user collection during "set version" has failed.
Action	Please contact your software supplier.

INOCVE8078	**The check for server extension installation has failed**
Explanation	The query to check whether a server extension is installed has failed.
Action	Please contact your software supplier.

INOCVW8066	**Schema "schema" in collection "collection" contains unknown attributes**
Explanation	The given schema in the given collection contains unknown attributes.
Action	Remove additional attributes before next schema update.

INOCVW8076	**The schema check for schema schema in collection collection has failed with response response**
Explanation	The test of defining all existing user collections during "set version" has failed.
Action	Please check the schema using the following admin-command ino:CheckSchema(collection-name, schema-name). Correct the schema and update it in Tamino.

INODCE6507	**Parameter structure mismatch**
Explanation	A parameter structure mismatch was detected.
Action	Please check and correct the given parameters and try again.

INODCE6508 **Not enough memory to create communication area**

Explanation There was not enough memory to create the communication area.

Action Please free some memory and try again.

INODCE6509 **Fatal error - unload aborted**

Explanation A fatal error was detected and the unload was aborted.

Action Please check for other error messages to obtain the cause of the abort.

INODCE6510 **Specify either the '-database' or the '-server' parameter, but do not specify both parameters together**

Explanation Please specify either the '-database' or the '-server' parameter, but do not specify both parameters together.

Action Please do not specify both parameters together.

INODCE6511 **Processing failed - cannot get server version**

Explanation The processing failed because it was not possible to get the server version.

Action Please check that you are using a version of the data loader client which is compatible with the server.

INODCE6512 **Path and/or file name too long**

Explanation The path and/or file name is too long.

Action Please change the file name and try again.

INODCE6514 **Cannot open log file 'file'**

Explanation It was not possible to open the log file.

Action Please make sure the log file can be written and try again.

INODCE6515 **Processing failed - corrupted response from server**

Explanation Processing failed because a corrupted response was received from the server.

Action Please contact your software supplier.

INODCE6517 **Server does not support mass loading of data**

Explanation The server does not support mass loading of data.

Action No action required.

INODCE6518 **Cannot retrieve information for input file 'file'**

Explanation It was not possible to retrieve information for the input file.

Action Please make sure the input file can be read and try again.

INODCE6519 **Cannot process an empty input file 'file'**

Explanation It is not possible to process the input file because it is empty.

Action Please make sure you specify the correct input file and try again.

INODCE6520 **Cannot open input file 'file'**

Explanation It was not possible to open the input file.

Action Please make sure the input file can be read and try again.

INODCE6521 **WSAStartup failed**

Explanation WSAStartup failed.

Action Please check the network configuration.

INODCE6522 **Winsock version mismatch**

Explanation A Winsock version mismatch was detected.

Action Please check the network configuration.

INODCE6523 **Not enough memory to create client host name**

Explanation There was not enough memory to create client host name.

Action Please free some memory and try again.

INODCE6524 **Invalid cursor handle delivered**

Explanation An invalid cursor handle was delivered.

Action Please contact your software supplier.

INODCE6525 **No cursor handle delivered**

Explanation No cursor handle was delivered.

Action Please contact your software supplier.

INODCE6526 **Not enough memory to create query object**

Explanation There was not enough memory to create the query object.

Action Please free some memory and try again.

INODCE6527 **Not enough memory to create query name buffer**

Explanation There was not enough memory to create the query name buffer.

Action Please free some memory and try again.

INODCE6528 **Cannot open output file 'file'**

Explanation It was not possible to open the named output file.

Action Please make sure the output file can be written and try again.

INODCE6529 **Invalid output format**

Explanation An invalid output format was detected.

Action Please contact your software supplier.

INODCE6530 **Cannot unload non-XML documents into a single file**

Explanation It is not possible to unload non-XML documents into a single file.

Action Please make sure you specified a valid output location for non-XML documents and try again.

INODCE6531 **Unload to a single file is not allowed**

Explanation An unload to a single file is not allowed.

Action Please make sure you specified a valid output location and try again.

INODCE6532 **Unload to a directory is not allowed**

Explanation An unload to a directory is not allowed.

Action Please make sure you specified a valid output location and try again.

INODCE6534 **Cannot read input file - I/O error code**

Explanation The input file could not be read due to an I/O error.

Action Please make sure the input file can be read and try again.

INODCE6536 **Not enough memory to create save area**

Explanation There was not enough memory to create the save area.

Action Please free some memory and try again.

INODCE6538 **Cannot initialize multi thread context**

Explanation It was not possible to initialize a multi thread context.

Action Please contact your software supplier.

INODCE6539 **Not enough memory to create request**

Explanation The was not enough memory to create a request.

Action Please free some memory and try again.

INODCE6543 **Not enough memory to create file offset area**

Explanation There was not enough memory to create the file offset area.

Action Please free some memory and try again.

INODCE6544 **Processing failed - no response from server**

Explanation The processing failed because there was no response from the server.

Action Please contact your software supplier.

INODCE6545 **Received empty answer from Tamino server**

Explanation An empty reply was received from the Tamino server.

Action Please contact your software supplier.

INODCE6547 **Invalid function code detected**

Explanation An invalid function code was detected.

Action Please enter either "load", "unload" or "define" for the parameter "-function"

INODCE6548 **Parameter 'parm' is only available with function code 'func'**

Explanation The given parameter is only available with the given function code.

Action Please correct your input and try again.

INODCE6549 **Argument for parameter 'arg' missing**

Explanation An argument for the given parameter is missing.

Action Please correct your input and try again.

INODCE6550 **Query filter must be enclosed in brackets: [...]**

Explanation A query filter must be enclosed in brackets: [...].

Action Please correct your input and try again.

INODCE6551 **Please specify the parameter 'parm' only once**

Explanation The given parameter was specified more than once. Please specify the parameter only once.

Action Please correct your input and try again.

INODCE6552 **Doctype is required**

Explanation A doctype is required.

Action Please correct your input and try again.

INODCE6553 **Server name is required**

Explanation The server name is required.

Action Please correct your input and try again.

INODCE6554 **Port number is required**

Explanation A port number is required.

Action Please correct your input and try again.

INODCE6555 **Parameter 'p1' not allowed in conjunction with parameter 'p2'**

Explanation The first parameter cannot be used together with the second parameter.

Action Please correct your input and try again.

INODCE6556 **Memory allocation failed during parsing**

Explanation Memory allocation failed during the parsing phase.

Action Please free some memory and try again.

INODCE6557 **Invalid hexBinary parameter detected**

Explanation An invalid hexBinary parameter was detected.

Action Please correct your input and try again.

INODCE6558 **Invalid parameter detected: 'parm'**

Explanation An invalid parameter was detected.

Action Please correct your input and try again.

INODCE6559 **Invalid argument for parameter -outputformat detected**

Explanation An invalid argument for parameter -outputformat was detected.

Action Please enter either "singlefile" or "multifiles".

INODCE6560 **Invalid argument for parameter -docname detected**

Explanation An invalid argument for parameter -docname was detected.

Action Please enter either "no", "full", "name" or "nameext".

INODCE6561 **Specify both '-sessionid' and '-sessionkey' or neither**

Explanation You must specify either both '-sessionid' and '-sessionkey' or neither.

Action Please correct your input and try again.

INODCE6562 **Mandatory parameter '-server' or '-database' missing**

Explanation The mandatory parameter '-server' or '-database' is missing.

Action Please correct your input and try again.

INODCE6563 **Mandatory parameter '-collection' missing**

Explanation The mandatory parameter '-collection' is missing.

Action Please correct your input and try again.

INODCE6566 **msg**

Explanation This is a general placeholder for a message text.

Action See the text of the message in the job log for more details.

INODCE6567 **Cannot open rejects file 'file'**

Explanation The rejects file could not be opened.

Action Please make sure the rejects file can be opened and try again.

INODCE6568 **Cannot write rejects file 'file'**

Explanation It was not possible to write to the rejects file.

Action Please make sure the rejects file can be written and try again.

INODCE6570 **Access to Tamino Server denied**

Explanation Because of security definitions access to the Tamino server is denied.

Action Please check your security definitions and try again.

INODCE6575 **Cannot write to output file - I/O error code**

Explanation The output file could not be written due to an I/O error.

Action Please make sure the output file can be written and try again.

INODCE6578 **Tamino Data Loader finished with errors**

Explanation The Tamino Data Loader has finished its processing with some error messages.

Action Check the log output, correct errors and try again.

INODCE6579 **libxni provided data buffer of bsize bytes, minimum of nsize bytes needed**

Explanation Internal error in massload utility detected.

Action Please contact your software supplier.

INODCE6580 **Memory allocation failed while loading data**

Explanation An out of memory condition occurred.

Action Restart the command when virtual memory is available.

INODCE6581	**Invalid media type specified for input file 'file'**
Explanation	An invalid media type was specified. You can load only documents of media type xml to a xml doctype.
Action	Please specify a legal xml media type and try again.

INODCE6582	**Error reading from input file 'file' while writing reject file**
Explanation	A file read error occurred while backing up rejected data.
Action	Check the file storage or contact your software supplier.

INODCE6583	**Cannot contact Tamino Server - HTTP status code code received**
Explanation	Cannot contact Tamino Server - HTTP status code received.
Action	Please contact your system administrator.

INODCE6584	**The operation was canceled by the user**
Explanation	The operation was canceled by the user.
Action	No action required.

INODCE6585	**Invalid argument for parameter -streaming detected**
Explanation	An invalid argument for parameter -streaming was detected.
Action	Please enter either "on" or "off".

INODCE6590	**Server does not support mass deleting of data**
Explanation	The server does not support mass deleting of data.
Action	No action required.

INODCE6592	**Disconnect from server failed due to a serious communication error**
Explanation	Disconnect from server failed due to a serious communication error.
Action	Please check your network settings.

INODCI6500	**Tamino Data Loader vvers - (c) Copyright Software AG 2002-year. All rights reserved.**
Explanation	This is the Tamino Data Loader start message.
Action	No action required.

INODCI6501 **Loading documents to database 'db', collection 'coll', doctype 'doctype'**

Explanation Documents are being loaded into the database.

Action No action required.

INODCI6502 **Loading documents to database on 'server:port', collection 'coll', doctype 'doctype'**

Explanation Documents are being loaded into the database.

Action No action required.

INODCI6503 **Unloading documents from database 'db', collection 'coll', doctype 'doctype'**

Explanation Documents are being unloaded from database.

Action No action required.

INODCI6504 **Unloading documents from database on 'server:port', collection 'coll', doctype 'doctype'**

Explanation Documents are being unloaded from the database.

Action No action required.

INODCI6505 **Defining schemas to database 'db'**

Explanation Schemas are being defined in the database.

Action No action required.

INODCI6506 **Defining schemas to database on 'server:port'**

Explanation Schemas are being defined in the database.

Action No action required.

INODCI6513 **Unloading file 'file'**

Explanation The given file is being unloaded.

Action No action required.

INODCI6516 **Loading file 'file'**

Explanation The given file is being loaded.

Action No action required.

INODCI6533 **No matching documents found**

Explanation The query you specified returned no results.

Action Please specify another query and try againg.

INODCI6535 **start MB of end MB loaded**

Explanation This shows the progress information.

Action No action required.

INODCI6537 **Loading document id**

Explanation The given document is being loaded.

Action No action required.

INODCI6540 **Unloading documents start to end**

Explanation The documents in the range from "start" to "end" are being unloaded.

Action No action required.

INODCI6541 **Data unloading completed, number of documents processed: num**

Explanation The unload of the data has completed.

Action No action required.

INODCI6542 **Committing loaded documents - this may take a while**

Explanation The loaded documents are being committed. This activity can last a while.

Action No action required.

INODCI6546 **Elapsed time: elapse second(s), data processed: amount**

Explanation The elapsed time and the amount of data processed are shown here.

Action No action required.

INODCI6564 **msg**

Explanation This is a general placeholder for a message text.

Action See the text of the message in the job log for more details.

INODCI6565	**Data loading completed, number of documents processed docsproc, loaded docsload, rejected docsrejected**
Explanation	The data processing has completed with the given number of loaded and rejected documents.
Action	No action required.

INODCI6569	**Process id: id**
Explanation	The process has the given ID.
Action	No action required.

INODCI6571	**Unloading schemas from database 'db', collection 'coll'**
Explanation	Schemas are being unloaded from the database.
Action	No action required.

INODCI6572	**Unloading schemas from database on 'server:port', collection 'coll'**
Explanation	Schemas are being unloaded from the given collection of the database on the given server and port.
Action	No action required.

INODCI6573	**Unloading schemas start to end**
Explanation	Schemas in the range from "start" to "end" are being unloaded.
Action	No action required.

INODCI6574	**Data unloading completed, number of schema files written: num**
Explanation	The unloading of data has completed.
Action	No action required.

INODCI6576	**Tamino Data Loader successfully finished**
Explanation	The Tamino Data Loader has successfully completed its processing.
Action	No action required.

INODCI6586 **Undefining schemas from database 'db'**

Explanation Schemas are being undefined from the database.

Action No action required.

INODCI6587 **Undefining schemas from database on 'server:port'**

Explanation Schemas are being undefined from the database.

Action No action required.

INODCI6588 **Deleting documents from database 'db', collection 'coll', doctype 'doctype'**

Explanation Documents are being deleted from database.

Action No action required.

INODCI6589 **Deleting documents from database on 'server:port', collection 'coll', doctype 'doctype'**

Explanation Documents are being deleted from the database.

Action No action required.

INODCI6591 **Data deleting completed, docsdel documents deleted**

Explanation The data deleting has completed with the given number of deleted documents.

Action No action required.

INODCW6577 **Tamino Data Loader finished with warnings**

Explanation The Tamino Data Loader has finished its processing with some warning messages.

Action Check the log output, correct errors and try again.

INODSA1000 **Starting autorepair after abnormal termination**

Explanation The last server session of the database was terminated abnormally. Before the database can be used, the data consistency will be re-established, changes which had not been written to disk will be redone, and transactions which were open at the time of the abnormal server session termination will be reset.

Action Wait for the end of the autorepair processing before using your database.

INODSA1001 **Start writing crash dump of database, writing to file filename**

Explanation The server has encountered an error situation which causes a crash. In order to enable error analysis, the server writes status information to a file in the reserved location.

Action Report the crash to your software supplier, together with the dump files in the reserved location.

INODSA1002 **name modifierversionmodifier2 on system info**

Explanation This is a generic message that is used for identification of an activity.

Action No action required.

INODSA1003 **Starting recovery**

Explanation The database recovery processing is starting. After restoring a database, the recovery processing re-applies all updates that were done since the database backup was created.

Action Wait for the end of the recovery processing before using your database.

INODSA1006 **Skipping database recovery during restore**

Explanation The database restore is being performed without recovery processing. Log space information will be marked as skipped.

Action Wait for the end of the recovery skipping before using your database.

INODSA1007 **Starting recovery until time**

Explanation The database recovery processing is starting. After restoring a database, the recovery processing re-applies all updates that were done between the database backup creation and the specified time.

Action Wait for the end of the recovery processing before using your database.

INODSA1249 **Starting recovery until time**

Explanation The database recovery processing is starting. After restoring a database, the recovery processing re-applies all updates that were done between the database backup creation and the specified time.

Action Wait for the end of the recovery processing before using your database.

INODSA2278 **Tamino name modifierversionmodifier2 on system info**

Explanation This is a generic message that is used for identification of an activity.

Action No action required.

INODSE1015 **Expanding the database has failed, because the licensed database size would have been exceeded**

Explanation The allowed database size is limited by the amount allowed in your license file. The attempted expansion of the database would have exceeded the allowed size.

Action Please contact your software supplier for an enhanced license which allows a larger database size.

INODSE1025 **Source and destination of the copy operation specify the same object (source)**

Explanation Source and destination of a copy operation must not specify the same object.

Action Please specify another source or destination for the copy operation.

INODSE1026 **Copy operation (src to dest) incomplete, copied done of expect bytes**

Explanation The copy operation was incomplete due to a system error.

Action Please consult your manufacturer's manual.

INODSE1027 **System error errno during operation call on file file**

Explanation There was an operating system error while performing the specified operation on the specified file.

Action Please consult your manufacturer's manual.

INODSE1028 **pathname does not specify a valid raw section (returned type error)**

Explanation The given path does not specify a valid raw section.

Action Specify a valid raw section.

INODSE1029 **Size of raw section section was computed as 0**

Explanation The size of the given raw section could not be determined.

Action Please contact your software supplier.

INODSE1030 **Raw section section is not empty and must not be reset**

Explanation The specified raw section is not empty and must not be reset.

Action Specify another raw section or deallocate all entries from the specified one.

INODSE1031 **database space space number of database server in raw section section is in use and must not be changed**

Explanation The specified container is still in use and must not be changed.

Action Ensure that the container is not in use before trying to change it.

INODSE1032 **Incremental backup cannot be used for database creation**

Explanation The backup file selected is an incremental one, but databases can only be created from full backups.

Action Use a full backup for database creation.

INODSE1036 **database space space number of database server in raw section section is in use and must not be deallocated**

Explanation The specified database space is currently in use and must not be deallocated.

Action No action required.

INODSE1037 **database space space number of database server in raw section section is in use and must not be reallocated**

Explanation The specified database space is in use and must not be reallocated.

Action No action required.

INODSE1042 **Incremental backup is not enabled**

Explanation Incremental backup cannot be issued because the feature is not enabled.

Action Switch on the server parameter for enabling incremental backup.

INODSE1043 **Incremental backup is not possible**

Explanation Incremental backup is not possible because there is no valid associated full or incremental backup present, or for some reason the server has deactivated the incremental block collection.

Action Perform a full backup to resolve this situation.

INODSE1045 **Incremental Backup is disabled at the database to be restored**

Explanation The database is not prepared to receive the given incremental backup.

Action Check the database. Possibly you must restore a full backup first.

INODSE1046 **Backup file has invalid or missing incremental backup data**

Explanation The backup file to be restored incrementally has no incremental backup data, or the backup data is corrupted.

Action Please contact your software supplier.

INODSE1048 **Backup numbers do not fit together: database dbnr, backup bcknr**

Explanation The incremental backup file and the database to receive the backup file no not fit together according the backup numbers. The backup number of the backup file must be one higher than the current backup number of the database

Action Check all your backup files and their numbers.

INODSE1051 **Structure level mismatch on log space from session session number**

Explanation The log space was generated by a previous Tamino version.

Action Use the previous Tamino version for restore/recovery and then switch again to the current version.

INODSE1052 **Internal error occurred: error string, location location**

Explanation An internal error has occurred. The database can still be used.

Action Please contact your software supplier and provide the message text.

INODSE1055 **Preparing for an emergency restart**

Explanation The server has terminated due to shortage of journal space. This has caused a situation in which the autorestart processing that will run automatically at the start of the next server session cannot be guaranteed to resolve internal data inconsistencies from the current terminated session. Therefore, the next server session will start with an emergency restart.

Action Restart the server. If the emergency restart completes without error, the database is in a consistent state and can be used normally. If the emergency start fails, you must recover your data using the latest backup.

INODSE1056 **During database restart, an error has occurred in an index on doctype doctype (ID). All indexes on this doctype have been dropped.**

Explanation There was an error in an operation on an index during the database restart processing. All indexes on the affected doctype have been dropped, but the doctype still is available.

Action After the restart has finished, recreate all indexes by choosing the "Check and Repair" function for the database in the Tamino Manager.

INODSE1057 **During database restart, an error has occurred on doctype doctype (ID). The doctype is no longer accessible.**

Explanation There was an error in an operation on the doctype during the database restart processing. The doctype has been destroyed.

Action After the restart has finished, restore the doctype.

INODSE1058 **Incremental Backup does not fit to latest database restore (different database backup ID)**

Explanation The incremental backup to be restored into the database cannot be performed because there the associated full database restore was a different one.

Action Check whether incremental backup file and its restored master full backup fit together.

INODSE1060 **Invalid internal database key found**

Explanation The database's internal database key is corrupt.

Action Please contact your software supplier.

INODSE1061 **No space left in raw section pathname for database space space number of database server**

Explanation The specified raw section does not contain enough contiguous space to allocate the specified database space.

Action Specify another raw section for this database space or free space in the given raw section.

INODSE1063 **database space space number of database server already present in raw section section**

Explanation The required database space is already present.

Action Remove the database space from the specified raw section.

INODSE1066 **Associated full backup not found for incremental backup savepoint**

Explanation A full backup as a base of a selected incremental backup was not found.

Action There is possibly a corruption of the internal configuration store.

INODSE1068 **The raw section section overlaps with a mounted file system**

Explanation Raw sections must not overlap with file systems since this can result in data corruption.

Action Define the raw section so that it does not overlap with a mounted file system.

INODSE1069 **Error accessing the mount table**

Explanation The operating system's mount table could not be processed.

Action Please contact your software supplier.

INODSE1070 **Decreasing the size of the raw section section failed**

Explanation An attempt to decrease the size of the specified raw section failed because the required new size is too small. Only free space at the end of a raw section can be removed.

Action Specify a raw section partition with a larger size.

INODSE1071 **Raw section section is already initialized**

Explanation An attempt was made to initialize a raw section that is already initialized. A raw section can be initialized only once.

Action No action required.

INODSE1072 **No space for database space space number of database server at specified position in raw section pathname**

Explanation At the specified position in the raw section there is not enough contiguous space to allocate the specified database space.

Action Specify another raw section or another position.

INODSE1073 **Overflow on raw section section**

Explanation The raw section contains too many database spaces in the management area.

Action Choose another raw section or remove obsolete database spaces.

INODSE1074 **Error allocating database space space number of database server on raw section section**

Explanation An error occurred while trying to allocate space on the specified raw section.

Action Please contact your software supplier.

INODSE1076 **System error errno during operation call on raw section section**

Explanation There was an operating system error while performing the specified operation on the specified raw section.

Action Please consult the manufacturer's manual.

INODSE1077 **Raw section section is corrupted or not initialized**

Explanation The data on the specified raw section is corrupted.

Action Please contact your software supplier if the section had been initialized.

INODSE1079 **path is a block device and cannot be used for raw sections**

Explanation An attempt was made to define a raw device on a block device. Raw sections must not be block devices.

Action No action required.

INODSE1080 **I/O error on block no in database space space no (operating system error errno)**

Explanation There has been an I/O error during an operation (initialization of a database space). This does not, however, lead to a loss of data.

Action Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.

INODSE1081 **Journal space must be writable**

Explanation The system could not write the specified database space.

Action Check the attributes (e.g. permissions) of the database space.

INODSE1082 **Error when opening database space space number (at path)**

Explanation The database space could not be opened.

Action Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.

INODSE1083 **System error errno when opening database space space no (path)**

Explanation The specified operating system error has occurred.

Action Please consult the manufacturer's manual.

INODSE1084 **Invalid block size block size**

Explanation The given block size is not allowed.

Action Provide a valid block size.

INODSE1085 **No space for source left on path**

Explanation There is not enough space on the device.

Action Specify another device or free some space.

INODSE1086 **Tape handling error: blocking factor not supported**

Explanation The specified tape device cannot be written because the blocking factor is not supported.

Action Change the blocking factor of the tape device. It must be either variable or a multiple of 1024.

INODSE1087 **Data error on source**

Explanation The file structure of the specified file does not match the expectations of the system.

Action Check the file's content and the defined structure.

INODSE1088 **A further extent of source cannot be created (reason reason, error err, errtxt)**

Explanation During any given server session, there is a limit on how much the database can grow. This limit has been reached in the current server session.

Action Stop the current server session and restart the database. In the new server session, the database can be extended.

INODSE1090 **Inconsistency detected when checking backup for timestamp savepoint**

Explanation A series of incremental backups cannot be restored completely.

Action Check if all incremental backups exist. If no backup is missing, please contact your software supplier.

INODSE1091 **Incremental Backup does not fit to latest database restore (database modified meanwhile)**

Explanation The incremental backup to be restored into the database cannot be performed because there were some updates to the database in the meantime.

Action Check if the database has been started between the restore of all involved backups and if there were any updates.

INODSE1092 **Incremental Backup does not fit to latest database restore (different backup sequence)**

Explanation The incremental backup to be restored into the database cannot be performed because the latest incremental or full backup restored and the given incremental backup are not in the expected chain.

Action Check if the incremental backup file and the most recently restored backup file really fit together.

INODSE1093 **Options "parallel" and "incremental" are mutually exclusive**

Explanation An incremental parallel backup is not supported.

Action Select only one of the options.

INODSE1094 **Tape device required**

Explanation A tape device is required, but the specified path does not point to a tape device.

Action Correct the path.

INODSE1095 **Incremental backup from timestamp must not be deleted**

Explanation A single incremental backup must not be deleted.

Action Select only full backups to be deleted. When deleting a full backup, associated incremental backups will be deleted as well.

INODSE1096 **Error errno has been signalled in the execution of an asynchronous I/O for id**

Explanation An asynchronous I/O operation has failed due to an operating system error.

Action Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by using operating system commands. Check the system log file for appropriate error messages.

INODSE1097	**An incremental backup must not be used to create a database**
Explanation	Only full backups are allowed to be used to create a database.
Action	Select a full backup to create a database.

INODSE1098	**Inconsistent backup count count1 found, expected count is count2**
Explanation	The existing incremental backups do not represent a valid sequence.
Action	Check if all incremental backups exist. If no backup is missing, please contact your software supplier.

INODSE1099	**Ambiguous keyword**
Explanation	The input does not uniquely identify a keyword.
Action	Please specify an unambiguous keyword.

INODSE1100	**Internal database error error on doctype doctype (ID). No further recovery on this doctype.**
Explanation	There was an error in an operation on a doctype. The doctype has been excluded from further recovery processing.
Action	Please contact your software supplier.

INODSE1101	**Internal error n f g h r in text index**
Explanation	A text index has encountered an error.
Action	Please contact your support center and provide them with the information given in the error message and with a backup copy of your database.

INODSE1102	**Internal error n f g h x in text index**
Explanation	A text index has encountered an error.
Action	Please contact your support center and provide them with the information given in the error message and with a backup copy of your database.

INODSE1103	**Loading of text index failed due to operating system error errno**
Explanation	This message indicates an installation error.
Action	Please consult the manufacturer's manual. If you cannot fix the error, contact your software supplier.

INODSE1104 **Journal overflow during recovery processing**

Explanation The journal space was insufficient. Recovery processing was terminated.

Action Provide more journal space. Restart the terminated activity.

INODSE1105 **Invalid structure for log space from session session number**

Explanation The log space does not contain correct log information.

Action Check if files have been moved or copied to the log space location.

INODSE1106 **Doctype doctype not found, no further recovery on this doctype**

Explanation A doctype required for recovery processing was not found. The doctype has been excluded from further recovery processing.

Action If the previous recovery processing aborted, restart the restore and recovery.

INODSE1107 **Doctype doctype locked, no further recovery on this doctype**

Explanation A doctype required for recovery processing was locked. The doctype has been excluded from further recovery processing.

Action The doctype may be locked due to an abort of previous recovery processing. Restart the restore and recovery.

INODSE1108 **Internal database error error on index index name of doctype doctype (ID). All indexes on this doctype have been dropped.**

Explanation There was an error in an operation on an index of a doctype. The index of the doctype has been disabled.

Action After the recovery has finished, recreate the index by choosing the "Check and Repair" function for the database in the Tamino Manager.

INODSE1109 **The index of doctype doctype is not accessible, recovery of this doctype will not include index**

Explanation The index remains in a disabled state from a previous abort during recovery processing.

Action After the recovery has finished, recreate the index by choosing the "Check and Repair" function for the database in the Tamino Manager.

INODSE1111 **Utility sub-function has not yet been implemented**

Explanation Although the sub-function is a valid function request, it has not yet been implemented for the utility. This is an internal message.

Action Please contact your software supplier.

INODSE1112 **Utility handling not implemented**

Explanation This is an internal message.

Action Please contact your software supplier.

INODSE1117 **No more memory can be allocated**

Explanation A utility issued a request to allocate temporary memory, but this request failed. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.

Action No action required. Please contact your system administrator for further information.

INODSE1118 **Internal configuration error**

Explanation An internal configuration error has occurred. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.

Action No action required. Please contact your system administrator for further information.

INODSE1119 **Invalid date/time specified. Valid format is YYYY-MM-DD:hh:mm:ss**

Explanation The date and time specified is invalid.

Action Specify a date and time using format YYYY-MM-DD:hh:mm:ss.

INODSE1120 **Sub-function is not valid for utility**

Explanation A sub-function was specified that is not valid for the utility.

Action Specify a valid sub-function for the utility.

INODSE1121 **Open of file path has failed due to operating system error errno**

Explanation The virtual operating system could not open the requested file.

Action Make sure that the file is available.

INODSE1122 **Service name for server servername not found**

Explanation The service name for the server was not found in the configuration store.

Action Please contact your software supplier.

INODSE1123 **SCM open failed with error rsp**

Explanation Service Control Manager open failed.

Action Please contact your software supplier.

INODSE1124 **Utility cannot run because of a pending autorepair on the database**

Explanation An attempt was made to start a utility against a database that had not terminated correctly.

Action Start the database, and let the autorepair processing complete. Then rerun the utility.

INODSE1125 **A syntax error has occurred in a utility**

Explanation A syntax error was detected in the parameters of a utility.

Action Correct the syntax error and rerun the utility.

INODSE1127 **SCM service open failed with error rsp**

Explanation Service Control Manager open service failed.

Action Please contact your software supplier.

INODSE1128 **System error errno occurred during file synchronization**

Explanation A file synchronization operation has failed at the operating system level.

Action Check the manufacturer's manual.

INODSE1130 **System error errno occurred during semaphore operation**

Explanation An error has occurred while an operation on a semaphore was requested from the operating system.

Action Check the manufacturer's manual.

INODSE1131 **Invalid server session number session number found in log space block block number**

Explanation The log space does not contain correct log information.

Action Check if files have been moved or copied to the log space location.

INODSE1132 **Invalid block sequence found in log space - expected block number1, current is block number2**

Explanation The log space does not contain correct log information.

Action Check if files have been moved or copied to the log space location.

INODSE1133 **Error opening log space: error message**

Explanation The log space could not be opened. The recovery function has been stopped.

Action Check if files have been moved or copied to the log space location.

INODSE1134 **SCM service start failed with error rsp**

Explanation Service Control Manager start service failed.

Action Please contact your software supplier.

INODSE1135 **SCM query service status failed with error rsp**

Explanation Service Control Manager query service status failed.

Action Please contact your software supplier.

INODSE1136 **Transaction aborted due to transaction timeout**

Explanation A transaction has been aborted. All changes of this transaction have been undone.

Action Check whether a higher transaction timeout value would make sense in your environment. Restart the transaction.

INODSE1137 **Transaction aborted due to non-active connection**

Explanation A transaction has been aborted. All changes of this transaction have been undone.

Action Check the reason for the transaction abort. Restart the transaction.

INODSE1138 **Transaction aborted because server session had been stopped by administrator**

Explanation A server session was explicitly stopped by the administrator. All changes of this transaction have been undone.

Action No action required.

INODSE1139 **Transaction aborted due to overflow in journal space journal space**

Explanation A transaction has been aborted because there was not enough space to log all the changes of the transaction or because too many transactions were active at the same time. All changes of this transaction have been undone.

Action Consider enlarging the journal space. Restart the transaction.

INODSE1140 **Transaction aborted due to security violation**

Explanation A transaction has been aborted. All changes of this transaction have been undone.

Action No action required.

INODSE1141 **Transaction aborted due to deadlock**

Explanation A transaction has been aborted because its locking requirements caused a deadlock with other transactions. All changes of this transaction have been undone.

Action Restart the transaction.

INODSE1142 **Transaction aborted due to internal error reason**

Explanation A transaction has been aborted. All changes of this transaction have been undone.

Action Please contact your software supplier.

INODSE1143 **Internal database error error has occurred**

Explanation The specified database error has occurred.

Action Please contact your software supplier.

INODSE1144 **The data of doctype doctype is not accessible**

Explanation The doctype may be locked or may have been corrupted by a previous action (e.g. failed server restart).

Action If the doctype is locked, wait until it is unlocked, then retry. If the doctype was corrupted by a previous action, the system administrator must rebuild the doctype from backups.

INODSE1145 **The indexes of doctype doctype are not accessible**

Explanation The indexes may have been corrupted by a previous action (e.g. failed server restart).

Action Wait for a short while, then retry. If the problem persists, this might indicate that the indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager.

INODSE1148	**I/O error on database space db space number**
Explanation	The operating system has signalled an I/O error. This is typically caused by a hardware error.
Action	Check whether any disk devices have gone offline. Check the error log for hardware errors.

INODSE1149	**Too many paths specified for a location**
Explanation	Only 8 paths are allowed to be specified for a location.
Action	Use less paths for the location to be set up.

INODSE1150	**The indexes of doctype doctype are corrupt, reason rsp**
Explanation	An internal inconsistency has been found in the indexes.
Action	The indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager.

INODSE1153	**filename is an invalid file name for a database space**
Explanation	The specified file name for a database space is not valid.
Action	Specify a valid file name for a database space.

INODSE1154	**Internal database error has occurred**
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INODSE1155	**filename is not a database space for server dbname**
Explanation	The specified file name is not a database space for the given database name.
Action	Make sure that the file name of the database space is a database space of the specified database.

INODSE1158	**I/O subsystem error (e1/e2): error text**
Explanation	An error in an I/O related function has occurred.
Action	Please contact your software supplier.

INODSE1167 **standard length out of range**

Explanation The specified length value is invalid.

Action Correct the length specification.

INODSE1171 **FI only allowed if standard-length is given**

Explanation The FI option is only allowed if a non-zero standard length is given.

Action Correct the input line.

INODSE1172 **Wrong input file assigned**

Explanation The wrong input file has been used for the utility.

Action Ensure that the correct input file is being used by the utility.

INODSE1173 **Checked and repaired database. Number of corrupted indexes was number. Of these, repairing failed for failed.**

Explanation The database could not be completely repaired.

Action Please contact your software supplier.

INODSE1175 **Invalid load data structure at file (ID id, length length)**

Explanation The structure of the data to be loaded is invalid.

Action Ensure that the correct input file is being used. Send the load files (extension 1C0/1C1) to your software supplier.

INODSE1176 **Unable to attach to shared memory**

Explanation It is not possible to attach the process to the shared memory.

Action Ensure that there is enough available memory, and contact your software supplier if required.

INODSE1181 **An unexpected server response (response) has occurred**

Explanation The specified response has been returned by the server.

Action Determine the reason for the response, or contact your support center.

INODSE1182 **Database server is not accessible**

Explanation It is not possible to access the database server.

Action Determine the reason why the database server is not accessible and retry the operation.

INODSE1189 **Reorganize database is not permitted while database is active**

Explanation To preserve data consistency, the database must not be active while reorganize function is processed.

Action Shut down the database

INODSE1194 **An internal buffer is too large (size)**

Explanation The size of an internal buffer has caused a record to overflow.

Action Please contact your software supplier.

INODSE1198 **Event token not supplied**

Explanation The recovery function was started without supplying an event token.

Action Check the usage of the administration tool.

INODSE1199 **Logging not disabled**

Explanation When the recovery function is started, logging must be disabled. In this case, the recovery function was started with logging enabled.

Action Check the usage of the administration tool.

INODSE1200 **Database name is too long**

Explanation The specified database name is too long. If the database name consists of ASCII characters, it can be up to 16 characters long. If the database name consists of multibyte characters, the total number of bytes required to store the database name must not exceed 16.

Action Please specify a shorter database name.

INODSE1201 **Database name contains invalid character "," (comma)**

Explanation A database name cannot contain a comma.

Action Please modify the database name.

INODSE1202 **Database name contains an invalid character**

Explanation A database name cannot contain certain characters, such as # " . [ ] .

Action Please modify the database name.

INODSE1203 **Database name contains invalid character "" (backslash)**

Explanation A database name cannot contain a backslash.

Action Please modify the database name.

INODSE1204 **Administration function terminated with error errornumber: errorstring**

Explanation An administration function failed with given error string.

Action Please restart the command using the option to write a job log and check if there is additional error information. If not, contact your software supplier.

INODSE1205 **Replication permission denied for hostname**

Explanation The host name is not in the master's list of permitted databases for replication

Action Add the host name of the replication instance to allow replication.

INODSE1206 **Cannot connect to master dbname on hostname**

Explanation An attempt accessing the master database failed.

Action Check that the master database is active on the specified node and retry the command.

INODSE1209 **Maximum number of space files reached**

Explanation The maximum allowed number of data/index files has been reached.

Action Please contact your software supplier.

INODSE1210 **Size of space file too large**

Explanation The size of the file to be created exceeds the limits of the operating system or of the underlying storage medium. For example, you want to create a file with a size greater than 2GB, but the operating system does not support this.

Action Select a smaller file size.

INODSE1212 **Internal free space error**

Explanation An unexpected free space management error occurred when adding a new database file.

Action Please contact your software supplier.

INODSE1213 **Error error accessing or modifying information in the internal configuration store**

Explanation The information for a log space or a savepoint entry could not be retrieved or set up.

Action Check the reasons for errors accessing and updating the internal configuration store (for example permissions or low disk space).

INODSE1214 **An error occurred during a create index process on doctype doctype**

Explanation The error is caused by an attempt to create a unique index on data that contains non-unique values.

Action No action required.

INODSE1215 **Database name contains a space**

Explanation A database name cannot contain a space.

Action Please modify the database name.

INODSE1217 **Error when opening database space, compressed state is not permitted (at path)**

Explanation The database file has the compressed attribute, which is not permitted, because write errors should be avoided if the device is getting full.

Action Remove the compressed attribute from the database file.

INODSE1221 **Error error when accessing internal information for savepoint savepoint**

Explanation The information for a savepoint entry could not be retrieved.

Action Contact your software supplier.

INODSE1222 **Error error when trying to move or delete file name**

Explanation A backup file or a file for recovery purpose could not be moved or removed.

Action Contact your software supplier.

INODSE1223 **Log space not found for savepoint savepoint, session number session number**

Explanation A log space entry for the given savepoint and session number could not be found.

Action Contact your software supplier.

INODSE1224 **Backup space not found for savepoint savepoint**

Explanation A backup space for the given savepoint could not be found.

Action Contact your software supplier.

INODSE1225 **Backup file type file type is invalid for savepoint savepoint**

Explanation The internal information for the file type associated with a savepoint is set up incorrectly.

Action Contact your software supplier.

INODSE1226 **Unexpected return code error when executing function function**

Explanation An internal error occurred.

Action Please contact your software supplier.

INODSE1231 **Errors have occurred during autorepair**

Explanation The autorepair from the crash of the previous server session was not completely successfully.

Action Check the detailed error messages and repair the affected data.

INODSE1232 **Database space is too large**

Explanation The database space specified for the current operation is too large.

Action Retry the operation specifying a smaller database space.

INODSE1233 **The limit of extents for container_name has been reached**

Explanation No more extents of the specified space type can be created because the maximum number has been reached.

Action Retry the operation with a smaller number of extents specified.

INODSE1234	**Server parameter 'number of backup generations' larger than 1 required**
Explanation	Supplying replication data requires log spaces to be kept for more than one backup.
Action	For a master server set the server property 'number of backup generations' to value larger than 1.

INODSE1235	**Crash dump file filename could not be created due to operating system error system errno (errtxt)**
Explanation	The backup file needed for error analysis could not be created due to the given reason.
Action	Please consult the manufacturer's manual.

INODSE1236	**Recovery skipping has terminated with an error**
Explanation	An error occurred during recovery skipping. This message indicates an internal inconsistency.
Action	Please contact your software supplier.

INODSE1247	**Replication processing disabled because master database was restored without full recovery**
Explanation	When the master database was restored not using 'recover all' option, synchronization is lost by updates already replicated but not recovered for the master database.
Action	Delete the replication database and set it up again using a backup created after the restore was done.

INODSE1289	**Error when opening database space space no (at path): size mismatch**
Explanation	The size of the database space is not equal to the size expected by the server.
Action	Please contact your software supplier.

INODSE1290	**I/O error occurred on database space space no. System error errno caused by operation operation on block block number.**
Explanation	The operating system has signalled that the specified I/O operation has failed.
Action	Please consult the manufacturer's manual.

INODSE1292	**Creation of database space space no (path) has failed**
Explanation	The database space could not be created at the specified location.
Action	Look for other error messages to find the reason for the failure.

INODSE1293 **Creation of database space space no (path) has failed due to system error errno**

Explanation The database space could not be created at the specified location because of an error signalled by the operating system.

Action Please consult the manufacturer's manual.

INODSE1295 **Creation of journal space 1 (path) has failed**

Explanation The database space could not be created at the specified location.

Action Look for other error messages to find the reason for the failure.

INODSE1318 **Internal server error during database creation, reason: reason**

Explanation The system has tried to allocate a new database space, probably because the existing database spaces did not contain enough free space. The allocation has failed.

Action Check which database space was affected by checking the free space. Allocate another database space manually.

INODSE1320 **Log space structure error error number**

Explanation The log information which is needed to recover the database is corrupt, so the database recovery was stopped when the corruption was detected.

Action Send the log space to your software supplier for analysis.

INODSE1358 **Creation of database space space no (path) has failed because the file already exists**

Explanation The database space could not be created at the specified location because the file is already present.

Action Remove or move the file to another location before repeating the action.

INODSE1374 **No abbreviation allowed for this keyword**

Explanation The specified keyword must not be abbreviated.

Action Please specify the keyword in full length.

INODSE1375 **Invalid keyword**

Explanation The specified keyword is not recognized or invalid.

Action Please specify a correct keyword.

INODSE1376 **Syntax error**

Explanation An internal syntax error occurred.

Action Please contact your software supplier to analyze the problem.

INODSE1380 **Given value not numeric**

Explanation The given value has to be in a numeric format.

Action Please specify a numeric value.

INODSE1381 **Only number value(s) allowed**

Explanation The number of allowed list elements is exceeded.

Action Please limit the number of list elements to the maximum allowed.

INODSE1382 **Value has to be greater than or equal to minvalue**

Explanation The specified value is too low.

Action Please enter a value greater than or equal to the required minimum.

INODSE1383 **Value has to be less than or equal to maxvalue**

Explanation The specified value is too high.

Action Please specify a value less than or equal to the allowed maximum.

INODSE1385 **Invalid range specified**

Explanation The range specified is invalid.

Action Please specify a range within the allowed limits.

INODSE1386 **At least minnum character(s) required**

Explanation The specified number of characters was too low.

Action Please specify a sufficient number of characters.

INODSE1387 **Only maxnum character(s) allowed**

Explanation The maximum allowed number of characters was exceeded.

Action Please specify no more than the maximum allowed number of characters.

INODSE1390 **Missing mandatory parameter param**

Explanation The displayed mandatory parameter could not be found and a default value is not available.

Action Supply the displayed mandatory parameter.

INODSE1391 **Invalid parameter value**

Explanation The specified parameter value is invalid.

Action Correct the input.

INODSE1413 **System error errno when opening database space space no (path)**

Explanation The specified operating system error has occurred.

Action Please consult the manufacturer's manual.

INODSE1416 **architecture mismatch detected, file from platform**

Explanation The crash dump file is from a different platform.

Action Go to the proper platform.

INODSE1419 **Incremental backup from timestamp must not be deleted**

Explanation A single incremental backup must not be deleted.

Action Select only full backups to be deleted. When deleting a full backup, associated incremental backups will be deleted as well.

INODSE1421 **Backup time has become invalid**

Explanation An earlier backup was used for a restore not using the recover all option. Due to new modifications done on this base, the newer backup must not be used for restore/recover.

Action Use another backup for restore/recover. The selected backup can only be used to create new database.

INODSE1498 **unknown option**

Explanation The option specified is unknown.

Action Correct the input line.

INODSE1506 **option not permitted**

Explanation The supplied option is not permitted for this function.

Action Check the input parameters.

INODSE1512 **transition to this level not allowed**

Explanation The specified level number is not allowed in this context.

Action Correct the input line.

INODSE1523 **reserved field name**

Explanation The specified field name is reserved.

Action Correct the field name.

INODSE1538 **Read-only mode is not permitted because the previous session was abnormally terminated**

Explanation The Tamino server cannot be started in read-only mode because the previous session was abnormally terminated.

Action Start the Tamino server in normal mode to do an autorepair for the abnormal termination. Restart the Tamino server in read-only mode.

INODSE1539 **Read-only mode is not permitted because of pending transactions**

Explanation The Tamino server cannot be started in read-only mode because of pending global transactions.

Action Start the Tamino server in normal mode and close the pending global transactions.

INODSE1603 **Error when adding a new type**

Explanation An unexpected error occurred while adding a container.

Action Check the device and the environment variable relating to the new container.

INODSE1604 **Number of additional cont extents currently exhausted**

Explanation The maximum number of created database spaces within one session has been reached.

Action Shut down and restart the database server and retry the operation.

INODSE1605 **No space for extending database space**

Explanation There is no more space on the disk for extending the current database space.

Action Check the disk size where the latest database space is located. Think about creating a new database space on another disk where space is available.

INODSE1606 **Database space to be removed is in use**

Explanation The request to remove a database space failed because the file space at the end of the file is in use.

Action Ensure that the database space is not in use and retry the operation.

INODSE1633 **Recovery terminated with error**

Explanation An error occurred during database recovery.

Action Check for additional error messages in the event log.

INODSE1769 **Invalid database root block header (size blocksize / next block)**

Explanation A database root block linkage is invalid.

Action Perform a restore/recover of the database.

INODSE1898 **The specified doctype is not available.**

Explanation It is not possible to access the specified doctype.

Action Check that the correct doctype name has been specified, and that it is currently available for use.

INODSE1913 **File file not loaded**

Explanation The file with the given number could not be loaded

Action Check whether the file exists or is not accessible.

INODSE1945 **Function not permitted while server is running**

Explanation The given function is invalid with an active server.

Action Shut down the server.

INODSE1976 **Internal database error error during recovery processing**

Explanation While processing a log space, re-applying updates resulted in an error.

Action Check if the database was in a different state than it was when the original command was executed. This may be caused by using a backup copy and log spaces inconsistently.

INODSE1979 **Database space space has reached the upper limit**

Explanation The maximum size of the given database space has been reached. This means the database cannot be extended any more.

Action A database redesign is necessary. Either delete doctypes from the database or create a second database.

INODSE1984 **Allocation of a new data space failed on required index allocation (reason)**

Explanation The database space (data) cannot be enlarged. The new database space requires allocations in the index space, but the index space allocation failed due to the internal reason displayed.

Action Investigate why the index database space cannot be enlarged.

INODSE1987 **Error when extending type**

Explanation A database space extension failed, so the database could not be enlarged.

Action View the subsequent error message for information about why the database could not be enlarged.

INODSE1992 **Invalid container request type**

Explanation An internal error occurred while accessing a database container file.

Action Contact your software supplier and report the number displayed in the message.

INODSE1995 **Access to configuration information for savepoint 'ts' failed: msg**

Explanation The backup with the given representation could not be determined in the database configuration.

Action Contact your software supplier to analyze the problem.

INODSE1996 **Database is inconsistent, restore required**

Explanation The database is in an inconsistent state that cannot be handled by the autorepair process. The database must be restored.

Action The reason for an inconsistent database can be re-applying a mass load during recovery. If no abort timestamp is shown in the event log of the aborted session, perhaps due to a power failure, restart with restore/recover. For any other reasons that will cause the error to re-occur, set up the restore/recover until a timestamp shortly before the recovery abort shown in the event log of the aborted session.

INODSE1999 **Internal database error error during recovery processing on doctype doctype**

Explanation While processing a log space, re-applying the updates resulted in an error.

Action Check if the database is in a different state than it was when the original command was executed. This may be caused by using a backup copy and log spaces inconsistently.

INODSE2000 **Starting replication failed**

Explanation Replication processing could not be started.

Action Check for for additional related messages in the event log.

INODSE2001 **Replication processing cannot be continued due to previous replication error**

Explanation An error during the previous replication processing prevents the continuation of the replication.

Action If the master database is lost, the Reset Replication function can be used to convert the database for usage as a substitution. In any other case, the replication database has to be recreated using a new backup from the master database.

INODSE2004 **Invalid operation detected**

Explanation Replication cannot be continued because a function (e.g. restore without full recover) was executed on the master database which is not yet supported for replication

Action A backup from the master database after the operation in question should be used to recreate the replication database.

INODSE2013 **Database identification already in use**

Explanation The database identification supplied is already in use.

Action Repeat the process using an unused database identification.

INODSE2014	**Failed to enumerate databases**
Explanation	An internal call has failed to enumerate the defined database names.
Action	Please contact your software supplier.

INODSE2019	**No log space data found for session session number**
Explanation	The master database could not find the log space to return the required log space data.
Action	Check the database properties for the number of backup generations and increase the value if set too low.

INODSE2020	**Replication database(s) defined, rename not allowed**
Explanation	The rename function is not allowed for a database which is to be used as a master database for replication purposes.
Action	Remove replication databases first before renaming the database. New replication databases can be created from a backup created after the rename operation.

INODSE2022	**Replication permission denied by master database**
Explanation	The name of the replication database was not found in the master database's list of permitted databases.
Action	Add the replication database name to the list of permitted replication databases of the master database.

INODSE2023	**Replication database origin mismatch**
Explanation	The replication database does not match the contents of the master database.
Action	Check whether the replication database was created using a backup from another database than the one specified as master database or check whether another database was renamed using the same database name as the master database's name.

INODSE2024	**An internal utility parameter error (location) has occurred**
Explanation	An internal parameter error has caused the utility to fail.
Action	Please contact your software supplier.

INODSE2031 **Internal error occurred: DSIF func [mod - line] what parameter param**

Explanation An internal error occurred.

Action Please contact your software supplier and provide the message text.

INODSE2033 **Internal error occurred: OVO func [mod - line] error**

Explanation An internal error occurred.

Action Please contact your software supplier and provide the message text.

INODSE2034 **Internal error occurred: SMP func [mod - line] error**

Explanation An internal error occurred.

Action Please contact your software supplier and provide the message text.

INODSE2035 **Server communication interface [mod - line] error error**

Explanation An unexpected error was returned by the server communication interface.

Action Please contact your software supplier and provide the message text.

INODSE2036 **path is not a valid directory**

Explanation The directory specified does not exist.

Action Specify a valid directory name.

INODSE2037 **Insufficient free disk space on path - available avail MB, needed needed MB**

Explanation There is not enough space in the given directory to complete the operation.

Action Free some disk space or specify another directory.

INODSE2042 **File file already exists in the destination directory dir**

Explanation The file cannot be created in the destination directory because another file with the same name already exists.

Action Change the destination directory parameter.

INODSE2043 **Infofile cannot be created, because otherwise the full path name of the info file would exceed operating system limit**

Explanation The infofile path is too long.

Action Please specify another directory for the CD database.

INODSE2045 **File path does not exist**

Explanation An invalid path was specified.

Action Specify a valid path.

INODSE2046 **Failed to parse infofile , line 'line'**

Explanation The CD database infofile could not be parsed.

Action Please contact your software supplier.

INODSE2048 **Cannot create database, because there are too many databases already**

Explanation A new database cannot be created because there are too many databases already.

Action Check if you still need all the databases you created and if possible delete some of them.

INODSE2050 **Requested operation not permitted in online mode**

Explanation The server must be offline to perform the requested operation.

Action Shut down the database.

INODSE2061 **Work pool too small**

Explanation The work pool used is too small.

Action Ensure that a sufficiently large work pool is available.

INODSE2064 **Invalid infofile format**

Explanation The CD database information file has an invalid format.

Action This error should not occur unless the file was modified manually. Avoid manual modification in the information file.

INODSE2065 **Incompatible operating system (original database was created on operating system)**

Explanation The CD database cannot be created because the database is incompatible with the target platform.

Action Create the CD database on the same platform as the original database.

INODSE2067 **Operation not allowed on read-only or CD databases**

Explanation The required operation cannot be performed on a CD database or read-only database.

Action Switch the "read only" server parameter to "no". This does not apply to databases on CD.

INODSE2069 **Location with the same name already exists**

Explanation A location with the same name already exists.

Action Choose another location name.

INODSE2070 **Cannot delete default location or default backup location**

Explanation There was an attempt to delete the default location or default backup location. Delete operations on these locations are not allowed.

Action No action required.

INODSE2071 **Location with the same path settings already exists**

Explanation A location with the same path settings already exists

Action Choose another location path.

INODSE2072 **Location locname not found**

Explanation The specified location was not found.

Action Correct the location name parameter and try again.

INODSE2080 **Internal error occurred: DSIF func [mod - line] not allowed in this context**

Explanation An internal error occurred.

Action Please contact your software supplier and provide the message text.

INODSE2081 **Internal error occurred: OVO memory what(bytes) [mod - line] error**

Explanation An internal error occurred.

Action Please contact your software supplier and provide the message text.

INODSE2082 **Granting port allocation lock failed with response err - int_err**

Explanation Unexpected response received while trying to lock the port allocation lock.

Action Please contact your software supplier.

INODSE2084 **Invalid port value port detected, valid port values are between portmin and portmax**

Explanation An invalid port value was detected.

Action Please specify a valid port value.

INODSE2085 **Invalid port range r1 - r2 detected, minimum min ports required in range**

Explanation A port range has to contain a minimum number of ports.

Action Please specify a valid port range.

INODSE2086 **Static port range r1 - r2 and dynamic port range r3 - r4 overlap**

Explanation Static and dynamic port range overlap, which is not allowed.

Action Please specify valid port ranges.

INODSE2087 **Port check function could not read static and / or dynamic port range**

Explanation An error occurred while retrieving the static and dynamic port range.

Action Please contact your software supplier.

INODSE2088 **The given dynamic port range r1 - r2 is not free**

Explanation At least one port in the given dynamic port range is already in use by another server.

Action Please specify a dynamic port range where no ports are used by other servers.

INODSE2092 **Internal error occurred: DSIF func [mod - line] invalid combination of parameters**

Explanation An internal error occurred.

Action Please contact your software supplier and provide the message text.

INODSE2093 **Web server webserver not registered**

Explanation The given web server is not registered.

Action Specify a registered web server.

INODSE2094 **Web server webserver not correctly registered**

Explanation The web server is not correctly registered. Either the IP address or the port number is missing.

Action Correct the web server registration.

INODSE2095 **Web server webserver not assigned to database dbname**

Explanation The web server is not assigned to the database.

Action Check your web server registrations.

INODSE2096 **Environment extension envext not registered for Tamino what what1**

Explanation The environment extension is not registered in the Tamino configuration.

Action No action required.

INODSE2097 **No environment extension registered for Tamino what what1**

Explanation No environment extension registered for Tamino version or server.

Action No action required.

INODSE2099 **No extension point definitions found for version version**

Explanation No extension point definitions were found for the specified version.

Action Check your configuration.

INODSE2103 **Invalid port range r1 - r2 detected**

Explanation An invalid port range was detected.

Action Specify a valid port range.

INODSE2104 **Component comp already exists for extension point extp in version vers**

Explanation The component already exists for the extension point in the specified version.

Action No action required.

INODSE2105 **Component comp already exists for extensions in version vers**

Explanation The component already exists in the extension section of the specified version.

Action No action required.

INODSE2106 **Component comp does not exist for extension point extp in version vers**

Explanation The specified component is not defined for the given extension point and version.

Action No action required.

INODSE2107 **Component comp does not exist in extensions for version vers**

Explanation The specified component does not exist in the extensions for the given version.

Action No action required.

INODSE2108 **Could not find function func for extension point extp, version vers, component comp**

Explanation The extension point function was not found in the specified extension point library.

Action Check library name, path and entry points of the extension point library.

INODSE2109 **Extension point extp does not exist in version vers**

Explanation The specified extension point does not exist in the given version.

Action No action required.

INODSE2110 **Could not load library lib for extension point extp, version vers, component comp**

Explanation The extension point library could not be loaded via the specified path.

Action Check the library name and path of the extension point definitions.

INODSE2111 **Could not allocate a port, because the static port range is full**

Explanation No port could be allocated in the static port range, because it is full.

Action Extend the static port range, use a port from outside the static port range or force reusage of a port from the static range.

INODSE2114 **Port allocation function could not read static and / or dynamic port range**

Explanation An error occurred while retrieving the static and dynamic port range.

Action Please contact your software supplier.

INODSE2117 **Granting raw section lock failed with response err - int_err**

Explanation Unexpected response received while trying to lock the raw section lock.

Action Please contact your software supplier.

INODSE2121 **Web server webserver is already registered, rename is not allowed**

Explanation The web server specified is already registered. Therefore the rename is not allowed.

Action Choose another name for the web server or delete the existing web server.

INODSE2124 **Internal error occurred: func [mod - line] what parameter param**

Explanation An internal error occurred.

Action Please contact your software supplier and provide the message text.

INODSE2125 **Web server webserver is already registered**

Explanation The specified web server is already present.

Action Update the web server.

INODSE2126 **database space of database server in raw section section is in use and must not be reallocated**

Explanation The specified database spaces are in use and must not be reallocated.

Action No action required.

INODSE2127 **database space of database server not present in raw section section**

Explanation The specified database space(s) could not be found in the raw section.

Action Please contact your software supplier.

INODSE2129 **pathname does not specify a regular file (returned type error)**

Explanation The given path does not specify a regular file.

Action Specify a regular file.

INODSE2130 **database space of database server in raw section section is in use and must not be deallocated**

Explanation The specified database spaces are in use and must not be deallocated.

Action No action required.

INODSE2134 **Index recreation not permitted at this item**

Explanation This item has no data records, therefore a reinvert cannot be performed.

Action Use the X-Machine programming command "admin" to recreate the index.

INODSE2135 **database space space number of server server not found**

Explanation The specified database space could not be found.

Action Correct the database space specification and try again.

INODSE2136	**database space of database server in raw section section is in use and must not be changed**
Explanation	The specified database space is in use and must not be changed.
Action	Ensure that the database space is not in use before changing it.

INODSE2137	**Database server is active, database spaces must not be moved**
Explanation	The database is active. Therefore database spaces must not be moved.
Action	Stop the database before moving any database spaces.

INODSE2138	**Granting container move lock failed with response err - int_err**
Explanation	An unexpected response was received while trying to grant the container move lock.
Action	Please contact your software supplier.

INODSE2140	**Error while reading data reference block block into internal pool**
Explanation	An unexpected error occurred while reading a data reference block into the internal cache.
Action	Please contact your software supplier.

INODSE2141	**Load file has unexpected structure level lev (compatibility comp)**
Explanation	The input file for a data load operation has a structure level mismatch, or the file is corrupted.
Action	Check if the input file has the wrong structure level or is corrupted.

INODSE2142	**Internal error occurred: DSIF func [mod - line] invalid parameter handle (parhdl) supplied**
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.

INODSE2143	**Server parameter "param" not available in current context**
Explanation	A server parameter was requested in an invalid context.
Action	Please contact your software supplier.

INODSE2144 **Invalid server parameter name "param" supplied**

Explanation The given server parameter name is invalid.

Action Specify a valid server parameter name.

INODSE2145 **Static server parameter "param" must not be changed online**

Explanation Static server parameters must not be changed while the server is active.

Action Stop the server before changing a static parameter.

INODSE2157 **Due to license restrictions, raw section access is not allowed**

Explanation The license file does not contain the permission to access raw sections.

Action Use the file system instead or obtain the required license from your software supplier.

INODSE2160 **Upgrade is not allowed for replication database**

Explanation An upgrade is not allowed for a replication database.

Action If the master database has been upgraded, the replication database must be newly created from the master backup.

INODSE2162 **Physical extent count 0 detected at typ**

Explanation The management of physical database spaces has an empty counter.

Action The database seems to be physically corrupted. Perform a restore/recover.

INODSE2163 **First Index blocksize incompatible (bls)**

Explanation The blocksize field of first index space does not match the real blocksize.

Action No action required.

INODSE2164 **Physical extent entry error (typ first - last)**

Explanation The physical management of the database is corrupted.

Action Perform a restore/recover.

INODSE2167 **Check for tape device failed on path. Check that the path is correct and whether tape is in drive.**

Explanation It was no possible to verify that the specified path points to a tape device.

Action Make sure that the path is correct, that the tape is in the drive, that the tape device is online and the tape device is properly connected to the system.

INODSE2168 **Location type mismatch - expected 'type1' , found 'type2'**

Explanation This error can occur during 'Add Location', if the requested location type does not match the actual file type.

Action Specify the correct location type.

INODSE2169 **Received response rsp (intrsp) while starting server**

Explanation Starting the server failed.

Action Please contact your software supplier.

INODSE2170 **Received response rsp (intrsp) while stopping server**

Explanation Stopping the server failed.

Action Please contact your software supplier.

INODSE2173 **Unexpected internal server error: errorstring**

Explanation An internal server call failed with given error string.

Action Please look into the server job log if there is additional error information. If not, contact your software supplier.

INODSE2175 **Unexpected internal server error: errorstring, location location**

Explanation An internal server call failed with given error string.

Action Please look into the server job log to see if there is additional error information. If not, contact your software supplier.

INODSE2178 **Doctype doctype is locked by another user**

Explanation The doctype has a lock conflict with a running action of another user.

Action Investigate which user is active and what activity is causing the lock.

INODSE2179 **Upgrade from version from_version to version to_version not supported**

Explanation The required database conversion between the stated versions is not supported.

Action Consult the documentation about possible upgrade options.

INODSE2187 **Cannot determine file type from path**

Explanation An unexpected error occurred while Tamino tried to determine the file type of the displayed location.

Action Check if the displayed location is accessible. If the location is accessible please contact your software supplier.

INODSE2192 **The maximum number of threads allowed per process (max_threads) is too low to start and manage the Tamino server**

Explanation The current parameter configuration does not allow the creation of all necessary threads to start and manage the Tamino server.

Action Either the system defined maximum number of threads per process is too low and should be increased, or the Tamino parameter configuration should be changed to decrease the number of threads to be created.

INODSE2193 **Insufficient system resources to create thread: thread 'name', error error returned by thread create function**

Explanation There are not enough system resources available to create a new thread.

Action There are not enough system resources available to create a new thread. The reason for that is either that the system defined maximum number of threads per process is exceeded, or that there is not enough memory available to allocate the necessary thread resources.

INODSE2194 **Restore from backup made in version old_version not supported to upgrade to new_version**

Explanation A backup made in the old version cannot be used, e.g. because this old version is not supported any more. This only applies for databases that are already in a higher version than the backup.

Action Use a more recent backup to restore the database.

INODSE2200 **Master database master dbname is not active**

Explanation An attempt was made to execute a replication command that requires the master database to be active.

Action Start the master database and retry the command.

INODSE2201 **Replication database replication dbname is active**

Explanation An attempt was made to execute a replication command that requires the replication database to be offline.

Action Stop the replication database and retry the command.

INODSE2202 **Master database must be restarted before a replication database can be set up**

Explanation A restart of the master database is necessary.

Action Restart the master database and try to set up the replication database again.

INODSE2203 **Update server sessions exist**

Explanation The database already has update sessions so it cannot be used to replicate another database.

Action Use a newly created database and retry this operation.

INODSE2204 **Replicate master database master dbname not permitted**

Explanation Permission to replicate the master database was denied.

Action Ask the administrator to permit replication access to the master database.

INODSE2205 **Inconsistency detected while setting the database to replication type**

Explanation This database is not suitable to be set as the replication database of the specified master database. Perhaps the versions are not identical or this one was not created from the backup of the master. Also possible is that this database has its own updates after the creation.

Action Use another database to replicate the master.

INODSE2206 **No permission to modify the type of the database**

Explanation To change the type of a database to a replication database or to set it back to a normal one, the user needs to have administrator rights. Other possible reason: The database is not allowed to replicate the master database.

Action Log in as administrator and try the operation again and check whether this database is in the permission list of the master database.

INODSE2208 **Internal error occurred: modification not allowed for replication database.**

Explanation An internal error occurred. The server will be stopped.

Action Please contact your software supplier and provide the message text.

INODSE2211 **No valid location provided for backup**

Explanation There can be a number of reasons for this error, for example no free space or the location directory was deleted outside of Tamino. The exact reason for the error is contained in the job log.

Action Study the job log to find the exact reason for the error. If the job log indicated that there is no space, free some space on the location device. Alternatively, you may provide another location for the backup.

INODSE2212 **The names of master and replication databases cannot be identical**

Explanation Identical names have been supplied for the master and a replication database, but this is not allowed.

Action Supply different names.

INODSE2213 **A former replication database cannot be set to replication type**

Explanation After a replication database has been reset by 'Set Type to Normal Database', it cannot become a replication database any more.

Action Delete the database, recreate it from a non-initial backup of the master and execute 'Set Type to Replication'.

INODSE2214 **Data field layout block rabn, invalid periodic group count count for fieldname**

Explanation The data field layout block with the given number is corrupted.

Action No action required.

INODSE2215 **Activity currently not permitted**

Explanation This error may occur when the server is in the starting or stopping phase. During these phases the server is neither online nor offline. The other reason for this error is when the server is offline and there are some activities on the database in parallel, e.g. adding some index space.

Action Wait until the server is definitely online or offline and than retry.

INODSE2216 **Operation is not permitted during a standby server session**

Explanation The operation cannot run in parallel with another operation that requires the server to be running in standby mode.

Action A standby session is used for the restore/recover operation. Wait until this operation is finished and the server is shut down.

INODSE2217 **Operation not allowed for external backup**

Explanation An external backup is an invalid object for this operation.

Action Some database operations are not allowed for external backups.

INODSE2218 **File currently locked**

Explanation A recovery input file must not be moved because it is used by the server.

Action Try to perform the operation later. A log space will be unlocked after a session switch. Other recovery input files will be unlocked after the termination of a mass load.

INODSE2219 **Savepoint not found for internal key key**

Explanation Necessary configuration information was not found.

Action Please contact your software supplier.

INODSE2220 **File filename does not exist**

Explanation A registered backup or recovery file to be moved or deleted does not exist.

Action Check the locations used for the database whether files have been lost due to unintended removal or restore operations.

INODSE2221 **File filename already exists**

Explanation A registered backup or recovery file to be moved already exists.

Action Check the locations used for the database whether files are present due to restore operations or files remaining from a deleted database.

INODSE2222 **File filename could not be moved**

Explanation Moving a backup or recovery file failed.

Action Check access control settings of the location where the file is to be moved.

INODSE2223 **File filename could not be removed**

Explanation Removing a backup or recovery file failed.

Action Check access control settings of the file to be deleted or of the source file to be moved.

INODSE2229 **Backup time has become invalid**

Explanation An earlier backup was used for a restore not using the recover all option. Due to new modifications done on this base, the newer backup must not be used for restore/recover.

Action Use another backup for restore/recover. The selected backup can only be used to create new database.

INODSE2231 **Cannot create initial backup**

Explanation This error can appear during database creation. There are a number of reasons why the creation of the initial backup might fail e.g. a file with the same name already exists in the backup location, a tape is not ready (if the backup medium is tape) or no reading process is attached to a pipe (if backup medium is pipe). The root cause of the error will be given in the job log.

Action Read the job log to find the root cause of the error. If there is the file with the same name as the initial backup name in the backup location on the file system, remove this file or move it to another place. If the backup medium is tape , ensure that the tape is ready. If the backup medium is a named pipe, ensure that there is a process reading from this pipe.

INODSE2232 **XML port must not be set to zero if the communication method includes native TCP/IP**

Explanation If native TCP/IP is used as a communication method for the Tamino server the TCP/IP port used must not be set to zero.

Action Use a valid port number for TCP/IP communication.

INODSE2233 **The database dbname must be online**

Explanation The database must be started for this operation.

Action Start the database.

INODSE2236 **Stopping database failed, reason: reason**

Explanation In specific situations it is not possible to shut down the database with rolling back open transactions. This is: 1. a mass load is active 2. an external backup is active 3. there is a LOG file full situation.

Action Wait until a mass load or external backup operation is finished and try again. If the log file is full, supply space for the LOG and try again.

INODSE2237 **No privilege to modify database, concurrent modifying process is currently active**

Explanation There is another modifying job or process active or the server is within startup. Those actions must be serialized.

Action Check your database state and wait until the server is up or check other modifying database actions.

INODSE2241 **Internal error occurred: DSIF func returncode returncode error error**

Explanation This is an internal error message.

Action Please contact your software supplier.

INODSE2242 **Replication instance replication dbname not found in the permission list**

Explanation An attempt was made to remove a replication instance from the permission list which does not exist.

Action Retry the command with a correct name.

INODSE2243 **Replication instance replication dbname already present in the permission list**

Explanation An attempt was made to add a replication instance to the permission list which already exists .

Action Retry the command with a correct name.

INODSE2249 **Physical file extent (extent) missing**

Explanation The database file has been divided among more than one physical file extents. Now while processing this file the given extent is not specified.

Action Specify all physical file extents.

INODSE2250 **A further extent of source cannot be created, because current file is incomplete**

Explanation The support of multiple physical file extents requires that the current file is completely written. However with network file systems (e.g. NFS) if getting full, the current file is less in size than expected. Therefore the switch to the next location is impossible in this case. A local file system should not have those problems.

Action Be sure that you have enough space at your file system because this one can only support one single file extent. Or take locally attached file systems.

INODSE2258 **Inconsistent usage or missing filetype file extent during processing extent extent**

Explanation Multiple physical file extents specified by the user are not consistent. Either the extent is missing, unexpected or specified twice or the file does not come from the same database.

Action Enter all required file extents and verify if they are from the same database.

INODSE2263 **(Re)Move of a single file extent is not possible because there is a reference from another database**

Explanation If the backup consists of multiple file extents it is not possible to (re)move single extents when another database has a reference to it.

Action Check which database references the backup.

INODSE2264 **Function not permitted for a replication database**

Explanation An administration function could not be executed because it must not be used for a replication database.

Action Check whether the function is to be executed for the master database.

INODSE2265 **Database is inconsistent and cannot be used**

Explanation During migration or restore/recover, the database is in an undefined state which cannot be solved. The database cannot be started anymore.

Action Recover from the latest valid backup or if not possible contact your software supplier.

INODSE2268 **Database refused startup after conversion**

Explanation During migration the database cannot be started because of an internal error.

Action View the server's startup text file (inosrv.txt) for more information.

INODSE2274 **Server died during startup**

Explanation The server died during the startup phase.

Action Inspect the server output file and correct the error.

INODSE2275 **Property propertyname must not be changed for read only / replication database**

Explanation The operation mode of the database is not suited for changes in this property. Changing it would jeopardize the database consistency.

Action For a read only database, if you really want to change the parameter, set the "read only" property to "no", modify the parameter, start the database, stop the database, set "read only" property to "yes".

INODSE2279 **Invalid version version of the conversion component**

Explanation There is no conversion utility of the most recent version found.

Action Upgrade the conversion only to the current one.

INODSE2282 **Open of source (path) has failed due to operating system error errno (errtxt)**

Explanation The file specified cannot be opened due to an internal operating system error.

Action Consult the manufacturer's manual.

INODSE2283 **io error error (errtxt) on block block no in database space space no**

Explanation An I/O error has occurred on the given database space.

Action Analyse the internal operating system error.

INODSE2285 **Creation of database space space no (path) has failed due to system error errno (errtxt)**

Explanation A database space could not be created because of an operating system error.

Action Analyse the system error and consult the manufacturer's manual.

INODSE2289 **Due to license restrictions, usage of replication management functions is not permitted**

Explanation Your license does not permit usage of replication databases.

Action Contact your software supplier for an upgrade of your license.

INODSE2290 **Due to license restrictions, server startup for replication database database name is not permitted**

Explanation Your license does not permit usage of replication databases.

Action Contact your software supplier for an upgrade of your license.

INODSE2291 **Due to license restrictions, server startup of database name as a master for replication databases is not permitted**

Explanation Your license does not permit usage of replication databases.

Action Contact your software supplier for an upgrade of your license.

INODSE2293	**Due to license restrictions, set version for replication master database dbname is not permitted**
Explanation	Your license does not permit usage of replication databases.
Action	Remove all databases from the master database's replication database table or contact your software supplier for an upgrade of your license.

INODSE2298	**Cannot establish connection to server**
Explanation	The utility cannot connect the server which is assumed to be online. Note that the communication goes over XTS.
Action	Check if the database is reachable over the XTS directory service. If you cannot find the reason switch on the XTS tracing facility.

INODSE2340	**Communication error when trying to contact server servername**
Explanation	An error was returned from the communication interface when trying to contact the server.
Action	Check whether the communication component is set up correctly and the communication process (e.g. Software AG XTS Directory Server) is running.

INODSE2341	**The last backup available must not be deleted**
Explanation	The last backup available must not be deleted because in the case of a database crash no restore is possible.
Action	No action required.

INODSE2342	**No valid location or directory specified**
Explanation	To create a backup, either a valid location or directory must be specified.
Action	Specify a valid location or directory.

INODSE4055	**Block size mismatch detected on database_space**
Explanation	A block size mismatch has been detected on the specified database space.
Action	Ensure that the block size of the database space to be restored is the same as that in the backup copy.

INODSE4058 **Database space storage (container) exhausted**

Explanation The storage for database space is exhausted.

Action Try to allocate more storage; if this is not possible contact your software supplier.

INODSE4100 **Failure accessing file**

Explanation An error has occurred accessing a Tamino file. The file may possibly be corrupt.

Action Check that it is the correct file and repeat the operation. If the error persists, contact your software supplier.

INODSE4109 **Failure calling external backup**

Explanation Tamino could not start external backup processing.

Action Check that the third party hardware and drivers are installed and working correctly. If the symptoms persist, contact your software supplier.

INODSE4110 **Failed to retrieve number of backup generations from internal configuration store**

Explanation There is possibly a corruption of the internal configuration store.

Action If the symptoms persist, contact your software supplier.

INODSE4111 **Failed to remove oldest savepoint information from internal configuration store.**

Explanation There is possibly a corruption of the internal configuration store.

Action If the symptoms persist, contact your software supplier.

INODSE4113 **Failed to retrieve server version**

Explanation There is possibly a corruption of the internal configuration store.

Action If the symptoms persist, contact your software supplier.

INODSE4114 **Failed to enumerate savepoint information**

Explanation There is possibly a corruption of the internal configuration store.

Action If the symptoms persist, contact your software supplier.

INODSE4118 **Failed to downgrade database**

Explanation There is a problem with the database downgrade utility.

Action If the symptoms persist, contact your software supplier.

INODSE4120 **Failed to execute inodmp utility**

Explanation The Create/Backup/Restore utility cannot be executed, possibly due to a corruption in the internal configuration store.

Action If the symptoms persist, contact your software supplier.

INODSE4121 **External Restore failed**

Explanation Tamino could not start external restore processing.

Action Check that the third party hardware and drivers are installed and working correctly. If the symptoms persist, contact your software supplier.

INODSE4122 **Failed to retrieve database identity**

Explanation There is possibly a corruption of the internal configuration store.

Action If the symptoms persist, contact your software supplier.

INODSE5251 **An inodmp client terminated with unexpected error err**

Explanation Within parallel backup a client process of the dump utility terminated unexpectedly.

Action The error value defines the exit code of the client process. There are generally additional error messages describing the situation in detail. Ask your software supplier for the reason of the given error.

INODSE5261 **Invalid or unsupported character set charset**

Explanation The specified character set is not supported by the current software version.

Action Check for possible typing errors in character set name.

INODSE5267 **Software configuration error**

Explanation The Tamino software components that you are using are not compatible.

Action Please request a new version of Tamino from your software supplier.

INODSE5268 **Failed to register server with the Software AG XTS Directory Server: why**

Explanation The database server failed to register with the Software AG XTS Directory Server. The error returned from the XTS layer is displayed as part of the message.

Action Fix the error situation described by the XTS message or contact your software supplier.

INODSE5271	**Failed to create the Software AG XTS Directory Server entries: why**
Explanation	The server failed to create the necessary Software AG XTS Directory Server entries and the server startup failed. The reason for the failure is returned by the XTS layer.
Action	Please check that the service "Software AG XTS Directory Server" is running. If not, please start it. On Windows this can be done using the Control Panel. On UNIX please use the scripts provided (which are normally executed at system start). If the service was running when the error occurred, and the XTS message does not specify enough details to fix the problem, please contact your software supplier.

INODSE5272	**Parameter setting for the Software AG XTS Directory Server failed: why**
Explanation	The server failed to do the necessary parameter setting for the Software AG XTS Directory Server and the server startup failed. The reason for the failure is returned by the XTS layer.
Action	Fix the error situation described by the XTS message or contact your software supplier.

INODSE5283	**Invalid parent field format for collation descriptor**
Explanation	The format for the parent field of a collation descriptor is invalid. The only allowed parent formats are "wide" and "alphanumeric".
Action	Check the collation descriptor definition.

INODSE5287	**Invalid collation locale s**
Explanation	The locale name is misspelled or the locale is not supported.
Action	Check the spelling.

INODSE5300	**Filename for database space container could not be determined**
Explanation	It was not possible to determine the full filename for the specified database space.
Action	This is an internal error. Please contact your software supplier.

INODSE5309	**Key id could not be changed, msg**
Explanation	An internal error occurred changing a key value in the internal configuration store.
Action	Please contact your software supplier.

INODSE5310 **Database name name could not be changed in the internal configuration store, msg**

Explanation Because of an internal error the internal configuration could not be changed.

Action Please contact your software supplier.

INODSE5320 **Database ID could not be determined, msg**

Explanation Internal error, while requesting database ID information.

Action Contact your software supplier.

INODSE5321 **Database name could not be determined, msg**

Explanation Internal error, while requesting database name information.

Action Please contact your software supplier.

INODSE5334 **Unable to get collator version for locale locale**

Explanation This is an internal error.

Action Please contact your software supplier.

INODSE5335 **Collation version does not match**

Explanation Most probably, a newer version of the ICU library has been installed and old data is not available In this case, all collating indexes must be rebuilt.

Action Rebuild the collating index.

INODSE5336 **Internal ICU error (error_text) occurred while producing collation key**

Explanation This is an internal error.

Action Please contact your software supplier.

INODSE5337 **Unable to determine server state**

Explanation This is an internal error.

Action Please contact your software supplier.

INODSE5341 **Database database name already exists**

Explanation This error can occur during database creation, or when trying to rename an existing database and a database with the same name already exists.

Action Specify another name.

INODSE5343 **External backup failed, reason: reason errcode**

Explanation The attempt to perform an external database backup failed due to the reason specified in the message.

Action Correct the error indicated and retry the operation.

INODSE5344 **External restore failed, reason: reason errcode**

Explanation A database restore with a connected external system failed due to the reason specified in the message.

Action Correct the error indicated and retry the operation.

INODSE5345 **External delete failed, reason: reason errcode**

Explanation The call to delete an external backup failed due to the reason given.

Action Correct the error indicated and retry the operation.

INODSE5346 **EMC request failed: text**

Explanation A call of EMC's SYMAPI failed for the given reason.

Action Correct the error indicated and retry the operation.

INODSE5354 **External backup configuration error, reason: reason**

Explanation Configuring the environment for an external backup failed.

Action Correct the error indicated and retry the operation.

INODSE5358 **Set version already running on this database**

Explanation The "Set version" operation is already running on this database.

Action Wait for the "set version" operation to complete.

INODSE5359 **Function is not permitted because of pending transactions**

Explanation The function cannot be processed because of pending global transactions.

Action Start the Tamino server in normal mode and close the pending global transactions.

INODSE5360 **Function is not permitted because the previous session was abnormally terminated**

Explanation The function cannot be processed because the previous session was abnormally terminated.

Action Start the Tamino server in normal mode to do an autorepair from the abnormal termination.

INODSE5361 **Downgrade to version version not supported**

Explanation This message can appear when trying to convert a database to a previous version, but the requested downgrade is not supported.

Action No action required.

INODSE5402 **Maximum number of users exceeded**

Explanation A new user was rejected due to internal reasons.

Action You can force a memory dump with "inodba database=name trap=9228" for further analysis after reproducing the error.

INODSE5404 **Insufficient temporary work space**

Explanation The temporary work space was too small to execute the requested function.

Action Consider increasing the temporary workspace by adding locations with free space to the temporary working location.

INODSE5405 **Insufficient temporary work space**

Explanation The temporary work space was too small to execute the requested function.

Action Consider increasing the temporary workspace.

INODSE5406 **Transaction internally aborted**

Explanation A transaction has been aborted due to internal reasons. All changes of this transaction have been undone.

Action You can force a memory dump with "inodba database=name trap=9291" for further analysis after reproducing the error.

INODSE5407 **Database is corrupt, invalid block block**

Explanation There are structural inconsistencies in the database. The database should not be used any longer.

Action Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9130" for further analysis after reproducing the error.

INODSE5408 **buffer pool overflow**

Explanation The current load could not be processed because the buffer pool is too small.

Action Consider increasing the buffer pool size or force a memory dump with "inodba database=name trap=9138" for further analysis after reproducing the error.

INODSE5410 **Database is corrupt, data block damaged**

Explanation There are structural inconsistencies in the database. The database should not be used any longer.

Action Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9127" for further analysis after reproducing the error.

INODSE5411 **Database is corrupt**

Explanation There are structural inconsistencies in the database. The database should not be used any longer.

Action Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9123" for further analysis after reproducing the error.

INODSE5416 **Database is corrupt, physical structures damaged**

Explanation There are structural inconsistencies in the database. The database should not be used any longer.

Action Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9057" for further analysis after reproducing the error.

INODSE5417 **Database is corrupt, allocation error detected**

Explanation There are structural inconsistencies in the database. The database should not be used any longer.

Action Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9058" for further analysis after reproducing the error.

INODSF1008 **The location of the license file could not be found**

Explanation The Tamino Server requires a valid license file. The location of the license file could not be determined.

Action Contact your software supplier.

INODSF1011 **The license of Tamino has expired**

Explanation The licensing period of Tamino has expired.

Action Please contact your software supplier for a renewal of your license.

INODSF1012 **The version of Tamino and the version used in the license file do not match**

Explanation The Tamino product version and the version used in the license file must match.

Action Use the license file that has been shipped with your product version.

INODSF1018 **Database creation has failed due to license restrictions. Licensed database size is licsize MB, attempted dataspace container size is datasize MB.**

Explanation The dataspace size of a database is limited by the amount given in your current license.

Action Create a database with a smaller dataspace size.

INODSF1020 **Error error accessing the raw section section via mode**

Explanation Accessing the raw section failed due to an unexpected system response.

Action Please consult your manufacturer's manual.

INODSF1021 **Verification error on raw section section (structure level mismatch)**

Explanation An error occurred while verifying the structure level in the raw section management structure.

Action Please contact your software supplier.

INODSF1022 **Verification error on raw section section (wrong architecture byte)**

Explanation An error occurred while verifying the architecture byte in the raw section management structure.

Action Please contact your software supplier.

INODSF1023 **Verification error on raw section section (section management header)**

Explanation An error occurred while verifying the management header in the raw section management structure.

Action Please contact your software supplier.

INODSF1024 **Raw section section is not initialized**

Explanation The raw section is not initialized.

Action Please initialize the raw section.

INODSF1062 **Replacing the license file after expiration failed**

Explanation Replacing the license file after expiration failed.

Action Provide a valid license to be able to start the server.

INODSF1180 **The operating system is not specified within the license file**

Explanation Check operating systems specification in the license file.

Action Verify that the license file is valid for the operating system used.

INODSF1250 **Open of source (path) has failed due to an incompatible file or a compatibility mismatch**

Explanation The file could not be opened because it either does not have the expected compatibility level or a subsequent file extent does not match the previously opened one.

Action Check that the correct file has been specified for the operation or if 2 physical file extents belong to each other.

INODSF1251 **Internal error error occurred**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1254 **Unexpected signal signal received in text index procedure call from thread thread**

Explanation An unexpected exception or signal has occurred.

Action If the exception or the signal was asynchronous (i.e. no access violation etc.), repeat the operation.

INODSF1255 **Index too deep**

Explanation The index structure exceeds the maximum levels of indexing supported.

Action Please contact your software supplier.

INODSF1256 **Internal error on doctype doctype: second error caused by failed recovery due to the following error: first error**

Explanation An error occurred on the specified doctype. While trying to undo the changes on the doctype, another error has occurred. The server must terminate in order to prevent the database from being corrupted.

Action Restart the server.

INODSF1257 **Log space full**

Explanation The server session has been abnormally terminated because there is no space left for logging.

Action Provide space for logging and restart the server.

INODSF1259 **Error closing a log space: error message**

Explanation The log space could not be closed properly. The server session is aborting.

Action Try to fix the reason for the error. It is recommended to back up the database. Restart the server.

INODSF1260 **Error on doctype doctype during rollback transaction: rspmsg**

Explanation An error occurred during the rollback of a transaction. The server must terminate in order to prevent the database from being corrupted.

Action Restart the server.

INODSF1261 **Assertion failed: assertion**

Explanation A coding error has occurred.

Action Please inform your software supplier. Restart the server.

INODSF1262 **Open of source (path) has failed due to an incorrect file type**

Explanation The file could not be opened because it does not have the expected type. It is possible that the file is internally corrupted. For example there is an index space with entirely binary zeroes in it.

Action Check that the correct file has been specified for the operation.

INODSF1263 **Error error number has occurred in SMP initialization.**

Explanation An internal error has occurred. The server has stopped.

Action Please contact your software supplier.

INODSF1264 **Setting the maximum number of resources to value has failed. Server stopped.**

Explanation The requested system resources were not available.

Action Check your system configuration.

INODSF1265 **Server already active**

Explanation There is another server running for the current database.

Action Please contact your software supplier.

INODSF1266 **Error error number during synchronization call in line line (address address)**

Explanation An internal error has occurred. The server has been stopped.

Action Please contact your software supplier.

INODSF1267 **SMP resource allocation failed with response rsp at line line**

Explanation An internal error has occurred. The server has been stopped.

Action Please contact your software supplier.

INODSF1268 **Error error number during synchronization call in line line**

Explanation An internal error has occurred. The server has been stopped.

Action Please contact your software supplier.

INODSF1269 **Increasing the number of resources by value has failed. Server stopped.**

Explanation The requested system resources were not available.

Action Check your system configuration.

INODSF1270 **Invalid value (value) found at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1271 **Invalid pointer (value) found at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1272 **Internal error error string occurred at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1273 **Invalid value (int value) found at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1274 **Internal error in block block number occurred at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1275 **Invalid value (int value) found on address address at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1276 **Invalid values (value 1, value 2) found on address address at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1277 **Invalid values (value1, value2) found at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1278 **Invalid value (value) found in block block number at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1279 **Invalid value (value) found on address address at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1280 **Internal error location-c1-c2 occurred**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1282 **Received response rsp (intrsp) while loading function(s) for extension point extp**

Explanation Loading a function for an extension point failed.

Action Please contact your software supplier.

INODSF1283 **Internal communication initialization failed**

Explanation The server's internal communication could not be activated.

Action Please contact your software supplier.

INODSF1284 **Internal memory management could not be initialized**

Explanation The initialization of the server's memory management has failed.

Action Please contact your software supplier.

INODSF1285 **Temporary working space could not be allocated**

Explanation The allocation of the working space needed for server operation has failed.

Action Please contact your software supplier.

INODSF1286 **Buffer pool too small. At least minimum value bytes required.**

Explanation The defined buffer pool is too small for the server to start.

Action Increase the buffer pool parameter and restart the server.

INODSF1287 **Buffer pool too small to start the server (internal reason reason)**

Explanation The defined buffer pool is too small for the server to start.

Action Increase the buffer pool parameter and restart the server.

INODSF1288 **Server for this database already active**

Explanation There is already an active server for the same database or at least some resources of the previous server run have not been released yet.

Action If there is no active server and you cannot determine which resources may cause the conflict, contact your software supplier.

INODSF1291 **Not enough memory available to execute process**

Explanation The operating system did not have enough resources to run another process. Possible reasons are too many concurrently active processes or a too small swap/paging space.

Action Please check the resource usage and the configuration of your computer.

INODSF1296 **source (path) is corrupted at offset**

Explanation The data cannot be used.

Action Please contact your software supplier.

INODSF1297 **Creation of source (path) has failed**

Explanation The file could not be created at the specified location.

Action Look for other error messages to find the reason for the failure.

INODSF1298 **source (path) could not be opened: device type not supported**

Explanation An invalid device type was chosen.

Action Choose a valid device type.

INODSF1299 **Open of source (path) has failed due to operating system error errno**

Explanation The file could not be opened.

Action Please consult the manufacturer's manual.

INODSF1300 **Open of source (path) has failed due to an invalid structure**

Explanation The file could not be opened because it does not have the expected structure.

Action Check if the file origin is the same machine architecture. If you cannot detect the error, please contact your software supplier.

INODSF1301 **Open of source (path) has failed. Missing extents or wrong sequence of extents. Please check and retry.**

Explanation The file could not be opened because the sequence in which devices are given (e.g. tapes) is not correct or not all sequences required were specified.

Action Specify all extents in the correct sequence.

INODSF1302 **Open of log space (path) has failed because sequence of log spaces is incorrect**

Explanation The file could not be opened because the sequence in which log spaces are given (e.g. tapes) is not correct.

Action Use the correct sequence.

INODSF1303 **Open of source (path) has failed due to an incorrect file type**

Explanation The file could not be opened because it does not have the expected type.

Action Check that the correct file has been specified for the operation.

INODSF1305 **Open of source has failed due to invalid or missing internal information**

Explanation The file could not be opened because its location was not specified.

Action Check the database parameters.

INODSF1306 **Internal error location occurred: Please report r t h c**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier and report the values given with the message. Restart the server.

INODSF1307 **Database database name not registered**

Explanation The specified database has not been properly created or the internal entries of this database have been destroyed.

Action Create the database again.

INODSF1308 **Executable name not found**

Explanation The system could not find the executable object specified.

Action Please check your installation.

INODSF1309 **System error errno occurred during the creation of another process**

Explanation The system could not create another process. You might have exceeded the amount of available memory or the maximum number of processes.

Action Please increase the amount of virtual memory available, or increase the number of possible processes. Please refer to the manual of your operating system for details.

INODSF1310 **Invalid value (value) found at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1311 **Error errno has been signalled during the execution of an asynchronous I/O on log space for id**

Explanation An asynchronous I/O has failed due to an operating system error.

Action Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.

INODSF1312 **Error errno has been signalled during the execution of an asynchronous I/O on journal space for id**

Explanation An asynchronous I/O has failed due to an operating system error.

Action Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.

INODSF1313 **Error errno has been signalled during the execution of an asynchronous I/O for id**

Explanation An asynchronous I/O has failed due to an operating system error.

Action Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.

INODSF1317 **Semaphore could not be created because system limit was reached**

Explanation The system limit for semaphores was reached.

Action Increase the number of semaphores supported by the operating system.

INODSF1319 **Unexpected signal signal received**

Explanation An unexpected exception or signal has occurred.

Action If the exception or the signal was asynchronous (i.e. no access violation etc.), repeat the operation.

INODSF1321 **Error opening sequential file: error**

Explanation An error occurred when opening a sequential file.

Action Correct the reason for the sequential file open failure and retry the operation.

INODSF1322 **Latest savepoint not found**

Explanation Internal information about the latest savepoint could not be found.

Action Contact your software supplier.

INODSF1323 **Path or type of log location not found**

Explanation The internal information for the log location, path or type could not be found.

Action Contact your software supplier.

INODSF1324 **Processing information for a log space is undefined**

Explanation A previous server session process was killed during restore/recover.

Action Use a later backup if possible or use a recover until a timestamp that is less than the creation date of the log space in question.

INODSF1325 **Signal signal number caught. Termination initiated.**

Explanation An unexpected signal was caught. This leads to an immediate termination.

Action If the signal cannot be explained by the environment (operator initiated or operating system initiated signal), please contact your software supplier.

INODSF1326 **database creation not completed**

Explanation The database creation is not finished, or terminated unexpectedly, leaving the database files on disk.

Action Check if the creation is still in progress. If so, wait until completed. If not, clean up and restart the database creation.

INODSF1328 **Unexpected buffer pool error**

Explanation An unexpected error has occurred when trying to access the buffer pool.

Action Repeat the action. If it still fails, contact your support center.

INODSF1329 **Unexpected error getting a page from the buffer pool**

Explanation An unexpected error has occurred when trying to get a page from the buffer pool. The operation was cancelled.

Action Contact your software supplier.

INODSF1330 **An unexpected I/O error has occurred**

Explanation An unexpected I/O error has occurred. The operation was cancelled.

Action Contact your software supplier.

INODSF1331 **Unable to extend database space. Reason: ret_code.**

Explanation The specified error has occurred while trying to extend a database space.

Action Determine the reason for the error code, and retry the operation.

INODSF1332 **Index chain is corrupt**

Explanation Corruption has been found for an index on a doctype.

Action The indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager, then retry the operation.

INODSF1334 **No index summary in input file**

Explanation The input file does not have the required index definitions.

Action Ensure that the correct input file has been specified.

INODSF1335 **No streams available**

Explanation Multi-file mode is being used but no streams are available.

Action Please contact your software supplier.

INODSF1336 **Cannot handle given extent type**

Explanation It is not possible to handle the type of extent specified.

Action This is an internal error. Please contact your software supplier.

INODSF1337 **Shared memory segment of server exists**

Explanation At least one shared memory segment of the server already exists.

Action Check if the server is already active. If not retry the operation. If the error persists remove the existing shared memory segment and retry.

INODSF1341 **Error on temporary storage space**

Explanation An error has occurred when trying to write to a temporary storage space.

Action Ensure that there are no errors on the device where temporary space is to be used and retry the operation.

INODSF1342 **No space for index space**

Explanation There are not enough system resources available for the index space.

Action Allocate sufficient resources to allow the operation to succeed.

INODSF1343 **Error opening data space**

Explanation An error has occurred while opening the data space.

Action Correct the error and retry the operation.

INODSF1344 **Error opening journal space**

Explanation An error has occurred while opening the journal space.

Action Correct the error and retry the operation.

INODSF1345 **Internal error: Provided memory not sufficient**

Explanation An area in memory used as working space was defined too small.

Action Please contact your software supplier.

INODSF1346 **No input slot could be allocated**

Explanation An internal error occurred preventing an input slot being allocated for an index.

Action Please contact your software supplier.

INODSF1347 **No space for preserved slot**

Explanation An internal error occurred preventing a preserved slot being allocated for an index.

Action Please contact your software supplier.

INODSF1348 **Invalid database space**

Explanation An internal error occurred.

Action Please contact your software supplier.

INODSF1349 **Error while reading index**

Explanation An internal error occurred while reading the index.

Action Please contact your software supplier.

INODSF1350 **No more temporary space**

Explanation Temporary space has been exhausted.

Action Ensure that there is enough free space to allocate the required temporary space.

INODSF1351 **No slot available**

Explanation An internal error occurred when trying to write to a slot.

Action Please contact your software supplier.

INODSF1353 **More than one block to be written (number)**

Explanation A disk write failed because more than one block was requested to be written. This is an internal error.

Action Please contact your software supplier.

INODSF1354 **Utility not permitted to run**

Explanation This utility is currently not permitted to run.

Action Wait until the database is available again.

INODSF1355 **Internal sort error**

Explanation An internal sort error has occurred.

Action Please contact your software supplier.

INODSF1356 **Internal error occurred: utility entry not found**

Explanation An internal error occurred.

Action Please contact your software supplier.

INODSF1359 **Invalid value (long value) found on address address at location location**

Explanation An internal error has caused the server to stop.

Action Please contact your software supplier. Restart the server.

INODSF1360 **The tape device is not responding, please ensure that a tape is mounted**

Explanation Response EINVAL was returned by the operating system. The most likely cause is that no tape has been mounted.

Action Ensure that a tape is mounted and the device is switched on.

INODSF1362 **Journal space too small (minimum required size is size MBytes)**

Explanation The journal space is not sufficient for the Tamino server.

Action Create a database with a larger journal space.

INODSF1363 **Journal overflow. Server cannot proceed.**

Explanation The journal space was insufficient. The current server session has to be terminated.

Action Check if more journal space can be provided. Restart the server.

INODSF1364 **Log space not found for savepoint savepoint**

Explanation A log space entry for the given savepoint could not be found.

Action Contact your software supplier.

INODSF1366 **License file not found at path**

Explanation Your license is not at the expected place.

Action Please move the license file to the place indicated.

INODSF1367 **License file not valid (error error)**

Explanation Your license is not valid. It is incomplete or has been edited.

Action Please acquire a correct license file from your software supplier.

INODSF1369 **Internal licensing error error**

Explanation There was an internal error in the processing of the licensing information.

Action Please contact your software supplier.

INODSF1373 **Database database name not registered**

Explanation The specified database has not been properly created or the internal entries of this database have been destroyed.

Action Create the database again.

INODSF1431 **Error during autorepair. The database is inconsistent.**

Explanation The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.

Action Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.

INODSF1432 **Start of autorepair information cannot be determined**

Explanation The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.

Action Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.

INODSF1433 **Journal overflow during database autorepair. The database is inconsistent.**

Explanation The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.

Action Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.

INODSF1436 **Terminated with errors**

Explanation A previous error has caused the termination of the process.

Action Please check the event log for detailed information about previous errors that have caused the process to terminate.

INODSF1454 **Internal error occurred: location thread module function. Server stopped.**

Explanation An internal error occurred.

Action Please contact your software supplier and provide the message text.

INODSF1688 **Shared memory of size size MB is not available (internal error errno)**

Explanation The server needs a shared memory of the specified size. However, this shared memory could not be created.

Action View the previous message which describes the operating system error in detail. Check the manufacturer's manual. Consider increasing the operating system limits on shared memory size or decreasing the needs of the server by decreasing parameters such as buffer pool size.

INODSF2002 **Error during replication processing, replication stopped**

Explanation Replication cannot be continued due to a previous error during replication processing

Action If the master database is lost, the Reset Replication function can be used to convert the database for usage as a substitution. In any other case a new backup from the master database should be used to recreate the replication database.

INODSF2005 **Internal replication error error/error info detected when processing data of server session session number - block block number, location record number**

Explanation The data required for replication processing could not be supplied by the master database.

Action Please check that the log space has not yet been deleted by creating new backups of the master database. If the log space still exists keep the error information and contact your software supplier.

INODSF2075 **Failure writing to tape device, please ensure that a tape is loaded**

Explanation The response EFAULT was returned by the operating system. The most likely cause is that no tape is loaded in the device.

Action Ensure that a tape is loaded and the device is switched on.

INODSF2116 **Internal command recovery failure (rsp1) on doctype doctype, caused by: rsp2**

Explanation A internal recovery failed and therefore the server cannot resolve a rollback. The server must terminate in order to prevent the database from being corrupted.

Action Restart the server.

INODSF2119 **Invalid compatibility level: DBMS complev1, backup file complev2 (filename)**

Explanation An invalid compatibility level of DBMS and backup file has been detected.

Action Please use a DBMS version with the same compatibility level as the backup file, or use a backup file with the compatibility of the DBMS.

INODSF2120 **IO [mod-line] error error**

Explanation An unexpected error occurred in an I/O function.

Action Please contact your software supplier and provide the message text.

INODSF2122 **Invalid compatibility level: DBMS complev1, database complev2**

Explanation An invalid compatibility level has been detected.

Action Please contact your software supplier.

INODSF2123 **CF [mod-line] error error**

Explanation An internal configuration error occurred.

Action Please contact your software supplier and provide the error message text.

INODSF2128 **Invalid data block detected at block blknr (doc doc, cont cont)**

Explanation An invalid data block was detected which refused a database backup. At least one collection has a data fault.

Action Repair the database with restore/recover from the latest good backup.

INODSF2188 **Failed to enter the new compatibility level in the internal configuration store**

Explanation The new compatibility level could not be entered in the internal configuration store.

Action Please contact your software supplier and provide the message text.

INODSF2227 **Internal error error during flush operation**

Explanation The write operation of the internal buffer cache to disk failed. A detailed error message precedes this message.

Action Analyse the error code, maybe check your disks and restart server.

INODSF2234 **SMP resource allocation failed at module[line] because of a lack of available memory**

Explanation The allocation of memory failed. The reason for that is either that the pagefile is too small or that the available virtual memory is exhausted.

Action Increase the size of the pagefile. If that doesn't help contact your software supplier.

INODSF2235 **Database key mismatch, required keyreq, present keypres**

Explanation The index space has an unexpected key within the first index space. The database space obviously comes from another database.

Action Check the index container spaces.

INODSF2266 **Cannot start Tamino utility of version due to system error errno**

Explanation Submitting a Tamino utility as a subprocess failed due to an operating system error.

Action Analyze the system error and check the installed version.

INODSF2280 **Unexpected I/O error (io operation) on database_space**

Explanation An I/O failed and the process cannot continue.

Action View any previous or related system error messages and analyse why the I/O operation on the given database space could have failed.

INODSF2284 **Error errno (errtxt) has been signalled during the execution of an asynchronous I/O on database space for id**

Explanation A severe read/write error has occurred.

Action Analyse the operating system error.

INODSF2286 **Internal replication error error/error info detected when processing data of mass load recovery input filename**

Explanation The mass load input required for replication processing could not be supplied by the master database.

Action Please check that the recovery input file has not yet been deleted by creating new backups of the master database. If the log space still exists, keep the error information and contact your software supplier.

INODSF2287 **Internal error error detected when processing mass load recovery input with key key**

Explanation The recovery of a mass load activity failed.

Action Please contact your software supplier.

INODSF2288 **Cannot grant server synchronization semaphore**

Explanation The server synchronization semaphore cannot be granted.

Action Check if the semaphore already exists and another process has granted it, or if the permission settings of the semaphore do not allow access.

INODSF2294 **Filename for database space container could not be determined**

Explanation It was not possible to determine the full filename for the specified database space. It was obviously missing in the internal configuration store.

Action This is an internal error. Please contact your software supplier.

INODSF2296 **Internal error interr on database space (reason)**

Explanation The writing of relevant information to the given database space (Log, Journal) failed due to an internal error.

Action Check the location where the database space resides and also analyse the previously given operating system error message.

INODSF2299 **Internal error number reading dbspace at block blocknumber**

Explanation Reading the given database block resulted in an internal I/O error.

Action No action required.

INODSF2306 **License timer interval too short**

Explanation The license timer detected an unexpected system data and time.

Action Please contact your software supplier.

INODSF2307 **Invalid combination of customer/partner information found in the license file**

Explanation An invalid combination of customer/partner information was found in the license file.

Action Please contact your software supplier to extend your license.

INODSF2308 **Product usage found in the license file is not allowed for an unlimited license**

Explanation The product usage found in the license file is only allowed for a time-limited license.

Action Please contact your software supplier to correct your license.

INODSF2309 **Server abort because of license expiration**

Explanation The grace period after license termination has expired. The server did an abort.

Action Please contact your software supplier to extend your license.

INODSF2334 **The license for name with ID id has expired, server aborts now**

Explanation The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.

INODSF2335 **The license for customername sub-licensed by partnername with ID partnerid has expired, server aborts now**

Explanation The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.

INODSF2336 **The license for customername with ID customerid sub-licensed by partnername has expired, server aborts now**

Explanation The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.

INODSF2337 **The license for customername with ID customerid sub-licensed by partnername with ID partnerid has expired, server aborts now**

Explanation The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.

INODSF2338 **Internal error number writing dbspace at block blocknumber**

Explanation Cannot write database block due to an internal I/O error.

Action Analyse the error number and check the database.

INODSF2339 **XTS refuses database connection, reason reason_code**

Explanation It is not possible to reach the database via XTS.

Action Switch on XTS_TRACE, repeat the function and check the trace file.

INODSF4256 **Structure level mismatch on database**

Explanation The version of the server differs from the version of the utility.

Action Run the correct version of the utility or server, or convert the database.

INODSF4258 **The database type and/or version does not match the backup**

Explanation This operation can only be performed against a database of the same type and/or version as the backup.

Action Ensure that the utility is being run against the correct type and version of database.

INODSF4262 **Database server mismatch: present db_name**

Explanation A mismatch occurred between the database server parameter and the database server name of the assigned index space.

Action Ensure that the correct database name is supplied.

INODSF5331 **Version version is not installed**

Explanation The required software version is not installed.

Action please contact your software supplier.

INODSF5332 **Invalid structure level strlev**

Explanation An invalid structure level has been detected.

Action Please contact your software supplier.

INODSI1004 **Stop of database successfully initiated - server is going down now**

Explanation All database activities are terminated - the server process is about to terminate.

Action No action required.

INODSI1010 **Backup file from older version version**

Explanation Indicates that the input backup file is from a previous version.

Action No action required.

INODSI1013 **Read-only database, word fragment index cannot be created**

Explanation Read-only database, no database update permitted.

Action Ensure that the database upon which you wish to carry out the operation is write-enabled.

INODSI1016 **Initializing journal space**

Explanation When the database first starts, the entire journal space must be formatted with binary zeroes.

Action Wait until the operation finished: This could take several seconds or even several minutes if the file is very large.

INODSI1019 **Database of older version version**

Explanation The database used for restore is from a previous version.

Action No action required.

INODSI1034 **The Tamino Server that is provided with this Tamino Developer Edition may be used for educational purposes only. For production purposes, you must use the Tamino Server that is included in the Tamino Server Edition.**

Explanation This is an informational message

Action None

INODSI1039 **Function function executed**

Explanation The specified function was executed.

Action Information only, no action required.

INODSI1041 **Starting mode database backup**

Explanation Indicates the start of database backup processing.

Action No action required.

INODSI1044 **Starting restore database using type backup from timestamp**

Explanation Indicates the backup that was used to start restore processing.

Action No action required.

INODSI1049 **Starting mode restore of database**

Explanation Indicates that the restore processing has been started.

Action No action required.

INODSI1059 **The time-limited license for the server has expired, switched to an unlimited Community Edition license**

Explanation The time-limited license for the server has expired. The server automatically switched to an unlimited Community Edition license. Some product features may no longer be available.

Action No action required.

INODSI1110 **Waiting time for count users to start a new transaction - min: min seconds, max: max seconds, average: average seconds seconds**

Explanation This message is used to give information about waiting times for users who want to open a new transaction while other users have not yet finished their transaction. This synchronization of all users who do not have an open transaction is required at the end of a backup.

Action No action required.

INODSI1113 **No real modified data for Incremental Backup**

Explanation There is no modification in the database, so an incremental backup will save no new data. Nevertheless a backup with only global data will be created.

Action No action required.

INODSI1114 **Incremental backup from date deleted**

Explanation A full backup to be deleted causes the deletion of dependent incremental backups as well.

Action No action required.

INODSI1146 **Archive Log Location has been reset**

Explanation An Archive Log Location will not be used.

Action None.

INODSI1147 **path set as location name**

Explanation A path or a set of paths has been set for the specified location type.

Action None.

INODSI1177 **Database database name Session session number (name modifierversion on system info, process ID pid)**

Explanation This is an informational message.

Action No action required.

INODSI1178 **Database database name Replication Session (name modifierversion on system info, processID pid)**

Explanation The server started for a replication database.

Action No action required.

INODSI1179 **Database database name Read-Only Session (name modifierversion on system info, process ID pid)**

Explanation This is an informational message.

Action No action required.

INODSI1183 **size MB empty data space found**

Explanation The amount of empty data space assigned to specific doctypes that can be returned to global free space

Action None.

INODSI1184 **No empty data space found**

Explanation Empty data space that can be returned to global free space does not exist

Action None.

INODSI1188 **Creating a temporary backup for free space defragmentation**

Explanation A temporary backup is created to be used for defragmenting free space

Action Wait until the reorganization is completed.

INODSI1190 **size MB empty data space converted to global free space**

Explanation The amount of empty data space that was de-allocated from specific doctypes and returned to global free space.

Action None.

INODSI1191 **Free data space in database is size MB (percent %)**

Explanation Information about the amount of global free data space after reorganization.

Action None.

INODSI1193 **Free space less than percent %, no free space defragmentation and data space shrinking**

Explanation The reorganize function converted empty space to global free space, but the amount of free space is less than a minimum value considered as worthwhile performing a free space defragmentation and data space shrinking.

Action None, if you are satisfied with the minimum value for free space defragmentation and data space shrinking. In any other case, use the reorganize function with a differnet minimum value.

INODSI1195 **Defragmenting free space**

Explanation A temporary backup is used for restore to defragment free space.

Action Wait until the reorganization is completed.

INODSI1196 **Shrinking data space**

Explanation The size of the data space is reduced by de-allocating free space.

Action Wait until the reorganization is completed.

INODSI1197 **No free data space found**

Explanation Free data space does not exist.

Action None.

INODSI1207 **rplname inserted into permission list of dbname**

Explanation This is an informational message.

Action No action required.

INODSI1208 **rplname removed from permission list of dbname**

Explanation This is an informational message.

Action No action required.

INODSI1211 **dbname set as replication server of master on hostname using port number**

Explanation This is an informational message.

Action No action required.

INODSI1218 **dbname set as replication server with simultaneous query, master is masterdb**

Explanation This is an informational message.

Action No action required.

INODSI1219 **dbname set as replication server without simultaneous query, master is masterdb**

Explanation This is an informational message.

Action No action required.

INODSI1220 **Replication server dbname reset to normal server**

Explanation This is an informational message.

Action No action required.

INODSI1246 **Read-only database, word fragment index cannot be removed**

Explanation The database is readonly, so no database update is permitted.

Action Ensure that the database upon which you wish to carry out this operation is write-enabled.

INODSI1248 **No backup exists for dbname - create a backup as soon as possible**

Explanation After converting a replication database to a normal database a backup of the database is not available, thus a restore/recover is not possible until a backup exists.

Action Create a backup of the database.

INODSI1252 **Starting restore database using type backup from timestamp**

Explanation Indicates the backup that was used to start restore processing.

Action No action required.

INODSI1253 **Incremental backup from date deleted**

Explanation A full backup to be deleted causes the deletion of dependent incremental backups as well.

Action No action required.

INODSI1294 **Log space of server session session number from time opened**

Explanation The log space of the specified server session has been opened.

Action No action required.

INODSI1304 **Read-only database db_name , startup at startup**

Explanation This message shows the time at which the database was started in read-only mode.

Action No action required.

INODSI1314 **Database db_name, startup at startup**

Explanation This message shows the time at which the database was started.

Action No action required.

INODSI1315 **Log space of server session session number processed until time**

Explanation All information generated before the given end timestamp of the log space of the specified server session was processed.

Action No action required.

INODSI1316 **The backup tape from time has been unregistered**

Explanation The information about the availability of the given backup tape has been removed.

Action The tape may be removed from the archive.

INODSI1327 **Database stopped**

Explanation The database has been stopped.

Action No action required.

INODSI1333 **Log space data processing end time stamp is time**

Explanation This is a progress message about the aborted recovery run or an abort of replication processing.

Action In the case of a recovery run, the information can be used to start a recover until.

INODSI1339	**Replication of server session session number suspended replication data processed until timestamp**
Explanation	Replication processing is suspended due to a server shutdown request of the replication database.
Action	No action required.

INODSI1352	**Replication of server session session number from timestamp started**
Explanation	The replication processing has started to process the log space data of the specified server session of the master database.
Action	No action required.

INODSI1361	**Replication of server session session number resumed using replication data from timestamp**
Explanation	The server continued replication processing after replication database startup.
Action	No action required.

INODSI1365	**Server session session number replicated until time stamp**
Explanation	This is the current replication status of the database.
Action	No action required.

INODSI1368	**Replication of server session session number resumed using replication data from timestamp. Simultaneous query permitted.**
Explanation	The server continued replication processing after replication database startup.
Action	No action required.

INODSI1370	**Replication of server session session number from timestamp started. Simultaneous query permitted.**
Explanation	The replication processing has started to process the log space data of the specified server session of the master database.
Action	No action required.

INODSI1371	**sufficient space in locations, continue**
Explanation	Now there is sufficient space on the location where the file was waiting for, the operation now continues
Action	Now there is a subsequent file extent

INODSI1384 **Setting of parname=parval**

Explanation no description available

Action no action required

INODSI1389 **Backup from backup_date deleted**

Explanation After backup, the number of backup generations is updated, i.e older backups are removed. For further information, please refer to the documentation of the server parameter "number of backup generations".

Action No action required.

INODSI1393 **Backup created with backup key 'backupkey' (from)**

Explanation The identification of the last created backup is displayed.

Action No action required.

INODSI1394 **Backup key 'backupkey' (from)**

Explanation This is a display of backup information.

Action No action required.

INODSI1397 **Deleting disabled backup from backup_date**

Explanation A disabled backup file is being deleted.

Action No action required.

INODSI1399 **Dataset dsn created on date**

Explanation The dataset was created on the specified date.

Action No action required.

INODSI1400 **A transaction has been heuristically rolled back at time**

Explanation The database system has rolled back a transaction for which a decision of the transaction manager was pending.

Action No action required.

INODSI1417 **database database name at structure level for version version**

Explanation This informational message states the structure level of the database.

Action No action required.

INODSI1420 **Dump file at version: vers, level level**

Explanation This informational message states the version and level of the dump file.

Action Select the version displayed.

INODSI1422 **Using backup filename**

Explanation Indicates the backup which is used to create the new database.

Action No action required.

INODSI1423 **Using location location**

Explanation Indicates the location which is to be used for the database spaces.

Action No action required.

INODSI1451 **Creation of word fragment index started**

Explanation The creation of the word fragment index has started.

Action No action required.

INODSI1452 **Server session session number started**

Explanation The server started successfully.

Action No action required.

INODSI1453 **Internal event event has occurred**

Explanation This message indicates a certain event in the server processing. It is not relevant to the user.

Action No action required.

INODSI1456 **The Tamino Server that is provided with the Tamino Developer Edition may be used for test purposes only. For production purposes, you must use the Tamino Server that is included in the Tamino Server Edition.**

Explanation This is an informational message.

Action Use the correct Tamino Server.

INODSI1457 **End of tape tape - rewinding**

Explanation The tape is being rewound.

Action No action required.

INODSI1458 **End of diskette path**

Explanation The diskette is full.

Action No action required.

INODSI1459 **Log space of server session session number from time opened**

Explanation The log space of the specified server session has been opened.

Action No action required.

INODSI1460 **Log space of server session session number completed**

Explanation The log space of the specified server session has been completed.

Action No action required.

INODSI1463 **Database 'database_name' accessed online**

Explanation The specified database has been accessed online.

Action No action required.

INODSI1464 **Database 'database_name' accessed offline**

Explanation The specified database has been accessed offline.

Action No action required.

INODSI1466 **Creation of database space space no (location name) has successfully finished**

Explanation The specified database space has been created.

Action No action required.

INODSI1467 **Tamino name modifierversion on system info**

Explanation This is a generic message used to identify an activity.

Action No action required.

INODSI1468 **No index found**

Explanation No index found.

Action No action required.

INODSI1469 **The database server is active on a remote node**

Explanation This is an informational message.

Action No action required.

INODSI1470 **Database spaces for database db_name have been created**

Explanation The database spaces for a database server have been successfully created. The next step of database creation will be restoring the initial contents of the database.

Action Restore the initial contents of the database.

INODSI1471 **Database db_name has been deleted**

Explanation The database with the given name has been successfully deleted.

Action No action required.

INODSI1474 **Read-only database db_name , startup at startup**

Explanation This message shows the time at which the database was started in read-only mode.

Action No action required.

INODSI1475 **Database db_name, startup at startup**

Explanation This message shows the time at which the database was started.

Action No action required.

INODSI1480 **Log space of server session session number processed until time**

Explanation All information generated before the given end timestamp of the log space of the specified server session was processed.

Action No action required.

INODSI1481 **Log space of server session session number skipped**

Explanation The log space of the specified server session was not processed because it contains only information generated after the given end timestamp.

Action No action required.

INODSI1484 **No log space information found**

Explanation The initial backup was used for restore, and no log space of another session exists.

Action No action required.

INODSI1485 **Checking finished. No inconsistencies found.**

Explanation The check and repair database action has finished.

Action No action required.

INODSI1486 **Log space of server session session number extent extent number archived**

Explanation A log space extent has been copied to the archive location.

Action No action required.

INODSI1487 **The backup tape from time has been unregistered**

Explanation The information about the availability of the given backup tape has been removed.

Action The tape may be removed from the archive.

INODSI1488 **Previous server session aborted when recovering session session number**

Explanation A previously started restore/recovery run did not complete the recovery phase.

Action See the instructions within subsequent messages.

INODSI1489 **Log space data processing end time stamp is time**

Explanation This is a progress message about the aborted recovery run or an abort of replication processing.

Action In the case of a recovery run, the information can be used to start a recover until.

INODSI1490 **Continuing server startup will disable subsequent backups**

Explanation When the server startup is continued, backups done later than the used one will become invalid.

Action No action required.

INODSI1491 **Due to an unexpected problem, Restore and/or Recover was not successful. Please re-execute the Restore and/or Recover now to ensure data integrity.**

Explanation For reasons stated in the job log, the Restore and/or Recover failed to execute properly. Depending on the reason for the abort, either "restore without recover" or "recover until" can be used to recover your data.

Action If the reason for the initial recovery abort was a missing or corrupted log space, use "restore without recover" or "recover until".

INODSI1492 **Subsequent backups disabled**

Explanation Backups older than the one used for the aborted recovery run are invalid now.

Action No action possible.

INODSI1493 **Tamino server successfully started in read-only mode**

Explanation This is an informational message.

Action No action required.

INODSI1494 **Destruction of word fragment index started**

Explanation Destruction of word fragment index started

Action No action required

INODSI1495 **Creation of word fragment index successfully finished**

Explanation Creation of the word fragment index successfully finished.

Action No action required

INODSI1496 **Destruction of word fragment index successfully finished**

Explanation Destruction of the word fragment index successfully finished

Action No action required

INODSI1532 **referential constraint name dropped (primary primary, foreign foreign)**

Explanation The specified referential integrity constraint has been dropped.

Action None.

INODSI1535 **file file refreshed**

Explanation The specified file has been refreshed.

Action None.

INODSI1550 **function not permitted, referential constraint defined**

Explanation The function not permitted because a referential constraint is defined.

Action None.

INODSI1631 **Autorepair completed without errors**

Explanation The autorepair from the crash of the previous server session was successful.

Action The database can now be used.

INODSI1632 **Recovery terminated successfully**

Explanation The recovery has processed all log spaces. All updates have been re-applied.

Action The server can now be restarted.

INODSI1634 **Successful completion**

Explanation The action has completed without errors.

Action No action required.

INODSI1635 **Crash dump of database finished**

Explanation The crash dump is complete.

Action No action required.

INODSI1636 **Tamino server successfully started**

Explanation This is an informational message.

Action No action required.

INODSI1637 **Skipping recovery terminated successfully**

Explanation The operation of skipping the recovery has terminated successfully. The update of the log space information has been completed.

Action The server can now be restarted.

INODSI1691 **Mass load recovery files archived**

Explanation The mass load recovery files have been copied to the archive location.

Action No action required.

INODSI1732 **Calculated RESTART point - BLOCK=block,CHECKPOINT=chkpt**

Explanation Recovery has restarted from the position shown.

Action No action required.

INODSI1986	**no file protection enabled**
Explanation	File protection is not enabled
Action	No action required.

INODSI1988	**PID pid**
Explanation	Process ID.
Action	None.

INODSI2003	**Replication of server session session number suspended replication data processed until timestamp**
Explanation	Replication processing is suspended due to a server shutdown request of the replication database.
Action	No action required.

INODSI2006	**No replication data for server session session number**
Explanation	No modifications have been made for a server session on the master database.
Action	No action required.

INODSI2007	**Replication of server session session number from timestamp started**
Explanation	The replication processing has started to process the log space data of the specified server session of the master database.
Action	No action required.

INODSI2008	**Replication of server session session number completed**
Explanation	The server completed replication of a master database's server session
Action	No action required.

INODSI2009	**Replication of server session session number resumed using replication data from timestamp**
Explanation	The server continued replication processing after replication database startup.
Action	No action required.

INODSI2010 **Server session session number replicated until time stamp**

Explanation This is the current replication status of the database.

Action No action required.

INODSI2011 **Starting replication using data from database master dbname**

Explanation Replication processing has started. The master database must be active to supply replication data.

Action No action required.

INODSI2012 **Initial server session session number for new replication database**

Explanation A replication database is started for replication the first time.

Action No action required.

INODSI2017 **Updating backup generations**

Explanation Older backups are being removed if the number of backup generations has been exceeded.

Action No action required.

INODSI2018 **Using hostname as host name for the Software AG XTS Directory Server entries**

Explanation The specified hostname has been assigned to the server property "server host name". This name will be registered in the Software AG XTS Directory Server as the host where the database is located.

Action No action required.

INODSI2021 **The following file type file was not deleted: file name**

Explanation In the case of abnormal server terminations, log and dump files will be written. To be able to analyze several problems, these files could be helpful and will not be deleted. Be aware that dump files could be very large.

Action It might be useful to keep the dump and log files for further examination. If you want to generate a new database in the same location you should move those files to a different location by hand.

INODSI2040 **File 'name' copied to directory**

Explanation This is an informational message.

Action No activity required.

INODSI2044 **Infofile 'path' created**

Explanation This is an informational message.

Action No action required.

INODSI2074 **Corrupted block repaired on space**

Explanation Due to a previous crash the latest written block may be corrupted (in the journal or log). In some cases this can be detected and repaired.

Action Check if the previous session was abnormally aborted. Only in this case should this message appear.

INODSI2091 **Process can make use of 3GB virtual address space**

Explanation The process can make use of 3GB virtual address space.

Action No action required.

INODSI2100 **Web server configuration changed, server server notified**

Explanation The web server configuration changed and the server was notified.

Action No action required.

INODSI2115 **Execution continues**

Explanation This message is displayed by debug-enabled executables if they have been selected for debugging.

Action No action required.

INODSI2146 **Replication of server session session number resumed using replication data from timestamp. Simultaneous query permitted.**

Explanation The server continued replication processing after replication database startup.

Action No action required.

INODSI2148 **At least one replication database allows simultaneous query**

Explanation The replication master writes additional locking information to the log space. A replication database with 'Simultaneous Query' enabled may be accessed with queries while it replicates updates.

Action No action required.

INODSI2149 **No replication databases allow simultaneous query**

Explanation The replication master does not write additional locking information to the log space. A replication database with 'Simultaneous Query' enabled cannot processs queries while replicating updates of this session.

Action No action required.

INODSI2150 **Database database name set to replication type with simultaneous query**

Explanation If at least one replication database is defined with 'simultaneous query' the master database writes additional locking information to the log space. If this replication database is the first of this kind, the master switches to a new session.

Action No action required.

INODSI2151 **Database database name set to replication type without simultaneous query**

Explanation If no replication database is defined with 'simultaneous query' the master database does not write additional locking information to the log space. If replication database mentioned is the last of that kind, the master switches to a new session

Action No action required.

INODSI2154 **Replication of server session session number from timestamp started. Simultaneous query permitted.**

Explanation The replication processing has started to process the log space data of the specified server session of the master database.

Action No action required.

INODSI2158 **Backup from backup_date deleted**

Explanation After backup, the number of backup generations is updated, i.e older backups are removed. For further information, please refer to the documentation of the server parameter "number of backup generations".

Action No action required.

INODSI2166 **Initial backup removed**

Explanation After backup, the number of backup generations is updated, i.e older backups are removed. For further information, please refer to the documentation of server parameter "number of backup generations".

Action No action required.

INODSI2190 **Doctype doctype has been loaded**

Explanation The specified doctype has been successfully loaded.

Action No action required.

INODSI2196 **Connection to master database master dbname reestablished**

Explanation The replication database obtained new replication data from its master database.

Action No action required.

INODSI2199 **Replication data of session session was generated with different update or hotfix level of Tamino version version: update level update, hotfix number hotfix**

Explanation At the master database node a new update of a Tamino version was installed.

Action Install the same update of the Tamino version at the replication database node.

INODSI2239 **The backup tape from initial savepoint has been unregistered**

Explanation The information about the availability of the initial backup tape has been removed.

Action The tape may be removed from the archive.

INODSI2259 **Creating / deleting database process active, wait for continue**

Explanation Another job which creates or deletes a database is active on the current node. View running jobs for more information.

Action Wait until this task has been completed. You should not wait longer than a couple of seconds.

INODSI2267 **Convert database to version version**

Explanation The database will be converted to the version displayed.

Action No action required.

INODSI2300 **Keep backup file filename**

Explanation The backup file was not deleted because it was selected to be kept by the user.

Action Keep in mind that there is still a backup file occupying disk space.

INODSI2310 **Licensed for name with ID id**

Explanation Display customer/partner information from the license file.

Action No action required.

INODSI2311 **Licensed for customername sub-licensed by partnername with ID partnerid**

Explanation This is a display of customer/partner information from the license file.

Action No action required.

INODSI2312 **Licensed for customername with ID customerid sub-licensed by partnername**

Explanation This is a display of customer/partner information from the license file.

Action No action required.

INODSI2313 **Licensed for customername with ID customerid sub-licensed by partnername with ID partnerid**

Explanation This is a display of customer/partner information from the license file.

Action No action required.

INODSI2314 **Licensed for name with ID id, license expires on date**

Explanation Display customer/partner and expiration information from the license file.

Action No action required.

INODSI2315 **Licensed for customername sub-licensed by partnername with ID partnerid, license expires on date**

Explanation This is a display of customer/partner and expiration information from the license file.

Action No action required.

INODSI2316 **Licensed for customername with ID customerid sub-licensed by partnername, license expires on date**

Explanation This is a display of customer/partner and expiration information from the license file.

Action No action required.

INODSI2317 **Licensed for customername with ID customerid sub-licensed by partnername with ID partnerid, license expires on date**

Explanation This is a display of customer/partner and expiration information from the license file.

Action No action required.

INODSI2343 **Backup created with backup key 'backupkey' (from)**

Explanation The identification of the last created backup is displayed.

Action No action required.

INODSI2344 **backup key 'backupkey' (from)**

Explanation This is a display of backup information.

Action No action required.

INODSI2345 **backup key 'backupkey' (initial backup)**

Explanation This is a display of backup information.

Action No action required.

INODSI2346 **Deleting disabled backup from backup_date**

Explanation A disabled backup file is being deleted.

Action No action required.

INODSI3469 **Dataset dsn created on date**

Explanation The dataset was created on the specified date.

Action No action required.

INODSI5263 **Restoring pending transactions**

Explanation Pending global transactions are being restored during the server startup processing.

Action No action required.

INODSI5270 **Use parameter "param" to force server registration**

Explanation The server could not register with the XTS directory service, because an entry for the server is already present. If this entry is no longer necessary the specified parameter can be used to overwrite the existing entry.

Action Set the specified parameter to YES to force server registration.

INODSI5282 **Overwriting Software AG XTS Directory Server entries**

Explanation The Software AG XTS Directory Server entries already existed. They are overwritten.

Action No action required.

INODSI5286 **New block allocations for database**

Explanation There were container size/blocksize correlations which require new allocations for all files in the database.

Action No action required.

INODSI5299 **Data space container, file file name removed**

Explanation The database space with the qualified type and name has been removed from the file system.

Action No action required.

INODSI5339 **Log space of server session session number from different version - recovery stopped**

Explanation The next log space to be processed was created by another program version.

Action See the product documentation for further information about migration between program versions.

INODSI5352 **Preparing for external backup**

Explanation The database is in synchronized mode, so an external backup can now take place.

Action No action required.

INODSI5353 **Continuing after external backup**

Explanation The synchronized mode of the database has ended. Normal database processing can resume.

Action No action required

INODSQ1651 **The currently inserted tape has been processed**

Explanation The currently inserted tape has been completely filled (backup) or completely read (restore).

Action Please insert the next tape in the set so that processing may continue.

INODSQ1652 **The diskette is full**

Explanation An operation writing to a diskette has completely filled up the diskette.

Action Provide the information you are prompted for to enable Tamino to switch to a new diskette.

INODSQ1653 **Please insert the next sequential tape and verify the selected device name is correct.**

Explanation Another tape is required in the current backup or restore sequence.

Action Insert the next sequential tape and verify the device name is correct.

INODSQ1654 **Please insert diskette diskette number and specify the device name**

Explanation Another diskette is required.

Action Insert the indicated diskette and specify the device name.

INODSQ1655 **First tape required**

Explanation The first tape is required.

Action Insert the first tape.

INODSQ1656 **First diskette required**

Explanation The first diskette is required.

Action Insert the first diskette.

INODSQ1657 **Please insert first tape again and specify the device name**

Explanation The first tape is required.

Action Insert the first tape and specify the device name.

INODSQ1658 **Waiting for space on LOG device**

Explanation The server can no longer perform update operations, because there is no more free space on the LOG device.

Action Create free space on the LOG device, e.g. by deleting files.

INODSQ1659 **Try to get free space on device where LOG is located**

Explanation The server can no longer perform update operations, because there is no more free space on the LOG device.

Action Create free space on the LOG device, e.g. by deleting files.

INODSQ1660 **Continue server startup or re-execute restore/recover**

Explanation When you continue the server startup, autorepair will be used. Database modifications not recovered during the recovery run of the previous aborted server session will be lost.

Action Decide whether to continue or abort the server startup.

INODSQ1661 **Please reply "yes" or "no" to continue server startup**

Explanation At this point in time you can continue or abort the server startup.

Action Enter "yes" to continue the server startup, enter "no" to abort it.

INODSQ2224 **Transfer via pipe stalled**

Explanation The backup activity via named pipe is hanging. One reason could be that the partner pipe process died for some reason, for example if the disk is full.

Action Find out the reason why the pipe processing is hanging and answer 'OK' to continue or 'Abort' to abort the backup processing.

INODSQ2225 **Continue or abort ?**

Explanation Continue or abort the processing. If you answer 'abort' the process immediately terminates with an appropriate message. Answer 'OK' to continue processing if you are sure that the pipe process is still active.

Action no action

INODSQ2256 **File extent extnumber missing**

Explanation A physical file extent of e.g. a backup file was not specified.

Action Enter the file/device name of the required file extent.

INODSQ2257 **Enter file/device name**

Explanation Enter here the full qualified file name of the required extent. Pipe or tape devices may be entered as well.

Action No action required.

INODSQ2295 **No location for database space extent no**

Explanation There is no location given for this database space.

Action Select a valid location.

INODSR1479 **Creating database space extent number of number of extents**

Explanation This is an informational message indicating how many extents of a group of extents have been created for the database space.

Action No action required.

INODSR1483 **Deleting database space extent number of number of extents**

Explanation This is an informational message indicating how many extents of a group of extents for the database space have been deleted.

Action No action required.

INODSR1682 **Analyzing journal information**

Explanation This is an informational message.

Action No action required.

INODSR1683 **Re-applying changes. Processing journal block block number.**

Explanation This is an informational message.

Action No action required.

INODSR1684 **Reconstructing consistent index structures. Processing journal block block number.**

Explanation This is an informational message.

Action No action required.

INODSR1685 **Resetting unfinished transactions. Processing journal block block number.**

Explanation This is an informational message.

Action No action required.

INODSR1686 **Recovered from abnormal termination**

Explanation This is an informational message.

Action No action required.

INODSR1687 **Reading parameters**

Explanation This is an informational message.

Action No action required.

INODSR2029 **Offline conversion phase**

Explanation This is an informational message.

Action No action required.

INODSR2077 **Re-applying updates started**

Explanation The recover process has started.

Action No action required.

INODSR2078 **Re-applying updates of session session**

Explanation The recover process has started re-applying updates of the next session.

Action No action required.

INODSR2079 **Re-applying updates completed**

Explanation The recover process has finished.

Action No action required.

INODSR5347 **Preparing external backup**

Explanation This is an information message.

Action No action required.

INODSR5348 **Synchronizing database**

Explanation This is an information message.

Action No action required.

INODSR5349 **Processing external backup**

Explanation This is an information message.

Action No action required.

INODSR5350 **Performing final cleanup**

Explanation This is an information message.

Action No action required.

INODSR5351 **Processing external restore**

Explanation This is an information message.

Action No action required.

INODSR5362 **Processing backup**

Explanation A backup operation is currently being processed.

Action No action required.

INODSR5363 **Processing restore**

Explanation A restore operation is currently being processed.

Action No action required.

INODSS1005 **Create database space**

Explanation This message indicates that the specified function is in progress.

Action No action required.

INODSS1009 **Delete database space**

Explanation This message indicates that the specified function is in progress.

Action No action required.

INODSS1089 **Creating database with reorganization ...**

Explanation The database will be created from a backup with defragmentation of the database layout.

Action No action required.

INODSS1711 **Recovering from abnormal termination**

Explanation This is an informational message.

Action No action required.

INODSS1712 **Starting database server**

Explanation This is an informational message.

Action No action required.

INODSS1713 **Checking database for index inconsistencies**

Explanation This is an informational message.

Action No action required.

INODSS1714 **Deleting database 'database_name'**

Explanation This is an informational message.

Action No action required.

INODSS2025 **Creating database ...**

Explanation Tamino is creating a new database.

Action No action required.

INODSS2076 **Performing recovery**

Explanation The restore/recover process is in the recover phase.

Action No action required.

INODSS2159 **Converting database**

Explanation The database is being upgraded or downgraded.

Action No action required.

INODST1751 **Start of Tamino name version modifierversionmodifier2 on system info**

Explanation This is an informational message.

Action No action required.

INODST1752 **Database database name Session session number (name modifierversion on system info, process ID pid)**

Explanation This is an informational message.

Action No action required.

INODST1753 **Database database name Read-Only Session (name modifierversion on system info, process ID pid)**

Explanation This is an informational message.

Action No action required.

INODST1766 **Database database name Replication Session (name modifierversion on system info, processID pid)**

Explanation The server started for a replication database.

Action No action required.

INODST1781 **Start of product name on system info**

Explanation This is an informational message.

Action No action required.

INODSV1053 **Database autorepair suppressed**

Explanation The previous server session terminated abnormally. The server attempted to perform an autorepair, but the autorepair has been suppressed by external manipulation. The database might be in an inconsistent state.

Action Determine what kind of manipulation has occurred and contact your software supplier.

INODSV1129 **System error errno occurred**

Explanation A system error has occurred in the context of the current task.

Action Check the manufacturer's manual.

INODSV1174 **No input data available**

Explanation The specified input file is empty.

Action Ensure that the correct input file is being used.

INODSV1245 **Error information: log space of server session session number - block block, location record**

Explanation The information describes the location of the recently processed log space data

Action Keep this information when log space data analysis is required.

INODSV1258 **Journal overflow. Server cannot proceed.**

Explanation The journal space was insufficient. The current server session has to be terminated.

Action Check if more journal space can be provided. Restart the server.

INODSV1281 **Component comp called at extension point extp returned response rsp**

Explanation The Tamino server called an external component which returned an error response.

Action Please contact your software supplier.

INODSV1473 **The database server is active on the local node**

Explanation This is an informational message.

Action No action required.

INODSV1587 **Internal event SCLOST has occurred**

Explanation A sort action has failed due to resource problems. A retry will be started automatically.

Action No action required.

INODSV1801 **Previous server session failed during write operation**

Explanation The previous server session was performing a write operation on modified data when the server session terminated abnormally.

Action If you can be sure that a single write operation is atomic on your system, you can ignore this warning. You can always assume so if there was no power failure and if the previous server session did not abort due to an I/O error. If you cannot be sure, recover your database from the last backup.

INODSV1806 **Aborted by operator**

Explanation The operator has explicitly aborted the operation.

Action No action required.

INODSV1818 **Log space of server session session number is empty**

Explanation An input file to be used for recovery is empty.

Action Check that the correct log space files are present at the log space location.

INODSV2083 **Unlocking port allocation lock failed with response err - int_err**

Explanation An unexpected response was received while trying to unlock the port allocation lock.

Action Please contact your software supplier.

INODSV2118 **Unlocking raw section lock failed with response err - int_err**

Explanation Unexpected response received while trying to unlock the raw section lock.

Action Please contact your software supplier.

INODSV2139 **Unlocking raw section lock failed with response err - int_err**

Explanation Unexpected response received while trying to unlock the container move lock.

Action Please contact your software supplier.

INODSV2226 **System error error (string) occurred**

Explanation An internal system service error occurred.

Action Analyze the error number and the human readable text.

INODSV2273 **The server servername is active**

Explanation The specified server is active.

Action No action required.

INODSV2276 **Aborted by High Availability monitor**

Explanation The High Availability monitor detected that the server did not respond within a specific timeout limit and forced an abnormal crash of this server. There could be two cases: either the server is really hanging or there is something very busy that the check by the High Availability monitor takes a very long time (e.g. a huge buffer flush is in progress).

Action Check if the HA timeout value is reasonable with the context. One dangerous situation can be a long enduring buffer flush which might block applications for a long time. Maybe it is reasonable to run with small flush limit and/or flush group size parameters.

INODSV2281 **System error errno (errtxt) when opening database space space no (path)**

Explanation An internal operating system error has occurred while trying to open a database space.

Action Analyse the error text and consult the manufacturer's manual.

INODSV5266 **Journal overflow. Current activity cancelled.**

Explanation The journal space was insufficient. The current activity has been cancelled. Typically, a transaction has been rolled back internally.

Action Provide more journal space. Restart the terminated activity.

INODSV5269 **Server is already registered with the Software AG XTS Directory Server**

Explanation When the server starts it registers with the Software AG XTS Directory Server. It is possible that entries for the server are already present (server already started somewhere else or previous server session failed). If this message comes as a warning message, the entry found exactly matches the one that should be entered. If this message comes as an error message, the entry found did not match the entry that the server wanted to add.

Action If this message comes as a warning message no action is required. If this message comes as an error message the Software AG XTS Directory Server entry found for the server should be checked and, if no longer necessary, the next server start should be done with the parameter for overwriting the Software AG XTS Directory Server entry activated.

INODSW1014 **Creation of word fragment index failed**

Explanation Creation of word fragment index failed, because corresponding index tree is inaccessible.

Action Use the function "check and repair database" and restart the server.

INODSW1017 **Due to license restrictions, recovery of the database will not be possible**

Explanation Your license file does not allow logging to be enabled. Due to this restriction, recovery of the database will not be possible.

Action Contact your software supplier for an upgrade of your license.

INODSW1035 **Synchronization semaphore lost and recreated**

Explanation The synchronization semaphore was deleted from outside and a new one was created.

Action No action required.

INODSW1115 **Incremental backup disabled due to buffer pool allocation failure**

Explanation An incremental backup is not possible because no space was available for the information of modified blocks.

Action Create the next backup as a full backup. To avoid the allocation failure increase the buffer pool.

INODSW1116 **Incremental backup disabled due to error error**

Explanation An incremental backup is not possible due to an error when maintaining the information of modified blocks.

Action Create the next backup as a full backup. If the error persists, contact your software supplier.

INODSW1151 **Further recovery for doctype doctype will not include index**

Explanation Due to an error during recovery the index of the doctype has been disabled.

Action Even though the index was disabled, data has been recovered. The index can be rebuilt using the"Check and Repair" function.

INODSW1340 **The last available backup could not be deleted**

Explanation It doesn't make much sense to delete all backups. To avoid the situation that someone deletes the last backup by mistake, this deletion is not allowed.

Action If you want to delete this special last backup, you have to create a new one.

INODSW1372 **Waiting for space on space location**

Explanation The location where the file wants to grow has no more free space and the current request will wait until space is available.

Action Either delete unused files from the location that has insufficient space or define a new location with enough space for that file.

INODSW1401 **A transaction has been heuristically committed at time**

Explanation The database system has committed a transaction for which a decision of the transaction manager was pending.

Action No action required.

INODSW1406 **Log space of server session session number processed until time**

Explanation None of the information generated after the given end timestamp of the log space of the specified server session was processed.

Action Verify that the skipped part of the log space is the same as was skipped with a previous recovery.

INODSW1407 **Replication of server session session number resumed using replication data from timestamp. Simultaneous query will be enabled when replication database is up-to-date.**

Explanation The server continued replication processing after replication database startup.

Action No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.

INODSW1409 **Error when opening database space space no (at path): size mismatch**

Explanation The size of the database space is not equal to the size expected by the server.

Action Please contact your software supplier.

INODSW1410 **Error when opening database space space number (at path)**

Explanation The database space could not be opened.

Action Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.

INODSW1411 **Error when opening database space, compressed state is not permitted (at path)**

Explanation The database file has the compressed attribute, which is not permitted, because write errors should be avoided if the device is getting full.

Action Remove the compressed attribute from the database file.

INODSW1412 **System error errno when opening database space space no (path)**

Explanation The specified operating system error has occurred.

Action Please consult the manufacturer's manual.

INODSW1414 **System error errno when opening database space space no (path)**

Explanation The specified operating system error has occurred.

Action Please consult the manufacturer's manual.

INODSW1415 **Replication of server session session number from timestamp started. Simultaneous query will be enabled when replication database is up-to-date.**

Explanation The replication processing has started to process the log space data of the specified server session of the master database.

Action No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.

INODSW1418 **Replication of server session session number stopped. Replication data processed until timestamp.**

Explanation Replication processing is stopped due to an error as described in previous messages. If simultaneous queries were permitted, then the replication database stays online and may be used for further queries.

Action Try to solve the problem at the master database's side or recreate the replication database from a new backup of the master.

INODSW1455 **Database start not allowed because of pending "set version" operation. Please re-execute "set version".**

Explanation A previous "set version" operation aborted. The database may be inconsistent.

Action Try "set version" again. If it fails also the second time, report the problem to your software supplier.

INODSW1482 **Log space of server session session number not to be processed.**

Explanation The log space of the specified server session was not processed because it was skipped by a previous recovery run.

Action Verify that the skipped log space has also been skipped by the previous recovery run.

INODSW1529 **switch internal I/O mode**

Explanation The I/O mode was switched because an internal I/O function is not supported by given platform. This could happen if a platform does not support the call lio_listio().

Action No action required.

INODSW1602 **Insufficient disk space for journal space, resize to: size MB**

Explanation There is insufficient disk space to create journal space of the required size; a reduced size will be used.

Action No action required.

INODSW1689 **Parallel backup not available on Windows, a sequential backup will be performed.**

Explanation The Windows version of backup does not support 'parallel backup', therefore a sequential backup will be performed.

Action No action required.

INODSW1784 **There is a pending autorepair for the database**

Explanation The database had previously not terminated correctly.

Action When the database has been restarted, it will perform an autorepair operation.

INODSW1800 **This is an emergency restart**

Explanation The server stopped the previous server session due to shortage of journal space. If this restart fails, data may be lost or inconsistent.

Action If the restart fails, please recover your data from the last backup.

INODSW1802 **A transaction has been heuristically rolled back at time**

Explanation The database system has rolled back a transaction for which a decision of the transaction manager was pending.

Action No action required.

INODSW1803 **A transaction has been heuristically committed at time**

Explanation The database system has committed a transaction for which a decision of the transaction manager was pending.

Action No action required.

INODSW1804 **Backup task not responding. Ignoring backup activity.**

Explanation A backup task was running when the server came up. The server synchronization with this backup task has failed. The backup will terminate eventually.

Action Check if the backup activity is still running. If so, it can be terminated. Redo the backup.

INODSW1805 **The server cannot proceed until the backup activity has finished**

Explanation The server will wait for the backup activity to complete. When it has finished, the server will continue.

Action No action required.

INODSW1807 **Switched to read-only mode because a database space is not writable**

Explanation The database will not accept updates.

Action If this behavior is not intended, make all database spaces write-accessible.

INODSW1808 **Read-only database**

Explanation The database is read-only. Some functions are disabled.

Action No action required.

INODSW1809 **Error when opening database space space no (at path): size mismatch, expected bytes bytes**

Explanation The size of the database space is not equal to the size expected by the server.

Action If the operation does not complete successfully, please contact your software supplier.

INODSW1810 **database space space no opened for read-only access**

Explanation The specified database space was opened for read-only access. No updates will be possible on this database space.

Action No action required.

INODSW1811 **Database might be corrupted**

Explanation An inconsistency has been found in the database.

Action Check the database for consistency.

INODSW1812 **Backup process is not responding**

Explanation The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.

Action Restart the backup.

INODSW1813 **Backup process is not communicating completion**

Explanation The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.

Action Restart the backup.

INODSW1814 **Backup process is not fetching modified data**

Explanation The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.

Action Restart the backup.

INODSW1815 **Before image mismatch for number instances on doctype doctype**

Explanation This is an internal error.

Action Please contact your software supplier.

INODSW1817 **Read-only database server accessed**

Explanation A utility is being run against a read-only database server. Certain functions may not be available.

Action No action required.

INODSW1819 **Invalid starting block number block number for log space from session session number**

Explanation The log space does not contain correct log information.

Action Check if files have been moved or copied to the log space location.

INODSW1823 **Unable to remove shared memory**

Explanation It has not been possible to remove a shared memory segment.

Action Remove any allocated shared memory with available system tools.

INODSW1825 **Unexpected database error: resp**

Explanation An internal database error has occurred.

Action Please contact your software supplier.

INODSW1827 **Function is deactivated**

Explanation The requested function is not activated at present.

Action No action required.

INODSW1828 **Doctype deleted but de-allocation failed (reason code reason)**

Explanation A doctype has been deleted from the database but it could not be de-allocated.

Action Determine the cause of the failure from the supplied reason code.

INODSW1829 **Unable to remove utility flag and/or write event**

Explanation The utility was in its final cleanup phase but could not complete all required actions.

Action The utility has terminated successfully, but the cause of the cleanup failure should be determined.

INODSW1830 **Event could not be written due to response response**

Explanation The utility has failed to write a final event due to the response reported.

Action The utility will end successfully. The response code indicates the reason for the failure to write an event.

INODSW1835	**Waiting for debugger to attach**
Explanation	This message is displayed by debug-enabled executables if they have been selected for debugging.
Action	Please contact your software supplier.

INODSW1836	**Mass load recovery files not archived**
Explanation	The mass load recovery files could not be copied to the archive location.
Action	Check for a reason why files could not be created at the archive location. Copy the mass load recovery files manually.

INODSW1837	**An error occurred during the create index process on doctype doctype**
Explanation	The error is caused by an attempt to create a unique index for non-unique data values.
Action	Contact your software supplier.

INODSW1838	**Log space of server session session number processed until time**
Explanation	None of the information generated after the given end timestamp of the log space of the specified server session was processed.
Action	Verify that the skipped part of the log space is the same as was skipped with a previous recovery.

INODSW1839	**Log space of server session session number extent extent number not archived**
Explanation	A log space extent could not be copied to the archive location.
Action	Check the log archive location name and for available space.

INODSW1840	**Log space of server session session number extent extent number not closed**
Explanation	A log space extent could not be closed.
Action	No action required.

INODSW1841	**Database successfully checked and repaired. Number of repaired indexes is number.**
Explanation	The database has been repaired.
Action	No action required.

INODSW1842 **Update in internal configuration store could not be logged**

Explanation Configuration was successfully updated, however the update could not be logged. Possible reasons may be - update log file is read-only or there is not enough space on device where Tamino is installed.

Action In most cases this warning can be ignored. Inform your system administrator about the warning.

INODSW1843 **No information about previous recovery processing**

Explanation Recovery processing was aborted without being able to write recovery progress information.

Action See the instructions within subsequent messages.

INODSW1845 **Continuing server startup will disable all existing backups**

Explanation A preceding Restore/Recover operation that specified an "until" date that is earlier than the latest backup was performed. This means that any backup that was performed after the "until" date of the Restore/Recover operation is no longer valid.

Action Create a new database backup as soon as possible.

INODSW1846 **All backups disabled, create a new backup copy**

Explanation No information about previous recovery processing was available, all backups have been disabled.

Action Create a new database backup as soon as possible.

INODSW1848 **Container file could not be extended, but attempt to continue**

Explanation The database could not be extended as the backup file signalled. The restore is continued but later I/O errors are possible.

Action You can ignore this message if the restore terminates successfully. If the restore fails due to an I/O error you must check why the database could not be extended.

INODSW1980 **Skipping recovery terminated with warning status**

Explanation While skipping the recovery a situation occurred that requires further investigation.

Action Check for additional messages in the event log.

INODSW1981	**Recovery terminated with warning status**
Explanation	During recovery a situation occurred that requires further investigation.
Action	Check for additional messages in the event log.

INODSW1993	**keyword combination not allowed**
Explanation	The supplied keyword combination is invalid.
Action	Correct the input parameters.

INODSW1997	**Due to license restrictions, the database will be started in readonly mode**
Explanation	Your license is restricted to readonly mode. Due to this restriction, updates of the database will not be possible.
Action	Contact your software supplier for an upgrade of your license.

INODSW2047	**Version cd database version not installed, using compatible version instead**
Explanation	The version of the CD database is not installed on the target system. However a compatible version was found and will be used.
Action	No action required.

INODSW2066	**Journal size specified is less than the minimum allowed size of numberMB. Increasing to numberMB.**
Explanation	The journal size specified is less than the minimum required to allow correct operation of the server. Tamino is adjusting the journal size up to the minimum size.
Action	No action required.

INODSW2073	**Previous log file corrupted (reason: reason). Please perform a database backup as soon as possible.**
Explanation	During restart after a database crash it was detected that the log file of the previous session is corrupt. A database recovery may fail, therefore a new backup would resolve this situation. Moreover a further database replication would fail, therefore if the database is or will be a replication master the replication must be newly set up with a new database backup.
Action	Perform a new database backup. Revise replication. Reestablish replication with the new database backup.

INODSW2089 **Port port already in use as name by server server**

Explanation The port to check is already in use.

Action Choose another port or be aware that problems with port usage might occur.

INODSW2090 **Port port used as name by server server is located in selected dynamic port range**

Explanation An allocated port was found in the dynamic port range.

Action Specify another dynamic port range or change the allocated port so that it is located outside the dynamic port range.

INODSW2098 **Web server webserver assigned to database server**

Explanation The web server is assigned to a database and must not be removed before it is deassigned.

Action Keep this web server definition or deassign it from all databases.

INODSW2101 **Web server configuration changed, notification of server server failed (rc1,rc2,rc3)**

Explanation The web server configuration was changed, but the server notification failed.

Action The server has to be restarted manually.

INODSW2102 **Web server configuration changed for web server webserver, but server notification failed**

Explanation The web server configuration was changed, but the notification of active servers failed.

Action Restart all active servers which have assigned the web server in question.

INODSW2112 **User specified record ID number is not within proposed range**

Explanation The load utility was called with at least one record ID which is within a used range. In the event of a crash the internal doctype may have a corruption.

Action This is an internal problem. Please contact your software supplier.

INODSW2113 **Cleanup of a mass load failed with error**

Explanation The cleanup task, e.g. within a rollback, of a mass load failed for internal reasons.

Action Please contact your software supplier.

INODSW2133 **Nothing to verify, no data available**

Explanation The item only contains index values, therefore no verification is necessary.

Action No action required.

INODSW2147 **Replication of server session session number resumed using replication data from timestamp. Simultaneous query will be enabled when replication database is up-to-date.**

Explanation The server continued replication processing after replication database startup.

Action No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.

INODSW2152 **Port port is currently active and may not be usable**

Explanation The specified port is currently active and may not be usable by the Tamino server.

Action Specify another port for the Tamino server or free up the active port before starting the Tamino server.

INODSW2153 **Flush limit too high. Value adjusted to new value.**

Explanation The flush limit specified was too high. It has been adjusted to a reasonable value.

Action To avoid this warning at each startup of the database, configure a lower value.

INODSW2155 **Replication of server session session number from timestamp started. Simultaneous query will be enabled when replication database is up-to-date.**

Explanation The replication processing has started to process the log space data of the specified server session of the master database.

Action No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.

INODSW2156 **Database name1 is fully overlaid with backup from database name2**

Explanation The backup file which was created by a foreign database has been restored into the current database. The previous content of the database has been completely deleted.

Action No action required.

INODSW2161 **corrupted data repaired**

Explanation A detected corruption was repaired immediately by Tamino.

Action No action required.

INODSW2171 **Replication data of session session requires new Tamino version version**

Explanation The replication database is using a different Tamino version than the master database.

Action Install the required Tamino version at the repliction database node. If the required version is already installed and the error still exists, re-create the replication database using a backup created from this Tamino version.

INODSW2172 **Master database must be restarted before a replication database can be set up**

Explanation The name of the first replication database has been added to the permission list. The database can be set up as a replication database of this master only after the master has been stopped and restarted.

Action Stop the master database and start it again.

INODSW2180 **Connection to server lost, reason reason**

Explanation The working process must be terminated because the server is stopping or has already stopped. There are 2 possible reasons: 0 means the server has stopped, 1 means the server is stopping and has aborted the process.

Action Check why the server stopped.

INODSW2186 **The configured buffer pool size (lbp MB) exceeds the machine's physical memory size (pms MB)**

Explanation The buffer pool size is configured so that it exceeds the physical memory size of the machine. This does not make sense because the buffer pool replacement strategy will collide with the operating systems memory management.

Action Choose a buffer pool size that is at least smaller than the machine's physical memory size.

INODSW2191 **The maximum number of threads allowed per process (max_threads) may not be sufficient to manage the database server**

Explanation The current parameter configuration may not allow the creation of all necessary threads to manage the database server.

Action Either the system defined maximum number of threads per process is too low and should be increased, or the database parameter configuration should be changed to decrease the number of threads to be created.

INODSW2195 **Connection to master database master dbname interrupted**

Explanation The replication database cannot obtain replication data from its master database.

Action No action required.

INODSW2197 **Replication of server session session number stopped. Replication data processed until timestamp.**

Explanation Replication processing is stopped due to an error as described in previous messages. If simultaneous queries were permitted, then the replication database stays online and may be used for further queries.

Action Try to solve the problem at the master database's side or recreate the replication database from a new backup of the master.

INODSW2198 **Update logging in internal configuration store is not active**

Explanation Updates in the internal configuration store are not logged because update logging is not activated in the current process.

Action Please contact your software supplier.

INODSW2207 **No reading process attached to pipe path**

Explanation Backup location is a named pipe and no process has the pipe open for reading. This situation may occur during database backup or database creation, when initial backup is being made.

Action Start the process that reads from the pipe and perform the backup again.

INODSW2209 **Inconsistent location definition (location) - expected type expected, real type real**

Explanation The location type is unexpected. This is typically the result of user intervention , for example the user deletes a location directory and creates a file with the same name.

Action Make sure that Tamino locations are not modified outside of Tamino.

INODSW2210 **Location location is nearly full**

Explanation Not enough disk space is left on the location.

Action Free some space or use another location.

INODSW2230 **Logging error in internal configuration store occurred at time, future updates may not be logged**

Explanation The internal configuration store showed an update logging error that occurred in the past. There is a chance that future updates will also not be logged, thus preventing a repair of the internal configuration store after a severe error. This message is displayed at each server startup unless you execute the described actions.

Action To be sure to be able to recreate all configuration data, you can do the following: Copy your registry (all under the key 'Tamino') to a file. Use the 'export' function of your registry editor. Then clean your registry logging file or use another file. The registry logging file is defined with a string value at the registry key 'Tamino'. Combining both files lets you repair your Tamino registry in the case of a corruption. Finally you can remove the 'registry logging error' string value from the registry either with your registry editor or with the Registry functions of your Tamino manager.

INODSW2238 **No space to remove**

Explanation The request to remove database space cannot be performed, because trailing space is in use.

Action No action required.

INODSW2240 **File/path path does not exist or is not accessible**

Explanation The given file/pathname does not exist or is not accessible. It will just be skipped.

Action Check the file/pathname.

INODSW2244 **Cannot create initial backup - reference to original one is not possible; perform backup for the database as soon as possible**

Explanation The initial backup for the new database could not be created. It tries to reference this backup, but the backup is already registered with another active database. So the database is left without a valid backup !

Action Perform a database backup as soon as possible.

INODSW2245 **Cannot create initial backup - but referred to original one**

Explanation The creation of the initial backup of the new database failed. Nevertheless a backup entry was set up pointing to the file/device where the creation-backup comes from. This has the same effect as when the nocopyoption has been used.

Action No action required.

INODSW2246 **Reference to original backup is not possible; perform backup for the database as soon as possible**

Explanation The create from backup was used with the nocopy option, which means that the incoming backup file will just be referenced instead of copied. But it is not permitted to reference a backup file which is already registered with an active database. Now there is no valid backup for the created database

Action Perform a database backup as soon as possible.

INODSW2247 **Location skipped (no space)**

Explanation The given location has not enough space for creating a database file. It skips to the next location if any.

Action Check the space in this location.

INODSW2248 **Location skipped, (internal error err)**

Explanation The current location cannot be used and will be skipped. The internal error displayed gives the detailed reason.

Action Analyse the error and check the path name of the location.

INODSW2260 **create / delete database synchronization failed with (error)**

Explanation The semaphore synchronisation failed with an internal error.

Action Do not start another create / delete database in parallel.

INODSW2261 **Removing backup file (filename) failed due to internal error error**

Explanation The given backup file cannot be removed due to displayed error reason, but it will be unregistered.

Action Delete the backup file by hand if you decide that it would never be needed any more.

INODSW2262 **Problem during referencing initial backup file (file), reason: reason**

Explanation A reference operation (insert/delete) to a backup file failed. A reference will be set up at create database from backup to the source backup file. If the setting of a reference failed, then it may happen that the owner of the backup deletes the backup fie although a foreign database has it still registered. If this operation failed at the owner side, it may happen that the backup file remains in the file system although it was logically deleted.

Action Check the databases where this backup file is registered. Maybe perform a new backup of databases which have this backup file registered.

INODSW2269 **Failed to load ADABAS interface (library)**

Explanation The Tamino server failed to load the ADABAS interface.

Action Provide a valid ADABAS interface in one of the locations searched during the library load.

INODSW2277 **Buffer pool size set to size MB due to shortage of shared memory**

Explanation The available shared memory was not large enough to allocate the buffer pool with the configured size.

Action Check whether the configured size of the buffer pool meets the memory resources available within the given environment.

INODSW2297 **Perform emergency shutdown, because server is within a space wait situation**

Explanation The server is waiting for space on the log file, therefore a clean shutdown is not possible. It aborts the server with a pending autorepair.

Action Clean up the log space location and restart the server.

INODSW2318 **The license for name with ID id expires in number days**

Explanation The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2319 **The license for customername sub-licensed by partnername with ID partnerid expires in number days**

Explanation The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2320 **The license for customername with ID customerid sub-licensed by partnername expires in number days**

Explanation The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2321 **The license for customername with ID customerid sub-licensed by partnername with ID partnerid expires in number days**

Explanation The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2322 **The license for name with ID id expires in 1 day**

Explanation The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2323 **The license for customername sub-licensed by partnername with ID partnerid expires in 1 day**

Explanation The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2324 **The license for customername with ID customerid sub-licensed by partnername expires in 1 day**

Explanation The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2325 **The license for customername with ID customerid sub-licensed by partnername with ID partnerid expires in 1 day**

Explanation The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2326 **The license for name with ID id has expired, server will abort in number days**

Explanation The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2327 **The license for customername sub-licensed by partnername with ID partnerid has expired, server will abort in number days**

Explanation The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2328 **The license for customername with ID customerid sub-licensed by partnername has expired, server will abort in number days**

Explanation The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2329 **The license for customername with ID customerid sub-licensed by partnername with ID partnerid has expired, server will abort in number days**

Explanation The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2330 **The license for name with ID id has expired, server will abort in 1 day**

Explanation The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2331 **The license for customername sub-licensed by partnername with ID partnerid has expired, server will abort in 1 day**

Explanation The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2332 **The license for customername with ID customerid sub-licensed by partnername has expired, server will abort in 1 day**

Explanation The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2333 **The license for customername with ID customerid sub-licensed by partnername with ID partnerid has expired, server will abort in 1 day**

Explanation The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.

Action Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW5255 **Internal parameter error (param), using default**

Explanation An invalid internal parameter value was found. The default parameter value is used.

Action Please contact your software supplier.

INODSW5274 **number updates excluded on doctype doctype**

Explanation Due to an error during recovery, not all updates have been re-applied.

Action Check the previous error messages to find more information about the error.

INODSW5275 **Updates performed between server startup and recovery start**

Explanation Updates between server startup and recovery start are not allowed.

Action Please check subsequent messages for more information.

INODSW5294 **waiting for buffer flush end**

Explanation The dump utility must wait until the Tamino server completes the buffer flush action.

Action No action required.

INODSW5329 **Sort request couldn't be specified, reason subc**

Explanation A sort request failed, for the reason specified in the message

Action Contact your software supplier.

INODSW5340 **Collating key truncated to size bytes**

Explanation The collation key was truncated due to the size limit for index values. Only less important information was truncated.

Action Normally, collation should be defined only for small pieces of data (e.g. words), not for the large texts. Consider reviewing your collation definitions.

INODSW5355 **File system UNMOUNT problem, reason reason errtxt**

Explanation Restoring an external backup may require the remounting of the file system. This is necessary to flush the file system cache.

Action Remount the file system manually and contact your software supplier.

INODSW5356 **File system MOUNT problem, reason reason errtxt**

Explanation Restoring an external backup may require the remounting of the file system. This is necessary to flush the file system cache

Action Remount the file system manually and contact your software supplier.

INODSW5400 **Internal sort order lost**

Explanation A sort request could not be satisfied due to internal reasons.

Action You can force a memory dump with "inodba database=name trap=9299" for further analysis after reproducing the error.

INODSW5401 **Function not completely executed**

Explanation A request failed due to internal reasons.

Action You can force a memory dump with "inodba database=name trap=9298" for further analysis after reproducing the error.

INOINE2051 **Resetting the unique status on all indices**

Explanation Duplicate values were detected. Therefore the unique status could not be set for the indices.

Action Resolve any uniqueness conflicts before trying to set the unique status.

INOINE2053 **Index name already in use**

Explanation The specified index name is already in use for this doctype.

Action Retry the required operation with an unused index name.

INOINF2251 **Sort file too small or work pool too large**

Explanation The sort file used is too small or the specified work pool is too large for the given sort file.

Action Ensure that a sufficiently large sort file is available.

INOINF2252 **Sort file too small**

Explanation The sort file used is too small.

Action Ensure that a sufficiently large sort file is available.

INOINF2253 **Corrupt index found**

Explanation Corrupt information has been found in the index.

Action Please contact your software supplier, and/or reload the data to repair the damage.

INOINI2174 **Index processing completed on doctype doctype**

Explanation The requested index operation has ended.

Action No action required.

INOINI2452 **Index modification started**

Explanation The database index modification process has started.

Action No action required.

INOINI2453 **Index modification completed**

Explanation The index modification process has completed.

Action No action required.

INOINI2454 **Index cannot be sorted in main memory**

Explanation The index process cannot perform the sort in main memory. This is an informational message. An external sort will be performed.

Action No action required.

INOINI2455 **Index cannot be sorted**

Explanation It is not possible to sort the index, probably due to a lack of space.

Action Allow more space to be allocated for a main memory sort of the index, if possible.

INOINI2456 **Index cannot be processed in two passes**

Explanation It is not possible to process the index in two passes due to insufficient temporary storage.

Action Allocate more temporary storage to allow the index to be processed in two passes.

INOINI2457 **Index cannot be processed in one pass**

Explanation It is not possible to process the index in one pass due to a lack of temporary storage.

Action Allocate more temporary storage to allow the index to be processed in one pass.

INOINI2459 **Index verification limit has been reached**

Explanation The number of errors found while verifying the index has reached the allowed limit.

Action Correct the errors in the index, and run the certification process again.

INOINI2460 **Data space passes required: count**

Explanation This is the number of passes of the data space required to perform the index operation.

Action No action required.

INOINI2461 **Sort file efficiency: sorteff %**

Explanation This is the calculated efficiency of the sort file during the index process.

Action No action required.

INOINI2462 **Work pool efficiency: workeff %**

Explanation This is the calculated efficiency of the work pool during the index process.

Action No action required.

INOINI2467 **Recommended minimum temporary storage size = size KB**

Explanation This is the recommended (minimum) temporary storage size that will be allocated for the process.

Action No action required.

INOINI2471 **Temporary storage size = size KB**

Explanation This is the size of the required temporary storage.

Action No action required.

INOINI2472 **Temporary storage size (1 pass) = size MB**

Explanation This is the temporary storage size required for 1 pass processing.

Action No action required.

INOINI2473 **Temporary storage size (2 passes) = size MB**

Explanation This is the temporary storage size required for 2 pass processing.

Action No action required.

INOINI2474 **Sorting index**

Explanation The index field is being sorted.

Action No action required.

INOINI2475 **No values for index (desc)**

Explanation No values are present for the index field.

Action No action required.

INOINI2476 **Loading index**

Explanation The index field specified is being loaded.

Action No action required.

INOINI2477 **Verifying index (desc)**

Explanation The index field specified is being verified.

Action No action required.

INOINI2478 **Unique status for specified index is being set**

Explanation The unique status for the specified index field is being set.

Action No action required.

INOINI2479 **Unique status for specified index is being reset**

Explanation The unique status for the specified index field is being reset.

Action No action required.

INOINI2480 **Unique status removed for index**

Explanation The unique status of an index field has been removed.

Action No action required.

INOINI2481 **No index fields were found for the specified doctype**

Explanation The index function could not be performed because no index fields were found in the specified doctype.

Action Check that the correct doctype was specified for the index operation.

INOINI2482 **Index processing started on doctype doctype**

Explanation The requested index operation has started.

Action No action required.

INOINW2800 **Errors found for count indices**

Explanation A number of indices were found to be in error during the index process.

Action Correct the errors and attempt to perform the index process again.

INOINW2801 **Number of errors found in index: indexerr**

Explanation This message shows the number of indices found to be in error during index processing.

Action Correct the indices in error and perform the index operation again.

INOINW2802 **Unique conflict detected**

Explanation Duplicate values were detected when trying to create a unique index.

Action Remove any unique conflicts in the data.

INOLDE3010 **Invalid combination of keywords**

Explanation The combination of keywords supplied is not allowed.

Action Check the keyword combination and retry the operation.

INOLDE3016 **FIELDS may be specified only once**

Explanation The parameter FIELDS may be specified only once.

Action Continue with other parameter settings.

INOLDE3051 **Invalid output status returned by user exit**

Explanation A user exit has returned an invalid output status to the load process.

Action Ensure that the user exit always returns a valid output status.

INOLDE3054 **Invalid range of sequence numbers**

Explanation The range of sequence numbers to be deleted is invalid.

Action Please contact your software supplier.

INOLDE3055 **Value must be less than or equal to value**

Explanation A value has exceeded the specified maximum.

Action Decrease the value specified.

INOLDE3056 **Invalid record length**

Explanation The input record length must be a multiple of four for binary data.

Action Check the input file.

INOLDE3057 **Sequence number to be deleted is not present**

Explanation The sequence number to be deleted is either not present or outside the specified doctype's limits.

Action Ensure that the sequence numbers to be deleted were specified correctly.

INOLDE3058 **Dataset dataset, record record, offset offset**

Explanation An error has occurred in the specified dataset at the position indicated.

Action Correct the input and retry the operation.

INOLDE3059 **Index index not defined for doctype doctype**

Explanation The specified index is defined in the load description file but is not present in the doctype to be updated.

Action Ensure that the load description file contains the correct information and that the correct doctype is specified.

INOLDE3060 **Read-only database, function not permitted to run**

Explanation The specified database is read-only and the requested function is not allowed for a read-only database.

Action Ensure that the database being accessed is not read-only for this type of operation.

INOLDF3018 **The requested doctype is locked, load aborted**

Explanation The doctype referenced is locked and the load is unable to proceed.

Action Wait until the doctype is available. If the lock is due to a previous problem or corrupt doctype, a server restart may clear the lock and return the doctype to a usable state.

INOLDF3251 **Load aborted in user exit at record number: record**

Explanation The load process has been aborted by a user exit while processing the specified record number.

Action Check the user exit for the reason for aborting the load process.

INOLDF3252 **Record too big for data storage device**

Explanation The record is too large for the data storage device used.

Action Decrease the size of the input record, or use a data storage device with a larger block size.

INOLDF3253 **Incomplete load definition file**

Explanation The input file containing the load definitions is incomplete.

Action Check the load definition file and ensure that it contains the correct information.

INOLDF3254 **Internal buffer overflow**

Explanation An unexpected overflow of an internal buffer has occurred.

Action Please contact your software supplier.

INOLDF3255 **Sort I/O error**

Explanation An I/O error has occurred on the sort data space.

Action Check the sort data space for system errors.

INOLDF3256 **Selection not yet implemented**

Explanation The selection of sequence numbers to be deleted is not yet implemented.

Action No action possible.

INOLDF3257 **Unexpected error while connecting**

Explanation An unexpected error has occurred while trying to connect to the server.

Action Please contact your software supplier.

INOLDF3260 **Error in user store function**

Explanation An error has occurred in a user-supplied store function.

Action Check and correct any user-supplied store functions.

INOLDF3261 **No free sequence numbers**

Explanation An internal shortage of sequence numbers has occurred.

Action Please contact your software supplier.

INOLDF3263 **No free sequence numbers**

Explanation There are no more free sequence numbers available.

Action Please contact your software supplier.

INOLDF3264 **Cannot allocate user-defined sequence number**

Explanation An error has occurred when trying to allocate a user-defined sequence number.

Action Check that the user routine that allocates sequence numbers is correct.

INOLDF3265 **No index read slots**

Explanation An internal error has occurred because there are no read slots available for the index.

Action Please contact your software supplier.

INOLDF3266 **Error while generating index**

Explanation An internal error has occurred while generating an index.

Action Please contact your software supplier.

INOLDF3267 **Temp stream overflow**

Explanation A stream overflow has occurred while processing the temporary data space.

Action Please contact your software supplier.

INOLDF3268 **Doctype locking failed**

Explanation It was not possible to lock a doctype for access.

Action Ensure that nothing else is accessing the doctype to be locked.

INOLDF3269 **Unexpected error while removing utility entry**

Explanation An unexpected internal error has occurred while removing a utility entry.

Action Please contact your software supplier.

INOLDF3270 **Unexpected error while opening sort space**

Explanation An unexpected internal error has occurred while opening the sort space.

Action Ensure that there is enough sort space available.

INOLDF3271 **Load description does not match**

Explanation The definitions in the load description file do not match those of the current doctype.

Action Check that the specifications in the load description file are correct.

INOLDI3002 **Preparing documents for load**

Explanation Preparing documents for load.

Action No action required.

INOLDI3019 **Loading documents in collection**

Explanation The collection is being modified.

Action No action required.

INOLDI3451 **Termination forced by user exit**

Explanation A user exit has forced the load process to terminate.

Action If the termination was unexpected, check the user exit for the reason.

INOLDI3452 **Number of records read: records**

Explanation This is the number of input records read during the load process.

Action No action required.

INOLDI3456 **Number of documents added to doctype doctype: number**

Explanation The load process has added the given number of documents to the specified doctype.

Action No action required.

INOLDI3457 **Number of documents deleted from doctype doctype: number**

Explanation The load process has deleted the given number of documents from the specified doctype.

Action No action required.

INOLDI3458 **Number of documents unloaded from doctype doctype: number**

Explanation The load process has unloaded the given number of documents from the specified doctype.

Action No action required.

INOLDI3459 **The specified number of records have been loaded**

Explanation The number of records to be loaded has been reached.

Action No action required.

INOLDI3460 **Preparing existing indices for merge**

Explanation Existing indices are being backed up before creating new ones.

Action No action required.

INOLDI3461 **No index modification**

Explanation No modifications have been made to any indices.

Action No action required.

INOLDI3464 **Data space is being modified**

Explanation The data space is being modified.

Action No action required.

INOLDI3465 **Data space prepared for delete**

Explanation The data space will be prepared for deleting records.

Action No action required.

INOLDI3467 **Number of referential integrity violations: number**

Explanation This message indicates the number of referential integrity violations encountered during the load process.

Action No action required.

INOLDI3468 **Erasure from referenced doctype is not supported**

Explanation It is not possible to erase from the referenced doctype.

Action No action possible.

INOLDI3474 **Sorting and loading indices**

Explanation The indices are being sorted and loaded.

Action No action required.

INORBE4002 **Function only permitted if restore database**

Explanation A function was chosen that is not permitted in the current context.

Action Use the function while restoring the database.

INORBE4005 **Backup not currently possible; parts of database are locked**

Explanation It is not currently possible to start a backup because parts of the database are locked by other users or operations.

Action Retry the backup when there are no longer any users or operations locking any parts of the database.

INORBE4006 **This function is not permitted on a system file while Tamino server is active**

Explanation To preserve data consistency, the Tamino server should not be active while restoring the database.

Action Shut down the Tamino server.

INORBE4007 **Restore database is not permitted while Tamino server is active**

Explanation To preserve data consistency, the Tamino server should not be active while restoring the database.

Action Shut down the Tamino server.

INORBE4053 **Terminator of backup copy not found**

Explanation The terminator of the backup copy could not be found. The error can occur if the backup was modified outside of Tamino.

Action Make sure that the backup copy was not modified outside of Tamino. If the problem persists , contact your software supplier.

INORBE4056 **Invalid database space size change**

Explanation The value for changing the database space size is invalid.

Action Specify a valid value.

INORBE4057 **No space for database block allocation at database space (number KB at block)**

Explanation The restore requires more space for the database, but it failed. There are two possible reasons: either the database cannot be extended because there is no more space on the disk, or there are internal structure problems.

Action Make sure that there is enough space for the database to be enlarged.

INORBE4060 **Input file is empty**

Explanation The input file specified for the operation is empty.

Action Check that the correct input file has been specified.

INORBE4061 **Invalid sequence of backup copy files**

Explanation The sequence of the specified backup copy files is incorrect.

Action Check that the correct backup copy files have been specified.

INORBE4064 **Synchronization with database server lost**

Explanation The synchronization with the database server has been lost.

Action Retry the backup operation. If the problem persists, contact your software supplier.

INORBE4065 **Invalid block type type**

Explanation I/O from an unexpected database space is going to be logged so command logging has been deactivated.

Action This is an unexpected error. Please contact your software supplier.

INORBE4067 **Unable to open journal space**

Explanation An error has occurred when trying to open the journal space.

Action Check that the journal space exists and is correctly defined.

INORBE4068 **Reference to missing doctype detected**

Explanation A doctype that does not exist has been referenced.

Action This is an internal error. Please contact your software supplier.

INORBF4013 **Server is in startup phase, backup not possible.**

Explanation The server is still in the startup phase and therefore a backup is not possible. This is probably caused by another (offline) backup running, or the server being started.

Action Wait until the other backup has finished, or the server has started, and run the backup again.

INORBF4251 **Invalid block allocation detected (blocks are shared between different doctypes)**

Explanation The database server is in an inconsistent state.

Action This is an internal error. Please contact your software supplier.

INORBF4253 **Error error number during backup: error message**

Explanation A fatal error occurred during backup.

Action Try to solve the problem based on the text of the error message. Otherwise, contact your software supplier.

INORBF4255 **An error occurred when updating the internal configuration store**

Explanation The operation has been terminated because an error occurred while trying to update the internal configuration store.

Action Please contact your software supplier and provide the message text of all messages displayed.

INORBF4257 **Corrupt structure on backup copy**

Explanation The backup copy does not contain the correct structure.

Action Check your input file assignments, and ensure that the correct backup copy is being used.

INORBF4259 **Error occurred in I/O block blockno**

Explanation An I/O error has occurred on the specified block.

Action The backup copy is corrupt; back up the database again to create another backup copy.

INORBF4260 **Online backup already active**

Explanation Another backup function is active. Only one online backup is possible at one time.

Action No action required.

INORBF4263 **Utility not permitted to run**

Explanation This utility is currently not permitted to run.

Action Wait until the database is available.

INORBF4265 **Internal error found in backup copy**

Explanation An internal structure error has occurred in the backup copy. The backup copy may be corrupt. A possible cause of the error is that the backup copy was modified outside of Tamino.

Action Check that the backup copy was not modified outside of Tamino. If the problem persists, please contact your software supplier.

INORBF4266 **Block size of output file too small**

Explanation The block size of the output file is too small.

Action Use an output device with a larger block size.

INORBF4267 **Invalid record detected, block blockno**

Explanation The backup copy file has a structure error with printed information. This backup copy file cannot be used as input for a restore.

Action Run the backup function again.

INORBF4268 **Internal configuration delete by Tamino utility failed**

Explanation The final stage of saveset processing failed; the internal configuration is incorrect.

Action Retry the operation.

INORBF4269 **Internal configuration update by Tamino utility failed because key could not be moved**

Explanation A utility attempted to create an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.

Action No action required. Please contact your system administrator for further information.

INORBF4270 **Internal configuration get by Tamino utility failed because value could not be read**

Explanation A utility attempted to read the values for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.

Action No action required. Please contact your system administrator for further information.

INORBF4271 **Internal configuration set by Tamino utility failed because value could not be set**

Explanation A utility attempted to set the value for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.

Action No action required. Please contact your system administrator for further information.

INORBF4272 **Internal configuration get by Tamino utility failed because values could not be enumerated**

Explanation A utility attempted to count the number of values for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.

Action No action required. Please contact your system administrator for further information.

INORBF4273 **Internal configuration create by Tamino utility failed**

Explanation A utility attempted to create a new internal configuration, but this call failed. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.

Action No action required. Please contact your system administrator for further information.

INORBF4276 **This operation is not allowed while the Tamino server is active**

Explanation The operation cannot be executed when the database has been started.

Action Stop the database and retry the operation.

INORBI4063 **Access to the Tamino server's shared memory is not possible**

Explanation It is not possible to access shared memory of the Tamino server. Synchronization with the server is lost. A possible cause is that the Tamino server has been shut down in the meantime.

Action Retry the backup operation. If the problem persists, please contact your software supplier.

INORBI4452 **Waiting for autorestart**

Explanation The utility action cannot be performed until the database has completed an autorestart.

Action No action required.

INORBI4453 **Initialization phase**

Explanation This is an informational message indicating that a utility is initializing.

Action No action required.

INORBI4454 **Waiting for transactions to commit**

Explanation The requested operation is waiting for all transactions to commit.

Action No action required.

INORBI4455 **Backup copy successfully checked**

Explanation The backup copy has been successfully checked.

Action No action required.

INORBI4456 **No doctype in backup copy**

Explanation The backup copy used for this operation does not contain any doctypes.

Action No action required.

INORBI4457 **Restore of database completed successfully**

Explanation The database has been successfully restored.

Action No action required.

INORBI4459 **Within allocation**

Explanation This informational message occurs when a utility is allocating space.

Action No action required.

INORBI4464 **Formatting of database_space completed**

Explanation This informational message indicates the completion time of the formatting operation.

Action No action required.

INORBI4465 **Formatting of database_space started**

Explanation This informational message indicates that the formatting operation has started.

Action No action required.

INORBI4466 **Database identification set to 'database_name'**

Explanation The database identification has been set to the specified name.

Action No action required.

INORBI4468 **Backup of database_space completed**

Explanation The indicated database space has been backed up.

Action No action required

INORBI4469 **Terminator block: type**

Explanation This message shows the value of the terminator block.

Action No action required.

INORBI4475 **New block allocations for doctype doctype**

Explanation New blocks have been allocated for the specified doctype.

Action No action required.

INORBI4478 **Doctype doctype contained in saveset**

Explanation The doctype specified is contained in the backup saveset.

Action No action required.

INORBI4631 **Backup of database completed successfully**

Explanation A database copy has been backed up successfully.

Action No action required.

INORBQ4000 **Error accessing database space extent no at location restore location**

Explanation The database space was not found at the specified location. The are many possible causes for this. The container may be corrupt or missing, the defined 'Location' may be missing or corrupt or you may not have sufficient access privileges for the specified location. If you have replaced a location and/or container that was previously missing, this error appears because the database server did not expect the container to re-appear after it detected it was missing.

Action Verify that the container exists in the correct location. If you have replaced a previously missing container, please move it out of the way to allow the database server to recreate the container and allow the restore process to continue. If the problem persists, please contact your software supplier.

INORBQ4001 **Confirm location for recreation of database space extent no**

Explanation Confirm the location for recreation of the database space.

Action Enter the location name.

INORBR4681 **Backing up database_space**

Explanation The specified server space is being backed up.

Action No action required.

INORBS4009 **Restoring database with reorganization ...**

Explanation The database is being restored and a data reorganization will be done..

Action No action required.

INORBS4458 **Restoring database ...**

Explanation The database is being restored.

Action No action required.

INORBV4012 **Doctype loaded = loaded_doctypes; actual number of doctypes = actual_doctypes**

Explanation The number of doctypes loaded differs from the number of doctypes in the backup copy.

Action Please contact your software supplier with an exact description of the functions that caused the error.

INORBW4010 **External backup/restore request failed, detailed info in file filename**

Explanation The specific external backup or restore action failed due to an internal reason. Please view the output file indicated by the error message for the problem.

Action Analyze the problem in the error file.

INORBW4015 **The space size will be increased by size MB**

Explanation The container size specified during create is not sufficient. Tamino is automatically extending the container to accommodate the data.

Action No action required.

INORBW4803 **Database identification could not be changed**

Explanation The database identification could not be changed.

Action Ensure that the database identification of the new database is correct.

INORBW4805 **Waiting for database restart**

Explanation The operation is waiting for the restart of the database (due to its abnormal termination).

Action Start the database.

INORBW4806 **Block block number ignored, run verify and repair function for doctype doctypes**

Explanation During backup a corrupt index block was found which will not be backed up to the backup copy.

Action Recreate the index of specified doctype and rerun the backup function.

INOSAE7351	**Duplicate attribute not allowed in element context**
Explanation	The result element will contain multiple attributes of the same name. This is not allowed in XML.
Action	Please verify your query for atrribute construction.

INOSAE7352	**No serialization for attributes without element context**
Explanation	A serialization of attributes without element context was requested but is undefined.
Action	Please verify that the atrribute construction belong to an element context.

INOSAE7353	**ino:document serialization supports only one document in serialization**
Explanation	The ino:document serialization supports only the serialization of a single document.
Action	The query returns more than one document. Correct the query and rerun.

INOSAE7354	**ino:serialization supports only the serialization of document nodes**
Explanation	The ino:document serialization supports only the serialization of document nodes.
Action	Verify that the query returns only nodes of type document.

INOSAE7356	**ino:document serialization has no Query Result**
Explanation	The query returned no matching document.
Action	Correct the query so that it delivers one single document node.

INOSAI7355	**Internal error**
Explanation	During the serialization an internal error occurred.
Action	Please contact your software supplier.

INOSXE6704	**Invalid character 'character' in name for compiler settings**
Explanation	Names for compiler settings must start with a letter and may be followed by letters or digits.
Action	Use a name that obeys this rule.

INOSXE6705	**Settings for default parameter must not be changed**
Explanation	The name 'default' is reserved for the compiler settings defined by the Tamino installation.
Action	Use a name other than 'default' to save these compiler settings.

INOSXE6706 **No configuration parameters found for compiler 'compiler'**

Explanation The current compiler for Direct X-Tension projects is currently set to the compiler indicated; however, one or all of its configuration parameter files have been deleted.

Action Use the default compiler as your current compiler; check your Tamino installation.

INOSXE6707 **X-Tension: COM initialization failed**

Explanation During X-Tension initialization the initialization of the COM library failed. No COM-based extension functions are available during this server session.

Action If COM-based server extension functions are required, fix the COM problem and start the Tamino server again.

INOSXE6709 **Invalid usage entry: 'value'**

Explanation The Usage entry found in file 'Install.xml' could not be recognized.

Action Check the documentation for valid values.

INOSXE6710 **Function 'function' not usable as 'usage'**

Explanation This function cannot be used as the function type indicated. The function's parameter count or parameter datatypes do not correspond to the specified function type.

Action Please check the 'Usage' entry in file 'Install.xml' as well as the parameter specification of the current function. See the documentation for the parameters required for the given Usage.

It is strongly recommended to use the X-Tension development tools to define new X-Tension functions.

INOSXE6711 **Value missing for Init Function 'func'**

Explanation The X-Tension function indicated has been declared as Init Function. However, values are missing for one or more of its parameters.

Action Use the X-Tension tools to create the X-Tension function and be careful editing the file Install.xml.

INOSXE6712 **The server extension crashed or threw an unknown exception**

Explanation Either the server extension has crashed or it threw an exception that could not be caught by the Tamino Server.

Action Please contact the vendor of the server extension.

INOSXE6713 **Extension tried to open message box. Message: 'message'.**

Explanation It is not allowed to display message boxes in a server extension. This terminates the current server extension function.

Action Please check the server extension code carefully. Maybe the C/C++ runtime system tried to open an assertion box because of programming errors in the server extension.

INOSXE6714 **Value is not of the selected data type 'type'**

Explanation The value entered cannot be converted to the data type selected in the 'Add Param' box.

Action Please check the value entered and the data type selected in the 'Add Param' box. See the documentation of Tamino X-Tension for more details on allowed values.

INOSXE6715 **Extension function 'func': Value of parameter 'param' is not of selected data type type**

Explanation The value entered cannot be converted to the data type specified for this parameter.

Action Please check the value entered and the data type specified for this parameter. See the documentation of Tamino X-Tension for more details on allowed values.

Use the Tamino X-Tension tools to specify parameter values!

INOSXE6716 **Unexpected error during callback function 'function'**

Explanation An unexpected error occurred during a call of a callback function. Probably it has been called with one or more incorrect parameters.

Action Check the documentation and your server extension code for the correct use of this callback function.

INOSXE6717 **Server extension function not found**

Explanation The desired function name was not found in the SXS repository. Maybe the function name is incorrect, or the function is not installed or was deinstalled.

Action Check and correct the function name or server extension installation.

INOSXE6725 **Callback not allowed in init function**

Explanation An SxsSetProperty callback is not allowed from a server extension init function.

Action Remove the SxsSetProperty callback from your server extension init function and retry the operation.

INOSXE7000 **Java server extension must have a package name**

Explanation The package name for a Java server extension must not be empty.

Action Define a package name, e.g. "package com.softwareag.mysxs".

INOSXE7001 **File name 'file.sxp' may not be changed**

Explanation Only the directory may be selected; the file name must remain unchanged.

Action Select a directory.

INOSXE7006 **XML callback failed. Transaction was rolled back.**

Explanation No more information.

Action Try with a modified XML request.

INOSXE7009 **Tamino X-Tension not available**

Explanation It is not possible to call a Tamino server extension because either X-Tension is not licensed or the X-Tension feature is not available on this platform.

Action If possible, buy a license for Tamino X-Tension.

INOSXE7010 **Project must be rebuilt before packing. Reason: 'reason'.**

Explanation The project must be rebuilt. See 'reason' for more information.

Action Call Build / Build <project name> in the Developer Studio before packing.

INOSXE7014 **Main class file cannot be removed**

Explanation In the Packaging Dialogue of the X-Tension Builder, the class file is about to be removed that contains the main class of the current server extension.

Action Do not remove this class file from the list or select a jar file containing this class.

INOSXE7015 **Callback not allowed in event function**

Explanation From Tamino server event functions, XML and ODBC callback are not allowed.

Action Remove the callback call from your server extension code.

INOSXE7016 **Illegal database command in callback**

Explanation A database command that is not allowed in callbacks was called in a callback.

Action Remove the database command from the callback and try again.

INOSXE7017	**Tamino server error when calling callback**
Explanation	An error occurred in the Tamino server when processing the callback, perhaps an XML or query syntax error.
Action	Method SXJBase.SXSGetInoMsgNo ( ) gives the error code of the Tamino server.

INOSXE7018	**Not enough memory for callback**
Explanation	The Tamino server could not allocate enough memory to process the callback.
Action	Try to repeat your query when the Tamino server is less loaded.

INOSXE7019	**SQL error when calling ODBC callback**
Explanation	An SQL error occurred while processing an ODBC callback, perhaps due to an SQL syntax error.
Action	Method SXJBase.SXSGetSQLMsgNo ( ) gives the SQL error code.

INOSXE7020	**Illegal handle type for ODBC callback**
Explanation	The ODBC callback methods SxsSQLAllocHandle and SxsSQLFreeHandle are only allowed for statement handles of type SQL_HANDLE_STMT.
Action	We recommend that you use the constant SXJBase.SQL_HANDLE_STMT as the parameter handle type.

INOSXE7021	**Commit and rollback are not allowed in callbacks**
Explanation	You must not use the database commands "commit" or "rollback" in your server extensions.
Action	Remove these commands from the server extension and try again.

INOSXE7022	**Result buffer for callback not initialized**
Explanation	Result buffers for callbacks must not be null, but should be initialized with an empty string.
Action	Ensure that all result buffers are initialized.

INOSXE7023	**Function 'name' failed, because XML callback failed with error 'no'**
Explanation	An XML callback failed while trying to perform a write operation. To avoid inconsistencies, the extension function must return with an error.
Action	Check the error caused by the XML callback and fix the problem that caused it to fail.

INOSXE7024 **COM error when calling callback**

Explanation A COM error occurred during a callback.

Action Consult your COM documentation.

INOSXE7025 **Another server extension deinstallation is running**

Explanation Only one server extension can be deinstalled at any given time.

Action Wait until the other deinstallation procedure has finished.

INOSXE7026 **Deinstallation timed out. The server extension is in use.**

Explanation A server extension cannot be deinstalled as long as an instance of it is in use. The deinstallation procedure has timed out.

Action Try it later. If there is a very long running instance of the server extension, try to stop it.

INOSXE7027 **The function cannot be executed. The server extension is being deinstalled.**

Explanation This function belongs to a server extension that is just being deinstalled.

Action The function cannot not be called again. If you need to, contact the database administrator.

INOSXE7032 **Cannot create directory 'dir'**

Explanation This directory cannot be created. Maybe the disk drive is unavailable or write protected.

Action Check the given path and your disk drive.

INOSXE7034 **Server extension 'source' threw exception 'errnr', 'errtext'**

Explanation The server extension threw an exception. The number and message of the exception are delivered.

Action See the documentation of the server extension in question for more information.

INOSXE7040 **Extension function name too long: 'name'**

Explanation The complete extension function name, consisting of the extension's name plus the function name plus a dot, must not exceed the length of 80 characters.

Action Select a shorter name.

INOSXE7041	**Wrong character in field: 'char'**
Explanation	Some special characters (ampersand, "less than", "greater than") are not allowed in comment fields for a server extension. This affects the "Short description" fields and the "Author" field.
Action	Avoid these characters.

INOSXE7045	**X-Tension Trace failed. Transaction was rolled back.**
Explanation	An internal server error occurred while X-Tension Trace information was written to the Tamino server.
Action	Deactivate X-Tension Trace

INOSXE7046	**XML Callback failed in user session. Transaction must be rolled back.**
Explanation	A writing XML call from a server extension failed. The current transaction should be rolled back for consistency reasons.
Action	Perform a rollback request.

INOSXE7047	**X-Tension Trace failed in user session. Transaction must be rolled back.**
Explanation	An internal server error occurred. The current transaction should be rolled back for consistency reasons.
Action	Deactivate X-Tension Trace

INOSXE7048	**Error starting help browser. Reason: 'reason'.**
Explanation	The currently configured help browser could not be started. See "reason" for more details.
Action	Use the function "Help/Configure Help Browser" to change your current help browser.

INOSXE7049	**'execfile' execution failed: rc = rc**
Explanation	The external program 'Program name' was successfully started but it returned with error.
Action	See the context of this error message for more information.

INOSXE7051	**COM error 'errno' occurred: 'errtext'**
Explanation	A COM error occurred. The COM error number of type HRESULT is delivered.
Action	Consult the COM documentation for more information.

INOSXE7052 **COM error 'errno' calling 'dllname': 'errtext'**

Explanation A COM error occurred. The COM error code of type HRESULT and the name of the Tamino server extension DLL which was called is delivered.

Action Consult the COM documentation for more information.

INOSXE7053 **Error 'errno' calling data map: 'errtext'**

Explanation An error occurred when the Tamino server extension part of the data map was accessed. The error number and message received from the Tamino data map is delivered.

Action Look up the delivered error number and see the action described there.

INOSXE7054 **X-Tension system function cannot be deleted**

Explanation An attempt was made to delete a function which is needed for the X-Tension administration.

Action No action required.

INOSXE7055 **The server extension threw exception 'errtext'.**

Explanation The server extension threw an exception. The message and occasionally the number of the exception are delivered.

Action See the documentation of the server extension in question for more information.

INOSXE7056 **X-Tension caller: Not enough memory**

Explanation There was not enough memory for execution of the server extension function.

Action Close some applications and try again.

INOSXE7057 **X-Tension caller: internal error**

Explanation Internal errors occurred within the X-Tension administration structure.

Action Please contact your software supplier.

INOSXE7058 **X-Tension caller: got no spinlock. Reason: 'retval'.**

Explanation An error occurred within the thread synchronization. A server extension could not be locked. The return value received from the thread administration is delivered.

Action Please contact your software supplier.

INOSXE7059	**X-Tension caller: could not get data map information**
Explanation	The X-Tension caller was unable to get any data map information.
Action	Please contact your software supplier.

INOSXE7060	**Mapping function 'n': Wrong number of parameters implemented. Expected: 'm'.**
Explanation	A Tamino server extension mapping function does not support the number of parameters needed for this function type.
Action	Install a correctly implemented server extension.

INOSXE7061	**Extension function 'n': Wrong type of parameter 'm' implemented**
Explanation	A mapping function does not support the correct parameter types.
Action	Compare the parameter type for this type of extension function as described in the manual with the parameter type supported by the extension function (found using Tamino Manager). Install a correctly implemented extension function.

INOSXE7062	**X-Tension caller: initialization failed**
Explanation	The X-Tension caller was not initialized when the Tamino server was started. It is impossible to call any extension function, maybe because server extension libraries could not be loaded.
Action	Check your Tamino installation.

INOSXE7063	**X-Tension caller: 'No' server event calls failed**
Explanation	A server event call to some server extensions failed. The number of failures is delivered.
Action	Please contact your software supplier.

INOSXE7064	**Unexpected end of file encountered before end of source**
Explanation	During the parsing of the X-Tension installation file, IDL file or one of the server extension source files, an unexpected end of file was found.
Action	Check the syntax of the file(s).

INOSXE7065	**Syntax error. Token: 'Token'.**
Explanation	An unspecified error was encountered during parsing near or at the place specified by 'Token'.
Action	Check the syntax of the X-Tension installation file.

INOSXE7066 **Unbalanced tag / end tag: 'tag1' /' tag2'**

Explanation In the X-Tension installation file, the names of begin-tag and end-tag are different.

Action Check the syntax of the X-Tension installation file.

INOSXE7067 **Tag 'tagname' not found**

Explanation The specified mandatory tag was not found in the X-Tension installation file.

Action Check the syntax of the X-Tension installation file.

INOSXE7068 **Tag 'tagname' is not a value**

Explanation A simple value was expected for the specified tag, but a node has been found.

Action Check the syntax of the X-Tension installation file.

INOSXE7069 **Tag 'tagname' is not a node**

Explanation A node was expected for the specified tag, but a simple value has been found.

Action Check the syntax of the X-Tension installation file.

INOSXE7070 **Duplicate name: 'name'**

Explanation The specified tag name was found twice in the X-Tension installation file.

Action Check the syntax of the X-Tension installation file.

INOSXE7071 **Error 'character' expected**

Explanation The specified character was expected but not found in the X-Tension installation file or one of the server extension source files.

Action Check the syntax of the X-Tension installation file and the server extension source files.

INOSXE7072 **Error 'character' expected, eof found**

Explanation The specified character was expected, but an end of file was found in the X-Tension installation file or one of the server extension source files.

Action Check the syntax of the X-Tension installation file and the server extension source files.

INOSXE7073 **IDL file 'segment name' is corrupt**

Explanation A syntax error was found in the IDL file for the definition of the server extension interface at or near the specified keyword.

Action Check the syntax of the IDL file.

INOSXE7074 **'SXF' not defined in interface**

Explanation The specified function has been defined in the X-Tension installation file but it had not been entered into the IDL file for the server extension interface.

Action Remove the function definition from the X-Tension installation file and use the X-Tension Developer Studio add-in to define a new one.

INOSXE7075 **Return type must be HRESULT, not 'type'**

Explanation A COM server extension must always return HRESULT.

Action Use the [retval] attribute for the last parameter as a return value of the server extension function.

INOSXE7076 **Method 'method': Different parameter names: 'param1' / 'param2'**

Explanation The parameter name of the indicated server extension function in the X-Tension installation file is different from that defined in the IDL file.

Action Check the implementation of the server extension function; use the X-Tension Developer Studio add-in to define a server extension function.

INOSXE7077 **Too many parameters: 'SXF'**

Explanation The specified server extension function has been implemented with more parameters than are defined in the X-Tension installation file.

Action Check the implementation of the server extension function; use the X-Tension Developer Studio add-in to define a server extension function.

INOSXE7078 **Cannot map parameter type**

Explanation A parameter type is used in the COM interface that cannot be used for server extension function parameters.

Action Use the X-Tension Developer Studio add-in to define a server extension function.

INOSXE7079 **Server extension implementation file could not be found**

Explanation The X-Tension Developer Studio add-in could not find the file with the implementation of the class for the server extension.

Action Use the X-Tension development tool to create a server extension.

INOSXE7080 **Unknown XML data type: 'type'**

Explanation The specification of the XML data type for a server extension function parameter is wrong. See the documentation for allowed data types.

Action Use the X-Tension Developer Studio add-in to define a new server extension function.

INOSXE7081 **Unknown programming language data type: 'type'**

Explanation The function implementation uses a data type for one of its parameters that is not supported when using this function as a server extension function. See the documentation for the allowed data types in this programming language

Action Use the X-Tension development tools to define a server extension function.

INOSXE7082 **Unknown execution mode: 'mode'**

Explanation The specified server extension execution mode is wrong. Allowed modes are: COM-INPROC, COM-LOCAL.

Action Use the Tamino Manager to change this mode.

INOSXE7083 **Wrong numeric value: 'val'**

Explanation The value was expected to be numeric but the given value is not numeric.

Action Enter a numeric value here.

INOSXE7084 **Wrong parameter position**

Explanation The parameter position in the X-Tension installation file must start at 1.

Action Check the parameter position values. Use X-Tension Developer Studio add-in to define a new server extension function.

INOSXE7085 **Cannot open file 'name'**

Explanation The specified file could not be opened.

Action Check if this file really exists, or if it is locked by another process.

INOSXE7086	**Wrong version format: 'string'**
Explanation	The server extension version is supposed to be of the form major.minor
Action	Check the server extension version.

INOSXE7087	**Event function 'function' not found**
Explanation	An event function has been specified in the SXS-EVENT-FUNCTION tag of the X-Tension installation file, but it could not be found in an SXS-FUNCTION tag.
Action	Delete the event function specification tag and use the X-Tension Developer Studio add-in to specify a new one.

INOSXE7088	**Wrong document type for X-Tension administration: 'type'**
Explanation	The document type (second level tag) of the X-Tension administration file is wrong. Allowed types are: SXS-INSTALL, SXS-DELETE, SXS-SHOW, SXS-RETURN.
Action	For a server extension installation, only SXS-INSTALL is valid.

INOSXE7089	**Missing XML attribute 'attribute' for SXS-SHOW**
Explanation	No attribute is given for the X-Tension administration type tag SXS-SHOW.
Action	One of the attributes list, object, function, permission, document must be given for the SXS-SHOW tag.

INOSXE7090	**Wrong XML attribute: 'attribute'**
Explanation	A wrong attribute is given for the X-Tension administration type tag SXS-SHOW.
Action	One of the attributes list, object, function, permission, document must be given for the SXS-SHOW tag.

INOSXE7091	**Wrong parameter attribute: 'attribute'**
Explanation	A wrong parameter attribute has been specified in the X-Tension installation file. Allowed attributes are: input, output, inout, retval.
Action	Use the X-Tension Developer Studio add-in to define a new server extension function.

INOSXE7092	**No current project**
Explanation	There is no project open in Developer Studio. The X-Tension add-in will not work.
Action	Open a server extension project first.

INOSXE7093 **This is not a C/C++ project**

Explanation The X-Tension add-in will not work for Java or Visual Basic projects.

Action Open a C/C++ project.

INOSXE7094 **This is not an X-Tension project**

Explanation The current project has not been created by an X-Tension development tool.

Action Use the X-Tension development tool to create a server extension.

INOSXE7095 **File 'filename' is read-only**

Explanation The specified file is read-only. Therefore, the X-Tension Developer Studio add-in cannot add the specifications for the new server extension function to it.

Action Change the ReadOnly parameter of the specified file.

INOSXE7096 **System error: 'errtext'**

Explanation An operating system error occurred in the X-Tension Developer Studio add-in.

Action Check the operating system documentation for further details.

INOSXE7099 **Cannot write to file 'filename'**

Explanation The file has been opened, but a write operation failed. Possibly the disk is full.

Action Check your hard disk space.

INOSXE7100 **Wrong package file: 'filename'**

Explanation The file specified is not an output file of the X-Tension Developer Studio add-in package function.

Action Only use package files created by the X-Tension Developer Studio add-in.

INOSXE7101 **Could not get XML session status. Server extension function rolled back at request end.**

Explanation The X-Tension caller could not determine whether there was a regular or an anonymous XML session. So the Tamino server event 'rollback' was sent to all server extensions.

Action No action required.

INOSXE7102 **Initialization of server extensions: server events not activated**

Explanation The Tamino server events could not be activated when the Tamino server was started. Server extensions are not initialized and will not work.

Action Restart the Tamino server. If this does not give the desired result, please contact your software supplier.

INOSXE7103 **Developer Studio automation error 'errno' (errtext)**

Explanation The add-in caused an error when executing a Developer Studio command.

Action Consult the Developer Studio documentation for further information.

INOSXE7104 **Method 'method' could not be found in file 'objfile'**

Explanation The method indicated is not defined in the current server extension object file (Java class file or DLL/Shared Object), or another severe error occurred when accessing the server extension object file.

Action Check the server extension project for the desired method.

Use the X-Tension development tools for developing server extensions!

INOSXE7105 **Project must be rebuilt before packing: 'file' is newer**

Explanation One of the project sources is newer than the resulting server extension package.

Action Call Build / Build <project name> in the Developer Studio before packing.

INOSXE7106 **One or more input fields are empty**

Explanation All fields of this form must be set, but at least one field is empty.

Action Make sure that all fields are correctly set.

INOSXE7107 **'name' is not a valid identifier**

Explanation The name entered does not match C/C++ naming conventions.

Action Check the name for proper syntax.

INOSXE7108 **Value for 'valuename' of a server extension not found in data map**

Explanation A value for the specified name of a server extension was expected in the data map but is not present. The problem occurs due to problems at installation or in the repository. Here, the specified name is the name of an expected value.

Action Re-install the server extension.

INOSXE7109 **Memory allocation failed**

Explanation Memory allocation failed.

Action Please contact your software supplier.

INOSXE7110 **Character conversion failed; error code = 'errcode'**

Explanation An internal character conversion failed.

Action See the Tamino documentation for the given error code. Check if Tamino is properly installed.

INOSXE7113 **Cannot find function 'funcname' in library 'libname'**

Explanation The specified function name could not be found in the library. Maybe there is a version problem.

Action Check your Tamino installation.

INOSXE7114 **Java error: Errtext: 'errtext'. Stacktrace: 'trace'.**

Explanation A Java error occurred. See "Errtext" for more specific details. "Stacktrace" is the exception stack trace.

Action See "Errtext" for more specific details and correct the code accordingly.

INOSXE7115 **Cannot create Java virtual machine; error 'errcode'**

Explanation The Java virtual machine could not be started.

Action Check the Java documentation for the given error code.

INOSXE7116 **Function 'sxfname' not found in server extension 'sxsname'**

Explanation The function could not be found in the server extension. Probably the server extension implementation has been changed after installation.

Action Try to re-install the server extension.

INOSXE7117 **Illegal call for Java method 'methodname' in class 'classname'**

Explanation An error occurred during a call for a Java method. Probably the parameter count or the type(s) of at least one parameter is incorrect. For a server extension function, its implementation may have changed since the last installation.

Action Re-install this server extension.

INOSXE7118 **'package' not available on this platform**

Explanation The package specified (COM, Java or Direct) is not available on this platform. Server extensions based on this package cannot be executed.

Action No action possible. This server extension cannot be run.

INOSXE7119 **'package' not installed on this platform**

Explanation The package specified (COM or Java) is not installed on this platform.

Action To run server extensions based on this package, install the specified package.

INOSXE7120 **X-Tension caller: parameter overflow, function 'name' parameter number 'no'**

Explanation The input value was too small or too big.

Action Change the input value and try again.

INOSXE7121 **XQL query function 'n': Wrong number of parameters. Required: 'm'.**

Explanation The user passed a wrong number of parameters to a function called from within an XQL query.

Action Repeat the call with the correct number of parameters.

INOSXE7122 **XQL query function 'n': Wrong type of parameter 'm'**

Explanation The user input is of the wrong data type.

Action Get information about parameter types of called functions (see the Tamino Manager or the third party manual for the corresponding server extension) and repeat the call with the correct input.

INOSXE7123 **Java error during initialization of Java server extension: 'errtext'**

Explanation The error text gives detailed information about the error.

Action Correct the fault and try again.

INOSXE7124 **Java error during call: 'errtext'**

Explanation The error text gives detailed information about the error.

Action Correct the fault and try again.

INOSXE7125 **Java error during server extension function parameter handling: 'errtext'**

Explanation The error text gives detailed information about the error.

Action Correct the fault and try again.

INOSXE7126 **Server extension failed**

Explanation An error occurred when a Tamino server extension was called. The message is followed by another more detailed message.

Action Analyze the detailed message and act accordingly.

INOSXE7127 **X-Tension : Java initialization failed**

Explanation During X-Tension initialization the initialization of the Java virtual machine failed. No Java-based extension functions are available during this server session.

Action If Java-based server extension functions are required, fix the Java problem (e.g. paths and internal configuration store entries) and start the Tamino server again.

INOSXE7129 **'location': Got no spinlock. Reason: 'retval'.**

Explanation There is no lock available for your thread.

Action Try again later.

INOSXE7130 **Internal error when 'location'**

Explanation An unknown internal error occurred.

Action Please contact your software supplier.

INOSXE7132 **'unusedinfrastructur' infrastructure is not available or currently disabled**

Explanation The X-Tension infrastructure specified is either not available in this environment or is currently configured as disabled in the Tamino server parameters.

Action If the required infrastructure is available in this environment, turn on the appropriate switch of the Tamino server parameters and restart the Tamino server to activate it. If the infrastructure is not available, the relevant server extension code attempting to use it should be modified to utilise a supported infrastructure.

INOSXE7136 **Wrong command line for the server extension wrapper tool: 'arg'**

Explanation The command line for the server extension wrapper tool has incorrect syntax.

Action Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.

INOSXE7137 **Duplicate option 'c'**

Explanation The given option may not occur more than once in the command line for the server extension wrapper tool.

Action Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.

INOSXE7138 **Wrong option 'c'**

Explanation The given option is invalid in the command line for the server extension wrapper tool.

Action Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.

INOSXE7140 **No valid JVM, install valid JVM or switch X-Tension Java Usage to 'NO'**

Explanation Error detected when loading a JVM for current Tamino version

Action Check if JVM is installed, if a valid JVM Version is installed or switch X-Tension Java Usage to 'NO'.

INOSXE7141 **Server extension 'name' already locked**

Explanation The server extension is locked by another operation.

Action Retry the requested operation when the lock has been removed.

INOSXE7142 **Server extension 'name' is active**

Explanation The server extension is in use.

Action Retry the requested operation when the server extension has finished.

INOSXE7143 **Server extension 'name' not found**

Explanation The server extension does not exist.

Action Correct the server extension name and retry the operation.

INOSXE7144 **Server extension function 'name' not found**

Explanation The server extension function does not exist.

Action Correct the function name and retry the operation.

INOSXE7145 **Wrong modification operation 'type'**

Explanation The requested modification operation is not implemented.

Action Correct the modification operation type and retry the operation.

INOSXE7146 **Wrong execution mode 'mode'**

Explanation The requested execution mode is not allowed.

Action Correct the execution mode and retry the operation.

INOSXE7147 **Files for server extension 'name' not restored**

Explanation Some files of the server extension have not been restored.

Action Ensure that the Tamino server has write access to the file system and retry the operation.

INOSXE7148 **Files for server extension 'name' not removed**

Explanation Some files of the server extension have not been removed.

Action Ensure that the files are not locked by another action and retry the operation.

INOSXE7149 **Files for server extension 'name' not stored**

Explanation Some files of the server extension have not been stored.

Action Ensure that the files are not locked by another action and retry the operation.

INOSXE7150 **Installation document for server extension 'name' not stored**

Explanation The installation document of the server extension has not been stored.

Action Ensure that the installation document is not locked by another action and retry the operation.

INOSXE7151 **Event Function call failed for server extension: a, Event: b**

Explanation Event functions are for cleaning up server extension data after commit, rollback, session end and so on. See the X-Tension manual (server extension Functions/Server Event Functions), for information about which event failed.

Action Analyze the cause of failure. If necessary, ask the programmer or vendor of the server extension. Check the data that was written outside the Tamino server by the failed extension for consistency.

INOSXE7152 **Attribute 'hidden' cannot be assigned to or removed from this parameter**

Explanation An attempt was made to assign or remove the 'hidden' attribute. This operation is only successful if the parameter has the 'input' direction (for assignment) or the parameter is 'hidden' (for removal).

Action Check the server extension function and its parameters and read the documentation.

INOSXE7153 **This parameter cannot be assigned a default value**

Explanation To assign a default value to a parameter, this parameter must have the 'input' direction.

Action Check the current server extension function and its parameters.

INOSXE7154 **Wrong position for optional / hidden parameter**

Explanation The order for parameters must be: mandatory - optional - hidden - return value.

Action Please check the order of the server extension function's parameters and their usage.

INOSXE7158 **Server extension function parameter 'name' not found**

Explanation The server extension function parameter does not exist.

Action Correct the parameter name and retry the operation.

INOSXE7160 **Duplicate occurrence of 'functiontype'**

Explanation Only one event function or init function may be defined within a server extension.

Action Check your server extension and delete one of the functions that is superfluous, or use the X-Tension development tools to create and edit the server extension.

INOSXE7161 **Invalid input for field: field**

Explanation The user input for the specified field is invalid. Either invalid characters have been used or the format of the characters used is incorrect.

Action Please correct the specified field.

INOSXE7162 **Document not found for specified ino:id/docname**

Explanation A document could not be found using the specified ino:id or docname.

Action Please specify a valid ino:id or docname.

INOSXE7255 **Java Exception**

Explanation Specified Java exception occurred

Action Resolve the specified Java exception

INOSXF6718 **Timeout during execution of server extension function**

Explanation Possible reasons are: 1) There is an endless loop in the server extension function. 2) A server extension function is executed with endless recursion.

Action Check the server extension carefully. For example, calling the callback SxsXmlProcess will result in an endless recursion if the collection name is the same as the current server extension function is assigned to.

INOSXF6719 **Process 'exefile' (for Direct Local) has stopped with rc = rc**

Explanation The external process for X-Tension direct infrastructure (local mode) has aborted. See error for more details.

Action Check your server extension. Probably it killed the external process for local mode.

INOSXF6720 **Stack overflow in server extension function**

Explanation A stack overflow occurred during call of a server extension function.

Action Check your server extension. Perhaps it has endless recursion.

INOSXF7028 **Illegal call of Connect/Disconnect**

Explanation This error may occur in a Visual Basic or Natural implementation of a server extension. Reasons for this error may be: The Connect and Disconnect methods of the InoCallback interface have been called outside ISXSConn_Connect or ISXSConn_Disconnect or have been called there more than once.

Action Implement ISXSConn_Connect and ISXSConn_Disconnect exactly as shown in the documentation. Do not call the Connect and Disconnect methods of InoCallback outside ISXSConn_Connect and ISXSConn_Disconnect.

INOSXF7030 **'tool' does not support server extensions of type 'type'**

Explanation The X-Tension Builder tried to open a COM server extension.

Action With the X-Tension Builder, open Java or Direct server extensions only.

INOSXF7033 **Server extension 'sxsname' not properly installed. Reason: 'reason'.**

Explanation One or more installation steps for this server extension have been skipped or failed. See 'Reason' for more information.

Action Use the X-Tension Administration of the Tamino Manager to install the server extension.

INOSXF7035 **Cannot load library sxcall**

Explanation The library sxcall necessary for Tamino X-Tension cannot be loaded. Therefore no server extensions can be executed in this Tamino installation.

Action Check your Tamino installation.

INOSXF7036 **Cannot load a function in library sxcall**

Explanation Not all functions necessary to run Tamino X-Tension can be found in library sxcall. Therefore no server extensions can be executed in this Tamino installation. Probably there is a version mismatch between the library sxcall and the rest of Tamino.

Action Check your Tamino installation.

INOSXF7037 **Internal configuration store entry not found**

Explanation An internal configuration store entry necessary to initialize Tamino X-Tension or one of the Tamino X-Tension components cannot be found. If this error occurs during Tamino startup, no server extensions can be executed in this Tamino installation.

Action Check your Tamino installation.

INOSXF7038 **Cannot find current version in internal configuration store**

Explanation The 'current version' entry in the internal configuration store that is necessary to initialize Tamino X-Tension or one of the Tamino X-Tension components cannot be found. If this error occurs during Tamino startup, no server extensions can be executed in this Tamino installation.

Action Check your Tamino installation.

INOSXF7039 **Cannot load jvm library**

Explanation The jvm library (libraries) necessary to run Java server extensions cannot be loaded. Therefore no server extensions can be executed in this Tamino installation.

Action Check your Tamino installation as well as your Java installation. Look if $LD_LIBRARY_PATH on UNIX (or %PATH% on Windows) includes all required JDK directories.

INOSXF7042 **Cannot find executable file 'execfile'**

Explanation The indicated file could not be found in any of the directories listed in PATH.

Action Check installation(s) on your computer and check your PATH setting.

INOSXF7043 **Tamino X-Tension not properly installed. Reason: 'reason'.**

Explanation The X-Tension development tool cannot create a new server extension project because Tamino X-Tension component is not properly installed on your computer.

Action Use the Install Tool for a correct installation of Tamino X-Tension.

INOSXF7044 **Error calling 'execfile'. Reason: 'reason'.**

Explanation An error occurred while trying to start an external process with the indicated file. See the additional text for more details.

Action Check the given file for correctness.

INOSXF7097 **Tamino X-Tension not properly installed**

Explanation The X-Tension development tool cannot create a new server extension project because Tamino X-Tension component is not properly installed on your computer.

Action Use the Install Tool for a correct installation of Tamino X-Tension.

INOSXF7098 **Fatal error**

Explanation An unspecified error occurred.

Action Please contact your software supplier.

INOSXF7111 **Server extension 'sxsname' not properly installed**

Explanation One or more installation steps for this server extension have been skipped or failed.

Action Use the X-Tension Administration of the Tamino Manager to install a server extension.

INOSXF7112 **Cannot load library 'libname': error 'rc'**

Explanation The specified library could not be loaded. Maybe it has been moved from its original location, or environment variables or internal configuration store entries have been changed since the last Tamino installation.

Action Check your PATH and your Tamino installation.

INOSXF7133 **No class has been found that can be used as a direct server extension class.**

Explanation Either there is no class defined in the given header file or none of the classes defined here can be used as a direct server extension.

Action Please check the documentation about requirements for direct Server Extension classes or use the X-Tension development tools to create a Server Extension.

INOSXF7134 **There are at least two classes ('class1', 'class2') that can be used as direct server extensions**

Explanation A header file that should be processed by the direct server extension wrapper tool may define only one class that can be used as a direct server extension.

Action Please check the documentation on how to mark C++ classes for use as direct server extensions or move all class definitions except the direct server extension class to a different header file.

INOSXF7155 **Internal error: 'id'**

Explanation A severe internal error occurred.

Action Please note the value of the internal error and contact your software supplier.

INOSXF7156 **Cannot start process 'exefile' for X-Tension direct infrastructure (local mode)**

Explanation The system cannot start a new process for X-Tension direct infrastructure (local mode).

Action Check the existence of the file indicated. It should be located in directory Tamino/<version>/bin.

INOSXF7157 **Process 'exefile' (for Direct Local) is not running**

Explanation The external process for X-Tension direct infrastructure (local mode) has aborted or is not running for other reason.

Action Check your server extension. Perhaps it killed the external process for local mode.

INOSXF7251 **Thread could not be attached to JVM, return code 'rc'**

Explanation The current XML worker thread could not be attached to the Java virtual machine. Tamino server extensions were not initialized. The return code is the return value of the JNI call "AttachCurrentThread()".

Action Analyze why the Java call failed and solve the cause of the problem. Then start Tamino server again.

INOSXF7252 **Metadata update failed: id**

Explanation Metadata update has failed.

Action In the case of CentraSite database startup failure indicated by the production of the console message: "INOSXF7252: Metadata update failed" the following information is essential to analyse the problem.

The most useful file in these circumstances is the "inosrv.txt" file. This is normally called something like AABinosrv.HH-MM-SS.txt and would normally be present in the same directory as the actual database data files.

inoadmin set CentraSite "request log" "full" norestart

inoadmin set CentraSite "X-Tension Java Options" "$-Dlog4j.configuration=file:/{full path to log4j.properties}" restart

log4j.rootLogger=WARN, file

log4j.logger.com.centrasite.centrasite.onstartup=DEBUG

log4j.appender.file=org.apache.log4j.FileAppender

log4j.appender.file.layout=org.apache.log4j.PatternLayout

log4j.appender.file.layout.ConversionPattern=%d %8r [%t]%-5p %c{3} %x - %m%n

log4j.appender.file.File={full path to log file}

INOSXI6708 **X-Tension usage is currently disabled**

Explanation All of the X-Tension infrastructures (COM, Java and Direct) are currently disabled.

Action Turn on the appropriate switch of the Tamino server parameters and restart the Tamino server.

INOSXI6723 **JVM started with user options '*jvm_options*'**

Explanation The JVM was started with the specified additional user options.

Action No action required.

INOSXI7029 **Finished searching the file**

Explanation The 'Find What' string has not been found after (Direction *Down*) or before (Direction *Up*) the current position.

Action Deselect 'Match case' or select another string.

INOSXI7050 **COM for server extension is deactivated**

Explanation COM for server extension is switched off.

Action Switch on COM for server extension with Tamino Manager.

INOSXI7128 **Java for server extension is deactivated**

Explanation Java for server extensions is switched off

Action Switch on Java for server extension with the Tamino Manager

INOSXI7131 **X-Tension 'unusedinfrastructur' usage is currently disabled**

Explanation The specified X-Tension infrastructure (COM, Java or Direct) is currently disabled.

Action Turn on the appropriate switch of the Tamino server parameters and restart the Tamino server.

INOSXI7253 **Metadata update succeeded: id**

Explanation Metadata update has finished successfully.

Action None

INOSXI7254 **Metadata update started.**

Explanation Metadata update has started. This may be a lengthy operation.

Action None.

INOSXV6726 **COM server extensions are deprecated**

Explanation COM server extensions are deprecated and will not be supported in future.

Action Plan the replacement of your COM server extensions by using a different server extension infrastructure.

INOSXW6700 **'function' can no longer be used as 'functype'**

Explanation One of the parameters has been modified or deleted. Therefore this server extension function can no longer be used as the specified function type.

Action Check the Tamino server extension documentation for the different function types.

INOSXW6701 **At least one of the help files does not exist. It will be removed from the list.**

Explanation The Install.xml file for your current X-Tension project has an entry for a help file that no longer exists. It will be removed from your list of help files.

Action Select a new file.

INOSXW6702 **Warning: Settings for compiler 'compiler' already exist and will be overwritten**

Explanation Compiler and linker flags already exist for the compiler specified in this warning. Choosing 'OK' will overwrite these settings.

Action Choose 'OK' to overwrite these settings or 'Cancel' to stop this action.

INOSXW6703 **The path 'path' will be added to the list of executable files of Visual Studio**

Explanation Some libraries residing in Tamino system directories are needed to build a server extension. These directories must be listed in the "Executable files" section of your Visual Studio configuration. If not yet present, sxwizard will add these directories automatically.

Action Click on OK to accept these changes to your Visual Studio configuration. If you click on Cancel, no changes will be made and sxwizard will be stopped.

INOSXW6721 **Project will be moved from platform 'platform1' to 'platform2'**

Explanation This (SXS Direct) project has been created on platform1. It is now opened on a different platform platform2, and a new make file will be created such that it can be compiled on this new platform.

Action Click OK to generate a new make file, or click cancel if you do not want to have a new make file created. However, this project probably cannot be compiled on this platform.

INOSXW6722 **Project will be moved from an older Tamino version to platform 'platform'**

Explanation This (SXS Direct) project has been created by an older version of Tamino. It is now opened by a newer Tamino version on a different platform. A new make file will be created such that it can be compiled in this version and on this new platform.

Action Click OK to generate a new make file, or click cancel if you do not want to have a new make file created. However, this project probably cannot be compiled in this Tamino version.

INOSXW6724 **Unable to start JVM with user options 'jvm_options'. Starting with default options instead.**

Explanation Conflicting or incorrect user options were specified for the JVM, so the JVM could not start. The JVM will be started with the default options.

Action Correct the user options specified for the JVM and restart the server.

INOSXW6727 **The server extension generated a warning.**

Explanation The server extension has invoked the warning XML callback. This will insert a warning into the Tamino response.

Action The warning message is for informational purposes.

INOSXW6728 **Execution failed: command**

Explanation The specified operating system command failed.

Action Check the SXS installation values for faults.

INOSXW7002 **Existing server extension project at 'pathname' will be overwritten**

Explanation A server extension project already exists in the given directory. It will be overwritten if you select "Finish".

Action Press "OK" to overwrite this project or select another directory.

INOSXW7003 **Java initialization failed. Reason: 'errno', 'errtxt'.**

Explanation Tamino was not able to create a Java virtual machine. Java based server extensions will not work.

Action Make the Java virtual machine available to Tamino and start the Tamino server again or switch the server property X-Tension Java Usage to 'NO'.

INOSXW7004 **Java thread initialization failed. Reason: 'errno', 'errtxt'.**

Explanation An XML worker thread could not be attached to the Java virtual machine. Java based server extensions will not work.

Action Fix the problem of Java initialization and start the Tamino server again.

INOSXW7005 **Initialization of COM library failed. Reason: 'errno', 'errtxt'.**

Explanation COM based server extensions will not work.

Action Make the COM library available to the Tamino server, then start it again.

INOSXW7007 **No license for Tamino X-Tension**

Explanation A special license must be bought to use the Tamino X-Tension feature.

Action Buy a license for Tamino X-Tension.

INOSXW7008 **Tamino X-Tension not available**

Explanation On this platform the Tamino X-Tension feature is not available.

Action No action required.

INOSXW7011 **This will remove all previously selected files from your package list**

Explanation For a server extension package, either one or more class files or ONE jar file can be used. This warning shows up in one of the following cases: 1) A jar file was selected and a class file will be added to the class file list: The jar file will be removed from the list. 2) One or more class files or another jar file were selected, and a jar file will be added: All recently selected files will be removed.

Action Choose "OK" to confirm or "Cancel" to cancel the current selection

INOSXW7012 **Main Class File for server extension missing**

Explanation For a server extension package, either one or more class files or ONE jar file can be used. This warning shows up when none of the selected class files contains the main class of the server extension.

Action Add another class file that contains the main class of the server extension.

INOSXW7013 **Server extension might not run without these class(es)**

Explanation In the Packaging Dialogue of the X-Tension Builder, one of the selected class files is about to be removed. Without this class file the installation of this server extension will be incomplete.

Action Check if this class file is really unnecessary for the current server extension.

INOSXW7031 **Directory 'dir' does not exist and will be created**

Explanation This directory does not exist and will be created.

Action Select "OK" to create this directory, select "Cancel" to cancel project creation.

INOSXW7135 **The given class contains no server extension function**

Explanation The given class does not contain any method that can be used as a server extension function.

Action Enter some methods using the direct server extension development tools.

INOSXW7139 **No valid JVM, install valid JVM or switch X-Tension Java Usage to 'NO'**

Explanation Error detected when loading a JVM for current Tamino version

Action Check if JVM is installed, if a valid JVM Version is installed or switch X-Tension Java Usage to 'NO'.

INOSXW7159 **Value will be set to empty string**

Explanation A default value or configuration parameter (Init Function) may be set to empty string if data type is charstring.

Action Please check if in this special case this effect is intended.

INOX2E8000 **Usage of distributed transaction processing is not supported on this platform**

Explanation It is not possible to use distributed transaction processing features on the Tamino server platform.

Action None - the platform does not support distributed transaction processing.

INOX2E8001 **Conversion of the distributed transaction processing transaction identifier was not possible**

Explanation The transaction identifier provided does not have a defined method to convert it to the internal format.

Action Contract your software supplier - this is a software error.

INOX2E8002 **An internal error occurred dealing with the transaction identifier in distributed transaction**

Explanation The transaction identifier caused an internal error when being processed.

Action Contract your software supplier - this is a software error.

INOX2E8003 **Server encountered an error while performing a distributed transaction processing action**

Explanation A distributed transaction processing action resulted in the server not being able to complete the action requested.

Action Contract your software supplier - this is a software error.

INOX2E8004 **The specified distributed transaction processing identifier is unknown by the server**

Explanation A transaction identifier was specified which is unknown to the server. This can happen if a timeout occurred or if the transaction has not been prepared before a server restart.

Action This message will be given back by the server to the transaction manager.

INOX2E8005 **An invalid argument was detected on a distributed transaction processing call**

Explanation An argument supplied by the transaction manager was invalid.

Action This message will be given back by the server to the transaction manager.

INOX2E8006 **Protocol error - an action requested by the transaction manager was invoked in an improper context**

Explanation The specified action cannot be carried out in the current distributed transaction state.

Action This message will be given back by the server to the transaction manager.

INOX2E8007 **An error has occurred which makes server unavailable to process the transaction manager's action**

Explanation The action requested by the transaction manager cannot be fulfilled by Tamino currently.

Action This message will be given back by the server to the transaction manager.

INOX2E8008 **Duplicate distributed transaction identifier encounter while enlisting in a distributed transaction**

Explanation A duplicate transaction identifier was encountered while enlisting in a distributed transaction.

Action This is an internal error and should be reported to your software supplier.

INOX2E8010 **The specified distributed transaction has been rollback**

Explanation The server has decided that this distributed transaction can only be rolled back.

Action This message is a reply to a transaction manager request.

INOX2E8011 **A communications error has occurred**

Explanation A communications error occurred while attempting a distributed transaction processing action sent by the transaction manager.

Action This message is a reply to a transaction manager request.

INOX2E8012	**The server has detected a deadlock involving the specified distributed transaction**
Explanation	A deadlock has been detected for the specified distributed transaction. The transaction has been rolled back.
Action	This message is a reply to a transaction manager request.

INOX2E8013	**The server has detected an integrity violation for the resources requested by the specified distributed transaction**
Explanation	An integrity violation has been detected for the specified distributed transaction. The transaction has been rolled back.
Action	This message is a reply to a transaction manager request

INOX2E8014	**The server has detected an unspecified error for the specified distributed transaction**
Explanation	An unspecified has been detected for the specified distributed transaction. The transaction has been rolled back.
Action	This message is a reply to a transaction manager request

INOX2E8015	**The server has detected an internal protocol error for the specified distributed transaction**
Explanation	An internal protocol error has been detected for the specified distributed transaction.
Action	This message is a reply to a transaction manager request.

INOX2E8016	**The server has timed out the specified distributed transaction**
Explanation	The server timed out the specified distributed transaction.
Action	This message is a reply to a transaction manager request.

INOX2E8017	**The server has detected a transient error for the specified distributed transaction**
Explanation	The server has detected a transient error for the specified distributed transaction.
Action	This message is a reply to a transaction manager request.

INOX2E8018	**The server has heuristically committed the specified distributed transaction**
Explanation	The server had to heuristically commit the specified distributed transaction.
Action	This message is reply to a transaction manager request.

INOX2E8019 **The server has heuristically rolled back the specified distributed transaction**

Explanation The server had to heuristically roll back the specified distributed transaction.

Action This is message is reply to a transaction manager request.

INOX2E8020 **The server has heuristically completed the distributed transaction. The outcome of the transaction is mixed.**

Explanation The server had to heuristically complete the specified distributed transaction. The outcome is however mixed; this means that part of the transaction was committed and the rest was rolled back.

Action This message is a reply to a transaction manager request.

INOX2E8021 **The specified distributed transaction is read-only**

Explanation There were no modifications made to the server by the specified distributed transaction and therefore the server does not need to receive the commit action from the transaction manager.

Action This message is a reply to a transaction manager request.

INOX2E8022 **An error occurred while issuing a call to the transaction manager**

Explanation The transaction manager rejected a request made by Tamino.

Action See the extended error messages for the transaction manager's reason for rejecting the call.

INOX2E8023 **The command is not allowed while a distributed transaction is active within this session**

Explanation An attempt was made to issue either a _DISCONNECT command before the completion of the distributed transaction or a _COMMIT/_ROLLBACK command in the distributed transaction. These are not allowed.

Action Complete the two phase commit transaction before issuing the _DISCONNECT command.

INOX2E8024 **The current session cannot accept commands while the two phase commit transaction completion protocol is active**

Explanation Issuing Tamino commands to a session that is between phase 1 and phase 2 of a two phase commit transaction completion protocol is not allowed. The two phase commit protocol must complete before the session can be used again.

Action Do not issue commands while the two phase commit transaction completion protocol is active.

INOX2E8025	**The transaction manager specified an invalid recovery action**
Explanation	The request action on recovery was invalid.
Action	This is an error sent to the transaction manager. It is internal and if seen should be reported to your software supplier.

INOX2E8027	**The outcome of a commit was inconsistent**
Explanation	The outcome of a commit was inconsistent: one or more data sources failed to commit.
Action	Check the extended error information for a list of which data sources failed to commit the transaction, then perform appropriate repairs.

INOX2E8028	**The outcome of a rollback was inconsistent**
Explanation	The outcome of a rollback was inconsistent: one or more data sources failed to roll back.
Action	Check the extended error information for a list of which data sources failed to commit the transaction, then perform appropriate repairs.

INOX2E8030	**Invalid transaction token**
Explanation	An invalid transaction token was specified.
Action	Provide a valid transaction token with the correct format.

INOX2E8047	**Recovery of distributed transactions has found outstanding transactions that are not for the current transaction manager**
Explanation	After completion by the transaction manager of recovery for distributed transactions, there are outstanding transactions that do not belong to the transaction manager.
Action	Contact your software supplier for help in resolving the outstanding transactions.

INOX2E8049	**An internal error occurred in the distributed transaction processing components of the server.**
Explanation	An internal error occurred.
Action	This is an internal error. Please contact your software supplier.

INOX2F8026	**Cannot find distributed transaction processing (DTP) library ino2pc**
Explanation	The shared library/DLL ino2pc cannot be found.
Action	This is a software installation configuration problem. Contact Software AG support for help

INOX2I8046	**Distributed transaction transaction_token with resource manager identifier rmid has been manually resolved to the 'state' state**
Explanation	This event is generated when someone manually resolves a distributed transaction.
Action	No action required. This message helps to track the progress of the distributed transaction.

INOX2I8048	**Server start-up detected pending or heuristically complete distributed transactions**
Explanation	On starting the server, it has been detected that there are outstanding distributed transactions. These transactions should normally be resolved by the transaction manager.
Action	Check the transaction manager log to check that all outstanding distributed transactions are resolved. If the transactions are not resolved, then contact your software supplier to get help in resolving them.

INOXCE8100	**Internal error: duplicate root element**
Explanation	Invalid migrated data records with duplicate root elements were detected.
Action	Please contact your software supplier.

INOXCE8102	**Internal error: document stack corrupted**
Explanation	An internal error has occurred.
Action	Please contact your software supplier.

INOXCE8103	**Memory allocation failed**
Explanation	There was not enough main memory available to perform the request.
Action	Possibly the machine is overloaded. Try again later.

INOXCE8104	**Internal error during document composition**
Explanation	An internal error has occurred.
Action	Please contact your software supplier.

INOXCE8105	**Invalid X-Tension response**
Explanation	An X-Tension function returned a string that is not well-formed XML.
Action	Correct the implementation of the X-Tension function

INOXCE8106	**Internal error: unknown request**
Explanation	An internal error occurred.
Action	Please contact your software supplier.

INOXCE8107	**Map to object: illegal document ID encountered.**
Explanation	The query attached to a node with map-type=object is of the form "@ino:id=%parent". The document ID found in the parent node is either zero or contains non-digit characters.
Action	The document ID in the parent node is illegal, correct it.

INOXCE8108	**Insufficient mapping information, document cannot be composed**
Explanation	An XML document could not be created due to insufficient mapping information.
Action	Look at the <ino:messageline> element in the <ino:response> document to find more information about the cause of the problem.

INOXCE8109	**Cannot delete externally mapped data**
Explanation	Tamino X-Query is not able to delete XML documents that are composed from external data sources like ODBC or Adabas if those documents have not been stored through Tamino. Typically, when displayed, these documents do not have an "ino:id" attribute. Similarly, X-Query cannot delete data from doctypes with "tsd:pure" mapping.
Action	Modify the query that selects the documents to be deleted. In the case of pure mapping, use XQuery update in order to delete documents.

INOXCE8110	**Internal error: document data corrupted**
Explanation	An internal error has occurred.
Action	Please contact your software supplier.

INOXCE8111	**Error in XNode Adabas processing during conversion of Natural date/time value**
Explanation	An error occurred while converting a Natural date or time value. The Tamino response contains details about the offending value, as well as an internal error code.
Action	Analyze the error.

INOXCE8114 **Document ID unknown, mapping type infofield**

Explanation This error message should never occur.

Action None

INOXCE8117 **Internal error:Document not found**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXCE8118 **Mapping type object: number of resulting objects too large**

Explanation This message should never occur

Action None

INOXCE8119 **Internal error: structure description too large**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXDE7500 **NOTATION must be restricted by an enumeration**

Explanation NOTATION must be restricted by an enumeration.

Action Please modify your XML schema accordingly.

INOXDE7501 **(a-props-correct.2) default or fixed value is not of declared type**

Explanation If there is a default or fixed value specification, the canonical lexical representation of its value must be valid with respect to the type definition.

Action Please modify your XML schema accordingly.

INOXDE7502 **(a-props-correct.3) If attributes has type ID or a derived type it must not have a value constraint, i.e. a default or fixed value**

Explanation Attributes of type ID or a derived type must not have a value constraint, i.e. a default or fixed value.

Action Please modify your XML schema accordingly.

INOXDE7503	**(e-props-correct.2) default or fixed value is not of declared type**
Explanation	If there is a default or fixed value specification, the canonical lexical representation of its value must be valid with respect to the type definition.
Action	Please modify your XML schema accordingly.

INOXDE7504	**(e-props-correct.4) Elements of type ID or a derived type must not have a value constraint, i.e. a default or fixed value**
Explanation	Elements of type ID or a derived type must not have a value constraint, i.e. a default or fixed value.
Action	Please modify your XML schema accordingly.

INOXDE7505	**(ct-props-correct.4) attributes must not have identical names**
Explanation	Two distinct attribute declarations in the attribute uses must not have identical names.
Action	Please modify your XML schema accordingly.

INOXDE7506	**(ct-props-correct.5) only one attribute may have type ID or a derived type**
Explanation	Two distinct attribute declarations in the attribute uses must not have type ID or a derived type.
Action	Please modify your XML schema accordingly.

INOXDE7507	**(au-props-correct.2) attribute's fixed value does not match declaration's fixed value**
Explanation	If the attribute declaration has a fixed value constraint, then if the attribute use itself has a value constraint, it must also be fixed and its value must match that of the attribute declaration's value constraint.
Action	Please modify your XML schema accordingly.

INOXDE7508	**(sch-props-correct.2) name conflict with global declarations**
Explanation	Each of the type definitions, element declarations, attribute group definitions, model group definitions and notation declarations must not contain two or more schema components with the same name.
Action	Please modify your XML schema accordingly.

INOXDE7509 **invalid type of default value**

Explanation If the type definition is a simple type definition, then the string must be valid with respect to that definition.

Action Please modify your XML schema accordingly.

INOXDE7510 **content type is neither a simple type definition nor mixed**

Explanation If an element declaration specifies a default value and the type definition is a complex type definition, then its content type must be a simple type definition or mixed.

Action Please modify your XML schema accordingly.

INOXDE7511 **element default value does not match type**

Explanation If an element declaration specifies a default value and the type definition is a complex type definition and its content type is a simple type definition, then the default value must be of declared type.

Action Please modify your XML schema accordingly.

INOXDE7512 **content type does not allow for default value**

Explanation If an element declaration specifies a default value and the type definition is a complex type definition and its content type is mixed, then the content type's particle must be emptiable.

Action Please modify your XML schema accordingly.

INOXDE7513 **missing name in type definition**

Explanation If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.

Action Please modify your XML schema accordingly.

INOXDE7514 **type definitions have different names**

Explanation If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.

Action Please modify your XML schema accordingly.

INOXDE7515	**type definitions have different namespaces**
Explanation	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
Action	Please modify your XML schema accordingly.

INOXDE7516	**(no-xmlns) attribute name not allowed**
Explanation	The name of an attribute declaration must not match xmlns.
Action	Use the targetNamespace attribute of the schema's root node in order to associate the current schema and objects defined therein with a namespace URI. The import element can be used to compose schemas defining objects for different namespaces.

INOXDE7517	**Below Attribute there may be only attributeInfo node but no schemaInfo or elementInfo nodes**
Explanation	Below Attribute there may be only attributeInfo node but no schemaInfo or elementInfo nodes.
Action	Please modify your XML schema accordingly.

INOXDE7518	**(enumeration-valid-restriction) value of enumeration does not match base type definition**
Explanation	The value attribute of an enumeration item must match the definition of the restriction's base type.
Action	Adapt your schema.

INOXDE7519	**(notation-defined-restriction) value of enumeration is not defined in a global notation element.**
Explanation	An enumeration value being used in a type derived from NOTATION must be defined in a global notation element.
Action	Adapt your schema.

INOXDE7520	**invalid index**
Explanation	It is not possible to define indices on elements or attributes with type "xs:long", "xs:unsignedLong" or "xs:decimal".
Action	Please modify your XML schema accordingly.

INOXDE7521	**invalid text index**
Explanation	It is not possible to define text indices on elements or attributes with numeric types.
Action	Please modify your XML schema accordingly.

INOXDE7522	**The element pointed to by tsd:refers needs to have a reference index defined for it**
Explanation	(mp-valid-refers.5:) The element pointed to by tsd:refers needs to have a reference index defined for it.
Action	Please modify the schema to include a reference index on the element pointed to by tsd:refers and try to define the schema again.

INOXDE7523	**Collations can only be defined for string datatypes (derived types of string in W3C XML schema part 2)**
Explanation	Collations can only be defined for string datatypes (derived types of string in W3C XML schema part 2).
Action	Please modify your XML schema accordingly.

INOXDE7524	**(src-single-facet-value) Facet is only permitted to be defined once**
Explanation	A facet has been specified more than once. This facet is only permitted to be defined once.
Action	Please modify the XML Schema accordingly.

INOXDE7525	**(cos-element-consistent) Element declarations are not consistent**
Explanation	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
Action	Please modify your XML schema accordingly.

INOXDE7526	**(maxInclusive-maxExclusive) 'maxInclusive' and 'maxExclusive' facets cannot be used together**
Explanation	A simple type restriction, containing both 'maxInclusive' and 'maxExclusive' facets, has been found.
Action	Remove either of the 'maxInclusive' or 'maxExclusive' facets.

INOXDE7527	**(minInclusive-minExclusive) 'minInclusive' and 'minExclusive' facets cannot be used together**
Explanation	A simple type restriction, containing both 'minInclusive' and 'minExclusive' facets, has been found.
Action	Remove either of the 'minInclusive' or 'minExclusive' facets.

INOXDE7528	**Node declarations are not consistent**
Explanation	The schema violates a constraint which is a Tamino-specific extension of the (cos-element-consistent) constraint as imposed by XML schema: If there are two attribute or element declarations in the set of complex type definitions being allowed for a given element node due to usage of the xsi:type attribute, then these attributes (or elements) must be consistent. Consistency requirements cover the datatype as well as physical properties (mapping, indexing,...), or logical properties (collation, trigger, ...).
Action	Modify the schema to avoid violation of the constraint. For example it may help to use the 'block' attribute of <xs:element> or <xs:complexType> , or the 'blockDefault' attribute of <xs:schema> in order to control the {prohibited substitutions} with respect to xsi:type. In particular, you may use blockDefault="#all" if you do not need to allow for usage of the xsi:type attribute in your XML documents.

INOXDE7529	**(src-resolve.1.1) Global type reference could not be resolved**
Explanation	Reference to a global complex or simple type definition could not be resolved.
Action	Check the names of the global type definition and the associated reference.

INOXDE7530	**(src-resolve.1.2) The ref attribute of an attribute needs to reference an existing global attribute**
Explanation	An attribute defined in the schema uses the 'ref' attribute, however the global attribute with that name cannot be found.
Action	Check that the global attribute is not missing. Also check that the global attribute name and reference have been correctly specified.

INOXDE7531	**(minLength-less-than-equal-to-maxLength) 'minLength' facet value must be 'less than or equal to' that of facet 'maxLength'**
Explanation	A simple type restriction, where the value of facet 'minLength' is greater than that of 'maxLength', has been found.
Action	Revise the facet values.

INOXDE7532 **Invalid pattern facet value found**

Explanation The schema being defined contains a pattern facet which has an invalid value.

Action Check the schema and consider revising the pattern facet's value.

INOXDE7533 **Below Schema there needs to be exactly one appinfo node which defines Tamino mappings**

Explanation Below Schema there needs to be exactly one appinfo node which defines Tamino mappings.

Action Modify the XML schema accordingly.

INOXDE7534 **(src-import.1.1) Invalid import element. If the namespace attribute is present, then its value must not match the value of the enclosing schema's targetNamespace attribute.**

Explanation The schema being defined contains an import element. The namespace attribute is present and its value is the same as the targetNamespace of the enclosing schema. This is not allowed.

Action Revise either the namespace attribute of the import element or the targetNamespace of the schema.

INOXDE7535 **(src-import.1.2) Invalid import element. If the namespace attribute is not present, then the enclosing schema must have a targetNamespace attribute.**

Explanation The schema being defined contains an import element. The namespace attribute is not present and the enclosing schema does not specify a targetNamespace. This is disallowed.

Action Revise the import element and/or the schema element.

INOXDE7536 **(src-import.2) Invalid import element. Schema reference could not be resolved.**

Explanation The schema being defined contains an import element. The schema referenced using either a schemaLocation or namespace attribute could not be located.

Action If referencing using schemaLocation, check the name of the referenced schema (and optionally the collection name also). If referencing using namespace alone, check the targetNamespace of the referenced schema.

INOXDE7537 **(src-import.3.1) Invalid import element. If there is a namespace attribute, then its value must be identical to the value of the targetNamespace attribute of the referenced schema.**

Explanation The schema being defined contains an import element. The namespace attribute is different from the targetNamespace of the referenced schema. This is not allowed.

Action Revise either the namespace attribute of the import element or the targetNamespace of the referenced schema.

INOXDE7538	**(src-import.3.2) Invalid import element. If there is no namespace attribute, then the referenced schema must have no targetNamespace attribute.**
Explanation	The schema being defined contains an import element. The namespace attribute is not present, but the referenced schema specifies a targetNamespace. This is not allowed.
Action	Revise the import element and/or the referenced schema element.

INOXDE7539	**The value of schema attribute targetNamespace is not allowed if another schema in the same database already imports the corresponding namespace using only the namespace attribute of the import element**
Explanation	The value of the targetNamespace attribute of the schema that you are trying to define is not allowed. This is because another schema in the same database already imports that namespace, using an import element with namespace alone.
Action	Revise the schema and/or the other schema importing that namespace. Either change the targetNamespace of the current schema, or change the import element of the referencing schema to also use the schemaLocation attribute.

INOXDE7540	**Found node with a mapped value which is used to construct index entries**
Explanation	A node with a mapped value must not be used to construct index entries. This restriction applies for text and standard as well as for the components of a compound index referring to an ancestor of the current node.
Action	Remove index definition causing this conflict.

INOXDE7541	**Undefine of schema failed. Schema to be undefined is referenced by other schema(s) in the database.**
Explanation	The undefine of a specific schema was performed. Other schema(s) in the database still reference this schema.
Action	Before the schema can be undefined, you must first undefine all referencing schemas.

INOXDE7542	**Attribute targetNamespace of element schema, if present, must not be empty.**
Explanation	The schema being defined specifies an empty targetNamespace attribute.
Action	Revise the schema. Either provide the targetNamespace attribute with a value, or completely remove it.

INOXDE7543 **Import using namespace attribute alone is forbidden, if more than one schema with the corresponding targetNamespace is already stored in the current database**

Explanation The schema being defined contains an import element with only a namespace attribute. More than one schema stored in the current database already contains a corresponding targetNamespace attribute.

Action Revise the schema and/or other schemas stored inside the current database. Consider using the schemaLocation attribute of import to clarify exactly which schema was intended.

INOXDE7544 **An import element must have attributes**

Explanation The schema being defined specifies an import element without attributes.

Action Revise the schema. Add either namespace or schemaLocation attributes to the import element, or remove it and consider using Tamino's content element with value open.

INOXDE7545 **Cannot define standard index or unique constraint based on a node whose associated datatype has a variety of 'union'**

Explanation It is not supported to define an index or unique constraint based on a node whose datatype has a variety of 'union' or which is derived via <xs:list> with an item type whose variety is 'union'.

Action Modify the schema accordingly.

INOXDE7546 **An element defined as a primary key cannot be defined as nillable**

Explanation An element which is defined as a primary key value cannot be defined as nillable.

Action Revise the schema. Either remove the xsi:nillable attribute or set the value to false.

INOXDE7547 **Undefine of collection failed. One or more schemas contained inside the collection to be undefined are referenced by other schema(s), from other collection(s) in the current database.**

Explanation The undefine of a specific collection was performed. Other schema(s) from other collection(s) in the database still reference one or more schemas contained inside the collection to be undefined.

Action Before the collection can be undefined, you must first undefine all referencing schemas.

INOXDE7548 **Cannot define standard index or unique constraint based on this element node with complex content if there is a validly derived complex type with simple content which can be used in an xsi:type attribute on that element node**

Explanation It is not allowed to define a standard index or unique constraint based on an element node whose associated datatype is a complex type with complex content if there is another complex type with simple content which can be validly used in an xsi:type attribute on that element node.

Action	Either remove the index definition or modify type definitions to avoid violation of this constraint.

INOXDE7549	**Mapping not allowed for datatype of variety**
Explanation	Mapping (ADABAS, SQL and SXS) is not allowed for datatypes derived via xs:list or xs:union.
Action	Please change the datatype and try to define the schema again.

INOXDE7550	**ElementInfo node is not allowed with a schema reference to a global element definition**
Explanation	Below Element an elementInfo node is only allowed if the element node starts an element definition. An elementInfo is not allowed with a reference to a global element definition.
Action	Please modify your XML schema accordingly.

INOXDE7551	**AttributeInfo node is not allowed with a schema reference to a global attribute definition**
Explanation	Below Attribute an attributeInfo node is only allowed if the attribute node starts an attribute definition. An attributeInfo is not allowed with a reference to a global attribute definition.
Action	Please modify your XML schema accordingly.

INOXDE7552	**The path contains invalid expressions**
Explanation	The path can only consists of named child steps with abbreviated XPath syntax. In particular, it cannot contain *, .., // operators.
Action	Modify the XML schema accordingly.

INOXDE7553	**The index types of elements and attributes having the same multipath index label must be identical**
Explanation	The index types of elements and attributes having the same multipath index label must be identical.
Action	Please change the schema so that multipath definitions with the same label are only used when the index types are identical and then try to define the schema again.

INOXDE7554	**(src-attribute-group.2) Intentional intersection of namespace constraints is not expressible**
Explanation	This may happen e.g. if two attribute wildcards are to be merged due to resolution of a reference to an attributeGroup definition. If those two attribute wildcards both have a namespace constraint ##other, thus referring to different target namespaces, the intentional intersection is not expressible.
Action	Adapt the schema according to XML schema constraint src-attribute-group.2

INOXDE7555	**The name attribute of tsd:unique definitions has to be unique within a doctype**
Explanation	The name attribute of tsd:unique definitions has to be unique within a doctype.
Action	Please change the duplicate name and try to define the schema again.

INOXDE7556	**The elements and attributes pointed to in tsd:unique definitions must have a cardinality of 1**
Explanation	The elements and attributes pointed to in tsd:unique definitions must have a cardinality of 1.
Action	Please change the cardinality and try to define the schema again.

INOXDE7557	**The path specified the xpath attribute of a field element needs to point to an existing element or attribute**
Explanation	The path specified the xpath attribute of a field element needs to point to an existing element or attribute.
Action	Please make sure the specified path is correct and try to define the schema again.

INOXDE7558	**multipath index definitions are not allowed in doctypes which have the structureIndex set to none**
Explanation	Multipath index definitions are not allowed in doctypes which have the structureIndex set to none.
Action	Please change the structure index to condensed or full and try to define the schema again.

INOXDE7559	**The elements and attributes having the same multipath index label must have matching datatypes**
Explanation	The elements and attributes having the same multipath index label must have matching datatypes.
Action	Please change the wrong datatype and try to define the schema again.

INOXDE7560	**The elements and attributes having the same multipath index label must have matching collations**
Explanation	The elements and attributes having the same multipath index label must have matching collations.
Action	Please change the wrong collation and try to define the schema again.

INOXDE7561	**The elements and attributes having the same multipath index label must have matching tsd:refers definitions**
Explanation	The elements and attributes having the same multipath index label must have matching tsd:refers definitions.
Action	Please change the wrong tsd:refers definition and try to define the schema again.

INOXDE7562	**The path defined in tsd:refers has to point to an existing element**
Explanation	The path defined in tsd:refers has to point to an existing element.
Action	Please change the path and try to define the schema again.

INOXDE7563	**The path defined in tsd:refers has to point to an element which is a predecessor of the element or attribute where it is defined**
Explanation	The path defined in tsd:refers has to point to an element which is a predecessor of the element or attribute where it is defined.
Action	Please change the path and try to define the schema again.

INOXDE7564	**The path defined in tsd:refers may only point to elements that are locally stored in a Tamino database**
Explanation	The path defined in tsd:refers may only point to elements that are locally stored in a Tamino database.
Action	Please change the path and try to define the schema again.

INOXDE7565	**The path defined in tsd:refers must point either to the doctype element or to an element for which a tsd:reference is defined**
Explanation	The path defined in tsd:refers must point either to the doctype element or to an element for which a tsd:reference is defined.
Action	Please change the path and try to define the schema again.

INOXDE7566 **The path specified in the xpath attribute of a field element needs to point to an element or attribute that is locally stored in a Tamino database**

Explanation The path specified in the xpath attribute of a field element needs to point to an element or attribute that is locally stored in a Tamino database.

Action Please change the path and try to define the schema again.

INOXDE7567 **The path specified in the xpath attribute of a field element of a compound index definition needs to point to a leaf node (an attribute or element having no children)**

Explanation The path specified in the xpath attribute of a field element of a compound index definition needs to point to a leaf node (an attribute or element having no children).

Action Please change the path and try to define the schema again.

INOXDE7568 **For a uniqueness constraint a certain path may only be defined once**

Explanation For a uniqueness constraint a certain path may only be defined once.

Action Please change the path and try to define the schema again.

INOXDE7569 **A reference index may not be defined for a doctype element**

Explanation A reference index may not be defined for a doctype element.

Action Please change the reference index value and try to define the schema again.

INOXDE7570 **There may only be one tsd:reference index definition per tsd:physical**

Explanation There may only be one tsd:reference index definition per tsd:physical.

Action Please make sure there is only one tsd:reference index definition per tsd:physical and try to define the schema again.

INOXDE7571 **If an index has been defined as a multipath index, there may not be a tsd:refers defined for that same index**

Explanation If an index has been defined as a multipath index, there may not be a tsd:refers defined for that same index.

Action Please remove either the multipath definition or the tsd:refers and try to define the schema again.

INOXDE7572	**For a compound index a certain path may only be defined once**
Explanation	For a compound index a certain path may only be defined once.
Action	Please change the schema and try to define it again.

INOXDE7573	**(src-resolve.1.4) Reference to an attribute group definition could not be resolved**
Explanation	Reference to an attribute group definition could not be resolved.
Action	Check the qualified names of the attribute group definition and the reference.

INOXDE7574	**(src-resolve.1.5) Reference to a model group definition could not be resolved**
Explanation	Reference to a model group definition could not be resolved.
Action	Check the qualified names of the model group definition and the reference.

INOXDE7575	**(src-attribute-group.3) Circular attribute group reference is disallowed**
Explanation	A cycle of attribute group references has been found.
Action	Check the attribute group references and remove the circular reference.

INOXDE7576	**(mg-props-correct.2) Circular group reference is disallowed**
Explanation	Within the particles of a group there must not be at any depth a reference to the group itself.
Action	Check group definition and remove circular reference inside.

INOXDE7577	**(src-include.2.1) Target namespace of the including and the included schema do not match.**
Explanation	The values of the targetNamespace attributes of the including and the included schema may not differ if both are present.
Action	Check targetNamespace attributes.

INOXDE7578	**(src-include.2.2) Included schema has target namespace whereas including has no target namespace.**
Explanation	If the including schema has no targetNamespace attribute, the included schema must not have a targetNamespace attribute as well.
Action	Check and adapt the schema documents.

INOXDE7579 **(src-include.2.3) Target namespace of included schema missing. Tamino does not yet support "chameleon include".**

Explanation This is a current limitation of Tamino.

Action Define the included schema using the same targetNamespace attribute as the including schema's targetNamespace.

INOXDE7580 **(src-include.1) Invalid include element. Schema reference could not be resolved.**

Explanation The schema being defined contains an include element. The schema referenced by the schemaLocation attribute could not be located.

Action Check the name of the referenced schema and, optionally, the collection name as well.

INOXDE7581 **invalid collation language**

Explanation The specified language string is not valid.

Action Please change the wrong collation language string and try to define the schema again.

INOXDE7583 **Invalid open content found in pure X-Node mapped doctype**

Explanation For pure X-Node mapping, no open content is allowed for that doctype. This includes wildcards with processContents being "strict" or "lax" and element nodes with type "xs:anyType" or no type at all.

Action Ensure that the doctype with the pure X-Node mapping is set to closed content, that any of the doctype's wildcards (xs:any and xs:anyAttribute) in scope have processContents set to "strict", and that all elements in scope have a non-absent type specification different from "xs:anyType".

INOXDE7584 **Invalid mixed content found in complex type within a pure X-Node mapped doctype**

Explanation Elements in a pure X-Node mapped doctype must not have a mixed content model.

Action Set the mixed attribute of the corresponding complex type definition to "false".

INOXDE7585 **Invalid mapping found in root element of pure X-Node mapped doctype**

Explanation Currently, only Adabas mapping is allowed for the root node of a pure X-Node mapped doctype.

Action Check the mapping of the root element.

INOXDE7586	**Invalid mapping found in non-root node within pure X-Node mapped doctype**
Explanation	All leaf nodes must be mapped corresponding to the mapping type of the root element, e.g. to Adabas fields if the root node is mapped to an Adabas file.
Action	Check the mapping of the node.

INOXDE7587	**Found invalid recursion in pure X-Node mapped doctype**
Explanation	Within a pure X-Node mapped doctype no recursive structures are permitted.
Action	Remove the recursion.

INOXDE7588	**Found empty leaf node in pure X-Node mapped doctype**
Explanation	A pure X-Node mapped doctype must not contain empty leaf nodes.
Action	Either remove the node or map to an X-Node data item, i.e. either an Adabas field or an SQL column.

INOXDE7589	**Reference index definitions are not allowed in doctypes which have the structureIndex set to none**
Explanation	Reference index definitions are not allowed in doctypes which have the structureIndex set to none.
Action	Please correct the schema and try to define it again.

INOXDE7590	**Unique index constraints may not be defined on elements or attributes on node of given type**
Explanation	Unique index constraints may not be defined on elements or attributes of xs:duration or any data type allowing for an optional timezone indicator, e.g. xs:dateTime.
Action	Please correct the schema and try to define it again.

INOXDE7591	**Found xs:include or xs:import referencing current schema**
Explanation	An xs:include or xs:import must not reference the current schema.
Action	Adapt the schema.

INOXDE7592	**Invalid level of structure index for pure X-Node mapped doctype**
Explanation	A pure X-Node mapped doctype must not have a full structure index.
Action	Set the structure index to 'condensed' or 'none'.

INOXDE7593 **A default function has been defined at an element node with a complex type**

Explanation A default function may only be defined at a node with a simple type.

Action Modify the schema in an appropriate way.

INOXDE7594 **Default function defined for required attribute node**

Explanation If a default function is defined for an attribute, the attribute must be optional.

Action Check and adapt schema in an appropriate way.

INOXDE7595 **Default function defined for a node which has a value constraint**

Explanation An element or attribute node may define either a default function or a value constraint (i.e. a default or fixed value) but not both.

Action Adapt the schema correspondingly.

INOXDE7596 **Too many tsd:elementInfo or tsd:attributeInfo nodes**

Explanation There may be only one tsd:elementInfo or tsd:attributeInfo node per xs:element or xs:attribute node.

Action Modify the schema accordingly.

INOXDE7597 **(src-list-itemType-or-simpleType) Definition of simple type via <xs:list> contains both 'itemType' attribute and <xs:simpleType> child.**

Explanation Either the 'itemType' attribute or the <xs:simpleType> child of the <xs:list> element must be present, but not both.

Action Remove either the 'itemType' attribute or the <xs:simpleType> child.

INOXDE7598 **(src-restriction-base-or-simpleType) Definition of simple type via <xs:restriction> must contain either 'base' attribute or <xs:simpleType> child.**

Explanation Either the 'base' attribute or the <xs:simpleType> child of the <xs:restriction> element must be present, but not both.

Action Remove either 'base' attribute or the <xs:simpleType> child.

INOXDE7599 **(src-union-memberTypes-or-simpleTypes) The 'memberTypes' attribute of the <xs:union> element is empty and there is no <xs:simpleType> child.**

Explanation Either the 'memberTypes' attribute of the <xs:union> element must be non-empty or there must be at least one <xs:simpleType> child.

Action Add either the 'memberTypes' attribute of the <xs:union> element or at least one <xs:simpleType> child.

INOXDE7614	**The noConversion option may only be changed for empty doctypes**
Explanation	Changing the noConversion option could make the existing data in the doctype invalid, so this option may only be modified for empty doctypes.
Action	Adapt the schema so that the noConversion option is not changed or make sure there are no documents stored in the doctype for which you are trying to modify the schema.

INOXDE7619	**Invalid type of parameter for server extension**
Explanation	The type of the parameter is invalid in the current context.
Action	Check and modify the type of parameter to be passed to the server extension function. for example, parameters being passed to a trigger function may only have a simple predefined type.

INOXDE7620	**Invalid parameter value**
Explanation	The value of the parameter is not valid with respect to the declared type.
Action	Modify the type or value in order to create a consistent parameter definition.

INOXDE7621	**(cos-st-restricts.1.1) Invalid base type definition of simple type**
Explanation	The base type definition must be an atomic simple type definition or a built-in primitive datatype.
Action	Adapt the type definitions or type hierarchy.

INOXDE7622	**(cos-st-restricts.1.2) Invalid base type of simple type definition - the 'final' attribute does not permit derivation of another simple type**
Explanation	The {final} of the {base type definition} of a simple type definition must not contain restriction.
Action	Adapt the schema according to the constraint.

INOXDE7623	**(cos-st-restricts.2.1) Invalid item type definition of simple type derived via <xs:list>**
Explanation	The {item type definition} must have a {variety} of atomic or union (in which case all the {member type definitions} must be atomic).
Action	Adapt the schema according to the constraint.

INOXDE7624	**(cos-st-restricts.2.3.1.1) Invalid item type definition of simple type derived via <xs:list>**
Explanation	The {final} of the {item type definition} must not contain list.
Action	Adapt the schema according to the constraint.

INOXDE7625	**(cos-st-restricts.3.3.2.2) Invalid base type for simple type derived via <xs:restriction>**
Explanation	The {final} of the {base type definition} must not contain restriction.
Action	Adapt the schema according to the constraint.

INOXDE7626	**(cos-st-restricts.2.3.2.2) Invalid base type for simple type derived via <xs:restriction>**
Explanation	The {final} of the {base type definition} must not contain restriction.
Action	Adapt the schema according to the constraint.

INOXDE7627	**(cos-st-restricts.2.3.2.4) Invalid facet for simple type derived via <xs:list>**
Explanation	Only length, minLength, maxLength, whiteSpace, pattern and enumeration facet components are allowed among the {facets}.
Action	Adapt the schema according to the constraint.

INOXDE7628	**(cos-st-restricts.3.1) Invalid member type definition for simple type derived via <xs:union>**
Explanation	The {member type definitions} must all have {variety} of atomic or list.
Action	Adapt the schema according to the constraint.

INOXDE7629	**(cos-st-restricts.3.3.1.1) Invalid member type definition for simple type derived via <xs:union>**
Explanation	All of the {member type definitions} must have a {final} which does not contain union.
Action	Adapt the schema according to the constraint.

INOXDE7630	**(cos-st-restricts.3.3.2.4) Invalid facet for simple type derived via <xs:union>**
Explanation	Only pattern and enumeration facet components are allowed among the {facets}.
Action	Adapt the schema according to the constraint.

INOXDE7631	**(a-props-correct.1) Invalid type of attribute declaration - must be a simple type**
Explanation	The type definition of an attribute declaration must be a simple type.
Action	Modify the type definition of the attribute declaration.

INOXDE7632	**(st-props-correct.2) Invalid or circular type hierarchy of simple type definition**
Explanation	All simple type definitions must be derived ultimately from the simple ur-type definition - circular definitions are disallowed.
Action	Adapt the schema according to the constraint.

INOXDE7633	**(ct-props-correct.2) Invalid derivation of complex type with simple base type definition**
Explanation	If the {base type definition} is a simple type definition, the {derivation method} must be extension.
Action	Adapt the schema according to the constraint.

INOXDE7634	**(ct-props-correct.3) Invalid or circular type hierarchy of complex type definition**
Explanation	Circular definitions are disallowed, except for the ur-type definition. That is, it must be possible to reach the ur-type definition by repeatedly following the {base type definition}.
Action	Adapt the schema according to the constraint.

INOXDE7635	**(no-xsi) Invalid attribute declaration for targetNamespace**
Explanation	The {target namespace} of an attribute declaration, whether local or top-level, must not match http://www.w3.org/2001/XMLSchema-instance, unless it is one of the four built-in declarations for xsi:type, xsi:nil, xsi:schemaLocation, xsi:noNamespaceSchemaLocation.
Action	Adapt the schema according to constraint. See XML Schema Part 1 for a valid declaration of the four built-in declarations.

INOXDE7636	**(src-ct.1) Invalid base type definition of complex type with complex content**
Explanation	If the <complexContent> alternative is chosen, the type definition resolved to by the actual value of the 'base' attribute must be a complex type definition.
Action	Adapt the schema according to the constraint.

INOXDE7637 **(src-ct.2.1) Invalid base type definition of complex type simple content**

Explanation The type definition resolved to by the actual value of the 'base' attribute must be one of the following: (1) a complex type definition whose {content type} is a simple type definition; (2) only if the <restriction> alternative is also chosen, a complex type definition whose {content type} is mixed and a particle which is emptiable.

Action Adapt the schema according to the constraint.

INOXDE7638 **(src-ct.2.2) Missing <xs:simpleType> below <xs:restriction> for a complex type with simple content which is derived from a complex type via restriction**

Explanation If the <simpleContent>/<restriction> alternative is chosen with the 'base' attribute resolving to a complex type definition whose {content type} is mixed and a particle which is emptiable, there must be a <simpleType> among the [children] of <restriction>.

Action Adapt the schema according to the constraint.

INOXDE7639 **(cos-ct-extends.1.1) Invalid base type of complex type derived via <xs:extension>**

Explanation The {final} of the {base type definition} must not contain extension.

Action Adapt the schema according to the constraint.

INOXDE7640 **(cos-ct-extends.1.4.1) Simple content types of complex type derived via <xs:extension> and the respective base type definition do not match**

Explanation The {content type} of the {base type definition} and the {content type} of the complex type definition itself must be the same simple type definition.

Action Adapt the schema according to the constraint.

INOXDE7641 **(cos-ct-extends.1.4.2) If the content type of a complex type derived via <xs:extension> is empty, the content type of the respective complex base type definition must be empty as well**

Explanation The {content type} of both the {base type definition} and the complex type definition itself must be empty.

Action Adapt the schema according to the constraint.

INOXDE7642 **(cos-ct-extends.1.4.3.1) Invalid content type of a complex type definition derived via <xs:extension> given the content type of the complex base type definition**

Explanation The {content type} of the complex type definition itself must specify a particle.

Action Adapt the schema according to the constraint.

INOXDE7643	**(cos-ct-extends.1.4.3.2.2.1) Invalid content type of complex type definition derived via <xs:extension> from complex type definition**
Explanation	Both {content type}s must be mixed or both must be element-only.
Action	Adapt the schema according to the constraint.

INOXDE7644	**(cos-ct-extends.2.2) Invalid base type of complex type definition derived via <xs:extension>**
Explanation	The {final} of the {base type definition} must not contain extension.
Action	Adapt the schema according to the constraint.

INOXDE7645	**(derivation-ok-restriction.1) Invalid base type definition of complex type derived via <xs:restriction>**
Explanation	The {base type definition} must be a complex type definition whose {final} does not contain restriction.
Action	Adapt the schema according to the constraint.

INOXDE7646	**(derivation-ok-restriction.2.1.1) Invalid value of 'use' attribute of attribute in complex type definition derived via <xs:restriction> compared to value of 'use' attribute for respective attribute in complex base type definition.**
Explanation	If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then one of the following must be true: (1) B's {required} is false. (2) the restricted type's {required} is true.
Action	Adapt the schema according to the constraint.

INOXDE7647	**(derivation-ok-restriction.2.1.2) Invalid type of attribute in complex type definition derived via <xs:restriction> compared to type of respective attribute in complex base type definition.**
Explanation	If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then the restricted type's {attribute declaration}'s {type definition} must be validly derived from B's {type definition}.
Action	Adapt the schema according to the constraint.

INOXDE7648 **(derivation-ok-restriction.2.1.3) Invalid value constraint of attribute in complex type definition derived via <xs:restriction> compared to value constraint of respective attribute in complex base type definition**

Explanation If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then one of the following must be true: (1) B's effective value constraint is absent or default. (2) the restricted type's effective value constraint is fixed with the same string as B's.

Action Adapt the schema according to the constraint.

INOXDE7649 **(derivation-ok-restriction.2.2) Invalid attribute use in complex type definition derived via <xs:restriction>, the complex base type definition neither contains a matching attribute use nor an attribute wildcard.**

Explanation If there is no attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, the {base type definition} must have an {attribute wildcard} and the {target namespace} of the restricted type's {attribute declaration} must be valid with respect to that wildcard.

Action Adapt the schema according to the constraint.

INOXDE7650 **(derivation-ok-restriction.3) Invalid value of 'use' attribute of attribute in complex type definition derived via <xs:restriction> compared to value of 'use' attribute for respective attribute in complex base type definition**

Explanation For each attribute use in the {attribute uses} of the {base type definition} whose {required} is true, there must be an attribute use with an {attribute declaration} with the same {name} and {target namespace} as its {attribute declaration} in the {attribute uses} of the complex type definition itself whose {required} is true.

Action Adapt the schema according to the constraint.

INOXDE7651 **(derivation-ok-restriction.4.1) Invalid attribute wildcard in complex type definition derived via <xs:restriction>, complex base type definition does not have an attribute wildcard**

Explanation If there is an {attribute wildcard}, the {base type definition} must also have one.

Action Adapt the schema according to the constraint.

INOXDE7652 **(derivation-ok-restriction.4.2) Invalid attribute wildcard in complex type definition derived via <xs:restriction>, its namespace constraint is not a subset of the namespace constraint of the attribute wildcard in the complex base type definition**

Explanation If there is an {attribute wildcard}, the complex type definition's {attribute wildcard}'s {namespace constraint} must be a subset of the {base type definition}'s {attribute wildcard}'s {namespace constraint}.

Action Adapt the schema according to the constraint.

INOXDE7653	**(derivation-ok-restriction.4.3) Invalid 'processContents' of attribute wildcard in complex type definition derived via <xs:restriction> compared to 'processContents' of attribute wildcard in complex base type definition**
Explanation	If there is an {attribute wildcard}, and the {base type definition} is not the ur-type definition, the complex type definition's {attribute wildcard}'s {process contents} must be identical to or stronger than the {base type definition}'s {attribute wildcard}'s {process contents}, where strict is stronger than lax is stronger than skip.
Action	Adapt the schema according to the constraint.

INOXDE7654	**(derivation-ok-restriction.5.1.2) Invalid base type for complex type with simple content derived via <xs:restriction>**
Explanation	If the {content type} of the complex type definition is a simple type definition, one of the following must be true: (1) The {content type} of the {base type definition} must be a simple type definition from which the {content type} is validly derived (2) The {base type definition} must be mixed and have a particle which is emptiable
Action	Adapt the schema according to the constraint.

INOXDE7655	**(derivation-ok-restriction.5.2.2) Invalid base type for complex type with empty content derived via <xs:restriction>**
Explanation	If the {content type} of the complex type is empty, one of the following must be true: (1) The {content type} of the {base type definition} must also be empty. (2) The {content type} of the {base type definition} must be elementOnly or mixed and have a particle which is emptiable
Action	Adapt the schema according to the constraint.

INOXDE7656	**(derivation-ok-restriction.5.3.1) Invalid base type for complex type with neither simple nor empty content derived via <xs:restriction>**
Explanation	If the {content type} of the complex type definition is neither a simple type definition nor empty, one of the following must be true: (1) The {content type} of the complex type definition itself must be element-only (2) The {content type} of the complex type definition itself and of the {base type definition} must be mixed.
Action	Adapt the schema according to the constraint.

INOXDE7657	**(derivation-ok-restriction.5.3.2) The particle of the complex type derived via restriction does not satisfy the "Particle Valid (Restriction)" constraint with respect to the particle of the complex base type**
Explanation	If the {content type} of the complex type definition is neither a simple type definition nor empty, the particle of the complex type definition itself must be a valid restriction of the particle of the {content type} of the {base type definition}.
Action	Adapt the schema according to the constraint.

INOXDE7658	**An element's or attribute's shortname definition does not match Adabas field definition**
Explanation	A field with the given shortname does not exist in the Adabas file defined for this element.
Action	Adapt the schema to the corresponding Adabas field and file definitions.

INOXDE7659	**The element's or attribute's Adabas format definition does not match the Adabas field definition**
Explanation	The Adabas format definition cannot be converted to the format defined in the Adabas FDT.
Action	Adapt your schema to the corresponding Adabas field definitions.

INOXDE7660	**An element's periodic group definition does not match the Adabas field definition**
Explanation	The correspondingf Adabas field is not defined as a periodic group in the Adabas FDT.
Action	Adapt your schema corresponding to the Adabas field definition

INOXDE7661	**An element's multiple field definition does not match the Adabas field definition**
Explanation	The corresponding Adabas field is not defined as multiple field in Adabas.
Action	Adapt your schema definition to the corresponding Adabas definitions.

INOXDE7662	**An element nillable definition does not match the Adabas field definition**
Explanation	The element defined as xsi:nillable is not defined with NC (SQL NUll-Value Representation) -option in the Adabas FDT.
Action	Adapt the schema corresponding to the Adabas field definition.

INOXDE7663	**An element's or attribute's format definition xs:date does not match the Adabas field definition**
Explanation	An element defined as xs:date must be mapped to an ADABAS field with format P4.
Action	Adapt the schema to the corresponding Adabas definition.

INOXDE7664	**An element's or attribute's format definition xs:dateTime does not match the Adabas field definition**
Explanation	The element which is defined as xs:dateTime must be mapped to an Adabas field with format P7.
Action	Adapt the schema definition to the corresponding Adabas format.

INOXDE7665	**(c-props-correct.1) An <xs:keyref> refers to an unknown <xs:key>**
Explanation	The 'refer' attribute of <xs:keyref> must refer to a sibling node of type <xs:key> with a matching value of its 'name' attribute.
Action	Correct the schema document.

INOXDE7666	**(c-props-correct.2) Invalid cardinality of <xs:field> child nodes of <xs:keyref>**
Explanation	If the {identity-constraint category} is keyref, the cardinality of the {fields} must equal that of the {fields} of the {referenced key}.
Action	Correct the schema document.

INOXDE7667	**(e-props-correct.3) The 'substitutionGroup' resolves to an unknown or invalid global element declaration**
Explanation	The 'substitutionGroup' attribute of an element declaration, E1, must resolve to a global element, say E2, whose effective 'block' attribute, i.e. the substitution group exclusions do not contain the value "substitution". The {type definition} of E1 must be validly derived from the {type definition} of E2, using a derivation method not given in the effective 'block' attribute.
Action	Adapt the schema to match this constraint.

INOXDE7668	**(cos-equiv-derived-ok-rec.1) Invalid relation of types of current element and its substitution group affiliate**
Explanation	The derivation method of the type of the current element must be derived from the type of the substitution group affiliate's (i.e. the global element referenced by the 'substitutionGroup' attribute) type. The derivation method must be compatible with the substitution group exclusions defined by the 'block' attribute of the affiliate and the 'blockDefault' attribute of the respective schema node.
Action	Adapt schema to meet this constraint.

INOXDE7669	**(e-props-correct.5) Found circular substitution group**
Explanation	Circular substitution groups are disallowed. That is, it must not be possible to return to an element declaration by repeatedly following the {substitution group affiliation} property.
Action	Modify the schema to fulfill the constraint.

INOXDE7670 **The 'final' attribute of a simple or complex type definition is more restrictive in the new schema compared to the old schema**

Explanation The 'final' attribute must not become more restrictive.

Action Either adapt the value of the 'final' attribute or use instance validation when updating the schema.

INOXDE7671 **A type definition has been set to abstract in the new schema**

Explanation When setting a type definition to abstract, this might cause documents to be invalid with respect to the new schema.

Action Either make the type definition non-abstract as in the old schema or use instance validation when updating the schema.

INOXDE7672 **An element declaration has been set to abstract in the new schema**

Explanation When setting an element declaration to abstract, this might cause documents to be invalid with respect to the new schema.

Action Either make the element declaration non-abstract as in the old schema or use instance validation when updating the schema.

INOXDE7673 **A complex type definition's 'block' attribute has been made more restrictive in the new schema**

Explanation When making a complex type definition's 'block' attribute more restrictive, this might cause documents to be invalid with respect to the new schema.

Action Either set the complex type definition's 'block' attribute as in the old schema or use instance validation when updating the schema.

INOXDE7674 **An element declaration's 'block' attribute has been made more restrictive in the new schema**

Explanation When making an element declaration's 'block' attribute more restrictive, this might cause documents to be invalid with respect to the new schema.

Action Either set the element declaration's 'block' attribute as in the old schema or use instance validation when updating the schema.

INOXDE7675 **An element's 'nillable' attribute was set to false in new schema**

Explanation If an element's 'nillable' attribute is set to false during a schema update, existing documents may become invalid.

Action Either leave the element declaration's 'nillable' attribute unchanged or use instance validation for schema update.

INOXDE7676	**Mismatch of identity constraints found during schema update**
Explanation	It is not possible to modify existing or add new identity constraints during a schema update without using instance validation.
Action	Either do not add or modify identity constraints during schema update, or use instance validation.

INOXDE7677	**An elements 'substitutionGroup' attribute was omitted or modified during schema update.**
Explanation	An element's 'substitutionGroup' attribute may not be omitted or modified during schema update unless instance validation is being used.
Action	Either leave the 'substitutionGroup' attribute as is or use instance validation during schema update.

INOXDE7680	**(length valid restriction) the length facet has been changed compared to the length facet of the base type**
Explanation	It is an error if length is among the members of {facets} of {base type definition} and {value} is not equal to the {value} of the parent length.
Action	Modify the schema accordingly.

INOXDE7681	**(maxLength valid restriction) the maxLength facet has been increased compared to the maxLength facet of the base type**
Explanation	It is an error if maxLength is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxLength.
Action	Modify the schema accordingly.

INOXDE7682	**(minLength valid restriction) the minLength facet has been decreased compared to the minLength facet of the base type**
Explanation	It is an error if minLength is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minLength.
Action	Modify the schema accordingly.

INOXDE7683	**(totalDigits valid restriction) the totalDigits facet has been increased compared to the totalDigits facet of the base type**
Explanation	It is an error if totalDigits is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent totalDigits.
Action	Modify the schema accordingly.

INOXDE7684 **(fractionDigits valid restriction) the fractionDigits facet has been increased compared to the fractionDigits facet of the base type**

Explanation It is an error if fractionDigits is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent totalDigits

Action Modify the schema accordingly.

INOXDE7685 **(maxExclusive valid restriction) the maxExclusive facet has been increased compared to the maxExclusive facet of the base type**

Explanation It is an error if any of the following conditions is true: 1. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxExclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxInclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minInclusive 4. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive

Action Modify the schema accordingly.

INOXDE7686 **(maxInclusive valid restriction) the maxInclusive facet has been increased compared to the maxInclusive facet of the base type**

Explanation It is an error if any of the following conditions is true: 1. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxInclusive 2. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 4. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive

Action Modify the schema accordingly.

INOXDE7687 **(minExclusive valid restriction) the minExclusive facet has been increased compared to the minExclusive facet of the base type**

Explanation It is an error if any of the following conditions is true: 1. minExclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minExclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater the {value} of the parent maxInclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 4. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive

Action Modify the schema accordingly.

INOXDE7688 **(minInclusive valid restriction) the minInclusive facet has been increased compared to the minInclusive facet of the base type**

Explanation It is an error if any of the following conditions is true: 1. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater the {value} of the parent maxInclusive 3. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive 4. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive

Action Modify the schema accordingly.

INOXDE7689 **(whiteSpace valid restriction) the whiteSpace facet has been changed to an invalid value compared to the whiteSpace facet of the base type**

Explanation It is an error if whiteSpace is among the members of {facets} of {base type definition} and any of the following conditions is true: 1. {value} is replace or preserve and the {value} of the parent whiteSpace is collapse 2. {value} is preserve and the {value} of the parent whiteSpace is replace

Action Modify the schema accordingly.

INOXDE7690 **(facet fixed) attempted to specify a different value for a facet which has fixed="true" in the base type definition**

Explanation The value of the facet differs from the value of the facet in the base type definition.

Action Omit the facet in the derived value or remove fixed="true" from the base type definition.

INOXDE7696 **Invalid change of schema-required property of collection**

Explanation A collection must be either schemaless or schemas are required for all documents to be stored. It is not allowed to change the schema-required property.

Action Adapt the collection description correspondingly.

INOXDE7697 **Could not create schemaless doctype in collection ino:etc**

Explanation It is not possible to have two schemaless doctypes in collection 'ino:etc' with the same lexical QName but different namespace of the root element.

Action A workaround is to change the namespace prefix of the root element of the first instance to be inserted in a new implicit doctype.

INOXDE7698	**(c-selector-xpath) Found invalid value of xpath attribute in definition of selector of identity constraint**
Explanation	The xpath attribute of the selector of an identity constraint must adhere to the (c-selector-xpath) constraint.
Action	Fix the value of the xpath attribute: all name tests must use valid QNames, all namespace prefixes must be declared, no attribute steps allowed.

INOXDE7699	**(c-fields-xpaths) Found invalid value of xpath attribute in definition of selector of identity constraint**
Explanation	The xpath attribute of all fields of an identity constraint must adhere to the (c-fields-xpaths) constraint.
Action	Fix the value of the xpath attribute: all name tests must use valid QNames, all namespace prefixes must be declared, an attribute step is only allowed at the last position.

INOXDE7700	**successful document validation**
Explanation	The document validated without error.
Action	No action required.

INOXDE7701	**memory allocation failed**
Explanation	Memory allocation failed during document validation.
Action	Please contact your software supplier.

INOXDE7702	**internal error**
Explanation	An internal processing error occurred during document validation.
Action	Please contact your software supplier.

INOXDE7703	**validation has detected an error in document**
Explanation	The document validation has discovered some invalid document content.
Action	Modify your document.

INOXDE7704	**(Parse error): document not well-formed**
Explanation	The document content is not well-formed.
Action	Modify your document

INOXDE7705	**(Parse error): junk data**
Explanation	The document contains junk data after the document content.
Action	Modify your input stream.

INOXDE7706	**(Parse error): close element error**
Explanation	The document contains a closing tag that does not match opening tag.
Action	Modify your document

INOXDE7707	**(Parse error): multiple attr**
Explanation	The document contains multiple occurrences of the same attribute.
Action	Modify your document

INOXDE7708	**Invalid root error**
Explanation	Tamino allows only insertion of documents with root elements whose names correspond to the name of some doctype in the collection where you tried to insert the current document.
Action	Modify your document or schema.

INOXDE7709	**Errors detected during document validation**
Explanation	Errors were detected during document validation.
Action	Please either modify your XML schema or fix errors in your document(s).

INOXDE7710	**(cvc-complex-type.2.1): empty content error**
Explanation	The schema requires empty element content but some content was detected.
Action	Modify your document or schema.

INOXDE7711	**(cvc-complex-type.2.3): mixed content error**
Explanation	The schema does not allow mixed element content but some mixed content was detected.
Action	Modify your document or schema.

INOXDE7712 **(cvc-complex-type.4): required attribute missing**

Explanation The schema requires an attribute that is not present in document.

Action Modify your document or schema.

INOXDE7713 **(cvc-wildcard.2): undeclared wildcard element**

Explanation Schema contains ANY with processContent = strict but element content's name does not match any globally declared element.

Action Modify your document or schema.

INOXDE7714 **(cvc-id.1): undefined IDREF value**

Explanation The document contains an IDREF value which does not exist as an ID value.

Action Modify your document.

INOXDE7715 **(cvc-id.2): duplicate ID value**

Explanation The document contains multiple copies of the same ID value.

Action Modify your document.

INOXDE7716 **(cvc-assess-attr.1): undeclared attribute**

Explanation No matching declaration can be found in the schema for an attribute, neither as an explicitly named attribute nor as attribute wildcard.

Action Modify your document.

INOXDE7717 **(cvc-type.3.1.1): invalid attribute**

Explanation A simple type description in the schema does not allow attributes here.

Action Modify your document.

INOXDE7718 **(cvc-type.3.1.2): invalid element content**

Explanation A simple type description in the schema does not allow element children here.

Action Modify your document.

INOXDE7719 **(cvc-particle): content of element does not match a particle description**

Explanation Element content cannot be successfully validated against a particle description in schema.

Action Modify your document.

INOXDE7720	**(cvc-particle.1.1): element content missing, minOccurs constraint violation in wildcard declaration**
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.

INOXDE7721	**(cvc-particle.1.2): too much element content, maxOccurs constraint violation in wildcard declaration**
Explanation	The length of the element content sequence does not satisfy the maxOccurs constraint of the wildcard declaration.
Action	Modify your document.

INOXDE7722	**(cvc-particle.2.1): element content missing, minOccurs constraint violation in element declaration**
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.

INOXDE7723	**(cvc-particle.2.2): too much element content, maxOccurs constraint violation in element declaration**
Explanation	The length of the element content sequence does not match the maxOccurs constraint for the element declaration.
Action	Modify your document.

INOXDE7724	**(cvc-particle.3.1): element content missing, minOccurs constraint violation in all model group declaration**
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.

INOXDE7725	**(cvc-particle.3.1): element content missing, minOccurs constraint violation in choice model group declaration**
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.

INOXDE7726 **(cvc-particle.3.1): element content missing, minOccurs constraint violation in sequence model group declaration**

Explanation The length of the element content sequence does not satisfy the minOccurs constraint.

Action Modify your document.

INOXDE7727 **(cvc-particle.3.2): too much element content, maxOccurs constraint violation in all model group declaration**

Explanation The length of the element content sequence does not satisfy the maxOccurs constraint of the all model group declaration.

Action Modify your document.

INOXDE7728 **(cvc-particle.3.2): too much element content, maxOccurs constraint violation in choice model group declaration**

Explanation The length of the element content sequence does not satisfy the maxOccurs constraint of the choice model group declaration.

Action Modify your document.

INOXDE7729 **(cvc-particle.3.2): too much element content, maxOccurs constraint violation in sequence model group declaration**

Explanation The length of the element content sequence does not satisfy the maxOccurs constraint of the sequence model group declaration.

Action Modify your document.

INOXDE7730 **(cvc-model-group.1):invalid end of sequence**

Explanation A sequence does not contain all required elements. In particular, the sequence ends without containing all required elements.

Action Modify your document.

INOXDE7731 **(cvc-model-group.1):invalid sequence**

Explanation A sequence does not contain all required elements.

Action Modify your document.

INOXDE7732	**(cvc-model-group.2):invalid choice**
Explanation	An element's child node does not match any choice in schema.
Action	Modify your document.

INOXDE7733	**(cvc-model-group.3):invalid all - missing element**
Explanation	An element's child node does not contain all required children of the all model group in the schema.
Action	Modify your document.

INOXDE7734	**(cvc-model-group.3):invalid all - undeclared element**
Explanation	An element's child node does not match any node declared in the all model group in the schema.
Action	Modify your document.

INOXDE7735	**(cvc-model-group.3):invalid all - too many child elements**
Explanation	All allowed elements in an all model group already appeared, but there are more illegal child elements.
Action	Modify your document.

INOXDE7736	**(cvc-model-group.3):invalid all - repeated occurrence of one element**
Explanation	Every child element in an all model group may appear at most once, but here the element appears more often.
Action	Modify your document.

INOXDE7737	**(cvc-wildcard-namespace): invalid namespace with respect to namespace constraint of wildcard**
Explanation	For namespace="##other" a non-absent namespace is required, which differs from the targetNamespace of the schema. For namespace="##targetNamespace" the namespace must match the current schema's targetNamespace. For namespace="##local" the element or attribute matching vs. the wildcard must not belong to any namespace. If the namespace attribute of the wildcard contains a list of URIs the namespace of the element or attribute matching vs. the wildcard must match one of the URIs in the list.
Action	Modify your document or schema.

INOXDE7738 **(cvc-wildcard-namespace.2.3): invalid namespace for wildcard with namespace="##other"**

Explanation The namespace of an element or attribute does not differ from the current schema's targetNamespace as required by namespace='##other' specified in a wildcard (xs:any or xs:anyAttribute).

Action Modify your document.

INOXDE7739 **(cvc-wildcard-namespace.3): invalid namespace for wildcard with namespace="##local"**

Explanation An element or attribute belongs to a namespace in contradiction to the namespace="##local" attribute of a wildcard (xs:any or xs:anyAttribute).

Action Modify your document.

INOXDE7740 **(cvc-complex-type.2.4): element child error**

Explanation The list of child elements could not to be partitioned in a way that it becomes valid with respect to the content type's particle.

Action Modify your document or schema.

INOXDE7741 **A namespace prefix conflict was detected when attempting to insert default or fixed value**

Explanation A namespace prefix used in a value constraint for a node whose datatype is xs:QName, xs:NOTATION or a derived type cannot be associated with the intended URI as the document already contains a namespace declaration for that prefix mapped to a different URI. Note that the default namespace is always assumed to be used.

Action Adapt the document to be stored or the fragment to be inserted to avoid conflict.

INOXDE7742 **(cvc-elt.4.3) The local type definition given by the xsi:type attribute is not validly derived from the type definition as of the underlying schema**

Explanation The local type definition given by the xsi:type attribute must be derived from the type definition as of the underlying schema. Derivation methods listed in the attribute named "block" of the element declaration or the associated complex type definition may not be used.

Action Either modify the schema by changing or removing the "block" attribute of the element declaration or complex type definition, or modify or remove the xsi:type attribute from the document to be stored.

INOXDE7743	**(cvc-elt.2) For an element information item to be locally valid with respect to an element declaration the declaration's abstract must be 'false'**
Explanation	Found an element declaration which is abstract when attempting to validate an element.
Action	Change the value of the 'abstract' property of the respective element declaration.

INOXDE7744	**(cvc-complex-type.1) For an element information item to be locally valid with respect to a complex type definition the type definition's abstract must be 'false'**
Explanation	Attempted to validate an element against a complex type definition which is abstract.
Action	Either make the type definition non-abstract, or use the xsi:type attribute in the XML document referring to a non-abstract derived type.

INOXDE7745	**(cvc-identity-constraint.3) An <xs:field> of an identity constraint caused multiple matching nodes or the respective node does not have a simple type**
Explanation	For each node in the target node set of an identity constraint, all of the {fields} for a selected context node evaluate to either an empty node-set or a node-set with exactly one member, which must have a simple type.
Action	Check the XML document or remove the identity constraint from the schema.

INOXDE7746	**(cvc-identity-constraint.4.1) Found multiple occurrence of same key-sequence for <xs:unique> identity constraint**
Explanation	No two members of the qualified node set of an <xs:unique> may have key-sequences whose members are pairwise equal.
Action	Check the XML document or remove the identity constraint from the schema.

INOXDE7747	**(cvc-identity-constraint.4.2.1) A field of an <xs:key> identity constraint evaluates to an empty node-set**
Explanation	For <xs:key>, all the {fields} must evaluate to a node-set with exactly one member.
Action	Check the XML document or remove the identity constraint from the schema.

INOXDE7748	**(cvc-identity-constraint.4.2.2) Found multiple occurrence of same key-sequence for <xs:key> identity constraint**
Explanation	No two members of the qualified node set of an <xs:key> may have key-sequences whose members are pairwise equal.
Action	Check the XML document or remove the identity constraint from the schema.

INOXDE7749 **(cvc-identity-constraint.4.3) Could not locate matching key sequence in node table of <xs:key> identity constraint referenced by <xs:keyref>**

Explanation For each member of the qualified node set of a <xs:keyref> there must be a corresponding entry in the node table of the referenced <xs:key>.

Action Check the XML document or remove the identity constraint from the schema.

INOXDE7750 **(cvc-elt.3.1) Attribute 'xsi:nil' not allowed if the 'nillable' attribute of the element declaration is not set to 'true'**

Explanation The predefined 'xsi:nil' attribute is only allowed on an element information item if the corresponding element declaration in the schema has its 'nillable' attribute to 'true'.

Action Check the schema or remove the 'xsi:nil' attribute from the document.

INOXDE7751 **(cvc-elt.3.2.1) Found character or element content inside element information item with xsi:nil='true'**

Explanation If an element has the xsi:nil='true' attribute, it must not have any character or element content.

Action Modify the document accordingly.

INOXDE7752 **(cvc-elt.3.2.2) Element declaration corresponding to element information item with xsi:nil='true' attribute has a fixed value constraint**

Explanation For an element information item with xsi:nil='true' attribute the corresponding element declaration in the schema must not have a fixed value constraint.

Action Remove either the 'nillable' or the 'fixed' attribute from the element declaration in the schema.

INOXDE7753 **(cos-equiv-derived-ok-rec.2.1) The effective blocking constraint of the element to be substituted contains 'substitution'**

Explanation The blocking constraint of an element to be substituted during validation must not contain 'substitution'.

Action Adapt the XML document or modify the 'block' or 'blockDefault' attributes in the schema to become consistent with the constraint.

INOXDE7754 **(cos-equiv-derived-ok-rec.2.3) Type derivation between type of element to be substituted and type of the substituting element is blocked by the effective 'block' attribute of the element to be substituted**

Explanation The type of the substituting element must be derived from the type of the element to be substituted by means of restriction and/or extension, unless one of those derivation methods is being blocked by the 'block' attribute (if present) of the element to be substituted, or the 'blockDefault' attribute of the parent schema.

Action	Adapt the XML document or modify the 'block' or 'blockDefault' attributes in the schema to become consistent with the constraint.

INOXDE7761	**(cvc-datatype-valid) Overflow detected during validation**
Explanation	A value overflow has been detected during validation against the XML schema.
Action	Ensure that the values adhere to datatype specific limits.

INOXDE7762	**(cvc-datatype-valid) Value out of range detected during validation**
Explanation	A value smaller than the valid minimum or larger than the allowed maximum has been detected during validation against the XML schema.
Action	Ensure that the values adhere to the datatype specific minimum and maximum.

INOXDE7763	**(cvc-datatype-valid) An invalid value has been found during validation**
Explanation	A value outside the lexical space has been detected during validation against the XML schema.
Action	Ensure that the value adheres to the datatype specific lexical space.

INOXDE7764	**(cvc-enumeration-valid) A value not defined in the respective enumeration has been found during validation.**
Explanation	A value which is not listed in the respective enumeration has been detected during validation against the XML schema.
Action	Ensure that the value matches one of the enumeration values specified in the XML schema.

INOXDE7765	**(cvc-length-valid) Facet 'length' was violated by a value during validation.**
Explanation	A value whose length does not match the 'length' facet has been detected during validation against the XML schema.
Action	Ensure that the value's length matches the restriction given by the schema.

INOXDE7766	**(cvc-attribute.4): fixed value error**
Explanation	An attribute declaration in schema requires a fixed value which is different from given value in document.
Action	Modify your document.

INOXDE7767 **(cvc-elt.5.2.2.2.1): fixed value error**

Explanation The element declaration in schema requires a fixed value which is different from given value in document.

Action Modify your document.

INOXDE7768 **(cvc-au): fixed value error**

Explanation The attribute use declaration in the schema requires a fixed value which is different from the given value in the document.

Action Modify your document.

INOXDE7769 **(cvc-elt.5.2.2.2.2): fixed value error**

Explanation The element declaration in the schema requires a fixed value which is different from given value in document.

Action Modify your document.

INOXDE7770 **(cvc-minLength-valid) Facet 'minLength' was violated by a value during validation**

Explanation A value whose length is less than the 'minLength' facet has been detected during validation against the XML schema.

Action Ensure that the value's length matches the restriction given by the schema.

INOXDE7771 **(cvc-maxLength-valid) Facet 'maxLength' was violated by a value during validation**

Explanation A value whose length is greater than the 'maxLength' facet has been detected during validation against the XML schema.

Action Ensure that the value's length matches the restriction given by the schema.

INOXDE7772 **(cvc-pattern-valid) Facet 'pattern' was violated by a value during validation**

Explanation A value whose pattern does not match the 'pattern' facet has been detected during validation against the XML schema.

Action Ensure that the value's pattern matches the restriction given by the schema.

INOXDE7773 **(cvc-enumeration-valid) Facet 'enumeration' was violated by a value during validation**

Explanation A value has been found which does not match the valid values specified by the 'enumeration' facet, during validation against the XML schema.

Action Ensure that the value matches the restriction given by the schema.

INOXDE7774	**(cvc-maxInclusive-valid) Facet 'maxInclusive' was violated by a value during validation**
Explanation	A value has been found which is greater than the 'maxInclusive' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.

INOXDE7775	**(cvc-maxExclusive-valid) Facet 'maxExclusive' was violated by a value during validation**
Explanation	A value has been found which is greater or equal to the 'maxExclusive' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.

INOXDE7776	**(cvc-minInclusive-valid) Facet 'minInclusive' was violated by a value during validation**
Explanation	A value has been found which is lower than the 'minInclusive' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.

INOXDE7777	**(cvc-minExclusive-valid) Facet 'minExclusive' was violated by a value during validation**
Explanation	A value has been found which is less than or equal to the 'minExclusive' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.

INOXDE7778	**(cvc-totalDigits-valid) Facet 'totalDigits' was violated by a value during validation**
Explanation	A numerical value has been found with more digits than specified by the 'totalDigits' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.

INOXDE7779	**(cvc-fractionDigits-valid) Facet 'fractionDigits' was violated by a value during validation**
Explanation	A numerical value has been found with more fractional digits (i.e. to the right of the decimal point) than specified by the 'fractionDigits' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.

INOXDE7780 **Divide by zero error**

Explanation An attempt was made to divide by zero. Division by zero is mathematically undefined.

Action Make sure that no division by zero occurs.

INOXDE7781 **Invalid or unsupported attribute found**

Explanation An attribute was found that is not supported by Tamino.

Action In order to enable xsi:type processing you have to set the server parameter "reject xsi:type" to "no".

INOXDE7782 **Namespace prefix is bound to an invalid URI**

Explanation A namespace prefix must be bound to a non-empty URI in a namespace declaration. In addition, some prefixes must be bound to a fixed URI.

Action Ensure e.g. that the prefix 'xml' is bound to 'http://www.w3.org/XML/1998/namespace', and that 'ino' is bound to 'http://namespaces.softwareag.com/tamino/response2'.

INOXDE7783 **The namespace prefix in an element or attribute value is not declared**

Explanation If an element's or attribute's type is xs:QName or xs:NOTATION, the respective prefix must be declared in the schema document.

Action Add the missing namespace declaration.

INOXDE7784 **Invalid namespace prefix**

Explanation A namespace prefix is invalid.

Action Modify the namespace definition and repeat the request.

INOXDE7785 **The datatype referenced by xsi:type is unknown**

Explanation The value of the xsi:type attribute must reference a datatype predefined by XML Schema or a user-defined global datatype.

Action Check the type reference via xsi:type in XML document.

INOXDE7786 **Invalid prefix bound to URI**

Explanation The URI cannot be bound to the given namespace prefix.

Action Use an appropriate prefix.

INOXDE7787 **Invalid value of 'xsi:nil' attribute**

Explanation The value of the 'xsi:nil' attribute must be a valid boolean, i.e. 'true', 'false', '1', or '0'.

Action Modify the document accordingly.

INOXDE7821 **Class not found**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7822 **Duplicated class name**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7823 **Illegal cast**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7824 **Internal API error**

Explanation Tamino schema tree internal error.

Action Please contact your software supplier.

INOXDE7827 **No memory**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7828 **No such element**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7829 **Not implemented**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7830 **Too many classes**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7831 **XML parser error**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7833 **Operation failed**

Explanation An internal error occurred.

Action Please contact your software supplier.

INOXDE7856 **Buffer size exceeded**

Explanation Tamino schema tree error message.

Action Please contact your system administrator.

INOXDE7860 **Internal error: invalid node type**

Explanation This is a Tamino schema tree error message.

Action Please contact your system administrator.

INOXDE7861 **Index out of range**

Explanation Tamino schema tree error message.

Action Please contact your system administrator.

INOXDE7862 **User abort**

Explanation Tamino schema tree internal error message.

Action Please contact your system administrator.

INOXDE7865 **Schema cache: access denied**

Explanation Schema cache: access denied.

Action Please contact your software supplier.

INOXDE7867	**Internal error: schema not in cache**
Explanation	Internal error: schema not in cache.
Action	Please contact your software supplier.

INOXDE7868	**Internal error: write lock expected**
Explanation	Internal error: write lock expected.
Action	Please contact your software supplier.

INOXDE7869	**Internal error: schema not locked**
Explanation	Internal error: schema not locked.
Action	Please contact your software supplier.

INOXDE7883	**(p-props-correct.2.1) If maxOccurs has a numeric value, then minOccurs must not be greater than maxOccurs**
Explanation	If maxOccurs has a numeric value, then minOccurs must not be greater than maxOccurs.
Action	Modify the XML schema accordingly.

INOXDE7884	**(p-props-correct.2.2) If maxOccurs has a numeric value, then maxOccurs must be greater than or equal to 1**
Explanation	If maxOccurs has a numeric value, then maxOccurs must be greater than or equal to 1.
Action	Modify the XML schema accordingly.

INOXDE7885	**(src-attribute.2) use must have value optional**
Explanation	If the attribute's "default" and "use" attributes are both present, then "use" must have the value "optional".
Action	Modify the XML schema accordingly.

INOXDE7886	**(src-attribute.4) For attribute the type and simpleType must not both be present**
Explanation	For attribute, the type and simpleType must not both be present.
Action	Modify the XML schema accordingly.

INOXDE7887	**(src-element.1) For element the attributes default and fixed must not both be present**
Explanation	For element, the attributes "default" and "fixed" must not both be present.
Action	Modify the XML schema accordingly.

INOXDE7888	**(src-element.3) For element the attributes type and either simpleType or complex Type are mutually exclusive**
Explanation	For element, the attributes "type" and either "simpleType" or "complex Type" are mutually exclusive.
Action	Modify the XML schema accordingly.

INOXDE7889	**(src-element.2.1) For element either the attribute ref or name must be present, but not both**
Explanation	For element, either the attribute ref or name must be present, but not both.
Action	Modify the XML schema accordingly.

INOXDE7890	**(src-element.2.2) For element if parent is not schema and attribute ref is present, only attributes minOccurs, maxOccurs and id are allowed in addition to ref**
Explanation	If the parent of the element is not schema and the attribute ref is present, then all of <xs:complexType>, <xs:simpleType>, <xs:key>, <xs:keyref>, <xs:unique>, nillable, default, fixed, form, block and type must be absent.
Action	Modify the XML schema accordingly.

INOXDE7891	**(valid-data-types.1) The type of nodes and base attribute of restriction nodes may only be of the supported types**
Explanation	The type of nodes and base attribute of restriction nodes may only be of the supported types, namely: date, decimal, double, float, integer, short, SQLNumeric,, SQLVarchar, string, time, timeinstant, ID, IDREF, IDREFS, NMTOKEN, NMTOKENS. No user-defined complexType or simpleType are allowed for type.
Action	Modify the XML schema accordingly.

INOXDE7895	**(valid-data-types.2) The facet is not valid for the base datatype**
Explanation	A facet has been specified which is not supported for the base datatype of a restriction.
Action	Modify the XML schema accordingly.

INOXDE7900	**(length and minLength or maxLength) Conflict between length facet and either minLength or maxLength**
Explanation	It is an error for both length and either of minLength or maxLength to be members of {facets}, unless they are specified in different derivation steps in which case the following must be true: the {value} of minLength <= the {value} of length <= the {value} of maxLength.
Action	Modify the XML schema accordingly.

INOXDE7901	**(fractionDigits less than or equal to totalDigits) The value of the fractionDigits facet is greater than the value of totalDigits**
Explanation	It is an error for fractionDigits to be greater than totalDigits.
Action	Modify the XML schema accordingly.

INOXDE7902	**The root node of a doctype has a non-trivial substitution group**
Explanation	The root node of a doctype must not have a non-trivial substitution group. The QName of the root element of an XML document stored in a doctype must be identical to the doctype's QName.
Action	Remove the substitutionGroup reference to the root node from the schema.

INOXDE7906	**Found illegal logical or physical property for shadowXML doctype**
Explanation	It is not allowed to specify certain logical or physical properties, e.g. XNode mapping, for a shadowXML doctype.
Action	Remove the illegal property below <tsd:logical> and <tsd:physical> for the shadowXML doctype.

INOXDE7907	**(src-resolve.1.3) The ref attribute of an element needs to reference an existing global element**
Explanation	The ref attribute of an element needs to reference an existing global element.
Action	Modify the XML schema accordingly.

INOXDE7908	**Found logical or physical properties for nonXML doctype**
Explanation	It is not allowed to specify logical or physical properties for a nonXML doctype.
Action	Remove <tsd:logical> and <tsd:physical> for the nonXML doctype.

INOXDE7909	**(cos-nonambig.1) Unique Particle Attribution failure**
Explanation	A content model must be formed such that during validation of an element information item sequence, the particle contained directly, indirectly or implicitly therein with which to attempt to validate each item in the sequence in turn can be uniquely determined without examining the content or attributes of that item, and without any information about the items in the remainder of the sequence.
Action	Modify the XML schema accordingly.

INOXDE7910	**(cos-all-limited.1.2) All group limitation failure**
Explanation	The cardinality of an all-model group must be exactly one.
Action	Modify the XML schema accordingly.

INOXDE7911	**(cos-all-limited.2) All group limitation failure**
Explanation	The maximum cardinality of all elements in all-model group must be 0 or 1.
Action	Modify the XML schema accordingly.

INOXDE7912	**(src-attribute.1) For attribute declarations, their attributes default and fixed must not both be present**
Explanation	For attribute declarations, the attributes "default" and "fixed" must not both be present.
Action	Modify the XML schema accordingly.

INOXDE7913	**(src-attribute.3.1) Either attribute ref or name must be present, but not both**
Explanation	Either the attribute "ref" or the attribute "name" must be present, but not both.
Action	Modify the XML schema accordingly.

INOXDE7914	**(src-attribute.3.2) If attribute's parent is not schema and ref is present, <simpleType>, form and type are not allowed**
Explanation	The form or type attribute as well as a simpleType cannot be specified with attribute declarations if the parent is not the schema node and the ref attribute is present.
Action	Modify the XML schema accordingly.

INOXDE7915	**The doctype name needs to be unique within a collection**
Explanation	The doctype name needs to be unique within a collection.
Action	Modify the XML schema accordingly.

INOXDE7916	**The given path must exist in the current schema**
Explanation	The given path must exist in the current schema.
Action	Modify the XML schema accordingly.

INOXDE7917	**For each doctype name where the doctype is not of plain non-XML type there must be a matching global element with a matching qualified name**
Explanation	For each doctype name where the doctype is not of plain non-XML type there must be a matching global element with a matching qualified name. In particular, for non-XML doctypes with non-XML indexing via a shadow XML document a matching global element must exist.
Action	Modify the XML schema accordingly.

INOXDE7918	**For each doctype name where the doctype is of type nonXML there must not be a matching global element with the same name**
Explanation	For each doctype name where the doctype is of type non-XML there must not be a matching global element with the same name.
Action	Modify the XML schema accordingly.

INOXDE7919	**For accessOptions at least one of read, insert, update or delete needs to be given, but no duplicate entries of these are allowed**
Explanation	For accessOptions at least one of read, insert, update or delete needs to be given, but no duplicate entries of these are allowed.
Action	Modify the XML schema accordingly.

INOXDE7920	**Invalid node name**
Explanation	The name of an element or attribute does not match the repository naming conventions.
Action	Change the name of element or attribute.

INOXDE7921	**Attempted to re-use a schema specifying physical properties from a schema belonging to a different collection**
Explanation	This constraint has been introduced in order to prevent database inconsistencies. It may vanish in a future version of Tamino.
Action	Change the collection name either of the referenced or the referring schema.

INOXDE7922 **The given path must exist in the current Schema and lead to the element or attribute for which it is specified**

Explanation The given path must exist in the current schema and lead to the element or attribute for which it is specified.

Action Modify the XML schema accordingly.

INOXDE7923 **No XPath expression may occur twice for one node to avoid conflicting mappings**

Explanation No XPath expression may occur twice for one node in order to avoid conflicting mappings (not even if it specifies the same mapping).

Action Modify the XML schema accordingly.

INOXDE7924 **At most one elementInfo or attributeInfo may have only empty or a nonexistent which-element, which is taken as the default mapping**

Explanation At most one elementInfo or attributeInfo may have only empty or a non-existent which element, which is taken as the default mapping (Note: empty which elements are ignored, so an elementInfo which has both empty and filled which elements is interpreted as an elementInfo with filled which elements).

Action Modify the XML schema accordingly.

INOXDE7925 **Below Schema there may only be one appinfo node which defines Tamino mappings**

Explanation Below Schema there may only be one appinfo node which defines Tamino mappings.

Action Modify the XML schema accordingly.

INOXDE7926 **Below Schema there must be a schemaInfo node but no elementInfo or attributeInfo nodes**

Explanation Below Schema there must be a schemaInfo node but no elementInfo or attributeInfo nodes.

Action Modify the XML schema accordingly.

INOXDE7927 **Below Element there may only be one appinfo node which defines Tamino mappings**

Explanation Below Element there may only be one appinfo node which defines Tamino mappings.

Action Modify the XML schema accordingly.

INOXDE7928	**Below Element there may be only elementInfo node but no schemaInfo or attributeInfo nodes**
Explanation	Below Element there may be only elementInfo node but no schemaInfo or attributeInfo nodes.
Action	Modify the XML schema accordingly.

INOXDE7929	**Below Attribute there may only be one appinfo node which defines Tamino mappings**
Explanation	Below Attribute there may only be one appinfo node which defines Tamino mappings.
Action	Modify the XML schema accordingly.

INOXDE7930	**internal error**
Explanation	While processing a schema document an internal error occurred.
Action	Please contact your software supplier.

INOXDE7931	**An error occurred while processing a schema document**
Explanation	An error occurred during processing of a TSD3 schema document.
Action	Details may be supplied by a secondary error message or can be retrieved using the admin-command ino:CheckSchema(collection-name, schema-name) or ino:CheckSchema() for all schemas in all collections. Correct the schema and update it in the database.

INOXDE7932	**Errors occurred when checking constraints for schema document**
Explanation	A TSD3 schema document does not adhere to all relevant restrictions.
Action	Check the secondary error message for details.

INOXDE7933	**Version mismatch occurred during schema processing**
Explanation	An attempt was made to load a TSD3 schema into a TSD2 collection or vice versa.
Action	Ensure that used schema language levels are consistent within a single collection.

INOXDE7934	**Invalid schema document**
Explanation	The XML document does not contain a valid TSD3 schema.
Action	Ensure that the schema document is consistent with the Tamino schema definition language TSD3.

INOXDE7935 **Schema not found**

Explanation The referenced schema does not exist.

Action Check for the existence of the referenced TSD3 schema.

INOXDE7936 **Invalid define of system collection**

Explanation The schema to be defined refers to a collection reserved for system usage.

Action Choose a different collection name.

INOXDE7938 **Internal error: invalid or unknown version information**

Explanation Internal error occurred when retrieving or checking version information.

Action Please contact your software supplier.

INOXDE7939 **Invalid schema document**

Explanation The schema document contains an invalid or outdated format.

Action Check the schema document. Possibly you are using TSD2. If so, convert to TSD3 using the Tamino Schema Editor.

INOXDE7940 **Invalid modification of doctype: cannot switch between storage of XML, nonXML and indexed nonXML documents**

Explanation An error was detected when updating the schema: an attempt was made to modify between storage of XML, nonXML and indexed nonXML documents.

Action Check the secondary error message for the context where the error was detected.

INOXDE7941 **Must not omit doctype during schema update**

Explanation An error was detected when updating the schema: all doctypes defined in the original schema must occur in the new schema.

Action Check the secondary error message for the context where the error was detected. Either extend the new schema document or undefine the obsolete doctype(s) before the next attempt to update the schema.

INOXDE7942 **Cannot switch doctype to closed content via schema update**

Explanation It is not permitted to turn a doctype back to closed content if it had been configured for open content before.

Action In order to switch a doctype back to closed content mode you have to undefine and re-create the doctype and reload the data.

INOXDE7943 **Mismatch of minOccurs attribute during schema update**

Explanation An error was detected when updating the schema: the new value of the minOccurs attribute must be less than or equal to the old one.

Action Check the secondary error message the for context where the error was detected.

INOXDE7944 **Mismatch of maxOccurs attribute during schema update**

Explanation An error was detected when updating the schema: the new value of the the maxOccurs attribute must be greater than or equal to the old one. If it was previously unbounded, it must not be changed at all.

Action Check the secondary error message for the context where the error was detected.

INOXDE7945 **Mismatch of mapping detected during schema update**

Explanation An error was detected when updating the schema: a path containing mapping information which has been added in the new schema was already valid in the old schema.

Action Check the secondary error message for the context where the error was detected.

INOXDE7946 **Mismatch of element or attribute name detected during schema update**

Explanation An error was detected when updating the schema: names of corresponding elements or attributes in old and new schema are different.

Action Check the secondary error message for the context where the error was detected.

INOXDE7947 **Mismatch of element or attribute type detected during schema update**

Explanation An error was detected when updating the schema: types of corresponding elements or attributes in the old and new schema are different.

Action Check the secondary error message for the context where the error was detected.

INOXDE7948 **Mismatch of content model detected during schema update**

Explanation An error was detected when updating the schema: the content models are not equivalent.

Action Check the secondary error message for the context where the error was detected.

INOXDE7949 **Mismatch of content model of sequence detected during schema update**

Explanation An error was detected when updating the schema: the content model inside a sequence of the new schema contains an additional non-optional component.

Action Check the secondary error message for the context where the error was detected.

INOXDE7950 **Mismatch of enumeration detected during schema update**

Explanation An error was detected when updating the schema: it is only possible to add enumeration values in the new schema if there had been at least one enumeration value in the old schema.

Action Check the secondary error message for the context where the error was detected.

INOXDE7951 **Mismatch of fixed attribute detected during schema update**

Explanation An error was detected when updating the schema: the value of the fixed attribute of an element must not be changed.

Action Check the secondary error message for the context where the error was detected.

INOXDE7952 **Mismatch of "default which" detected during schema update**

Explanation An error was detected when updating the schema: no elementInfo or attributeInfo without a which element may be added in the new schema.

Action Check the secondary error message for the context where the error was detected.

INOXDE7953 **Invalid modification of processContents attribute detected during schema update**

Explanation An error was detected when updating the schema: the processContents attribute may only change from "strict" to "lax" to "skip".

Action Check the secondary error message for the context where the error was detected.

INOXDE7954 **Invalid modification of mixed attribute detected during schema update**

Explanation An error was detected when updating the schema: the mixed attribute may only change from "false" to "true".

Action Check the secondary error message for the context where the error was detected.

INOXDE7955 **Invalid modification of components of choice detected during schema update**

Explanation An error was detected when updating the schema: choice in the new schema must contain all components of choice in the old schema in arbitrary order. Additional components may be added for closed content. For open content, components may only be removed from the content model.

Action Check the secondary error message for the context where the error was detected.

INOXDE7956 **Invalid modification of components of sequence detected during schema update**

Explanation An error was detected when updating the schema: sequence in the new schema must contain all components of sequence in the old schema in the same order. Additional optional components with minOccurs=0 may be added in the case of closed content of the doctype. For open content, components may only be removed from the content model.

Action Check the secondary error message for the context where the error was detected.

INOXDE7957 **Invalid modification of element's or attribute's simpleType detected during schema update**

Explanation An error was detected when updating the schema: element or attribute may not be defined with simpleType in the old schema and without simpleType in the new schema or vice versa.

Action Check the secondary error message for the context where the error was detected.

INOXDE7958 **Invalid modification of element's complexType detected during schema update**

Explanation An error was detected when updating the schema: element or attribute may not be defined with complexType in the old schema and without complexType in the new schema or vice versa.

Action Check the secondary error message for the context where the error was detected.

INOXDE7960 **Invalid path in schema definition**

Explanation The specified path inside the which element is invalid for this schema.

Action Check the path and schema definition.

INOXDE7961 **Invalid path in schema definition**

Explanation The specified path inside the which element has an invalid syntax.

Action Check the path value.

INOXDE7962 **Invalid modification of attribute list detected during schema update**

Explanation An error was detected when updating the schema: all attributes defined for an element in the old schema must occur in the new schema in arbitrary order. Optional attributes may be added.

Action Check the secondary error message for the context where the error was detected.

INOXDE7963 **Additional attribute must be optional during schema update**

Explanation An error was detected when updating the schema: all additional attributes must be optional in the case of closed content. For open content, attributes may only be removed.

Action Check the secondary error message for the context where the error was detected.

INOXDE7964 **Mismatch of use attribute detected during schema update.**

Explanation An error was detected when updating the schema: the use attribute of an xsd:attribute may only be changed from "required" to "optional".

Action Check the secondary error message for the context where the error was detected.

INOXDE7965 **Invalid modification of components of all detected during schema update**

Explanation Invalid modification of components of all detected during schema update. Additional optional components may be added in the case of closed content. For open content, components may only be removed from the content model.

Action Please modify your XML schema.

INOXDE7966 **Mismatch of targetNamespace attribute detected during schema update**

Explanation The targetNamespace attribute may not be changed during a schema update.

Action Please adapt your schema.

INOXDE7967 **Mismatch of namespace declaration detected during schema update**

Explanation Namespace declarations may not be changed during a schema update.

Action Please adapt your schema.

INOXDE7968 **New global element detected during schema update**

Explanation Global elements may not be added during a schema update if there is an <xs:any> element by which they may be referred to implicitly.

Action Please check your schema.

INOXDE7969 **New global attribute detected during schema update**

Explanation Global attributes may not be added during a schema update if there is an <xs:anyAttribute> element they may be referred by implicitly.

Action Please check your schema.

INOXDE7970	**Invalid attempt to remove an attribute wildcard (xs:anyAttribute) during a schema update**
Explanation	An attribute wildcard may not be removed during a schema update.
Action	Please check your schema.

INOXDE7971	**Removed global element during schema update**
Explanation	Global elements may not be removed during a schema update if there is an <xs:any> element they may be referred by implicitly.
Action	Please check your schema.

INOXDE7972	**Removed global attribute during schema update**
Explanation	Global attributes may not be removed during a schema update if there is an <xs:anyAttribute> element they may be referred by implicitly.
Action	Please check your schema.

INOXDE7973	**Facet added during schema update**
Explanation	The new schema contains a facet which is not present in the existing schema.
Action	Consider removing the facet from the new schema or use instance validation.

INOXDE7974	**Attempted to make value of facet more restrictive during schema update**
Explanation	The new schema definition contains a facet with a value more restrictive than in the existing schema. This is not allowed by the restricting facet.
Action	Consider changing the value of the facet in the new schema or use instance validation.

INOXDE7975	**Restriction facet's value must not change during schema update**
Explanation	The new schema definition contains a facet with a value different from that in the existing schema. This is not allowed by the restricting facet.
Action	Consider changing the value of the facet in the new schema or use instance validation.

INOXDE7976	**Mismatch of pattern detected during schema update**
Explanation	An error was detected when updating the schema: It is only possible to add pattern values in the new schema if there had been at least one pattern value in the old schema. It is only possible to remove pattern values from the new schema if this results in having no pattern values in the new schema.
Action	Check the secondary error message for the context where the error was detected.

INOXDE7978 **Mismatch of namespace declarations found during schema update checks**

Explanation An attempt was made to modify the URI associated with a namespace prefix. This is based on namespace declarations in the schema document. Either a namespace declaration was omitted or the URI has been changed. This is not allowed because it would change the semantics of X-Query requests on namespace-clean doctypes.

Action Modify the schema accordingly.

INOXDE7979 **Invalid schema changes found when adding a unique constraint - no other schema changes are permitted**

Explanation When adding a unique constraint no other schema changes are permitted in the same schema update operation. It is also not permitted to add multiple unique constraints in a single schema update.

Action Either add a single unique constraint or perform other schema changes in separate steps.

INOXDE7980 **At least one doctype contains instances with xsi:type attributes. Schema update requires explicit validation.**

Explanation This error may show up e.g. if the set of global types is going to change due to the schema update. Thus, XML instances containing xsi:type attributes require re-validation. Note that this status of the doctype remains set even after the respective XML documents have been deleted.

Action Perform a schema update with instance validation (_mode=validate).

INOXDE7981 **Attempted to remove member of substitution group during schema update for doctype with closed content**

Explanation You cannot remove a member of a substitution group during a schema update for a doctype with closed content without instance validation.

Action Use instance validation during the schema update.

INOXDE7982 **Attempted to add member of substitution group during schema update for doctype with open content**

Explanation You cannot add a member of a substitution group during a schema update for a doctype with open content without using instance validation.

Action Use instance validation during the schema update.

INOXDE7988	**Failed to lock schema document.**
Explanation	A schema document could not be locked due to a parallel transaction.
Action	Check for parallel transaction using the same schema with a conflicting type of lock. Typically, commands modifying a schema require a write lock for the schema and will conflict with each other, or with other transactions having a read lock on the schema.

INOXDE7989	**Cannot define schema in schemaless collection**
Explanation	It is not allowed to define a schema if the collection is defined with schema use 'prohibited'.
Action	Use another collection - or just do not define schema at all. Schemaless collections (like ino:etc) allow documents to be stored without defining a schema. You may also change the collection for optional schema usage.

INOXDE7992	**Index migration for doctype 'doctype' in collection 'collection' failed with error code errorCode**
Explanation	This is an internal error.
Action	Please contact your software supplier.

INOXDE7993	**Schema operation failed because the same request has doctype already in use**
Explanation	Schemas cannot be modified or deleted from a server extension if the calling command has an affected doctype in use.
Action	Change your application.

INOXDE7996	**Doctype requires xsi:type migration - schema update requires instance validation**
Explanation	The given doctype contains documents with xsi:type attribute(s) that were stored in previous version of Tamino. As the processing of xsi:type was not complete in previous versions of Tamino up to version 4.2, explicit validation of the documents against the schema is required.
Action	Perform a schema update with instance validation (_MODE=validate). Depending on the type definitions being referenced by the xsi:type attribute, the original schema may need to be adapted, as the type being referenced by xsi:type must be validly derived from the default type of the respective element as given in the schema.

INOXDE7997 **Missing 'type' attribute in definition of computed index.**

Explanation The <tsd:computed> elements must have a 'type' attribute if it is not a compound index.

Action Fix the schema accordingly.

INOXDE7998 **Found unexpected 'type' attribute in definition of computed index with multiple components.**

Explanation For a compound computed index, i.e. with multiple components, only the component definitions may have a 'type' attribute.

Action Fix the schema accordingly.

INOXDE7999 **Found component of a computed index which does not have a simple type.**

Explanation The component of a computed index must have a simple type.

Action Fix the schema accordingly.

INOXDF7601 **XML initialization: failed to define collection/doctype, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXDF7613 **Unexpected error (rsp,line) occurred during op (parm).**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXDI7582 **The path specified in the xpath attribute of a field element may not be empty or start with a slash**

Explanation mp-valid-field.3: The path specified in the xpath attribute of a field element may not be empty or start with a slash.

Action Please change the schema and try to define it again.

INOXDI7608 **Upgrade system collections**

Explanation The system collections need to be upgraded.

Action No action required.

INOXDI7991	**Indexes of doctype 'doctype' in collection 'collection' have been migrated successfully**
Explanation	In the given doctype, all indexes marked for migration have been rebuilt successfully.
Action	No action required.

INOXDS7600	**Define 'doctype' in collection 'collection'**
Explanation	The given system doctype will be defined or upgraded.
Action	No action required.

INOXDS7602	**Define collection 'collection'**
Explanation	The given system collection will be defined or upgraded.
Action	No action required.

INOXDS7611	**Define missing collection objects**
Explanation	For all existing collections the respective objects are now being loaded.
Action	No action required.

INOXDW7678	**Usage of a non-field element as element or attribute in schema definition**
Explanation	Field is defined as phonetic, sub, super or hyper-descriptor in Adabas field definition.
Action	Check your schema definition.

INOXDW7990	**Doctype 'doctype' in collection 'collection' requires index migration**
Explanation	The referenced doctype contains nodes whose indexes should be newly created.
Action	Refer to the migration related topics in the Tamino documentation.

INOXDW7994	**Multipath index 'label' in doctype 'doctype' in collection 'collection' is marked as not available**
Explanation	A previous schema update or index repair option could not be finished successfully. The given multipath index is still marked as being not available, and cannot be used for the efficient evaluation of query results.
Action	Update the respective schema in Tamino. This will enforce a rebuild of the respective multipath index.

INOXDW7995 **Doctype 'doctype' in collection 'collection' requires xsi:type migration**

Explanation The given doctype contains documents with xsi:type attribute(s) that were stored in a previous version of Tamino. As the processing of xsi:type was not complete in previous Tamino versions up to version 4.2, explicit validation of the documents against the schema is required.

Action Perform a schema update with instance validation (_MODE=validate). Depending on the type definitions being referenced by the xsi:type attribute, the original schema may need to be adapted, as the type being referenced by xsi:type must be validly derived from the default type of the respective element as given in the schema.

INOXHA8259 **Start writing XML dump of database, writing to file filename**

Explanation The server has encountered an error situation which causes a crash. In order to enable error analysis, the server writes XML status information to a file in the reserved location.

Action Report the crash to your software supplier, together with the dump files in the reserved location.

INOXHE8152 **Web server ws: specified node host unknown (DNS rsp: rsp).**

Explanation The given web server on the given node is defined as one of the web servers that are allowed to communicate with this Tamino database. Unfortunately the Tamino database is not able resolve the specified node name.

Action Check whether the node name is correct. If it is correct, check whether DNS lookups may fail due to network problems. In this case, use the IP address instead of the node name.

INOXHE8153 **Insufficient system resources to create thread: thread 'name', error error returned by thread create function**

Explanation There are not enough system resources available to create a new thread.

Action There are not enough system resources available to create a new thread. The reason is either that the system defined maximum for the number of threads per process is exceeded, or that there is not enough memory available to allocate the necessary thread resources.

INOXHE8201 **Cannot connect to server on host host at port port. TCP error code rsp.**

Explanation The web server interface module was not able to connect to the Tamino server.

Action Check if the Tamino server is active and accessible (e.g. using Telnet).

INOXHE8202 **Tamino database unknown**

Explanation The web server interface module was not able to determine the network address (hostname and port number) of the Tamino database server.

Action Check if the issued URL really points to the desired Tamino database server. If this is OK, check the configuration data of the web server interface module. If this is OK too, please contact your software supplier.

INOXHE8203 **Database server and web server interface module not compatible**

Explanation The versions of the Tamino database server and the Tamino web server interface module are not compatible.

Action Please use compatible versions of the Tamino database server and the Tamino web server interface module.

INOXHE8220 **XML initialization:SXS initialization failed: sxsMsg**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHE8254 **Failed to create the Software AG XTS Directory Server entries: why**

Explanation The server failed to create the necessary Software AG XTS Directory Server entries and the server startup failed. The reason for the failure is returned by the XTS layer.

Action Please check that the service "Software AG XTS Directory Server" is running. If not, please start it. On Windows this can be done using the Control Panel. On UNIX please use the scripts provided (which are normally executed at system start). If the service was running when the error occurred, and the XTS message does not specify enough details to fix the problem, please contact your software supplier.

INOXHE8257 **Conversion failed, output encoding enc, error code rsp**

Explanation The conversion into the desired document encoding failed.

Action Check the desired encoding and correct it.

INOXHE8258 **Unable to start request**

Explanation There is a resource shortage on the server.

Action Increase number of XML work threads. If the problem persists, increase the number of data working threads also.

INOXHE8261 **XML crash dump file filename could not be created due to operating system error system errno**

Explanation The XML crash dump file needed for error analysis could not be created due to the given reason.

Action Please consult the manufacturer's manual.

INOXHE8270 **XML internal error num: Session sess, Rsp rsp, time**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHE8278 **Internal error**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXHE8282 **Internal error**

Explanation Internal error.

Action Please contact your software supplier.

INOXHE8283 **Internal error**

Explanation Internal error.

Action Please contact your software supplier.

INOXHE8284 **Internal error**

Explanation Internal error.

Action Please contact your software supplier.

INOXHE8285 **Invalid Session ID**

Explanation The specified session does not exist or it is currently executing a different request.

Action Specify a valid Session ID.

INOXHE8286 **Internal error**

Explanation Internal error.

Action Please contact your software supplier.

INOXHE8287 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8288 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8289 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8290 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8291 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8292 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8293 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8294 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8295 **Internal error**

Explanation Internal error.

Action Please contact your software supplier.

INOXHE8296 **Internal error**

Explanation Internal error.

Action Please contact your software supplier.

INOXHE8297 **Error occurred in communication with client**

Explanation A communication problem occurred when receiving a request or sending a response to the client.

Action Please check the web server log files or network configuration for possible reasons.

INOXHE8298 **Internal error**

Explanation Internal error.

Action Please contact your software supplier.

INOXHE8299 **Internal error**

Explanation Internal error.

Action Please contact your software supplier.

INOXHF8155 **Communication method 'SSL' requires a certificate**

Explanation The server property 'communication method' is set to 'SSL', but the server property 'SSL certificate file' is not set. A certificate is mandatory for encrypted communication.

Action Specify the location of the certificate that the server should use.

INOXHF8158 **Set version failed. Reason: reason. Internal response d.**

Explanation An error occurred during migration.

Action Please contact your software suplier and provide the server startup logfile.

INOXHF8159 **Exception d occurred during server startup: msg**

Explanation The server could not be started.

Action Please contact your software supplier.

INOXHF8160 **Communication method 'SSL' requires a private key**

Explanation The server property 'communication method' is set to 'SSL', but the server property 'SSL key file' is not set. A private key is mandatory for encrypted communication.

Action Specify the location of the private key that the server should use.

INOXHF8162 **Error in SSL cipher list detected.**

Explanation SSL Cipher list provided shows incorrect syntax.

Action please correct

INOXHF8200 **XML thread initialization failed**

Explanation The initialization of X-Machine failed with the mentioned response code. This is an internal error.

Action Please contact your software supplier.

INOXHF8205 **XML thread initialization: data map initialization failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8206 **XML thread initialization: define of ino:collection failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8207 **XML thread initialization: check of ino:collection failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8208 **XML thread initialization: check of security collection failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8209 **XML thread initialization: insert security collection failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8210 **XML thread initialization: insert vocabulary collection failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8211 **XML thread initialization: check of vocabulary collection failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8212 **XML thread initialization: security initialization failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8213 **XML thread initialization: vocabulary initialization failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8214 **XML thread initialization: commit failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8215 **XML thread initialization: rollback failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8216 **XML thread initialization: Memory allocation failed**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8217 **XML work thread thid abended**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8218 **XML receive thread thid abended**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8219 **XML listen thread accept failed, rsp: tprsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8221 **TCP/IP select failed, rsp: tprsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8223 **XML connection initialization failed (error error number)**

Explanation The initialization of the XML communication did not work as expected. The server could not be started.

Action Repeat the action. If it still fails, contact your software supplier.

INOXHF8224 **Unexpected receive count: cnt**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8225 **XML initialization: data map initialization failed**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8226 **XML initialization:security initialization failed**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8227 **XML initialization: internal error**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8228 **XML thread initialization: creation of anonymous session failed**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8229 **XML thread initialization: server extension thread initialization failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8230 **XML initialization:TCP/IP startup failed**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8233 **XML initialization: gethostname failed**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8234 **XML initialization: gethostbyname failed, host: host, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8235 **XML initialization: invalid port number "port" found for web server webserver**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8237 **XTS Register Server failed for XML: xtsmsg**

Explanation The registration of the Tamino XML server via XTS failed.

Action Check and correct the XTS configuration and/or directory server.

INOXHF8239 **XML initialization: failed to define collection/doctype, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8240 **XML thread thread_number has exited due to communication error error_number (text)**

Explanation Either adding the service to the directory server has failed, or registering with the directory server has failed.

Action Check the XTS configuration.

INOXHF8241 **XML thread thread_number has exited due to communication error error_number (text)**

Explanation Either adding the service to the directory has failed, or the registration with the directory server failed.

Action Check the XTS configuration.

INOXHF8243 **XML processing not initialized**

Explanation The initialization of the XML processing did not work as expected. The server could not be started.

Action Repeat the action. If it still fails, contact your support center.

INOXHF8244 **Binding to TCP/IP socket socket number (port type port) has failed**

Explanation The server could not connect to the specified socket. Maybe it is in use.

Action Check the reason for the error. If the error persists, choose another port number.

INOXHF8255 **XML initialization: invalid IP address "ipaddr" found for web server webserver**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8256 **XML initialization: Memory allocation failed**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8262 **XML thread initialization: initialization of tokenizer failed, rsp: rsp**

Explanation This is an internal error.

Action Please contact your software supplier.

INOXHF8263	**XML initialization: No license for tok tokenizer**
Explanation	No valid license found for the default tokenizer.
Action	Please check the setting of database parameter "default tokenizer" and the used license file. If the problem persists, please contact your software supplier.

INOXHF8264	**XML thread initialization: Create failed for obj**
Explanation	This is an internal error.
Action	Please contact your software supplier.

INOXHF8266	**Invalid default tokenizer: tok**
Explanation	The value of the parameter "default tokenizer" is invalid.
Action	Use a valid value.

INOXHF8269	**XML thread initialization: data map initialization for server extensions failed, rsp: rsp**
Explanation	Internal error: Data map entries needed by X-Tension could not be initialized.
Action	Please contact your software supplier.

INOXHF8271	**XML initialization: invalid/unsupported default encoding 'defEnc'**
Explanation	An invalid/unsupported MIME or IANA encoding name is specified for the 'default encoding' database parameter.
Action	Please check the setting of the 'default encoding' database parameter. If the problem persists, please contact your software supplier.

INOXHF8272	**XML initialization: Word stemming algorithm initialization failed, rsp: rsp**
Explanation	This is an internal error.
Action	Please contact your software supplier.

INOXHF8273	**Failed to attach definition of system collections**
Explanation	The shared library containing in particular the meta schema could not be loaded.
Action	Check your installation.

INOXHF8279 **Necessary allocation of static port failed**

Explanation The allocation of a necessary static port failed.

Action Please contact your software supplier.

INOXHI8151 **Communication method: s**

Explanation The given communication method will be used for the server that is starting. See the user documentation for the server property "Communication Method" for more information.

Action No action required.

INOXHI8156 **TCP/IP send failed, rsp: rsp, time**

Explanation The Tamino server failed to respond to a request. The communication method used was TCP/IP. The reported response code is the error which the Tamino server got from TCP/IP "send".

Action Please check the state of TCP/IP.

INOXHI8157 **XTS send failed, rsp: rsp, time**

Explanation The Tamino server failed to respond to a request. The communication method used was XTS. The reported response code is the error which the Tamino server got from XTS "SendMessageByRT".

Action Please check the state of XTS.

INOXHI8222 **TCP/IP receive failed, rsp: rsp**

Explanation Error in the TCP/IP stack.

Action Please check the state of TCP/IP.

INOXHI8242 **Define doctype in collection collection**

Explanation A system doctype with given name is being created in the given collection.

Action No action required

INOXHI8247 **Dynamic what worker thread created**

Explanation The server increased the number of worker threads to avoid a possible deadlock.

Action No action required.

INOXHI8251 **Overwriting Software AG XTS Directory Server entries**

Explanation The Software AG XTS Directory Server entries already existed. They are overwritten.

Action No action required.

INOXHI8252 **type - 'dsentry'**

Explanation This is an informational message.

Action No action required.

INOXHI8253 **Use switch parameter 'param' to force server registration**

Explanation This is an informational message.

Action No action required.

INOXHI8260 **XML crash dump of database finished**

Explanation The XML crash dump is complete.

Action No action required.

INOXHI8265 **Default tokenizer 'tok'**

Explanation This is an informational message.

Action No action required.

INOXHI8267 **User dictionary 'udict'**

Explanation This is an informational message.

Action No action required.

INOXHI8274 **Word stemming index successfully created**

Explanation The database parameter 'stemming index' is enabled and the stemming index for documents with text indices is created.

Action No action required.

INOXHI8275 **Word stemming index successfully dropped**

Explanation The database parameter 'stemming index' is disabled and the stemming index for documents with text indices is removed.

Action No action required.

INOXHI8276 **Web server configuration updated**

Explanation The web server configuration was changed and is now updated in the server.

Action No action required.

INOXHI8277 **Internal error**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXHR8245 **Initializing XML processing**

Explanation This is an informational message.

Action No action required.

INOXHR8246 **Starting XML threads**

Explanation This is an informational message.

Action No action required.

INOXHV8250 **Server is already registered with the Software AG XTS Directory Server**

Explanation When the Tamino server starts it registers with the Software AG XTS Directory Server. It is possible that entries for the server are already present (server already started somewhere else or previous server session failed). If this message comes as a warning message, the entry found exactly matches the one that should be entered. If this message comes as an error message, the entry found did not match the entry that the server wanted to add.

Action If this message comes as a warning message no action is required. If this message comes as an error message the Software AG XTS Directory Server entry found for the server should be checked and, if no longer necessary, the next server start should be done with the parameter for overwriting the Software AG XTS Directory Server entry activated.

INOXHW8154 **TCP connection timed out**

Explanation A violation of Tamino Network Protocol was detected.

Action Check the client application / network.

INOXHW8161 **HTTP connection timed out**

Explanation A violation of Tamino Network Protocol was detected.

Action Check the client application / network.

INOXHW8204 **XML thread initialization: data map initialization for server extension failed, rsp: rsp**

Explanation This is an internal error. Tamino will work as expected unless server extensions are used.

Action Please contact your software supplier.

INOXHW8231 **No license for Tamino XML**

Explanation A special license must be bought to use the Tamino XML feature.

Action Buy a license for Tamino XML.

INOXHW8232 **Only numLic concurrent XML sessions licensed**

Explanation The server parameter "XML maximum sessions" contains a value that is larger than the number of concurrent sessions that is included in the used license.

Only the number of sessions that is covered by the license used is allowed.

Action Buy an enhanced license.

INOXHW8236 **XML connection refused; current number of connections: totCon**

Explanation Tamino is not able to accept another XML request. The connection attempt is refused.

Action Increase the number of XML work threads.

INOXHW8238 **Unable to free storage.**

Explanation This is an internal error. X-Machine is not able to free all storage during shutdown.

Action Please contact your software supplier.

INOXHW8248 **Maximum number of dynamic what worker threads reached**

Explanation The maximum number of dynamic worker threads is reached. No further threads are created.

Action The number of worker threads should be increased and the server should be restarted.

INOXHW8249 **Creation of dynamic what worker thread failed with response err**

Explanation The server failed to increase the number of worker threads.

Action No action required.

INOXHW8268 **Invalid entry in user dictionary 'tok'**

Explanation The user dictionary contains an invalid entry. It is ignored.

Action Check the user dictionary contents.

INOXIE8300 **No matching document found**

Explanation The specified query did not not find any matching documents.

Action None. This is only an informational error message.

INOXIE8301 **Illegal document ID specified**

Explanation The specified document ID is illegal.

Action Supply a legal document ID.

INOXIE8303 **Deleting a document is forbidden**

Explanation A _DELETE operation was issued against a doctype where DELETE is missing in the doctype options as supplied in the schema definition.

Action Change the doctype options accordingly.

INOXIE8304 **Reading a document is forbidden**

Explanation An _XQL operation was issued against a doctype where READ is missing in the doctype options as supplied in the schema definition.

Action Change the doctype options accordingly.

INOXIE8305 **Invalid cursor handle**

Explanation The supplied cursor handle is invalid: either it was never created during the current session, or the corresponding cursor was closed in the meantime.

Action Supply a correct cursor handle.

INOXIE8306 **Invalid cursor position**

Explanation The supplied cursor position is invalid: there is no document in the cursor's result set corresponding to the position. In particular, this error will be returned when positioning beyond the end of the cursor result set.

Action Supply a correct cursor position.

INOXIE8307 **Trying to position backwards in a non-scrollable cursor**

Explanation The position supplied with the "fetch cursor" request would result in a backward positioning which is not possible for a non-scrollable cursor.

Action Supply a correct cursor position.

INOXIE8309 **Duplicate in sort key**

Explanation The system cannot handle sort key values which consist of more than a single node.

Action Change your query expression so that no multiple node is to be sorted.

INOXIE8310 **Invalid parameter detected**

Explanation Either the function is unknown or the number of parameters is invalid or the parameter values are invalid.

Action Please check the function name, the number of parameters and the parameter values and correct them.

INOXIE8312 **Version fromVersion is incompatible with Version toVersion**

Explanation The current version of the database is not compatible with the selected version.

Action Data must be unloaded and loaded into a new database manually.

INOXIE8313 **Internal communication error**

Explanation Database cannot be converted because of an internal error.

Action Check that the database is running.

INOXIE8314 **Database's compatibility level is no longer supported**

Explanation Migration from and to this compatibility level is not possible because this compatibility level is no longer supported.

Action Data must be unloaded and loaded into a new database manually.

INOXIE8315	**Duplicate docnames found in ino:collection = 'collection' ino:doctype='doctype'**
Explanation	The upgrade has been rejected because because of duplicate docnames.
Action	Use the administration command ino:AdminDocname("check-unique") to get a list of duplicate docnames. Please delete the duplicate docnames and call the administration command ino:AdminDocname("set-unique").

INOXIE8316	**Attempted to delete a partial document**
Explanation	With _delete, it is only possible to delete complete XML documents.
Action	Supply a query that selects complete documents.

INOXIE8319	**Internal error occurred during query processing: unknown request**
Explanation	An internal error has occurred.
Action	Please contact your software supplier.

INOXIE8320	**Error parsing the XQL query**
Explanation	One or more errors occurred while parsing the XQL query.
Action	Correct query appropriately and re-issue

INOXIE8321	**Missing end quotation character**
Explanation	The end quotation character of a literal was not found. It could also be that the start and end quotation characters do not match.
Action	Correct query appropriately and re-issue.

INOXIE8322	**Named axes are not supported**
Explanation	The specification of named axes is not supported in Tamino.
Action	No action possible.

INOXIE8331	**Failed to set the server parameter**
Explanation	Failed to set the server parameter.
Action	Please contact your software supplier.

INOXIE8332 **The old server parameter could not be deleted**

Explanation The old server parameter could not be deleted.

Action Please contact your software supplier.

INOXIE8333 **An old TSD2 collection could not be deleted**

Explanation An old TSD2 collection could not be deleted.

Action Please contact your software supplier.

INOXIE8334 **The database contains data which uses lite mapping**

Explanation The version to which the database should be upgraded does not support lite mapping.

Action Please delete the data which uses lite mapping and start the upgrade again.

INOXIE8335 **Upgrade of metaschema failed with following response code RESPONSE.**

Explanation The upgrade of the metaschema which was performed during upgrade of the database has failed with the specified response code.

Action Please contact your software supplier.

INOXIE8336 **Upgrade is not supported**

Explanation Upgrade is not supported.

Action Select another version to upgrade the database.

INOXIE8337 **Downgrade is not supported**

Explanation Downgrade to an older Tamino version is not supported.

Action Please contact your software supplier.

INOXIE8338 **Data format 'VERSION' found in collection 'COLLECTION' doctype 'DOCTYPE'.**

Explanation The data format found in the user collection is no longer supported.

Action Please clean up the user collection.

INOXIE8339 **Unknown function**

Explanation The provided function name is unknown.

Action Check if you provided the correct function name and try again.

INOXIE8340 **Truncated index detected**

Explanation An index containing truncated entries was detected at query execution time, though the Data Map had no information about truncation available at compile time. This may occur for an index that has been migrated from Tamino version 4.1.4. As a side effect of the failing query, the index has been marked as truncated in the Data Map.

Action Repeat the query.

INOXIE8341 **Internal error**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXIE8342 **Memory allocation failed**

Explanation There was not enough main memory available to perform the request.

Action Possibly the machine is overloaded. Try again later.

INOXIE8343 **Postprocessing not supported for non-XML text search**

Explanation A query that contains a text search operator can be executed on a non-XML doctype only if a text index has been defined for that doctype and the query does not require postprocessing.

Action Modify your schema definition to contain a non-XML text index or change query to avoid postprocessing.

INOXIE8344 **Internal error**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXIE8345 **Illegal parent operator follows sort operator**

Explanation A query contains a parent operator which might be applied to a node which serves as input for a sort operator. This is not allowed.

Action Please change your query so that no parent operator can be applied to a sort input node.

INOXIE8346 **Malformed proximity expression**

Explanation A subexpression of the query uses either the "adj" or the "near" operator, but there is no corresponding "~=" operator.

Action Correct the query.

INOXIE8347 **Query not supported**

Explanation The specified query is not supported.

Action Change the query.

INOXIE8348 **Wrong arguments for function**

Explanation The function cannot be applied on the current parm settings, i.e. number or type of arguments that a function is called with is not as expected by the function.

Action Check either the XPath specification for the proper usage of XPath's built in functions or check the documentation for server extension functions.

INOXIE8349 **Maximum word length exceeded**

Explanation Text searches are restricted to a maximum word length of 64 characters.

Action Reduce the length of the search pattern inside the query.

INOXIE8350 **No whitespace search is supported with ~=**

Explanation Whitespaces are ignored by a "~=" search, so searching for a whitespace is not possible.

Action Use the "=" operator to find whitespaces.

INOXIE8351 **Wrong direction of result type**

Explanation The result type must be output.

Action Uninstall the function, change the signature of the external function, install the function again.

INOXIE8352 **Operator used outside a document**

Explanation Some operators can only be used inside a document e.g. before/after.

Action Do not use the operator outside of a document context.

INOXIE8353	**Invalid invocation of ino:fullscan**
Explanation	The ino:fullscan function can be used only on query level, it cannot be applied to subexpressions.
Action	Correct ino:fullscan invocation.

INOXIE8354	**Invalid invocation of ino:explain**
Explanation	The ino:explain function can be used only on query level, it can not be applied to subexpressions.
Action	Correct ino:explain invocation.

INOXIE8355	**Too many inter-document sort operators**
Explanation	The system can process only a single inter-document sort operator. Please note that a "sortby" applied to a root node is also an inter-document sort operator.
Action	Please change your query.

INOXIE8356	**Illegal inter-document sort operators**
Explanation	Within a query an inter-document sort operator must not follow an intra-document sort operator.
Action	Please change your query.

INOXIE8357	**Internal error**
Explanation	An internal error has occurred.
Action	Please contact your software supplier.

INOXIE8358	**Internal error**
Explanation	An internal error has occurred.
Action	Please contact your software supplier.

INOXIE8359	**Internal error**
Explanation	An internal error has occurred.
Action	Please contact your software supplier.

INOXIE8360 **Nodeset is empty**

Explanation The current-node (.) or parent (..) operator was applied upon an empty nodeset during query evaluation.

Action A subquery executed prior to the current-node or parent operation yielded an empty result.

INOXIE8361 **Invalid type occurred when executing query**

Explanation Some query operations can only be applied upon objects of a specific type, e.g. current-node (.) or parent (..) only make sense when working upon nodes. This error may also occur when calling XPath functions upon a set of arguments they cannot be applied upon.

Action Check whether . (=current node) or .. (= parent) are used in connection with nodes, and that an XPath function's usage corresponds to its type.

INOXIE8362 **Internal Error : Invalid Node**

Explanation An invalid XML node was encountered during the evaluation of an XPath function.

Action Please contact your software supplier.

INOXIE8364 **Conversion failed**

Explanation In order to execute a query an invalid conversion was attempted. This happens e.g. if a numerical operation is applied upon data that cannot be converted to a number. This error occurs also if an operator requires two operands of the same type (e.g. between) and the operands are of different types.

Action Check the operand's types.

INOXIE8366 **Wrong arguments for function**

Explanation The function cannot be applied on the current parm settings, i.e. number or type of arguments that a function is called with is not as expected by the function.

Action Check either the XPath specification for the proper usage of XPath's built in functions or check the documentation for server extension functions.

INOXIE8367 **Internal error : Missing root node**

Explanation The query postprocessor encountered a missing node in the XPath parsing tree when evaluating an XPath expression.

Action Please contact your software supplier.

INOXIE8368 **ICU collator definition failed**

Explanation An error was received while opening an ICU collator.

Action Please contact your software supplier.

INOXIE8369 **Right side of ~= must be a single string**

Explanation The match operand requires an operand that evaluates to string on its right side.

Action Check whether your idea of what match does is correct. It typically looks like list-of-nodes ~= 'pattern' or list-of-nodes ~= 'word' . If the right side of your match is detected dynamically from Tamino data, it does not evaluate to a string as you expected. If the right side of your match is given literally in the query, it might help to add quotes.

INOXIE8371 **Invalid comparison operator**

Explanation Within 'adjacent' or 'near' statements, currently only the match comparison operator is allowed.

Action Replace an equal by a match and a not-equal by a match and the XPath function 'not()'.

INOXIE8372 **Too many match tokens**

Explanation The right side of a ~= contains a string that gets tokenized in order to check the expression on the left side for the occurrence of these tokens in the given sequence. The tokenization must not lead to more than ten tokens.

Action Shorten the pattern to avoid tokenization into more than ten tokens.

INOXIE8374 **Invalid Match Pattern**

Explanation The string provided as the right side of a match (~=) must contain at least one character that is not a separation character, i.e. quote or comma. The string may contain wildcards (*), but only in the forms *x, x*, x*x, or *x*.

Action Correct the pattern.

INOXIE8375 **Sortkey too long**

Explanation The internally generated sort key is too long.

Action Reduce the number of sort criteria.

INOXIE8376 **Duplicate in sort key**

Explanation The system cannot handle sort key values which consist of more than a single node.

Action Please try to fix your data or your query.

INOXIE8378 **Server extension returned binary data without setting media type**

Explanation The media type must be defined when a server extension returns binary data.

Action Use the method SxsSetProperty() with the property of SX_PROPERTY_RSP_MEDIATYPE to define the media type of the binary data.

INOXIE8379 **Internal error occurred during query processing: unknown request**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXII8302 **Overflow during sorting**

Explanation internal error

Action Please contact your software supplier.

INOXII8311 **Version fromVersion is compatible with Version toVersion**

Explanation The current version of the database is compatible with the selected version.

Action None

INOXII8317 **Internal error during sorting**

Explanation internal error

Action Please contact your software supplier.

INOXII8318 **Locking conflict**

Explanation internal error

Action Please contact your software supplier.

INOXII8323 **Recreation of all indices started in collection COLLECTION, doctype DOCTYPE**

Explanation The administrative command ino:RecreateIndex was issued.

Action Be aware that the collection is not accessible until index recreation is completed.

INOXII8324 **Recreation of all indices in collection COLLECTION, doctype DOCTYPE terminated with code CODE**

Explanation The administrative command ino:RecreateIndex terminated.

Action Be aware that if the given return code is not 0, the index recreation has been rolled back.

INOXII8325 **Recreation of all text indices started in collection COLLECTION, doctype DOCTYPE**

Explanation The administrative command ino:RecreateTextIndex was issued.

Action Be aware that access to the collection is constricted until the operation is completed.

INOXII8326 **Recreation of all text indices in collection COLLECTION, doctype DOCTYPE terminated successfully**

Explanation The administrative command ino:RecreateTextIndex completed.

Action The collection is fully usable again.

INOXII8327 **Recreation of all text indices in collection COLLECTION, doctype DOCTYPE terminated with error CODE**

Explanation The administrative command ino:RecreateTextIndex aborted due to the stated error code.

Action Repair the indices via the administrative command ino:RepairIndex().

INOXII8328 **Repair indices started in collection COLLECTION, doctype DOCTYPE, mode MODE**

Explanation The administrative command ino:RepairIndex was issued.

Action Be aware that access to the collection is constricted until the operation is completed.

INOXII8329 **Repair indices in collection COLLECTION, doctype DOCTYPE, mode MODE terminated successfully**

Explanation The administrative command ino:RepairIndex completed successfully.

Action Note that if the mode was "drop", the indices have been dropped from the schema.

INOXII8330 **Repair indices in collection COLLECTION, doctype DOCTYPE, mode MODE terminated with error CODE**

Explanation The administrative command ino:RepairIndex aborted due to the given error.

Action Correct the problem if possible and repeat the command.

INOXIW8373 **The id() function is not supported**

Explanation XPath describes the result of the id() function as being the node-set containing the elements in the same document as the context node that have a unique ID equal to any of the tokens in the id() function's argument list (see XPath 4.1). As specified in XPath, 5.2.1, a unique ID is the value of the attribute that is declared in the DTD as type ID. Since Tamino currently offers no means to declare attributes as type ID, applying the id() function makes no sense, its result will always be the empty node set.

Action If some attribute 'att1' has the semantics of an ID, retrieving the node for which this attribute is set to a certain value, e.g. 'val1', is achieved via //*[@att1="val1"].

INOXIW8399 **The required function has not been completely executed**

Explanation See details in the warning line accompanying this message. Possible reasons for this warning are: a sort operation was performed based on an index, and that index contains truncated values. The result is sorted according to the truncated values, and not according to the real values.

Action No action required, this is a warning only.

INOXME8501 **Memory allocation failed**

Explanation Allocation of virtual memory failed.

Action Either extend the amount of memory resources available for Tamino on your system or reduce resource consumption of Tamino, e.g. by using a smaller buffer pool.

INOXME8502 **Internal error: DBMS environment not found**

Explanation The DBMS environment could not be found for X-Node - this is an internal error.

Action Please contact your software supplier.

INOXME8503 **Invalid or unknown encoding found in input document**

Explanation The encoding of the input document could not be recognized.

Action Check your input document.

INOXME8504 **XML maximum request duration exceeded**

Explanation The request was cancelled because the maximum request duration was exceeded.

Action Either improve the request performance by tuning the database, or increase the value of the "XML maximum request duration" server parameter.

INOXME8505 **ODBC error occurred**

Explanation While issuing a command via ODBC to the SQL system an error occurred.

Action The text of the external error is provided in the extended message.

INOXME8506 **Adabas error occurred**

Explanation An error occurred when accessing an Adabas database via X-Node.

Action Check the Adabas documentation for the reason for the reported error code.

INOXME8507 **Maximum parallel databases for session reached**

Explanation The number of parallel databases allowed for one session has been reached.

Action No action required.

INOXME8508 **X-Node licensing error, insufficient rights**

Explanation An attempt was made to access an X-Node datasource or an Adabas version that has not been licensed.

Action Check that all datasources defined in the schema are correct, or upgrade the X-Node license.

INOXME8509 **X-Node datasource mismatch**

Explanation The datasource DBMS name given (implicitly or explicitly) in the schema does not match that of the DBMS vendor to which this datasource has attempted to connect.

Action The DBMS name must be the same at execution time as it was at schema creation time.

INOXME8510 **Request has been cancelled**

Explanation The request has been cancelled by the operator or accessor.

Action No action required.

INOXME8511 **Internal maximum for parallel ODBC access reached**

Explanation Within one transaction, Tamino keeps track of parallel OBDC access. An internal list reached its maximum.

Action No action required.

INOXME8512 **Invalid request ID**

Explanation The given ID is invalid either because the respective request is already terminated or because it is invalid as an accessor-provided unique identifier.

Action No action required, if the request is already terminated. Otherwise the request ID cannot be used within _admin=ino:Accessor("cancelRequest",...).

INOXME8513 **Cannot create unique text index**

Explanation A unique index cannot be set because duplicate entries are stored in the translated word table.

Action Please contact your software supplier.

INOXME8514 **X-Node SQL column not found or authorization error**

Explanation The specified column was not found in the SQL table or you are not authorized to access the column/table.

Action Correct the schema.

INOXME8515 **X-Node SQL table not found or authorization error**

Explanation The error may occur because: 1. the specified SQL table/schema was not found OR 2. you are not authorized to access the table.

Action Correct the schema.

INOXME8516 **Internal error: cannot lock collection**

Explanation Migration attempted to lock a collection for which it is not possible.

Action Please contact your software supplier.

INOXME8517 **Unlock of collection failed**

Explanation It was not possible to unlock the specified collection.

Action Please contact your software supplier.

INOXME8518 **Unlock of collection failed because the lock is in an incorrect state**

Explanation It was not possible to unlock the specified collection because the lock is in an incorrect state.

Action Please contact your software supplier.

INOXME8519 **Cannot cancel a mass load/unload as a session user**

Explanation Cancelling of a mass load/unload in a session is not possible.

Action Issue the administration command in an anonymous session.

INOXME8520 **Error writing to temporary file during data load**

Explanation An error occurred while writing to a temporary file during a data load request.

Action Check that temporary directory ($SAGTMP or $TMP) is writable and that disk space is available.

INOXME8521 **Invalid or unsupported datastore format detected during data load**

Explanation An internal error occurred during data load.

Action Please contact your software supplier.

INOXME8522 **Unsupported datastore descriptor type detected during data load**

Explanation An internal error occurred while data was being loaded.

Action Please contact your software supplier.

INOXME8523 **Unsupported datastore request detected during data load**

Explanation An internal error occurred while data was being loaded.

Action Please contact your software supplier.

INOXME8524 **Value exceeding maximum length detected during data load**

Explanation An internal error occurred while data was being loaded.

Action Please contact your software supplier.

INOXME8525 **Internal error detected in data load module**

Explanation An internal error occurred while data was being loaded.

Action Please contact your software supplier.

INOXME8527 **Data loading/unloading for doctype not supported**

Explanation For data loading: - doctypes of map-type NonXML or Lite are not supported. - doctypes created in Tamino version prior to v2.3 are not supported.

For data unloading: - doc-types of map-type NonXML are not supported

Action Either migrate your doctype to v2.3 or later or use the XML loaders.

INOXME8528 **Data loading aborted; cannot create temporary files**

Explanation The data loader was unable to create temporary files.

Action Using the Tamino Manager or the batch utility "argbatch", check that the settings for the temporary location are correct and that there is space available.

INOXME8529 **Data loading into multiple doctypes not supported**

Explanation Data loading is only possible into the collection/doctype given when the data loader is started.

Action Remove documents from the input file that do not belong to the doctype specified at the start-up of the XML data loader.

INOXME8531 **Data load rejected document**

Explanation An error was found while processing the document during a data load operation.

Action Correct and restart the data loader.

INOXME8536 **XML data load recovery of doctype doctype in collection collection was unsuccessful**

Explanation During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information that Tamino could not restore the doctype to the state before the XML data load operation was initiated.

Action Perform a restore/regenerate of the Tamino database to get it into a consistent state.

INOXME8539 **XML data loading failed**

Explanation An XML data load operation was aborted or stopped.

Action Depending on the reason for the failure, correct and re-process.

INOXME8540 **Data loading aborted with rejects**

Explanation Data loading has aborted because a reject was found and the norejects option was chosen.

Action Either correct the rejected document or load without setting the norejects option.

INOXME8543 **Internal error - unexpected response occurred in call to function function, function gave response code(s) codes**

Explanation An internal error has occurred.

Action Please contact your software supplier with the exact message (the function and codes are important).

INOXME8544 **Query using "mapping-type=object" cannot be evaluated**

Explanation The query cannot be evaluated because "mapping-type=object" is involved and the post-processor is needed, or because the "mapping-type=object" node is used within a filter.

Action Supply a correct query.

INOXME8546 **Feature not implemented**

Explanation You attempted to use a feature which is not available in the current environment.

Action Please contact your software supplier.

INOXME8547 **Invalid syntax of _XQL command inside _HTMLREQ**

Explanation An error occurred when converting an _HTMLREQ=_XQL request to an _XQL request.

Action Check the appropriate documentation.

INOXME8548 **Invalid syntax of _PROCESS command inside _HTMLREQ**

Explanation An error occurred when converting an _HTMLREQ=_PROCESS request to a _PROCESS request.

Action Check the appropriate documentation.

INOXME8549 **Doctype not found**

Explanation The doctype indicated in the ino:messageline could not be found during an _UNDEFINE request.

Action Check the specified name.

INOXME8551 **Invalid doctype**

Explanation Storing or deleting documents in the collection "ino:collection" is not permitted.

Action Check the collection name specified in the request.

INOXME8552 **Not a valid request**

Explanation The request has been rejected due to invalid or missing parameters.

Action Check the request parameters using supplementary error diagnostics in other messages.

INOXME8554 **No message received**

Explanation The request did not specify any supported operation or command.

Action Check the parameters of the request.

INOXME8555 **Session error occurred**

Explanation An error occurred when attempting to establish a session context.

Action Check the supplementary diagnostic message for a detailed explanation.

INOXME8557 **Request rejected because a deprecated feature is used**

Explanation The used feature will not be supported in the next version.

Action Change the server parameter to allow and log deprecated features.

INOXME8558 **Error during commit in user transaction**

Explanation A user transaction received an error during commit processing.

Action The error has to be handled in your application.

INOXME8559 **Error during rollback of user transaction**

Explanation A user transaction has been rolled back due to an error. However, the indicated error occurred.

Action Please contact your system administrator.

INOXME8560 **Failed to allocate SMP key**

Explanation An internal error occurred when attempting to allocate a key for thread local storage.

Action Please contact your system administrator.

INOXME8561 **Failed to deallocate SMP key**

Explanation An internal error occurred when attempting to release a key for thread local storage.

Action Please contact your system administrator.

INOXME8562 **Invalid handle**

Explanation Internal error: an invalid handle was passed to an internal interface.

Action Please contact your system administrator.

INOXME8563 **Invalid parameter**

Explanation Internal error: an invalid parameter was passed to an internal interface.

Action Please contact your system administrator.

INOXME8564 **Illegal load factor**

Explanation An internal error occurred when creating a hash map.

Action Please contact your system administrator.

INOXME8565 **Illegal initial capacity**

Explanation An internal error occurred when creating a hash map.

Action Please contact your system administrator.

INOXME8566 **Duplicate key**

Explanation An attempt was made to store the same key twice in a hash map.

Action Please contact your system administrator.

INOXME8570 **Locking failed during data load operation**

Explanation The specified collection or doctype could not be locked.

Action Check the parameters of the data load request.

INOXME8596 **Internal error in locking**

Explanation An unexpected server status caused a lock operation failure.

Action Please contact your software supplier.

INOXME8598 **Access violation**

Explanation The request was rejected due to insufficient access permissions.

Action Check if the request was as intended and if so, try to get the required access privileges from the system administrator.

INOXME8599 **Internal error**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXMF8530 **Internal error occurred during data loading**

Explanation An internal error was detected while data was being loaded.

Action Please contact your software supplier.

INOXMI8532 **XML data load recovery initiated**

Explanation During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message defines the start of recovery handling for cleaning up anything that was left over after the data load operation.

Action No action required.

INOXMI8533 **XML data load recovery completed**

Explanation During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message defines the completion of recovery handling for cleaning up anything that was left over after the data load operation.

Action No action required.

INOXMI8534 **XML data load recovery initiated for doctype doctype in collection collection**

Explanation During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information about which doctypes are being recovered.

Action No action required.

INOXMI8535 **XML data load recovery of doctype doctype in collection collection completed successfully**

Explanation During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information that Tamino has successfully restored the doctype to the state before the XML data load operation was initiated.

Action No action required.

INOXMI8537 **XML data loading initiated for doctype doctype of collection collection**

Explanation This is an information message to indicate the start of XML data load operation.

Action No action required.

INOXMI8538	**XML data loading completed, number of documents processed docsproc, loaded docsload, rejected docsrejected**
Explanation	This is an information message to indicate the end of an XML data load operation.
Action	Depending on if there were documents rejected, these may need to be investigated and re-processed.

INOXMV8550	**Deprecated feature used: feature**
Explanation	The request uses a feature which is planned to be removed in the next product version.
Action	Do not use the deprecated feature.

INOXMW8526	**Failed to write XML request log to path**
Explanation	An error occurred when attempting to write the XML request log to given location.
Action	Check the location for possible reasons such as: a non-existing XML request log folder may have been specified, the directory cannot be accessed, or the disk is full.

INOXMW8545	**ino:docname uniqueness is not removed in downgrade**
Explanation	The downgrade does not allow the uniqueness of ino:docnames to be removed.
Action	No action required.

INOXMW8571	**Request logging was switched off dynamically due to IO errors**
Explanation	Probably the disk is full.
Action	Check the disk. Except for request logging, the Tamino server continues operation.

INOXPE8700	**Internal error: inconsistent document retrieval**
Explanation	The database storage of the retrieved document is inconsistent.
Action	Please contact your software supplier.

INOXPE8701	**Memory allocation failed**
Explanation	There was not enough main memory available to perform the request.
Action	Possibly the machine is overloaded. Try again later.

INOXPE8702 **Invalid document prolog**

Explanation Invalid document prolog found in the file to be loaded.

Action Please correct the document prolog.

INOXPE8703 **Invalid document declaration or more than one declaration found in the file to be loaded**

Explanation Invalid document declaration or more than one declaration found in the file to be loaded.

Action Correct the document declaration or remove all declarations except for the first.

INOXPE8704 **Unknown encoding found**

Explanation Unknown encoding found.

Action Please correct the document instance.

INOXPE8705 **Incompatible encoding found**

Explanation The given encoding isn't supported yet.

Action Please use another encoding.

INOXPE8706 **Entity found twice**

Explanation An entity with same name was found twice.

Action Please remove one of these entities.

INOXPE8707 **Wrong entity definition**

Explanation The definition of an entity isn't correct.

Action Please correct the entity definition.

INOXPE8708 **Document without content**

Explanation An empty document cannot be loaded.

Action Please provide the document with contents.

INOXPE8709 **Encoding not supported**

Explanation The given encoding isn't supported yet.

Action Please use another encoding.

INOXPE8710 **Invalid token found or document incomplete**

Explanation Invalid token found or the document is incomplete.

Action Please correct the document.

INOXPE8711 **Document not well-formed**

Explanation The document to be loaded isn't well-formed.

Action Please correct the document.

INOXPE8712 **Invalid element name**

Explanation The name of the element is either too long or not correct.

Action Please correct the document.

INOXPE8713 **Invalid attribute name**

Explanation The name of the attribute is either too long or not correct.

Action Please correct the document.

INOXPE8714 **Invalid document ID (ino:id) specified**

Explanation The given document ID (ino:id) is either not numeric or not available.

Action Please correct the document.

INOXPE8715 **Inserting or changing a document is forbidden**

Explanation It isn't permitted when using this doctype to insert or to change documents.

Action Please contact your system administrator.

INOXPE8716 **Inserting a document is forbidden**

Explanation It isn't permitted when using this doctype to insert a new document.

Action Please contact your system administrator.

INOXPE8717 **Changing a document is forbidden**

Explanation It isn't permitted while using this doctype to change a document.

Action Please contact your system administrator.

INOXPE8718 **Document incomplete**

Explanation The document to be loaded is incomplete.

Action Please correct the document.

INOXPE8719 **Document contains invalid character reference**

Explanation The document contains an invalid character reference.

Action Please correct the document.

INOXPE8720 **Document contains invalid entity reference**

Explanation The document contains a reference to an entity which wasn't defined before.

Action Please correct the document.

INOXPE8721 **Root element does not match doctype declaration**

Explanation The given root element doesn't correspond to the root element of the used doctype.

Action Please correct the document.

INOXPE8722 **Element with wrong obj-type encountered**

Explanation The given element is defined in the schema as an attribute.

Action Correct either the document or the accompanying schema.

INOXPE8723 **Attribute with wrong obj-type encountered**

Explanation The given attribute is defined in the schema as an element.

Action Correct either the document or the accompanying schema.

INOXPE8724 **Invalid attribute value encountered**

Explanation The value of the attribute contains contents which aren't permitted.

Action Please correct the document.

INOXPE8725 **Attribute was found twice**

Explanation An attribute with same name was found twice.

Action Please remove one of these attributes.

INOXPE8726 **Occurrence count does not match multiplicity option**

Explanation The occurrence count of an element or attribute in an XML instance does not match the multiplicity option specified in the schema.

Action Please correct the document.

INOXPE8727 **Document structure does not match schema definition (choice)**

Explanation The document structure does not match the schema definition for the choice case.

Action Please correct the document.

INOXPE8728 **Internal error: parent object not found**

Explanation Accompanying parent object couldn't be found.

Action Please contact your system administrator.

INOXPE8729 **Unclosed CDATA section detected**

Explanation Unclosed CDATA section detected.

Action Please correct the document.

INOXPE8730 **Required child object not specified**

Explanation An element or an attribute which is defined in the schema as mandatory wasn't specified in the document.

Action Please correct the document.

INOXPE8731 **Internal error: Parse in progress**

Explanation The attempt was made to parse a second document while still parsing the first document.

Action Please contact your system administrator.

INOXPE8732 **Value too long**

Explanation The value of a numeric node or of a node mapped to an external datasource or of a node with search type STANDARD is too long.

Action Please shorten the corresponding value.

INOXPE8733 **Value not numeric**

Explanation The value for an object with an numeric datatype is not numeric.

Action Please correct the document.

INOXPE8734 **Numeric value too large**

Explanation The value of an object with a numeric datatype is too large.

Action Please shorten the corresponding value.

INOXPE8735 **Insufficient space to convert data according to encoding**

Explanation The length of data in an attribute/element that is defined to AdaField exceeds the defined length in the schema.

Action Correct either the XML input data or modify the schema to increase the defined length.

INOXPE8736 **Internal error: buffer exceeded**

Explanation For InfoFile mapping, the size of a document or the size of parts of a document that are mapped to any InfoField construct (like InfoArray) is limited to 64KB at the node level where map type InfoFile is specified. If there is no node with an explicit map type of InfoFile, the limit of 64KB applies to the root node.

Action Reduce the number of nodes that are mapped to InfoField constructs. Use map type Native instead.

INOXPE8737 **Invalid document update attempted**

Explanation The request tried to modify the document such that it would have generated an SQL UPDATE statement without a WHERE clause. This is not allowed.

Action To accomplish this, delete the document and insert a new document instead of updating the document.

INOXPE8738 **Only a single document may be processed.**

Explanation If the document name or the document ID is given, only a single document can be processed.

Action Please remove additional documents.

INOXPE8740 **Internal error in document serialization module detected**

Explanation An internal error occurred in the serialization module.

Action Please contact your software supplier.

INOXPE8741 **Internal error in document serialization module detected**

Explanation An internal error occurred in serialization module.

Action Please contact your software supplier.

INOXPE8742 **Recursion of entities detected**

Explanation During the processing of references to entities a recursion was discovered.

Action Please check the entity definition and correct the document.

INOXPE8743 **Entity stack overflow**

Explanation Entity stack overflow.

Action Please reduce the nested entity references.

INOXPE8744 **Internal error in index processing module detected**

Explanation An internal error occurred in the index processing module.

Action Please contact your software supplier.

INOXPE8745 **Internal error in index processing module detected**

Explanation An internal error occurred in the index processing module.

Action Please contact your software supplier.

INOXPE8746 **Internal error**

Explanation An internal error occurred during document processing.

Action Please contact your software supplier.

INOXPE8747 **Internal error in index processing module detected**

Explanation An internal error occurred in the index processing module.

Action Please contact your software supplier.

INOXPE8748 **Internal error in document processing module detected**

Explanation Processing aborted due to a server internal error.

Action Please contact your software supplier.

INOXPE8749 **Access to XNODEs / trigger functions during massload is not allowed**

Explanation The access to parts of the schema that specify X-Node or trigger function usage is not allowed when loading data with the Tamino Data Loader.

Action Set "ignore update" for the X-Node or trigger function parts of the schema or use the concurrentWrite option of the Tamino Data Loader.

INOXPE8750 **Tag or attribute name is too long**

Explanation The number of characters of a tag or attribute name exceeds the maximum supported value.

Action Shorten the name of the tag or attribute in question.

INOXPE8751 **Storing an object of this mapping type is not permitted**

Explanation Storing an object which is linked to another object is not permitted.

Action Please correct the document.

INOXPE8752 **Document not found in database**

Explanation A document referenced by the current command was not found in the database, because it was deleted by another concurrent access.

Action Re-issue the command.

INOXPE8753 **The element has contents although it is defined with object type "EMPTY"**

Explanation The element has contents although it is defined with object type "EMPTY".

Action Please correct either the document instance or the schema definition.

INOXPE8754 **Comments are not allowed between documents**

Explanation The input file contains a comment between two documents. This is not allowed.

Action Remove the comment.

INOXPE8755	**Invalid document name (ino:docname) specified**
Explanation	The document name given in the attribute ino:docname is empty.
Action	Either provide a document name in the attribute ino:docname or remove the ino:docname attribute.

INOXPE8756	**Invalid versioning mode**
Explanation	The document could not be stored, because the auto-version mode is invalid or the document is not in the correct versioning state.
Action	Make sure that the document is in the checkout-checkin auto-version mode and that the document is not checked out.

INOXQE6250	**Feature not implemented**
Explanation	The feature you tried to use is not implemented yet.
Action	Try an other method.

INOXQE6251	**internal exception**
Explanation	An internal exception has occurred.
Action	Please contact your software supplier.

INOXQE6252	**Type exception: non-atomic type in element/attribute**
Explanation	This error occurs if a non-atomizable type is encountered where a simple type is required, e.g. an element node belonging to a type that allows sub-elements is provided as a parameter for a function that expects a string.
Action	Check the operand's types or adopt the schema definition.

INOXQE6253	**Type exception: sequence occurred where atomic value required**
Explanation	Some functions and operators do not operate on sequences that contain that more than one entry.
Action	Check the operand types.

INOXQE6254	**Type can not be compared / sorted**
Explanation	Only totally ordered types such as numeric types, string types, boolean, dateTime, date and time can be compared and sorted.
Action	Try to use a totally ordered type or convert into such a type.

INOXQE6255 **Invalid argument to aggregation function**

Explanation The atomic values in a sequence upon which the avg() or sum() function is applied must have a common super-type that is either numeric or a date/time type.

Action Check the values in the sequence.

INOXQE6256 **Conversion detected an invalid value**

Explanation An invalid value could not be converted.

Action Check the query and the data.

INOXQE6257 **Invalid type denotation for atomic type**

Explanation A string provided as an atomic type denotation, for example with a user-defined function, does not denote a type.

Action Use proper type denotations, for example xs:integer or xdt:anyAtomicType.

INOXQE6261 **Duplicate function definition**

Explanation A query or a module definition contains two definitions of the same function, or an imported module defines a function that is already defined.

Action Remove the extra function definition.

INOXQE6262 **Module not found**

Explanation An XQuery module import directive could not be satisfied, because there is no such module.

Action Correct the import directive, or load an appropriate module definition.

INOXQE6263 **Invalid server extension type detected**

Explanation A server extension function is called that returns or consumes a type that is not supported by the XQuery processor.

Action Check the signature of the called server extension function.

INOXQE6264 **Cyclic module import**

Explanation A module M may not import another module that directly or indirectly imports module M.

Action Remove the cycle from the module import dependencies.

INOXQE6300 **Internal error**

Explanation An internal error has occurred in the XQuery execution engine.

Action Please contact your software supplier.

INOXQE6301 **Runtime type exception**

Explanation An invalid type was detected at XQuery execution time.

Action Correct the query.

INOXQE6302 **XQuery feature not implemented**

Explanation The query uses an unimplemented language feature. Please see the documentation and release notes for current product limitations.

Action Change the query.

INOXQE6303 **Invalid position for range**

Explanation The first position parameter for 'range' is negative or zero.

Action Check the query and data to find the wrong position value.

INOXQE6304 **Internal error: buffer overflow**

Explanation An intermediate result is too large.

Action Please contact your software supplier.

INOXQE6305 **Division by zero**

Explanation A division by zero was attempted (not defined mathematically).

Action Make sure that a divide by zero does not occur.

INOXQE6306 **numeric overflow has occurred**

Explanation An arithmetic operation yielded a result which is not representable with the data type.

Action Make sure that results do not exceed the representable range.

INOXQE6307 **duplicate attribute name occurred in element constructor**

Explanation An element constructor contained multiple attributes of the same name.

Action Make sure that attribute names of constructed elements are unique.

INOXQE6308 **sort utility failed**

Explanation An explicit or implicit invocation of the sorting utility failed. This may occur due to insufficient disk space for temporary files.

Action Check whether sufficient disk space is available for temporary files.

INOXQE6309 **namespace prefix conflict between constructed element and attribute**

Explanation A constructed element contained a conflicting namespace declaration while an attribute was added to it.

Action Use a different namespace prefix in the attribute's target environment.

INOXQE6310 **Processing of data with X-Tension or X-Node mapping is not supported by XQuery**

Explanation Currently no data with X-Tension (server extension) or X-Node mapping can be accessed by an XQuery query.

Action Formulate your query using Tamino X-Query instead of XQuery.

INOXQE6311 **temporary file access failed**

Explanation A problem has occurred while accessing a temporary disk file. This may occur due to insufficient disk space for temporary files.

Action Check whether sufficient disk space is available for temporary files.

INOXQE6312 **Document access error**

Explanation A document did not exist though it was part of a query result. This situation can occur when a query is executed with isolation level "uncommitted document", while another transaction has been rolled back after concurrently inserting the document.

Action Retry the query or use an isolation level different from "uncommitted document".

INOXQE6313 **Runtime type exception: non-atomic type in element/attribute**

Explanation This error occurs if a non-atomizable type is encountered where a simple type is required, e.g. an element node belonging to a type that allows sub-elements is provided as a parameter for a function that expects a string.

Action Check the operand's types or adopt the schema definition.

INOXQE6314	**Value cannot be converted**
Explanation	The textual representation of the value does not match the type it is being converted to.
Action	Check the query and the data.

INOXQE6315	**Runtime type exception: sequence occurred where atomic value required**
Explanation	Some functions and operators do not operate on sequences that contain more than one entry.
Action	Check the operand's types.

INOXQE6316	**Run-time encountered non-comparable type**
Explanation	Only totally ordered types such as numeric types, string types, boolean, dateTime, date and time can be compared and sorted.
Action	Try to use a totally ordered type or convert into such a type.

INOXQE6317	**Run-time encountered invalid argument to aggregation function**
Explanation	The atomic values in a sequence upon which the avg() or sum() function is applied must have a common super-type that is either numeric or a date/time type.
Action	Check the values in the sequence.

INOXQE6318	**Runtime type exception: empty sequence occurred where atomic value required**
Explanation	Some functions and operators do not operate on an empty sequence.
Action	Check the operand's types.

INOXQE6319	**Invalid simple type detected**
Explanation	In an expression, an invalid simple type was used.
Action	Check the actual type and the expected type with your query.

INOXQE6320	**Invalid combination of operand types for an arithmetic operation**
Explanation	The type of at least one operand is not valid for an arithmetic operation.
Action	Check where the types can occur in your query and correct it.

INOXQE6321 **Runtime type exception: invalid node-type**

Explanation Some operations only operate on nodes of certain types.

Action Check the node's type. Correct the path used to obtain the node.

INOXQE6322 **Non-simple type detected**

Explanation A non-simple type was detected where a simple type is required.

Action Check your query and the data to find a type mismatch.

INOXQE6323 **Conversion: facet 'minLength' was violated by a value**

Explanation The value to be converted was too short.

Action Check the query and the data.

INOXQE6324 **Incompatible types for cast operation**

Explanation The source type cannot be cast to the target type.

Action Check the type of the argument to the cast.

INOXQE6325 **Conversion error for comparison**

Explanation During the execution of a comparison, the values must be converted to a common type. This conversion failed, either because of incomparable types or because of invalid data.

Action Check your query and data to find the mismatch.

INOXQE6326 **Comparison undefined**

Explanation Some data types cannot be compared because they are partially ordered.

Action Check your query and data for undefined comparisons.

INOXQE6327 **Invalid last position for range**

Explanation The last position parameter for 'range' is smaller than the first and is not -1.

Action Check the query and data to find the wrong position value.

INOXQE6328 **Value out of range**

Explanation A value could not be converted into the internal representation because it is out of range, for example the allowed range for a month is 1 to 12.

Action Check your query and/or data.

INOXQE6329 **Invalid collation URI exception**

Explanation The specified collation URI is invalid.

Action Check the collation URI.

INOXQE6330 **Invalid collation attributes exception**

Explanation The specified collation attributes are invalid.

Action Check the collation attributes.

INOXQE6331 **Namespace prefix undefined**

Explanation An invalid namespace prefix was detected when casting a string value as a QName at query execution time.

Action Extend the static namespace context by adding a definition for the missing prefix.

INOXQE6332 **Invalid content expression in computed processing instruction**

Explanation The value of the content expression in a computed processing instruction constructor contains the string "?>".

Action Avoid expressions that may produce strings containing "?>".

INOXQE6333 **Invalid name for processing instruction**

Explanation The name of a constructed processing instruction must be different from "XML" (in any combination of upper and lower case).

Action Avoid expressions that may produce the string "XML".

INOXQE6334 **"Treat as" operation has detected two non-matching types during query execution**

Explanation A "Treat as" operation has detected two non-matching types during query execution.

Action Reformulate your query.

INOXQE6335 **Call stack overflow**

Explanation The call stack for user defined functions has exceeded its defined maximum size.

Action Inspect your XQuery program for potential programming errors, or increase the call stack's maximum size by means of the {?execution?} pragma.

INOXQE6336 **Memory allocation limit exceeded**

Explanation The memory limit that has been set by an XQuery execution pragma has been exceeded.

Action Extend the memory limit, or try to reduce the memory requirements by modifying the query.

INOXQE6337 **Invalid content expression in computed comment constructor**

Explanation The result of the content expression of a computed comment constructor contains two adjacent hyphens or ends with a hyphen.

Action Avoid expressions that produce adjacent hyphens or hyphens at the end.

INOXQE6338 **Sort buffer overflow**

Explanation An internal sort buffer has overflowed, because the representation of a single tuple did not fit into it.

Action Modify the query to reduce the size of tuples to be sorted.

INOXQE6339 **Multiple element children in document constructor**

Explanation An XQuery document constructor was supplied with more than one element child. This is not supported by the underlying data model.

Action Correct the query to avoid constructing multiple element children into a document node.

INOXQE6340 **XML parsing error while executing fn:parse()**

Explanation An XQuery invoked fn:parse, but the argument could not be parsed successfully as XML.

Action Provide well-formed XML.

INOXQE6349 **fetching result that is not available**

Explanation A non-sensitive cursor pre-calculates a system defined maximum number of result items. A fetch request has tried to access an item that was not pre-calculated.

Action Please contact your software supplier.

INOXQE6350 **Internal error**

Explanation An internal error has occurred in the XQuery compiler.

Action Please contact your software supplier.

INOXQE6351	**XQuery feature not implemented**
Explanation	The query uses an unimplemented language feature. Please see the documentation and release notes for current product limitations.
Action	Change the query.

INOXQE6352	**XQuery parsing error**
Explanation	One or more errors occurred while parsing the query.
Action	Correct the query appropriately and re-issue.

INOXQE6353	**End tag does not match start tag**
Explanation	The end tag of an element constructor does not match the start tag.
Action	Correct the query.

INOXQE6354	**Namespace prefix undefined**
Explanation	The namespace declaration is missing.
Action	Include a namespace declaration in the XQuery prolog.

INOXQE6355	**Invalid namespace URI specification**
Explanation	URIs must be given as string constants.
Action	Declare the URI literally.

INOXQE6356	**Attempted to redefine prefix**
Explanation	A prefix may only be defined once.
Action	Rename the prefix in subsequent declarations.

INOXQE6357	**The prefix 'xml' must be bound to the namespace 'http://www.w3.org/XML/1998/namespace'**
Explanation	The prefix 'xml' can only be declared when bound to the XML namespace URL as defined by the W3C.
Action	If your intent was to include the W3C's XML namespace, correct the URL. Otherwise use a different prefix.

INOXQE6358 **Function unknown**

Explanation This function is unknown. The function name is either misspelt or the wrong prefix is used.

Action Check the spelling and the function namespace.

INOXQE6359 **Variable undefined**

Explanation A variable that is used must be declared in a 'for' or 'let' expression.

Action Check spelling or add a 'for' or 'let' clause.

INOXQE6360 **Unbound path not allowed here**

Explanation Currently access to database data is only allowed via the input() function.

Action Use the input() function.

INOXQE6361 **Type exception: invalid operands for operator**

Explanation Static typing detected invalid operand types for the operator.

Action Please check the static types for the operator.

INOXQE6362 **Invalid path: documents have no parent**

Explanation The path tries to apply the parent axis (or '..') to a document node.

Action Check the path.

INOXQE6363 **Unknown collection**

Explanation The URL refers to a collection that does not exist in the chosen database.

Action Check the URL.

INOXQE6364 **XQuery applied on non-XML doctype**

Explanation XQuery is only applicable to XML data.

Action Use another tool for querying.

INOXQE6365 **XQuery applied on non-namespace-clean doctype:**

Explanation XQuery is only applicable on namespace-clean doctypes.

Action Apply proper namespace migration to doctype or use X-Query.

INOXQE6366 **Type exception: invalid input for function**

Explanation The parameters provided as an input to the function do not have the required type.

Action Check the correct parameter types in the documentation for the function.

INOXQE6367 **Compile time type exception**

Explanation An invalid type has beed detected at XQuery compile time

Action Correct the query.

INOXQE6368 **Default element namespaces are not allowed**

Explanation The XQuery draft is still uncertain whether default element namespaces defined in the query prolog or in generated elements pertain to element steps in location paths. To avoid migration problems with subsequent versions of Tamino, the use of default element namespaces is prohibited.

Action Please use a namespace prefix instead.

INOXQE6369 **A prefix must not begin with 'xml'**

Explanation This is stated in the Errata Document for the XML Namespaces Recommendation.

Action Chose a prefix that does not begin with 'xml'.

INOXQE6370 **Processing of data with X-Tension or X-Node mapping is not supported by XQuery**

Explanation Currently no data with X-Tension (server extension) or X-Node mapping can be accessed by an XQuery query.

Action Formulate your query using Tamino X-Query instead of XQuery.

INOXQE6371 **The URI 'http://www.w3.org/XML/1998/namespace' can only be bound to the prefix 'xml'**

Explanation According to "Namespaces in XML Errata, 4 November 2002" (http://www.w3.org/XML/xml-names-19990114-erratаNE05 substantive), the prefix xml is by definition bound to the namespace name http://www.w3.org/XML/1998/namespace. It may, but need not, be declared, and must not be bound to any other namespace name. No other prefix may be bound to this namespace name.

Action Use the prefix 'xml' or a different URI.

INOXQE6372 **No prefix may be bound to the URI 'http://www.w3.org/2000/xmlns/'**

Explanation This URI is by definition bound to the prefix 'xmlns'. It must not be declared.

Action Use a different URI.

INOXQE6373 **Invalid comparison**

Explanation Items to be compared must be of the same type, or both numeric, or both string or one of the types derived thereof.

Action Use string comparison via applying the xf:string() function to non-string operands.

INOXQE6374 **The prefix xmlns is used only to declare namespace bindings**

Explanation The prefix xmlns cannot be used unless in the form xmlns:prefix="uri" to declare a namespace binding.

Action Use another prefix.

INOXQE6375 **No multiple default collations allowed.**

Explanation Only one default collation can be defined.

Action To use more than one collation within a single query give the collation's URI explicitly in the comparison function or use the getCollation() function.

INOXQE6376 **Collation could not be obtained.**

Explanation The getCollation() function was not applied upon a path that pointed to an appropriate node.

Action The input to the getCollation() function must be a path that points to an appropriate element or attribute node. A node is appropriate if its corresponding schema definition contains a collation specification.

INOXQE6377 **Invalid Collation Identifier**

Explanation This string does not denote a valid collation.

Action Correct the spelling or make the collection known to the database.

INOXQE6378 **Invalid step in path**

Explanation A flat structure, i.e. something that is not a node, cannot be stepped into using any other axis than the self axis.

Action Either change the object that is stepped into so that it is of type node or node-set, or use only the self axis (or the dot) to refer to the object.

INOXQE6379 **Evaluation context undefined**

Explanation Processing of an expression relies on some component of the evaluation context that has not been assigned a value. Many context-sensitive functions like local-name() rely on the context item.

Action Make sure that expressions relying on the evaluation context are called when an evaluation context is defined as for example within a filter.

INOXQE6382 **XQuery cursor request must not specify a serialization method**

Explanation It is not possible to use a serialization method for an XQuery cursor request.

Action If you want to apply a serialization method to your query result, use a non-cursor query.

INOXQE6383 **Type exception: invalid input for internal function**

Explanation The parameters provided as an input to an internal function do not have the required type. Calls to internal functions are, for instance, contained in update queries. This error may thus indicate an invalid update statement.

Action Reformulate the update statement or check whether the intended update operation is possible at all.

INOXQE6384 **Invalid key or value in an optimization pragma.**

Explanation Valid optimization keys are "join" (possible values "default" and "index-only") and "level" (possible values "0" and "1").

Action Correct the optimization key and/or value.

INOXQE6385 **Invalid output handler function detected**

Explanation An invalid output handler has been detected. Please check the signature of the given output handler function.

Action Please check the signature of the given output handler function.

INOXQE6386 **This name must not be local**

Explanation Some names, for example those of user-defined functions, must be in a namespace. They must either be qualified, i.e. consist of a prefix and a local part, or be in a namespace by a default namespace declaration.

Action Use either a prefix declared in the query or add a default namespace declaration. For user-defined functions the predefined prefix 'local' can be used.

INOXQE6387 **The prefix 'local' may only be used when declaring a user-defined function.**

Explanation The 'local' prefix is by definition bound to the URI "http://www.w3.org/2003/11/xquery-local-functions" and is reserved for the definition of user-defined, i.e. local, functions.

Action Use another prefix.

INOXQE6388 **The name of a computed node is neither a string nor a QName.**

Explanation The name of a computed node, such as for example element or attribute node, must either be of type string or derived or of type QName.

Action Ensure that the expression provided as a computed node's name is of an appropriate type.

INOXQE6389 **A user-defined function returns a non-matching type**

Explanation If a user-defined function declares a result type, the type of the function's body must match this declaration.

Action Correct the function's body or delete the result type declaration.

INOXQE6390 **The prefix 'xs' must be bound to the namespace 'http://www.w3.org/2001/XMLSchema'**

Explanation The prefix 'xs' can only be declared when bound to the appropriate namespace URL as defined by the W3C's XML Schema spec.

Action If your intent was to include the W3C's xs namespace, correct the URL. Otherwise use a different prefix.

INOXQE6391 **The name of a computed PI node is not an NCName.**

Explanation The name of a computed PI node must be an NCName.

Action Ensure that the expression provided as a computed PI node's name is of an appropriate type.

INOXQE6392 **The content of a generated PI must be a string.**

Explanation The expression provided as the content of a generated PI node must evaluate to a sequence of strings.

Action Provide suitable content.

INOXQE6393	**Pragma not supported in library module**
Explanation	An XQuery library module contains a pragma that is valid only in a main module.
Action	Remove the pragma from the library module.

INOXQE6394	**Invalid node comparison**
Explanation	A node comparison requires that each operand is either a singleton or an empty sequence.
Action	Check the operands. If an operand is possibly a sequence with more than one entry, use round brackets and a [1] filter.

INOXQE6395	**Invalid key or value in an serialization pragma.**
Explanation	A valid serialization key is "provide-type-information" (possible values "yes" and "no").
Action	Correct the serialization value.

INOXQE6396	**Invalid key or value in an execution pragma.**
Explanation	Valid execution keys are "memory" (possible values are integers) and "call-stack-depth" (possible values are also integers).
Action	Correct the execution key/value.

INOXQE6397	**Duplicate parameter name in user-defined function**
Explanation	Each parameter in a user-defined function's parameter list must have a unique name.
Action	Rename one or more parameters.

INOXQE6398	**External variable definition does not conform to restricted XQuery syntax**
Explanation	An XQuery expression that is supplied to define an external variable is restricted to sequences of constants, type-specific constructor functions and node constructors.
Action	Reformulate the external variable definition to conform to the restrictions.

INOXQE6399	**Duplicate import directive**
Explanation	Two 'import module' declarations specify the same module namespace.
Action	Remove the extra import directive or replace it by a namespace declaration.

INOXQE6400 **Duplicate main-module pragma**

Explanation More than a single main-module pragma has been found in an XQuery.

Action Remove the duplicate pragma.

INOXQE6401 **Multiple declarations of element/type default namespace not allowed**

Explanation Only one default namespace for elements/types can be defined.

Action Delete one of the default namespace declarations.

INOXQE6402 **Multiple declarations of function default namespace not allowed**

Explanation Only one default namespace for functions can be defined.

Action Delete one of the default namespace declarations.

INOXQE6403 **Function is in a namespace different from the module's target namespace.**

Explanation The name of every function declared in a library module must have a namespace URI that is the same as the target namespace of the module.

Action Change the function's namespace or move to another module.

INOXQE6404 **A user-defined function is in a forbidden namespace**

Explanation The function name in a function declaration (when expanded) must not be in any of the following namespaces (among others): http://www.w3.org/XML/1998/namespace, http://www.w3.org/2001/XMLSchema, http://www.w3.org/2001/XMLSchema-instance, http://www.w3.org/2005/04/xpath-functions, http://www.w3.org/2005/04/xpath-datatypes.

Action Change the user-defined function's namespace by changing the prefix, or the prefix's binding, or the default function namespace.

INOXQE6406 **Invalid context for updating function**

Explanation An updating function was invoked in a context where only a non-updating function is permitted.

Action Modify the query to provide a proper function or context.

INOXQE6407 **Invalid context for non-updating function**

Explanation A non-updating function was invoked in a context where only an updating function is permitted.

Action Modify the query to provide a proper function or context.

INOXQE6408 **Invalid name for external variable**

Explanation A qualified name including a prefix is not supported as the name of an external variable.

Action Use a non-qualified name.

INOXQE6420 **Query not found**

Explanation The given handle does not address any prepared query.

Action Please correct the given query handle.

INOXQE6421 **Invalid query handle**

Explanation The format of the given query handle is wrong. The query handle must be an integer.

Action Correct the query handle.

INOXQE6424 **Missing parameter for query execution**

Explanation The prepared query declares external variables. For at least one of these variables, no suitable input parameter was provided.

Action Provide input parameter.

INOXQE6450 **Update results in non-well-formed document**

Explanation The update statement tries a modification that would result in a non-well-formed document, e.g., insert an element into an attribute, or insert a second root element. The error is accompanied by a message that explains the actual reason in more detail.

Action Correct the update statement.

INOXQE6451 **Conflicting update operations**

Explanation An update statement can consist of several atomic update operations. There may be conflicts between those operations, e.g., a subtree cannot be replaced and deleted at the same time.

Action Correct the update statement.

INOXQE6452 **Attempted to insert or modify one of the meta-attributes ino:id or ino:docname**

Explanation Using XQuery update, it is not allowed to modify the meta-attributes ino:id or ino:docname.

Action Correct your XQuery update statement.

INOXQE6453 **Attempt to modify a nonxml document**

Explanation It is not possible to modify non-XML documents using an XQuery update statement. Only deletion of complete non-XML documents is allowed by XQuery update.

Action Use the _process command in order to replace and thus modify a non-XML document.

INOXQE6454 **Attempt to update the same XNode-mapped field twice with different values**

Explanation An XNode column/field appears at different paths in the schema, and an XQuery update statement tried to modify at least two paths with different values.

Action Correct the XQuery update statement.

INOXQE6455 **Invalid node type passed to updating function**

Explanation A node was passed to an updating function, but the node type was not suitable for the function. tf:setDocname and tdf:setProperty can be applied to document nodes only, while tf:put can be applied to document or element nodes.

Action Modify the query to provide a node with a proper node type.

INOXQE6456 **Invalid invocation of tdf:setProperty for live property**

Explanation tdf:setProperty was used in an XQuery update on a live property. This is not allowed, live properties cannot be updated this way.

Action Modify the update statement, removing the invalid invocation of tdf:setProperty.

INOXQE6457 **Invalid doctype name**

Explanation The URI used in a call to fn:put contained an invalid doctype name. The provided doctype name was either not a valid QName, or it did not match the root element name of the XML document to be stored.

Action Provide a valid doctype name in the URI used with fn:put, or omit the doctype name from the URI.

INOXQE6458 **XML parsing error while converting nonXML document**

Explanation A nonXML document was passed to fn:put() with a URI indicating an XML doctype. The nonXML content however failed to be parsed successfully as XML.

Action Provide well-formed XML or store the document into an XML doctype.

INOXQE6459 **Cannot update transient node**

Explanation A transient node, i.e. a node resulting from a previous constructor, was detected as the subject of an update operation. XQuery update however can only be applied to persistent nodes.

Action Modify XQuery update statement to avoid applying update operations to transient nodes.

INOXQW6380 **A path expression results in an empty node-set**

Explanation An empty node-set as a result of a path expression might indicate an error in referencing the document structure or in a name spelling.

Action Ensure that the empty result is not due to a wrong path.

INOXQW6405 **Invalid entity or character reference**

Explanation The query contains an invalid entity or a character reference that does not map to a valid character. As a corrective action, the ampersand character has been treated as a literal, not as an entity introducer.

Action To avoid this warning, correct the query appropriately and re-issue.

INOXQW6423 **Execution of prepared query requires recompilation**

Explanation Due to schema, security or structure index changes the compiled query yielded by previous preparation is not longer valid. This requires a recompilation of the prepared query.

Action Recompile the prepared query.

INOXQW6425 **querySearchMode=approximate not applicable for this query**

Explanation This query cannot be executed in a streaming mode, thus the specified request parameter querySearchMode=approximate has no effect.

Action Do not use this request parameter.

INOXRE8802 **Internal error: input parameter error**

Explanation Internal error: Data Map was called with missing or invalid parameters.

Action Please contact your software supplier.

INOXRE8803 **Specified name too long**

Explanation The specified name is too long. Length limitations are described in the Tamino documentation.

Action Modify the schema definition and repeat your request.

INOXRE8805 **Invalid collection, element, attribute or server extension name**

Explanation The specified name is not a valid QName. The specified name starts with a colon and/or contains more than one colon.

Action Correct the schema definition and repeat the request.

INOXRE8806 **Collection is currently used by another user**

Explanation The request cannot be executed because at least one of the affected collections is currently held by another user.

Action Repeat the request.

INOXRE8807 **Doctype is currently used by another user**

Explanation There is a persistent lock on a doctype which prevents the current request from continuing.

Action Repeat the request when the request that has the persistent lock has finished.

INOXRE8808 **Index recreation currently not pending on the specified collection**

Explanation There is no index recreation pending to continue or reset. It is not necessary to execute the _admin command.

Action No action required.

INOXRE8809 **Index recreation is pending**

Explanation On the specified doctype an index recreation is pending. The requested action cannot be executed.

Action Execute the corresponding _admin request to continue or reset the index recreation.

INOXRE8810 **Index recreation is running**

Explanation The requested action cannot be executed while an index recreation is running on the specified doctype.

Action No action required.

INOXRE8811 **Collection name not found**

Explanation The specified collection is unknown.

Action Correct the collection name and repeat the request.

INOXRE8814 **Element/attribute name not found**

Explanation The specified element or attribute is unknown.

Action Correct the element or attribute name and repeat the request.

INOXRE8815 **Internal error: mapping already defined**

Explanation Internal error: mapping already defined.

Action Please contact your software supplier.

INOXRE8816 **Internal error while inserting an implicit element or attribute**

Explanation An internal error occurred while inserting an implicit element or attribute.

Action Please contact your software supplier.

INOXRE8818 **Duplicate collection name**

Explanation There is already a collection with the specified name.

Action Specify another collection name or undefine the existing collection.

INOXRE8819 **Duplicate element/attribute name**

Explanation The element or attribute to be inserted is already defined. It is not allowed to specify a schema containing two or more elements or attributes with the same name and the same parent.

Action Correct the schema definition and repeat the request.

INOXRE8821 **Internal error: invalid parent specification**

Explanation Internal error: invalid parent specification.

Action Please contact your software supplier.

INOXRE8822 **Invalid options specification**

Explanation The specified options are incorrect. Either unexpected options are specified or expected options are missing.

Action Refer to the Tamino documentation, correct your schema definition and repeat the request.

INOXRE8823 **Internal error: invalid object ID specification**

Explanation Internal error: an invalid ID was specified.

Action Retry with an increased transaction timeout value. If that doesn't help restart the Tamino database. If the problem still occurs please contact your software supplier.

INOXRE8824 **Internal error: invalid collection ID specification**

Explanation Internal error: an invalid ID was specified.

Action Please contact your software supplier.

INOXRE8825 **Invalid multiplicity specification**

Explanation The specified multiplicity is invalid. Either the multiplicity does not correspond with the mapping type, or a multiplicity of + or * is specified for attributes, or a multiplicity not equal to blank is specified for the root element.

Action Correct the schema definition and repeat the request.

INOXRE8826 **Invalid search type specification**

Explanation The search type is invalid or does not match the specified mapping type. For an external document summary file the specified shortname may be invalid.

Action Correct the schema definition and repeat the request.

INOXRE8827 **Internal error: invalid index ID specification**

Explanation Internal error: an invalid ID was specified.

Action Please contact your software supplier.

INOXRE8830 **Invalid schema structure: missing node definition**

Explanation An attempt was made to specify a node with a mapping type which requires at least one child with a specific other mapping type. This element is missing. (Example: Mapping to an SQL table requires at least one child mapped to an SQL column.)

Action Correct the schema definition and repeat the request.

INOXRE8831 **Deletion rejected because of depending objects**

Explanation The server extension object could not be deleted because at least one node references a server extensions function of the object to be deleted.

Action Update the schema definitions containing referencing nodes and repeat the request.

INOXRE8833 **Internal error: file structure/schema definition mismatch**

Explanation Internal error: file structure/schema definition mismatch.

Action Please contact your software supplier.

INOXRE8834 **Data map record could not be stored**

Explanation A Data Map record could not be stored. The definition of one node is too large.

Action Modify the schema definition and repeat the request. Please inform your software supplier.

INOXRE8835 **Data map record could not be updated**

Explanation A data map record could not be updated. The number of children for one collection or node is too large.

Action Modify the schema definition and repeat the request. Please inform your software supplier.

INOXRE8836 **Modifying or deleting of system collection/doctype rejected**

Explanation Collections and doctypes containing the Tamino namespace may not be modified or deleted.

Action No action required.

INOXRE8841 **Invalid mapping specification: invalid or unexpected primary key definition**

Explanation For a mapped SQL table at least one mapped SQL column must be indicated as the primary key using the keyword ino:sqlprimarykeys.

Action Correct the schema definition and repeat the request.

INOXRE8842 **Invalid mapping specification: invalid or unexpected password specification**

Explanation The specified Adabas password is either too long (maximum length is 8 characters) or unexpected (for nodes not mapped to AdaFile).

Action Correct the schema definition and repeat the request.

INOXRE8843 **Invalid mapping specification: invalid parent - child relation**

Explanation The relation between parent node and child node is not allowed. This is mostly caused by the object type of either parent or child node.

Action Correct the schema definition and repeat the request.

INOXRE8844 **Invalid mapping specification: invalid parent - child relation**

Explanation The relation between parent node and child node is not allowed. This is caused by either an unexpected mapping type of the child node or a node having a multiplicity of + or * between a node mapped to an SQL table or an Adabas file and the corresponding nodes mapped to an SQL column or Adabas field, multiple field or periodic group.

Action Correct the schema definition and repeat the request.

INOXRE8845 **Invalid schema structure: missing elements**

Explanation The mapping of the node is invalid. It requires other mapping in parent nodes. This error is mostly caused by a node mapped to an SQL column without having a corresponding node mapped to an SQL table, or mapped to an Adabas field without having a corresponding node mapped to an Adabas file.

Action Correct the schema definition and repeat the request.

INOXRE8847 **Invalid mapping specification: invalid or unexpected shortname specification**

Explanation The specification of a shortname is not allowed or does not conform to Adabas shortname rules.

Action Correct the schema definition and repeat the request.

INOXRE8848 **Invalid mapping specification: invalid or unexpected Adabas file specification**

Explanation The specification of a database ID and or file number is missing or invalid (Adabas file mapping) or not allowed (other mappings).

Action Correct the schema definition and repeat the request.

INOXRE8854 **Invalid mapping specification: invalid object reference specification**

Explanation The specified object reference was unexpected or refers to an undefined object. An object reference may only be specified for nodes mapped to another node.

Action Correct the schema definition and repeat the request.

INOXRE8856 **Invalid mapping specification: invalid or unexpected SQL specification**

Explanation For an SQL table mapping the table name was missing or a password was specified without userid. For an SQL column mapping the column was not specified. For other mappings SQL specific keywords are unexpected.

Action Correct the schema definition and repeat the request.

INOXRE8859 **Invalid mapping specification: invalid or unexpected format specification**

Explanation A format specification is either invalid (for Adafield mappings) or unexpected (for other mappings). A list of all valid formats is specified in the Tamino documentation.

Action Correct the schema an repeat the request.

INOXRE8860 **Invalid mapping specification: invalid or unexpected length specification**

Explanation A length specification is either invalid (for Adafield mappings) or unexpected (for other mappings). The length specification must conform to the format specification as defined in Adabas.

Action Correct the schema definition and repeat the request.

INOXRE8861 **Invalid mapping specification: invalid or unexpected precision specification**

Explanation A precision was either specified for a non-SQL column mapping, or is unexpected or out of range for the specified datatype. Dependencies between datatype and precision are described in the Tamino documentation.

Action Correct the schema and repeat the request.

INOXRE8862 **Invalid mapping specification: invalid or unexpected scale specification**

Explanation A scale was either specified for a non-SQL column mapping, or is unexpected or out of range for the specified datatype. Dependencies between datatype, precision and scale are described in the Tamino documentation.

Action Correct the schema definition and repeat the request.

INOXRE8863 **Invalid mapping specification: invalid or unexpected data type specification**

Explanation The specification of a data type is not allowed or does not conform to the list of supported datatypes. Please refer to the Tamino documentation for a list of supported data types.

Action Correct the schema definition and repeat the request.

INOXRE8865 **Invalid mapping specification: invalid or unexpected encoding specification**

Explanation The value for an encoding may only be specified for nodes mapped to an Adabas file or mapped to an Adabas field that has an alphanumeric format. The encoding must be a valid encoding string.

Action Correct the schema and repeat the request.

INOXRE8873 **Server extensions: function not found**

Explanation There is no server extension function with the specified function name.

Action Check the specified function name. Be aware that function names are case sensitive.

INOXRE8887 **The request cannot be executed within a session context**

Explanation In a session context it is not possible to recreate indexes for ino:creationDate or ino:lastModified.

Action Recreate the indexes in a session-less request.

INOXRE8888 **Adding a new node definition with the specified attributes is not supported**

Explanation Adding a new node definition with the specified attributes is not supported because of already existing documents.

Action Remove the affected documents and repeat the request.

INOXRE8889 **Modifying an existing node definition with the specified attributes is not supported**

Explanation The requested parameter may not be changed after the schema definition.

Action Undefine the schema and define the modified schema definition once again.

INOXRE8890 **Internal error: unsupported request**

Explanation The internal data map was called for an unsupported request.

Action Please contact your software supplier.

INOXRE8891 **Internal error: Data Map function failed**

Explanation The internal data map encountered an unexpected situation.

Action Please contact your software supplier.

INOXRE8892 **Internal error: Data Map corrupted**

Explanation The internal data map found insufficient data.

Action Please contact your software supplier.

INOXRE8893 **Internal error: conversion services failed**

Explanation An error occurred while the internal data map used conversion services.

Action Please contact your software supplier.

INOXRE8894	**Internal error: invalid file specification**
Explanation	An internal error occurred during access to an Infofile.
Action	Please contact your software supplier.

INOXRF8899	**Index recreation could not be finished successfully for doctype DOCTYPE in collection COLLECTION**
Explanation	An error occurred while finishing the index recreation. The collection is currently not usable.
Action	Restart the server and execute the _admin command to finish the index recreation.

INOXRI8838	**Request to create the unique constraint CONSTRAINT for doctype DOCTYPE in collection COLLECTION has failed and will be backed out**
Explanation	A request to create a unique constraint was running during server shutdown. The unique constraint is dropped during server start.
Action	Repeat the request to create the unique constraint.

INOXRW8801	**Request to create indexes for doctype DOCTYPE in collection COLLECTION is pending**
Explanation	A request to create indexes was aborted with an error or was running during server shutdown.
Action	Start the corresponding admin command to continue or reset the index creation.

INOXSE8903	**Memory allocation failed**
Explanation	There was not enough main memory available to perform the request.
Action	Possibly the machine is overloaded. Try again later.

INOXSE8905	**The combination of index-shortname and the search-type and/or map-type is not valid**
Explanation	The node with the search-type and/or map-type cannot contain a definition of index-shortname
Action	Check the map-type and the search-type.

INOXSE8906 **XML parser failure for schema definition**

Explanation The supplied schema definition is not well-formed XML.

Action Correct the schema definition.

INOXSE8909 **Internal error during schema processing**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXSE8910 **Invalid element content in schema definition**

Explanation The schema definition contains elements with mixed content, or the ino:file-format attribute has an illegal value.

Action Correct the schema definition.

INOXSE8911 **The specified mapping parameter(s) (adadsfnr, adadsdbid, adavoc...) can only be specified in a node which has the mapping type AdaFile**

Explanation The specifications such as adadsfnr, adadsdbid, adavoc etc. cannot be used with a mapping type other than AdaFile

Action Remove the mapping parameters or change the mapping type to AdaFile.

INOXSE8913 **Invalid structure of schema definition, hierarchy has to be collection - doctype - node**

Explanation The structure of the schema definition is invalid. It should be defined with the hierarchy collection - doctype - node(s).

Action Check the schema definition and fix the affected nodes.

INOXSE8914 **Internal error: buffer overflow**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXSE8915 **The keywords index-shortname, adadsdbid, adadsfnr, adavocdbid and adavocfnr are not supported in the current version**

Explanation These keywords are not supported in the current version.

Action Remove these keywords from the schema definition.

INOXSE8917 **Internal error: doctype without root element**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXSE8918 **Internal error: unknown object type**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXSE8920 **Internal error: unknown mapping type**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXSE8921 **ino:format or ino:length specified with SQL mapping**

Explanation ino:format and ino:length must not be specified with SQL mapping.

Action Correct the schema definition.

INOXSE8922 **Value has to be a number**

Explanation The given value could not be converted to a number.

Action Correct the schema definition.

INOXSE8923 **Specified number larger than allowed maximum**

Explanation The specified number was too large.

Action Correct the schema definition.

INOXSE8924 **Invalid doctype option specified**

Explanation An illegal value was specified for ino:options in the <ino:doctype> element.

Action Correct the schema definition.

INOXSE8926 **Collection name missing or invalid**

Explanation The name supplied in the ino:name attribute of the <ino:collection> element was either illegal or missing.

Action Check the schema document.

INOXSE8927 **Doctype name missing or invalid**

Explanation The name supplied in the ino:name attribute of the <ino:doctype> element was either illegal or missing.

Action Correct the schema definition.

INOXSE8929 **The node name specified does not conform to the XML specification**

Explanation The name specified in the ino:name attribute of an <ino:node> element does not conform to the XML specification.

Action Correct the schema definition.

INOXSE8930 **Doctype specified without any nodes**

Explanation Each doctype must have at least a root node.

Action Correct the schema definition.

INOXSE8931 **Node key missing**

Explanation The required ino:key attribute was missing for a <ino:node> element.

Action Correct the schema definition.

INOXSE8932 **Node object type missing**

Explanation The required ino:obj-type attribute was missing for a <ino:node> element.

Action Correct the schema definition.

INOXSE8933 **Node parent missing**

Explanation The required ino:parent attribute was missing for a <ino:node> element.

Action Correct the schema definition.

INOXSE8934 **Doctype contains multiple root nodes**

Explanation Each doctype must contain exactly one root node.

Action Correct the schema definition.

INOXSE8935 **Doctype contains no root nodes**

Explanation Each doctype must contain exactly one root node.

Action Correct the schema definition.

INOXSE8937 **Invalid parent reference**

Explanation The ino:parent attribute of an <ino:node> element did not point to another node.

Action Correct the schema definition.

INOXSE8938 **Invalid node option specified**

Explanation An illegal value was specified for ino:options in an <ino:node> element.

Action Correct the schema definition.

INOXSE8939 **Adabas dbid value too large**

Explanation The value specified for an Adabas database ID was too large.

Action Correct the schema definition.

INOXSE8940 **Adabas fnr value too large**

Explanation The value specified for an Adabas file number was too large.

Action Correct the schema definition.

INOXSE8941 **Length value too large**

Explanation The length value specified for an Adabas field was too large.

Action Correct the schema definition.

INOXSE8942 **Internal error: invalid ID reference**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXSE8943 **Internal error: bad query**

Explanation An internal error has occurred.

Action Please contact your software supplier.

INOXSE8944 **Object definition missing in the new schema definition**

Explanation One or more objects are missing in the schema definition although they are already defined in the data map. The current version does not support object deletion.

Action Complete the schema definition.

INOXSE8945 **Invalid type change**

Explanation Modification of type is not supported if type is CDATA.

Action Fix the schema definition.

INOXSE8946 **Shortname specified for ADAFile without adadsdbid/fnr**

Explanation Shortname specified for ADAFile without adadsdbid/fnr.

Action Complete the schema definition.

INOXSE8947 **Bad value for structure-index**

Explanation The specified value for structure-index of doctype is not supported.

Action Fix the schema definition.

INOXSE8948 **Attribute already declared**

Explanation An attribute is specified more than once.

Action Fix the schema definition.

INOXSE8949 **Different doctype and root element name**

Explanation The doctype and root element must have the same name.

Action Fix the schema definition.

INOXSE8950 **Too many indexes in schema**

Explanation The schema defines more than the maximum possible number of indexes.

Action Adapt the schema definition. For example, you may use multipath indexes in order to reduce the number of indexes being created.

INOXSE8951 **Too many elements/attributes for "lite" mapping"**

Explanation The schema defines more than the maximum possible number of elements/attributes for "lite" mapping".

Action Correct the schema definition.

INOXSE8952 **No more indexes available**

Explanation Attempted to create too many standard or text indexes in the schema definition.

Action Remove standard or text indexes or use multi-path indexes where applicable.

INOXSE8953 **Invalid node search type specified**

Explanation An illegal value was specified for the ino:search-type attribute.

Action Correct the schema definition.

INOXSE8954 **Scale value too large**

Explanation An illegal value was specified for the ino:scale attribute.

Action Correct the schema definition.

INOXSE8955 **Attribute missing**

Explanation There is a required attribute missing.

Action Fix a schema definition.

INOXSE8956 **Required node attribute missing**

Explanation One of the required attributes for the <ino:node> element is missing.

Action Correct the schema definition.

INOXSE8957 **Required doctype attribute missing**

Explanation One of the required attributes for the <ino:doctype> element is missing.

Action Correct the schema definition.

INOXSE8958 **Required collection attribute missing**

Explanation One of the required attributes for the <ino:collection> element is missing.

Action Correct the schema definition.

INOXSE8959 **Unknown node attribute specified**

Explanation An illegal attribute was specified for an <ino:node> element.

Action Correct the schema definition.

INOXSE8960 **Unknown doctype attribute specified**

Explanation An illegal attribute was specified for the <ino:doctype> element.

Action Correct the schema definition.

INOXSE8961 **Unknown collection attribute specified**

Explanation An illegal attribute was specified for the <ino:collection> element.

Action Correct the schema definition.

INOXSE8962 **Invalid or missing dbid parameter**

Explanation The explanation text in the< ino:messageline> element gives more information about the cause of the error.

Action Correct the schema definition.

INOXSE8963 **Invalid format value**

Explanation An illegal value was supplied in the ino:format attribute.

Action Correct the schema definition.

INOXSE8964 **Invalid object type value**

Explanation An illegal value was specified for the ino:obj-type attribute.

Action Correct the schema definition.

INOXSE8965 **Invalid data type value**

Explanation An illegal value was specified for the ino:data-type attribute.

Action Correct the schema definition.

INOXSE8966 **Invalid multiplicity value**

Explanation An illegal value was specified for the ino:multiplicity attribute.

Action Correct the schema definition.

INOXSE8967 **Invalid mapping type value**

Explanation An illegal value was specified for the ino:map-type attribute.

Action Correct the schema definition

INOXSE8968 **Invalid shortname value**

Explanation An illegal value was specified for the ino:shortname attribute.

Action Correct the schema definition.

INOXSE8969 **Unknown element name in schema definition**

Explanation Only <ino:collection>, <ino:doctype>, and <ino:node> are allowed as elements in a schema definition.

Action Correct the schema definition.

INOXSE8970 **Duplicate key value in schema definition**

Explanation The ino:key values must be unique within a schema definition.

Action Correct the schema definition.

INOXSE8971 **Invalid primary key reference in schema definition**

Explanation Every column reference in a primary definition for SQL table mapping needs to be declared as an SQL column mapping for one node in a subtree of the SQL table mapped node.

Action Correct the schema definition.

INOXSE8978 **Bad value for compression**

Explanation The specified value for compression of the doctype is not supported.

Action Fix the schema definition.

INOXSE8979 **Collection is currently used by another user**

Explanation The request cannot be executed because at least one of the affected collections is currently held by another user.

Action Repeat the request.

INOXSE8980 **Server extensions: external name and module name / function name are mutually exclusive**

Explanation Do not specify both external name and module name/function name for a server extension.

Action Correct the schema definition.

INOXTE7400 **Internal error**

Explanation A text retrieval internal error has occurred.

Action Please contact your software supplier.

INOXTE7401 **Empty search term**

Explanation An empty-valued search term is specified.

Action Please specify a non-empty search term in the query.

INOXTE7402 **Empty search token(s)**

Explanation One or more empty search tokens are specified.

Action Please specify non-empty search tokens in the query.

INOXTE7403 **Empty search term in word function**

Explanation An empty-valued search term is specified in the word function.

Action Please specify a non-empty search term in the word function.

INOXTE7404 **Invalid search term**

Explanation An invalid search term is specified.

Action Please specify a valid search term in the query.

INOXTE7405 **Invalid search token**

Explanation One or more invalid search tokens are specified.

Action Please specify valid search tokens in the query.

INOXTE7406 **Invalid search term in word function**

Explanation An invalid search term is specified in the word function.

Action Please specify a valid search term in the word function.

INOXTE7407 **Maximum number of search tokens exceeded**

Explanation The derived search tokens from the search term or specified search tokens have exceeded the maximum number allowed.

Action Please correct your search term/tokens in the query.

INOXTE7408 **Invalid wildcard usage**

Explanation Invalid wildcards are specified in the query.

Action Please refer to Tamino documentation for more details.

INOXTE7409 **Word function nesting**

Explanation Nesting of word functions is not allowed.

Action Please correct the query.

INOXTE7410 **Invalid highlighting marker**

Explanation Highlighting marker does not conform to an NCName.

Action Please correct the marker parameter for the highlighting function.

INOXTE7411 **Fragmented document reference**

Explanation Highlighting of document fragments is not supported.

Action Please correct the query for the highlighting function.

INOXTE7412 **Invalid node addressing**

Explanation Invalid node addressing of the document has occurred during the highlighting process.

Action Please correct the query for the highlighting function.

INOXTE7413 **No valid document node**

Explanation No valid document node is found for highlighting.

Action Please correct the query for the highlighting function.

INOXTE7415 **Invalid distance for proximity function**

Explanation The distance for a proximity function must be a positive integer.

Action Correct the distance and try again.

INOXTE7416 **index nonXML tsd:onTextInsert shadow X-Tension function not defined**

Explanation A shadow X-Tension function for the insertion of a non-XML text document was expected in the schema.

Action Define a shadow X-Tension function tsd:onTextInsert in the schema.

INOXTE7417 **index nonXML tsd:onBinaryInsert shadow X-Tension function not defined**

Explanation A shadow X-Tension function for the insertion of a non-XML binary object was expected in the schema.

Action Define a shadow X-Tension function tsd:onBinaryInsert in the schema.

INOXTE7418 **illegal phonrule definition**

Explanation The number of replace characters must not be higher than the number of characters to be replaced.

Action Correct the phonrule(s) in question.

INOXTE7419 **illegal stemrule definition**

Explanation The number of replace characters must not be higher than the number of characters to be replaced.

Action Correct the stemrule(s) in question.

INOXXE8600 **The group with name ino:admin may not contain any aclref elements**

Explanation The group with name ino:admin may not contain any aclref elements.

Action Make sure that the group ino:admin contains no aclref elements and try again.

INOXXE8601 **Not enough memory for the requested security operation**

Explanation Not enough memory for the requested security operation.

Action Free up some memory resources and try executing the operation again.

INOXXE8602 **This operation is not allowed for the special 2-Phase-Commit user**

Explanation This operation is not allowed for the special 2-Phase-Commit user.

Action Make sure you specify a user with the needed privileges for this operation.

INOXXE8603 **Namespace prefixes specified in ino:ace paths need to be defined**

Explanation Namespace prefixes specified in ino:ace paths need to be defined.

Action Please specify a namespace definition for each namespace prefix and try again.

INOXXE8604 **The aclref attribute may only reference existing documents**

Explanation The aclref attribute may only reference existing documents.

Action Please check that only valid references to existing documents are specified in the aclref attribute.

INOXXE8610	**Definitions for ino:userid, ino:groupname, and ino:aclname in the collection ino:security need to be unique**
Explanation	Definitions for ino:userid, ino:groupname, and ino:aclname in the collection ino:security need to be unique.
Action	First delete the existing entry before loading the new one with the same name into the database.

INOXXE8611	**Invalid path specified in an ino:ace element**
Explanation	Invalid path specified in an ino:ace element. The path must consist of names that are valid for XML element or attribute names, separated by slashes.
Action	Please correct the path specified in the ino:ace element and try loading the security definitions again.

INOXXE8699	**Administration command is not available**
Explanation	An administration command is not available.
Action	Please contact your software supplier.

INOXYE9002	**Internal database error has occurred**
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9003	**Internal database error has occurred**
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9004	**Internal database error has occurred**
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9005	**Internal database error has occurred**
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9006 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9007 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9008 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9009 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9010 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9011 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9012 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9013 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9014 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9015 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9016 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9017 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9018 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9019 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9020 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9021 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9022 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9023 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9024 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9025 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9026 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9027 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9028 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9029 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9030 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9031 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9032 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9033 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9034 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9035 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9036 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9037 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9038 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9039 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9040 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9041 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9042 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9043 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9044 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9045 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9046 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9047 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9048 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9049 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9050 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9051 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9052 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9053 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9054 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9055 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9056 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9057 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9058 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9059 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9060 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9061 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9062 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9063 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9064 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9065 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9066 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9067 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9068 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9069 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9070 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9071 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9072 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9073 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9074 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9075 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9076 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9077 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9078 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9079 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9080 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9081 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9082 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9083 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9084 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9085 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9086 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9087 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9088 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9089 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9090 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9091 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9092 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9093 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9094 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9095 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9096 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9097 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9098 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9099 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9100 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9101 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9102 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9103 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9104 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9105 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9106 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9107 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9108 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9109 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9110 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9111 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9112 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9113 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9114 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9115 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9116 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9117 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9118 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9119 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9120 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9121 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9122 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9123 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9124 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9125 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9126 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9127 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9128 **Doctype storage limit exceeded**

Explanation The storage limit for a single doctype was exceeded with regard to any of the following: -total number of documents -total collected size of documents -total number of occurrences of elements with reference index.

Action Please contact your database adminstrator.

INOXYE9129 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9130 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9131 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9132 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9133 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9134 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9135 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9136 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9137 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9138 **Bufferpool too small**

Explanation The buffer pool is to small to keep all data to be processed. In most cases this is caused by large amount of lock data.

Action Increase the value of database property "buffer pool size".

INOXYE9139 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9140 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9141 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9142 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9143 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9144 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9145 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9146 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9147 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9148 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9149 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9150 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9151 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9152 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9153 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9154 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9155 **The requested document(s) could not be locked**

Explanation An _XQL request was issued with _LOCKWAIT=no and _ISOLATION=shared/protected. At least one of the requested documents was locked by another user, therefore the lock could not be granted immediately.

Action Retry the query, or specify _LOCKWAIT=yes.

INOXYE9156 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9157 **Locking conflict has occurred**

Explanation The concurrently active transactions have issued conflicting lock requests.

Action No action required.

INOXYE9158 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9159 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9160 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9161 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9162 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9163 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9164 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9165 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9166 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9167 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9168 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9169 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9170 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9171 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9172 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9173 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9174 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9175 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9176 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9177 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9178 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9179 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9180 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9181 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9182 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9183 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9184 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9185 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9186 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9187 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9188 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9189 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9190 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9191 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9192 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9193 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9194 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9195 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9196 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9197 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9198 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9199 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9200 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9201 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9202 **Unique constraint violated**

Explanation Tamino detected either a duplicate ino:docname or a duplicate value for a unique constraint.

Action Either choose a unique ino:docname or modify the documents.

INOXYE9203 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9204 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9205 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9206 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9207 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9208 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9209 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9210 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9211 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9212 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9213 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9214 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9215 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9216 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9217 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9218 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9219 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9220 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9221 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9222 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9223 **Failed to create an additional database container**

Explanation Tamino failed to create an additional database container. This might be caused for example by a full disk or if the auto-expand option is set to "no".

Action Analyze and remove the cause of the error. Typically, the job log of the database session will provide more information. In the Tamino Manager, select the node "Job Monitor" below "Tamino", and view the job of the database session in the category "Running Jobs" or "Pending Alerts".

INOXYE9224 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9225 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9226 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9227 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9228 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9229 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9230 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9231 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9232 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9233 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9234 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9235 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9236 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9237 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9238 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9239 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9240 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9241 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9242 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9243 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9244 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9245 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9246 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9247 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9248 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9249 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9250 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9251 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9252 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9253 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9254 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9255 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9256 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9257 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9258 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9259 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9260 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9261 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9262 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9263 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9264 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9265 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9266 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9267 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9268 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9269 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9270 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9271 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9272 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9273 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9274 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9275 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9276 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9277 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9278 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9279 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9280 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9281 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9282 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9283 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9284 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9285 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9286 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9287 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9288 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9289 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9290 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9291 **Transaction aborted because it has taken too long**

Explanation The duration of the transaction has exceeded the maximum transaction duration. This can be caused by several circumstances: 1) The transaction could have done too much work to complete in the given time frame. 2) The number of transactions running in parallel has caused considerable delays in transaction execution. 3) The transaction might have waited for a resource that was held by another transaction for a very long time. In particular, this can happen if the number of XML work threads is too low. In this case, the transactions waiting for a resource block the XML work threads, and no XML work thread is available for the transaction holding the resource. 4) The transaction had to wait for a free XML work thread for a long time

Action The maximum transaction duration and the number of XML work threads can be configured using the Tamino Manager.

INOXYE9292 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9293 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9294 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9295 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9296 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9297 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9298 **Internal database error has occurred**

Explanation An internal error occurred. This could result in incorrect data.

Action Please contact your software supplier.

INOXYE9484 **Marked corrupt index for subsequent repair: collection name = COLL_NAME, node = NODE_PATH**

Explanation A corrupt index has been found and has been marked for index repair. It will not be used for query processing until it has been repaired.

Action Repair indexes in the corresponding doctype using _admin=ino:RepairIndex() - then retry the operation and recreate the index if necessary.

INOXYE9485 **Failed to prepare index marked as corrupt for subsequent repair index: collection name = COLL_NAME, node = NODE_PATH, reason = REASON**

Explanation An error occurred when attempting to prepare a corrupt index for a subsequent index repair.

Action Please contact your software supplier.

INOXYE9486 **Failed to mark index as corrupt due to a pending recreate index operation: collection name = COLL_NAME, node = NODE_PATH**

Explanation A corrupt index cannot be marked as corrupt while a recreate index operation or schema update is pending.

Action Repair the indexes in the corresponding doctype using _admin=ino:RepairIndex() - then retry the operation and recreate the index if necessary.

INOXYE9487 **Failed to mark index as corrupt due to recreate index operation in progress: collection name = COLL_NAME, node = NODE_PATH**

Explanation A corrupt index cannot be marked while a recreate index operation or schema update is in progress.

Action Wait until recreate index operation or schema update on the corresponding doctype is finished, then retry the operation or recreate the index.

INOXYE9488 **Error during index or constraint access**

Explanation An index or constraint is corrupted and must be recreated.

Action Recreate all indexes and constraints of the doctype via ino:RecreateIndex admin command.

INOXYE9489 **Error during index or constraint access**

Explanation An index or constraint is corrupted.

Action Please contact your software supplier.

INOXYE9490 **Error during index or constraint access**

Explanation An index or constraint is corrupted and must be recreated.

Action Recreate the indexes and constraints via the ino:RecreateIndex admin command or update define.

INOXYE9491 **Transaction aborted due to non-activity timeout**

Explanation The transaction has been aborted because there was no activity for a long time.

Action The time period for non-activity timeout can be configured using the Tamino Manager (Property "non-activity timeout").

INOXYE9492 **Transaction aborted due to administrator action**

Explanation The database administrator has cancelled this transaction.

Action No action required.

INOXYE9493 **Transaction aborted because journal space was too small**

Explanation The journal space could not accommodate all the information that was necessary to back out the update command.

Action Enlarge the journal space.

INOXYE9494 **Request terminated because it tried to modify a replication database**

Explanation The request was sent to a replication database. User requests are not allowed to modify a replication database; only the replication process can do this.

Action Send your request to the master of this replication database.

INOXYE9495 **Request terminated because the replication database is currently not up-to-date**

Explanation The database is set to replication type with 'Simultaneous Query', but the currently replicated log space of the server does not contain additional locking information. Therefore the database cannot process queries while it replicates updates of this log space. Simultaneous query will be enabled, however, when the log space of the current session of the master is replicated.

Action Wait until the log space of a session is replicated that permits simultaneous queries.

Alternatively, send your request to the master of this replication database.

INOXYE9496 **Transaction aborted due to deadlock**

Explanation The lock requests of concurrent transactions have caused a deadlock.

Action No action required.

INOXYE9497	**Transaction terminated because of ongoing replication process**
Explanation	There is a replication process in progress that does not allow simultaneous queries. Because the replication process always has top priority on a replication database, any user transactions that had been active were terminated.
Action	Wait until the replication process has finished or starts another session that allows simultaneous queries. Alternatively send your request to the master of this replication database.

INOXYE9498	**Request terminated due to database shutdown**
Explanation	The request has been terminated because the database is being shut down.
Action	No action required.

INOXYE9499	**Transaction aborted due to non-activity timeout or administration intervention**
Explanation	The transaction has been aborted because there was no activity for a long time or because it was stopped by the database administrator.
Action	The time period for non-activity timeout can be configured using the Tamino Manager (Property "non-activity timeout").

INOXYW9483	**Found indexes marked as corrupt which cannot be dropped - subsequent index repair with "continue" option required: collection name = COLL_NAME, doctype = DOCTYPE_NAME**
Explanation	A Tamino doctype contains indexes which must not be dropped, e.g. because they are used to implement a unique constraint.
Action	Issue _admin=inoRepairIndex() with the "continue" option for the same doctype in order to fix the corrupt indexes.

27 Trading Network Messages

1003	**System property {0} is invalid: {1}. To correct the property, go to the TN Properties page of the WmTN package in the Integration Server Administrator, or edit the "packagesWmTNconfigproperties.cnf" file.**
Explanation	The system property provided for Trading Networks is invalid.
Action	Correct the property in the Configure Properties page in My webMethods, or edit the 'IntegrationServer_directory\packages\WmTN\config\properties.cnf" file.

1008	**"{0}" is required.**
Explanation	Required input value is missing.
Action	Provide value for required input fields and try again.

1027	**You have attempted to use a feature that is restricted by your license. To be able to use all product features, please contact webMethods or your webMethods OEM solution provider to upgrade to an unrestricted version of Trading Networks.**
Explanation	User not allowed to create doctypes, attempt failed.
Action	To be able to use all product features, please contact Software AG Global Support to upgrade to an unrestricted version of Trading Networks.

1035	**User Status value(s) {0} already exist.**

1046	**Error registering TN''s XML content handler.**
Explanation	Error while registering content handler for "text/xml".
Action	Contact Software AG Global Support.

1119	**Encountered error while creating TN document**

1157	**New verify certificate set not added.**
Explanation	In webMethods Trading Networks, if a verify certificate set is not added to a partner, this error shows up.
Action	Add the very certificate set to the partner and try again.

1158	**New verify certificate set not updated.**
Explanation	In webMethods Trading Networks, if the new verify certificate set for a partner is not updated, this error shows up.
Action	Ensure that the new verify certifcicate set for a partner is updated and try again.

1160W	**Asset already exists in Trading Networks**
Explanation	The asset selected for import already exists in Trading Networks.
Action	To overwrite the existing asset with the one in the imported file, select the "force" option during the import process.

1161E	**An error occurred while retrieving package names.**
Explanation	My webMethods encountered an error while displaying the names of Integration Server packages.
Action	Take appropriate action to resolve the problem described in the exception and try to perform the action again.

1162W	**All processing rules were imported successfully. Processing rules that existed before the import were removed.**
Explanation	All the processing rules present in the import file were added to the Trading Networks database. All processing rules that existed before the import process were removed from the database. This happens when the Replace Rule List option is selected during the import of Trading Networks data.

1166	**Unable to delete doc type. There are some activity logs associated with this doc type. Either delete the associated activity logs or run this service again with "deleteLogs=true" to have them deleted automatically.**
Explanation	Unable to delete doc type because there are some activity logs associated with this doc type.
Action	Either delete the associated activity logs or run this service again with "deleteLogs=true" to have them deleted automatically.
1170	**Unable to import processing rule {0}. Document type(s) used in the processing rule is not defined.**
1171	**inserted**
1172	**updated**
1173	**deleted**
1174	**Inserted.**
1175	**Updated.**
1176	**Deleted.**
1177	**Invalid status provided. Provide the proper status.**
1178	**Manage Export Import**
1179	**The {0} you are trying to save has been modified by another user. To ensure that you are using the latest version, cancel your changes and reopen the {1}. Modify the latest version and save your changes**

1180 **Invalid "{0}". It should not start with "=".**

1181 **No Validator found for "{0}" Service: "{0}".**

1203E **Error retrieving certificates for keystore alias {0} and key alias {1}. Check the keystore configuration in Integration Server.**

Explanation The keystore was modified or deleted in Integration Server, which caused the keystore mapping in Trading Networks to break.

Action Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, create the keystore. If the keystore mapping in Trading Networks is incorrect, select the correct keystore alias and key name for the certificate.

1204E **Error retrieving keystore aliases.**

Explanation Trading Networks could not retrieve the keystore from Integration Server.

Action Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, ask the Integration Server administrator to create the keystore.

1205E **Error retrieving key aliases for the keystore alias {0}.**

Explanation Trading Networks could not retrieve the keystore from Integration Server.

Action Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, ask the Integration Server administrator to create the keystore.

19000 **Invalid facet provided to API - {0}.**

19001E **Error occurred while initializing Trading Networks charts during initialization of Trading Networks.**

Explanation Trading Networks charts could not be initialized due to an error faced during startup.

Action Restart Trading Networks.

19002E **Error occurred while initializing Trading Networks dashboarding store during initialization of Trading Networks.**

Explanation Trading Networks dashboarding store could not be initialized due to an error faced during startup.

Action Restart Trading Networks.

19003	**Hour value {0} is not in range.**
19004	**Dashboarding API inputs not valid.**
19005E	**Error occurred during Analytics API call.**
Explanation	An error occurred during Analytics API call.
Action	Check the Trading Networks logs for the cause of the failure and if required, contact your system administrator.
19006E	**afterDays parameter cannot be null.**
Explanation	afterDays parameter cannot be null.
Action	Supply a value for afterDays parameter.
19007E	**afterDays parameter should be a positive integer.**
Explanation	afterDays parameter provided is not a positive integer.
Action	Supply a valid value for afterDays parameter. The value must be a positive integer.
19008	**batchSize parameter should be a positive integer.**
19010	**API error**
19011	**Transaction data {0} written to dashboarding table**
2017	**Could not delete field definition**
2020E	**Error occurred while publishing event messages to ERF.**
Explanation	An error occurred while publishing event messages to NERV.
Action	Check the Trading Networks logs for the cause of the failure and if required, contact your system administrator.

2021	**Successfully published event message of type {0} to ERF.**
2023	**Error redefining type {0} ({1})**
Explanation	Error while updating the document type.
Action	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.
2061	**Error initializing type cache.**
Explanation	There may have been an SQLException that prevented the initialization of the document type cache.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
2069	**Error while defining type {0} ({1}).**
Explanation	The error encountered while defining the document type may be due to an SQLException or to a missing mandatory field.
Action	Look at the associated error message or stack trace in the logs and take appropriate action.
2103	**MODIFY AND RESUBMIT**
2105	**Invalid input. Provide a value from the configured list of User Status values.**
2120	**Error initializing attribute cache.**
Explanation	An SQLException may have prevented the attribute cache from being initialized.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
2174	**Unable to import init.xml due to exception message: {0}. Manually import init.xml as described in the Installation Guide.**
Explanation	An exception occurred while importing init.xml, as described in the message.
Action	Manually import init.xml as described in the Installation Guide.

2200...0	**Error encountered while reading USER status from the database. Exception message: {0}.**
Explanation	Encountered SQLException while reading user status from database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
2262	**Processing of invitation failed. {0}**
2263	**User not created for the partner.**
2264	**Updating the partner status to Invited has failed.**
2265	**Error occurred while changing the status of the invitations.**
2266	**Error occurred while changing the status of the following invitation: {0}.**
2267	**Error occurred while changing the status of the following archival service: {0}.**
2268	**Error occurred while changing the status of the archival services.**
2269	**Error occurred while changing the status of the invitations.The status should be either {0} or {1}.**
2270	**Error occurred while changing the status of the archival services.The status should be either {0} or {1}.**
2271	**Error occurred while changing the status of the queues.The status should be either {0}, {1}, {2}, or {3}.**
2272	**Error occurred while changing the status of the following invitation: {0}.Check the invite and provide all the necessary details.**

2303	**Exception encountered while getting TN assets dependency.**
Explanation	In the webMethods Trading Networks Export Import feature using MWS, when webMethods Trading Networks fails to get the dependency of the asset type during export, this exception is thrown.
Action	You need to select the dependent asset and perform the export again.

2304	**Exception encountered while exporting TN assets.The exception message is : {0}.**
Explanation	In the webMethods Trading Networks Export Import feature using MWS, when webMethods Trading Networks fails to get the asset data during export, this exception is thrown.
Action	Contact your system administrator.

2305	**Exception encountered while importing TN assets.The exception message is : {0}.**
Explanation	In the webMethods Trading Networks Import feature using MWS, when webMethods Trading Networks fails to import data, this exception is thrown.
Action	Contact your system administrator.

2306	**The import data file name is null or empty.**
Explanation	In webMethods Trading Networks, when you try to import data and the import data file name is null or empty, this error is thrown.
Action	Import the data again after adding the import data file.

2307	**The import data file {0} does not exist.**
Explanation	In webMethods Trading Networks, when you try to import a data file but the file does not exist, this error is thrown.
Action	Ensure that the file is available and try again.

2308	**The import file does not contain valid data.**
Explanation	In webMethods Trading Networks, when you try to import a file and it does not contain valid data according to the type format, this error is thrown.
Action	Add a file that contains valid data according to the type format and try to import it again.

24001E	**Error occurred for the following Document ID while writing to TRANSACTIONSUMMARYDATA table:{0}.**
Explanation	Writing to TransactionSummaryData table might fail due to many reasons. One reason is when the Trading Networks database is down.
Action	Check the Integration Server logs for the cause of the failure and if required, contact your system administrator.
24002	**Volume value summary data for the following Document ID was successfully written to CUSTOMATTRIBUTEVOLUMEVALUE table: {0}.**
24003	**Error occurred for the following Document ID while writing to CUSTOMATTRIBUTEVOLUMEVALUE table:{0}.**
24004	**Success and failed transactions summary data for the following Document ID was successfully written to TRANSACTIONSUCCESSFAILEDDATA and SUCCESSFAILEDCHARTDOCIDMAP tables: {0}.**
24005	**Error occurred for the following Document ID while writing to TRANSACTIONSUCCESSFAILEDDATA and SUCCESSFAILEDCHARTDOCIDMAP tables:{0}.**
24006	**Success and failed transactions summary data for the following Document ID was successfully updated in TRANSACTIONSUCCESSFAILEDDATA and SUCCESSFAILEDCHARTDOCIDMAP tables: {0}.**
24007	**Error occurred for the following Document ID while updating TRANSACTIONSUCCESSFAILEDDATA and SUCCESSFAILEDCHARTDOCIDMAP tables:{0}.**
24008	**Late FA summary data for the following Document ID was successfully written to TRANSACTIONLATEFADATA table: {0}.**
24009	**Error occurred for the following Document ID while writing to TRANSACTIONLATEFADATA table:{0}.**

24010 **The following custom class required to filter run-time events of type Document Attribute Added based on event's attribute name was not found in classpath: {0}**

24011 **The following error occurred while trying to filter run-time events of type Document Attribute Added: {0}**

24500 **Exception {0} occured during execution of event processor {1}**

25002W **Error occurred while subscribing to {0} run-time event. The dashboards may not display any data.**

Explanation Event processor did not subscribe to the run-time event type due to one of the following reasons:- Trading Networks NERV custom bundle was not copied to the NERV config bundles location.- Universal Messaging server was not up and running.

Action Ensure the following:- If you are using Trading Networks NERV custom bundle, ensure to copy the bundle to the NERV config bundles location. Refer to 9.7 webMethods Trading Networks Administrators guide for details.- If you are using Universal Messaging, ensure the server is up and running.

25003W **Error occurred while unsubscribing from {0} run-time event.**

Explanation Event processor did not unsubscribe from the run-time event type due to one of the following reasons:- Event processor did not subscribe to the run-time event type successfully.- Universal Messaging server was down after the processor subscribed to the run-time event type.

Action Ensure the following:- If the event processor subscribed to the run-time event type successfully.- If you are using Universal Messaging, ensure the server is up and running at all times.

25500 **The following error occurred while suspending or unsuspending document delivery for a partner: {2}. The PartnerId is {0}, and the Id of the schedule is {1}.**

25501 **Error occurred while adding a delivery suspension schedule.**

25502 **Error occurred while updating a delivery suspension schedule.**

25503	**Error occurred while viewing a delivery suspension schedule.**
25504	**Error occurred while deleting a delivery suspension schedule.**
25505	**Error occurred while activating a delivery suspension schedule.**
25506	**Error occurred while deactivating a delivery suspension schedule.**
25507	**Error occurred while changing the Suspension Status of a delivery suspension schedule.**
25508	**Error occurred while checking the validity of a delivery suspension schedule.**
25509	**Error occurred while checking or unchecking the Suspend Delivery checkbox.**
25510	**An exception occurred while switching a deliverySuspendData validity to {0}.**
25511	**An exception occurred while selecting invalid status deliverySuspendData.**
25512	**An exception occurred while selecting invalid status deliverySuspendData.**
26000	**Error occurred while adding a delivery suspension schedule to Integration Server.**
26001	**Error occurred while updating a delivery suspension schedule on Integration Server.**
26002	**Error occurred while viewing a delivery suspension schedule on Integration Server.**
26003	**Error occurred while cancelling a delivery suspension schedule on Integration Server.**

26004	**Error occurred on Integration Server while changing the status of a delivery suspension schedule to inactive.**
26005	**Error occurred on Integration Server while changing the status of a delivery suspension schedule to active.**
26006	**Successfully added the following delivery suspension schedule to Integration Server: {0}**
26007	**Successfully updated the following delivery suspension schedule on Integration Server: {0}**
26008	**Successfully fetched the following delivery suspension schedule from Integration Server: {0}**
26009	**Successfully cancelled the following delivery suspension schedule on Integration Server: {0}**
26010	**Successfully suspended the following delivery suspension schedule on Integration Server: {0}**
26011	**Successfully resumed the following delivery suspension schedule on Integration Server: {0}**
26012	**Error occurred on Integration Server while checking for the existence of a delivery suspension schedule.**
26013	**Error occurred while parsing the date and time of a delivery suspension schedule.**
26014	**Error invoking remote service - {0} for alias - {1}.**

26015 **Error invoking local service - {0}.**

26016 **Error occured retriving VFS list from ActiveTransfer aliases**

26017 **ActiveTransfer service is not executable, please check alias - {0} is accessible or not.**

26018 **Large Document Delivery to remote ActiveTransfer not supported**

26019 **View Transaction Settings**

26020 **Edit Transaction Settings**

26021 **Unable to connect to ActiveTransfer. Contact your System Administrator**

3011 **(username={0})already exists.No new account created.Mapping done.**

Explanation While creating a partner account, Trading Networks found an existing user with the same name. No new account was created. Mapping was completed..

Action Provide a unique name and try again.

3012 **Encountered error while enabling the {0} package.**

Explanation This error shows up when trying to enable the WmTN package.

Action Contact your system administrator.

3013 **Encountered error while disabling the {0} package.**

Explanation This error shows up while trying to disable the WmTN package.

Action Contact your system administrator.

3017 **An error occurred while trying to insert document (doc id = {0}, sender id = {1}) into the database.**

Explanation Exception occurred during inserting the documentinto the database, possibly due to a database or usage error.

Action See the exception message for details. Take appropriate action to resolve the problem described in the exception.

3023	**No such documents: {0}.**
3024	**Could not instantiate documents {0}.**
3025E	**Error occurred while reinitializing Trading Networks JDBC connection pool in Integration Server.**
Explanation	Trading Networks reinitializes the JDBC connection pool when a connection error occurs. This reinitialization disconnects all connections to the Trading Networks database. An error occurred during the reinitialization.
Action	Use the Integration Server Administrator JDBC Pools page to reinitialize the Trading Networks JDBC connection pool.
3027	**Exception in finding database specific Class: {0}**
3028	**TPA with id {0} is locked**
3068	**Error while persisting queue. For details check the full stack trace.**
Explanation	In webMethods Trading Networks, while registering a queue, if there is anyu error in scheduling the queue, this error is thrown.
Action	Check the full stack trace or contact your system administrator.
3069	**Error occurred while changing the status of the following queue: {0}.**
3070	**Error occurred while changing the status of the queues.**
3100	**Exception occured while clearing TNASSET_READTIMEKEEPER table.**
3243	**Cannot process message that is not javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart. Current message is: {0}**
Explanation	Cannot parse the message as it is not a javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart.
Action	Check the error message and take action as appropriate.

4000	**Successfully saved the {1} delivery suspension schedule to Trading Networks database. The Id of the schedule is {0}.**
4001	**Successfully updated the {1} delivery suspension schedule on Trading Networks database. The Id of the schedule is {0}.**
4002	**Successfully fetched the following delivery suspension schedule from Trading Networks database: {0}**
4003	**Successfully deleted the following delivery suspension schedule from Trading Networks database: {0}**
4004	**Successfully changed the status of the following delivery suspension schedule to {1} on Trading Networks database: {0}**
4005	**Successfully changed the suspension status of the following delivery suspension schedule to {1} on Trading Networks database: {0}**
4006	**Successfully fetched the delivery suspension schedule with PartnerId {0} from Trading Networks database.**
4007	**A delivery suspension schedule with the following name already exists in Trading Networks database: {0}**
4008	**Error occured while executing Stored Procedures**
4009	**Error occurred while creating jdbc pool for tenantId: {0} and stageId: {1}. The exception message is : {2}.**
4010	**No jobs queued on queue {0}**

4024	**Invalid Receiver ID**
Explanation	In webMethods Trading Networks, while setting the BizDoc envelope attribute, if the receiver ID is not a valid partner ID, this error is thrown.
Action	Enter a valid partner ID (for a receiver ID) and try again.

4168	**Exception encountered while listing all the processing rules.**
Explanation	Encountered an exception while getting the list of rules from the cache. Either the cache is not updated with data, or there is some exception in the database.
Action	The details of the exception is in the full message. Take appropriate action to resolve the problem described in the exception message.

4169	**Access denied, as the User "{0}" does not have the privilege to {1} {2}.**
Explanation	You do not have the required permission to take this action on the processing rule.
Action	Request that the Integration Server administrator assign the required permission.

4170	**Error while recognizing the document.**
Explanation	Error encountered while recognizing the document. The document may be corrupted.
Action	Check if the document is a valid XML document and not a corrupt document.

4177	**{0} contacts deleted with ContactID {1}.**
Explanation	Encountered data inconsistency issue while contact deletion. Expected exactly one matching contact.
Action	Contact Software AG Global Support.

4178	**{0} addresses deleted with AddressID {1}.**
Explanation	Encountered data inconsistency issue while address deletion. Expected exactly one matching address.
Action	Contact Software AG Global Support.

4179	**{0} connections deleted with ID {1}.**
Explanation	Encountered data inconsistency issue while destination deletion. Expected exactly one matching destination.
Action	Contact Software AG Global Support.

4209 **Error encountered while getting the host ID**

Explanation The Trading Networks profile cache might be corrupted.

Action The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

4210 **Error encountered while getting all the Processing Rule matches for the document.**

Explanation Encountered exception while retrieving rules from cache. The cache might not be updated.

Action The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message. Reload the WmTNWeb package.

4211 **Error encountered while getting all the Delivery Services.**

Explanation Encountered exception while retrieving delivery services from the database.

Action The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

4212 **Error encountered while getting RuleName with the name - {0}.**

Explanation The rule may have been deleted by someone in a different session.

Action Refresh the rule cache by executing the search again.

4213 **Error encountered while getting Last Change ID.**

Explanation This may be due to an exception while fetching the Last Change ID from the database.

Action The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

4214 **Error encountered while getting Processing Rule with ID - {0}.**

Explanation The rule may have been deleted by someone in a different session.

Action Refresh the rule cache by running the search again.

4215 **Error encountered while changing the ordinality of the Processing Rule.**

Explanation Changing the ordering of the processing rules in another session might have caused an error while validating or updating the ordinal numbering in the database.

Action Refresh the rule cache by executing the search again.

4216	**Error encountered while deleting the processing rules.**
Explanation	The rule might have been deleted by someone in a different session.
Action	Refresh the rule cache by executing the search again.

4217	**Error encountered while updating the processing rule with Rule Name - {0}.**
Explanation	The rule might have been deleted by someone in a different session.
Action	Refresh the rule cache by executing the search again.

4218	**Error encountered while creating the processing rule with Rule Name - {0}.**
Explanation	Error encountered while inserting the rule into the database.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

4219	**Error encountered while querying the processing rules.**
Explanation	The query would have failed while picking the rules. Check the database actions.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

4220	**Access denied, as the User "{0}" does not have the permission to {1} processing rule.**
Explanation	You do not have the permission to do the necessary action on the processing rule.
Action	Request that the Integration Server administrator assign the required permission.

4221	**Access denied, as the User "{0}" does not have the permission to {1} processing rule - "{2}".**
Explanation	You do not have the permission to do the necessary action on the processing rule.
Action	Request that the Integration Server administrator assign the required permission.

4228	**Exception while changing the processing rule status.**
Explanation	The rule might have been deleted by someone in a different session.
Action	Refresh the rule cache by executing the search again.

4237	**Error encountered while getting the profiles associated with Profile Group.**
Explanation	There might be a database error while retrieving the profile groups.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

4238	**Access denied, as the User "{0}" does not have the permission to {1} processing rule - "{2}".**
Explanation	You do not have the permission to do the necessary action on the processing rule.
Action	Request that the Integration Server administrator assign the required permission.

4241E	**Processing rule "{0}" change status failed. Processing rule update collision detected. This rule has been modified by another user. Refresh your rule list and retry this operation.**
Explanation	In webMethods Trading Networks, while changing the status of a processing rule, if it is modified by another user, this error is thrown.
Action	Refresh your rule list and try again.

4247E	**Exception encountered while moving the processing rule. Invalid Ordinal given in Select Location.**
Explanation	In webMethods Trading Networks, while moving the processing rule, if an invalid ordinal location is specified, this error is thrown.
Action	Specify a valid ordinal location and try again.

4258E	**Error encountered while creating the processing rule with Rule Name - "{0}". Rule name already exists. Change the name and save again.**
Explanation	In webMethods Trading Networks, while creating a processing rule, if the rule name already exists, this error is thrown.
Action	Ensure to give a unique processing rule name and try again.

4274E	**Error encountered while querying for the delivery queues.**
Explanation	In webMethods Trading Networks, if any error occurs while retrieving registered queues, this error is thrown.
Action	Contact your system administrator.

4305E	**The following sender(s) and receiver(s) configured in the processing rule do not exist in the system. Sender(s):"{0}" Receiver(s):"{1}"**
Explanation	An error occurred while trying to create or update a processing rule with senders and receivers that do not exist in Trading Networks.
Action	Ensure the senders and receivers are valid.

4306E	**The following sender(s) configured in the processing rule do not exist in the system: "{0}"**
Explanation	An error occurred while trying to create or update a processing rule with senders that do not exist in Trading Networks.
Action	Ensure the senders are valid.

4307E	**The following receiver(s) configured in the processing rule do not exist in the system: "{0}"**
Explanation	An error occurred while trying to create or update a processing rule with receivers that do not exist in Trading Networks.
Action	Ensure the receivers are valid.

4415	**IS DocType signature (ISDocType ={0}) is invalid. Provide a valid IS DocType signature.**
Explanation	Exception encountered while loading the corresponding IS docType.
Action	Check whether the namespace of the corresponding IS docType is correct.

4416	**Cannot add extended field definition. Extended field with name "{0}" already exists.**
Explanation	Extended field with same name already exists.
Action	Supply different name for extended field.

4417	**Cannot update extended field definition. Extended field with name "{0}" already exists.**
Explanation	Extended field with same name already exists.
Action	Supply a different name for the extended field.

4422 **A problem was encountered deleting the field defintion.**

4423 **Created New Permission "{0}" for role "{1}".**

4424 **Deleted Permission "{0}" for role "{1}".**

4429E **Importing a profile for {0} (id={1}), which is marked as "My Enterprise", but it has different ID than the existing My Enterprise profile for this Trading Network. Cannot change the identity of the My Enterprise profile.**

Explanation You are attempting to import a partner profile marked as "My Enterprise." However, the target Trading Networks server already contains a My Enterprise profile, with a different ID. The existing My Enterprise cannot be overwritten because the IDs are different.

Action Import the partner data without selecting the "My Enterprise" profile.

4430E **Importing a profile for {0} (id={1}), which is marked as "My Enterprise". A "My Enterprise" profile already exists for this Trading Network. If you want to update it, use the Force option.**

Explanation You are attempting to import a partner profile marked as "My Enterprise" without using the "Force import" option; however, the target Trading Networks server already contains a My Enterprise profile.

Action Import the partner data using the "Force import" option.

4431E **Error encountered while adding DLS artifacts with name {0}. The permissions for role {1} is null or empty.**

Explanation You are attempting to import or add a DLS dataset, but the dataset does not contain any permissions.

Action If you are adding a DLS dataset, specify the required permissions for the dataset. If you are importing a DLS dataset, make sure that the data is correct.

4432 **Error encountered while adding DLS artifacts with name {0}. The role name is null or empty.**

Explanation You are attempting to import or add a DLS dataset, but the dataset does not contain any roles.

Action If you are adding a DLS dataset, specify the required roles for the dataset. If you are importing a DLS dataset, make sure that the data is correct.

4433E	**Error encountered while adding DLS artifacts with name {0}. The partner with name {1} is referenced in DLS data, but this partner does not exist on your Trading Networks system.**
Explanation	You are attempting to import or add a DLS dataset, but the partner specified in the dataset is not present in the Trading Networks database.
Action	If this happens while importing a DLS dataset, make sure that the dependent partner profile is also imported along with the DLS dataset.

4434E	**Error encountered while adding DLS artifacts with name {0}. The document type with name {1} is referenced in DLS data, but this document type does not exist on your Trading Networks system.**
Explanation	You are attempting to import or add a DLS dataset, but the document type specified in the dataset is not present in the Trading Networks database.
Action	If this happens while importing a DLS dataset, make sure that the dependent document type is also imported along with the DLS dataset.

4435E	**Error encountered while adding DLS artifacts with name {0}. The processing rule with name {1} is referenced in DLS data, but this processing rule does not exist on your Trading Networks system.**
Explanation	You are attempting to import or add a DLS dataset, but the processing rule specified in the dataset is not present in the Trading Networks database.
Action	If this happens while importing a DLS dataset, make sure that the dependent processing rule is also imported along with the DLS dataset.

4436W	**A deleted profile with the same internal id already exists. Unable to recreate a deleted profile.**
Explanation	You are attempting to import a partner. However, the target Trading Networks server already contains a deleted partner with the same ID.
Action	Import the partner using the "Force import" option.

4461	**Profile has errors.**
Explanation	In webMethods Trading Networks, while adding a profile information, if the profile has any error, this error message is displayed.
Action	Contact your system administrator.

4464	**Attempt to import extended field "{0}" associated with the fieldgroup "{1}" failed. The extended field "{0}" associated with the fieldgroup "{1}" is not defined on your Trading Networks system.**
Explanation	This error occured because the extended field associated with the fieldgroup is not defined on your Trading Networks system.
Action	Define the extended field associated with the fieldgroup on your Trading Networks system and try again.
4467	**Administering Partner Onboarding**
4468	**The invitation with id "{0}" does not exist.**
4469	**Error occurred while changing the status of the partners.**
4470	**Error occurred while changing the status of the following partner: {0}.**
4471	**Partner Delivery Suspended**
4472	**Partner Delivery Unsuspended**
4473	**Error encountered deleting contact (contactID={0}).**
4474	**Error encountered deleting address (addressID={0}).**
4500	**A database error occurred while deleting a Binary Type.**
Explanation	In webMethods Trading Networks, at the time of deleting a binary type, if there is a database error, then this error shows up.
Action	Contact your system administrator.
5030	**Exception encountered while adding a new TPA.**
Explanation	Encountered an exception while writing the TPA to the database. There might be an SQL Exception while writing to the database or some of the constraints were missed out.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

5031	**Exception encountered while updating the TPA.**
Explanation	Encountered an exception while writing the TPA to the database. There might be an SQL Exception while writing to the database or some of the constraints were missed out.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

5032	**Exception encountered while fetching the TPA.**
Explanation	Encountered an exception while fetching the TPA from the database. There might be an SQL Exception while retrieving the TPA from the database or there are TPA caching errors.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

5033	**Exception encountered while deleting the TPA.**
Explanation	Encountered an exception while deleting the TPA from the database. This may be bacause of SQL Exception during writing to database or may be due to removing the TPA from Cache.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

5034	**No initial value created for tpaData.**
Explanation	The tpaData parameter was not created. A wrong service output might have caused the issue.
Action	Check if the initService defined in the TPA is correct and generates the correct output. The output of the TPA initService must generate an IData for the "tpaData" parameter.

5036E	**An exception occurred while retrieving TPA names.**
Explanation	My webMethods encountered an error while displaying the TPA names.
Action	Take appropriate action to resolve the problem described in the exception and try to perform the action again.

5037E	**An exception occurred while executing the validation service.**
Explanation	My webMethods encountered an error while validating TPA data on the Trading Partner Agreement Details page.
Action	Take appropriate action to resolve the problem described in the exception and try to perform the action again.

5038	**No output data was returned by the validation service.**
Explanation	The validation service does not conform to the format of the TPA validation service output record "wm.tn.rec:TPAValidateServiceOutput."
Action	Correct the service to pass the output in the format described by the output record "wm.tn.rec:TPAValidateServiceOutput."
5042	**Queue**
5043	**TPA updated on {0} at {1}**
5096	**Document delivered via ActiveTransfer. VFS Path: {0} ActiveTransfer Transaction ID: {1}**
6006	**Export file location not specified**
Explanation	Trading Networks is not able to find the export directory location.
Action	Specify the export directory location in the tn.deployer.export.dir TN property
6011	**Asset deletion failed - roll back to previous state failed.**
Explanation	Trading Networks is not able to delete the asset, because of which rollback to the previous state has failed.
Action	Contact your system administrator.
6013	**The binary file is either corrupt or not as expected.**
Explanation	The binary file provided for deployment is not valid.
Action	Provide a valid binary file.
6014	**The artifact ID is not available in the corresponding artifact properties file.**
Explanation	Trading Networks needs the artifact ID for installing the artifacts for deployment. This is missing from the artifact properties file.
Action	Provide the artifact ID in the artifact properties file or recreate the artifact ID.

6015	**checkpointId is required.**
Explanation	Trading Networks needs the checkpoint ID as input for the execution of the checkpoint service. This is missing.
Action	Add the checkpointId in the checkpoint service.

6016	**Delete Archive Schedule failed during rollback.**
Explanation	Trading Networks may need to delete the archive schedule during deployment roll back. This deletion of archive schedule has failed during rollback.
Action	Contact your system administrator.

6017	**Delete Private Queue for Partner failed during rollback.**
Explanation	Trading Networks may need to delete the private queue for Partner during deployment roll back. This deletion of private queue has failed during rollback.
Action	Contact your system administrator.

6018	**Delete Public Queue failed during rollback.**
Explanation	Trading Networks may need to delete the public queue during deployment roll back. The deletion of public has failed during rollback.
Action	Contact your system administrator.

6024	**The ProductNamespace "{0}" is not specific to Trading Networks.The expected ProductNamespace is "TN".**
Explanation	During deployment, a ProductNamespace, which needs to be passed to the service, is required. The expected ProductNamespace specific to Trading Networks that needs to be passed to the service is "TN".
Action	Specify the ProductNamespace as TN.

6025	**The runtime type is not specific to Trading Networks.**
Explanation	The Ping service requires type as input. The value of "type" for Trading Networks is TN.
Action	Specify type as TN.

6026	**deploymentId is required.**
Explanation	The deleteDeliveredArtifacts and activateArtifacts services need the deploymentId. This is not specified.
Action	Specify the deploymentId as the service input.

6030	**assetIdentifier(s) is required.**
Explanation	The Trading Networks assets that are to be deleted has not been provided.
Action	Provide the Trading Networks assets.

6032	**Asset deletion has failed.**
Explanation	If the deletion of a Trading Networks asset has failed, this message is displayed.
Action	Based on the additional details in the message, you need to fix the issue and try to delete the Trading Networks asset again.

6034	**Trading Networks is not able to retrieve the asset references for the asset: "{0}" of asset type: "{1}". "{2}"**
Explanation	Trading Networks is not able to retrieve the asset references for the specified asset due to an unexpected error.
Action	Try to delete the asset again. If it still does not go through, contact your system administrator.

6056	**Access denied. User "{0}" does not have the permission to {1} {2}, for Sender "{3}" and Receiver "{4}".**
Explanation	User does not have the permission required to perform the necessary action on the TPA.
Action	Ask the B2B Administrator to assign the user the required permission.

6057	**Access denied. User "{0}" does not have the permission to view {1}.**
Explanation	User does not have the permission required to view the TPA.
Action	Request the B2B Administrator to assign user the required permission.

6065	**Invalid "{0}". It should not start with "=".**

7010	**{0} is not a valid Trading Networks version. Rerun this program by specifying the supported version of your old Trading Networks.**
Explanation	The Trading Networks version selected for migration is not valid.
Action	Rerun this program by specifying the correct version number.

7011	**Source Server version is not provided. Rerun this program by specifying the source server version of Trading Networks.**
Explanation	The Trading Networks version selected for migration is not provided.
Action	Rerun the migration utility by specifying the version number.

7019	**The property file {0} does not exist.**
Explanation	The properties.cnf file does not exist.
Action	Add the properties.cnf file to the "IntegrationServer > packages > WmTN > config" location.

7020E	**Document Type with name "{0}" already exists. Change the name and save again.**
Explanation	Document type with the same name already exists.
Action	Change the document type name and save again.

7021E	**Error while changing the status of the doctype.**
Explanation	Document type status update operation failed.
Action	See the stack trace and take appropriate action.

7022E	**Error while changing the status of the doctype {0}.**
Explanation	Document type status update operation failed.
Action	See the stack trace and take appropriate action.

7023	**List of doctypes for changing status can not be empty.**
Explanation	List of doctypes is a mandatory field.
Action	Configure a list of doctypes while changing the status.

7031	**The Trading Networks configuration file was successfully migrated.**
7033	**The Trading Networks data was successfully migrated.**
7034	**Started migrating onboarding templates data.**
7035	**Successfully completed migrating onboarding templates data.**
7036	**Migrating onboarding templates data failed.**
7037	**Started migrating onboarding idtype.**
7038	**Successfully completed migrating onboarding idtype.**
7039	**Migrating onboarding idtype failed.**
7040	**Migrating Trading Networks dashboard data.**
7041	**Trading Networks dashboard data**
7042	**Trading Networks dashboard data was successfully migrated.**
7043	**Migrating summary data from runtime tables.**
7044	**Successfully migrated Trading Networks dashboard data.**
7045	**Failed to migrate Trading Networks dashboard data.**

7046	**Migrate Trading Networks dashboard data? (Note: This will take longer if runtime data size is big. This operation involves purging of existing data in the dashboard tables, followed by populating data in the dashboard tables from runtime tables.)**
7047	**Migration selected for Trading Networks dashboard data.**
7048	**Migration not selected for Trading Networks dashboard data.**
7059	**Exception while fetching codes list for document type "{0}" and UUID "{1}" .**
7060	**Invalid document type passed while fetching codes list for document type "{0}" and UUID "{1}" .**
8001E	**new String[]{"Cannot process message that is not javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart. Current message is: {0} ","","0"}**
Explanation	Message cannot be parsed because it is neither a MimeMessage, nor a MimeBodyPart.
Action	Check the message type before invoking the service.
8013E	**Error encountered while downloading sample csv file. Please see error log for more details, contact your Administrator.**
Explanation	In webMethods Trading Networks, in Parner Onboarding, while downloading a sample csv file for uploading a partner, if any error is encountered, this message appears.
Action	Contact your system administrator.
8050	**A template field with this name already exists: {0}.**
Explanation	In webMethods Trading Networks, while creating a new template field, if the name is not unique, this error shows up.
Action	Ensure to have a unique template field name and try again.
8052	**An exception occurred while inserting template field (ID = "{0}", Name = "{1}").**
Explanation	In webMethods Trading Networks, while adding a template field, if an exception occurs while adding a new template field, this error is thrown.
Action	See the exception stack trace to find out the reason for this error.

8053 **An exception occurred while updating template field (ID = "{0}", Name = "{1}").**

Explanation In webMethods Trading Networks, while updating a template field, if an exception occurs while updating the template field, this error occurs.

Action Check the exception stack trace to find out the reason for the error.

8054 **An exception occurred while inserting template group (ID = "{0}", Name = "{1}").**

Explanation In webMethods Trading Networks, while inserting a template field group, if an exception occurs while updating the template field, this error occurs.

Action Check the exception stack trace to find out the reason for the error.

8055 **A group with this name already exists: {0}.**

Explanation In webMethods Trading Networks, while adding a group to a questionnaire template, if the name already exists, this error shows up.

Action Ensure to use a unique group name and try again.

8056 **An exception occurred while fetching template fields for group(ID = "{0}", Name = "{1}").**

Explanation In webMethods Trading Networks, while fetching template fields for a group, if an exception occurs, this error shows up.

Action Check the exception stack trace to find out the reason for the error.

8057 **A template with this name already exists: {0}.**

Explanation In webMethods Trading Networks, while adding a questionnaire template, if the name already exists, this error shows up.

Action Ensure to use a unique questionnaire template name and try again.

8059 **The invitation has expired. Contact your administrator.**

8060 **The invitation is disabled now. Contact your administrator.**

8061 **An exception occurred while querying templates.**

8062	**changed as following:**
8146	**VFS Path**
8146...0	**Sending the new email invitation failed.**
9000	**Invalid facet provided to API - {0}**
9001	**Access denied, as the User "{0}" doesnot have the permission to {1} {2}.**
Explanation	The corresponding user does not have permissions to perform the associated actions.
Action	Contact a B2B Administrator for granting the corresponding permissions.
9001...0	**Please supply the required value.**
9002	**Error encountered while fetching search results, page {0} requested is not found for queryId={1}. Contact your administrator to optimize the configuration of the TNQueryResults cache.**
Explanation	In webMethods Trading Networks, while getting the query results, if the page request for a query ID is null, this error is thrown.
Action	Contact your administrator to optimize the configuration of the TNQueryResults cache.
9002...0	**Please restore the original version of this service.**
9003	**Access denied, as the User "{0}" doesnot have the privilege to {1} {2}.**
Explanation	The corresponding user does not have permissions to perform the associated action.
Action	Contact a B2B Administrator for granting the corresponding permissions.
9003...0	**Could not configure Ehcache. Either the SoftwareAG-IS-TN.xml file is missing from the config folder or it is an invalid XML file.**

9004	**Access denied, as the User "{0}" doesnot have the privilege to view {1}.**
Explanation	The corresponding user does not have permissions to view the corresponding Trading Networks asset.
Action	Contact a B2B Administrator for granting the corresponding permissions.
9004...0	**Trading Networks Server startup failed. Error initializing Ehcache manager {0}. Contact your administrator to restore the SoftwareAG-IS-TN.xml file.**
9005	**Recipient info is not available for the recipientCert**
9006E	**Primary and secondary certificates already exist for this owner, partner, and usage combination.**
Explanation	A maximum of two certificates can be uploaded per unique combination of owner, partner, and usage.
Action	Delete the primary or secondary certificate before uploading an additional certificate.
9007	**Error occurred while initializing Ehcache cache manager and accessing cache from it. Error message : {0}.**
Explanation	An error occurred while initializing the Ehcache cache manager and accessing cache from it.
Action	Contact your system administrator.
9008	**Failed to initialize cache manager for Ehcache. The SoftwareAG_IS_TN.xml file is missing, replaced, or invalid.**
Explanation	webMethods Trading Networks failed to initialize the cache manager for Ehcache. The SoftwareAG_IS_TN.xml file is missing, replaced, or invalid.
Action	Add a valid SoftwareAG_IS_TN.xml file in the configurations folder.
9009E	**Error occurred while initializing Trading Networks because the following caches are not configured: {0}**
Explanation	An error occurred while initializing Trading Networks because one or more caches are not configured.
Action	Check the cache manager SoftwareAG.IS.TN, configure the missing caches, and restart Integration Server.

9010	**Error occurred while adding Ehcache Manager for tenantId: {0} and stageId: {1}. The exception message is: {2}**
9012E	**Certificate with certificate ID {0} is already the primary certificate.**
Explanation	The wm.tn.security:setPrimaryCertificate service was called incorrectly using the certificate ID of a primary certificate.
Action	Specify the certificate ID of the secondary certificate as input to wm.tn.security:setPrimaryCertificate service.
9015	**Database error in getting prepared statement or Set proper dequeue strategy map entry**
9016	**Error encountered in wm.tn.security:setPrimaryCertificate.**
TNS.0000.1010E	**Error while running archive operation: {0}.**
Explanation	Trading Networks encountered an exception while archiving documents.
Action	See the exception in the full message. Take appropriate action to resolve the problem described in the exception.
TNS.0000.1013	**{0} could not be completed because another {1} operation was under way or Archive_WorkTable has contents that were not cleaned up. If there is no archive/deletion service running, cleanup the table to complete the operation.**
Explanation	Trading Networks cannot complete the archive or delete operation either because another archive or delete operation is in progress or because the Archive_WorkTable has contents that need to be cleaned up.
Action	If no other archive or delete operation is in progress, clean up the Archive_WorkTable contents and restart the incomplete archive or delete operation.
TNS.0000.2004E	**Cannot save a {0} without a {1}.**
Explanation	Trading Networks cannot save the specified profile component because a required field is missing.
Action	Enter the value for the required field.

TNS.0000.2005E	**Error logging database event.**
Explanation	Trading Networks encountered an exception while writing an activity log entry to the database.
Action	See the exception written to the server log. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2006E	**Error encountered while deleting {0}. {1} rows changed in the database.**
Explanation	Instead of deleting exactly one row from a table in the database, Trading Networks deleted the specified number of rows.
Action	See the exception written to the server log. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2008E	**Table not recognized: {0}.**
Explanation	Trading Networks found a profile field in the database that refers to a nonexistent table.
Action	Ensure that your query is for an existing profile field.

TNS.0000.2009E	**Error while inserting document {0}.**
Explanation	Trading Networks encountered an exception while writing a document to the database.
Action	See the exception in the full message. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2011E	**Error while querying documents: {0}. Original SQL: {1}.**
Explanation	Encountered an SQLException while performing a document query.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0000.2012E	**Inserting field definition failed.**
Explanation	Attempted to add a profile field definition, but the database was unchanged.
Action	Contact webMethods Customer Care.

TNS.0000.2016E	**An attempt was made to access the SQL statement {0}, which was not defined in the configuration file.**
Explanation	Attempted to execute an SQL statement that is not available in the file of externalized SQL statements (dbops.sql).
Action	If you have modified the dbops.sql file, restore the file to its prior state.

TNS.0000.2026E	**An attempt was made to save an extended field with an unsupported data type. Name={0}, Data type={1}.**
Explanation	Attempted to save an extended field for a partner, but the field's value is not a supported data type.
Action	Supply a value that is one of the supported data types for an extended field.

TNS.0000.2027D	**Could not update type {0} for attribute {1}.**
Explanation	Attempted to save a document attribute, but the attribute did not reference a valid document type.
Action	If you are explicitly calling services to save an attribute, ensure that the attribute refers to a valid document type.

TNS.0000.2029E	**The database has no version information. Either it has not been initialized, or it has been changed to an invalid state by an external process.**
Explanation	The TNModelVersion table is missing. Data from this table was accidentally deleted, the table was dropped, or the database is corrupt.
Action	Restore this table from the most recent backup. If the database is corrupt, work with your DBA to determine the cause. In this case, you will need to restore the entire database to the most recent backup.

TNS.0000.2031S	**No model version information was available from the database.**
Explanation	The TNModelVersion table is missing. Data from this table was accidentally deleted, the table was dropped, or the database is corrupt.
Action	Restore this table from the most recent backup. If the database is corrupt, work with your DBA to determine the cause. In this case, you will need to restore the entire database to the most recent backup.

TNS.0000.2036E	**Unsupported encoding {0} declared in the TN config file (tn.store.encoding).**
Explanation	The tn.store.encoding property was set to an invalid value.
Action	Set the tn.store.encoding property to a valid value.

TNS.0000.2037S	**The model version specified (tnmv:) seems to be missing from the dbops.sql file in your WmTN package. Check the file and try again.**
Explanation	The dbops.sql file must begin with "-- tnmv: x.x", where "x.x" is the current TNModelVersion number. This line has been removed or altered.
Action	Restore the dbops.sql file to the correct state.

TNS.0000.2039S	**There was an error while reading the dbops.sql file in your WmTN package. The original error message was: {0}.**
Explanation	Encountered an exception while reading the dbops.sql file. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0000.2040E	**Error encountered while updating {0}. {1} rows changed in the database.**
Explanation	Instead of updating exactly one row in a table in the database, Trading Networks updated the specified number of rows.
Action	Contact webMethods Customer Care.

TNS.0000.2041W	**Error while redefining attribute {0} ({1}).**
Explanation	Encountered an SQLException while updating a document attribute.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0000.2042E	**Error encountered while updating {0}. {1} rows changed in the database for {2}.**
Explanation	Instead of updating exactly one row in a table in the database, Trading Networks updated the specified number of rows.
Action	Contact webMethods Customer Care.

TNS.0000.2047E	**No extended fields were deleted for group {0} (partnerID={1}).**
Explanation	Expected to delete exactly one row in the PartnerProfileField table in the database. Instead, Trading Networks did not delete any rows.
Action	There seems to be an error while deleting. Find out why the row did not get deleted.

TNS.0000.2051E	**Unable to insert binary object (partnerID={0}).**
Explanation	An INSERT statement was unsuccessful in adding a row to the database.
Action	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2064S	**There was an error interpreting the model version specifier (tnmv:) in the dbops.sql file in your WmTN package. The original error message was: {0}.**
Explanation	The dbops.sql table must begin with "-- tnmv: x.x", where "x.x" is the current TN Model Version number. This line has been altered.
Action	Restore this line to its correct state.

TNS.0000.2066E	**The main connection to the data store has not been initialized. Check the Trading Networks JDBC connection pool.**
Explanation	There is no connection to the Trading Networks database.
Action	Use the Integration Server Administrator JDBC Pools page to test the connection to the Trading Networks database. You may need to adjust the connection pool settings or verify that the database is functioning normally.

TNS.0000.2067E	**Extended field (fieldID={0}) not deleted (partnerID={1}).**
Explanation	A DELETE statement was unsuccessful in removing a row from the database.
Action	Check the database connection or see the logs for more detailed stack trace information and take appropriate action.

TNS.0000.2079E	**More than one extended field (fieldID={0}) removed in a single delete operation (partnerID={1}).**
Explanation	Instead of deleting exactly one extended field in the database, Trading Networks deleted the specified number of fields.
Action	Check which other extended fields could have been deleted along with the intended one, then recreate the appropriate extended fields and redo the mapping.

TNS.0000.2085E	**Cannot change a {0} without a {1}.**
Explanation	Attempting to update a profile component, but a required field is missing.
Action	Supply a value for the missing field.

TNS.0000.2089E	**Trading Networks could not retrieve data from your database. Go to the JDBC Pools page in the Integration Server Administrator and make sure your database URL, user name, and password are set correctly. Also make sure you created the Trading Networks database tables as described in the webMethods Installation Guide.**
Explanation	The TNModelVersion table is missing from the Trading Networks database. The reason can be one of the following: 1) The Trading Networks database tables have not yet been created. 2) Data from TNModelVersion table was accidentally deleted. 3) The TNModelVersion table was dropped. 4) Your database is corrupt.
Action	Check your database. If the Trading Networks tables have not been created, create them. If the TNModelVersion table is missing or not valid, recreate it. If your database is corrupt, work with your database administrator to determine the cause. You might need to restore your entire database from the most recent backup.

TNS.0000.2096E	**Document {0} from this sender was not successfully stored in the data store. The original exception message was: {1}.**
Explanation	Encountered an exception while writing a document to the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0000.2104E	**An attempt was made to access the SQL statement {0} before SQL statements were read from the disk.**
Explanation	An SQL statement was used before the SQL statement cache was initialized.
Action	If your package uses Trading Networks facilities, be sure to declare a dependency on the WmTN package in your package's manifest.v3 file.

TNS.0000.2110E	**Error decoding type {0}.**
Explanation	Encountered an IOException while decoding binary data from the database into a BizDocType object.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2112E	**Document type not saved. A document type with the name [{0}] already exists. Cannot have two document types with the same name but different IDs.**
Explanation	You cannot have two document types with the same name.
Action	Change the name of the document type and save it again.

TNS.0000.2114E	**The system could not load the JDBC driver {0} for connection to the data store. Check the CLASSPATH setting and try again.**
Explanation	The driver specified for the Trading Networks functional alias on the JDBC Pools Configuration page of the Integration Server could not be found.
Action	Make sure the driver is in your classpath.

TNS.0000.2119E	**Unknown or deleted attribute {0}.**
Explanation	The wm.tn.doc:setAttribute service was supplied an invalid attribute ID or name.
Action	Supply a valid attribute ID or name.

TNS.0000.2127E	**Error encountered while updating Contact. {0} rows changed in database for {1} {2}.**
Explanation	Instead of updating exactly one row in the Contact table in the database, Trading Networks updated the specified number of rows.
Action	Check the affected details and verify whether the data can be recreated.

TNS.0000.2131E	**Could not find doc {0}; no document type {1}.**
Explanation	Could not create a bizdoc from binary data in the database. The TN document type it references does not exist.
Action	The document type corresponding to the bizdoc may have been deleted, or the associated data may be corrupted. Contact Customer Care.

TNS.0000.2132E	**Could not archive documents.**
Explanation	Encountered an SQLException while archiving documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2133E	**Could not delete archived documents.**
Explanation	Encountered an SQLException while deleting archived documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2134E	**Could not delete documents.**
Explanation	Encountered an SQLException while deleting documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2135E	**Could not queue documents.**
Explanation	Encountered an SQLException while queuing a document for polling.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2136E	**Could not poll documents.**
Explanation	Encountered an SQLException while polling for documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2137E **Could not accept document.**

Explanation Encountered an SQLException while accepting a polled document.

Action The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2138E **Could not query the event table.**

Explanation Encountered an SQLException while querying activity log entries.

Action The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2139E **Could not delete the events.**

Explanation Encountered an SQLException while deleting activity log entries.

Action The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2140E **Could not instantiate document {0}.**

Explanation Encountered an SQLException while retrieving a document.

Action The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2141E **Could not check uniqueness {0}.**

Explanation Encountered an SQLException while querying the database to determine if a document is unique.

Action The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2142E **Could not get the user status.**

Explanation Encountered an SQLException while retrieving the user status of a document.

Action The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2143E **Could not insert the new document.**

Explanation Encountered an SQLException while saving a new document.

Action The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2144E	**Could not change status for {0}.**
Explanation	Encountered an SQLException while changing the status of a document.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2145E	**One of (fromdoc,todoc) must be persisted.**
Explanation	Attempted to relate two documents, but neither of them has been saved to the database.
Action	Save one or both of the documents to be related.

TNS.0000.2146E	**Could not relate {0} and {1}.**
Explanation	Encountered an SQLException while relating two documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2147E	**Could not get rels: doc={0}, gr={1}.**
Explanation	Encountered an SQLException while retrieving related documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2148E	**The following exceptions occurred:**
Explanation	The following exceptions were encountered while retrieving the full set of TN document types.
Action	See each of the following exceptions for details. Take appropriate action to resolve the problem described in each exception.

TNS.0000.2149E	**Database error while fetching all types: {0}.**
Explanation	Encountered an SQLException while retrieving the full set of TN document types.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2150E	**Database error while adding type {0}: {1}.**
Explanation	Encountered an SQLException while saving a new TN document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2151E	**Encoding error while putting type {0}: {1}.**
Explanation	Encountered an IOException while saving a new TN document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2152E	**Database error while updating type {0}: {1}.**
Explanation	Encountered an SQLException while updating a TN document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2153E	**Encoding error while updating type {0}: {1}.**
Explanation	Encountered an IOException while saving a new TN document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2154E	**Cannot aggregate STRING attributes.**
Explanation	Attempted to execute an aggregation operation (SUM, AVG, MIN, MAX) on a String attribute.
Action	Do not specify the aggregation operation.

TNS.0000.2160E	**Could not queue document for delivery (id={0}).**
Explanation	Encountered an SQLException while changing the status of a document to "QUEUED".
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2162E	**Trading Networks database pool is not configured. Please configure a database pool for functional alias "TN" and restart the WmTN package.**
Explanation	Data required to configure a connection to the database is missing or invalid.
Action	Use the Integration Server Administrator JDBC Pools page to recreate this data.

TNS.0000.2164E	**Error while logging an activity entry to the audit sub system. The exception message is : {0}.**
Explanation	Encountered an exception while publishing an activity log entry.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0000.2165E	**Error while reading the database configuration. The exception message is : {0}.**
Explanation	Trading Networks encountered an exception while reading the database configuration data.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception. You might need to use the JDBC Pools page in the Integration Server Administrator to recreate this data.

TNS.0000.2168E	**Trading Networks database pool is not configured properly. Make sure that a valid database pool is assigned for functional alias "TN" and restart the WmTN package.**
Explanation	Data required to configure a connection to the database is missing or invalid.
Action	Use the Integration Server Administrator JDBC Pools page to recreate this data.

TNS.0000.2169E	**Unable to locate the database configuration information. File {0} does not exist.**
Explanation	A file required to configure a connection to the database is missing.
Action	Use the Integration Server Administrator JDBC Pools page to recreate this data.

TNS.0000.2170E	**Trading Networks database pool is not configured properly. Make sure that a valid database pool is assigned to functional alias "TN" and try again.**
Explanation	Data required to configure a connection to the database is missing or invalid.
Action	Use the Integration Server Administrator JDBC Pools page to recreate this data.

TNS.0000.2175E	**The database connection pool associated with TN should allow at least 2 connections. Your TN pool is currently configured with a maximum of {0} connections. Aborting TN startup. Please increase your TN database pool maximum and restart the server.**
Explanation	Trading Networks requires at least two connections for its pool. Trading Networks will not initialize with fewer than two connections.
Action	Use the Integration Server Administrator JDBC Pools page to increase the number of connections allowed for the Trading Networks database pool. Then restart your server.

TNS.0000.2180U	**Database error while deleting document type {0}: {1}.**
Explanation	Encountered an SQLException while deleting a document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2181E	**A BizDocType with this name already exists: {0}.**
Explanation	You cannot have two document types with the same name.
Action	Save the document type with a different name.

TNS.0000.2184E	**The profile field definition "{0}" already exists with a different ID. The field definition was not imported.**
Explanation	This error can occur when importing extended profile fields. The most likely cause is that the field was already manually created on the target server.
Action	If you do not intend to import extended field values, this error can be ignored. If you do intend to import extended field values, and no partner yet has a value for this field on your target server, you can change the ID of the field definition to match the one on the source server. Carefully update the ProfileFieldID key in the ProfileField table of the database into which you are importing.

TNS.0000.2185E	**An IDType with a key of "{0}" already exists with a different ID description. The IDType "{1}" was not imported. You will need to directly edit the IDType table in your database to correct this problem.**
Explanation	The error can occur when importing extended ID types. The most likely cause is that the IDType was already manually created on the target server.
Action	Change the Type column of the IDType table on the target database to match that of the source database.

TNS.0000.2186	**Could not update comments for document {0}.**
Explanation	Encountered SQLException while updating comments for document.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2199	**Error encountered while reading routing status from the database. Exception message: {0}.**
Explanation	Encountered SQLException while reading routing status from database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2212	**A scheduled archival service with this name already exists.**
Explanation	A scheduled archival service with the same name already exists.
Action	Change the name of the scheduled archival service and save again.

TNS.0000.2215	**Unable to save scheduled archive service "{0}".**
Explanation	Error encountered while updating the archive service.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2221	**Interval is not a valid integer.**
Explanation	Interval set in the schedule is wrong; it must be a valid integer.
Action	Correct the interval field in the schedule and save the schedule again.

TNS.0000.2222	**Interval must be greater than zero.**
Explanation	Interval set in the schedule is wrong; it must be greater than zero.
Action	Correct the interval field in the schedule and save the schedule again.

TNS.0000.2223	**The scheduled {0} is invalid. Format must be YYYY/MM/DD.**
Explanation	Schedule date must be of format YYYY/MM/DD.
Action	Change the schedule according to the format and save it again.

TNS.0000.2224	**The scheduled {0} is invalid. Format must be hh:mm:ss.**
Explanation	Schedule time must be of format hh:mm:ss.
Action	Change the schedule according to the format and save it again.

TNS.0000.2231	**The scheduled delivery date/time is in the past.**
Explanation	Schedule delivery date/time set must not be in the past.
Action	Change the delivery schedule with the date/time in the future.

TNS.0000.2232	**If an end time is supplied, an end date must also be supplied.**
Explanation	End date has to be supplied along with end time.
Action	Set the end date along with the end time, and save the schedule.

TNS.0000.2233	**End date/time is in the past.**
Explanation	End date/time must not be set in the past.
Action	End date/time should always be later than the start date/time. Correct the end date/time and save the schedule again.

TNS.0000.2234	**End date/time is before start date/time.**
Explanation	End date/time must not be before the start date/time.
Action	End date/time should always be later than the start date/time. Correct the end date/time and save the schedule again.

TNS.0000.2235	**Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.**
Explanation	Delivery schedule created with an incorrectly formatted date.
Action	Correct the date format and save the delivery schedule.

TNS.0000.2236	**Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss".**
Explanation	Delivery schedule created with an incorrectly formatted date.
Action	Correct the date format and save the delivery schedule.

TNS.0000.2244	**Unable to remove scheduled archival service "{0}".**
Explanation	Encountered exception while deleting archival service from database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2246	**Unable to update scheduled archival service "{0}".**
Explanation	Encountered exception while updating archival service to database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2301	**An exception occurred while listing the document attributes.**
Explanation	Encountered exception while getting document attributes from cache or database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.3001E	**Persistence Service Failed.**
Explanation	Encountered an exception while saving the document to the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.3002E	**An error occurred while trying to insert this document into the database. The original error message was: {0}.**
Explanation	Encountered an exception while saving the document to the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.3007E	**Non-unique ID(s) detected.**
Explanation	This incoming document already exists in the database. This is a duplicate document, based on the unique document criteria.
Action	Notify the document sender that the document sent is a duplicate.

TNS.0000.3008W	**This document is not unique. It matched {0} existing documents in the database.**
Explanation	This incoming document already exists in the database. This is a duplicate document, based on the unique document criteria.
Action	Notify the document sender that the document sent is a duplicate.

TNS.0000.3015E	**Could not get the document bytes.**
Explanation	An exception was thrown while adding the document content to the BizDocEnvelope. The document might be corrupt.
Action	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.3016E	**No such document: {0}.**
Explanation	The wm.tn.doc:view service was passed an invalid internal document ID.
Action	Supply a valid internal document ID to the wm.tn.doc:view service.

TNS.0000.3018E	**Invalid duplicate checking service.**
Explanation	Custom duplicate check was selected, but either a duplicate check service was not specified or the specified duplicate check service was invalid.
Action	Using My webMethods Server, update the TN document type and/or the processing rule and specify a valid duplicate checking service.

TNS.0000.3019E **The BizDocType refers to a non-existent duplicate checking service: {0}. It may have been renamed, disabled, or deleted.**

Explanation Custom duplicate check was selected, but no duplicate check service was specified or the specified duplicate check service was invalid. This error could also occur when the specified duplicate check service has been renamed, disabled, or deleted.

Action Using My webMethods Server, update the TN document type and/or the processing rule and specify a valid duplicate checking service.

TNS.0000.3020E **Duplicate document detected.**

Explanation You received a document that failed a custom duplicate document check. The custom duplicate checking service flagged the document as a duplicate.

Action You can ignore this message, or you can notify the sender of the document that you have received a duplicate.

TNS.0001.1001E **Content Part {0} does not exist in document {1}.**

Explanation The document does not contain the requested content part.

Action Request a different content part, or request this content part from a different document.

TNS.0001.1002E **Content for Part {0} of document {1} does not exist in TSpace.**

Explanation This is a large document and the requested content part was not found in the temporary storage.

Action Request a different content part, or request this content part from a different document.

TNS.0001.1003E **Error retrieving content of content part {0} of document {1}. The exception message is : {2}. The stack trace is : {3}**

Explanation An exception was thrown while retrieving the document content.

Action Take appropriate action to resolve the problem described in the exception message.

TNS.0001.1004E **Unable to find a document type for the given document type name, {0}.**

Explanation Could not find the document type specified for deleting.

Action Provide a valid TN document type name to the wm.tn.doc:deleteDocuments service.

TNS.0001.1006E	**Attempted to update system attributes for the document, but no rows were changed in the database.**
Explanation	Trading Networks encountered an error while attempting to update the system attributes of the document.
Action	Retrieve this document from the database and examine it to determine why the error occurred.

TNS.0001.1017	**System Attribute update failed.**
Explanation	Encountered an exception while updating the system attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.1018E	**Error when adding large content part named {0} to this document**
Explanation	Encountered an exception while adding a large content part to the document.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.1019E	**The actual exception is {0}.**
Explanation	Encountered an exception while adding a large content part to a document.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.1020E	**User{0} is not an administrator and attempted to retrieve a document (docID={1}) that does not belong to him.**
Explanation	Users without administrative rights can only retrieve documents that they have either sent or received.
Action	None.

TNS.0001.1021E	**You do not have the authority to retrieve this document. Only administrators may access documents that they did not send or receive.**
Explanation	Users without administrative rights can only retrieve documents that they have either sent or received.
Action	Request a user with administrative rights to access the document.

TNS.0001.2035E	**Recognize: unable to get XML DTD for comparison: {0} {1} {2} {3}**
Explanation	The DTD statement in the document may be incorrect.
Action	Check the document that is being processed to ensure that it is structured correctly. If it is not, notify the responsible party about this document.

TNS.0001.2036E	**BizDocTypeReg: ERROR invoking recognize for {0}**
Explanation	See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0001.2040E	**{0}: No envelope queries specified**
Explanation	The TN document type has no envelope queries defined.
Action	Use My webMethods to edit the TN document type and define envelope queries.

TNS.0001.2041E	**Error filling BizDocTypeStore cache**
Explanation	Encountered an error while reading the TN document types from the database and caching them in memory.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database.

TNS.0001.2042E	**Doctype info not initialized**
Explanation	The BizDocType Registry was not initialized.
Action	Try reloading the WmTN package.

TNS.0001.2043E	**Unknown type name: {0}**
Explanation	The wm.tn.doctype:view service was passed an invalid TN document type name.
Action	Pass a valid TN document type name to the service.

TNS.0001.2044E	**Unknown type id: {0}**
Explanation	The wm.tn.doctype:view service was passed an invalid TN document type ID.
Action	Pass a valid TN document type ID to this service.

TNS.0001.2045E	**Operation not supported for RecordDocType**
Explanation	You cannot create an instance of the RecordDocType.
Action	Creating an instance of the RecordDocType is not allowed.

TNS.0001.2054E	**IOException encoding pipeline**
Explanation	Encountered an exception while binary-encoding the data for an unknown document type. See the nested exception for details.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.2056E	**Query or Transform Failed**
Explanation	Encountered an exception while extracting a document attribute and converting its value.
Action	Verify that the attribute extraction query in the TN document type is valid.

TNS.0001.2057E	**Transform Failed**
Explanation	An error occurred while converting the attribute value.
Action	Use My webMethods to verify that the attribute details about the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.

TNS.0001.2058E	**Error generating query expression**
Explanation	Encountered an exception while generating an XML query to extract a document attribute.
Action	Correct the attribute extraction query on the TN document type.

TNS.0001.2059E	**No such BizDocType: {0}**
Explanation	The wm.tn.doc:createReply service was passed an invalid replyTypeId.
Action	Pass a valid replyTypeId to the service.

TNS.0001.2060E	**Doctype info not initialized. BizDocType registry has not been created.**
Explanation	The BizDocType Registry was not initialized.
Action	Try reloading the WmTN package.

TNS.0001.2061E	**An error occurred when constructing the XML Document object**
Explanation	A document object could not be constructed from the XML. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0001.2062E	**Recognition failed.**
Explanation	Unable to recognize document. See the next message for details.
Action	Take appropriate action to resolve the problem described in the next message.

TNS.0001.2063E	**There is not enough space on TSpace storage system to store the content of this large document**
Explanation	The HDD partition used for temporary storage of large documents is full.
Action	Either change the value of the tn.tspace.location property, or increase the size of the partition.

TNS.0001.2065E	**Unknown datatype encountered transforming attribute for FFDocType {0}**
Explanation	The attribute value supplied in the pipeline for the flat file document is not a String.
Action	Correct the document gateway service that puts this value in the pipeline. The attribute value must be a String.

TNS.0001.2066E	**FFDocType {0} encountered an unknown datatype while applying the {1} transformation to the "{2}" attribute.**
Explanation	The attribute value supplied in the pipeline for the flat file document is not a String.
Action	Correct the document gateway service that puts this value in the pipeline. The attribute value must be a String.

TNS.0001.2067E	**The {0} attribute is required by the {1} doctype. It is missing.**
Explanation	The attribute that is required for the flat file TN document type is missing in the pipeline.
Action	Correct the document gateway service that supplies the value for this attribute.

TNS.0001.2068E	**FFDocType {0} encountered an error transforming an attribute.**
Explanation	The specified flat file document type extracts an attribute. Trading Networks encountered an error while transforming the attribute value.
Action	Use My webMethods to verify that the attribute details for the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.

TNS.0001.2069E	**FFDocType {0} encountered an error while applying the {1} transformation to the "{2}" attribute: {3} : {4}**
Explanation	An error occurred while transforming the attribute value.
Action	Use My webMethods to verify that the attribute details for the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.

TNS.0001.2070E	**FFDocType {0} encountered an error reading the document bytes.**
Explanation	Encountered a problem while processing the "ffdata" InputStream.
Action	See the entire message for details.

TNS.0001.2071E	**FFDocType {0} encountered an error reading the document bytes. {1} : {2}**
Explanation	Encountered an exception while reading the "ffdata" InputStream. See the exception message and stack trace for details.
Action	Verify that your document gateway service is not corrupting the "ffdata" InputStream. Resend the document.

TNS.0001.2072E	**Cannot unregister a built-in DocType Category: {0}**
Explanation	The wm.tn.doctype:unregisterCategory service was passed the name of a built-in TN document type category, such as "XML", or "Flat file".
Action	Do not unregister a built-in category.

TNS.0001.2079E	**Could not determine document sender.**
Explanation	The TN document type is configured to determine the document sender from the connected user but it could not.
Action	See the entire message for details.

TNS.0001.2080E	**Could not determine document sender for doctype "{0}"because there is no connected user.**
Explanation	The TN document type is configured to determine the document sender from the connected user but it could not. A possible reason for the error is the lack of a connected user.
Action	Determine why there is not a connected user. Perhaps the document has been submitted by a background thread.

TNS.0001.2081E	**Could not get ProfileSummary for sender from connected user "{0}".**
Explanation	The TN document type is configured to determine the document sender from the connected user but it could not. There is a connected user, but it does not have a partner profile.
Action	Create a partner profile for the user, or instruct the user to log on the system using a valid partner account.

TNS.0001.2083E	**FFDocType {0} encountered an error reading the document bytes. Key "ffdata" is not found in the pipeline**
Explanation	The "ffdata" InputStream is missing in the pipeline.
Action	Verify that your document gateway service is not dropping "ffdata" from the pipeline. Resend the document.

TNS.0001.2084E	**FFDocType {0} encountered an error reading the content of document {1}.**
Explanation	This is a large document and Trading Networks encountered an error while reading the document's InputStream from Tspace (hard disk drive space). See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0001.2085E	**Error turning stream into bytes (docid={0})**
Explanation	The document has an unsupported encoding. See the server log or open this document in Transaction Analysis to see details about the error.
Action	Request the document to be resend using supported encoding.

TNS.0001.2086E	**Attribute transformation "{0}" has no data**
Explanation	The attribute referenced by this transformation is null.
Action	Gather details about this error, and contact Software AG Global Support.

TNS.0001.2088E	**A corrupted document was encountered in recognition: {0}**
Explanation	Trading Networks received an XML document that was not structured well.
Action	Correct the original document and resend it.

TNS.0001.2090E	**Unable to load the following TN document types because their classes are not found in the classpath: {0}. Either correct the classpath to include the required classes and restart the Server or, if you no longer use these document types, delete them using the wm.tn.doctype:delete service and then restart the Server.**
Explanation	There are TN document types in the database that are not available on the classpath.
Action	Correct the classpath to include the required classes and restart the server; or, if you no longer use these TN document types, delete them using the wm.tn.doctype:delete service, and then restart the server.

TNS.0001.2091	**Encountered an unsupported encoding**
Explanation	Encoding passed in the document is not supported by Integration Server.
Action	Change the document to a supported encoding.

TNS.0001.2092	**Error turning stream into bytes: {0}**
Explanation	Error encountered while converting the stream to bytes. This could happen if the stream was closed while still being read.
Action	Examine why the connection dropped while reading the stream.

TNS.0001.2093E	**This operation is not supported for MissingDocType.**
Explanation	The operation attempted to create a BizDocEnvelope from the MissingDocType class.
Action	If you developed code that creates instances of (No Suggestions) ensure that it does not attempt to create a BizDocEnvelope from the MissingDocType class.

TNS.0001.2094E	**ERROR: The Java class for this document type was not found.**
Explanation	The JAR file that holds the TN document type editor was not found.
Action	If you are viewing a Trading Networks XML or flat file document type, make sure that the tnclient.jar file is in the webMethods6\IntegrationServer\packages\WmTN\code\jars directory on the Integration Server file system. If you are viewing another category of TN document type, make sure that the JAR file with that TN document type editor is in the IntegrationServer\packages\WmTN\code\jars directory.

TNS.0001.2097	**Encountered an error while creating MAPI event to Optimize for EventMap {0} and for Sender with PartnerID {1}.**
Explanation	The error may be caused due to Broker being stopped.
Action	Start the associated Broker if it is stopped.

TNS.0001.3000E	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3001	**Unable to read mime message data source**
Explanation	The MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3002E	**Unable to read mime message data source**
Explanation	Problem while reading from input data source.
Action	Check input data source for errors.

TNS.0001.3003E	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3004E	**Unable to handle data of type: {0}**
Explanation	Attempted to add a message of type <msgType> to a multi-part MIME message. This type cannot be part of a multi-part MIME message.
Action	Check the message type that is being added to the multi-part MIME message. It must be either a multi-part MIME or a MIME message.

TNS.0001.3005E	**Unable to handle null data source**
Explanation	Cannot construct a MIME message from null data source.
Action	Pass valid, non-null data source to the service.

TNS.0001.3006	**Unable to read mime message data source**
Explanation	Problem while reading from input data source.
Action	Check input data source for errors.

TNS.0001.3007	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3008E	**Can not replace existing body part**
Explanation	Attempted to add a MIME body part to a MIME message that already contains a body part.
Action	Set the input flag 'replace' on the wm.tn.mime:addBodyPart service to 'yes'. This will replace the existing body part with the new one. Another solution is to set the flag 'multipart' to 'yes'. This will append the new body part to the existing one, making the message a multi-part MIME message.

TNS.0001.3009	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3010	**Unable to read mime message data source**
Explanation	Problem while reading the input data source.
Action	Check input data source for errors.

TNS.0001.3011E	**getBodyPart not supported on non multipart message**
Explanation	Attempted to get a MIME body part other than zero from a non-multipart MIME message.
Action	The number '0' (zero) is the only valid value for the input parameter 'index' of the wm.tn.mime:getBodyPartHeader and wm.tn.mime:getBodyPartContent services when the input MIME message is not a multi-part MIME message.

TNS.0001.3012	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3013 **Unable to read mime message data source**

Explanation Problem while reading the input data source.

Action Check input data source for errors.

TNS.0001.3014 **Unable to construct mime message**

Explanation Source data used to construct the MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3015 **Unable to read mime message data source**

Explanation Problem while reading the input data source.

Action Check input data source for errors.

TNS.0001.3016 **Unable to construct mime message**

Explanation Source data used to construct the MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3017 **Unable to construct mime message**

Explanation Source data used to construct the MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3018 **Unable to construct mime message**

Explanation Source data used to construct the MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3019 **Unable to construct mime message**

Explanation Source data used to construct the MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3020	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3021	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3022	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3023	**Unable to construct mime message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3024E	**Unable to determine Content type**
Explanation	MIME message does not contain content-type information. Message is improperly structured.
Action	Inform the message sender about the error.

TNS.0001.3025E	**Unable to get boundary for multipart mime message**
Explanation	MIME message does not contain message boundary information. Message is improperly structured.
Action	Inform the message sender about the error.

TNS.0001.3026	**Unable to determine content-type**
Explanation	MIME message does not contain content-type information. Message is improperly structured.
Action	Inform the message sender about the error.

TNS.0001.3027 **Unable to construct mime message**

Explanation Source data used to construct the MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3028 **Unable to read mime message data source**

Explanation The MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3029 **Unable to construct mime message**

Explanation Source data used to construct the MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3030 **Unable to determine content-type**

Explanation MIME message does not contain content-type information. Message is improperly structured.

Action Inform the message sender about the error.

TNS.0001.3031E **Unable to determine content-type**

Explanation MIME message does not contain content-type information. Message is improperly structured.

Action Inform the message sender about the error.

TNS.0001.3032E **Unable to read mime message data source**

Explanation The MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3033E **Unable to construct mime message**

Explanation Source data used to construct the MIME message is not a properly structured MIME message.

Action Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3034E	**Unable to parse Content-Type string**
Explanation	MIME message does not contain content-type information. Message is improperly structured.
Action	Inform the message sender about the error.

TNS.0001.3035E	**Cannot write message to outputStream, content is null**
Explanation	Message does not contain any data.
Action	Construct a MIME message with valid input data.

TNS.0001.3036E	**Operation can only be performed on parsed message.**
Explanation	The size of a MIME body part can only be determined for MIME messages that are parsed from a complete message. The size of each part cannot be determined when composing a MIME message.
Action	Do not attempt to obtain the size of a MIME body part that is part of a message that is being composed.

TNS.0001.3037E	**Unable to parse "Content-Disposition"**
Explanation	MIME message does not contain content-disposition information. Message is improperly structured.
Action	Inform the message sender about the error.

TNS.0001.3039E	**Unable to get content.**
Explanation	Error occurred while reading the message content.
Action	Check input data source for errors.

TNS.0001.3040E	**Message Digest Algorithm "{0}" not supported.**
Explanation	User has specified an invalid value for the 'digestAlgorithm' input parameter of the wm.tn.mime:setDigestAlgorithm service.
Action	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.

TNS.0001.3041E	**Cannot set header for message that is not multipart. Either specify subType or set header using addBodyPart**
Explanation	When calling the wm.tn.mime:createMimeData service, header for a non-multipart message cannot be set .
Action	Specify a value for subType, which will create a multi-part MIME message. Alternatively, for a MIME message that is not multi-part, headers can be specified when calling the wm.tn.mime:addBodyPart service.

TNS.0001.3101E	**Parameter input must be an InputStream**
Explanation	Input parameter 'input' must be an InputStream object.
Action	Pass in an InputStream object.

TNS.0001.3102	**Parameter mimeData cannot be null**
Explanation	Input parameter 'mimeData' must be sent.
Action	Pass in an mimeData object.

TNS.0001.3103E	**content cannot be null when adding a mime body part**
Explanation	Content cannot be null when adding a MIME body part
Action	Specify valid content.

TNS.0001.3104E	**Unable to handle content of type {0}**
Explanation	Input parameter 'content' must be one of the following types: InputStream, byte, array, or MIME message.
Action	Specify the value of the 'content' input parameter using one of the three allowed types.

TNS.0001.3105E	**Parameter index must be of type int**
Explanation	Specified a non-integer value for the 'index' input parameter when attempting to obtain a MIME body part.
Action	Check the value of the input parameter 'index' to ensure it is a non-negative integer.

TNS.0001.3106E	**outputStream required**
Explanation	Calls to the wm.tn.mime:writeToStream service require an OutputStream object to be specified for the 'outputStream' parameter.
Action	Pass an OutputStream object to the wm.tn.mime:writeToStream service.

TNS.0001.3107E	**Unknown digest algorithm {0}**
Explanation	User has specified an invalid value for the 'digestAlgorithm' input parameter.
Action	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.

TNS.0001.3108E	**Parameter mimeData cannot be null**
Explanation	The 'mimeData' input parameter has a null value.
Action	Specify a valid value for the 'mimeData' parameter.

TNS.0001.3109E	**Parameter headerName cannot be null**
Explanation	The headerName parameter cannot be null.
Action	Specify a valid value for the 'headerName' parameter.

TNS.0001.3112E	**A digest algorithm must be specified when creating a message digest.**
Explanation	The user has specified an invalid value for the 'digestAlgorithm' input parameter.
Action	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.

TNS.0001.3200E	**Cannot recognize certificates**
Explanation	Cannot recognize certificates.
Action	Certificates must be passed in as byte array objects.

TNS.0001.3201E	**Cannot recognize certificate**
Explanation	Cannot recognize certificates.
Action	Check the certificate format. The certificates must be a DER encoded ASN.1 format.

TNS.0001.3202E	**Cannot recognize certificate at index {0}**
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3203E	**Certificate at index {0} is not valid**
Explanation	Cannot recognize certificate at index: <index>
Action	Certificate must be passed in as byte array object.

TNS.0001.3204E	**Error attempting to parse message contents**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3205E **Error attempting to read from message source**

Explanation An error occurred while reading message content.

Action Check input data source for errors.

TNS.0001.3206E **Recipient certificate is not valid**

Explanation Cannot recognize certificates.

Action Check the certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3207 **Cannot recognize recipient certificate at index {0}**

Explanation Cannot recognize certificate in chain at index: <index>

Action Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3208 **Cannot recognize recipient certificate at index {0}**

Explanation Cannot recognize certificate in chain at index: <index>

Action Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3209E **Cannot recognize recipient certificate at index {0}**

Explanation Cannot recognize certificate at index: <index>.

Action Check the certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3210E **Certificate format is invalid for recipient certificate at index {0}**

Explanation Cannot recognize certificate in chain at index: <index>.

Action Check the certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3211E **Specified keylength {0}, is not allowed**

Explanation Invalid value specified for key length of RC2 encryption algorithm.

Action Specify one of the allowed key length values: "40", "64", or "128".

TNS.0001.3212E **Specified algorithm `{0}`, is not supported**

Explanation Invalid encryption algorithm is specified.

Action Specify one of the supported encryption algorithms: "TripleDES", "RC2", or "DES".

TNS.0001.3213E	**In getEncryptedMimeObject: Cannot handle datasource of type: {0}**
Explanation	When trying to create an encrypted message, the 'mimeSrc' object must be a MimeData object.
Action	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.

TNS.0001.3214E	**In getEncryptedMimeObject: Cannot handle null datasource**
Explanation	The 'mimeSrc' input parameter cannot be null.
Action	Specify a valid MimeData object in the 'mimeSrc' parameter.

TNS.0001.3215	**Unable to get signer''s private key**
Explanation	Private key for sender may be missing.
Action	Ensure in My webMethods that the sender's private key is associated.

TNS.0001.3216E	**Unable to get signer''s private key**
Explanation	Cannot recognize the private key.
Action	Check the supplied private key. It should be a DER encoded ASN.1 representation of an RSA private key.

TNS.0001.3217E	**Unable to get recipient certificate(s).**
Explanation	Cannot recognize the certificates.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3218E	**Signer''s certificate is not a valid data format**
Explanation	Cannot recognize certificates.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3219E	**Signer''s certificate is not recognized**
Explanation	Cannot recognize certificates.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3220E	**Input parameter mimeSrc to service createSignedData cannot be of type {0}. It should be of type MimeData.**
Explanation	When trying to create a signed message, the 'mimeSrc' object must be a MimeData object.
Action	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.

TNS.0001.3221E	**Input parameter mimeSrc to service createSignedData cannot be null. It should be of type MimeData.**
Explanation	When trying to create a signed message, the 'mimeSrc' object must be a MimeData object.
Action	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.

TNS.0001.3222E	**Unable to parse message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3223E	**Input parameter mimeSrc should be of type MimeData**
Explanation	The 'mimeSrc' object must be a MimeData object or an InputStream object.
Action	Pass in a MimeData or InputStream object. MimeData objects are created using the wm.tn.mime:createMimeData service.

TNS.0001.3224E	**Could not obtain message content**
Explanation	Error occurred while reading the message content.
Action	Check input data source for errors.

TNS.0001.3225E	**Content is not of a recognized encryption type**
Explanation	Cannot process the encrypted message.
Action	Contact the sender to re-send the message using the correct format.

TNS.0001.3226E	**Given certificate does not decrypt message**
Explanation	The message was not encrypted for the certificate that was passed to the service.
Action	First, validate that the correct certificate is used to decrypt the message. Then, if the certificate is the correct one, contact the message sender to determine which certificate was actually used to create the encrypted message.

TNS.0001.3229E	**Cannot Process this object. Write this MimeData to stream, then process that stream.**
Explanation	Cannot process the object.
Action	Write the MimeData to a stream and then process the stream again.

TNS.0001.3230E	**Input parameter mimeData must be a MimeData object**
Explanation	The 'mimeData' input parameter is not a MimeData object.
Action	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.

TNS.0001.3231E	**Message content is not certificates only data. Message could not be processed.**
Explanation	The message cannot be handled by the wm.tn.mime:processCertsOnlyData service.
Action	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate.

TNS.0001.3232E	**Input parameter mimeSrc must be a MimeData object**
Explanation	The 'mimeSrc' object must be a MimeData object.
Action	Pass a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.

TNS.0001.3233E	**Message content is not signed data. Message could not be processed**
Explanation	The message cannot be handled by the wm.tn.mime:processSignedData service.
Action	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate.

TNS.0001.3234E **Signing key is not valid**

Explanation The key used to sign the message is invalid.

Action Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3235E **Unable to sign document**

Explanation The key used to sign the message is invalid.

Action Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3236E **Invalid signer certificate file information**

Explanation The signer certificate chain is invalid.

Action The signer certificate chain must be an array of certificates.

TNS.0001.3237E **Certificate at index {0} not in recognizable format**

Explanation Cannot recognize certificate in chain at index: <index>.

Action Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3238E **Invalid certificate input at index {0}**

Explanation Cannot recognize certificate in chain at index: <index>.

Action Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3239E **Signature could not be verified**

Explanation The signature is invalid. The signature cannot be validated.

Action Contact the message creator to determine what message was originally sent.

TNS.0001.3240E **Expired certificate chain**

Explanation A certificate used to sign the message has expired.

Action Notify the message creator that the certificates used to sign the message are invalid.

TNS.0001.3241E **Error in certificate chain**

Explanation The certificate chain is invalid.

Action Check certificate format. The certificates must be a DER encoded ASN.1 format. Ensure that the certificates form a chain. If the chain consists of Cert A and Cert B, the issuer of Cert A should be the same as the subject of Cert B.

TNS.0001.3242E	**Untrusted certificate**
Explanation	The certificate used to sign the message is not signed by a trusted certificate authority. On the other hand, the signature is structured correctly.
Action	The message should not be trusted because the certificate authority is not trusted. Add the certificate authority to the trusted certificate authorities, or the message creator must use a certificate issued by a trusted certificate authority to sign the message.

TNS.0001.3244E	**Error using temporary storage space**
Explanation	An error occurred when using the temporary storage system.
Action	See the webMethods Integration Server User Guide for more details. Additional details are available in the exception message.

TNS.0001.3245E	**Unable to parse Encrypted Content. Invalid encrypted data.**
Explanation	The message cannot be decrypted.
Action	Check the server log for additional error information. The stack trace of this error should contain additional information why this message cannot be decrypted.

TNS.0001.3246E	**Unable to decrypt data.**
Explanation	The message could not be decrypted.
Action	Check the server log for additional error information. The stack trace of this error should contain additional information why this message cannot be decrypted.

TNS.0001.3247E	**Unable to parse Encrypted Content. Private key does not decrypt data.**
Explanation	The private key used to decrypt the message cannot decrypt the message.
Action	First, validate that the correct private key is used to decrypt the message. Then, if the private key is correct, contact the message sender to determine which certificate was used to create the encrypted message.

TNS.0001.3248E	**Unable to determine hash algorithm. Parameter micalg was null**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3249E	**Unable to determine hash algorithm. Unknown micalg: {0}**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3250E	**Improperly formed multipart/signed message**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3251E	**Cannot process body part of type {0}**
Explanation	Error occurred while processing the message.
Action	Check the error message and take action as appropriate.

TNS.0001.3252E	**Cannot process signed data with content type {0}**
Explanation	Message does not seem to be a signed message and thus cannot be processed by the wm.tn.mime:processSignedData service.
Action	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then, use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate. Otherwise, obtain the message content by using the wm.tn.mime:getBodyPartContent service.

TNS.0001.3253E	**Unable to parse Content Type**
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3254E	**Unable to compute message digest using algorithm: {0}**
Explanation	The digest algorithm is either invalid or is not a supported algorithm.
Action	Specify a supported algorithm. Valid values for the digest algorithm are: "SHA-1" or "MD5".

TNS.0001.3255E	**Either "profileAlias" or ("privKey","signerCert") are required**
Explanation	To execute properly, the service requires either a valid value for 'profileAlias' or a valid value for the 'privKey' and 'signerCert' input parameters.
Action	Specify a value for either 'profileAlias', or 'privKey' and 'signerCert'. See the webMethods Trading Networks Built-In Services Reference for more details about this service.

TNS.0001.3256E	**Either "profileAlias" or ("privKey","recipientCert") are required**
Explanation	To execute properly, the service requires either a valid value for 'profileAlias', or a valid value for the 'privKey' and 'recipientCert' input parameters.
Action	Specify a value for either 'profileAlias', or 'privKey' and 'recipientCert'. See the webMethods Trading Networks Built-In Services Reference for more details about this service.

TNS.0001.3257E	**Algorithm {0} not supported**
Explanation	The message was encrypted using the <algorithmName> algorithm. Cannot decrypt messages encrypted with this algorithm.
Action	Can decrypt messages that are encrypted with RC2, TripleDes, or DES algorithms only.

TNS.0001.3258E	**Invalid RC2 parameter version: {0}**
Explanation	This version of the RC2 algorithm is unsupported or invalid. The RC2 algorithm is supported with 40, 64, or 128 bit keys.
Action	Contact the message sender to ensure that a supported RC2 key length is being used.

TNS.0001.3259	**Supplied certificate cannot decrypt content**
Explanation	Decryption failed as the available certificates failed to decrypt content.
Action	Check if the certificates are correctly mapped to the user.

TNS.0001.3300E	**No algorithm specified**
Explanation	Mandatory 'algorithm' input parameter contained no value.
Action	Specify a valid value for the 'algorithm' input parameter. Valid values are either "SHA-1" or "MD5".

TNS.0001.3301E	**Specified algorithm {0}, not supported**
Explanation	The 'algorithm' Input parameter contained an invalid value.
Action	Specify a valid value for the 'algorithm' input parameter. Valid values are either "SHA-1" or "MD5".

TNS.0001.3302E	**Security provider not found**
Explanation	An internal error occurred.
Action	Contact Software AG Global Support.

TNS.0001.3303E	**Input to createMessageDigest must be byte[] or InputStream**
Explanation	The 'input' parameter must be a byte array or InputStream object.
Action	Specify a byte array or InputStream for the 'input' parameter.

TNS.0001.3304E	**Parameter "data" must be a byte[] or InputStream**
Explanation	The 'data' input parameter must be a byte array or InputStream object.
Action	Specify a byte array or InputStream for the 'data' parameter.

TNS.0001.3305E	**Parameter "signerInfo" cannot be null**
Explanation	Mandatory 'signerInfo' input parameter must contain a value.
Action	Specify valid information for the 'signerInfo' input parameter.

TNS.0001.3306E	**Unable to process "signerInfo" at index {0}**
Explanation	An error occurred attempting to process the signerInfo at index <index>.
Action	The server error log contains a stack trace with additional information about the error.

TNS.0001.3307E	**Invalid certificate chain**
Explanation	Cannot recognize certificates.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3308E	**Invalid certificate at index {0}**
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3309E	**Required parameter "signatureStream" cannot be null.**
Explanation	Required 'signatureStream' parameter cannot be null.
Action	Pass an OutputStream object to the wm.tn.mime:sign service, in the 'signatureStream' parameter.

TNS.0001.3310E	**Error occured reading input stream, cannot construct signature.**
Explanation	Error occurred while reading the message content.
Action	Check input data source for errors.

TNS.0001.3311E	**Hash Algorithm {0} not supported for signer at index {1}**
Explanation	Hash Algorithm <algorithmName> not supported for signer at index <index>.
Action	Change the <algorithmName> at <index> to be one of the allowed algorithm names: "MD5" or "SHA-1".

TNS.0001.3312E	**Bad certificate. Unable to set signer certificates.**
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3313E	**Input parameter "signature" cannot be null.**
Explanation	The 'signature' input parameter cannot be null.
Action	Pass the signature to verify into the service in the 'signature' input parameter. The 'signature' object should be either a byte array or an InputStream object.

TNS.0001.3314E	**Input parameter "signature" must be a byte[] or InputStream**
Explanation	The 'signature' input parameter must be a byte[] or InputStream.
Action	The 'signature' input parameter must be a byte[] or InputStream.

TNS.0001.3315E	**Input parameter "data" required for verifying detached signature**
Explanation	The 'data' input parameter cannot be null.
Action	Pass in the 'data' input parameter of the service, the data that is to be verified. The 'data' object should be either a byte array or an InputStream object.

TNS.0001.3316E	**Input parameter "data" must be a byte[] or InputStream**
Explanation	The 'data' input parameter must be a byte[] or InputStream.
Action	The 'data' input parameter must be a byte[] or InputStream.

TNS.0001.3317E	**An error occured while attempting to verify the signature.**
Explanation	Problem while reading from input data source.
Action	Check input data source for errors.

TNS.0001.3318E	**Signature provided is not PKCS#7 SignedData**
Explanation	Signature provided is not PKCS#7 SignedData.
Action	The wm.tn.mime:verify service can verify PKCS#7 SignedData signature only.

TNS.0001.3319E	**Input parameter "outputStream" must be an OutputStream**
Explanation	The 'outputStream' input parameter must be an OutputStream.
Action	The 'outputStream' input parameter must be an OutputStream.

TNS.0001.3320E	**Input contained no signer information when processed as {0} type signature**
Explanation	The message is not properly signed.
Action	This message cannot be verified. Contact the message creator to verify the proper message structure.

TNS.0001.3321E	**Parameter "data" must be null when parameter detachedSignature equals false.**
Explanation	The 'data' parameter must be null when 'detachedSignature' parameter equals to false.
Action	If the signature is detached, then set the 'detachedSignature' parameter to "true". Otherwise, do not pass in a value for 'data'. The signed message should be passed in via the 'signature' input parameter.

TNS.0001.3322	**Parameter "data" must not be null**
Explanation	The 'data' input parameter cannot be null.
Action	Pass the data into the service in the 'data' input parameter. The 'data' object should be either a byte array or an InputStream object.

TNS.0001.3323E	**Certificate chain cannont be null**
Explanation	Certificate chain cannot be null.
Action	Specify a certificate chain to use to sign this message.

TNS.0001.3324E	**Private key or keyAlias required**
Explanation	Private key or keyAlias required.
Action	To sign this message, specify either a private key, or use a keyAlias.

TNS.0001.3325E	**Unable to decode signed message. Verify that signature type specified (detached or implicit) matches actual type.**
Explanation	Unable to decode the signed message.
Action	Verify that the specified signature type (detached or implicit) matches the actual type.

TNS.0001.3326	**Unable to create digest. Input parameter "data" must be of type com.wm.app.tn.mime.DigestableInputStream or byte[].**
Explanation	Error while creating message digest.
Action	Check that the input parameter is passed correctly. Input parameter 'data' must be of type com.wm.app.tn.mime.DigestableInputStream, or byte[].

TNS.0001.3327E	**Unable to write message to outputStream.**
Explanation	Error occurred while writing the signed message.
Action	The server error log contains a stack trace with additional information about the error.

TNS.0001.3328E	**Only one "{0}" can be specified in "signerInfo"**
Explanation	When signing a message using a profile alias, you can only use one alias.
Action	Sign the message with only one profile alias.

TNS.0001.3400E	**Values are required for both input parameters type and id**
Explanation	Values are required for both 'type' and 'id' input parameters.
Action	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.

TNS.0001.3401E	**Input parameter type cannot be null**
Explanation	Values are required for both 'type' and 'id' input parameters.
Action	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.

TNS.0001.3402E	**Input parameter id cannot be null**
Explanation	Values are required for both 'type' and 'id' input parameters.
Action	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.

TNS.0001.3403E	**Unable to open SharedInputStream**
Explanation	An error occurred while reading from the specified data source.
Action	Check that the specified data source exists. The Integration Server error log should contain additional error information.

TNS.0001.3404E	**Value "{0}" for parameter type is not supported. Please select from allowed values.**
Explanation	The 'type' input parameter must be set to "file".
Action	Provide an allowed value. The 'type' input parameter must be set to "file".

TNS.0001.3501E	**Parameter "{0}" must not be null**
Explanation	The parameter called <parameterName> must be available but it does not exist in the pipeline .
Action	Specify a valid value for the <parameterName> parameter.

TNS.0001.4001E	**No profile store to validate partner ID**
Explanation	Unable to retrieve the profile store, probably due to a database error or a validation error.
Action	Check that the data is not corrupted or the database connection is active.

TNS.0001.4002E	**Error transforming attribute {0}: {1}**
Explanation	An exception was thrown while transforming a document attribute value.
Action	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.4003E	**BizDocAttribute: can''t connect to profile store**
Explanation	Encountered an exception during initialization.
Action	Contact Software AG Global Support. Prepare the following information: server and error logs, a copy of the Support Information page from the Trading Networks Console, and the WmTN/config/properties.cnf file.

TNS.0001.4006E	**No profile store to transform attribute {0}**
Explanation	Trading Networks was unable to retrieve the profile store.
Action	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.4007E	**Unable to transform attribute {0}: attribute type {1} doesn''t match function type {2}**
Explanation	Trading Networks could not transform the value of the attribute because the selected transformation is inappropriate for the data type of the attribute.
Action	Using My webMethods, update the TN document type that specifies the invalid transformation for the specified attribute. Select a transformation that is appropriate for the data type of the attribute.

TNS.0001.4008E	**Error fetching all attributes: {0}**
Explanation	An exception was thrown while reading all attributes from the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0001.4009E	**Error defining attribute {0}: {1}**
Explanation	An exception was thrown while saving an attribute to the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0001.4010E	**Error listing types for {0}: {1}**
Explanation	An exception was thrown while retrieving all TN document types that use an attribute.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0001.4011E	**Error redefining attribute {0}: {1}**
Explanation	An exception was thrown while updating an attribute in the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0001.4012E **Supplied value must be a number**

Explanation A processing rule contains extended criteria that uses a custom attribute with a NUMBER data type. However, the value you specified in the condition for this attribute is not a numeric value.

Action Using My webmethods, update the extended criteria in the processing rule to provide a numeric value for attributes that have a NUMBER data type.

TNS.0001.4013E **Supplied value can not be transformed to a date**

Explanation A processing rule contains extended criteria that uses a custom attribute with a DATETIME data type. However, the value you specified in the condition for this attribute is not a date.

Action Using My webmethods, update the extended criteria in the processing rule to supply a date value for attributes that have a DATETIME data type.

TNS.0001.4014E **{0} attribute value is a date but there is no transform.**

Explanation A TN document type indicates that a custom attribute with a DATETIME data type should be extracted from a document. However, the TN document type does not specify a date transformation for the custom attribute.

Action Using My webmethods, update the TN document type to specify an appropriate date transformation for the custom attribute.

TNS.0001.4015E **{0} attribute is configured for custom transformation, but no transformation service is specified.**

Explanation A TN document type indicates that a custom attribute should perform custom attribute transformation. However, the TN document type does not specify a transformation service.

Action Using My webMethods, update the TN document type to specify a transformation service.

TNS.0001.4016E **Error performing custom transformation on the {0} attribute.**

Explanation Encountered an exception while updating an attribute in the database.

Action See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.4017E	**Custom transformation {0} for the {1} attribute returned the wrong type. Should be {2}**
Explanation	Custom attribute transformation did not return the data type that matches the data type of the associated attribute.
Action	Modify the custom attribute transformation service to return the correct data type specified in the error message.

TNS.0001.4018E	**Custom transformation service {0} for the {1} attribute did not return "newValues" in the pipeline.**
Explanation	Custom attribute transformation service did not return the required output parameter 'newValues'.
Action	Modify the custom attribute transformation service to return the 'newValues' output parameter.

TNS.0001.4019E	**{0} attribute value is a date list but there is no transform.**
Explanation	The TN document type does not specify a transformation for a date list type attribute.
Action	Using My webMethods, update the TN document type to specify a transformation service.

TNS.0001.4020E	**Unable to parse the given value. Value {0} could not be converted to date format**
Explanation	Unable to convert the value extracted from the document to a date format.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.4021E	**Attribute transformation for {0} of doctype {1} generated an exception. The original exception message is: {2}.**
Explanation	Encountered an exception while updating an attribute in the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.4022E	**Attribute transformation function code {0} is invalid.**
Explanation	A TN document type indicates an invalid attribute transformation function.
Action	Using My webMethods, update the TN document type to specify a valid transformation function.

TNS.0001.5006E	**Converting the signed body of this document into a string failed. Verification cannot continue. The original signed body was {0}.**
Explanation	Conversion failed for a document.
Action	If the signed body of the document is invalid, notify the document sender.

TNS.0001.5008E	**This doctype ({0}) has no verification service defined. Verification cannot continue.**
Explanation	This TN document type (<doctypeName>) has no verification service defined.
Action	If you are using a built-in TN document type, contact Software AG Global Support. If you are using your own TN document type, specify a verification service for it.

TNS.0001.5009E	**No Verification Service**
Explanation	The TN document type has no verification service defined. Verification cannot continue.
Action	If you are using a built-in TN document type, contact Software AG Global Support. If you are using your own TN document type, specify a verification service for it.

TNS.0001.5011E	**The signature query for doctype {0} ({1}) generated an error. The error was {2}.**
Explanation	The signature query (<query>) for the TN document type (<doctypeName>) generated an error. The error was <exceptionMessage>.
Action	If the signed body of the document is invalid, notify the document sender.

TNS.0001.5015E	**Query Failed**
Explanation	A signature query was defined for the TN document type but it failed to produce a result for this document.
Action	Either adjust the signature query that is defined in the TN document type, or notify the document sender that the structure of the document is incorrect.

TNS.0001.5017E	**This document type ({0}) is missing one or both of its signature queries (Signature and SignedBody). Verification cannot proceed.**
Explanation	One or both of this document type signature queries (Signature and SignedBody) may be missing.
Action	Using My webMethods, update the TN document type to specify both, a signature query and a signed body query.

TNS.0001.5018E	**Missing Signature Query(s)**
Explanation	This TN document type is missing one or both of its signature queries (Signature and SignedBody). Trading Networks cannot proceed with the verification of the signature.
Action	Using My webMethods, update the TN document type to specify both, a signature query and a signed body query.

TNS.0001.5019E	**The signed body query for doctype {0} ({1}) generated an error. The error was {2}.**
Explanation	The signed body query (<query>) for the TN document type (<doctypeName>) generated an error. The error was <exceptionMessage>.
Action	Take appropriate action to resolve the problem described in the exception. If the structure of the document is incorrect, notify the document sender.

TNS.0001.5020E	**The signature of this document was invalid; no information was available about the party or parties that signed it.**
Explanation	The signature of this document might be invalid.
Action	Notify the document sender.

TNS.0001.5021E	**No Signer Info Available**
Explanation	The signature of this document was not valid. No information was available about the party or parties that signed it.
Action	Notify the document sender.

TNS.0001.5022E	**The PKCS verification service, pub.security.pkcs7:verify, produced an error trying to verify this document. The error was {0}.**
Explanation	Encountered an exception while verifying a document signature.
Action	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.

TNS.0001.5023E	**PKCS Service Error**
Explanation	The PKCS verification service pub.security.pkcs7:verify, produced an error while trying to verify this document.
Action	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.

TNS.0001.5024E	**The verification service for this document ({0}) generated an error. The original error was {1}.**
Explanation	An exception was thrown while verifying a document signature.
Action	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.

TNS.0001.5025E	**Verification Failed**
Explanation	An exception was thrown while verifying a document signature.
Action	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.

TNS.0001.5026E	**The signature query for doctype {0} ({1}) failed to produce a value. Without a signature, verification cannot proceed.**
Explanation	A signature query was defined for the TN document type but it failed to produce a result for this document.
Action	Either update the TN document type to adjust the signature query, or notify the document sender that the structure of the document is incorrect.

TNS.0001.5028E	**The signed body query for doctype {0} ({1}) failed to produce a value. Without a signed body, verification cannot proceed.**
Explanation	A signed body query was defined for the TN document type but it failed to produce a result for this document.
Action	Either update the TN document type to adjust the signed body query, or notify the document sender that the structure of the document is incorrect.

TNS.0001.5030E	**Base-64 decoding the signature for this document failed to produce a value. The signature (before decoding) was {0,number} bytes.**
Explanation	An error occurred while decoding the signature. The signature might be invalid.
Action	Notify the document sender.

TNS.0001.5031E	**Decoding Error**
Explanation	Trading Networks could not decode the signature. The signature might be invalid.
Action	Notify the document sender.

TNS.0001.5032E	**XML {0} failed: does not apply to non-XML documents**
Explanation	Trading Networks attempted to perform an operation on a non-XML document. However, the operation can be performed only on XML documents.
Action	Check whether the input document is a valid XML document.

TNS.0001.5033E	**XML {0} failed: no document content available**
Explanation	Trading Networks attempted to perform an operation that failed because the document has no content.
Action	Notify the document sender.

TNS.0001.5034E	**Bad XML content**
Explanation	An exception was thrown while retrieving the document.
Action	The document may not be a valid XML document.

TNS.0001.5035E	**An error prevented fetching the content of this XML document for {0}. The original error was {2}.**
Explanation	An exception was thrown while retrieving the document.
Action	Check the database and make sure that the data is not corrupted.

TNS.0001.5036E	**Signature Verification failed : The verification service, {0} aborted processing of this document. The message was {1}.**
Explanation	A RoutingAbortedException was thrown by the verification service that caused the document processing to abort.
Action	Take appropriate action to resolve the problem described in the exception. If the document is invalid, notify the sender.

TNS.0001.5037E	**The signing service, {0} aborted processing of this document. The message was {1}.**
Explanation	A RoutingAbortedException was thrown by the verification service, which caused the document processing to abort.
Action	Take appropriate action to resolve the problem described in the exception. If the document is invalid, notify the sender.

TNS.0001.6001E	**Attribute transform for {0} of doctype {1} failed to produce a value. The transform function was {3}, the first original value was {2}.**
Explanation	The data type of the attribute might not match the type of the data extracted from the document.
Action	Make sure that the data type of the attribute matches the type of the data extracted from the document. If this is an XML TN document type, make sure that the XQL query that extracts the attribute is correct.

TNS.0001.6002E	**Attribute query for {0} of doctype {1} failed to produce a result. The document may not be complete. The query was: {2}**
Explanation	The XQL query for the attribute did not return a value.
Action	Change the XQL query accordingly to return correct result.

TNS.0001.6003E	**Attribute query for {0} of doctype {1} generated an exception. The original exception message is: {2}.**
Explanation	There is either a problem with the document, or with the query.
Action	Examine the document to see if it is well-structured XML. Correct and resubmit if needed. Examine the query to ensure that it is valid. Change the query if needed.

TNS.0001.6004E	**Unable to get XML content for corrupted doc {0}. The original exception message is: {1}.**
Explanation	The document may be corrupted.
Action	Fix the document and submit it again.

TNS.0001.6005E	**Transform for {0} of doctype {1} generated an exception. The transform function was {2}. The original exception message is: {3}.**
Explanation	There is either a problem with the document, or with the query.
Action	Examine the document to ensure that it is well-structured XML. Correct and resubmit if needed. Examine the query to ensure that it is valid. Adjust the query if needed.

TNS.0001.6006E	**Transform for {0} of doctype {1} failed to produce a value. The transform function was {3}, the first original value was {2}.**
Explanation	Perhaps the data type of the attribute does not match the type of the data extracted from the document.
Action	Make sure that the data extracted from the document is the same type as the attribute. If this is an XML TN document type, make sure that the XQL query that extracts the attribute is correct.

TNS.0001.6007E	**Envelope query for {0} of doctype {1} failed to produce a result. The document may not be complete. The query was: {2}**
Explanation	The XQL query for the attribute did not return a value.
Action	Fix the XQL query, if needed.

TNS.0001.6008E	**Envelope query for {0} of doctype {1} generated an exception. The original exception message is: {2}.**
Explanation	The document may be corrupted.
Action	Correct the document and submit it again.

TNS.0001.6009E	**There was an error in trying to get XML header information (DOCTYPE and DTD). The document ({0}) is probably not valid XML.**
Explanation	Probably, the document is not a well-structured XML.
Action	Correct the document and submit it again.

TNS.0001.6010E	**There was an error in trying to get XML header information (DOCTYPE and DTD). The document ({0}) is probably not valid XML. The original exception message is: {1}**
Explanation	Probably, the document is not a well-structured XML.
Action	Correct the document and submit it again.

TNS.0001.6011E	**XQL query {1} failed recognizing document {0}. The document is probably not valid XML. The original exception message is: {2}.**
Explanation	Probably, the document is not a well-structured XML. See the exception message for details.
Action	Correct the document and submit it again.

TNS.0001.6013E	**No bizdoc supplied to lookup validation schema**
Explanation	The wm.tn.doc.xml:getRecordBlueprint service was invoked with no BizDocEnvelope in the pipeline.
Action	Supply a BizDocEnvelope when invoking the wm.tn.doc.xml:getRecordBlueprint service.

TNS.0001.6014E	**Non-XML bizdoc supplied to lookup validation schema**
Explanation	The BizDocEnvelope passed to the wm.tn.doc.xml:getRecordBlueprint service is not an XML document type.
Action	Supply a BizDocEnvelope that matches an XML TN document type when invoking the wm.tn.doc.xml:getRecordBlueprint service.

TNS.0001.6015E	**No bizdoc ID supplied for testing validation**
Explanation	The wm.tn.doc.xml:testValidate service was invoked with no internal document ID in the pipeline.
Action	Supply an internal document ID (docID) when invoking the wm.tn.doc.xml:testValidate service.

TNS.0001.6016E	**No such bizdoc: {0}**
Explanation	The wm.tn.doc.xml:testValidate service was invoked with an invalid internal document ID in the pipeline.
Action	Provide a valid internal document ID when invoking the wm.tn.doc.xml:testValidate service.

TNS.0001.6017E	**Required attribute is missing**
Explanation	An attribute is defined as required by the document type but the document that matched the document type did not contain this attribute.
Action	Either change the document type so that this attribute is no longer required, or instruct the document sender to supply a value for the attribute.

TNS.0001.6018E	**The {0} attribute is required by the {1} doctype. The query {2} did not return any results**
Explanation	An attribute is defined as required by the document type but the document that matched the document type did not contain this attribute.
Action	Either change the document type so that this attribute is no longer required, or instruct the document sender to supply a value for the attribute.

TNS.0001.6019E	**Attribute transformation for {0} of doctype {1} generated an exception. The query is {2}. The original exception message is: {3}.**
Explanation	Encountered an exception.
Action	If the document is corrupted, notify the document sender.

TNS.0001.7003	**Error while getting {0}. Find if the EDI package is enabled and running in Integration Server.**
Explanation	WmEDI Package may be disabled.
Action	Check if the WmEDI package is enabled and running in Integration Server.

TNS.0001.7004	**Error while getting EDI Standards. Input for standard field cannot be null, its is a mandatory field.**
Explanation	Input for standard field cannot be null, it is a mandatory field.
Action	Configure the standard field in the input and run the service.

TNS.0001.7005	**Error while getting EDI Transactions. Input for standard field cannot be null, its is a mandatory field.**
Explanation	Input for standard field cannot be null, it is a mandatory field.
Action	Configure the standard field and run the query again.

TNS.0001.7006	**Error while getting EDI Transactions. Input for version field cannot be null, its is a mandatory field.**
Explanation	Input for version field cannot be null, it is a mandatory field.
Action	Configure the version field and run the query again.

TNS.0001.7007	**Error while getting {0}. Input for {1} field cannot be null, its is a mandatory field.**
Explanation	Input field suggested in error message is a mandatory field.
Action	Configure the input field and run the query again.

TNS.0001.7008	**Error while querying for document attributes.**
Explanation	Encountered an exception while querying document attributes.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7009	**Error while getting the related doctypes for doctype attribute {0}.**
Explanation	An error occurred while getting related doctypes for the associated doctype attribute. The error may be because of an SQLException.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7010	**Error while changing the status of the doctype attributes.**
Explanation	An error occurred while changing the status of the doctype attributes.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7011	**Error while getting doctype attribute for doctype attribute ID {0}.**
Explanation	An error occurred while getting doctype attribute for the associated attribute ID. This may be because of an SQLException while querying the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7012	**Error while updating doctype attribute for doctype attribute ID {0}.**
Explanation	An error occurred while updating the doctype attribute. This may be because of an SQLException while updating the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7013	**Error while changing the status of the doctype attribute ID {0}.**
Explanation	An error occurred while updating the doctype attribute. This may be because of an SQLException while updating the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7014	**Error while viewing doctype attribute. Input for docAttrID field cannot be null, its is a mandatory field.**
Explanation	An error occurred while viewing the doctype attribute. This may be because of an SQLException while querying for the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7015	**Error while updating doctype attribute. Input for docAttrID field cannot be null, its is a mandatory field.**
Explanation	Input for docAttrID field cannot be null, it is a mandatory field.
Action	Configure the docAttrID field while updating the doctype attribute.

TNS.0001.7016	**Error while adding doctype attribute. Check whether all input variables have been passed properly.**
Explanation	Some mandatory fields may not have been passed before calling the service.
Action	Configure all input variables before calling the service.

TNS.0001.7017E	**Attribute name "{0}" already exists. Change the name and save again.**
Explanation	Attribute with the same name already exists.
Action	Change the attribute name and save.

TNS.0001.7018	**Error while updating doctype attribute. Attribute name with "{0}" already exists. Change the name and save again.**
Explanation	Attribute with same name already exists.
Action	Change the name and save.

TNS.0001.7019	**Error while querying for document attributes {0}.**
Explanation	An error occurred while querying doctype attributes. This may be because of an SQLException while querying the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0002.1001E	**"{0}" is empty. At least one {1} must be supplied. Please supply the required value.**
Explanation	You did not supply a value for the specified variable. At least one value is required.
Action	Supply at least one value for the specified field and try again.

TNS.0002.1002E	**"{0}" and "{1}" are required ({0}={2}, {1}={3}). Please supply the required values.**
Explanation	Both values are required.
Action	Supply both values.

TNS.0002.1009E	**The value originally supplied as sender ID for this document was not a valid partner ID. The value was {0}.**
Explanation	Partner ID supplied as sender ID is not being recognized as valid partner.
Action	Either create a partner profile for the document sender, add this ID to an existing partner's profile, or tell the document sender to resend the document using a different sender ID value.

TNS.0002.1010E	**Error formatting error message {0}: {1}**
Explanation	Unable to format the error message.
Action	Contact Software AG Global Support.

TNS.0002.1011E	**The value originally supplied as receiver ID for this document was not a valid partner ID. The value was {0}.**
Explanation	Partner ID supplied as receiver ID is not being recognized as valid partner.
Action	Either create a partner profile for the document receiver, add this ID to an existing partner's profile, or tell the document sender to resend the document using a different receiver ID value.

TNS.0002.1012E	**{0} is null.**
Explanation	An internal variable is unexpectedly null.
Action	Contact Software AG Global Support.

TNS.0002.1013E	**At least one of "{0}" and "{1}" is required.**
Explanation	At least one of the input fields is required, either its null or empty.
Action	Provide non-null value for at least one input parameter and try again.

TNS.0002.1016E	**"sourceVersion" is required. Please supply the required value.**
Explanation	A required value is missing.
Action	Supply the required value.

TNS.0002.1017E	**"feature" is required. Please supply the required value.**
Explanation	A required value is missing.
Action	Supply the required value.

TNS.0002.1018E	**At least one input is required.**
Explanation	All input fields are found to be null, at least one input should not be null.
Action	Provide at least one non-null value for input and try again.

TNS.0002.1019E	**Enumeration contains elements that are not Strings.**
Explanation	An unexpected value was passed to an internal method.
Action	Contact Software AG Global Support.

TNS.0002.1021E	**schema cannot be null.**
Explanation	Attempted to create a Trading Networks IData object with an empty set of name/value pairs.
Action	Contact Software AG Global Support.

TNS.0002.1022E	**schema rows must be 2 wide**
Explanation	Attempted to create a Trading Networks IData object without set of name/value pairs.
Action	Contact Software AG Global Support.

TNS.0002.1023E	**keys cannot be null**
Explanation	Attempted to create a Trading Networks IData object with keys as null. Keys cannot be null.
Action	Contact Software AG Global Support.

TNS.0002.1024E	**index out of bounds: {0}**
Explanation	Attempted to seek beyond the end of or before the start of a TNFixedData object.
Action	Supply a valid index to the seek method.

TNS.0002.1025E	**TNFixedData does not support setKey**
Explanation	Attempted to use an unsupported method.
Action	Do not call the setKey method.

TNS.0002.1027E	**TNFixedData does not support delete**
Explanation	Attempted to use an unsupported method.
Action	Do not call the delete method.

TNS.0002.1028E	**illegal null key**
Explanation	Supplied a null key to the keyMatch method on a TNFixedData object.
Action	Supply a valid key value.

TNS.0002.1031E	**Must supply props**
Explanation	A required value(props) is missing for wm.tn.admin:setProperties().
Action	Supply the required value for field(props) and try again.

TNS.0002.1032E	**Must shutdown before starting up again**
Explanation	Invoked the wm.tn.admin:startup service while the WmTN package is enabled and loaded.
Action	Use the Integration Server Administrator to stop and start the WmTN package. Do not invoke the wm.tn.admin:start service directly.

TNS.0002.1042E	**No such enum: {0}**
Explanation	A wm.tn.enumerate service was invoked with an invalid query enumeration identifier.
Action	Supply a valid enumeration identifier.

TNS.0002.1043E	**Either {0} or {1} must be supplied. Please supply one of these values.**
Explanation	A valid value for either of the required field was not supplied.
Action	Supply one of the valid values which are listed in the error message.

TNS.0002.1044E	**{0} is required whenever a value for {1} is supplied. Please supply a value for {0}.**
Explanation	A storageRef value was supplied, but no value was supplied for storageType.
Action	Supply a value for the storageType variable. Either supply value for both related fields or keep both fields null and try again.

TNS.0002.1047E	**The following TN properties can only take numeric values: {0}**
Explanation	Attempted to assign non-numeric values to numeric system properties.
Action	Supply numeric values for numeric system properties.

TNS.0002.1048E	**Error setting features on SAX parser. Exception message is: {0}**
Explanation	Threw a SAXException while initializing the SAX parser.
Action	Contact Software AG Global Support.

TNS.0002.1056E	**The {0} service is for Trading Networks internal use only.**
Explanation	The specified service was invoked, but not by Trading Networks. This service is for Trading Networks internal use only.
Action	Do not invoke this service.

TNS.0002.1057E	**Error encountered in invoking service wm.tn.samples.helpServices:installTNSamplesACLs**
Explanation	Internal error installing ACLs for Trading Networks Sample services.
Action	If you want to protect the WmTNSamples services, invoke the wm.tn.samples:installTNSamplesACLs service.

TNS.0002.1058E	**Error encountered in writing TN ACL information to disk**
Explanation	An exception was thrown saving the Trading Networks ACLs to the file system.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0002.1059E	**ThreadQueue: too many jobs waiting**
Explanation	Attempted to spawn more threads than the configured limit.
Action	Use the wm.tn.admin:setThreadQueueConfig service to increase the value of the tn.thread.maxWaiting system property.

TNS.0002.1061E	**{0} is not an Integer**
Explanation	Invalid data type supplied to a service, expected an Integer value
Action	Supply an Integer for the specified field.

TNS.0002.1065	**Error encountered while unregistering TN''s XML content handler. The exception message is: {0}**
Explanation	Error occurred while unregistering TN's content handler and activating default XML content handler.
Action	See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0002.1066	**When scheduleType is {0}, a value must be supplied for {1}. Please supply a value for {1}.**
Explanation	Attempted to create new queue with schedule values null for a selected scheduleType.
Action	Supply valid values corresponding to selected schedule type.

TNS.0002.1067E	**Unable to update password for {0} with handle {1}**
Explanation	An exception was thrown when Trading Networks attempted to update the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0002.1068E	**Unable to retrieve password for {0} with handle {1}**
Explanation	An exception was thrown when Trading Networks attempted to retrieve the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0002.1069E	**Unable to insert password for {0} with handle {1}**
Explanation	An exception was thrown when Trading Networks attempted to insert the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0002.1070E	**Unable to save password for {0} with handle {1}**
Explanation	An exception was thrown when Trading Networks attempted to save the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0002.1071E	**Unable to delete password for {0} with handle {1}**
Explanation	An exception was thrown when Trading Networks attempted to delete the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0002.1072E	**Either {0} or {1} must be supplied, but not both. Please supply a value for only one of these.**
Explanation	You supplied the specified two values; however, only one value can be specified.
Action	Supply value for either partByets or partStream and try again.

TNS.0002.1073	**Unable to import document type {0}. Attribute {1} is used in the document type but, it is not defined.**
Explanation	While importing a doctype, related attribute not found, so unable to import the doctype.
Action	Please either import the related attribute or define before importing the doctype.

TNS.0002.1075	**Unable to import processing rule {0}. Sender profile {1} is used in the processing rule but, it is not defined.**
Explanation	While importing a processing rule, related sender profile not found, so unable to import the processing rule.
Action	Either import the related sender profile or define it before importing the processing rule.

TNS.0002.1076	**Unable to import processing rule {0}. Receiver profile {1} is used in the processing rule but, it is not defined.**
Explanation	While importing a processing rule, related receiver profile not found, so unable to import the processing rule.
Action	Either import the related receiver profile or define it before importing the processing rule.

TNS.0002.1077	**Unable to import processing rule {0}. Document type {1} is used in the processing rule but, it is not defined.**
Explanation	While importing a processing rule, related Document Type not found, so unable to import the processing rule.
Action	Either import the related document type or define it before importing the processing rule.

TNS.0002.1081	**Error encountered while extracting doctype with doctypeID {0}. Please check whether it is a valid ID.**
Explanation	Could not retrieve Document Type from BizDocStore with provided docTypeID, would not be able to enable/update doc type for monitoring.
Action	Please check whether provided docTypeID is a valid ID, as system was not able to retrieve corresponding Document Type from store.

TNS.0002.1083	**Error encountered while setting TN BAM Monitoring status to {0}**
Explanation	Error encountered while enabling/disabling TN BAM monitoring. This happened while setting monitoring properties invoking service wm.tn.admin:setProperties().
Action	Please see the error log.

TNS.0002.2005S	**Error(s) encountered in WmTN initialization: {0}**
Explanation	Encountered an exception while Trading Networks was initializing.This happened during filling the cache of attribute, type, routing rule and profile.
Action	Take appropriate action to resolve the problem described in the exception and try to reload the package.

TNS.0002.2013S	**The wm.tn.access:getConsoleRestrictions service has been deleted, renamed or replaced. Aborting Trading Networks initialization.**
Explanation	Aborting Trading Networks initialization as the wm.tn.access:getConsoleRestrictions service has been tempered.
Action	Please contact your administrator to restore the original version of this service.

TNS.0002.2014E	**Error filling BizDocAttributeStore cache**
Explanation	Encountered an error while reading the document attributes from the database during startup.
Action	An exception was written to the server log. Take appropriate action to resolve the problem described in the exception.

TNS.0002.2018W	**Unable to register content types with the FlatFile Content Handler. The WmFlatFile package may be disabled. The WmFlatFile package must be enabled in order to use FlatFile capabilities in Trading Networks.**
Explanation	The WmFlatFile package is disabled. Unable to register content types with the FlatFile Content Handler.
Action	The WmFlatFile package may be disabled. The WmFlatFile package must be enabled in order to use FlatFile capabilities in Trading Networks.

TNS.0002.3007E	**wm.tn.admin:installACLs: Unable to find group, {0}**
Explanation	The specified group, <group>, has not been created.
Action	Run the wm.tn.admin:install service to create the Trading Networks user groups.

TNS.0002.3010S	**Can not create IS user group {0}**
Explanation	An exception was thrown while creating a user group during server startup.
Action	Contact Software AG Global Support.

TNS.0002.3011E	**Can not create IS user {0}**
Explanation	An exception was thrown while creating a user during server startup.
Action	Contact Software AG Global Support.

TNS.0002.4011E	**Error encountered during TN server starting: {0}**
Explanation	An exception was thrown while Trading Networks was starting.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0002.4012E	**Error encountered during TN server stopping: {0}**
Explanation	An exception was thrown while Trading Networks was stopping.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0002.4013E	**Error encountered during TN server restarting: {0}**
Explanation	An exception was thrown while Trading Networks was restarting.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0002.4019E	**TN database connection pool failed: error initializing Datastore**
Explanation	An exception was thrown while initializing the Trading Networks database connection pool.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception. Check TN DB configuration details.

TNS.0002.4020E	**TN Server failed starting up: error initializing database connection pool**
Explanation	An exception was thrown while initializing the Trading Networks database connection pool.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception. Check TN DB configuration details.

TNS.0002.4021E	**TN Server failed starting up: OEM restriction was hacked**
Explanation	A user or developer attempted to bypass the OEM restrictions. The server will not start.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0002.4024E	**TN task manager encountered error: {0}**
Explanation	An exception was thrown that has terminated execution of the task manager.
Action	Take appropriate action to resolve the problem described in the exception. You might need to contact Software AG Global Support.

TNS.0002.4025E	**TN temporary storage space initialization failed: {0}**
Explanation	An exception was thrown while preparing temporary disk space for large files.
Action	Take appropriate action to resolve the problem described in the exception. You might need to change the tn.tspace.location system property to a disk partition that has more free space.

TNS.0002.4028E	**Invalid notification type encountered in pkginit:sendNotif**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0002.4039E	**MBean cannot record statistics for document id {0}. Document does not exist.**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0002.4040E	**Exception thrown while saving document processing statistics.**
Explanation	Error encountered while saving document processing statistics to DB.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.1001E	**Invalid datatype. "cert" must be a byte[] or a X509Certificate.**
Explanation	You invoked a service and supplied a digital certificate value that is not a recognized data type.
Action	Supply either an X509Certificate or the bytes from an X509Certificate.

TNS.0003.1005E	**The user associated with this certificate ({0}) does not have a TN profile.**
Explanation	The supplied digital certificate is associated with an Integration Server user, but that user is not a Trading Networks partner.
Action	Either create a partner profile for the user, or supply a certificate that is associated with a Trading Networks partner.

TNS.0003.1007E	**An error occurred when the intended receiver tried to accept this document. The original error message was {0}.**
Explanation	An exception was thrown while accepting a polled document.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.1008E	**Unable to retrieve partner profile associated with supplied certificate.**
Explanation	An exception was thrown while retrieving the partner associated with a digital certificate.
Action	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.1010E	**Unable to save partner''s certificate.**
Explanation	An exception was thrown while saving a partner's certificate.
Action	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.1015E	**Unable to retrieve signing keys to be used for sending documents to specified partner.**
Explanation	The wm.tn.access:getSigningKeys service was unable to retrieve the security information needed to sign documents sent to a partner.
Action	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.1028E	**Invalid feature specified.**
Explanation	While checking whether a feature was enabled, Trading Networks discovered that an invalid feature was specified.
Action	Contact Software AG Global Support.

TNS.0003.1029E	**Error retrieving Console restrictions.**
Explanation	An exception was thrown while determining what features are available to My webMethods Server.
Action	Contact Software AG Global Support.

TNS.0003.1030E	**No session available**
Explanation	Attempted an action that requires an active session, but no active session was found.
Action	Contact Software AG Global Support.

TNS.0003.1031E	**No user available from session**
Explanation	Unable to determine the connected user as session doesn't have any user defined.
Action	Try defining users and retry or contact your administrator to check database and Integtation Server status.

TNS.0003.1032E	**Group TNPartners not defined**
Explanation	TNPartners Group was not found
Action	Run the wm.tn.admin:install service to create TNPartners and other required user groups.

TNS.0003.1033	**Empty or null username for partner {0}.Also,The username may not have whitespace.**
Explanation	Encountered validation error while creating partner account. Iinput field username can't be null and should not contain spaces.
Action	Provide a valid user name and try again.

TNS.0003.2002E	**An ID type named {0} already exists.**
Explanation	Trading Networks attempted to create an external ID type with the provided name, but an external ID type with that name already exists.
Action	Specify the name of an external ID type that does not already exist when creating an external ID type.

TNS.0003.2003E	**A contact type named {0} already exists.**
Explanation	Trading Networks attempted to create a contact type with the provided name, but a contact type with that name already exists.
Action	Specify the name of a contact type that does not already exist when creating a contact type.

TNS.0003.2004E	**A field group named {0} already exists.**
Explanation	Trading Networks attempted to create a field group with the provided name, but a field group with that name already exists.
Action	Specify the name of a field group that does not already exist when creating a field group.

TNS.0003.2005E	**Could not get profile dictionary**
Explanation	Trading Networks encountered an unexpected error during profile dictionary initialization.
Action	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.

TNS.0003.2006E	**Could not retrieve field definitions**
Explanation	An exception was thrown while retrieving profile field definitions.
Action	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.

TNS.0003.2007E	**Could not add field definition**
Explanation	An exception was thrown while saving a profile field definition.
Action	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.

TNS.0003.2008E	**Could not update field definition**
Explanation	An exception was thrown while updating a profile field definition.
Action	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.

TNS.0003.2009E	**"definition" is required.**
Explanation	A required field value was not supplied.
Action	Supply the required value.

TNS.0003.3010E	**Unable to map certificate to user for new partner {0}.**
Explanation	The wm.tn.security:setVerifyCertificateSet service was unable to save certificates for a new trading partner.
Action	Save the partner's profile with no certificates and then add the partner's certificates.

TNS.0003.3019E	**{0} could not retrieve the ProfileStore.**
Explanation	The Profile Store is inaccessible.
Action	Reload the WmTN package or restart the Integration Serve that hosts Trading Networks Server.

TNS.0003.3030E	**Unable to retrieve the {0} ID for partner {1}.**
Explanation	Could not convert the internal partner ID into an external ID.
Action	Make sure the partner has a value for this type of external ID.

TNS.0003.3034W	**An invalid or expired certificate was received from {0} and rejected.**
Explanation	An invalid or expired certificate was received and rejected from the Trading Partner specified in the message.
Action	Notify the Trading Partner specified in the message that their certificate is either invalid or expired.

TNS.0003.3037W	**Received a certificate issued by {0}, who is not on your list of trusted Certificate Authorities.**
Explanation	The Certificate Authority specified in the message is not on your list of trusted sources.
Action	You either can add this Certificate Authority to your list of trusted Certificate Authorities, or you can notify the trading partner that you do not trust their Certificate Authority.

TNS.0003.3038E	**Problem creating B2B account for partner (username={0}).**
Explanation	An account could not be created on the Integration Server for the partner.
Action	Create the account manually for the partner. The user name must match the partner's required external ID.

TNS.0003.3050E	**If {0} is supplied, {1} must also be supplied.**
Explanation	You must supply either both values or neither value.
Action	Supply both values or neither value.

TNS.0003.3085W	**The Trading Networks user does not have permission to change System properties. The certificate chain verifier is not correctly initialized. All incoming certificate chains will be trusted.**
Explanation	The watt.security.cert.wmChainVerifier.trustByDefault property might not be set correctly.
Action	Ask the Administrator to set the watt.security.cert.wmChainVerifier.trustByDefault property appropriately.

TNS.0003.3102E	**Either {0} or {1} must be supplied.**
Explanation	A value must be supplied for one of the two variables, but no value was supplied for either variable.
Action	Supply a value for one of the variables.

TNS.0003.4001E	**Could not delete field group.**
Explanation	An exception was thrown while deleting a profile field group.
Action	The exception was written to the error log. See the log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4003E	**Could not add partner profile for {0}.**
Explanation	An exception was thrown while saving a partner profile.
Action	The exception was written to the error log. See the log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4005E	**The partner specified (id={0}) has a {1} ID of {2}, but there is no matching IS user account.**
Explanation	Trading Networks could not find an Integration Server user account for this partner.
Action	Verify that the partner has a user account on the Integration Server and that the account name matches the partner's required external ID value.

TNS.0003.4006E	**Attempted to save an extended field value with an unknown field ID (id={0}).**
Explanation	Field with this ID doesn't exist. Trading Networks could not save the extended field for this ID.
Action	Specify a valid field ID.

TNS.0003.4008E	**Got null or empty extended profile fields**
Explanation	The "fields" input variable is required.
Action	Pass the extended fields you want to save in the "fields" variable.

TNS.0003.4009E	**Attempted to save an external ID that has an unknown type (type code={0}).**
Explanation	Trading Networks attempted to save an external ID for a partner, but the external ID is associated with an external ID type that has not been defined.
Action	To save a new type of external ID for a partner, you must first define the external ID type. To do so, use the wm.tn.dictionary:addIDType service.

TNS.0003.4010E	**ID Type {0} is not valid. Not found in the Trading Networks database.**
Explanation	ID Type provided is not recognized by Trading Networks.
Action	Supply a valid external ID type. Use the wm.tn.dictionary:addIDType service to define a new external ID type.

TNS.0003.4011E	**Attempted to save a contact that has an unknown type (type code={0}).**
Explanation	Trading Networks attempted to save a contact for a partner, but the contact is associated with a contact type that has not been defined.
Action	To save a new type of contact for a partner, you must first define the contact type. To do so, use the wm.tn.dictionary:addContactType service.

TNS.0003.4012E	**Cannot delete a standard field**
Explanation	Attempted to delete a standard profile field. You can only delete extended profile fields.
Action	No action required.

TNS.0003.4014E	**{0} not a valid Group ID. Must be greater than {1}.**
Explanation	Group ID provided is not a positive integer.
Action	Supply a valid group ID value. It should be positive integer.

TNS.0003.4015E	**Port must be a positive integer**
Explanation	When specifying a partner's host and port, the port value must be greater than zero.
Action	Supply a valid value that is greater than zero for the port number.

TNS.0003.4016E	**Could not decode bizdoc**
Explanation	Trading Networks created an internal BizDocEnvelope to validate the profile data, but could not decode the BizDocEnvelope.
Action	Contact Software AG Global Support.

TNS.0003.4017E	**Could not add {0}. A {0} with an ID of {1} already exists.**
Explanation	While adding lookup type (Contact Type/ ID Type/ Binary Type), Trading Networks found that a similar lookup type with same ID already exists. Trading Networks did not add the lookup type.
Action	Save this type with a different ID.

TNS.0003.4018E	**A profile already exists for the host of this Trading Network. Turn off the SELF setting on the corporate component of the profile and save it again.**
Explanation	The Enterprise profile already exists.
Action	If you are programmatically saving profiles, set the Self? variable to false before attempting to save the profile. If you are using My webMethods to save profiles, contact Software AG Global Support.

TNS.0003.4019E	**Could not validate profile: received null bizdoc**
Explanation	Trading Networks should have created an internal BizDocEnvelope to validate profile data, but the BizDocEnvelope is null.
Action	Contact Software AG Global Support. Please have the server and error logs and the WmTN/config/properties.cnf file available.

TNS.0003.4020E	**No ''{0}'' element found in bizdoc**
Explanation	Trading Networks created an internal BizDocEnvelope to validate profile data, but the BizDocEnvelope did not contain the "errors" element.
Action	Contact Software AG Global Support. Please have the server and error logs and the WmTN/config/properties.cnf file available.

TNS.0003.4021E	**Cannot set extended fields.**
Explanation	An exception was thrown while saving extended fields to the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4024E	**Cannot access profile store.**
Explanation	An exception was thrown while accessing the Profile store.
Action	Contact Software AG Global Support.

TNS.0003.4026E	**You are using webMethods Trading Partners. To be able to add more partner profiles, please upgrade to webMethods Trading Networks.**
Explanation	When using webMethods Trading Partners, you are allowed to create only one profile other than your own.
Action	If you need to create additional partner profiles, upgrade to webMethods Trading Networks.

TNS.0003.4027E	**Could not retrieve {0} using {1}**
Explanation	Invalid id is provided. Trading Networks could not retrieve partner details using this ID.
Action	Supply a valid value.

TNS.0003.4028E	**An error occurred while retrieving company logos.**
Explanation	An exception was thrown while retrieving company logos.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4029E	**Importing a profile for {0} (id={1}), which is marked as "My Enterprise", but it has different ID than the existing My Enterprise profile for this Trading Network. Cannot change the identity of the My Enterprise profile. Process terminated.**
Explanation	You attempted to import the Enterprise. However, the target Trading Networks system already has an Enterprise profile, which has a different ID than the one you are attempting to import. Trading Networks cannot import the Enterprise profile.
Action	Import Enterprise profile carefully only to those Trading Networks Servers where it's not already defined.

TNS.0003.4030E	**Could not get profile for user (username={0}).**
Explanation	An exception was thrown while retrieving a partner profile for a user.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4032E	**Extended fields cannot have a column name.**
Explanation	Validation of profile fields failed.The column name on an extended profile field should be null.
Action	If you are programmatically creating extended fields, do not set the Column Name.

TNS.0003.4033E	**Extended fields cannot have a table name.**
Explanation	Validation of profile fields failed. The table name on an extended profile field should be null.
Action	If you are programmatically creating extended fields, do not set the Table Name.

TNS.0003.4034E	**Partner status can only be "Active" or "Inactive" when adding a new profile.**
Explanation	Invalid status provided for profile to be added.
Action	Supply a valid value for the Partner Status field.

TNS.0003.4035E	**Corporation is invalid: no partnerID.**
Explanation	Trading Networks attempted to update a partner profile, but the corporation component has no partner ID.
Action	Set the partnerID field to a valid value.

TNS.0003.4036E	**Attempted to save a binary object that has an unknown type (type code={0}).**
Explanation	The database does not have binary types defined.
Action	Populate your database with initial values by importing the file <IntegrationServer>/packages/WmTN/bin/init.xml, where <IntegrationServer> is the location where your server is installed.

TNS.0003.4037E	**Could not add Field Group {0}.**
Explanation	An exception was thrown while adding a profile field group.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4039E	**Could not get {0} for partner (partnerID={1}).**
Explanation	An exception was thrown while retrieving protocol information for a partner.
Action	Verify whether the database connection is available.Take appropriate action to resolve the problem described in the exception.

TNS.0003.4041E	**Cannot delete the External ID,there has to be at least one external ID**
Explanation	Each partner must have a value for the required external ID type. The required external ID value is used for the user name of the partner's Integration Server user account.
Action	Do not attempt to delete the required external ID from a partner's profile.

TNS.0003.4042E	**The value for profile field {0} is not one of the valid values.**
Explanation	Invalid value provided for profile field.
Action	Supply a valid value.

TNS.0003.4044E	**Standard fields must have a column name.**
Explanation	Profile field Validation failed. The column name on a standard profile field is null.
Action	Contact Software AG Global Support.

TNS.0003.4045E	**Could not update {0}.**
Explanation	An exception was thrown while updating a profile component.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4046E	**A profile already exists in the database with the supplied PartnerID ({0}).**
Explanation	Trading Networks attempted to save a new profile with the same partnerID as an existing profile.
Action	Do not specify a value for the partnerID when creating a new profile. Trading Networks will generate a unique ID for you.

TNS.0003.4047	**{0} cannot be null.**
Explanation	Partner ID is required field while fetching the Profile and it should not be null.
Action	Supply Partner ID to fetch profile.

TNS.0003.4048E	**Could not get profile for partner (id={0})**
Explanation	An exception was thrown while retrieving a partner profile.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4049E	**webMethods Trading Partners is restricted to the creation of one profile in addition to your own.**
Explanation	When using webMethods Trading Partners, you can create only one profile other than your own.
Action	If you need to create additional partner profiles, upgrade to webMethods Trading Networks.

TNS.0003.4050E	**Could not upgrade your profile. Please contact webMethods Customer Service.**
Explanation	An exception was thrown while upgrading your profile from webMethods for Partners to webMethods Trading Networks.
Action	Take appropriate action to resolve the problem described in the exception. If necessary, contact Software AG Global Support.

TNS.0003.4051E	**At least 1 field has been defined for this group. Cannot delete.**
Explanation	Found at least one field still associated to group. Unable to delete this group.
Action	To delete this field group, you must first delete all extended profile fields in the group, or assign them to other groups.

TNS.0003.4053E	**Could not delete {0} ({1}={2}).**
Explanation	An exception was thrown while deleting a profile component.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4054E	**Cannot set valid values for a standard field**
Explanation	You cannot define a list of valid values for standard fields.
Action	Do not attempt to define a list of valid values for a standard field. Valid values are applicable for extended fields.

TNS.0003.4056E	**Errors encountered validating profile/profile fields**
Explanation	A list of one or more validation errors follows this message after invoking wm.tn:submit.
Action	Take appropriate action to resolve the errors.

TNS.0003.4058E	**Another partner profile with the name "{0}" already exists. Cannot have duplicate partner names. Please enter a different name.**
Explanation	You are attempting to create a profile; howeve , a profile with the Corporation Name and User Name that you specified already exists in Trading Networks.
Action	Supply a different Corporation Name and/or Unit Name.

TNS.0003.4060E	**You must add a profile for your enterprise before you can upgrade to webMethods Trading Networks. Please create a profile for your enterprise.**
Explanation	You have not defined the Enterprise profile. The Enterprise profile must exist before you can upgrade Trading Networks.
Action	Create the Enterprise profile.

TNS.0003.4062E	**Cannot undelete a standard field**
Explanation	Standard fields cannot be deleted or undeleted.
Action	Do not attempt to delete or undelete a standard field.

TNS.0003.4064E	**{0}, no change made on server**
Explanation	Trading Networks encountered an error while saving partner profile information. See the error message for details.
Action	Take appropriate action to resolve the problem described in the error message.

TNS.0003.4065E	**An error was encountered deleting a partner''s profile (partnerID={0}).**
Explanation	An exception was thrown while deleting a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4066E	**Could not get host profile.**
Explanation	An exception was thrown while retrieving the Enterprise profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4068E	**{0} is required.**
Explanation	No value was supplied for a required input variable.
Action	Supply the required value.

TNS.0003.4069E	**Standard fields must have a table name.**
Explanation	Trading Networks encountered an invalid field definition in the Trading Networks database.
Action	Contact Software AG Global Support.

TNS.0003.4072E	**Error initializing ProfileStore**
Explanation	Encountered error while initializing Profile Store.
Action	Contact Software AG Global Support.

TNS.0003.4073E	**Could not set binary object for partner (id={0}).**
Explanation	An exception was thrown while saving binary data to the Trading Networks database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4075E	**Could not get Extended Field template (group={0}).**
Explanation	An exception was thrown while creating a new extended field.
Action	Contact Software AG Global Support.

TNS.0003.4076E	**Invalid group specified.**
Explanation	The group that was specified is not a valid group.
Action	Use the wm.tn.dictionary:getFieldGroups service to retrieve a list of valid groups.

TNS.0003.4077E	**{0} must be specified for partner {1}**
Explanation	Profile validation failed! Required data is missing from a partner profile.
Action	Supply a value for the required fields.

TNS.0003.4078E	**Datatype cannot be null.**
Explanation	Found Datatype parameter null while setting it to profile.
Action	Supply a valid data type.

TNS.0003.4079E	**Your webmethods Trading Networks server is restricted to the creation of {0} profiles in addition to your own.**
Explanation	Your Trading Networks Server is restricted to the creation of the number of profiles specified in the message.
Action	If you need to add more profiles, contact Software AG Global Support to upgrade your server.

TNS.0003.4080E	**Attempted to set the datatype of a field to an unrecognized value: {0}.**
Explanation	Provided datatype is not recognized by Trading Networks.
Action	Supply a valid data type.

TNS.0003.4082E	**Binary type not found in the Trading Networks database: {0}.**
Explanation	Trading Networks attempted to set the value of a binary object, but the type does not exist in the database.
Action	Supply a valid binaryTypeDescription or binaryTypeCode. If you have specified a valid binary type and the problem persists, import the init.xml file from the <IntegrationServer>packages/WmTN/bin directory, where <IntegrationServer> is the location where you installed your server.

TNS.0003.4083E	**Could not change {0} Type {1}.**
Explanation	An exception was thrown while attempting to update an external ID type or contact type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4084E	**Standard fields cannot have a set of extended valid values**
Explanation	Trading Networks encountered an invalid field definition in the Trading Networks database.
Action	Contact Software AG Global Support.

TNS.0003.4085E	**The specified delivery data (id={0}) does not exist in the database. Cannot delete.**
Explanation	Trading Networks was unable to perform the specified database action because the Destination data does not exist.
Action	Contact Software AG Global Support. Have the server and error logs and the WmTN/config/properties.cnf file available.

TNS.0003.4086E	**Standard fields cannot have an extended default value**
Explanation	Trading Networks encountered an invalid field definition in the Trading Networks database.
Action	Contact Software AG Global Support.

TNS.0003.4087E	**The value for {0} must be a String.**
Explanation	Found unexpected non-String value when datatype is String, validation failed.
Action	Supply a String value for the field.

TNS.0003.4088E	**A {0} ID of {1} already exists in the database. External IDs must be unique.**
Explanation	Cannot have two external IDs of the same external ID type that have the same value.
Action	Supply another value for this external ID.

TNS.0003.4089E	**Could not get internal ID for partner (id={0}, typeCode={1}, typeDesc={2}).**
Explanation	An exception was thrown while retrieving the internal partnerID.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4090E	**Fields must have a datatype**
Explanation	Trading Networks encountered an invalid field definition in the Trading Networks database.
Action	Contact Software AG Global Support.

TNS.0003.4091E	**Could not get profile summaries.**
Explanation	An exception was thrown while retrieving profile summaries.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4092E	**{0} cannot be null. {1} not {2}.**
Explanation	Trading Networks did not add or update the changes because a required value is missing.
Action	Supply the required value.

TNS.0003.4093E	**{0} must be equal or greater than {1}**
Explanation	Numeric field validation failed as supplied value found lesser than limit value, should be greater or equal to limit value.
Action	Supply a valid value.

TNS.0003.4094E	**You are already using webMethods Trading Networks. No upgrade is necessary.**
Explanation	Attempted to upgrade from webMethods for Partners to webMethods Trading Networks, but you are already using webMethods Trading Networks.
Action	No action required.

TNS.0003.4096E	**Could not get {0}.**
Explanation	An exception was thrown while retrieving a profile component.
Action	An exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4099E	**Status was not changed to {0} because the profile has the following errors {1}**
Explanation	The profile has issues that must be resolved before the status can be changed.
Action	Take appropriate action to resolve the problem described in the errors.

TNS.0003.4100E	**Cannot set Column Name for an extended field**
Explanation	It is not valid for an extended profile field to have a value for Column Name.
Action	Do not attempt to set a value for Column Name for an extended profile field.

TNS.0003.4102E	**Cannot set Table Name for an extended field**
Explanation	It is not valid for an extended profile field to have a value for Table Name.
Action	Do not attempt to set a value for Table Name for an extended profile field.

TNS.0003.4105E	**Could not add {0} Type {1}.**
Explanation	An exception was thrown while attempting to create an IDType or ContactType.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4106E	**Could not get profile summary (partnerID={0}).**
Explanation	An exception was thrown while attempting to retrieve a profile summary.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4107E	**An error occurred while retrieving polling frequencies.**
Explanation	An exception was thrown while retrieving a partner's polling frequency.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4108E	**Could not delete External Partner ID (internal PartnerID={0}).**
Explanation	An exception was thrown while deleting a partner's external ID.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4109E	**Got null profile field metadata for extended field at index {0}**
Explanation	Required internal data is missing.
Action	Contact Software AG Global Support.

TNS.0003.4110E	**Could not undelete profile for partner (id={0}).**
Explanation	An exception was thrown while undeleting a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4113E	**Attempted to save a field definition for an unknown group (group id={0}).**
Explanation	The specified field group does not exist and is not valid.
Action	Supply a valid field group. If you are using the Trading Networks Console to create an extended field, contact Software AG Global Support.

TNS.0003.4114E	**Could not get profile summary (username={0}).**
Explanation	An exception was thrown while retrieving a profile summary.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4115E	**Profile has errors. Saved with a status of {0}.**
Explanation	Validation error found for the provided profile, saving with status as inactive.
Action	Take appropriate action to resolve the errors listed below this message.

TNS.0003.4116E	**Could not add external ID data for partner (id={1}).**
Explanation	Encountered an Exception while saving a profile component.
Action	See the Exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4117E	**webMethods Trading Networks requires a special license key. Please contact webMethods to get a Trading Networks key. Until you do so, you will be limited to the creation of one profile in addition to your own.**
Explanation	You currently have a webMethods for Partners license key, which allows you to create only a single partner profile.
Action	If you need to create additional partner profiles, upgrade to webMethods Trading Networks.

TNS.0003.4118E **Profile status may only be changed to {0} or {1}.**

Explanation Attempted to change the profile status to an invalid status.

Action Supply a valid value.

TNS.0003.4120E **Could not change partner''s status.**

Explanation An exception was thrown while updating the status of a partner profile.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4121E **{0} {1} delivery data already exists in the database for this partner.**

Explanation You attempted to add a delivery method for a partner that is already defined for the partner. You cannot have two instances of the same delivery method for a partner.

Action If the existing delivery method contains the information you want, no action is required. Otherwise, you can update the information for the existing delivery method.

TNS.0003.4122E **Extended fields must have a name.**

Explanation You did not specify a name for the extended profile field.

Action Supply the required value.

TNS.0003.4123E **Problem initializing Profile services.**

Explanation An exception was thrown during initialization.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4124E **Cannot set default value for a standard field.**

Explanation You cannot define a default value for a standard profile field.

Action Do not attempt to define a default value for a standard profile field.

TNS.0003.4125E **Could not retrieve extended fields.**

Explanation An exception was thrown while retrieving extended fields for a partner.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4126E	**Standard fields cannot be marked as deleted**
Explanation	You cannot delete a standard profile field.
Action	Do not attempt to delete a standard profile field.

TNS.0003.4129E	**Following errors occurred during updating profile**
Explanation	A list of one or more errors follows this message.
Action	Take appropriate action to resolve the problems described in the errors.

TNS.0003.4130E	**Cannot delete preferred delivery method**
Explanation	The delivery method you tried to delete is the preferred delivery method for the partner.
Action	Before you can delete this delivery method, choose another delivery method to be "preferred."

TNS.0003.4131E	**Could not delete {0} Type {1}.**
Explanation	An exception was thrown while deleting profile data.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4132E	**Could not update corporation.**
Explanation	An exception was thrown while updating the Corporate component of a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4133E	**Could not update addresses.**
Explanation	An exception was thrown while updating one or more addresses on a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4136E	**Could not delete connection ({1}={2}).**
Explanation	An exception was thrown while deleting a delivery method from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4138E	**Could not update external IDs.**
Explanation	An exception was thrown while updating one or more external IDs in a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4141E	**Could not get binary object for partner (partnerID={1}).**
Explanation	An exception was thrown while retrieving a binary object for a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4142E	**"extID" is required.**
Explanation	You attempted to invoke a service that requires a value for the extID input variable, but no value was supplied.
Action	Supply the required value.

TNS.0003.4143E	**Either idTypeCode or idTypeDesc must be supplied (idTypeCode={0}, idTypeDesc={1}).**
Explanation	You invoked a service without providing a required input variable to identify the external ID type.
Action	Supply one of the required values.

TNS.0003.4144E	**partnerID is required.**
Explanation	You invoked a service without providing a required input variable to identify the partner.
Action	Supply the required value.

TNS.0003.4145E	**Could not get external ID for partner (partnerID={0}).**
Explanation	An exception was thrown while retrieving an external ID for a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4146E	**Error encountered updating binary object in the database (partnerID={0}).**
Explanation	An exception was thrown while updating a binary object for a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4147E	**{0} must be supplied.**
Explanation	You called a Java method without supplying a value for a required field (<fieldName>).
Action	Supply the required value.

TNS.0003.4148E	**A status of {0} is not one of the permitted values.**
Explanation	Attempted to set the status to an invalid value.
Action	Supply a valid value.

TNS.0003.4149E	**Error encountered changing partner status.**
Explanation	An exception was thrown while updating the status of a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4151E	**A profile is required.**
Explanation	While adding profile to the Data store, profile found to be null.
Action	Supply the valid profile data.

TNS.0003.4152E	**Error encountered adding profile to the database.**
Explanation	An exception was thrown while adding a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4153E	**Error encountered adding contacts to the database.**
Explanation	An exception was thrown while adding one or more contacts to a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4155E	**Error encountered adding destinations to the database.**
Explanation	An exception was thrown while adding one or more delivery methods (destinations) to a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4156E **Error encountered adding IDs to the database.**

Explanation An exception was thrown while adding one or more external IDs to a partner profile.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4157E **Error encountered adding addresses to the database.**

Explanation An exception was thrown while adding one or more addresses to a partner profile.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4158E **Error encountered adding binary objects to the database.**

Explanation An exception was thrown while adding one or more binary objects to a partner profile.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4160E **{0} cannot be null.**

Explanation When attempting to delete a profile-related asset from the Profile store, required asset ID was not provided.

Action Supply the required asset ID.

TNS.0003.4161E **Error encountered deleting profile from the database.**

Explanation An exception was thrown while deleting a partner profile.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4162E **Error encountered undeleting profile from the database.**

Explanation An exception was thrown while undeleting a partner profile.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4163E **Error encountered deleting contact (contactID={0}, partnerID={1}).**

Explanation An exception was thrown while deleting a contact from a partner profile.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4164E	**Error encountered deleting address (addressID={0}, partnerID={1}).**
Explanation	An exception was thrown while deleting an address from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4165E	**Error encountered deleting destination (destID={0}).**
Explanation	An exception was thrown while deleting a delivery method (destination) from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4166E	**Error encountered deleting external id (id={0}).**
Explanation	An exception was thrown while deleting an external ID from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4167E	**Error encountered retrieving extended fields.**
Explanation	An exception was thrown while retrieving extended fields for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4168E	**Error encountered adding extended field {0} to the database (partnerID={1}).**
Explanation	An exception was thrown while adding an extended profile field for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4170E	**Error encountered retrieving contact {0} (partnerID={1}).**
Explanation	Encountered an exception while retrieving a contact for a partner.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4171E	**Error encountered retrieving binary type {0} (partnerID={1}).**
Explanation	An exception was thrown while retrieving a binary object for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4172E	**Invalid binary type: {0}.**
Explanation	The supplied binary type is not recognized as a valid binary type. It does not match any existing binary type.
Action	Supply a valid binary type value.

TNS.0003.4173E	**A connection was requested for an unknown partner (partnerID={0}).**
Explanation	Attempted to establish a connection to a partner's server, but the supplied partnerID was invalid.
Action	Supply a valid partner ID.

TNS.0003.4174E	**Delivery method is {0}. Can only create contexts for HTTP or HTTPS destinations.**
Explanation	A webMethods context can only be established when using HTTP or HTTPS.
Action	If you want to connect to a partner's server with a different protocol (e.g., FTP or SMTP) use the appropriate service in the WmPublic package or one of the delivery services in the wm.tn.transport folder.

TNS.0003.4175E	**Error encountered connecting to partner''s server.**
Explanation	An exception was thrown while connecting to a partner's server.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4181E	**constant must start with FLD_[TBL]_**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0003.4182E	**bad constant results in non or multiple fields**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0003.4184E	**RetryFactor cannot be zero**
Explanation	Supplied RetryFactor is unexpectedly lower than 1, RetryFactor should be greater than or equal to 1.
Action	Supply a valid value for RetryFatctor. It should be greater than or equal to 1.

TNS.0003.4187E	**External Field: {0} has errors. Error = {1}**
Explanation	See the errors listed in the message.
Action	Take appropriate action to resolve the problems described in the errors.

TNS.0003.4188E	**Is a required External Field**
Explanation	No data was supplied for a required extended profile field.
Action	Supply a value for this field.

TNS.0003.4189E	**Field value must be of data type java.lang.String**
Explanation	Data type for the extended profile field is String, value must be a String.
Action	Supply a String value.

TNS.0003.4190E	**Invalid value selected**
Explanation	Supplied value for extended profile field found to be invalid.
Action	Supply a valid value.

TNS.0003.4192E	**Could not retrieve ID Types from database**
Explanation	An exception was thrown while retrieving external ID types.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4193E	**Could not retrieve IDType Descriptions from database**
Explanation	An exception was thrown while retrieving external ID type descriptions.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4194E	**A database error occurred while adding an ID Type.**
Explanation	An exception was thrown while adding an external ID type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4195E **A database error occurred while changing an ID Type.**

Explanation An exception was thrown while updating an external ID type.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4196E **A database error occurred while deleting an External ID Type.**

Explanation An exception was thrown while deleting an external ID type.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4197E **Could not retrieve Contact Types from database**

Explanation An exception was thrown while retrieving contact types.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4198E **A database error occurred while adding a Contact Type.**

Explanation An exception was thrown while adding a contact type.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4199E **A database error occurred while changing a Contact Type.**

Explanation An exception was thrown while updating a contact type.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4200E **A database error occurred while deleting a Contact Type.**

Explanation An exception was thrown while deleting a contact type.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4201E **Could not retrieve Binary Types from database**

Explanation An exception was thrown while retrieving binary types.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4202E	**Could not retrieve Field Groups from database**
Explanation	An exception was thrown while retrieving field groups.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4203E	**A database error occurred while adding a Field Group.**
Explanation	An exception was thrown while adding a field group.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4204E	**A database error occurred while changing a Field Group.**
Explanation	An exception was thrown while updating a field group.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4205E	**A database error occurred while deleting a Field Group.**
Explanation	An exception was thrown while deleting a field group.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4206E	**Error initializing Profile Dictionary.**
Explanation	An exception was thrown during initialization.
Action	Contact Software AG Global Support.

TNS.0003.4207E	**pfmd cannot be null.**
Explanation	You did not supply a required value.
Action	Supply the required data.

TNS.0003.4208E	**A problem was encountered updating the field defintion.**
Explanation	An exception was thrown while updating a field definition.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4209E **Cannot add a standard field definition. Set Extended to true before saving this definition.**

Explanation Attempted to add a standard profile field. You cannot add standard profile fields.

Action Add the profile field as an extended profile field.

TNS.0003.4210E **A problem was encountered adding the field defintion.**

Explanation An exception was thrown while adding a field definition.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4211E **Error retrieving profile**

Explanation Encountered an exception while retrieving a partner profile.

Action See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4212E **Could not retrieve profile from database using external ID**

Explanation An exception was thrown while retrieving a partner profile.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4213E **Could not retrieve Profile Summaries from database**

Explanation An exception was thrown while retrieving a profile summary.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4216E **Could not retrieve Custom Fields from database**

Explanation An exception was thrown while retrieving extended profile fields.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4218E **Could not retrieve internal ID from database using PartnerIDID ({0}).**

Explanation An exception was thrown while retrieving a partner profile ID.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4219E	**Could not retrieve internal ID from database using DestinationID ({0}).**
Explanation	An exception was thrown while retrieving a partner profile ID.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4220E	**Error retrieving {0} external ID for {1}.**
Explanation	An exception was thrown while retrieving the external ID for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4221E	**Could not retrieve IDType from database using PartnerIDID ({0}).**
Explanation	An exception was thrown while retrieving an external ID type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4222E	**Could not update profile.**
Explanation	An exception was thrown while updating a profile that has been marked deleted.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4223E	**Corporation can not be null.**
Explanation	Required Corporate information was not supplied.
Action	Supply the required Corporate information.

TNS.0003.4224E	**Could not update Corporation.**
Explanation	An exception was thrown while updating a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4225E	**Contacts can not be null.**
Explanation	Required Contact information was not supplied.
Action	Supply the required data.

TNS.0003.4226E **At least one Contact is required.**

Explanation The supplied Vector must contain at least one contact.

Action Supply the required data.

TNS.0003.4227E **Could not update Contacts.**

Explanation An exception was thrown while updating a partner's contact information.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4228E **Address can not be null.**

Explanation Required address information was not supplied.

Action Supply the required data.

TNS.0003.4229E **At least one Address is required.**

Explanation The supplied vector must contain at least one address.

Action Supply the required data.

TNS.0003.4230E **Could not update Addresses.**

Explanation An exception was thrown while updating a partner's address information.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4231E **Destinations can not be null.**

Explanation Required delivery method (destination) information was not supplied.

Action Supply the required data.

TNS.0003.4232E **At least one Destination is required.**

Explanation The supplied vector must contain at least one delivery method (destination).

Action Supply the required data.

TNS.0003.4233E **Could not update Destinations.**

Explanation An exception was thrown while updating a partner's delivery method (destination) information.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4235E	**At least one ID is required.**
Explanation	The supplied vector must contain at least one external ID.
Action	Supply the required data.

TNS.0003.4236E	**Could not update IDs.**
Explanation	An exception was thrown while updating a partner's external ID information.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4237E	**A vector of Contacts is required**
Explanation	The first argument to ProfileStore.addContacts is null.
Action	Supply the required data.

TNS.0003.4238E	**A vector of Destinations is required**
Explanation	The first argument to ProfileStore.addDestinations is null.
Action	Supply the required data.

TNS.0003.4239E	**A vector of IDs is required**
Explanation	The first argument to ProfileStore.addIDs is null.
Action	Supply the required data.

TNS.0003.4240E	**A vector of Addresses is required**
Explanation	The first argument to ProfileStore.addAddresses is null.
Action	Supply the required data.

TNS.0003.4242E	**"addresses" is empty. At least one Address must be supplied.**
Explanation	No address was supplied.
Action	Supply the required value.

TNS.0003.4243E	**"connections" is empty. At least one Destination must be supplied.**
Explanation	No delivery method (destination) was supplied.
Action	Supply the required value.

TNS.0003.4244E	**Could not validate profile extended fields: received null bizdoc**
Explanation	Internal error occurred during profile validation.
Action	Contact Software AG Global Support.

TNS.0003.4245E	**No extended fields found in bizdoc**
Explanation	Internal error occurred during profile validation.
Action	This error can be safely ignored. If it persists, contact Software AG Global Support.

TNS.0003.4246E	**Could not validate profile standard fields: received null bizdoc**
Explanation	Internal error occurred during profile validation.
Action	Contact Software AG Global Support.

TNS.0003.4247E	**No standard fields found in bizdoc**
Explanation	Internal error occurred during profile validation.
Action	Contact Software AG Global Support.

TNS.0003.4252E	**Attempted to import extended field "{0}" for partner ID {1}, but this partner does not exist on your Trading Networks system.**
Explanation	Attempted to import extended field for a partner, but this partner does not exist on your Trading Networks.
Action	You must import the partner's profile before you can import extended fields for the partner.

TNS.0003.4253E	**Attempted to import extended field "{0}" that has an extended profile field ID of {1}, but this extended field is not defined on your Trading Networks system.**
Explanation	Cannot import the value of the extended profile field because there is no definition for the extended field.
Action	You must import the extended field definitions before you can import extended field values.

TNS.0003.4254E	**Error encountered invoking wm.tn.profile:addProfile {0}.**
Explanation	An exception was thrown while saving a new partner profile.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4257E	**Error encountered refreshing ID cache.**
Explanation	An exception was thrown while refreshing an internal cache.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4258E	**Could not get external IDs for partner (partnerID={0}).**
Explanation	An exception was thrown while retrieving external IDs.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4259E	**At least one ID must be specified for partner {0}.**
Explanation	Because the value of the required external ID type is used as the user name for an Integration Server user account, it must be specified.
Action	Specify the required external ID.

TNS.0003.4260E	**Could not retrieve Profile Groups from database.**
Explanation	Encountered a SQLException while retrieving profile group information from the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4262E	**profileGroupName can not be null or empty.**
Explanation	Trading Networks cannot accept null or an empty string for the profile group name.
Action	Specify a non-null a profile group name.

TNS.0003.4263E	**profileGroupName {0} already exists in database.**
Explanation	Trading Networks cannot accept a duplicate profile group name.
Action	Specify a unique profile group name.

TNS.0003.4264E	**A database error occurred while adding Profile Group {0}.**
Explanation	Encountered a SQLException while adding the new profile group.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4265E	**A database error occurred while changing Profile Group {0}.**
Explanation	Encountered a SQLException while changing the profile group name from its old name to a new name.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4266E	**A database error occurred while deleting Profile Group {0}.**
Explanation	Encountered a SQLException while deleting the profile group from the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4267E	**A databse error occurred while querying profile information.**
Explanation	Encountered a SQLException while executing a profile query.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4275E	**Error encountered invoking service {0}**
Explanation	Encountered an exception while invoking the specified service.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4276E	**{0} can not be null or a 0-length array.**
Explanation	The input signature profileGroupIds should be a non-null array.
Action	Specify non-null values for the profileGroupIds input.

TNS.0003.4281E	**Attempted to import security data for partner ID {0}, but this partner does not exist on your Trading Networks system.**
Explanation	You attempted to import a trading partner's security data without first importing this trading partner's profile.
Action	Import the trading partner's profile before you attempt to import the security data for this trading partner.

TNS.0003.4282E	**No {0} {1} delivery data exists in the database for this partner. Cannot update.**
Explanation	The profile update operation cannot be completed because the delivery protocol data is not available.
Action	Provide the delivery protocol details.

TNS.0003.4283E	**Could not add contact data for partner (id="{0}").**
Explanation	Encountered an exception while invoking wm.tn.profile:addContacts. The operation cannot be completed.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4284E	**Could not add address data for partner (id="{0}").**
Explanation	Encountered an exception while invoking wm.tn.profile:addAddresses. The operation cannot be completed.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4285E	**Could not add delivery data for partner (id="{0}").**
Explanation	Encountered an exception while invoking wm.tn.profile:addConnections. The operation cannot be completed.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4287E	**Could not delete profile group {0}, it is still in use.**
Explanation	The delete operation cannot be completed because the profile group is in use.
Action	Check the trading partner profiles to make sure that no partner belongs to the group you are attempting to delete.

TNS.0003.4289E	**Database error in adding partner {0} to profile groups. Import operation aborted.**
Explanation	Trading Networks encountered a problem with its database. There is a problem in the database or database driver.
Action	Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0003.4290E	**Cannot import partner profile(s) without My Enterprise profile.**
Explanation	You are attempting to import one or more partner profiles; however, the target Trading Networks server does not have an Enterprise profile.
Action	Create an Enterprise profile on the target server. Then, import the partner profiles.

TNS.0003.4291E **SQLException encountered in ProfileStore.addPartnerCertificate().**

Explanation Trading Networks encountered a problem with its database. There is a problem in the database or database driver.

Action Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0003.4292E **EXMLException encountered in ProfileStore.addPartnerCertificate().**

Explanation Trading Networks encountered a problem when attempting to save a certificate for a partner.

Action Take appropriate action to resolve the problem described in the exception.

TNS.0003.4293E **SQLException encountered in ProfileStore.getPartnerIDForCertificate().**

Explanation Trading Networks encountered a problem with its database. There is a problem in the database or database driver.

Action Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0003.4294E **EXMLException encountered in ProfileStore.getPartnerIDForCertificate().**

Explanation Trading Networks encountered a problem when attempting to retrieve a certificate for a partner.

Action Take appropriate action to resolve the problem described in the exception.

TNS.0003.4295E **Cannot deliver to My Enterprise. The supplied partnerID ({0}) is the partnerID of the My Enterprise profile. Please supply a different partnerID.**

Explanation The document receiver is the Enterprise profile, which indicates Trading Networks is to deliver the document to itself. This is not valid; Trading Networks cannot deliver a document to itself.

Action Either change the receiver to specify a trading partner, or do not attempt to deliver this document.

TNS.0003.4296E	**A deleted partner profile with the name "{0}" already exists. Cannot have duplicate partner names. Please enter a different name.**
Explanation	You attempted to create a profile. However, the Corporation Name and Unit Name you specify will make the profile a duplicate of a profile that was previously deleted. Although a profile is deleted, Trading Networks continues to maintain information about it in its database. As a result, you cannot create another profile using the same Corporation Name and Unit Name.
Action	If you want to reinstate the deleted profile, use the wm.tn.profile:undeleteProfile service. Otherwise, enter a different Corporation Name and Unit Name when creating a profile.

TNS.0003.4297E	**Importing a profile for {0} (id={1}), which is marked as "My Enterprise". A "My Enterprise" profile already exists for this Trading Network. If you want to update it, use the Force option. Process terminated.**
Explanation	You attempted to import an Enterprise profile into a Trading Networks system that already has an Enterprise profile.
Action	If you want to replace the existing Enterprise profile with the profile you are trying to import, use the Force option.

TNS.0003.4298E	**A deleted profile with the name "{0}" already exists. Unable to recreate a deleted profile.**
Explanation	A deleted partner profile with this Corporation Name already exists. Trading Networks maintains information about deleted profiles in its database and does not allow duplicate partner names.
Action	You can either use a different Corporation Name, or use the wm.tn.profile:undeleteProfile service to reinstate the deleted partner profile.

TNS.0003.4299	**Could not get Users for partner (partnerID={0}).**
Explanation	Encountered SQL Exception, not able to fetch users for specified partner.
Action	Check database connection

TNS.0003.4300	**Could not get partners for user (username={0}).**
Explanation	Encountered SQL Exception, not able to fetch partners for specified user.
Action	Check database connection

TNS.0003.4301 **Could not add users data for partner (id={1}).**

Explanation An exception was thrown while adding users to a partner.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4302 **Could not delete users data for partner (id={1}).**

Explanation An exception was thrown while deleting users for a partner.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4303 **Attempted to import a field definition "{0}" that uses a field group {1}, but this field group is not defined on your Trading Networks system.**

Explanation You attempted to import a field definition that uses a field group, but this field group is not defined on your Trading Networks.

Action Try importing field group before importing the field definition.

TNS.0003.4304 **Attempted to import a profile "{0}" that uses a contact type {1}, but this Contact Type is not defined on your Trading Networks system.**

Explanation You attempted to import a profile that uses a contact type, but this contact type is not defined on your Trading Networks system.

Action Try importing contact type before importing the profile.

TNS.0003.4305 **Attempted to import a profile "{0}" that uses an external id type {1}, but this external id type is not defined on your Trading Networks system.**

Explanation You attempted to import a profile that uses an external ID type, but this external ID type is not defined on your Trading Networks system.

Action Try importing external ID before importing the profile.

TNS.0003.4306 **Attempted to import a profile "{0}" that uses a profile group {1}, but this profile group is not defined on your Trading Networks system.**

Explanation You attempted to import a profile that uses a profile group, but this profile group is not defined on your Trading Networks system.

Action Try importing profile group before importing the profile.

TNS.0003.4309	**Could not validate the EXTERNAL ID with (idType={0}) and (externalID={1})**
Explanation	An exception was thrown while validating the specified external ID.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4310	**Error encountered while getting the External IDs associated with partner with (partnerID={0})**
Explanation	Error encountered while getting the External IDs associated with the supplied partnerID.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4311	**Following errors occurred during updating externalID**
Explanation	Errors occurred during updating external ID.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4312	**ID not added as the (externalIDType={0}) given is not a valid one.**
Explanation	Validation failed while updating the set of external IDs associated with a profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4313	**The partner specified (partnerID={0}) doesnot exist in the trading networks. Give a correct one.**
Explanation	Supplied partnerID does not exist in the Trading Networks.
Action	Supply valid partner ID.

TNS.0003.4314	**ID not added as the (externalIDType={0}) given already exists.**
Explanation	ID not added as the externalIDType=0 supplied already exists.
Action	Supply valid ID

TNS.0003.4316	**Error encountered while getting registered EDI IDTypes.**
Explanation	Error encountered while fetching registered EDI IDTypes.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4317	**Error encountered while cleaning up registered EDI IDTypes.**
Explanation	Error encountered while deregistering EDI ID Types.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4318	**Error encountered while getting the Internal ID of the Enterprise profile.**
Explanation	Error encountered while getting the Internal ID of the Enterprise profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4319	**Error encountered while getting the Internal Identifier for the environment.**
Explanation	Error encountered while getting the Internal Identifier for the environment.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4320	**"deliveryInfo" is empty. At least one Destination must be supplied.**
Explanation	While adding delivery settings, no destination supplied. At least one destination must be supplied.
Action	Supply at least one destination.

TNS.0003.4321	**"DestinationID" is empty. At least one DestinationID must be supplied.**
Explanation	While removing delivery settings, no destination ID supplied. At least one destination ID must be supplied.
Action	Supply at least one destination ID.

TNS.0003.4322	**Error encountered while adding the (externalIDType={0}).**
Explanation	Error encountered while adding the External ID type to Trading Networks.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4323	**Service Signature given (Service Signature ={0}) is invalid. Give a valid one.**
Explanation	Validation failed while retrieving the input or output signature of a specified service.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4324	**Error encountered while extracting Registered delivery Services.**
Explanation	Error encountered while extracting registered delivery Services.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4325	**Cannot set extended field {0} for partnerID {1}.**
Explanation	Error encountered while updating extended field for a profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4326	**Could not add user mapping for partnerID {0} and User {1}.**
Explanation	Error encountered while adding user mapping for a profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4327	**Either one of the inputs of simpleQuery or queryInput is mandatory for querying the profile.**
Explanation	Neither input of simpleQuery nor queryInput fields supplied for querying the profile.
Action	Supply either input of simpleQuery or queryInput fields for querying the profile.

TNS.0003.4328	**Error encountered while executing Profile Query**
Explanation	Error encountered while executing Profile Query
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4329	**My Enterprise Profile with specified (partnerID={0}) cannot be deleted.**
Explanation	You tried to delete the Enterpise Profile, but the Enterprise profile cannot be deleted.
Action	Don not attempt to delete the Enterprise profile.

TNS.0003.4332	**Please specify correct value for routing field. Mandatory values for it are true and false.**
Explanation	Supplied value for routing field is neither true nor false.
Action	Supply valid routing field value. It should be either true or false.

TNS.0003.4334	**Error encountered while adding DLS artifacts with name ({0}).**
Explanation	Error encountered while adding DLS artifacts, found artifact with specified name as null.
Action	Supply valid value for specified artifact name.

TNS.0003.4336	**Error encountered while querying on DLS Rules.**
Explanation	Error encountered while querying on DLS Rules and roles.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4337	**Pipeline for modifying the Rules and RuleRoleInfo shouldn''t be null.**
Explanation	Input fields found to be null, while modifying the Rules and RuleRoleInfo.
Action	Supply the input fields containing IData/pipeline.

TNS.0003.4338	**Either of the Rules or RoleRoleInfo shouldn''t be present.**
Explanation	Either Rules or RoleRoleInfo should be present while modifying.
Action	Supply either Rules or RoleRoleInfo.

TNS.0003.4339	**Error while Rule Addition/Modification, as a Rule already exists with the name ({0}).**
Explanation	Error encountered while adding or modifying rule, because a rule with the same name already exists.
Action	Supply rule with a different name.

TNS.0003.4340	**Error while Role Addition/Modification, as a Role already exists with the name ({0}).**
Explanation	Error encountered while adding or modifying a role, because a role with the same name already exists.
Action	Supply a role with different name.

TNS.0003.4341	**Please specify either Permission or ProfileID. Both of them are either null or empty. Either one of them is mandatory.**
Explanation	Found that Permission and ProfileID both are either null or empty while checking whether the current user can perform the required action.
Action	Supply either Permission and ProfileID.

TNS.0003.4342	**Please specify Permission. Either it is null or empty. Its a mandatory field.**
Explanation	During functional permission check, input field Permission found to be null or empty.
Action	Supply mandatory input field Permission.

TNS.0003.4343	**Error encountered while during operation on Functional Privileges.**
Explanation	Error encountered while checking functional privileges.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4344	**Error encountered while querying for Functional Privileges.**
Explanation	Error encountered while querying for functional privileges.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4345	**Please specify either Add or Remove. Both of them are either null or empty. Either one of them is mandatory.**
Explanation	While modifying functional privileges, both of the input field Add/Remove found empty or null.
Action	Supply valid values for the field Add/Remove.

TNS.0003.4346	**Access denied, as the User "{0}" does not have the permission to {1} {2}.**
Explanation	User is not permitted to perform the specified action.
Action	Contact your administrator.

TNS.0003.4347	**Access denied, as the User "{0}" does not have the permission to view {1}.**
Explanation	User is not allowed to perform the specified action.
Action	Contact your administrator.

TNS.0003.4348	**Access denied, as the User "{0}" does not have the privilege to {1} {2}.**
Explanation	User is not allowed to perform the specified action.
Action	Contact your administrator.

TNS.0003.4349	**Access denied, as the User "{0}" does not have the privilege to view {1}.**
Explanation	User is not allowed to perform the specified action.
Action	Contact your administrator.

TNS.0003.4393	**Access Denied. User "{0}" does not have permission to query expired certificates.**
Explanation	Specified user does not have permission to query expired certificates.
Action	Contact your administrator.

TNS.0003.4399	**Error encountered while getting list of permissions for the user "{0}".**
Explanation	Error encountered while getting list of permissions for the specified user.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4401	**Error encountered while profile "{0}" disassociation with DataSet "{1}".**
Explanation	Error encountered while profile disassociation with DataSet.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4402	**Disassociation of profile "{0}" from DataSet "{1}" is disallowed. Dissassociation would have made profile disappear from your profile list.**
Explanation	Disassociation of profile from DataSet is disallowed. Dissassociation would have made profile disappear from your profile list.
Action	No action required.

TNS.0003.4404	**Could not create delivery service {0}. A delivery service named {0} already exists.**
Explanation	Delivery service with the same name already exists in Trading Networks.
Action	Add delivery service with different name.

TNS.0003.4405	**The WmTN Property file {0} does not exist**
Explanation	Not able to locate Trading Networks properties file at expected location.
Action	Restore the TN Properties file. Contact Software AG Global Support.

TNS.0003.4406	**The WmTN Property file {0} is read only**
Explanation	Not able to write to the Trading Networks properties file.
Action	Make the Trading Networks properties file writable. Contact Software AG Global Support.

TNS.0003.5001E	**This document type ({0}) is missing one or both of its signature queries (Signature and SignedBody). Signing cannot proceed.**
Explanation	Trading Networks cannot create a digital signature because the TN document type did not instruct Trading Networks to extract the signature or signed body system attributes.
Action	Add queries to extract the Signature and SignedBody system attributes to the TN document type. For instructions, see the Trading Networks documentation.

TNS.0003.5002E	**The signing service for this document ({0}) generated an error. The original error was {1}.**
Explanation	Error encountered while signing the specified document.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.5003E	**Signing Failed**
Explanation	See message TRNSERV.000013.000002 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000002.

TNS.0003.5005E	**Base-64 encoding the signed body for this document failed to produce a value. The signed body (before encoding) was {0}.**
Explanation	The query used to extract the signed body from the document might be invalid. You specify the query that Trading Networks uses in the TN document type used for the document.
Action	If the query used for the signed body returned an empty string, adjust the signed body query for this TN document type. For instructions, see the Trading Networks documentation.

TNS.0003.5006E	**Encoding Error**
Explanation	See message TRNSERV.000013.000005 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000005.

TNS.0003.5007E	**An error prevented fetching certificate info for the sender of this document.**
Explanation	An exception was thrown while retrieving certificates needed to sign a document.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.5008E	**Error fetching cert info**
Explanation	See message TRNSERV.000013.000007 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000007.

TNS.0003.5010E	**No private key information was available for the sender of this document. {0}**
Explanation	Trading Networks encountered an error while fetching a private key. See the error message for details.
Action	You might need to import security data for this partner.

TNS.0003.5012E	**Applying the {1} query to this document failed. The error: {2}**
Explanation	Trading Networks encountered an error while executing the query to extract the signature from a document. See the exception for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.5013E	**Query Error**
Explanation	See message TRNSERV.000013.000012 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000012.

TNS.0003.5014E	**The signature query for doctype {0} identified the {1} node as the target of the signature, but this node is missing in this document. Signing cannot proceed.**
Explanation	The query used to extract the signature from the document identified a node that is not in the document. You specify the query that Trading Networks uses in the TN document type used for the document.
Action	Adjust the signature and/or signed body query for this TN document type. For instructions, see the Trading Networks documentation.

TNS.0003.5015E	**Missing Document Node**
Explanation	See message TRNSERV.000013.000014 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000014.

TNS.0003.5017E	**No cert chains are available for the sender of this document. {0}**
Explanation	Trading Networks encountered an error while fetching a certificate chain. See the error message for details.
Action	Take appropriate action to resolve the problem described in the error.

TNS.0003.5019E	**Cannot sign documents from UNKNOWN sender**
Explanation	The sender of the document is unknown to Trading Networks. Reasons that Trading Networks might be unable to determine the sender are: 1) The query that Trading Networks uses to extract the Sender value from the document might be incorrect. The query is defined in the TN document type. 2) The value extracted from the document for the Sender query does not match the external ID of any partner in the Trading Networks database. 3) The structure of the document is incorrect.
Action	Do one of the following: 1) If the query used to extract the Sender value is not valid, adjust the query in the TN document type. For instructions, see the Trading Networks documentation. 2) If the value extracted for the Sender query does not match an external ID in the Trading Networks database, add the external ID to the appropriate partner's profile. For instructions, see the Trading Networks documentation. 3) If the document structure is incorrect, notify the partner that sent the document.

TNS.0003.5021E	**This doctype ({0}) has no signing service defined. Signing cannot continue.**
Explanation	This TN document type has no signing service defined, so Trading Networks cannot continue with signing.
Action	If this is an XML TN document type, contact Software AG Global Support. If this is not an XML TN document type and the TN document type supports signing services, define a signing service for the TN document type.

TNS.0003.5024E	**The signature query for doctype {0} ({1}) failed to identify a node to insert the signature into. Signing cannot proceed.**
Explanation	Either the query that Trading Networks uses to extract the signature is incorrect in the TN document type or the structure of the document is incorrect.
Action	If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. If the document structure is incorrect, notify the document sender.

TNS.0003.5025E **The signature query for doctype {0} identified the {1} node as the target of the signature, but this node is not unique in this document. Signing cannot proceed.**

Explanation Either the structure of the document is incorrect or the query that Trading Networks uses to extract the signature is incorrect in the TN document type.

Action If the document structure is incorrect, notify the document sender. If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. Note that if your XQL query is returning an array of nodes, you can force it to return a single node by adding a subscript. For example, change "/anXMLtag" to "/anXMLtag[0]".

TNS.0003.5027W **No signing service for doctype {0}**

Explanation This TN document type has no signing service defined, so Trading Networks cannot continue with signing.

Action If this is an XML TN document type, contact Software AG Global Support. If this is not an XML TN document type and the TN document type supports signing services, define a signing service for the TN document type.

TNS.0003.5030E **Trading Networks will not sign documents originating from the Unknown partner. Signing fails.**

Explanation The sender of the document is unknown to Trading Networks. Reasons that Trading Networks might be unable to determine the sender are: 1) The query that Trading Networks uses to extract the Sender value from the document might be incorrect. The query is defined in the TN document type. 2) The value extracted from the document for the Sender query does not match the external ID of any partner in the Trading Networks database. 3) The structure of the document is incorrect.

Action Do one of the following: 1) If the query used to extract the Sender value is not valid, adjust the query in the TN document type. For instructions, see the Trading Networks documentation. 2) If the value extracted for the Sender query does not match an external ID in the Trading Networks database, add the external ID to the appropriate partner's profile. For instructions, see the Trading Networks documentation. 3) If the document structure is incorrect, notify the partner that sent the document.

TNS.0003.5031E **The signed body query for this document type ({0}) failed to produce a value. Signing the document fails. The query was {1}.**

Explanation Either the query that Trading Networks uses to extract the signature is incorrect in the TN document type or the structure of the document is incorrect.

Action If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. If the document structure is incorrect, notify the document sender.

TNS.0003.6001E	**Cannot persist a TPA**
Explanation	An exception was thrown while saving a TPA to the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6002E	**Cannot retrieve a TPA**
Explanation	An exception was thrown while reading a TPA from the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6006E	**Cannot delete a TPA with status="agreed"**
Explanation	You cannot delete a TPA with status Agreed.
Action	Change the TPA's status to Proposed and then delete it.

TNS.0003.6007E	**Cannot delete a TPA**
Explanation	An exception was thrown while deleting a TPA from the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6008E	**Cannot update a TPA that has status="agreed"**
Explanation	A TPA in "Agreed" status cannot be revised.
Action	Change the TPA's status to "Proposed" before updating the TPA.

TNS.0003.6009E	**Cannot update a TPA**
Explanation	An exception was thrown while updating a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6010E	**Cannot get a TPA lock**
Explanation	An exception was thrown while getting a lock on a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6011E	**Cannot update controlNumber for a TPA**
Explanation	An exception was thrown while updating the control number of a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6014E	**Cannot update tpaData when status="agreed" and dataStatus="immutable"**
Explanation	You attempted to update the TPA data that is associated with a TPA. The Agreement Status of the TPA is "Agreed" and the Data Status is "Non-modifiable." You cannot update the TPA data when the Data Status is "Non-modifiable."
Action	To be able to update the TPA data, perform one of the following actions: 1) change the Data Status to "Modifiable," or 2) change the Agreement Status to "Proposed."

TNS.0003.6017E	**Cannot update tpaData**
Explanation	An exception was thrown while updating the TPA data in a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6018E	**Cannot get the next controlNumber for a TPA**
Explanation	An exception was thrown while determining the next control number for a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6020E	**Cannot change status for a TPA**
Explanation	An exception was thrown while changing the status of a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6021E	**A TPA that matches senderID, receiverID and agreementID does not exists**
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0003.6022E	**Missing senderID, or receiverID, or agreementID or initService**
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0003.6023E	**Cannot invoke initService**
Explanation	Unable to initialize the data in a TPA because the TPA's initialization service could not be invoked.
Action	Make sure the TPA's initialization service is an existing service in an enabled package.

TNS.0003.6025E	**Query TPA exception**
Explanation	An exception was thrown while executing a TPA database query.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6026E	**Cannot get all TPAs**
Explanation	An exception was thrown while retrieving a list of TPAs from the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6027E	**Cannot import TPA**
Explanation	An exception was thrown while importing one or more TPAs.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6028E	**Missing data schema**
Explanation	No IS document type is defined for the TPA.
Action	Define an IS document type for the TPA.

TNS.0003.6029E	**Missing TPA data**
Explanation	The TPA Data field in the TPA is empty.
Action	Enter values into the TPA Data field.

TNS.0003.6030E	**Cannot invoke validation service**
Explanation	An exception was thrown while invoking the pub.schema:validate service while validating the structure of the IS document type in the TPA.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6031E	**Missing {0}**
Explanation	A required input variable was not supplied to the wm.tn.tpa:updateTPA service.
Action	Supply a value for the required variable.

TNS.0003.6032E	**A TPA that matches senderID, receiverID and agreementID already exists**
Explanation	Cannot save this TPA because it would duplicate an existing TPA.
Action	Either add the data in this TPA to the one that already exists, or specify a different agreementID.

TNS.0003.6033E	**A TPA that matches senderID, receiverID and agreementID does not exist**
Explanation	Cannot update the TPA because Trading Networks cannot locate a TPA in the database that has the supplied senderID, receiverID, and agreementID.
Action	Specify a senderID, receiverID and agreementID that matches an existing TPA.

TNS.0003.6034E	**controlNumber cannot not be null**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0003.6035E	**tpaData cannot not be null**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0003.6036E	**Cannot update tpaData when dataStatus="immutable"**
Explanation	You cannot make changes to a TPA's data when the TPA's Data Status is "Non-modifiable."
Action	To make changes to the TPA data, change the TPA's Data Status to "Modifiable."

TNS.0003.6037E	**Cannot update controlNumber**
Explanation	An exception was thrown while updating the control number of a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6038E	**There are more than one TPA that matches senderID, receiverID and agreementID**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0003.6039E	**Cannot serialize tpaData**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0003.6040E	**Cannot de-serialize tpaData**
Explanation	The supplied control number is not a valid integer.
Action	Supply a valid integer value.

TNS.0003.6041	**New controlNumber is not an integer**
Explanation	Encountered error while parsing supplied controlNumber because it is not an integer.
Action	Supply an integer value for controlNumber.

TNS.0003.6042E	**A TPA with the supplied ID ({0}) does not exist.**
Explanation	An invalid value was supplied for the tpaID field.
Action	Supply a valid TPA ID.

TNS.0003.6043E	**If "tpaID" is not supplied, then "senderID", "receiverID" and "agreementID" must be supplied.**
Explanation	The user did not supply the correct required inputs.
Action	Supply the required inputs.

TNS.0003.6044	**Attempted to import a TPA for Sender {0}, but the sender''s profile is not defined on your Trading Networks system.**
Explanation	Attempted to import a TPA for Sender, but the sender's profile is not defined on your Trading Networks system.
Action	Import Sender's profile first.

TNS.0003.6045 **Attempted to import a TPA for Receiver {0}, but the receiver''s profile is not defined on your Trading Networks system.**

Explanation Attempted to import a TPA for Receiver, but the receiver's profile is not defined on your Trading Networks system.

Action Import Receiver's profile first.

TNS.0003.6050 **Attempted to import a Archive Scheduled Service for Sender {0}, but the sender''s profile is not defined on your Trading Networks system.**

Explanation Attempted to import a Archive Scheduled Service for specified Sender, but the sender's profile is not defined on your Trading Networks system.

Action Import Sender's profile first.

TNS.0003.6051 **Attempted to import a Archive Scheduled Service for Receiver {0}, but the receiver''s profile is not defined on your Trading Networks system.**

Explanation Attempted to import a Archive Scheduled Service for Receiver, but the receiver's profile is not defined on your Trading Networks system.

Action Import Receiver's profile first.

TNS.0003.7002E **Document type {0} has no validation service defined. Validation fails.**

Explanation Supplied document type has no validation service defined.

Action Contact Software AG Global Support.

TNS.0003.7003E **No Validation Service**

Explanation A TN document type has no validation service defined. Validation fails.

Action Contact Software AG Global Support.

TNS.0003.7004E **{0}: {1}**

Explanation A document sent to Trading Networks failed validation.

Action Notify the document sender.

TNS.0003.7005W **Doctype {0}: no validation svc. defined; validation skipped**

Explanation Document type has no validation service defined. Validation fails.

Action Contact Software AG Global Support.

TNS.0003.7010E	**The doctype for this document ({0}) does not have a validation schema defined; validation fails.**
Explanation	The document matches a TN document type that indicates the document's structure should be validated, but no schema was defined.
Action	Update the TN document type, and specify the schema to use for document validation.

TNS.0003.7011E	**No Validation Schema**
Explanation	The document matches a processing rule that indicates the document's structure should be validated, but no schema was defined.
Action	Update the TN document type that the document matches to specify the schema to use for document validation.

TNS.0003.7012E	**The validation service for this XML document, {0}, could not be successfully invoked. The original exception message is: {1}**
Explanation	The service used to validate the document's structure threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.7013E	**The validation service used for this document ({0}) failed with the following exception message: {1}**
Explanation	The service used to validate the document's structure threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.7014E	**Validation Service Failed**
Explanation	The service used to validate the document's structure threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.7015E	**XML validation failed: does not apply to non-XML documents.**
Explanation	Invoked the wm.tn.doc.xml:validate service with a document that is not XML.
Action	Supply an XML document.

TNS.0003.7016E	**XML validation failed: no document content available**
Explanation	Document is empty.
Action	Supply an XML document that has content.

TNS.0003.7017E	**The validation service, {0} aborted processing of this document. The message was {1}.**
Explanation	The document is not valid XML.
Action	Notify the document sender.

TNS.0003.7019E	**Flat file validation failed. Document type is not "flat file".**
Explanation	Attempted to use a flat file validation service to validate a document that is not a flat file.
Action	Supply a flat file document.

TNS.0003.7020E	**Flat file validation failed: no document content available**
Explanation	Document is empty.
Action	Supply a flat file document that has content.

TNS.0003.7021E	**Flat file validation failed. Document type "{0}" has no parsing schema.**
Explanation	The document matches a TN document type that indicates the document's structure should be validated, but no schema was defined.
Action	Update the TN document type, and specify the schema to use for document validation.

TNS.0003.7022E	**Validation error**
Explanation	The flat file document structure is invalid.
Action	Notify the document sender.

TNS.0004.1001E	**Invalid or missing page number.**
Explanation	This error occurs if a value for the pageNum variable is not specified for the wm.tn.enumerate:nth service or if a value for the pageNumber variable is not specified for the wm.tn.query:getQueryResults service.
Action	Specify a value for the pageNum variable or pageNumber variable.

TNS.0004.1002E	**id is required.**
Explanation	A value for the id input variable was not specified for either the wm.tn.enumerate:nth service or the wm.tn.enumerate:first service.
Action	Specify a value for the input variable id.

TNS.0004.1004E	**Invalid time interval {0} for query.**
Explanation	The wm.tn.query:createDocumentQuery service was supplied an invalid value for the input variable timeInterval.
Action	Provide a valid value for the input variable timeInterval.

TNS.0004.1005E	**Unknown attribute ID: {0}.**
Explanation	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable attribId.
Action	Provide a valid value for the input variable attribId.

TNS.0004.1006E	**Unknown attribute name: {0}.**
Explanation	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable attribName.
Action	Provide a valid value for the input variable attribName.

TNS.0004.1007E	**Unknown op: {0}.**
Explanation	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable op.
Action	Provide a valid value for the input variable op. For more information about valid values, refer to the Trading Networks documentation.

TNS.0004.1008E	**Invalid entry type {0} for event.**
Explanation	The wm.tn.query:createEventQuery service was provided an invalid value for the input variable entryType.
Action	Provide a valid value for the input variable entryType.

TNS.0004.1009E	**Invalid time interval {0} for query**
Explanation	Either the wm.tn.query:createEventQuery service or the wm.tn.query:createTPAQuery service has an invalid value specified for the input variable timeInterval.
Action	Specify a valid value for the input variable timeInterval.

TNS.0004.1010E	**Invalid timeCreated interval {0} for query**
Explanation	The wm.tn.query:createTaskQuery service has an invalid value specified for the input variable timeCreated.
Action	Specify a valid value for the input variable timeCreated.

TNS.0004.1012D	**Requested page is not available**
Explanation	Requested page is not available. This error occurs when Trading Networks attempts to read beyond the end of the query results while invoking the wm.tn.enumerate:nth service. This error can also occur when data corresponding to the pageNumber input variable for the service wm.tn.query:getQueryResults is not available to Trading Networks.
Action	If the error occurs while invoking the wm.tn.enumerate:nth service, ensure the value specified for pageNum is valid. If the error occurs while invoking the wm.tn.query:getQueryResults service, ensure the value specified for pageNumber is valid. If the problem still persists, refresh the query.

TNS.0004.1013D	**Unable to retrieve page. Operation timed out.**
Explanation	The Integration Server might be busy doing other work.
Action	Attempt to retrieve the page again, or re-execute the query.

TNS.0004.1014E	**Query execution failed.**
Explanation	An exception occurred while executing a database query.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0004.1015E	**External ID value is required.**
Explanation	You created a profile query that specifies an externalIDType, but did not specify an externalIDValue.
Action	Provide a valid value for the externalIDValue input variable to the createProfileQuery service.

TNS.0004.1016E	**fieldId[{0}] is null or empty.**
Explanation	You created a profile query that specifies an externalIDValue, but you did not specify an externalIDType.
Action	Supply a valid value for the externalIDType input variable to the createProfileQuery service.

TNS.0004.2001E	**Illegal query type: {0}.**
Explanation	The query type specified as the input to the service is not valid.
Action	Supply a valid value for the query type. For a list of valid values, see the Trading Networks documentation.

TNS.0004.2002E	**pageNumber should be a positive integer.**
Explanation	The wm.tn.query:getQueryResults service was supplied an invalid value for the input variable pageNumber.
Action	Supply a valid value for the input variable pageNumber. The value must be a positive integer.

TNS.0004.2003E	**A valid pageNumber is required.**
Explanation	The pageNumber input variable for the wm.tn.query:getQueryResults service is not valid.
Action	Specify a valid value for pageNumber. The value must be a positive integer.

TNS.0004.2005E	**Got null query result data for queryId={0}, page={1}.**
Explanation	The wm.tn.query:getQueryResults service is not able to find the data corresponding to the specified queryId and pageNumber.
Action	Ensure the queryId and pageNumber are correct. If the issue persists, resumbit the query.

TNS.0004.2006E	**Got null row at index {0}.**
Explanation	There is no data corresponding to the specified index.
Action	Make sure the specified index is correct.

TNS.0004.2008I	**Can not retrieve task {0}.**
Explanation	While searching for tasks in My webMethods Server, no data corresponding to the specified taskid was found.
Action	Make sure the taskid is correct. If you update the taskid, then you must resubmit the query.

TNS.0004.2010E	**User does not have adequate privilege to obtain requested data.**
Explanation	The user's attempt to view the data failed because the user does not have permission to view the requested data.
Action	An administrator can grant permission to the user. For information about assigning permissions, refer to the Trading Networks documentation.

TNS.0004.2011E	**Bizdoc with internal id={0} does not exist.**
Explanation	The bizdoc with the specified docId cannot be found in the Trading Networks database .
Action	Make sure the docId is correct. If you change the docId, resubmit the query.

TNS.0004.2012E	**Null bizdoc retrieved for internal id = {0}.**
Explanation	The bizdoc with the specified docID cannot be found in the Trading Networks database.
Action	Make sure the specified docId is correct. If you change the docId, then you must resubmit the query.

TNS.0004.2013E	**Can not parse {0}: {1}.**
Explanation	The specified input value must be an integer.
Action	Supply a valid integer for the specified input value.

TNS.0004.2017E	**Retrieved null content part for document id = {0}, part name = {1}.**
Explanation	There are no content parts available for the bizdoc that corresponds to the specified docId.
Action	Make sure that the specified docId is correct and the content parts are recieved. After specifying the correct docId, resubmit the query.

TNS.0004.2019	**{0} encountered execution error.**
Explanation	An exception occurred while executing the service wm.tn.portal.queries.getContentPartBytes.
Action	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.

TNS.0004.2027	**{0} encountered error resubmitting internalDocIDs[{1}] = {2}.**
Explanation	In webMethods Trading Networks, when you resubmit the Bizdocs, this exception is thrown if the resubmission fails.
Action	Contact your system administrator.

TNS.0004.2028	**{0} encountered error while resubmitting following internalDocIDs: {1}. Access denied, as user {2} doesn''t have permission to resubmit these documents.**
Explanation	In webMethods Trading Networks, while resubmitting the BizDoc documents, if the user does not have access permission to resubmit these documents, this error is thrown.
Action	The administrator needs to give permission to the user for resubmitting the BizDoc documents.

TNS.0004.2030	**{0} encountered null or empty internalDocIDs[{1}], this document was not reprocessed.**
Explanation	In webMethods Trading Networks, while reprocessing BizDocs, if null or empty internal DocIDs are passed, this error is thrown.
Action	Ensure that the internal DocIDs are not null or empty.

TNS.0004.2031	**{0} encountered error reprocessing internalDocIDs[{1}] {2}.**
Explanation	In webMethods Trading Networks, if an error is encountered while reprocessing BizDocs, this error is thrown.
Action	Contact your system administrator.

TNS.0004.2032	**{0} encountered error while reprocessing following internalDocIDs: {1}. Access denied, as user {2} doesn''t have permission to reprocess these documents.**
Explanation	In webMethods Trading Networks, if an error is encountered while reprocessing BizDocs, access is denied as the user does not have permission to reprocess the documents.
Action	Ensure that the administrator gives permission to the user to reprocess BizDocs.

TNS.0004.2034	**{0} encountered null or empty taskIDs[{1}] {2}, this task was not stopped.**
Explanation	In webMethods Trading Networks, while stopping the tasks, if null or empty taskIDs are passed, this error is thrown.
Action	Ensure that the taskID is not null or empty and try again.

TNS.0004.2035	**{0} encountered error stopping taskIDs[{1}] {2}.**
Explanation	In webMethods Trading Networks, while stopping the tasks, if the stopping fails for any reason, this error is thrown
Action	Contact your system administrator.

TNS.0004.2036	**{0} encountered error while stopping following tasks: {1}. Access denied, as user {2} doesn''t have permission to stop these tasks.**
Explanation	In webMethods Trading Networks, while stopping the tasks, if the user does not have permission to stop the tasks, this error is thrown.
Action	Ensure that the user has permission to stop the tasks.

TNS.0004.2038	**{0} encountered null or empty taskIDs[{1}], this task was not restarted.**
Explanation	In webMethods Trading Networks, while restarting tasks, if null or empty taskIDs are passed, this error is thrown.
Action	Ensure that the taskID is not null or empty and try again.

TNS.0004.2039	**{0} encountered error restarting taskIDs[{1}] {2}.**
Explanation	In webMethods Trading Networks, if restarting tasks fails, this error is thrown.
Action	Contact your system administrator.

TNS.0004.2040	**{0} encountered error while restarting following tasks: {1}. Access denied, as user {2} doesn''t have permission to restart these tasks.**
Explanation	In webMethods Trading Networks, while restarting tasks, if access is denied to the user, this error is thrown.
Action	Ensure that the user has access permission to restart tasks and try again.

TNS.0004.2042	**{0} encountered null or empty taskIDs[{1}], this task was not deleted.**
Explanation	In webMethods Trading Networks, while deleting tasks, if null or empty taskIDs are passed, this error is thrown.
Action	Ensure that the taskIDs passed are not null or empty, and try again.

TNS.0004.2043	**{0} encountered error deleting taskIDs[{1}] {2}.**
Explanation	In webMethods Trading Networks, if an error occurs while deleting the tasks, this error is thrown.
Action	Contact your system administrator.

TNS.0004.2044	**{0} encountered error while deleting following tasks: {1}. Access denied, as user{2} doesn''t have permission to delete these tasks.**
Explanation	In webMethods Trading Networks, while deleting tasks, if the user does not have permission, this error is thrown.
Action	Ensure that the user has permission to delete tasks, and try again.

TNS.0004.2048	**{0} encountered error while updating User Status for internalDocID {1}. Access denied, as user {2} doesn''t have permission to change UserStatus for this document.**
Explanation	In webMethods Trading Networks, while updating the user status for XXX, if access is denied because the user does not have permission to change UserStatus for this document, this error is thrown.
Action	Ensure to give permission to the user to change UserSTatus for the document, and try again.

TNS.0004.2050	**{0} encountered error while updating comments for internalDocID {1}. Access denied, as user {2} doesn''t have permission to edit comments for this document.**
Explanation	In webMethods Trading Networks, while updating comments for an internal document, if access is denied because the user does not have access permissions, this error is thrown.
Action	Ensure that the user has access permissions and try again.

TNS.0004.2052	**{0} encountered error while deleting following ActivityLogIDs: {1}. Access denied, as user {2} doesn't have permission to delete these activity logs.**
Explanation	In webMethods Trading Networks, while deleting activity logs, if access is denied because the user does not have access permissions, this error is thrown.
Action	Ensure that the user has access permissions, and try again.

TNS.0004.2054	**{0} can not reassign task {1} to {2}.**
Explanation	In webMethods Trading Networks, while reassigning the task to another server, if it is unsuccessful, this error is thrown.
Action	Contact your system administrator.

TNS.0004.2055	**{0} encountered error while reassigning following tasks. Access denied, as user {2} doesn''t have permission to reassign these tasks.**
Explanation	In webMethods Trading Networks, while reassigning tasks to another server, if the user does not have access permissions, this error is thrown.
Action	Ensure that the user has access permissions, and try again.

TNS.0004.2057	**ws.monitor.process.instance:getList returns null output.**
Explanation	In webMethods Trading Networks, while getting process information, if ws.monitor.process.instance:getList service returns null output, this error is thrown.
Action	Ensure that the ws.monitor.process.instance:getList service does not return null output, and try again.

TNS.0004.2058	**{0} can not get instance information for conversationId {1}.**
Explanation	In webMethods Trading Networks, when the user gets a null value of the process information for the conversation ID, this error is thrown.
Action	Ensure the conversation ID is valid and try again.

TNS.0004.2060	**{0} retrieved null instance at index 0 for conversationId {1}.**
Explanation	In webMethods Trading Networks, while getting process information for a conversation ID, if the instance at index 0 is null, this error is thrown.
Action	Ensure that the instance at index 0 is not null and try again.

TNS.0004.2065	**WmMonitor package is not enabled.**
Explanation	In webMethods Trading Networks, while checking process information, the WmMonitor package is not installed or enabled.
Action	Ensure that the WmMonitor package is installed and enabled.

TNS.0004.2066	**{0} can not submit document.**
Explanation	In webMethods Trading Networks, if resubmission of a modified document fails, this error is thrown.
Action	Contact your system administrator.

TNS.0004.2067	**{0} encountered error retrieving submitted document from pipeline.**
Explanation	In webMethods Trading Networks, while resubmitting documents with modifications, if the retrieved BizDoc is null, this error is encountered.
Action	Ensure that the resubmitted BizDoc is not null and try again.

TNS.0004.2071	**{0} encountered error while modifying & resubmitting following document {1}. Access denied, as user {2} doesn''t have permission to modify and resubmit this document.**
Explanation	In webMethods Trading Networks, while resubmitting modified BizDoc documents, if the user does not have access permissions, this error is displayed.
Action	Ensure that the user has access permissions to resubmit and modify BizDoc documents, and try again.

TNS.0004.2072	**{0} encountered execution error.**
Explanation	In webMethods Trading Networks, if the execution of any query related serivce fails, this error is displayed.
Action	Contact your system administrator.

TNS.0004.2074	**can not parse {0} to long number.**
Explanation	In webMethods Trading Networks Server portal util, in the getTimestampFromLong utility, if the time is not in numbered format, this error is thrown.
Action	Enter time in a numbered format and try again.

TNS.0004.2075	**null or empty field name**
Explanation	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws this exception when the column name is null or empty.
Action	Enter a column name that is not null.

TNS.0004.2076	**Invalid query column name: {0}.**
Explanation	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the column name is invalid.
Action	Enter a valid column name and try again.

TNS.0004.2077	**Invalid document attribute ''{0}''.**
Explanation	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the query type is of doc query and the attribute list of the document does not contain the name passed to the utility.
Action	Ensure that the attribute list of the document contains the name passed to the utility and try again.

TNS.0004.2078	**Invalid whichQuery value ({0}) for PortalUtils.checkQueryColumnName().**
Explanation	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the query type passed to the utility is invalid.
Action	Ensure to enter a valid query type and try again.

TNS.0004.2079	**Invalid value for {0}: null or empty.**
Explanation	In webMethods Trading Networks portal util, the validateOperator utility throws an exception if the operator passed to the utility is null or empty.
Action	Pass a valid operator to the utility and try again.

TNS.0004.2080	**Invalid operator {0} for data type {1}.**
Explanation	In webMethods Trading Networks portal util, the validateOpValPair utility throws an exception if the operator passed to the utility is null or empty.
Action	Enter a valid operator and try again.

TNS.0004.2081	**Invalid null value for {0}, corresponding operator is {1}.**
Explanation	In webMethods Trading Networks portal util, the validateOpValPair utility throws an exception if the value supplied corresponding to an operator is null.
Action	Enter a not null value corresponding to the operator.

TNS.0004.2082	**Illegal value for number query, {0}: {1}.**
Explanation	In webMethods Trading Networks portal util, the validateOpValPair utility throws this exception if the value passed to this utility corresponding to an operator is not in numeric value.
Action	Pass the value to the utility in numeric value and try again.

TNS.0004.2083	**Illegal value for date and time query, {0}: {1}.**
Explanation	In webMethods Trading Networks portal util, the validateOpValPair utility throws this exception if the value passed to this utility corresponding to an operator is not parsed to a long value.
Action	Enter a numeric long value for the date and time query and try again.

TNS.0004.2084	**Unable to display the error message. An internal error has occured. Please contact customer support.**
Explanation	In webMethods Trading Networks portal util, the decodeErrorMessage2 utility throws an exception and is unable to decode the error message.
Action	Contact your system administrator.

TNS.0004.2085	**Can not get related document information for docId={0}: null data returned**
Explanation	In webMethods Trading Networks, while getting document information for a document ID, If the data extracted for the document ID is null, it throws an error.
Action	Contact your system administrator.

TNS.0004.2086	**Invalid whichQuery value {0}.**
Explanation	In webMethod Trading Networks, this error message is shown if the query type (whichQuery) for creating a query is invalid.
Action	Enter a valid query type (whichQuery) in creating a query.

TNS.0004.2088	**Invalid non-number value for queryInput/pageSize: {0}.**
Explanation	In webMethods Trading Networks, in creating a query, the query input or page size entered is a non-number value.
Action	Enter a valid numeric value for the query input or the page size.

TNS.0004.2089	**queryInput/pageSize value is equal or less than 0.**
Explanation	In the webMethods Trading Networks, while creating or retrieving a query, the queryInput or pageSize value entered is not valid because it is equal to or less than 0.
Action	Enter a valid queryInput or pageSize value for creating or retrieving a query.

TNS.0004.2090	**queryInput/criteria/dateRange/startDate {0} is after queryInput/criteria/dateRange/endDate {1}.},**
Explanation	In webMethods Trading Networks, while creating a query, if the start time is earlier than the end time, this error is shown.
Action	Ensure to correct the start time.

TNS.0004.2091	**Invalid null value for queryInput/sortOrder[{0}].**
Explanation	In webMethods Trading Networks, while creating or retrieving a query, if any of the sorting columns is null, this error is shown.
Action	Ensure that the sorting column is not null.

TNS.0004.2092	**{0} queryInput/sortOrder[{1}]/columnName ({2}) is not valid, ignored this column for query sorting.**
Explanation	In webMethods Trading Networks, while creating a query, if the sorting column specified in the query input is not valid, the column is ignored for query sorting.
Action	Ensure to enter a valid sorting column in the query.

TNS.0004.2093	**Invalid null value for queryInput/criteria/fields[{0}].**
Explanation	In webMethods Trading Networks, while creating a query, if any of the given fields is null, this error is shown.
Action	Ensure to enter a valid valiue (not null) for all the fields.

TNS.0004.2094	**Invalid null or empty queryInput/criteria/fields[{0}]/fieldName value.**
Explanation	In webMethods Trading Networks, while creating a query, if the field name is null or empty, this error is thrown.
Action	Ensure that all field names are valid.

TNS.0004.2095	**query criteria for field {0} already exists, additional criteria found at index {1}.**
Explanation	In webMethods Trading Networks, while creating a query, if the query criteria for the field already exists, this error is thrown.
Action	Enter a query criteria that is unique.

TNS.0004.2096	**Invalid value: {0} for queryInput/criteria/fields/isOrQuery.**
Explanation	In webMethods Trading Networks, while creating a query, an invalid value is entered for the IsOrQuery (value of OR is undefined).
Action	Enter a valid value for the IsOrQuery (value of OR).

TNS.0004.2097	**queryInput/criteria/fields[{0}]/criteria is null or 0-length.**
Explanation	In webMethods Trading Networks, while creating a query object based on filter criteria, the criteria list for query fields is null or empty.
Action	Enter a valid criteria list for query fields in queryInput.

TNS.0004.2100	**Invalid value for {0}: null or empty.**
Explanation	In webMethods Trading Networks, while creating a query object based on filter criteria, if the criteria does not contain any operator, this error is thrown.
Action	Enter the operator for the criteria.

TNS.0004.2101	**{0} criteria can only be a list plus a dynamic profile query.**
Explanation	In webMethods Trading Networks, while creating a query object based on filter criteria, if the query type is a doc query, there should be only one list of values and profile query in the sender and receiver criteria.
Action	Enter only one list of values and profile query in the sender and receiver criteria and try again.

TNS.0004.2102	**Invalid value for {0}.**
Explanation	In webMethods Trading Networks, while creating a query object based on filter criteria, if the query is of jobQuery type, the internal doc ID or the sender ID or the task ID or the server ID or the instance ID cannot be null.
Action	Ensure that the internal doc ID or the sender ID or the task ID or the server ID or the instance ID are not null and try again.

TNS.0004.2103	**Can not understand query {0}.**
Explanation	In webMethods Trading Networks, while performing a query, if the query type is not a doc, task, event, profile, bizdoc type, attrib, tpa, or invite type of query, this error message is thrown.
Action	Enter the valid query type and try again.

TNS.0005.1003E	**Service manager create failed for server {0} - {1}**
Explanation	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1005E	**Unable to get profile for {0} - {1}**
Explanation	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1006E	**Unable to remove delivery service {0} - {1}**
Explanation	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1014E	**Unable to create delivery task {0} - service {1} does not exist**
Explanation	Attempted to deliver a document using a non-existent delivery service.
Action	Correct the serviceName parameter sent to wm.tn.delivery:deliver.

TNS.0005.1027E	**Unable to create service data for partner {0} - {1}**
Explanation	Attempted to deliver a document to a partner that cannot receive the document. Receiver is either INACTIVE or is My Enterprise (the entity hosting this Trading Network).
Action	Deliver the document to a valid trading partner with an ACTIVE status.

TNS.0005.1028E	**Unable to set private key and certificate chain - {0}**
Explanation	Encountered an exception while setting the certificate chain and private key in preparation to deliver a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.1032E	**{0} refreshing {1} cache: {2}**
Explanation	Encountered an exception while refreshing an internal cache. See the exception message for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1038E	**Error transporting via {0}: {1}**
Explanation	Encountered an exception while delivering a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.

TNS.0005.1040E	**{0} initializing task store: {1}**
Explanation	Encountered an exception while initializing internal caches used for document delivery. See the exception message for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1041E	**{0} deleting delivery service {1}: {2}**
Explanation	Encountered an exception while removing a registered delivery service from the database.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1050E	**{0} deleting task {1}: {2}**
Explanation	Encountered an exception while deleting a delivery or routing task.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1054E	**DeliveryUtils init error: Unable to get profile store: {0}**
Explanation	Could not access the profile store during server initialization.
Action	Copy the exception details and call Software AG Global Support.

TNS.0005.1055E	**Unable to register delivery service {0} - {1}**
Explanation	Encountered an exception while registering a delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1064E	**Unable to initialize delivery interface**
Explanation	Encountered an exception while initializing the Delivery Service Manager.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1065E	**Unable to register delivery defaults**
Explanation	Encountered an exception while registering the built-in delivery services.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1066E	**Unable to deliver bizdoc by service**
Explanation	Encountered an exception when wm.tn.deliver:deliverByService was invoked.
Action	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.

TNS.0005.1067E	**Error delivering bizdoc**
Explanation	Encountered an exception while delivering a document.
Action	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.

TNS.0005.1068E	**Error getting delivery job**
Explanation	Encountered an exception while retrieving a delivery job.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1069E	**Error getting delivery job output**
Explanation	Encountered an exception while retrieving the output of a reliable delivery job.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1070E	**Error getting delivery job status**
Explanation	Encountered an exception while retrieving the status of a delivery job.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1071E	**Error removing delivery job**
Explanation	Encountered an exception while removing a reliable delivery job.
Action	Use the JDBC Pools page on the Integration Server Administrator to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1072E	**Error restarting delivery job**
Explanation	Encountered an exception while restarting a reliable delivery job.
Action	Use the JDBC Pools page on the Integration Server Administrator to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1073E	**Error getting registered delivery service {0}**
Explanation	Encountered an exception while retrieving a registered delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1074E	**Error getting registered delivery services**
Explanation	Encountered an exception while retrieving the set of registered delivery services.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1075E	**Error determining if delivery service {0} is registered**
Explanation	Encountered an exception while retrieving a named registered delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1076E	**Error refreshing service cache**
Explanation	Encountered an exception while refreshing the cache of registered delivery services.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1077E	**Error registering service {0}**
Explanation	Encountered an exception while registering a delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1078E	**Error removing service {0}**
Explanation	Encountered an exception while unregistering a delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1081E	**Couldn''t query delivery service table**
Explanation	Encountered a SQLException while reading delivery services.
Action	Take appropriate action to resolve the problem described in the exception, if possible.

TNS.0005.1082E	**Couldn''t query delivery job table**
Explanation	Encountered a SQLException while reading delivery jobs.
Action	Take appropriate action to resolve the problem described in the exception, if possible.

TNS.0005.1083E	**Property watt.server.smtpServer is not set**
Explanation	Cannot send e-mail messages because the system property, watt.server.smtpServer, has not been set.
Action	Use the Properties page of the Integration Server Administrator to supply a value for the watt.server.smtpServer property.

TNS.0005.1084E	**Receiver of document cannot be self**
Explanation	A document is being sent from this Trading Networks server and the receiver of the document is a host of Trading Network. You cannot send a document to yourself.
Action	Ensure that the receiver of the document is not a host of Trading Networks.

TNS.0005.1085E	**Receiver of document is not Active**
Explanation	Status of the partner profile for the receiver of the document is not in active state. Documents can only be sent to active partners.
Action	Ensure the receiver of the document is an active partner.

TNS.0005.1086E	**Unknown protocol: {0}**
Explanation	Attempted to send a document via an unknown protocol. Documents must be sent using one of the registered delivery services.
Action	Use a registered delivery service to send the document.

TNS.0005.1087E	**Destination info not found**
Explanation	Attempting to send a document, but the receiver's destination information cannot be found.
Action	Examine the document to learn the intended receiver. Make sure the receiver's profile has valid delivery method information.

TNS.0005.1090E	**Unable to initialize DeliveryStore {0}**
Explanation	Encountered an exception during initialization.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.1092E	**Service not registered**
Explanation	Attempted to remove a delivery service that is not registered.
Action	Check the name of the registered delivery service you want to remove.

TNS.0005.1096E	**Delivery queue {0} refers to Delivery service {1} which is not registered.**
Explanation	In webMethods Trading Networks, during batch delivery of queued tasks, if the delivery service used is not registered and the delivery queue refers to it, this error is thrown.
Action	Use the webMethods Trading Networks to update the delivery queue so that it uses a valid batch delivery service.

TNS.0005.1097E	**Cannot deliver document. Receiver is not active. (DocID={0}, ReceiverD={1})**
Explanation	Queued a document for scheduled delivery, but the receiver is inactive and cannot receive documents.
Action	Activate the receiver's trading partner profile, if appropriate.

TNS.0005.1098E	**Unable to get document content for delivery. (DocID={0})**
Explanation	Queued a document for scheduled delivery and encountered an error while retrieving document content.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1099E	**Cannot register a delivery service with the same name as a built-in delivery service ({0}).**
Explanation	This name is reserved for a built-in Trading Networks delivery service.
Action	Change the delivery service's name.

TNS.0005.1101E	**Cannot get certificate information from security store for partner {0} in getting delivery information: {1}**
Explanation	Encountered an exception while retrieving the certificate chain and private key for a trading partner.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.1105E	**Unable to get profile for partner {0} - {1}**
Explanation	Encountered an exception while retrieving a trading partner profile.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1106E	**Unable to get destination info for partner {0} - {1}**
Explanation	Encountered an exception while retrieving destination information from a trading partner profile in preparation for document delivery.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1107E	**Encountered error while delivering by context: {0}**
Explanation	Encountered an exception while delivering a document using an internal webMethods protocol.
Action	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.

TNS.0005.1108E	**Unable to deliver document {0}. Delivery service [{1}] does not exist**
Explanation	Document delivery failed because the associated delivery service does not exist.
Action	Create the missing delivery service or specify a different delivery service.

TNS.0005.1109	**The document (id={0}) was not persisted. The "{1}" delivery service will not be invoked. The document will not be delivered.**
Explanation	In webMethods Trading Networks, while delivering documents, if the BizDoc is not persisted, the delivery service is not invoked and the document is not delivered.
Action	Contact your system administrator.

TNS.0005.1115	**Event found to be null**
Explanation	In webMethods Trading Networks, while writing routing events, if the event is found to be null, then this error is thrown.
Action	Contact your system administrator.

TNS.0005.1117	**Encountered error while creating TN document from service response: {0}**
Explanation	In webMethods Trading Networks, while delivering a document via WebService, if the document cannot be created from response data, this error is thrown.
Action	Contact your system administrator.

TNS.0005.1118	**Encountered error while adding service response to bizdoc: {0}**
Explanation	In webMethods Trading Networks, while delivering a document via WebService, if the response data cannot be added as content to the BizDoc, this error is thrown.
Action	Contact your system administrator.

TNS.0005.2002E	**An error occurred when this partner polled for documents on this server. The original error message was {0}.**
Explanation	An exception was thrown while polling for documents.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.2014E	**Error polling for documents**
Explanation	An exception was thrown while polling for documents.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.2017E	**An error occurred when trying to connect to this partner for polling. The original error was: {0}**
Explanation	In webMethods Trading Networks, during a remote checking of a partner, if the connection to the partner cannot be made, this error is thrown.
Action	Ensure that the partner connection information is valid and try again.

TNS.0005.2018E	**Error connecting for polling**
Explanation	An error occurred when trying to connect to this partner for polling.
Action	Take appropriate action to resolve the problem described in the exception. You might need to contact your trading partner about the error.

TNS.0005.2021E	**The user account that schedules polling jobs is {0}. The account does not exist on the B2B Server.**
Explanation	In webMethods Trading Networks, during scheduling of a polling job, if the user account that starts the polling job does not exist on the B2B server, this error is thrown.
Action	Create a user account for the user and reload the WmTN package or restart the Integration Server.

TNS.0005.2031E	**An error occurred in the process of accepting a document polled from this partner. The original document ID was {0}. The original error message was {1}.**
Explanation	In webMethods Trading Networks, if any error occurs during the process of submitting a document locally that is polled from a remote partner, this error is thrown.
Action	Contact your system administrator.

TNS.0005.2037E	**Error accepting document**
Explanation	An exception was thrown while accepting a document polled from a partner.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.2052E	**Unable to initialize TN Polling.**
Explanation	An exception was thrown during initialization.
Action	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.2053E	**User {0} is not an administrator and attempted to accept a document (docID={1}) that does not belong to him.**
Explanation	A partner attempted to accept a pollable document; however, the partner is not the specified receiver of the document.
Action	Review the log message. Contact the partner identified in the log message to explain that a partner can only accept pollable documents for which that partner is the specified receiver.

TNS.0005.2054E	**You do not have the authority to accept this document. Only administrators may accept documents that they did not receive.**
Explanation	A partner attempted to accept a pollable document; however, the partner is not the specified receiver of the document.
Action	Review the log message. Contact the partner identified in the log message to explain that a partner can only accept pollable documents for which that partner is the specified receiver.

TNS.0005.2055E	**No document with an ID of {0} exists. No document accepted.**
Explanation	A partner is trying to accept a pollable document that does not exist within Trading Networks.
Action	Review the log message. Work with the partner specified in the log message to resolve the issue.

TNS.0005.3001E	**{0} is required.**
Explanation	A service was invoked, and a required input variable was not supplied.
Action	Supply a value for the specified variable.

TNS.0005.3002E	**Unable to save queue "{0}".**
Explanation	Attempt to insert queue information into the Trading Networks database failed.
Action	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.

TNS.0005.3003E	**Cannot reassign tasks to a private queue.**
Explanation	Each partner might have its own private queue. Private queues are defined in the profile for a partner. A private queue can contain only tasks for the partner identified by the profile; private queues cannot contain tasks from other partners.
Action	You can reassign these tasks to a public queue.

TNS.0005.3004E	**Unable to remove queue "{0}".**
Explanation	Attempt to delete queue information from the Trading Networks database failed.
Action	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.

TNS.0005.3005E	**Unable to update queue "{0}".**
Explanation	Attempt to update queue information in the Trading Networks database failed.
Action	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.

TNS.0005.3006E	**The queue cannot be deleted because there is data that depends on it.**
Explanation	The queue cannot be deleted for one or more of the following reasons: 1) There might be tasks currently on the queue. 2) There are partner profiles and/or processing rules that refer to the queue. A list of objects that depend on the queue follow this message.
Action	Take one or more of the following actions: 1) If there are tasks on the queue, place it in a DRAINING state so that the queue will empty. After all tasks in the queue are processed, you can delete the queue. 2) If there are profiles and/or processing rules that refer to the queue, remove those references. After you remove the references, you can delete the queue.

TNS.0005.3007E	**There are {0} tasks on the queue.**
Explanation	The queue cannot be removed because it has tasks on it.
Action	Place the queue in a DRAINING state so that the queue will empty. After the tasks in the queue have been processed, you can delete it.

TNS.0005.3008E	**There are {0} partner profiles that refer to the queue.**
Explanation	The queue cannot be removed because one or more partner profiles refers to it.
Action	This message is followed by a list of partners whose profiles refer to the queue. Modify these profiles so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.

TNS.0005.3009E	**There are {0} processing rules that refer to the queue.**
Explanation	The queue cannot be removed because one or more processing rules refers to it.
Action	This message is followed by a list of processing rules that refer to the queue. Modify these processing rules so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.

TNS.0005.3012E	**There is no task with the supplied ID ({0}).**
Explanation	The wm.tn.queuing:updateQueuedTask service was supplied an invalid task ID.
Action	Supply a valid task ID.

TNS.0005.3013E	**updateQueuedTask may only be invoked for tasks that are currently being processed from a DeliveryQueue. This task ({0}) has a status of {1}.**
Explanation	You attempted to run the wm.tn.queuing:updateQueuedTask service for a task; however, you did not first invoke the wm.tn.queuing:getQueuedTask service.
Action	Be sure to use the wm.tn.queuing:getQueuedTask service to retrieve a task from a queue.

TNS.0005.3018E	**Attempted to update a DeliveryQueue that has not been registered (queue name={0}).**
Explanation	The specified queue does not exist.
Action	Either supply a valid queue name or use My webMethods to define the delivery queue.

TNS.0005.3019E	**status must be "success" or "fail". {0} was supplied.**
Explanation	The wm.tn.queuing:updateQueuedTask service was supplied an invalid status.
Action	Supply a valid status value.

TNS.0005.3020E	**Attempted to remove a DeliveryQueue that has not been registered (queue name={0}).**
Explanation	The specified queue does not exist.
Action	Supply a valid queue name.

TNS.0005.3021E	**Unable to decode TypeData for a DeliveryJob (ID={0}) while dequeuing from {1}**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0005.3023E	**The scheduled delivery date/time is in the past.**
Explanation	Trading Networks cannot schedule delivery to run in the past.
Action	Supply a future date and time.

TNS.0005.3024E	**The delivery schedule is empty. It has been ignored.**
Explanation	The delivery queue does not have a delivery schedule. The operation has failed.
Action	If you receive this error while invoking a service, make sure that you are supplying a valid DeliveryQueue object that contains a DeliverySchedule. If you receive this error while using My webMethods, contact Software AG Global Support.

TNS.0005.3025E	**Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss"**
Explanation	A date and/or time in the delivery schedule is invalid.
Action	All dates and times in the delivery schedule must be in the specified formats.

TNS.0005.3027E	**Unable to schedule delivery for queue "{0}". The pipeline for the delivery service does not contain "queue".**
Explanation	The variable "queue" was not supplied in the pipeline.
Action	Supply the name of the delivery queue.

TNS.0005.3028E	**The delivery schedule has no schedule type. It has been ignored.**
Explanation	The delivery schedule must have a type of "repeat", "complex", or "once".
Action	Set the type on the delivery schedule to a valid value.

TNS.0005.3029E	**The queue "{0}" does not exist.**
Explanation	In webMethods Trading Networks, while updating a queue, if the queue does not exist, this error is thrown.
Action	Ensure that the queue that is to be updated exists, and try again.

TNS.0005.3037E	**Scheduled delivery failed. No more retries.**
Explanation	The final attempt to delivery a document failed.
Action	See the message TRNSERV.000022.000038 for full details.

TNS.0005.3038E	**Scheduled delivery of document {0} failed. No more retries. {1}**
Explanation	The final attempt to deliver a document failed.
Action	See the error message for details. You might need to contact your trading partner.

TNS.0005.3039E	**The queue "{0}" has a status of "{1}". It is not accepting documents. This document will not be delivered.**
Explanation	Attempted to route a document to a delivery queue that is either disabled or draining. Queues in either of these statuses cannot accept documents.
Action	Either change the status of this queue or route the document to a different queue.

TNS.0005.3040E	**Unable to validate private queue/partner relationship (id={0}) because the partner could not be retrieved. The queue has been saved with a "disabled" status.**
Explanation	You can only create a private queue for a partner that has an active profile. The specified partnerID identifies a partner that does not exist or whose profile is not active.
Action	Perform one of the following actions: 1) Specify a different queue. 2) If the profile is not active, change its status to active.

TNS.0005.3041E	**Private queue "{0}" has a status of "{1}", but the partner''s profile is not active. The queue has been saved with a "disabled" status.**
Explanation	Trading Networks attempted to route a document to a private queue that is defined for a profile that is not active. Trading Networks can only route documents to private queues belonging to active partners; it cannot route documents to private queues of inactive partners. Trading Networks has disabled the queue.
Action	Enable the partner by changing the profile status to active. Then enable the partner's private queue.

TNS.0005.3042E	**Delivery not scheduled from queue.**
Explanation	In webMethods Trading Networks, while scheduling delivery of documents from queues, if the queue is private and the partner is either inactive or not found, this error is thrown.
Action	Ensure that the partner of the private queue is available and active, and try again.

TNS.0005.3044E	**Document was not queued for delivery on queue {0}. The receiver''s profile was not found. (receiverID={1}).**
Explanation	A processing rule indicated that the document should be delivered to a queue that is associated with a receiver. However, there is no profile for the receiver.
Action	Use My webMethods to determine who the intended receiver is. If the receiver is valid but does not have a profile, create a partner profile for the receiver. If the receiver is not valid, notify the document sender that the receiver information in the document is incorrect.

TNS.0005.3045E	**Document was not queued for delivery on queue {0}. The receiver is not active (receiverID={1}).**
Explanation	A processing rule indicated that the document should be delivered to a queue that is associated with a receiver. However, the receiver's profile is not active. Trading Networks can only route documents to active partners.
Action	Enable the partner by changing the profile status to active. Then enable the partner's private queue.

TNS.0005.3046E	**The queue "{0}" does not exist.**
Explanation	The wm.tn.queuing:deliverBatch service was supplied an invalid queue name.
Action	Supply the name of an existing queue.

TNS.0005.3048E	**The scheduled {0} is invalid. Format must be YYYY/MM/DD**
Explanation	In webMethods Trading Networks, while validating scheduling of tasks, if the format of the schedule date is invalid, this error is thrown.
Action	Enter the schedule date in the correct format and try again.

TNS.0005.3049E	**The scheduled {0} is invalid. Format must be hh:mm:ss**
Explanation	In webMethods Trading Networks, while validing the schedule task, if the format of the time is invalid, this error is thrown.
Action	Enter the schedule time in the correct format and try again.

TNS.0005.3056E	**Interval is required.**
Explanation	An interval must be specified for repeating tasks.
Action	Supply an interval value.

TNS.0005.3057E	**Interval is not a valid integer.**
Explanation	In webMethods Trading Networks, while validing a scheduling task, if the time interval is not a valid integer, this error is thrown.
Action	Enter the time interval as a valid integer and try again.

TNS.0005.3058E	**Interval must be greater than zero.**
Explanation	In webMethods Trading Networks, while validing a scheduling task, if the time interval is not greater than zero, this error is thrown.
Action	Enter the time interval as a valid integer greater than zero and try again.

TNS.0005.3059E	**End date/time is in the past.**
Explanation	In webMethods Trading Networks, while validing a scheduling task, if the end date/time is occuring in the past, this error is thrown.
Action	Enter a valid end date/time and try again.

TNS.0005.3060E	**End date/time is before start date/time.**
Explanation	In webMethods Trading Networks, while valiting a scheduling task, if the end date/time occurs before the start date/time, this error is thrown.
Action	Enter the valid end date/time and try again.

TNS.0005.3061E	**Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.**
Explanation	In webMethods Trading Networks, while validating the scheduling task, if the end date is not in YYYY/MM/DD format and the end time is not in hh:mm:ss format, this error is thrown.
Action	Ensure that the end date and time are in the correct format and try again.

TNS.0005.3062E	**A queue with this name already exists.**
Explanation	In webMethods Trading Networks, while registering a queue, if a queue with this name already exists, this error is thrown.
Action	Ensure to have a unique queue name and try again.

TNS.0005.3063E	**There is a task on the queue (task id={0}).**
Explanation	The queue cannot be removed because it has tasks on it.
Action	Place the queue in a DRAINING state so that the queue will empty. After the tasks in the queue have been processed, you can delete it.

TNS.0005.3064E	**The profile for {0} refers to the queue (partner id={1}).**
Explanation	The queue cannot be removed because one or more partner profiles refers to it.
Action	This message is followed by a list of partners whose profiles refer to the queue. Modify these profiles so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.

TNS.0005.3065E	**The {0} processing rule refers to the queue.**
Explanation	The queue cannot be removed because one or more processing rules refers to it.
Action	This message is followed by a list of processing rules that refer to the queue. Modify these processing rules so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.

TNS.0005.3066E	**If an end time is supplied, an end date must also be supplied.**
Explanation	In webMethods Trading Networks, while validating a scheduling task, if the delivery schedule is of complex type, and the end time is supplied but the end date is not supplied, this error is thrown.
Action	Ensure to also supply the end date along with the end time and try again.

TNS.0005.3067	**Unable to import partner private queue {0}. Partner profile for {1} does not exist.**
Explanation	In webMethods Trading Networks, while importing Trading Networks assets, if the partner profile for which a partner private queue is to be imported does not exist, this error is thrown.
Action	Ensure that the partner profile exists, and try again.

TNS.0005.4002E	**Processing recursion was detected: the processing rule {0} invoked itself, most recently with document {1}. Processing fails.**
Explanation	A processing rule recursed. Either no recursion is allowed, or recursion is allowed, and the maximum recursion level was exceeded.
Action	If you want a processing rule to recurse (to call itself), set the tn.recursion.max property to an appropriate value. If you do not want the processing rule to recurse, check the service that the processing rule invokes. The service is submitting a document that matches the same routing rule.

TNS.0005.4004E	**If alertPartner is not specified, neither alertContact, alertSubject nor alertMessage may be specified.**
Explanation	An invalid combination of input values was sent to wm.tn.route:create.
Action	If you are not supplying a value for alertPartner, do not supply a value for alertContact, alertSubject, or alertMessage.

TNS.0005.4008E	**Error sending mail: {0}**
Explanation	Encountered an exception while sending an email alert.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4011E	**An error occurred invoking the processing service ({2}) for this document. The original error was of type {0}; the message was {1} and the service output this pipeline: {3}**
Explanation	A processing rule invoked a service, and that service returned an error.
Action	Take appropriate action to resolve the problem described in the error message.

TNS.0005.4012E	**Error signaled in processing service**
Explanation	A processing rule invoked a service, and that service returned an error.
Action	See the full message (TRNSERV.000014.000012) for details.

TNS.0005.4013E	**An internal error prevented processing from finishing normally on this document. The aborted rule was {0}, and the original error message was {1}.**
Explanation	See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4014E	**Internal processing error**
Explanation	See the full message (TRNSERV.000014.000013) for details.
Action	See the full message for details.

TNS.0005.4017E	**{0} loading rules**
Explanation	Encountered an exception while reading processing rules from the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4023S	**{0} saving rules**
Explanation	Encountered an exception while saving processing rules to the database. Trading Networks wrote the exception to the server log.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4027E	**An exception occurred invoking a processing service for document {0}. The processing service was {1}, and the original error message was: {2}.**
Explanation	A processing rule invoked a service, and that service threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4028E	**An error occurred invoking the processing service {0} for this document. The original error was {1}.**
Explanation	A processing rule invoked a service, and that service threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4029E **Service invoke err: {0}**

Explanation A processing rule invoked a service, and that service threw an exception.

Action See the full message for details.

TNS.0005.4034E **Error sending via {0}**

Explanation Error encountered.

Action See the full message for details.

TNS.0005.4035E **Fatal processing error: {0}**

Explanation Encountered an exception while processing a document. See the exception for details.

Action Take appropriate action to resolve the problem described in the exception.

TNS.0005.4038W **Changing the user status on document {0} generated an error. The original error message was: {1}**

Explanation Encountered an exception while changing the status for a document. See the exception for details.

Action Take appropriate action to resolve the problem described in the exception.

TNS.0005.4039E **Error changing status**

Explanation Encountered an exception while changing the status for a document. See the exception for details.

Action Take appropriate action to resolve the problem described in the exception.

TNS.0005.4040E **An error occurred sending via protocol {0}. The original error message was: {1}**

Explanation Encountered an exception while sending a document. See the exception message for details.

Action Take appropriate action to resolve the problem described in the exception.

TNS.0005.4041E **Error delivering document**

Explanation Encountered an exception while sending a document.

Action Take appropriate action to resolve the problem described in the exception.

TNS.0005.4052E	**Processing Alert Failed**
Explanation	Encountered an error while sending an email alert.
Action	See full message for details.

TNS.0005.4053E	**The server was unable to send email to {0} during processing. The subject of the email was {1}. The error message was: {2}.**
Explanation	Encountered an error while sending an email alert.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4054E	**PROCESSING ERROR: partner contact {0}/{1} is not defined**
Explanation	Processing is configured to send alerts to a specific contact type, but the partner profile does not have a contact of that type.
Action	Either change the processing rule to send alerts to a different contact type (or use a hard-coded email address), or create a contact of this type for the partner.

TNS.0005.4055E	**Partner {1} sent this document posing as {0}.**
Explanation	When Trading Networks receives a document, it determines the partner initiating the request based on the user account that sent the document. The partner that sent the request does not match the sender from within the document content.
Action	You might want to notify the partner who sent the document and/or the partner being impersonated.

TNS.0005.4056E	**Partner {1} sent document {2} posing as {0}.**
Explanation	When Trading Networks receives a document, it determines the partner initiating the request based on the user account that sent the document. The partner that sent the request does not match the sender from within the document content.
Action	You might want to notify the partner who sent the document and/or the partner being impersonated.

TNS.0005.4057E	**Partner ID mismatch**
Explanation	The partner who sent the document does not match the partner in the document content.
Action	See full message for details.

TNS.0005.4058E **The sender of this document ({0}) has been deleted. Documents from this partner are not permitted at this time.**

Explanation Trading Networks received a document from a partner whose profile was deleted. Although Trading Networks still maintains a copy of the deleted profile in its database, it will not accept documents nor process documents from the partner.

Action If you do not want to accept documents from the partner, you can either ignore this error or notify the partner to stop sending documents. If you want to receive and process documents from this partner, use the wm.tn.profile:undeleteProfile service to reinstate the partner's profile.

TNS.0005.4059E **The sender of document {2} ({0}) had been deleted. Documents from this partner are not permitted at this time.**

Explanation Trading Networks received a document from a partner whose profile was deleted. Although Trading Networks still maintains a copy of the deleted profile in its database, it will not accept documents nor process documents from the partner.

Action If you do not want to accept documents from the partner, you can either ignore this error or notify the partner to stop sending documents. If you want to receive and process documents from this partner, use the wm.tn.profile:undeleteProfile service to reinstate the partner's profile.

TNS.0005.4060E **Partner deleted**

Explanation Received a document from a partner whose profile was deleted.

Action See full message for details.

TNS.0005.4067E **An attempt was made to send email to the {0} contact of the Unknown partner. No email was sent.**

Explanation The processing rule is configured to send an alert to a partner's contact, but Trading Networks could not identify the partner.

Action Examine the document content and the Sender/Receiver queries on the document type to determine why Trading Networks could not identify the partner.

TNS.0005.4068E **Can''t send to UNKNOWN**

Explanation The processing rule is configured to send an alert to a partner, but Trading Networks could not identify the partner.

Action Examine the document content and the Sender/Receiver queries on the document type to determine why Trading Networks could not identify the partner.

TNS.0005.4070E	**Processing aborted**
Explanation	Threw a RoutingAbortedException while processing the document.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4071E	**The processing service, {0} aborted processing of this document. The message was {1}.**
Explanation	Threw a RoutingAbortedException while processing the document.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4074E	**The user that posted this document ({0}) could not be associated with a partner to check their identity.**
Explanation	Received a document from someone other than a trading partner.
Action	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.

TNS.0005.4075E	**The user that posted document {1} ({0}) could not be associated with a partner to check their identity.**
Explanation	Received a document from someone other than a trading partner.
Action	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.

TNS.0005.4076E	**No user ID**
Explanation	Received a document from someone other than a trading partner.
Action	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.

TNS.0005.4078E	**No email address**
Explanation	Could not determine the address to send an email alert.
Action	Examine the processing rule and the receiver's profile. You must specify an address either in the processing rule or the receiver's profile.

TNS.0005.4079E	**No email address was available for sending to {0} ({1}). No email was sent.**
Explanation	Could not determine the address to send an email alert.
Action	Examine the processing rule and the receiver's profile. You must specify an address either in the processing rule or the receiver's profile.

TNS.0005.4086E	**No SMTP server defined: check property watt.server.smtpServer**
Explanation	The processing rule is configured to send an email alert, but no email server is defined.
Action	Set the SMTP Server on the Settings > Logging page of the Integration Server Administrator, or directly set the watt.server.smtpServer property.

TNS.0005.4087E	**Cannot specify a Sender of {0} and also supply a specific senderId''s.**
Explanation	When invoking wm.tn.route:create, you cannot specify that the processing rule matches 'Any' sender or the 'Unknown' sender, and also supply specific senderIDs.
Action	Either remove "Any", "Unknown", or the specific senderIDs.

TNS.0005.4089E	**Cannot specify a DocType of {0} and also supply specific docTypeId''s.**
Explanation	When invoking wm.tn.route:create, you cannot specify that the processing rule matches 'Any' document type or the document type is 'Unknown', and also supply specific document type IDs.
Action	Either remove "Any", "Unknown", or the specific document type IDs.

TNS.0005.4090E	**An exception prevented the sender''s identity from being completely checked. The original exception was {0}.**
Explanation	Threw a ProfileStoreException while checking the identity of the document sender.
Action	Contact Software AG Global Support.

TNS.0005.4094E	**The sender of this document ({0}/{1}) is in status {2}. Documents from this partner are not permitted at this time.**
Explanation	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
Action	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.

TNS.0005.4095E	**The sender of document {3} ({0}/{1}) is in status {2}. Documents from this partner are not permitted at this time.**
Explanation	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
Action	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.

TNS.0005.4096E	**Bad status**
Explanation	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
Action	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.

TNS.0005.4097E	**An error occurred trying to send this document via {0} (intended receiver: {1}). The original error message was: {2}.**
Explanation	Encountered an exception while sending a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4098E	**An error occurred trying to send this document via {0} (sender: {1}). The original error message was: {2}.**
Explanation	Encountered an exception while sending a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4099E	**Couldn''t send doc {0} via {1}: {2}**
Explanation	Encountered an exception while sending a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4100E	**An error occurred trying to fetch profile information for sending email to the {1} contact of partner {0}. The original error was: {2}**
Explanation	Unable to retrieve the partner profile while sending an email alert. See the exception message for details.
Action	Contact Software AG Global Support.

TNS.0005.4101E	**Profile error**
Explanation	Unable to retrieve the partner profile while sending an email alert. See the exception message for details.
Action	Contact Software AG Global Support.

TNS.0005.4102E	**Processing aborted: {0}**
Explanation	Threw a RoutingAbortedException while processing the document.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4104E	**{0} is not a known document attribute.**
Explanation	The wm.tn.route:create service was supplied an invalid attribute name.
Action	Supply only names of existing document attributes.

TNS.0005.4107E	**No preferred protocol. Status changed to POLLABLE.**
Explanation	The processing rule was configured to send the document using the receiver's preferred protocol, but the receiver does not have a preferred protocol.
Action	Signify one of the receiver's delivery methods as the preferred protocol.

TNS.0005.4111E	**No profile summary was available for the sender of this document**
Explanation	Could not process the document because Trading Networks could not find a partner profile for the sender.
Action	Modify either the sender identification in the document or the external ID in the profile.

TNS.0005.4112E	**No profile summary was available for the sender of document {2}. The sender ID was {0}, and the sender logged in as {1}.**
Explanation	Could not process the document because Trading Networks could not find a partner profile for the sender.
Action	Modify either the sender identification in the document or the external ID in the profile.

TNS.0005.4113E	**No profile summary available**
Explanation	Could not process the document because Trading Networks could not find a partner profile for the sender.
Action	Modify either the sender identification in the document or the external ID in the profile.

TNS.0005.4114E	**A supplied attribute condition has an invalid combination of datatype, operator and value ({0} {1} {2}).**
Explanation	The wm.tn.route:create service was supplied an invalid attribute condition.
Action	Correct the attribute condition.

TNS.0005.4115E	**An invalid value was supplied for the tn.recursion.max property. No recursion of processing rules will be allowed.**
Explanation	The value of the tn.recursion.max property is not a valid number.
Action	Supply a valid number for this property.

TNS.0005.4116E	**Processing recursion exceeded the allowed recursion depth of {0}. The processing rule {1} invoked itself, most recently with document {2}. Processing fails.**
Explanation	One or more processing rules invoked services that resubmitted documents to Trading Networks, exceeding the recursion limit defined by the tn.recursion.max property.
Action	Increase the value of the tn.recursion.max property, or configure your processing rules not to resubmit documents.

TNS.0005.4117E	**Couldn''t load routing schedule: {0}**
Explanation	Encountered an exception while reading the set of processing rules from the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4118E	**Couldn''t save routing schedule: {0}**
Explanation	Encountered an exception while saving the set of processing rules to the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4119E	**Cannot specify a Receiver of Any and also supply a specific receiverId''s.**
Explanation	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches 'Any' receiver and also supply specific receivers.
Action	Remove either "Any" or the specific receivers.

TNS.0005.4120E	**Cannot specify a Receiver of Unknown and also supply a specific receiverId's.**
Explanation	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches an 'Unknown' receiver and also supply specific receivers.
Action	Remove either "Unknown" or the specific receivers.

TNS.0005.4121E	**Cannot specify a DocType of Any and also supply specific docTypeIds.**
Explanation	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches 'Any' TN document type and also supply specific TN document types.
Action	Remove either "Any" or the specific TN document types.

TNS.0005.4122E	**Cannot specify a DocType of Unknown and also supply specific docTypeIds.**
Explanation	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches the 'Unknown' TN document type and also supply specific TN document types.
Action	Remove either "Unknown" or the specific TN document types.

TNS.0005.4123E	**If deliverUsing is "Queue for delivery", then deliveryQueue cannot be null**
Explanation	An invalid combination of input values was sent to the wm.tn.route:create service.
Action	Supply a value for the "deliveryQueue" variable.

TNS.0005.4125E	**Cannot queue a bizdoc for deliver that has not been persisted. This bizdoc (id={0}) has not been persisted.**
Explanation	The scheduled delivery mechanism requires that the document be saved to the database.
Action	Change the TN document type or processing rule to save documents of this type.

TNS.0005.4130E	**qname is required**
Explanation	Attempted to enqueue a delivery job without supplying a queue name for the "qname" parameter.
Action	Supply a valid queue name for the "qname" parameter.

TNS.0005.4131E	**Invalid queue name ({0}).**
Explanation	Attempted to enqueue a delivery job without supplying a queue name for the "qname" parameter.
Action	Supply a valid queue name for the "qname" parameter.

TNS.0005.4132E	**Receiver does not have a delivery queue.**
Explanation	The processing rule is configured to send the document to the receiver's private delivery queue, but the receiver does not have a delivery queue.
Action	Change the processing rule to deliver the document by a different means, or create a delivery queue for the receiver.

TNS.0005.4133E	**Receiver does not have a delivery queue. Document has been made POLLABLE (document id={0})**
Explanation	The processing rule is configured to send the document to the receiver's private delivery queue, but the receiver's profile does not contain a definition for a delivery queue.
Action	Change the processing rule to deliver the document by a different means, or update the receiver's profile to specify a delivery queue.

TNS.0005.4134E	**Receiver does not have a preferred protocol. Document has been made POLLABLE. (document id={0})**
Explanation	The processing rule is configured to send the document by the receiver's preferred delivery method, but the receiver does not have a preferred delivery method.
Action	Change the processing rule to deliver the document by a different means, or signify one of the delivery methods on the receiver's profile as "preferred".

TNS.0005.4135E	**Error encountered in RoutingActions.invoke(): can not clone input pipeline.**
Explanation	An internal error occurred while invoking a service to process the document.
Action	Contact Software AG Global Support.

TNS.0005.4136E	**Unable to save document: {0}.**
Explanation	Encountered an exception while saving the document to the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4138E	**The processing rule list has been modified by another user. Added this rule to the bottom of the list. Refresh your rule list.**
Explanation	The rule list displayed on your Trading Networks Console is not the current list that resides in the database. As a result, the newly added rule is appended to the end of the rule list rather than the specific position required in the list.
Action	Refresh your routing rule list and move the newly added rule to the desired position.

TNS.0005.4139S	**Error encountered while inserting processing rule {0}. The exception message is : {1}.**
Explanation	Encountered an exception while inserting a processing rule.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4140E	**Error encountered while updating processing rule {0}. The rule index cannot be changed during an update operation.**
Explanation	You attempted to update both the contents of a processing rule and its location within the list of processing rules (its index) at the same time. You cannot make both these changes at the same time.
Action	Please update the rule first, and then move the rule to a new position in the rule list.

TNS.0005.4141E	**Error encountered while updating processing rule {0}. The exception message is : {1}.**
Explanation	Encountered an exception while updating a processing rule.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4142E	**Processing rule update failed. Processing rule update collision detected. This rule has been modified by another user. Refresh your rule list and retry this operation.**
Explanation	While you were updating this processing rule, another user edited and saved the same processing rule. To prevent your changes from overwriting those made by the other user, Trading Networks did not save your changes.
Action	Refresh the list of processing rules and update the processing rule again.

TNS.0005.4145S	**Error encountered while deleting processing rule(s). The exception message is : {0}.**
Explanation	Encountered an exception while deleting processing rule(s).
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4146E	**Processing rule delete operation aborted. The processing rule list has been modified by another user. Refresh your rule list and retry this operation.**
Explanation	While you were deleting this processing rule, another user edited and saved the rule. So that your changes do not overwrite those made by the other user, your changes have not been saved.
Action	Refresh your rule list, and then delete the rule again.

TNS.0005.4147E	**Processing rule {0} does not exist.**
Explanation	The specified routing rule cannot be retrieved because the rule ID does not exist in the database.
Action	Check that the rule ID is correct, modify it if necessary, and then attempt to retrieve it again.

TNS.0005.4148S	**Error encountered while reading processing rules from the database. The exception message is : {0}.**
Explanation	Encountered an exception while retrieving processing rules from the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4149S	**Error encountered while moving processing rules. The exception message is : {0}.**
Explanation	Encountered an exception while moving processing rules in the rule list.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4150E	**Processing rule move operation aborted. The processing rule list has been modified by another user. Refresh your rule list and retry this operation.**
Explanation	While you were moving this processing rule, another user edited and saved the rule list. So that your changes do not overwrite those made by the other user, your changes have not been saved.
Action	Refresh the rule list, and then move the rule again.

TNS.0005.4151E	**Illegal move operation. The insertAt position cannot be within the range of rules to be moved.**
Explanation	The insertAt position must be outside the range of rules to be moved.
Action	Change the insertAt position to be outside of the range of rules to be moved.

TNS.0005.4152E	**Illegal move operation. You cannot move a non-contiguous set of rules.**
Explanation	You attempted to change the order of processing rules by moving a non-contiguous set of rules. Trading Networks does not support this type of operation.
Action	Define a contiguous set of rules to be moved.

TNS.0005.4156E	**Encountered an error retrieving the Profile Summary for partner ID {0}.**
Explanation	An error occurred attempting to look up the Profile Summary.
Action	Ensure that the partner IDs on the document being processed are valid.

TNS.0005.4157E **Encountered an error while sending MAPI event to Optimize for EventMap {0} and for Sender with PartnerID {1}.**

Explanation In webMethods Trading Networks, while routing a document, if a TN BAM monitoring event cannot be logged in Optimize, this error is thrown.

Action Contact your system administrator.

TNS.0005.4160E **The content-length ({0}) specified in handleLargeDoc is less than the length of the content ({1}) sent.**

Explanation In webMethods Trading Networks, in a document transaction, while handling large documents, if the content length specified in the handleLargeDoc is less than the length of the BizDoc content, this error is thrown.

Action Ensure that the content length specified in the handleLargeDoc is equal to the length of the BizDoc content and try again.

TNS.0005.4162E **Routing Aborted as the Receiver is disabled.**

Explanation In webMethods Trading Networks, while routing a document, if the receiver is in an inactive state, this error is thrown.

Action Ensure to set the receiver to active state and try again.

TNS.0005.4163E **Routing Aborted as the Receiver is deleted.**

Explanation In webMethods Trading Networks, while routing a document, if the receiver is in deleted state, this error is thrown.

Action Ensure to set the receiver profile is not deleted and try again.

TNS.0005.4164E **Routing Aborted as the Sender is disabled.**

Explanation In webMethods Trading Networks, while routing a document, if the sender is in inactive state, this error is thrown.

Action Ensure to set the sender to active state and try again.

TNS.0005.4165E **Routing Aborted as the Sender is deleted.**

Explanation In webMethods Trading Networks, while routing a document, if the sender is deleted, this error is thrown.

Action Ensure to set the sender profile is not deleted and try again.

TNS.0005.4166E	**The processing service aborted processing of this document. The message was {0}.**
Explanation	In webMethods Trading Networks, while routing a document, if an error occurs in processing the document, this error is thrown.
Action	Contact your system administrator.

TNS.0005.4167E	**Posting of BAM events failed because of following errors - {0}.**
Explanation	In webMethods Trading Networks, if any error occurs while posting BAM events, this error is thrown.
Action	Contact your system administrator.

TNS.0005.5002E	**Delivery service for {0} failed with a status of {1} and status message of {2}**
Explanation	Unable to deliver the document, possibly due to a problem with the network or the destination server.
Action	Verify that your server has network connectivity. If a problem exists with the destination server, contact the person responsible for that server.

TNS.0005.5004E	**Unable to get output for task {0} - Task has not finished. Status is {1}**
Explanation	The task was still executing when the request for output expired.
Action	Request the output again.

TNS.0005.5005E	**Unable to refresh {0} cache on server {1} - {2}**
Explanation	A cache could not be refreshed, probably due to a database problem.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.

TNS.0005.5007E	**Unable to remove task {0} - Does not exist**
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.

TNS.0005.5011S	**Disabling reliable task manager at {0} - Fatal error: {1}**
Explanation	Encountered an exception that requires the task manager to shut down.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.5013W	**Unable to restart task {0} upon initialization**
Explanation	The task status could not be updated to "Pending" in the database.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.

TNS.0005.5015E	**Unable to persist task {0}**
Explanation	Encountered an exception while saving the task to the database.
Action	See the full message (TRNSERV.000015.000089) for details.

TNS.0005.5019E	**Task {0} unable to move to server {1} - {2}**
Explanation	Task has already completed. Status is "Done".
Action	No action required.

TNS.0005.5020E	**Unable to refresh {0} cache - {1}**
Explanation	See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.5025E	**Task {0} failed, status changed to {1}**
Explanation	The task has failed. No more retries.
Action	See full message (TRNSERV.000015.000036) for details.

TNS.0005.5026E	**Unable to init task manager for server {0} - {1}**
Explanation	The task manager could not be initialized, probably due to a database problem.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.

TNS.0005.5031E	**Error invoking service {0} - message: {1} - stacktrace: {2}**
Explanation	The task manager invoked a service to process a document, and that service threw an exception.
Action	See the exception message for details. Correct the invoked service to handle the exception condition.

TNS.0005.5036E	**Task {0} failed with no more retries available. Reason for failure - {1}**
Explanation	See the status message for details.
Action	If the failure is due to an error on another server, contact the person responsible for that server.

TNS.0005.5037E	**Unable to restart task {0} - {1}**
Explanation	The task status is neither "Failed" nor "Stopped", so the task cannot be restarted.
Action	No action necessary.

TNS.0005.5039E	**Unable to shut down the task manager.**
Explanation	The wm.tn.task:shutdown service was unable to stop the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5042E	**Unable to initialize task manager.**
Explanation	The wm.tn.task:init service was unable to start the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5043E	**Unable to reset task manager.**
Explanation	The wm.tn.task:restart service was unable to restart the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5044E	**Unable to retrieve tasks.**
Explanation	The wm.tn.task:getTasks service was unable to get tasks from the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5045E	**Unable to retrieve task {0}.**
Explanation	The wm.tn.task:getTask service was unable to get a task from the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5046E	**Unable to get output for task {0}.**
Explanation	The wm.tn.task:getTaskOutput service was unable to get output for a task. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5047E	**Unable to get status for task {0}.**
Explanation	The wm.tn.task:getTaskStatus service was unable to get the status of a task. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5048E	**Unable to change server for task {0}.**
Explanation	The wm.tn.task:changeServerForTask service was unable to move a task from one server to another. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5049E	**Unable to remove task {0}.**
Explanation	The wm.tn.task:removeTask service was unable to remove a task from the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5050E	**Unable to restart task {0}.**
Explanation	The wm.tn.task:restartTask service was unable to restart a task in the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5051E	**Unable to stop task {0}.**
Explanation	The wm.tn.task:stopTask service was unable to stop a task in the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5052E	**Unable to move task {0} to server {1}. Task does not exist.**
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.

TNS.0005.5053E	**Unable to move task {0} to server {1}. Task has completed.**
Explanation	Task status is "Done". Cannot move a completed task.
Action	No action necessary.

TNS.0005.5054E	**Unable to move task {0} to server {1}. Could not "ping" server: {2}**
Explanation	Invoked the wm.server:ping service on the other server, and it threw an exception.
Action	Take appropriate action to resolve the problem on the other server as described in the exception.

TNS.0005.5055E	**Unable to move task {0} to server {1}. Server {2} is up, but the task has not failed.**
Explanation	The server that created this task is running. Therefore, the task cannot be moved because the task status is neither "Failed" nor "Stopped".
Action	No action necessary.

TNS.0005.5056E	**Unable to move task {0} to server {1}. Server {2} is down, but the task is done.**
Explanation	Task status is "Done". Cannot move a completed task.
Action	No action necessary.

TNS.0005.5057E	**Unable to stop task {0}. Job has completed.**
Explanation	Cannot stop a completed task.
Action	No action necessary.

TNS.0005.5058E	**Unable to stop task {0}. Job does not exist.**
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.

TNS.0005.5060E	**Delivery Job Manager error: task {0} is not NEW.**
Explanation	Cannot start a task that does not have a "New" status.
Action	No action necessary. Task has already started.

TNS.0005.5061E	**Delivery Job Manager error with task {0}. {1}**
Explanation	Encountered an exception while writing to the database. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.5062E	**Task {0} unable to restart. Does not exist.**
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.

TNS.0005.5064E	**Unable to remove task {0}. {1}**
Explanation	Encountered an exception while writing to the database. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.5065E	**Cannot get job output. Job does not exist.**
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.

TNS.0005.5066E	**Unable to initialize task manager. ServerId is null.**
Explanation	Unable to determine server ID.
Action	Supply a value for the watt.net.localhost property in the server.cnf file on the Integration Server.

TNS.0005.5068E	**Unable to delete tasks. There are {0} active jobs in the list of jobs to be deleted. Stop the active jobs and retry**
Explanation	Cannot delete active tasks.
Action	If you want to delete tasks that are active, stop them first.

TNS.0005.5069E	**Unable to get task**
Explanation	The wm.tn.route:getTask service can only retrieve tasks that are service execution tasks. A taskID of a delivery task was supplied.
Action	Request only service execution tasks from the wm.tn.route:getTask service.

TNS.0005.5070E	**Error getting task**
Explanation	The wm.tn.route:getTask service encountered an exception while retrieving a task. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5072E	**Unable to restart queued task (id={0}). Its delivery queue no longer exists. You can resubmit the document to process it again.**
Explanation	The delivery queue for this document has been deleted. Cannot be requeued.
Action	Verify that the processing rule that handles this document is configured to use a valid delivery queue. Resubmit the document.

TNS.0005.5081E	**Error invoking service, {0} - Service did not return valid output**
Explanation	The task manager invoked a service to process a document. The output of the service did not conform to the expected format.
Action	If this is a delivery service, make sure the output matches the wm.tn.rec:DeliveryServiceOutput IS document type. If this is a service invoked by a service execution task, make sure the output matches the wm.tn.rec:reliableServiceOutput IS document type.

TNS.0005.5082E	**ERROR: Unable to update task {0} due to database error : {1}. Since task update retry is turned off, manual correction is required. Please correct the database errors and manually update the task using the additional task details provided. Additional Details of this task : Task ID={2}; DocID={3}; TaskStatus={4}; Retries={5}; TransportStatus={6}; TransportStatusMessage={7}; TransportTime={8}**
Explanation	Could not update the task. See exception message for details.
Action	Manually update the task in My webMethods using the details provided in the message.

TNS.0005.5089E	**ERROR: Unable to update task {0} due to IOException : {1}. Task update will continue to fail until this exception is rectified. Until this error is rectified, manual correction is required. Manually update the task using the additional task details provided. Additional Details of this task : Task ID={2}; DocID={3}; TaskStatus={4}; Retries={5}; TransportStatus={6}; TransportStatusMessage={7}; TransportTime={8}**
Explanation	Could not update the task. See exception message for details.
Action	Manually update the task in My webMethods using the details provided in the message.

TNS.0005.5091S	**TN Job Manager sweep time property tn.task.sweepTime contains ({0}), which is not a numeric value. Using the default value 300 seconds**
Explanation	The tn.task.sweepTime property contains an invalid value.
Action	Supply a valid numeric value.

TNS.0005.5094E	**Task {0} failed at {1}: Probable reason for failure - {2}. {3} more retries left.**
Explanation	In webMethods Trading Networks, if any error occurs while disabling the delivery for a partner, this error is thrown.
Action	Contact your system administrator.

TNS.0006.1001E	**Cannot setIData for CertificateData because the supplied data is null.**
Explanation	The setIData method on a CertificateData object passed a null IData object.
Action	If your code is calling CertificateData.setIData, supply an IData object that is not null. If it is not your code that is calling this method, contact Software AG Global Support. .

TNS.0006.1002E	**Cannot setIData for CertificateData.**
Explanation	The setIData method on a CertificateData object was not successful.
Action	If Integration Server logging is set to logging level 4 or higher, the exception was written to the server log. See the server log for more information. Take the appropriate action to resolve the problem described in the exception.

TNS.0006.1003S	**Certificate provider Entrust/IAIK was not found, so Trading Networks cannot convert byte[] to java.security.cert.X509Certificate. Please ensure that entrust jar files are in the Integration Server''s classpath.**
Explanation	The Entrust jar files are missing from the Integration Server's classpath.
Action	Place the Entrust jar files in the Integration Server's classpath. If you need assistance, contact Software AG Global support.

TNS.0006.1004E	**CertificateException encountered; Trading Networks cannot convert byte[] to java.security.cert.X509Certificat.**
Explanation	Trading Networks encountered a certificateException when attempting to convert a byte array to a java.security.cert.X509Certificat.
Action	If Integration Server logging is configured at logging level 4 or higher, the exception was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.

TNS.0006.1005E	**Cannot convert byte[][] to X509Certificate[], exception encountered at index {0}.**
Explanation	Trading Networks could not create a certificate chain from the bytes. Trading Networks encountered the error at <zeroBasedIndexNum> certificate.
Action	Check the byte array to ensure that it is in the correct format.

TNS.0006.1006E	**Cannot convert byte[] to java.security.PrivateKey.**
Explanation	Trading Networks could not create a private key object from bytes.
Action	Check the byte array to ensure that it is in the correct format.

TNS.0006.1007E	**Cannot convert X509Certificate[] to byte[][], CertificateEncodingException encountered at index {0}. Please verify that the certificate is valid.**
Explanation	The certificate chain is not valid.
Action	Provide a valid certificate chain.

TNS.0006.1008E	**Cannot convert PKCS7 formatted byte[] into .der formatted byte[][].**
Explanation	The PKCS7-formatted bytes are not valid.
Action	Check the byte array to ensure that it is in the correct format. Provide a valid byte array.

TNS.0006.1009E	**Cannot load certificate from null File. Please supply a valid File.**
Explanation	The supplied certificate file is null.
Action	Supply a certificate file that is not null.

TNS.0006.1010S	**Certificate provider Entrust/IAIK not found, so Trading Networks cannot load java.security.cert.X509Certificate from file <filename>. Ensure that entrust jar files are in the Integration Server''s classpath.**
Explanation	The Entrust jar files are missing from the Integration Server's classpath.
Action	Place the Entrust jar files in the Integration Server's classpath. If you need assistance, contact Software AG Global Support.

TNS.0006.1011E	**CertificateException encountered getting certificate from file {0}.**
Explanation	An error occurred while attempting to load certificates from the specified file.
Action	Check the certificate file to ensure that it is in the correct format.

TNS.0006.1012E	**Cannot load private key from null File.**
Explanation	Trading Networks attempted to load the private key from a file; however, the file is null.
Action	Supply a private key file that is not null.

TNS.0006.1013E	**IOException encountered loading RSA private key from file {0}.**
Explanation	An error occurred while the server attempted to load a private key from the specified file.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.

TNS.0006.1014E	**InvalidKeyException encountered loading RSA private key from file {0}.**
Explanation	An error occurred while the server attempted to load a private key from the specified file.
Action	Check the private key file to ensure that it is in the correct format.

TNS.0006.1015E	**Cannot determine whether the certificate is self-signed because the certificate byte[] is null.**
Explanation	The supplied certificate byte array is null.
Action	Supply a non-null certificate byte array.

TNS.0006.1016E	**Cannot determine whether the certificate is self-signed because both the subject and issuer are null.**
Explanation	The supplied certificate is not in a valid format. Both the subject and issuer are null.
Action	Supply a valid certificate.

TNS.0006.1017E	**Cannot determine whether the certificate is self-signed because the certificate is null.**
Explanation	The supplied certificate is null.
Action	Supply a non-null certificate.

TNS.0006.1018E	**Integration Server''s certificate file {0} not found.**
Explanation	Trading Networks could not find the specified file that contains the Integration Server's client certificate.
Action	Specify a file that contains a client certificate for the Integration Server.

TNS.0006.1019E	**Integration Server''s CA certificate file {0} not found.**
Explanation	Trading Networks could not find the specified file that contains the Integration Server's CA certificate.
Action	Specify a file that contains the Integration Server's CA certificate.

TNS.0006.1020E	**IOException encountered when retrieving the Integration Server''s private key from {0}.**
Explanation	IOException thrown when Trading Networks was attempting to retrieve the Integration Server's private key from the specified file.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.

TNS.0006.1021E	**InvalidKeyException encountered when retrieving the Integration Server''s private key from {0}.**
Explanation	An error occurred when Trading Networks was attempting to retrieve the Integration Server's private key from the specified file.
Action	Specify a file that contains a valid private key for the Integration Server.

TNS.0006.1022E	**Certificate chain bytes cannot be null or zero length.**
Explanation	The certificate chainBytes parameter is either null or has a length of zero.
Action	Supply a valid certificate chain.

TNS.0006.1023E	**Certificate chain contains a single certificate, and that certificate is not self-signed.**
Explanation	The certificate chain is not valid. The certificate chain contains only one certificate, and that certificate is not self-signed. When you are not using a self-signed certificate, a certificate chain must include a certificate and its corresponding CA certificate(s).
Action	Supply a valid certificate chain. That is a single self-signed certificate or a certificate and its corresponding CA certificates.

TNS.0006.1024E	**Entrust cannot verify the certificate chain: {0}**
Explanation	Entrust could not verify the certificate chain.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem.

TNS.0006.1027E	**Cannot determine whether to trust the sign/verify certificate because there is no Enterprise profile.**
Explanation	Trading Networks cannot determine whether to trust the sign/verify certificate because there is no Enterprise profile.
Action	Create an Enterprise profile. For information about creating profiles, see the Trading Networks documentation.

TNS.0006.1028E	**Cannot set sign/verify certificate for receiver, Enterprise, because a CertificateException was encountered when determining whether the Integration Server trusts the certificate chain.**
Explanation	Before setting the sign/verify certificates that are specified in the Enterprise profile, Trading Networks ensures that the Integration Server trusts the certificates. A CertificateException was thrown when determining whether the Integration Server trusts the certificates.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem.

TNS.0006.1029W	**Cannot set sign/verify certificate for receiver, Enterprise, because the Integration Server is not set up to trust the certificate specified in the Enterprise profile.**
Explanation	Before setting the sign/verify certificate that is specified in the Enterprise profile, Trading Networks ensures that the Integration Server trusts the certificate. The certificate supplied in the Enterprise profile is not among the certificates that the Integration Server trusts.
Action	Add this certificate to the Integration Server's directory of trusted certificates.

TNS.0006.1031E	**SQLException encountered when setting certificate data for partner {0}; error message is {1}.**
Explanation	An error occurred when Trading Networks attempted to set the certificate data for the partner with the specified partner ID.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0006.1032E	**SQLException encountered when retrieving certificate data for partner {0}; error message is {1}.**
Explanation	An error occurred when Trading Networks attempted to retrieve the certificate data for the partner with the specified partner ID.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.

TNS.0006.1035E	**Cannot setIData() for CertData: CertData is null.**
Explanation	The setIData method on a CertData object passed a null IData object.
Action	If your code is calling CertData.setIData, supply a non-null IData object. If it is not your code that is calling this method, contact Software AG Global Support.

TNS.0006.1036E	**EXMLException encountered in CertData.setIData().**
Explanation	com.wm.app.tn.err.EXMLException was thrown in the setIData() method.
Action	If your code is calling CertData.setIData, check the server log for a stack trace. Take the appropriate action to resolve the problem described in the exception. If it is not your code that is calling this method, contact Software AG Global Support.

TNS.0006.1037E	**Cannot get expiration date for node certificate.**
Explanation	The certificate does not have expiration date information.
Action	Ensure that the certificate is in a valid format.

TNS.0006.1038E	**Cannot convert byte array to java.lang.PrivateKey.**
Explanation	Trading Networks could not convert the byte array because it is corrupted.
Action	Ensure that the byte array in the private key file is in a valid format.

TNS.0006.1039E	**Cannot set illegal usage {0} for CertData.**
Explanation	The CertData object contains a certificate usage parameter that is not legal.
Action	Ensure the certificate usage parameter in the CertData object has one of the following values: "sign", "decrypt", or "ssl".

TNS.0006.1040E	**Cannot insert CertData into database, CertData is null.**
Explanation	The CertData object is null.
Action	Supply a non-null CertData object.

TNS.0006.1041E	**Cannot insert CertData into database because data already exists for supplied owner={0}, partner={1} and usage={2}.**
Explanation	You attempted to add certificate information for the specified owner/partner/usage combination. However, there is already certificate information for this owner/partner/usage combination in the Trading Networks database.
Action	If you want to update the certificate information for the specified owner/partner/usage combination, use the update operation instead of insert operation. Otherwise, specify a unique owner/partner/usage combination that does not already exist in the Trading Networks database.

TNS.0006.1042E	**Error inserting CertData into the database; update row count is not 1.**
Explanation	Trading Networks encountered a database error when performing the insert operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1043E	**Error inserting CertData into the database; IOException encountered encoding data into binary format.**
Explanation	Trading Networks encountered an error when performing the insert operation; an IOException was thrown when encoding data into binary format.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1044E	**Error inserting CertData into the database; SQLException encountered with the error message {0}.**
Explanation	An SQLException occurred while Trading Networks was attempting to perform a database insert operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1045E	**Cannot update CertData because the supplied CertData object is null.**
Explanation	Trading Networks was attempting to perform a database update operation to update certificate information. However, the supplied CertData object that Trading Networks is to use to update the existing certificate information is null. As a result, Trading Networks cannot perform the database update operation.
Action	Supply a non-null CertData object.

TNS.0006.1046E	**Cannot update CertData because the supplied CertID is null.**
Explanation	Trading Networks is not able to update the certificate information because the supplied unique identifier, CertID, is null.
Action	Supply a non-null CertID.

TNS.0006.1047E	**Cannot update CertData because the specified CertID, {0} does not match the CertID that Trading Networks has for the supplied owner/partner/usage.**
Explanation	You attempted to update certificate information for the specified owner/partner/usage combination. However, the supplied CertID does not match CertID that Trading Networks has for this owner/partner/usage combination.
Action	Retrieve the correct CertID for the owner/partner/usage combination from database, and issue the request again. This time specify the correct CertID for the owner/partner/usage combination.

TNS.0006.1048E	**Error updating CertData; the update count from the update operation is not 1.**
Explanation	Trading Networks encountered a database error when performing the update operation.
Action	If the Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1049E	**Error updating CertData in the database; IOException encountered encoding data into binary format.**
Explanation	Trading Networks encountered an error when performing the update operation; an IOException was thrown when encoding data into binary format.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1050E	**Error updating CertData in the database; SQLException encountered with the error message {0}.**
Explanation	An SQLException occurred when Trading Networks was attempting to perform a database update operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1051E	**Cannot delete CertData because the supplied CertID is null.**
Explanation	Trading Networks is not able to delete the certificate information because the supplied unique identifier, CertID, is null.
Action	Supply a non-null CertID.

TNS.0006.1052E	**Error deleting CertData; the delete count from the delete operation is not 1.**
Explanation	Trading Networks encountered a database error when performing the delete operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1053E	**Error deleting CertData from the database; SQLException encountered with the error message {0}.**
Explanation	An SQLException was thrown when Trading Networks was attempting to perform a database delete operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1054E	**Cannot construct new CertData from SecurityOps.getCertificateData().**
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0006.1055E	**Error selecting CertData for ownerId={0}, partnerId={1}, usage={2}; IOException encountered decoding bytes to IData.**
Explanation	When Trading Networks was attempting to select CertData for the owner/partner/usage combination, an IOException was thrown when decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1056E	**Error selecting CertData for ownerId={0}, partnerId={1}, usage={2}; SQLException encountered with the error message {3}.**
Explanation	An SQLException occurred while Trading Networks was attempting select CertData for the owner/partner/usage combination.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1057E	**Cannot construct new CertData from SecurityOps.getCertificateDataByCertID().**
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0006.1058E	**Error selecting CertData for CertId=<certID>; IOException encountered decoding bytes to IData.**
Explanation	When Trading Networks was attempting to select CertData with the specified CertID, an IOException was thrown when decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1059E	**Error selecting CertData for CertId={0}; SQLException encountered with the error message {1}.**
Explanation	An SQLException occurred while Trading Networks was attempting select CertData with the specified CertID.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1060E	**Cannot construct new CertData from SecurityOps.getCertificateDataForOwner().**
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0006.1061E	**Error selecting CertData for ownerId={0}; IOException encountered decoding bytes to IData.**
Explanation	When Trading Networks was attempting to select CertData for the specified owner, an IOException was thrown while decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1062E	**Error selecting CertData for ownerId={0}; SQLException encountered with the error message {1}.**
Explanation	An SQLException occurred while Trading Networks was attempting to select CertData for the specified owner.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1063E	**Cannot search certificate data because the expiration date is null.**
Explanation	The certificate expiration date search criterion is null.
Action	Supply a valid certificate expiration date for this search criterion.

TNS.0006.1064E	**Cannot construct new CertData from SecurityOps.getCertificateDataForUpdate().**
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0006.1065E	**Error selecting CertData for ownerId={0} and expDate={1}; IOException encountered decoding bytes to IData.**
Explanation	While Trading Networks was attempting to select CertData for the specified owner and with the specified expiration date, an IOException was thrown when decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1066E	**Error selecting CertData for ownerId={0} and expDate={1}; SQLException encountered with the error message {2}.**
Explanation	An SQLException occurred while Trading Networks was attempting to select CertData for the specified owner and with the specified expiration date.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1067E	**Cannot construct new CertData from SecurityOps.getCertificateDataForPartnerAndUsage().**
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0006.1068E	**Error selecting CertData for partnerId={0} with usage={1}; IOException encountered decoding bytes to IData.**
Explanation	While Trading Networks was attempting to select CertData for the specified partner and with the specified certificate usage, an IOException was thrown when decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1069E	**Error selecting CertData for partnerId={0} with usage={1}; SQLException encountered with the error message {2}.**
Explanation	An SQLException occurred while Trading Networks was attempting to select CertData for the specified partner and with the specified certificate usage.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1070E	**Cannot get profile store or profile summary list, so Trading Networks cannot migrate certificates.**
Explanation	An exception was thrown while retrieving profile data.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1071W	**Cannot get partner''s ({0}) profile data; skip migrating this partner''s certificate set.**
Explanation	Trading Networks was not able to find profile data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partners certificate set.
Action	Contact Software AG Global Support.

TNS.0006.1074E	**Error loading partner''s ({0}) certificate; skip migrating this partner''s certificate set.**
Explanation	An exception occurred while loading certificate data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1075E	**Cannot migrate partner''s ({0}) certificate set because the certificate is null.**
Explanation	While Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null certificate. As a result, Trading Networks cannot migrate the certificate set.
Action	Supply a valid, non-null certificate.

TNS.0006.1077E	**Error loading partner''s ({0}) CACertificate; skip migrating this partner''s certificate set.**
Explanation	An exception was thrown while loading certificate data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.

Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1078E	**Cannot migrate partner''s ({0}) certificate set because a CA certificate is null.**
Explanation	While Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null CA certificate. As a result, Trading Networks cannot migrate the certificate set.
Action	Supply a valid CA certificate.

TNS.0006.1079E	**Error loading partner''s ({0}) private key; skip migrating this partner''s certificate set.**
Explanation	An exception occurred while loading the private key for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1080E	**Cannot migrate partner''s ({0}) certificate set because the private key is null.**
Explanation	The private key is null. When Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null private key. As a result, Trading Networks cannot migrate the certificate set.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1081E	**Error adding partner''s verify certificate to Trading Networks database (partner ID={0}, Integration Server user account={1}); skip migrating this partner''s verify certificate set.**
Explanation	An exception was thrown while attempting to add the verify certificate to the database. As a result, Trading Networks cannot migrate this partner's verify certificate set.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1082E	**Found null node certificate for CertId={0} in migration.**
Explanation	Trading Networks cannot migrate the certificate with the specified CertID because the node certificate is null.
Action	Supply a valid certificate.

TNS.0006.1083E	**IOException encountered in migration, CertID={0}.**
Explanation	IOException thrown when Trading Networks attempted to migrate the certificate with the specified CertID.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1084E	**Error duplicating sign certitificate data to SSL certificate data for owner={0}, partner={1}.**
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0006.1085E	**Cannot migrate certificate information. Cannot get current Trading Networks version from database.**
Explanation	Trading Networks cannot migrate certificate information because it cannot determine the Trading Networks version. The database information is not up-to-date or the database is not running.
Action	Ensure that the Trading Networks database is running. Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database.

TNS.0006.1087E	**fromVersion is required to run wm.tn.admin.migrate:migrateCerts.**
Explanation	The required fromVersion parameter was not supplied.
Action	Supply a valid fromVersion.

TNS.0006.1092E	**SQLException encountered in wm.tn.admin.migrate:migrateCerts.**
Explanation	An SQLException thrown was when executing the wm.tn.admin.migrate:migrateCerts service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1093E	**Error encountered in wm.tn.admin.migrate:migrateCerts.**
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0006.1094E	**Error encountered invoking service {0}.**
Explanation	An error occurred when invoking the specified service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1098E	**Cannot get certificate for verification of sender={0}, receiver={1}.**
Explanation	The certificates used to verify the Sender-Receiver partner pair are not available.
Action	Specify the certificates that you want to use for the partners in the Trading Networks profiles.

TNS.0006.1099E	**Cannot get certificate for verification of sender={0}, receiver={1}, stack trace is {2}.**
Explanation	Trading Networks could not retrieve the verify certificate for the specified sender and receiver.
Action	Ensure the verify certificate information is provided for specified sender and receiver.

TNS.0006.1101I	**No chain for signer {0} ({1}).**
Explanation	Required security data is missing.
Action	If your application code is creating or updating certificates, ensure that you supply all required certificate data to the services you are invoking. If you receive this error while using the Trading Networks Console, contact Software AG Global Support.

TNS.0006.1102E	**Cannot find verification cert.**
Explanation	Trading Networks could not retrieve a verify certificate.
Action	Contact Software AG Global Support.

TNS.0006.1103E	**Cannot find verification cert for sender={0}, receiver={1}.**
Explanation	Trading Networks could not retrieve the verify certificate for the specified sender and receiver.
Action	Ensure the verify certificate information is provided for specified sender and receiver.

TNS.0006.1104E	**Error encountered verifying XML document.**
Explanation	An error was thrown when verifying an XML document.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1109E	**Error encountered signing XML document.**
Explanation	An error was thrown while signing an XML document.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1110E	**Signing certificate for sender={0} receiver={1} not valid.**
Explanation	The signing certificate for the specified sender and receiver is not valid.
Action	Provide a valid signing certificate for the sender/receiver pair.

TNS.0006.1111E	**Verify certificate for sender={0} receiver={1} not valid.**
Explanation	The verify certificate for the specified sender and receiver is not valid.
Action	Provide a valid verify certificate for the sender/receiver pair.

TNS.0006.1115E	**Error encountered invoking wm.tn.security:getDecryptCACertificates.**
Explanation	An error was encountered while invoking the wm.tn.security:getDecryptCACertificates service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1116E	**Error encountered invoking wm.tn.security:getDecryptCertificate.**
Explanation	An error was encountered while invoking the wm.tn.security:getDecryptCertificate service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1117E **Error encountered invoking wm.tn.security:getDecryptKey.**

Explanation An error was encountered while invoking the wm.tn.security:getDecryptKey service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1118E **Error encountered invoking wm.tn.security:getEncryptCACertificates.**

Explanation An error was encountered while invoking the wm.tn.security:getEncryptCACertificates service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1119E **Error encountered invoking wm.tn.security:getEncryptCertificate.**

Explanation An error was encountered while invoking the wm.tn.security:getEncryptCertificate service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1120E **Error encountered invoking wm.tn.security:getEncryptKey.**

Explanation An error was encountered while invoking the wm.tn.security:getEncryptKey service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1121E **Error encountered invoking wm.tn.security:getSecurity.**

Explanation An error was encountered while invoking the wm.tn.security:getSecurity service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1122E **Error encountered invoking wm.tn.security:getSignCACertificates.**

Explanation An error was encountered while invoking the wm.tn.security:getSignCACertificates service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1123E	**Error encountered invoking wm.tn.security:getSignCertificate.**
Explanation	An error was encountered while invoking the wm.tn.security:getSignCertificate service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1124E	**Error encountered invoking wm.tn.security:getSignKey.**
Explanation	An error was encountered while invoking the wm.tn.security:getSignKey service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1125E	**Error encountered invoking wm.tn.security:getVerifyCACertificates.**
Explanation	An error was encountered while invoking the wm.tn.security:getVerifyCACertificates service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1126E	**Error encountered invoking wm.tn.security:getVerifyCertificate.**
Explanation	An error was encountered while invoking the wm.tn.security:getVerifyCertificate service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1132E	**Error encountered invoking wm.tn.security:setDecryptCertificateSet.**
Explanation	An error was encountered while invoking the wm.tn.security:setDecryptCertificateSet service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1133E	**cert is null; however, CACerts is not null.**
Explanation	You provided information in CACerts to specify CA certificates; however, you did not specify a certificate for the cert variable.
Action	Provide a valid certificate for the cert variable.

TNS.0006.1134E	**CACerts is required when the certificate is not self-signed.**
Explanation	You did not specify CA certificates for the CACerts variable. CA certificates are required unless the certificate you specify is self-signed.
Action	Provide valid CA certificates for the CACerts variable.

TNS.0006.1137E	**Error encountered invoking wm.tn.security:setEncryptCertificateSet.**
Explanation	An error was encountered while invoking the wm.tn.security:setEncryptCertificateSet service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1151E	**Error encountered invoking wm.tn.security:setSecurity.**
Explanation	An error was encountered while invoking the wm.tn.security:setSecurity service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1152E	**privateKey and cert should be both null or neither null.**
Explanation	You specified a value for either privateKey or cert, but not for both. The values for privateKey and cert must either both be null or both have non-null values.
Action	Provide valid values for privateKey and cert.

TNS.0006.1153W	**CACerts is required for non self signed certificates.**
Explanation	A value for CACerts must be specified for non self-signed certificates.
Action	Provide valid value for CACerts.

TNS.0006.1156E	**Error encountered invoking wm.tn.security:setSignCertificateSet.**
Explanation	An error was encountered while invoking the wm.tn.security:setSignCertificateSet service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1159E	**Error encountered invoking wm.tn.security:setVerifyCertificateSet.**
Explanation	An error was encountered while invoking the wm.tn.security:setVerifyCertificateSet service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1164E	**Error encountered invoking wm.tn.security:updateCertificate.**
Explanation	An error was encountered while invoking the wm.tn.security:updateCertificate service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1165E	**Error encountered in wm.tn.security:addCertificateData.**
Explanation	An error was encountered while executing the wm.tn.security:addCertificateData service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1166E	**Cannot get existing Certificate Data from supplied certID={0}.**
Explanation	Cannot get existing certificate data for the certificate information with certID=<certID>. The supplied certID might be invalid.
Action	Ensure that the value for certID is valid.

TNS.0006.1167E	**Cannot get existing CertID from supplied ownerID={0} partnerID={1} and usage={2}.**
Explanation	Cannot get existing CertID for certificate data that is associated with ownerID=<ownerID> partnerID=<partnerID> and usage=<certificateUage>.
Action	Ensure that the values for ownerID, partnerID, and usage are valid.

TNS.0006.1168E **Cannot construct new CertData in wm.tn.security:updateCertificateData.**

Explanation Internal error.

Action Contact Software AG Global Support.

TNS.0006.1169E **Error encountered in wm.tn.security:updateCertificateData.**

Explanation An error was encountered while executing the wm.tn.security:updateCertificateData service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1170E **Cannot delete non-existing CertData for ownerID={0}, partnerID={1} and usage={2}.**

Explanation Trading Networks could not locate certificate data for the specified ownerID, partnerID, or usage.

Action Ensure the values for ownerID, partnerID, and usage are valid.

TNS.0006.1171E **Error encountered in wm.tn.security:deleteCertificateData.**

Explanation An error was encountered while executing the wm.tn.security:deleteCertificateData service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1172E **Error encountered in wm.tn.security:getCertificateData.**

Explanation An error was encountered while executing the wm.tn.security:getCertificateData service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1175E **Error encountered in wm.tn.security:getSigningKeyAndChain.**

Explanation An error was encountered while executing the wm.tn.security:getSigningKeyAndChain service.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1176E	**Error encountered in wm.tn.security:getVerifyingChain.**
Explanation	An error was encountered while executing the wm.tn.security:getVerifyingChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1178E	**Error encountered in wm.tn.security:getDecryptionKeyAndCert.**
Explanation	An error was encountered while executing the wm.tn.security:getDecryptionKeyAndCert service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1179E	**Error encountered in wm.tn.security:getEncryptionChain.**
Explanation	An error was encountered while executing the wm.tn.security:getEncryptionChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1182E	**{0} private key not defined.**
Explanation	The private key for the SSL client certificate set was not defined.
Action	Provide a valid SSL private key for the SSL client certificate set.

TNS.0006.1183E	**{0} certificate chain not defined.**
Explanation	The certificate chain for the SSL client certificate set was not defined.
Action	Provide a valid SSL certificate chain for the SSL client certificate set.

TNS.0006.1184E	**Error encountered in wm.tn.security:getSSLKeyAndChain.**
Explanation	Error encountered when executing the wm.tn.security:getSSLKeyAndChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1185E	**No SSL key and cert defined.**
Explanation	The SSL private key and certificate are not defined.
Action	Provide a valid SSL private key and certificates.

TNS.0006.1187E	**Error encountered in wm.tn.security:setSSLKeyAndChain.**
Explanation	An error was encountered while executing the wm.tn.security:setSSLKeyAndChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1190E	**Certificate chain bytes cannot be null or zero length.**
Explanation	The certificate chainBytes value is either null or a zero length. The certificate chain must contain data.
Action	Provide valid certificate chain byte array.

TNS.0006.1191E	**Invalid RSA Private Key file.**
Explanation	The RSA private key file is not valid.
Action	Provide a valid RSA private key file.

TNS.0006.1192E	**Cannot construct new CertData.**
Explanation	Internal Error.
Action	Contact Software AG Global Support.

TNS.0006.1193E	**Bad private key for usage {0}: {1}**
Explanation	The private key that was provide is not valid.
Action	Provide a valid private key.

TNS.0006.1194	**Unable to import security data for owner {0} because the owner is not defined in your Trading Networks system.**
Explanation	In webMethods Trading Networks, it is not possible to import the security data for the owner as the owner is not defined.
Action	Define the owner in webMethods Trading Networks and try again.

TNS.0006.1196	**Unable to import security data of owner {0} for partner {1} because the partner {1} is not defined in your Trading Networks system.**
Explanation	In webMethods Trading Networks, if the partner is not defined as the owner of the certificate, the security data cannot be imported.
Action	Ensure that the partner is the owner of the certificate and try again.

TNS.0006.1198	**Error encountered while viewing certificate data for partnerID={0}. The error is {1}**
Explanation	In webMethods Trading Networks, an error is encountered while viewing certicate data for the partner.
Action	Contact your system administrator.

TNS.0006.1199	**Error encountered in wm.tn.security:updateCertificateData for partnerID={0}. The error is {1}**
Explanation	In webMethods Trading Networks, an error is encounterred while updating a certificate.
Action	Contact your system administrator.

TNS.0006.1200	**Error encountered while validating chain The error is {0}**
Explanation	In webMethods Trading Networks, an error is encountered when the certificate details that are entered is not correct.
Action	Ensure to define the certificate details correctly and try again.

TNS.0006.1201	**Unable to import security data for partner {0} because this partner is not defined in your Trading Networks system.**
Explanation	webMethods Trading Networks is unable to import security data for the partner because this partner is not defined in your webMethods Trading Networks system.
Action	Define the partner in your webMethods Trading Networks system and try again.

TNS.0007.1001E	**{0} is required.**
Explanation	A value was not supplied for the specified variable.
Action	Supply the required value.

TNS.0007.1002E	**wm.tnweb.wrapper:xmlEncode: could not encode IData to binary**
Explanation	An exception was thrown while encoding an IData.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1003E	**wm.tnweb.wrapper:xmlDecode: could not decode binary to IData**
Explanation	An exception was thrown while decoding an IData.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1004E	**wm.tnweb.wrapper:xmlDecode2: could not decode binary to Values**
Explanation	An exception was thrown while decoding an IData.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1005E	**wm.tnweb.wrapper:removeNullAlerts: error caught in removing null alerts**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1006E	**wm.tnweb.wrapper:compareRights: error caught in comparing rights**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1007E	**wm.tnweb.wrapper:getTNRights: error caught in getting Trading Networks partner ACL privilege**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1008E	**wm.tnweb.wrapper:getUserGroups: error caught in getting Trading Networks partner ACL group memberships**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1009E	**wm.tnweb.wrapper:getUserInfo: error caught in getting Trading Networks partner IS login name**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1010E	**wm.tnweb.wrapper:getHashKeys: error caught in getting Hashtable keys**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1011E	**{0} cannot be null**
Explanation	A value was not supplied for the specified variable.
Action	Supply the required value.

TNS.0007.1012E	**wm.tnweb.wrapper:IntegerToStrng: error caught converting Integer datatype to String datatype**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1013E	**wm.tnweb.wrapper:ShortToStrng: error caught converting Short datatype to String datatype**
Explanation	Trading Networks encountered an internal error
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1014E	**wm.tnweb.wrapper:isBIEnabled: error caught in retrieving enabled Integration Server packages**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1015E	**wm.tnweb.wrapper:isBIEnabled: could not find if Business Integrator (ProcessMonitor) package is installed and enabled**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1016E	**wm.tnweb.wrapper:getStringFromBundle: could not get String from resource bundle wm.tnweb.wrapper_bundle for key = {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1017E	**wm.tnweb.querySvc:getQuery: could not get pre-saved query ({0}) for partnerID={1}.**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1018E	**{0} cannot be null or empty**
Explanation	A value was not supplied for the specified variable.
Action	Supply the required value.

TNS.0007.1019E	**partnerID is null or empty in invoking wm.tnweb.querySvc:getSavedQueries**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1020E	**wm.tnweb.querySvc:getSavedQueries: could not get pre-saved queries for partnerID={0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1021E	**wm.tnweb.querySvc:getDocuments: could not get documents**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1022E	**wm.tnweb.querySvc:createTaskQuery: could not create task query for document id={0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1023E	**wm.tnweb.querySvc:getCalendar: invalid input {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1024E	**wm.tnweb.querySvc:getCalendar: could not get calender for year={0}, month={1}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1025E	**wm.tnweb.querySvc:getQueryRestriction: could not get document query restriction for document id = {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1026E	**Could not get profile store**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1027E	**Could not get document attributes for id = {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1028E	**Could not get internal document type id for name = {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1029E	**wm.tnweb.configSvc:checkDefaultConfigLoaded: could not check if default config is loaded**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1030E	**wm.tnweb.configSvc:getHashes: could not construct Hashtables for TNAdministrators and TNPartners**
Explanation	Internal error Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1035E	**wm.tnweb.configSvc:getUserConfig: could not get membership info for user {0}.**
Explanation	The user account for the specified user does not exist in the Integration Server.
Action	If you have deleted the user account for this user, use the Integration Server Administrator to create the user account again. If this is for an external user, ensure that the user account is a member of the TNPartners group.

TNS.0007.1039E	**wm.tnweb.configSvc:getUserConfig: could not get partner specific config for {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1040E	**wm.tnweb.configSvc:getGroupConfig: could not get group specific config for {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1041E	**wm.tnweb.configSvc:getTNPartners: could not get partner information**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1042E	**wm.tnweb.configSvc:getTNGroups: could not get IS group information**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1043E	**wm.tnweb.configSvc:getTNUsers: could not get Trading Networks IS user information**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1044E	**wm.tnweb.configSvc:getUserConfigDisplay: could not get specific user config information**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1045E	**wm.tnweb.configSvc:getAvailableStatus: could not get user status from database**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1047E	**wm.tnweb.configSvc:saveCustomPages: error encountered in saving new custom pages setting**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1048E	**wm.tnweb.configSvc:addToHashes: invalid type value**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1049E	**wm.tnweb.configSvc:addToHashes: could not add new config IData to hashtable**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1050E	**wm.tnweb.configSvc:changeConfig: could not change config setting**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1051E	**wm.tnweb.querySvc:getQueryRestriction: do not have privilege to check query restriction**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1053E	**wm.tnweb.wrapper:logBrowserLocale: error encountered in getting browser locale**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1054E	**cert is null**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1055E	**CACerts is null**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1056E	**CACerts[{0}] is null**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1057E	**privateKey is null**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1058E	**Can not get user specific configuration: no such user {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1059E	**Error encountered calling wm.tnweb.configSvc:checkAndUpdateConfig**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1061E	**Error updating/retrieving configuration info from repo**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1062E	**Error encountered in invoking service wm.tnweb.querySvc:getPartnerNameAndID**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1063E	**Can not get valid profile summary list: list is null or empty**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1064E	**Error encountered in invoking service wm.tnweb.querySvc:runTaskQuery**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1065E	**Error encountered in invoking service wm.tnweb.querySvc:taskQueryById**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1066E	**Error encountered in invoking service wm.tnweb.querySvc:getDocDetails**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1067E	**Got null bizdoc, docId = {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1068E	**Got null or 0-length bizdoc content parts, docId = {0}**
Explanation	The contents of this document might not have been saved to the Trading Networks database.
Action	Check the corresponding TN document type and processing rule to determine whether Trading Networks has saved the document contents to the database.

TNS.0007.1069E	**Invalid startIndex = {0}**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1070E	**Can not convert content bytes to String: unsupported encoding**
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1071E	**NOTE: No privilege to view contents of this document**
Explanation	You attempted to view a document of which you are neither the sender nor the receiver.
Action	You can only view a document that you have sent or received.

TNS.0007.1072E	**NOTE: No more data to display**
Explanation	Either the document has no content or the startIndex is beyond the end of the content.
Action	If you determine that this is an error, gather error information and contact webMethods Customer Care.

TNS.0007.1073E **Got null bizdoc content part, docId={0}, content part name={2}**

Explanation The content of this document might not have been saved to the Trading Networks database.

Action Check the corresponding TN document type and processing rule to determine whether Trading Networks saved the document content to the database.

TNS.0007.1074E **Error encountered in invoking service wm.tnweb.wrapper:getTNInfo**

Explanation Trading Networks encountered an internal error.

Action Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1075E **Error encountered in invoking service wm.tnweb.wrapper:registerTNOnIntegrationServer**

Explanation Trading Networks encountered an internal error.

Action Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1076E **Error encountered parsing date {0} or {1}.**

Explanation Trading Networks encountered an internal error.

Action Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1077E **Error encountered in invoking service wm.tnweb.wrapper:installTNWebACLs**

Explanation Trading Networks encountered an internal error.

Action Gather error information from the logs and contact Software AG Global Support.

TRNSERV.000018.000001 – new String[]{"{0} is required","Please supply the required value","0"}

Explanation A value for the specified input field is not supplied.

Action Supply a valid value for the specified input field.

TRNSERV.000018.000018 – new String[]{"{0} cannot be null or empty","","0"}

Explanation The specified input field does not contain a value. A value for this input field is required.

Action Supply a valid value for the specified input field.

TRNSERV.000018.000025 – new String[]{"wm.tnweb.querySvc:getQueryRestriction: could not get document query restriction for document id = {0}","","0"}

Explanation An error occurred while fetching a document query restriction for specified document.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TRNSERV.000018.000051 – new String[]{"wm.tnweb.querySvc:getQueryRestriction: do not have privilege to check query restriction","","0"}

Explanation You are not allowed to check the query restriction.

Action Contact your administrator.

TRNSERV.000018.000066 – new String[]{"Error encountered in invoking service wm.tnweb.querySvc:getDocDetails","","0"}

Explanation An error occurred while retrieving content part bytes.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TRNSERV.000018.000067 – new String[]{"Got null bizdoc, docId = {0}","","0"}

Explanation While checking the query restriction, a null bizdoc was found for the specified docID.

Action Supply a valid docId.

TRNSERV.000024.000204 – new String[]{"Error attempting to parse message contents","","0"}

Explanation A MessagingException error occurred while parsing the MIME message.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TRNSERV.000024.000205 – new String[]{"Error attempting to read from message source","","0"}

Explanation An IOException error occurred while reading a MIME message from the message source.

Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

bizDocDeletionError – You did not select an item to delete. Select at least one item to delete.

Explanation You did not select an item to delete.

Action Select at least one item to delete.

bizDocSelectionError – You did not select an item to archive. Select at least one item to archive.

Explanation You did not select an item to archive.

Action Select at least one item to archive.

cert.err **An error occurred while validating the certificate chain. Take corrective action based on the error details.**

Explanation An error occurred while validating the certificate chain.

Action Take corrective action based on the error details.

corp.name.required **You did not supply a value for the required Corporation Name field. Provide a value for this field.**

Explanation You did not supply a value for the required Corporation Name field.

Action Provide a value for this field.

date.is.required **You did not specify a date. Specify a date to proceed.**

Explanation You did not specify a date.

Action Specify a date to proceed.

default.connection.error.msg – Trading Networks Server is not configured, or it is not available.

Explanation Trading Networks server is not configured, or it is not available.

Action Contact the Administrator.

dlscheck.dialogMessage – You do not have permission to perform this action. Contact your system administrator for the required privileges.

Explanation You do not have permission to perform this action.

Action Contact your system administrator for the required privileges.

docTypeDetails_NameRequiredError – The document type name is a required field. Provide a document type name.

Explanation The document type name is required.

Action Provide a document type name.

docTypeSearch.fileInput.required.msg – No document was provided for testing. Provide the document.

Explanation No document was provided for testing.

Action Provide the document.

doctype.instantiation.error – The EDI document type could not be instantiated. Make sure that a valid schema standard is specified.

Explanation The EDI document type could not be instantiated.

Action Make sure that a valid schema standard is specified.

editor.detailsid.missing.error – Document Type ID is missing.

Explanation In webMethods Trading Networks, if the Document Type ID is missing, this error shows up.

Action Ensure to log out and log in again to webMethods Trading Networks.

empty.attribute.name.error – The Name field cannot be blank. Provide a valid value for this field.

Explanation The Name field cannot be blank.

Action Provide a valid value for this field.

error.InvalidDefaultValue – You specified a default value of %1$s. This value is not valid. Select a value from the list of valid values.

Explanation The specified default value is not valid.

Action Select a value from the list of valid values.

error.InvalidFieldId – Invalid Field Id Specified: %1$s

Explanation In webMethods Trading Networks, if the Field Definition ID of the profile is null or invalid, this error shows up.

Action Contact your system administrator.

error.InvalidFieldLength – You specified a field length of %1$s. This field length is not valid. Specify a positive integer value.

Explanation The specified field length is not valid.

Action Specify a positive integer value.

error.WmEDIPackageNotEnabled – The WmEDI package is not enabled on the Integration Server. Enable the package.

Explanation The WmEDI package is not enabled on the Integration Server.

Action Enable the package.

error.days.greaterthan.zero – Specify a value greater than zero for Days field.

Explanation You entered a value for Days that is not valid.

Action Enter an integer value greater than zero.

error.defValue.exceeds.maxLength – Default Value %1$s exceeds specified Maximum Length %2$s

Explanation In webMethods Trading Networks, if the default value of a field definition exceeds the maximum length permissible, this error throws up.

Action Enter a field definition with default value within the permissible maximum length, and try again.

error.delete **The activity log(s) could not be deleted. Take corrective action based on the error details.**

Explanation The activity log(s) could not be deleted.

Action Take corrective action based on the error details.

error.enter.valid.file.name – Enter a valid file name

Explanation The file name is empty or contains invalid characters such as ", /, \, *, or ?.

Action Specify a valid file name.

error.enter.valid.solution.name – Enter a valid solution name

Explanation The solution name is empty or contains invalid characters such as ", /, \, *, or ?.

Action Specify a valid solution name.

error.extract.file	**The file you uploaded is not in a valid format. Provide an XML or a binary file containing valid asset data to import.**
Explanation	The file you uploaded is not in a valid format.
Action	Provide an XML or a binary file containing valid asset data to import.

error.getComment	**An error occurred while retrieving comments from Trading Networks. Take corrective action based on the error details and trace.**
Explanation	An error occurred while retrieving comments from Trading Networks.
Action	Take corrective action based on the error details and trace.

error.getEDIINTProperties – My webMethods encountered an error while trying to retrieve WmEDIforTN package properties. Take corrective action based on the error details.

Explanation	My webMethods Server encountered an error while trying to retrieve WmEDIforTN package properties.
Action	Take corrective action based on the error details.

error.getEDIProperties – My webMethods Server encountered an error while trying to retrieve WmEDI package properties. Take corrective action based on the error details.

Explanation	My webMethods Server encountered an error while trying to retrieve WmEDI package properties.
Action	Take corrective action based on the error details.

error.getTNProperties – My webMethods Server encountered an error while trying to retrieve Trading Networks properties. Make sure the WmTN package is properly installed and loaded.

Explanation	My webMethods Server encountered an error while trying to retrieve Trading Networks properties.
Action	Make sure the WmTN package is properly installed and loaded.

error.message	**Download action failed.**
Explanation	An exception occurred while downloading the file.
Action	Check the server connection. Contact the system administrator to check your security and locale settings.

error.message.edi.not.installed – This feature requires the WmEDI and WmEDIforTN packages. These packages are either not loaded or are disabled. Enable these packages.

Explanation This feature requires the WmEDI and WmEDIforTN packages.

Action These packages are either not loaded or are disabled. Enable these packages.

error.name.already.exists – The name you have chosen for this field, %1$s, already exists. Enter a different name.

Explanation The name you have chosen for this field already exists.

Action Enter a different name.

error.noserver **My WebMethods Server could not reassign the task(s) because no target was specified. Specify the target server.**

Explanation My webMethods Server could not reassign the task(s) because no target was specified.

Action Specify the target server.

error.reassign **My WebMethods Server encountered an error while reassigning the task(s). Take corrective action based on the error details.**

Explanation My webMethods Server encountered an error while reassigning the task(s).

Action Take corrective action based on the error details.

error.restart **My WebMethods Server encountered an error while restarting the task(s). Take corrective action based on the error details.**

Explanation My webMethods Server encountered an error while restarting the task(s).

Action Take corrective action based on the error details.

error.saveEDIFormatSettings – My webMethods encountered an error while trying to update EDI Module format settings. Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while trying to update EDI Module format settings.

Action Take corrective action based on the error details.

error.saveEDIINTProperties – My webMethods encountered an error while trying to update EDI Module configuration properties. Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while trying to update EDI Module configuration properties.

Action Take corrective action based on the error details.

error.saveEDIProperties – My webMethods encountered an error while trying to save EDI Module configuration properties. Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while trying to save EDI Module configuration properties.

Action Take corrective action based on the error details.

error.saveTNProperties – My webMethods Server encountered an error while trying to save Trading Networks properties. Make sure the WmTN package is properly installed and loaded.

Explanation My webMethods Server encountered an error while trying to save Trading Networks properties.

Action Make sure the WmTN package is properly installed and loaded.

error.setComment **An error occurred while setting comments from Trading Networks. Take corrective action based on the error details and trace.**

Explanation An error occurred while setting comments from Trading Networks.

Action Take corrective action based on the error details and trace.

error.stop **My WebMethods Server encountered an error while stopping the task(s). Take corrective action based on the error details.**

Explanation My webMethods Server encountered an error while stopping the task(s).

Action Take corrective action based on the error details.

error.submitDocument – An error occurred while submitting the document to Trading Networks. Check the file path and resubmit the document.

Explanation An error occurred while submitting the document to Trading Networks.

Action Check the file path and resubmit the document.

file.validation.messageE – Invalid file format. Supported format: csv

Explanation The file uploaded is not a valid file format.

Action Upload .csv files.

g11n.wm_tn_bam_attributes.default.optimize_not_installed – Optimize is not installed. Install webMethods Optimize.

Explanation Optimize is not installed.

Action Install webMethods Optimize.

g11n.wm_tn_bam_doctypes.default.optimize_not_installed – Optimize is not installed. Install webMethods Optimize.

Explanation Optimize is not installed.

Action Install webMethods Optimize.

g11n.wm_tn_dls_viewDataSet.default.at_least_one_permission – Permissions have not yet been granted to this role. Grant at least one permission to this role on the Permissions tab.

Explanation Permissions have not yet been granted to this role.

Action On the Permissions tab, grant at least one permission to this role.

g11n.wm_tn_pf_profile.users.invalid_user_name – You did not specify a user name. Provide a valid user name.

Explanation You did not specify a user name.

Action Provide a valid user name.

g11n.wm_tn_pf_profile.users.no_password – The password is missing. Provide and confirm the password.

Explanation The password is missing.

Action Provide and confirm the password.

g11n.wm_tn_pf_profile.users.passwords_do_not_match – The values for Password and Confirm Password do not match. Enter the same values for these fields.

Explanation The values for Password and Confirm Password do not match.

Action Enter the same values for these fields.

g11n.wm_tn_pf_profile.users.user_already_exists_please – The specified user name already exists. Provide a unique user name.

Explanation The specified user name already exists.

Action Provide a unique user name.

g11n.wm_tn_pf_profile.users.user_name_invalid – The user name provided is not valid because it contains special characters.Specify a user name that contains only alphanumeric characters.

Explanation The user name provided is not valid because it contains special characters.

Action Specify a user name that contains only alphanumeric characters.

id.generate.error	**Can not generate EDI document type ID. Try again.**
Explanation	Cannot generate EDI document type ID.
Action	Try again.

invalid.fileE	**Invalid file format. Supported formats: xml,txt**
Explanation	The file uploaded is not a valid file format.
Action	Upload .xml or .txt files.

invalid.integer.value.detail – The value you provided for the Control Number Minimum is not an integer. For the VDA standard, enter an integer value greater than or equal to 0. For other standards, enter an integer value greater than or equal to 1.

Explanation	The value you provided for the Control Number Minimum is not an integer.
Action	For the VDA standard, enter an integer value greater than or equal to 0. For other standards, enter an integer value greater than or equal to 1.

invalid.message.minimum.value – The value you provided for the Control Number Minimum is not valid. For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

Explanation	The value you provided for the Control Number Minimum is not valid.
Action	For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

invalid.role	**You cannot add or remove privileges for Trading Networks or My webMethods administrators. Contact your system administrator.**
Explanation	You cannot add or remove privileges for Trading Networks or My webMethods administrators.
Action	Contact your system administrator.

invalid.value.inputcontrol – The value you provided for the Control Number Minimum is not valid. Enter an integer value. For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

Explanation	The value you provided for the Control Number Minimum is not valid. Enter an integer value.
Action	For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

label.error.maxrowsexceededE – Number of records to fetch exceeds the maximum limit.

Explanation	Error occurred while trying to access Trading Networks dashboard because the number of records to fetch from the dashboard table (TransactionSummaryData table) exceeds the maximum limit.
Action	Contact your system administrator to either purge records or specify a larger value for the tn.chart.fetchMaxRows property.

missing.required.extended – The required extended field {1} of group {0} is missing. Provide a value for this extended field.

Explanation	The required extended field is missing.
Action	Provide a value for this field.

msg.badDateRange	**The start date is later than the end date. Correct the start date so that it occurs before the end date.**
Explanation	The start date is later than the end date.
Action	Correct the start date so that it occurs before the end date.

msg.badDynamicData	**You submitted dynamic query criteria that are incomplete. Provide all expected elements for the dynamic query.**
Explanation	The dynamic query criteria are incomplete.
Action	Provide all expected elements for the dynamic query.

msg.errSave	**The content viewer page size is empty or is not valid. Enter an integer value greater than zero.**
Explanation	The content viewer page size is empty or is not valid.
Action	Enter an integer value greater than zero.

msg.maxReprocessDocuments – You cannot reprocess more than {0} documents. To change this limit, contact your system administrator.

Explanation	Reprocessing limit exceeded.
Action	To change this limit, contact your system administrator.

msg.maxResubmitDocuments – You cannot resubmit more than {0} documents. To change this limit, contact your system administrator.

Explanation	Resubmission limit exceeded.
Action	To change this limit, contact your system administrator.

name.is.required	**You did not specify a queue name. Specify a queue name to proceed.**
Explanation	You did not specify a queue name.
Action	Specify a queue name to proceed.

no.data.set	**My webMethods was unable to find the dataset for the specified ID. Log in to My webMethods again.**
Explanation	Unable to find the dataset for the specified ID.
Action	Log in to My webMethods again.

no.return.url	**My webMethods could not navigate to the specified page because of a caching issue. Log in to My webMethods again.**
Explanation	My webMethods could not navigate to the specified page because of a caching issue.
Action	Log in to My webMethods again.

no.root.vailable.error – The sample document used for creating the XML document type does not contain a Root tag. Provide a properly formatted document that contains a Root tag.

Explanation	The sample document used for creating XML document type does not contain a Root tag.
Action	Provide a properly formatted document that contains a Root tag.

not.valid.document	**You uploaded a sample document that is not valid. Provide a sample document with a valid root node.**
Explanation	You uploaded a sample document that is not valid.
Action	Provide a sample document with a valid root node.

optionsTab.check.duplicate.doc.error.msg – You selected the "Check for Duplicate Document" option but did not specify a duplication service. Select a service.

Explanation	You selected the "Check for Duplicate Document" option but did not specify a duplication service.
Action	Select a service.

partnerid.missing.message – The partner ID is missing. Click here to go to the Partner Profiles page, and then specify a valid partner ID.

Explanation The partner ID is missing.

Action Click here to go to the Partner Profiles page, and then specify a valid partner ID.

problem.AccessException – You do not have permission to perform the requested action. Check with your system administrator.

Explanation You do not have permission to perform the requested action.

Action Request that your system administrator assign you the permission.

problem.ConnectException – My webMethods Server could not connect to the Trading Networks Server because that server is not available. Make sure the server is running on the specified host and port ''{0}''.

Explanation The specified Trading Networks server is not available.

Action Make sure the server is running on the specified host and port.

problem.UnknownHostException – My webMethods Server could not connect to the Trading Networks Server named ''{0}'' because that server is either not available or its host name is not recognized. Start the Trading Networks Server or specify a different server to connect to.

Explanation The specified Trading Networks server is not available.

Action Verify the host name of the Trading Networks Server.

problem.noSelection – You did not select any items to act on. Select one or more items and retry the action.

Explanation You did not select any items to act on.

Action Select one or more items and then retry the action.

proc.rules.detailsno.server.error – Trading Networks Server is not configured, or it is not available.

Explanation The configured Trading Networks instance may be down, or the system administrator may not have granted you permission to access the Trading Networks Server.

Action Make sure the server is running. If it is, contact the system administrator for permission to access the server.

procrule.details.name.invalid.errorE – Invalid Processing rule name. Special characters are not allowed.

Explanation	Processing rule name cannot have special characters.
Action	Provide a valid name for the processing rule.

profile.externalid.required – You did not specify an external ID for this profile. Provide the external ID.

Explanation	You did not specify an external ID for this profile.
Action	Provide an external ID.

query.not.found.error – You uploaded a sample document that does not contain a valid root node. Provide a sample document with a valid root node.

Explanation	You uploaded a sample document that does not contain a valid root node.
Action	Provide a sample document with a valid root node.

query.not.match	**Your query does not match any of the nodes present in the sample document. Resubmit the query with a valid node.**
Explanation	Your query does not match any of the nodes present in the sample document.
Action	Resubmit the query with a valid node.

role.is.required	**Permissions have not yet been granted to any roles. Grant permission(s) to at least one role on the Permissions tab.**
Explanation	Permissions have not yet been granted to any roles.
Action	On the Permissions tab, grant permission(s) to at least one role.

rule.name.is.required – The dataset could not be created or updated because no dataset name was specified. Provide the dataset name.

Explanation	Dataset name not specified while creating or updating the dataset.
Action	Enter the dataset name.

std.version.trans.not.sel.error – You did not specify a standard, version, or transaction while creating the EDI document type. Select a standard, version, and transaction.

Explanation	You did not specify a standard, version, or transaction while creating the EDI document type.
Action	Select a standard, version, and transaction.

text.futuredate.validationE – Date selected cannot be in the future.

Explanation Error occurred while trying to retrive records from the TransactionSummaryData table because the date selected was a future date.

Action Select an appropriate date to view data.

text.response.nodataI – No records found for the selected date.

tpa.details.agreementID.required.error – Agreement ID cannot be empty.

Explanation Agreement ID is empty.

Action Provide an Agreement ID.

tpa.details.controlnumber.notInteger – Control Number must be an integer. Provide an integer value.

Explanation Control Number must be an integer.

Action Provide an integer value.

tpa.details.profiles.required.error – Sender or Receiver fields cannot be empty.

Explanation Sender or Receiver field is empty.

Action Specify Sender and Receiver.

tree.load.error **My webMethods encountered an error while loading the XML node tree. Click Upload to try loading the tree again.**

Explanation My webMethods Server encountered an error while loading the XML node tree.

Action Click Upload to try loading the tree again.

updateFAStatus.errorMsg – Error in updating EDI FA status.

Explanation Error in updating EDI FA status.

Action Take corrective action according to the error details.

warn.noFileSelected – No document was chosen for submission. Specify the file path to the document to be submitted.

Explanation No document was chosen for submission.

Action Specify the file path to the document to be submitted.

28 webMethods Social BPM Messages

SBPAPIE0000	**Could not establish session for {0} server. Status: {1}**
Explanation	Connection to the client failed.
Action	Check the connection settings for the client.

SBPAPIE0001	**Could not send the email. Enter the recipients' email address, subject, and message in their respective fields.**
Explanation	The values for the recipients' email address, subject, and message fields cannot be null or invalid.
Action	Make sure the email address, subject, and message fields are not empty.

SBPAPIE0002	**Could not send the email. Read the log file for more details.**
Explanation	The email address might be wrong or empty.
Action	Check the error details in the log file. Provide the correct email address.

SBPAPIE0004	**The remote resource, {0} did not return a valid session.**
Explanation	Client connection is not valid.
Action	Check the connection settings.

SBPAPIE0005	**{0} HTTP method is not supported.**
Explanation	Only GET, POST, PUT, and DELETE methods are supported.
Action	Use only GET, POST, PUT, or DELETE methods.

SBPAPIE0006	**You do not have the required privileges to view task data. Contact the Administrator.**
Explanation	Only users with the required privileges can view task data.
Action	Request the Administrator to provide you the privileges to view task data.

SBPAPIE0007	**Task ID cannot be null.**
Explanation	A valid Task ID is required.
Action	Provide a valid Task ID.

SBPAPIE0008	**At least one group is required if you set {groupByField=<field> / groupByTaskType = <true} parameter.**
Explanation	You cannot use groupByField or groupByTaskType when there are no groups.
Action	Use groupByField or groupByTaskType only when there are groups.

SBPAPIE0009	**Wrong operator specified for task list search.**
Explanation	The criteria for task list search is incorrect.
Action	Provide the correct search criteria.

SBPAPIE0010	**AppSpace not found. You might not have access to the AppSpace or the AppSpace might have been removed.**
Explanation	Either the Administrator might have removed the AppSpace or you do not have the privileges to view the AppSpace.
Action	Request the Administrator to verify the AppSpace availability or provide you the privileges to view the AppSpace.

SBPAPIE0011	**Invalid input. The JSON payload for the {0} is not valid.**
Explanation	The input to the RESTful service is invalid.
Action	Verify the JSON payload to the RESTful service.

SBPAPIE0012	**Avoid using reserved words for {0} name**
Explanation	The dashboard name should not contain programming keywords such as null or var.
Action	Do not use programming keywords in the dashboard name.

SBPAPIE0013	**Insufficient Privileges. You cannot view {0}.**
Explanation	You do not have the privileges to view the dashboard.
Action	Request the Administrator to provide you the privileges to view the dashboard.

SBPAPIE0014	**Insufficient Privileges. You cannot edit {0}.**
Explanation	You do not have the privileges to edit the dashboard.
Action	Request the Administrator to provide you the privileges to edit the dashboard.

SBPAPIE0015	**Insufficient Privileges. You cannot delete {0}.**
Explanation	You do not have the privileges to delete the dashboard.
Action	Request the Administrator to provide you the privileges to delete the dashboard.

SBPAPIE0016	**Insufficient Privileges. You cannot create {0}.**
Explanation	You do not have the privileges to create the dashboard.
Action	Request the Administrator to provide you the privileges to create the dashboard.

SBPAPIE0017	**Unable to remove the delegation. You cannot remove delegations done by other users.**
Explanation	You cannot remove delegations done by other users.
Action	Request the user who has delegated the task to remove the delegation.

SBPAPIE0047	**Cannot retrieve the preferences for {0}**
Explanation	Cannot retrieve the preference settings.
Action	Verify if the preferences set in Business Console are available.

SBPAPIE0050	**A server error has occured: {0}**
Explanation	An internal error has occured.
Action	Contact the System Administrator or verify the log to resolve the error.

SBPAPII0003	**Task ID not found.**
Explanation	The task instance is not available in the database.
Action	Request the Administrator to verify the task instance availability.

SBPAPII0018 **Invalid email**

Explanation Cannot send task reminder to an invalid email.

Action Provide a valid email.

SBPAPII0019 **Internal server error**

Explanation Cannot send task reminder because of an internal server error.

Action Contact the Administrator for resolving this error.

SBPAPII0020 **Integration Server connection error**

Explanation Cannot connect to the Integration Server.

Action Contact the Administrator for resolving this error.

SBPAPII0023 **AgileApps server connection error**

Explanation Cannot connect to the AgileApps server.

Action Contact the Administrator for resolving this error.

SBPAPII0024 **Failed to retrieve the 'isDelegated' property from task: {0}**

Explanation Cannot retrieve the delegation status of the task.

Action Contact the Administrator for resolving this error.

SBPAPII0025 **No delegation to remove. The task ID {0} is not delegated.**

Explanation The task is not delegated to a user.

Action Contact the Administrator for resolving this error.

SBPAPII0027 **Invalid input parameters**

Explanation The input parameters specified for the AppSpace is not valid.

Action Verify the input parameters.

SBPAPII0028 **The task {0} is not active.**

Explanation You cannot set the status because the task in not active.

Action Contact the Administrator for resolving this error.

SBPAPII0029	**Insufficient privileges**
Explanation	You do not have the privileges to perform this action.
Action	Request the Administrator to provide you the required privileges.

SBPAPII0030	**User, group, or role name is null or does not exist.**
Explanation	User, group, or role name is null or does not exist.
Action	Use a valid user, group, or role name.

SBPAPII0031	**Insufficient privileges. {0} does not have the privileges to add comments.**
Explanation	You do not have the privileges to add comments.
Action	Request the Administrator to provide you the privileges to add comments.

SBPAPII0032	**The task ID: {0} is not found.**
Explanation	The task ID is not found.
Action	Verify if the task ID is correct or contact the Administrator.

SBPAPII0033	**Profile picture not loaded**
Explanation	Cannot load the profile picture.
Action	Contact the Administrator for resolving this error.

SBPAPII0034	**Insufficient privileges. {0} cannot update the profile of {1}.**
Explanation	You do not have the privileges to update the profile.
Action	Request the Administrator to provide you the privileges to update the profile.

SBPAPII0035	**Cannot retrieve the file.**
Explanation	The file is not found.
Action	Contact the Administrator for resolving this error.

SBPAPII0036	**The Task Engine host: {0} not found.**
Explanation	The specified host name for the Task Engine is not found.
Action	Contact the Administrator for resolving this error.

SBPAPII0037 **Task Engine server connection error**

Explanation Cannot connect to the Task Engine server.

Action Contact the Administrator for resolving this error.

SBPAPII0038 **I/O exception in Task Engine: {0}**

Explanation Cannot resolve the Task Engine URL.

Action Contact the Administrator for resolving this error.

SBPAPII0039 **Exception in Task Engine: {0}**

Explanation An error has occurred in Task Engine.

Action Contact the Administrator for resolving this error.

SBPAPII0040 **Task definition URI error**

Explanation Cannot resolve the task definition URI.

Action Provide a valid task definition URI.

SBPAPII0041 **You are not logged on.**

Explanation You must log on to perform the action.

Action Log on to perform the action.

SBPAPII0044 **Invalid search**

Explanation Search is not valid.

Action Use valid search criteria.

SBPAPII0045 **Cannot sync {0} task types.**

Explanation Cannot sync the indicated number of task types from Task Engine.

Action Contact the Administrator for resolving this error.

SBPAPII0046 **Invalid URL: {0}**

Explanation Cannot resolve the URL.

Action Provide a valid URL.

SBPCORI1046 Duration

29 Web Services Stack Messages

WSSAPE0029	**Failed to initialize argus configuration due to the following: {0}.**
Explanation	An argus configuration file is invalid or unavailable, or a WS_STACK_HOME variable is not set.
Action	Make sure that the WS_STACK_HOME environment variable is properly set. Check the path to the argus configuration file and make sure that the argus configuration file is valid and not empty.

WSSAPE0030	**Unknown user: {0}.**
Explanation	The user cannot be authenticated because the supplied username is not correct.
Action	Provide a valid username.

WSSAPE0031	**Unknown password callback type: {0}**
Explanation	Only UsernameToken authentication is supported. You use a different authentication mechanism.
Action	Provide a valid username and password.

WSSAPE0032	**An argus username is not configured in the argus agents properties file.**
Explanation	The entries in argus agents properties file must be initialized. The "wsstack.adminservice.user" property does not contain a valid value.
Action	Provide a valid, non-empty value for "wsstack.adminservice.user" property in the argus agents properties file.

WSSARE0000	**Login failed.**
Explanation	Authentication fails. Invalid or empty credentials provided.
Action	Provide valid, non-empty username and password.

WSSARE0001	**The following Web service archive does not comply with the naming standards: {0}. The archive is not deployed.**
Explanation	The artifact name and extension contain invalid characters or do not comply with the correct name format.
Action	Edit the current artifact to conform to the AAR standards. Rename the archive using a valid name. The '.aar' extension cannot contain capital letters.

WSSARE0030	**A problem occurred while executing a Web service. The Web service name is ''{0}'' with request payload ''{1}''.**
Explanation	There is a problem while executing the Web service.
Action	Make sure that the requested Web service is operational.

WSSARI0027	**Version information.**
Explanation	A version information label.
Action	None.

WSSASE0000	**Cannot find library jar file ''{0}''**
Explanation	The message appears when Web Services Stack administration service is tyring to locate the axis2-kernel jar but the file does not exist or its location cannot be determined.
Action	Assert that the reported file exists and it is not locked by another process on the system.

WSSASE0009	**Cannot find library directory ''{0}''**
Explanation	The message appears when Web Services stack administration service is trying to locate the library directory with the jar files used by the Web Services Stack runtime.
Action	Assert that the reported path exists and it is a valid directory.

WSSCLE0001	**Deployment configuration file cannot be null.**
Explanation	A valid deployment configuration file was not specified or an empty value for deployment configuration file was provided.
Action	Specify a valid deployment configuration file.

WSSCLE0002	**[{0}] object cannot be null.**
Explanation	Deployment configurator is not initialized correctly and returns null.
Action	You must initialize the deployment configurator with a valid, non-empty deployment configuration file or valid deployment configuration properties.

WSSCLE0003	**The specified transport protocol [{0}] is not supported.**
Explanation	The transport protocol defined in the DeploymentConfigurator is not supported.
Action	Set HTTP or HTTPS transport in the DeploymentConfigurator.

WSSCLE0004	**Deployment configuration properties object cannot be null.**
Explanation	Valid deployment configuration properties are not specified or empty values for deployment configuration properties are provided.
Action	Specify valid, non-empty deployment configuration properties.

WSSCLE0005	**Problems while loading the deployment configuration from the file with the following location path: [{0}].**
Explanation	Deployment configuration cannot be loaded from the specified file.
Action	Check whether the provided configuration file is valid and whether its location path is correct.

WSSCLE0006	**"Servlet context" configuration is not found. The needed "servlet context" configuration is not set into the deployment configuration file.**
Explanation	The deployment configuration property that specifies the servlet context is not set into the deployment configuration file.
Action	Set the servlet deployment configuration property into the deployment configuration file.

WSSCLE0007	**"Host name" configuration is not found. The needed "host name" configuration is not set into the deployment configuration file.**
Explanation	The deployment configuration property hostname is not set into the deployment configuration file or the given value cannot be resolved.
Action	Set a valid, non-empty value for the hostname property into the deployment configuration file.

WSSCLE0008	**Unknown "host name" configuration found. You can find the needed "host name" configuration into the deployment configuration file.**
Explanation	The deployment configuration property hostname is set with a value that cannot be resolved.
Action	Set a valid, non-empty value for the hostname property into the deployment configuration file.

WSSCLE0009	**Invalid "port number" configuration found. You can find the needed "port number" configuration into the deployment configuration file.**
Explanation	In the deployment configuration property port is set an invalid value.
Action	Set a valid port property into the deployment configuration file.

WSSCLE0010	**Service name [{0}] for undeployment is invalid.**
Explanation	The Web service added for undeployment does not have a valid service name.
Action	Add a valid service name for the Web service that you want to undeploy.

WSSCLE0011	**Archive data unit must not be "null".**
Explanation	The archive file added for deployment is null or invalid.
Action	Add a valid archive file for deployment.

WSSCLE0012	**Failed to parse the configured [{0}] with value [{1}]. The default value [{2}] will be used.**
Explanation	The given value for maxConnectionsPerHost is invalid or cannot be processed. A default value will be used instead.
Action	Set a valid positive integer for the value of maxConnectionsPerHost. Otherwise, an alternative default value will be used.

WSSCLE0013	**Failed to parse the configured [{0}] with value [{1}]. The default value [{2}] will be used.**
Explanation	The given value for maxTotalConnections is invalid or cannot be processed. A default value will be used instead.
Action	Set a valid positive integer for the value of maxTotalConnections. Otherwise, an alternative default value will be used.

WSSCLE0014	**There are no archives added for deployment.**
Explanation	Web service archives are not added for deployment or undeployment.
Action	Add Web service archives for deployment or undeployment.

WSSCLE0015	**An error is thrown during the retrieval of the deployment result.**
Explanation	Deployment result cannot be retrieved because of an error while executing the remote operation.
Action	Check the connection to the server and the error log.

WSSCLE0016	**An error is thrown during the retrieval of the deployment result. The cause of the error is: {0}**
Explanation	Deployment result cannot be retrieved because of an error while executing the remote operation.
Action	Check the connection to the server and the error log.

WSSCLE0017	**The URI given for deployment is invalid. The passed value is [{0}].**
Explanation	The given URI for deployment is empty or the given value cannot be parsed as a URI reference.
Action	Provide a valid, non-empty URI for deployment.

WSSCLE0018	**The org.apache.commons.httpclient.HostConfiguration object passed is "null".**
Explanation	The HostConfiguration is empty.
Action	Check that the properties set for the host have valid, non-empty values and check the connection.

WSSCLE0019	**An error while deploying Web services occurs due to a problem while invoking the operation on the remote server . Reason: {0}.**
Explanation	An error occurs during the deployment. The services cannot be deployed.
Action	Check the error log for details.

WSSCLE0020	**An error while undeploying services occurs due to a problem while invoking the operation on the remote server. Reason: {0}.**
Explanation	An error occurs during undeployment. The services cannot be undeployed.
Action	Check the error log for details.

WSSCLE0021	**An error while listing the Web services occurs due to a problem while invoking the operation on the remote server. Reason: {0}.**
Explanation	An error occurs while listing services.
Action	Check the error log for details.

WSSCLE0022	**An error while listing properties occurs due to a problem while invoking the operation on the remote server. Reason: {0}.**
Explanation	An error occurs while listing properties.
Action	Check the error log for details.

WSSCLE0023	**The given keystore file {0} cannot be converted to a URL.**
Explanation	The given value for the keystore file cannot be parsed.
Action	Provide a valid, non-empty value for the keystore file and check its location path.

WSSCLE0024	**The given truststore file {0} cannot be converted to a URL.**
Explanation	The given value for the truststore file cannot be parsed.
Action	Provide a valid, non-empty value for the truststore file and check its location path.

WSSCLE0025	**The given proxy port with value [{0}] is invalid.**
Explanation	The value provided for a proxy port is not in the correct format.
Action	Provide a valid proxy port. If you do not want to use a proxy port do not set a value to it.

WSSCLE0030	**The WSDL definition cannot be null.**
Explanation	You have not specified a WSDL definition.
Action	Specify a valid, non-empty WSDL definition.

WSSCLE0031	**The WSDL URL cannot be null.**
Explanation	You have not specified a WSDL URL or you have provided a null or empty value.
Action	Specify a valid, non-empty WSDL URL.

WSSCLE0032	**The constructor is not found.**
Explanation	You did not provide a valid constructor for the class.
Action	Check the parameters you used. One or more of them are not suitable for the class. Use one of the available constructors for instantiating the class.

WSSCLE0033	**This action is not supported.**
Explanation	You are trying to use functionality that is not yet implemented.
Action	This action is not supported. Contact Software AG Global Support.

WSSCLE0034	**Service [{0}] is not found.**
Explanation	The service with the specified name [{0}] is not available.
Action	Check the service name.

WSSCLE0035	**Problem getting the WSDL, HTTP error code: {0}.**
Explanation	The operation for getting the WSDL encounters a problem.
Action	Check the causes for the HTTP status error code.

WSSCLE0036	**Cannot apply Web service client policy.**
Explanation	Policy cannot be applied to the description hierarchy.
Action	Check and validate the configuration and the policy.

WSSCLE0037	**Cannot locate the security configuration file "{0}" specified in the axis2 configuration under the key "securityConfigFile".**
Explanation	The specified configuration security in the axis2 configuration file cannot be found. The properties cannot be loaded.
Action	If you want to load security properties from a custom security configuration file it must be placed in the proper place. The file is searched as defined in axis2 configuration under the key "securityConfigFile". Check the path and the file name.

WSSCLE0038	**Cannot close security configuration file properly.**
Explanation	An error occurs during close operation of the security configuration file.
Action	None.

WSSCLE0039	**The WSDL file or WSDL definition cannot be found.**
Explanation	In order to extract policies, either the WSDL location or the WSDL4J definition object must be valid. They are both missing or empty.
Action	Provide either a WSDL file or a valid WSDL definition.

WSSCLE0040	**The class of the supplied callback must extend org.apache.axis2.client.async.Callback.**
Explanation	The class of the supplied callback does not extend org.apache.axis2.client.async.Callback. It cannot be used.
Action	Provide a valid callback class.

WSSCLE0041	**Failed to create a new client factory instance.**
Explanation	Client factory instance cannot be created because the class cannot be found or instantiated.
Action	Check the configuration and the validity of the used constructor.

WSSCLE0042	**Failed to create new client factory instance.**
Explanation	The supplied factory class name argument does not resolve to a valid com.softwareag.wsstack.client.api.AbstractClientFactory implementation. Client factory instance cannot be created because the class name argument is not a com.softwareag.wsstack.client.api.AbstractClientFactory implementation.
Action	Give a fully quialified name of the factory implementation class that is going to be instantiated.

WSSCLE0043	**Output stream cannot be null.**
Explanation	The given output stream is not initialized or empty.
Action	Give a valid, non-empty output stream.

WSSCLE0044	**Policy input stream cannot be null.**
Explanation	The given policy input stream is not initialized or empty.
Action	Give a valid, non-empty policy input stream.

WSSCLE0045	**Failed to close the WSDL input stream after reading.**
Explanation	The close operation for the used WSDL input stream did not finish successfully.
Action	None.

WSSCLE0046	**The provided content is too large to be buffered: {0} bytes.**
Explanation	The content exceeds the maximum possible value that can be buffered.
Action	Contact Software AG Global Support.

WSSCLE0047	**Cannot create DataObject for type {0}.**
Explanation	The requested type {0} cannot be identified.
Action	The used data type is not supported. Use an alternative data type.

WSSCLE0048	**Failed to create a wsstack client instance out of the following class: "{0}".**
Explanation	A client instance cannot be created because the class cannot be found or instantiated.
Action	Check whether the name of the used class is correct.

WSSCLE0049	**Failed to create a wsstack client instance. The class "{0}" is not a valid IWSBasicClient implementation.**
Explanation	The defined class exists but its usage is incorrect. The class "{0}" cannot be used for instantiating a wsstack client because it is not a valid IWSBasicClient implementation.
Action	Define a valid implementation class.

WSSCLE0050	**The services are not added for undeployment**
Explanation	Web service archives are not added for undeployment.
Action	Add service archives for undeployment.

WSSCLE0051	**The WS-Stack Java version is older than the Java version of the compiled archive "{0}".**
Explanation	You compiled your archive with a newer Java version than the available in WS-Stack. The service cannot be deployed successfully.
Action	Compile the archive with an older Java version. You can check the supported Java version in the validation page of WS-Stack listed as java.version.

WSSCLE0052	**There is a corrupted Java class file in the following archive: "{0}".**
Explanation	One or more of the class files in the archive is corrupted or it is not a valid Java class file.
Action	Check the classes in your archive. Compile them with a supported Java version in WS-Stack and deploy the archive again.

WSSCLE0053	**An error occurred while reading the archive "{0}"; the archive is corrupted or empty.**
Explanation	The archive that you want to deploy is not valid. It may be empty or cannot be read.
Action	Check and validate the content of archive "{0}". You may need to repack the content and deploy it again.

WSSCLE0054	**An error occurred while manipulating the archive "{0}". The archive is locked or another Input/Output related problem has occurred.**
Explanation	Other processes locked the archive and it cannot be processed or an Input/Output related problem has interrupted the execution of the command.
Action	Deploy the archive again.

WSSCLE0056	**Cannot configure client factory thread pool.**
Explanation	The error occurs when the WSStack client factory tries to configure a client instance to use a thread pool, and the client already has a thread pool set.
Action	Contact Software AG Global Support.

WSSCLE0057	**The specified attachment lifecycle manager instance is not valid.**
Explanation	The error occurs when the WSStack client factory configures a client instance to use an attachment lifecycle manager set by the user, and the specified lifecycle manager property is not a valid instance of org.apache.axiom.attachments.lifecycle.LifecycleManager.
Action	Specify a valid instance of "org.apache.axiom.attachments.lifecycle.LifecycleManager" under the client factory property key "attachmentsLifecycleManager".

WSSCLE0058	**Cannot configure attachment lifecycle manager for a client instance.**
Explanation	The error occurs when the Web Services Stack client factory configures a client instance to use a specific attachment lifecycle manager set by the user. Essentially, the error occurs when the attachment lifecycle parameter is locked.
Action	Contact Software AG Global Support.

WSSCLE0059	**The supplier object (an instance of {0}) is not a proxy instance.**
Explanation	The Web Services Stack client registry API provides a utility for retrieving the internal client configuration from a Web service proxy object. This error indicates that the tool is being used with a wrong proxy implementation (it is not a WSS compliant Web service client proxy).
Action	Modify your client implementation as the utility is used only with proxies created by the Web Services Stack registry API.

WSSCLI0000	**Unable to locate the default security configuration file "{0}".**
Explanation	The default security configuration file cannot be found and its properties are not loaded.
Action	If you want to load security properties from the default security configuration file, the file must be placed in the proper directory. The default security configuration file name is "wsclientsec.properties" and it must be either in the current working directory, or in "<REPOSITORY_DIRECTORY>/conf".

WSSCLI0026	**An XMLStreamException thrown.**
Explanation	The close operation for the used XMLStreamWriter did not finish successfully.
Action	None.

WSSCLW0027	**Unable to locate the default security configuration file: "{0}".**
Explanation	The default security configuration file cannot be found. Its properties are not loaded.
Action	If you want to load security properties from the default security configuration file you must put it in the proper place. The file is searched on the following location: "{0}".

WSSCLW0028	**The service policy is not set; cannot write service policy to the given stream.**
Explanation	The service policy is not set.
Action	To associate a policy, use one of the setPolicy methods first.

WSSCLW0029	**Overwriting an existing policy.**
Explanation	This is an existing policy and it is going to be overwritten.
Action	Do not use this method if you expect different behavior.

WSSCLW0055	**The parameters for max connections settings passed to configure the connection manager, associated with the HttpClient, caused a problem.**
Explanation	The default parameters will be used for the non-standard ones. \n MAX_HOST_CONNECTIONS parameter passed is "{0}". \n MAX_TOTAL_CONNECTIONS parameter passed is "{1}".
Action	None.

WSSCME0001	**Key value cannot be null or empty**
Explanation	The error appears when you prepare configuration properties parser of a security module. This implementation is used only in private constructors and therefore the error appears only if a severe implementation fault occurs.
Action	The error indicates a severe fault in the Web Services Stack implementation. If the error occurs, report it to the software development team.

WSSCME0002	**Rampart configuration element value cannot be null or empty**
Explanation	The message appears in an application program interface (API) method and reflects to an error in the implementation. The error appears when you update the security module configuration. It shows that you did not provide configuration to the update process.
Action	When you call a WSClientSecurityProperty#updateRampartConfigElement(OMElement, String) the implementation ensures that the given OMElement argument is not null or empty. Specify a valid entry for the OMElement.

WSSCME0003	**Invalid value is configured for time-to-live timestamp: "{0}"**
Explanation	The configured time-to-live value for the timestamp used by the security module is invalid. The system expects an integer as a configuration value.
Action	Security module configuration for timestamp time-to-live must be an integer.

WSSCME0004	**Invalid value is configured for max skew timestamp: "{0}"**
Explanation	The configured max skew value for the timestamp used by the security module is invalid. The system expects an integer as a configuration value.
Action	Security module configuration for timestamp max skew must be an integer.

WSSCME0005 **Property name cannot be null or empty**

Explanation You updated the security module configuration and did not specify a property for update.

Action The error indicates a severe fault in the Web Services Stack implementation. If the error occurs, report it to the software development team.

WSSCME0009 **Rampart configuration assertion update error**

Explanation The error occurs when xml serialization of an existing rampart configuration assertion fails. Prior to the update, the configuration assertion is serialized to stax stream and parsed with axiom. An invalid rampart configuration assertion can cause the error.

Action If you configure the rampart configuration assertion manually, an invalid configuration can cause the error. Use the Web Services Stack configuration properties instead of providing manual configuration.

WSSCME0019 **Failed to decode the basic authentication header.**

Explanation Web Services Stack security utility failed to decode the received HTTP Basic authentication header. The header should be encoded with base64 encoding. The error suggests that an illegal character (non-ASCII) was found within the header value.

Action Make sure the http client sends an HTTP basic authentication header properly encoded in base64 encoding.

WSSCMI0000 **Cannot recognize the security configuration key ''{0}''; the key is ignored.**

Explanation Rampart configuration updater searches through the client options and dynamic service parameters for keys that refer to the security module configuration. The message is logged when it encounters an unrecognized key. For example, a general purpose key that does not control Rampart specific configuration.

Action None.

WSSCMW0020 **Axis2 configuration file: '{0}' does not exist. Password change will be disabled.**

Explanation The axis2 configuration file is missing. This disables the password change functionality.

Action Contact Software AG global support.

WSSCMW0021 **Axis2 configuration file: '{0}' cannot be written. Password change will be disabled.**

Explanation The axis2 configuration file cannot be written. This disables the password change functionality.

Action Ensure that you can write in the axis2 configuration file.

WSSCMW0022	**Axis2 configuration URL '{0}' does not denote a valid file path. Password change will be disabled.**
Explanation	The path to the axis2 configuration file is invalid.
Action	Ensure that the URL to the axis2 configuration file is valid and that it is using file protocol.

WSSCMW0023	**AxisConfiguration instance does not have a valid configuration file URL set. Password change will be disabled.**
Explanation	AxisConfiguration is missing.
Action	Contact SoftwareAG global support.

WSSCMW0025	**Failed to close input stream to Axis2 configuration file: {0}**
Explanation	Internal error. Cannot change the axis2 configuration.
Action	Contact SoftwareAG global support.

WSSCMW0026	**Failed to close output stream to Axis2 configuration file: {0}**
Explanation	Internal error. Cannot change the axis2 configuration.
Action	Contact SoftwareAG global support.

WSSDAE0000	**Unsupported algorithm exception: {0}**
Explanation	A particular cryptographic algorithm is requested but is not available in the environment.
Action	Ensure that you have enabled unlimited strength JCE (Java Cryptographic Extension) on your machine. If you already have it enabled, contact Software AG Global Support.

WSSDAE0016	**Keystore exception: {0}**
Explanation	Keystore file can not be proccessed.
Action	Ensure that the keystore file is not corrupted and all required certificates are available in it.

WSSDAE0017	**Key management exception: {0}**
Explanation	Keystore file can not be proccessed.
Action	Ensure that the keystore file is not corrupted and all required certificates are available in it.

WSSDAE0018	**I/O error reading keystore/truststore file: {0}**
Explanation	Keystore file can not be proccessed.
Action	Ensure that the keystore file is available in the particular location.

WSSDIE0000	**Invalid or unsupported service scope set to AxisService: {0}.**
Explanation	The message appears when a service with an invalid scope is created or accessed. The following scopes are supported by Web Services Stack: application; transportsession; soapsession; request.
Action	Recreate your service using one of the following scopes: application; transportsession; soapsession; request.

WSSDIE0001	**Cannot create valid policy manager factory implementation.**
Explanation	The abstract policy manager factory fails to instantiate the default policy manager factory instance. The default factory implementation class is either not available or the user does not have permissions to access it.
Action	Ensure that the wsstack deployer-impl-[VERSION].jar is available on the classpath and the user who starts the java process has the proper permissions to access it.

WSSDIE0002	**Cannot create valid policy repository factory implementation.**
Explanation	The abstract policy repository factory fails to instantiate the default policy repository factory instance. The default factory implementation class is either not available or the user does not have permissions to access it.
Action	Ensure that the wsstack deployer-impl-[VERSION].jar is available on the classpath and that the user who starts the java process has the proper permissions to access it.

WSSDIE0003	**Cannot close a policy stream after parsing it.**
Explanation	Policy supplier cannot close the policy stream after parsing it.
Action	Ensure that the stream source is available and it is not locked by another process.

WSSDIE0004	**Cannot initialize the local policy repository; the axis configuration is not available.**
Explanation	Axis runtime configuration is not available to the policy repository. This means that the code is not executed in a properly initialized runtime.
Action	Ensure that you access the policy repository inside a properly initialized and started wsstack runtime.

WSSDIE0005	**Cannot create an invalid policies directory; the policy repository is null.**
Explanation	Invalid policies are automatically moved to a directory inside the policy repository. If the policy repository directory is not available, the invalid policies directory cannot be created.
Action	Ensure that the policy repository is properly initialized.

WSSDIE0006	**Duplicate policy ID; the policy file is moved to {0}.**
Explanation	The system detects that a policy is deployed with an ID that already exists in the policy repository. The new policy is moved to the invalid policies directory.
Action	When you deploy a policy, ensure that a policy with the same ID does not exist in the repository.

WSSDIE0007	**Cannot verify module support for a policy with the following ID: {0}.**
Explanation	The policy repository cannot verify whether a policy is supported (all assertions in it are recognized and there are modules deployed in the runtime that handle those assertions). The error occurs when the policy is invalid and/or does not contain any assertions.
Action	Ensure that the verified policy is valid and contains valid policy assertions.

WSSDIE0008	**Policy with the following key: {0} exists in the repository.**
Explanation	The policy repository contains a policy with the same ID as the policy that is deployed and the "updateIfPresent" flag is set to false.
Action	Ensure that the policy does not contain a policy with the same ID as the deployed one or set the flag "updateIfPresent" to true; that enables the update of the existing policy in the repository.

WSSDIE0009	**An error occurred during policy deployment.**
Explanation	An unexpected error occurs during policy deployment.
Action	Contact Software AG Global Support

WSSDIE0010	**The given policy does not contain any policy alternatives.**
Explanation	Cannot verify the policy against modules that support it because it does not contain any policy alternatives.
Action	Ensure that the deployed policy is valid and contains at least one policy alternative.

WSSDIE0011	**Cannot find a module to process the following assertion: {0}**
Explanation	There is no module deployed in the wsstack runtime that supports the given assertion.
Action	If the assertion requires additional processsing by a specific module, ensure that the corresponding module is deployed on the wsstack runtime.

WSSDIE0012	**The following module: {0}; cannot process the assertion: {1}.**
Explanation	Although the module is registered to handle a certain policy assertion namespace, the module does not support the particular assertion.
Action	Ensure that the policy and all of its assertions are valid and can be processed by the module.

WSSDIE0013	**Cannot find a policy with the specified ID: {0}.**
Explanation	You are searching for a policy ID that is not available in the policy repository.
Action	Ensure that the policy you use is deployed to the policy repository.

WSSDIE0014	**The policy XML does not contain an ID, or a name that can be associated with the ID.**
Explanation	When a policy is deployed to the policy repository, the repository attempts to parse it and get its ID, or its name if an ID is not available. The ID or name afterward is used as a key for retrieving the policy from the repository. If there is no ID or a name in the policy XML, the repository cannot deploy it.
Action	Ensure that the policy XML that is deployed in the repository has either a valid (not empty) ID or a valid (not empty) name so that it can be deployed.

WSSDIE0015	**Cannot find an element with the following name: {0} and the following namespace: {1} in the policy input stream; the policy document is invalid.**
Explanation	When a policy is deployed to the policy repository, the repository attempts to parse it and get its ID, or its name if an ID is not available. The ID or name is used afterward as a key for retrieving the policy from the repository. If there is no ID or a name in the policy XML the repository cannot deploy it.
Action	Ensure that the policy XML includes a name or a wsu:Id attribute declared.

WSSDIE0016	**An exception occurs while trying to parse the policy input stream.**
Explanation	The policy repository fails to parse the policy XML stream.
Action	Assert that the deployed policy source is a valid XML.

WSSDIE0017	**Cannot close policy file input stream.**
Explanation	The policy repository cannot close policy stream after reading it.
Action	Ensure that the policy source is available.

WSSDIE0018	**Cannot initialize local policy repository; the following repository path is incorrect: "{0}".**
Explanation	When the policy repository is initialized it tries to create its directory or use the one that exists. This error occurs when the repository path exists on the file system but it is not a directory.
Action	Ensure that the repository path is a directory on the file system or does not exist (so that the policy repository can create it). Alternatively, you can configure another repository path if the configured one cannot be used.

WSSDIE0019	**Cannot move the following invalid policy file: "{0}"; to the invalid policies directory.**
Explanation	The policy repository detects that an invalid policy is deployed. The repository cannot move the invalid policy into the invalid policies directory.
Action	Ensure that you deploy a valid XML policy.

WSSDIE0020	**Cannot load a policy file during policy repository initialization.**
Explanation	The policy repository fails to deploy a problematic policy file.
Action	Ensure that the policy files in the policy repository are valid XML policies.

WSSDIE0021	**Cannot initialize local policy repository; the following repository path: "{0}" does not exist and cannot be created.**
Explanation	While the policy repository is initialized it checks whether the repository directory exists and if it does not, the repository attempts to create it. This message shows that the creation of the directory fails. The policy repository is not functional.
Action	Ensure that either the repository directory exists or the user who starts the java processes is authorized to create it.

WSSDIE0022	**Cannot initialize a local policy repository; the following repository path is incorrect: "{0}".**
Explanation	When the policy repository is initialized it tries to determine the repository directory path but it fails. The reason is that the code is not invoked inside an initialized wsstack runtime or the wsstack repository directory is not available (in case if a URL configurator is used, for example).
Action	Ensure that either the wsstack repository directory is available or configure a specific directory to be used as a policy repository directory.

WSSDIE0023 **Cannot create a default policy supplier object; the following policy file: "{0}" is not a valid file.**

Explanation The file argument of the policy file that is deployed through a default policy supplier is either null or does not exist.

Action When you deploy a file through the default policy supplier, ensure that the policy file exists on the file system at the time it is detected by the policy repository.

WSSDIE0024 **The following policy file does not exist: "{0}".**

Explanation When a policy stream is retrieved through a default policy supplier instance, the policy file that is used by the supplier is not available.

Action Ensure that the file with the policy you try to access is available in the policy repository.

WSSDIE0025 **Policy repository location must not be null.**

Explanation Policy repository path is not available and therefore the default policy supplier cannot be created since it cannot store the policy in the repository.

Action Ensure that the policy repository is properly initialized.

WSSDIE0026 **Cannot copy a policy to the repository.**

Explanation When a policy stream is deployed through the default policy supplier, the supplier attempts to store the policy in repository directory. However, the copy procedure of the policy file to the repository directory fails.

Action Ensure that the user who starts the java process is authorized to write to the policy repository directory. Another reason for the error is that the stream is closed before policy file is copied.

WSSDIE0027 **An error occurred during policy deployment while trying to close the file output stream.**

Explanation A policy stream is deployed in the policy repository through a default policy supplier instance. While storing the stream to the policy repository directory, the supplier fails to close the original stream. However, the policy XML is successfully stored in the repository and the policy is effectively deployed.

Action None.

WSSDIE0028 **The following policy repository does not exist and cannot be created: {0}.**

Explanation The policy repository directory does not exist and cannot be created.

Action Ensure that the policy repository is properly initialized. Ensure that the user who starts the java process is authorized to write in the specified repository directory.

WSSDIE0029	**Failed to delete a policy file.**
Explanation	A policy file deployed through a default policy supplier cannot be deleted.
Action	Ensure that the policy file is not locked by another process.

WSSDIE0138	**Cannot assign a policy to a service; a policy with the following ID cannot be found: "{0}".**
Explanation	The policy manager is requested to assign a policy to a certain service but the policy denoted by the supplied policy ID cannot be found in the policy repository.
Action	Ensure that the policy you attach exists in the policy repository.

WSSDIE0144	**Unsupported IDynamicDescription implementation; the WSPolicyManager implementation works only with dynamic description instances of type {0} but {1} is available.**
Explanation	Encountered an unrecognized dynamic description instance. Web Services Stack policy manager is intended to work with a specific implementation of the underlying dynamic description.
Action	If you use the default Web Services Stack policy manager, implement your dynamic assets so that they extend the default implementation of the deployer API.

WSSDIE0158	**Service {0} does not use a standard deployment classloader; the resource jar is not appended to the classpath of the classloader.**
Explanation	Service resource jar cannot be added to the service classpath. The service class loader is not an instance of org.apache.axis2.deployment.DeploymentClassLoader.
Action	Contact Software AG Global Support.

WSSDIE0162	**The method can be called on a deployed unit only.**
Explanation	The boolean isEngaged(String, boolean) method is called on an AxisDescription instance that has not been deployed on the Web Services Stack runtime yet. Therefore, it has no AxisConfiguration instance associated with it.
Action	Assert that the isEngaged module check is invoked on the deployed instance.

WSSDIE0164	**Web Services Stack policy manager failed to update or remove policy from associated services when handling a "policy file deleted" event fired by the policy repository due to: "{0}".**
Explanation	By default, the Web Services Stack policy manager is registered as a policy repository listener so it is notified when the policy repository detects that a policy file has been deleted. When such an event is received the policy manager attempts to remove the deleted policy from any associated attachment points (services, operations, or messages) and in the course of these actions the error occurs.
Action	This is an internal error. Contact Software AG Global Support.

WSSDIE0165	**Web Services Stack policy manager fails to update or remove policy from associated services when handling a "policy file updated" event fired by the policy repository due to: "{0}".**
Explanation	By default, the Web Services Stack policy manager is registered as a policy repository listener so it is notified when the policy repository detects that a policy file has been updated. When such an event is received the policy manager attempts to remove the policy from any associated attachment points (services, operations, or messages) in case the new policy has a different ID. If the new policy has the same ID as the previously deployed one (true update) it tries to refresh the policy attached to the respective subjects. In the course of these actions the error occurs.
Action	This is an internal error. Contact Software AG Global Support.

WSSDIE0166	**Cannot deploy policy file "{0}" as the policy is invalid. A file with name "{0}" already exists in the invalid policies directory. The existing file is overwritten.**
Explanation	You try to deploy more than once an invalid policy. A policy file with the same name already exists in the directory, in which invalid policies are maintained. The existing file is overwritten with the new one (the file is updated).
Action	Check the policy you want to deploy.

WSSDIE0167	**The policy ID or name is invalid. The policy is not deployed.**
Explanation	The policy ID or name, if available, cannot contain whitespace characters inside. If whitespace characters are found inside, the policy is considered invalid and the policy file is moved to the invalid folder.
Action	Check the policy ID or name for whitespace characters and remove them, if any.

WSSDIE0168	**Cannot deploy policy "{0}"; the policy is invalid and cannot be processed.**
Explanation	There is a problem while processing the policy. The policy file is corrupted or the XML is invalid.
Action	Check and validate the policy XML, check for typographical errors, and so on. Finally, deploy the policy again.

WSSDIE0169	**Failed to roll back disengage of the following module: {0}.**
Explanation	An error occurs while disengaging modules, the system attempts to re-engage them but the corresponding module fails.
Action	Contact Software AG Global Support.

WSSDIE0170	**Failed to disengage module {0}. Reason: {1}**
Explanation	While removing policy components for the current DynamicDescription instance, the system attempts to disengage a referenced module but it fails.
Action	Contact Software AG Global Support.

WSSDIE0171	**Exceptions must not be generated when skipping module disengagement.**
Explanation	Policy cleanup must not generate any exceptions if module disengagement argument is not set.
Action	Contact Software AG Global Support.

WSSDIE0172	**Cannot refresh services after the "{0}" policy is updated due to the following: "{1}".**
Explanation	Web Services Stack policy manager is automatically updating policy subjects upon a policy update with a certain ID. The update fails when applying the new policy to the subjects.
Action	Contact Software AG Global Support.

WSSDIE0173	**Failed to create a dynamic deployer instance.**
Explanation	The exception occurs while trying to initialize the default policy manager instance and it fails to initialize the dynamic deployer. This happens when no valid Axis configuration is found.
Action	Ensure that the code is running in properly started and initialized Web Services Stack runtime.

WSSDIE0174	**Cannot clean policy of the following Web service: "{0}".**
Explanation	The policy manager failed to remove policies for the given Web service. Generally, the exception is generated when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
Action	Redeploy your Web service.

WSSDIE0175	**Cannot clean policy of the Web service "{0}" operation "{1}".**
Explanation	The policy manager failed to clean the policy on the given operation of the given Web service. Generally, the exception is thrown only when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
Action	Redeploy your Web service.

WSSDIE0176	**Cannot clean message policy for service "{0}" operation "{1}".**
Explanation	The policy manager failed to clean the message policy on the given operation of the given service. Generally, the exception is thrown only when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
Action	Redeploy your Web service.

WSSDIE0178	**Failed to retrieve the following service group after persisting and redeploying it: "{0}".**
Explanation	The Dynamic deployer API was used to persist a service group but after redeploying the service group could not be found in Web Services Stack runtime. A possible cause for the error is a problem during the deployment.
Action	Ensure that the service group file or directory is not locked, and the current user has the credentials to write to it. Redeploy your Web service manually.

WSSDIE0179	**Exception occurs while trying to obtain policy manager instance and the policy manager cannot be notified about redeployed Web services.**
Explanation	When a service is persisted the Web Services Stack runtime undeploys and redeploys it again. That makes any references kept to the previous Web service invalid. Since the policy manager keeps associations between policies and attachment points (such as Web services) it needs to be notified to synchronize its cache.
Action	The system is automatically recovered but the policy manager's cached association for the updated Web services are lost.

WSSDIE0180	**Failed to retrieve the following Web service "{0}" after persisting and redeploying it.**
Explanation	The Dynamic deployer API was used to persist a Web service but after redeploying the Web service cannot be found in the Web Services Stack runtime. A possible cause for the error is a problem during the deployment.
Action	Ensure that the Web service file or directory is not locked and the current user has permissions to write to it. Redeploy your Web service manually.

WSSDIE0181	**Web Services Stack policy engine failed to parse the deployed policy.**
Explanation	An exception occurred while the policy engine was processing a freshly deployed policy. Most probably the policy xml is invalid.
Action	Correct the policy xml and redeploy it.

WSSDIE0184	**Security exception during fetch of class field.**
Explanation	This is an internal error caused by an API inconsistency.
Action	Contact SoftwareAG global support.

WSSDIE0185	**Unreachable field with name {0} in class {1}**
Explanation	This is an internal error caused by an API inconsistency.
Action	Contact SoftwareAG global support.

WSSDIE0186	**Illegal argument: engageModules passed to method.**
Explanation	This is an internal error caused by an API inconsistency.
Action	Contact SoftwareAG global support.

WSSDIE0187	**Illegal access to field with name {0} in class {1}**
Explanation	This is an internal error caused by an API inconsistency.
Action	Contact SoftwareAG global support.

WSSDIE0189	**Failed to read the policy file.**
Explanation	The policy file could not be read or is invalid.
Action	Verify that your policy file is compliant with WS Security specification.

WSSDIW0163	**Modules cannot be engaged at the following binding hierarchy - Endpoint (port), Binding, Binding operation, Binding Message.**
Explanation	Axis2 does not support engaging modules at the listed subjects and respectfully calling isEngaged on those axis objects throws an UnsupportedOperationException.
Action	Invalid invocation. This method cannot be invoked on IDynamicPort, IDynamicBinding, IDynamicBindingOperation, or IDynamicBindingMessage.

WSSDIW0177	**Parent service group is not found for the following Web service: ''{0}''.**
Explanation	The dynamic deployer could not find the parent service group of the given Web service.
Action	Ensure that the Web service is properly deployed or redeploy it.

WSSDIW0190	**Expected dialect "{0}" but found "{1}" ,cannot proceed.**
Explanation	Found unexpected dialect in the specified request.
Action	Set proper dialect. If you are unable to do so, contact Software AG global support.

WSSDIW0191	**Null or empty policy identifier given, cannot proceed.**
Explanation	Policy identifier is invalid.
Action	Set proper identifier. If you are unable to do so, contact Software AG global support.

WSSDSE0000	**In order to deploy JAX-WS services you must have a JAX-WS Deployer configured in your axis2.xml.**
Explanation	The <deployer extension=".jar" directory="servicejars"class="org.apache.axis2.jaxws.framework.JAXWSDeployer"/> line in your axis2.xml is commented or missing.
Action	Uncomment the <deployer extension=".jar" directory="servicejars"class="org.apache.axis2.jaxws.framework.JAXWSDeployer"/> line in the axis2.xml, or add it if it is missing.

WSSDSE0011	**An error occurs while trying to remove the following security provider: "{0}".**
Explanation	Before the SAGAdminServlet is destroyed, it checks whether the BouncyCastle and JuiCE are added to the java security providers and whether they are loaded by the current web application classloader. If it is true, the servlet tries to remove them, as they are not available to other web applications. This error occurs when the servlet tries to cleanup the BouncyCastle and JuiCE providers from the list.
Action	Contact Software AG Global Support

WSSDSE0012	**DeployServlet requires the following instance in the servlet context but cannot find it: "{0}".**
Explanation	An Axis2 "org.apache.axis2.deployment.DeploymentEngine" instance has to be available in Web Services Stack DeployServlet's servlet context under the DEPLOYER servlet context attribute but such an attribute is not found.
Action	The reason for the error is that Web Services Stack Administration servlet fails to initialize. Make sure that the servlet is properly initialized.

WSSDSW0013	**Cannot find the axi2.xml file location in the known locations.**
Explanation	The axis2 configuration file is missing.
Action	Make sure the axis2 configuration file is the proper location.

WSSDSW0014	**Cannot find the axi2.xml location due to an error.**
Explanation	The axis2 configuration could not be obtained.
Action	Contact SoftwareAG global support.

WSSJCE0012	**Module "{0}" is engaged but configuration for a JAX-WS handler-chain was not found.**
Explanation	The module is engaged, but it does not contain any JAX-WS handlers configured into the chain.
Action	Inspect the engaged module if it contains the expected JAX-WS handlers.

WSSJCE0015	**The JAX-WS handler chain cannot be loaded.**
Explanation	The JAX-WS handler-chain descriptor (XML) file is not correct or the handler instances configured in it cannot be loaded.
Action	Inspect and correct the JAX-WS handler-chain descriptor (XML) file.

WSSJCE0018	**An incorrect property value is set for the JAX-WS handler-chain.**
Explanation	The JAX-WS handler-chain descriptor (XML) file has an incorrect property value set for a JAX-WS handler.
Action	Check and correct the JAX-WS handler-chain descriptor (XML) file.

WSSJCE0019	**An error occurs in the JAX-WS handler-chain execution.**
Explanation	At the invocation of JAX-WS in/out flow, an exception is thrown while processing the chain.
Action	For more information about the failure, see the AxisFault response message. Check the JAX-WS chain configuration.

WSSJCW0001	**A handler class of the handler chain cannot be found.**
Explanation	Classes are missing for some handler instances configured into the handler-chain descriptor (XML) file.
Action	Check that the handler classes configured into the handler-chain descriptor (XML) file are available into the jar library (class-path).

WSSJCW0002	**A handler of the handler chain cannot be instantiated.**
Explanation	A class of the handler available into the classpath is not a standard one.
Action	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.

WSSJCW0004	**The configuration of a class from the handler chain is incorrect.**
Explanation	A class of the handler available into the classpath is not a standard one.
Action	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.

WSSJCW0005	**An error occurs while loading the JAX-WS handler chain.**
Explanation	A class of the handler available into the classpath is not a standard one.
Action	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.

WSSJCW0009	**An error occurs while executing PreDestroy methods of the JAX-WS handlers. {0}**
Explanation	A JAX-WS handler executed into the chain, throws an exception while destroying it after being used.
Action	Check that the handler class available into the jar library or its XML configuration file were not modified improperly.

WSSJCW0011	**An error occurs while executing PostConstruct methods of the JAX-WS handlers. {0}**
Explanation	A JAX-WS handler executed into the chain throws an exception during its initialization.
Action	Check that the handler jar archive or its XML configuration file were not modified improperly.

WSSJHE0003	**An error occurs during the completion of a JAX-WS handler.**
Explanation	An error occurs into the flow when closing a JAX-WS handler.
Action	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.

WSSJHE0004	**JAX-WS handler PreDestroy method failed.**
Explanation	An error occurs when invoking a JAX-WS handler PreDestroy method.
Action	Check whether the Handler class that is available into the jar library or its XML configuration file are not modified improperly.

WSSJHE0008	**A JAX-WS handler failed.**
Explanation	An error occurs when invoking a JAX-WS handler.
Action	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.

WSSJHE0010	**A JAX-WS handler instantiation failed for the following classname: {0}.**
Explanation	An error occurs during JAX-WS handler instantiation.
Action	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.

WSSJHE0011	**The JAX-WS handler {1} is not type {0}.**
Explanation	An error occurs during JAX-WS handler invocation.
Action	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.

WSSJNE0000	**Could not read the value, Illegal state exception.**
Explanation	The provided JSON data is invalid.
Action	Make sure the provided JSON data is valid.

WSSJNE0001	**IO error while reading JSON stream.**
Explanation	An error during reading/writing JSON data.
Action	Check your connectivity and try again.

WSSJNE0004	**Could not load configured json type converter ''{0}''.**
Explanation	Missing JSON type converter class.
Action	Make sure that the service archive (aar file) contains a configured JSON type converter class.

WSSJNE0005	**Could not instantiate configured json type converter ''{0}''.**
Explanation	Invalid converter class definition.
Action	Check the converter class definition.

WSSJNE0006	**Could not access configured json type converter class ''{0}''.**
Explanation	Invalid converter class definition.
Action	Check the converter class definition. Make your class/default constructor public.

WSSJNE0007	**Could not load configured json type converter ''{0}''.**
Explanation	Missing JSON type converter class.
Action	Make sure that the service archive (aar file) contains a configured JSON type converter class.

WSSJNE0008	**Configured json type converter class ''{0}'' cannot be cast to type converter interface class ''{1}''.**
Explanation	Invalid converter class definition.
Action	Check the converter class definition and ensure it implements the type converter interface.

WSSJNE0014	**Failed to configure type converter, the JSON formatter will use the default type converter. Reason: {0}**
Explanation	Could not load the configured custom JSON type converter.
Action	Ensure the configured custom JSON type converter class is valid and available on the classpath.

WSSJNW0010	**Could not load configured json type converter ''{0}'' using class loader of service ''{1}'', falling back to Web Services Stack class loader.**
Explanation	The configured JSON type converter could not be loaded from service archive (aar file) and Web Services Stack will attempt to load it using Web Services Stack class loader.

WSSJNW0011	**{0} - Ignoring ''{1}'' parameter with null value.**
Explanation	The configured JSON type converter parameter has a null value.
Action	Check the configured 'json.type.converter' parameter definition and ensure it specifies a non-null value.

WSSJNW0012	**Unable to obtain current element class name due to {0}**
Explanation	Current class name element could not be obtained.
Action	Contact SoftwareAG global support.

WSSJNW0013	**{0} - Ignoring "{1}" parameter with a non-String value ({2})**
Explanation	The configured JSON type converter parameter has a non-String value.
Action	Check the configured 'json.type.converter' parameter definition and ensure it specifies a String value.

WSSMRE0003	**The service does not define adapter class parameter: "{0}".**
Explanation	When com.softwareag.wsstack.messagereceivers.AdapterMessageReceiver is invoked, it tries to find a parameter named adapter in the currently invoked service. The adapter parameter denotes a name of a class that implements the com.softwareag.wsstack.adapter.api.Adapter interface. The message receiver attempts to instantiate and execute the configured adapter.
Action	Add an adapter parameter to your service definition (in your services.xml file). As a value to the parameter, set the required adapter implementation class.

WSSMRE0004	**The configured adapter class is invalid: "{0}"**
Explanation	When com.softwareag.wsstack.messagereceivers.AdapterMessageReceiver is invoked, it tries to find a parameter named adapter in the currently invoked service. The adapter parameter denotes a name of a class that implements the com.softwareag.wsstack.adapter.api.Adapter interface. The message receiver attempts to instantiate and execute the configured adapter.
Action	Specify a valid adapter class name as a value to the adapter parameter in your service definition.

WSSOGE0000	**Failed to add service {0}**
Explanation	Failed to add service.
Action	Contact SoftwareAG global support.

WSSOGE0001	**Failed to handle service modification {0}**
Explanation	Failed to handle service modification.
Action	Contact SoftwareAG global support.

WSSOGE0002	**Failed to handle service removal {0}**
Explanation	Failed to handle service removal.
Action	Contact SoftwareAG global support.

WSSOGE0003	**Failed to add service {0}**
Explanation	Internal error. Failed to add service.
Action	Contact SoftwareAG global support.

WSSOGE0004	**Failed to handle service removal {0}**
Explanation	Internal error. Failed to handle service removal.
Action	Contact SoftwareAG global support.

WSSOGE0010	**The specified {0} property points to a non-existing or non-readable file. Using default.**
Explanation	The main axis2.xml configuration file is missing.
Action	Make sure that the configured axis2.xml file is in the correct location and is readable.

WSSOGE0013	**Cannot set axi2.xml URL as axisConfig parameter.**
Explanation	Internal error. Cannot set the axi2.xml URL as an axisConfig parameter.
Action	Contact SoftwareAG global support.

WSSOGE0016	**Error during module shutdown: {0}**
Explanation	Internal error. The error occured during module shutdown.
Action	Contact SoftwareAG global support.

WSSOGE0021	**Failed to remove group {0}**
Explanation	Internal error. Failed to remove group.
Action	Contact Software AG global support.

WSSOGE0023	**Failed to resolve relative resource: {0} from bundle {1}**
Explanation	Internal error. Failed to resolve resource from a bundle.
Action	Contact Software AG global support.

WSSOGE0025	**Failed to resolve relative resource {0} from bundle {1}**
Explanation	Internal error. Failed to resolve resource from a bundle.
Action	Contact Software AG global support.

WSSOGE0031	**AxisConfigurator instance (class '{0}') does not derive from {1}, Web Services Stack Deploy Servlet will not be functional.**
Explanation	Provided axis configurator is not aware of the axis deploy engine.
Action	Contact Software AG global support.

WSSPWE0000	**UsernameToken authentication failed.**
Explanation	Invalid or empty password provided.
Action	Provide valid credentials.

WSSPWE0001	**Unknown password callback type: {0}.**
Explanation	Invalid usage of the password callback handler. Valid usage is for signing, decryption, and username password validation.
Action	Provide a valid usage of the callback handler.

WSSPWE0004	**The system cannot load the LDAP configuration for the password callback handler: {0}.**
Explanation	The password callback handler needs LDAP configuration. If it is not configured, the default LDAP configuration ldap.properties is used. LDAP configuration file cannot be loaded.
Action	Provide valid LDAP configuration.

WSSPWE0008	**Invalid LDAP configuration for the password callback handler.**
Explanation	One or more of the required LDAP configuration properties are not available in the LDAP configuration.
Action	Provide all required LDAP configuration properties.

WSSPWE0009	**UsernameToken authentication failed.**
Explanation	Invalid or empty password provided. The user cannot be authenticated.
Action	Provide valid, non-empty values for username and password.

WSSPWE0010	**Cannot recognize the following user ID: ''{0}''.**
Explanation	Invalid or empty username, or certificate alias provided.
Action	Check the spelling and provide a valid, non-empty value for username, or certificate alias (depending on the use case).

WSSPWE0012	**System cannot load the password callback handler configuration file: {0}.**
Explanation	The password callback handler configuration file is not found and cannot be loaded.
Action	Check if the configuration file exists and if the path to the file is correct.

WSSPWE0013	**Cannot convert the configuration from a stream to an OMElement: {0}.**
Explanation	A problem occurs while converting the configuration file content to an OMElement.
Action	Check and validate the XML format of the configuration file.

WSSRME0000	**Exception on callback.**
Explanation	Internal error. Failed to receive message on callback.
Action	Contact Software AG global support.

WSSRME0001	**Exception on callback.**
Explanation	Internal error. Failed to receive message on callback.
Action	Contact Software AG global support.

WSSTLW0012	**Password must comply with 3 out of the following 4 rules: at least 1 uppercase character, 1 lowercase character, 1 digit, and 1 special character. Minimum password length is 10 characters.**

WSSTRE0001	**Cannot close the input stream of the file; the file absolute path value is [{0}]. The exception message is: {1}.**
Explanation	Cannot close a file input stream or cannot release system resources associated with the stream.
Action	Check the file state. For example, it can be locked by another process.

WSSTRE0002	**The used key cannot be "null".**
Explanation	The key that is used for a property is null.
Action	Contact Software AG Global Support.

WSSTRE0003	**Cannot close an input/output stream of type [{0}]; the exception message is: {1}**
Explanation	There is an exception during input/output stream closure.
Action	Contact Software AG Global Support.

WSSTRE0004	**There is an error while manipulating an input/output stream in use.**
Explanation	There is an exception during input/output stream processing.
Action	Contact Software AG Global Support.

WSSTRE0005	**The repository listener is not initialized.**
Explanation	The repository listener is not initialized.
Action	Contact Software AG Global Support.

WSSTRE0006	**The following operation is not supported: [{0}].**
Explanation	Non existing operation requested.
Action	Check that an operation with the specified name exists. Contact Software AG Global Support.

WSSTRE0007	**Cannot delete the file with the following file path: [{0}].**
Explanation	There is a problem deleting the file.
Action	Check that the file exists and it is not locked. Check that you have sufficient permissions to delete the file.

WSSTRE0008	**Cannot create a directory in the following location: [{0}].**
Explanation	There is a problem while creating a "services" directory.
Action	Contact Software AG Global Support.

WSSTRE0009	**The following Web service element cannot be null: {0}.**
Explanation	The Web service element is null.
Action	Check the content structure of the Web service that is deployed dynamically.

WSSTRE0010	**The name of the Web service client {0} must not be null or empty.**
Explanation	The name of the Web service client that is instantiated is null or empty.
Action	Check the Web service client implementation.

WSSTRE0011	**Cannot delete the following directory: [{0}].**
Explanation	There is a problem while deleting a Web service directory.
Action	Check that the Web service directory is not locked and check that you have sufficient permissions to delete the directory.

WSSXTE0000	**{0}: An XML document that is empty, invalid or does not exist.**
Explanation	The document is empty or invalid.
Action	Provide a valid, non-empty XML document.

WSSXTE0013	**Unexpected element found after the SOAP Body element:** "{0}"
Explanation	Web Services Stack is processing an invalid message. The sent message contains an unexpected element in the SOAP Envelope after the SOAP Body element. A SOAP Envelope is expected to contains only an optional SOAP Header element followed by one SOAP Body element.
Action	Inform the web service conversation partner that they are generating invalid web service messages.

WSSXTE0014	**Unexpected element found after the SOAP envelope has been consumed:** "{0}"
Explanation	Web Services Stack is processing an invalid message. The sent message contains an unexpected element after the already consumed SOAP Envelope. A web service message is expected to contain a single SOAP Envelope element.
Action	Inform the web service conversation partner that they are generating invalid web service messages.

WSSXTE0016	**Failed to marshall response object.**
Explanation	Internal error. Failed to marshall response object.
Action	Contact Software AG global support.

WSSXTE0017	**Could not close piped output stream.**
Explanation	Internal error. Could not close piped output stream.
Action	Contact Software AG global support.

WSSXTE0018	**Invalid timeout value format: not a number.**
Explanation	Illegal number for timeout config parameter.
Action	Check timeout parameters: SO_TIMEOUT, CONNECTION_TIMEOUT

WSSXTW0019	**Could not obtain inbound message context.**
Explanation	The obtained axis2 message context is invalid.
Action	Contact SoftwareAG global support.

30 Universal Messaging Messages

NUMSPME0001	**Unexpected exception encountered.**
Explanation	An unexpected exception occurred.
Action	Check the detailed error message. Contact Software AG Global Support for further assistance.

NUMSPME0002	**An error occurred while identifying the inventory components of Universal Messaging.**
Explanation	Unexpected exception occurred while identifying the inventory components of Universal Messaging.
Action	Please contact webMethods Administrator.

NUMSPME0003	**An error occurred while retrieving the interfaces configured for Universal Messaging.**
Explanation	Unable to read the adapters.nst file.
Action	Please contact webMethods Administrator.

NUMSPME0005	**Invalid configuration instance. {0} entered.**
Explanation	Format of the port configuration is wrong.
Action	Contact your webMethods product administrator and re-configure the port settings.

NUMSPME0006	**Invalid configuration object. {0} expected.**
Explanation	Format of the port configuration is wrong.
Action	Contact your webMethods product administrator and re-configure the port settings.

NUMSPME0007	**Invalid input for the port alias.**
Explanation	The input for the port alias is not valid.
Action	Input a valid port alias or keep the port alias field empty.

NUMSPME0008	**SSL configuration cannot be set for a non-SSL port.**
Explanation	SSL configuration can be set only for the SSL ports.
Action	Remove the SSL configuration from the non-SSL port and try again.

NUMSPME0009	**The configuration instance ID argument is missing.**
Explanation	The configuration instance ID is required to load the port configuration.
Action	Specify the configuration instance ID.

NUMSPME0010	**No port matches the provided configuration instance ID.**
Explanation	The provided configuration instance ID is incorrect.
Action	Verify the configuration instance ID provided for configuration update.

NUMSPME0011	**Protocol entered for the interface is incorrect.**
Explanation	The protocol can only be NSP, NHP, NSPS, or NHPS.
Action	Verify the protocol value entered for the port.

NUMSPME0012E	**Unable to connect to the UM realm server.**
Explanation	Unable to connect to the UM realm server. None of the interfaces can connect to the realm server.
Action	Verify if at least one interface is available for the relam server.

NUMSPME0013	**At least one port must be specified.**
Explanation	Port configuration is not specified in the port settings input.
Action	Add the port configuration to the port settings input.

NUMSPME0014	**Error occurred while saving the port configurations.**
Explanation	Unable to save the port configurations.
Action	See the detailed error message and verify the cause of failure.

NUMSPME0015	**Only one set of port settings is allowed.**
Explanation	More than one set of port settings are passed in the input.
Action	Configure only one set of port setting.

NUMSPME0016	**Universal Messaging port number must not be changed.**
Explanation	Attempted to change the Universal Messaging port number.
Action	Do not modify the port number.

NUMSPME0017	**Universal Messaging Server port type must be STANDARD.**
Explanation	Universal Messaging Server port type is not STANDARD.
Action	Set the Universal Messaging Server port type as STANDARD.

NUMSPME0018	**Universal Messaging Server protocol must be NSP, NHP, NHPS, or NSPS.**
Explanation	Universal Messaging Server protocol is not valid.
Action	Set NSP, NHP, NSPS, or NHPS as the Universal Messaging port protocol.

NUMSPME0019	**Do not modify the BindAddress.**
Explanation	Attempted to modify the BindAddress.
Action	Do not modify the BindAddress in the input.

NUMSPME0020	**Invalid argument provided.**
Explanation	Invalid value provided for argument. Port cannot be configured.
Action	Verify and provide correct value for all the arguments. Refer to the Universal Messaging documentaion for more information about argument values.

NUMSPME0021	**IPAccess is not supported by Universal Messaging.**
Explanation	IPAccess is set, but Universal Messaging does not support IPAccess.
Action	Do not set the IPAccess.

NUMSPME0022	**KeepAliveTimeout is not supported by Universal Messaging.**
Explanation	KeepAliveTimeout is set, but Universal Messaging does not support KeepAliveTimeout.
Action	Do not set the KeepAliveTimeout.

NUMSPME0023	**ThreadPool is not supported by Universal Messaging.**
Explanation	ThreadPool is set, but Universal Messaging does not support ThreadPool.
Action	Do not set the ThreadPool.

NUMSPME0024	**URLAccess is not supported by Universal Messaging.**
Explanation	URLAccess is set, but Universal Messaging does not support URLAccess.
Action	Do not set the URLAccess.

NUMSPME0025	**Keystore definition must not be null.**
Explanation	Keystore definition for SSL in the port configuration input is set to Null.
Action	Set a valid value for the keystore definition.

NUMSPME0026	**Truststore definition must not be null.**
Explanation	Truststore definition for SSL in the port configuration input is set to Null.
Action	Set a valid value for the truststore definition.

NUMSPME0027	**Cannot delete this interface. At least one interface is required for a Universal Messaging server.**
Explanation	At least one interface must exist for a Universal Messaging server.
Action	Make sure you retain at least one interface for a Universal Messaging server.

NUMSPME0028	**Unexpected error occurred while fetching the monitoring data.**
Explanation	An internal error occurred while fetching the monitoring data.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0029	**The primary port cannot be stopped.**
Explanation	The primary port of a ream server cannot be stopped.
Action	Do not attempt to stop the primary port of a ream server.

NUMSPME0030	**Keystore definition type can only be JKS.**
Explanation	Keystore definition type can only be JKS.
Action	Specify JKS in the keystore type.

NUMSPME0031	**Truststore definition type can only be JKS.**
Explanation	Truststore definition type can only be JKS.
Action	Specify JKS for the Truststore type.

NUMSPME0032	**Client Authentication cannot be set to REQUEST_CERTIFICATE.**
Explanation	Only values supported for client authentication is REQUIRE_CERTIFICATE or NONE.
Action	Use either REQUIRE_CERTIFICATE or NONE.

NUMSPME0033	**Universal Messaging instance management operation failed.**
Explanation	An error occurred during the instance management operation.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0034	**Universal Messaging instance creation operation failed for the instance with name {0}.**
Explanation	An error occurred while creating the Universal Messaging instance.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0035	**Universal Messaging instance deletion operation failed for the instance with name {0}.**
Explanation	An error occurred while deleting the Universal Messaging instance.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0036	**Universal Messaging instance management read operation failed for the runtime component {0}.**
Explanation	An error occurred while reading the Universal Messaging instance.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0037	**Universal Messaging instance management does not support the operation called on the runtime component {0}.**
Explanation	The specified operation is not supported by Universal Messaging instance management.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0038	**Universal Messaging instance management operation was called with an invalid server name for the runtime component {0}.**
Explanation	Universal Messaging instance name specified for the operation is invalid or empty.
Action	Provide a valid Universal Messaging instance name.

NUMSPME0039	**Universal Messaging instance management operation was called with an empty server name for product-id {0}.**
Explanation	Universal Messaging instance name specified for the operation is invalid or empty.
Action	Provide a valid Universal Messaging instance name.

NUMSPME0040	**Universal Messaging instance management operation was called with an empty port for product-id {0}.**
Explanation	The port specified for the Universal Messaging instance management operation is invalid or empty.
Action	Provide a valid port number for the Universal Messaging instance.

NUMSPME0041	**Universal Messaging instance name, {0}, already exists.**
Explanation	The Universal Messaging instance name specified already exists.
Action	Choose a Universal Messaging instance name, which is not already present.

NUMSPME0042	**Universal Messaging instance management operation was called with the wrong product id, {0}.**
Explanation	An error occurred during the instance management operation.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0043	**Universal Messaging user repository file does not exist.**
Explanation	The new repository file for the Universal Messaging users does not exist on the file system.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0044	**Universal Messaging cluster update operation failed for the instance with name {0}.**
Explanation	An error occurred while updating the cluster details of the Universal Messaging instance.
Action	Check the detailed error message. Contact Software AG Global Support for further assistance.

NUMSPME0045	**Universal Messaging cluster management operation failed.**
Explanation	An error occurred during the cluster management operation.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0046	**Universal Messaging cluster get operation failed for the instance with name {0}.**
Explanation	An error occurred while getting the cluster details of the Universal Messaging instance.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0047	**The configuration instance ID argument is missing.**
Explanation	The configuration instance ID is required to load the cluster configuration.
Action	Specify the configuration instance ID.

NUMSPME0049	**Universal Messaging cluster operation failed. Minimum of two Universal Messaging server instances are required in the cluster.**
Explanation	Minimum of two Universal Messaging server instances are required in the cluster.
Action	Make sure the cluster has a minimum of two Universal Messaging server instances. Contact Software AG Global Support for further assistance.

NUMSPME0050	**Cannot update the {0} site information for {1} Universal Messaging server instance in {2} cluster.**
Explanation	Failed to add or delete the site information to a server node in the cluster.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0051	**Cannot update {0} prime site for {1} cluster. The specified prime site does not belong to the cluster.**
Explanation	Failed to update the prime site of the cluster. Only a site defined in the cluster can be specified as the prime site.
Action	Specify one of the sites defined in the cluster as the prime site. Contact Software AG Global Support for further assistance.

NUMSPME0052	**Cannot create the {0} site information for {1} Universal Messaging server instance in {2} cluster.**
Explanation	Failed to create the site for the server node in the cluster.
Action	Check the detailed error message. Contact Software AG Global Support for further assistance.

NUMSPME0053	**Universal Messaging cluster create operation failed.**
Explanation	An error occurred while creating the Universal Messaging cluster.
Action	Check the detailed error message. Contact Software AG Global Support for further assistance.

NUMSPME0054	**Universal Messaging cluster delete operation failed for the cluster with name {0}.**
Explanation	An error occurred while deleting the Universal Messaging cluster.
Action	Check the detailed error message. Contact Software AG Global Support for further assistance.

NUMSPME0055	**Universal Messaging cluster create operation failed because the cluster name is not provided.**
Explanation	To create a Universal Messaging cluster, you must provide a cluster name.
Action	Specify the cluster name in the input for Universal Messaging cluster creation.

NUMSPME0056	**Universal Messaging server instance {0} is either offline or not reachable.**
Explanation	For performing cluster management operations, all the nodes of the cluster must be online.
Action	Make sure that the Universal Messaging server instance is online. Contact Software AG Global Support for further assistance.

NUMSPME0057	**The cluster update operation failed because there is a mismatch in the cluster name. Actual cluster name is {0} where as the cluster name input is {1}.**
Explanation	There is a mismatch between the cluster name specified in the input and the name of the existing cluster.
Action	Input the correct cluster name. Contact Software AG Global Support for further assistance.

NUMSPME0058	**The license file you have provided is invalid. Provide a valid license file.**
Explanation	Invalid license file provided.
Action	Provide a valid Software AG license file. Please contact Software AG Global Support for further assistance.

NUMSPME0060	**Unable to configure the Universal Messaging server properties.**
Explanation	An error occurred while configuring server properties.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0061	**Unable to load the Universal Messaging server configuration properties. Provide a valid configuration instance ID.**
Explanation	Configuration instance ID is invalid or not provided.
Action	Provide a valid configuration instance ID.

NUMSPME0062	**Parameter validation failed. Unable to update the Universal Messaging server configuration parameters.**
Explanation	Incorrect configuration parameter values provided.
Action	See the Universal Messaging documentation for information about valid configuration parameter values.

NUMSPME0063	**Unable to update Universal Messaging server configuration parameters.**
Explanation	An error occurred when updating the Universal Messaging server configuration properties.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0064	**The Universal Messaging server configuration parameter provided is null or does not exist within the group.**
Explanation	The Universal Messaging server parameter is null or does not exist.
Action	See the Command Central Help and Universal Messaging documentation for information about valid parameters and values.

NUMSPME0065	**Cannot create the {0} site information for {1} Universal Messaging server instance in {2} cluster within the event time interval.**
Explanation	Failed to create the site information for the server node in the cluster, in the time interval.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0066	**An error occurred while initializing the Universal Messaging Context.**
Explanation	An error occurred while initializing the Universal Messaging Context for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0067	**An error occurred while initializing the Universal Messaging Context for Universal Messaging server {0}.**
Explanation	An error occurred while initializing the Universal Messaging Context for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0068	**An error occurred while retrieving the JNDI connection factory entries.**
Explanation	An error occurred while retrieving the JNDI connection factory entries from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the JNDI connection factories are present on the server.

NUMSPME0069	**An error occurred while retrieving the JNDI connection factory entries for the Universal Messaging server {0}.**
Explanation	An error occurred while retrieving the JNDI connection factory entries from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the JNDI connection factories are present on the server.

NUMSPME0070	**An error occurred while retrieving JNDI connection factory {0} for Universal Messaging server {1}.**
Explanation	An error occurred while retrieving the JNDI connection factory entry from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the JNDI connection factory is present on the server.

NUMSPME0071	**An error occurred while deleting the JNDI connection factory.**
Explanation	An error occurred while deleting the JNDI connection factory from the Universal Messaging server.
Action	Ensure that the JNDI connection factory is present on the server.

NUMSPME0072	**An error occurred while deleting the JNDI connection factory {0} for Universal Messaging server {1}.**
Explanation	An error occurred while deleting the JNDI connection factory from the Universal Messaging server.
Action	Ensure that the JNDI connection factory is present on the server.

NUMSPME0073	**An error occurred while binding the JNDI connection factory.**
Explanation	An error occurred while binding the JNDI connection factory for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0074	**An error occurred while binding the JNDI connection factory {0} for Universal Messaging server {1}.**
Explanation	An error occurred while binding the JNDI connection factory for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0075	**An error occurred while updating the JNDI connection factory.**
Explanation	An error occurred while updating the JNDI connection factory for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the JNDI connection factory is present on the server.

NUMSPME0076	**An error occurred while updating the JNDI connection factory {0} for Universal Messaging server {1}.**
Explanation	An error occurred while updating the JNDI connection factory for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the JNDI connection factory is present on the server.

NUMSPME0077	**An error occurred while loading the JNDI connection factory type for Universal Messaging server {0}.**
Explanation	An error occurred while loading the JNDI connection factory type for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0078	**An error occurred while creating the JNDI connection factory type {0} for Universal Messaging server {1}.**
Explanation	An error occurred while creating the JNDI connection factory type for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0079	**An error occurred while binding the JNDI destination.**
Explanation	An error occurred while binding the JNDI destination on the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0080	**An error occurred while binding the JNDI destination {0} on Universal Messaging server {1}.**
Explanation	An error occurred while binding the JNDI destination on the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0081	**An error occurred while retrieving the JNDI destination.**
Explanation	An error occurred while retrieving the JNDI destination from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and JNDI destinations are present on the server.

NUMSPME0082	**An error occurred while retrieving the JNDI destination from Universal Messaging server {0}.**
Explanation	An error occurred while retrieving the JNDI destination from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and JNDI destinations are present on the server.

NUMSPME0083	**An error occurred while retrieving the JNDI destination {0} from Universal Messaging server {1}.**
Explanation	An error occurred while retrieving the JNDI destination from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and JNDI destinations are present on the server.

NUMSPME0084	**An error occurred while deleting the JNDI destination.**
Explanation	An error occurred while deleting the JNDI destination from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the JNDI destinations are present on the server.

NUMSPME0085	**An error occurred while deleting the JNDI destination {0} from Universal Messaging server {1}.**
Explanation	An error occurred while deleting the JNDI destination from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the JNDI destinations are present on the server.

NUMSPME0086	**An error occurred while loading the JNDI destination type for Universal Messaging server {0}.**
Explanation	An error occurred while loading the JNDI destination type for Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0087	**An error occurred while creating the JNDI destination {0} for Universal Messaging server {1}.**
Explanation	An error occurred while creating the JNDI destination on the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0088	**Updating a JNDI destination type is not supported.**
Explanation	Update operation for a JNDI destination type is not supported for Universal Messaging server.
Action	No action required.

NUMSPME0089	**The Universal Messaging server is unavailable, check the status of the Universal Messaging server.**
Explanation	The Universal Messaging server might not be running.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0090	**An error occurred while retrieving the Universal Messaging session.**
Explanation	An error occurred while retrieving the Universal Messaging session.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0091	**An error occurred while retrieving the session for Universal Messaging server {0}.**
Explanation	An error occurred while retrieving the session for Universal Messaging server {0}.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0092	**JNDI connection factory name is either empty or contains invalid characaters.**
Explanation	JNDI connection factory name is either empty or contains invalid characaters.
Action	Provide a valid JNDI connection factory name.

NUMSPME0093	**Updating JNDI connection factory name is not supported.**
Explanation	Update operation for JNDI connection factory name is not supported for the Universal Messaging server.
Action	No action required.

NUMSPME0094	**Updating JNDI connection factory {0} name is not supported.**
Explanation	Update operation for JNDI connection factory name is not supported for the Universal Messaging server.
Action	No action required.

NUMSPME0095	**Invalid JNDI connection factory type. Allowed types are Connection Factory, Topic Connection Factory, Queue Connection Factory, and XA Connection Factory.**
Explanation	Invalid JNDI connection factory type. Allowed types are Connection Factory, Topic Connection Factory, Queue Connection Factory, and XA Connection Factory.
Action	Provide a valid JNDI connection factory type.

NUMSPME0096	**JNDI connection factory URL is either empty or invalid.**
Explanation	JNDI connection factory URL is either empty or invalid.
Action	Provide a valid JNDI connection factory URL.

NUMSPME0097	**Invalid value provided for JNDI connection factory shared durable property. Allowed values are true and false.**
Explanation	Invalid value provided for JNDI connection factory shared durable property. Allowed values are true and false.
Action	Provide true to enable and false to disable shared durable for the JNDI connection factory.

NUMSPME0098	**JNDI destination name is either empty or contains invalid characters.**
Explanation	JNDI destination name is either empty or contains invalid characters.
Action	Provide a valid JNDI destination name.

NUMSPME0099	**Invalid JNDI destination type. Allowed types are Topic and Queue.**
Explanation	Invalid JNDI destination type. Allowed types are Topic and Queue.
Action	Provide a valid JNDI destination type.

NUMSPME0100	**JNDI store name is either empty or contains invalid characaters.**
Explanation	JNDI store name is either empty or contains invalid characaters.
Action	Provide a valid JNDI store name.

NUMSPME0101	**Invalid value provided for the JNDI destination auto-create option. Allowed values are true and false**
Explanation	Invalid value provided for the JNDI destination auto-create option. Allowed values are true and false.
Action	Provide true to enable and false to disable auto-creation of JNDI destinations.

NUMSPME0102	**An error occurred while creating a channel on the Universal Messaging server.**
Explanation	An error occurred while creating a channel on the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0103	**An error occured while creating channel {0} on Universal Messaging server {1}.**
Explanation	An error occured while creating a channel on the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0104	**An error occured while creating a queue on the Universal Messaging server.**
Explanation	An error occured while creating a queue on the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0105	**An error occured while creating queue {0} on Universal Messaging server {1}.**
Explanation	An error occured while creating a queue on the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0106	**The JNDI connection factory already exists on the Universal Messaging server.**
Explanation	The JNDI connection factory already exists on the Universal Messaging server.
Action	Provide a different name for the JNDI connection factory.

NUMSPME0107	**JNDI connection factory {0} already exists on Universal Messaging server {1}.**
Explanation	JNDI connection factory already exists on the Universal Messaging server.
Action	Provide a different name for the JNDI connection factory.

NUMSPME0108	**The JNDI destination already exists on the Universal Messaging server.**
Explanation	The JNDI destination already exists on the Universal Messaging server.
Action	Provide a different name for the JNDI destination.

NUMSPME0109	**JNDI destination {0} already exists on Universal Messaging server {1}.**
Explanation	JNDI destination already exists on Universal Messaging server.
Action	Provide a different name for the JNDI destination.

NUMSPME0110	**Unable to load Universal Messaging server configuration properties user interface.**
Explanation	An error occurred while reading or writing configuration properties.
Action	Contact Software AG Global Support for further assistance.

NUMSPME0111	**Unable to establish connection with the Universal Messaging server.**
Explanation	An error occurred while retrieving the session from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0112	**Unable to retrieve the session attribute object associated with with Universal Messaging server session.**
Explanation	An exception occurred while retrieving the session attribute.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0113	**Unable to find the Universal Messaging channel on this Universal Messaging sever.**
Explanation	An error occurred while retrieving the Universal Messaging channel on the Universal Messaging realm server connected to this session, or a joined realm.
Action	Please check if the channel exists on this Universal Messaging sever.

NUMSPME0114	**Unable to retrieve the named object on this channel.**
Explanation	An error occurred while retrieving the named object details from this channel on the Universal Messaging server.
Action	Please check if the namd object exists on this channel.

NUMSPME0115	**Unable to delete the named object on this channel.**
Explanation	An error occurred while deleting the named object from this channel on the Universal Messaging server.
Action	Please check if the named object exists on this channel.

NUMSPME0116	**Missing argument: {0}.**
Explanation	Arguments not provided. Please provide both the channel and durable subscriber names to view details or delete a durable subscriber.
Action	Provide valid arguments for durable subscriber or channel.

NUMSPME0117	**Unable to connect to the Universal Messaging server.**
Explanation	An error occurred while retrieving the session from the Universal Messaging server.
Action	Please check if the Universal Messaging server is running.

NUMSPME0118	**Unable to retrieve the channel/queue {0} from Universal Messaging server {1}.**
Explanation	An error occurred while retrieving the channel/queue from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the specified channel/queue exists on the server.

NUMSPME0119	**Unable to establish connection with the Universal Messaging server {0}.**
Explanation	An error occurred while connecting to the Universal Messaging server.
Action	Ensure that the Universal Messaging server exists and is running.

NUMSPME0120	**An error occurred while loading channel configuration for the Universal Messaging server {0}.**
Explanation	An error occurred while loading channel configuration for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0121	**Unable to retrieve the channel list for the Universal Messaging server {0}.**
Explanation	An error occured while retrieving the list of channels for the Universal Messaging server.
Action	Check if the Universal Messaging server is running and if the channels are configured.

NUMSPME0122	**Unable to retrieve the details of channel {0} in Universal Messaging server {1}.**
Explanation	An error occured while retrieving the channel details for the Universal Messaging server.
Action	Check if the Universal Messaging server is running and if the channel exists on the server.

NUMSPME0123	**Unable to connect to the Universal Messaging server {0}.**
Explanation	An error occurred while connecting to the Universal Messaging server.
Action	Ensure that the Universal Messaging server exists and is running.

NUMSPME0124	**An error occurred while loading the queues for the Universal Messaging server {0}.**
Explanation	An error occurred while loading the queues for the Universal Messaging server.
Action	Ensure that the Universal Messaging server exists and is running.

NUMSPME0125	**Unable to retrieve the queue list for the Universal Messaging server {0}.**
Explanation	An error occured while retrieving the queue list for the Universal Messaging server.
Action	Please check if the Universal Messaging server is running and has queues configured.

NUMSPME0126	**Unable to retrieve the details of the queue {0} in Universal Messaging server {1}.**
Explanation	An error occured while retrieving the queue details from the Universal Messaging server.
Action	Please check if Universal Messaging server is running and the queue exists on the server.

NUMSPME0127	**Universal Messaging instance management operation failed, exit code - {0}, full command - {1}, standard output - {2}**
Explanation	The Universal Messaging instance management operation failed due to an error.
Action	Check the Platform Manager and Universal Messaging logs to find the error, resolve the error and retry.

NUMSPME0128	**Unable to create or update the channel as the channel name is not provided or is invalid.**
Explanation	Cannot create or update the channel with an empty or invalid name.
Action	Provide a valid channel name.

NUMSPME0129	**Unable to create or update the channel as the channel TTL value provided is invalid.**
Explanation	Cannot create or update a channel as the TTL is negative.
Action	Provide a TTL value between 0 to 2147483647.

NUMSPME0130	**Unable to create or update the channel as the provided channel capacity value is invalid.**
Explanation	Cannot create or update a channel as the provided value for the channel capacity is in negative.
Action	Provide a capacity value between 0 to 2147483647.

NUMSPME0131	**Unable to create or update the channel as the channel type provided is invalid.**
Explanation	Cannot create or update a channel because the channel type provided is invalid.
Action	Provide a valid channel type.

NUMSPME0132	**Unable to create or update the channel as the channel engine provided is invalid**
Explanation	Cannot create or update the channel because the channel engine type provided is invalid.
Action	Provide a valid channel engine type.

NUMSPME0133	**Unable to create or update the channel as the publish key name provided is invalid.**
Explanation	Cannot create or update a channel becaue the publish key name provided is invalid .
Action	Provide a valid channel publish key name.

NUMSPME0134	**Unable to create or update the channel as the key depth value provided is invalid.**
Explanation	Cannot create or update a channel bacause the key depth value provided is invalid.
Action	Provide a valid channel key depth.

NUMSPME0135	**Unable to create or update the channel as the priority value provided is invalid.**
Explanation	Cannot create or update a channel because the priority value provided is invalid.
Action	Provide a value between 0 to 9.

NUMSPME0136	**Unable to create or update the channel as the selected stamp dictionary is invalid.**
Explanation	Cannot create /update a channel with an invalid stamping dictionary
Action	Select a valid stamp dictionary.

NUMSPME0137	**Unable to create the channel {0} on Universal Messaging server {1}.**
Explanation	An error occured while creating the channel on the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0138	**Unable to create/update the channel attributes as the provided parameters are invalid.**
Explanation	An error occured while creating/updating the channel attributes as the provided input parameters are invalid.
Action	Ensure that the provided input channel parameter values are valid.

NUMSPME0139	**Unable to create/update the channel as the dead event store provided is invalid.**
Explanation	An error occured while creating/updating the channel as the provided dead event store does not exist on the Universal Messaging server.
Action	Ensure that the dead event store channel or queue provided exists on the server.

NUMSPME0140	**Unable to create the channel as channel {0} already exists on server {1}.**
Explanation	Channel already exists on the server.
Action	Create a channel with a different name.

NUMSPME0141	**Unable to delete the channel or queue {0} on Universal Messaging server {1}.**
Explanation	An error occured while deleting the channel or queue on the Universal Messaging server.
Action	Check if the Universal Messaging server is running.

NUMSPME0142	**Unable to update the channel or queue {0} on Universal Messaging server {1}.**
Explanation	An error occured while updating the channel or queue on the Universal Messaging server.
Action	Check if the Universal Messaging server is running.

NUMSPME0143	**Cannot update the channel or queue {0} on Universal Messaging server {1} because of invalid input parameters.**
Explanation	An error occured while updating the channel or queue for the Universal Messaging server because of invalid input parameters.
Action	Ensure that the input parameters are valid and correct.

NUMSPME0144	**Unable to update the channel or queue {0} on Universal Messaging server {1}.**
Explanation	Update failed because an error occurred while copying the new configuration over the existing channel or queue configuration.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0145	**Unable to create or update the channel or queue {0} on Universal Messaging server {1}.**
Explanation	An error occured while creating or updating the channel or queue on Universal Messaging server because of invalid input storage parameters.
Action	Ensure that the input storage parameters are valid and correct.

NUMSPME0146	**Unable to create queue {0} on Universal Messaging server {1}.**
Explanation	An error occured while creating the queue on Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0147	**Unable to create or update the queue.**
Explanation	Cannot create or update the queue because of empty or invalid name.
Action	Ensure that you provide a valid name.

NUMSPME0148	**Unable to create or update the queue bacause the TTL value is invalid.**
Explanation	Cannot create or update a queue as the TTL value is negative.
Action	PLease provide a TTL between 0 to 2147483647 (exclusive)

NUMSPME0149	**Unable to create or update the queue as the channel capacity value is invalid.**
Explanation	Cannot create or update a queue as the capacity is negative.
Action	Enter a capacity value between 0 to 2147483647.

NUMSPME0150	**Unable to create or update the channel because the queue type is invalid.**
Explanation	Cannot create or update a queue with an invalid type.
Action	Provide a valid queue type.

NUMSPME0151	**Unable to create or update the channel because the priority value is invalid.**
Explanation	Cannot create or update a channel with an invalid event priority.
Action	Provide a priority value between 0 to 9 (lowest to highest) .

NUMSPME0152	**Unable to create or update the channel as the stamping dictionary value provided is invalid.**
Explanation	Cannot create or update a channel with an invalid stamping dictionary.
Action	Provide a valid stamping dictionary value.

NUMSPME0153	**Unable to create the queue attributes as the provided parameters are invalid.**
Explanation	An error occured while creating the queue attributes as the input parameters are invalid.
Action	Provide valid queue parameters.

NUMSPME0154	**Unable to create the channel attributes as the dead event store is invalid.**
Explanation	An error occured while creating the channel attributes as the provided dead event store does not exist on the Universal messaging server.
Action	Ensure that the dead event store channel or queue exists on the server.

NUMSPME0155	**Unable to create the queue as queue {0} already exists on server {1}.**
Explanation	Queue exists on the server.
Action	Create a queue with a different name.

NUMSPME0156	**Missing argument: {0}.**
Explanation	Arguments not provided. Provide the channel name to view status of a channel.
Action	Provide a valid channel name.

NUMSPME0157	**Unable to retrieve the status of channel {0} in Universal Messaging server {1}.**
Explanation	An error occured while retrieving the channel details from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the channel exists on the server.

NUMSPME0158	**Arguments not provided.**
Explanation	Arguments not provided. Provide the queue name to view status of a queue.
Action	Provide queue name as the argument.

NUMSPME0159	**Unable to retrieve the status of queue {0} for Universal Messaging server {1}.**
Explanation	An error occured while retrieving the queue status from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running and the queue exists on the server.

NUMSPME0160	**Unable to retrieve ACLs for channel {0}.**
Explanation	An error occurred while retrieving ACLs for channel {0}.
Action	Check the Platform Manager and Universal Messaging logs to find the error resolve the error and retry.

NUMSPME0161	**Unable to add ACLs for channel {0}.**
Explanation	An error occurred while adding ACLs to a channel.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0162	**Unable to update ACLs for channel {0}.**
Explanation	An error occurred while updating ACLs for channel {0}.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0163	**Unable to create an ACL entry with subject {0} for channel {1}.**
Explanation	An error occurred when creating an ACL entry object for the channel.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0164	**Unable to retrieve ACLs for queue {0}.**
Explanation	An error occurred when retrieving ACLs for the queue.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0165	**Unable to add ACLs for queue {0}.**
Explanation	Adding ACLs to a queue failed due to an error.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0166	**Unable to update ACLs for queue {0}.**
Explanation	An error occurred when updating ACLs for a queue.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0167	**Unable to create the ACL entry with name {0} for queue {1}.**
Explanation	An error occurred in creating ACL entry object with name {0} for queue {1}.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0168	**Unable to create the ACL entry with subject {0} for channel {1}.**
Explanation	Invalid group name provided for ACL entry object with subject {0} for channel {1}.
Action	Provide a valid group name.

NUMSPME0169 **Unable to create the ACL entry with name {0} for queue {1}.**

Explanation Invalid group name provided for ACL entry with name {0}, for queue {1}.

Action Provide a valid group name.

NUMSPME0170 **Unable to create a join from {0} to {1} because the operation is unsupported.**

Explanation An error occurred while creating the join.

Action Ensure that the source node is a valid channel. For archived join, ensure that the destination node is a queue.

NUMSPME0171 **Unable to create a join from {0} to {1}.**

Explanation An error occurred while creating the join.

Action Ensure that the source is a valid channel and the Universal Messaging server is running.

NUMSPME0172 **Unable to delete the join from {0} to {1} as this operation is unsupported.**

Explanation An error occurred while deleting the join.

Action Ensure that the source node is a valid channel.

NUMSPME0173 **Unable to delete the join from {0} to {1}.**

Explanation An error occurred while deleting the join.

Action Ensure that the source is a valid channel and the Universal Messaging server is running.

NUMSPME0174 **Unable to delete the join from {0} to {1} as this is not a source node.**

Explanation An error occurred while deleting the join.

Action Delete the join from the source node. A join cannot be deleted from a destination node.

NUMSPME0175 **Unable to create the cluster.**

Explanation Unable to create the cluster because the Universal Messaging server instance is already part or another cluster or the server instance already exists in the cluster or a local store is configured in one of the server instances that you are adding to the cluster.

Action Ensure that the Universal Messaging server instance added to the cluster complies to the restrictions provided in the error message explanation.

NUMSPME0176	**Unable to create the cluster.**
Explanation	Session error.
Action	Check the detailed error message in the Command Central and Universal Messaging logs. Resolve the error and retry.

NUMSPME0177	**Unable to create the cluster.**
Explanation	Request timed out.
Action	Retry creating the cluster.

NUMSPME0178	**Unable to create the cluster.**
Explanation	Error in the response received from the realm server.
Action	Check for the detailed error message in the Universal Messaging logs. Resolve the error and retry.

NUMSPME0179	**Unable to create the cluster.**
Explanation	The Universal Messaging server instance is currently unreachable.
Action	Check for the detailed error message in the Universal Messaging logs. Resolve the error and retry.

NUMSPME0180	**Unable to create the cluster.**
Explanation	Conflicting realm names provided.
Action	Ensure that you provide the correct realm names to create the cluster.

NUMSPME0181	**Unable to create the cluster.**
Explanation	The Universal Messaging server instance could not be found.
Action	Check for detailed error messages in the Command Central and Universal Messaging logs. Contact Software AG Global Support for further assistance.

NUMSPME0182	**Unable to create the cluster.**
Explanation	You do not have the required administration rights for the realm.
Action	Ensure that you have the relevant administration rights for the realm.

NUMSPME0183	**Channel created successfully but cannot create a join from {0} to {1} because the operation is not supported.**
Explanation	An error occurred while creating the join.
Action	Ensure that the source is a valid channel. For archived join, ensure that the destination node is a queue.

NUMSPME0184	**Channel created successfully but cannot create a join from {0} to {1}.**
Explanation	An error occurred while creating the join.
Action	Ensure that the source is a valid channel and the Universal Messaging server is running.

NUMSPME0185	**Unable to create a join from {0} to {1} because the operation is not suppported. The other channel properties are sucessfully updated.**
Explanation	An error occurred while creating the join.
Action	Ensure that the source is a valid channel. For archived join, ensure that the destination node is a queue.

NUMSPME0186	**Unable to create a join from {0} to {1}. The other channel properties are sucessfully updated.**
Explanation	An error occurred while creating the join.
Action	Ensure that the source is a valid channel and the Universal Messaging server is running.

NUMSPME0187	**Unable to delete the join from {0} to {1} as the operation is not supported. Other channel properties are updated.**
Explanation	An error occurred while deleting the join.
Action	Ensure that the source node is a valid channel.

NUMSPME0188	**Unable to delete the join from {0} to {1}. Other channel properties are updated.**
Explanation	An error occurred while deleting the join.
Action	Ensure that the source is a valid channel and the Universal Messaging server is running.

NUMSPME0189	**Cannot delete the join from {0} to {1} because {0} is not the source node. Other channel properties are updated.**
Explanation	An error occurred while deleting the join.
Action	Delete the join from the source node. A join cannot be deleted from a destination node.

NUMSPME0190	**Unable to create or update the channel as the protobuf descriptor file does not exist.**
Explanation	Cannot create or update a channel with an invalid protobuf descriptor file.
Action	Ensure that the protobuf descriptor file exists in the provided path.

NUMSPME0191	**Unable to create or update the channel as the protobuf descriptor file provided is invalid.**
Explanation	An error occured while creating or updating the channel because the protobuf descriptor file provided is invalid.
Action	Provide a valid protobuf descriptor file.

NUMSPME0192	**Unable to create or update the queue as the protobuf descriptor file does not exist.**
Explanation	Cannot create or update a queue with an invalid protobuf descriptor file.
Action	Ensure that the protobuf descriptor file exists in the provided path.

NUMSPME0193	**Unable to create or update the queue as the protobuf descriptor provided is invalid.**
Explanation	An error occured while creating or updating the queue because the protobuf descriptor file provided is invalid.
Action	Provide a valid protobuf descriptor file.

NUMSPME0194	**Unable to edit the name of the channel.**
Explanation	You cannot edit the name of a channel, operation not supported.
Action	Delete and recreate the channel.

NUMSPME0195	**Unable to edit the name of the queue.**
Explanation	You cannot edit the name of a queue, operation not supported.
Action	Delete and recreate the queue.

NUMSPME0196	**Unable to retrieve the channel or queue {0} from Universal Messaging server {1}.**
Explanation	An error occurred while retrieving the channel or queue from the Universal Messaging server as the node addition has failed.
Action	Ensure that the Universal Messaging server instances are not clustered.

NUMSPME0197	**An error occurred while creating the join.**
Explanation	Cannot create the join between {0} and {1} because remote node {1} is not a valid node.
Action	Ensure that the remote node is a valid channel or queue and the Universal Messaging server is running.

NUMSPME0198	**Cannot edit a channel join. Operation not supported.**
Explanation	Channel joins can only be created and deleted. Editing is not supported.
Action	Delete and recreate the join with the new join attributes.

NUMSPME0199	**Missing argument: {0}.**
Explanation	Arguments not provided. Please provide both the channel and durable subscriber names to delete a durable subscriber.
Action	Provide valid arguments for durable subscriber or channel.

NUMSPME0200	**An error occurred while creating file {0} for the Universal Messaging server instance {1}.**
Explanation	An error occurred while creating the file for Universal Messaging instance {1}.
Action	Check the Platform Manager logs for more information about the error.

NUMSPME0201	**Invalid cluster configuration. Cluster name not provided for Universal Messaging server instance {0}.**
Explanation	Invalid cluster configuration provided. Cluster name not provided for Universal Messaging server instance {0}.
Action	Provide a valid cluster name in the cluster configuration.

NUMSPME0202	**Invalid cluster configuration. Servers element is required and is not provided for the Universal Messaging server instance {0}.**
Explanation	Invalid cluster configuration. Servers element is required in the cluster configuration and is not provided for the Universal Messaging server instance {0}.
Action	Provide valid cluster configuration with the necessary servers element.

NUMSPME0203	**Invalid cluster configuration. Server name is required and is not provided for the Universal Messaging server instance {0}.**
Explanation	Invalid cluster configuration. Server name is required and is not provided for the Universal Messaging server instance {0}.
Action	Provide a valid server name in the cluster configuration.

NUMSPME0204	**Invalid cluster configuration. Server URL {0} is not provided or is invalid for Universal Messaging server name {1} for server instance {2}.**
Explanation	Invalid cluster configuration. Server URL {0} is not provided or is invalid for Universal Messaging server name {1} for server instance {2}.
Action	Provide a valid server URL in the cluster configuration.

NUMSPME0205	**Unable to establish connection with the Universal Messaging server {0}.**
Explanation	An error occurred while connecting to the Universal Messaging server.
Action	Ensure that the Universal Messaging server exists and is running.

NUMSPME0206	**An error occurred while loading the realm ACL configuration for the Universal Messaging server {0}.**
Explanation	An error occurred while loading the realm ACL configuration for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0207	**Unable to retrieve the realm ACLs for Universal Messaging server {0}.**
Explanation	An error occurred while retrieving the realm ACLs for {0}.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0208	**Unable to update realm ACLs for Universal Messaging server {0}.**
Explanation	An error occurred while updating ACLs for Universal Messaging server {0}.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0209	**Unable to create an ACL entry with subject {0} for Universal Messaging server {1}.**
Explanation	An error occurred when creating an ACL entry for the realm.
Action	Check the Platform Manager and Universal Messaging logs to find the error; resolve the error and retry.

NUMSPME0210	**Unable to create the ACL entry with subject {0} for Universal Messaging server {1}.**
Explanation	Invalid group name provided for ACL entry object with subject {0} for realm {1}.
Action	Provide an existing group name.

NUMSPME0211	**Purge operation not supported on the durable subscriber of type {0}.**
Explanation	Purge operation is not allowed for this durable subscriber type.
Action	Purge events on a different durable type.

NUMSPME0212	**Unable to establish connection to the Universal Messaging server.**
Explanation	An error occurred while retrieving the session from the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0213	**An error occurred while trying to view events on the durable subscriber.**
Explanation	An error occurred while trying to view events on the durable subscriber.
Action	Ensure that the channel and durable type exists, and the Universal Messaging server is running.

NUMSPME0214	**An error occured while purging events on the durable subscriber.**
Explanation	An error occured while purging events on the durable subscriber.
Action	Ensure that the channel and durable type exists, and the Universal Messaging server is running.

NUMSPME0215	**An error occurred while parsing the event header.**
Explanation	An error occurred while parsing the event header.
Action	Ensure that the header does not contain corrupted information.

NUMSPME0217	**Invalid arguments provided.**
Explanation	Invalid arguments provided.
Action	Ensure that you provide valid arguments and try again.

NUMSPME0227	**Creation of realm ACLs for Universal Messaging server is not supported.**
Explanation	Create operation for realm ACLs is not supported for a Universal Messaging server.

NUMSPME0228	**Deletion of realm ACLs for Universal Messaging server is not supported.**
Explanation	Delete operation for realm ACLs is not supported for Universal Messaging server.

NUMSPME0229	**Universal Messaging cluster update operation failed for the instance with name {0}.**
Explanation	An error occurred while updating the cluster details of the Universal Messaging instance.
Action	Ensure that all the cluster nodes are online and the cluster has the quorum.

NUMSPME0239	**XA Connection Factory does not support round robin URL.**
Action	Change the connection factory type or the URL.

NUMSPME0240	**Unable to load the groups configuration instance for the Universal Messaging instance {0}.**
Explanation	An error occurred when loading the group configuration for the Universal Messaging server instance.
Action	Specify a valid group name.

NUMSPME0241	**Unable to retrieve groups for Universal Messaging instance {0}.**
Explanation	Cannot retrieve groups for the Universal Messaging instance. There are no groups present for the Universal Messaging instance.
Action	Groups don't exist for this Universal Messaging instance. You need to create a group for the Universal Messaging instance before you retrieve the group.

NUMSPME0242	**Unable to add entry with the subject or group {0} for the Universal Messaging instance {1}.**
Explanation	Invalid subject or group name provided.
Action	Provide a valid existing subject and group name.

NUMSPME0243	**Unable to create group {0} for the Universal Messaging instance {1}.**
Explanation	An error occured while creating a group for the Universal Messaging instance.
Action	Ensure that you have sufficient privileges to add new groups to the Universal Messaging instance.

NUMSPME0244	**Unable to delete group {0} for the Universal Messaging instance {1}.**
Explanation	An error occured while deleting a group for the Universal Messaging instance.
Action	Ensure that you have sufficient privileges to delete groups in the Universal Messaging instance.

NUMSPME0245	**Unable to update group {0} for the Universal Messaging instance {1}.**
Explanation	An error occured while updating a group for the Universal Messaging server.
Action	Ensure that you have sufficient privileges to update groups in the Universal Messaging instance.

NUMSPME0246	**Unable to add an entry with subject {0} for the group {1} for Universal Messaging instance {2}.**
Explanation	An error occured when adding a subject to the group for the Universal Messaging instance.
Action	Ensure that you have sufficient privileges to update groups in the Universal Messaging instance.

NUMSPME0247	**Unable to connect to the Universal Messaging instance {0}.**
Explanation	An error occurred while connecting to the Universal Messaging server.
Action	Ensure that the Universal Messaging instance is online.

NUMSPME0248	**Unable to create the group as the group name is not provided or is invalid.**
Explanation	Cannot create or update group with an empty or invalid name.
Action	Provide a valid group name.

NUMSPME0249	**Unable to create zone {0} with Universal Messaging server {1}.**
Explanation	An error occurred while creating a zone with the Universal Messaging server.
Action	Check the detailed error message. Resolve any errors, and then retry.

NUMSPME0250	**Unable to create or update the channel as the read buffer size value provided is invalid.**
Explanation	Cannot create or update a channel because the read buffer size value provided is invalid.
Action	Provide a read buffer size value between 0 to 2147483647.

NUMSPME0251	**Unable to create or update the channel as the events per spindle value provided is invalid.**
Explanation	Cannot create or update a channel because the events per spindle value provided is invalid.
Action	Provide a value between 0 to 2147483647.

NUMSPME0252	**Unable to create or update the channel as the sync batch property values provided are invalid.**
Explanation	Cannot create or update a channel because the sync batch property values provided are invalid.
Action	Provide a sync batch property value between 0 to 2147483647.

NUMSPME0253	**Unable to create or update the queue as the read buffer size value provided is invalid.**
Explanation	Cannot create or update a queue because the read buffer size value provided is invalid.
Action	Provide a read buffer size value between 0 to 2147483647.

NUMSPME0254	**Unable to create or update the queue as the events per spindle value provided is invalid.**
Explanation	Cannot create or update a queue because the events per spindle value provided is invalid.
Action	Provide a events per spindle value between 0 to 2147483647.

NUMSPME0255	**Unable to create or update the queue as the sync batch property values provided are invalid.**
Explanation	Cannot create or update a queue because the sync batch property values provided are invalid.
Action	Provide a sync batch property value between 0 to 2147483647.

NUMSPME0256	**Unable to update zone {0} with Universal Messaging server {1}.**
Explanation	An error occurred while updating a zone with the Universal Messaging server.
Action	Check the detailed error message in the Universal Messaging server logs.

NUMSPME0257	**Unable to remove link from Universal Messaging server {0} to Universal Messaging server {1}.**
Explanation	An error occurred while removing links between Universal Messaging servers in the zone.
Action	Check for the detailed error message in the Universal Messaging logs. Resolve the error and retry.

NUMSPME0258	**Failed to remove cluster link from cluster {0} to cluster {1}.**
Explanation	An error occurred while removing links between clusters in the zone.
Action	Ensure the clusters are available and connected.

NUMSPME0259	**Unable to retrieve zone details for Universal Messaging server {0}.**
Explanation	An error occurred while retrieving the zone members list for the Universal Messaging server.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0260	**The Universal Messaging server instance is currently not accessible .**
Explanation	Check for the detailed error messages in the Universal Messaging logs. Resolve the error and retry.
Action	Ensure that the Universal Messaging server is running.

NUMSPME0261	**An error occurred while creating a zone.**
Explanation	Zone members are incompatible, clustered and non-clustered Universal Messaging server instances cannot be in the same zone.
Action	Ensure that the clustered and non-clustered Universal Messaging server instances are not added to the same zone. Clustered and non-clustered Universal Messaging server instances need to be grouped in separate zones.

NUMSPME0262	**Unable to create a link to the Universal Messaging server {0} from Universal Messaging server {1}.**
Explanation	An error occurred while linking the Universal Messaging servers. Rolling back the created links.
Action	Ensure that all the Universal Messaging servers that are being linked are running.

NUMSPME0263	**Unable to rollback the added Universal Messaging server instance links.**
Explanation	An error occurred when rolling back the Universal Messaging instance links added to the zone.
Action	Check the detailed error message.

NUMSPME0264	**Unable to delete zone {0} with Universal Messaging server {1}.**
Explanation	An error occurred while deleting a zone with the Universal Messaging server.
Action	Check the detailed error message.

NUMSPME0265	**Unable to create or update the cluster as the server URL provided is invalid.**
Explanation	The URL provided for the Universal Messaging server instance is invalid.
Action	Please provide a valid URL for the Universal Messaging server instance.

NUMSPME0266	**Cannot disable this interface. At least one interface needs to be enabled.**
Explanation	At least one interface should be enabled for a Universal Messaging server.
Action	Ensure that you enable at least one interface for a Universal Messaging server.

NUMSPME0267	**The specified prime site is invalid, the prime site specified does not belong to the cluster.**
Explanation	The specified prime site is invalid.
Action	Specify one of the sites defined in the cluster as the prime site.

NUMSPME0268	**Unable to create zone as the zone name is not provided or is invalid.**
Explanation	Cannot create or update zone with an empty or invalid name.
Action	Provide a valid zone name.

NUMSPME0269	**Unable to add Universal Messaging server {0} to the zone. It is already part of zone {1}.**
Explanation	Unable to add Universal Messaging server to the zone as it is already a part of a different zone.
Action	Provide a different Universal Messaging server or remove the server from the other zone.

NUMSPME0270	**Unable to create or update the zone as the server URL provided is invalid.**
Explanation	The URL provided for the Universal Messaging server instance is invalid.
Action	Please provide a valid URL for the Universal Messaging server instance.

NUMSPME0271	**Unable to create/update the zone as it should contain at least one cluster.**
Explanation	The zone create/update cannot be performed because a zone should contain at least one cluster.
Action	Ensure that at least one cluster is part of the zone.

NUMSPME0272	**Unable to retrieve the configured user repository file path for instance {0}.**
Explanation	Unable to retrieve the configured user repository file path for instance {0}.
Action	Verify if the user repository file is configured for the instance {0}.

NUMSPME0273	**Unable to create/update the zone as it should contain at least one realm.**
Explanation	The zone create/update cannot be performed because a zone should contain at least one realm.
Action	Ensure that at least one realm is part of the zone.

NUMSPME0274	**Universal Messaging instance management update operation has failed for instance {0}.**
Explanation	Universal Messaging instance management update operation has failed.
Action	Please confirm that the Universal Messaging instance is stopped.

NUMSPME0275	**Cannot create a clustered store on a non-clustered realm.**
Explanation	Cannot create a clustered store on a non-clustered realm.
Action	Create a cluster and recreate the store, or change the store to local.

NUMSPME0276	**Property name {0} is invalid.**
Explanation	Property names cannot be empty or start with "-D".
Action	Contact your Software AG product administrator and modify the property name.

NUMSPME0278	**The value of property {0} cannot be empty.**
Explanation	Property values cannot be empty.
Action	Contact your Software AG product administrator and specify a property value.

NUMSPME0282	**Unable to create or update the channel as the ACL contains an invalid subject name.**
Explanation	Channel ACL subject is in an invalid format.
Action	Enter a valid subject in the format user@host.

NUMSPME0283	**Unable to create or update the queue as the ACL contains an invalid subject name.**
Explanation	Queue ACL subject is in an invalid format.
Action	Enter a valid subject in the format user@host.

NUMSPME0284	**Unable to create or update the Realm ACL as the ACL contains invalid subject.**
Explanation	Realm ACL subject is in an invalid format.
Action	Enter a valid subject in the format user@host.

NUMSPME0285	**Unable to create or update the channel as the provided Protocol Buffers (protobuf) file type is not supported.**
Explanation	The provided Protocol Buffers (protobuf) file is not supported.
Action	Provide a protobuf file with a .proto file extension.

NUMSPME0286	**Unable to create or update the queue as the provided Protocol Buffers (protobuf) file type is not supported.**
Explanation	The provided Protocol Buffers (protobuf) file is not supported.
Action	Provide a protobuf file with a .proto file extension.

NUMSPME0287	**Unable to create or update the zone as the server URL provided is invalid.**
Explanation	The URL provided for the Universal Messaging server instance is invalid.
Action	Please provide a valid URL for the Universal Messaging server instance.

NUMSPME0288 **Unable to create or update the port because the specified Buffer size value is invalid.**

Explanation The Buffer size value cannot be empty, a negative number, or a fraction.

Action Specify a Buffer size value between 0 and 2147483647.

NUMSPME0289 **Unable to create or update the port because the provided Path value is invalid.**

Explanation The Path value cannot be empty.

Action Specify a Path value.

NUMSPME0290 **Cannot create a SHM Interface on the selected realm, since the selected realm already has a configured SHM port.**

NUMSPME0291 **Unable to create SHM Interface**

Explanation Cannot create a SHM Interface on the selected realm, since the selected realm already has a configured SHM port.

NUMSPME0292 **Unable to create or update the port as the Timeout value provided is invalid.**

Explanation Timeout value cannot be empty, negative number or a fraction.

Action Provide a Timeout value between 0 and 2147483647.

NUMSPME0293 **The Buffer size value cannot be empty, negative number or a fraction. Provide a Buffer size value between 0 and 2147483647.**

NUMSPME0294 **The Path value cannot be empty. Specify a Path value.**

NUMSPME0295 **The Timeout value cannot be empty, a negative number, or a fraction. Specify a Timeout value between 0 and 2147483647.**

NUMSPME0296 **Unable to create or update the port because some of the required properties were not provided.**

Explanation The buffer size, timeout, and path properties must be specified.

Action Ensure that values are specified for the buffer size, timeout, and path properties.

NUMSPME0297	**The buffer size, timeout, and path properties must be specified. Ensure that values are specified for the buffer size, timeout, and path properties.**
NUMSPMI0048	**The Universal Messaging server instance {0} is not a part of any cluster.**
Explanation	This Universal Messaging sever instance is not a part of any cluster.
Action	No action required.
NUMSPMW0004	**Unable to connect to the Command Central interface of the Universal Messaging server {0}.**
Explanation	Interface factory could not connect to any interface.
Action	Please contact webMethods Administrator.
NUMSPMW0280	**Empty configuration.**
Explanation	If no properties are defined, the default configuration file will be used.
Action	Define properties for the configuration.