

webMethods ActiveTransfer 10.3 Readme

October 2018

This file contains important information you must read before using webMethods ActiveTransfer 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find the suite-related information listed below.

webMethods Product Suite Release Notes

webMethods and Intelligent Business Operations System Requirements

webMethods System Cache Specifications

Using the Software AG Installer

Installing webMethods and Intelligent Business Operations Products

Using the Software AG Update Manager (fixes)

Upgrading webMethods and Intelligent Business Operations Products

Security and globalization information

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information	2
2.0	Known Issues	2
3.0	Usage Notes	3
4.0	Fixes Included in Each Release	3
5.0	Other Resolved Issues	4
6.0	Documentation Changes	12
7.0	Terminology Changes	15
8.0	Added, Removed, Deprecated, or Changed Items	15
9.0	Added, Removed, Deprecated, or Changed Built-In Services	22
10.0	Added, Removed, Deprecated, or Changed Parameters	22
11.0	Added, Removed, Deprecated, or Changed APIs	26
12.0	Copyright Information	27
13.0	Support	27

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

ActiveTransfer Server

- MAT-8936
Scheduled events fail with an "Assertion Failed" error when the events execute the find and move actions. This issue occurs when the move action is executed to move files to an SFTP server that requires a private key and passphrase.
There is currently no workaround for this issue.
- MAT-9205
When multiple agents are connected to ActiveTransfer Server, the number of database connections required is very high.
The workaround for this issue is to increase the number of database connections for ActiveTransfer Server.
- MAT-9523
When multiple agent installations are performed on the same machine at exactly the same time, the same Node ID is generated for multiple agents sometimes.
The workaround for this issue is to delete the "nodeId" file in the <Agent Install Dir>\profiles\MAG\configuration\agent\ folder and restart the agent.
- MAT-1198
In ActiveTransfer Server, if you delete an event, the event activities logged for the deleted event are listed in the Monitoring > Integration > Managed File Transfer > Event Log page in My webMethods without the Event Name.
There is currently no workaround for this issue.

ActiveTransfer Agent

- MAT-9610
At high load, duplicated entries for agent events are created and displayed in the Agent Event Logs screen in My webMethods Server.
There is currently no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

ActiveTransfer Server

Release 10.3

- MAT_10.1_MWS_Fix8
- MAT_10.1_Server_Fix8
- MAT_9.8_MWS_Fix27
- MAT_9.8_Server_Fix27

Release 10.2

- MAT_10.1_MWS_Fix3
- MAT_10.1_Server_Fix3
- MAT_9.8_MWS_Fix23
- MAT_9.8_Server_Fix23
- MAT_9.7_MWS_Fix23
- MAT_9.7_Server_Fix23

Release 10.1

- MAT_9.8_Server_Fix17
- MAT_9.8_MWS_Fix17
- MAT_9.7_MWS_Fix22
- MAT_9.7_Server_Fix22

- MAT_9.6_MWS_Fix27
- MAT_9.6_Server_Fix27

Release 10.0

- MAT_9.8_Server_Fix12
- MAT_9.8_MWS_Fix12
- MAT_9.12_SPM_Fix1
- MAT_9.0_SP1_MWS_Fix6
- MAT_8.2_SP2_MWS_Fix3

Release 9.8

- MAT_8.2_SP2_MWS_Fix3
- MAT_8.2_SP2_Server_Fix3
- MAT_9.0_SP1_MWS_Fix6
- MAT_9.0_SP1_Server_Fix6
- MAT_9.5_SP1_MWS_Fix7
- MAT_9.5_SP1_Server_Fix7
- MAT_9.6_MWS_Fix9
- MAT_9.6_Server_Fix9
- MAT_9.7_MWS_Fix3
- MAT_9.7_Server_Fix3

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

ActiveTransfer Server

Release 10.3

- MAT-7879

On migrating to ActiveTransfer version 10.2, external users (not configured in My webMethods Server) cannot access files shared in ActiveTransfer version 9.8 and earlier.

This issue is resolved. The relative path of the old TempAccounts folder is provided in the `mft.sharing.account.tempdir` property available in the following location:

new_Software AG_directory

/IntegrationServer/instances/instance/packages/WmMFT/config/properties.cnf file.

Release 10.2

- **MAT-7464**
ActiveTransfer fails to update an event if the user enables the "Execute error task" option for a copy action.
This issue is resolved.
- **MAT-7448**
ActiveTransfer does not accept any new connections following a file upload that is timed out due to prolonged processing by the Internet Content Adaptation Protocol (ICAP) server virus scanning service.
When the ICAP server takes a very long time to process a file, the file upload might exceed the timeout configured for ActiveTransfer Server and fail. The expected behavior in this context is that ActiveTransfer Gateway must reset the total scan buffer size by adjusting the buffer size for the failed file transfer. However, currently, ActiveTransfer Gateway fails to adjust the total scan buffer size. Consequently, when the total buffer size falsely reaches the configured limit, ActiveTransfer Gateway denies additional file connections.
This issue is resolved.
- **MAT-6740**
ActiveTransfer file transactions fail when connecting to remote HTTP(S) servers through HTTP(S) proxy servers.
This issue is resolved.

Release 10.1

- **MAT-6633**
If the copy action in an event is configured to point to a third-party HTTP(S) server, even though the event log indicates that the event execution was successful, ActiveTransfer fails to copy files to the specified destination.
This issue is resolved.
- **MAT-6522**
Issue with triggering of post-processing events on upload of files in parallel.
Post-processing events are configured to trigger on file upload. However, when a large number of files are uploaded to ActiveTransfer Server in parallel (for example, through acceleration), post-processing events are not triggered for a small percentage (1% to 2%) of the files.
This issue is resolved.
- **MAT-684**
When you upgrade to ActiveTransfer 9.8 from an earlier version such as 8.2.2, 9.0.1, 9.5.1, 9.6, or 9.7,

the properties.cnf file in the Integration Server_directory\instances\instance_name\packages\WmMFT\config directory of the 9.8 installation is replaced with the file from the old installation. As a result entries for new properties in the properties.cnf file that were introduced in later versions are lost.

This issue is resolved.

Release 10.0

- MAT-2887
The ActiveTransfer log shows information that is not necessary to be logged for event actions that are configured using a remote file path.
This issue is resolved.
- MAT-2755
In ActiveTransfer Event Log, duplicate content is seen with different page numbers when the Event Log page is loading the results of your search. Sometimes, you might not see pagination information until the page loads the complete search result.
This issue is resolved.
- MAT-2738
ActiveTransfer does not recover gracefully from a database outage since it still uses some old connections in the database pool. This issue occurs when the minimum pool size is a non-zero number. As a result, the data displayed in ActiveTransfer configuration screens might not be current.
This issue is resolved.
- MAT-2708
In ActiveTransfer Server, a Filename filter configured for a find action which is not the first action in the event is not considered for listing. This impacts the performance of the event.
This issue is resolved.
- MAT-2706
In ActiveTransfer Server, when you configure event actions with a VFS which points to a remote location and if a request to the remote location receives no response, an incorrect error, is logged in the activity log.
This issue is resolved.
- MAT-2705
In ActiveTransfer Server, if a Filename filter is configured for a find action and if the source location is a remote FTP server, the filter is not taken into consideration when listing files. This impacts the performance of the event.
This issue is resolved.
- MAT-2702
ActiveTransfer Server changes the name of the file it is processing in a find action if the file name contains "{url}". This issue is specifically observed when the file is processed by calling an Integration Server service. The URL details substituted contain additional information that is not

required to be displayed.
This issue is resolved.

- **MAT-2676**
Using the `wm.mft.admin:changeLogLevel` service sometimes does not change the logging level in ActiveTransfer.
This issue is resolved.
- **MAT-2673**
In ActiveTransfer Server, concurrency issues were observed while logging in to the server in a high load environment which affects the overall performance of the server.
This issue is resolved.
- **MAT-2671**
In ActiveTransfer Server, if an event is configured without providing values for mandatory field, the action fails with null error. For example, when a copy action is configured without giving Destination URL value, the action fails with null error. This issue is observed in Zip, Move, Encrypt, and Delete tasks when the required input is not provided.
This issue is resolved.
- **MAT-2651**
In an ActiveTransfer Server scheduled event, when a rename action which is part of a series of actions configured in an event fails with a null value, the error action in the event is not triggered. As a result, the Event Log does not show that an error occurred in the event.
This issue is resolved.
- **MAT-2623**
The ActiveTransfer Event Log entries for event actions that fail due to network issues should contain the actual reason for the failure instead of the entry "Action failed : Broken pipe". ActiveTransfer logs "Action failed : Broken pipe". These log entries do not convey the reason for the failure and hence are not useful in troubleshooting event failures.
This issue is resolved.
- **MAT-2609**
ActiveTransfer Server sometimes bans its own IP address based on repeated requests from the IP address. This error is however not passed on to the error variable, `task_error`. The result is that this error is not logged.
This issue is resolved.
- **MAT-2605**
The Integration Server startup log in TRACE mode for WmMFT package shows entries for a user group called MFT Users which does not exist. Each time the WmMFT package is refreshed in Integration Server, it tries to register an incorrect user group called MFT Users in order to add the Administrator account to the system repository. As the MFT Users group does not exist, multiple messages are logged in the stack trace.
This issue is resolved.

- MAT-2585

The ActiveTransfer Server Event Log does not provide sufficient details on the event transaction errors. Some errors are logged with descriptions like "null", "broken pipe", and "connection reset" which are not helpful in troubleshooting the issue.

This issue is resolved.
- MAT-2536

In an ActiveTransfer Server event action, if you use wild card characters in the Source Filter, the action fails for a file name that has a character used for pattern matching (such as +, &, []). For example, if you have a source filter, *[filename] defined in an action where you specify the file name R3+My_File.zip.OK, the filter does not match any file name. This might cause the processing of incorrect files and the action might fail.

This issue is resolved.
- MAT-2523

In ActiveTransfer Server, a copy/move action involving FTP protocol in the source URL or SFTP protocol in the destination URL takes time to complete when there is an error because the FTP/SFTP connections to the remote servers are not released. This results in the task taking more time to complete.

This issue is resolved.
- MAT-2444

ActiveTransfer Server by default uses ssh-dss as the preferred public key algorithm when it communicates with a SFTP server. There should be a way to change the preferred public key algorithm based on the configuration in the remote SFTP server.

This issue is resolved.
- MAT-2412

ActiveTransfer Server specifies some details that should not be displayed in the ActiveTransfer.log file in clear text when log entries are created for event actions where the URL points to a remote server. The details in the URL which are not required to be displayed should always be masked.

This issue is resolved.
- MAT-2337

The ActiveTransfer Server management page does not provide adequate information on the status of the ActiveTransfer port that you create. The information provided in the server status section can sometimes lead to confusion with respect to the status of the port in the ActiveTransfer Server group.

This issue is resolved.
- MAT-2321

In ActiveTransfer Server, if you have a VFS pointing to remote SFTP server, the performance of the file transactions related to the remote server slow down if there is a high number of requests.

This issue is resolved.

Release 9.8

- MAT-1209
ActiveTransfer Server encodes any special characters used in filenames as a result of which these file names are shown with encoded characters in the My webMethods > Monitoring > Integration > Managed File Transfer > Event Log page. For example, the space character in a file name is replaced with "%20".
This issue is resolved.
- MAT-1052
In ActiveTransfer Server, a recursive directory browsing issue is observed when you access a VFS using HTTP or HTTPS ports and if the VFS name is the same as the name of a subfolder in that VFS.
This issue is resolved.
- MAT-1200
ActiveTransfer Server sometimes logs the status, Success for an event although one or more actions in the event are not successful. This issue occurs only in cases where ActiveTransfer Server is accessing files in a remote location using HTTP/HTTPS, and the user configured for the remote location does not have sufficient access privileges to the remote folder(s).
This issue is resolved.
- MAT-1256
In the ActiveTransfer Server Users page in My webMethods, if you select server ports to be included in the Send Email option for an existing ActiveTransfer user, the email received by the user does not contain the server port details selected.
This issue is resolved.
- MAT-1248
In an ActiveTransfer Server event, if you configure more than one Execute Integration Server Service action, ActiveTransfer might not display the Extract Service Output variables that you configure, correctly in the ActiveTransfer Event Management page in My webMethods.
This issue is resolved.
- MAT-1291
In the ActiveTransfer Server Event Management page in My webMethods, when you try to verify destination paths configured for any file action using the Test Connection button, the result of the test is not displayed.
This issue is resolved.

Release 9.6

- MAT-381
A "move" file operation does not delete files from the source server.
When you configure a "move" file operation as an action in ActiveTransfer post-processing and scheduled events to transfer files from one server to another, ActiveTransfer copies the files to the destination server but does not delete the files from the source server.
This issue is resolved.
- MAT-393

Encrypted content is missing from a file that is uploaded to a remote virtual file system. If file-based encryption is activated for an ActiveTransfer Server and files are uploaded to a remote VFS, the files are not encrypted correctly on the target VFS. These files contain headers but no content.

This issue is resolved.

- MAT-418 (MAT_8.2_SP2_Server_Fix1, MAT_9.0_SP1_Server_Fix1, MAT_9.5_SP1_Server_Fix1)
A "class not found" exception occurs at ActiveTransfer Server startup.
When ActiveTransfer Server starts up, the following error message is written to the Integration Server log file: java.lang.ClassNotFoundException: crushftp.db.StatTools.
This issue is resolved.
- MAT-420 (MAT_8.2_SP2_Server_Fix1, MAT_9.0_SP1_Server_Fix1, MAT_9.5_SP1_Server_Fix1)
ActiveTransfer Server does not execute configured error actions when some tasks fail.
ActiveTransfer Server does not execute the error action configured for a post-processing event when the following tasks fail: execute Integration Server service, execute Trading Networks service, send Broker notification, and send email.
This issue is resolved.
- MAT-425 (MAT_8.2_SP2_Server_Fix1, MAT_9.0_SP1_Server_Fix1)
ActiveTransfer Server does not execute some tasks configured for a scheduled event.
ActiveTransfer Server does not execute the following tasks configured for a scheduled event: execute Integration Server service, execute Trading Networks service, send Broker notification, and send email.
This issue is resolved.
- MAT-431 (MAT_8.2_SP2_Server_Fix1, MAT_9.0_SP1_Server_Fix1, MAT_9.5_SP1_Server_Fix1)
Attempts to access a remote virtual folder fail when using SSL-based protocols.
Accessing a remote virtual folder using an SSL-based protocol such as HTTPS or WebDAVs results in a NoClassDefFoundError error.
This issue is resolved. You can now access virtual folders using SSL-based protocols like HTTPS and WebDAVs.
- MAT-453 (MAT_9.0_SP1_Server_Fix2, MAT_9.5_SP1_Server_Fix2)
The webMethods ActiveTransfer File Transactions page does not display failed file transfers.
The transactions data displayed in webMethods ActiveTransfer File Transactions page does not include failed file transfers.
This issue is resolved. ActiveTransfer File Transactions page now lists successful as well as failed transactions.
- MAT-469 (MAT_9.0_SP1_Server_Fix2, MAT_9.5_SP1_Server_Fix2)
webMethods ActiveTransfer ignores the Source Filter defined for post-processing and scheduled events that contain Execute Integration Server Service actions.
ActiveTransfer triggers the Execute Integration Server Service action for all the files irrespective of the Source Filter that you have specified when defining the post-processing or scheduled events.
This issue is resolved.

- MAT-571 (MAT_9.0_SP1_Server_Fix2, MAT_9.5_SP1_Server_Fix2)
 My webMethods does not display a new user that you create in ActiveTransfer Administration > Integration > Managed File Transfer > Virtual Folder Management page.
 When you create a new user in My webMethods ActiveTransfer Administration > Integration > Managed File Transfer > Virtual Folder Management page, the user is not displayed when you refresh the page. The webMethods log shows an entry "User already exists". To add the user to ActiveTransfer, you need to search for the user in the existing user list and then add the user in ActiveTransfer.
 This issue is resolved.
- MAT-594
 An error occurs in My webMethods when you try to edit the configuration of a VFS to link it to a physical folder.
 In My webMethods, when you try to edit the configuration of an existing VFS to link it to a physical folder, the following error is thrown in the ActiveTransfer Virtual Folder Management page:
 [POP.016.0056] Invalid session token detected. Please reload the page.
 This issue is resolved.
- MAT-598 (MAT_9.0_SP1_Server_Fix2, MAT_9.5_SP1_Server_Fix2)
 webMethods ActiveTransfer does not execute an action when you set the "Execute asynchronously" option. ActiveTransfer does not execute a post-processing or scheduled action when you set the "Execute asynchronously" option. A ClassNotFoundException exception is displayed and the action fails.
 This issue is resolved.
- MAT-601
 A Soap Message Coder warning is logged in the Integration Server log.
 The following warning is logged in the Integration Server log when ActiveTransfer calls the wm.mft.portal.queries: doQuery service: Soap Message Coder warning; unregistered coder for variable fields, using String... This log entry is not because of an issue with the service. These warning messages should not be logged as they clutter the Integration Server log and may indicate that there is a problem with the service when there is none.
 This issue is resolved. The Soap Message Coder warnings are no longer logged in the Integration Server logs.
- MAT-602
 The browse button in the SSL options section of the ActiveTransfer Server Management page does not work.
 In My webMethods, the browse button for the Keystore Location field of the SSL options in the Advanced tab of the Administration > Integration > Managed File Transfer > Server Management page does not work.
 This issue is resolved.
- MAT-609 (MAT_9.5_SP1_Server_Fix2)
 webMethods ActiveTransfer does not display the Server and User logs in My webMethods.
 The Administration > Integration > Managed File Transfer > Logs page in My webMethods is empty and does not display the ActiveTransfer Server and User logs.

This issue is resolved.

- MAT-624
webMethods ActiveTransfer does not retain the change made to the default value in the scheduled event criteria, Fixed Interval.
When you configure a scheduled event based on the Fixed Interval criteria and change the default value, ActiveTransfer resets the Fixed Interval back to the default value (1 second) when you save the scheduled event.
This issue is resolved.
- MAT-630
In webMethods ActiveTransfer Server, user details are missing when you add an external LDAP user to an ActiveTransfer Server user profile.
When you add an external LDAP user to an ActiveTransfer Server profile, user information such as User Name, First Name, Last Name are missing in the user profile which in turn causes an error in My webMethods when you save the ActiveTransfer user configuration.
This issue is resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

ActiveTransfer Server

Release 10.3

The following context-sensitive webhelp is added and integrated in the user interface for ActiveTransfer 10.3 release:

- *Administering webMethods ActiveTransfer*

The PDF publication *Managing File Transfers with webMethods ActiveTransfer* has been updated as follows:

- Updated information related to configuring ActiveTransfer logs.
- Added a new chapter “Removing User Data from ActiveTransfer” to include information related to viewing and removing personally identifiable information (PII) to comply with the EU General Data Protection Regulation (GDPR).

The PDF publication *Managing File Transfers with webMethods ActiveTransfer Agent* has been updated to include changes related to installing, configuring, and using ActiveTransfer agents.

Release 10.2

All PDF publications, *Managing File Transfers with webMethods ActiveTransfer*, *webMethods ActiveTransfer Built-In Services Reference*, and *webMethods ActiveTransfer Web Client User's Guide* have been updated to include information related to new features and fixes since the ActiveTransfer 10.1 release.

The PDF publication *Managing File Transfers with webMethods ActiveTransfer* has been updated as follows:

- All ActiveTransfer Gateway information has been removed.
- The Command Central information in Chapter 1 "Understanding ActiveTransfer" has been moved to a new chapter 15 "Using Command Central to Manage ActiveTransfer."

The PDF publication *webMethods ActiveTransfer Web Client User's Guide* has been updated to include enhancements for file sharing with external users in Chapter 4, "Sharing Files and Folders."

A new PDF publication *Managing File Transfers with webMethods ActiveTransfer Gateway* includes all information related to configuring and managing ActiveTransfer Gateway.

A new PDF publication *Managing File Transfers with webMethods ActiveTransfer Agent* includes all information related to installing, configuring, and using ActiveTransfer agents.

Release 10.1

All PDF publications, *Managing File Transfers with webMethods ActiveTransfer*, *webMethods ActiveTransfer Built-In Services Reference*, and *webMethods ActiveTransfer Web Client User's Guide* have been updated to include information related to new features and fixes since the ActiveTransfer 10.1 release.

The PDF publication *Managing File Transfers with webMethods ActiveTransfer* has been updated as follows:

- In Chapter 2, Configuring webMethods ActiveTransfer and Chapter 11, Monitoring ActiveTransfer, webMethods MashZone information is modified to include information about newer version of the MashZone product, webMethods MashZone Next Gen.
- Chapter 13, Migrating Assets includes information about webMethods Deployer support of migration of assets and also corrections to the ActiveTransfer asset dependencies.
- In Chapter 1, Understanding ActiveTransfer, the section "How does ActiveTransfer work with Trading Networks?" has been enhanced to include more information about ActiveTransfer and Trading Networks integration.
- In Chapter 10, Managing Events, has the following changes:
 - Includes a new section "Activating, Deactivating, and Deleting Multiple Events," and a corresponding update has been made in the section "Activating Events".
 - Section "Encrypting and Decrypting Files" has been updated to include information about the new option to delete the original encrypted or decrypted file in encrypt and decrypt event actions.
- The following chapters have been updated with information on how ActiveTransfer handles

encryption and decryption keys are configured at the user management, virtual folder, and server management levels:

- Chapter 5, *Managing ActiveTransfer Server*, section “Activating File-Based Encryption and Decryption”
- Chapter 8, *Managing Users, User Groups, and User Roles*, section “Specifying Encryption and Decryption Options for a User”
- Chapter 9, *Managing Virtual Folders in a Virtual File System*, includes a new section “Specifying Encryption and Decryption Options for a Virtual Folder.”

Release 10.0

All PDF publications, *Managing File Transfers with webMethods ActiveTransfer*, *webMethods ActiveTransfer Built-In Services Reference*, and *webMethods ActiveTransfer Web Client User’s Guide* have been updated to include information related to new features and fixes since the ActiveTransfer 10.0 release.

The PDF publication *Managing File Transfers with webMethods ActiveTransfer* has been updated as follows:

- Chapter 2, *Configuring webMethods ActiveTransfer*, includes a new topic ‘Connecting to HTTP(S) Servers.’ This topic describes how ActiveTransfer interacts with third-party and ActiveTransfer HTTP(S) servers, and also includes information on the functionalities supported for file transfers to HTTP(S) servers.
- In Chapter 10, *Managing Events*, the find action, copy or move action procedures have been updated to include user interface changes for the support for third-party HTTP(S) servers.
- Information related to ports, and banning of ports in particular, has been enhanced in Chapter 5, *Managing ActiveTransfer Server*; Chapter 6, *Managing ActiveTransfer Gateway*; and Appendix A, *Server Configuration Parameters and Variables*.
- Appendix A, *Server Configuration Parameters and Variables* includes two new parameters, `mft.client.file.optimizeListing` and `mft.sharing.account.tempdir`.
- In Chapter 4, *Preparing to Manage and Monitor ActiveTransfer Server in My webMethods*, the topic ‘Searching for Items and Managing Search Results’ includes a new note about limiting the search criteria when exporting search results.
- In Chapter 8, *Managing Users and User Groups*, the procedural information has been enhanced for **Default Ports** and **Select Servers** field options.
- In Chapter 5, *Managing ActiveTransfer Server*, the procedural information has been enhanced for the option **Require Public Key Authentication**.

ActiveTransfer Gateway

Release 10.1

A new section, “Supporting Virus Scanning with Internet Content Adaptation Protocol,” which includes conceptual and task information, has been added to Chapter 6, Configuring ActiveTransfer Gateway in *Managing File Transfers with webMethods ActiveTransfer*.

Release 9.6

Conceptual information has been added to *Managing File Transfers with webMethods ActiveTransfer* for the following topics:

- Failover Support for File Transfer Operations: Multiple ActiveTransfer Servers can connect to one ActiveTransfer Gateway
- ActiveTransfer License File

The following procedural information has been added to *Managing File Transfers with webMethods ActiveTransfer*:

- Changing the ActiveTransfer License File

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

ActiveTransfer Server

Release 10.3

Old Term	New Term
Ports	Listeners

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

ActiveTransfer Server

Release 10.2

Added Item	Description
File Share	Use this tab under MFT Settings to set default values for the files shared with external users. These default values appear in the file share screen of the ActiveTransfer web client.
Direct link to file?	Use this field in the file share screen of the ActiveTransfer web client to allow users to directly view a single shared file on clicking the share link in the file share email.
View	Use this field in the file share screen of the ActiveTransfer web client to allow users to view the shared file. This field is selected by default.
Rename	Use this field in the file share screen of the ActiveTransfer web client to allow users to rename the shared file.
Create Folder	Use this field in the file share screen of the ActiveTransfer web client to allow users to create a new folder in the shared location.
Delete Folder	Use this field in the file share screen of the ActiveTransfer web client to allow users to delete a shared folder.
MFTAgentEventLog	This database table that captures the ActiveTransfer Agent the execution details of each agent event.
MFTAgentActivityDetails	This database table that captures the attribute details of ActiveTransfer Agent activities.
MFTAgentEventLog	This database table that captures detailed task level information on ActiveTransfer Agent activities.
PartitionTimestamp	Partition key column added to the MFTEventLog table.
PartitionTimestamp	Partition key column added to the MFTActivityLog table.
PartitionTimestamp	Partition key column added to the MFTActivityLogMessage table.

Added Item	Description
EventExecutionTime	Partition key column added to the MFTActivityDetails table.
Agent Event Log	Use this screen to access all the event execution details for ActiveTransfer agents.
Agent Activity Log	<p>Use this screen to access all details of all activities (asset download, event execution, and authentication) for ActiveTransfer agents. This screen has two tabs:</p> <ul style="list-style-type: none"> ▪ Details. Displays the basic agent activity information. ▪ Activities. Displays the complete activity log.
Agent Management	<p>Use this menu option in the navigation panel of My webMethods user interface to access the following configuration screens for ActiveTransfer Agent:</p> <ul style="list-style-type: none"> ▪ Agents ▪ Agent Groups ▪ Agent Events
CommandCentral.cnf	<p>Use this new properties file to add the webMethods Command Central details so that ActiveTransfer can establish a connection with the Command Central instance and fetch details of the ActiveTransfer agents installed.</p> <p>For details of the parameters in CommandCentral.cnf, see the added parameters section in this document or see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>
Removed Item	Replacement, if any
Advanced	Under the Share Type field, the fields that appeared on selection of this check box in the file share screen of the ActiveTransfer web client now appear along with the Copy field.
Advanced/Attach Thumbnail	None.

Removed Item	Replacement, if any
Advanced/Full Access	A new section Permissions replaces this checkbox and associated field. The Permissions section provides a list of new file access permissions in the file share screen of the ActiveTransfer web client.
External Share	None.
Internal Share	None.

Deprecated Item	Replacement, if any
Search for files by keyword in the ActiveTransfer web client	None.
Broker notification action in events	None.

Changed Item	Description
Reference	The fields that appeared on selection of this check box in the file share screen of the ActiveTransfer web client now appear along with the Copy field.
Move	The fields that appeared on selection of this check box in the file share screen of the ActiveTransfer web client now appear along with the Copy field.

Release 10.1

Added Item	Description
Activate	Use this button in the events list tables of the Events Management page to select multiple events and activate them.
Deactivate	Use this button in the events list tables of the Events Management page to select multiple active events and deactivate them.
	Use this button in the events list tables of the Events Management page to select multiple events and delete them. Note: If the deletion of a single event fails, the deletion of all selected events fails.

Added Item	Description
<p>Delete original file</p>	<p>Use this field when configuring encrypt and decrypt actions for events in the Event Management page. Select this field to perform one of these actions:</p> <ul style="list-style-type: none"> ▪ For encrypt action: Delete the original file and retain only the encrypted file. ▪ For decrypt action: Delete the original file and retain only the decrypted file.
<p>File-Based Encryption section</p>	<p>Use this section in the Virtual Folder Management page to specify file-based encryption PGP keys for a virtual folder. This section contains the following fields:</p> <ul style="list-style-type: none"> ▪ Activate. Select this check box to activate the use file-based encryption keys. <p>Public PGP Key Location. Specify the file path to the public PGP key in this text box.</p>
<p>File-Based Decryption section</p>	<p>Use this section in the Virtual Folder Management page to specify file-based decryption PGP keys for a virtual folder. This section contains the following fields:</p> <ul style="list-style-type: none"> ▪ Activate. Select this check box to activate the use file-based decryption keys. ▪ Public PGP Key Location. Specify the file path to the public PGP key in this text box. ▪ Private PGP Key Password. Enter the password for the private PGP key.
Changed Item	Description
<p>webMethods MashZone analytics and dashboards</p>	<p>ActiveTransfer now uses webMethods MashZone Next Gen analytics and dashboards. For more details on MashZone Next Gen, see MashZone Next Gen documentation. For details on how to configure and MashZone Next Gen to monitor file transactions in ActiveTransfer, see <i>Managing File Transfers with webMethods ActiveTransfer</i>.</p>

Release 10.0

Added Item	Description
SMB	Server message block (SMB) protocol is supported in event and virtual folder configurations.
ActiveTransfer HTTP(S) Server	<p>Use this field to enable or disable the use of third-party HTTP(S) servers in event configuration for the find and copy or move actions.</p> <p>In the copy or move actions, these additional HTTP request options are also available:</p> <ul style="list-style-type: none">▪ Request Method, with POST and PUT HTTP methods.▪ Request Headers table, that allows you to specify additional headers and values in the respective text boxes for the request method selected.

ActiveTransfer Gateway

Release 10.1

Added Item	Description
Antivirus Scan	Use this tab in the Server Management page for ActiveTransfer Gateway configure virus scanning using a third-party to perform antivirus scanning of inbound files by using a third-party antivirus scanner which supports ICAP(Internet Content Adaptation Protocol).

ActiveTransfer Agent

Release 10.3

Removed Item	Replacement, if any
--------------	---------------------

Removed Item	Replacement, if any
security.cnf	<p>com.softwareag.mag.common.properties. Use this file to provide the password for the ActiveTransfer Agent user in plain text. This ensures that the password is encrypted.</p> <p>The file is available on the ActiveTransfer Agent host in the <i>Installation_directory</i>\profiles\MAG\configuration\com.softwareag.platform.config.propsloader directory.</p>
ATServerDetail.xml	<p>com.softwareag.mag.common.properties. Use this file to provide the ActiveTransfer Server details and the ActiveTransfer Agent user credentials registered in ActiveTransfer Server if you have installed the ActiveTransfer Agent instance directly by using Software AG installer or an image. This file is automatically populated if you used Command Central to install the agent instance.</p> <p>The file is available on the ActiveTransfer Agent host in the <i>Installation_directory</i>\profiles\MAG\configuration\com.softwareag.platform.config.propsloader directory.</p>

Release 10.2

Added Item	Description
security.cnf	<p>Use this file to provide the password for the ActiveTransfer Agent user in plain text. This ensures that the password is encrypted.</p> <p>The file is available on the ActiveTransfer Agent host in the <i>Integration Server_directory</i>\instances\<i>instance_name</i>\packages\WmMFTAgent\config directory.</p> <p>For more details on the security.cnf file, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>

Added Item	Description
ATServerDetail.xml	<p>Use this file to provide the ActiveTransfer Server details and the ActiveTransfer Agent user credentials registered in ActiveTransfer Server if you have installed the ActiveTransfer Agent instance directly by using Software AG installer or an image. This file is automatically populated if you used Command Central to install the agent instance.</p> <p>The file is available on the ActiveTransfer Agent host in the <i>Integration Server_directory</i>\instances\<i>instance_name</i>\packages\WmMFTAgent\config directory.</p> <p>For more details on the security.cnf file, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

ActiveTransfer Server

Release 10.3

Deprecated Service	Replacement, if any
wm.mft.assets.rec.event.action.properties:SendBrokerNotification	None.

Release 9.8

Deprecated Service	Replacement, if any
wm.mft.admin:property	wm.mft.admin:manageProperties

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

ActiveTransfer Server

Release 10.3

Added Parameter	Description
mft.agent.event.log.activityTypes	<p>Use this parameter to specify the types of agent event activities for which logs are created.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>

Release 10.1

Removed Parameter	Replacement, if any
mft.external.tn.maxFileSize	None.

Changed Item	Description
mft.group.aliases	<p>Use this parameter to specify remote server aliases of ActiveTransfer nodes that are part of a group (that is, nodes that share a common database). The ActiveTransfer instance shares asset information with the ActiveTransfer nodes specified in this property.</p> <p>Earlier, this property was used only if ActiveTransfer was configured to use Trading Networks partners.</p> <p>For more details on mft.group.aliases , see <i>Managing File Transfers with webMethods ActiveTransfer</i>.</p>

ActiveTransfer Gateway

Release 10.0

Added Parameter	Description
mft.client.file.optimizeListing	<p>Use this parameter if ActiveTransfer's optimized or normal file listing functionality must be used on Microsoft Windows Server directories.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Gateway</i>.</p>
mft.sharing.account.tempdir	<p>Use this parameter to specify a custom shared file location to use instead of the default shared file location. This custom shared file location can be any local or shared directory.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Gateway</i>.</p>

ActiveTransfer Agent

Release 10.3

Added Parameter	Description
mft.agent.client.assets.refresh.interval	<p>Use this parameter to specify the time interval at which an agent interacts with an ActiveTransfer Server instance to check for updates about the agent event assets.</p>
mft.agent.client.auth.retry.interval	<p>Use this parameter to specify the interval at which an agent checks for client authentication with an ActiveTransfer Server instance after every failed attempt.</p>
mft.agent.client.auth.retry.count	<p>Use this parameter to specify the number of retries allowed after failed attempts by an agent for client authentication checks with an ActiveTransfer Server instance.</p>

Release 10.2

Added Parameter	Description
-----------------	-------------

Added Parameter	Description
mft.server.commandCentral.host	<p>Use this parameter to specify the name of the machine that hosts Command Central. The property is available in the CommandCentral.cnf file available in <i>Integration Server_directory</i>\instances\<i>instance_name</i>\packages\WmMFT\config directory.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>
mft.server.commandCentral.port	<p>Use this parameter to specify the port used for Command Central. The property is available in the CommandCentral.cnf file available in <i>Integration Server_directory</i>\instances\<i>instance_name</i>\packages\WmMFT\config directory.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>
mft.server.commandCentral.port.secure	<p>Use this parameter to specify if communication protocol with Command Central must be HTTP or HTTPS port. The property is available in the CommandCentral.cnf file available in <i>Integration Server_directory</i>\instances\<i>instance_name</i>\packages\WmMFT\config directory.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>
mft.server.commandCentral.username	<p>Use this parameter to specify the user name to use when connecting to Command Central. The property is available in the CommandCentral.cnf file available in <i>Integration Server_directory</i>\instances\<i>instance_name</i>\packages\WmMFT\config directory.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>
mft.server.commandCentral.password	<p>Use this parameter to specify the password to use when connecting to Command Central. The property is available in the CommandCentral.cnf file available in <i>Integration Server_directory</i>\instances\<i>instance_name</i>\packages\WmMFT\config directory.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>

Added Parameter	Description
mft.agent.user	<p>Use this parameter in the properties.cnf file to specify user names that the ActiveTransfer Agent instance uses to connect to ActiveTransfer Server, with comma as the separator.</p> <p>The properties.cnf file is available on the ActiveTransfer Server host in the <i>Integration Server_directory</i>\instances\<i>instance_name</i>\packages\WmMFT\config directory.</p> <p>For more details on the parameter, see <i>Managing File Transfers with ActiveTransfer Agent</i>.</p>

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

ACTR-RM-103-20181015

Apama 10.3 Readme

October 2018

This file contains important information you must read before using Apama 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	3
4.0	Fixes Included in Each Release.....	8
5.0	Other Resolved Issues.....	9
6.0	Documentation Changes	29
7.0	Terminology Changes	29
8.0	Added, Removed, Deprecated, or Changed Items.....	30
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	30
10.0	Added, Removed, Deprecated, or Changed Parameters.....	30
11.0	Added, Removed, Deprecated, or Changed APIs	30
12.0	Copyright Information.....	30
13.0	Support.....	31

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

Important: The Software AG Update Manager allows you to individually select which fix packages you wish to install. However, to ensure that all dependencies between the Apama fix packages are met, it is essential that you always select, and thus install, all Apama fix packages - do not try to install fixes for a subset of the Apama components you have installed.

For installation information, see *Installing Apama* in the downloaded package (accessible via the index.html file which is in the doc/apama-onlinehelp directory of your Apama installation directory) or on the [Documentation website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- PAM-28499
Cannot correctly override configuration properties with UTF-8 strings in a Command Central template (since 10.2.0.0).
When using Command Central templates to configure an instance of an Apama correlator, the UTF-8 character encoding of property keys and values in the `APAMA-PROPS-OVERRIDES` configuration item will not always be honored.
We do not recommend using characters in property keys and values outside of the ASCII range.
- WF-5508
Designer does not start after install if UAC is turned on (since 9.9.0).
If this issue is encountered, see the section "Managing Designer User Configuration" in *Working with Software AG Designer*, which can be found in the "Guides for Tools Shared by Software AG Products" section of the [Documentation website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

ADBC

- PAM-28453
Core dump in `ADBC AP_NormalisedEvent_dtor/_int_free - double free`.
We recommend that you install the latest RHEL patches and we strongly recommend the patch `glibc-2.17-106.el7_2.6 (7.2)` as it is known to fix an issue which can result in a crash when freeing memory.
- PAM-21466
Bundled Oracle JDBC driver can incorrectly report Oracle Advanced Security errors (since 5.2.0.0). Even when Oracle Advanced Security is not turned on for the server, the following error can occur during connect:
`[Oracle JDBC Driver]The connect attempt failed because the server requires Oracle Advanced Security. To enable the driver to use OAS, please use the "dataIntegrityLevel" and/or "encryptionLevel" connect options.`
To work around the issue, set the connection URL option `randomNumberGenerationOptions` to one of the following values:
"1" - The driver uses secure random numbers for handshake. The driver generates secure random numbers before the start of handshake, thus preventing this issue to occur due to the amount of time the connection needs to be made.
"2" - The driver uses random numbers instead of secure random numbers for handshake. This is less secure but provides a faster connection to occur.
DataDirect recommends setting this to the value of "1" and then re-testing. If the issue still occurs, then try the value of "2".
- PAM-23063
Occasional connection errors with some JDBC drivers. It is not recommended to use multiple correlators against a single IAF, as the message IDs might not be unique and therefore could result in failures.
- PAM-10573
Some supported databases store empty strings as NULL (since 5.3.0.0).
Some databases such as Oracle are known to store empty strings as NULL values, which can lead to confusion when executing queries where a field is compared to the empty string. For example, the following would not match rows where the field was null for such databases:
`select * from table where field = ""`
To ensure the desired results are returned when running queries against databases that store empty strings as null, we recommend queries to be written to check for NULL instead of empty string literals.

- PAM-3876
Support for NaN in Apama ADBC adapter (since 5.0).
Support for storing and retrieving a NaN value is not supported with all databases. The following databases have been tested:
 - MS SQL Server and MySQL - No support. Database does not support NaN values.
 - DB2 - Not supported for JDBC.
 - Oracle - Full support for JDBC.

Adapters

- PAM-28507
RabbitMQ limitations - this applies to RabbitMQ 3.6.12.

Reliability concerns

- Messages can be lost when queues become full: RabbitMQ requires a maximum queue length or size to be set, and when the maximum is reached it will drop or dead-letter (that is, republish to another exchange) the oldest messages in the queue by default. Setting the `overflow` configuration option to `reject-publish` discards the most recently published messages. There is no behavior that does not involve silently dropping messages once the queue limit is reached, and the sender will not be aware when this happens. If dead-lettering is configured, RabbitMQ routes rejected messages to a special dead-letter queue.

The problem is mitigated somewhat by the fact that RabbitMQ also blocks publishers once available memory to the entire process goes below a certain level, but this is a lot less fine-grained than other JMS providers' per-channel limits. It should however be possible to configure the queue size to be large enough such that the available memory limit is reached before the queue size limit is reached.

Features of the JMS specification not supported by RabbitMQ

- Message selectors for queues (which allow a JMS application to filter messages using an expression based on SQL syntax) are not currently supported. Message selectors can be used with topics but only if the RabbitMQ Topic Selector plug-in is installed on the RabbitMQ server.
- No local support: RabbitMQ does not support the `no-local` parameter when receiving. This is a rarely-used JMS flag which prevents a topic receiving messages that were published using the same connection object.
- RabbitMQ ignores attempts to specify the delivery mode (`PERSISTENT/NON_PERSISTENT`) on a per-message basis, so it is only possible to set this for the entire sender.

Other limitations

- Unlike most JMS providers, RabbitMQ does not have its own JNDI server, and for technical reasons related to the way it loads queue/topic classes, it is not possible to use it from Apama without JNDI. As a result, it is necessary for customers to manually configure the JDK's built-in file system JNDI store to point to the RabbitMQ JMS connection factory.

- PAM-15644
Unicode variable names in mapping rules cannot be resolved (since 5.0).
Mapping in Web Services Client adapter and correlator-integrated messaging adapter for JMS does not support internationalization for variable names. That is, only English characters are allowed in complex mapping template variable names.

Software AG Designer

- PAM-21618
Pre-existing JDBC/ODBC projects do not start after Ant export (since 5.3.0.0).
Existing JDBC adapter projects (5.2 and older) will require manual updating when used with Apama 5.3 and older to address a problem with Ant Export project referencing incorrect location for the adapters folder. To perform this update, you need to follow the steps below:
 - In the Project Explorer, right-click the project and select **Properties**.
 - Navigate to **Apama > MonitorScript Build Path** and select the **Bundles** tab.
 - Select the **JDBC Adapter:\ADBC-JDBC.bnd [Adapter catalog]** node.
 - Click the **Update** button.
 - A **Bundle instance** warning box will be shown to ask you for whether to back up existing files.
 - Choose **Yes**.
 - Your instance file should be updated to address this Ant Export issue.
- PAM-21378
Creating duplicate launch configuration does not honor previous launch values (since 5.2.0.0).
Duplicating the Apama launch configuration whose mode is set as “shared” will not duplicate the deploy configuration. When the “Duplicate” action of the launch configuration dialog is invoked on selecting an Apama launch configuration which is in “shared mode”, an error dialog appears, saying that deploy configuration does not exist and it then reverts to the default settings. To complete the duplication of the launch, go to the folder where the launch configuration exists and copy the contents of its deploy file at the same location and name as launch. Paste the contents to the new deploy file (which shares the name of the new launch configuration) and save the file. This extra manual step will complete the “Duplicate” action.

Correlator

- PAM-21747
Apama queries do not appropriately map line numbers when reporting exceptions (since 5.3.0.0).
While compile-time errors are reported with the correct line number for Apama queries, runtime exceptions are not. If a runtime exception is thrown, then the stack trace of the exception (whether uncaught and reported by the correlator, or inspected by a catch statement in EPL) will show some details of the queries runtime system, and the line numbers will not correspond to lines in the query source file.

Dashboards

- PAM-21512
Dashboard client is showing exception in log when dashboard server is stopped (since 5.2.0.0). The following error message will be logged to the dashboard client log file(s) when shutting down the connected dashboard server process(es):

```
ERROR [GmsClientReceiverThread-<host>:<port>] - error receiving message:  
java.net.SocketException: Connection reseterror receiving message:  
java.net.SocketException: Connection reset (<host>:<port>)
```

This message merely indicates the disconnection between the dashboard components and the server. Despite being logged as `ERROR`, these messages are informational only.
- PAM-12975
Panels deployments can save header when disconnected from webserver (since 4.3).
If `panels.ini` is used for display server dashboard, then an invalid HTTP session (for example, re-start Tomcat) will result in a `sessionExpired` page inside the main frame of the dashboard. Clicking on the login link on that page to re-login will *not* clear the previously displaying tabs/trees. Refresh the web browser or re-visit the dashboard URL to fix the problem.
- PAM-12699
Filters containing quotes are broken when running with enhanced query mode (since 4.3). Attachments where the filter value is a string containing a quote do not work in enhanced query mode. In enhanced query mode, attachment filters are turned into SQL WHERE clauses. When using enhanced query mode and having the need to filter by values containing quotes, you need to escape each quote with a quote. Double quotes do not need to be escaped.
- PAM-11994
Re-deploy of dashboard does not delete cached files (since 4.2.2).
If dashboard files were removed between two display server deployments (that is, deploy `foo.rtv`, then delete `foo.rtv` from project and re-deploy), the deleted dashboard files will still be available for the re-deployed client. To work around this, delete the reference directory, `APAMA_WORK/dashboards/depoyed_dashboard`, manually before re-deploying.
- PAM-11830
Improperly defined JDBC connection causes CPU spike in SQL server when using Dashboard Builder (since 4.2.2).
Dashboards using the SQL datasource with invalid JDBC connection parameters can sometimes cause high CPU usage due to numerous failed JDBC connection attempts to the SQL server. This issue can occur if an invalid JDBC password is specified and the Dashboard Builder SQL option **Get Tables and Columns** is enabled.

- PAM-11716
 Custom window title from Dashboard Builder options is not supported (since 4.2.2).
 Setting window titles in the Dashboard Builder using **Custom Window Title** in **Tools > Options > General** tab is not supported. Window titles can be set on the command line used to invoke the dashboard viewer.
- PAM-11551
 Apama commands in display server with large amounts of string data may fail (since 4.2).
 Executing Apama commands in display server deployments with large amounts of string data may fail if the resulting HTTP GET request exceeds the maximum allowed string length.
- PAM-10722
 Dashboard deployment wizard does not re-sign already signed jars (since 4.2).
 The dashboard deployment utility in Software AG Designer will not re-sign jar files that are already signed. If you add jar files to your dashboard deployment that are already signed, you may see errors when accessing the deployed dashboards. When using the dashboard deployment utility, you can sign all jars, or none of them (in this case, they would all need to be signed already), or (if you have a mix of signed and unsigned jars) sign with the same certificate that was used for the jars that have already been signed. If you'd like the deployment utility to sign jars that have been previously signed, you will have to first remove their signatures.
- PAM-5474
 Display server dashboards clearing edited text field on update (since 3.0.2).
 Input controls when displayed via the dashboard server may clear any edits when the display is updated. This makes it very difficult to use input forms with the display server. The problem occurs with input controls that are attached to either an Apama scenario, DataView, or dashboard function. When creating input forms in dashboards that will be deployed via the display server, you can follow one of the following techniques:

 - Do not attach the value property of input controls to Apama scenarios, DataViews, or functions. This is fine if the current value of the attachment does not need to be displayed in the control.
 - Attach the value property of input controls to variables set as the result of a drilldown. This will allow the initial value to be set to the value of the variable. The deficiency here is that if the value changes externally, it is not reflected in the control unless a new drilldown is performed.
- PAM-4405
 Delete All with many instances blocks UI (since 3.0).
 Using the Dashboard Builder's **Delete All** command to delete large numbers of scenario instances can make the dashboard user interface appear blocked. This is because control is not returned to the user interface until the **Delete All** operation has completed.

Other

- PAM-29492
The `python` executable is no longer provided in Apama-shipped Python on Linux (since 10.3). Starting with Apama 10.3, Apama will be providing Python 3 on distributions which include Python and will no longer provide a symlink to the `python` executable on UNIX distributions. Users wishing to invoke the Python 3 interpreter need to run `python3` instead of `python` to invoke the Apama-provided Python interpreter on UNIX distributions.
- PAM-24164
ApamaDoc link in online help does not work in Internet Explorer (since 9.10). With Internet Explorer 11, it is not possible to invoke the ApamaDoc from the *API Reference for EPL (ApamaDoc)* page of the online help. This problem does not occur in other browsers such as Firefox. As a workaround for Internet Explorer 11, right-click the link, copy the link using the **Copy shortcut** command, and then paste the link into the Internet Explorer's address bar.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.2

- PAM_10.2.0_Fix3

Release 10.1

- PAM_10.1.0_Fix9

Release 9.12

- PAM_9.12.0_Fix11

Release 9.10

- PAM_9.10.0_Fix10

Release 9.9

- PAM_9.9.0_Fix14

Release 5.3

- PAM_5.3.0_Fix7

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3.0

Correlator

- PAM-29565
Permanent split brain in clustered queries due to the primary key optimization (since 10.3.0.1). A bug was fixed in which the contents of an Apama queries window could diverge between correlators that were executing Apama queries in a cluster. This data divergence would only usually occur if the injection order of the Apama queries differed between correlators. Since this fix will change how some data is stored in the underlying data store, if you were running queries prior to the fix installation, there may be a loss of temporary in-process data after the fix is applied. For proper Apama query results, all correlators in the cluster must have the fix applied.
- PAM-29311
LLVM caching does not take primitive constants into account as dependencies (since 10.3.0.1). EPL that uses only primitive constants in the event type is not counted as depending on that event type and that breaks the LLVM caching. This issue has been fixed. Now data-only events are counted as dependent on whatever uses them.
- PAM-29377
Occasionally lose a few lines or crash during log rotation (since 10.3.0.0). The issue has been fixed whereby in some cases, it was possible for the correlator to lose a few lines or, in extreme cases, crash during log rotation.
- PAM-29233
Correlator crash on Linux when logging bumps up against disk limits (since 10.3.0.0). When the correlator cannot log due to disk limits, the correlator will now attempt to log a helpful error message and call immediate exit instead of crashing.
- PAM-29143
Correlator crash in interpreter for unmatched `switch` case (since 10.3.0.0). In some cases, it was possible for the correlator to crash if an EPL exception were thrown during `switch` statement execution. This issue has been fixed.

Dashboards

- PAM-29291
In dashboards, the button foreground (font) property is not honored when the button is disabled (always grey) (since 10.3.0.1).
In previous versions of Apama dashboards, the foreground color of a disabled button was always grey. In this fix, there is a new property to allow for the selection of a specific foreground color when a button is disabled. The default will remain grey.

EPL Plug-ins

- PAM-29511
Python plug-in logging needs to be less spammy (since 10.3.0.1).
The Python plug-in would log messages unnecessarily at INFO log level. The implementation has been changed to log several issues at DEBUG to reduce INFO level logging.
- PAM-29295
HTTP client transport should not send `Accept-Encoding: *` since we do not support all encodings (since 10.3.0.0).
The HTTP client no longer incorrectly sends `Accept-Encoding: *` as a header since we do not accept gzip encoding.
- PAM-29260
Crash sending recursive types from plug-ins (since 10.3.0.0).
A crash in the correlator when sending events containing cycles or any values from EPL plug-ins has been fixed.
- PAM-29116
HTTP Generic client sends GET requests with `payload = ""` by default (since 10.3.0.0).
If no value was specified for the payload in EPL, we sent an empty string as a payload. Some servers assume that there will be no payload, despite a `Content-Length` header and fail to read the request. This issue has been fixed. Now GET requests do not have any payload unless the user specifies this in the EPL.
- PAM-29115
Mapper codec - `defaultValue` overrides metadata values (since 10.3.0.0).
The `defaultValue` rule of the Mapper codec will no longer always be applied to metadata fields, and instead will only be applied in the case of an empty/null metadata field.
- PAM-29039
The `persist()` method on the Management interface sometimes fails to call back (since 10.3.0.0).
The persistence thread would sometimes get blocked while waiting for a large snapshot interval to expire. The fix mitigates the issue which happens only when `snapshotInterval` is set to a very large number causing the thread to miss the signal from a context.

Designer

- PAM-29521
No Designer support for hash methods (since 10.3.0.1).
The `hash()` method has been added to the completion proposal list for the following built-in types: `boolean`, `any`, `Channel`, `context`, `location`, `decimal`, `dictionary`, `Exception`, `float`, `integer`, `optional`, `sequence`, `StackTraceElement`, and `string`.
- PAM-29434
Issue with auto-completion of several methods of the `any` type (since 10.3.0.1).
The following methods have been added to content-assist for the `any` type :
`hasAction(string actionName)`, `hasEntry(any key)`, `hasField(string fieldName)`, `parseType(string typeName, string stringForm)`, `empty()`, and `hash()`.
- PAM-29231
`engine_deploy --outputCDP` does not correctly package queries (since 10.3.0.0).
When using the `engine_deploy` tool to create a correlator deployment package from a project using the `--outputCDP` option, any query files (`.qry`) in the project would not be correctly converted. This would manifest as injection errors at the point the user attempted to inject the CDP into the correlator. This issue has been fixed.
- PAM-28577
Linked-resources are not getting honored from dependent bundles (since 10.3.0.0).
Projects were not considering linked resources inside of dependant bundles when resolving dependencies, leading to errors for the dependant bundles. Linked resources will now be included when resolving dependencies of dependant bundles.
- PAM-28576
Terminate and relaunch from history fails for Apama correlator (since 10.3.0.0).
In previous versions, the Designer process would sometimes hang if **Terminate and Relaunch from history** was used. The confirmation dialog to confirm stopping of the project was removed as this caused a race which led to a Designer deadlock.
- PAM-28026
Connectivity and Adapters node should be visible in all projects (since 10.3.0.0).
The **Connectivity and Adapters** and the **EPL bundles** nodes are now shown for every project irrespective of whether the project has an adapter/bundle or not. Now users can add adapters/bundles by right-clicking the respective node . The **Add Connectivity and Adapters** and **Add Bundle** commands have therefore been removed from the **Apama** context menu.

Documentation

- PAM-28945
`optional.parse` is wrong about the string form of optionals (since 10.3.0.0).
The EPL comments which generate the ApamaDoc documentation for `optional.parse` have been updated to correctly reflect the correct string form which can be parsed.

APIs

- PAM-29583
Connectivity and EPL plug-in headers - bugs with modern compilers (since 10.3.0.1).
An error in the connectivity and EPL plug-in headers has been fixed, which failed to compile in more recent compilers than provided by default on C++11. An issue has also been fixed which assumed you would be importing with `using namespace` instead of importing symbols individually.

Release 10.2.0

Correlator

- PAM-29143
Correlator crash in interpreter for unmatched switch case (since 10.2.0.3).
In some cases, it was possible for the correlator to crash if an EPL exception was thrown during switch statement execution. This issue has been fixed.
- PAM-29092
Crash when quitting event expressions with a single string equality filter (since 10.2.0.3).
A correlator crash caused by the incorrect management of the lifetime of string objects used in single-value listeners has been fixed.
- PAM-28797
`StatusItem::setStatus(const std::string &)` not thread safe in C++ connectivity API (since 10.2.0.3).
The connectivity helper class function `StatusReporter::setStatus(std::string)` is now thread safe.
- PAM-28663
Correlator crash when calling action on an event instance created through reflection.
A potential crash while calling an action on an event created through reflection has been fixed.
- PAM-28643
Intermittent crash in `persistObjects`.
A rare crash when a context goes empty (when the last monitor instance in it terminates) while events are being delivered to it when using persistence has been fixed.
- PAM-28591
Correlator crash in LLVM mode when using `any()` syntax to create an empty `any` value.
A correlator crash in LLVM mode when creating an empty `any` value using `any()` syntax has been fixed.

EPL Plug-ins

- PAM-29091
Connectivity 'weather' sample relies on an API being removed in July (since 10.2.0.3).
The geo-location API used for the Weather sample (freegeoip.net deprecated in July 2018) has been updated.

Dashboards

- PAM-24000
Dashboard HTTP XML request for `info/envp` fails if environment variable has invalid Unicode characters.
An issue has been fixed so that Unicode characters, both valid and invalid ones, can be passed.
Even the surrogate pairs (multi-byte or wide characters) can be passed. No exception shall happen.

Release 10.1.0

Software AG Designer

- PAM-26968
Cannot install Apama products incrementally using Command Central (since 9.12.0.0).
Once Apama server is installed via Command Central, attempting to install components via Command Central that have a dependency on Apama server will fail. The only alternative is to install all components that have a dependency on Apama server at the same time. This issue has been fixed.

Adapters

- PAM-28320
RabbitMQ should be enabled as a JMS provider (since 10.1.0.3).
Support for RabbitMQ as a JMS provider has been added. There is no drop-down to select RabbitMQ in Software AG Designer 10.1, but RabbitMQ can be configured using JNDI configuration.

ADBC

- PAM-28264
Memory leak in ADBCHelper API `doSQLQuery` (since 10.1.0.3).
A per-query memory leak in the ADBC adapter has been fixed when running multiple `select` queries.

Correlator

- PAM-28338
Copies of optionals in cyclic values are not persisted correctly (since 10.1.0.3).
A bug has been fixed where cloned `optional` values containing cyclic types could result in a corrupt persistence database which would crash the correlator when trying to recover.
- PAM-28309
Monitors may not be garbage-collected sufficiently frequently - large strings (since 10.1.0.3).
Monitor instances now count the sizes of containers and strings and use these sizes to determine when to perform garbage collection. This avoids excessive memory usage and improves performance if using persistence by reducing the amount of garbage objects persisted.
- PAM-28269
Persistent monitors may not be garbage-collected sufficiently frequently - large containers (since 10.1.0.3).
Monitor instances now count the sizes of containers and strings and use these sizes to determine when to perform garbage collection. This avoids excessive memory usage and improves performance if using persistence by reducing the amount of garbage objects persisted.
- PAM-28248
Race to losing context names and state from persistence database (since 10.1.0.3).
A defect has been fixed to prevent a race condition in an edge case that could, if certain application patterns were followed, lead to a context losing its name and public flag (that is, not receiving events sent to the default channel).
- PAM-28169
Crash in garbage collection in a persistent correlator: persisting an event on a queue incorrectly sets `containingContext` (since 10.1.0.3)
A correlator defect has been fixed where an event on a context queue at the point when a persistent snapshot was taken would be left in a slightly incorrect state. If the context that was processing it then performed certain actions, this could lead to a race condition whereby subsequent garbage collection of a string from the event in a monitor instance could crash.
- PAM-28137
Deadlock in persistent correlator during CDP injection (since 10.1.0.3)
A rare deadlock which was introduced by a previous fix, has been fixed. This deadlock could occur when injecting a CDP containing event files into a persistent correlator.
- PAM-27506
Flow control is to be added if persistence snapshots fail to complete in a reasonable time (since 10.1.0.3).
Tighter flow control has been implemented, blocking external senders sending events into a persistent correlator if the correlator has not been able to complete a persistent snapshot. This should avoid excessive queuing of JMS events in reliable receive databases.

- PAM-27991
Crash in recovering a `MonitorAdder` of a non-persistent monitor instance (since 10.1.0.2).
A defect where the correlator could crash if recovered immediately after injecting a non-persistent monitor has been fixed.
- PAM-27964
Monitor-internal events of non-persistent monitors should be persistable (since 10.1.0.2).
A defect where the correlator would not correctly handle monitor-internal events from other monitors in a persistent monitor accessed via the `any` type has been fixed.
- PAM-27775
`engine_debug` cannot access numbers above 999 (since 10.1.0.2).
The command line EPL debugger (`engine_debug`) and the EPL debugger available through Software AG Designer did not work with monitor instance IDs (or other numbers) above 999. This restriction has been removed.
- PAM-27626
Terminated `mThread`'s dictionary contents are not removed from persistence database (since 9.9.0.0).
A correlator defect has been fixed which would leave redundant entries in the persistence database if a monitor instance was terminated while it had non-empty dictionary objects.
- PAM-27370
Coassigning a cyclic object in a persistent monitor can cause the correlator to crash (since 9.9.0.0).
A defect with the incorrect persistence of an object with a cyclic data structure that is copied into a persistent monitor has been fixed.

EPL Plug-ins

- PAM-28374
Profiling showing zero for `getTotal` output for plug-ins (since 10.1.0.3).
The profiling option `getTotal` no longer incorrectly returns zero for all columns other than cumulative time and CPU time.
- PAM-28159
HTTP server and client fail to parse unknown content-type parameter (since 10.1.0.3).
A bug has been fixed where the HTTP server and transport would reject messages which had a `Content-Type` with a non-standard parameter which also did not have a `charset` parameter. These messages are now accepted and the non-standard parameters are ignored.
- PAM-27910
MQTT transport requires explicit configuration of SSL options for non-SSL use (since 10.1.0.2).
The default value for `acceptUnrecognizedCertificates` in the MQTT bundle has been corrected to be `false` rather than the empty string.

- PAM-27816
Occasional core dump in `MQTTAsync_receiveThread/MQTTAsync_retry` (since 10.1.0.2).
When the MQTT transport dropped a connection to a broker due to an authentication or SSL error, on very rare occasions the transport would lock up or cause a correlator crash. This has now been fixed.
- PAM-27360
HTTPClient inserts nulls into data stream around the 100k mark (since 9.12.0.0).
The HTTP client with long messages could insert nulls into the message if it was longer than 100k (but not all bytes after 100k), which then caused the resulting string to appear truncated. The result would be 100k of data, then 100k of 0s, followed by more data. This has been fixed so that all the message data is now available.
- PAM-27296
Wrong object type created when a `Channel` object is constructed from a context inside a Java plug-in (since 9.9.0.0).
In a Java plug-in, if a `com.apama.epl.plugin.Channel` object was constructed from a `com.apama.epl.plugin.Context`, the returned object type was `com.apama.epl.plugin.Context` - which is incorrect. This issue has been fixed such that the expected object type is now returned.
- PAM-27150
Sending events to Kafka at a high rate can result in some being dropped (since 10.0.0.0).
This is a Kafka issue. The producer should not be dropping events when there is progress. The workaround is defaulting `request.timeout.ms` to `Integer.MAX_VALUE`. This value is now the default (the user can override it though).

Dashboards

- PAM-28121
Improper handling of decimal types with `--enhancedQuery mode` (since 10.1.0.3).
Decimals support in the dashboards as `double` with `enhancedQuery mode` is now enabled.

Other

- PAM-26580
`engine_management` return code is 0 for failure (since 9.9.0.0).
In the majority of cases, `engine_management` gave a zero return code in the previous release, even when it failed. It will now give a non-zero return code on failure.

Release 10.0.0

ADBC

- PAM-24864
ADBC `deleteStoreStatement` does nothing and cannot be used.
The `deleteStoreStatement()` now works correctly.

Software AG Designer

- PAM-27151
The command `engine_deploy --outputDeployDir <relative path>` fails only when DES is enabled (since 10.0.0.2).
YAML generation was failing when a project with Digital Event Services (DES) enabled was exported to an output directory specified with a relative path. This issue is fixed now.
- PAM-27177
ApamaDoc export fails when the Apama project contains query files (since 10.0.0.0).
When ApamaDoc is generated for an Apama project containing query files, the operation fails. This issue has been fixed.
- PAM-27039
Ant run fails if a project has a parent excluded folder and a child folder has a jar (since 10.0.0.2).
If an Apama project contains an excluded parent folder and an included inner child folder which contains a jar file, Ant failed with this error:
`"IllegalStateException: Workspace is closed"`
This issue has been fixed whereby any included folders, inside the excluded folder, will have their files injected correctly into the correlator.
- PAM-27012
Ant exported build.xml has absolute path for the standard-codecs.yaml configuration file (since 10.0.0.0).
When a Software AG Designer project containing connectivity plug-ins was exported to an Ant script, the resulting build.xml used an absolute path to refer to some of the YAML files. This may have prevented the script from running correctly on other machines and operating systems. This issue was fixed in 10.0.0.1.
- PAM-26942
Exporting CDP to the same (exported earlier) location is showing an error dialog in Designer (since 10.0.0.0).
If a CDP file was exported to an already existing file, then the CDP export wizard showed a warning and after clicking **Finish**, it failed with the exception "File already exists". This has been fixed to just show a warning, but no exception will be thrown. Also, if there are multiple projects with the scenario file using project blocks and if the user tries to do a CDP export without opening the scenario file, then the export failed with an exception. This issue was fixed in 10.0.0.1.

- PAM-26189
Invalid stream query inputs in combination with equi-join can crash the correlator/Designer (since 9.10.0.0).
An EPL stream query that uses an equi-join and has an invalid input item will cause the correlator to crash upon injection, or cause a fatal error in Software AG Designer when built inside an Apama project. For example:

```
from e1 in noSuchVariable join e2 in all E() on e1.i equals e2.i select  
f(e1, e2)
```


This has now been fixed in both the correlator and Software AG Designer.

Correlator

- PAM-26964
It is no longer possible to inject the Management.mon file followed by the OutOfBandEventDefs.mon file, due to a change in the management plug-in which both use (since 10.0.0.0).
When injecting the Management.mon file followed by the OutOfBandEventDefs.mon file, the error message looked like:

```
Error injecting monitorscript from file  
monitors/outofband/OutOfBandEventDefs.mon: Error on line 138: Trying to  
return a 'sequence<unknown type>' from an action which returns a  
sequence<com.apama.oob.ReceiverConnected> (error reported to client)
```


This was fixed in 10.0.0.1. The OutOfBandEventDefs.mon file now uses the new OOBPlugin, not the ManagementPlugin, which removes an injection ordering dependency between Management.mon and OutOfBandEventDefs.mon.
- PAM-26730
Repeated calls to `monitor.subscribe()` cause memory leak.
In previous releases, calling `monitor.subscribe()` from EPL would allocate some additional memory for each call even if the current context was already subscribed, which in some cases would mean EPL applications would have needed to perform their own reference counting to avoid repeated calls using more memory. This has now been fixed and EPL applications can call `monitor.subscribe()` any number of times from a given context without any extra memory being allocated.
- PAM-27032
Correlator crashes with YAML configuration files with invalid spacing in maps (since 9.10.0.0). The correlator would crash if a YAML file with invalid spacing in maps was provided. This has been fixed such that an error will be generated in lieu of crashing when invalid YAML files are read.
- PAM-27017
Changing `storeLocation`, `storeName` is broken when writing input log (since 10.0.0.2).
An error has been fixed in handling command line arguments where the correlator would always use the default persistence database name and location as the source to copy the persistence database into the input log.

- PAM-26826
Correlator crash when sending in malformed `&TIME` events (since 9.9.0.0).
This issue is with the correlator crashing on Windows while trying to parse an `&TIME` event containing a single backslash inside, for example:
`&TIME ("a\")`
The backslash was expected to be followed by a valid escape sequence such as `n`, `quote`, `t` etc. If the backslash was not followed by a valid escape sequence, then this resulted in an unhandled exception on Windows, causing a correlator crash. This has now been fixed.

Release 9.12.0

EPL Plug-ins

- PAM-24713
Emitting a string to a map connectivity chain causes a correlator crash. (9.10.0)
Emitting a string to a connectivity plug-in chain using the `eventMap` would crash the correlator. This is now reported as an error.

Software AG Designer

- PAM-24170
Editing connectivity plug-in configuration in Software AG Designer can contaminate it with tabs. (9.10.0)
The issue of contamination of YAML files with tabs has been resolved.
- PAM-24638
Stopping a correlator launch in Software AG Designer can take longer than in previous releases. (9.10.0)
Correlator shutdown from Software AG Designer can take a longer time than in previous releases. This issue is observed in a project where the Dashboard Viewer and the IAF plug-in are used. There is a race which causes the termination of all processes to wait, which again causes the termination of the correlator to lag. This issue has now been fixed, so that when a shutdown is initiated, it terminates all the processes (IAF etc.), which results in a proper correlator shutdown.
- PAM-24254
Variables in assign template are not being added as nodes in correlator-JMS adapter mapping rules. (9.9.0)
When configuring correlator-JMS send mapping rules using the **Assign Template** dialog, mappings may not be added as expected, with error messages related to "Velocity" in the Software AG Designer log file. This issue has been resolved.

Dashboards

- PAM-26817
Dashboard files with query attachments do not work if opened with 9.12 Dashboard Builder. (9.12.0.5)
When opening a dashboard file with an old query attachment or command created before the 9.12 release, the attachment and command dialog box do not show the correct contents. When clicking **OK/Apply** and **Save**, the dashboard file is corrupted. This issue has been fixed by allowing those dashboards files to be treated as the native query attachment/command.
- PAM-24227
`IDashboardContext`'s `getSubstitutionValue()` should clarify the expected behavior and avoid returning null. (9.9.0.3)
The `getSubstitutionValue()` API in the `IDashboardContext` interface now returns an empty string instead of null. The corresponding Javadoc has been changed to say that explicitly.

Correlator

- PAM-26619
Core dump in persistent `dictionary.parse`. (9.12.0.4)
The `dictionary.parse` method has been corrected to write the correct state to a persistent database if running in a persistent monitor. If this function has been used, then the persistence database may have an incorrect state in it. The database should be cleared and the application re-started by re-injecting the EPL.
- PAM-24162
Arbitrary streams behavior – adding “select” projection changes window semantics. (9.10.0)
In previous releases, there was a bug which would cause these two constructs to behave differently:

```
from sA: local { ... }  
from a in sA select a: local { ... }
```


Specifically, this happened when `sA` was a stream with a `within` window and an aggregate. Updates to the window caused by events getting too old rather than new events arriving could be missed by the second listener.
This has been fixed in 9.12, but may cause a change in behavior in any customer applications which were relying on the incorrect behavior.

IAF

- PAM-26657
Vulnerable libxml2 third party used. (9.12.0.5)
Libxml2 has been updated to the latest version 2.9.4, due to a known security issue.

Other

- PAM-23946
Ant copy tasks are much slower than they should be. (since JDK1.7.0_06) (5.3.0)
The version of Ant being shipped with Apama 9.12.0 has been updated to version 1.9.7. This update fixes the issue of Ant copy tasks taking logarithmically longer to copy as file size increases when using a Java Virtual Machine version of 1.7 Update 6 or greater.

Release 9.10.0

ADBC

- PAM-22738
ADBC event mapper does not work with empty namespace. (5.3.0.1)
An issue has been fixed where the ADBC event mapper GUI would not display the mapper objects when an event with no package was selected to be mapped.

Queries Runtime

- PAM-23131
Definitive time moves backwards. (9.10.0)
In cases where multiple events are processed in a short amount of time, the correlator may have logged the definitive time of an event as being earlier than previous events, which should not happen. This has been corrected. This only affects query diagnostic logging, not the behavior, which was correct previously anyway.
- PAM-22873
Queries performance is heavily affected when using external clocking. (5.3.0.3)
The issue causing performance to be affected when external clocking is used with queries has been fixed.
- BF-3573
Queries documentation updated. (5.3.0.3)
The Apama queries documentation has been updated to include more detailed information, especially regarding tooling.
- PAM-22821
Query runtime leaks on every aggregate evaluation. (5.3.0.2)
The issue causing a listener and stream to be leaked on aggregate evaluations has been fixed.
- PAM-22806
A query with multiple `having` clauses with no `select` clause generates invalid EPL. (5.3.0.2)
The issue, of queries with multiple `having` clauses and no `select` clause to generate invalid EPL, has been fixed.

Dashboards

- PAM-24049
Queries do not show up in the Apama attach and command dialogs of the Dashboard Builder. (9.10.0)
The issue with queries not showing up in the attach and command dialogs of the Dashboard Builder has been resolved.
- PAM-23442
Data server does not disconnect cleanly. Socket for management port left in `TIME_WAIT` for several seconds. (9.10.0)
After shutting down dashboard/display server processes on Linux, the management port was held open by the operating system until the socket timed out. As a result, the subsequent restarting of the dashboard/display server processes would fail until the port was released by the operating system. This issue has been solved in this release.
- PAM-23044
Deployed dashboards can throw `NullPointerException` in `Init Local Var` function. (9.9.0)
Under certain circumstances, "Init Local Var" and other Apama-provided dashboard functions could throw a `NullPointerException`. This issue has been solved in this release.
- PAM-22993
XSS Security vulnerability in dashboard display server. (5.3.0.3)
A vulnerability issue was found in the display server client. This issue has been solved with this release.
- PAM-22484
Dashboard `SQLException` with `--enhancedQuery` mode. (5.3.0.1)
When `--enhancedQuery` is being used and `DataView/scenario` contains a long string value, a `SQLException` may be seen in dashboard log files. This issue has been solved in this release.
- PAM-22142
Dashboard class cast exception may be raised when using `enhancedQuery` option. (since 5.3.0.0)
When `--enhancedQuery` option is used, the following `ClassCastException` may be found in dashboard log files:

```
java.lang.ClassCastException: java.lang.Integer cannot be cast to  
java.lang.Long  
at  
com.apama.sl.data.scenario.ScenarioCurrentTable.setCellValue(ScenarioCurrentTable.java:1474)  
at  
com.apama.sl.data.scenario.ScenarioCurrentTable.getSqlResultsTable(ScenarioCurrentTable.java:1229)
```


This issue has been fixed in this release.

- PAM-22032
Dashboard processes are unable to use shipped JDBC drivers. (5.2.0.2)
The issue affecting the JDBC jars, shipped with Apama, which previously prevented them from being used by Dashboard processes, has been resolved.

Designer

- PAM-23742
EPL color coding is lost when opening Designer with .mon file open. (9.10.0)
Activation of plug-in preferences after loading a monitorscript file would cause color coding to be lost on the file. This issue has been fixed.
- PAM-23630
FrameworkEvent ERROR on Unresolved requirement while starting Suite Designer session. (9.10.0)
Bundle dependency resolution errors between com.apama.thirdparty and com.ctc.wstx plug-ins due to conflicting exported packages have been resolved.
- PAM-23618
Correlator JMS mapper - constants in event definitions break mapping, should be ignored. (9.10.0)
An issue, where constants defined in an event would cause errors in JMS mapping rules, has been resolved.
- PAM-23566
Invalid thread access from MSPluginActivator.start. (9.10.0)
Apama plug-in may occasionally fail with the error message "An error occurred while automatically activating bundle com.apama.text" ... "Caused by: org.eclipse.swt.SWTException: Invalid thread access" in the apama_designer.log file. This issue has now been fixed.
- PAM-23394
BasicIndexOutOfBoundsException and internal error dialog when manually adding time from clause in queries source editor. (9.10.0)
In a query source tab, on adding the time from clause in the input section, an exception would be thrown. This has been fixed.
- PAM-23332
Errors in **Edit Query Send Event Action** dialog for ImprobableWithdrawal.qry in ATM_Fraud_Sample sample. (9.10.0)
In the ATM_Fraud_Sample, on opening "Send Fraud2_Alert event" in the Actions section of an ImprobableWithdrawal.qry file, errors are shown up in the dialog. This issue has been fixed.
- PAM-23327
Added input events should not be listed in Event chooser dialog while editing query input. (9.10.0)
For any query file in the design tab, when adding two input events and on editing either of the input events, the added inputs event should not be available on clicking **Choose**. This issue has been fixed.

- PAM-23324
 Error should not be flagged when the channel field is empty in Send Event action. (9.10.0)
 In a **Send Event Action** dialog, if the value of **Channel** is empty, then the dialog shows up an error.
 This issue has been fixed.
- PAM-23298
 Null pointer exception in queries editor when user deletes all code from source view and then tries
 to edit query in design tab. (9.10.0)
 An empty query file can no longer be injected into the correlator as it is considered invalid.
- PAM-23295
 Designer is logging GCMB "Lost connection to agent" after shutting down queries project. (9.10.0)
 On launching a queries project and terminating it, Software AG Designer would continually log the
 message
 "AbstractGenericComponentManagementBean\$ConnectionPollingThread.run() -
 Lost connection to agent." This issue has been solved in this release.
- PAM-23177
 Renaming a query in Software AG Designer confuses Designer. (9.10.0)
 The issue with Software AG Designer becoming "confused" when renaming a query file, has been
 resolved. It is no longer necessary to close and re-open the editor when renaming a query file.
- PAM-22814
 Query editor goes into incorrect syntax state if aggregates are present and pattern is removed and
 re-added. (9.10.0)
 In a query file, having an aggregates clause if a find node is removed and added back again, then
 the query file goes into a syntax error state. This issue has been resolved.
- PAM-22942
 Excluded EPL files are getting added to launch configuration on editing them. (5.3.0.3)
 Monitor files which had been explicitly excluded from the injections list in the launch configuration
 of a Software AG Designer project were added back in if the excluded monitor was subsequently
 edited. Designer now behaves correctly, and respects the exclusion when making edits.
- PAM-22809
 Incorrect completion proposals in the queries editor. (5.3.0.2)
 In the queries editor, several issues that caused some invalid completion proposals to be offered,
 and also prevented other valid completion proposals from being suggested, have been resolved.
- PAM-22367
 Incorrectly flagged errors in Query Designer action panel and send event action dialog. (5.3.0.1)
 An issue has been fixed where valid hand-written code would be flagged as an error in the query
 designer and send event dialog.

- PAM-22369
Pattern drag and drop does not always retain package relative values. (5.3.0.1)
The issue is now fixed so pattern drag and drop and **Without Conditions** dialog will now retain package relative values.
- PAM-22474
A blank query shows as an error in Query Designer. (5.3.0.1)
An issue has been fixed where, under certain conditions, empty queries could be flagged as being in error in the Query Designer.
- PAM-22377
Errors related to `every` keyword are not reported against aggregates in Query Designer. (5.3.0.1)
Errors related to `every` keyword should be reported against aggregates in the Query Designer.
- BF-2980
Missing documentation on queries tooling. (5.3.0.1)
Several sections documenting various features of Query Designer tooling have been added.
- PAM-21873
A default filter added to **Event Chooser** dialog. (since 5.3.0.0)
A default filter with value "com.apama.*" has been added to the **Event Chooser** dialog to automatically remove events in the "com.apama" namespace from the event list.
- PAM-21016
Ability to select multiple EDA events for mapping in both send and receive. (since 5.2.0.0)
Multiple EDA events for mapping can now be selected in both send and receive.

Management

- PAM-23959
`engine_management` dumps core when any `--<anything>` argument is passed after `-r`. (9.10.0)
An `engine_management` crash has been fixed when invalid parameters were supplied, specifically when `-r` was not followed by a valid request.

Correlator

- PAM-23703
Correlator crash during GC caused by bug in pile deletion
(`PersistentDictionary::preDelete`). (9.10.0)
An issue has been fixed where a correlator crash could occur with dictionaries in persistent monitors that have string keys which are "garbage" on the first garbage collection run.
- PAM-23635
Latency regression - max latency is worse. (9.10.0)
A performance regression causing intermittent high latencies (over 1 millisecond at 99 percentile) has been fixed.

- PAM-23519
Correlator crashes on Windows if the time zone has DST disabled. (9.10.0)
An error has been fixed in logging the time zone which could cause a crash at correlator startup on Windows if the time zone does not use daylight savings time.
- PAM-23245
Parsing strings parallelism hit by `CorrelatorString.getInterned` read lock. (9.10.0)
A scalability issue which would reduce performance when multiple threads were parsing events with a lot of interned strings has been fixed. Performance now scales well with the number of threads sending events or calling `event.parse()`.
- PAM-22879
Ctrl+C or termination of parent command prompt kills background correlator process on Windows. (9.10.0)
Customers using Ant for deployment or testing on Windows should be aware that when using Ant launches a correlator, IAF or other background process from an interactive Command Prompt, these processes will be automatically terminated when the Command Prompt window is closed, or when Ctrl+C is pressed at any time within that Command Prompt. This is the result of a reported bug in the Java Runtime Environment (since 1.7.0_60).
Until the underlying Java bug can be fixed, customers should be careful not to use an interactive Command Prompt for launching any important server processes using Ant.
- PAM-22959
Crash caused by incorrect escape flags on dictionary methods. (5.3.0.3)
Some EPL methods were incorrectly considered by the correlator to not escape their parameters, which when optimizations were enabled (the default) could in particular cases lead to the correlator crashing. This has been fixed to avoid optimizing out copies in code using methods where it is not safe to avoid the copy.
- PAM-22830
Status lines do not show in log file when the correlator is started through Software AG Designer. (5.3.0.2)
Correlators started from Software AG Designer will no longer have the logging of "Status:" lines automatically disabled if logging to a file.
- PAM-22774
Race when disconnecting and connecting using `engine_connect` concurrently. (5.3.0.2)
The use of multiple disconnecting and connecting `engine_connect` clients no longer results in a correlator crash.
- PAM-22621
The correlator is not passing all UM SSL Cert options to UM. (5.3.0.1)
An issue has been fixed where several of the documented UM configuration properties were not properly passed when configured for UM integration.

- PAM-22100
 Correlator input log does not contain the channel name. (5.3.0.0)
 The addition of channels in 5.2.0.0 was missing support for them in the input log. This has been corrected so that input log files of applications using channels can be used correctly for replay.
- PAM-21634
 Memory may not be returned when using `dictionary.clear()`. (5.2.0.1)
 The `clear()` method on the EPL `dictionary` type could previously cause a memory leak. Prior to the fix, if a monitor instance invoked this method on a dictionary in a certain set of circumstances, garbage collection would no longer run for EPL objects on the monitor instance. All current and future EPL objects on the instance would leak correlator memory, even if they were no longer in use.
- PAM-21516
 Correlator or IAF process sometimes log exceptions and unload monitors when using Universal Messaging integration during a cluster failover. (5.2.0.1)
 A defect, where a channel that is being looked up on a UM broker (as it has not been recently sent-to or subscribed-to) during failover of UM brokers could result in silently killing a monitor, has been fixed; the correlator will now re-try channel look-ups during failover until it can contact a UM broker.
- PAM-21579
 UM enabled correlator performance enhancement. (5.2.0.1)
 The correlator now publishes events in batches to Universal Messaging in lieu of individually publishing events. This change can improve throughput by as much as 4X the previous implementation.

Release 9.9.0

- PAM-22168
 Small leak in .NET client disconnect (9.9.0)
 The .NET client library, under unusual circumstances, would leak a small amount of memory when it disconnected and reconnected. This issue has been resolved.
- PAM-1920
`TimeFormatPlugin` use of TZ environment variable (9.9.0)
 The `TimeFormatPlugin` now honors the TZ environment variable on Windows as well as on UNIX. Note that the rest of the correlator processing will continue to use the system-configured time zone on Windows.

Release 5.3.0

- PAM-21911
ADBC transport reversed counts for TrEvRx and TrEvTx in log (since 5.3.0.0)
The ADBC adapter status log line previously had its events received (TrEvRx) and events transmitted (TrEvTx) reversed, this has been corrected.
- PAM-14809
Log message improvements when a plug-in call fails (since 5.3.0.0)
When a C++ EPL plug-in throws an exception, it is possible for an application to catch it in EPL, and to take action based on the type and message in the caught `com.apama.exceptions.Exception` object. A small change has been made to the format of the message that results from a plug-in method call error, which could potentially affect EPL logic that depends on the message string. The old message was "Caught exception (%s) while executing plugin method %s", but from 5.3 onwards this has been simplified to "%s (in plugin method %s)".
- PAM-13580
Simplify how to cleanly remove event .NET consumers/suppliers (since 5.3.0.0)
For users of the low-level `EngineManagement` layer in the .NET API, the rules for safely disposing of the `EngineManagement`, `EventSupplier` and `EventConsumer` have been changed to be more simple, more robust and better documented. Instead of calling various `Disconnect()` methods, all objects should be cleaned up by calling the `Dispose()` method, with any `EventSupplier` objects disposed before `EventConsumer` and `EngineManagement` objects.
An INFO level warning will now be written to the client logger (if enabled) during finalization of the objects if `Dispose` was not called. The `Api.DisconnectFromEngine` and `EventSupplier.Disconnect` methods have been deprecated. For C# developers, the simplest way to ensure objects are disposed correctly is usually to construct them in a `using` clause (see C# language documentation for more information).
- PAM-21566
Subscriber element in "Configuring adapters to use UM" incorrectly written as optional (5.3.0.0)
The IAF configuration for Universal Messaging requires that the `<subscriber>` element is present in the `<universal-messaging>` element. This was previously incorrectly marked as optional.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 9.10

PDF documentation is no longer included in the installed product. It can be viewed and downloaded from the [Documentation website](#) if required.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 9.12

Old Term	New Term
Correlator plug-in	EPL plug-in

Release 9.9

Old Term	New Term
Apama Studio	Software AG Designer

8.0 Added, Removed, Deprecated, or Changed Items

See *Release Notes* in the Apama documentation.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

See *Release Notes* in the Apama documentation.

10.0 Added, Removed, Deprecated, or Changed Parameters

See *Release Notes* in the Apama documentation.

11.0 Added, Removed, Deprecated, or Changed APIs

See *Release Notes* in the Apama documentation.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to “License Texts, Copyright Notices and Disclaimers of Third Party Products”. For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under “License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products”. These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

PAM-RM-103-20181015

Apama Capital Markets Foundation 10.3 Readme

October 2018

This file contains important information you must read before using Apama Capital Markets Foundation 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	3
4.0	Fixes Included in Each Release	3
5.0	Other Resolved Issues.....	4
6.0	Documentation Changes	5
7.0	Terminology Changes	5
8.0	Added, Removed, Deprecated, or Changed Items.....	5
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	5
10.0	Added, Removed, Deprecated, or Changed Parameters.....	5
11.0	Added, Removed, Deprecated, or Changed APIs	5
12.0	Copyright Information.....	6
13.0	Support.....	6

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

Capital Markets Foundation 10.3 requires Apama 10.3 to already be installed.

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- PAF-2844
New Risk Firewall Position Limit and Client Credit Limit Rule Classes limits can be breached in some cases (since 5.1).
The new Risk Firewall's Position Limit Rule Class and Client Credit Limit Rule Class limits can be breached in some cases. This is due to the fact that the Position Service requires OMS events to be routed/enqueued to it in order to track the position correctly.
If the Position Tracker is in the same context, then the Risk Firewall's OrderReceiver implementation must route OMS events to it. However, this means that a fully synchronous OrderSender could send an order to the Risk Firewall that is evaluated against the previous position, as it has not processed the routed OMS event at that point.
Similarly, if the Position Tracker is in a different context, then the Risk Firewall's OrderReceiver implementation must enqueue the OMS events to it. However, this means that either a fully synchronous OrderSender, or an OrderSender that is handling routed OMS events, could send an order to the Risk Firewall that is evaluated against the previous position, as it has not processed the enqueued OMS event at that point.
- PAF-1230
ATA SymbolSet MARKETDATADRIVEN or SIMPLE_MD_DRIVEN simulation modes cause infinite loop (since 2.3).
When defining SymbolSets for the ATA, users can define a "SIMULATION_MODE". Two experimental market data driven modes were added to allow the simulated data to be driven by market data inputs. However, use of these experimental market data driven modes will cause an infinite loop to occur in this release, and should not be used. This infinite loop will cause large amounts of memory to be consumed before the correlator shuts down.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- PAF-2818
Crossrate Service does not support .X feeds with more than one leg (since 5.2).
The Crossrate Service does not support crossing the .X datastream type with more than one leg (that is, from an aggregator or different Crossrate Service).
- PAF-2834
Aggregator does not support an already aggregated Depth/MBP feed (since 5.2).
The aggregator does not support an input Depth/MBP feed from another aggregator. The input feed lacks enough information to build the Priority Index key, causing a “Trying to add/remove/modify duplicate entries” error and an incorrect aggregated book.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 9.12

- PAF_9.12.0_Fix1

Release 9.10

- PAF_9.10.0_Fix1

Release 9.9

- PAF_9.9.0_Fix3

Release 5.3

- PAF_5.3.0_Fix1

Release 5.2

- PAF_5.2.0_Fix6

Release 5.1

- PAF_5.1.1_Fix3

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.2

- PAF-3741 (CMF 10.2.0)
Unable to add non-singleton bundles to an existing Designer project.
Some of the bundle catalogues which should be of type singleton were incorrectly tagged as being non-singleton type. Due to this, there were issues while adding the following bundles to a Designer project: Legacy Application Bridge bundle, Generic Source bundle, NMDA MDBridge bundle, Symbol Conversion bundle. This has been fixed and these bundles are now of type singleton.

Release 9.12

- PAF-3542 (CMF 9.12.0)
Extra Parameter delta errors on duplicate subscription.
A race condition has been fixed where a duplicate subscription was sent an incorrect Extra Parameters snapshot which could cause delta update errors.

Release 9.10

- PAF-3438 (CMF 9.10.0)
Subscription race with multiple subscriptions from different contexts.
A race condition has been fixed where duplicate subscriptions from different contexts could cause the initial data snapshot to be sent before a context had subscribed to the channel. This would cause Market Data update callbacks to not be called.
- PAF-3428 (CMF 9.10.0)
Issue with missing EP data for duplicate subscriptions.
An issue has been fixed where a duplicate subscription with Extra Parameters enabled would not have the Extra Parameter values set in the initial snapshot.
- PAF-3426 (CMF 9.10.0)
Delete of EP not working for Datastreams.
An issue has been fixed where the deletion of all EPs was not being reflected in the data published to the user.

- PAF-3396 (CMF 9.10.0)
Position Limit and Client Credit Firewall Rule should allow CancelOrders.
A new parameter CHECK_CANCEL has been added to the Position Limit and Client Credit Firewall Rules (defaults to true), so rule instances can be configured to never reject Cancel Orders.
- PAF-3392 (CMF 9.10.0)
WrappedD is corrupted for duplicate subscriptions.
An issue has been fixed where a duplicate depth subscription would receive a corrupt book in the initial snapshot.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

See *Capital Markets Foundation Release Notes* in the Apama Capital Markets Foundation documentation.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

See *Capital Markets Foundation Release Notes* in the Apama Capital Markets Foundation documentation.

10.0 Added, Removed, Deprecated, or Changed Parameters

See *Capital Markets Foundation Release Notes* in the Apama Capital Markets Foundation documentation.

11.0 Added, Removed, Deprecated, or Changed APIs

See *Capital Markets Foundation Release Notes* in the Apama Capital Markets Foundation documentation.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to “License Texts, Copyright Notices and Disclaimers of Third Party Products”. For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under “License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products”. These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

PAF-RM-103-20181015

Apama Predictive Analytics Plug-in 10.3 Readme

October 2018

This file contains important information you must read before using Apama Predictive Analytics Plug-in 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release	2
5.0	Other Resolved Issues.....	3
6.0	Documentation Changes	4
7.0	Terminology Changes	4
8.0	Added, Removed, Deprecated, or Changed Items.....	4
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	4
10.0	Added, Removed, Deprecated, or Changed Parameters.....	4
11.0	Added, Removed, Deprecated, or Changed APIs	4
12.0	Copyright Information.....	5
13.0	Support.....	6

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

Predictive Analytics Plug-in 10.3 requires Apama 10.3 and Predictive Analytics Engine 10.3 to be installed.

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.1

- PAD_10.1.0_Fix1

Release 10.0

- PAD_10.0.0_Fix1

Release 9.12

- PAD_9.12.0_Fix2

Release 9.9

- PAD_9.9.0_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3.0

- PAMA-6443
Predictive Analytics Plug-in ships more samples which help when understanding how to use the plug-in.

Release 10.2.0

- PAMA-6082
Race issue with Predictive Analytics Plug-in when updating models/resources.
In certain rare scenarios, a race condition can occur where new incoming requests can get scored using an earlier version of the model while an operation to update the same model to a newer version is pending.

Release 10.0.0

- PAMA-5640
Injecting Predictive Analytics Plug-in CDP into the correlator will now display the alias of the underlying component.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

See Release Notes section in *Predictive Analytics Add-on* documentation.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

See Release Notes section in *Predictive Analytics Add-on* documentation.

10.0 Added, Removed, Deprecated, or Changed Parameters

See Release Notes section in *Predictive Analytics Add-on* documentation.

11.0 Added, Removed, Deprecated, or Changed APIs

See Release Notes section in *Predictive Analytics Add-on* documentation.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to “License Texts, Copyright Notices and Disclaimers of Third Party Products”. For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under “License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products”. These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

PAD-RM-103-20181015

webMethods API Gateway 10.3 Readme

October 2018

This file contains important information you must read before using webMethods API Gateway 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	3
4.0	Fixes Included in Each Release.....	5
5.0	Other Resolved Issues.....	5
6.0	Documentation Changes	5
7.0	Terminology Changes	6
8.0	Added, Removed, Deprecated, or Changed Items.....	6
9.0	Copyright Information.....	13
10.0	Support.....	14

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- YAI-8968
Response message is not masked for REST XML requests of REST-enabled SOAP APIs.
When a SOAP API is REST-enabled and the response data masking policy is applied, the response data is not masked for REST XML requests
- YAI-9240
GET API details through REST using 10.2 URL is not returned appropriately.
When API details are requested through REST API using 10.2 URL, some of the parameters of the API are not returned appropriately.
- YAI-9281
Active APIs are allowed to be updated using REST API.
APIs are allowed to be updated, the Name, version or mocking, even when they are in active state using REST APIs. Also API update by attaching document is allowed. These updates are expected to be allowed only in deactivated state.
- YAI-9286
Users with Manage APIs functional privilege only are allowed to update active APIs.
Users having the functional privilege, Activate / Deactivate APIs, should be able to modify active APIs and not users with functional privilege Manage APIs.
- YAI-9422
Migration to 10.3 with 500 APIs leads to incomplete migration.
When API Gateway data with 500 APIs is migrated to 10.3 version of API Gateway, migration is incomplete. Not all APIs are migrated but some of them are migrated.
- YAI-9255
Ports are not synchronized in Integration Server when port clustering is disabled and enabled.
When portClusteringEnabled is set to false and external ports are created and the portClusteringEnabled is set to true again, on API Gateway restart the ports are not displayed appropriately in the API Gateway user interface.

- YAI-7189
API associated with a package is allowed to be deleted.
An API, which is associated with a package, is deleted and imported again using export archive of the API, the association of API and Package is created automatically.
- YAI-8804
Deactivating API terminates ongoing requests.
Any ongoing requests are terminated when an API is deactivated.
- PIE-53165
Unable to update registration port.
API Gateway port update returns with an empty message box. In addition, the ports are removed and not visible in the API Gateway user interface.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- YAI-1286
Activating an API, with a big WSDL file, from Gateway UI displays StackOverFlowError.
When you see a StackOverFlowError while activating an API, increase the thread stack size in *IS_Installed_Folder\profiles\IS_default\configurations\wrapper.conf* in IS using the command:
`wrapper.java.additional.7=-Xss2048k`
- Before using API Gateway, consider the following points:
 - While using API Gateway on HP-UX OS , consider increasing Java heap size in *SAG_install_dir/profiles/IS_default/configuration/custom_wrapper.conf*:
`wrapper.java.initmemory=512`
`wrapper.java.maxmemory=2048`
Use different Java executable in *SAG_install_dir /profiles/IS_default/configuration/wrapper.conf*:
`wrapper.java.command= SAG_install_dir /jvm/jvm/jre/bin/IA64W/java_q4p`
 - API Gateway package in Integration Server cannot co-exist with the WmMediator or WmCloudStreams packages. WmMediator and WmCloudStreams packages must be disabled for API Gateway to function properly.
 - webMethods API Gateway combines current webMethods Enterprise Gateway and webMethods Mediator capabilities in a single product. API Gateway offers the same capabilities within a simplified architecture. It also removes the dependency on CentraSite for API definition and policy definition.
 - API Gateway comes in two editions. The Standard edition allows users to define threat protection policies, and provides analytics for threat protection use cases. Typically Standard editions are deployed in DMZ.
Full edition supports all use cases of Standard edition, supports managing APIs, consumer

applications, API-level policies, and managing API packages and plans.

- When API Gateway and Internal Data Store are already running and IP address is changed, connection between API Gateway and Internal Data Store is lost. Restart the Internal Data Store to reconnect to API Gateway.
- API Gateway uses the `pub.client:http` IS service to invoke HTTP based services.
 - An Integration Server property `'watt.net.http401.throwException'` allows the `pub.client:http` service to throw `NetException` for a 401 Unauthorized response from native service. This property was by default set to 'true' in Integration Server (in the Integration Server Administrator, go to Settings > Extended link). As a result, the response from API Gateway did not include the native service response body in case of 401 responses from native service. Beginning with API Gateway version 10.3, the `watt.net.http401.throwException` property is by default set to 'false' in Integration Server. Now, the `pub.client:http` service will not throw a `NetException` for 401 unauthorized responses from the native service. API Gateway will receive the 401 response body and send the native API provider's fault content (if available) to the application if the Send native provider fault option is enabled in API Gateway (in the API Gateway user interface, go to Username > Administration > General > API fault).
 - An Integration Server property `'watt.net.http501-599.throwException'` allows the `pub.client:http` service to throw `NetException` for a HTTP response status code that varies from 501 to 599 from native service. This property was by default set to 'true' in Integration Server (in the Integration Server Administrator, go to Settings > Extended link). As a result, the response from API Gateway did not include the native service response body in case of 501 to 599 responses from native service. Beginning with API Gateway version 10.3, the `'watt.net.http501-599.throwException'` property is by default set to 'false' in Integration Server. Now, the `pub.client:http` service will not throw a `NetException` for HTTP 501 to 599 responses from the native service. API Gateway will receive the 501 to 599 response body and send the native API provider's fault content (if available) to the application if the Send native provider fault option is enabled in API Gateway (in the API Gateway user interface, go to Username > Administration > General > API fault).

Note: These configuration changes may negatively impact any webMethods product instance which is installed with an instance of Integration Server on which API Gateway is running. Software AG recommends that you use an instance of Integration Server dedicated for API Gateway.

- The PDF and webhelp documentation deliverables on Empower have the latest content available for the AMQP support and JWT enhancements in API Gateway 10.3.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.2

- YAI_10.2_Fix4

Release 10.1

- YAI_10.1_Fix12

Release 10.0

- YAI_10.0_Fix9

Release 9.12

- YAI_9.12_Fix9

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

The following artifacts have been introduced for API Gateway 10.3:

- webMethods API Gateway WebHelp: This is single HTML output that contains all the PDFs available for API Gateway on Empower.

Release 10.0

The following artifacts have been introduced for API Gateway 10.0:

- webMethods API Gateway Quick Start Guide: This is single page PDF output that gives an overview of setting up API Gateway.

Release 9.12

The following artifacts have been introduced for API Gateway 9.12:

- webMethods API Gateway Online Help
- webMethods API Gateway User’s Guide: This guide describes how you can use API Gateway and other API Gateway components to effectively manage APIs for services that you want to expose to consumers, whether inside your organization or outside to partners and third parties.
- webMethods API Gateway Configuration Guide: This guide describes how you can configure API Gateway and other API Gateway components to effectively manage APIs for services that you want to expose to consumers, whether inside your organization or outside to partners and third parties.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists features, functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Open API Support	Users can create an API by importing an open API document file or URL in API Gateway. OpenAPI Specification (formerly Swagger Specification) is an API description format for REST APIs.
Support for API Mashups	Individual microservices and APIs can be composed into one mashed up API. API Gateway handles a request by invoking multiple microservices and aggregating the results and provide final response.
Support Async APIs	APIs which take longer than usual invocation time, may end up with Read Time out. API Gateway could enforce policies to use the callback URL defined for the APIs.

Added Item	Description
Support AMQP protocol	Support AMQP as an inbound and outbound endpoint for API Gateway APIs of type SOAP and REST. AMQP is open standard for passing messages between applications and provides standard messaging protocol across platforms.
API hot deploy	API updates can be done without deactivating or affecting the ongoing requests. Each request finishes without being affected by updates to the API and policy definition.
Support runtime service registries	API Gateway APIs can be published to service registries and clients can get the endpoints from service registry. APIs routing endpoint can be configured with service registry to discover endpoint from registry during outbound.
Log aggregation	API Gateway aggregates different log files used for logging API Gateway usage and provides a comprehensive log file. Logs can be also viewed in the dashboard with filtering capabilities.
Security enhancements	Security configuration is unified for OAuth, OpenID and JWT configuration, and is simplified. Support for multiple active Authorization servers simultaneously is included. Added capability to register clients dynamically in third-party Authorization servers. Support for third-party clients introspection. PKCE client application support for third-party Authorization servers. Mapping of OAuth scopes with API scopes.

Removed Item	Replacement, if any
Inbound Authentication – Transport policy was removed from API Gateway10.3	This functionality was added into the Identify and Authorize Application policy.

Release 10.2

Added Item	Description
API Tagging	<p>APIs or its resources and operations can be tagged. You can use the tags for searching artifacts in API Gateway and publish the tags along with the API to API Portal.</p> <p>API creation using Swagger can acquire the tags from the swagger file and also API export should include the assigned tags.</p>
Bulk Publish, Unpublish and Delete	<p>You can publish, unpublish or delete more than one API at a time to API Portal.</p>
File attachments support for API	<p>APIs can be attached with supporting files as attachments and the attached files are available in API Portal after publishing to the Portal.</p>
JWKS endpoint for JSON Web Tokens	<p>As an ID provider, API Gateway provides the JWKS endpoint that helps the relying parties to fetch the certificates that can be used for validation of the JSON Web tokens.</p>
HTTP Client for Elastic Search	<p>Relaxes the hard limitation of using the Elastic search shipped along with API Gateway product; you can use other elastic search instance configured with API Gateway</p>
Application suspension	<p>You can now suspend applications to deactivate the runtime access to the applications in API Gateway and the same application can be activated again.</p>
CORS Support in API gateway	<p>API Gateway can process cross origin requests sent by clients as inbound policy and also as transparent mode of native service processing cross origin requests.</p>
Specification for Invoke IS Service	<p>You can now define IS Service to get and set headers, status code, body, and other MessageContext variables using the specification in the service and do not have to write code to extract the variables.</p>

Added Item	Description
Enhance Transaction events	Transaction events are enhanced to log headers and query parameters of request and response along with the payload.
Caching enhancements	You can manage different caches of API Gateway to auto scale or allocate static percentage of data to be held in cache.
Data masking	API Gateway's data masking policy can be configured to mask or filter specific data in request and response messages and also mask the data in transaction events.
JSON Schema and JSON Path Support	JSON payload can be evaluated for schema validation and JSON path can be used in policies like content-based routing, error processing, and identify application.
User profile management	You can now configure your preferences like name, email passwords, and display language.
Audit logging support	Audit logging would capture user activities in API Gateway for API, application, approvals, and user management. Audit logs would capture who has done the action and when. These logs help in securing the system.
API Monetization	Plans and packages can be managed by quotas, usage, and rate limits with soft and hard limits. Consumers can subscribe to plans and monitor usage and re-subscribe as required.

Release 10.1

Added Item	Description
Migration from Mediator to API Gateway	<p>APIs and associated data can be published from CentraSite to API Gateway 10.1 version.</p> <p>This allows users to publish Virtual Services of SOAP and REST with applied policies, consumer applications, runtime alias to API Gateway, which play the role of policy enforcement point and replace Mediator.</p>
Migration from Enterprise Gateway to API Gateway	Enterprise Gateway configurations and Rules can be migrated to API Gateway, which replace and play the role of Enterprise Gateway.

Added Item	Description
Staging and Promotion support	<p>You can now promote assets from one stage to another. API Gateway uses webMethods Deployer for promoting assets across stages. Promoting an asset involves calculating its dependencies and promoting them unless explicitly specified by the user. Stage-specific configurations and alias values can be modified to respective values.</p> <p>API Gateway assets can be managed with version control system and perform scheduled or automatic promotion to stages as configured.</p>
Support for SOAP over JMS	<p>Support JMS protocol of Inbound and Outbound for SOAP. Allow JMS-HHTTP bridging between Inbound and Outbound.</p>
Backup and Restore	<p>Backup API Gateway assets and configuration using command line and you can restore the backed up data.</p>
Transaction based licensing	<p>License model based on transactions and appropriate alerts can be implemented</p>
Approval model for applications	<p>Approval model can be implemented for creating or updating applications, associating applications with APIs, and subscribing to packages.</p>
API Mocking	<p>Mocking mode allows users to make mock calls to APIs. User can specify API response for each resource or operation and can set status codes for responses. API responses can be configured on conditional basis too.</p>
Support 3rd party OAuth providers	<p>Users can use 3rd party Authorization Servers for authenticating API invocations using OAuth2</p> <p>Third party OAuth2 providers like OKTA and Ping Federate can be used for OAuth2 authentication.</p>
Support JSON Web Tokens	<p>API Gateway can authenticate clients using JSON Web Tokens supplied during invocations.</p>
Open ID Support	<p>API Gateway can authenticate clients using Open ID Tokens supplied during invocations.</p>
HTTP Header Validation	<p>Providers can mandate consumers to send HTTP headers and values defined in policy for API Invocations.</p>

Release 10.0

Added Item	Description
API Versioning	New version for an API can be created. Different versions of an API can be viewed and invoked.
SOAP to REST transformation	API Provider can enable some of the operations of SOAP service as REST endpoints. These operations can be invoked with different paths and the operation path can contain Path parameters that can be saved as templates and can be hierarchical. The operation can be invoked in a method other than POST.
API export and import	APIs in API Gateway can be exported and imported into a different API Gateway. This implies that the export archive for an API includes all the information to establish an API in the importing API Gateway.
Support Service Result Cache	Service result of the first invocation is cached when the criteria defined in the policy is met. Subsequent requests are from cache and do not require to go to native service for every similar invocation.
Schema Validation Support	Validates the incoming requests and responses against a schema referenced in the WSDL for SOAP APIs. For REST API, user should be able to validate incoming requests and responses against the specified schema.
API usage reports and dashboards	Package-level and API-specific usage and utilization reports. API Gateway provides number widgets for package invocations and API invocations.
Archive purge and restore events data	Administrators can archive and purge events data to a configured file location. The archived data is restored from the created archives.
Resources or Operation level policies	Policies can be applied to one or more resources or operations and must be applied on an API always. Scope can be created with a collection of resources, methods or operations of an API and policies can be applied to the scope to apply to the specific operation or resources.

Added Item	Description
Global policies and policy templates	Global Policy is a common policy that can be associated to multiple APIs based upon the criteria defined for the policy. Policy Template is a base template defined, which can be imported in multiple APIs.
SAML Authentication	APIs can be applied with SAML authentication policies at Inbound and Outbound. Bearer and Holder of Key SAML subject confirmation are supported for SAML 1.0 and 2.0 versions.
Kerberos Authentication	Kerberos authentication is supported at message and transport level for SOAP APIs and at transport level for REST APIs. APIs can be applied with Kerberos authentication policies at Inbound and Outbound.
XML Threat Protection Support	API Gateway application should be resilient to attacks through XML payload. XML payloads sent through external port go through the XML threat protection filter when the rule is defined and enabled.
JSON Threat Protection Support	API Gateway application should be resilient to attacks through JSON payload. JSON payloads sent through external port go through the JSON threat protection filter when the rule is defined and enabled.

Release 9.12

Added Item	Description
API CRUD	Both REST and SOAP APIs can be imported. Swagger and RAML are supported formats for REST and WSDL for SOAP. REST APIs can be created from scratch as well.
Policies and Aliases CRUD	Both threat protection and API-specific policies based in selected edition. For more information, see documentation for supported policies. Create and manage aliases that improve the reuse and maintenance.

Added Item	Description
Consumer Applications CRUD	Manage consumer applications and associations with APIs.
Packages and Plans	Organizations can group APIs and define enforcements on the same as a single unit, which can be subscribed by developers.
API Portal Integration	APIs can be published to API Portal from API Gateway for the developers reach.
Analytics	API Gateway provides dashboards for greater insights on various topics like Summary, Trends, Consumer applications, and Threat protection.

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

YAI-RM-103-20181015

webMethods API Portal 10.3 Readme

October 2018

This file contains important information you must read before using webMethods API Portal 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	3
5.0	Other Resolved Issues.....	3
6.0	Documentation Changes	5
7.0	Terminology Changes	7
8.0	Added, Removed, Deprecated, or Changed Items.....	7
9.0	Copyright Information.....	12
10.0	Support.....	12

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- YAP-5045

Restoring backups from older API Portal versions in API Portal 10.2 fails.

When a backup taken from API Portal version 10.0 or earlier is restored in API Portal 10.2, the restore functionality through UI fails with the following error message: "Invalid backup file. Please upload valid backup file to restore." However, the restore functionality through the ACC console command line utility works as expected.

The workaround to restore data through UI is to clear the "API Portal analytics" checkbox in the Restore UI and then perform the restore operation.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- webMethods API Portal 10.3 can either import APIs directly or have API published by CentraSite and API Gateway.
In case APIs are published from CentraSite, webMethods API Portal 10.3 requires CentraSite 9.7 or higher.
In case APIs are published from API Gateway, webMethods API Portal 10.3 requires API Gateway 9.12 or higher.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.2

- YAP_10.2_Fix2

Release 10.1

- YAP_10.1_Fix9

Release 10.0

- YAP_10.0_Fix2

Release 9.12

- YAP_9.12_Fix7

Release 9.10

- YAP_9.10_Fix4

Release 9.9

- YAP_9.9_Fix9

Release 9.8

- YAP_9.8_Fix3

Release 9.7

- YAP_9.7_Fix2

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.0

- YAP-3398
Subscription tokens are not deleted while unpublishing packages from API Portal.
When a package is unpublished from API Portal, the associated subscription tokens are not deleted.
This issue is now resolved.

Release 9.12

- YAP-1389
Scheduled reports - back navigation
When editing or creating a scheduled report, on clicking Back the modifications are lost.
This issue is now resolved.
- YAP-2280
API Runtime metrics published from Mediator to API Portal creates Active sessions in UMC.
For every runtime metric published from Mediator to API Portal, an active session is created which is valid for 1 hour. If more data is published from Mediator to API Portal multiple active sessions will be created and this results in the unavailability of UMC.
This issue is now resolved.

Release 9.8

- YAP-605
Access token page does not refresh after deleting or renewing an API.
You have to refresh the page manually to clear the display of the deleted access token.
This issue is now resolved.
- YAP-595
Links for downloading API documents always provides a HTTPS link irrespective of whether we access the portal using HTTP/HTTPS.
By default the load balancer is configured to run using both HTTP and HTTPS ports. In such a case, ARIS Document store always provides a HTTPS link. So even when you login to API Portal using http port, the link to download documents for an API, will always be HTTPS.
This issue is now resolved.
- YAP-576
Expired API key is set only in the request header though the new API key is set in the key setting dialog.
The proxy configuration in the browser can cause undesirable effects while trying out an API from API Tryout page. Whenever a particular API is tested multiple times from the API Tryout page the request is cached in the proxy server. So every time when the request reaches the proxy server, instead of hitting the origin server to get the requested object the proxy server serves the request from the cache.

This issue is now resolved.

- YAP-540

An exception occurs on testing an API for API Key enabled REST API.

The proxy configuration in the browser can cause undesirable effects while trying out an API from API Tryout page. Whenever a particular API is tested multiple times from the API Tryout page the request is cached in the proxy server. So every time when the request reaches the proxy server, instead of hitting the origin server to get the requested object the proxy server serves the request from the cache.

This issue is now resolved.

- YAP-578

Miscellaneous issues with Collaboration and the API Comment Stream section.

The following issues occur in the API Comment Stream section in API Portal Collaboration:

- API Comment Stream does not support file attachments.
- Guest users cannot see the API Comment Stream section.
- After clicking Add Tag, the placeholder to enter the tags does not appear correctly.

This issue is now resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

The following artifacts have been introduced for API Portal 10.3:

- *webMethods API Portal WebHelp*: This is a single HTML output that contains all the PDFs available for API Portal on Empower.

Release 10.2

The online help content is now also available in PDF format on Empower.

- *API Portal Administrator's Guide* (includes the online help content)
- *API Portal Provider's Guide*
- *API Portal Consumer's Guide*

Release 10.1

- For information on OAuth2 support in API Portal, see *webMethods API Portal Administrator's Guide*.

- For more information on multi-factor authentication, see *webMethods API Portal Administrator's Guide and API Portal Online Help*.

Release 10.0

- For information on SAML 2.0 configuration for Consumer user in API Portal, see *webMethods API Portal Administrator's Guide*.
- For more information on API Provider Administration, see *API Portal Online Help*.
- For information on API SDK generation in API Portal, see *API Portal Online Help*.
- For information on custom navigation links, see *API Portal Customization Guide*.
- Removed the Manage Reports section from *webMethods API Portal Administrator's Guide* and *API Portal Online Help*.

Release 9.12

- For information on API Portal Extension points in API Portal, see *webMethods API Portal Administrator's Guide*.

Release 9.10

- For information on configuring the High Availability functionality in API Portal, see *webMethods API Portal Administrator's Guide*.

Release 9.9

- For information about customizing the API Portal, see the API Portal Customization Guide and online help. Note that the help is role-based, with the help set displayed based on the user's credentials and role: configuration and administration (ca), provider (pv), consumer (ct).

Release 9.8

- For information about customizing the API Portal, see the online help. Note that the help is role-based, with the help set displayed based on the user's credentials and role: configuration and administration (ca), provider (pv), consumer (ct).

Release 9.7

- For information about hardware requirements, installing, and uninstalling webMethods API Portal, see *Installing webMethods and Intelligent Business Operations Products*.
- For information about how to configure API Portal for use with CentraSite and webMethods

Mediator, how to manage API Portal and its users, and how to manage APIs published to API Portal, see *webMethods API Portal Administrator's Guide*.

- For information about using the API Portal, see the online help. Note that the help is role-based, with the help set displayed based on the user's credentials and role: configuration and administration (ca), provider (pv), consumer (ct).

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed.

Release 10.3

Added Item	Description
OData support in API Portal	API Portal supports publishing of OData APIs from API Gateway. API metadata such as entity sets, singletons, entity types, complex types, functions and actions can be viewed in API details page. OData APIs can be tested in the Try API page.
Open API support in API Portal	API Portal supports publishing of Open APIs from API Gateway and direct import of Open APIs. Open API specific metadata such as components can be viewed in the API details page. Rendering of request and response sections have been enhanced for better readability.
Allow community admins to configure multiple LDAPs and use it to add/sync users	Multiple LDAP servers can be configured in API Portal. LDAP users and user groups can be synchronized with UMC during user login.
Allow community specific LDAP configuration within private communities	LDAP user groups present in the UMC can be associated with a community.
Default Customized Themes for API Portal	API Portal provides a pre-shipped theme called "dracula" and a light theme based on the dracula theme. New themes based on dracula theme can be developed using API Portal's customization UI.
Command Central support in API Portal	Installation and uninstallation of API Portal using Command Central is supported.

Release 10.2

Added Item	Description
API Portal Testing Enhancements	API Portal Try API page has been enhanced for better usability. Accessibility of resources and methods has been improved. The request and response sections are now formatted based on the content types. JSON Web Token (JWT) support has been added. This enables an API consumer to test APIs protected by JWT.
API details page should include details of API scopes	If methods of an API are protected by API Key, OAuth2 or JWT, the same is indicated by a lock symbol in API details and Try API page. In API details page, an API scopes section containing the details of scopes associated with the API has been added.
Viewing REST enabled SOAP APIs in API Portal	SOAP APIs that have REST transformation enabled in API Gateway can be viewed as hybrid APIs in API Portal. A user can switch between REST and SOAP views in API details and Try API page.
Reports (including scheduling) from API Portal data	An API consumer can schedule reports that provide periodic alerts on the usage of applications, which he owns. The application usage metrics are collected and mailed to the configured email address. The report execution frequency can be configured as Daily, Weekly or Monthly in the user profile page.
API tagging in API Portal	Tags can be added at the API level using the edit functionality in API details page. The added tags can be viewed below the API name in API details page. If an API with tags at resource and method level is published to API Portal, the tags are rendered in the respective sections.
API Portal Customization enhancements	Customization of font and color, layout, and locale properties is possible through the UI. Layout customization is supported only for API gallery and App gallery pages. New properties for different locales can be added.

Release 10. 1

Added Item	Description
API Editing	Once an API is imported or published to API Portal, the API provider can modify the API metadata in the details page. Basic editing enables the provider to edit API name and description, resource, method and parameter description, and additional attributes. Advanced editing enables the provider to modify the icon, supporting documents, and categories of an API.
Backup and Restore analytics data	In addition to API metadata and collaboration data, an API administrator can now backup and restore API Portal analytics data. This includes data related to page views, user registrations, API lifecycle events, access token lifecycle events, provider lifecycle events, and run-time analytics data of APIs.
OAuth support enhancements	OAuth support in API Portal has been extended to include Authorization code and Implicit grant types.
Multifactor Authentication support	API Portal provides multi-factor authentication (MFA) that requires the use of a one-time password to verify a user's identity for a login. API administrator can enable this feature in the user management console (UMC).
Advanced search in API Portal	Search capabilities in API Portal have been enhanced to enable a user to search APIs based on resources, methods, parameters, endpoints and policies. Packages and applications are also searchable by name and description.

Release 10. 0

Added Item	Description
API SDK Generation	The client code for an API in a specified language can be downloaded as a zip file. The zip file contains necessary code package that can be used for testing and communicating with the API. This is available for REST APIs.
API Portal Versioning	API Portal supports versioned APIs that are published from API Gateway and CentraSite. APIs that have been directly imported into API Portal can also be versioned.

Added Item	Description
Consumer analytics dashboards	<p>Consumer dashboard captures the KPIs specific to the users who access API Portal. It is used to track the total API requests over a period of time, requests over time per API, and API request log.</p> <p>Dashboards are now displayed based on the role of the user.</p>
API Portal provider administration	<p>API Portal offers a user interface to easily manage API providers. An API Provider has the privileges to enable an API Portal Administrator or Provider to manage APIs, and configure notification types that are used for API-related events.</p>
Custom navigation links	<p>API Portal enables adding custom navigation links in the header section. The links can be customized to render the required display text and navigate to the configured pages.</p>

Deleted Item	Description
Managing Reports in API Portal	<p>Managing reports is no longer possible in API Portal.</p>

Release 9.12

Added Item	Description
API Portal Extension Points for Standalone Deployments	<p>API Portal is configurable to work as a standalone component and can be integrated into any third-party API Management systems, which may not necessarily have Mediator or CentraSite present. You can configure API Portal to work with different key management systems for access token retrieval functions for the APIs deployed in the third-party environments.</p>
API Plans and Subscriptions	<p>Plans are offered as tiered offerings with varying availability guarantees, SLAs or cost structures associated to it. An API Package can be associated with multiple plans at a time. This helps the API Providers in providing tiered access to their APIs to allow for different service levels and pricing plans.</p>

Added Item	Description
HTTP PATCH support	The HTTP PATCH support is available in API Portal 9.12 onwards. You can use this method in API testing.
Dashboards Enhancement	<p>API Portal dashboards have been enhanced to bring better visualizations and capabilities.</p> <p>A new dashboard called API trends dashboard has been added. The API Trends Dashboard is used to learn more about the API invocation trend as per response time, success and failure rate.</p>

Release 9.10

Added Item	Description
API Runtime Events Dashboard	API Runtime Events Dashboard is used to know more about the API's invocations and its performance during runtime. You can filter the data as required, configure the dashboard to display the required data, and view the required data by highlighting the KPI.
Adoption of ECP Enhancements for Collaboration in API Portal	<p>Authenticated users have the ability to:</p> <ul style="list-style-type: none"> ▪ view the list of notifications for the followed items ▪ mark a notification as read or unread delete a notification ▪ configure the notification destination settings

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

YAP-RM-103-20181015

webMethods Application Platform 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Application Platform 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

- 1.0 **Critical Information**.....2
- 2.0 **Known Issues**.....2
- 3.0 **Usage Notes**.....3
- 4.0 **Fixes Included in Each Release**.....3
- 5.0 **Other Resolved Issues**.....5
- 6.0 **Documentation Changes**6
- 7.0 **Terminology Changes**6
- 8.0 **Added, Removed, Deprecated, or Changed Items**.....7
- 9.0 **Copyright Information**.....8
- 10.0 **Support**.....9

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- PLS-231
In some cases registering Gemini Blueprint-injected beans in Application Platform might fail with a timeout.
There is currently no workaround for this issue.
- PLS-265
The webMethods Application Platform Tutorial on the TECHcommunity website is only available for Application Platform versions 9.8 and 9.9. The exercises from the tutorial cannot be fully used with Application Platform version 10.0 and higher.
There is currently no workaround for this issue.
- PLS-267
Application Platform fails to produce a valid war file when migrating Integration Server web packages on platforms.
Migrating Integration Server web projects to Application Platform war projects fails on Windows.
The issue occurs because Application Platform does not produce a valid war file.
The issue is resolved in PLS_10.3_IS_Fix1.
- PLS-268
The Application Platform service configuration provider, which detects changes in the Application Platform properties file and updates the in-memory store is not always loaded before the OSGi service tracker. This produces a run-time exception error in the Application Platform logs.
However, in-memory store updates are handled properly.
There is currently no workaround for this issue.
- PLS-269
Executing Application Platform WAR projects that contain Tomcat Server Side Includes (SSI) components fails with an error.
The issue is resolved in PLS_10.3_IS_Fix1.
- PLS-275
Integration Server might get overloaded and require a restart due to a memory leak in the Application Platform “webm” tag library.
The issue is resolved in PLS_10.3_IS_Fix1. Application Platform removes from memory all Java objects created for the “webm” custom tag library after an HTTP session is destroyed.

- PLS-279
Web resources that are protected with the `</security-constraint>` declaration in Application Platform WAR projects may not be properly enforced.
The issue is resolved in PLS_10.3_IS_Fix1. Application Platform now imports the Java packages required for authenticating JAAS login modules.
- PLS-284
With Application Platform, invoking an Integration Server service from a JSP page using the `com.wm.app.b2b.server.Service.doInvoke()` method fails with an error.
The issue is resolved in PLS_10.3_IS_Fix1. The Application Platform fragment bundle now imports the `com.wm.util` Java package, which is required to perform the `com.wm.app.b2b.server.Service.doInvoke()` method directly from a JSP page.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- PLS-248
Application Platform is in compliance with the General Data Protection Regulation (GDPR) and does not store, collect, or process any personally identifiable information.
- PLS-251
Application Platform is updated to Spring 5.0.6.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.1

- PLS_10.1_IS_Fix1

Release 10.0

- PLS_10.0_IS_Fix1
- PLS_10.0_SPM_Fix1

Release 9.12

- PLS_9.12_IS_Fix1
- PLD_9.12_IS_Fix1
- PLD_9.12_Core_Fix1

Release 9.10

- PLS_9.10_IS_Fix4
- PLS_9.10_SPM_Fix1
- PLS_9.10_Core_Fix3
- PLS_9.10_IS_Fix3
- PLD_9.10_Core_Fix2

Release 9.9

- PLS_9.9_IS_Fix2
- PLS_9.9_Core_Fix1
- PLS_9.9_SPM_Fix1
- PLD_9.9_IS_Fix1

Release 9.8

- PLS_9.8_IS_Fix2
- PLS_9.8_Core_Fix1
- PLD_9.8_IS_Fix1
- PLD_9.8_Core_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- PLS-252
In Designer, when attempting to publish Application Platform projects to the server, an exception error occurs in the Dynamic Bundle Deployer service.
The issue is resolved.
- PLS-241
The Application Platform migration utility command line help returns arguments that are not used.
The issue is resolved. The help command now returns only the relevant arguments with an updated description.

Release 10.2

- PLS-219
When installing Application Platform on AIX, an incorrect key is used for the encryption algorithm.
The issue is resolved.
- PLS-197
The Integration Server profile does not work properly after uninstalling Application Platform.
The issue is resolved.
- PLS-179
Application Platform does not support JDK class types for service values.
The issue is resolved.
- PLS-209
Application Platform cannot publish projects after upgrading to Eclipse Equinox version 4.7.1a.
The issue is resolved.
- PLS-210
Application Platform project bundles are not fully deployed to the new runtime after upgrading to Eclipse Equinox version 4.7.1a.
The issue is resolved.

Release 10.1

- PLS-159
Application Platform POJO wrappers do not support Integration Server IData object instances.
The issue is resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 9.10

- A new webhelp, named *webMethods Application Platform Webhelp*, is available on the Software AG Documentation website. The *webMethods Application Platform Webhelp* includes information about how to configure Application Platform, how to develop projects in Application Platform, how to deploy your Application Platform projects, how to diagnose and troubleshoot Application Platform issues, and how to use the Application Platform API.
- The *webMethods Application Platform Help* in Designer now features native content. It no longer redirects the user to the Application Platform guides on the Documentation website.
- The *webMethods Application Platform Tutorial* is no longer available on the Documentation website. The *webMethods Application Platform Tutorial*, together with code samples, can be downloaded from the Software AG TECHcommunity website.

Release 9.9

The following guides will be available on the Empower website:

- *webMethods Application Platform Tutorial*
- *webMethods Application Platform User's Guide*
- *webMethods Application Platform API Guide*

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists features, functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.1

Changed Item	Description
Application Platform support for JDK class types for service values	The flow service projections that Application Platform generates from its OSGi services now support pipeline data that contain Integration Server Object data types, for objects whose class type is part of the JDK, for example <code>java.io.InputStream</code> .

Release 10.0

Changed Item	Description
Application Platform API Libraries Classpath Container in Designer	The classpath container functionality is enhanced to allow you to select specific libraries from the runtime to add as classpath dependencies to Application Platform projects. When you deploy the project, the selected libraries are resolved from the runtime. For more information, see the Application Platform Users Guide.
Integration Server Service Wizard in Designer	The Integration Server Service Wizard dialog is enhanced to allow you to select Integration Server Document Types and Specifications when generating Java wrappers to use with Application Platform projects. For more information, see the Application Platform Users Guide.

Release 9.12

Changed Item	Description
Application Platform product icons in Designer	The Application Platform product icons in the Application Platform perspective, views, Welcome page, and About page in Designer are updated to reflect changes in the Software AG corporate branding.

Release 9.9

Added Item	Description
Create Bnd template menu option in the App Platform context menu	Generates a Bnd configuration file, <code>bnd.bnd</code> , in the <code>src/main/resources/OSGI-OPT</code> directory under the project root folder. If you customize the Bnd template, the contents of the project bundle manifest file are updated dynamically when you create a project bundle in Designer, or when you deploy your project to the runtime container.

Removed Item	Replacement, if any
Create Project Manifest menu option in the App Platform context menu	The Create Bnd template menu option, which generates a Bnd configuration file that allows you to update the contents of the project bundle manifest file dynamically.

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

PLD-RM-103-20181015

webMethods ApplinX 10.3 Readme

October 2018

This file contains important information you must read before using webMethods ApplinX 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0 Critical Information	1
2.0 Known Issues	2
3.0 Usage Notes	4
4.0 Fixes Included in Each Release	5
5.0 Other Resolved Issues	5
6.0 Documentation Changes	5
7.0 Terminology Changes	5
8.0 Added, Removed, Deprecated, or Changed Items	6
9.0 Added, Removed, Deprecated, or Changed Built-In Services	12
10.0 Added, Removed, Deprecated, or Changed Parameters	12
11.0 Added, Removed, Deprecated, or Changed APIs	13
12.0 Copyright Information	13
13.0 Support	13

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

- APX-12032
Autoskip problem occurs using English characters or numbers in a right-to-left ApplinX application. For the autoskip feature, the caret needs to be at the end of the field. However, with a Chrome or FireFox browser, the caret is at the beginning of the field. Press 'Home' to achieve the expected autoskip behavior on these browsers.
- APX-9278
After upgrading ApplinX from 5.2, Web services were not redirected to the new WSS/Axis 2 endpoint.
- APX-6104
Performance Monitoring: When using the Performance Monitor, all sessions are always traced and it is not possible to trace a specific session. The Framework Configuration Editor doesn't save the "Trace Specific Session" field contents and always reverts to "Trace all session" after saving.
- APX-8522
In the Mapper, when linking a value from nested arrays, the mapped attribute does not have the parent array's source index. To map from nested arrays, use the "Value Of" expression that will provide a source index for each level.
- APX-9686
When generating a JSP page from a screen group, the class name and the file name are not the same. In Java, the class name and file name have to be the same for the class to pass compilation.
- APX-3605
The ApplinX HTTP session in Eclipse's internal browser does not support popup windows.
- APX-7737
When the ApplinX server is deployed on Tomcat as a J2EE application, when connecting to the server from within Eclipse, the message box which is displayed, indicating that changes made in the Designer are not saved, should not be displayed and is incorrect.
- APX-10853
When pasting an expression from one procedure (Flow path etc.) to another, if there were references to other entities, the references are copied regardless whether the actual entities exist or not in the target location. No error or warning will appear when saving the procedure. It is the responsibility of the developer to check if the expression is valid or not, otherwise such a copy may result in failures at runtime.
- APX-5715
Blinking fields in generated pages is currently not supported.
- APX-7238
When using the hotfix distribution to install a hotfix, the ApplinX Designer is also upgraded. However the uninstall of the hotfix does not rollback the Designer to its previous version.

- APX-5288
When canceling the installation in critical points (for example, while installing the ApplinX plug-in) the installation folder is left in an unusable form.
- APX-8014
When attempting to download the same Natural Data Transfer file twice, the Save File dialog box is not opened.
- When a screen is identified as a window, the window title is not displayed in the Session View.
- When upgrading a web application, if in the original web application, folders or files were removed, the upgrade process will fail.
- APX-4036
Backward compatibility for macros: Due to changes in the framework infrastructure, macros from version 8.0 and below cannot be run and your users will have to record macros again.
- To run ApplinX under webLogic Application server, you are required to follow these steps: Unpack the WAR file with the WebLogic JAR utility. To deploy the application, in the webLogic Administrator, set the upload directory name the Upload Directory Name attribute to the root directory of the exploded application (instead of the location of the WAR file).
- When applying a Path procedure Screen Mapper node on a numeric multiple field, if there are some empty values, an exception error may occur. To avoid this from happening, change the multiple field type from numeric to alphanumeric.
- APX-8088
When importing or exporting a screen group without its referring entities, the reference to the entities is not saved.
- The method setLoadAsWindow(true) in the GXChangeNextForm event doesn't work.
- APX-5312
When using the Application Manager, on IIS7/IIS7.5, you need to configure the default application pool and ensure that the Managed Pipeline Mode is set to "Classic" (In the IIS manager, in the Application Pools node, edit the default application pool). When using the Application Manager on IIS7.5, you need to convert your application from a virtual directory to a web application (in the IIS manager, right-click on your application and select Convert to Application).
- In Procedures, when an output attribute is empty, the output element is not displayed in the console.
- APX-5009
In right-to-left applications, the string in fields in Screen Group is reversed when there are two field mappings to the same place. This can be solved by using only single mappings.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

Third-party Products

Some of the third-party products shipped with this version of ApplinX may contain security vulnerabilities. These third-party products are not updated when you apply a fix between releases, so you need to update the third-party products yourself as appropriate.

Frameworks API

- In order to work with the .NET Framework on 64-bit machines, enable 32-bit applications in the application pool.
- Keyboard mapping node in the Framework configuration editor has been moved to the Application properties in the ApplinX Designer. Configuring this via the framework is still possible, by directly editing the XML configuration file (gx_keyboardMappings.xml).
- Visual Studio 2003 is no longer supported. You must first convert your ApplinX VS.NET project to VS 2008 (by opening it in VS 2008) in order to upgrade your ApplinX .NET project. It is recommended to convert from .NET project type "Web Project" to "Web Site", as from the current version ApplinX generates .NET Web pages based on the "Web Site" format and file structure.
- Serialization of the ApplinX API table class (GXTable) to XML is no longer supported (typically used when exporting tables to Excel). A new solution can be found in the Composite demo Web Application.
- In order to work with the .NET Framework on IIS 6 and above, configure the application pool.
- ApplinX Java API/JSP Framework must be run under Java 1.8 or higher.

ApplinX Designer

- ApplinX HTTP console is no longer available for testing web services. Web Services can be tested in any development environment which supports Web Services.
- Screen group generation from .NET is not available.

Batch Files

- Using a batch file to reload an application is no longer required and this functionality is supported by configuring the archive interval parameter in the ApplinX Server Properties.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 9.9

- New full-text search engine no longer uses deprecated Java plug-in technology. New look and feel.

Release 9.8

- Software AG documentation is no longer available on the Software AG installer. You can access all Software AG documentation on the [Documentation website](#).

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 9.8

Old Term	New Term
Read-only repository	Locked repository

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Docker Support	You can build an ApplinX Docker image and run the Docker container using scripts provided with ApplinX.
Passing Natural parameters dynamically	You can specify different parameters at runtime (for example NATPARAM) depending on the business rule you choose.
License Metering using Command Central	ApplinX now supports the license metering functionality provided by Command Central. License metering depends on license manifest files. Each license manifest file issued by Software AG contains all contracts for one location of your organization. If you received license manifest files from Software AG, you can generate or view a report of the current state of your landscape.

Release 10.2

Added Item	Description
Sort Function for List of Field Mappings	You can sort the contents of a List of Field Mappings table by field name or by any other column. Click the header of the column by which you want to sort.
Single Sign-on under AS/400	ApplinX now supports Single Sign-on using a Kerberos ticket on the platform AS/400. A corresponding start-up response code is given.

Release 10.1

Added Item	Description
Support of Windows Server 2016	ApplinX now supports the operating system Windows Server 2016. This includes support for the following: <ul style="list-style-type: none">• IIS 10• .NET Framework 4.6
Visual Studio version 2015	ApplinX now supports Microsoft Visual Studio version 2015. Older version 2008/2010 are no longer supported.

Removed Item	Description
Visual Studio Version 2008/2010	These Visual Studio versions are no longer supported. ApplinX currently supports versions 2012/2015.

Release 10.0

Added Item	Description
Exclude connection information sets when importing applications	A new option is provided in the Import Entities wizard. This enables better transition from development to test and production environments.
Enhanced Search Options in Software AG Designer	You can now search for the following components of each entity: screens and screen groups; session data and date structure; path and flow procedures.
Visual Studio Version 2012/2015	Support added for these Visual Studio versions. Older versions 2008/2010 are still supported with this version but are deprecated.
Template handling	Template handling when creating an ApplinX Web application has been streamlined.

Removed Item	Description
Templates	Obsolete templates are no longer provided.

Deprecated Item

Visual Studio Version 2008/2010

Description

Support for these Visual Studio versions will be dropped in the next ApplinX version. ApplinX currently supports versions 2012/2015.

Release 9.12**Added Item**

Start/stop connection pools from Designer

Description

You can now start and stop connection pools from the context menu of a selected pool in the Software AG Designer.

Usability

Usability has been enhanced throughout the product and a troubleshooting guide has been added.

Removed Item

Automatically attempt to reconnect

Description

The "Automatically attempt to reconnect" check box in the Host connectivity property panel is redundant. The same action can be performed using a connection pool.

Deprecated Item

Print applet

Description

Applet technology will soon be deprecated or no longer supported in new browser versions. An alternative for host printing is provided using Java Web Start technology.

Release 9.10

Added Item	Description
Platform Certifications	<p>ApplinX now supports the following:</p> <ul style="list-style-type: none">• Java 8 The ApplinX code now compiles with Java 8, which means that customers can use Java 8 syntax in their ApplinX web applications.• Windows 10 The Windows 10 platform is now supported.• Eclipse 4.5 The ApplinX Designer Eclipse is now version 4.5.• Microsoft Edge Microsoft's Edge browser is now supported.
Updating to CentraSite	<p>You can now update an ApplinX application to CentraSite; this updates the assets that were changed since last registration/update. (Functionality available with fix-in-hand after GA.)</p>

Deprecated Item	Description
Automatically attempt to reconnect	<p>The feature Automatically attempt to reconnect, in the Host Configuration > Connectivity options is deprecated and will be removed in the next version. We suggest you use ApplinX Connection Pool functionality instead. A connection pool allows you to reconnect a session based on the pool's policy.</p>

Deprecated Item	Description
ActiveX technology	<p>Internet Explorer version 11 (which ApplinX currently supports) is the last IE version that can use Microsoft's ActiveX technology. At some point in the future this legacy technology will no longer be supported.</p> <p>For ApplinX, this will affect the following features:</p> <ul style="list-style-type: none"> • Type Ahead • Natural Data Transfer using ActiveX: <ul style="list-style-type: none"> ○ silent download and upload ○ downloading files to any folder on the client machine ○ Activating a Natural Command • Opening Multiple Web Sessions <p>Note: Natural Data Transfer without the use of ActiveX will continue to be supported.</p>

Changed Item	Description
Font Size	<p>The following changes have been made to font size handling in this version:</p> <ul style="list-style-type: none"> • Default font size for web application is 'Dynamic by resolution' instead of 13px. • In the fontSize combo box in the Configuration and Emulation windows, you can select font size from 10-24px (10, 12, 14, 16... 24px). See The HTML Emulation Toolbar. • In the fontSize combo box in the Emulation window, the new option 'Default' allows you to use the font size defined in Configuration. This is the default value in the Emulation window.
Rebranding	<p>ApplinX product and documentation have been updated to match the new Software AG look-and-feel.</p>

Changed Item	Description
--------------	-------------

DocType	Parameter <code>DocType</code> is no longer applicable for Framework Configuration - all pages now have the HTML5 doctype.
---------	--

However, the option was retained in the configuration window for reasons of backward compatibility. You can remove this obsolete option if you prefer: Update file `z_editConfig.htm` (.NET application) or `z_editConfig.jsp` (Java application) and remove the following code:

```
<tr>
  <td><gx:gxcheckbox runat="server" id="appConfig_AddDocTypeToFrameset"
    onclick="flipDisable('appConfig_DocTypeStr');"/></td>
  <td><a href="#" class="help1"
onclick="showHelp('framework/GXWebAppConfig.html#setAddDocTypeToFrameset(boolean)') ">Set
doc type attribute:</a></td>
  <td><input runat="server" id="appConfig_DocTypeStr"size="50"/></td>
</tr>
```

Release 9.9

Added Item	Description
------------	-------------

Comparing ApplinX applications	With the function Compare Application you can compare two ApplinX applications, typically two versions of the same application. In terms of application lifecycle management, being able to compare two different versions means you can perform impact analysis before deploying a new application version.
--------------------------------	--

Invoking a procedure, using REST	In addition to SOAP, ApplinX web services can now be invoked using REST. From the Procedure Group Entity Editor, select a procedure and choose the new option Copy REST URL to clipboard.
----------------------------------	---

Upgrade to Tomcat Server 8.0	The ApplinX internal Tomcat server is now version 8.0.
------------------------------	--

Enter key recognition	A distinction is now made between the two Enter keys (on numeric keypad and the main keyboard). Applies only to the following browsers: Firefox 29 and above; Chrome; Internet Explorer 11.
-----------------------	---

Changed Item	Description
--------------	-------------

Improved performance for large send sections	Performance for large send sections (for example Natural Data Transfer upload or the AS/400 save state feature) has been improved.
--	--

Changed Item	Description
Improved usability in flow mappers	Links now show source / target index expressions (if any exist). Double clicking anywhere on a link opens the link properties dialog (if the link can have properties). If a target index exists, "Append" is now off by default.

Release 9.8

Added Item	Description
Usability improvements	You no longer need to define a repository, because the application now uses an internal one instead.
Session filtering	In the ApplinX Administrator you can now filter your sessions by Session ID, Application, Device Name, Duration, State, Connection Pool and Type.
Mobile browser support	ApplinX now supports mobile browsers, for example the Safari Browser. The look and feel of the new ApplinX Web applications has been enhanced, in particular for applications specifically designed for easier use on mobile devices.
Property <code>isUsingactivex()</code>	When downloading Natural file, detects whether process is using ActiveX and changes the logic accordingly.

Removed Item	Replacement, if any
Storing ApplinX entities in an external repository is no longer supported.	Use instead the recommended internal repository that is already provided.

Changed Item	Description
New look and feel for the web applications.	

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 9.8

Added API	Description
Property <code>isUsingactivex()</code>	When downloading Natural file, detects whether process is using ActiveX and changes the logic accordingly.

Release 9.6

Added API	Description
<code>gx_getNdtDefaultDownloadFileName</code>	Use this user exit to manipulate/modify the name of a downloaded Natural file.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

APX-RM-103- 20181015

webMethods Business Console 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Business Console 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	5
6.0	Documentation Changes	10
7.0	Terminology Changes	11
8.0	Added, Removed, Deprecated, or Changed Items.....	11
9.0	Added, Removed, Deprecated, or Changed APIs	15
10.0	Copyright Information.....	17
11.0	Support.....	17

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- SBP_10.2_Portal_Fix1
- SBP_10.2_Runtime_Fix1
- SBP_10.1_Portal_Fix4
- SBP_10.1_Runtime_Fix4
- SBP_9.12_Portal_Fix13
- SBP_9.12_Runtime_Fix13
- SBP_9.9_Portal_Fix9
- SBP_9.9_Runtime_Fix9
- SBP_9.8_Runtime_Fix6
- SBP_9.8_Portal_Fix6

Release 10.2

- SBP_10.1_Portal_Fix3
- SBP_10.1_Runtime_Fix3
- SBP_10.0_Portal_Fix5
- SBP_10.0_Runtime_Fix5

- SBP_9.12_Portal_Fix11
- SBP_9.12_Runtime_Fix11
- SBP_9.10_Runtime_Fix4
- SBP_9.10_Portal_Fix4
- SBP_9.9_Portal_Fix7
- SBP_9.9_Runtime_Fix7

Release 10.1

- SBP_10.0_Portal_Fix4
- SBP_10.0_Runtime_Fix4
- SBP_9.12_Portal_Fix8
- SBP_9.12_Runtime_Fix8
- SBP_9.10_Runtime_Fix4
- SBP_9.10_Portal_Fix4
- SBP_9.9_Portal_Fix7
- SBP_9.9_Runtime_Fix7

Release 10.0

- SBP_9.12_Portal_Fix4
- SBP_9.12_Runtime_Fix4
- SBP_9.9_Portal_Fix6
- SBP_9.9_Runtime_Fix6
- SBP_9.8_Runtime_Fix5
- SBP_9.8_Portal_Fix5

Release 9.12

- SBP_9.10_Portal_Fix3
- SBP_9.10_Runtime_Fix3

Release 9.10

- SBP_9.9_Portal_Fix2
- SBP_9.9_Runtime_Fix2

Release 9.9

- SBP_9.8_Runtime_Fix2
- SBP_9.8_Portal_Fix2

Release 9.8

- SBP_9.7_Runtime_Fix2
- SBP_9.7_Portal_Fix2

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- SBP-3245
Deletion of AppSpace does not happen from the expanded section of the AppSpace tab.
This issue is now resolved.
- SBP-3388
DBO process in work stream on the What's Happening Now tab displays the error 'Unable to retrieve Business Rules.'
This issue is now resolved.
- SBP-3400
Task Business data does not get populated in a gadget that is added to the task details page in Business Console.
This issue is now resolved.
- SBP-3404
Unable to delete the AppSpace created with the option, "Is Internal" YES.
This issue is now resolved.
- SBP-3439
When you create an AgileApps gadget in SoftwareAG Designer, the JsonObject error is displayed.
This issue is resolved.
- SBP-3539
When you delete a task instance ID in the Business Console, an internal server error is displayed.
This issue is now resolved.
- SBP-3544
When you trigger a process instance which has a case type object, and open and update the case record from step summary, case record displays an error.
This issue is now resolved.
- SBP-3552
Child Task in Business Console for the Task deployed on Integration Server is not displayed.
This issue is now resolved.

Release 10.2

- SBP-3144
If you select a DBO process in work stream on the What's Happening Now tab, and then click on the process instance, the details of process instance are not displayed.
This issue is now resolved.
- SBP-3027
Certain labels in the user interface are not translated.
This issue is now resolved.
- SBP-3007
PUT operation with GET operation on load does not allow modification of string table input values.
This issue is now resolved.
- SBP-3005
Duplicate values in a string list that is provided as an input to a service leads to no output values.
This issue is now resolved.
- SBP-2993
Mandatory content in document list and document reference list are not deployed properly.
This issue is now resolved.
- SBP-2984
In localized languages such as Japanese, when a user performs scheduled delegation, an error occurs because the AM/PM strings are translated.
This issue is now resolved.
- SBP-2974
Default values in a document list that are specified in Designer are not displayed in the user interface.
This issue is now resolved.
- SBP-2963
StringList data type has no user interface control.
This issue is now resolved.
- SBP-2899
In Business Console, when you click the Get Current Location button in the Business Data tab of the case details page, an error appears and the geographic location is not fetched.
This issue is now resolved.
- SBP-2856
Landing page takes a long time to render.
This issue is now resolved.
- SBP-2779
Pin and hide actions for tasks, processes, and cases are not functioning as expected.
This issue is now resolved.

Release 10.1

- SBP-1944

In Designer, when you change the title, description, and hosts for a gadget, it does not update the gadget that was previously added to an AppSpace in Business Console.

This issue is now resolved.

- SBP-2513

What's Happening Now tab does not consider the latest statuses of DBO models and displays incorrect status counts.

This issue is now resolved.

- SBP-2615

My webMethods Server log shows 'unable to load ResourceBundle, basename=caf.war.wm_socialbpm_defaulttask.AppResources' when accessing Monitoring > Business > Tasks > DefaultTask > DefaultTask Inbox.

This issue is now resolved.

- SBP-2700

Masthead does not indicate the number of unaccepted tasks for roles. The icon on the masthead of Business Console indicates no unaccepted tasks even when unaccepted tasks are present for a role.

This issue is now resolved.

Release 10.0

- SBP-2345

User should be able to use unary operator (+) as part of expressions in gadgets using JavaScript.

This issue is now resolved.

- SBP-2966

For a new MWS user with view permissions, the dashboard with 'Activity streams' keeps displaying the loading page.

This issue is now resolved.

- SBP-1994

Upgraded 9.12 from 9.8 / 9.9 / 9.10 fails to load the WHN data as it fails to invoke user preference REST calls.

This issue is now resolved.

- SBP-2044

TLM Business Data saved search with values Boolean, Integer, Date, and Double are broken.

This issue is now resolved.

- SBP-2047

Business Console is not BiDi compliant.

This issue is now resolved.

- SBP-1952

Create case management gadgets in Business Console.

This issue is now resolved.

Release 9.12

- SBP-1816

Task details page modal should have inline scrolling.

This issue is now resolved.

- SBP-1808
To-do list people picker not launching for the second and subsequent items in the to-do list.
This issue is now resolved.
- SBP-1564
Certain issues with Action menu in Task Inbox gadget.
This issue is now resolved.
- SBP-1510
Unable to endorse users from Task Details page in Work Stream (within an AppSpace).
This issue is now resolved.
- SBP-1509
Configure columns not working in Work Stream (within an AppSpace).
This issue is now resolved.
- SBP-1502
Certain issues with Activity Stream comments in the Process Details page.
This issue is now resolved.
- SBP-1483
A loading image does not appear when reloading process list, but it appears when loading task list.
This issue is now resolved.
- SBP-1471
Task list management pagination has dependency on process list management pagination.
This issue is now resolved.

Release 9.10

- SBP-1648
Expert endorsements are not saved accurately in My webMethods Server with Microsoft SQL Server database.
If you endorse an expert with a rating in floating point value, the endorsement is not saved accurately in SQL Server database.
For example, a rating of 4.5 might be saved as 4.
This issue is now resolved.
- SBP-1359
URL to retrieve task business data is not accessible.
This issue is now resolved.
- SBP-1166
Clicking “Reset to default” for color theme returns incorrect selected theme in the REST URL.
This issue is now resolved.
- SBP-1116
Business Console does not display details of process instances belonging to version 9.5 or earlier.
Even after you migrate older process models that contain task steps to version 9.9, Business Console does not display these migrated processes.

To work around this issue, build and upload the 9.5 or earlier versions of process models in Software AG Designer, so that Business Console displays details of older processes that contain tasks.

This issue is now resolved.

- SBP-1109
Delegation of a task to multiple users for the first time is not working.
This issue is now resolved.
- SBP-1096
Task panels display in Work Stream toggles with "to-do -list" drop-down option.
This issue is now resolved.

Release 9.9

- SBP-1110
Task Inbox contains duplicate filters.
This issue is now resolved.
- SBP-916
Parent task node takes a long time to display the child tasks if the number of child tasks is large.
This issue is resolved by disabling the expand option on the parent node if the parent task has more than 200 child tasks. You can view the child tasks in the task details page.
- SBP-380
Keyword search text box disabled in Select Principals dialog.
This issue is now resolved.

Release 9.8

- SBP-734
Business Console does not display the business data of a task, if the task type name contains "." character.
This issue is resolved.
- SBP-654
Business Console does not update the task contributor list when the task is accepted in the Task Detail tab.
This issue is resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- Included information about Process with Case Task type step in *Working with webMethods Business Console* guide.
- Included information about REST Service timeout & Task details for assets created in Web Designer in *Working with webMethods Business Console* guide.
- Included information about AppSpace drop-down in *Developing Gadgets for Business Console* guide.

Release 10.1

- Included information about events for built-in gadgets in the *Working with Business Console* guide.

Release 9.12

- Included information about case management in the *Working with Business Console* guide.

Release 9.10

- Updated the *Working with Business Console* guide to include description for scheduling tasks, using My Calendar, using gadgets for creating dashboards, and using gadgets for customizing process details and task details.

Release 9.9

- Included permission reference for Business Console users in the *Working with Business Console* guide.

Release 9.8

- Added context-sensitive online help.
- Updated the *Working with Business Console* guide to include description for using group tasks, saved searches, and the user interface customization options.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 10.0

Old Term	New Term
Copy AppSpace	Clone AppSpace

Release 9.12

Old Term	New Term
Dashboard	AppSpace

Release 9.10

Old Term	New Term
Collaboration task or child task	Instant task

Release 9.9

Old Term	New Term
Process Stream	Work Stream
Group Task	To-Do List
Inbox	Task Inbox

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.1

Added Item	Description
Case gadgets	Built-in gadgets for cases in Business Console.
Scheduled task delegation	Enables you to schedule the delegation of tasks associated with a particular task type.

Added Item	Description
Gadget information in the Add New Gadget dialog	Information about a gadget such as events and description appears on the dialog when you select the gadget.
MashZone NextGen gadget	Displays the MashZone NextGen data on Business Console as a gadget.
Action menu orientation in Task Inbox	Enables you to select a position to display the task actions menu in the Task Inbox gadget.

Release 9.12

Added Item	Description
AppSpace permissions	Enables you to provide AppSpace permissions in Business Console.
Gadget enhancements	<p>Ability to do the following:</p> <ul style="list-style-type: none"> ▪ Group and share AppSpaces. ▪ Create custom AppSpace layouts. ▪ Expand and collapse gadgets in an AppSpace. ▪ Search for gadgets in the Add New Gadgets dialog box. ▪ Access AppSpaces independently using a URL outside of Business Console. ▪ Show/hide case types, process types, and task types in Work Stream. ▪ Generate to-do lists sequentially. ▪ Customize gadget panels to use custom icons/actions.
Scheduled child task	Enables you to create a scheduled child task.
Case management	Enables you to manage AgileApps cases in Work Stream.

Release 9.10

Added Item	Description
Gadgets	Enables you to: <ul style="list-style-type: none">▪ Create UI components by using HTML, CSS, and JavaScript.▪ Use built-in gadgets and user-created gadgets for customizing dashboards.
Dashboards tab	Enables you to: <ul style="list-style-type: none">▪ Create new dashboards using gadgets.▪ Edit dashboards and configure the gadgets used in the dashboard.▪ Use a customized dashboard instead of the default What's Happening Now page.
My Calendar panel on What's Happening Now tab	Enables you to: <ul style="list-style-type: none">▪ View the days when you have scheduled tasks.▪ View which tasks are scheduled to start on a date.▪ Identify the days when more task are scheduled. Darker shade of blue indicates that there are more tasks scheduled on that day.▪ View, reschedule, or edit a scheduled task.
Task Schedule Date and Time fields in Start Task dialog	Enables you to specify the date and time when the task instance should start.
Work Stream Settings in Administration page	Enables you to specify whether to display project name along with process type name and task type name on Work Stream.
Gadgets option in Customize Business Console page	Enables you to specify colors for gadget components.
Callable Process Instances	Enables you to view the callable processes or reference processes of parent processes in a process list in Work Stream.

Release 9.9

Added Item	Description
Process instance details page	Enables you to: <ul style="list-style-type: none">▪ View process instance details, process diagram, task instances related to the process, process duration, and the consolidated list of attachments and comments of the process tasks.▪ Attach files or add comments to process tasks.▪ Navigate to the task instance details page of task instances related to the process.
Process instance search	Enables you to search for process instances based on one or more search criteria.
Process list column configuration	Enables you to configure the columns to be displayed in the process list.
Child Instances panel in task detail page	Enables you to view the child instances, if any.
Hide/Show toggle buttons for panels in instance detail page	Enables you show or hide panels in the instance detail page of a process or task.
Mandatory task	Enables you to specify mandatory child tasks.
Task type setting	Enables you to specify whether to display the task ID, custom ID or name of task types in task lists and task detail pages.
Tab label customization	Enables you to customize the labels of the tabs in the process detail and task detail pages.

Release 9.8

Added Item	Description
Group task	Ability to create and manage grouped tasks.
User interface customization	Ability to customize the logo, title, color theme, masthead, and the landing page.
Saved searches	Ability to create and re-use the saved searches for tasks.
“Do Not Show Endorsements” option	Specifies whether to display or hide endorsements in the Task Detail tab and the Task Experts panel.
Processes tab	Ability to view the process analytics dashboard.

9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 9.9

Added API	Description
GET Access Privileges	This REST request retrieves the access privileges of the user.
GET Functional Privileges	This REST request retrieves the functional privileges assigned to user for a task type.
GET Process Instances	This REST request retrieves the process instances of a specified process type.
GET Process Instance Status Summary	This REST request retrieves the summarized status of all the process instances belonging to all versions of the specified process type.
GET Task Types	This REST request retrieves the list of all task types.
GET Task List	This REST request retrieves paginated list of tasks specified by the search criteria.
GET Task Details	This REST request retrieves the details of a specified task.
PUT Task Detail	This REST request updates the parameters of a specified task.
GET Task Attachment Count	This REST request retrieves the number of attachments of a specified task.
GET Task Attachments	This REST request retrieves a paginated list of attachments of a specified task.
POST Task Attachment	This REST request adds an attachment to a specified task.
DELETE Task Attachment	This REST request deletes a specified attachment.
GET Task Comments	This REST request retrieves the task comments of a task.
GET Task Comments for a Task Type	This REST request retrieves the list of comments of a task type.
POST Task Comment	This REST request adds a comment to the specified task.

Added API	Description
DELETE Task Comment	This REST request removes a comment from a specified task.
GET All Task Tags	This REST request retrieves all the task tags.
POST Task Tags	This REST request adds a new tag for tasks.
DELETE Task Tags	This REST request removes the specified tags.
POST Child Task	This REST request creates a child task for the specified parent task.
PUT Delegate Task	This REST request delegates a task to the specified user.
DELETE Task Delegation	This REST request removes delegation of the specified task from a user.
GET Task Audit Information	This REST request retrieves the paginated audit information of a specified task.
GET Task Inbox Names	This REST request retrieves all the custom and default task inbox names.
GET Task Expert Count	This REST request retrieves the number of experts identified for a task type.
GET Task Expert List By Task Type	This REST request retrieves a paginated list of experts for the specified task type.
POST Default Endorsement	This REST adds the default endorsement rating to the user for a task.
POST Endorsement Rating	This REST request adds endorsement rating for users for a specified tag.
GET Group Task Template	This REST request retrieves a to-do list template.
GET All Group Task Template	This REST request retrieves all to-do list templates.
POST Group Task Template	This REST request adds a to-do list template.
PUT Group Task Template	This REST request updates a to-do list template.
DELETE Group Task Template	This REST request deletes a to-do list template.
POST Group Task Using Template	This REST request adds a to-do list by using a template.
POST Group Task Without Template	This REST request adds a to-do list without using a template.
DELETE Group Task	This REST request deletes a to-do list.

Added API	Description
GET Saved Search	This REST request retrieves the saved searches for one the following as specified in the request input: <ul style="list-style-type: none"> All task lists Task list specific to a task type My Inbox Custom Inbox
POST Saved Search	This REST request adds a new saved search.
PUT Saved Search	This REST request modifies a saved search.
DELETE Saved Search	This REST request removes a saved search.

10.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

BC-RM-103-20181015

webMethods Business Process 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Business Process 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information	2
2.0	Known Issues	2
3.0	Usage Notes	6
4.0	Fixes Included in Each Release	7
5.0	Other Resolved Issues	9
6.0	Documentation Changes	12
7.0	Copyright Information	12
8.0	Support	12

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

Business Process Development

Process Development

- WMDPD-357
The input/output of a web service connector defined for a step results in an unknown data type if the input/output contains a record structure.
If a web service connector with a record structure in its input/output definition is defined for a step, the resulting input/output for the step is defined as an unknown data type.
Workaround: Manually map the inputs/outputs of elements of the record structure.
- WMDPD-662
webMethods Monitor cannot distinguish between models after a process model is exported from one project and imported into another project in Process Development.
This can occur when a process model is exported from Designer into a source control system, then checked out of the source control system and subsequently imported into another project in Process Development. This causes the two models to be indistinguishable in webMethods Monitor.
Workaround: To avoid this situation, export projects along with their corresponding .process files for storage into a source control system. See WMDPD-5659 below for additional check-in/check-out information.
- WMDPD-1555
Annotations cannot be attached to steps that are not located in the same pool as the annotation. A step and its annotations must be located in the same pool in order to be connected.
Workaround: Ensure that each annotation is located inside the same pool as the step it annotates.
- WMDPD-1898
Pools may not be dragged directly vertically within a process canvas if the drop location overlaps the current pool location.
Dragging a pool does not allow the drop to occur unless the pool has been moved totally beneath the current location or slightly to one side.
Workaround: Either drag the pool slightly horizontally or use the keyboard arrow keys to move the pool. Note that the keyboard arrow keys are enabled by pressing "." after the item is selected.

- WMDPD-2328

Renaming Integration Server (IS) documents or services in the Package Navigator view does not update references to those documents or services in any processes, and may result in errors during build and upload.

Errors in building and uploading processes occur because Designer attempts to access documents or services using their original names, which no longer exist.

Workaround: Manually update all references to IS documents and services after modifying them.
- WMDPD-5035

When deploying e-forms, connection properties for JCR and Content Service Provider settings cannot be configured in offline mode.

Workaround: When deploying e-forms, you must manually configure the JCR and Content Service Provider in the target environment.
- WMDPD-5081

Post-deployment verification of BPM assets fails.

When BPM assets are deployed through a repository type project and then deployed using the target server as the run-time source in another project, that other project does not retain the required process dependencies as the BPM process that was deployed using the repository.

There is currently no workaround for this issue.
- WMDPD-5231

Master build scripts fail to generate ACDL and composites for BPM assets named with double-byte characters.

BPM assets named with double-byte characters fail to generate ACDL and Composites when deploying with master build scripts. This can cause Deployer to not work properly.

Workaround: Do not use double-byte characters when naming processes.
- WMDPD-5245

Designer limits the number of boundary events displayed on an activity.

Designer displays a maximum of six (6) boundary events on an activity. Additional events are "hidden," though they exist in the model.

There is currently no workaround for this issue.
- WMDPD-5659

The Solutions view does not display assets checked out from SVN.

If you create solutions and process projects in a non-default location, care must be taken when multiple users are checking out the associated assets from SVN. Due to the way Eclipse stores metadata associated with its resources, checking out from SVN requires the use of Designer's import capability (rather than the use of the SVN plug-in's checkout capability). When you check into SVN a solution defined in a non-default location, Eclipse maintains additional metadata about that non-default location (a workspace-specific path to get there). This additional metadata should not be checked into SVN. First, the metadata is different for each workspace. Second, it is internal to the Eclipse framework and can change when Eclipse versions change.

Workaround: Perform check-in/check-out steps as follows:

 - To check in an asset from a single workspace (Workspace A), use the SVN plug-in in the

Navigator view in the Process Developer perspective. Right-click the solution containing the asset. Click Team > Share Project, then select SVN and follow the wizard. The .process file and its supporting assets/resources (the .project, build.xml, and .solution files) are checked into SVN. As you make changes to your process and Eclipse makes changes to the associated assets, use the SVN plug-in in the Navigator view to check in these changes.

- To check out an asset into a different workspace (Workspace B), do not use the SVN plug-in in the Navigator view. Instead, check out the solution from SVN outside of Designer, using your file system. Create a solution in Workspace B, and then import the .process file into it. During the import, you can define a new process project (in either a default or non-default location) for the imported .process file. Any supporting assets and resources, such as Integration Server packages, that contain necessary documents and/or services also need to be made available to Workspace B. Be sure to check in/out supporting assets as necessary.

- WMDPD-6863
Models containing Event Types in logged fields are not generated properly with the command line generation tool.
There is currently no workaround for this issue.
- WMDPD-7381
Concurrent deployment to a cluster hangs the PRT service.
Choosing the concurrent deployment option in Deployer causes a hang in the PRT service that is called to enable/disable the process model after deployment.
There is currently no workaround for this issue.
- WMDPD-7899
Process models may fail to generate using the command-line generation tool.
Process models may fail to generate using the command-line generation tool with the message “Unsupported Action: Create Queue”. This occurs when the PE_NONTRANSACTIONAL_ALIAS setting for “Manage Destinations” is set to “No” in the Integration Server Administration Messaging page under JMS Settings.
Workaround: Set the “Manage Destinations” setting to “Yes” for the PE_NONTRANSACTIONAL_ALIAS.

ARIS Integration

- WMDPD-4518
Process models that contain gateway steps and that are exported into XPDL display transition lines incorrectly when imported back to Designer from ARIS.
If a process model containing gateway steps is exported as XPDL to ARIS and then imported back to Designer from ARIS, the imported model displays transition lines incorrectly.
Workaround: Use the “Arrange > Layout” operation to correctly draw the lines.
- WMDPD-5422
Designer does not import ARIS processes that refer to a WSDL that has no operations defined.
During import of a process that contains service requests that specify a WSDL with no operations,

exceptions appear in the Designer wizard.

Workaround: Ensure that all services that are referenced in ARIS have operations defined.

- WMDPD-5754
WSDL files that do not contain bindings used in abstract operations are rejected in the XPDL Import Wizard.
Importing a WSDL file that does not contain bindings from ARIS using “Share with IT” causes the XPDL Import Wizard to reject the import.
There is currently no workaround for this issue.

- WMDPD-7654
Models that contain CentraSite predefined web services cannot be used in a round-trip operation between ARIS and Designer.
A CentraSite installation contains a set of web services. Process models that include a predefined CentraSite web service cannot be used in a round-trip operation between ARIS and Designer. If used, the services may not be recognizable by ARIS. The list of predefined CentraSite services includes:
UDDI Publish API Services
UDDI Inquiry Services
UDDI Custody and Ownership Transfer API
UDDI Security Service
LifecycleManagementService
ImportXPDLService
SearchService
ApprovalService
RegistrationService
ImportWsdService
ImportXsdService
There is currently no workaround for this issue.

- WMDPD-8880
Processes will not start for models having specific subscription filters on String data types.
For process models defined with subscription filters on String data types that use logical operators “>”, “>=”, “<=”, or “<”, processes will not start as expected after publishing documents that satisfy the filtering criteria.
Workaround: For String data types, use the operators “does not start with”, “does not end with”, “does not contain”, “contains”, “starts with”, and “ends with”.

Process Engine

- WPE-1551
A process with an invalid SOAP address in the web service descriptor executes successfully.
If a process containing an invalid SOAP address in a web service descriptor is executed by the Process Engine, the process executes successfully and no error is displayed in webMethods Monitor.

Workaround: The error shows in the Integration Server log as a “service cannot be found” error.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- Business Process configuration advice for CLARC use cases:
 - PPM uses the end time of a process step when displaying business data for that step. Depending on where the business data occurs in the events, the timestamp used in the KPIs in Optimize may be different from the timestamp in the PPM charts. In order to get the closest representation of the data from Optimize and PPM, it is recommended to configure the business process to send the business data at the end of a step.
 - PPM merges multiple PSIC events for one process step to one function and this results in the use of only the last attribute value. When multiple events for a process step contain business data with the same event type, or one PSIC event contains the same business data event type multiple times, data may be lost due to PPM using only the last attribute value. To get the closest representation of the business data from both Optimize and PPM, when configuring the business process it is recommended that only one copy of the business data is sent. Additionally, that business data must also be sent at the end of the process step.
 - Converting an EDA event type to an Integration Server document type causes the elements in the Integration Server document type to appear with a namespace identifier prefix, for example “p:Order”. This may lead to inappropriate content in the businessData elements of the corresponding EDA events. It is recommended to edit the Integration Server document type and remove the prefix from all elements, for example, the element name will then be “Order”.

Business Process Development

- When a send task step is used in a process invoked as a referenced subprocess:
 - If an IS document is configured both as a Send Document and a Return Document for the parent process, the document is not published to the messaging provider.
 - If an IS document is configured as a Send Document, but not as a Return Document for the parent process, the document is published to the messaging provider.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Business Process Development

Release 10.3

- DES_10.2_Process_Fix2
- DES_9.12_Process_Fix9
- DES_9.9_Process_Fix8
- DES_9.7_Deployer_Fix6

Release 10.2

- DES_9.8_Process_Fix8
- DES_9.12_Process_Fix6
- DES_9.12_Deployer_Fix3
- DES_10.1_Process_Fix4

Release 10.1

- DES_9.10_Process_Fix4
- DES_9.12_Process_Fix3
- DES_10.0_Process_Fix1

Release 10.0

- DES_9.9_Process_Fix5
- DES_9.12_Process_Fix2

Release 9.12

- DES_9.6_Process_Fix7
- DES_9.8_Process_Fix2

- DES_9.9_Process_Fix3
- DES_9.10_Process_Fix2

Release 9.10

- DES_8.2_SP2_Deployer_Fix5
- DES_9.8_Process_Fix2
- DES_9.9_Process_Fix2

Release 9.9

- DES_8.2_SP2_Process_Fix33
- DES_9.6_Process_Fix6
- DES_9.7_Process_Fix5
- DES_9.7_Deployer_Fix1

Release 9.8

- DES_9.6_Process_Fix4
- DES_9.7_Process_Fix1

Process Engine

Release 10.0

- PRT_9.7_Fix12
- PRT_9.8_Fix13
- PRT_9.9_Fix7
- PRT_9.10_Fix2

Release 9.12

- PRT_9.7_Fix11
- PRT_9.8_Fix10

Release 9.10

- PRT_9.6_Fix9

- PRT_9.9_Fix1

Release 9.9

- PRT_8.2_SP2_Fix20
- PRT_9.7_Fix6
- PRT_9.8_Fix1

Release 9.8

- PRT_8.2_SP2_Fix19
- PRT_9.0_SP1_Fix6
- PRT_9.7_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Business Process Development

Release 10.2

- WMDPD-8667
SoftwareAG Installer cannot install Designer->Business Processes into a subfolder of Program Files
When using the SAG Installer to install into a subfolder of Program Files, selecting the Designer->Business Processes install tree node will display an error dialog showing missing dependencies.
The issue is resolved.

Release 9.12

- WMDPD-8406
Models created with EDA as receive protocol do not generate.
If a model is defined with receive protocol as EDA, the model will fail to generate in Designer. This is because the EventBus JMS Connection Alias is not defined on the Integration Server which is connected to the Designer instance.
This issue is now resolved.

Release 9.10

- WMDPD-8265
Resubmitting a process instance in a distributed logical server configuration results in an exception.

If a process instance is resubmitted in a configuration where multiple logical servers are defined in a distributed multi-node environment, a null pointer exception may be raised and the resubmission will fail.

The issue is resolved.

Release 9.8

- BZA-296
When you include a decision tree in a rule, you get an exception in My webMethods when you try to view the decision tree in the RMA.
This issue has now been resolved.
- WMDPD-7979
On XPDL export/re-import, the Receive document may get lost.
This issue is now resolved.
- WMDPD-7943
The `pub.monitor.process.instance:generateInstanceImage` may report incorrect coordinates.
This issue is now resolved.
- WMDPD-7627 (DES_9.6_Process_Fix1)
If a process was exported using XPDL and later was changed to upper/lowercase, the re-import may fail silently.
This issue is now resolved. A warning should be displayed.
- WMDPD-7951
Subscription document property on Start Message Event and Receive Task is not set.
Selecting subscription document using the Browse button does not allow the document type to be set. However, drag and drop the document type onto the canvas or receive task sets the document type properly.
This issue is now resolved.
- WMDPD-7937
The initial minimum log level setting in Designer is not uploaded on first generation of the process. The first time a process is generated during build and upload, the minimum log level setting is not included. Instead, the minimum log level setting reverts to "5 - Process and all events and activities and looped activities" upon first build and upload of the process. In subsequent build and upload actions, the minimum log level setting is captured as expected.
This issue is now resolved.
- WMDPD-7913
XPDL import does not set all references to IS Documents.
The XPDL import may ignore references to IS Documents for "Start Events", "End Events" and "Task" Output". Only the documents referenced as "Task" input are correct referenced.
This issue is now resolved.

- WMDPD-7931
Receive task with no subscription document does not produce an error on build and upload.
When a process contains a receive task that has no subscription document defined for it, the process can be successfully built and uploaded. The expected behavior is that an error message should occur that prevents the process from being built and uploaded successfully.
This issue is now resolved.
- WMDPD-7908
There may be reduced performance on certain type of JMS models.
This could be caused due to the Max Prefetch property was defaulted to 10.
This issue should now be resolved. The Max Prefetch will default to 1.

Process Engine

Release 9.8

- WPE-3278
In some situations, user task step iterations may complete out of order.
When a user task step is executed multiple times to have several iterations in a process instance and one of the iteration is completed, it would appear Process Engine completed another iteration of the same step.
This issue is now resolved.
- WPE-3266
In some situations, activity log may not be logged properly.
When `pub.prt.log:logActivityMessages` is invoked from an outbound mapping service of a user task step, it does not come up in Process Instance Details view.
This issue is now resolved.
- WPE-3280
In some situations, a migrated process model instance may fail.
When the migrated process model has a boundary timer event step, but no timeout value is set for the timer, the instances may fail.
This issue is now resolved.
- WPE-3251
In some situations, a Task Engine callback may result in a process instance restart.
Upon receiving a callback from Task Engine for a completed process instance, Process Engine attempts to restart the user task step, which results in process failure.
This issue is now resolved. Process Engine will check the status of the process instance before attempting to restart the user task step. If the instance was not running, the callback will be ignored.
- WPE-3274
In some situations, a completed process instance may fail.
A parent process that completes before any of its child instances complete is erroneously logged as failed when the child instance rejoins the parent.

This issue is now resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

The Process Engine documentation is available as a webhelp on the Software AG Empower website.

7.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

8.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

BP-RM-103-20181015

webMethods Business Rules 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Business Rules 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	3
5.0	Other Resolved Issues.....	5
6.0	Documentation Changes	9
7.0	Terminology Changes	10
8.0	Added, Removed, Deprecated, or Changed Items.....	11
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	11
10.0	Added, Removed, Deprecated, or Changed Parameters.....	11
11.0	Added, Removed, Deprecated, or Changed APIs	11
12.0	Copyright Information.....	13
13.0	Support.....	14

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

Rules Engine

- It is possible to design rules that evaluate in an infinite loop at runtime. webMethods Rules Engine has no validation logic to identify possible infinite loops at design time. With the help of the Run As... option, the rule designer can execute rules locally in webMethods Rules Engine to test and verify rule behavior. This local rule execution might expose loops at design time.

Rules Development

- It is possible to design rules that evaluate in an infinite loop at runtime. webMethods Rules Development has no validation logic to identify possible infinite loops at design time. With the help of the Run As... option, the rule designer can execute rules locally in webMethods Rules Development to test and verify rule behavior. This local rule execution might expose loops at design time.
- Manual decision process actions can currently not be created for Dynamic Business Orchestrator processes.

Rules Management Console

- If you upgrade a rule project in Rules Management Console from a version prior to 9.10, you must assign access rights to users who are supposed to see the new navigation tree item Decision Trees.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Rules Engine

Release 10.3

- WOK_10.1_RuleEngine_Fix5

Release 10.2

- WOK_10.1_RuleEngine_Fix2

Release 10.0

- WOK_9.12_RuleEngine_Fix3

Release 9.12

- WOK_9.7_RuleEngine_Fix5
- WOK_9.10_RuleEngine_Fix1

Release 9.10

- WOK_9.7_RuleEngine_Fix3

Release 9.9

- WOK_9.8_RuleEngine_Fix1

Release 9.8

- WOK_9.6_RuleEngine_Fix4
- WOK_9.7_RuleEngine_Fix1

Rules Management Console

Release 10.3

- WOK_9.12_RMC_Fix7

- WOK_10.1_RMC_Fix5

Release 10.2

- WOK_10.1_RMC_Fix2

Release 10.1

- WOK_10.0_RMC_Fix1

Release 10.0

- WOK_9.12_RMC_Fix3

Release 9.12

- WOK_9.10_RMC_Fix1
- WOK_9.9_RMC_Fix1
- WOK_9.8_RMC_Fix4
- WOK_9.7_RMC_Fix5

Release 9.10

- WOK_9.8_RMC_Fix3
- WOK_9.7_RMC_Fix3

Release 9.9

- WOK_9.8_RMC_Fix2
- WOK_9.7_RMC_Fix2
- WOK_9.6_RMC_Fix6

Release 9.8

- WOK_9.7_RMC_Fix1
- WOK_9.6_RMC_Fix4

Rules Development

Release 10.3

- WOK_10.1_RuleDesigner_Fix5

Release 10.2

- WOK_10.1_RuleDesigner_Fix2

Release 10.0

- WOK_9.12_RuleDesigner_Fix2

Release 9.12

- WOK_9.10_RuleDesigner_Fix1
- WOK_9.7_RuleDesigner_Fix5

Release 9.9

- WOK_9.8_RuleDesigner_Fix1

Release 9.8

- WOK_9.6_RuleDesigner_Fix4
- WOK_9.7_RuleDesigner_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Rules Engine

Release 10.1

- WOK-11680
Create checkpoint fails for a webMethods Deployer deletion set.
Using webMethods Deployer, it is not possible to delete a rule project on Integration Server.
Deployer fails at CreateCheckpoint with a “composite that should be checkpointed [null] is of wrong type: null” error.

This issue has been resolved.

Rules Management Console

Release 10.2

- WOK-12220
Rules Management Console does not start if webMethods Task Engine is not installed.
If webMethods Task Engine is not installed on My webMethods Server, Rules Management Console fails to start with an “ERROR installing: wm_rma.war java.lang.reflect.InvocationTargetException”.
This issue has been resolved.
- WOK-12222
The Business Rules Settings page does not work if webMethods Task Engine is not installed.
If webMethods Task Engine is not installed on My webMethods Server, navigating to the Business Rules Settings page on My webMethods Server results in a “javax.portlet.PortletException”.
This issue has been resolved.

Release 10.1

- WOK-11283
Inline editor changes constants, actions, and parameter elements to literal values.
When you select a constant, action, or parameter element of a result node or a condition node and confirm it with the enter key, the value is changed to a literal value and processed accordingly.
This issue has been resolved.
- WOK-11222
Rule project is hot deployed twice when clicking the Close button.
When you hot deploy a rule project and click the Close button of the Hot Deployment Results pop-up window, you may trigger a second hot deployment of this rule project.
This issue has been resolved.

Release 9.10

- WOK-8983
Rule project migration via Public API fails in AIX environment.
On AIX OS, invoking the Rules REST API service
PUT http://%mws_host%:%port%/wm_rma/rest/raw/project/%ruleProjectName%
with a rule project created in a version prior to 9.9 results in an HTTP error 400 and a “RuleProjectTransformationException ... ”.
This issue has been resolved.

Release 9.9

- WOK-8197
Cancel button does not cancel all changes and may cause an exception on Internet Explorer 11.

On Internet Explorer 11, the Cancel button in the decision entity editor will not cancel all edits if only an operator and no value were selected as cell content. Upon closing and re-opening the decision table, an exception may occur.

This issue has been resolved.

- WOK-8110

Show hidden warnings link causes an exception if no decision entity is selected.

If no decision entity is selected in the Rules Management Console, clicking on the Show hidden warnings link in the Rule Project Verification window causes a NullPointerException.

This issue has been resolved.

Release 9.8

- WOK-7465

Rows added to decision tables are lost when assigning principals.

When assigning principals to two or more condition cells or result cells, the rows added to a decision table are lost.

This issue has been resolved.

Rules Development

Release 10.2

- WOK-11712

After Integration Server migration to 10.1, the configuration for subscribing to rules-related events is missing.

When migrating the WmBusinessRules package on Integration Server from a previous release to 10.1, the “DRulesAuditingOnOff” and “DRulesAuditingEDAOnOff” configurations in the SAG_DIR\profiles\IS_default\configuration\wrapper.conf file are missing.

This issue has been resolved.

Release 10.1

- WOK-11285

ALWAYS is listed as an assignable constant in Software AG Designer.

When using the Condition Value Modification dialog in Software AG Designer, ALWAYS is listed as a selectable option in the Constants tab. If you select this option, it is not evaluated properly at runtime.

This issue has been resolved.

Release 9.9

- WOK-8178

Restore Defaults button on the Rule Verification Preference page produces error.

If the Optimistic radio button on the Rule Verification Preference page is selected, and you click Restore Defaults, both radio buttons (optimistic and pessimistic) are checked.

This issue has been resolved.

- WOK-8031
Content assist error dialog may appear when editing rules.
When editing rules, an Errors During Content Assist dialog may appear.
This issue has been resolved.
- WOK-8112
Misleading message appears when deleting an unused parameter.
A misleading message appears when trying to delete an unused parameter, as unused parameters cannot be successfully deleted.
This issue has been resolved.

Release 9.8

- WOK-7515
When dragging and dropping a decision entity into a rule set, an exception is thrown.
An exception is thrown when dragging and dropping one or more decision entities into a rule set.
The action is successful and the items are copied.
This issue has been resolved.
- WOK-7516
Right-clicking a result row in an external event rule causes an exception.
A problem exists when selecting result rows in an external event rule. A “ClassCastException” is reported to the error log, and the ability to cut, copy, and paste is disabled. In addition, it is not possible to open the context menu.
This issue has been resolved.
- WOK-7520
Data model generation can fail when model fields contain special characters.
When generating a new data model from document types that contain certain special characters, the generated fields are not complete and are incorrect. This can result in incorrect decision column header names and errors in functions.
This issue has been resolved.
- WOK-7530
An exception occurs before a rule project is upgraded.
When attempting to open a decision table that requires an upgrade to version 9.7, a “NullPointerException” is reported to the error log. The decision table is still opened within an upgrade editor, and it is still possible to upgrade to 9.7.
This issue has been resolved.
- WOK-7533
When exporting or importing a rule project to or from a My webMethods Server repository, a misleading error message is displayed.
When attempting to export or import a rule project to or from a My webMethods Server repository, the error message does not contain sufficient information if the credentials for the My webMethods

Server connection are invalid. The error message states: "Can't connect to server. Check the connection!"

This issue has been resolved.

- WOK-7544

Problems occur when special characters are used in functions.

When the names of parameter elements that are used in functions contain dot, percent, backslash, or double quote characters, errors occur when editing the functions.

This issue has been resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Rules Management Console

Release 10.3

- GDPR information was added.

Release 10.1

- New user interface was documented.

Release 10.0

- Additional API REST services were documented in the webMethods Business Rules Reference help.

Release 9.12

- Information about editing decision trees and working with a data provider service was added.
- Additional API REST services were documented in the webMethods Business Rules Reference help.

Release 9.10

- Chapter "Working with Decision Trees" was added.

Release 9.9

- API REST services were documented in the webMethods Business Rules Reference help.

Release 9.8

- Chapter “Working with Functions” was renamed to “Working with Expressions” and modified.
- All function descriptions were removed from the Working with Business Rules in My webMethods guide and assembled in the new webMethods Business Rules Reference help.
- Changes in the user interface were documented.

Rules Development

Release 10.3

- GDPR information was added.

Release 10.2

- Auditing was documented in the webMethods Business Rules Reference help.

Release 10.1

- Information about working with Predictive Analytics was added.

Release 9.12

- Information about working with a data provider service was added.

Release 9.10

- Chapter “Working with Decision Trees” was added.

Release 9.8

- Chapter “Working with Functions” was renamed to “Working with Expressions” and modified.
- All descriptions of functions, built-in services and rules-related event types were removed from the webMethods BPM Rules Development Help and assembled in the new webMethods Business Rules Reference help.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 10.0

Added API	Description
GET <base URL>/projects/%ruleProjectName%/decision_tables/%decisionTableName%	Returns the specified decision table.

Deprecated API	Replacement
GET <base URL>/project/%ruleProjectName%/decisiontable/%decisionTableName%	GET <base URL>/projects/%ruleProjectName%/decision_tables/%decisionTableName%

Release 9.12

Added API	Description
PUT <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%	Updates the specified decision tree in the given rule project with the provided decision tree JSON.
GET <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/condition_nodes/%conditionNodeId%	Retrieves a condition node with the specified conditionNodeId in the given decision tree and rule project.
PUT <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/condition_nodes/%conditionNodeId%	Updates a condition node with the specified ConditionNode JSON for the conditionNodeId in the given decision tree and rule project.

Added API	Description
GET <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/lines/%lineId%	Retrieves a condition line with the specified lineId in the given decision tree and rule project.
PUT <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/lines/%lineId%	Updates a condition line with the specified Line JSON for the lineId in the given decision tree and rule project.
GET <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/result_nodes/%resultNodeId%	Retrieves a result node with the specified resultNodeId in the given decision tree and rule project.
PUT <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/result_nodes/%resultNodeId%	Updates a result node with the specified ResultNode JSON for the resultNodeId in the given decision tree and rule project.
GET <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/results/%resultId%	Retrieves a result with the specified resultId in the given decision tree and rule project.
PUT <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/results/%resultId%	Updates a result with the specified Result JSON for the resultId in the given decision tree and rule project.
PUT <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/lock	Locks a decision tree so that it can be modified exclusively by the user applying the lock.
PUT <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%/unlock	Unlocks a decision tree so that it can be locked by another user for exclusive modification.

Release 9.10

Added API	Description
GET <base URL>/projects/%ruleProjectName%/decision_trees/%decisionTreeName%	Returns the specified decision tree.
PUT <base URL>/project/%ruleProjectName%/unlockall	Unlock all entities of a rule project and the project itself.

Release 9.9

Added API	Description
GET <base URL>/projects	Returns a list of rule projects that are currently available on My webMethods Server.
GET <base URL>/project/%ruleProjectName%	Returns the content and metadata for a given rule project.

Added API	Description
PUT <base URL>/project/%ruleProjectName%/lock	Locks the given rule project.
PUT <base URL>/project/%ruleProjectName%/unlock	Unlocks the given rule project.
GET <base URL>/project/%ruleProjectName%/decisiontable/%decisionTableName%	Retrieves the given decision table.
PUT <base URL>/project/%ruleProjectName%/decisiontable/%decisionTableName%	Writes the changes for the given decision table to the My webMethods Server.
PUT <base URL>/project/%ruleProjectName%/decisiontable /%decisionTableName%/lock	Locks the given decision table.
PUT <base URL>/project/%ruleProjectName%/decisiontable /%decisionTableName%/unlock	Unlocks the given decision table.
POST <base URL>/project/%ruleProjectName%/deploy	Hot deploys the given rule project to an Integration Server that was configured on the My webMethods Server.
GET <base URL>/project/%ruleProjectName%	Retrieves the given rule project from the My webMethods Server.
PUT <base URL>/project/%ruleProjectName%	Stores the given rule project on the My webMethods Server.
DELETE <base URL>/project/%ruleProjectName%	Deletes the given rule project from the My webMethods Server.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to “License Texts, Copyright Notices and Disclaimers of Third Party Products”. For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under “License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products”. These documents are part of

the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

RULES-RM-103-20181015

CentraSite 10.3 Readme

October 2018

This file contains important information you must read before using CentraSite 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information	2
2.0	Known Issues	2
3.0	Usage Notes	3
4.0	Fixes Included in Each Release	6
5.0	Other Resolved Issues	7
6.0	Documentation Changes	7
7.0	Terminology Changes	9
8.0	Added, Removed, Deprecated, or Changed Items	9
9.0	Copyright Information	22
10.0	Support	22

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- INM-19625
SOAP API configured with “Enable REST support” policy action shows invalid endpoint in API Portal Try-Out page.
When a SOAP API configured with the “Enable REST support” policy action is published to API Portal, one invalid endpoint is added to the list of possible valid endpoints in the API Portal Try-Out page. However, the invalid endpoint has no functionality impact.
There is no workaround for this issue.
- INM-19867
Graphical asset navigator charts are not saved in Internet Explorer.
When CentraSite Business UI is accessed via Internet Explorer, if attempts are made to save the graphical representation of relationships between assets by way of any one of the Asset Navigator charts, for example, TreeChart, SunBurst, Icicle, and GraphChart, CentraSite does not save the graphical chart as an image (.png, .jpg, .bmp or .gif) file.
To work around this issue, right-click on the required chart, and then select the "Save picture as..." option from the context menu.
- INM-16782
Potential conflicts between predefined profiles and user-defined profiles.
In the user interface, the sequence number plays a vital role in the profile display order and the instance level profile permission. In general, the sequence numbers assigned to the predefined profiles and computed profiles are odd numbers and even numbers are assigned to the user-defined profiles. However, some predefined profiles are designated with an even sequence number. When a user creates a new profile, consider the system assigns an even sequence number that matches with one of the predefined profiles. When the user sets the profile-level permissions for the new profile, the same permissions are also assigned to the predefined profile that has the same even sequence number within the asset type. As a result, the user might get permissions to more profiles than intended.
The following list shows some of the predefined profiles that have an even sequence number:
 - Identification
 - Summary
 - Technical Details
 - Default
 - Details
 - Specification

- Support

There is currently no workaround for this issue. However, Software AG strongly recommends that you create a new profile and delete the conflicting user-defined profile within the asset type. Additionally, if the predefined profiles "Runtime Events" and "Runtime Metrics" are missing due to a conflicting sequence number, execute the Java tool named FixProfileSequenceNumber.jar in the command line interface CentraSiteToolbox.cmd (Windows) or CentraSiteToolbox.sh (UNIX) of CentraSite, to fix the sequence number issue.

The syntax is of the format:

```
C:\SoftwareAG\CentraSite\utilities>CentraSiteToolbox.cmd FixProfileSequenceNumber.jar  
<CentraSite URL> <admin user id> <password>
```

Example:

```
C:\SoftwareAG\CentraSite\utilities>CentraSiteToolbox.cmd FixProfileSequenceNumber.jar  
http://localhost:53307 Administrator manage
```

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- The Impact Analysis feature of CentraSite Control which was already deprecated in version 9.9 will not work in Microsoft Edge browser.
- Performance profile of a Virtual Service asset in CentraSite Control will not work in Microsoft Edge browser.
- INM-17284
Unable to renew expired API keys in CentraSite.
In CentraSite, it is not possible to renew an API key that has expired. Therefore, it is necessary to renew the API key before it expires.
To work around this issue, request a new key for consuming the API whose key has expired. You also need to update the applications of that particular API to use the new API key.
- PIE-33367
IS assets cannot be retracted from CentraSite after migrating Integration Server to version 9.7 or later.
After migrating Integration Server to version 9.7 or later, Integration Server cannot retract IS assets that were published to CentraSite by an earlier version of Integration Server.
There is currently no workaround for this issue. If you encounter this situation, contact Software AG Global Support.
- CentraSite and webMethods API Portal Product Compatibility Matrix
The following table provides information about compatibility and coexistence for products, CentraSite and webMethods API Portal:

API Portal / CentraSite	API Portal 9.9	API Portal 9.10	API Portal 9.12	API Portal 10.0	API Portal 10.1	API Portal 10.2	API Portal 10.3
CentraSite 9.8	Supported	Supported	Supported	Supported	Supported	Support ed	Supporte d
CentraSite 9.9	Supported	Supported	Supported	Supported	Supported	Support ed	Supporte d
CentraSite 9.10	Supported	Supported	Supported	Supported	Supported	Support ed	Supporte d
CentraSite 9.12	Supported	Supported	Supported	Supported	Supported	Support ed	Supporte d
CentraSite 10.0	Supported	Supported	Supported	Supported	Supported	Support ed	Supporte d
CentraSite 10.1	Supported	Supported	Supported	Supported	Supported	Support ed	Supporte d
CentraSite 10.2	Supported	Supported	Supported	Supported	Supported	Support ed	Supporte d
CentraSite 10.3	Supported	Supported	Supported	Supported	Supported	Support ed	Supporte d

- API Portal instances must be republished right after upgrading CentraSite to versions 9.9 and later. After upgrading CentraSite and webMethods API Portal to versions 9.9 and later, you must republish all of the API Portal instances that were created in earlier versions of CentraSite before executing publish or unpublish actions on APIs.
- If the machines support ONLY IPv4, *com.softwareag.centrasite.soalink.events.snmp.host* property in <SAG_Root>/CentraSite/cast/cwebapps/SOALinkSNMPEventsListener/WEB-INF/web.xml should point to the hostname of the machine. The default value works fine for dual IP stacks.
- INM-18818
 After upgrading to CentraSite 9.0 SP1 and later from an earlier version of CentraSite, the location of the WSDL and schema files imported in the new CentraSite installation point to a unique folder in WebDAV directory.
 Prior to CentraSite 9.0 SP1, the location of WSDL and schema files was defined by the targetNamespace of the file.
 For example:
 .../ino:dav/ino:dav/projects/WSDL/<Target Namespace in WSDL>/uddi_<key>/<Name of WSDL>.wsdl
 This resulted in long file names and complex relative paths of the imported files in WebDAV.
 To address this issue, the location of newly imported WSDL and schema files is redefined by the unique folder in WebDAV directory.

For example:

```
.../ino:dav/ino:dav/projects/WSDL/uddi_<key>/<Name of WSDL>.wsdl
```

However, the WSDL and schema files imported with previous versions of CentraSite and transferred to CentraSite 9.0 SP1 and later will continue to include the targetNamespace of the file.

- INM-17023

Importing older versions of predefined asset types is no longer allowed.

Importing predefined asset types is no longer possible if the asset type is exported from a CentraSite installation prior to 9.6. For example, a predefined asset type from version 8.2 cannot be imported to CentraSite 9.8.

You can, however, import asset instances of older versions if the predefined asset type definition in the export archive matches with the existing asset type definition in the version 9.8 registry.

- INM-17243

NTLM Transparent Mode with Kerberos Authentication Support.

When a virtual service is configured for NTLM authentication scheme in transparent mode, Mediator behaves in "pass by" mode, allowing an NTLM handshake to occur between the client and server. This kind of NTLM handshake becomes unreliable on certain circumstances.

Mediator now supports Kerberos handshake in Transparent mode. If you choose to use the NTLM Transparent mode with Kerberos authentication, set the value of the `watt.pg.disableNtlmAuthHandler` property to "true" in the extended settings for the Integration Server. For information about the `watt.pg.disableNtlmAuthHandler` property, see *Administering webMethods Mediator* (version 9.8). For more information about working with extended configuration settings, see the *webMethods Integration Server Administrator's Guide*.

- CentraSite does not support overinstall since version 9.7.

CentraSite does not support overinstallation in versions 9.7 and later. This means that there is no overinstallation procedure for CentraSite. Instead, if you are upgrading to CentraSite 9.9 from an earlier version of CentraSite, you must use the side-by-side (SBS) installation. For detailed upgrade instruction, see *Upgrading webMethods and Intelligent Business Operations Products*.

- Upgrade procedure does not update custom SSL client configurations.

If you perform an upgrade from CentraSite version 9.x to versions 9.9 and later, the upgrade does not automatically upgrade your custom SSL configurations for communication between clients and the CentraSite Registry Repository. As a result, some of your existing CentraSite 9.x custom configurations might not be valid for CentraSite versions 9.9 and later.

Therefore, you need to adjust your custom SSL configurations after upgrading to CentraSite versions 9.9 and later. For detailed information about setting SSL configurations, see the *CentraSite Administrator's Guide*.

- CentraSite does not retrieve the runtime policy information of an API published to API Gateway.

Beginning with version 10.1, CentraSite supports publishing of APIs to API Gateway. When an API is published from CentraSite to API Gateway, the policy information for the API is updated in API Gateway. However, CentraSite is unable to retrieve the last policy information from API Gateway when the API is published to API Portal.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.1

- INM_10.1_Fix13

Release 9.12

- INM_9.12_Fix24

Release 9.10

- INM_9.10_Fix22

Release 9.9

- INM_9.9_Fix31

Release 9.8

- INM_9.8_Fix32

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- The chapter “Policy Management” in the CentraSite User’s Guide has been updated to include the new section “Managing Design Time Policies through CentraSite Business UI” which describes how to create and manage design time policies through CentraSite Business UI.

Release 10.2

- The chapter “Lifecycle Management” in the CentraSite User’s Guide has been updated to describe the newly introduced CRUD functionalities on lifecycle models and stages through CentraSite Business UI.

Release 10.1

- The chapter “Type Management” in the CentraSite User’s Guide has been updated to include the newly introduced CRUD functionalities for managing asset types through CentraSite Business UI.
- A new chapter “CentraSite and API Gateway Integration”, which describes how the Virtual Service assets and their associated runtime components defined and published from CentraSite Business UI are mapped into API Gateway, has been added to the CentraSite User’s Guide.

Release 10.0

- Beginning with version 10.0, CentraSite’s old set of documentation is replaced with the following PDF deliverables on the [Documentation website](#):
 - CentraSite Administrator’s Guide: This guide describes the various configurations required for the proper functioning of CentraSite and the administration-level tasks that you can perform in the CentraSite environment.
 - CentraSite User’s Guide: This guide describes how to use CentraSite once it is installed and configured in your environment. It describes various CentraSite features and how these features can be used.

- CentraSite Developer's Guide: This guide describes how you can use programming interfaces to access and modify the CentraSite Registry Repository. Additionally, it describes how you can customize the CentraSite graphical user interfaces to suit the requirements or standards of your organization.

Release 9.12

- The Run-Time Governance with CentraSite Guide contains information on Axis free mediation of REST services.
- The Run-Time Governance with CentraSite Guide contains information on SAML.
- The Working with REST-based APIs Guide contains information on HTTP Patch support.
- The Run-Time Governance Guide and the Working with the CentraSite Business UI Guide contains information on Kerberos support.
- The CentraSite Users Guide contains information on granular permission to Report templates and JDBC support for reports.

Release 9.10

- The CentraSite Business UI Guide includes a new chapter called "OData Service Management". This chapter provides conceptual information on the OData Entity Data Model (EDM), and the procedures for creating and managing OData services using the CentraSite Business UI.
- The chapter "Taxonomies" in the CentraSite Administrator's Guide has been updated to include the enhanced CRUD functionalities for Taxonomies using the CentraSite Business UI.

Release 9.9

- The CentraSite Administrator's Guide includes a new chapter called "Usage of the CentraSite Command Tools". This chapter provides usage information for the various CentraSite Command line utilities.
- The Run-Time Governance with CentraSite guide contains the following new chapters:
 - "Consumer Applications" - This chapter provides information about creating and managing run-consumer applications using CentraSite Control and Business User Interfaces.
 - "Consumer Registrations" - This chapter provides information about providing users and any arbitrary assets the ability to consume other assets in CentraSite.
- The chapter "Working with Reports and Report Templates" in the CentraSite User's Guide has been updated to include the enhanced reporting functionalities of CentraSite Business UI.

Release 9.8

- Software AG documentation is no longer available on the Software AG installer. You can access all Software AG documentation on the [Documentation website](#).
- A new chapter “Importing a RESTful API” has been added to the Working with REST-based APIs guide.
- The chapter “Modelling a RESTful API” has been renamed to “Creating a RESTful API from Scratch” in the Working with REST-based APIs guide.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 9.9

Old Term	New Term
Impact Analysis	Asset Navigator

Release 9.8

Old Term	New Term
Targets	Gateways

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Replacement, if any
Design Time policy Management in Business UI	Beginning with version 10.3, CentraSite Business UI supports the design/change time policy management. You can now use CentraSite Business UI to create and manage design/change time policies in CentraSite.

Release 10.2

Added Item

Lifecycle management in Business UI

Replacement, if any

Beginning with version 10.2, CentraSite Business UI supports the lifecycle management. You can now use CentraSite Business UI to create and manage lifecycle models and stages in CentraSite.

Deprecated Item

CentraSite Control UI (Pluggable UI)

Replacement, if any

CentraSite Control UI is deprecated and will be removed in future releases. Instead, use CentraSite Business UI for managing and integrating the SOA governance processes.

Release 10.1

Added Item

Asset type management in Business UI

Replacement, if any

Beginning with version 10.1, CentraSite Business UI supports asset type management. You can now use CentraSite Business UI to create and manage asset types in CentraSite.

Design time policy actions

CentraSite Command Line Interface (CLI) offers new commands for design-time policy management. You can now use the CentraSite command tools to create and manage design-time policy actions in CentraSite. You can create the design-time policy action skeleton as an Eclipse project, upload, delete, download, and list the available policy actions in CentraSite. You do not need to suspend a policy before making any changes to its action parameters.

Consumers synchronization

CentraSite Business UI supports synchronizing of global consumers with one or more Mediator gateways.

LDAP user synchronization

CentraSite Business UI supports synchronizing of user attributes from an active LDAP directory for the ease of user management. CentraSite introduces a new command tool “sync LDAP Group” to synchronize the group attributes along with its user attributes in LDAP.

Added Item

Introduction to API Gateway asset

Replacement, if any

CentraSite offers a new gateway type “API Gateway” to publish and unpublish APIs from CentraSite to API Gateway.

Deprecated Item

Type management in Control UI

Replacement, if any

Beginning with version 10.1, Type management in CentraSite Control UI is deprecated and will be removed in future releases. Instead, use Asset Type management in CentraSite Business UI to create and manage asset types in CentraSite.

Removed Item

Runtime policy management

Replacement, if any

You cannot manage the runtime policy actions of an API that is published to API Gateway through CentraSite Business UI. Instead, you must manage the API’s policy actions through API Gateway. However, CentraSite introduces a new link “View Runtime Enforcements” to view the runtime policy actions for the API in API gateway for a holistic view.

Release 10.0**Added Item**

API Portal publish enhancement

Replacement, if any

You can now publish the versioned APIs to API Portal. When versioning an API, the access tokens associated to the old version of the API are cloned and associated to the new version of the API. Each cloned access token has its own expiration time within the API. When publishing the old version of the API to API Portal, CentraSite automatically associates and publishes the new version of the API to API Portal.

Reporting enhancements

CentraSite now supports RDBMS as data source for runtime events and metrics. With this feature it is not required that the Mediator events and metrics should be sent to CentraSite to generate reports.

Removed Item	Replacement, if any
Federation	The UDDI-based federation which provides the functionality to federate data between two UDDI v3 compliant registries has been removed from the product. There is no replacement for the UDDI federation.
SSXLoginModule	CentraSite no longer supports the SSXLoginModule. This implies that the CentraSiteCommands related to SSX are no longer supported.

Release 9.12

Added Item	Replacement, if any
HTTP PATCH support	CentraSite supports HTTP PATCH for native and virtualized REST services.
JDBC support	CentraSite reporting framework supports JDBC as one of the data source.
Report template permission	CentraSite supports fine grained permission model for Report templates.

Removed Item	Replacement, if any
XTS support removal	CentraSite used to use XTS for replication. This has been dropped in this release to simplify the deployment. This means customers do not have to open the XTS port in firewall.
53305 port	CentraSite will no longer use the port number 53305 but instead the port number 53307.

Release 9.10

Added Item	Description
Taxonomy management	CentraSite supports creating and managing taxonomies using the CentraSite Business UI. The same is deprecated in CentraSite Control UI.
LDAP validation service	CentraSite now supports validation of the LDAP authentication configuration at each step in the configuration process.
OData support	CentraSite now provides Open Data Protocol (OData) service management. CentraSite Business UI enables the creation of HTTP-based OData services, which allow resources to be identified using Uniform Resource Identifiers (URIs), and the virtualization of OData services. However, an instance of Virtual OData service can be published to the webMethods Mediator gateway only after applying the XB_9.10_Fix1.
New action added to the CentraSite Business UI	This release introduces a new action, “Notify Consumer” that you can use to send ad hoc e-mail notifications to all registered consumers of a particular API.
Enhancements to CentraSiteCommand	CentraSiteCommand line tool has been enhanced to include the following functionalities: 1. The following two CentraSite Commands are introduced to allow access token management using the command line interface: - restore accesstokens - purge accesstokens 2. Report management using the command line interface has been improved to include additional commands for execution of the CRUD operations on reports.
Pluggable actions for CentraSite Business UI	In addition to the preconfigured set of actions, users now have the option to plug-in their own custom action implementations. The custom-created actions allow users to extend the product functionality. The following rendering mechanisms are supported for any custom action: - WithUiRendering - WithoutUiRendering

Added Item	Description
Access token enhancements	<p>The following changes were made to improve the access token management using the CentraSite Business UI:</p> <ul style="list-style-type: none"> - Access token configuration screens have been improved to display a warning message because there is a possibility that changing the configuration of an API could invalidate the user access tokens. This improvisation ultimately offers a better user experience. - The configuration screen for policy actions, for example, Throttling Traffic Optimization, has been simplified to display only the access tokens created for a particular API as the possible list of consumers during the virtualization process. This simplified user interface prevents users from choosing an unknown consumer accidentally. - Previously, when an API is unpublished from webMethods API Portal, access tokens associated with API were deleted from the API Portal registry. Upon republishing, only the API was published to API Portal. Now, republishing the API also publishes the associated access tokens to API Portal.
Swagger enhancements	<p>A new policy action, "Generate Swagger2.0 file", has been introduced to export a REST API or a Virtual REST API in Swagger format. This policy action applies to the following set of events:</p> <ul style="list-style-type: none"> - Post-Create - Post-Update - Post-State Change - OnTrigger
Handling of CentraSite logs	<p>CentraSite logs have been separated from the logging containers and placed inside a dedicated log file called centrasite.log. This log file is available in the <Software AG_directory>/profiles/CTP/configuration directory where wrapper.log is available.</p>

Deprecated Item	Replacement, if any
Taxonomy management in Control	Beginning with version 9.10, CentraSite does not support creating and managing taxonomies using the Control UI. Instead, CentraSite supports creating and managing taxonomies using the CentraSite Business UI.

Release 9.9

Added Item	Description
Pending approval enhancement	Now, an Administrator can override pending approval. This will be very useful if the approval is stuck for various reasons like user unavailability.
OAuth client revocation	CentraSite Business UI supports revocation of OAuth clients.
Support for Insight gateway	Beginning with CentraSite version 9.9, Insight gateway is supported out of the box.
Virtualization enhancements	Beginning with CentraSite version 9.9, a Virtual service can be re-virtualized. This helps users to quickly change the policy actions instead of navigating back to Native service. If the native REST service undergoes any change, say a new Resource is added, re-virtualization from native service allows users to take advantage of the new additions without versioning the virtual service.
Report Scheduling	Users can schedule the Report execution. The report will be sent to the registered e-mail address as an attachment.

Removed Item	Replacement, if any
CentraSite report execution from CentraSite Control and Designer	The execution of reports will no longer be possible neither from CentraSite Control nor from the Designer's 'CentraSite Search and Browse' perspective. This will be possible only from CentraSite Business UI.

Deprecated Item	Replacement, if any
Impact Analysis	For use case except the generic traversal, Asset Navigator is preferred.

Release 9.8

Added Item	Description
New concept "Gateway"	Beginning with CentraSite 9.8, both API Portal and Mediators are grouped under the concept "Gateway".

Added Item	Description
<p>Predefined roles for managing gateways and publishing APIs</p>	<p>This release introduces the following predefined roles:</p> <ul style="list-style-type: none"> - Mediator Administrator - API Portal Administrator - Mediator Publisher - API Portal Publisher <p>To manage a Mediator gateway, you must belong to the "Mediator Administrator" role or have the "Full" instance-level permission on the Mediator instance itself.</p> <p>To manage an API Portal gateway, you must belong to the "API Portal Administrator" role or have the "Full" instance-level permission on the API Portal instance itself.</p> <p>To publish API to a Mediator gateway, you must have the "Mediator Publisher" role for the organization to which the Mediator instance belongs, or have the "Edit" instance-level permission on the Mediator instance itself.</p> <p>To publish API to an API Portal gateway, you must have the "API Portal Publisher" role for the organization to which the API Portal instance belongs, or have the "Edit" instance-level permission on the API Portal instance itself.</p> <p>After migrating CentraSite from previous versions to version 9.8, users who have the "Operations Administrator" role to create Mediator targets in previous versions of CentraSite will automatically get the "Mediator Administrator" role.</p> <p>After migrating CentraSite from previous versions to version 9.8, users who have the "API Portal Administrator" role to manage API Portal instances and publish APIs to the API Portal instances in previous versions of CentraSite will automatically get the "API Portal Publisher" role.</p> <p>For more information about roles, see <i>Getting Started with CentraSite</i>.</p>

Added Item	Description
New Asset Details layout	<p>CentraSite Business UI offers an enhanced profile layout that provides easier access to the details of the individual profiles of APIs and other assets. The enhanced profile layout provides a split view representation of the profile details for an individual object and includes a navigation panel and a content panel. The layout maintains a list of all of the profile names on the navigation panel and displays the details for the selected profile on the content panel. For complete information, see <i>Working with the CentraSite Business UI</i>.</p>
Importing Archived Assets	<p>CentraSite Business UI provides the Import Archive functionality to import an asset by importing the archive file (zip file) to which the asset was previously exported. The Import Archive functionality offers the same import preview and options that are provided by CentraSite Control. For more information about using this functionality, see <i>Working with the CentraSite Business UI</i>.</p>
Importers for RAML and Swagger	<p>In CentraSite 9.8, the existing REST data model interface is enhanced to support direct importing of REST APIs described in the RAML and Swagger API documentation formats. The CentraSite Business UI introduces a new field called “Import from a Specification File” that takes in the specification file of a RAML - version 0.8 or Swagger - version 2.0 format as the input, and then creates a REST Service asset that best describes the REST API with RAML or Swagger specification. For complete information, see <i>Working with REST-based APIs</i>.</p>
Scheduled Report Execution	<p>CentraSite provides default reports that API Portal consumers can use to monitor their API usage over a specific period. You can schedule these reports on a regular basis (daily, weekly, monthly) to automatically generate and distribute reports as an email attachment, in PDF format, to the consumer at the email address provided at registration. The consumer clicks the attachment to access the API usage metrics.</p>
Easy navigation between Native Service and Virtual Service	<p>Beginning with version 9.8, CentraSite Business UI provides a link that enables you to easily navigate from the virtual service details page to the corresponding native service details page in the user interface.</p>

Added Item	Description
Robust access token management between CentraSite and API Portal	<p>CentraSite supports configurable retry mechanism that ensures the delivery of messages from CentraSite to API Portal, and protects requests from transient failures that might occur while sending messages from CentraSite to API Portal. If access tokens are not delivered during the retry attempts, the undelivered tokens are flagged and persisted in the database. At a later time, these undelivered tokens can be viewed using the predefined “GetUndeliveredAccessTokens” portlet, which is introduced in this release. CentraSite uses a scheduler to automatically pick up the undelivered tokens, and resend them to the API Portals. For complete information about this mechanism, see <i>Working with the CentraSite Business UI</i>.</p>
Merged Publish and Unpublish actions for Mediator and API Portal.	<p>Prior to CentraSite 9.8, you publish and unpublish APIs to and from Mediator and API Portal instances, in sequence, using the following four distinct actions:</p> <ul style="list-style-type: none"> - Publish - Publish to API Portal - Unpublish - Unpublish from API Portal <p>In CentraSite 9.8, the above actions are replaced by two actions - Publish and Unpublish, which allow you to publish and unpublish APIs to and from Mediator and API Portal instances, simultaneously. These actions are also introduced in the Search Results page for performing bulk publish and unpublish of APIs. For more information about using these actions, see <i>Run-Time Governance with CentraSite</i>.</p>
CentraSite Control supports IE standard mode	<p>In previous versions, CentraSite Control used Quirks mode to render the content properly. CentraSite Control now supports standard mode in IE 11 and above.</p>

Added Item	Description
Target Management in CentraSite Control	<p>Beginning with version 9.8, CentraSite Control does not support creation of Mediator and Insight targets. This means that there is no option for creating targets using the “Add Target” wizard in CentraSite Control.</p> <p>However, if you have targets created with the previous versions or using the current version of CentraSite Business UI, you will be able to view the list of targets in the Targets page, and deploy services to the targets using the Deployment page. You cannot edit or delete these targets using the CentraSite Control user interface (even if you belong to the CentraSite Administrator role). Going forward, you must use the CentraSite Business UI to create and manage targets (now called gateways). For complete information, see <i>Run-Time Governance with CentraSite</i>.</p>
<p>Policy Actions using Groovy</p> <p>Support for policy actions written in Groovy (a scripting language) is removed. Going forward, CentraSite will cease support for any Groovy action.</p>	None.
<p>The following ESB (Enterprise Service Bus) types that appear in the Type Management page of CentraSite Control are removed.</p> <ul style="list-style-type: none"> ▪ ESB Document ▪ ESB Document Field ▪ ESB Document Type ▪ ESB Folder ▪ ESB Package ▪ ESB Service ▪ ESB Specification ▪ ESB WS Descriptor ▪ ESB WS Operation 	None.

Deprecated Item	Replacement, if any
Legacy Asset Details layout	<p>The legacy asset details layout in CentraSite Business UI has been deprecated. The legacy layout is replaced with an enhanced profile layout which provides a split view representation of the profile details for an asset and includes a navigation panel and a content panel. The layout maintains a list of all of the profile names on the navigation panel and displays the details for the selected profile on the content panel. For complete information, see <i>Working with the CentraSite Business UI</i>.</p>
Run-time functionalities in CentraSite Control	<p>Beginning with CentraSite 9.8, the support for various run-time functionalities which include Virtualization of Services, Definition of Targets, Run-time Policies, Deployment Operations in CentraSite Control is deprecated and will be removed in future releases.</p>

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

CS-RM-103-20181015

Closed Loop Analytics 10.3 Readme

October 2018

This file contains important information you must read before using Closed Loop Analytics 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	2
6.0	Documentation Changes	3
7.0	Terminology Changes	3
8.0	Added, Removed, Deprecated, or Changed Items.....	3
9.0	Copyright Information.....	3
10.0	Support.....	4

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 9.8

- CLA_9.7_Sources_Fix1
- CLA_9.7_Assets_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 9.9

- WOK-8177
Closed Loop Analytics shows a wrong timestamp in an escalation task at noon.
If you trigger a Closed Loop Analytics escalation between 12:00 and 13:00, the Business Data tab for the escalation task shows wrong time values for the fields Time stamp of creation, Start date range and End date range.
This issue has been resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- GDPR information was added.
- Content was rewritten to reflect that Process Dashboards can only be accessed in webMethods Business Console. They cannot be accessed in MashZone NextGen any longer.

Release 9.9

- Product guide “webMethods Closed Loop Analytics Help” was added.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to “License Texts, Copyright Notices and Disclaimers of Third Party Products”. For certain specific third-party license restrictions, please refer to

section E of the Legal Notices available under “License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products”. These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

CLA-RM-103-20181015

webMethods CloudStreams 10.3 Readme

October 2018

This file contains important information you must read before using webMethods CloudStreams 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	4
4.0	Fixes Included in Each Release.....	6
5.0	Other Resolved Issues.....	7
6.0	Documentation Changes	14
7.0	Terminology Changes	14
8.0	Added, Removed, Deprecated, or Changed Items.....	15
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	23
10.0	Copyright Information.....	24
11.0	Support.....	24

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

CloudStreams Server

- WST-3895
When a CloudStreams connection referenced by a CloudStreams connector listener explicitly references a proxy configuration, or when a default proxy configuration is available in Integration Server Administrator > Settings > Proxy Servers, and the configured proxy server throws a Basic Authentication challenge to the CloudStreams connector listener, the listener fails to enable. There is currently no workaround for this issue.

- WST-3910
If a user adds a custom header while updating the subscription details for a connector listener, CloudStreams Server ignores it and does not send it in the request. There is currently no workaround for this issue.

- WST-3917
Errors occur while applying OAuth v1.0a alias configurations from a source system to a target system. Because of the errors, OAuth aliases are not listed on the target system, which includes the newly created OAuth aliases. This is because update to the Access Token Secret of the respective OAuth aliases fails on the target system. There is currently no workaround for this issue.

- WST-3918
When a provider is selected in the Integration Server Administrator, CloudStreams page, the provider label text for the selected provider is not visible. There is currently no workaround for this issue.

- WST-3921
The "Notify Meta Channel Events" configuration option is available for a CloudStreams connector listener with the connection type defined as "Bayeux HTTP Long Polling" in the Integration Server Administrator, irrespective of whether the "Logging Invocation" action is configured. However, meta channel events are logged in the server log only if the "Logging Invocation" action is

configured.

There is currently no workaround for this issue.

- WST-3925

If a connector listener is enabled and the user deletes the actionable service from the Service Development perspective in Software AG Designer, CloudStreams does not notify that the actionable service is not available.

There is currently no workaround for this issue.

- WST-3930

Subscription errors for connector listeners with "Bayeux HTTP Long Polling" connection type do not appear on the CloudStreams Administration page if the subscription has failed and the listener is enabled. The errors may be due to connection related issues, wrong subscriber configurations such as invalid or missing PushTopic name, missing or insufficient access permissions, or exceeding the concurrent user limit for the user or organization.

There is currently no workaround for this issue.

- WST-3963

"Enable Debug" option does not work for CloudStreams Streaming configuration.

Enabling the "Enable Debug" option for the CloudStreams Streaming configuration does not log additional connectivity-related information in the server logs. This is because after upgrading the cometD client library adoption, the "Enable Debug" option can no longer be supported.

There is currently no workaround for this issue.

CloudStreams Development

- WCD-1156

Assignment from services is not removed from the Connector XML file when the service is deleted from a perspective other than CloudStreams Development.

When Rest elements such as Parameters, Headers, Body, and Connection properties have assignments from a service and the service is deleted from a perspective other than CloudStreams Development, the user interface and the Connector XML file still show the assignments.

Workaround: Remove the assignments (*Unassign*) manually.

- WCD-1739

When a connector listener is either enabled or unlocked for edit, the connector listener fields are disabled in the Service Development perspective in Software AG Designer. If multiple Actions are configured, the user is not able to select the Actions to view the details.

There is currently no workaround for this issue.

- WCD-1747
While creating a Schema type abstract object in a SOAP connector, the “Finish” button is not enabled after selecting the service on the “Assign services” page.
There is currently no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

CloudStreams Server

- A CloudStreams REST resource supports only one type of message builder and formatter for all response codes.
- CloudStreams does not support the RPC/encoded style WSDL.
- CloudStreams does not support the RPC/literal style WSDL.
- CloudStreams does not support sharing of Connector Virtual Services, Virtual Services, and Policies across nodes in a clustered setup. These artifacts should be manually deployed to a clustered node on need basis.
- CloudStreams SOAP services support sending an attachment through MTOM as a base64 encoded input. The support to wrap an attachment as a XOPObject type and sending large attachments is not supported.
- For SOAP based connectors, if the WSDL has multiple bindings for a given service, CloudStreams does not support changing multiple URLs dynamically to connect to the service endpoint.
- webMethods Mediator and CloudStreams products are not compatible. The products must be installed on separate webMethods Integration Server instances.
- While enabling a CloudStreams connector listener, if there are connectivity issues such as network and proxy issues while connecting to the streaming API endpoint, the listener automatically goes into retry mode and attempts to connect to the API endpoint until the configured connection timeout is exhausted. The connector listener inherits the timeouts (Connection Timeout and Socket Read Timeout) from the connector connection. In case the timeout is set to a large value, the update to the connector listener “enabled” status takes quite a while to reflect in the Integration Server Administrator. This may convey an impression to the user that nothing is happening. To confirm the processing, the user should check the server logs with “Streaming” logging component configured to *Debug* or above, or alternatively reduce the timeout values to speed up the “enabled” status update for the connector listener.
- When a user disables a CloudStreams connector listener, a disconnect call is sent to the streaming provider. However, in the server logs, a META_CONNECT event is observed soon after the

META_DISCONNECT event. This is because when a disconnect is sent to the streaming provider, the provider server also wakes up the long poll that may be outstanding, and replies with a connect message that may reach the client after the disconnect reply message. This is expected behavior.

- CloudStreams connector listeners do not have any exclusive support in a clustered setup. The listener behaves in the same way as it behaves in a stand-alone Integration Server setup.

CloudStreams Development

- CloudStreams Provider projects developed using the older plug-in, that is, v9.12 and earlier, cannot be migrated or upgraded to the v10.2 plug-in. You must create new projects.
- While creating a connector, if the connector ID contains dots (.), nested or hierarchical folders will be created. For example, if the connector ID is a.b.c.d.e.f.g, nested folders will be created named as a, b, c, d, e, f, and g. It is recommended to have as less dots as possible in the connector ID in order to have a smaller hierarchical structure in the Package Navigator view in the Service Development perspective.
- While creating a connector using a Swagger file, authentication schemes are not parsed. You must add the authentication schemes after creating the connector.
- You will not be able to delete a provider package if it is published. You must first *unpublish* the provider package and then delete it.
- You will not be able to update the Resource Group reference if a provider package is published. You must first *unpublish* the provider package and then update the Resource Group reference.
- GET, PUT, POST, DELETE, and PATCH are the only methods supported while creating a REST resource. If you are creating a connector using a Swagger file, any other method available in the Swagger file will not be supported.
- In order to view the newly added assets, you must refresh the package from the Package Navigator view in the Service Development perspective.
- In order to import a Provider folder, if the Provider package is created on a different server, you must have access rights on that server.
- In order to import a published Provider package, *nsName* must follow the following namespace convention: <connector_id>.<service_name>. If this convention is not followed, the Provider package can still be imported, but a few functionalities might not work after import.
- Assignment from services is not removed from the Connector XML file when the service is deleted from a perspective other than CloudStreams Development. When Rest elements such as Parameters, Headers, Body, and Connection properties have assignments from a service and the service is deleted from a perspective other than CloudStreams Development, the user interface and the Connector XML file still show the assignments. These assignments will have to be removed (*Unassign*) manually.

- Adding or deleting a user will not reflect automatically on the “Run As User” list for a “Service Invocation” configuration on the “Event” tab of an already open listener node. The listener node must be closed and reopened to reflect the updated user list. Additionally, if the “Service Invocation” action has been configured to be applied on the incoming events and the configured “Run As User” user has been deleted, then the “Run As User” value has to be manually reconfigured.

4.0 Fixes Included in Each Release

This section lists the *latest fix level* that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

CloudStreams Server

Release 10.3

- WST_10.2_Fix2
- WST_10.1_Fix8
- WST_9.12_Fix6

Release 10.2

- WST_10.1_Fix4
- WST_9.12_Fix5
- WST_9.10_Fix11
- WST_9.9_Fix6

Release 10.1

- WST_9.12_Fix3

Release 9.12

- WST_9.10_Fix4

Release 9.10

- WST_9.9_Fix2

Release 9.9

- WST_9.8_Fix2

Release 9.8

- WST_9.7_Fix1

CloudStreams Development

Release 10.3

- WCD_10.2_Fix1
- WCD_10.1_Fix2
- WCD_9.12_Fix2
- WCD_9.10_Fix4

Release 10.2

- WCD_10.1_Fix1

Release 9.12

- WCD_9.10_Fix2

Release 9.8

- WCD_9.7_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

CloudStreams Server

Release 10.3

- WST-3634
Migration of CloudStreams user assets to v10.2 is not supported.
The *pub.cloudstreams.migration:migrate* service does not migrate user assets to v10.2. The following error is observed when this service is run on CloudStreams v10.2 with a package containing assets created on an older version:
"No CloudStreams migrator found for the package."
There is currently no workaround for this issue.
- WST-3646
"SignatureDoesNotMatch" error appears while running an Amazon S3 cloud connector service.
This error appears if the cloud connector service involves redirection and is created using AWS

Signature Version 3.

There is currently no workaround for this issue.

- WST-3869
CloudStreams is not able to handle the parenthesis in query parameters and the request call fails. CloudStreams Server is not able to encode the URI containing the parenthesis and due to this, requests are failing.
This issue is resolved.
- WST-3884
Cloud connector service execution fails while sending a JSON payload, which contains German characters. This is observed for back ends that use AWS Signature Version 4 for authentication.
This issue is resolved.

Release 10.2

- WST-3269
Multiple errors are observed while executing cloud connector services concurrently. For some SaaS back ends, errors such as “Read timed out” and “Premature end of Content” are observed while invoking cloud connector services at the same time. This issue is found in the Apache HTTP library, which is currently used in CloudStreams.
This issue is resolved.
- WST-3241
Null JSON response is not supported by CloudStreams server.
If a REST service returns Null as a JSON response, CloudStreams does not recognize or parse the Null JSON response.
This issue is resolved.
- WST-3344
CloudStreams Analytics dashboard does not display all the event records for a given date and time. In the CloudStreams Analytics dashboard, the grid in the Event tab does not show all the records for a given date and time. This is because MashZone NextGen considers date columns as dimension columns, as far as aggregation is concerned.
This issue is resolved.
- WST-3352
Provider charts in the API Usage tab of the CloudStreams Analytics dashboard also display data for inbound invocations.
The provider charts should display data corresponding to the outbound (cloud connector service) invocations only. However, the charts also display data for inbound invocations, with the provider names being displayed as blank values.
This issue is resolved.
- WST-3350

Cloud connector services, which allow multiple operations/objects selection, do not persist duplicate operations/objects in the cloud connector service node.

From v10.1, the CloudStreams server allows one resource/operation that can take/return multiple operations/objects in the request or response. For example, in the OData connector, you can select an operation as *changeset*, which allows you to select multiple operations/objects. For the *changeset* operation, if you select a combination of “create” and “Account” multiple times, even then it does not get stored in the cloud connector service node.

This issue is resolved.

- WST-2819

CloudStreams fails to parse a response when the response formatter/builder is configured as “binary”, and the request Accept header is set to “application/json”.

When the response formatter/builder for a cloud connector service is configured to “binary”, and the Accept header is configured to “application/json”, CloudStreams fails to parse the resulting back end response.

This issue is resolved.

Release 10.1

- WST-3213

Issue while adding a custom field as document.

Cloud connector service allows adding a custom field of type Document. When a custom field data type Document is added to a business object, and the field does not have any child fields, the field appears as a string in the cloud connector service signature.

This issue is resolved.

- WST-3165

CloudStreams fails to encode single quotes (') inside a querystring parameter.

This issue occurs when you invoke back end queries that have single quotes, to quantify certain entity values as part of the filtering criteria, and the criteria is a part of the query string parameter. For example, a query that returns details of an account object for a certain id match is as follows: *Select id from account where id = '84'*. This issue prevents encoding the single quote ('), resulting in service execution failure.

This issue is resolved.

- WST-3165

CloudStreams fails to encode single quotes (') inside a querystring parameter.

This issue occurs when you invoke back end queries that have single quotes, to quantify certain entity values as part of the filtering criteria, and the criteria is a part of the query string parameter. For example, a query that returns details of an account object for a certain id match is as follows: *Select id from account where id = '84'*. This issue prevents encoding the single quote ('), resulting in service execution failure.

This issue is resolved.

- WST-3195

CloudStreams does not throw a fault in case of a stream response, if the cloud connector service

execution fails with client side fault issues.

CloudStreams does not throw a fault in case of a stream response if the cloud connector service execution fails with client side fault issues. Instead of fault, the service execution returns a response with a null body.

This issue is resolved.

- WST-3192

Error occurred while enabling the connection.

While enabling the connection, the following errors are found:

Error occurred while enabling the connection: null and Connections alias already exist.

This issue is resolved.

- WST-2907

Some of the alert messages shown in the CloudStreams Admin screens are not localized.

The connectors enable, disable, and delete alert messages are not localized. The alert message shown while enabling the wire logging is also not localized.

This issue is resolved.

Release 9.12

- WST-3149

CloudStreams connector uses the default proxy server alias of Integration Server even if the default proxy server alias is disabled.

Now CloudStreams does not use the default proxy server alias if it is disabled in Integration Server and skips the proxy route for a connection, if the host name of the connection Provider URL is present in the Integration Server "Proxy Bypass" list.

This issue is resolved.

Release 9.10

- WST-2378

CloudStreams does not support creating cloud connector services that have an array of JSON objects without the key/root in the request payload.

In the absence of a parent root for the collection, it is not possible to represent the objects under the request payload. Because of this limitation, it is not possible to create or invoke services, which expect a root less array in the request payload.

This issue is resolved.

- WST-2644

Cloud connector services, which require mapping of parameters, fail to run.

For a REST based connector, a parameter value cannot be assigned to another parameter by specifying a parameter to parameter mapping. This is because CloudStreams does not support parameter to parameter mapping.

This issue is resolved. Parameter to parameter mapping is now supported.

- WST-2638

CloudStreams is unable to handle excludeRoot properties in Request signature using XML.

For a REST based connector that communicates in XML, if the “excludeRoot” option is set to “true”, then while sending a Request to the back end, CloudStreams is not able to exclude the root of the Request.

This issue is resolved.

- WST-2639
Cloud Connector service signature does not populate the picklist values.
Cloud Connector service signature does not populate the picklist values even if the schema element has enumeration defined.
This issue is resolved. Now cloud connector service signature field's picklist attributes are populated with enumerated values available from the schema.

Release 9.9

- WST-2555
Authentication failure when Twitter resources expect messages to be sent as a query parameter. Some Twitter resources expect messages to be sent as a query parameter. While using such resources, if the messages sent contain a space, authentication failure is observed.
This issue is resolved.
- WST-2524
User is not able to see service references or dependents for CloudStreams artifacts.
While checking dependents or references for CloudStreams assets using Software AG Designer, the user is not able to see the service references or dependents.
This issue is resolved.

Release 9.8

- WST-2126
Connections after given timeouts are not automatically refreshed using OAuth refresh tokens. If OAuth refresh tokens are provided and session management is turned on, CloudStreams connections are not refreshing the access tokens automatically using the provided refresh tokens. This functionality may work with only the Salesforce provider and without using any proxies in the connection.
Workaround: Manually update the access tokens with the latest valid access tokens.
- WST-2142
Virtual service deployment errors are reported by CloudStreams Server at startup, when a cluster is enabled.
In a clustered environment, at server startup, when a CloudStreams Server node joins a cluster, for each virtual service deployed on that node, if there is a corresponding entry in the shared virtual services cache, the CloudStreams Server node attempts to undeploy the existing deployed service, and thereafter attempts to redeploy the same service using the shared cache data for that service entry. Undeploy and subsequent redeploy of the connector virtual service fails with errors reported in the server logs.
Extract of the error for the default SOAP connector virtual service WmCloudStreams.SoapVS:
[CLS.0050.0212E] Unknown exception deploying virtual service: WmCloudStreams.SoapVS Cause: 0

[CLS.0050.0048E] Error getting endpoints for service:WmCloudStreams.SoapVS, Cause: Unknown exception deploying virtual service: WmCloudStreams.SoapVS Cause: 0
[CLS.0030.0356E] VirtualServiceDeployer - unable to get endpoints for WmCloudStreams.SoapVS, caught this: type (com.softwareag.pg.exceptions.PGException), msg (Error getting endpoints for service:WmCloudStreams.SoapVS, Cause: Unknown exception deploying virtual service: WmCloudStreams.SoapVS Cause: 0)
[CLS.0030.0363W] VirtualServiceDeployer.redployUndeployedIfNecessary - service (WmCloudStreams.SoapVS) caught this: type (com.softwareag.pg.exceptions.DeploymentException) message (VirtualServiceDeployer - unable to get endpoints for WmCloudStreams.SoapVS, caught this: type (com.softwareag.pg.exceptions.PGException), msg (Error getting endpoints for service:WmCloudStreams.SoapVS, Cause: Unknown exception deploying virtual service: WmCloudStreams.SoapVS Cause: 0))

This error is benign. Syncing up virtual service from shared cache is not supported in CloudStreams, so the sync up action performed by the node is redundant.

CloudStreams Development

Release 10.3

- WCD-1593
Multiple connectors having same IDs and located in different servers cannot be opened.
This issue is resolved.

Release 10.2

- WCD-1318
Server name changes when a new entry (user) is added to the Integration Server list.
In Preferences > Integration Servers, adding a new Integration Server with a different user but with the same host name and port shows only one Integration Server.
This issue is resolved.
- WCD-1341
Errors observed while creating a connector, if the connector name has spaces.
This issue is resolved.
- WCD-1348
Validation errors are observed while creating a connector from a Swagger file.
While creating a connector using a Swagger file, validation errors are observed in certain cases where the name/id of a connector, resource name, parameter name, header name, and property name contains characters, which are not supported, for example, spaces or special characters in the name.
This issue is resolved.

Release 9.9

- WCD-716
For a cloud connector service, fields that have the *recordList* parameter populated, do not show up as documents.
While creating a cloud connector service, once an operation and object are selected, the next screen shows a list of fields. While choosing a field, if the field has the *recordList* parameter populated, it should show up as a Document. Currently these fields show up as String fields.
This issue is resolved.
- WCD-724
Errors that are related to creating or editing a Cloud Connector Service are not displayed in a dialog box.
While creating or editing a Cloud Connector Service, if there is any error, the error is logged only in the error logs and not displayed in a dialog box. As a result, the user is not informed about the problem.
This issue is resolved. The error information now appears in a dialog box.

Release 9.8

- WCD-612
Older connectors do not appear in the Integration Server Administration page even after a successful deployment from Designer.
The following errors are observed in the Integration Server error log:
*com.wm.app.b2b.server.ServiceException: java.io.FileNotFoundException:
C:\SoftwareAG\profiles\IS_default\workspace\temp\tempDocTypeDir\sqs.xsd (The system cannot find the file specified)
Caused by: com.wm.app.b2b.server.ServiceException: java.io.FileNotFoundException:
C:\SoftwareAG\profiles\IS_default\workspace\temp\tempDocTypeDir\sqs.xsd (The system cannot find the file specified)
Caused by: java.io.FileNotFoundException:
C:\SoftwareAG\profiles\IS_default\workspace\temp\tempDocTypeDir\sqs.xsd (The system cannot find the file specified).*
This issue is resolved.

6.0 Documentation Changes

This section describes *significant* changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

CloudStreams Server

Release 9.9

- The *webMethods CloudStreams FAQ and Troubleshooting* guide available at <http://documentation.softwareag.com/> provides FAQs and troubleshooting tips.

Release 9.8

- Software AG documentation is now no longer available on the Software AG installer from this release. You can access all Software AG documentation on the [Documentation website](#).

CloudStreams Development

Release 10.1

- The CloudStreams Provider Project chapter in the context-sensitive webMethods CloudStreams Development Help has been completely rewritten.

Release 9.8

- Software AG documentation is no longer available on the Software AG installer. You can now access all Software AG documentation on the [Documentation website](#).

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

CloudStreams Development

Release 10.2

Old Term	New Term
Login/Logout Sequence	Start/Stop Sequence
CFG Parameter	Internal

Release 9.8

Old Term	New Term
Group	Provider Group
Connector Package	Package
Plug-In Content	Connector Content

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

CloudStreams Server

Release 10.3

Added Item	Description
Support for streaming at the connector level	You can now use a CloudStreams connector to connect to streaming APIs. You can create a CloudStreams connector listener, select a subscription channel from a list of available channels for an endpoint, and configure the action(s) to be applied on the incoming events.
Support for dynamic/inline connection	You can now run a cloud connector service by passing connection details that are different than the connection details configured in the connection configuration page in webMethods Integration Server Administrator. The cloud connector service input signature is automatically updated based on your selections in the <i>Connection</i> panel.
Support for multipart/form-data request payload	You can now send a multipart/form-data payload which contains either a file, or text, or a document type to a service provider. The multipart/form-data payload is supported only at the request level, that is, only in the input signature.

Added Item	Description
Support for dynamic configurations with Microservices	<p>CloudStreams now allows you to use a configuration variables template to externalize the configuration information and pass the configuration information to the Microservices Runtime at startup. By externalizing configuration information, a single Docker image created for a Microservices Runtime can be used across multiple environments, including different stages of the production cycle.</p> <p>The configuration variables template contains configuration properties that map to properties on the Microservices Runtime. The property values can be set externally in the template and then passed to the Microservices Runtime when it starts up. As part of the startup process, Microservices Runtime loads the information from the configuration variables template and replaces the configuration information stored in the file system.</p>
Deployer support for large payload handling configurations and listeners	<p>Deployer now supports deploying large payload handling configurations and connector level listeners.</p>

Changed Item	Description
CloudStreams User Interface	<p>Selecting a connector from a provider connector list under Integration Server Administrator > CloudStreams, now opens up a tabbed page display. The page defaults to the Connections tab which lists the connections configured for the selected connector. The newly introduced <i>Listener</i> tab displays the listeners configured for the selected listener.</p> <p>Additionally, the CloudStreams Administration pages in Integration Server Administrator now use a primary blue colour scheme, which is optimized for accessibility and for brightness.</p>

Release 10.2

Added Item	Description
Changes in connection configuration fields	<p>The following new connection fields are added:</p> <ul style="list-style-type: none">• Validate After Inactivity• Enable Compression <p>The following connection fields are updated:</p> <ul style="list-style-type: none">• Hostname verifier*• Use Stale Checking** <p>The following connection fields are deleted:</p> <ul style="list-style-type: none">• Element Character Set• Wait For Continue Time• Strict Transfer Encoding <p>*The Hostname verifier field exposes the following closed set of updated options:</p> <ul style="list-style-type: none">• org.apache.http.conn.ssl.DefaultHostnameVerifier• org.apache.http.conn.ssl.NoopHostnameVerifier <p>**The default value of <i>Use Stale Checking</i> has been set to <i>true</i>.</p>
Support for large data configuration	<p>Large data configuration enables CloudStreams to send and receive large binary streams over HTTP/HTTPS. If the new option <i>Handle Binary Streams</i> is enabled, then during outbound and inbound invocations, if the stream is greater than the <i>Threshold Size (bytes)</i>, the entire stream is not stored in memory. Threshold Size (bytes) is applicable only if <i>Handle Binary Streams</i> is enabled. Before enabling the large data handling capability of CloudStreams, configure the TSpace properties (watt.server.tspace.*) in the webMethods Integration Server Administrator.</p>
MTOM	<p>You can now transmit and receive binary content from SaaS providers in an optimized and efficient way using the Message Transmission Optimization Mechanism (MTOM).</p>
Enhanced Concurrency Support	<p>CloudStreams server now handles concurrent executions of cloud connector services in a more efficient way. This improves how parallel requests are handled without running into concurrency issues.</p>
Enhanced server redirection capabilities	<p>CloudStreams server now supports redirection capabilities with other HTTP methods like PUT and DELETE too. This allows interacting with back ends like AWS S3 for redirected data transfers across different regions and geographies.</p>

Release 10.1

Added Item	Description
Support for form encoded parameter	You can now send simple key value parameters embedded in the Request Body for POST or PUT requests. This uses the default web form encoding, which is <i>application/x-www-form-urlencoded</i> .
Support for CloudStreams Analytics dashboard on MashZone NextGen instead of the legacy MashZone	You can now use the CloudStreams Analytics dashboard with Software AG Mashzone NextGen Server.
Support for deploying CloudStreams user-created assets using webMethods Deployer	You can now deploy CloudStreams user-created assets such as connections, connector services, and administrative assets or configurations such as oauth token, streaming provider, streaming subscriber and database settings that reside on source webMethods repositories to target webMethods runtime components (runtimes) using webMethods Deployer. You can deploy CloudStreams user-created assets in repository-based deployment only.
Support for Single or Multiple Operations and Multiple Business Objects with dependencies	Software AG Designer now displays different Business Object panels based on the following scenarios: <ul style="list-style-type: none">• Single Operation has a single Business Object• Single Operation has multiple Business Objects• Single Operation has multiple Business Objects with dependencies• Multiple Operations have multiple Business Objects• Multiple Operations have multiple Business Objects with dependencies
Support for nested, hierarchical, or multi-level business objects	Software AG Designer now displays nested, hierarchical, or multi-level business objects if the resource is designed to support nested business objects. You can expand the nested business objects to display the child-level objects.
Support for NTLM basic authentication	CloudStreams now supports NT LAN Manager (NTLM) authentication protocol. CloudStreams provides basic support for NTLM authentication protocol using the credentials connection group. Limited support is available in this release.

Added Item	Description
Support for service signatures for back ends having very complex nested document structures	You can now create service signatures for back ends with extremely complex and deep signature structures.
Support for adding nested custom fields in the cloud connector service business object fields.	You can now add complex nested custom fields while selecting a cloud connector service business object field. This is useful for SaaS back ends where the metadata is dynamic, for example, Amazon DynamoDB.

Release 9.12

Added Item	Description
Support for Transport Layer Security (TLS) 1.1 and 1.2	CloudStreams now supports the latest versions of TLS standard v1.1 and v1.2. Using Java Secure Socket Extension (JSSE) based libraries, CloudStreams supports TLS v1.1 and v1.2 for outbound connections.
Wire logging message	If you now enable the Connection factory wire logging option from the CloudStreams > Administration > General screen in the Integration Server Administrator, a warning message appears. The message informs the side effects of turning on this setting.

Changed Item	Description
Regrouping between <i>Basic</i> and <i>Advanced</i> views and reordering of fields within the <i>Credentials</i> , <i>Transport Protocol</i> , and <i>Request Headers</i> connection groups.	<p>Authentication Type field is now moved ahead of the Preemptive Auth field so that fields in the Basic view stay ahead of the fields visible in the Advanced view for the Credentials connection group.</p> <p>Element Character Set and Strict Transfer Encoding fields are moved to the Advanced view for the Transport Protocol connection group.</p> <p>Request Header Names and Request Header Values fields are moved to the Advanced view for the Request Headers connection group.</p>

Release 9.10

Deprecated Item

Software AG MashZone based CloudStreams Analytics dashboard.

Replacement, if any

The Software AG MashZone based CloudStreams Analytics dashboard is deprecated from this release.

Changed Item

CloudStreams User Interface

Description

The HTML-based utility used to administer webMethods CloudStreams has a new look and feel. Menu and screen locations have not changed and there is no change in the User Interface functionality.

CloudStreams Development

Release 10.3

Added Item

Support for assignments on Cookies and Service Context

Description

You can now apply assignments on Cookies and Service Context.

Support for applying assignments at the Resource Group level

You can now apply assignments at the *Resource Group* level, which enables you to apply assignments to each resource and operation in the selected Resource Group. Further, assignments are applied in the sequence they appear in the *Configure Assignment* panel.

Release 10.2

Added Item

Change the sequence of assignments

Description

You can now change the sequence of both local and global assignments. The assignments will be applied in the sequence they appear in the *Order* pane.

Support for Start and Stop sequences

You can now define optional Start and Stop sequences, which allow you to manage the connection behavior for both REST-based and SOAP-based providers. Start and Stop sequence is currently in BETA.

Added Item	Description
Support for moving and copying elements	You can now cut, copy, and paste request parameters, request headers, and response headers for REST-based connectors. For SOAP-based connectors, only request parameters can be currently moved or copied.
Enhanced provider package import process	Import process has been enhanced and allows you to import a provider package as an archive file or import the package from a workspace. Importing published packages is currently in BETA.
Refresh providers and connectors	Refresh button has now been added for enhanced usability to sync assets between the plugin and server for providers and connectors.
Support for Record type Parameter Formatter	You can now add record type parameter formatters. A new parameter style <i>Record (as Query)</i> has been added, which is a complex record structure representation, split into one or more query string parameters.

Release 10.1

Added Item	Description
Redesigned connector development plug-in	In this release, the <i>CloudStreams Provider Project</i> in the CloudStreams connector development plug-in has been redesigned and enhanced for better usability. Note: SOAP connector development is in BETA.

Deprecated Item	Replacement, if any
Old connector development plug-in	New connector development plug-in.

Release 9.12

Changed Item	Description
Icons updated to reflect changes in corporate branding.	Icons are updated in Perspectives, Views, Welcome screen, and About contributions.

Release 9.10

Removed Item

Redundant fields in REST service interface

Replacement, if any

Serialization type fields are removed from the Cloud Connector Service (REST) > Resource tab > **Request Processing** section.

Parsing type fields are removed from the Cloud Connector Service (REST) > Resource tab > **Response Processing** section.

Release 9.9

Added Item

Publisher

An optional field "Publisher" is added for the CloudStreams Provider and CloudStreams Governance projects to obtain the publisher name.

Description

An optional field "Description" is added for the CloudStreams Provider and CloudStreams Governance projects to obtain the description.

Release 9.8

Added Item

Display Name

Description

Added an optional field "Display Name" for Services, Operations, and Resources. This value is used for displaying the name of the item (Service, Operation, or Resource) in a connector.

New Group Dialog

Added the "New Group" dialog for a connection group selection which shows all available connection groups.

Copy

Added the "Copy" menu item in the CloudStreams Connector view to copy the CloudStreams Provider Project into the system clipboard.

Paste

Added the "Paste" menu item in the CloudStreams Connector view to paste the CloudStreams Provider Project from the system clipboard.

Hide

Added an optional field "Hide" for Operations for the SOAP Connector development. The CloudStreams Server will hide the operations during the Cloud Connector Service creation/selection.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

CloudStreams Server

Release 10.3

Added Service	Description
pub.cloudstreams.admin.listener:enable	Enables an existing listener.
pub.cloudstreams.admin.listener:disable	Disables an existing listener. Also, disconnects the listener.
pub.cloudstreams.admin.listener:queryListenerState	Returns the current listener state (enabled/disabled) for a listener node.
pub.cloudstreams.admin.listener:listEnabledListeners	Returns a list of aliases for listeners in enabled state for a given connection alias.
pub.cloudstreams.admin.listener:update	Updates a CloudStreams connector listener node with a new set of inputs.

Release 9.9

Added Service	Description
pub.cloudstreams.admin.service:batchupdate	The <i>batchUpdate</i> service complements the update service by allowing batches of CloudStreams connector service nodes to be updated in one operation. You can use the batchUpdate service to update multiple CloudStreams connector service nodes from a lower version of the connector API to a higher version.

Changed Service	Description
pub.cloudstreams.admin.service:update	This service allows you to update a CloudStreams connector service node from one version of connector API to a higher version for various attributes such as the <i>Connection Alias</i> and the <i>Virtual Service Name</i> . The changes in this service are two new input parameters, <i>simulate</i> and <i>force</i> .

10.0 Copyright Information

Copyright © 2013-2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

WCD-WST-RM-103-20181015

Software AG Command Central 10.3 and Software AG Platform Manager 10.3 Readme

October 2018

This file contains important information you must read before using Software AG Command Central 10.3 and Software AG Platform Manager 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information	1
2.0	Known Issues	2
3.0	Usage Notes	4
4.0	Fixes Included in Each Release	5
5.0	Other Resolved Issues	7
6.0	Documentation Changes	8
7.0	Terminology Changes	12
8.0	Added, Removed, Deprecated, or Changed Items	13
9.0	Added, Removed, Deprecated, or Changed APIs	31
10.0	Copyright Information	34
11.0	Support	34

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

The following issues are resolved in Command Central 10.3 Fix 1:

- CCE-4279
When configuring LDAP in Command Central, saving the configuration fails with the "Provided configuration is not valid" message. The issue occurs even when the specified data is correct, because the data used for validation does not include the real login credentials of the end user. The issue is resolved. To save the LDAP configuration, you can disable LDAP validation by setting the following system property in Platform Manager:
`com.softwareag.platform.management.configuration.spi.CommonLDAPConfigurationValidator.skipValidation=true`
- CCE-4287
When you execute a CLI command with the "--expected-values" option and use the "," or "!" operators, the command does not return the correct expected values as follows:
 - does not list in the response all values specified with the "," operator
 - ignores the "!" operator.The issue is resolved.
- CCE-4405
On Windows, if you do not run the .exe under a user account with system administrator privileges, the console window will close automatically and you will not be able to see output describing success or errors, nor will you be able to see -help output.
- CCE-4458
Saving proxy settings in Command Central fails with the following error message: "The requested functionality is not supported." The message does not explain that the issue occurs because a shared secret should be set for multiple environments. The issue is resolved. Now the error message states that a shared secret is not configured.
- CCE-4473
Installing fixes for Optimize using the Command Central web user interface fails with an internal server error immediately after the installing fixes job has started. The issue occurs because when loading fixes from the repository, Command Central does not filter the fixes by installed products. The issue is resolved. Now when Command Central loads the fixes from the fix repository, it filters the fixes by installed products and the installing fixes job completes successfully.
- CCE-4497
Snapshot metering report IDs do not contain a zero in front of single-digit date and time values. This issue is resolved. A zero is now added in front of single-digit date and time values in snapshot report IDs.

- CCE-4504
In the Stacks > Jobs view in the Command Central web user interface, the text of the job description and start time might overlap.
The issue is resolved.
- CCE-4507
Some fixes, for example fixes provided for Software AG Update Manager, cannot be uninstalled. If you attempt to uninstall such fixes using Command Central, you get an error message with the following explanation:
"The fixes, provided for uninstallation are not found on the target installation."
The explanation does not specify the names of the fixes that cannot be uninstalled.
The issue is resolved. Now the explanation of the error message is:
"The following fixes provided for uninstallation are not uninstalleable: {fixName}"
- CCE-4549
When you update the license key for a product instance or create a new product instance, Command Central lists all valid license keys for the product instance, including some license keys that have a different major version.
The issue is resolved. The Command Central web user interface now lists the license keys only for the product major version you are updating.
- SPM-4499
When configuring ports in Command Central, the port validation fails when two port configuration instances have the same port number, but different bind addresses.
The issue is resolved. Now you can configure two port configuration instances with the same port number and different bind addresses.
- SPM-4699
In Command Central, when you attempt to create a fix mirror repository and filter by multiple product repositories for different operating systems, the create mirror repository job fails.
The issue is resolved.
- SPM-4701
Using credentials that contain special encoding characters in Command Central fails with an internal server error.
The issue is resolved. Command Central now supports all UTF-8 characters.
- SPM-4707
Error message text is missing from the Platform Manager wrapper.log.
The Platform Manager wrapper.log does not display the message text for the error messages with the following message IDs:
SPMTEME0031
SPMTEME0019
The issue is resolved. The error message text is now displayed in the log.
- SPM-4718
When collecting data for the run-time components, Platform Manager can now distinguish

correctly between default IDs and component-specific IDs.

- SPM-4720
When parameterizing configurations for the cloud deployment scenario, Command Central assigns null values to parameters with no configuration data.
The issue is resolved. Parameters with no configuration data are not parameterized by Command Central.
- SPM-4743
In Command Central, adding an existing installation takes a long time, because the Command Central landscape service is slow to respond.
The issue is resolved.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

Command Central and Platform Manager

- Installing assets and creating stacks are preview features that have limited functions and are:
 - Not intended for use in a production environment
 - Subject to change in the future without deprecation announcements

If you want to provide feedback on both preview features, go to the Command Central area in the Software AG TechCommunity.

- See the “Software AG Command Central Feature Support Matrix” on the documentation website for details about which Command Central functions are supported for each product release.
- You cannot create mirror repositories for the following operating systems:
 - LNX Linux RHEL and SLES x86
 - HP11 HP HP-UX PA-RISC
 - LNXS390X Linux RHEL and SLES IBM System z
 - AS400 IBM AS/400
 - WNT Microsoft Windows x86

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Command Central

Release 10.2

- CCE_10.2_Core_Fix4
- CCE_10.2_WebUI_Fix4
- CCE_10.2_SPMplugin_Fix4
- CCE_10.2_CLI_Fix4

Release 10.1

- CCE_10.1_Core_Fix12
- CCE_10.1_CCCommon_Fix12
- CCE_10.1_WebUI_Fix12
- CCE_10.1_SPMplugin_Fix12
- CCE_10.1_CLI_Fix12

Release 10.0

- CCE_10.0_Core_Fix6
- CCE_10.0_CCCommon_Fix6
- CCE_10.0_WebUI_Fix6
- CCE_10.0_SPMplugin_Fix6
- CCE_10.0_CLI_Fix6

Release 9.12

- CCE_9.12_Core_Fix18
- CCE_9.12_CCCommon_Fix18
- CCE_9.12_WebUI_Fix18

- CCE_9.12_SPMplugin_Fix18
- CCE_9.12_CLI_Fix18

Release 9.10

- CCE_9.10_Core_Fix9
- CCE_9.10_CCCommon_Fix9
- CCE_9.10_WebUI_Fix9
- CCE_9.10_SPMplugin_Fix9
- CCE_9.10_CLI_Fix9

Release 9.9

- CCE_9.9_Core_Fix11
- CCE_9.9_CCCommon_Fix11
- CCE_9.9_WebUI_Fix11
- CCE_9.9_SPMplugin_Fix11
- CCE_9.9_CLI_Fix11

Release 9.8

- CCE_9.8_Core_Fix15
- CCE_9.8_CCCommon_Fix15
- CCE_9.8_WebUI_Fix15
- CCE_9.8_SPMplugin_Fix15
- CCE_9.8_CLI_Fix15

Platform Manager

Release 10.2

- SPM_10.2_Core_Fix4
- SPM_10.2_SPMCommon_Fix4

Release 10.1

- SPM_10.1_Core_Fix12
- SPM_10.1_SPMCommon_Fix12

Release 10.0

- SPM_10.0_Core_Fix6
- SPM_10.0_SPMCommon_Fix6

Release 9.12

- SPM_9.12_Core_Fix18
- SPM_9.12_SPMCommon_Fix18

Release 9.10

- SPM_9.10_Core_Fix9
- SPM_9.10_SPMCommon_Fix9

Release 9.9

- SPM_9.9_Core_Fix11
- SPM_9.9_SPMCommon_Fix11

Release 9.8

- SPM_9.8_Core_Fix15
- SPM_9.8_SPMCommon_Fix15

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Command Central and Platform Manager

Release 9.9

- SPM-2472
When Command Central and Platform Manager connect to the Empower website to download

products and fixes via a proxy server, in Command Central you configure the proxy server details for the Platform Manger component that connects to Empower. However, some of the Command Central functions disregard the Command Central proxy configuration. The following list describes the functions that do not take into account the proxy configuration completely or support only specific proxy configuration:

- When creating bootstrap installer images, Command Central uses the OSGI-SPM proxy configuration of the installation with alias "local" and supports only HTTP, HTTPS, and SOCKS proxy configuration.
- When applying templates on a target installation to install products or fixes, Command Central uses the OSGI-SPM proxy configuration of the target installation and supports only HTTP, HTTPS, and SOCKS proxy configuration.
- When using the Command Central command line interface commands to list the content of fixes on the Empower website, Command Central does not use the proxy configuration details.
- When using the Command Central command line interface provisioning commands to install fixes on a target installation from the Empower website, Command Central does not use the proxy configuration.

The issue is resolved.

Release 9.8

- CCE-1417

When bootstrapping the complete distribution of Platform Manager, Command Central is also installed.

The complete distribution of Platform Manager includes Platform Manager, Update Manager, the Command Central command line interface, and all Platform Manager plug-ins. However, when bootstrapping the complete distribution, Command Central is also installed.

The issue is resolved.

- CCE-1429

When using Command Central to apply the "um-layer" composite template for a cluster environment, the template does not create product instances.

The issue is resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Command Central and Platform Manager

Release 10.3

For information about Command Central composite assets, see:

- *Designer Service Development Help* and *Deploying to webMethods Integration Cloud* about details how to generate and deploy Command Central assets to webMethods Integration Cloud

- *Software AG Command Central Help* and *webMethods Deployer User's Guide* about details how to generate, export, and build Command Central composite assets to deploy on Software AG run-time components running on premise.

Release 10.2

Administering Software AG Products using Command Central is a new web help that includes details about performing administration and configuration tasks in Command Central specific to a product.

Software AG Command Central Help is now updated with information about how to delete Command Central and Platform Manager logs in compliance with the General Data Protection Regulation (GDPR).

Release 10.1

Software AG Command Central Help includes new topics about:

- “Working with Software Stacks” and “Stacks and Layers Commands”
- “Using Micro Templates”
- “Template Definition DSL Reference” (includes the DSL reference template and micro-template reference)
- “Provisioning Assets Commands” and “Repository Commands” (includes the asset repositories commands)

Release 9.12

The *Software AG Command Central Help* has been re-organized as follows:

- The “Getting Started with Command Central” topic contains the information that helps you understand, install, and upgrade Command Central.
- All topics related to tasks that you can do from the Command Central web user interface to manage your landscape are streamlined and much of the information has been moved to the web user interface, where it appears in the form of instructions and tooltips.
- The “Automation and Template-based Provisioning” topic includes all topics about using and developing composite templates.
- The “Command Central Developer Reference” topic includes reference details about the Command Central CLI and REST API.

All product-specific topics about administering product plug-ins for Platform Manager have been relocated to the product administration guides. For example, the administering Integration Server plug-in topics are now included in the Integration Server administration guide.

The *Getting Started with Command Central REST API* is no longer published as a separate PDF guide.

The Software AG Command Central Feature Support Matrix is a separate document that includes a feature support matrix for Command Central and all product plug-ins.

Release 9.10

- The “Installing Command Central Using Bootstrap Installer” topic includes information about new custom options when running bootstrap installer and a section on migrating an existing Command Central installation using bootstrap installer.
- The “Provisioning Environments” topic includes sections that describe how to use composite templates to update or migrate product environments.
- The “Managing Database Components Using Command Central” is a new topic that describes how to create or migrate database schemas as part of provisioning or migration through a composite template.
- In the “Repository Management” topic, updated the sections about mirror repositories with information how to create, refresh, and update fix mirror repositories.
- The following product plug-ins for Platform Manager have added new sections:
 - Apama (“Administering Apama”)
 - Integration Server, My webMethods, and Universal Messaging (new sections about migrating product instances using the Command Central command line interface)
 - Universal Messaging (“JNDI Management”)

Release 9.9

- Command Central and Platform Manager now have one release readme, named “Software AG Command Central and Software AG Platform Manager Readme”.
- Added a new topic about “Bootstrapping a Command Central Installation”. To access the topic from the Command Central online help, you must install Command Central 9.9 Fix 1.
- Added the “Installing and Uninstalling Fixes” topic.
- Updated the “Managing Users, Groups, and Roles” topic with LDAP-related changes.
- In the “Repository Management” topic, added a new section about creating, refreshing, and updating mirror repositories.
- Updated the “Managing Product License Reports” section to include information about aggregate monthly reports.
- In the “Java Service Wrapper” topic, added the “Configuring Java System Properties” section.
- Updated the provisioning topics with information about provisioning enhancements, such as

viewing the status of a composite template apply job and bootstrapping Platform Manager over the OpenSSH service.

- Updated the monitoring topics with information about monitoring enhancements, for example consistent status reporting for run-time components.
- Added the “Using Command Central to Publish Events” section that replaces the section about using NERV.
- Removed the “Cloud Factory Services Overview” topic from the Command Central Help.
- The following product plug-ins for Platform Manager have added new sections:
 - Universal Messaging (“Universal Messaging Properties Configuration”)
 - EntireX Broker (“Administering webMethods EntireX Broker”)
 - Event Routing (“Administering Event Routing”)
 - Optimize (“Administering Optimize Analytic Engine”)

Release 9.8

- Following are major content changes in Software AG Command Central Help (online and PDF format):
 - In the “Template-based Provisioning” topic, added a new section about “Provisioning Environments”.
 - In the “Template Commands” topic, added information about the new composite template commands.
 - Updated the “Setting Outbound Authentication” and “Security Credentials” topics with information about using trusted authentication.
 - Added the “Working with Configurations that Include Passwords” topic to describe how to use shared secret password.
 - Added details about the syntax and usage of the product provisioning (in “Provisioning Products and Fixes Commands”) and list repositories commands (in “Repositories Commands”).
 - Added details about “Managing License Manifests” and using the license manifest commands.
 - Added the “Using Command Central to Manage Landscapes with Lower Versions” section.

- In the “Universal Messaging Server Instance Management” section, added the following new parameters and relevant examples how to manage Universal Messaging Instances using the Universal Messaging instance management commands:
 - NumEnterpriseManager
 - NumTemplateApplications
 - instance.DataDir
- In the *Software AG Command Central Help* PDF guide, added:
 - The “Administering Terracotta” section.
 - A new appendix that lists the Command Central functions and types of configuration supported for different product versions. The appendix contains a reference section for each product that has a Platform Manager plug-in.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Command Central

Release 10.3

Old Term	New Term
License manifest report	Snapshot report
License key report	Snapshot report by license key

Release 10.2

Old Term	New Term
n/a	Indexed node alias

Release 10.1

Old Term	New Term
n/a	Stack
n/a	Micro template

Release 9.8

Old Term	New Term
n/a	Composite Template
n/a	Layer

Old Term	New Term
Template	Snapshot Template

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Command Central

Release 10.3

Added Item	Description
Command Central composite assets	<p>Command Central exports configuration properties for Software AG run-time components as YAML templates.</p> <p>You can generate composite assets from YAML templates using:</p> <ul style="list-style-type: none"> ▪ Designer (to deploy to Integration Cloud) ▪ Asset Build Environment ▪ <pre>sagcc get templates composite export templateAlias {--output -o} filename.zip [{--output-format -f} application/vnd.sagcc.asset+zip]</pre> <p>You can store the Command Central composite assets in a local or remote Landscape Asset Repository (LAR) and deploy them on Software AG run-time components running on premise, or on webMethods Integration Cloud.</p>
<pre>sagcc exec templates composite generate</pre>	Generates run-time component configurations as a template YAML file.
<pre>sagcc exec templates composite generate input</pre>	Generates run-time component configurations as a template YAML file, based on an input template metadata file.
<pre>application/vnd.sagcc.asset+zip</pre>	Content type for Command Central composite assets.
<pre>application/yaml</pre>	Content type for YAML files.

Added Item	Description
sagcc exec repository mirror validateContent	Validates the integrity of a mirror repository against the source repository.
com.softwareag.platform.management.client.fix.mirror.platform.validation=false	Disable validating whether a source fix repository (from which you want to create a mirror repository) includes all of the platforms in the product repository you select as a filter.
com.softwareag.platform.management.client.template.composite.skip.restart.for=<componentID>	Indicates whether to bypass the restart of a specific run-time component at the end of the composite template application.
Fixes to include	In Repositories > Fixes > Create Mirror Repository, use the Fixes to include option to select whether to include only the Latest fixes or All fixes in the fix mirror repository.
Command Central default templates library	A library of templates for products that you can install and manage with Command Central, including all supported product configurations. The library is located at https://github.com/SoftwareAG/sagdevops-templates
Provide monitoring data in Prometheus metrics format	Command Central exposes run-time monitoring metrics, which can be consumed by Prometheus when managed containers are deployed in K8S environment.

Changed Item	Description
sagcc get templates composite export	<p>Use the command with:</p> <ul style="list-style-type: none"> ▪ the <code>-f application/yaml</code> option to export a template into a YAML file. ▪ the <code>-f application/vnd.sagcc.asset+zip</code> option to export a template as a Command Central composite asset zip file.
Create a fix mirror repository for a single operating system	Command Central can create a mirror repository with fixes for a single operating system, based on the platform in the product repository you select as a filter.
Command Central bootstrap installer for Windows	The Command Central bootstrap installer for Windows is now an .exe file.

Changed Item	Description
Jobs view	Streamlined the Jobs view in the Stacks area of the Command Central web user interface
<code>[artifacts= fixName1[_version], fixName2[_version] FixId1, FixId2]</code>	In the <code>artifacts</code> argument of the <code>sagcc exec provisioning fixes install</code> command, you can specify either the fix names, or the Empower fix IDs.
<code>fixes: [fix1_v1, ProductCode_10.3_Fix2] ALL</code>	In the <code>fixes:</code> section of a template, you can list either the fix names, or the Empower fix IDs.
<code>sagcc add license-tools manifests</code>	A license manifest file that you add with this command can contain embedded license keys that you register in Command Central when you add the license manifest.
<code>sagcc list license-tools keys</code>	The command returns a list of all license keys registered in Command Central, including license keys added individually and license keys added with a license manifest file.
<code>sagcc delete license-tools keys</code>	You cannot delete license keys embedded in a license manifest with this command. To delete license keys registered in Command Central with a license manifest file, you must delete the license manifest file using the <code>sagcc delete license-tools manifests</code> command.
<code>sagcc get license-tools reports aggregated [usage meteringonly] <reportId></code>	The command now generates different representations of the aggregated license report.

Release 10.2

Added Item	Description
Command Central Docker Builder	An official Docker image of Command Central on Docker Store: https://store.docker.com/images/software-commandcentral
SSL to connect to master repositories (Empower)	Command Central now uses SSL to connect to master repositories (Empower), managed by Command Central 10.2 and hosted on Platform Manager 10.2, when downloading products and fixes to install in an environment.

Added Item	Description
General Data Protection Regulation (GDPR) compliance	Included information in the Command Central Help about how to delete Command Central and Platform Manager logs.
Support for new parameters for cross-host product migration	<ul style="list-style-type: none"> - Enabled products to identify the old hostnames to be replaced with the new host names during migration. - Enabled renaming a product instance during migration (for products supporting instance renaming).
dslVersion: 1.1	A new parameter in the composite template declaration to indicate the DSL version.
<pre>nodes: <envType>: aliasMapping: policy: INDEX prefix: \${node.alias.prefix}</pre>	With DSL 1.1, a new <code>aliasMapping:policy</code> section to enable the mapping of node alias to hosts. When <code>policy: INDEX</code> , the <code>prefix</code> parameter specifies a custom prefix to include in the indexed node alias.
<pre>provision: <envType>: infrastructure: hosts: [host1, host2, host3]</pre>	With DSL 1.1, when <code>aliasMapping:policy: INDEX</code> , the first layer in each <code>provisioning:envType</code> section is defined as an infrastructure layer that includes the <code>hosts</code> parameter.
<pre>aliases: [my_node_3,my_node_4] indexes: [3,4]</pre>	With DSL 1.1, when <code>policy: INDEX</code> , each of the layers in <code>provision</code> (except the infrastructure layer) includes the <code>aliases</code> (list of indexed node aliases) or <code>indexes</code> (list of index numbers) parameters.
Reference parameters for node aliases	You can refer to a node alias from an inline template in the <code>templates</code> section using one of the parameters listed in the reference parameters for node aliases table in “Templates” in the Command Central Help.

Added Item	Description
<pre>patches: [patchKey1, patchKey2]</pre>	<p>With DSL 1.1, a new section in <code>templates</code>, in which you specify a list of support patches that you want to install on top of installed fixes.</p>
<pre>"target/licenseKey": "*_<productCode>_<majorVersion>.*_<os.platform>"</pre>	<p>The <code>"target/licenseKey": "\${alias}"</code> parameter in the <code>templates:<templateAlias>:licenses</code> section of the composite template supports using wildcard characters when specifying the license key alias.</p>
<pre>{--sync-job -j}</pre>	<p>A new CLI command option to monitor and report progress details while a job is running, and return the job status and status description after the job completes.</p>
<pre>{--retry -y}[count]</pre>	<p>A new CLI command option to specify the number of times to resubmit the command when Command Central gets restarted during an operation and does not respond within the time interval specified in the <code>--wait-for-cc</code> option.</p>
<pre>{--wait-for-cc -t} [seconds]</pre>	<p>A new CLI option to set the time interval for which the command waits for Command Central to come online after starting or restarting Command Central.</p>

Changed Item	Description
<p>DSL version 1.1</p>	<p>The new version of the DSL has been enhanced with new sections and parameters. See the “Added Items” table for details.</p>

Changed Item	Description
templates:fixes:	<p>With DSL 1.1 the following changes apply for the templates:fixes section of the composite templates:</p> <ul style="list-style-type: none"> You cannot list support patches in fixes: fixes:ALL installs all fixes applicable for products in the inline template and their dependencies.
sagcc list license tools keys	<p>Added the following parameters:</p> <pre>[release=releaseNumber] [aliasFilter=filter] [excludeExpired=true false] [nodeAlias=nodealias]</pre>

Release 10.1

Added Item	Description
Stacks web user interface and CLI commands	You can now create product layers and build a product stack out of those layers to provision new environments.
Micro templates	<p>The layers in a product stack are created based on the properties defined in a micro template, which is referenced in the layer definition you select for the layer.</p> <p>You can find sample micro templates at https://github.com/SoftwareAG/sagdevops-templates</p>
Asset repositories	Flatfile and git asset repositories that you register in Command Central to install assets.
Asset provisioning commands	CLI commands that you use to install/uninstall product assets.
Composite template validation	Composite templates are validated as a first step in the apply composite template operation or using the CLI validate composite templates command.
COMMON-JAAS-REALMS	A new configuration type to use for JAAS realms authentication.

Added Item	Description
CCE-LAYER-TYPES	A new configuration type for layer definitions.
COMMON-JSW	A new configuration type to use for configuring Java Service Wrapper settings.
Disconnected migration	You can now use disconnected migration (migrate from a source archive) with a composite template.
Exporting product configuration as template snippets	With the Command Central web user interface, you can export product configurations from existing installations as template snippets.
Jobs view	New Jobs view in the Command Central web user interface (with a tree structure for the jobs)
Encrypted proxy authentication for Command Central and Platform Manager	
Automated migration of custom certificates and their configuration for SSO and HTTPS ports.	
Importing license keys from a license key archive (zip file).	

Changed Item	Description														
Base and Peak Report	Changed to “Product Usage Report for Billing”. A new metering type, “Total usage”, has been added to the license metering. The “Product Usage Report for Billing” contains both “Base and Peak” and “Total usage” licenses.														
Download aggregated report menu items in the Command Central web user interface	<table border="1"> <thead> <tr> <th>Old menu item</th> <th>New menu item</th> </tr> </thead> <tbody> <tr> <td>PDF</td> <td>License Inventory PDF</td> </tr> <tr> <td>XML</td> <td>License Inventory XML</td> </tr> <tr> <td>JSON</td> <td>License Inventory JSON</td> </tr> <tr> <td>Base&Peak PDF</td> <td>Product Usage PDF</td> </tr> <tr> <td>Base&Peak XML</td> <td>Product Usage XML</td> </tr> <tr> <td>Base&Peak JSON</td> <td>Product Usage JSON</td> </tr> </tbody> </table>	Old menu item	New menu item	PDF	License Inventory PDF	XML	License Inventory XML	JSON	License Inventory JSON	Base&Peak PDF	Product Usage PDF	Base&Peak XML	Product Usage XML	Base&Peak JSON	Product Usage JSON
Old menu item	New menu item														
PDF	License Inventory PDF														
XML	License Inventory XML														
JSON	License Inventory JSON														
Base&Peak PDF	Product Usage PDF														
Base&Peak XML	Product Usage XML														
Base&Peak JSON	Product Usage JSON														

Deprecated Item in template definition	Replacement, if any
In nodes/default/default/bootstrapInfo: repo.spm: repositoryName platform: platformCode userName: password:	installer: bootstrapInstallerFileName installer: bootstrapInstallerFileName credentials: credentialsAlias
In repositories/fix and repositories/product: userName: password:	credentials: credentialsAlias

Removed Item	Description
Default composite templates	The default composite templates are now removed from the product and available here: https://github.com/SoftwareAG/sagdevops-9.x-template-samples
Snapshot templates	Removed from the product.

Release 10.0

Added Item	Description
Fix ID column in the fix repository details page in the Command Central web user interface	
List of the details available in a specified license manifest	You can use the Command Central web user interface and CLI commands to list details about license manifests, such as type, name, version, and status.
Correlation ID in the logs	You can use the number of the Correlation ID as a search filter when tracing an operation in the Command Central and Platform Manager logs.
“patterns” and “except” parameters	With the two new optional parameters, added in the migration/options/backup/excludes section of the composite template definition, you can select which file types to exclude from the source archive in a more granular way. Also, now the default value of the "excludes" parameter under migration/backup is "*.log".

Added Item	Description
Fix Repository ID	<ul style="list-style-type: none"> You can use the fix repository ID to select a repository in the instance creation wizard in the Command Central web user interface. When creating instances of Integration Server and My webMethods Server with the “sagcc create instances” command, you can use the <code>fixRepository=repo_ID</code> argument to ensure that all required fixes are applied on all product instances. When applying a composite template, the template now automatically re-applies fixes after a product instance is created.
<code>\${environment.mode}</code>	Added migration settings that you can define for a product instance in the composite template definition.
<code>\${migration.type}</code>	
<code>\${src.node.host}</code>	
COMMON-CREDENTIALS	A new configuration type to add and store the user credentials for a specific alias.
<code>sagcc list repository products languages</code>	Lists language packs available for the products in the repository.
Changed Item	Description
LDAP configuration	Added validation of the LDAP configuration settings in the Command Central web user interface.
<code>sagcc update repository</code>	Each type of product or fix repository (master, mirror, and image) now has a separate syntax for the update repository command. For details, see the Command Central Help.
Removed Item	Description
System Properties	On the Configuration tab in the web user interface, the System Properties configuration is replaced by Java System Properties.
<code>sagcc exec repository register</code>	

Release 9.12

Added Item	Description
Cross-site-request forgery prevention	Protected the Command Central web user interface against cross-site-request forgery attacks.
Web user interface instance creation wizard	Creates, updates, or deletes instances of Integration Server, My webMethods, Universal Messaging, and Apama for installations of release 9.12.
Instructions and tooltips	The wizards and screens of the Command Central web user interface have been enhanced with new instructions and tooltips.
Web user interface product installation wizard	<p data-bbox="812 682 1393 791">Installs products of release 9.8 or higher. You must consider the following when using this wizard:</p> <ul data-bbox="812 827 1463 1640" style="list-style-type: none"><li data-bbox="812 827 1463 936">▪ Use mirror or master repositories. The product installation wizard does not support image repositories.<li data-bbox="812 972 1463 1281">▪ For installations of release 9.10 or higher, installing a Platform Manager product plug-in automatically restarts Platform Manager to activate the plug-in. For earlier releases, Platform Manager is not restarted automatically and you should use the ALL distribution (which includes all product plug-ins) or restart Platform Manager manually.<li data-bbox="812 1316 1430 1425">▪ Checking for dependencies is not supported for older releases, which is indicated by a warning.<li data-bbox="812 1461 1425 1528">▪ Installing language packs is supported only for installations of release 9.12.<li data-bbox="812 1564 1365 1640">▪ Use the Software AG Installer to install products of release 9.7 and earlier.
sagcc get templates composite export	Exports an existing composite template into a zip archive.

Changed Item	Description
Command Central bootstrap installer	Added support for the HP-UX and IBM AIX operating systems.
Logs	The Command Central logs are now reduced in number and made easier to read and understand.
Product and fix repository wizards	Streamlined and enhanced repository wizards to support browsing and searching the repositories.
Template-based provisioning enhancements	Enabled migration of existing environments to a different host, using a live or cloned database.
Command Central REST API	<ul style="list-style-type: none"> ▪ Improved performance and memory usage. ▪ A single WADL document for the Command Central REST API services. The document is located at <a href="http(s)://<ccehost>:<cceport>/cce/application.wadl">http(s)://<ccehost>:<cceport>/cce/application.wadl

Removed Item	Description
Create/apply snapshot templates wizards in the Command Central web user interface	Use composite templates to provision existing installations with version 9.8 or higher.
Event Routing	Removed Event Routing from the Command Central bootstrap installer.

Release 9.10

Added Item	Description
dbc	A new default composite template that installs the Database Component Configurator (DBC) on a local or remote installation and uses DBC to create a new database on a supported database server.
Configuration types	The COMMON-JVM-OPTIONS configuration type to configure extended options for JVM.
Command Central bootstrap installer	<ul style="list-style-type: none"> - New custom options for the Command Central bootstrap installer: -D and -H - Migrating an existing Command Central installation
CLI administration commands	Commands that perform custom administrative tasks for managed products.

Added Item	Description
Fix mirror repositories	Creating and updating fix mirror repositories, using the Command Central web user interface and CLI repository commands.
License keys	Adding and managing product license keys.
Login page and logout link	The Command Central web user interface now uses form-based login page and has a logout link.
Template-based provisioning enhancements	<p>The following enhancements were added in the composite templates:</p> <ul style="list-style-type: none"> - use composite templates to migrate existing environments - customize migration options by adding an optional “migration” section in a composite template definition - define shell actions that a composite template executes at different points in the apply composite template operation
“environment.mode” parameter	Added in the “cc exec templates composite apply” command to specify whether the composite template will provision or migrate the environment.
Migrate products using composite templates and the Command Central CLI	<ul style="list-style-type: none"> ▪ Migrate Integration Server, My webMethods Server, and Universal Messaging using composite templates and the CLI composite template commands. ▪ Migrate Integration Server, My webMethods Server, and Universal Messaging instances using the CLI administration commands.
Universal Messaging JNDI management	Configure Universal Messaging connection factories and destinations in a JNDI namespace using the Command Central web user interface or command line interface.
Deprecated Item	Replacement, if any
COMMON-MEMORY	Deprecated for configuring extended options for JVM. Use COMMON-JVM-OPTIONS.

Deprecated Item	Replacement, if any
Snapshot templates create and apply web user interface and CLI commands	Use composite templates to provision existing environments with version 9.8 or higher
Emitting XML-based events using Event Routing	

Release 9.9

Added Item	Description
generic-layer	Added a new default composite template to provision multiple nodes using an external snapshot template, which is created from an existing installation using Command Central.
Configuration types	Added the COMMON-LDAP configuration type.
Fix installation web user interface	Installing and unstalling fixes and support patches remotely.
LDAP configuration properties	Configuring LDAP properties for Command Central and the products managed by Command Central. You configure LDAP properties using the Command Central web user interface and command line tool.
Mirror repositories	Creating and updating mirror repositories, using the Command Central web user interface and repository commands that you run in the Command Central command line tool.
Aggregate license reports	Generate aggregate monthly reports of the Command Central landscape, showing installed instances on an hourly/daily basis.
Java system properties configuration	Configure the Java system properties of managed products, such as My webMethods Server (including Task Engine), Integration Server, and Command Central using the COMMON-SYSPROPS configuration type for product instances.

Added Item	Description
Template-based provisioning enhancements	<p>The following enhancements were added in the composite templates:</p> <ul style="list-style-type: none"> - Reference to external snapshot templates that the composite template applies for a given layer - Using the <code>\${node.host}</code> and <code>\${node.alias}</code> variables inside inline templates to create dynamic content that is host/alias specific - Reference to Java system properties in the <code>template.yaml</code> definition - Updating existing product instances when a composite template is re-applied - Combining an input properties files with additional parameters when running the <code>apply composite template</code> command - Specifying the path to the target installation directory in UNIX format that works for both UNIX and Windows hosts - Applying composite templates layer by layer - Returning WARNING status when a sub-job in a composite template apply job fails
Consistent status reporting	<p>Reporting the status of run-time components after a lifecycle operation consistently in Command Central. The status on the summary and details screens is the same status reported by the run-time component.</p>
Command Central bootstrap installer	<p>Installing Command Central using a single executable installer package, downloaded from Empower.</p>
Support for the OpenSSH service on Windows	<p>Bootstrapping Platform Manager remotely over the OpenSSH service.</p>
Creating or editing a JDBC connection pool for Integration Server using Command Central	<p>The Available Connections Warning Threshold and Waiting Thread Threshold Count properties can be set when creating or editing a JDBC connection pool through Command Central.</p>

Added Item	Description
Universal Messaging properties configuration	Configuring a Universal Messaging server instance by editing the configuration parameters using the Command Central web user interface or command line interface.

Changed Item	Description
cc get monitoring state	The command now supports additional arguments.

Deprecated Item	Replacement, if any
cc get monitoring	cc get monitoring state

Release 9.8

Added Item	Description
bpms	Default composite template. Provisions a typical BPMS environment.
is-layer	Default composite template. Provisions a standalone local or remote Integration Server, or an Integration Server cluster with multiple hosts.
mws-layer	Default composite template. Provision a standalone local or remote My webMethods Server, or a My webMethods Server cluster with multiple hosts.
reference	Default composite template. Contains DSL documentation and reference details.
repos	Default composite template. Contains the public master product and fix repositories version 9.5 or higher.
spm-layer	Default composite template. Bootstraps a single local or remote Platform Manager, or a number of remote Platform Managers on UNIX hosts via an SSH connection.
tc-layer	Default composite template. Provisions a standalone local or remote Terracotta Server or a two-server master/slave cluster on remote machines.

Added Item	Description
um-layer	Default composite template. Provisions a standalone Universal Messaging realm instance or a two-instance cluster on local or remote machines.
Composite template commands	Command Central command line interface commands that you use to import and apply composite templates.
Product provisioning commands	Command Central command line interface commands that you use to install and uninstall products.
Filtering product repository content	Command Central command line interface commands that you use to search and filter the contents of a product repository.
Trusted authentication	Added trusted authentication mode when administering run-time components in OSGI profiles with version 9.8.
Shared secret	Shared secret that Platform Manager uses when retrieving or updating run-time component configuration settings that contain passwords.
License reports based on license manifests	Creating and managing license reports for an installation, based on license manifest files.
Platform Manager plug-ins	<p>Added Platform Manager plug-ins for the following run-time components:</p> <ul style="list-style-type: none"> ▪ Terracotta ▪ Task Engine on My webMethods Server and WmTask Client ▪ Event Routing ▪ My webMethods user interface for Optimize

Platform Manager

Release 10.3

Added Item	Description
Platform Manager plug-ins	<ul style="list-style-type: none">▪ Zementis Integrated Server▪ Dynamic Business Orchestrator▪ Task Engine on Integration Server▪ AgileApps Server
Pull deployment from asset repositories	Platform Manager can be configured to listen and pull assets when changes are detected in an asset repository, and then deploys the assets automatically on product instances.
Processing and applying YAML composite templates	Platform Manager can pull Command Central assets (YAML template files with product configurations) from an asset repository and deploy the templates on product instances running in containers on Integration Cloud.
Provide monitoring data in Prometheus metrics format	Platform Manager exposes run-time monitoring metrics, which can be consumed by Prometheus when managed containers are deployed in K8S environment.
syscap UNIX shell script	Collects system information that you use when troubleshooting issues.

Release 10.2

Added Item	Description
Platform Manager plug-ins	<ul style="list-style-type: none">▪ Microservices Runtime▪ MashZone NextGen Event Service (RTBS)

Release 10.0

Added Item	Description
Logs	The Platform Manager logs are now reduced in number and made easier to read and understand.

Added Item	Description
Correlation ID in the logs	You can use the number of the correlation ID as a search filter when tracing an operation in the Command Central and Platform Manager logs.

Deprecated Item	Replacement, if any
COMMON-SYSPROPS	COMMON-JAVASYSPROPS

Release 9.12

Added Item	Description
Platform Manager plug-ins	<ul style="list-style-type: none"> ▪ Platform Manager plug-in for ActiveTransfer ▪ Platform Manager plug-in for PPM

Release 9.10

Added Item	Description
Platform Manager plug-ins	Platform Manager plug-in for Apama.
Configuration types	The COMMON-JVM-OPTIONS configuration type to configure extended options for JVM.
CLI administration commands	Commands that perform custom administrative tasks for managed products.

Deprecated Item	Replacement, if any
COMMON-MEMORY	Deprecated for configuring extended options for JVM. Use COMMON-JVM-OPTIONS.

Release 9.9

Added Item	Description
Platform Manager plug-ins	<p>Added Platform Manager plug-ins for the following run-time components:</p> <ul style="list-style-type: none"> - EntireX Broker - Optimize Analytic Engine

Changed Item	Description
cc get monitoring state	The command now supports additional arguments.
cc list monitoring alerts	The command now supports additional arguments.

Deprecated Item	Replacement, if any
cc get monitoring	cc get monitoring state

Release 9.8

Added Item	Description
Shared secret	Shared secret that Platform Manager uses when retrieving or updating run-time component configuration settings that contain passwords.
Platform Manager plug-ins	<p>Added Platform Manager plug-ins for the following run-time components:</p> <ul style="list-style-type: none"> ▪ Terracotta ▪ Task Engine and WmTask Client ▪ Event Routing ▪ My webMethods user interface for Optimize

9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Command Central

Release 10.3

Changed API	Description
	<ul style="list-style-type: none">▪ Enhanced the following services:<ul style="list-style-type: none">▪ Repository▪ Monitoring▪ Template▪ License Tools

Release 10.2

Changed API	Description
Command Central REST API	With DSL 1.1, enhanced the Template service with new sections.

Release 10.1

Changed API	Description
Command Central REST API	<ul style="list-style-type: none">▪ Added the Stacks service that you use to create stacks and layers.▪ Enhanced the following services:<ul style="list-style-type: none">▪ Repository (added assets repositories)▪ Provisioning (added install/uninstall assets)▪ Template (added validate a template)▪ License Tools (enhanced base and peak license inventory and report commands)

Release 10.0

Changed API	Description
Command Central REST API	Refactoring of the Repository service

Release 9.9

Changed API	Description
Command Central REST API	<ul style="list-style-type: none">▪ Enhanced the following services:<ul style="list-style-type: none">▪ Repository▪ Provisioning▪ Monitoring▪ License Tools

Release 9.8

Changed API	Description
Command Central REST API	<ul style="list-style-type: none">▪ Added the Template Composite service that you use to manage composite templates of environments.▪ Added the Template Snapshot service that you use to manage snapshot templates of installations.

Platform Manager

Release 10.3

Changed API	Description
Platform Manager REST API	Enhanced the following services: <ul style="list-style-type: none">▪ Monitoring▪ Repository

Release 9.9

Changed API	Description
Platform Manager REST API	Enhanced the Monitoring service

10.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

CC-PM-RM-103-20181015

webMethods Composite Application Development 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Composite Application Development 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	4
6.0	Documentation Changes	5
7.0	Terminology Changes	6
8.0	Added, Removed, Deprecated, or Changed Items.....	6
9.0	Added, Removed, Deprecated, or Changed APIs	9
10.0	Copyright Information.....	104
11.0	Support.....	104

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- WMC-4485
When Composite Application Framework (CAF) is installed, the initial startup of Software AG Designer might take longer than usual.
There is currently no workaround for this issue.
- WMC-4486
When Composite Application Framework is installed, other Software AG Designer development plug-ins might report unresolved bundles. This issue does not affect the plug-in functionality.
There is currently no workaround for this issue.
- MWS-21070
When using an IS Document type to define the business data for a HPSTRA-enabled task, the Composite Application Framework might duplicate business data fields in the runtime.
There is currently no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- DES_10.1_CAD_Fix2

Release 10.2

- DES_10.1_CAD_Fix1
- DES_10.0_CAD_Fix3
- DES_9.12_CAD_Fix3

Release 10.1

- DES_10.0_CAD_Fix2

Release 10.0

- DES_9.12_Fix1
- DES_9.9_CAD_Fix2
- DES_9.8_CAD_Fix3
- DES_9.7_Fix3

Release 9.12

- DES_9.10_Fix2
- DES_9.9_CAD_Fix1
- DES_9.8_CAD_Fix2
- DES_9.6_CAD_Fix5
- DES_9.5_SP1_CAD_Fix2

Release 9.10

- DES_9.8_CAD_Fix1
- DES_9.7_CAD_Fix2
- DES_9.0_SP1_CAD_Fix1

Release 9.9

- DES_9.7_CAD_Fix1
- DES_9.6_CAD_Fix4
- DES_9.5_SP1_CAD_Fix1

Release 9.8

- DES_9.6_CAD_Fix2
- DES_8.2_SP1_CAD_Fix10

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- WMC-3951
Installing a Composite Application Framework fix fails when the fix applies to multiple components, but the installation does not have all the components installed.
The fix installation rolls back because it expects all components that the fix addresses to be present in the installation directory.
The workaround is to install the missing components before installing the fix.

Release 10.0

- WMC-4039
In Software AG Designer, validation of xmlImport files fails for CAF projects that do not contain portlets.
The Problems tab for a project displays the following error: "Referenced file contains errors (<http://www.webmethods.com/schema/xmlImport.xsd>)."
The issue is resolved.
- WMC-4059
When using My webMethods in Internet Explorer, the CAF Toggle Tab control might cause increasing memory consumption.
The issue is resolved.

Release 9.12

- MWS-16031
The time zone of the CAF Date Range Input control does not match a My webMethods user's preferred time zone.
When a Date Range Input control is added to a portlet, the time zone of the Date Range Input control does not match the user's preferred time zone when the user's time zone uses daylight savings time.
The issue is resolved.

Release 9.9

- MWS-14667
Converting Composite Application Framework (CAF) applications to OpenCAF does not update navigation rules.
When a CAF application is converted to OpenCAF, the navigation rules in the CAF faces-

config.xml files are not updated to reference OpenCAF .xhtml files. The navigation rules still have references to removed .view files.

This issue is now resolved.

- MWS-14666

After converting a Task List Management CAF portlet to OpenCAF, clicking the Return button on the Task List Management page results in a javax.portlet.PortletException with the following message: "Cannot remove the same component twice".

This issue is now resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.1

- *webMethods CAF and OpenCAF Development Help* is renamed *webMethods CAF and OpenUI Development Help*.
- The topic "Working with Business Console Gadgets" is moved to a new Eclipse help set, *Working with Business Console Gadgets Help*.

Release 9.12

- *webMethods CAF Development Help* is renamed *webMethods CAF and OpenCAF Development Help*.
- A new topic, "Developing OpenCAF Applications", is added to *webMethods CAF and OpenCAF Development Help*. The topic provides an overview of the main OpenCAF functions as well as information about additional resources for developing OpenCAF applications.

Release 9.10

A new topic, "Working with Gadgets", has been added to the *webMethods CAF Development Help* online help and PDF guide.

Release 9.9

A new topic, "Getting Started with OpenCAF Shell Page Development", has been added to the *webMethods CAF Development Help* online help.

Release 9.8

A new chapter, "Getting Started with OpenCAF Shell Page Development", has been added to the

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 10.1

Old Term	New Term
OpenCAF	webMethods OpenUI OpenUI

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Changed Item	Description
Gadget Development	The UI Development node under Composite Applications in Installer no longer installs Gadget Development. To be able to develop Business Console gadgets, you must select Gadget Development under Composite Applications.

Release 10.2

Removed Item	Replacement, if any
Support for Axis 1.4, which is used for exposing web services from My webMethods Server, is removed.	Now My webMethods Server web services use Axis 1.7.7

Release 9.12

Deprecated Item	Replacement, if any
Support for Axis 1.x, which is used for exposing web services from My webMethods Server, is deprecated.	

Deprecated Item

Support for using webMethods Glue to create web service connectors in CAF and OpenCAF applications is deprecated.

Replacement, if any

WS-Stack Client library

Release 9.10**Added Item**

Drag And Drop File Input CAF control

Description

Replaces the Drag And Drop applet.

Client-side validation support for the CAF File Validator

With the recent HTML5 changes in browsers, it is now possible to perform client-side validation of the value specified in the file input element.

Client-side validation prevents uploading the wrong type of file to the server or uploading files that are too large.

The browsers that support this capability are:

Google Chrome version 6.0 and higher
Internet Explorer version 10.0 and higher
Firefox version 3.6 and higher

For browsers that do not support HTML5, server-side validation would have to be performed instead.

Support for the "multiple" attribute in the File Input CAF control

With the "multiple" attribute enabled, you can select and upload more than one file using the File Input control.

When the "multiple" attribute is enabled, the value of the control should be bound to a List<Part> object.

The browsers that support this capability are:

Google Chrome version 6.0 and higher
Internet Explorer version 10.0 and higher
Firefox version 3.6 and higher

If using other browsers, you can select only a single file through the File Input control.

Added Item	Description
<p>Support for standard JavaServer Faces (JSF) 2 methods to do Ajax requests</p> <p>webMethods Task Development now supports the String List data type when you configure task assignees with a webMethods Business Rules decision table in Software AG Designer.</p>	<p>CAF used a proprietary technique for performing partial page updates (Ajax) before the JSF standard offered support for Ajax requests. Now CAF supports the JSF 2.x standard for doing Ajax requests, replacing the proprietary technique.</p> <p>You can assign a task to multiple user IDs by using a String List in the assignee field of your IS document type. For more information about working with task assignments, see <i>webMethods BPM Task Development Help</i>.</p>

Changed Item	Description
<p>The Attachments List CAF control has been improved.</p> <p>The SOAP Monitor, Color Picker, and File Attachment applets have been converted to CAF components.</p> <p>The CAF project classpath has been simplified.</p>	<p>The changes to the Attachments List control include replacing the Java applet-based drag and drop panel with an HTML5-based equivalent.</p> <p>In more recent versions of Chrome and Firefox applets are disabled by default and must be manually enabled. Applets represent security risks.</p> <p>When you create a new portlet application or web application project in Software AG Designer, on the JSF Capabilities page of the new project wizard, selecting the CAF Libraries JSF implementation library now displays the following message: 'The targeted "My webMethods Server" runtime will contribute the libraries required by this facet to the project classpath.'</p> <p>Also, when you specify project properties by right-clicking the project and going to Properties > Project Facets > Java Server Faces > CAF Libraries, the properties wizard displays the same message.</p> <p>To clean up the project classpath for existing projects, right-click the project and go to CAF Tools > Repair CAF Project.</p>

Deprecated Item	Replacement, if any
<p>Applet CAF control</p>	

Release 9.9

Changed Item	Description
The internal structure of the Import Template View CAF control	Instead of being direct children of the Import Template View control, the controls loaded from the imported view are now held in a new "__viewLoaded" facet. However, because a facet can contain only one component, the imported controls are wrapped in a UIPanel control. As a result, the direct parent of the imported controls is the UIPanel wrapper, and the Import Template View control, in turn, is the parent of the UIPanel wrapper.

Release 9.8

Changed Item	Description
Update JSF library to version 2.2.8.	The JSF library is updated to version 2.2.8 to integrate bug fixes from the community.
Switch to new JSF 2.2 tag library namespaces.	In JSF 2.2, the core JSF tag library namespaces that start with <code>http://java.sun.com/jsf/</code> are renamed to <code>http://xmlns.jcp.org/jsf/*</code> . CAF has switched to using the new namespaces for new projects in order to avoid using deprecated items.

9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added API	Description
<code>com.softwareag.mws.screens.BaseScreenClass</code> : Class	<code>com.softwareag.mws.screens.BaseScreenClass</code> added
<code>com.softwareag.mws.screens.Constants</code> : Class	<code>com.softwareag.mws.screens.Constants</code> added
<code>com.softwareag.mws.screens.MWSLoginLogoutScreen</code> : Class	<code>com.softwareag.mws.screens.MWSLoginLogoutScreen</code> added
<code>com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen</code> : Class	

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen added

com.webmethods.bpm.process.impl.BpmProcess: Method 'protected void loadFromIS()' has been added

com.webmethods.bpm.process.impl.BpmProcessManager: Method 'public BpmProcessManager()' has been added

com.webmethods.bpm.process.impl.BpmProcessManager: Method 'public java.lang.String getDatasourceLibMode()' has been added

com.webmethods.bpm.process.impl.BpmProcessManagerIS: Class
com.webmethods.bpm.process.impl.BpmProcessManagerIS added

com.webmethods.bpm.process.impl.db.common.LoadProcessStepsIS: Class
com.webmethods.bpm.process.impl.db.common.LoadProcessStepsIS added

com.webmethods.caf.common.ServerCommon: Class com.webmethods.caf.common.ServerCommon added

com.webmethods.caf.common.XMLUtil: Method 'public javax.xml.parsers.DocumentBuilderFactory getBuilderFactory()' has been added

com.webmethods.caf.common.XMLUtil: Method 'public javax.xml.parsers.SAXParserFactory getSAXParserFactory()' has been added

com.webmethods.caf.common.XMLUtil: Method 'public org.xml.sax.XMLReader getXMLParser(java.lang.ClassLoader)' has been added

com.webmethods.caf.faces.application.CAFValueExpression: Method 'public java.lang.Object getCAFValue(javax.el.ELContext)' has been added

com.webmethods.caf.faces.data.object.ObjectMethodContentProvider: Method 'protected boolean isSessionExpired()' has been added

com.webmethods.caf.faces.data.task.TaskBusinessCalendarModel: Method 'protected
com.webmethods.sc.calendar.IWorkdayCalendar getCalendarByID(java.lang.String)' has been added

com.webmethods.caf.faces.data.ws.wss.WSSContentProvider: Method 'protected boolean isSessionExpired()' has been added

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected java.lang.String convertViewId(javax.faces.context.FacesContext, java.lang.String)' has been added

com.webmethods.caf.faces.render.html.input.DateInputRenderer: Method 'protected java.lang.Object convertDate(javax.faces.context.FacesContext, javax.faces.component.UIComponent, java.lang.Object, boolean, boolean)' has been added

com.webmethods.caf.wsclient.util.WSClientUtil: Method 'public java.util.Map constructClientAPI(java.lang.Class, java.lang.String, java.lang.String)' has been added

com.webmethods.caf.wsclient.util.WSClientUtil: Method 'public void reloadResource(java.lang.Class)' has been added

com.webmethods.caf.wsclient.util.XSDDateFormatMWS: Class
com.webmethods.caf.wsclient.util.XSDDateFormatMWS added

com.webmethods.portal.bizPolicy.command.install.InstallBootstrapComponentsWithDependencies:
Method 'protected boolean checkRealLocation(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.install.InstallBootstrapComponentsWithDependencies:
Method 'protected java.lang.String getComponentRealLocation(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContent: Method 'protected
boolean checkResourceExists(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS: Method 'protected
java.io.InputStream getISTaskAppStream(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.impl.BootstrapPhase: Method 'protected void
waitForOSGIServices()' has been added

com.webmethods.portal.jms.JMSPhaseProvider: Method 'protected void
bindGlobalProvider(com.webmethods.portal.service.global.IGlobalProvider)' has been added

com.webmethods.portal.jms.JMSPhaseProvider: Method 'protected void
bindRemoteEventDelivery(com.webmethods.portal.system.init.IInitializable)' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public
com.webmethods.portal.service.meta2.IUserService getUserService()' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public
com.webmethods.portal.service.meta2.thing.IThingID
initializeUserWithResult(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public void
initializeUser(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.install.impl.BasicInstallMechanics: Method 'protected boolean
checkNeedsComponent(java.util.List, java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.BasicInstallMechanics: Method 'protected java.lang.String
getComponentLocationToRealLocation(java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.InstallResolver: Method 'public void
init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.PortletInstallMechanics: Method 'protected
com.webmethods.portal.service.portlet.info.IPortletInfo loadPortletInfo(java.lang.String)' has been
added

com.webmethods.portal.mech.install.impl.UpgradeInstallComponentData: Method 'protected
java.lang.String getComponentLocationToRealLocation(java.lang.String)' has been added

com.webmethods.portal.mech.portlet.IPortletProviderMechanics: Method 'public
com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream,
java.io.InputStream)' has been added to an interface

com.webmethods.portal.mech.portlet.impl.PortletProviderMechanics: Method 'public com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream, java.io.InputStream)' has been added

com.webmethods.portal.mech.portlet.impl.PortletProviderMechanics: Method 'public void init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.socialbpm.comments.impl.CommentsMechanics: Method 'public com.webmethods.portal.service.meta2.thing.IThingID getThingID(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.sql.impl.ConnectionManagerMechanicsIS: Class
com.webmethods.portal.mech.sql.impl.ConnectionManagerMechanicsIS added

com.webmethods.portal.mech.task.ITaskHelper: Method 'public com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added to an interface

com.webmethods.portal.mech.task.impl.TaskChangeHandler: Method 'public TaskChangeHandler()' has been added

com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS: Method 'public void ensureTaskLwqFileExist(java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskCompletionHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskCompletionHandlerIS added

com.webmethods.portal.mech.task.impl.TaskHelper: Method 'public com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.mech.task.impl.TaskHelperService: Method 'public com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.mech.task.impl.TaskMechanics: Method 'protected void initHandlers(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskMechanicsIS: Method 'protected void initHandlers(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskScheduleHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskScheduleHandlerIS added

com.webmethods.portal.mech.task.impl.TaskTimedEventHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskTimedEventHandlerIS added

com.webmethods.portal.noodle.util.NoodleUtils: Method 'public boolean isForceNewTab(com.webmethods.portal.service.view.IView)' has been added

com.webmethods.portal.service.dir.IDirPrincipal: Method 'public boolean isInitialized()' has been added to an interface

com.webmethods.portal.service.dir.impl.DirSystem: Method 'public void onSynchronousEvent(com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent)' has been added

com.webmethods.portal.service.install.impl.BaseInstallService: Method 'protected java.lang.String getLocation(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.service.install.impl.BaseInstallService: Method 'protected void registerComponent(com.webmethods.portal.system.IInitializableComponentData, java.lang.String)' has been added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected com.webmethods.portal.schema.wmportletapp.PortletType _loadPortletType(java.util.Map)' has been added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected void _doRegisterComponent(java.util.Map)' has been added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected void _saveTempPortletInitData(java.util.Map)' has been added

com.webmethods.portal.service.meta2.util.ThingHelper: Class
com.webmethods.portal.service.meta2.util.ThingHelper added

com.webmethods.portal.service.portlet.IPortletProvider: Method 'public com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream, java.io.InputStream)' has been added to an interface

com.webmethods.portal.service.portlet.impl.PortletProvider: Method 'public com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream, java.io.InputStream)' has been added

com.webmethods.portal.service.socialbpm.comments.impl.CommentsServiceIS: Class
com.webmethods.portal.service.socialbpm.comments.impl.CommentsServiceIS added

com.webmethods.portal.service.sql.ISqlWorker: Method 'public void close()' has been added to an interface

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public boolean isCurrentlyInUse()' has been added

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public void close()' has been added

com.webmethods.portal.service.sql.runtime.base.CommentEntryUserDeleted: Class
com.webmethods.portal.service.sql.runtime.base.CommentEntryUserDeleted added

com.webmethods.portal.service.task.ITaskDefinition: Method 'public com.softwareag.caf.shared.task.core.model.TaskDataDefTable getTaskDataTable()' has been added to an interface

com.webmethods.portal.service.task.ITaskSystem: Method 'public com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added to an interface

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Method 'public boolean isHiddenUpdate()' has been added

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Method 'public void setHiddenUpdate(boolean)' has been added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Method 'public java.net.URLClassLoader getTaskClassLoader(java.lang.String)' has been added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Method 'public void removeTaskClassLoader(java.lang.String)' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public com.softwareag.caf.shared.task.core.model.TaskDataDefTable getTaskDataTable()' has been added

com.webmethods.portal.service.task.impl.TaskDistributionServiceIS: Class
com.webmethods.portal.service.task.impl.TaskDistributionServiceIS added

com.webmethods.portal.service.task.impl.TaskProcessAuditServiceIS: Class
com.webmethods.portal.service.task.impl.TaskProcessAuditServiceIS added

com.webmethods.portal.service.task.impl.TaskSystem: Method 'protected void bindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been added

com.webmethods.portal.service.task.impl.TaskSystem: Method 'public com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.system.BaseComponent: Method 'protected void bindGlobalProvider(com.webmethods.portal.service.global.IGlobalProvider)' has been added

com.webmethods.portal.system.PortalSystem: Method 'public boolean isTELibrary()' has been added

com.webmethods.portal.system.init.impl.ClusterPhaseProvider: Method 'protected java.lang.String getLocalConfigRootPath()' has been added

com.webmethods.portal.system.init.impl.ClusterPhaseProvider: Method 'protected void initDbConnection()' has been added

com.webmethods.portal.system.lock.impl.LockKey: Class
com.webmethods.portal.system.lock.impl.LockKey added

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Method 'protected java.lang.String checkTaskAppVersionIsUptodate(java.lang.String)' has been added

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Method 'protected void fixOldTaskClasses(java.io.File, java.lang.String)' has been added

com.webmethods.rtl.locator.impl.ClassLocator: Method 'public ClassLocator(java.lang.String, java.lang.String)' has been added

com.webmethods.rtl.tools.PrettyProperties\$NameValue: Class
com.webmethods.rtl.tools.PrettyProperties\$NameValue added

com.webmethods.rtl.tools.PrettyProperties: Class com.webmethods.rtl.tools.PrettyProperties added

com.webmethods.rtl.util.xml.XMLUtil: Method 'public java.lang.String toString(org.w3c.dom.Node,

int, boolean)' has been added

com.webmethods.caf.faces.portlet.PortletViewHandler: Added

com.sun.faces.application.view.MultiViewHandler to the list of superclasses

com.webmethods.caf.jcr.faces.data.query.PropertySearchTerm: Added protected field sRandom

com.webmethods.caf.wsclient.proxy.impl.WSClientDynamicProxy: Added public field REMOVE_WSDL_FROM_GLUE_CACHE

com.webmethods.mws.acdl.GenerateAcdlForProject: Added public field OPTION_IS_TASK_ENGINE

com.webmethods.portal.bizPolicy.command.task.webservice.QueueTaskWS: Added protected field DELAY_DEFAULT_VALUE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field DB_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field DB_ATTR_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field LDAP_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field LDAP_ATTR_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field PROFILE_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field USER_INFORMATION_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field USER_PROFILE_ATTR_TITLE

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_CUSTOM_HOSTS_PROP

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_DISABLED_PROP

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_POLICY_ENABLED

com.webmethods.portal.service.dir.impl.DirSystem: Added

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent\$ISynchronousListener to the set of implemented interfaces

com.webmethods.portal.service.sql.ISqlWorker: Added java.lang.AutoCloseable to the set of implemented interfaces

com.webmethods.portal.service.sql.core.BaseSqlWorker: Added java.lang.AutoCloseable to the set of implemented interfaces

com.webmethods.portal.service.sql.core.ConnectionManager: Added public field ORACLE_URL_PARSER_EXPRESSION_SERVICENAME

com.webmethods.portal.service.sql.core.ConnectionManager: Added public field ORACLE_URL_TEMPLATE_SERVICENAME

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Added protected field hiddenUpdate

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Added public field TASK_ASSETS_HOME_PROP

com.webmethods.portal.system.PortalSystem: Added public field TASK_ENGINE_LIBRARY_MODE

com.webmethods.rtl.locator.impl.StreamLocatorFactory: Added public field TEMP_PROTOCOL

Removed API

Replacement, if any

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'public java.lang.Object getWrapped()' has been removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'public javax.faces.application.ViewHandler getWrapped()' has been removed

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource: Method 'protected java.util.List getProfileAttributes(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.service.dir.IDirPrincipal)' has been removed

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS: Method 'protected com.webmethods.portal.system.IURI importNode(com.webmethods.portal.bizPolicy.IContext, org.w3c.dom.Element, com.webmethods.portal.system.IURI, java.util.List)' has been removed, but an inherited definition exists.

com.webmethods.portal.event.impl.RemoteEventDeliveryInitializer: Method 'protected void bindJMSPhaseProvider(com.webmethods.portal.system.IComponent)' has been removed

com.webmethods.portal.framework.mech.install.PortletAppilcationInstallMechanics: Method 'protected void clearContextRequestAttributes(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.mech.task.ITaskHelper: Method 'public com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been removed

com.webmethods.portal.mech.task.impl.TaskHelperService: Method 'public com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been removed

com.webmethods.portal.mech.task.impl.TaskMechanicsIS: Method 'protected com.webmethods.portal.service.task.ITaskList listTasks(com.webmethods.portal.system.IURI, com.webmethods.portal.service.task.TaskSearchQuery, boolean, boolean)' has been removed, but an inherited definition exists.

com.webmethods.portal.service.task.ITaskLockingService: Method 'public

com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has been removed

com.webmethods.portal.service.task.ITaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' has been removed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader: Class
com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has been removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' has been removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public long getDbTimeOffset()' has been removed

com.webmethods.portal.system.lock.impl.ClusterLockingService: Method 'public long getDbTimeOffset()' has been removed

com.webmethods.rtl.util.PrettyProperties\$NameValue: Class
com.webmethods.rtl.util.PrettyProperties\$NameValue removed

com.webmethods.rtl.util.PrettyProperties: Class com.webmethods.rtl.util.PrettyProperties removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed field wrapped

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed javax.faces.FacesWrapper from the set of implemented interfaces

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed javax.faces.application.ViewHandlerWrapper from the list of superclasses

com.webmethods.caf.jcr.faces.data.query.PropertySearchTerm: Removed field random

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field
MIN_INBOX_SEARCH_THREADS

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field
MIN_TASK_UPDATE_THREADS

Deprecated API

Replacement, if any

com.webmethods.portal.mech.task.impl.TaskHelper: Method 'public com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been deprecated

com.webmethods.portal.service.sql.ISqlWorker: Method 'public void release()' has been deprecated

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public void release()' has been deprecated

Changed API

Description

com.webmethods.caf.faces.component.output.ChartDataColumn: Parameter 1 of 'public void setItemValue(java.lang.Number)' has changed its type to java.lang.Object

com.webmethods.caf.faces.component.output.ChartDataColumn: Return type of method 'public java.lang.Number getItemValue()' has been changed to java.lang.Object

com.webmethods.caf.faces.portlet.PortletViewHandler: In method 'public PortletViewHandler(javax.faces.application.ViewHandler)' the number of arguments has changed

com.webmethods.caf.faces.render.html.input.DateInputRenderer: In method 'protected void writeTimeZone(javax.faces.context.FacesContext, javax.faces.component.UIComponent, java.util.Date)' the number of arguments has changed

com.webmethods.portal.mech.task.impl.TaskMechanics: In method 'public void fireTaskChangedEvent(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, com.webmethods.portal.service.task.ITask, com.webmethods.portal.service.task.ITask, java.lang.Object, java.lang.Object, int, boolean)' the number of arguments has changed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: In method 'public java.lang.Object getTaskInstance(java.lang.String)' the number of arguments has changed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: In method 'public void addTaskClassLoader(com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader)' the number of arguments has changed

com.webmethods.portal.system.lock.IClusterLockingService: In method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' the number of arguments has changed

com.webmethods.portal.system.lock.IClusterLockingService: Parameter 2 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to long

com.webmethods.portal.system.lock.IClusterLockingService: Parameter 4 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to boolean

com.webmethods.portal.system.lock.impl.ClusterLockingService: In method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' the number of arguments has changed

com.webmethods.portal.system.lock.impl.ClusterLockingService: Parameter 2 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to long

com.webmethods.portal.system.lock.impl.ClusterLockingService: Parameter 4 of 'public

com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to boolean

com.webmethods.rtl.util.xml.XMLUtil: In method 'protected void _dumpXML(org.w3c.dom.Node, java.io.Writer, int, int)' the number of arguments has changed

Release 10.2

Added API

Description

com.softwareag.mws.screens.BaseScreenClass Class com.softwareag.mws.screens.BaseScreenClass added

com.softwareag.mws.screens.Constants Class com.softwareag.mws.screens.Constants added

com.softwareag.mws.screens.MWSLoginLogoutScreen Class
com.softwareag.mws.screens.MWSLoginLogoutScreen added

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen Class
com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen added

com.webmethods.caf.common.cipher.MWSCipherDataStore Class
com.webmethods.caf.common.cipher.MWSCipherDataStore added

com.webmethods.caf.common.cipher.MWSCipherMasterPassword Class
com.webmethods.caf.common.cipher.MWSCipherMasterPassword added

com.webmethods.caf.common.cipher.SecretDS Class com.webmethods.caf.common.cipher.SecretDS added

com.webmethods.caf.faces.component.util.ShadowComponentMapCacheEntry Class
com.webmethods.caf.faces.component.util.ShadowComponentMapCacheEntry added

com.webmethods.caf.faces.data.attachments.BasePortalContainerAttachmentsProvider Method 'public java.lang.String getEncoding(java.lang.String)' has been added

com.webmethods.caf.faces.data.comments.impl.CommentsListProvider Method 'public com.webmethods.portal.service.access.IAclManager createAclManager(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskAuditBizPolicy Method 'public java.util.Collection getWebServiceCommands(com.webmethods.portal.bizPolicy.IContext)' has been added

com.webmethods.portal.bizPolicy.command.IJSONAdapter Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added to an interface

com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory Method 'public java.util.Map

getSchemaFields(java.lang.Class, java.util.Map, java.util.Map)' has been added to an interface

com.webmethods.portal.bizPolicy.command.alias.SetThingAliases Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.alias.IAliasMechanics, com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource Method 'protected java.util.List getProfileAttributes(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.service.dir.IDirPrincipal)' has been added

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource Method 'public javax.ws.rs.core.Response getPersonalData(javax.servlet.http.HttpServletRequest, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.dir.rs.DirJSONAdapter Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandBean Method 'protected java.text.SimpleDateFormat getSDF()' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandBean Method 'protected java.text.SimpleDateFormat getSDFDotNet()' has been added

com.webmethods.portal.bizPolicy.command.impl.JSONAdapterFactory Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.AbstractJSONAdapter Class
com.webmethods.portal.bizPolicy.command.impl.rs.AbstractJSONAdapter added

com.webmethods.portal.bizPolicy.command.impl.rs.BaseRestResource Method 'protected java.lang.String sanitizeMessage(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BaseRestResource Method 'protected javax.ws.rs.core.Response sendException(javax.servlet.http.HttpServletRequest, java.lang.Exception, java.lang.String, int)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'protected com.webmethods.portal.service.view.IView getView(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'protected void addIfNotSetAndNonNullValue(java.lang.String, java.lang.Object, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BizPolicyResource Class
com.webmethods.portal.bizPolicy.command.impl.rs.BizPolicyResource added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandDocBuilder Class

com.webmethods.portal.bizPolicy.command.impl.rs.CommandDocBuilder added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource Method 'public javax.ws.rs.core.Response getCommandSpecification(javax.servlet.http.HttpServletRequest, javax.servlet.http.HttpServletResponse, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource Method 'public javax.ws.rs.core.Response getSpecification(javax.servlet.http.HttpServletRequest)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.ConnectionInfoJSONAdapter Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.DefaultJSONAdapter Class
com.webmethods.portal.bizPolicy.command.impl.rs.DefaultJSONAdapter added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentList Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentList added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentMap added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentOrderedMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentOrderedMap added

com.webmethods.portal.bizPolicy.command.impl.rs.util.IFluentMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.IFluentMap added

com.webmethods.portal.bizPolicy.command.page.ModifyPage2IS Class
com.webmethods.portal.bizPolicy.command.page.ModifyPage2IS added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS Class
com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS Class
com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS added

com.webmethods.portal.bizPolicy.command.task.rs.TaskJSONAdapter Class
com.webmethods.portal.bizPolicy.command.task.rs.TaskJSONAdapter added

com.webmethods.portal.bizPolicy.command.task.webservice.UpdateTaskAttachmentWS\$updateTaskAttachmentCommandBean Method 'protected boolean excludePropertyDescriptor(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.task.webservice.UpdateTaskAttachmentWS\$updateTaskAttachmentCommandBean Method 'public void setAttachmentID(java.lang.String)' has been added

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public com.webmethods.portal.service.meta2.thing.IThingID getGetDirectoryServiceThingID()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public
com.webmethods.portal.system.IURI getDirectoryURI()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public java.lang.String
getEmail()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public java.lang.String
getPrincipalDN()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalModifyEvent Method 'public java.lang.Object
getPropertyOldValue()' has been added to an interface

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public
DirPrincipalDeleteEvent(com.webmethods.portal.service.dir.IDirPrincipal,
com.webmethods.portal.service.dir.IDirPrincipalList,
com.webmethods.portal.service.dir.IDirPrincipalList,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public
com.webmethods.portal.service.meta2.thing.IThingID getGetDirectoryServiceThingID()' has been
added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public
com.webmethods.portal.system.IURI getDirectoryURI()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public
com.webmethods.portal.system.IURI getPrincipalURI()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public java.lang.String
getEmail()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public java.lang.String
getPrincipalDN()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public
DirPrincipalModifyEvent(com.webmethods.portal.system.IURI,
com.webmethods.portal.service.meta2.thing.IThingID, java.lang.String, java.lang.Object,
java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public
DirPrincipalModifyEvent(com.webmethods.portal.system.IURI, java.lang.String, java.lang.Object,
java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public java.lang.Object
getPropertyOldValue()' has been added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$IListener Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$IListener added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$ISynchronousListener Class

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$ISynchronousListener added
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$Listeners Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$Listeners added
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$SynchronousListeners Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$SynchronousListeners added
com.webmethods.portal.event.system.impl.DistributedConfigChangedEvent Class
com.webmethods.portal.event.system.impl.DistributedConfigChangedEvent added
com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler Class
com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler added
com.webmethods.portal.framework.session.handlers.LoginScript Method 'protected void
bindSystemPolicy(com.webmethods.portal.bizPolicy.biz.system.ISystemPolicy)' has been added
com.webmethods.portal.framework.session.handlers.Validate Method 'protected void
bindJMSPHaseProvider(com.webmethods.portal.system.IComponent)' has been added
com.webmethods.portal.framework.session.impl.SessionManager Method 'protected void
bindAuthManager(com.webmethods.portal.framework.IAuthManager)' has been added
com.webmethods.portal.jms.db.impl.db2.PurgeEvents Method 'protected java.lang.String
getDeleteEventsQuery()' has been added
com.webmethods.portal.jms.um.UmJMSConnProvider Method 'protected void
registerJMSObjects(org.w3c.dom.Element)' has been added
com.webmethods.portal.mech.dir.IDirServiceMechanics Method 'public void
fireDeletePrincipalEvent(com.webmethods.portal.service.dir.IDirPrincipal,
com.webmethods.portal.service.dir.IDirPrincipalList,
com.webmethods.portal.service.dir.IDirPrincipalList)' has been added to an interface
com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics Method 'public void
fireModifyPrincipalEvent(com.webmethods.portal.service.meta2.thing.IThingID,
com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID,
java.lang.String, java.lang.Object, java.lang.Object)' has been added to an interface
com.webmethods.portal.mech.dir.impl.DirServiceMechanics Method 'protected boolean
isUserPrivacyEnabled()' has been added
com.webmethods.portal.mech.dir.impl.DirServiceMechanics Method 'public void
fireDeletePrincipalEvent(com.webmethods.portal.service.dir.IDirPrincipal,
com.webmethods.portal.service.dir.IDirPrincipalList,
com.webmethods.portal.service.dir.IDirPrincipalList)' has been added
com.webmethods.portal.mech.dir.impl.PrincipalAttributeMechanics Method 'public void
fireModifyPrincipalEvent(com.webmethods.portal.service.meta2.thing.IThingID,
com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID,
java.lang.String, java.lang.Object, java.lang.Object)' has been added
com.webmethods.portal.mech.rules.impl.TEELContext Class

com.webmethods.portal.mech.rules.impl.TEELContext added

com.webmethods.portal.mech.rules.impl.TEExpressionResolver Class
com.webmethods.portal.mech.rules.impl.TEExpressionResolver added

com.webmethods.portal.mech.schedule.impl.ScheduleMechanicsIS Class
com.webmethods.portal.mech.schedule.impl.ScheduleMechanicsIS added

com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS Class
com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS added

com.webmethods.portal.mech.task.impl.TaskContextHelper Class
com.webmethods.portal.mech.task.impl.TaskContextHelper added

com.webmethods.portal.mech.task.impl.TaskDataHelper Method 'public java.lang.Object[]
resolveTaskFields(com.webmethods.portal.service.task.ITask,
com.webmethods.portal.service.task.ITaskData, java.lang.String[])' has been added

com.webmethods.portal.mech.task.impl.TaskMechanics Method 'protected void
bindMechanicsManager(com.webmethods.portal.mech.IMechanicsManager)' has been added

com.webmethods.portal.mech.task.impl.TaskMechanicsIS Class
com.webmethods.portal.mech.task.impl.TaskMechanicsIS added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public
TaskRuleContext(com.webmethods.caf.rules.IRuleContext, java.util.Map)' has been added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public java.util.Map
getContextMap()' has been added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public void
setContextMap(java.util.Map)' has been added

com.webmethods.portal.service.access.IAclManager Method 'public void
setResourceType(java.lang.String)' has been added to an interface

com.webmethods.portal.service.access.IAclManager Method 'public void setUserID(java.lang.String)'
has been added to an interface

com.webmethods.portal.service.cache.ICacheManager Method 'public void
configureCache(java.lang.String, java.util.Map)' has been added to an interface

com.webmethods.portal.service.cache.impl.CacheManager Method 'protected java.util.Collection
getRegistryBasedComponentCollection()' has been added

com.webmethods.portal.service.cache.impl.CacheManager Method 'protected void
configureCacheFromRegisrty(java.lang.String)' has been added

com.webmethods.portal.service.cache.impl.CacheManager Method 'public void
configureCache(java.lang.String, java.util.Map)' has been added

com.webmethods.portal.service.dir.IDirCache Method 'public void clearQueryCache()' has been added
to an interface

com.webmethods.portal.service.dir.IDirServiceThing Class
com.webmethods.portal.service.dir.IDirServiceThing added

com.webmethods.portal.service.dir.IUserPrivacyService Class
com.webmethods.portal.service.dir.IUserPrivacyService added

com.webmethods.portal.service.dir.IUserPrivacyService\$NotificationType Class
com.webmethods.portal.service.dir.IUserPrivacyService\$NotificationType added

com.webmethods.portal.service.dir.impl.DirCache Method 'public void clearQueryCache()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected
com.webmethods.portal.service.dir.IDirPrincipal getCurrentDirPrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected
com.webmethods.portal.service.meta2.thing.IThingID getCurrentPrincipalThingID()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected long
getCreatedTime()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected long
getLastModifiedTime()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected void
deletePrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean
canDeleteUser()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean
isEditingSelf(com.webmethods.portal.bizPolicy.IContext)' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean
isMemberOfAdminRole()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean
isSysAdminPrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean
isUserPrivacyEnabled()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public void DeleteUser()' has
been added

com.webmethods.portal.service.portlet.impl.PortletProvider Method 'protected void
bindThingIDService(com.webmethods.portal.service.meta2.IThingIDService)' has been added

com.webmethods.portal.service.portlet.impl.PortletProvider Method 'protected void
bindXTypeService(com.webmethods.portal.service.meta2.IXTypeService)' has been added

com.webmethods.portal.service.scheduler.Scheduler Method 'protected void
bindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been
added

com.webmethods.portal.service.scheduler.Scheduler Method 'protected void unbindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.service.meta2.thing.IThingID getThingIDHelper(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI getURIHelper(java.lang.String)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI lookupPrincipalHelper(java.lang.Object)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI lookupPrincipalHelper(java.lang.Object, int)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public int getIntPriorityHelper(java.lang.String)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public int getIntStatusHelper(java.lang.String)' has been added

com.webmethods.portal.service.task.TaskSearchQuery Method 'public boolean matches(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)' has been added

com.webmethods.portal.service.task.TaskSearchQueryTerm Method 'public boolean matches(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)' has been added

com.webmethods.portal.service.task.TaskSearchQueryTerm Method 'public java.util.List getFieldExpressionsString(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)' has been added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory Class
com.webmethods.portal.service.task.impl.TaskClassLoaderFactory added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader Class
com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader added

com.webmethods.portal.service.task.impl.TaskDBIndexManagerHelper Class
com.webmethods.portal.service.task.impl.TaskDBIndexManagerHelper added

com.webmethods.portal.service.task.impl.TaskIndexTableViewHelper Class
com.webmethods.portal.service.task.impl.TaskIndexTableViewHelper added

com.webmethods.portal.service.task.impl.TaskService Method 'public void flushTaskInfoCache(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.service.task.impl.TaskServiceIS Class
com.webmethods.portal.service.task.impl.TaskServiceIS added

com.webmethods.portal.service.task.impl.TaskSystem Method 'protected com.webmethods.portal.system.IComponentData

createComponentData(com.webmethods.portal.system.IInitializableComponentData)' has been added

com.webmethods.portal.service.task.impl.TaskSystem Method 'protected java.util.Collection
getThingBasedComponentCollection()' has been added

com.webmethods.portal.system.PortalSystem Method 'public java.lang.Boolean isLibraryMode()' has
been added

com.webmethods.portal.webservices.SOAPMonitorConstants Class
com.webmethods.portal.webservices.SOAPMonitorConstants added

com.webmethods.portal.webservices.SOAPMonitorData Method 'public
SOAPMonitorData(java.lang.Integer, java.lang.Long, java.lang.String, java.lang.String,
java.lang.String)' has been added

com.webmethods.portal.webservices.SOAPMonitorData Method 'public java.lang.String
getContentType()' has been added

com.webmethods.portal.webservices.SOAPMonitorData Method 'public java.lang.String
getMessageText()' has been added

com.webmethods.portal.webservices.SOAPMonitorData Method 'public void
setContentType(java.lang.String)' has been added

com.webmethods.portal.webservices.SOAPMonitorData Method 'public void
setMessageText(java.lang.String)' has been added

com.webmethods.rtl.locator.impl.DBConfigLocator Method 'protected void
fireConfigChangedEvent(java.lang.String)' has been added

com.webmethods.rtl.util.FileUtil Method 'public java.lang.String
getRealLocationAtIS(java.lang.String)' has been added

com.webmethods.rtl.util.FileUtil Method 'public java.lang.String
getRealLocationAtISatTaskApp(java.lang.String, java.lang.String)' has been added

Removed API	Replacement, if any
com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public java.lang.Class[] getExtraWsdlsSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed	
com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public org.apache.axis.description.ServiceDesc initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext, org.apache.axis.description.ServiceDesc)' has been removed	
com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public org.apache.axis.handlers.soap.SOAPService initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed	
com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,	

javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.access.GetAcView Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.access.ListSecurityRealmObjects Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.alias.CreateAlias Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.dir.GetTypedAttributes Method 'public java.lang.Class[] getExtraWsdSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.dir.GetTypedAttributes Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'protected java.beans.PropertyDescriptor[] getClassPropertyDescriptors(java.lang.Class)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'protected void registerWebServiceMarshallingFactories(java.lang.Class, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public java.lang.Class[] getExtraWsdSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public org.apache.axis.description.ServiceDesc initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext, org.apache.axis.description.ServiceDesc)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public org.apache.axis.handlers.soap.SOAPService initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.WebServiceHelper Class
com.webmethods.portal.bizPolicy.command.impl.WebServiceHelper removed

com.webmethods.portal.bizPolicy.command.meta.GetSelectedList Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListChildrenFiltered Method 'public void

initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListContainers Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListNotes Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.schedule.ListSchedulesCommand Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.page.ModifyPage2 Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.socialkeyword.GetKeyword Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.socialkeyword.ListKeywords Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.sql.ListDataSources Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.sql.ListDataSources Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.system.ImportFiles Class
com.webmethods.portal.bizPolicy.command.system.ImportFiles removed

com.webmethods.portal.bizPolicy.command.system.ImportFilesBean Class
com.webmethods.portal.bizPolicy.command.system.ImportFilesBean removed

com.webmethods.portal.bizPolicy.command.system.Ping Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.system.Ping Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus Method 'public void

initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.task.BaseTaskCommand Method 'protected java.beans.PropertyDescriptor[] getClassPropertyDescriptors(java.lang.Class)' has been removed

com.webmethods.portal.bizPolicy.command.task.GetTaskAudit Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.task.GetTaskAuditPaginated Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.version.ListVersionsCommand Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.webspace.ListWebSpaces Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.impl.ContextProvider Method 'protected com.webmethods.portal.bizPolicy.IContext getContextBySessionId(java.lang.String)' has been removed

com.webmethods.portal.framework.dispatch.handlers.webservices.GetWSDL Class
com.webmethods.portal.framework.dispatch.handlers.webservices.GetWSDL removed

com.webmethods.portal.framework.propertyeditor.command.ListPropertyEditors Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public org.apache.axis.description.ServiceDesc initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext, org.apache.axis.description.ServiceDesc)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public org.apache.axis.handlers.soap.SOAPService initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.webservices.SOAPMonitorData Method 'public java.lang.String getSoap()' has been removed

com.webmethods.portal.webservices.SOAPMonitorData Method 'public void

setSoap(java.lang.String)' has been removed

com.webmethods.portal.webservices.configuration.MwsEngineConfigurationFactoryServlet Class
com.webmethods.portal.webservices.configuration.MwsEngineConfigurationFactoryServlet removed

com.webmethods.portal.webservices.configuration.MwsFileProvider Class
com.webmethods.portal.webservices.configuration.MwsFileProvider removed

com.webmethods.portal.webservices.configuration.UpgradeAxisConfiguration Class
com.webmethods.portal.webservices.configuration.UpgradeAxisConfiguration removed

com.webmethods.portal.webservices.encoding.AliasValueSerializer Class
com.webmethods.portal.webservices.encoding.AliasValueSerializer removed

com.webmethods.portal.webservices.encoding.AliasValueSerializerFactory Class
com.webmethods.portal.webservices.encoding.AliasValueSerializerFactory removed

com.webmethods.portal.webservices.encoding.BeanPropertiesTypeDesc Class
com.webmethods.portal.webservices.encoding.BeanPropertiesTypeDesc removed

com.webmethods.portal.webservices.encoding.CertificateSerializer Class
com.webmethods.portal.webservices.encoding.CertificateSerializer removed

com.webmethods.portal.webservices.encoding.CertificateSerializerFactory Class
com.webmethods.portal.webservices.encoding.CertificateSerializerFactory removed

com.webmethods.portal.webservices.encoding.CharacterSerializer Class
com.webmethods.portal.webservices.encoding.CharacterSerializer removed

com.webmethods.portal.webservices.encoding.CharacterSerializerFactory Class
com.webmethods.portal.webservices.encoding.CharacterSerializerFactory removed

com.webmethods.portal.webservices.encoding.ConnectionInfoSerializer Class
com.webmethods.portal.webservices.encoding.ConnectionInfoSerializer removed

com.webmethods.portal.webservices.encoding.ConnectionInfoSerializerFactory Class
com.webmethods.portal.webservices.encoding.ConnectionInfoSerializerFactory removed

com.webmethods.portal.webservices.encoding.DifferenceMapSerializer Class
com.webmethods.portal.webservices.encoding.DifferenceMapSerializer removed

com.webmethods.portal.webservices.encoding.DifferenceMapSerializerFactory Class
com.webmethods.portal.webservices.encoding.DifferenceMapSerializerFactory removed

com.webmethods.portal.webservices.encoding.DirServiceSerializer Class
com.webmethods.portal.webservices.encoding.DirServiceSerializer removed

com.webmethods.portal.webservices.encoding.DirServiceSerializerFactory Class
com.webmethods.portal.webservices.encoding.DirServiceSerializerFactory removed

com.webmethods.portal.webservices.encoding.IDataDeserializer Class
com.webmethods.portal.webservices.encoding.IDataDeserializer removed

com.webmethods.portal.webservices.encoding.IDataDeserializerFactory Class

com.webmethods.portal.webservices.encoding.IDataDeserializerFactory removed
com.webmethods.portal.webservices.encoding.IOutOnly Class
com.webmethods.portal.webservices.encoding.IOutOnly removed
com.webmethods.portal.webservices.encoding.ISoapComplexTypeBean Class
com.webmethods.portal.webservices.encoding.ISoapComplexTypeBean removed
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializer Class
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializer removed
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializerFactory Class
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializerFactory removed
com.webmethods.portal.webservices.encoding.ListViewSerializer Class
com.webmethods.portal.webservices.encoding.ListViewSerializer removed
com.webmethods.portal.webservices.encoding.ListViewSerializerFactory Class
com.webmethods.portal.webservices.encoding.ListViewSerializerFactory removed
com.webmethods.portal.webservices.encoding.LocaleDeserializer Class
com.webmethods.portal.webservices.encoding.LocaleDeserializer removed
com.webmethods.portal.webservices.encoding.LocaleDeserializerFactory Class
com.webmethods.portal.webservices.encoding.LocaleDeserializerFactory removed
com.webmethods.portal.webservices.encoding.LocaleSerializer Class
com.webmethods.portal.webservices.encoding.LocaleSerializer removed
com.webmethods.portal.webservices.encoding.LocaleSerializerFactory Class
com.webmethods.portal.webservices.encoding.LocaleSerializerFactory removed
com.webmethods.portal.webservices.encoding.PageDataDeserializer Class
com.webmethods.portal.webservices.encoding.PageDataDeserializer removed
com.webmethods.portal.webservices.encoding.PageDataDeserializerFactory Class
com.webmethods.portal.webservices.encoding.PageDataDeserializerFactory removed
com.webmethods.portal.webservices.encoding.PageDataSerializer Class
com.webmethods.portal.webservices.encoding.PageDataSerializer removed
com.webmethods.portal.webservices.encoding.PageDataSerializerFactory Class
com.webmethods.portal.webservices.encoding.PageDataSerializerFactory removed
com.webmethods.portal.webservices.encoding.PagingBeanDeserializer Class
com.webmethods.portal.webservices.encoding.PagingBeanDeserializer removed
com.webmethods.portal.webservices.encoding.PagingBeanDeserializerFactory Class
com.webmethods.portal.webservices.encoding.PagingBeanDeserializerFactory removed
com.webmethods.portal.webservices.encoding.PagingBeanSerializer Class
com.webmethods.portal.webservices.encoding.PagingBeanSerializer removed
com.webmethods.portal.webservices.encoding.PagingBeanSerializerFactory Class

com.webmethods.portal.webservices.encoding.PagingBeanSerializerFactory removed
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializer Class
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializer removed
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializerFactory Class
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializerFactory removed
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializer Class
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializer removed
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializerFactory Class
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializerFactory removed
com.webmethods.portal.webservices.encoding.RightSetDeserializer Class
com.webmethods.portal.webservices.encoding.RightSetDeserializer removed
com.webmethods.portal.webservices.encoding.RightSetDeserializerFactory Class
com.webmethods.portal.webservices.encoding.RightSetDeserializerFactory removed
com.webmethods.portal.webservices.encoding.RightSetSerializer Class
com.webmethods.portal.webservices.encoding.RightSetSerializer removed
com.webmethods.portal.webservices.encoding.RightSetSerializerFactory Class
com.webmethods.portal.webservices.encoding.RightSetSerializerFactory removed
com.webmethods.portal.webservices.encoding.SelectedListViewSerializer Class
com.webmethods.portal.webservices.encoding.SelectedListViewSerializer removed
com.webmethods.portal.webservices.encoding.SelectedListViewSerializerFactory Class
com.webmethods.portal.webservices.encoding.SelectedListViewSerializerFactory removed
com.webmethods.portal.webservices.encoding.ThingIDListSerializer Class
com.webmethods.portal.webservices.encoding.ThingIDListSerializer removed
com.webmethods.portal.webservices.encoding.ThingIDListSerializerFactory Class
com.webmethods.portal.webservices.encoding.ThingIDListSerializerFactory removed
com.webmethods.portal.webservices.encoding.ThingNameAtomSerializer Class
com.webmethods.portal.webservices.encoding.ThingNameAtomSerializer removed
com.webmethods.portal.webservices.encoding.ThingNameAtomSerializerFactory Class
com.webmethods.portal.webservices.encoding.ThingNameAtomSerializerFactory removed
com.webmethods.portal.webservices.encoding.URIDeserializer Class
com.webmethods.portal.webservices.encoding.URIDeserializer removed
com.webmethods.portal.webservices.encoding.URIDeserializerFactory Class
com.webmethods.portal.webservices.encoding.URIDeserializerFactory removed
com.webmethods.portal.webservices.encoding.URISerializer Class
com.webmethods.portal.webservices.encoding.URISerializer removed
com.webmethods.portal.webservices.encoding.URISerializerFactory Class

com.webmethods.portal.webservices.encoding.URISerializerFactory removed

com.webmethods.portal.webservices.encoding.ViewProperty Class
com.webmethods.portal.webservices.encoding.ViewProperty removed

com.webmethods.portal.webservices.encoding.ViewSerializer Class
com.webmethods.portal.webservices.encoding.ViewSerializer removed

com.webmethods.portal.webservices.encoding.ViewSerializerFactory Class
com.webmethods.portal.webservices.encoding.ViewSerializerFactory removed

com.webmethods.portal.webservices.handlers.CommandHandler Class
com.webmethods.portal.webservices.handlers.CommandHandler removed

com.webmethods.portal.webservices.handlers.CommandProvider Class
com.webmethods.portal.webservices.handlers.CommandProvider removed

com.webmethods.portal.webservices.handlers.SOAPMonitorHandler Class
com.webmethods.portal.webservices.handlers.SOAPMonitorHandler removed

com.webmethods.portal.webservices.servlet.PortalAxisServlet Class
com.webmethods.portal.webservices.servlet.PortalAxisServlet removed

Changed API

Description

com.webmethods.portal.bizPolicy.command.dir.DeletePrincipal In method 'protected void fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList)' the number of arguments has changed

com.webmethods.portal.bizPolicy.command.dir.ModifyPrincipal In method 'protected void fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics, com.webmethods.portal.system.IURI, java.lang.String, java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' the number of arguments has changed

com.webmethods.portal.bizPolicy.command.dir.ModifyPrincipalEx In method 'protected void fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics, com.webmethods.portal.system.IURI, java.util.Map, com.webmethods.portal.service.meta2.thing.IThingID)' the number of arguments has changed

com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource In method 'public javax.ws.rs.core.Response invokeCommandFromForm(javax.servlet.http.HttpServletRequest, javax.servlet.http.HttpServletResponse, java.lang.String)' the number of arguments has changed

Release 10.1

Added API	Description
<code>com.webmethods.portal.bizPolicy.biz.dir.IDirSystemBizPolicy</code> : Method 'public <code>authenticateUser(com.webmethods.portal.bizPolicy.IContext, java.lang.String, java.lang.String, boolean)</code> ' has been added to an interface	
<code>com.webmethods.portal.framework.IAuthManager</code> : Method 'public <code>createAuthInfo()</code> ' has been added to an interface	
<code>com.webmethods.portal.service.task.ITaskDistributionService</code> : Method 'public <code>searchAllTasks(com.webmethods.portal.service.task.TaskSearchQuery, java.lang.Boolean)</code> ' has been added to an interface	
<code>com.webmethods.portal.service.task.ITaskLockingService</code> : Method 'public <code>acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)</code> ' has been added to an interface	
<code>com.webmethods.portal.service.task.ITaskLockingService</code> : Method 'public <code>acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)</code> ' has been added to an interface	
<code>com.webmethods.portal.service.task.ITaskLockingService</code> : Method 'public <code>getLock(com.webmethods.portal.system.IURI)</code> ' has been added to an interface	
<code>com.webmethods.portal.system.IURIResolver</code> : Method 'public <code>acquireURI(java.lang.String, boolean)</code> ' has been added to an interface	
<code>com.webmethods.portal.system.init.IPhaseProvider</code> : Method 'public void <code>preInit(java.lang.String)</code> ' has been added to an interface	
<code>com.webmethods.portal.webservices.IWebService</code> : Method 'public <code>java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)</code> ' has been added to an interface	

Removed API**Replacement, if any**

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo: Removed
com.webmethods.caf.faces.data.task.IQueryAggregationInfo from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxIndexedSearchContentProvider\$InboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxSearchContentProvider\$InboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskIndexedSearchContentProvider\$TaskData: Removed
com.webmethods.caf.faces.data.task.ITaskData from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.portal.mech.task.impl.TaskQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Removed
com.webmethods.portal.system.init.IInitializable from the set of implemented interfaces

com.webmethods.portal.socialbpm.charts.SocialBPMSearchQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.impl.TaskSearchQuery from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2 from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.impl.TaskSearchQuery from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2 from the list of superclasses

com.webmethods.caf.mobile.notify.impl.PushNotification: Removed
com.webmethods.portal.system.impl.BaseComponent from the list of superclasses

com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean: Removed
com.webmethods.rtl.util.obj.MapPropertyBag from the list of superclasses

com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean: Removed
com.webmethods.rtl.util.obj.MapPropertyBag from the list of superclasses

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus: Removed
com.webmethods.portal.system.impl.BaseComponent from the list of superclasses

com.webmethods.rtl.locator.ClassLocator: Removed com.webmethods.rtl.locator.FileLocator from the list of superclasses

com.webmethods.rtl.util.SystemPaths\$UserPathLocator: Removed
com.webmethods.rtl.locator.FileLocator from the list of superclasses

com.webmethods.caf.mobile.notify.task.APNSCleanUpThread: Removed field expiredID

com.webmethods.portal.service.portlet.impl.PortletProvider: Removed field
portletProviderFactoryServiceReg

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field
TASK_LOCK_MAX_TIME

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field
TASK_LOCK_MAX_WAIT_TIME

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field dbOffsetLastCalced

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field dbTimeOffsetMs

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm findTerm(java.lang.String,
java.lang.String)' has been removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm findTerm(java.lang.String)' has been removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.IQueryAggregationInfo getQueryAggregationInfo()' has been removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm[] getTerms()' has been removed

com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider: Method 'protected
java.util.Collection loadConfig(com.webmethods.portal.system.IComponentData)' has been removed

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void
includeBCScript(java.lang.String, java.util.Locale, java.io.Writer, boolean)' has been removed

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void stripBCScript(java.io.Reader,
java.io.Writer)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_sep_for_bc(int)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_unambiguous_sep_for_bc(int)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'public void stripBCScript(java.io.Reader, java.io.Writer)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected int strip_c_comment_for_bc(java.io.Reader, java.io.Writer)' has been removed

com.webmethods.portal.framework.auth.AuthInfo: Method 'public void copy(com.webmethods.portal.framework.auth.AuthInfo)' has been removed

com.webmethods.portal.framework.presentation.PresentationData: Method 'public com.webmethods.portal.framework.presentation.PresentationData init(java.lang.Object, int, java.util.HashMap)' has been removed

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Method 'public void init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been removed

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Method 'public void shutdown()' has been removed

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool: Method 'public void initialize(com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager, java.util.Map)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public javax.servlet.ServletContext getServletContext(java.lang.String)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public org.eclipse.jetty.webapp.WebAppContext getWebAppContext(java.lang.String)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void refreshBundle(org.osgi.framework.Bundle)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void refreshRemovalPendingBundles()' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void startBundle(org.osgi.framework.Bundle)' has been removed

com.webmethods.caf.faces.data.task.AggregationType: Class
com.webmethods.caf.faces.data.task.AggregationType removed

com.webmethods.caf.faces.data.task.IQueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.IQueryAggregationInfo removed

com.webmethods.caf.faces.data.task.IndexEngineType: Class
com.webmethods.caf.faces.data.task.IndexEngineType removed

com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider: Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider removed

com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher: Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestPingInfo: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestPingInfo removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestResource: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestResource removed

com.webmethods.portal.framework.presentation.handlers.djsp.FlexiblePoolBoy: Class
com.webmethods.portal.framework.presentation.handlers.djsp.FlexiblePoolBoy removed

com.webmethods.rtl.locator.BundleLocator: Class com.webmethods.rtl.locator.BundleLocator removed

com.webmethods.rtl.locator.ClusterConfigLocator: Class
com.webmethods.rtl.locator.ClusterConfigLocator removed

com.webmethods.rtl.locator.ConfigLocator: Class com.webmethods.rtl.locator.ConfigLocator removed

com.webmethods.rtl.locator.FileLocator: Class com.webmethods.rtl.locator.FileLocator removed

com.webmethods.rtl.locator.NullLocator: Class com.webmethods.rtl.locator.NullLocator removed

com.webmethods.rtl.locator.StreamLocatorFactory: Class
com.webmethods.rtl.locator.StreamLocatorFactory removed

com.webmethods.rtl.locator.WebResourceLocator: Class
com.webmethods.rtl.locator.WebResourceLocator removed

Release 10.0

Added API	Description
<code>com.webmethods.caf.faces.data.task.impl.TaskInboxIndexedSearchContentProvider\$InboxSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskInboxSearchContentProvider\$InboxSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider</code>	Added <code>com.webmethods.portal.event.modify.IUpdateEvent\$ISynchronousListener</code> to the set of implemented interfaces
<code>com.webmethods.caf.mobile.notify.task.NotificationSender</code>	Added <code>java.util.concurrent.Callable</code> to the set of implemented interfaces
<code>com.webmethods.portal.mech.task.impl.TaskQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAll</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllByTagCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllByTagPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllGroupedCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxes</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesByTagCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesByTagPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesCount: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesGroupedCount: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesPaged: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.socialbpm.charts.SocialBPMSearchQuery: Added
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended to the set of implemented interfaces

com.webmethods.caf.faces.render.html.table.MoveRowDownIconRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowDownLinkRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowUpIconRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowUpLinkRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Added
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper to the list of superclasses

com.webmethods.caf.common.deployer.MwsDeployerConstants: Added public field
PROJ_PROP_EXPORT_PAGE_DEPTH

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field IOS_CERT

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_HOST_NAME

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_HOST_PORT

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_PASSWORD

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
NOTIFIER_QUEUE_SIZE_THRESHOLD

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Added protected field
m_connPoolProvider

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Added public field
IOS_JASON_PAYLOAD_TEMPLATE

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field
PROPERTY_HPSTRA_INDEXTABLEDIS

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field

PROPERTY_HPSTRA_INDEX_JOB_STATUS

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field
PROPERTY_ISHPSTRAENABLED

com.webmethods.portal.bizPolicy.command.task.rs.BaseTaskResource: Added public field
DEFAULT_JSON_DATE_FORMAT

com.webmethods.portal.service.bcgadget.IBCGadgetConstants: Added public field
BC_GADGET_DEF_CONTAINER_NOT_FOUND_ERROR_MSG

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field
ATTR_PREFIX_LENGTH

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field
EDIT_ATTR_CURRPASSWORD

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field USERNAME

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field exceptionMessage

com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Added public field
TE_MAX_LAST_ACTIVE

com.webmethods.portal.service.task.impl.TaskDefinitionView: Added protected field
m_taskDetailGadgetURIs

com.webmethods.caf.common.ObjectUtil: Method 'public void sortObjectList(java.util.List,
java.lang.String, boolean)' has been added

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Method 'public boolean
isPropagateEvents()' has been added

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Method 'public void
setPropagateEvents(boolean)' has been added

com.webmethods.caf.faces.component.tree.AsyncTree: Method 'protected
com.webmethods.caf.faces.data.ITableContentProvider getContentProvider(boolean)' has been added

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Method 'public java.lang.String
getSearchEngineType()' has been added

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Method 'public void
setSearchEngineType(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider: Method 'public void
onSynchronousEvent(com.webmethods.portal.event.modify.IUpdateEvent)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public
com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails
getM_iOSConnectionDetails()' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public
java.util.concurrent.BlockingQueue getMessageQueue()' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public java.util.List scheduleCleanUpService(java.util.List)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public void setMessageQueue(java.util.concurrent.BlockingQueue)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public void stopExecutorService()' has been added

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Method 'public java.lang.String createMessage(com.webmethods.portal.service.task.event.ITaskChangedEvent)' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public java.util.List getAndroidSubscriptionList()' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public java.util.List getIOSSubscriptionList()' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public void setAndroidSubscriptionList(java.util.List)' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public void setIOSSubscriptionList(java.util.List)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public java.util.List call()' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public java.lang.Object call()' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] convertPayloadtoUTF8Bytes(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] decodeHex(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] formAPNSMessage(byte, byte[], byte[])' has been added

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Method 'public java.lang.String generateIOSPayload(java.util.List, java.lang.String, java.lang.String)' has been added

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void includeBCScript(java.lang.String, java.util.Locale, java.io.Writer, boolean)' has been added

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void stripBCScript(java.io.Reader, java.io.Writer)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_sep_for_bc(int)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_unambiguous_sep_for_bc(int)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'public void stripBCScript(java.io.Reader, java.io.Writer)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected int strip_c_comment_for_bc(java.io.Reader, java.io.Writer)' has been added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable createHpstraIndexTableFromXml(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.task.rs.TaskResource: Method 'public void convertJSONToJavaObj(java.util.Map, java.lang.Class)' has been added

com.webmethods.portal.framework.presentation.handlers.Nbsp: Method 'public java.lang.Object lookup(java.util.Map, java.lang.String, boolean)' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalListView: Method 'public java.util.Map getExceptions()' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalListView: Method 'public void setExceptions(java.util.Map)' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalProvider: Method 'protected void populateGroupMembership(com.webmethods.portal.service.dir.IDirPrincipal, java.util.Set, java.util.Map)' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'protected void EditPrincipalEx()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public void EditUserEx()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public boolean isAuthenticated(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Method 'protected java.lang.String getConditionalInsertStatement()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable getHpstraIndexTable()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public java.lang.String getTaskDetailGadgetURIs()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public boolean isHpstraEnabled()' has been added

com.webmethods.portal.system.cluster.impl.ClusterProvider: Method 'public void reloadClusterServers()' has been added

com.webmethods.portal.webapp.jetty7.MwsSessionManager: Method 'protected void addContextLocale(org.eclipse.jetty.server.session.AbstractSession)' has been added

com.webmethods.rtl.event.DeliveryService: Method 'public boolean isConfigLoaded()' has been added

com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics\$NameComparator: Method 'public int compare(com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics, com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics)' has been added

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected boolean isMaintenanceMode()' has been added

com.webmethods.rtl.script.nbsp.NBSPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.NBSPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.Object get(java.lang.String, java.lang.Class, java.lang.Object, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails getM_iOSConnectionDetails()' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public java.util.concurrent.BlockingQueue getMessageQueue()' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public java.util.List scheduleCleanUpService(java.util.List)' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public void setMessageQueue(java.util.concurrent.BlockingQueue)' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public void stopExecutorService()' has been added to an interface

com.webmethods.common.search.ISliceableSearchContext: Method 'public java.util.Map getExceptions()' has been added to an interface

com.webmethods.portal.mech.task.ITaskMechanics: Method 'public void fireTaskReindexStopEvent(com.webmethods.portal.service.task.ITaskDefinition, java.lang.String)' has been added to an interface

com.webmethods.portal.service.dir.IDirPrincipalList: Method 'public java.util.Map getExceptions()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable getHpstraIndexTable()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public java.lang.String

getTaskDetailGadgetURIs()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public boolean isHpstraEnabled()' has been added to an interface

com.webmethods.portal.service.task.ITaskDistributionService: Method 'public java.util.List getPrincipalActors(com.webmethods.portal.system.IURI[], boolean)' has been added to an interface

com.webmethods.portal.service.task.event.ITaskReindexStopEvent: Method 'public java.lang.String getIndexEngineType()' has been added to an interface

com.webmethods.portal.system.cluster.IClusterProvider: Method 'public void reloadClusterServers()' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPRuntime: Method 'public java.lang.Object lookup(java.util.Map, java.lang.String, boolean)' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added to an interface

com.softwareag.mws.screens.BaseScreenClass: Class com.softwareag.mws.screens.BaseScreenClass added

com.softwareag.mws.screens.Constants: Class com.softwareag.mws.screens.Constants added

com.softwareag.mws.screens.MWSLoginLogoutScreen: Class
com.softwareag.mws.screens.MWSLoginLogoutScreen added

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen: Class

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen added

com.webmethods.caf.faces.data.task.AggregationType: Class
com.webmethods.caf.faces.data.task.AggregationType added

com.webmethods.caf.faces.data.task.IQueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.IQueryAggregationInfo added

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Class
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended added

com.webmethods.caf.faces.data.task.IndexEngineType: Class
com.webmethods.caf.faces.data.task.IndexEngineType added

com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo added

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider: Class
com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider added

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearch
Query: Class
com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearch
Query added

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Class
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended added

com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer: Class
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer added

com.webmethods.caf.mobile.notify.impl.PushNotification: Class
com.webmethods.caf.mobile.notify.impl.PushNotification added

com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean: Class
com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean added

com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpEvent: Class
com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpEvent added

com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpHandler: Class
com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpHandler added

com.webmethods.caf.mobile.notify.task.APNSCleanUpThread: Class
com.webmethods.caf.mobile.notify.task.APNSCleanUpThread added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper\$DBIndexer: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper\$DBIndexer added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper\$Indexer: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper\$Indexer added

com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean added

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus added

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus\$StatusInfo: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus\$StatusInfo added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource: Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$Product: Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$Product added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$ProductHolder:
Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$ProductHolder

added

com.webmethods.portal.jms.um.QueueType: Class com.webmethods.portal.jms.um.QueueType added

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable: Class

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable added

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable\$DisplayField: Class

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable\$DisplayField added

com.webmethods.portal.service.sql.runtime.base.TaskPendingUpdatesCleanup: Class

com.webmethods.portal.service.sql.runtime.base.TaskPendingUpdatesCleanup added

com.webmethods.portal.service.sql.runtime.db2.TaskLockSetNew: Class

com.webmethods.portal.service.sql.runtime.db2.TaskLockSetNew added

com.webmethods.portal.service.sql.runtime.db2.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.db2.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.mssql.ThingNewPar: Class

com.webmethods.portal.service.sql.runtime.mssql.ThingNewPar added

com.webmethods.portal.service.sql.runtime.mssql.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.mssql.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.mysql.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.mysql.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.oracle.TaskLockSetNew: Class

com.webmethods.portal.service.sql.runtime.oracle.TaskLockSetNew added

com.webmethods.portal.service.sql.runtime.oracle.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.oracle.UpdateThingCounter added

com.webmethods.portal.service.task.ITaskIndexEngineConfiguration: Class

com.webmethods.portal.service.task.ITaskIndexEngineConfiguration added

com.webmethods.portal.service.task.ITaskIndexManager: Class

com.webmethods.portal.service.task.ITaskIndexManager added

com.webmethods.portal.service.task.ITaskInfoFieldConverters: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$AcceptedByListValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$AcceptedByListValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$CurrentUserValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$CurrentUserValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$DateValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$DateValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$PriorityValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$PriorityValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$StatusValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$StatusValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskIDValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskIDValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskTypeIDValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskTypeIDValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$URIValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$URIValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$UserValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$UserValueConverter added

com.webmethods.portal.service.task.SearchContext: Class
com.webmethods.portal.service.task.SearchContext added

com.webmethods.portal.service.task.SearchKey: Class com.webmethods.portal.service.task.SearchKey
added

com.webmethods.portal.service.task.SearchKey\$TE_SearchKeys: Class
com.webmethods.portal.service.task.SearchKey\$TE_SearchKeys added

com.webmethods.portal.service.task.TaskIndexEngineFactory: Class
com.webmethods.portal.service.task.TaskIndexEngineFactory added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$DistributionChangeType:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$DistributionChangeType
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$IListener: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$IListener added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$ISynchronousListener:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$ISynchronousListener
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$Listeners: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$Listeners added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners\$SynchronousListener: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners\$SynchronousListener added

com.webmethods.portal.service.task.event.impl.TaskDistributionChangedEvent: Class
com.webmethods.portal.service.task.event.impl.TaskDistributionChangedEvent added

com.webmethods.portal.service.task.event.impl.TaskReindexStopEvent: Class
com.webmethods.portal.service.task.event.impl.TaskReindexStopEvent added

com.webmethods.portal.service.task.impl.TaskDBIndexConfiguration: Class
com.webmethods.portal.service.task.impl.TaskDBIndexConfiguration added

com.webmethods.portal.system.cluster.impl.ClusterNodeRegisteredNotifier: Class
com.webmethods.portal.system.cluster.impl.ClusterNodeRegisteredNotifier added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool: Class
com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager: Class
com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionProvider: Class
com.webmethods.pushNotification.apns.connection.pool.APNSConnectionProvider added

com.webmethods.pushNotification.apns.connection.pool.APNSPoolableConnection: Class
com.webmethods.pushNotification.apns.connection.pool.APNSPoolableConnection added

com.webmethods.pushNotification.apns.connection.pool.IConnectionProvider: Class
com.webmethods.pushNotification.apns.connection.pool.IConnectionProvider added

com.webmethods.pushNotification.apns.connection.pool.IPoolableConnection: Class
com.webmethods.pushNotification.apns.connection.pool.IPoolableConnection added

Removed API**Replacement, if any**

com.webmethods.caf.mobile.notify.task.NotificationSender: Removed java.lang.Runnable from the set of implemented interfaces

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_ACCEPTED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_CANCELLED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_COMPLETED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_EXPIRED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_FAILED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_QUEUED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_REASSIGNED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_RELEASED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_RESUMED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_SUSPENDED

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Removed field reindexAllTaskExecutor

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Removed field reindexingTasks

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field USE_LIGHT_WEIGHT_EVENTS

Deprecated API**Replacement, if any**

com.webmethods.portal.service.task.impl.TaskDistributionService: Method 'public java.util.List getPrincipalActors(com.webmethods.portal.system.IURI[], boolean)' has been deprecated

com.webmethods.portal.service.task.impl.TaskDistributionService: Method 'protected java.util.List returnPagedTaskList(java.lang.String, java.lang.Object[], boolean)' has been deprecated

Changed API**Description**

com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails: Increased visibility of class from package to public

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Value of compile-time constant ANDROID_JASON_PAYLOAD_TEMPLATE has been changed

com.webmethods.caf.faces.bean.BaseFacesBean: Accessibility of field EMPTY_RESOURCES has been increased from package to public

com.webmethods.caf.mobile.notify.task.NotificationSender: In method 'public NotificationSender(java.util.concurrent.BlockingQueue, com.sun.jersey.api.client.WebResource\$Builder)' the number of arguments has changed

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: In method 'public com.webmethods.caf.mobile.notify.task.Message generatePayload(java.util.List, java.lang.String, java.lang.String)' the number of arguments has changed

com.webmethods.portal.jms.um.UmJMSClient: In method 'protected void createQueue(java.lang.String, boolean, int)' the number of arguments has changed

com.webmethods.portal.jms.um.UmJMSClient: In method 'protected void createTopic(java.lang.String, boolean, int)' the number of arguments has changed

com.webmethods.portal.mech.task.impl.TaskMechanics: In method 'public void fireTaskReindexStopEvent(com.webmethods.portal.service.task.ITaskDefinition)' the number of arguments has changed

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Return type of method 'public com.webmethods.caf.mobile.notify.task.Message generateAndroidPayload(java.util.List, java.lang.String, java.lang.String)' has been changed to java.lang.String

com.webmethods.portal.jms.db.DbJMSConnProvider: Accessibility of method 'public DbJMSConnProvider()' has been decreased from public to private

Release 9.12**Added API****Description**

com.webmethods.caf.common.thread.NamedThreadFactory: Method 'public NamedThreadFactory(java.lang.String, boolean)' has been added

com.webmethods.caf.faces.bean.mws_ui.HtmlHead: Method 'public java.lang.String getEffectsJS()' has been added

com.webmethods.caf.faces.convert.FormattedDateTimeConverter: Added protected field dateFormatDefault

com.webmethods.caf.faces.data.object.DateRange: Added protected field controlCalendar

Added API	Description
com.webmethods.caf.faces.data.object.DateRange:	Method 'protected java.util.Calendar getControlCalendar(javax.faces.context.FacesContext)' has been added
com.webmethods.caf.faces.data.object.DateRange:	Method 'public void setControlCalendar(java.util.Calendar)' has been added
com.webmethods.caf.mobile.notify.IMobileNotificationConstants:	Class com.webmethods.caf.mobile.notify.IMobileNotificationConstants added
com.webmethods.caf.mobile.notify.IMobileNotificationProvider:	Class com.webmethods.caf.mobile.notify.IMobileNotificationProvider added
com.webmethods.caf.mobile.notify.IMobileNotifierComponent:	Class com.webmethods.caf.mobile.notify.IMobileNotifierComponent added
com.webmethods.caf.mobile.notify.activator.MobileNotificationActivator:	Class com.webmethods.caf.mobile.notify.activator.MobileNotificationActivator added
com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider:	Class com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider added
com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent:	Class com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent added
com.webmethods.caf.mobile.notify.impl.TaskEventsHandler:	Class com.webmethods.caf.mobile.notify.impl.TaskEventsHandler added
com.webmethods.caf.mobile.notify.task.Message:	Class com.webmethods.caf.mobile.notify.task.Message added
com.webmethods.caf.mobile.notify.task.MonitorPendingNotificationMessages:	Class com.webmethods.caf.mobile.notify.task.MonitorPendingNotificationMessages added
com.webmethods.caf.mobile.notify.task.NotificationSender:	Class com.webmethods.caf.mobile.notify.task.NotificationSender added
com.webmethods.caf.mobile.notify.util.MobileNotifierUtil:	Class com.webmethods.caf.mobile.notify.util.MobileNotifierUtil added
com.webmethods.caf.wssserver.auth.saml.SamlUtils:	Method 'public org.w3c.dom.Element marshalSamlObject(org.opensaml.xml.XMLObject)' has been added
com.webmethods.caf.wssserver.auth.saml.SamlUtils:	Method 'public org.opensaml.xml.XMLObject unmarshalElement(org.w3c.dom.Element)' has been added
com.webmethods.portal.bizPolicy.biz.dir.IGroupBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces
com.webmethods.portal.bizPolicy.biz.dir.IPrincipalBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented

Added API**Description**

interfaces

com.webmethods.portal.bizPolicy.biz.dir.IUserBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.dir.impl.GroupBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.dir.impl.GroupBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses

com.webmethods.portal.bizPolicy.biz.dir.impl.PrincipalBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.dir.impl.PrincipalBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses

com.webmethods.portal.bizPolicy.biz.dir.impl.UserBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.dir.impl.UserBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses

com.webmethods.portal.bizPolicy.biz.task.impl.TaskInfo: Added java.io.Serializable to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.task.impl.TaskInfoExtended: Added java.io.Serializable to the set of implemented interfaces

com.webmethods.portal.bizPolicy.command.ICommandManager: Method 'public
com.webmethods.portal.bizPolicy.command.IRemoteCommandTransport
getRemoteCommandTransport(java.lang.String)' has been added to an interface

com.webmethods.portal.bizPolicy.command.ICommandManager: Method 'public java.util.List
invokeClusterCommand(com.webmethods.portal.bizPolicy.IContext,

com.webmethods.portal.bizPolicy.command.ICommand,
com.webmethods.portal.bizPolicy.command.ICommandBean)' has been added to an interface

com.webmethods.portal.bizPolicy.command.ICommandResponseEntry: Class

com.webmethods.portal.bizPolicy.command.ICommandResponseEntry added

com.webmethods.portal.bizPolicy.command.dir.GetPortalStyle: Method 'protected void
checkAccess(com.webmethods.portal.bizPolicy.IContext,

com.webmethods.portal.mech.dir.IPrincipalMechanics, com.webmethods.portal.system.IURI)' has been added

Added API**Description**

com.webmethods.portal.bizPolicy.command.dir.SearchDirectory: Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryEx: Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryRefined: Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryRefinedPaged: Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandManager: Method 'public com.webmethods.portal.bizPolicy.command.IRemoteCommandTransport getRemoteCommandTransport(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandManager: Method 'public java.util.List invokeClusterCommand(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.bizPolicy.command.ICommand, com.webmethods.portal.bizPolicy.command.ICommandBean)' has been added

com.webmethods.portal.bizPolicy.command.remote.RemoteCommand: Class
com.webmethods.portal.bizPolicy.command.remote.RemoteCommand added

com.webmethods.portal.bizPolicy.command.remote.RemoteCommandBean: Class
com.webmethods.portal.bizPolicy.command.remote.RemoteCommandBean added

com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport: Class
com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport added

com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport\$RemoteJmsException: Class

com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport\$RemoteJmsException added

com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteTransaction: Class
com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteTransaction added

Added API**Description**

com.webmethods.portal.bizPolicy.command.system.JndiRefreshCluster: Class
com.webmethods.portal.bizPolicy.command.system.JndiRefreshCluster added

com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommand: Class
com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommand added

com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommandBean: Class
com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommandBean added

com.webmethods.portal.bizPolicy.command.task.jms.AddTaskAttachmentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.AddTaskAttachmentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.AddTaskCommentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.AddTaskCommentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskAttachmentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskAttachmentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskCommentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskCommentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAttachmentsJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAttachmentsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAuditJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAuditJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskCommentsJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.GetTaskCommentsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.GetTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.QueueTaskJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.QueueTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksFieldsJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksFieldsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksPagedJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksPagedJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksTotalCountJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksTotalCountJMS added

com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskAttachmentJMS: Class

Added API	Description
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskAttachmentJMS	added
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskCommentJMS	Class
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskCommentJMS	added
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskJMS	Class
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskJMS	added
com.webmethods.portal.bizPolicy.command.task.jms.impl.TaskJMSUtils	Class
com.webmethods.portal.bizPolicy.command.task.jms.impl.TaskJMSUtils	added
com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider	Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider	added
com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher	Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher	added
com.webmethods.portal.bizPolicy.command.task.webservice.SearchTasksFieldsWS	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.task.webservice.SearchTasksWS	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.task.webservice.Task	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.task.webservice.dotnet.SearchTasksDotNetWS	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.task.webservice.dotnet.SearchTasksFieldsDotNetWS	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.impl.upgrade.MoveVersionSystemComponentData	Class
com.webmethods.portal.bizPolicy.impl.upgrade.MoveVersionSystemComponentData	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ILListener	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ILListener	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ISynchronousListener	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ISynchronousListener	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$Listeners	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$Listeners	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$QueueListeners	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$QueueListeners	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$SynchronousListeners	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$SynchronousListeners	added

Added API	Description
com.webmethods.portal.event.dir.impl.DirPrincipalDNUpdateEvent: Class com.webmethods.portal.event.dir.impl.DirPrincipalDNUpdateEvent added	
com.webmethods.portal.event.sso.ISSODataChangeEvent: Class com.webmethods.portal.event.sso.ISSODataChangeEvent added	
com.webmethods.portal.event.sso.ISSODataChangeEvent\$IListener: Class com.webmethods.portal.event.sso.ISSODataChangeEvent\$IListener added	
com.webmethods.portal.event.sso.ISSODataChangeEvent\$ISynchronousListener: Class com.webmethods.portal.event.sso.ISSODataChangeEvent\$ISynchronousListener added	
com.webmethods.portal.event.sso.ISSODataChangeEvent\$Listeners: Class com.webmethods.portal.event.sso.ISSODataChangeEvent\$Listeners added	
com.webmethods.portal.event.sso.ISSODataChangeEvent\$QueueListeners: Class com.webmethods.portal.event.sso.ISSODataChangeEvent\$QueueListeners added	
com.webmethods.portal.event.sso.ISSODataChangeEvent\$SynchronousListeners: Class com.webmethods.portal.event.sso.ISSODataChangeEvent\$SynchronousListeners added	
com.webmethods.portal.event.sso.impl.SSODataChangeEvent: Class com.webmethods.portal.event.sso.impl.SSODataChangeEvent added	
com.webmethods.portal.framework.dispatch.handlers.system.SAMLSSOHandler: Class com.webmethods.portal.framework.dispatch.handlers.system.SAMLSSOHandler added	
com.webmethods.portal.framework.dispatch.preProcessors.OpenRedirectCheck: Class com.webmethods.portal.framework.dispatch.preProcessors.OpenRedirectCheck added	
com.webmethods.portal.framework.dispatch.resolvers.SAMLAuthReqResolver: Class com.webmethods.portal.framework.dispatch.resolvers.SAMLAuthReqResolver added	
com.webmethods.portal.framework.impl.PortalServlet: Added public field PORTAL_SERVLET_LOCK_OBJ	
com.webmethods.portal.framework.portletcontainer.servlet.JettyPortletRequestWrapper: Method 'public org.eclipse.jetty.util.MultiMap getParameterMultiMap()' has been added	
com.webmethods.portal.framework.portletcontainer.servlet.JettyPortletRequestWrapper: Method 'public java.util.Map getParameters()' has been added	
com.webmethods.portal.jms.JMSPhaseProvider: Added com.webmethods.portal.system.IComponent to the set of implemented interfaces	
com.webmethods.portal.jms.JMSPhaseProvider: Added com.webmethods.portal.system.IConstants to the set of implemented interfaces	
com.webmethods.portal.jms.JMSPhaseProvider: Added com.webmethods.portal.system.impl.BaseComponent to the list of superclasses	
com.webmethods.portal.jms.JMSPhaseProvider: Added public field COMPONENT_NAME	

Added API	Description
com.webmethods.portal.jms.um.UmJMSSClient:	Added abstract modifier to class
com.webmethods.portal.jms.um.UmJMSSClient:	Added
com.webmethods.portal.system.init.IInitializable	to the set of implemented interfaces
com.webmethods.portal.jms.um.UmJMSSClient:	Added com.webmethods.rtl.msg.jms.IJMSPProvider to the set of implemented interfaces
com.webmethods.portal.jms.um.UmJMSSClient:	Added com.webmethods.rtl.msg.jms.JMSPProvider to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSClient:	Added
com.webmethods.rtl.msg.jms.JMSStdConnProvider	to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected boolean createInitialContext()' has been added
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected void registerFactory(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected void registerQueue(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected void registerTopic(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected void resetContext()' has been added
com.webmethods.portal.jms.um.UmJMSSConnProvider:	Added
com.webmethods.portal.jms.um.UmJMSSClient	to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSConnProvider:	Method 'protected void onDisconnect(boolean)' has been added
com.webmethods.portal.jms.um.UmJMSSConnProvider:	Method 'public void onShutdown()' has been added
com.webmethods.portal.mech.dir.IDirServiceMechanics:	Method 'public java.util.List updatePrincipalUUID(int)' has been added to an interface
com.webmethods.portal.mech.dir.IGroupMechanics:	Added
com.webmethods.portal.mech.view.IViewableContainerMechanics	to the set of implemented interfaces
com.webmethods.portal.mech.dir.IPrincipalMechanics:	Added
com.webmethods.portal.mech.view.IViewableContainerMechanics	to the set of implemented interfaces
com.webmethods.portal.mech.dir.IRoleMechanics:	Added
com.webmethods.portal.mech.view.IViewableContainerMechanics	to the set of implemented interfaces
com.webmethods.portal.mech.dir.IUserMechanics:	Added
com.webmethods.portal.mech.view.IViewableContainerMechanics	to the set of implemented interfaces
com.webmethods.portal.mech.dir.impl.DirMechanicsUtils:	Method 'public java.lang.String

Added API**Description**

generateUUIDQuery(com.webmethods.portal.service.dir.IDirService, java.lang.String, int)' has been added

com.webmethods.portal.mech.dir.impl.DirServiceMechanics: Method 'public java.util.List updatePrincipalUUID(int)' has been added

com.webmethods.portal.mech.dir.impl.GroupMechanics: Added
com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces

com.webmethods.portal.mech.dir.impl.GroupMechanics: Added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses

com.webmethods.portal.mech.dir.impl.PrincipalMechanics: Added
com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces

com.webmethods.portal.mech.dir.impl.PrincipalMechanics: Added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses

com.webmethods.portal.mech.dir.impl.RoleMechanics: Added
com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces

com.webmethods.portal.mech.dir.impl.RoleMechanics: Added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses

com.webmethods.portal.mech.dir.impl.UserMechanics: Added
com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces

com.webmethods.portal.mech.dir.impl.UserMechanics: Added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses

com.webmethods.portal.mech.task.impl.RefreshTaskHandler: Class
com.webmethods.portal.mech.task.impl.RefreshTaskHandler added

com.webmethods.portal.mech.task.impl.TaskHelper: Method 'public java.lang.ClassLoader getClassLoaderIfExists(com.webmethods.portal.service.task.ITaskDefinition)' has been added

com.webmethods.portal.mech.view.impl.ViewableContainerMechanics: Method 'protected
com.webmethods.portal.service.view.IPagingCookie
createPagingCookie(com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.service.access.IAccessPrivilegeConfiguration: Class
com.webmethods.portal.service.access.IAccessPrivilegeConfiguration added

com.webmethods.portal.service.access.impl.DashboardAclManager: Class
com.webmethods.portal.service.access.impl.DashboardAclManager added

com.webmethods.portal.service.access.impl.DashboardAclManager\$DashboardAclResource: Class
com.webmethods.portal.service.access.impl.DashboardAclManager\$DashboardAclResource added

com.webmethods.portal.service.access.impl.DashboardContainerAclManager: Class
com.webmethods.portal.service.access.impl.DashboardContainerAclManager added

Added API	Description
com.webmethods.portal.service.access.impl.DashboardContainerAclManager\$DashboardContainerAclResource: Class	
com.webmethods.portal.service.access.impl.DashboardContainerAclManager\$DashboardContainerAclResource added	
com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'public java.util.Map getResultColumnMetadata()' has been added	
com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'public java.util.List searchResources(com.webmethods.caf.faces.search.query.ISearchQuery)' has been added	
com.webmethods.portal.service.access.impl.GadgetsAclManager\$GadgetAclResource: Method 'public java.lang.Object getValue(java.lang.Object)' has been added	
com.webmethods.portal.service.access.impl.WMAppsAclManager: Method 'public void addServiceTracker(org.osgi.framework.BundleContext)' has been added	
com.webmethods.portal.service.access.impl.WMAppsAclManager: Method 'public void stopServiceTracker()' has been added	
com.webmethods.portal.service.cache.impl.AliasCache: Added	com.webmethods.portal.event.remove.IDeleteEvent\$ISynchronousListener to the set of implemented interfaces
com.webmethods.portal.service.cache.impl.AliasCache: Method 'public void onSynchronousEvent(com.webmethods.portal.event.remove.IDeleteEvent)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Added public field UUIDUserResolution	
com.webmethods.portal.service.dir.DirectoryTools: Added protected field UUID_CONFIG	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public com.webmethods.portal.service.dir.IDirService getDirectoryService(com.webmethods.portal.system.IURI)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.util.List getEmptyUUIDUsers()' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.lang.Boolean getUUIDResolution()' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.lang.String getUserDNFromUserUUID(java.lang.String, com.webmethods.portal.service.meta2.IUserService)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public void invalidateGroupRoleCache(com.webmethods.portal.service.meta2.thing.IThingID)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public com.webmethods.portal.service.meta2.thing.IThingID	

Added API	Description
	resolveUserByUUID(com.webmethods.portal.service.dir.init.IInitializableUser)' has been added
	com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.util.List updatePrincipalUUID()' has been added
	com.webmethods.portal.service.dir.IDirConstants: Added public field USER_UUID
	com.webmethods.portal.service.dir.IDirQueryProvider: Method 'public com.webmethods.portal.service.dir.IDirPrincipal lookupByUUID(int, java.lang.String)' has been added to an interface
	com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public boolean isSirNameFirst(com.webmethods.portal.bizPolicy.IContext)' has been added
	com.webmethods.portal.service.dir.init.IInitializablePrincipal: Method 'public java.lang.String getUUID()' has been added to an interface
	com.webmethods.portal.service.dir.init.impl.InitializablePrincipal: Method 'public java.lang.String getUUID()' has been added
	com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.List getEmptyUUIDUsers()' has been added to an interface
	com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.Map getUserDetailsByURI(com.webmethods.portal.system.IURI)' has been added to an interface
	com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.Map getUserDetailsByUUID(java.lang.String)' has been added to an interface
	com.webmethods.portal.service.meta2.IUserService: Method 'public void invalidateUserUUID()' has been added to an interface
	com.webmethods.portal.service.meta2.IUserService: Method 'public void updateDistinguishedName(java.lang.String, java.lang.String, int)' has been added to an interface
	com.webmethods.portal.service.meta2.IUserService: Method 'public void updateUUID(java.lang.String, java.lang.String, int)' has been added to an interface
	com.webmethods.portal.service.meta2.directory.IUserInfo: Method 'public java.lang.String getUUID()' has been added to an interface
	com.webmethods.portal.service.meta2.directory.impl.User: Method 'public java.lang.String getUUID()' has been added
	com.webmethods.portal.service.meta2.directory.impl.UserInfo: Added protected field uuid
	com.webmethods.portal.service.meta2.directory.impl.UserInfo: Method 'public java.lang.String getUUID()' has been added
	com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.List getEmptyUUIDUsers()' has been added
	com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.Map

Added API	Description
getUserDetailsByURI(com.webmethods.portal.system.IURI)	' has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.Map getUserDetailsByUUID(java.lang.String)'	' has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void invalidateUserUUID()'	' has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void updateDistinguishedName(java.lang.String, java.lang.String, int)'	' has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void updateUUID(java.lang.String, java.lang.String, int)'	' has been added
com.webmethods.portal.service.socialbpm.chart.impl.ChartData: Method 'public java.lang.String getTaskTypeID()'	' has been added
com.webmethods.portal.service.socialbpm.chart.impl.ChartData: Method 'public void setTaskTypeID(java.lang.String)'	' has been added
com.webmethods.portal.service.socialbpm.chart.impl.ChartService: Method 'protected java.lang.String getTaskTypeID(java.lang.String)'	' has been added
com.webmethods.portal.service.sql.runtime.base.EmptyUUIDUserList: Class	com.webmethods.portal.service.sql.runtime.base.EmptyUUIDUserList added
com.webmethods.portal.service.sql.runtime.base.InvalidateUserUUID: Class	com.webmethods.portal.service.sql.runtime.base.InvalidateUserUUID added
com.webmethods.portal.service.sql.runtime.base.SetUserGroupUUID: Class	com.webmethods.portal.service.sql.runtime.base.SetUserGroupUUID added
com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Class	com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew added
com.webmethods.portal.service.sql.runtime.base.UserDetailsByURI: Class	com.webmethods.portal.service.sql.runtime.base.UserDetailsByURI added
com.webmethods.portal.service.sql.runtime.base.UserDetailsByUUID: Class	com.webmethods.portal.service.sql.runtime.base.UserDetailsByUUID added
com.webmethods.portal.service.task.ITaskLockingService: Method 'public com.webmethods.portal.service.task.ITaskLock acquireLock(com.webmethods.portal.system.IURI,	com.webmethods.portal.system.IURI, long, long, boolean)'
com.webmethods.portal.service.task.event.RefreshTaskEvent: Class	com.webmethods.portal.service.task.event.RefreshTaskEvent added
com.webmethods.portal.service.task.event.RefreshTaskEvent\$ISynchronousListener: Class	com.webmethods.portal.service.task.event.RefreshTaskEvent\$ISynchronousListener added
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners: Class	

Added API	Description
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners	added
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners\$SynchronousListener	Class
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners\$SynchronousListener	added
com.webmethods.portal.service.task.event.TaskChangedEventRetry	Class
com.webmethods.portal.service.task.event.TaskChangedEventRetry	added
com.webmethods.portal.service.task.event.impl.RefreshTaskEvent	Class
com.webmethods.portal.service.task.event.impl.RefreshTaskEvent	added
com.webmethods.portal.service.task.impl.TaskLockingService	Method 'public
com.webmethods.portal.service.task.ITaskLock	acquireLock(com.webmethods.portal.system.IURI,
com.webmethods.portal.system.IURI, long, long, boolean)'	has been added
com.webmethods.portal.system.ISAMLSSOConstants	Class
com.webmethods.portal.system.ISAMLSSOConstants	added
com.webmethods.portal.system.cluster.IClusterProvider	Method 'public java.lang.String
getClusterId()'	has been added to an interface
com.webmethods.portal.system.cluster.IClusterProvider	Method 'public boolean
isCurrentServer(com.webmethods.portal.system.cluster.IServer)'	has been added to an interface
com.webmethods.portal.system.cluster.IClusterProvider	Method 'public void
recreateJNDIConnection()'	has been added to an interface
com.webmethods.portal.system.cluster.IClusterProvider	Method 'public boolean
reloadJNDIProviderURL()'	has been added to an interface
com.webmethods.portal.system.cluster.impl.ClusterProvider	Added public field
CLUSTER_ID_PROP_KEY	
com.webmethods.portal.system.cluster.impl.ClusterProvider	Added public field s_logCategory
com.webmethods.portal.system.cluster.impl.ClusterProvider	Method 'public java.lang.String
getClusterId()'	has been added
com.webmethods.portal.system.cluster.impl.ClusterProvider	Method 'public boolean
isCurrentServer(com.webmethods.portal.system.cluster.IServer)'	has been added
com.webmethods.portal.system.cluster.impl.ClusterProvider	Method 'public void
recreateJNDIConnection()'	has been added
com.webmethods.portal.system.cluster.impl.ClusterProvider	Method 'public boolean
reloadJNDIProviderURL()'	has been added
com.webmethods.portal.system.sso.saml.idp.SAMLIdentityProvider	Class
com.webmethods.portal.system.sso.saml.idp.SAMLIdentityProvider	added

Added API	Description
com.webmethods.portal.system.sso.saml.idp.SAMLSSODataChangeListener: Class com.webmethods.portal.system.sso.saml.idp.SAMLSSODataChangeListener added	
com.webmethods.portal.system.sso.saml.idp.SAMLServiceProvider: Class com.webmethods.portal.system.sso.saml.idp.SAMLServiceProvider added	
com.webmethods.portal.system.sso.saml.idp.SSOIDPConfiguration: Class com.webmethods.portal.system.sso.saml.idp.SSOIDPConfiguration added	
com.webmethods.portal.system.sso.saml.idp.WebSSOPropsUtil: Class com.webmethods.portal.system.sso.saml.idp.WebSSOPropsUtil added	
com.webmethods.portal.taglib.TaglibUtil: Method 'public java.lang.String generateUniqueID()' has been added	
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory: Method 'public org.opensaml.saml2.core.AuthnRequest getAuthnRequest(java.lang.String)' has been added	
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory: Method 'public java.lang.String getResponse(java.net.URL, java.lang.String, java.util.Map, java.lang.String[], java.util.Map, org.opensaml.saml2.core.AuthnRequest)' has been added	
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory: Method 'public void reInitSecurityTokenService()' has been added	
com.webmethods.rtl.event.DeliveryService: Method 'public java.lang.String addClusterIdPrefix(java.lang.String)' has been added	
com.webmethods.rtl.event.DeliveryService: Method 'public void setClusterId(java.lang.String)' has been added	
com.webmethods.rtl.event.DeliveryService: Method 'public void startRemoteDelivery()' has been added	
com.webmethods.rtl.event.DeliveryService: Method 'public void stopRemoteDelivery()' has been added	
com.webmethods.rtl.event.Event: Method 'public java.lang.String getJcrSessionUserData()' has been added	
com.webmethods.rtl.event.IEvent: Method 'public java.lang.String getJcrSessionUserData()' has been added to an interface	
com.webmethods.rtl.jms.PortalClientOverJMS: Class com.webmethods.rtl.jms.PortalClientOverJMS added	
com.webmethods.rtl.logging.EnhancedPatternLayout: Class com.webmethods.rtl.logging.EnhancedPatternLayout added	
com.webmethods.rtl.msg.jms.IJMSPProvider: Method 'public java.lang.String getEndpointAddress()' has been added to an interface	

Added API	Description
com.webmethods.rtl.msg.jms.IJMSPProvider:	Method 'public boolean isConnected()' has been added to an interface
com.webmethods.rtl.msg.jms.JMSPProvider:	Added protected field m_endpointAddress
com.webmethods.rtl.msg.jms.JMSPProvider:	Added protected field m_isConnected
com.webmethods.rtl.msg.jms.JMSPProvider:	Method 'public java.lang.String getEndpointAddress()' has been added
com.webmethods.rtl.msg.jms.JMSPProvider:	Method 'public boolean isConnected()' has been added
com.webmethods.rtl.msg.jms.JMSPProvider:	Abstract method 'protected void stopConnections()' has been added
com.webmethods.rtl.msg.jms.JMSStdConnProvider:	Method 'protected void stopConnections()' has been added
com.webmethods.rtl.script.JspC:	Method 'public java.lang.String getExcludes()' has been added
com.webmethods.rtl.script.JspC:	Method 'public void setExcludes(java.lang.String)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'protected org.w3c.dom.Document _loadDocumentUncaught(org.xml.sax.InputSource)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromInputStreamUncaught(java.io.InputStream)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromReaderUncaught(java.io.Reader)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromXMLUncaught(java.lang.String)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentUncaught(java.lang.String)' has been added

Removed API	Replacement, if any
com.webmethods.caf.jcr.rmi.IRMITunnelHttpPortAware:	Class com.webmethods.caf.jcr.rmi.IRMITunnelHttpPortAware removed
com.webmethods.caf.jcr.rmi.JcrRMIHttpToCGISocketFactory:	Class com.webmethods.caf.jcr.rmi.JcrRMIHttpToCGISocketFactory removed
com.webmethods.caf.jcr.rmi.JcrRMIMasterSocketFactory:	Class com.webmethods.caf.jcr.rmi.JcrRMIMasterSocketFactory removed
com.webmethods.jackrabbit.server.io.DefaultHandler:	Class com.webmethods.jackrabbit.server.io.DefaultHandler removed

Removed API**Replacement, if any**

com.webmethods.jackrabbit.servlet.JCRWebdavServerServlet: Class
com.webmethods.jackrabbit.servlet.JCRWebdavServerServlet removed

com.webmethods.jackrabbit.servlet.SimpleWebdavServlet: Class
com.webmethods.jackrabbit.servlet.SimpleWebdavServlet removed

com.webmethods.portal.jms.um.UmJMSClient: Field DEFAULT_UM_REALM has been removed, but it was previously a constant

com.webmethods.portal.jms.um.UmJMSClient: Method 'public void init()' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Removed field gadgetExternalScripts

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Method 'public
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts
getGadgetExternalScripts()' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Method 'public void
setGadgetExternalScripts(com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternal
Scripts)' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts: Class
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts removed

com.webmethods.portal.schema.bcgadget.ObjectFactory: Method 'public
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts
createGadgetDefinitionGadgetExternalScripts()' has been removed

com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'protected java.lang.String
buildXPathQuery(java.util.Map)' has been removed, but an inherited definition exists.

com.webmethods.portal.service.access.impl.GadgetsAclManager\$GadgetAclResource: Method 'public
GadgetsAclManager\$GadgetAclResource(javax.jcr.Node, java.lang.String)' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'public void enableMessageDelivery()' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'public boolean hasInitialized()' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected void
setInstance(com.webmethods.rtl.msg.jms.JMSProvider)' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected void startConnections()' has been removed

com.webmethods.rtl.msg.jms.JMSStdConnProvider: Method 'protected void startConnections()' has been removed

Changed API**Description**

com.webmethods.caf.common.bnd.PortletXmlAnalyzer: Parameter 1 of 'public boolean analyzeJar(aQute.lib.osgi.Analyzer)' has changed its type to aQute.bnd.osgi.Analyzer

com.webmethods.caf.common.bnd.WebXmlAnalyzer: Parameter 1 of 'public boolean analyzeJar(aQute.lib.osgi.Analyzer)' has changed its type to aQute.bnd.osgi.Analyzer

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 2 of 'public void displayAssertion(java.io.PrintWriter, org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public java.lang.String getLoginName(org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLAssertion getSamlAssertion(java.lang.String, java.lang.String)' has been changed to org.opensaml.saml1.core.Assertion

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public org.opensaml.SAMLAssertion getSamlAssertion(org.opensaml.SAMLResponse)' has changed its type to org.opensaml.saml1.core.Response

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLAssertion getSamlAssertion(org.opensaml.SAMLResponse)' has been changed to org.opensaml.saml1.core.Assertion

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLResponse getSamlResponse(java.lang.String, java.lang.String)' has been changed to org.opensaml.saml1.core.Response

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public java.lang.String verifyAssertion(org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public UmJMSClient()' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void closeUMSession(com.pcbSYS.nirvana.client.nSession)' has been decreased from public to private

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createConnectionFactory(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Return type of method 'public javax.naming.Context createJNDIContext()' has been changed to void

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public javax.naming.Context createJNDIContext()' has been decreased from public to private

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void

Changed API**Description**

`createQueue(java.lang.String, boolean, int)` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void createQueueConnectionFactory(java.lang.String)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void createStringVal(java.lang.String, java.lang.String)'` has been decreased from public to package

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void createTopic(java.lang.String, boolean, int)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void createTopicConnectionFactory(java.lang.String)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void createXAConnectionFactory(java.lang.String)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void deleteConnectionFactory(java.lang.String)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void deleteQueue(java.lang.String)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void deleteQueueConnectionFactory(java.lang.String)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void deleteTopic(java.lang.String)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public void deleteTopicConnectionFactory(java.lang.String)'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public javax.naming.Context getJNDIContext()'` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method `'public com.pcbsys.nirvana.client.nSession getSession()'` has been decreased from public to private

`com.webmethods.portal.service.bcgadget.IBCGadgetProvider`: Return type of method `'public java.util.List getAccessibleGadgets(com.webmethods.portal.service.meta2.thing.IThingID)'` has been changed to `java.util.Map`

`com.webmethods.portal.service.bcgadget.impl.BCGadgetProvider`: Return type of method `'public java.util.List getAccessibleGadgets(com.webmethods.portal.service.meta2.thing.IThingID)'` has been changed to `java.util.Map`

`com.webmethods.portal.service.task.impl.TaskLockingService`: Accessibility of field `TASK_LOCK_MAX_TIME` has been increased from private to public

`com.webmethods.portal.service.task.impl.TaskLockingService`: Accessibility of field `TASK_LOCK_MAX_WAIT_TIME` has been increased from private to public

Changed API**Description**

com.webmethods.portal.service.task.impl.TaskLockingService: In method 'protected

com.webmethods.portal.service.task.ITaskLock

createDbLock(com.webmethods.portal.service.sql.ISqlWorker,

com.webmethods.portal.service.meta2.thing.IThingID, java.util.Date, java.util.Date)' the number of arguments has changed

com.webmethods.portal.system.PortalSystem: Accessibility of method 'private void initGuestUser()' has been increased from private to public

com.webmethods.rtl.msg.jms.JMSProvider: Accessibility of method 'public void onShutdown()' has been decreased from public to protected

com.webmethods.rtl.msg.jms.JMSProvider: Accessibility of method 'private void setMaintenanceMode(boolean)' has been increased from private to protected

com.webmethods.rtl.msg.jms.JMSStdConnProvider: Accessibility of method 'public JMSStdConnProvider()' has been decreased from public to protected

com.webmethods.portal.service.version.impl.dcv.DCVersionService: Value of compile-time constant VERSION_SERVICES_ROOT has been changed

Release 9.10

Added API/ Description

com.webmethods.portal.bizPolicy.biz.access.IAccessPolicy: Method 'public

com.webmethods.portal.service.view.IListView

listSecurityRealmObjects(com.webmethods.portal.bizPolicy.IContext,

com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.mech.subscription.ISubscribableMechanics: Method 'public void

checkViewSubscription(com.webmethods.portal.system.IURI,

com.webmethods.portal.service.meta2.thing.IThingID, java.util.Map,

com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.bizPolicy.biz.IBizPolicyResolver: Method 'public

com.webmethods.portal.bizPolicy.biz.IBizPolicy getBizPolicyByType(java.lang.String, java.util.Map)'

has been added to an interface

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String

getAssertion(java.lang.String, java.lang.String[], java.util.Map)' has been added to an interface

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String

getAssertion(java.lang.String, java.lang.String[], java.util.Map, java.util.Map)' has been added to an

interface

com.webmethods.caf.wsclient.session.IWSClientSession: Method 'public java.util.Map

getSessionCookieMap()' has been added to an interface

com.webmethods.caf.wsclient.session.IWSClientSession: Method 'public void

setSessionCookieMap(java.util.Map)' has been added to an interface

com.webmethods.caf.wsclient.session.IWSClientSessionManager: Method 'public

com.webmethods.caf.wsclient.session.IWSClientSessionPool

getSessionPool(com.webmethods.caf.wsclient.proxy.IWSClientProxy, java.lang.String)' has been added

to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public java.util.Date getTaskScheduleDate()'

has been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void setCreatedDate(java.util.Date)' has

been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void

setTaskScheduleDate(java.util.Date)' has been added to an interface

com.webmethods.portal.service.task.ITask: Method 'public java.util.Date getTaskScheduleDate()' has

been added to an interface

Changed API/ Description

com.webmethods.portal.event.system.ICriterionEvent\$IListener: Parameter 1 of 'public void onEvent(com.webmethods.portal.event.system.ISubscriptionEvent)' has changed its type to com.webmethods.portal.event.system.ICriterionEvent

com.webmethods.portal.event.system.ICriterionEvent\$ISynchronousListener: Parameter 1 of 'public void onSynchronousEvent(com.webmethods.portal.event.system.ISubscriptionEvent)' has changed its type to com.webmethods.portal.event.system.ICriterionEvent

com.webmethods.portal.service.access.impl.MwsObjectAclManager: In method 'protected int countAceProperties(java.util.List)' the number of arguments has changed

com.webmethods.caf.wsclient.session.impl.WSClientSessionManager: Parameter 2 of 'protected java.lang.String getSessionPoolID(com.webmethods.caf.wsclient.proxy.IWSClientProxy, com.webmethods.caf.wsclient.AuthCredentials)' has changed its type to java.lang.String

Removed API/ Description

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Removed field
COMPONENT_DELETE_RETRIES

com.webmethods.portal.service.global.impl.LanguagePackManager: Field QUERY_STRING has been
removed, but it was previously a constant

com.webmethods.caf.faces.convert.FormattedDateTimeConverter: Method 'protected
java.text.DateFormat setupGMTDateTimeFormatter(javax.faces.context.FacesContext)' has been
removed

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.util.List getTaskCommentsByProcessModelId(java.lang.String, int, int, int)' has been added to an
interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List
getPaginatedTaskCommentsByProcessModelId(java.lang.String, int, int, int)' has been added to an
interface

com.webmethods.portal.service.dir.IRoleSystem: Method 'public void
clearCache(com.webmethods.portal.service.dir.IDirPrincipal)' has been added to an interface

com.webmethods.portal.mech.dir.IPrincipalMechanics: Method 'public void
fireRoleMembershipEvent(com.webmethods.portal.service.meta2.thing.IThingID,
com.webmethods.portal.system.IURI, com.webmethods.portal.service.dir.IDirPrincipalList,
com.webmethods.portal.service.dir.IDirPrincipalList, int)' has been added to an interface

move the com.webmethods.jms.** packages from caf-server bundle to a unique package name

com.webmethods.jms.JMSPhaseProvider: Class com.webmethods.jms.JMSPhaseProvider removed

com.webmethods.jms.db.DbJMSClient: Class com.webmethods.jms.db.DbJMSClient removed

com.webmethods.jms.db.DbJMSConnProvider: Class com.webmethods.jms.db.DbJMSConnProvider
removed

com.webmethods.jms.db.impl.JMSConnection: Class com.webmethods.jms.db.impl.JMSConnection
removed

com.webmethods.jms.db.impl.JMSConnection\$CompressedObject: Class
com.webmethods.jms.db.impl.JMSConnection\$CompressedObject removed

com.webmethods.jms.db.impl.JMSDestination: Class com.webmethods.jms.db.impl.JMSDestination
removed

com.webmethods.jms.db.impl.JMSDispatcherThread: Class
com.webmethods.jms.db.impl.JMSDispatcherThread removed

com.webmethods.jms.db.impl.JMSEvent: Class com.webmethods.jms.db.impl.JMSEvent removed

com.webmethods.jms.db.impl.JMSMessage: Class com.webmethods.jms.db.impl.JMSMessage
removed

com.webmethods.jms.db.impl.JMSMessageConsumer: Class
com.webmethods.jms.db.impl.JMSMessageConsumer removed

com.webmethods.jms.db.impl.JMSMessageProducer: Class
com.webmethods.jms.db.impl.JMSMessageProducer removed

com.webmethods.jms.db.impl.JMSObjectMessage: Class
com.webmethods.jms.db.impl.JMSObjectMessage removed

com.webmethods.jms.db.impl.JMSPollThread: Class com.webmethods.jms.db.impl.JMSPollThread
removed

com.webmethods.jms.db.impl.JMSQueue: Class com.webmethods.jms.db.impl.JMSQueue removed

com.webmethods.jms.db.impl.JMSQueuePollThread: Class
com.webmethods.jms.db.impl.JMSQueuePollThread removed

com.webmethods.jms.db.impl.JMSQueueReceiver: Class
com.webmethods.jms.db.impl.JMSQueueReceiver removed

com.webmethods.jms.db.impl.JMSQueueSender: Class
com.webmethods.jms.db.impl.JMSQueueSender removed

com.webmethods.jms.db.impl.JMSQueueSession: Class
com.webmethods.jms.db.impl.JMSQueueSession removed

com.webmethods.jms.db.impl.JMSSession: Class com.webmethods.jms.db.impl.JMSSession removed

com.webmethods.jms.db.impl.JMSTopic: Class com.webmethods.jms.db.impl.JMSTopic removed

com.webmethods.jms.db.impl.JMSTopicBatchMessage: Class
com.webmethods.jms.db.impl.JMSTopicBatchMessage removed

com.webmethods.jms.db.impl.JMSTopicPublisher: Class
com.webmethods.jms.db.impl.JMSTopicPublisher removed

com.webmethods.jms.db.impl.JMSTopicSession: Class com.webmethods.jms.db.impl.JMSTopicSession
removed

com.webmethods.jms.db.impl.JMSTopicSubscriber: Class
com.webmethods.jms.db.impl.JMSTopicSubscriber removed

com.webmethods.jms.db.impl.QueueFactory: Class com.webmethods.jms.db.impl.QueueFactory
removed

com.webmethods.jms.db.impl.TopicFactory: Class com.webmethods.jms.db.impl.TopicFactory
removed

com.webmethods.jms.db.impl.db2.EventDelivered: Class
com.webmethods.jms.db.impl.db2.EventDelivered removed

com.webmethods.jms.db.impl.db2.EventPoll: Class com.webmethods.jms.db.impl.db2.EventPoll
removed

com.webmethods.jms.db.impl.db2.EventSave: Class com.webmethods.jms.db.impl.db2.EventSave
removed

com.webmethods.jms.db.impl.db2.GetSqlTime: Class com.webmethods.jms.db.impl.db2.GetSqlTime
removed

com.webmethods.jms.db.impl.db2.PublishQueue: Class
com.webmethods.jms.db.impl.db2.PublishQueue removed

com.webmethods.jms.db.impl.db2.PurgeEvents: Class com.webmethods.jms.db.impl.db2.PurgeEvents
removed

com.webmethods.jms.db.impl.db2.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.db2.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.db2.RegisterDestination: Class
com.webmethods.jms.db.impl.db2.RegisterDestination removed

com.webmethods.jms.db.impl.db2.RegisterSubscription: Class
com.webmethods.jms.db.impl.db2.RegisterSubscription removed

com.webmethods.jms.db.impl.db2.UnregisterSubscription: Class
com.webmethods.jms.db.impl.db2.UnregisterSubscription removed

com.webmethods.jms.db.impl.db2.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.db2.UpdateSubscriptions removed

com.webmethods.jms.db.impl.mssql.EventDelivered: Class
com.webmethods.jms.db.impl.mssql.EventDelivered removed

com.webmethods.jms.db.impl.mssql.EventPoll: Class com.webmethods.jms.db.impl.mssql.EventPoll
removed

com.webmethods.jms.db.impl.mssql.EventSave: Class com.webmethods.jms.db.impl.mssql.EventSave
removed

com.webmethods.jms.db.impl.mssql.GetSqlTime: Class
com.webmethods.jms.db.impl.mssql.GetSqlTime removed

com.webmethods.jms.db.impl.mssql.PublishQueue: Class
com.webmethods.jms.db.impl.mssql.PublishQueue removed

com.webmethods.jms.db.impl.mssql.PurgeEvents: Class
com.webmethods.jms.db.impl.mssql.PurgeEvents removed

com.webmethods.jms.db.impl.mssql.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.mssql.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.mssql.RegisterDestination: Class
com.webmethods.jms.db.impl.mssql.RegisterDestination removed

com.webmethods.jms.db.impl.mssql.RegisterSubscription: Class
com.webmethods.jms.db.impl.mssql.RegisterSubscription removed

com.webmethods.jms.db.impl.mssql.UnregisterSubscription: Class
com.webmethods.jms.db.impl.mssql.UnregisterSubscription removed

com.webmethods.jms.db.impl.mssql.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.mssql.UpdateSubscriptions removed

com.webmethods.jms.db.impl.mysql.EventDelivered: Class
com.webmethods.jms.db.impl.mysql.EventDelivered removed

com.webmethods.jms.db.impl.mysql.EventPoll: Class com.webmethods.jms.db.impl.mysql.EventPoll
removed

com.webmethods.jms.db.impl.mysql.EventSave: Class com.webmethods.jms.db.impl.mysql.EventSave
removed

com.webmethods.jms.db.impl.mysql.GetSqlTime: Class
com.webmethods.jms.db.impl.mysql.GetSqlTime removed

com.webmethods.jms.db.impl.mysql.PublishQueue: Class
com.webmethods.jms.db.impl.mysql.PublishQueue removed

com.webmethods.jms.db.impl.mysql.PurgeEvents: Class
com.webmethods.jms.db.impl.mysql.PurgeEvents removed

com.webmethods.jms.db.impl.mysql.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.mysql.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.mysql.RegisterDestination: Class
com.webmethods.jms.db.impl.mysql.RegisterDestination removed

com.webmethods.jms.db.impl.mysql.RegisterSubscription: Class
com.webmethods.jms.db.impl.mysql.RegisterSubscription removed

com.webmethods.jms.db.impl.mysql.UnregisterSubscription: Class
com.webmethods.jms.db.impl.mysql.UnregisterSubscription removed

com.webmethods.jms.db.impl.mysql.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.mysql.UpdateSubscriptions removed

com.webmethods.jms.db.impl.oracle.EventDelivered: Class
com.webmethods.jms.db.impl.oracle.EventDelivered removed

com.webmethods.jms.db.impl.oracle.EventPoll: Class com.webmethods.jms.db.impl.oracle.EventPoll
removed

com.webmethods.jms.db.impl.oracle.EventSave: Class com.webmethods.jms.db.impl.oracle.EventSave
removed

com.webmethods.jms.db.impl.oracle.GetSqlTime: Class
com.webmethods.jms.db.impl.oracle.GetSqlTime removed

com.webmethods.jms.db.impl.oracle.PublishQueue: Class
com.webmethods.jms.db.impl.oracle.PublishQueue removed

com.webmethods.jms.db.impl.oracle.PurgeEvents: Class
com.webmethods.jms.db.impl.oracle.PurgeEvents removed

com.webmethods.jms.db.impl.oracle.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.oracle.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.oracle.RegisterDestination: Class
com.webmethods.jms.db.impl.oracle.RegisterDestination removed

com.webmethods.jms.db.impl.oracle.RegisterSubscription: Class
com.webmethods.jms.db.impl.oracle.RegisterSubscription removed

com.webmethods.jms.db.impl.oracle.UnregisterSubscription: Class
com.webmethods.jms.db.impl.oracle.UnregisterSubscription removed

com.webmethods.jms.db.impl.oracle.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.oracle.UpdateSubscriptions removed

com.webmethods.jms.db.impl.sybase.EventPoll: Class com.webmethods.jms.db.impl.sybase.EventPoll removed

com.webmethods.jms.db.impl.sybase.PublishQueue: Class
com.webmethods.jms.db.impl.sybase.PublishQueue removed

com.webmethods.jms.db.impl.sybase.PurgeEvents: Class
com.webmethods.jms.db.impl.sybase.PurgeEvents removed

com.webmethods.jms.um.UmJMSClient: Class com.webmethods.jms.um.UmJMSClient removed

com.webmethods.jms.um.UmJMSConnProvider: Class
com.webmethods.jms.um.UmJMSConnProvider removed

electric.util.holder.ArrayOfbyteInOut: Class electric.util.holder.ArrayOfbyteInOut removed

electric.util.holder.ArrayOfbyteOut: Class electric.util.holder.ArrayOfbyteOut removed

com.webmethods.portal.bizPolicy.command.system.xml.XMLImport: Field
OVERWRITE_PERMISSIONS_KEY has been removed, but it was previously a constant

com.webmethods.portal.service.dir.IDirService: Method 'public boolean supportsNestedGroups()' has been added to an interface

com.webmethods.caf.faces.application.CAFStateManager: Class
com.webmethods.caf.faces.application.CAFStateManager removed

com.webmethods.caf.faces.application.CAFStateManager\$TreeStructure: Class
com.webmethods.caf.faces.application.CAFStateManager\$TreeStructure removed

com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListener: Class
com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListener removed

com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListenerWrapper: Class
com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListenerWrapper removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected void
initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected void
renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been
removed

com.webmethods.caf.faces.render.html.command.CommandFormRenderer: In method 'protected
java.lang.String getTagName()' the number of arguments has changed

com.webmethods.caf.faces.render.html.command.DisjointFormRenderer: In method 'protected
java.lang.String getTagName()' the number of arguments has changed

com.webmethods.caf.faces.view.BaseViewHandler: Field STATE_KEY has been removed, but it was
previously a constant

com.webmethods.caf.faces.view.BaseViewHandler: Method 'protected void
initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.view.BaseViewHandler: Method 'protected void
renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been
removed

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field INJECT_STATE has been
removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field NO_RENDER has been removed,
but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field STATE_KEY has been removed,
but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field VIEW_FRAGMENT has been
removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field VIEW_FRAGMENT_CLIENT_ID
has been removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Return type of method 'protected void
initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been changed
to javax.faces.context.ResponseWriter

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Method 'protected void
renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been
removed

com.webmethods.caf.faces.view.ViewFragmentPhaseListener: Class
com.webmethods.caf.faces.view.ViewFragmentPhaseListener removed

Release 9.9

Added API/ Description

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public java.lang.Integer getIsMandatory()' has been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void setIsMandatory(java.lang.Integer)' has been added to an interface

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String validateSAMLResponse(javax.servlet.http.HttpServletRequest, java.lang.String)' has been added to an interface

com.webmethods.portal.bizPolicy.biz.access.IAccessPolicy: Method 'public
com.webmethods.portal.service.view.IListView
listSecurityRealmObjects(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.util.List getAllTaskAttachments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.lang.Integer getAllTaskAttachmentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.util.List getTaskComments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.lang.Integer getTaskCommentsCount(int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.lang.Integer getTaskCommentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.mech.subscription.ISubscribableMechanics: Method 'public void
checkViewSubscription(com.webmethods.portal.system.IURI,
com.webmethods.portal.service.meta2.thing.IThingID, java.util.Map,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List
getAllTaskAttachments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public
java.lang.Integer getAllTaskAttachmentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List
getTaskComments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public

Added API/ Description

java.lang.Integer getTaskCommentsCount(int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.lang.Integer getTaskCommentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.service.task.ITask: Method 'public java.lang.Integer getIsMandatory()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public java.lang.String getTaskDescription()' has been added to an interface

Removed API/ Description

com.webmethods.caf.faces.component.gmap.GMarkerGroup: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.gmap.GMarkerList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.AsyncIterator: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.Import: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.ImportTemplate: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.Iterator: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.Breadcrumbs: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.FirstLevelList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.NavList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.PopupMenus: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.SecondLevelList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.StaticMenus\$SubList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.StaticMenus\$SubSubList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

Removed API/ Description

com.webmethods.caf.faces.component.nav.ThirdLevelList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncListbox: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncTabsList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.DataList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.ListBox: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.TabsList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

Removed API/ Description

com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.rtl.script.JspC: Removed java.lang.Cloneable from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.ProjectComponent from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.Task from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.ProjectComponent from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.Task from the list of superclasses

com.webmethods.caf.faces.component.logic.Import: Method 'public boolean isListenerForSource(java.lang.Object)' has been removed

com.webmethods.caf.faces.component.logic.Import: Method 'public void processEvent(javax.faces.event.SystemEvent)' has been removed

com.webmethods.caf.faces.component.logic.ImportTemplate: Method 'public boolean isListenerForSource(java.lang.Object)' has been removed

com.webmethods.caf.faces.component.logic.ImportTemplate: Method 'public void processEvent(javax.faces.event.SystemEvent)' has been removed

com.webmethods.caf.faces.component.nav.PopupMenus: Method 'protected javax.faces.component.UIColumn getColumn()' has been removed

com.webmethods.caf.faces.component.table.html.DataList: Method 'public boolean

Removed API/ Description

`isListenerForSource(java.lang.Object)` has been removed

`com.webmethods.caf.faces.component.table.html.DataList`: Method `'public void processEvent(javax.faces.event.SystemEvent)'` has been removed

`com.webmethods.caf.faces.component.tree.DataTree`: Method `'protected void autogenerate()'` has been removed

`com.webmethods.portal.service.install.impl.BaseInstallService`: Method `'protected com.webmethods.portal.service.install.IInstallServiceConfig getConfig()'` has been removed

`com.webmethods.portal.service.sql.runtime.base.TaskSearchAll`: Method `'protected void parseSearchQuery(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQuery, com.webmethods.portal.service.sql.runtime.base.TaskSearchAll$QueryInfo)'` has been removed

`com.webmethods.portal.service.sql.runtime.base.TaskSearchAll`: Method `'protected void parseSearchQueryTerm(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm, com.webmethods.portal.service.sql.runtime.base.TaskSearchAll$QueryInfo)'` has been removed

`com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesPaged`: Method `'protected void parseSearchQueryTerm(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm, com.webmethods.portal.service.sql.runtime.base.TaskSearchAll$QueryInfo)'` has been removed

`com.webmethods.rtl.script.JspC`: Method `'public void init()'` has been removed

`com.softwareag.caf.controls.mwsx.PeoplePickerDialog$FacetsMap`: Class
`com.softwareag.caf.controls.mwsx.PeoplePickerDialog$FacetsMap` removed

`com.softwareag.caf.controls.mwsx.PeopleSwapBox$FacetsMap`: Class
`com.softwareag.caf.controls.mwsx.PeopleSwapBox$FacetsMap` removed

`com.webmethods.caf.faces.component.nav.StaticMenus$ChildrenList`: Class
`com.webmethods.caf.faces.component.nav.StaticMenus$ChildrenList` removed

`com.webmethods.caf.faces.component.nav.StaticMenus$FacetsMap`: Class
`com.webmethods.caf.faces.component.nav.StaticMenus$FacetsMap` removed

`com.webmethods.caf.faces.component.nav.ToggleMenus$ChildrenList`: Class
`com.webmethods.caf.faces.component.nav.ToggleMenus$ChildrenList` removed

`com.webmethods.caf.faces.component.nav.ToggleMenus$FacetsMap`: Class
`com.webmethods.caf.faces.component.nav.ToggleMenus$FacetsMap` removed

`com.webmethods.caf.faces.component.search.SearchBar$FacetsMap`: Class
`com.webmethods.caf.faces.component.search.SearchBar$FacetsMap` removed

`com.webmethods.caf.faces.component.table.SelectRowCheckbox$ChildrenList`: Class
`com.webmethods.caf.faces.component.table.SelectRowCheckbox$ChildrenList` removed

`com.webmethods.caf.faces.component.table.SelectRowCheckbox$FacetsMap`: Class

Removed API/ Description

com.webmethods.caf.faces.component.table.SelectRowCheckbox\$FacetsMap removed

com.webmethods.caf.faces.component.table.html.HtmlTableColumn\$FacetsMap: Class
com.webmethods.caf.faces.component.table.html.HtmlTableColumn\$FacetsMap removed

com.webmethods.caf.faces.component.table.specialized.Newsfeed\$ChildrenList: Class
com.webmethods.caf.faces.component.table.specialized.Newsfeed\$ChildrenList removed

com.webmethods.caf.faces.component.table.specialized.Newsfeed\$FacetsMap: Class
com.webmethods.caf.faces.component.table.specialized.Newsfeed\$FacetsMap removed

com.webmethods.caf.faces.component.util.BaseChildrenList: Class
com.webmethods.caf.faces.component.util.BaseChildrenList removed

com.webmethods.caf.faces.component.util.BaseFacetsAndChildrenIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsAndChildrenIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection\$BaseIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection\$BaseIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries\$EntrySetIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries\$EntrySetIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys\$KeySetIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys\$KeySetIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values\$ValuesIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values\$ValuesIterator removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseFileListTask: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseFileListTask removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseTask: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseTask removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GenerateOSGiManifest: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GenerateOSGiManifest removed

Removed API/ Description

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GetPortletInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GetPortletInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PostRegisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PostRegisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreRegisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreRegisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreUnregisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreUnregisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateSkinInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateSkinInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateThemeInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateThemeInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.GetSkinInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.GetSkinInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveSkinInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveSkinInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveThemeInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveThemeInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.CreateDBOTables: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.CreateDBOTables removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.DropDBOTables: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.DropDBOTables removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteCommand: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteCommand removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteTargetLoop: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteTargetLoop removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime: Class

Removed API/ Description

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.InstallComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.InstallComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadClasses: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadClasses removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadConfig: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadConfig removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LookupComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LookupComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RegisterComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RegisterComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RunSQLScript: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RunSQLScript removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UninstallComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UninstallComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UnregisterComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UnregisterComponent removed

com.webmethods.portal.mech.install.impl.NativeInstallMechanics: Class
com.webmethods.portal.mech.install.impl.NativeInstallMechanics removed

com.webmethods.portal.service.install.IInstallServiceConfig: Class
com.webmethods.portal.service.install.IInstallServiceConfig removed

com.webmethods.portal.service.install.impl.InstallServiceConfig: Class
com.webmethods.portal.service.install.impl.InstallServiceConfig removed

com.webmethods.portal.service.install.impl.ant.AntInstallService: Class
com.webmethods.portal.service.install.impl.ant.AntInstallService removed

com.webmethods.portal.service.install.impl.ant.AntLogSupport: Class
com.webmethods.portal.service.install.impl.ant.AntLogSupport removed

com.webmethods.portal.service.install.impl.ant.AntRunner: Class
com.webmethods.portal.service.install.impl.ant.AntRunner removed

com.webmethods.portal.service.install.impl.ant.AntRunner\$AntPropertyHelper: Class
com.webmethods.portal.service.install.impl.ant.AntRunner\$AntPropertyHelper removed

com.webmethods.portal.service.install.impl.ant.LpInstallService: Class
com.webmethods.portal.service.install.impl.ant.LpInstallService removed

Removed API/ Description

com.webmethods.portal.service.install.impl.ant.WarLpInstallService: Class
com.webmethods.portal.service.install.impl.ant.WarLpInstallService removed

com.webmethods.rtl.logging.Mws13818Filter: Class com.webmethods.rtl.logging.Mws13818Filter removed

com.webmethods.rtl.util.msg.IRuntimeMessage: Class com.webmethods.rtl.util.msg.IRuntimeMessage removed

com.webmethods.rtl.util.msg.IRuntimeMessageCallback: Class
com.webmethods.rtl.util.msg.IRuntimeMessageCallback removed

com.webmethods.rtl.util.msg.IRuntimeMessageHook: Class
com.webmethods.rtl.util.msg.IRuntimeMessageHook removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeListeners: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeListeners removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeMessageListener: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeMessageListener removed

com.webmethods.rtl.util.obj.CyclicIterator: Class com.webmethods.rtl.util.obj.CyclicIterator removed

com.webmethods.rtl.util.obj.EmptyEnumeration: Class
com.webmethods.rtl.util.obj.EmptyEnumeration removed

com.webmethods.rtl.util.obj.EmptyIterator: Class com.webmethods.rtl.util.obj.EmptyIterator removed

com.webmethods.rtl.util.obj.FileClassLoader: Class com.webmethods.rtl.util.obj.FileClassLoader removed

com.webmethods.rtl.util.obj.IntMinMaxInfo: Class com.webmethods.rtl.util.obj.IntMinMaxInfo removed

com.webmethods.rtl.util.obj.IntStringMap: Class com.webmethods.rtl.util.obj.IntStringMap removed

com.webmethods.rtl.util.obj.IteratorTools: Class com.webmethods.rtl.util.obj.IteratorTools removed

com.webmethods.rtl.util.obj.PersistentMap: Class com.webmethods.rtl.util.obj.PersistentMap removed

com.webmethods.rtl.util.obj.PropertyGroup: Class com.webmethods.rtl.util.obj.PropertyGroup removed

com.webmethods.rtl.util.obj.PropertyGroups: Class com.webmethods.rtl.util.obj.PropertyGroups removed

com.webmethods.rtl.util.obj.SortableArray: Class com.webmethods.rtl.util.obj.SortableArray removed

com.webmethods.rtl.util.thread.ReadWriteMutex: Class
com.webmethods.rtl.util.thread.ReadWriteMutex removed

Removed API/ Description

com.softwareag.caf.controls.mwsx.PeoplePickerDialog: Removed field m_facets

com.softwareag.caf.controls.mwsx.PeopleSwapBox: Removed field m_facets

com.webmethods.caf.faces.component.behavior.BaseBehavior: Removed field m_for

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_allowDrag

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_cursor

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_move

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_propagateEvent

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_allowDrop

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_handleDrop

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_hoverClass

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_onDropSetValue

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_add

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_allowDrag

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_allowDrop

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_copy

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_handleDrop

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_hoverClass

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_remove

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_reorder

com.webmethods.caf.faces.component.behavior.DragToReorderColumnsBehavior: Removed field m_storePreferences

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeBottom

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeLeft

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeRight

Removed API/ Description

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeTop

com.webmethods.caf.faces.component.behavior.DragToResizeColumnsBehavior: Removed field m_storePreferences

com.webmethods.caf.faces.component.behavior.RaiseOnChangeBehavior: Removed field m_command

com.webmethods.caf.faces.component.behavior.SynchronizeValuesBehavior: Removed field m_with

com.webmethods.caf.faces.component.command.html.AsyncCommandButton: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.AsyncCommandIcon: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.AsyncCommandInterval: Removed field m_interval

com.webmethods.caf.faces.component.command.html.AsyncCommandInterval: Removed field m_waitUntilReloaded

com.webmethods.caf.faces.component.command.html.AsyncCommandLink: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.AsyncHiddenCommand: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.CommandForm: Removed field m_forms

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_alt

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_url

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_urlMouseDown

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_urlMouseover

com.webmethods.caf.faces.component.events.OpenAjaxScript: Removed field openAjaxTopic

com.webmethods.caf.faces.component.events.OpenAjaxScript: Removed field shouldSubscribe

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_converter

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_entriesProvider

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_exportCharacterEncoding

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_exportFileName

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_exportForceDownload

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_feedProvider

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_feedUrl

Removed API/ Description

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_for

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_height

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_initialAddress

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_initialCountry

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_key

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_latitude

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_longitude

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_type

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_width

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_zoom

com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_anchor

com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_offsetX

com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_offsetY

com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_type

com.webmethods.caf.faces.component.gmap.GMapGetCoordsScript: Removed field m_latitude

com.webmethods.caf.faces.component.gmap.GMapGetCoordsScript: Removed field m_longitude

com.webmethods.caf.faces.component.gmap.GMapKey: Removed field m_key

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_clickable

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_draggable

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_icon

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_iconSizeHeight

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_iconSizeWidth

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_initialAddress

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_initialCountry

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_latitude

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_longitude

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_selected

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_title

com.webmethods.caf.faces.component.gmap.GMarkerGroup: Removed field m_groupProvider

Removed API/ Description

com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_clickable
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_draggable
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_icon
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_iconSizeHeight
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_iconSizeWidth
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_initialAddress
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_initialCountry
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_latitude
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_longitude
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_multiple
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_title
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_multiple
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_title
com.webmethods.caf.faces.component.input.DateInput: Removed field m_pattern
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showMonthAndYearMenus
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showSeconds
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showTime
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showTimezone
com.webmethods.caf.faces.component.input.DateInput: Removed field m_timezone
com.webmethods.caf.faces.component.input.DateInput: Removed field m_valuePattern
com.webmethods.caf.faces.component.input.DateInput: Removed field m_yearMenuRange
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_futureRanges
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_label
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_layout
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_pastRanges
com.webmethods.caf.faces.component.logic.If: Removed field m_value
com.webmethods.caf.faces.component.logic.Import: Removed field m_value
com.webmethods.caf.faces.component.logic.ImportTemplate: Removed field m_value
com.webmethods.caf.faces.component.logic.LoadResourceBundle: Removed field m_basename

Removed API/ Description

com.webmethods.caf.faces.component.logic.LoadResourceBundle: Removed field m_var
com.webmethods.caf.faces.component.logic.VariableContainer: Removed field m_value
com.webmethods.caf.faces.component.logic.VariableContainer: Removed field m_var
com.webmethods.caf.faces.component.message.FormattedMessage: Removed field m_showDetail
com.webmethods.caf.faces.component.message.FormattedMessages: Removed field m_showDetail
com.webmethods.caf.faces.component.message.SpecificFormattedMessages: Removed field m_for
com.webmethods.caf.faces.component.message.SpecificMessages: Removed field m_for
com.webmethods.caf.faces.component.mws_ui.MwsResourceInclude: Removed field renderer
com.webmethods.caf.faces.component.mws_ui.MwsResourceInclude: Removed field uri
com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_appNavBean
com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_children
com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_facets
com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_appNavBean
com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_children
com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_facets
com.webmethods.caf.faces.component.output.Chart: Removed field m_barPadding
com.webmethods.caf.faces.component.output.Chart: Removed field m_barWidth
com.webmethods.caf.faces.component.output.Chart: Removed field m_color
com.webmethods.caf.faces.component.output.Chart: Removed field m_gridColor
com.webmethods.caf.faces.component.output.Chart: Removed field m_gridStyle
com.webmethods.caf.faces.component.output.Chart: Removed field m_height
com.webmethods.caf.faces.component.output.Chart: Removed field m_legendLocation
com.webmethods.caf.faces.component.output.Chart: Removed field m_legendStyleClass
com.webmethods.caf.faces.component.output.Chart: Removed field m_numberofGridLines
com.webmethods.caf.faces.component.output.Chart: Removed field m_padding
com.webmethods.caf.faces.component.output.Chart: Removed field m_rowColors
com.webmethods.caf.faces.component.output.Chart: Removed field m_series
com.webmethods.caf.faces.component.output.Chart: Removed field m_showLegend
com.webmethods.caf.faces.component.output.Chart: Removed field m_type

Removed API/ Description

com.webmethods.caf.faces.component.output.Chart: Removed field m_width
com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_color
com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_toolTip
com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_value
com.webmethods.caf.faces.component.output.ChartLabelColumn: Removed field m_label
com.webmethods.caf.faces.component.output.Custom: Removed field m_name
com.webmethods.caf.faces.component.output.Icon: Removed field m_converter
com.webmethods.caf.faces.component.output.Icon: Removed field m_label
com.webmethods.caf.faces.component.output.Icon: Removed field m_url
com.webmethods.caf.faces.component.output.Icon: Removed field m_urlMousedown
com.webmethods.caf.faces.component.output.Icon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_accesskey
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_alt
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_dir
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_disabled
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_image
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_label
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_lang
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onblur
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onclick
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_ondblclick
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onfocus
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onkeydown
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseout
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseover
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseup
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_readonly
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_style
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_styleClass

Removed API/ Description

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_tabindex

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_title

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_type

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_width

com.webmethods.caf.faces.component.output.html.HtmlLink: Removed field m_label

com.webmethods.caf.faces.component.output.refresh.RefreshButton: Removed field m_for

com.webmethods.caf.faces.component.output.refresh.RefreshIcon: Removed field m_for

com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_for

com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_interval

com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_waitUntilReloaded

com.webmethods.caf.faces.component.output.refresh.RefreshLink: Removed field m_for

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_disableWhenHidden

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_lazy

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_refreshOnShow

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_suppressInputs

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_twoPass

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_visible

com.webmethods.caf.faces.component.panel.OverlayPanel: Removed field m_hideEffect

com.webmethods.caf.faces.component.panel.OverlayPanel: Removed field m_showEffect

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_click

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_close

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_closeOnClick

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_forRightClick

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hideEffect

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hideEffectOptions

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hover

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_position

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_showEffect

Removed API/ Description

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_showEffectOptions

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_description

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_label

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_overflow

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_parentId

com.webmethods.caf.faces.component.panel.StackPanel: Removed field m_value

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_align

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_height

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_width

com.webmethods.caf.faces.component.panel.StaticRow: Removed field m_height

com.webmethods.caf.faces.component.panel.StaticRow: Removed field m_width

com.webmethods.caf.faces.component.search.BaseSearchControlHelper: Removed field fQuerySupplied

com.webmethods.caf.faces.component.search.BaseSearchControlHelper: Removed field fQuerySuppliedExpr

com.webmethods.caf.faces.component.search.SearchBar: Removed field m_facets

com.webmethods.caf.faces.component.select.FilterInput: Removed field m_labelText

com.webmethods.caf.faces.component.select.FilterInput: Removed field m_showGoButton

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_filter

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_other

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_sortByLabel

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_filter

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_other

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_sortByLabel

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_dir

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_disabled

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_lang

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_dir

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_disabled

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_lang

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_name

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onblur

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onchange

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onclick

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_ondblclick

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onfocus

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeydown

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeypress

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeyup

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmousedown

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmousemove

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseout

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseover

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseup

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_readonly

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_size

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_style

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_styleClass

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_tabindex

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_title

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_border

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_dir

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_disabled

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_disabledClass

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_enabledClass

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_lang
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_layout
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onblur
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onchange
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onclick
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_ondblclick
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onfocus
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeydown
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeypress
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeyup
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmousedown
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmousemove
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseout
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseover
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseup
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onselect
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_readonly
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_size
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_style
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_styleClass
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_tabindex
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onblur
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onchange
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onclick
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_ondblclick
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onfocus
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeydown
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeypress
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeyup

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmousedown
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmousemove
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseout
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseover
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseup
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onselect
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_readonly
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_size
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_style
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_styleClass
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_tabindex
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_title
com.webmethods.caf.faces.component.table.AddRow: Removed field m_addLastRowOnly
com.webmethods.caf.faces.component.table.AddRow: Removed field m_for
com.webmethods.caf.faces.component.table.AddRow: Removed field m_row
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_title
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_url
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_urlMouseDown
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_align
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_ascending
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_exportable
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_group
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_hidden
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_label
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_nowrap
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_optional
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_ordinal
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondary

Removed API/ Description

com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondaryEnd
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondaryStart
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_sort
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_valign
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_width
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_accesskey
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_disabled
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_multiple
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_tabindex
com.webmethods.caf.faces.component.table.DataPager: Removed field m_for
com.webmethods.caf.faces.component.table.DataPages: Removed field m_maxPages
com.webmethods.caf.faces.component.table.DataPages: Removed field m_showAlways
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_title
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_url
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_urlMouseDown
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_expandToEdges
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_nextIconUrl
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_nextText
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_prevIconUrl
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_prevText
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_showAlways
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_for
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_removeLastRow
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_row
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_title
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_url
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_urlMouseDown
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_urlMouseover

Removed API/ Description

com.webmethods.caf.faces.component.table.SelectRow: Removed field m_accesskey
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_disabled
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_for
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_multiple
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_tabindex
com.webmethods.caf.faces.component.table.SelectRowCheckbox: Removed field m_children
com.webmethods.caf.faces.component.table.SelectRowCheckbox: Removed field m_facets
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferChunk
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferMax
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferMin
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_clientSideCache
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_flashOnChange
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_progressDelay
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_progressMsg
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_suppressInputs
com.webmethods.caf.faces.component.table.html.AsyncListbox: Removed field m_rowClasses
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferChunk
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferMax
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferMin
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_clientSideCache
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_flashOnChange
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_progressDelay
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_progressMsg
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_suppressInputs
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field dayVar
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field eventVar
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_allDay
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_calendarEndDate
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_calendarStartDate

Removed API/ Description

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_displayUnits

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_events

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_eventsSet

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_initialDate

com.webmethods.caf.faces.component.table.html.DataList: Removed field m_marker

com.webmethods.caf.faces.component.table.html.DataList: Removed field m_selected

com.webmethods.caf.faces.component.table.html.DataList: Removed field m_selectedRowClass

com.webmethods.caf.faces.component.table.html.DataTable: Removed field createdToOriginalRowIds

com.webmethods.caf.faces.component.table.html.DataTable: Removed field filter

com.webmethods.caf.faces.component.table.html.DataTable: Removed field first

com.webmethods.caf.faces.component.table.html.DataTable: Removed field firstSet

com.webmethods.caf.faces.component.table.html.DataTable: Removed field originalToCreatedRowIds

com.webmethods.caf.faces.component.table.html.DataTable: Removed field var

com.webmethods.caf.faces.component.table.html.HtmlTableColumn: Removed field m_facets

com.webmethods.caf.faces.component.table.html.ListBox: Removed field m_rowClasses

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_children

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_facets

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_layout

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_size

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_url

com.webmethods.caf.faces.component.toggle.InitiateToggle: Removed field m_for

com.webmethods.caf.faces.component.toggle.OneWayToggle: Removed field m_for

com.webmethods.caf.faces.component.toggle.OneWayToggle: Removed field m_way

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_disabled

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_disabledClass

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_enabledClass

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_width

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggleCheckbox: Removed field

Removed API/ Description

`m_checked`

`com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggleCheckbox`: Removed field `m_checkedWhenVisible`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_disabled`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_disabledClass`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_enabledClass`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_layout`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_width`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_initialDepth`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_progressDelay`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_progressFlashOnComplete`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_progressMsg`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_refillDepth`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_refreshOnShow`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_suppressInputs`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_collapseAllIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_collapseIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_expandAllIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_expandIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_leafIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_lineBottomIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_lineIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_lineNoneIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_lineTopIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_loadingIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_showSortLink`

`com.webmethods.caf.faces.view.BaseViewHandler`: Removed field `RE_FE_URL`

`com.webmethods.portal.faces.view.PortalViewHandler`: Removed field `RE_FE_URL`

`com.webmethods.portal.taglib.PortalIterationTagSupport`: Removed field `EMPTY_ITERATOR`

10.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

CAF-RM-103-20181015

webMethods Database Component Configurator 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Database Component Configurator 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information	2
2.0	Known Issues	2
3.0	Usage Notes	2
4.0	Fixes Included in Each Release	2
5.0	Other Resolved Issues	4
6.0	Documentation Changes	6
7.0	Terminology Changes	6
8.0	Added, Removed, Deprecated, or Changed Items	6
9.0	Copyright Information	6
10.0	Support	7

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the *latest fix level* that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- DC_10.1_DBS_Fix7
- DC_9.12_DBS_Fix12
- DC_9.10_DBS_Fix10
- DC_9.8_DBS_Fix15
- DC_9.7_DBS_Fix16

Release 10.2

- DC_10.1_DBS_Fix6
- DC_9.12_DBS_Fix8
- DC_9.10_DBS_Fix9
- DC_9.9_DBS_Fix12
- DC_9.8_DBS_Fix14

Release 10.1

- DC_10.0_DBS_Fix2
- DC_9.12_DBS_Fix6

- DC_9.10_DBS_Fix7
- DC_9.9_DBS_Fix10
- DC_9.8_DBS_Fix12
- DC_9.7_DBS_Fix14

Release 10.0

- DC_9.9_DBS_Fix7
- DC_9.8_DBS_Fix11
- DC_9.7_DBS_Fix12
- DC_9.6_DBS_Fix13

Release 9.12

- DC_9.9_DBS_Fix5
- DC_9.8_DBS_Fix8
- DC_9.7_DBS_Fix10
- DC_9.6_DBS_Fix11

Release 9.10

- DC_9.9_DBS_Fix3
- DC_9.8_DBS_Fix6
- DC_9.7_DBS_Fix8
- DC_9.6_DBS_Fix9

Release 9.9

- DC_9.8_DBS_Fix2
- DC_9.7_DBS_Fix5
- DC_9.6_DBS_Fix6
- DC_8.2_SP2_DBS_Fix12

Release 9.8

- DC_9.6_DBS_Fix4
- DC_9.0_SP1_DBS_Fix5
- DC_8.2_SP2_DBS_Fix11

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- PIE-52250
Migration fails on Common DB Configurator.
Migration fails on Common DB Configurator due to changes introduced in the DB script for an earlier version of Integration Server as part of PIE-52084.
This issue is resolved.
- OBE-10316
When you use webMethods Database Component Configurator to migrate the CentralConfiguration component from version 9.12 to the latest version, an error occurs and the migration fails.
The issue is resolved.
- OBE-10432
After migrating Optimize, the schema objects of the BAM_DIM_JOIN_TMP table might be different from the schema objects after a fresh installation. The issue occurs for Optimize environments that are configured to use a MySQL database.
The issue is resolved.
- OTN-18293
There was a performance degradation when an update was made to a Trading Partner Agreement that was in use. With this fix, the partner table is optimized by including a Database index.
This issue is resolved.
- OTN-18452
When using MySQL as an external database, importing a client certificate fails with an expiry date beyond 2038-01-19 UTC. This is because the datatype "Timestamp" associated with the MySQL table column of certificate expiry has an upper limit set to 2038-01-19 UTC. The issue is now resolved because the datatype for the column is changed to "DateTime" which has an upper expiry limit of year 9999.
The issue is resolved.

Release 10.1

- WDA-1031
Command Central bootstrapper installs Database Configurator 10.0 but the program group item displays 9.12.
This issue is resolved.

- WDA-1026
Desktop shortcut incorrectly displays the version as Database Component Configurator 9.12.
This issue is resolved.
- WDA-979
DCC 10.0 displays incorrect copyright year and version in the console.
This issue is resolved.
- WDA-918
In the Database Component Configurator, when a product is selected and then the mouse cursor is pointed to the radio button component, the selection is set back to "All". Moving the mouse cursor without clicking the button should not change the selection.
This issue is resolved.
- WDA-976
Database Component Configurator version shows 9.12 instead of 10.0 in the Windows Start menu.
This issue is resolved.
- WDA-844
Incorrect Copyright year in the DCC "About" window.
The Copyright year in the DCC "About" window shows 2006 – 2015. It should be 2006 – 2016.
This issue is resolved.

Release 9.12

- WDA-844
Incorrect Copyright year in the DCC "About" window.
The Copyright year in the DCC "About" window shows 2006 – 2015. It should be 2006 – 2016.
This issue is resolved.

Release 9.8

- WDA-768
Database Component Configurator does not work with SSO/NTLM authentication when it is installed on Microsoft Windows.
When you try to use the Authentication Method as NTLM to establish a connection to Microsoft SQL Server, Database Component Configurator fails with the following exception:
Authentication was requested but the required DDJDBCx64Auth05.dll was not found on the path specified by the java.library.path system property.
Workaround: Add the following statement in the setEnv.bat file available at
<Install_Dir>\common\db\bin:
set SSO=<Install_Dir>\common\bin
set JAVA_OPTS=%JAVA_OPTS% -Djava.library.path="%SSO%"
where <Install_Dir> is the installation directory.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 9.8

- Software AG documentation is no longer available on the Software AG installer. You can access all Software AG documentation on the [Documentation website](#).

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.1

Added Item	Description
Support for MySQL Community Edition	MySQL Community Edition is now supported with Database Component Configurator.

Changed Item	Description
Changed logging behavior	The logging behavior of Database Component Configurator has changed in this release. Now Database Component Configurator will generate only one log file named as <i>dcc.log</i> . Once the <i>dcc.log</i> file size crosses 10 MB, it will be renamed as <i>dcc.log.NUMBER</i> .

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

DCC-RM-103-20181015

webMethods Deployer 10.3 and webMethods Asset Build Environment 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Deployer 10.3 and webMethods Asset Build Environment 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	3
5.0	Other Resolved Issues.....	6
6.0	Documentation Changes	7
7.0	Terminology Changes	8
8.0	Added, Removed, Deprecated, or Changed Items.....	8
9.0	Copyright Information.....	12
10.0	Support.....	12

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

Deployer

- Runtime-based deployment projects can deploy assets from 7.1 SP3 and later releases of webMethods runtimes. To accommodate deployment of assets from earlier releases, create source and target servers for specific versions of the Deployer. Projects can include only sources and targets of the same version except for version 8.0 assets, which you can deploy to either 8.0 or 8.2 servers.
- Repository-based deployment projects support checkpoint and rollback for all runtimes except for webMethods Optimize.
- Repository-based deployment projects support deletion sets for all runtimes except for Optimize.
- Repository-based projects support configuration of project settings through the Project Automator.
- Deployer now supports using zip file as a source in SideBySide upgrade.
- If you are upgrading from an earlier release and you already have repository aliases, you must recreate the indexes of those repository aliases.
- Deployer supports deployment of Task Engine assets only to Integration Server runtimes.

4.0 Fixes Included in Each Release

This section lists the *latest fix level* that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Deployer

Release 10.3

- DEP_10.1_Fix2
- DEP_9.12_Fix5
- DEP_9.10_Fix5
- DEP_9.8_Fix10

Release 10.2

- DEP_8.2_SP2_Fix21
- DEP_9.6_Fix10
- DEP_9.7_Fix9
- DEP_9.8_Fix9
- DEP_9.9_Fix7
- DEP_9.12_Fix4
- DEP_10.1_Fix1

Release 10.1

- DEP_8.2_SP2_Fix20
- DEP_9.5_SP1_Fix9
- DEP_9.8_Fix8
- DEP_9.9_Fix6
- DEP_9.10_Fix4
- DEP_9.12_Fix2

Release 10.0

- DEP_8.2_SP2_Fix19
- DEP_9.5_SP1_Fix8
- DEP_9.6_Fix9
- DEP_9.7_Fix8

- DEP_9.8_Fix6
- DEP_9.9_Fix4
- DEP_9.10_Fix2

Release 9.12

- DEP_9.0_SP1_Fix10
- DEP_9.6_Fix8
- DEP_9.7_Fix7
- DEP_9.8_Fix4
- DEP_9.9_Fix3
- DEP_9.10_Fix1

Release 9.10

- DEP_9.0_SP1_Fix9
- DEP_9.5_SP1_Fix7
- DEP_9.6_Fix6
- DEP_9.7_Fix5
- DEP_9.8_Fix3
- DEP_9.9_Fix1

Release 9.9

- DEP_8.2_SP2_Fix18
- DEP_9.0_SP1_Fix8
- DEP_9.5_SP1_Fix6
- DEP_9.6_Fix5
- DEP_9.7_Fix4
- DEP_9.8_Fix2

Release 9.8

- DEP_8.2_SP2_Fix17
- DEP_9.0_SP1_Fix6
- DEP_9.5_SP1_Fix4
- DEP_9.6_Fix3
- DEP_9.7_Fix2

Asset Build Environment

Release 10.3

- ABE_10.1_Fix2
- ABE_9.12_Fix2
- ABE_9.9_Fix5

Release 10.2

- ABE_9.10_Fix1
- ABE_9.12_Fix1
- ABE_10.1_Fix1

Release 10.1

- ABE_9.8_Fix4
- ABE_9.9_Fix4
- ABE_10.0_Fix2

Release 10.0

- ABE_9.5_SP1_Fix4
- ABE_9.6_Fix5
- ABE_9.9_Fix3

Release 9.12

- ABE_9.7_Fix4
- ABE_9.8_Fix3
- ABE_9.9_Fix1
- ABE_9.10_Fix1

Release 9.10

- ABE_9.0_SP1_Fix5
- ABE_9.5_SP1_Fix4
- ABE_9.7_Fix3
- ABE_9.8_Fix2

Release 9.9

- ABE_8.2_SP2_Fix11

- ABE_9.0_SP1_Fix4
- ABE_9.5_SP1_Fix3
- ABE_9.6_Fix4
- ABE_9.7_Fix2
- ABE_9.8_Fix1

Release 9.8

- ABE_8.2_SP2_Fix10
- ABE_9.0_SP1_Fix4
- ABE_9.5_SP1_Fix3
- ABE_9.6_Fix3
- ABE_9.7_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- LJP-2016
For AgileApps assets, Deployer displays the asset ID instead of the asset name while checking for unresolved dependencies.
While adding AgileApps package assets to a Deployment set, asset IDs are shown instead of asset names for unresolved dependencies of selected packages.
This issue is resolved.

Release 10.0

- WMDPD-1067
Deployer does not show process models as dependencies for associated event maps.
When you include an event map that is associated with a process model in an Optimize deployment set, Deployer does not list the process model as a dependency. You therefore cannot resolve this dependency and include the process model in the deployment set.
To resolve this issue, create and deploy a deployment set that includes the process model and then deploy the event map.

Release 9.10

- PIF-12248

Cannot deploy JNDI assets from a source Universal Messaging server to a target Universal Messaging server using webMethods Deployer.
This issue is resolved.

6.0 Documentation Changes

This section describes *significant* changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

The “webMethods Deployer User’s Guide” contains information on deploying Task Engine assets.

Release 10.1

The “webMethods Deployer User’s Guide” contains information on deploying the following assets:

- API Gateway
- ActiveTransfer
- Digital Event Services
- CloudStreams

Release 9.12

- The “webMethods Deployer User’s Guide” contains information on deploying AgileApps assets.

Release 9.8

- In the “webMethods Deployer User’s Guide”, under the section “Universal Messaging Assets”, the following new assets were added:
 - Topic Connection Factories
 - Queue Connection Factories
 - XA Connection Factories
 - JNDI Topics
 - JNDI Queues

These assets can now be deployed to a target server using Deployer.

- The “webMethods Deployer User’s Guide” now contains information on deploying Application Platform assets.
- Software AG documentation is no longer available on the Software AG installer. You can access all

Software AG documentation on the [Documentation website](#).

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Deployer

Release 10.3

Added Item	Description
Option to include Java shared code for Java services in the Project Automator XML file	<p>You can now include or exclude Java shared code for selected Java services. In the exported XML file, add the new attribute “selectAllFiles” for the “JavaService” element to include or exclude the Java shared code</p> <p>Example:</p> <pre><JavaService name="testDeployPkg.javaSvc:javaSvc" package="testDeployPkg" srcAlias="ISSource" selectAllFiles="true"/></pre> <p>Set “selectAllFiles” to “true” to include the Java shared code. The default value is “false”.</p> <p>For more information about the <i>JavaService</i> tag, see the sample XML file <i>ProjectAutomatorSampleForRuntime.xml</i> provided in the <i>Integration Server_directory/instances/instance_name/packages/WmDeployer/config</i> directory.</p>
Task Engine	Deployer now supports deployment of Task Engine assets to Integration Server runtimes.

Release 10.1

Added Item	Description
CreateIndex attribute	A new attribute <i>createIndex</i> is now available that allows you to create repository indexes. Set this attribute to "true" to create the index in the source repository. Setting this attribute to "false" will not create the index in the source repository. Default value is "false".
Page Depth property	<p>If the project is for My webMethods Server, you can set the <i>Page Depth</i> property for the project under the MWS Deployment Options area.</p> <p>If the value of this property is 1, all first level child pages that are under a selected parent page are deployed, even if the child pages are not selected in the deployment set. Default value is 1.</p> <p>If the value of this property is 0, only those child pages that are selected will be deployed. Child pages that are not selected will not be deployed.</p>
Digital Event Services	Deployer now supports deployment of Digital Event Services (DES) assets.
CloudStreams	Deployer now supports deployment of CloudStreams assets.
ActiveTransfer	Deployer now supports deployment of ActiveTransfer assets.
API Gateway	Deployer now supports deployment of API Gateway assets.

Release 9.12

Added Item	Description
AgileApps	Deployer now supports deployment of AgileApps version 10.7 assets and later.

Release 9.10

Deprecated Item

Universal Messaging cluster configuration

Replacement, if any

Cluster configuration is deprecated as a deployable asset type. Use the Universal Messaging cluster management feature in Software AG Command Central.

Release 9.9

Added Item

webMethods Business Rules

Description

- Deployer now allows webMethods Business Rules assets to be built and deployed to the Rules Management Console in My webMethods Server.
- Rule project is a new asset added to Business Rules Assets section.
- Business Rules runtime is now renamed to Business Rules IS.
- Deployer now supports Business Rules MWS runtime.

Universal Messaging

Deployer now supports deployment of assets to Universal Messaging servers that are configured to enforce authentication. Both basic authentication (username/password) and certificate-based authentication are supported.

Release 9.8

Added Item

Application Platform

Description

Deployer now supports deployment of Application Platform assets.

My webMethods Server

Deployer now allows users to rollback a previous deployment of My webMethods Server assets. Deployer also allows users to browse and delete existing My webMethods assets from a My webMethods Server.

Added Item	Description
webMethods Business Rules	<p>Deployer now allows users to rollback a previous deployment of webMethods Business Rules assets from a Rules Engine on Integration Server.</p> <p>Deployer also allows users to browse and delete existing webMethods Business Rules assets from a Rules Engine on Integration Server.</p>

Asset Build Environment

Release 10.3

Added Item	Description
Uploading Composites and Descriptors to a Git repository	You can now use Asset Build Environment to push composites and descriptors to a Git repository by specifying additional properties in the <i>build.properties</i> file.
Command Central	Asset Build Environment now supports building of Command Central composite assets. Software AG Command Central can now export configuration properties for Software AG runtime components as YAML templates, from which you can create composite assets.

Release 10.1

Added Item	Description
API Gateway	Asset Build Environment can now be used to build the composites for API Gateway.
ActiveTransfer	Asset Build Environment can now be used to build the composites for ActiveTransfer.
CloudStreams	Asset Build Environment can now be used to build the composites for CloudStreams.
Digital Event Services	Asset Build Environment can now be used to build the composites for Digital Event Services (DES).

Release 9.12

Added Item	Description
AgileApps	Asset Build Environment can now be used to build the composites for AgileApps.

Release 9.8

Added Item	Description
Application Platform	Asset Build Environment can now be used to build the composites for Application Platform.

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

DEPABE-RM-103-20181015

Software AG Designer 10.3 Readme

October 2018

This file contains important information you must read before using Software AG Designer 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes	3
4.0	Fixes Included in Each Release.....	4
5.0	Other Resolved Issues.....	5
6.0	Documentation Changes.....	8
7.0	Added, Removed, Deprecated, or Changed Items.....	9
8.0	Copyright Information.....	12
9.0	Support.....	12

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- SDEF-2269
Secure storage master password provider that uses Windows APIs to encrypt a randomly generated 'master' password specific to the login credentials, fails to work in Amazon EC2 Windows 2012 R2 server system. An exception is displayed "Unable to encrypt master password for storage." in that case.
To work around this problem, navigate to Designer secure storage preference. Clear Windows Integration provider option. This would then use the "UI prompt" master password provider.
- SDEF-1929
In high screen resolution, Designer does not auto-scale icons and fonts as per the specified DPI. This issue occurs as a result of Eclipse Bug 462952.
There is currently no workaround for this issue.
- SDEF-1960
On Windows 10 operating system, Designer does not have default preference for the user interface appearance. This causes a difference in the appearance of Designer user interface.
To work around this issue, you must select the appearance theme in the Preferences page. In Preferences > General > Appearance, select Windows as Theme and select Default (current) as Color and Font theme. Restart Designer.
- SDEF-1832
On Mac OS X, the layout of Software AG Designer installation has changed to keep in line with Eclipse 4.5. As part of the layout change, the shell script designerc.sh is used to launch Software AG Designer. You can customize the bash script at Designer/Eclipse.app/Contents/MacOS/designerc.sh file. However, there is an issue with restarting Software AG Designer from within the Workbench. To work around this issue, close Software AG Designer and relaunch.
- SDEF-2369
On Linux platform (RHEL 7.3 or SUSE 12)

Designer stops responding on accessing SWT browser. This is due to the Eclipse bug https://bugs.eclipse.org/bugs/show_bug.cgi?id=467646.

Designer support for XULRunner 31.x is not available. To work around this issue, downgrade XULRunner version.

Upon clicking Help > About Software AG Designer, Designer displays the error message "MOZILLA_FIVE_HOME not set".

Also, the Welcome page for Designer does not appear properly. The links on the page are not ordering correctly and some icons on the Welcome page are not displayed. To resolve these problems, add the following JVM options in the 'eclipse.ini' file:

- Dorg.eclipse.swt.browser.DefaultType=Mozilla
- Dorg.eclipse.swt.browser.XULRunnerPath=/usr/lib64/xulrunner

Note: Modify the path based on the XULRunner installation path.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of Software AG Designer.

- The Eclipse update sites listed in Window > Preferences > Install/Update > Available Software Sites have been disabled. Software AG does not recommend using these sites to update Designer's Eclipse platform because doing so might have undesired consequences. Use the Software AG Update Manager to apply updates to Designer.
- On RHEL 7, while Software AG Designer is starting up, the following alert message appears: "Software AG Designer is not responding"
This message indicates that the initialization of Designer is in progress and does not indicate any issue with Designer. Software AG recommends that you click Wait in the alert message window and wait until Designer starts up completely.
- Opening an editor freezes the Designer workstation due to a particular gtk bug https://bugzilla.gnome.org/show_bug.cgi?id=686838.

To work around the problem, add the following Java option in the 'eclipse.ini' file:

- Dorg.eclipse.swt.internal.gtk.disablePrinting
- To Setup Software AG Designer in Linux platform, refer <http://www.eclipse.org/swt/faq.php#browserwebkitgtk> for recommended configurations.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.2

- SDF_9.12_Fix1
- SDF_9.10_Fix2
- SDF_10.1_Fix1
- CEP_10.1_Fix1

Release 10.0

- CEP_9.7_Fix1
- CEP_9.8_Fix1

Release 9.10

- SDF_9.8_Fix1

Release 9.8

- SDF_9.7_Fix1
- SDF_9.6_Fix2
- SDF_9.5_SP1_Fix2

Release 9.7

- CEP_9.5_SP1_Fix4
- SDF_9.6_Fix1
- SDF_9.5_SP1_Fix1

Release 9.6

- CEP_9.5_SP1_Fix3

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 9.12

- SDEF-2006
When Designer is launched for the first time from the Start menu, the following error message appears: "An internal error occurred during: "Setup check". There is no eclipse.launcher property defined". This error message can be ignored and does not notify any problem with the Designer setup. This issue occurs due to Eclipse bugs 471731 and 464122.
This issue is resolved.

Release 9.10

- SDEF-1185
The context menu in the Project Explorer view of Designer displays the Import option twice upon deleting a project from the Project Explorer view.
This issue occurs as the result of the Eclipse Bug 448873.
This issue is resolved.
- SDEF-1495
Designer displays the same icons multiple times in the toolbars of various views in Designer upon resetting a perspective to its original layout.
This issue occurs due to an Eclipse known issue Bug 448873.
This issue is resolved.

Release 9.8

- SDEF-1339
Designer requires an installation of Java SE in order to run on Mac OS X.
If no other Java SE is installed apart from the JVM that was installed with Designer, Designer running on Mac OS X displays a message at startup stating that a Java SE Runtime must be installed.
This issue is resolved. To resolve this issue, a new shell script, designerc.sh, is provided to launch Designer from a terminal shell. This shell script is available in the Software AG root installation directory/Designer/eclipse directory. Alternatively, installing Java SE also resolves this issue. In both these cases, Designer will use the JVM provided by Software AG.
- SDEF-1575
Designer updated to include JGit version 3.4.2 that resolves a JGit client vulnerability in Eclipse. A vulnerability affecting all versions of Git clients was announced in <https://github.com/blog/1938-vulnerability-announced-update-your-git-clients> (Eclipse Bug 456947).

This problem is resolved in JGit version 3.4.2, which is shipped along with Designer 9.8.

- SDEF-1498
After configuring NTLM authentication for the process audit database in Integration Server, Designer issues the following error when testing the connection:
[SoftwareAG][SQLServer JDBC Driver]NTLM (type-2) Authentication was requested but the required DDJDBCx64Auth05.dll was not found on the path specified by the java.library.path system property.
This issue is resolved.
- SDEF-1280
Right-clicking in the SVN Repositories view does not display the context menu.
When you right-click in the SVN Repositories view in Software AG Designer, the context menu does not show up. The menu is displayed only after right-clicking several times. The problem occurs due to Eclipse 4.3 compatibility issues with the SVN Repositories right-click context menu.
This issue is resolved.
- SDEF-915
When defining a Software AG Runtime instance in the Servers view, two Password Required dialog boxes appear.
When you define a Software AG Runtime instance in the Servers view after starting Designer with a new workspace, two Password Required dialog boxes appear when you select the Platform Manager URL box.
This issue is resolved.

Release 9.7

- SDEF-1243
Creating a Software AG Runtime instance using a secure connection fails.
In the Servers View, when you attempt to create a Software AG Runtime instance using an https Platform Manager URL and then click 'List Servers', Software AG Designer returns an error and no connection is established.
The issue is resolved. A secure connection is now the default when creating a Software AG Runtime instance.
- SDEF-917
Fix names are not clearly displayed in Software AG Designer.
Software AG Eclipse features and plug-ins encode the fix number as the fourth part of their full versions. For example, the version 8.2.3.0001-0235 represents fix #1 of version 8.2, service pack 3, build 235. In addition, a single product might comprise several features, and a fix might update only some features. Thus, identifying the latest fix becomes complex.
The About Software AG Designer dialog box has been enhanced to display clear information about the installed products, organized in tabs according to the provider.
The Software AG tab displays all installed Software AG products by name, including version and the highest fix number, if a fix has been applied. For example:
webMethods Service Development

Version 9.7 (fix #3 applied)

- SDEF-916

The button labels in the About Software AG Designer dialog box do not provide information about the installed products.

The button tool-tips in the About Software AG Designer dialog box display the provider name, for example Software AG, instead of the product name. When checking the version and fix level of a Designer plug-in, you might need to click a number of buttons before identifying the correct button for the product.

Now the About Software AG Designer dialog box displays clear information about the installed products, organized in tabs according to the provider.

The Software AG tab displays all installed Software AG products by name, including version and fix number, if a fix has been applied. For example:

webMethods Service Development

Version 9.7 (fix #3 applied)

In addition, the button tool-tips display the Eclipse feature(s) related to a particular product.

Release 9.6

- SDEF-1291

The New Server wizard in Software AG Designer displays an incorrect error message when validating an IPv6 address.

While creating a new Software AG Runtime server in Designer, if you provide an invalid IPv6 address in the Platform Manager URL field, the New Server wizard displays the following incorrect error message: "Cannot connect to the Platform Manager. Check the URL and the credentials."

This issue is resolved. Now the New Server wizard displays the message: "The URL is invalid."

- SDEF-1010

Software AG Designer does not display the Welcome page properly.

On the Welcome page in Designer, when you click the "Visit Software AG Community Website" link and then go back to the Welcome page using the "Navigate to previous topic" arrow, Designer displays an empty Welcome page.

This issue is resolved. Now Designer opens the "Software AG Community Website" link in an external window.

- SDEF-894

When the Welcome page of Software AG Designer is open as a view, the page does not inform you that you have no products installed.

With only Designer installed, when you open the Welcome page and then double-click the page tab, the minimized Welcome page does not display the message: "You have no installed products."

This issue is resolved.

- SDEF-893

The Welcome page of Software AG Designer is not displayed properly after using the "Customize page" toolbar icon.

When you click the "Customize page" toolbar icon on the Designer Welcome page and select a

home page theme other than Software AG, the Welcome page layout becomes unreadable. This issue is resolved. The "Customize page" icon is no longer available.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 9.12

- The following new topic is included in the online help set *Tips, Training, and Other Resources* and in the PDF publication *Working with Software AG Designer*:
 - Configuring the Secure Storage

Release 9.10

- The following new topics are included in the online help set *Tips, Training, and Other Resources* and in the PDF publication *Working with Software AG Designer*:
 - Enabling Automatic Updates
 - Enabling Eclipse Update Sites
 - Enabling Error Reporting Notifications
 - Enabling Preference Recorder

Release 9.9

- The following new topics are included in the online help set *Tips, Training, and Other Resources* and in the PDF publication *Working with Software AG Designer*:
 - Verifying Java Byte Code
 - Java Code Cache

Release 9.8

- Software AG documentation is no longer available on the Software AG installer. You can access all Software AG documentation on the [Documentation website](#).
Note: Software AG Designer online help and other online helps that are installed along with Designer features are still available as part of Designer Eclipse Help under the Software AG Designer Guides node. However, the Designer documentation that is available on the

[Documentation website](#) might contain more comprehensive information about the new features.

- Working with Software AG Designer now contains a new topic, Managing the Designer User Configuration, which includes information that was available in the following topics as well additional information related to installing Designer into a subfolder of Program Files:
 - Implementing a Multi-User Eclipse Configuration
 - Configuring Eclipse for Non-Administrator Accounts
 - Considerations when Starting Designer on Windows

Release 9.7

- A new section, “Finding Installed Products, Versions, and Fixes”, has been added to the PDF publication *Working with Software AG Designer* and to the online help set *Tips, Training, and Other Resources*.

Release 9.6

- A new section, “Considerations when Starting Designer on Windows”, has been added to the PDF publication *Working with Software AG Designer* and to the online help set *Tips, Training, and Other Resources*.

Release 9.5

- The topic “Configuring SSL Connections in Designer” is added to the online help set *Tips, Training, and Other Resources* and to the PDF publication *Working with Software AG Designer*.

7.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Changed Item	Description
Eclipse version upgrade	Software AG Designer and all its plug-ins are now supported on the latest service release of Eclipse 4.7.3.

Release 10.1

Changed Item	Description
Eclipse version upgrade	Software AG Designer and all its plug-ins are now supported on the latest service release of Eclipse 4.6.3.

Release 9.12

Changed Item	Description
Eclipse version upgrade	Software AG Designer and all its plug-ins are now supported on the latest service release of Eclipse 4.5.2.
Default encrypting algorithm	Software AG Designer is enhanced with PBEWithSHA1AndDESede as the preselected algorithm.

Release 9.10

Removed Item	Replacement, if any
CVS Support	CVS is no longer included with Eclipse packages by default. You can install CVS integration component into Software AG Designer from the Eclipse Marketplace.

Changed Item	Description
Eclipse version upgrade	Software AG Designer and all its plug-ins are now supported on the latest service release of Eclipse 4.5.

Release 9.9

Changed Item	Description
Eclipse version upgrade	Software AG Designer and all its plug-ins are now supported on the latest service release of Eclipse, 4.4.2.

Release 9.8

Added Item	Description
Installation folder for Designer	It is now possible to install Designer in a subfolder of Program Files.

Changed Item	Description
Eclipse version upgrade	Software AG Designer and all its plug-ins are now supported on Eclipse 4.4.

Release 9.7

Added Item	Description
Ability to select and copy product information from the Software AG Preferences page.	It is now possible to select some or all rows in the Installed Software AG Features table and copy the information to the clipboard.

Changed Item	Description
"About Software AG Designer" dialog box.	The "About Software AG Designer" dialog box was redesigned and enhanced to display installed products categorized by provider. It displays information about version and applied fixes for the products provided by Software AG.

Release 9.6

Removed Item	Replacement, if any
"Customize page" icon on Welcome page.	

Changed Item	Description
Eclipse update sites are disabled by default.	The Eclipse update sites listed in Window > Preferences > Install/Update > Available Software Sites have been disabled. Software AG does not recommend using these sites to update Designer's Eclipse platform because doing so may have undesired consequences.

Release 9.5

Software AG Designer is now based on Eclipse version 4.3. The plugins that Software AG provides are developed and tested for Eclipse version 4.3.

8.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

9.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

DES-RM-103-201801015

webMethods Digital Event Persistence 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Digital Event Persistence 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find the suite-related information listed below.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	1
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	3
5.0	Other Resolved Issues.....	3
6.0	Documentation Changes	4
7.0	Terminology Changes	4
8.0	Added, Removed, Deprecated, or Changed Items.....	4
9.0	Added, Removed, Deprecated, or Changed APIs	5
10.0	Copyright Information.....	6
11.0	Support.....	7

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published.

For known issues found later, go to the Knowledge Center on the [Empower website](#).

- WF-6298
webMethods Digital Event Persistence does not support persistence to Elasticsearch clusters with Shield enabled.
There is currently no workaround for this issue.
- EVS-205
When you configure a Digital Event Persistence service in an Apama correlator runtime, the connection to the event store cannot be tested. The system always displays a warning when you save the service, even if the configuration is correct.
There is currently no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- EVS-458
webMethods Digital Event Persistence is in compliance with the General Data Protection Regulation (GDPR) and does not store, collect, or process any personally identifiable information.
- Before you can use Digital Event Persistence with HDFS as the storage engine, you must configure the Hadoop cluster. You must copy the custom Hive SerDe and Joda Date/Time libraries from your Event Persistence installation to your HDFS CDH 5.3.0 distribution.
 1. In your Software AG installation, locate the Joda Date/Time and the custom Event Persistence Hive SerDe .jar files:
 - `joda-time_2.9.3.jar` – available in the *Software AG_directory*\common\runtime\bundles\platform\eclipse\plugins directory.
 - `com.softwareag.evp.hive.serde_10.3.0.0000-nnnn.jar` – available in the *Software AG_directory*\common\runtime\bundles\evs-cdh530\eclipse\plugins directory (where *nnnn* is the build number of your Event Persistence installation).
 2. Copy both files to the Hive library directory on all nodes in the Hadoop cluster where Hive is running, for example *HDFS_directory*/lib/hive/lib.
 3. Copy both files into the Yarn library directory on all data nodes in the Hadoop cluster, for example *HDFS_directory*/lib/hadoop-yarn/lib or *HDFS_directory* /lib/hadoop-mapreduce/lib if using MRv1.
 4. Restart Hive.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.1

- Event Persistence 10.0 Fix 1

Release 9.12

- Event Persistence 9.10 Fix 1

Release 9.10

- Event Persistence 9.9.0 Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.2

- WF-8168
webMethods Digital Event Persistence does not provide a migration utility for migrating Event Persistence services from previous releases.
The issue is resolved. Digital Event Persistence service configurations can now be migrated from previous releases using the Digital Event Services Migration Utility.
- EVS-285
Digital Event Persistence cannot persist Digital Event Services (DES) events to HDFS if the events consist only of ANY and MAP type fields.
The issue is resolved.
- EVS-311
Digital Event Persistence cannot persist events to HDFS if the event type definition contains an underscore in the namespace or in the event type name.
The issue is resolved.
- EVS-312
The Digital Event Persistence driver for JDBC date/time methods are not compatible with the Software AG MashZone NextGen date/time methods.
The issue is resolved.

Release 10.1

- WF-6022
webMethods Digital Event Persistence is not supported in non-OSGi event-driven architecture environments.
The issue is resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.2

- A new guide was added for Digital Event Persistence called *Using Digital Event Persistence Driver for JDBC*.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.1

Added Item	Description
Digital Event Persistence driver for JDBC	Digital Event Persistence supports querying digital and EDA events from Elasticsearch 2.3.2 using a JDBC driver.

Release 10.0

Added Item	Description
Support for Digital Event Services	Event Persistence supports persisting digital events to, and querying events from, HDFS CDH 5.3.0 and Elasticsearch 2.3.2.

Added Item	Description
Support for SSL with Search Guard for Elasticsearch 2.3.2	Event Persistence supports persisting digital and EDA events to an Elasticsearch 2.3.2 instance or cluster with an installed Search Guard plugin.

Removed Item	Replacement, if any
Support for Elasticsearch 1.7.2 as an event store	Elasticsearch 2.3.2

Release 9.12

Added Item	Description
Support for Elasticsearch 2.3.2 as an EDA event store	Event Persistence supports persisting EDA events to and querying events from Elasticsearch 2.3.2.

9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 9.12

Added API	Description
com.softwareag.eda.estimate.query.api.builder.QueryBuilder	In addition to using an SQL-like language, the EVP simple query API now supports a simple query domain-specific language (DSL). The QueryBuilder enables a user to generate simple queries using Java.
BETWEEN	Added support for BETWEEN operator to the simple query API, the simple query DSL, and to the full text search DSL.

Changed API	Description
com.softwareag.eda.estimate.query.api.FullTextQuery	Added setFilter(ExpressionBuilder filter) method to enable filters on full text searches.

Release 9.10

Added API	Description
com.softwareag.eda.estimate.query.api.FullTextQuery	Contains methods that allow a user to define and execute a full text query. Currently, only the Elasticsearch storage engine supports full text search.
com.softwareag.eda.estimate.query.api.FullTextQueryResponse	Contains the result set from the execution of a full text query. A full text query response contains an array of full text query hits.
com.softwareag.eda.estimate.query.api.FullTextQueryHit	Contains an individual event result from a full text query.

Changed API	Description
com.softwareag.eda.estimate.query.api.Query	Added an explain() method for debugging purposes. Query.explain() method returns a byte[] containing the user specified query and the native query that is generated from it.

10.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

EVS-RM-103-20181015

Software AG Digital Event Services 10.3 Readme

October 2018

This file contains important information you must read before using Software AG Digital Event Services 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	1
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	3
5.0	Documentation Changes	3
6.0	Added, Removed, Deprecated, or Changed Items.....	4
7.0	Copyright Information.....	6
8.0	Support.....	6

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- DEV-1350
When you configure an Event Console with "Use Universal Messaging Service" selected and specify a non-default "Provider URL", the Event Console uses the default Universal Messaging provider

URL.

The Event Console is a tool in Software AG Designer that enables administrators to monitor the publishing of digital events. When launching an Event Console, you can specify a Universal Messaging server in the "Provider URL" configuration field. However, the Event Console ignores this setting and always uses the default Universal Messaging configuration that points to `nsp://localhost:9000`.

As a workaround, select "Use External Configuration" and specify the URL location for the Universal Messaging server in the "Configuration Location" field.

- DEV-1428

If Digital Event Services (DES) is embedded in an OSGi-based product runtime, restarting that product runtime might result in the following error:

`"com.softwareag.events.routing.EventRoutingException: Invalid Configuration class type null."`

The issue is caused by the order in which the DES bundles start.

As a workaround, use the following procedure to resolve the error:

1. Navigate to `Software_AG_Directory\profiles\instance_name\configuration\org.eclipse.equinox.simpleconfigurator`.
2. Open the `bundles.info` file in a text editor.
3. On the line that starts with `"com.softwareag.events.routing,10.3.0.0000-0nnn"`, replace "4" with "5" to increase the start level of DES, for example:
`com.softwareag.events.routing,10.3.0.0000-0nnn,..../common/runtime/bundles/digital-event-services/eclipse/plugins/com.softwareag.events.routing_10.3.0.0000-0nnn.jar,5,true`
4. Restart the runtime in which DES is embedded.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- DEV-1219

Software AG Digital Event Services is in compliance with the General Data Protection Regulation (GDPR) and does not store, collect, or process any personally identifiable information.

- NUM-6873

After you restart a shared durable subscriber to a Digital Event Services (DES) event type, the subscriber might receive events out of order.

The issue occurs when the subscriber is configured with a Universal Messaging source service and the target Universal Messaging server has the `SyncQueuePublisher` property set to `"true"`. The default value of `SyncQueuePublisher` for the `webMethods` configuration profile of Universal Messaging is set to `"false"`. However, the Universal Messaging custom configuration profile for Terracotta has `SyncQueuePublisher` set to `"true"`.

If you switch to the Universal Messaging custom configuration profile for Terracotta, make sure that `SyncQueuePublisher` is set to `"false"`.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.2

- DEV_10.2_DigitalEventServicesSharedBundles_Fix1

Release 10.1

- DEV_10.1_Digital Event Services Libraries_Fix4
- DEV_10.1_Digital Event Services Runtime Bundles_Fix4
- DEV_10.1_Digital Event Services Shared Bundles_Fix2
- DEV_10.1_Digital Event Services Designer_Fix1

Release 10.0

- DEV_10.0_Digital Event Services Libraries_Fix1
- DEV_10.0_Digital Event Services Runtime Bundles_Fix1
- DEV_10.0_Digital Event Services Shared Bundles_Fix1

Release 9.12

- EDA_9.12_Digital Event Services Libraries_Fix9
- EDA_9.12_Digital Event Services Runtime Bundles_Fix9
- EDA_9.12_Digital Event Services Shared Bundles_Fix1

5.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 9.12

- A new guide was added for Digital Event Services: *“Using Digital Event Services to Communicate*

between Software AG Products”.

6.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Event Generator Utility	The Event Generator is a tool in Software AG Designer that enables developers to generate streams of digital events. The Event Generator is also available as a command-line tool. For more information, see the Digital Event Services documentation.
Non-queued Delivery Mode	Digital Event Services now provides a configuration switch to bypass the store-and-forward queue. You can use non-queued delivery for service groups that have one destination service of type Universal Messaging or Digital Event Persistence.

Release 10.2

Added Item	Description
Secure communication configuration through Command Central	Using Software AG Command Central, you can configure Digital Event Services (DES) Universal Messaging services for communication over Secure Sockets Layer (SSL) with a Universal Messaging server. For more information, see the Digital Event Services documentation.
License configuration through Command Central	You can now manage Digital Event Services licenses using Software AG Command Central. For more information, see the Digital Event Services documentation.

Release 10.1

Added Item	Description
Deployment of custom event types	Software AG Deployer now supports deployment of DES assets. You can use webMethods Asset Build Environment to build composites for DES.
Migration from Command Central	You can use a standalone DES migration utility in Software AG Command Central.
Encrypted event transmission	Digital Event Services supports the Universal Messaging NSPS protocol for secure communication. For more information, see the Digital Event Services product documentation.
Software AG Event Console in Software AG Designer	A tool in Designer that enables administrators to monitor and diagnose the publishing of digital events of a given event type.
Digital Event Type Language Updates	
- New "Any" field data type	A field that can have values of any data type that the DES event type language supports.
- New "Map" field data type	A field that maps keys to values.
- New "Time" field data type	A field that represents a specific instant of time with millisecond precision.
Reliable delivery over In-Process (IP) service	The In-Process (IP) service now supports durable subscriptions and can be used for reliable communication.

Release 10.0

Added Item	Description
In-Process (IP) service	The IP service allows different parts of an application runtime to exchange events.

7.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

8.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

DEV-RM-103-20181015

Dynamic Business Orchestrator 10.3 Readme

October 2018

This file contains important information you must read before using Dynamic Business Orchestrator 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	3
5.0	Other Resolved Issues.....	3
6.0	Documentation Changes	5
7.0	Added, Removed, Deprecated, or Changed Items.....	5
8.0	Copyright Information.....	5
9.0	Support.....	6

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

- Creating and saving DBO processes in Designer requires installation of Designer->Business Processes-> Process Task Development 10.1.

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- DBU-438
Searching for logged fields of type "float" in a DBO process instance will not return correct values when using the equals operator.
When constructing a search of logged fields of type "float" in a DBO process instance, using the equals operator will not return correct results in Business Console for DBO processes.
Workaround: When searching for logged fields of type float, supported comparisons are greater than (">") and less than ("<").
- DBU-482
DBO actions like play and restart involve encoding and decoding of the process pipeline. In the event, numeric fields in the pipeline with datatypes like integer and float may get altered to long and double respectively. This may cause issues with the evaluation of conditions in the decision table that use those fields when a restart or play action is involved.
There is no workaround for this issue.
- DBU-519
An incorrect status is displayed for a user task step in a loop where one of the loop iterations fails.
When a process containing a user task contained in a loop fails in one of the loop iterations, the step is incorrectly shown as running rather than failed.
There is no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- WMN-6319
pub.monitor.archive:processArchive does not archive DBO instances in addition to PE instances. In order to archive DBO instances, two new parameters are added to Operation parameters table, DBO_PROCESS_STATUS_CRITERIA and DBO_PROCESSES. To archive DBO processes set

DBO_PROCESSES to true. By default DBO_PROCESS_STATUS_CRITERIA are set to archive instances with status Completed, Canceled and Terminated. These parameters can be set using the pub.monitor.archive:setOperationParameters service.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- MON_10.1_Fix3
- MON_10.1_MWS_Fix3
- DBU_10.1_Fix1
- DBO_10.2_Fix2

Release 10.2

- DBO_10.1_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

- DBO-113
Configuring an IS cluster results in an exception on the WmDBO home page.
After installing and starting an Integration Server instance where DBO is installed, configuring an IS cluster will result in the exception “could not initialize cache manager SoftwareAG.IS.DBO” on the WmDBO home page.
This issue is resolved.
- DBO-124
DBO process containing step with inline document cannot be saved.
A DBO process that uses IS services with Document or Document list in the service signature of a step will result in process not able to upload or execute exception when saving in Designer.
This issue is resolved.
- DBU-523
Stage is incorrectly shown as completed when hitting the breakpoint of an End Milestone step.
An “End Milestone” for a stage on a step that has breakpoint will incorrectly show the stage as

completed when the breakpoint hits.

This issue is resolved.

- WMDPD-9337
DBO models fail deployment
If a DBO model is deployed using Deployer ACDL, a class loading failure may be observed.
This issue is resolved.
- WMDPD-8889
No visual cue is provided for setting input or output mapping for a step with Dynamic processes.
When setting the pipeline mapping for Dynamic processes, the Pipeline view displays map elements for that step depending upon the area of the step selected. The step type that supports mapping now has a left "side" and a right "side", such that when you select the left side of the step its input mapping is shown in the Pipeline view, and when you select the right side of the step its output mapping is shown in the Pipeline view. However, there is no visual cue that indicates input our output mapping is being selected.
This issue is resolved.
- DBU-241
Step Summary panel may display incorrect entries for subprocesses and steps.
Executing a DBO process containing a subprocess with looping and nested subprocess with looping will display incorrect entries for the looped instances in the Step Summary panel.
This issue is resolved.
- DBU-343
Status of task step execution in a loop displays all task steps with status of the last task step executed.
When a DBO process with a task step contained in a loop is executed, the status of all the task steps is displayed as the status of the last iteration of the task step in the loop in the Step Summary panel.
This issue is resolved.
- DBU-336
Instances of task steps executed in a loop contain the same task ID in Step Summary table.
If a DBO process with a task step contained in a loop is executed with multiple instances, each instance will contain the same task ID when displayed in the Step Summary panel.
This issue is resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.1

- Dynamic Business Orchestrator Help is a help set available in online help and PDF format. Dynamic Business Orchestrator Help includes information on how to configure and use Dynamic Business Orchestrator.

7.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Dynamic Business Orchestrator plug-in for Software AG Platform Manager	

8.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

9.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

DBO-RM-103-20181015

webMethods EntireX 10.3 Readme

October 2018

This file contains important information you must read before using webMethods EntireX 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	4
6.0	Documentation Changes	4
7.0	Terminology Changes	6
8.0	Added, Removed, Deprecated, or Changed Items.....	7
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	28
10.0	Added, Removed, Deprecated, or Changed Parameters.....	29
11.0	Added, Removed, Deprecated, or Changed APIs	31
12.0	Copyright Information.....	31
13.0	Support.....	31

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- EXX-11107
COBOL Wrapper limits long Broker password to 32 characters.
COBOL Wrapper limits long RPC user ID/password to 8 characters
- EXX-11183
Administration of Mainframe Brokers with one-time passwords not possible.
- EXX-11174
RPC Server for CICS does not validate passphrases (long RPC user ID/password).
- EXX-11159
Impersonation=yes not working if client uses old protocol (prior to 2050).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

UNIX / Windows:

- EntireX Bundles 10.1 Fix 12
- EntireX Designer 10.1 Fix 13
- EntireX Core 10.1 Fix 14
- EntireX Broker 10.1 Fix 17

z/OS:

- EntireX RPC Server 10.1 Fix 8 for z/OS
- EntireX Broker and Stubs 10.1 Fix 12 for z/OS

Release 10.1

- EXX_9.12_Designer_Fix1
- EXX_9.12_SPM_Fix3
- EXP912P010
- EXX_9.12_Core_Fix11
- EXX_9.12_Broker_Fix12
- EXX912L016
- EXB912L016

Release 9.12

- EXX_9.10_Designer_Fix2 Fix 2 for Eclipse

Release 9.10

- EXX_9.9_Core_Fix2 Fix 2 for EntireX Core
- EXX_9.9_SPM_Fix3 Fix 3 for SPM
- EXX_9.9_Designer_Fix5 Fix 5 for Eclipse
- EXB990L006 Fix 6 for z/OS
- EXX990L006 Fix 6 for z/OS
- XAI_9.9_Fix2 Fix 2 for the EntireX Adapter

Release 9.9

- EXX_9.7.0_Fix10 Fix 10 for EntireX Core
- XAI_9.7.0_Fix10 Fix 10 for EntireX Adapter
- EXX_9.7.0_Designer_Fix15 Fix 15 for Eclipse
(if Natural ONE is installed, must be version 8.3.5 or above)
- EXX_9.7.0_Fix11 Fix 11 for EntireX Runtime
- EXX970L019 Fix 19 for z/OS
- EXP970P020 Fix 20 for z/OS

Release 9.7

- EXB960P001 Fix 1 for z/OS
- EXX960P001 Fix 1 for z/OS

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 9.7

- EXX-6228
Under UNIX and Windows, you can now keep the current and the previous four Broker log files.
- EXX-6303
For COBOL RPC clients, performance for marshalling has been enhanced.
- EXX-6519
Some errors (e.g. error 0148) in the stub log did not contain the error class (e.g. 0215).
Stub log now contains the error class to identify the error.
- EXX-7019
Description of broker attribute `HEAP-SIZE` and dynamic memory management has been enhanced.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- Integration Scenarios
The scenarios Calling COBOL from REST and Calling Natural from REST have been added to reflect the new support of REST technology.

Release 10.1

- Integration Scenarios
The scenarios Calling Integration Server from COBOL and Calling Integration Server from Natural have been thoroughly reworked and expanded.

Release 9.12

- Command Central
The separate Command Central documentation has been reorganized; product-specific information is now provided with the product itself. See *Administering EntireX Broker with Command Central* in

the EntireX documentation. The command-line documentation has been enhanced, and a new section describing the graphical user interface is provided.

- Application Monitoring MashApp
As in earlier versions, a sample Application Monitoring MashApp is provided in Empower under Products & Documentation > Download Components > EntireX - Application Monitoring MashApp. This MashApp is no longer described in the main EntireX documentation. Separate documentation (PDF) and a readme file are also provided for download from Empower.

Release 9.10

- Web Services Stack
Multiple sections of the EntireX documentation reference the separate Web Services Stack documentation. Since webMethods Suite 9.8, this documentation is part of the *Software AG Infrastructure Administrator's Guide*, also available under <http://documentation.softwareag.com> > *Guides for Tools Shared by Software AG Products*.

Release 9.9

- Software AG documentation is no longer available on the Software AG installer. You can access all Software AG documentation on the [Documentation website](#).
- Documentation for EntireX Adapter is now incorporated in the EntireX documentation for ease of use. A standalone PDF file of the Adapter documentation is also provided for your convenience.
- For platform z/VSE, sections have been added to set up ATLS (Automatic Transport Layer Security).

Release 9.7

- COBOL Mapping Editor documentation thoroughly reworked. Functions documented for each interface type.
- Scenario "Calling Integration Server from COBOL" expanded.
- New documentation section Installing EntireX RPC Servers under IMS.
- Application Transparent Transport Layer Security (AT-TLS): various sections dealing with SSL or TLS support have been reworked and also include sections on how to set up AT-TLS.

Release 9.6

- Common Integration Scenarios section has been enhanced with regard to navigation. High-level, illustrated scenario descriptions lead to more detailed sections below.
- Documentation for mapping of fixed and unbounded arrays has been enhanced.

- Various sections dealing with SSL or TLS support have been reworked. See *Using SSL or TLS with the RPC Server* under CICS | Batch | IMS, and *SSL or TLS and Certificates with EntireX* in the Security documentation.
- A new section describes IBM Language Environment runtime options relevant for CICS, Batch and IMS RPC servers.

Release 9.5

- SVM File Handling
Documentation of SVM file handling has been enhanced for all supported RPC servers.
- CVM File Handling
Documentation of CVM file handling has been enhanced.
- Supported RPC Protocols
New section lists the RPC protocols supported by the different EntireX and Natural versions.
- Conversion Error Messages
All error messages of class 1003 have been reworked and several new messages have been added.
- Internationalization
The internationalization documentation has been thoroughly reworked.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 10.3

Old Term	New Term
EntireX Workbench	Designer

Release 9.12

Old Term	New Term
WebSphere MQ RPC Server	webMethods EntireX RPC Server for IBM® MQ
WebSphere MQ RPC Listener	webMethods EntireX RPC Listener for IBM® MQ

Release 9.7

Old Term	New Term
SVM file	Server-side mapping file.
CVM file	Client-side mapping file.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists features, functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Unbounded arrays with COBOL RPC clients	Now supported with COBOL 6 on z/OS.
Mapping COBOL data items to binary	In the COBOL Mapping Editor you can now map COBOL data items to IDL binary data.
Command Central Support for Mainframe Brokers	EntireX now supports Command Central for EntireX Brokers running on mainframe platforms.
Generating REST Resources from Adapter	You can now generate REST resources using the EntireX Adapter. All connection types are supported.
CICS Socket Listener Connection	The new Adapter connection type CICS Socket Listener Connection supports all CICS interface types: (DFHCOMMAREA, Channel Container and Large Buffer). CICS Socket Listener Connections use the CICS Socket Listener, a remote connector on z/OS to call CICS mainframe programs.
Direct Reliable RPC Listener Connection	The new Direct Reliable Listener Connection type for the Adapter supports inbound reliable connections using the Direct RPC component.
Service to generate a RACF PassTicket	With the new built-in Adapter service <code>pub.wmentirex.RACFPassTicket:generate</code> you can generate a RACF PassTicket.
Support for the new product "Adabas Replication Service for webMethods Integration Server"	The EntireX Adapter provides support for this product with two new connection types and additional screens in the Integration Server Administration Console.

Added Item	Description
Long Broker Password Support	New ACI Version 12 of Broker supports long passwords and password phrases. You are no longer limited to 32 bytes for password and new password in the ACI.
Long RPC User ID/Password Support	You can now use long RPC user IDs and passwords.
RACF Password Phrases	You can now use RACF password phrases with EntireX Broker and RPC servers under z/OS running with impersonation.
Application Monitoring	<ul style="list-style-type: none"> • The following connection types of the EntireX Adapter now support application monitoring: AS/400 Connection and CICS Socket Listener Connection. • All EntireX RPC servers now support Application Monitoring.
Docker Support	You have a choice of two methods of building a Docker image and running the Docker container: using scripts provided by EntireX, or using Command Central. This functionality is available for the components EntireX Broker, EntireX RPC Server for Java and EntireX RPC Server for XML/SOAP.
EntireX RPC Server for CICS Socket Listener	Allows standard RPC clients to communicate with CICS programs running on IBM CICS®.
EntireX CICS Socket Listener	A remote connector on z/OS to call CICS mainframe programs from the RPC Server for CICS Socket Listener or EntireX Adapter running on a UNIX or Windows platform.
Docker Support	<p>You can build an Docker image and run the Docker container using scripts provided with EntireX for the following EntireX components:</p> <ul style="list-style-type: none"> • EntireX Broker • EntireX RPC Server for Java • EntireX RPC Server for XML/SOAP
Long Password Support	The new ACI Version 12 of Broker supports long passwords and password phrases. The limitation to 32 bytes for password and new password in the ACI no longer applies.

Removed Item	Replacement, if any
The EntireX RPC Server for IBM i of EntireX version 7.1.1 running under IBM i (AS/400)	No longer supported. We strongly recommend using the RPC Server for AS/400 or the EntireX Adapter.
Methods <code>getEnvironment()</code> , <code>setEnvironment(String)</code> , <code>useCodePage()</code> and <code>useCodePage(Boolean)</code> of the Java class <code>BrokerService</code>	The methods are obsolete and deprecated. They have been removed.

Deprecated Item	Replacement, if any
Server-side mapping files (SVM)	These will be dropped in a future version. We strongly recommend using client-side server mapping files (CVM) for ease-of-use.
HP-UX	Software AG is deprecating support for HP-UX. There will be no new versions of EntireX on HP-UX in future releases.
EntireX Broker Administration Service	Will be dropped in the next version. The most important functionality will be covered adequately with other EntireX components.

Changed Item	Description
Installation package EntireX > Installation and Monitoring	This package is now provided as a new installation node with three subpackages: <ul style="list-style-type: none"> • Application Monitoring Data Collector • Command-line Scripts • Mainframe Broker Monitoring
Licensing	All EntireX RPC servers under UNIX and Windows now check for a valid license file.
Enhanced USTATUS Handling	By default, ACI request and response strings of USTATUS are now converted with ICU.
Adapter Listeners	When you create or update a listener, missing or necessary services are now generated automatically.
Enhanced Integration Server to IDL data type mapping	There are no more restrictions on the data types used in the Integration Server service.
OpenSSL	EntireX now uses OpenSSL 1.1.0 instead of OpenSSL 1.0.2.

Release 10.1

Added Item	Description
Increased platform support	EntireX now runs under Windows Server 2016.
COBOL Integration Enhancements	
COBOL Server using fixed-length tables in variable manner	Support for COBOL server programs that process a variable number of array elements in a fixed-size COBOL table has been extended. This affects the IDL Extractor for COBOL together with the RPC Server for CICS, the EntireX Adapter, the RPC Server for CICS ECI and the RPC Server for IMS Connect.
Interface Type COBOL Converter	A new interface type COBOL Converter has been introduced in the IDL Extractor for COBOL. This interface type is used together with the COBOL Converter connection type of the EntireX Adapter to convert Integration Server data structures from/to a byte array representing COBOL binary data.
IBM i (AS/400) COBOL Extraction	COBOL computational data items extracted for AS/400 are mapped to IDL type P (packed decimal) instead of IDL type I (integer).
IBM Enterprise COBOL for z/OS Support	EntireX RPC client and server components now support IBM Enterprise COBOL for z/OS V6.1, in addition to the versions 4.2 and 5.1 supported in earlier versions of EntireX.
Command Central Enhancements	
Installing EntireX using Command Central	EntireX can now also be installed using Command Central instead of the Software AG Installer.
Template-based provisioning	EntireX now supports template-based provisioning with Command Central. Using templates within Command Central you can install EntireX and - at the same time - add instances such as EntireX Broker and multiple RPC servers on local and remote hosts.
Administering RPC Servers using Command Central	EntireX RPC server for C, .NET, IMS Connect, Java, IBM MQ and SOAP/XML can be administered using Command Central.
Workbench Enhancements	

Added Item	Description
Preferences	The structure of EntireX preference pages in the EntireX Workbench has been simplified. It is now more compact with the most commonly used target environments - COBOL, Integration Server, Natural, PL/I and Web Services - on the first level relative to EntireX preference page. From preference page EntireX > Wrappers you can navigate to all wrappers.
IDL Extractor for Integration Server and Integration Server Wrapper	When the Extractor or the Wizard either creates a new connection or updates an existing connection, both the list of connection types and connections are now filtered. Connection types that require a license are only shown if a corresponding license file is available. Reliable RPC connections are only shown if all IDL programs contain only IN parameters. Also, if a server mapping file is available, only those connection types that support the interface type specified in the server mapping file are shown.
CVM/SVM Handling	Client-side mapping files (CVM) are now default in the EntireX Workbench. As server-side mapping files (SVM) will be dropped in a future version, we strongly recommend using client-side mapping files. These are easier to use and do not require any deployment on your server. Support for CVM files for platforms z/VSE and BS2000 will be introduced in a future version.
EntireX RPC Server Enhancements New RPC Server for AS/400	The new EntireX RPC Server for IBM® AS/400® enables you to remotely call server programs written in all ILE-based languages, for example C, COBOL, RPG.
RPC Server for CICS Abend Handling	As of version 10.1, the exit for the CICS RPC abend handling is no longer delivered in the LOAD module of the z/OS installation. The exit is assembled from the CEEWUCHA source delivered with the z/OS LE sample library CEE.SCEESAMP. The install job EXPINSTA delivered on EXX1010.JOBS has a step that assembles the CEEWUCHA exit.

Added Item	Description
User Exit for Additional HTTP Headers with RPC Server for XML/SOAP	A new user exit allows you to add HTTP headers before an RPC call, or to add an HTTP header to an optional retry call.
Configuration Parameter <code>entirex.server.verbose</code>	The configuration parameters <code>entirex.server.verbose</code> and <code>entirex.bridge.verbose</code> previously used by multiple servers and listeners are no longer available. Verbose logging is now enabled whenever the configuration parameter <code>entirex.trace</code> has a value greater than 0.
EntireX Adapter Enhancements	
COBOL Server using Fixed-length Tables in Variable Manner	The EntireX Adapter - together with the IDL Extractor for COBOL - supports additional approaches of a COBOL server that process a variable number of array elements in a fixed-size COBOL table (array).
New Interface Type AS/400 Connection	The new interface type AS/400 connection enables you to remotely call server programs written in all ILE-based languages, for example C, COBOL, RPG.
Alternative Mapping of IDL Data Types to Integration Server Data Types	IDL data types can now be mapped to non-string Integration Server data types. The main use case is to support JSON document types in Integration Server.
Other Changes and Enhancements	
Microsoft Visual Studio 2017 support	The C Wrapper and the DCOM Wrapper now support Microsoft Visual Studio 2017.
Unique message ID	With ACI version 11 and above, all messages sent to the broker are given a unique message ID. This message ID is useful for tracking individual messages in the trace and log files.
Postpone units of work	Service-specific attributes <code>POSTPONE-ATTEMPTS</code> and <code>POSTPONE-DELAY</code> have been added to postpone processing of UOWs that have been cancelled by the receiver. The UOWs are moved to the postpone queue instead of being deleted.
Support of 64-bit Time Values on z/OS	Broker attribute <code>PSTORE-VERSION</code> now has a new version 5 to support 64-bit time values on z/OS.

Added Item	Description
Improved Adabas PSTORE Handling	Adabas persistent store handling has been enhanced on all platforms. The new PSTORE version 5 offers significant improvement in performance. We strongly recommend you use this version.
CIS Version 10	The new object UOW-STATISTICS supplies important information on units of work per service. The CIS command SET-UOW-STATUS has been added to control postponed units of work.
Consistent Handling of Duplicates in Broker Attribute File	With this release, additional checks are performed on service-specific attributes in the broker attribute file. Duplicate entries are now detected and error message 00210035 is given. This applies to the default definitions and the individual definitions in all DEFAULTS=SERVICES sections. This behavior is now consistent for all sections of the attribute file.
SSL/TLS Hostname Verification in Java Components	For all Java-based components that act as an SSL client, the hostname verification has been changed to conform to the RFC 2818 standard. If the server certificate contains a subjectAltName extension of type dNSName, this name is now used as the identity. Otherwise, the Common Name field in the Subject field of the certificate is used. If only the Common Name field should be used as before, the SSL parameter ignore_rfc_2818=yes must be set in the Broker ID.

Removed Item	Replacement, if any
z/VM	EntireX no longer supports the operating system z/VM.
ETBSRV	The EntireX Broker command-line utility ETBSRV is no longer provided. You can use ETBINFO under z/OS UNIX Windows z/VSE BS2000 or Command Central instead.
EntireX Broker Tutorial	The Natural-based EntireX Broker Tutorial is no longer provided.

Deprecated Item	Description
Java API Class BrokerService	The obsolete methods <code>getEnvironment()</code> , <code>setEnvironment(String)</code> , <code>useCodePage()</code> and <code>useCodePage(Boolean)</code> of the Java class <code>BrokerService</code> have been deprecated. They will be removed with the next version of EntireX.
Server-side mapping files (SVM)	Server-side mapping files (SVM) will be dropped in a future version. We strongly recommend using client-side server mapping files (CVM) for ease-of-use.
EntireX RPC Server for IBM i	The of EntireX version 7.1.1 running under IBM i (AS/400) will no longer be supported in the next version of EntireX. We strongly recommend using the new RPC Server for AS/400 or the EntireX Adapter.
Java class BrokerService	The obsolete and deprecated methods <code>getEnvironment()</code> , <code>setEnvironment(String)</code> , <code>useCodePage()</code> and <code>useCodePage(Boolean)</code> of the Java class <code>BrokerService</code> will be removed in the next version.

Changed Item	Description
Automatic character conversion	EntireX Broker has a reworked mechanism for character conversion. Incorrect configurations (e.g. RPC communication without character conversion configured) are detected. In these cases the configuration defined in the broker attribute file is not used and a warning message is written to the broker's log file. Adapt your broker attribute file to avoid the message.
New SSL port default for Broker Administration Service	The default SSL port for the Broker Administration Service has changed from 57708 to 57808.
License file Handling	Under UNIX and Windows, the license file specified during installation is renamed by the Software AG Installer to "license.xml" and copied to the EntireX/config directory. The name and location of this file can no longer be changed as in earlier EntireX versions.

Changed Item	Description
EntireX Adapter license file handling	The license file specified in the Adapter license administration is renamed by the Adapter to 'license.entirex.xml' and copied to the IntegrationServer/instances/<instance_name>/config directory. The name and location of this file can no longer be changed as in earlier EntireX Adapter versions.
Support of 64-bit time values on z/OS	Broker attribute PSTORE-VERSION now has a new version 5 to support 64-bit time values on z/OS.
Enhancement to the Broker Agent	You can now specify the address of the network interface on which the Broker Agent will listen.
Broker Installation Verification	The broker verification programs bcoc (client) and bcos (server) are delivered in executable form (binary, load module) only.

Release 9.12

Added Item	Description
Increased platform support Workbench enhancements	EntireX now supports AIX 7.2. <ul style="list-style-type: none">Enhanced COBOL MPO support: For MPO groups based on a <code>REDEFINE</code> declaration, the MPO selector definition can be anywhere in the <code>DATA DIVISION</code> of the COBOL source: before, inside or after the MPO group. With the IMS MPP Message Interface (IMS Connect) you can now determine the position of an MPO selector using a fixed offset starting from the end of the message. You can also use an offset from the beginning of the message as in earlier versions.
Brainstorm ideas	<ul style="list-style-type: none">The IDL Extractor for Natural now supports Arabic shaping as well as multibyte character sets.Date and Time support for EntireX Adapter [02848]. The EntireX Adapter now supports user-defined formats for mapping the IDL data types Date and Time.Trace Utility enhancement [03277]. The EntireX Trace Utility has been enhanced: a date field has been added to the generated CSV file.
Command Central	The following operations on EntireX Broker have been added: <ul style="list-style-type: none">Display ServicesDisplay Server Instances of a ServiceStop Server InstanceCreate new EntireX BrokersDelete existing EntireX Brokers
RPC server	Enhanced COBOL MPO support for EntireX COBOL RPC servers (CICS, Batch, IMS BMP, Micro Focus, CICS ECI, IMS Connect). See Workbench enhancements above for details.

Added Item	Description
EntireX Adapter enhancements	<ul style="list-style-type: none"> • User-defined formats for mapping the IDL data types Date and Time are now supported. • You can now use mixed-case passwords for CICS ECI connections. • Enhanced COBOL MPO support. See Workbench enhancements above for details.
XML/SOAP Listener and high availability	<p>The XML/SOAP Listener now supports persistent sockets, socket reconnect and security handling. This means it can now be used in high-availability scenarios where the EntireX Broker is load-balanced.</p>
ICU custom conversion under z/OS	<p>Custom conversion using ICU is now available under z/OS in addition to the support already provided under UNIX and Windows.</p>

Removed Item	Replacement, if any
Direct SSL/TLS support for broker stubs under z/OS	<p>Direct SSL/TLS support (using GSK) inside the broker stubs under z/OS has been dropped. We recommend using IBM's Application Transparent Transport Layer Security (AT-TLS) instead.</p>
Administration using System Management Hub	<p>Administration with SMH is no longer supported. This also includes the batch interface argbatch and SNMP. The most important functionality is provided by Command Central. Minor features have been moved to the command line or were dropped.</p>
Dynamic IDL/RPC parameters with IBM® MQ	<p>webMethods EntireX RPC Server and Listener for IBM® MQ no longer support dynamic IDL/RPC parameters.</p>
Microsoft Visual Studio 2010, 2012 or 2013	<p>These versions are no longer supported. The following EntireX components support Microsoft Visual Studio version 2015:</p> <ul style="list-style-type: none"> • C Wrapper • DCOM Wrapper • Microsoft Visual Studio Wizard for .NET Wrapper

Changed Item	Description
Command Central	When using the command-line mode to get information from or to administer EntireX, the data representation for input and output of some commands has changed.
Authorization rules	Authorization rules for UNIX and Windows are no longer managed with System Management Hub. Instead, rules can be stored in an LDAP repository (as in earlier versions of EntireX) or in a new section of the Broker attribute file, <code>DEFAULTS=AUTHORIZATION-RULES</code> .
Broker attribute file validation	The validation of the broker attribute file has been thoroughly reworked. Inconsistent definitions may result in an unexpected error when you start your broker.
COBOL RPC Client and Server	The sources generated by the EntireX Workbench component COBOL Wrapper can be compiled by any compiler supported by the COBOL Wrapper: standard COBOL compiler, for example IBM Enterprise COBOL for z/OS 4.2 or 5.1.
Microsoft Visual Studio support	<p>The following EntireX components support Microsoft Visual Studio version 2015:</p> <ul style="list-style-type: none"> • C Wrapper • DCOM Wrapper • Microsoft Visual Studio Wizard for .NET Wrapper <p>Older versions of Microsoft Visual Studio (2010, 2012 or 2013) are no longer supported.</p>

Changed Item	Description
EntireX Adapter	<p>The mapping of MPO groups to Integration Server data structures and to the signature has been changed with this version to simplify the usage of the MPO construct in the Integration Server.</p> <p>Previously the alternatives of an MPO group (groups in the IDL file with the attribute CHOICE) were mapped to arrays with either zero array elements (unselected alternative) or one array element (selected alternative). This has been changed such that arrays are no longer used. Unselected alternatives are suppressed and thus not visible in the output pipeline. The selected alternative is directly represented in the output pipeline without the enclosing array.</p> <p>However, this enhancement means the new output signature is not compatible with existing Adapter services. This also affects the runtime behavior. If you use MPO groups, regenerate these Adapter services from the Designer and adapt the services that are using the new Adapter service to the changed output signature.</p>
DIV Persistent Store Parameter Handling	<p>Defining a DIV persistent store has been streamlined. New broker attributes have been introduced to replace format parameters.</p>

Release 9.10

Added Item	Description
Increased platform support	<p>EntireX now supports z/OS version 2.2 and Windows 10 Professional and Enterprise 64-bit editions.</p>
Workbench enhancements	<ul style="list-style-type: none"> • COBOL program ID and Channel name can now be modified after extraction, using the COBOL Mapping Editor. • EntireX now uses Eclipse version 4.5.
EntireX Adapter	<p>New connection type "COBOL Converter" introduced to convert IS data structures from/to a byte array representing the COBOL binary data.</p>

Added Item	Description
Command Central	<p>Enhanced support for EntireX Broker instances running under UNIX or Windows. You can now perform the following operations on EntireX Broker in addition to the operations supported in EntireX version 9.9:</p> <ul style="list-style-type: none"> • Configure Application Monitoring • Configure EntireX Broker Persistent Store • Configure EntireX Broker Security • Enable and specify EntireX Broker Trace Level dynamically
KPIs for CPU time	<p>New KPIs are available with Command and Information Services interface for showing amount of CPU time consumed since Broker start. CPU time can also be shown in the Software AG product Optimize for Infrastructure.</p>
Support for Visual Studio 2012 and 2013	<p>The EntireX .NET Wrapper Wizard now supports Microsoft Visual Studio version 2012 and 2013 in addition to version 2010 already supported.</p>

Removed Item	Description
Windows 32-bit Operating Systems	<p>Software AG no longer supports Windows 32-bit operating systems. However, the following EntireX components are supported for 32-bit applications on Windows 64-bit operating systems:</p> <ul style="list-style-type: none"> • EntireX Mini Runtime • Transaction Object Editor of Broker ActiveX Control • .NET Wrapper Runtime
Java Message Service	<p>JMS support has been dropped.</p>
Publish and Subscribe	<p>The EntireX Broker communication model Publish and Subscribe is no longer supported. You therefore need to remove the broker attribute PUBLISH-AND-SUBSCRIBE from your broker attribute file, otherwise error ETBE0023 'Unknown attribute PUBLISH-AND-SUBSCRIBE ' is returned.</p>

Removed Item	Description
Swapping out New Units of Work	The ability to swap out new units of work that was provided in earlier EntireX versions is now no longer required. The corresponding broker attributes <code>SWAP-OUT-NEW-UOWS</code> and <code>MIN-UOW-CONVERSATIONS-IN-MEMORY</code> are no longer supported and will be ignored.
Library <i>broker.so</i>	Under UNIX, library <i>broker.so</i> has been replaced by library <i>libbroker.so</i> . Library <i>libbroker.so</i> was already delivered in earlier EntireX versions and is identical. Make sure you applications use only <i>libbroker.so</i> .
SMH Technical Information	The System Management Hub Technical Information Agent is no longer delivered.
SNMP	The SNMP (Simple Network Management Protocol) interface of the System Management Hub is no longer supported.

Deprecated Item	Description
Direct SSL/TLS Support for Broker Stubs under z/OS	Direct SSL/TLS support (using GSK) inside the broker stubs under z/OS will be dropped in the next version. We recommend using IBM's Application Transparent Transport Layer Security (AT-TLS) instead.
Administration using System Management Hub	Administration with SMH (including the batch interface <code>argbatch</code>) will be dropped in the next version of EntireX. The most important functionality will be provided by Command Central.
Encryption/decryption mechanism provided by EntireX Security	We strongly recommend using the Secure Sockets Layer/Transport Layer Security protocol.
Microsoft Visual Studio 2010, 2012, 2013	<p>With the next version of EntireX, the following components will support Microsoft Visual Studio version 2015:</p> <ul style="list-style-type: none"> • C Wrapper • DCOM Wrapper • .NET Wrapper Wizard for Microsoft Visual Studio <p>Older versions will no longer be supported.</p>

Deprecated Item	Description
WebSphere MQ RPC Server and Listener Support for dynamic IDL/RPC parameters	

Changed Item	Description
Installation Packages	<p>The EntireX installation packages have been streamlined and restructured:</p> <ul style="list-style-type: none"> • EntireX Broker can now stay running while runtime updates outside EntireX Broker are made. • Administration and Monitoring functionality has been clearly separated from the runtime parts. • Mini Runtime is now a separate installation package. • Examples have been reworked and streamlined.
EntireX built with Visual Studio 2015	<p>This version of EntireX was built with Microsoft Visual Studio 2015. When you install EntireX components, the necessary Microsoft Redistributable Files are also installed.</p>
COBOL Wrapper, generic RPC service modules	<p>The generic RPC service modules for the following interface types need to be generated with the EntireX Workbench. See COBOL Wrapper documentation for details.</p> <ul style="list-style-type: none"> • COBSRVID for CICS with standard linkage calling convention • COBSRVIB for Batch with standard linkage calling convention

Release 9.9

Added Item	Description
Enhanced null value suppression	<p>A new button in the XML Mapping Editor Overview Page enables you to set the current null value suppression settings to all mappings.</p>

Added Item	Description
COBOL MPO support	The IDL Extractor for COBOL - together with the EntireX Adapter or EntireX RPC Servers - supports the concept of multiple possible output (MPO). This means that the output structure returned is decided by the COBOL server at runtime; the COBOL layout on output varies.
COBOL server using data length to process a variable number of array elements	The IDL Extractor for COBOL - together with the CICS RPC Server, the EntireX Adapter with IMS Connect connections, or the IMS Connect RPC Server - supports COBOL server programs that use the data length of their interface to process a variable number of array elements in a fixed-size COBOL table.
Command Central support	<p data-bbox="808 772 1474 1157">With the Software AG's Command Central you can configure, manage, and administer one or more installations of the webMethods product suite in your enterprise. EntireX supports Command Central for EntireX Broker instances running on Linux, UNIX or Windows. They must have been created with version EntireX 9.9 by System Management Hub, Command Central or command line (SMH, CC, or Broker command-line utility etbsrv).</p> <p data-bbox="808 1184 1451 1373">You can start, stop and configure EntireX Broker instances from a single location, using the Command Central user interface or from a command line. Basic monitoring KPIs for EntireX Broker instances can be seen from the UI.</p>
EntireX Adapter Listeners	A new information screen provides statistics about the listeners of the EntireX Adapter.
Application Monitoring Data Collector	The Data Collector now provides callback functionality for the processing of incoming events.

Added Item	Description
Logging exit for EntireX scripting commands	Since version 9.7, EntireX has provided a set of command-line scripts with which, for example, you can monitor your environment and check that all components (broker, RPC servers) are up and running. Now an optional logging exit is provided. This is called every time a component in the environment is checked; results can be written to a CSV file. You can use the sample script <code>log_environment.bat</code> as a template.
Set application name with .NET Wrapper	For accounting purposes, a new property <code>ApplicationName</code> has been introduced for the .NET Wrapper. Set this property before calling one of the Logon methods if you want to replace the default application name.
Preview of Date/DateTime Pattern in XML Mapping Editor	The Preferences page of the XML Mapping Editor now shows a preview for date and dateTime patterns entered.

Removed Item	Replacement, if any
EntireX Mini Runtime is no longer delivered with EntireX.	Functionality is provided with EntireX Libraries in the Software AG Installer.
EntireX support for Software AG's Integrated Authentication Framework (IAF) has been dropped from all interfaces.	
EntireX Wrapper for Enterprise JavaBeans. It is no longer possible to enable Java-based components to access an EntireX RPC server using Enterprise JavaBeans.	
Adapter Services Wrapper for Natural.	The functionality is already covered by using the IDL Extractor for Natural and the Integration Server Wrapper.
Partner Broker ID.	
Support for IBM compiler PL/I for MVS & VM.	Support for Enterprise PL/I for z/OS compiler will continue.
Microsoft Visual Studio Wizard for EntireX DCOM Wrapper.	The functionality is provided by the EntireX Workbench.

Removed Item	Replacement, if any
Broker Control Block Definitions NATDEF12 and NATDEF21 of ACI for Natural.	Use NATDEF in your application for Broker control block definition.
Deprecated Item	Replacement, if any
Encryption/decryption provided by EntireX Security will be deprecated in the next version.	For encrypted transport we strongly recommend using the Secure Sockets Layer/Transport Layer Security protocol.
EntireX Broker support for Java Message Service will be dropped in the next version.	
EntireX Broker support for Publish and Subscribe communication model will be dropped in the next version.	
Direct SSL/TLS support (using GSK) inside the broker stubs under z/OS will be dropped in the future.	We recommend using IBM's Application Transparent Transport Layer Security (A T-TLS) instead.
Administration using System Management Hub (including batch interface <code>argbatch</code>) and SNMP support is planned to be dropped in a future version of EntireX.	
The Generic RPC services modules COBSRVIB and COBSRVID delivered on mainframe will be moved to the examples in the next version.	For your integration scenarios, use the modules generated by the EntireX Workbench.
Changed Item	Description
DCOM Wrapper	The wrapper now supports Microsoft Visual Studio 2012 and 2013 in addition to the already supported Visual Studio versions.
Integration Server Wrapper	The wrapper no longer creates the <code><IDL>_IS.properties</code> file. Existing property files are ignored.
Platform support	EntireX and EntireX Adapter 9.9 now run under SUSE Linux Enterprise Server for x86-64 (64-bit) version 12 in addition to version 11.

Changed Item	Description
Java 8 support in Java Wrapper and IDL Extractor for WSDL	<p>When generating Java RPC clients (Bean-compliant) with the Java Wrapper, the name generation rules have changed slightly to ensure greater consistency. This means a name used for more than one IDL group parameter with different content is always changed.</p> <p>With the IDL Extractor for WSDL, prefix name assigning has been enhanced to ensure consistent generation of XML mapping files. If more than one prefix is associated with a URL, the last prefix (in alphabetical order) is used.</p> <p>See EntireX Release Notes for examples.</p>
EntireX Adapter license handling	<p>License handling for EntireX Broker connections now better reflects the EntireX pricing model: a license status line has been introduced for EntireX Broker connections (ACI connections or normal RPC connections), and a warning message is given in the case of a possible license coverage mismatch.</p>
CICS RPC user exit COBUEX02	<p>The user exit now provides the maximum expected length of output data (reply) before calling the target CICS program.</p>
Compatibility with webMethods Suite Naming Conventions	<p>The name of the UNIX start/stop script for the EntireX Broker Administration Service has changed to comply with webMethods suite naming conventions:</p> <p>in <i>directory etc/init.d</i>: from <i>sag<n>etbsrv</i> to <i>sag<n>exx99</i> in directory <i>EntireX/bin</i>: from <i>sag<n>etbsrv</i> to <i>sagexx</i></p>
Running the XML/SOAP RPC server in the Software AG Runtime	<p>After installation, the default XML/SOAP RPC Server using Broker "localhost:1971" and server address "RPC/XMLSERVER/CALLNAT" is no longer started automatically.</p>
OpenSSL Support	<p>The OpenSSL Project has announced it will no longer support version 0.9.8 from December 31, 2015. EntireX now supports OpenSSL version 1.0.1. See CIPHER-SUITE under <i>Broker Attributes</i> in the EntireX documentation.</p>

Release 9.7

Removed Item

Broker Services were partially retired with EntireX version 8.0; they are now fully retired.

Location Transparency support was dropped in EntireX version 9.5. Location Transparency has now been removed from all major interfaces.

Replacement, if any

See Release Notes

Deprecated Item

See *Features to be Dropped in Future Versions* in the EntireX Release Notes for comprehensive list.

Replacement, if any

Changed Item

IDL Extractor for Integration Server

Description

The handling of content types when mapping Integration Server data types to IDL has changed. See *IDL Extraction from Integration Server* in the webMethods EntireX Adapter documentation.

WebSphere MQ Listener

The handling of the correlationId and the messageId in synchronous request/reply scenarios has been changed. See *Support for Synchronous Request/Reply Scenarios* under *Advanced WebSphere MQ Listener Functionality* in the EntireX documentation.

Release 9.6

Removed Item

Removed support for z/OS 1.12, z/VSE 4.3.

Replacement, if any

The following platforms are no longer supported: z/OS 1.12, z/VSE 4.3.

No new version of IAF is delivered with this release of the webMethods suite.

If you are running IAF, you can continue using the version delivered with an earlier suite version.

Deprecated Item

Broker stub BKIMBTSO is no longer provided.

Replacement, if any

The functionality is covered by stub BROKER. The default transport method for BKIMBTSO was TCP; default for BROKER is NET. However, this can be changed to TCP if required.

Release 9.5

The following functionality has been dropped in this release:

- Location Transparency Location transparency is no longer supported in this version.
- Windows Server 2008 (32-bit) Windows Server 2008 (32-bit) is no longer supported. We suggest you upgrade to the 64-bit or a more recent Windows version. See *List of Components per Platform* in the EntireX Release Notes for full list.
- JBoss Application server JBoss is no longer supported.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

Release 9.9

All services apply to EntireX Adapter.

Added Service	Description
<code>pub.listener.createDocumentTypes</code>	Creates document type objects, using the metadata stored in the listener, connection or adapter service object.
<code>pub.listener.createFlow</code>	Creates flow objects for the specified EntireX Adapter listener object.
<code>pub.listener.createIDL</code>	Creates an IDL file, using the metadata which is stored in the listener, connection or adapter service object.
<code>pub.wmentirex.directrpc.admin.setTLSProtocols</code>	Change the set of enabled TLS protocols.
<code>pub.wmentirex.directrpc.admin.getTLSProtocols</code>	Return the value of <code>setTLSProtocols</code> .
<code>pub.wmentirex.directrpc.admin.setCipherSuites</code>	Change the set of enabled cipher suites.
<code>pub.wmentirex.directrpc.admin.getCipherSuites</code>	Return the value of <code>setCipherSuites</code> .

Changed Service	Description
<code>com.softwareag.entirex.wmadapter.Deployment</code>	Namespace changed to <code>pub.wmentirex.listener</code> . The service is still available using the old namespace.

Changed Service	Description
pub.wmentirex.listener: generateIDLfromService	The meaning of parameter <code>fileName</code> has changed. This is the name of the IDL file with extension ".idl". You cannot specify a folder name. The file is created in the folder <code><IntegrationServer_instance>/packages/WmEntireX/resources</code> .

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Parameter	Description
ACI fields LONG-PASSWORD-LENGTH and LONG-NEWPASSWORD-LENGTH	New fields in ACI 12 to support long passwords and password phrases.

Changed Parameter	Description
Broker attribute ACI-CONVERSION.	Default value YES. This means ACI request and response strings of USTATUS are now converted with ICU. This attribute was undocumented in earlier EntireX versions and had default value NO. This meant that a translation user exit was used instead; this is no longer recommended.

Release 9.12

Added Parameter	Description
Multiple broker attributes under DEFAULTS=AUTHORIZATION-RULES	Use these attributes to define authorization rules in the broker attribute file.
Multiple security-specific attributes starting with LDAP	Use these attributes to define authorization rules stored in an LDAP repository.
Multiple broker attributes under DEFAULTS=DIV	DIV persistent store handling has been streamlined and these new attributes replace format parameters.

Added Parameter	Description
SECURITY-SYSTEM	Specifies whether authentication is performed against the local operating system or LDAP repository.

Removed Parameter	Description
Security-specific broker attributes AUTHENTICATION-TYPE and AUTHORIZATIONRULE	Replaced by new DEFAULTS=AUTHORIZATION-RULES section.
Multiple broker-specific attributes SSL* and TCP*, for example SSL-RESTART	Use the corresponding SSL-specific and TCP-specific attributes instead, for example RESTART in the attribute file section DEFAULTS=SSL.

Release 9.9

Added Parameter	Description
Broker attribute MAX-TRACE-FILES	Maximum number of backup copies of trace file ETB.LOG.
Broker attribute TRACE-FILE-SIZE	Maximum size of one trace file. If this value is exceeded, a new trace file is allocated up to the limit specified in MAX-TRACE-FILES.

Changed Parameter	Description
Broker attribute CIPHER-SUITE.	New default value to support OpenSSL version 1.0.1.

Deprecated Parameter	Replacement, if any
Support for dynamic IDL/RPC parameters will be dropped in a future version.	

Release 9.7

Changed Parameter	Description
Broker attribute POLL.	Default value changed from YES to NO for z/OS and z/VSE.

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 9.7

Removed API	Replacement, if any
Location Transparency.	No replacement. Support for Location Transparency was dropped in EntireX version 9.5. It has now been removed from all major interfaces.

12.0 Copyright Information

Copyright © 2017 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

EXX-RM-103-20181015

webMethods Event Routing 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Event Routing 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find the suite-related information listed below.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	1
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	3
6.0	Documentation Changes	4
7.0	Added, Removed, Deprecated, or Changed Items.....	4
8.0	Copyright Information.....	5
9.0	Support.....	5

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- EDA-2825
Event Routing might not deliver events to the correct service group when a configuration change

coincides with the first event being sent by the client application.

Event Routing enables the administrator to define one or more services to which events can be sent. Services are grouped together as a set of one or more services. Each product runtime where Event Routing is used has a default service group. Any event types that are not explicitly associated with a custom service group are associated with the default group. However, if the administrator modifies the event type association configuration at the same time when a client application sends its first event of a particular event type, Event Routing might fail to deliver the events.

Note: This issue does not occur if the client application has already sent events of the particular event type.

As a workaround, make sure to stop the server runtime and restart it after the event type association configuration updates are completed.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- EDA-4167
Event Routing is in compliance with the General Data Protection Regulation (GDPR) and does not store, collect, or process any personally identifiable information.
- If your event-driven environment contains applications that use the JMS functions of Integration Server (or the JMS protocol in general) to send and receive events of a particular EDA event type, and you create applications that use Event Routing to send and receive events of the same EDA event type, the respective JNDI entries might not be created correctly in the Universal Messaging server for the two application types to work.
As a workaround, open a command line prompt in *Software AG_directory\common\lib*, and run the *event-routing-jms-util.jar* utility. This will ensure the JNDI entries and topics are created in your Universal Messaging server. For more information about how to run the utility, see the readme file in *event-routing-jms-util.jar*.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.1

- EDA_10.1_ERSharedBundles_Fix5
- EDA_10.1_Designer_Fix2
- EDA_10.1_NERV_Fix5

Release 10.0

- EDA_10.0_Event Routing Platform Manager Plugin_Fix1

Release 9.12

- EDA_9.12_NERV_Fix11
- EDA_9.12_ERSharedBundles_Fix11
- EDA_9.12_Designer_Fix4
- EDA_9.12_Event Routing Platform Manager Plugin_Fix7

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- EDA-4142
In Software AG Designer, creating an EDA event type from an existing Integration Server (IS) document type fails. When you select the “Use an existing IS document type” option in the Event Type Editor, Designer returns the following error: “A null service reference is not allowed”. The issue occurs because a required software module is not active by default.
This issue is resolved.

Release 9.10

- EDA-2371
A NullPointerException occurs during deployment of a NERV route bundle.
If an invalid NERV route bundle is constructed and deployed to an EDA target server using webMethods Deployer, the deployment fails. The log file of the corresponding Software AG Platform Manager contains a NullPointerException.
The issue is now fixed, and no NullPointerException occurs even if the deployed NERV bundle is invalid.

6.0 Documentation Changes

This section describes significant changes to the documentation in each release, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

An HTML version of *“Communicating between Software AG Products Using Event Routing”* is available on the Software AG Empower website under the name *“Event Routing Webhelp”*.

Release 9.9

The new *“Communicating between Software AG Products Using Event Routing”* PDF publication has been included in this release. It contains information about administering, configuring, and using Event Routing.

7.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.1

Added Item	Description
Encrypted event transmission	Event Routing supports the Universal Messaging NSPS protocol for secure communication. For more information, see the Event Routing product documentation.

Release 10.0

Removed Item	Description
NERV	NERV has been removed.

Release 9.9

Added Item	Description
com.softwareag.event.routing.EventRouting	Central interface for sending and consuming events.
com.softwareag.event.routing.nonosgi.EventRoutingProvider	Entry point for usage of Event Routing outside OSGi.

8.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

9.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

ER-RM-103-20181015

webMethods Extended Character Set 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Extended Character Set 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find the suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Other Resolved Issues.....	2
5.0	Documentation Changes	3
6.0	Terminology Changes	3
7.0	Added, Removed, Deprecated, or Changed Items.....	3
8.0	Copyright Information.....	4
9.0	Support.....	4

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- LPUT-107
LPFW - G11n cannot find sc-core resource bundle

Release 10.2

- LPUT-103
Support International Components for Unicode version 58.2.0.

Release 10.1

- LPUT-100
Support International Components for Unicode version 56.1.0.

Release 10.0

- No change in 10.0 release

Release 9.12

- LPUT-93
The time containing half an hour for a different time zone is incorrectly converted and displayed in the Users profile page. For example, GMT (Greenwich Mean Time) + 5:30 IST (Indian Standard Time) is displayed as GMT + 5:00 IST.
This issue is resolved. If the time is GMT + 5:30 IST, then GMT + 5:30 IST is displayed in the Users profile page.

Release 9.10

- No change in 9.10 release

Release 9.8

- LPUT-76
`com.softwareag.g11n.text.NCNameCoder.validate` affects the performance of Integration Server when the version of java being used is Java 8.
When Integration Server validates XML documents, `com.softwareag.g11n.text.NCNameCoder.validate` validates if the given string satisfies NCName datatype specification. However, the performance of Integration Server is affected when the version of java being used is Java 8.
This issue is resolved.

5.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

6.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

7.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

8.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

9.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

ECS-RM-103-20181015

Software AG Infrastructure 10.3 Readme

October 2018

This file contains important information you must read before using Software AG Infrastructure 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	5
6.0	Documentation Changes	6
7.0	Terminology Changes	7
8.0	Added, Removed, Deprecated, or Changed Items.....	7
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	10
10.0	Added, Removed, Deprecated, or Changed Parameters.....	11
11.0	Added, Removed, Deprecated, or Changed APIs	13
12.0	Copyright Information.....	14
13.0	Support.....	14

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- Common Landscape Asset Registry does not support Git LFS repositories when a Git installation is installed without the Git LFS plugin.
To work around this issue, remove the Git installation or install the Git LFS plugin in addition to the Git installation.
- JConsole has some known issues when using a JMX connection to the CTP profile. The connection over SSL is not possible due to Java limitations. This capability is disabled for versions higher than 1.7.0_25 (removed due to vulnerabilities found: [CVE-2013-2453](#), [CVE-2013-2457](#))
There is currently no workaround for this issue. This affects the following releases: 9.5, 9.6, 9.7, 9.8, 9.9, 9.10, 9.12, 10.0, 10.1, and 10.2.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Common Landscape Asset Registry

Release 10.3

- LAR_10.2_Fix1

Release 10.2

- LAR_10.1_Fix1

Common Service Container

Release 10.2

- SEC_10.1_Fix2

Software AG Runtime

Release 10.3

- OGI_10.2_Fix3
- OGI_10.2_Migration_Fix1

Release 10.2

- OGI_10.1_Fix4
- OGI_10.1_Migration_Fix3
- OGI_10.1_Agent_Fix1

Release 10.1

- OGI_10.0_Fix1

Release 10.0

- OGI_9.10_Fix5

Release 9.12

- OGI_9.10_Fix3

Release 9.10

- OGI_9.9_Fix1

Release 9.9

- OGI_9.8_Fix4

Release 9.8

- OSGi_Platform_9.7_Fix10

Software AG Security Infrastructure

Release 10.2

- SIN_10.1_Fix3

Release 10.0

- SIN_9.9_Fix4

Release 9.10

- SIN_9.9_Fix1

Release 9.9

- SIN_9.8_Fix2

Software AG Web Services Stack

Release 10.3

- WSS_10.2_Core_Fix2
- WSS_10.2_WebApp_Fix2
- WSS_10.2_OSGi_Fix2

Release 10.2

- WSS_10.1_Core_Fix3
- WSS_10.1_WebApp_Fix3
- WSS_10.1_OSGi_Fix3

Release 10.1

- WSS_10.0_Fix1

Release 10.0

- WSS_9.12_Fix2

Release 9.12

- WSS_9.10_Fix3

Release 9.10

- WSS_9.9_Fix10

Release 9.9

- WSS_9.8_Fix4

Release 9.8

- WSS_9.7_Fix3

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Software AG Runtime

Release 9.9

- OGI-927
With OSGi Common Platform, when a daily time-based rollover is used, a size-based rollover causes the timestamp in the filename to be wrongly incremented by one day.
The issue is resolved.
- OGI-1005
PseudoUUID class produces non-unique IDs. Tests showed that non-unique UUID string would be created when 40 or more threads were requesting UUIDs simultaneously. The source of random values used by this class was changed to provide a more secure list of random values.

Release 9.8

- OGI-723
In the OSGi platform, the JAAS configuration file contains plain text credentials. The issue is resolved. The OSGi platform can now modify the JAAS configuration file to hide the values of certain fields marked by the user as secure. You can mark plain text credentials as secure in the JAAS configuration file and the OSGi platform automatically hides the credentials the first time it reads the configuration file.

Software AG Web Services Stack

Release 9.12

- WSSTACK- 2190
With Web Services Stack, potential clickjacking security vulnerability

is detected in the Web Services Stack administration pages.
The issue is resolved.

- WSSTACK- 2499
Software AG Web Services Stack has a potential security vulnerability regarding access to Web Services Stack web pages.
The issue is resolved. The vulnerability has been addressed and the pages are no longer accessible.

Release 9.9

- WSSTACK- 1904
With Web Services Stack, HttpClient 4.2 causes issues when used with HttpClient 4.4.1.
The issue is resolved. The HttpClient component set is updated to 4.4.1.
- WSSTACK-1862
With Web Services Stack, serving the WSDL when there are references/imports to external schemes may fail with a "String out of range -1" error. The issue is resolved.

Software AG Security Infrastructure

Release 9.9

- SIN-1087
ClassCastException during MWS startup The initialization of the OWASP Enterprise Security API used by Software AG Security infrastructure fails with ClassCastException if ESAPI loggers are accessed before its initialization is complete. The issue is resolved.
- SIN-1096
With Software AG Common Platform, the bouncycastle-bcprov 1.47 library has a known security vulnerability. The issue is resolved. The library is updated to the stable version bouncycastle-bcprov 1.52.
- SIN-1077
The recursive search for users and groups does not work properly. With Software AG Security Infrastructure, the recursive search for users and groups does not work properly when memberInfoInGroups=false. The issue is resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- A new chapter, “Software AG Runtime Logging”, is added to *Software AG Infrastructure Administrator’s Guide*.
- A new chapter, “Collecting Diagnostic Information About Software AG Products”, is added to *Software AG Infrastructure Administrator’s Guide*.
- *Software AG Infrastructure Administrator’s Guide* is available as a web help on the Software AG Empower website.

Release 10.0

A new chapter, “Working with Software AG Common Landscape Asset Registry”, is added to *Software AG Infrastructure Administrator’s Guide*.

Release 9.9

- New Software AG Infrastructure Administrator’s Guide

The documentation for Software AG Common Platform, Software AG Runtime, Software AG Security Infrastructure, Software AG Web Services Stack, and the Tanuki Software, Ltd. Java Server Wrapper as it is used by Software AG products has been combined into a single guide named Software AG Infrastructure Administrator’s Guide.

- New Software AG Infrastructure Readme

The readmes for Software AG Common Platform, Software AG Runtime, Software AG Security Infrastructure, and Software AG Web Services Stack have been combined into a single Software AG Infrastructure readme. In addition, the combined readme has been expanded to contain cumulative information for these products back to the 9.5 release.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Software AG Security Infrastructure

Release 10.3

Deprecated Item	Replacement, if any
LdapLoginModule com.softwareag.security.jaas.login.LdapLoginModule	com.softwareag.security.sin.is.ldap.lm.LdapLoginModule

Release 10.0

Removed Item	Replacement, if any
SSX authentication removed	

Release 9.10

Deprecated Item	Description
IAF	SSX authentication over IAF is deprecated.

Software AG Runtime

Release 10.3

Added Item	Description
Diagnostic Information Collector Tool	Collects diagnostic information about the Software AG Common Platform and the OSGi profiles of Software AG products. The tool collects and archives files for troubleshooting from the Software AG installation directory and the Software AG Update Manager directory. It also enables you to edit the log configuration file for each profile. For more information about using the tool, see <i>Software AG Infrastructure Administrator's Guide</i> .

Release 10.2

Added Item	Description
Tomcat Upgrade	Apache Tomcat is upgraded to version 8.5.23, which resolves known security vulnerabilities.

Release 10.1

Added Item	Description
Tomcat Upgrade	Apache Tomcat is upgraded to version 8.5.11, which resolves known security vulnerabilities.

Release 10.0

Added Item	Description
Tomcat Upgrade	Apache Tomcat is upgraded to version 8.5.5, which resolves known security vulnerabilities.

Added Item	Description
Gemini Web Upgrade	Gemini Web is upgraded to version 3.0.0.RC2 , which resolves known issues.

Release 9.12

Added Item	Description
Tomcat Upgrade	Apache Tomcat is upgraded to version 7.0.70, which resolves known security vulnerabilities.

Release 9.9

Added Item	Description
Tomcat Upgrade	Apache Tomcat is upgraded to version 7.0.62, which resolves known security vulnerabilities.
Gemini Web Upgrade	Gemini Web is upgraded to version 2.2.7, which resolves known issues.
Direct the Java Util Logging framework to the Software AG Runtime log	Provides efficient bridging of the Java Util Logging logs to the Log4J backend used by Software AG Runtime.

Release 9.8

Added Item	Description
Dynamic Bundle Deployment	Allows the OSGi platform to deploy bundles from a target directory at runtime. The directory can be continuously monitored by the platform or the deployment can be triggered explicitly via a call to an OSGi service.

Software AG Web Services Stack

Release 10.3

Added Item	Description
AES128-GCM Encryption Algorithm	Software AG Web Services Stack supports the AES128-GCM encryption algorithm.

Release 9.12

Changed Item	Description
Spring Upgrade	Spring Framework is upgraded to version 3.2.17, which resolves known security vulnerabilities.

Release 9.8

Changed Item	Description
Secured WSS Admin and Happy Axis pages	WSS Admin page and Happy Axis page are now secured with Software AG Security Infrastructure.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

Software AG Runtime

Release 9.8

Added Service	Description
Passman MBean	This service provides password retrieval using passman handles.

Common Landscape Asset Registry

Release 9.12

Added Service	Description
Common Landscape Asset Registry built-in services	This is the initial release. All services are effectively added.

Common Service Container

Release 9.12

Added Service	Description
Common Service Container built-in services	This is the initial release. All services are effectively added.

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

Software AG Runtime

Release 9.9

Added Parameter	Description
com.softwareag.catalina.env.pid-suffix.properties	<p>Configuration property files for Environment Entries Configuration, which are located in <code><SoftwareAG_directory>\profiles\CTP\configuration\com.softwareag.platform.config.propsloader</code>. They have the following properties: <code>context</code>, <code>enabled</code>, <code>(1-9).env-entry.name</code>, <code>(1-9).env-entry.type</code>, <code>(1-9).env-entry.value</code>, <code>(1-9).env-entry.override</code>.</p> <p>This configuration can be applied to every profile.</p> <p>Environment Entries support multiple configurations, which must have different names. To achieve this, the 'suffix' in the configuration name must be changed.</p>

Release 9.8

Added Parameter	Description
com.softwareag.bundle.watchdog.pid	A configuration file for Dynamic Bundle Deployment, which is located in <code><SoftwareAG_directory>\profiles\CTP\configuration\com.softwareag.platform.config.propsloader</code> . It has the following properties: <code>directory</code> , <code>scanPoll</code> , <code>scanInitial</code> , <code>start</code> , <code>startLevel</code> . This configuration can be applied to every profile.
com.softwareag.bundle.watchdog.global.pid	A configuration file for Dynamic Bundle Deployment, which is located in <code><SoftwareAG_directory>\profiles\CTP\configuration\com.softwareag.platform.config.propsloader</code> . It has the following properties: <code>refreshToWireOptionals</code> , <code>refreshToAttachFragments</code> and controls the common behavior of the Bundle Deployment.

Common Landscape Asset Registry

Release 9.12

Added Parameter	Description
Common Landscape Asset Registry configuration parameters	This is the initial release. All configuration parameters are effectively added.

Common Service Container

Release 9.12

Added Parameter	Description
Common Service Container configuration parameters	This is the initial release. All configuration parameters are effectively added.

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Common Landscape Asset Registry

Release 10.3

Added API	Description
Common Landscape Asset Registry Transformer APIs	APIs that provide an easily extensible way of modifying binary and metadata assets.

Release 10.2

Added API	Description
Common Landscape Asset Registry Roll back APIs	API that allows roll back of assets in a repository.
Common Landscape Asset Registry Promotion APIs	API that allows promotion of assets between repositories.

Release 9.12

Added API	Description
Common Landscape Asset Registry APIs	This is the initial release. All APIs are effectively added.

Common Service Container

Release 9.12

Added API	Description
Common Service Container APIs	This is the initial release. All APIs are effectively added.

Software AG Runtime

Release 10.2

Added Parameter	Description
Audit log APIs	API that provides audit logging functionality.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

INFRA-RM-103-20181015

Software AG Installer Readme

October 2018

This file contains important information you must read before using the Software AG Installer October 2018 release. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Other Resolved Issues.....	3
5.0	Documentation Changes	6
6.0	Terminology Changes	6
7.0	Added, Removed, Deprecated, or Changed Items.....	6
8.0	Copyright Information.....	6
9.0	Support.....	7

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

- Always read the Critical Requirements and Recommendations chapter in *Using the Software AG Installer* before installing products.
- You might experience download issues while using the Software Installer. For suggestions on diagnosing and resolving the issues, see *Using the Software AG Installer*.
- Software AG strongly recommends that you create installation images of your products and store them on your internal network. Create an image for each operating system on which you plan to

install that is covered by your license agreement. Storing images enables you to ensure consistency across installations over time; the installer provides only the latest product releases, while installation images contain the product releases you download into them. In addition, installing from images helps you reduce WAN traffic and improve installation speeds. For instructions on creating images, see *Using the Software AG Installer*.

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- WIR-5418
UAC dialog box that prompts for administrator privilege settings is minimized in taskbar
When you install on a Windows system using the exe, a UAC dialog box may display that prompts administrator privileges. However, the dialog box minimizes to the taskbar instead of displaying on top of other windows.
The workaround is to click the taskbar to maximize the window and grant administrative privileges.
- WIR-7037
Download fails and installer log shows warning about password-protected Zip files
The installation files for some Software AG products contain password-protected Zip files that are used for MashZone. These products are Application Monitor Data Collector, Active File Transfer, Business Event Server, CloudStreams, MashZone, and OneData. If you have selected any of these products for installation, a warning that a Zip file was blocked due to security policy settings might be written to the installation log file. In some circumstances, a company's firewall or security application policy settings may notice this warning and block downloading of those products from the Software AG Software Download Center, causing the installation download to fail.
The workaround is to restart the installer, set logging to verbose, and select the products to install again. If you get the same failure, search the log file for the warning. If you find the warning, deselect the products listed above and finish the installation of any other products. Then contact Software AG Global Support to request an installation image of the blocked products.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- The installer does not support running in compatibility mode on Windows systems. For example, the installer does not support running in Windows XP compatibility mode on Windows Vista or Windows 7.

4.0 Other Resolved Issues

This section lists the issues that were resolved in each release. A release is listed in this section only if changes occurred in that release.

Release 10.2

WIR-10860

Installer does not list all products on Azure RHEL 7

When you install on an Azure RHEL 7 system, the installer shows the first 1-7 products and then asks you to press the “+” key to view 11-19 product list. The 8-10 products are missing.

This issue has been resolved.

Release 10.1

- WIR-10287

Installation from image aborts on SPARC systems

On Solaris 11.3 SPARC systems, installation from an image can abort with a Java crash (SIGSEGV in class 'installBuildModule'). This is a SPARC system bug.

Until Oracle provides a fix, the workaround is to use this Java option:

```
-XX:CompileCommand="exclude,com/wm/distman/custominstall/  
CopyFilesProgressPanel.installBuildModule"
```

Alternatively you can pass this option with a file .hotspot_compiler in the current working directory that has this content:

```
exclude com/wm/distman/custominstall/CopyFilesProgressPanel installBuildModule
```

Release 10.0

- WIR-9963, MWS-19466

UNIX daemon is not registered when installing My webMethods Server on AIX

When installing My webMethods Server on an AIX system, you chose the option 'Register UNIX daemon for automatic start up,' but the daemon was not registered, and you received this error from the mkitab command:

```
[daemon.sh] /usr/sbin/mkitab "sag5mws912_default_5:235:wait:/etc/sag5mws912_default_5 start ..."  
(1)
```

The root cause is that the init-script name sag5mws912_default_5 is more than 14 characters long.

The workaround is to use the daemon.sh tool and register the My webMethods Server daemon manually with a shorter base name, as shown in the following example where the base name is passed with -n mws912:

```
/opt/softwareag/common/bin/daemon.sh -f  
/opt/softwareag/profiles/MWS_default/bin/sagmws912_default_1 -n mws912
```

```
/usr/sbin/rmitab: 0481-204 The ident field is not correct.  
Usage: /usr/sbin/rmitab "ident"  
[daemon.sh] ERROR: /usr/sbin/rmitab sag1mws912_default_1 failed (1)  
[daemon.sh] /etc/sag1mws912_default_1 removed (ok)  
[daemon.sh] Created /etc/sag1mws912 (ok)  
[daemon.sh] chmod 775 /etc/sag1mws912 (ok)  
[daemon.sh] /usr/sbin/mkitab "sag1mws912:235:wait:/etc/sag1mws912 start ..." (ok)
```

Note: The output shows the message "The indent field is not correct." with the rmitab command. You can ignore this message.

If the mkitab command shows no ERROR like in the example, then you have successfully registered the daemon on AIX.

- WIR-9986
My webMethods Server does not register Windows service or UNIX daemon correctly. When installing on Windows, the installer will not create a service even if the "Register Windows service/UNIX daemon" check box is selected. The workaround is to run mws.bat to register the Windows service.
When installing on UNIX, the installer will always try to create a daemon even if the check box is cleared. This means that if the sudo password is provided, a daemon will always be registered. If the sudo password is not provided, the installer will add a script line that will be executed when afterInstallAsRoot.sh is run later. The workaround is to use the daemon.sh command line tool to unregister the UNIX daemon. For instructions, see *Installing Software AG Products*.
- WIR-9975
Product daemons do not start automatically on Solaris.
During installation on a Solaris system, you chose the daemon registration option for products that offer that option. However, product daemons are not starting automatically with the Multi User Runlevel (Runlevel 2). The root cause is that the common/bin/daemon.sh does not include Runlevel 2 by default.
The workaround is to use the daemon.sh tool to register the daemons again while specifying the intended runlevels with option '-N', as shown in the following example for Platform Manager:
 1. Change to root user:
\$ su root # or sudo sh
cd /opt/softwareag/common/bin
 2. List the init-script and rc-script names of all registered daemons:
./daemon.sh -L
/etc/init.d/sag5spm912 /opt/softwareag/profiles/SPM/bin/sagspm912
 3. Register the daemon again for Runlevels 2 and 3, using the rc-script names:
cd /opt/softwareag/common/bin
./daemon.sh -N 2,3 -f /opt/softwareag/profiles/SPM/bin/sagspm912

Release 9.12

- WIR-9462
Cannot create image generation script
When trying to create an image generation script (select Create script and For image generation on Scripts tab, select Create image on Images tab), the installer displays the message “You cannot create a script and create an image at the same time.”
The workaround for UNIX is to create the image generation script in console mode. For Windows, there is no workaround.
The issue has been resolved.

Release 9.10

- WIR-8895
Products cannot access JDK
When creating a script and installing on local machine, the path to the installer-provided JDK is not set, and products cannot access it.
This issue has been resolved.

Release 9.9

- WIR-8320
Installer looped over identifying a 1.7 JVM location.
This issue has been resolved.
- WIR-8411
Changing the log level in Advanced Options after invoking the installer with the `-readImage` option changed the image path.
This issue has been resolved.
- WIR-8762
Product jars were deleted when an uninstallation script was created.
If you tried to create an uninstallation script and cleared the Uninstall Product checkbox, the script was created successfully but the product jars were removed.
This issue has been resolved.

Release 9.8

- WIR-7665
Inconsistent behavior when moving backwards and forward through installer wizard
Moving backwards and forwards after selecting products may cause some fields in the custom product panels to behave improperly (for example, by disabling fields).
This issue has been resolved.
- WIR-7651

Restore Defaults feature is not available in console mode.
Restore Defaults has been removed from the installer.

5.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

6.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

7.0 Added, Removed, Deprecated, or Changed Items

This section lists features, functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

8.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

9.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

INSTLR-RM-20181015

webMethods Integration Agent 10.3 Readme

October 2018

This is an innovation release. Innovation releases have a much shorter support cycle than standard releases. To learn more, please visit <http://empower.softwareag.com/innovationrelease/>

This file contains important information you must read before using webMethods Integration Agent 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

webMethods Integration Agent provides a subset of the functionality available in webMethods Integration Server. Review the webMethods Integration Server 10.3 readme for information about webMethods Integration Server 10.3.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	2
6.0	Documentation Changes	2
7.0	Terminology Changes	2
8.0	Added, Removed, Deprecated, or Changed Items.....	3
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	3
10.0	Added, Removed, Deprecated, or Changed Parameters.....	3
11.0	Added, Removed, Deprecated, or Changed APIs	3
12.0	Copyright Information.....	3
13.0	Support.....	4

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 9.9

- Information about using webMethods Integration Agent is located in the *webMethods Integration Agent Administrator's Guide*.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

IA-RM-103-201801015

webMethods Integration Agent 10.3 Readme

October 2018

This is an innovation release. Innovation releases have a much shorter support cycle than standard releases. To learn more, please visit <http://empower.softwareag.com/innovationrelease/>

This file contains important information you must read before using webMethods Integration Agent 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

webMethods Integration Agent provides a subset of the functionality available in webMethods Integration Server. Review the webMethods Integration Server 10.3 readme for information about webMethods Integration Server 10.3.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	2
6.0	Documentation Changes	2
7.0	Terminology Changes	2
8.0	Added, Removed, Deprecated, or Changed Items.....	3
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	3
10.0	Added, Removed, Deprecated, or Changed Parameters.....	3
11.0	Added, Removed, Deprecated, or Changed APIs	3
12.0	Copyright Information.....	3
13.0	Support.....	4

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 9.9

- Information about using webMethods Integration Agent is located in the *webMethods Integration Agent Administrator's Guide*.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

IA-RM-103-201801015

webMethods Integration Server 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Integration Server 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	11
4.0	Fixes Included in Each Release.....	15
5.0	Other Resolved Issues.....	22
6.0	Documentation Changes	111
7.0	Terminology Changes	112
8.0	Added, Removed, Deprecated, or Changed Items.....	112
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	140
10.0	Added, Removed, Deprecated, or Changed Parameters.....	151
11.0	Added, Removed, Deprecated, or Changed APIs	172
12.0	Copyright Information.....	178
13.0	Support.....	179

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

- WFF-407
The pub.flatFile:convertToString service does not return any output.

There is no workaround for this issue.
You must install WFF_10.3_Fix1 which contains a fix for this issue.

- PIE-53255
The `pub.string:urlEncode` service behaves differently in Integration Server 10.3.
Prior to Integration Server 10.3, the `pub.string:urlEncode` service did not encode the `@` symbol.
However, the service now encodes the `@` symbol. This behavior change may impact existing usages of this service.
There is no work around for this issue.

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- PIE-53293
After restart, Integration Sever invalidates all active OAuth access tokens.
When Integration Server restarts, Integration Server does not load active OAuth access tokens from the database. As a result, all active access tokens become invalid after Integration Server restart.
There is no workaround for this issue.
- PIE-53373
OAuth client is able to use authorization code grant and implicit grant even if those grant types are not selected on the Allowed Grants field.
The Allowed Grants field on the OAuth Client Registration page in Integration Server Administrator indicates which OAuth grants the client is allowed to use. When Authorization Code Grant or Implicit Grant is not selected, the client is not allowed to use the authorization code or implicit grants. However, this is not enforced. The client is able to use these grants even though they are not included in the set of grants the client is configured to be able to use.
There is no workaround for this issue.
- PIE-51115
Integration Server generates incorrect source type for parameters for GET request.
Integration Server generates Formdata as default Source Type for parameters in GET request. This is invalid because Integration Server does not support Formdata mediatype for GET requests.
As a work around for this, users can manually change the source type in RAD editor and update the corresponding Swagger document.
- PIE-52534
Integration Server generates invalid Swagger document for REST V2 resource.
While generating a REST API Descriptor (RAD), Integration Server generates an invalid Swagger for the REST V2 resource that is renamed after the Swagger is generated. This is because after renaming the required type definitions, the links and sources do not exist in the Swagger.
There is no workaround for this issue.
- PIE-52432

Integration Server fails to save the nested object properties as part of Swagger document definitions.

When you import a Swagger document, the document definitions contain nested object properties. Integration Server fails to store these nested object properties as part of REST definitions in the Swagger document. As a result, the regenerated Swagger document does not contain the nested object properties.

There is no workaround for this issue.

- PIE-8533 (was 1-1Z6J9O)

Integration Server does not shut down if an audit logging queue contains records waiting to be written to a destination.

To work around this issue, wait for the records in the queue to be written to the destination.

- PIE-25824

Cache-related failures on HP-UX.

When Overflow To Disk is enabled for a local cache, Integration Server returns multiple cache-related exceptions in the log at start up. For example,

```
"java.lang.IllegalArgumentException: Initial table allocation failed. Initial Table Size (slots) : 64  
Allocation Will Require : 1KB Table Page Source :  
com.terracottatech.offheapstore.disk.paging.MappedPageSource@56cac09  
at com.terracottatech.offheapstore.OffHeapHashMap.<init>(OffHeapHashMap.java:204)...."
```

This issue occurs only on HP-UX 11.

To work around this issue, update wrapper.conf file located under profiles/IS_<instanceName>/configuration directory. Modify wrapper.java.command parameter in wrapper.conf file to point to <SAG_DIR>/jvm/jvm/jre/bin/IA64W/java_q4p

- PIE-8045 (was 1-1Y1BZ7)

Installing a package that contains a schema with a target namespace that is the same as an existing schema on the Integration Server may result in two sets of definitions or declarations for the same components.

If you only need the schema definitions or declarations contained in one schema, delete the other schema. However, if you need definitions from both schemas, there is no workaround for this issue.

- PIE-52691

When enhanced logging is configured for a specific trigger that uses a JMS connection alias, the enhanced logging stops after the first message is received.

Integration Server stops writing log entries after the first message is received if the JMS connection alias' Consumer Message ID Tracking: Include Triggers property contains the name of one or more triggers.

To work around this issue, leave the Consumer Message ID Tracking: Include Triggers field blank to obtain enhanced logging for all triggers that use the alias.

- PIE-53165

For an API Gateway external port, when update action is performed for enabled port, the gateway external and registration ports are getting removed from Integration Server Administrator.

In API Gateway, when external port with a registration port is updated, Integration Server

Administrator does not display the updated external port or its associated registration port.
There is no workaround for this issue.

- PIE-52559
The automatic package deployment feature is not available on an Integration Server licensed for Microservices Runtime features.
The autodeploy system task does not correctly check the license to determine if the automatic package deployment functionality should be available.
There is no work around for this issue.
- PIE-52962
The autodeploy system task fails with a NullPointerException.
When the autodeploy system task runs, the task deletes archived files related to failed deployment. In some cases, deleting the files fails with a NullPointerException.
There is no workaround for this issue.
- PIE-52894
Validation issue when creating users via Command Central
While creating a user with invalid groups using Command Central, user is created. However, error messages to invalid groups are not displayed.
There is no workaround for this issue.
- PIE-52558
Integration Server fails to return empty array for resource collection.
Integration Server must respond to a successful request to fetch a resource collection with an empty array ([]) as the response document's primary data. Integration Server fails to return empty array for such requests to fetch one to many relations.
There is currently no workaround for this issue.
- PIE-53174
Building Docker image on Windows platform prints an error message like the following.
failed to copy files: GetFileAttributesEx?
To work around this issue, once you execute the createDockerfile, createLeanDockerfile or createPackageDockerfile commands, update the generated Dockerfile that exists under <SAG_DIR> or <SAG_DIR>/IntegrationServer/instances/<instanceName>/packages directory to use the following line as the first line .
escape=`
Building of Docker image on Windows platform is successful after adding this line in the generated Dockerfile.
- PIE-52580
Integration Server adds incorrect pagination links in resource documents.
Integration Server is generating incorrect pagination links for the link section of the resource document.
There is no workaround for this issue.
- PIE-53123

Integration Server fails to execute a REST API call to a REST resource generated using a Swagger document.

Integration Server generates a REST resource by importing a Swagger document which contains the body parameter. While invoking a REST API call, Integration Server fails to pass the body parameters to the mapped service correctly. Hence the execution is unsuccessful.

There is no workaround for this issue.

- PIE-52380

Integration Server fails to identify the REST V2 resource and throws NullPointerException.

While invoking a REST V2 resource using the same URL templates, one is having an additional "/", for example, "/test/1" and "/test/1/", Integration Server fails to identify the REST V2 resource and throws a NullPointerException.

There is no workaround for this issue.

- PIE-52581

Integration Server returns successful response for invalid sparse field query parameter.

Integration server fails to validate the format or data provided in sparse fieldset query parameter as part of request to fetch resource. This results in successful response even the query parameters are invalid.

There is no workaround for this issue.

- PIE-52943

Integration Server incorrectly adds header and query parameter values to the REST API request body in pipeline.

Integration Server builds the pipeline from the REST API request body and maps the body structure with the document in the input signature. Integration Server incorrectly adds the query and header parameters that are passed in the REST request to the same structure.

There is no workaround for this issue.

- PIE-53158

Integration Server sometimes incorrectly generates service signature for JSON API resource.

Integration Server cannot generate service signatures for JSON API resources. The output signature of the resource contains one-to-one cardinality and a document reference list and does not include some of the relationship URLs in the signature. Integration Server must change the cardinality to document reference or document reference list based on one-to-one or one-to-many relationship.

There is currently no workaround for this issue.

- PIE-53153

Integration Server fails to execute the include relation feature for JSON API resource.

While naming a unique identifier attribute other than "id", Integration Server does not execute the include relation feature for the JSON API resource. .

There is no workaround for this issue.

- PIE-53152

Integration Server generates decode errors for filter criteria of a JSON API request.

Integration Server cannot identify the attribute path in a filter criteria of a JSON API request because the path is built as linked text and generates class cast exceptions.

There is no workaround for this issue.

- PIE-52610
Integration Server incorrectly accepts invalid JSON API request.
Integration Server does not validate the request type parameter present in the resource document and hence accepts the requests with invalid request types.
There is no workaround for this issue.
- PIE-53121
Integration Server does not generate a Swagger document and throws NullPointerException.
While renaming a REST API Descriptor (RAD) and accessing the Swagger document using the Swagger URL, Integration Server throws an error, 'Swagger could not be generated'.
To work around this issue reload the package that contains that RAD.
- PIE-53115
Integration Server fails to confirm the JSON API resource existence and returns incorrect error status code.
While requesting a JSON API resource with a specific ID that does not exist, Integration Server returns a success status code "200" incorrectly with "null" as primary data in resource document.
Integration Server should return failure code "404" as non-existent of resource.
There is no workaround for this issue.
- PIE-51164
Integration Server fails to update the Swagger document definition while creating a new integration or service for Integration Cloud.
While creating a new integration or service and a REST API Descriptor that uses this integration in Integration Cloud, Integration Server fails to update the input signatures in the Swagger definition.
There is currently no workaround for this issue.
- PIE-53076
The xmlschema-core and woden-core libraries are outdated in Web Services Stack.
Software AG Web Services Stack client uses outdated xmlschema-core and woden-core libraries and hence, generating web service connectors fail.
There is no work around for this issue.
- PIE-53016
Issue when renaming a unique attribute in the Attribute configuration tab of a restv2 resource.
For a REST V2 resource, where the "Generate JSONAPI urls" property is set to true and unique identifier attribute is renamed, Integration Server retains the old attribute in the signature of the generated services along with the new attribute instead of replacing the old attribute with the new attribute.
There is no workaround for this issue.
- PIE-52984
Integration Server shows incorrect error message for invalid sort parameters in JSON API request.
Integration Server returns an error with incorrect usage details if invalid and unsupported sort attributes are used as sort parameters.

There is no workaround for this issue.

- PIE-53098
In Integration Server Administrator, scrolling is not cannot be used under the Adapters Menu when using Internet Explorer.
To work around this issue, reduce the Zoom ratio of the browser.
- PIE-52697
Erroneous messages appear in the SPM wrapper.log.
The following messages appear in the SPM wrapper log but do not affect the lifecycle operations.
INFO | jvm 3 | 2018/08/19 18:04:44 | 2018/08/19 18:04:44 ERROR # LifecycleOperationsServiceImpl [SPMLCCE0000] runtimeComponentId for productId MSC is null.
INFO | jvm 3 | 2018/08/19 18:04:44 | 2018/08/19 18:04:44 ERROR # LifecycleOperationsServiceImpl [SPMLCCE0000] runtimeComponentId for productId integrationServer is null.
There is no workaround for this issue
- PIE-52345
Delete and Send Release options fail when the CSRF guard is enabled.
When the CSRF guard is enabled in Integration Server, Send Release and Delete options in Integration Server Administrator (Packages> Publishing> Create and Delete) fail. This issue occurs only when multiple releases are created.
There is no workaround for this issue.
- PIE-47159
Variables referred to in map set values and selected for refactoring are not previewed.
If more than one variable is referred to in a map set value, selecting one of them for refactoring does not list the particular variable in the Refactor Variable preview window.
There is no workaround for this issue.
- PIE-51392
Integration Server does not refactor signature variables that are mapped from a transformer to pipeline output.
Integration Server does not refactor the transformer output if the flow step includes a map step that contains the transformer and if there is a mapping from transformer output to signature output variable.
There is no workaround for this issue.
- WSC-515
Known issue in the JVM Cipher implementation for certain JVM builds may cause decryption failures in Integration Server and other products that use the outbound password manager provided in Integration Server.
A change in the PBEWithHmacSHA256AndAES_256 implementation causes Strings encrypted with the cipher in Open JDK builds 1.8.0_64 and before do not decrypt in later builds, beginning around build number 1.8.0_71. If your Integration Server runs on a JVM from Open JDK builds 1.8.0_64 up to, but not including 1.8.0_71, and then upgrade to Open JDK build 1.8.0_71 and after, passwords stored in the Integration Server outbound password manager cannot be decrypted.
To avoid this issue, change the encryptor before upgrading the JVM. That is, store the password

using the same handle but a different encryption code such as `EntrustPbePlus`.

For information about changing the encryption method for the outbound password file and resetting outbound passwords, see the “Master Passwords and Outbound Passwords” chapter in the *webMethods Integration Server Administrator’s Guide*. You can also change an outbound password using the `pub.security.outboundPasswords:updatePassword` service which is documented in the *webMethods Integration Server Built-In Services Reference*.

A description of this Open JDK defect can be found here:

<https://bugs.openjdk.java.net/browse/JDK-8162690>

Note that the Open JDK defect description has some ambiguity regarding the build number in which this issue was introduced. The issue is observed in build number 1.8.0_74 but may have been introduced in earlier builds. Builds 1.8.0_64 through 1.8.0_74 were not tested by the defect reporter. The WSC-515 description cites build 1.8.0_71 as the Open JDK defect identities 71 as the "Introduced in version" value.

- **PIE-51086**

The `pub.publish:deliver` and `pub.publish:deliverAndWait` services are no longer working as expected with Universal Messaging.

In Universal Messaging 10.0 the implementation of shared durables was rewritten to improve stability and performance. However, these changes are not compatible with the `pub.publish:deliver*` services which relied on the previous implementation of shared durables to ensure that delivered documents were routed by Universal Messaging to the intended destination. This incompatibility results in incorrect behavior such as receipt and processing of the delivered message by triggers that do not have the specified destination ID or documents that are never received by the intended trigger.

There is no work around for this issue.

- **PIE-53198**

The health gauge accessed via the `/health` URI always shows the server status as `DOWN` if the Integration Server license does not include the remote invoke and guaranteed delivery features. An Integration Server license key that does not include access to the remote invoke and guaranteed delivery features will always return a status of `DOWN` for the `RemoteServers` health indicator which, in turn, causes the server status to be `DOWN`.

To work around this issue, disable the `RemoteServers` health indicator on the `Microservices > Health Gauge` page in Integration Server Administrator.

- **PIE-52968**

Selection property of `CATCH` step does not update properly based on other `CATCH` step property values.

The `CATCH` step Selection property can have the following values, `empty`, `INCLUDE`, or `EXCLUDE`. The following issues are observed:

- If the `Failures` property contains a value and Selection is set to `EXCLUDE`, and a user then clears the `Failures` property value, the `SELECTION` property is still set to `EXCLUDE`. This is incorrect. The Selection property should automatically be cleared because there are no specific failures to be caught.
- If the `Failures` property contains a value and Selection is left empty, the Selection property should default to `INCLUDE`.

To work around these issues, manually change the Selection property of the CATCH step to be the correct value.

- PIE-45939
State options are not localized in Settings > Messaging > JMS Settings > View JMS Trigger Management> Edit Global JMS Trigger Controls > Individual Standard JMS Trigger Controls screen.
In Integration Server Administrator, the following options for State field in Settings > Messaging > JMS Settings > View JMS Trigger Management> Edit Global JMS Trigger Controls > Individual Standard JMS Trigger Controls > edit all screen are not localized:
Enabled, Disabled, Suspended
There is no workaround for this issue.
- PIE-8185 (was 1-1YBYQD)
Web service connector ends with the error [ISC.0082.9034] Field is absent, field must exist.
If the output signature of a service used as an operation in a provider web service descriptor (WSD) contains a field that has a namespace URI without a prefix, Integration Server adds a prefix when generating a WSDL document for the provider WSD. In the consumer WSD created from the WSDL, the web service connector that corresponds to the operation (IS service) specifies a prefix for the field in the service output. However, the web service provider does not include a prefix with the field in the response. As a result, the contents of the SOAP response cannot be mapped to the web service connector output and the web service connector ends with the error [ISC.0082.9034] Field is absent, field must exist.
To avoid this issue, if a service will be exposed as a web service, always associate a prefix with a namespace URI for fields in the service signature.
- PIE-8494 (was 1-1Z342R)
The xsi:nil attribute in an element does not convert properly when generating an IS document from an XML document.
If an XML document has an element containing only xsi:nil as an attribute and an IS document is generated from that XML document using the pub.xml.xmlNodeToDocument service, the xsi:nil attribute is generated as an @xsi:nil field for the element in the resulting IS document. This occurs even if the element with the xsi:nil attribute has a simple type string; however, the document type that is created from the XML schema (which is used by the XML document) has a string field for the xsi:nil element instead of the IS document. There is a type difference between the generated document and the document type.
To work around this issue, manually edit the generated IS document to remove the @xsi:nil attribute and then convert the IS document to string field.
- PIE-16451
WSDL generated for a web service descriptor with a service signature, header document type, or a fault document type containing derived document types does not contain the schema definitions for the derived document types.
To work around this issue, create a WSDL with the schema definitions for the derived document types and then create a WSDL first web service descriptor.

- PIE-18649

When creating a WSDL first provider web service descriptor, Integration Server does not preserve the original service name from the WSDL document.

When Integration Server generates a WSDL document for the provider web service descriptor, the service name will not match the service name in the source WSDL document.

There is currently no workaround for this issue.
- PIE-19157

IMAP email listener does not start.

This issue occurs when an IMAP e-mail port is configured to receive requests from an e-mail server that uses NTLM for authentication. With this configuration, the following error is returned when the port is enabled:

"Failed to start EmailListener:imap: <UserName>@<HostName>: [ISS.0070.9003] Enable failed: Could not log into account <UserName>@<HostName>"

To resolve this issue, do one of the following:

If you want to disable NTLM authentication, follow these steps:

 1. Open custom_wrapper.conf located under <Software AG_directory>/profiles/IS_default/configuration directory.
 2. Add the following property:
wrapper.java.additional.n=-Dmail.imap.auth.ntlm.disable=true
where n is the next unused sequential number in the file.
 3. Restart Integration Server.

Note that this behavior is consistent with the past releases of Integration Server.

If you want to enable NTLM authentication, follow these steps:

 1. Download jcifs-1.3.15.jar file from <http://jcifs.samba.org/src/> into the <IntegrationServer_directory>/instances/<instanceName>/lib/jars or <IntegrationServer_directory>/lib/jars directory.
 2. Restart Integration Server.
- PIE-22556

Java service throws java.lang.reflect.InvocationTargetException when attempting to use jars from <JRE_directory>/lib/ext directory, such as classes in the com.sun.crypto.provider package.

If you plan to use jars from the <JRE_directory>/lib/ext directory, you can avoid this issue by modifying the config.ini as follows:

 1. Open the config.ini file located in <Software AG_directory>/profiles/IS_<instanceName>/configuration.
 2. Add the following line:
osgi.parentClassLoader=app
 3. Restart Integration Server.
- PIE-32205

Integration Server does not provide Java-based NTLM (Windows NT LAN Manager) support for proxy servers that support NTLM authentication. You can only use the NTLM authentication support in Integration Server to allow clients to access resources on web servers that support NTLM authentication, such as Microsoft Internet Information Server (IIS).

- PIE-51883
Integration Server fails to generate document reference during REST API Descriptor (RAD) creation.
While creating a RAD, Integration Server fails to generate document reference correctly when comments are added in the document reference.
There is no workaround for this issue.
- PIE-50571
The text "API Gateway Transaction Logger" is not translated.
In Integration Server Administrator, on the Settings > Logging > View API Gateway Transaction Logger Details screen, the text "API Gateway Transaction Logger" is not translated into the targeted language.
There is no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- webMethods Broker is deprecated.
- In Universal Messaging version 10.0 the implementation of shared durables was rewritten to improve stability and performance. However, these changes were not compatible with the `pub.publish:deliver*` services which relied on the previous implementation of shared durables to ensure that delivered documents were routed by Universal Messaging to the intended destination. As of version 10.3 (and in fixes delivered on earlier releases), Universal Messaging implemented subscriber name filtering for its durable subscriptions. In subscriber name filtering, when a publisher designates a message for a specific subscriber, Universal Messaging routes the message to a consumer whose durable subscription name matches the designated subscriber name in the message. For Integration Server, the subscription name filtering requires some modifications, specifically:
 - Enable the subscription name filtering feature on Universal Messaging To enable the feature through Universal Messaging Enterprise Manager, navigate to the realm and select the Config tab. In the realm server configuration panel, click Show Advanced Config. Expand Advanced Configuration - Durable Config, and set Durable Name Filtering to true.
 - Change the `destID` input parameter value in invocations of `pub.publish:deliver` and `pub.publish:deliverAndWait`, if necessary. This may only be necessary when the trigger to which the message is to be delivered contains an underscore in its name. For more information about client IDs for triggers and how this change may impact existing services that invoke `pub.publish:deliver*`, see the *Publish-Subscribe Developer's Guide*.
- Take care when setting the `watt.security.max*` server configuration parameters. If the parameters values are set too low, Integration Server rejects legitimate requests. It is also possible to lock yourself out of Integration Server Administrator by setting the parameters too low. If this happens,

you can try changing the configuration parameter values by invoking the `wm.server.admin:setSettings` service with a command-line HTTP client. If you are still unable to change the value of these parameters, you need to kill the Integration Server process, manually edit the parameters in the `Integration Server_directory/instances/instanceName/config/server.cnf` file, and restart Integration Server.

- **PIE-4086 (was 1-1MDBR7)**
In the ClearCase dynamic view, reverting a node after performing a checkout, edit, save, or rename command causes the node to disappear.
When an uncheckout command is issued in ClearCase dynamic view, there is a delay of few seconds before the file is copied to the view. During the delay, the node disappears from Designer. This node reappears in Designer only after the view is refreshed.
This issue occurs only for direct installation of Integration Server in the Dynamic view for certain types of nodes, such as flat file schema. The issue does not occur when working directly in SnapShot view or when working with a folder that is mapped to a SnapShot or Dynamic view.
- **PIE-16497**
Integration Server does not generate the `*doctype` field for IS document types generated from derived document types in a schema, when:
 - Deriving a complex type from an empty complex type by extension.
 - Deriving a complex type from a simple type by extension.
- **PIE-42419**
As of Integration Server 10.0, the Allow List for any new port with an Access Mode of “Deny by Default” now includes the `wm.server.csrfguard:getCSRFSecretToken` service and the `wm.server.csrfguard:isCSRFGuardEnabled` service. When migrating to Integration Server 10.0 or higher from a version lower than 10.0, for any existing ports with an Access Mode of “Deny by Default”, you must manually update the Allow List to include the `wm.server.csrfguard:getCSRFSecretToken` and `wm.server.csrfguard:isCSRFGuardEnabled` services.
- **PIE-48484**
A web service request that specifies a content type of `application/xml` succeeds in versions of Integration Server prior to version 9.12. However, the web service request fails in Integration Server version 9.12. Prior to Integration Server 9.12, Integration Server did not provide out of the box support to directly handle the content type `application/xml`. If a content handler was not specified for `application/xml`, Integration Server used the default content handler. The default handling is the same as the handling of `text/html`, resulting in XML being placed in the pipeline as an `InputStream`. In version 9.12, Integration Server added a content handler named `ContentHandler_XML` to support the content type `application/xml`, resulting in the content being placed in the pipeline as an XML node. This behavior change causes the web service request to fail in version 9.12 because the web service expects an `InputStream`, not an XML node. To address this issue and avoid having to change the service to accept an XML node instead of an `InputStream`, you can use the `watt.server.content.type.mappings` server configuration parameter to map the `application/xml` content type to the `text/xml` content type. Integration Server will use the `text/xml` content handler when receiving a request that specifies a content type of `application/xml`. Specify the following:
`watt.server.content.type.mappings=application/xml text/xml`

- If your solution includes publishable document types with an encoding type of protocol buffers, you need to edit, save, and synchronize the publishable document types to Universal Messaging while the queues of subscribing triggers are empty. This ensures that subscribing triggers will not fail with a NullPointerException if you later choose to edit the publishable document type while queues of subscribing triggers contain published documents that conform to earlier iterations of the publishable document type.
- Integration Server 10.0 introduces the ability to enable or disable follow the master behavior on a per messaging connection alias basis. Prior to Integration Server 10.0, follow the master was enabled globally for webMethods messaging. The only way to disable follow the master behavior was to modify the custom_wrapper.conf file to include the wrapper.java.additional.n=DFollowTheMaster=false where n was the next available wrapper.java.additional number. Do not use the DFollowTheMaster parameter to control the follow the master behavior for Integration Server. This parameter setting will override the follow the master behavior set in Universal Messaging connection aliases and JMS connection aliases.
- When securing web services using policies based on WS-SecurityPolicy, you cannot alter an inbound message before the security processing executes or alter an outbound message after the security processing completes. For inbound messages, Integration Server always performs the security processing first upon receiving the message. As a result, Integration Server cannot invoke custom handlers before the security processing of an inbound message. For outbound messages, Integration Server always performs the security processing last, right before it sends the message. As a result, Integration Server cannot invoke custom handlers after the security processing of an outbound message.
- Integration Server uses Xerces Java parser version J-2.12.0. Limitations for this version are listed at <https://xerces.apache.org/xerces2-j/>.
- If you want to use WS-SecurityPolicy to secure a web service and also want to use MTOM streaming, be aware that if the fields to be streamed are being signed and/or encrypted, Integration Server cannot use MTOM streaming because Integration Server needs to keep the entire message in memory to sign and/or encrypt the message.
- Web services security implemented using WS-Security facility in Integration Server does not support partial message operations (Sign/Encrypt). Integration Server allows only the body of the SOAP message to be signed and encrypted.
- Do not modify the following file unless instructed to do so by Software AG:
 <IntegrationServer_directory>\instances\<instanceName>\config\wss\axis2.xml
 Changes to this file may result in an unstable configuration. Software AG will not support issues that arise as a result of changes to this file that were not authorized by Software AG.
- Software AG does not support the deployment of custom handlers or modules via placement of an Axis Module (*.mar) file in the following directory:
 <IntegrationServer_directory>\instances\<instanceName>\config\wss\modules
 Unexpected behavior that arises due to the manual deployment of mar files directly to this location is the responsibility of the user and will not be addressed by Software AG.

- Software AG does not support the deployment of web services via placement of an Axis Archive (*.aar) file in the following directory:
`<IntegrationServer_directory>\instances\<instanceName>\config\wss\services`
 Unexpected behavior that arises due to the manual deployment of aar files directly to this location is the responsibility of the user and will not be addressed by Software AG.
- In Integration Server version 10.1, the default behavior of the enhanced XML parser now prohibits the support of DTDs and resolution of external entity references. For the `pub.xml:loadEnhancedXMLNode` and `pub.xml:XMLStringToEnhancedXMLNode` services the `inputProcessing\supportDTD` input parameter and the `inputProcessing\isSupportingExternalEntities` now have a default value of false. If an existing solution relies in the previous default behavior (`inputProcessing\supportDTD` and `inputProcessing\isSupportinExternalEntities` were set to true), after migrating to Integration Server 10.1 or higher, you must update invocations of `pub.xml:loadEnhancedXMLNode` and `pub.xml:XMLStringToEnhancedXMLNode` to set `inputProcessing\supportDTD` and `\or inputProcessing\isSupportinExternalEntities` to true.
- Now, when you start Integration Server, Integration Server receives configuration settings (for example, the size of the Java heap) from the `wrapper.conf` and `custom_wrapper.conf` files located in the `Software AG_directory\profiles\IS_instance_name\configuration` directory. Integration Server no longer obtains settings from `setenv.bat/sh` or `server.bat/sh`.
 If you need to modify the default property settings for Integration Server, you can override the settings using the `custom_wrapper.conf` file. The following table shows the settings formerly set in the `setenv.bat/sh` file that are now set using properties in the `custom_wrapper.conf` file:

This setting in setenv.bat/sh...	Is replaced with the following property in custom_wrapper.conf...
APPENDCLASSES/ APPEND_SYSTEM_CLASSPATH	wrapper.java.additional.203= Dwatt.server.append.classes=
JAVA_CUSTOM_OPTS	wrapper.java.additional.n
JAVA_MAX_DIRECT_SIZE	wrapper.java.additional.n=XX:MaxDirectMemorySize=
JAVA_MAX_MEM	wrapper.java.maxmemory
JAVA_MAX_PERM_SIZE	wrapper.java.additional.n=XX:MaxPermSize=
JAVA_MIN_MEM	wrapper.java.initmemory
PREPENDCLASSES/ PREPEND_SYSTEM_CLASSPATH	wrapper.java.additional.202= Dwatt.server.prepend.classes=

The following table shows settings you can change that were formerly in the `setenv.bat/sh` file, but are now located in other files or removed:

Setting	New location (if applicable)
DEBUG_ENABLED	<code>Software AG_directory\profiles\IS_instance_name\bin\startDebugMode.bat/sh</code>

JAVA_PROFILER_OPTS/ PROFILER_ENABLED	Removed.
Java location	wrapper.java.command in <i>Software AG_directory</i> \profiles\ <i>IS_instance_name</i> \configuration\wrapper.conf
JMX_ENABLED	Removed. JMX monitoring is enabled by default and cannot be disabled.
JMX_PORT	The port property in <i>Software AG_directory</i> \profiles\ <i>IS_instance_name</i> \configuration\com.software.jmx.connector.pid-port.properties

The startup.bat/sh and shutdown.bat/sh scripts contained in the *Integration Server_directory*\instances*instance_name*\bin and *Integration Server_directory*\bin directories are deprecated. You should use the scripts contained in the *Software AG_directory*\profiles*IS_instance_name*\bin directory to start and stop Integration Server. If you will manage Integration Server through Command Central, you *must* use the scripts located in the *Software AG_directory*\profiles*IS_instance_name*\bin directory.

The installSvc.bat file located in *Integration Server_directory*\instances*instance_name*\support\win32 directory is also deprecated. You should use the service.bat file from the *Software AG_directory*\profiles*IS_instance_name*\bin directory to register or remove an Integration Server instance as a Windows service.

For complete instructions for using any of the features affected by these changes, see *webMethods Integration Server Administrator's Guide* and *Working with the webMethods Product Suite and the Java Service Wrapper*.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- IS_9.5_SP1_Core_Fix19
- IS_9.7_Core_Fix25
- IS_9.8_Core_Fix21
- IS_9.9_Core_Fix26
- IS_9.10_Core_Fix15
- IS_9.12_Core_Fix17

- IS_9.12_SPM_Fix5
- IS_10.1_Core_Fix5
- IS_10.1_SPM_Fix3
- IS_10.2_Core_Fix2
- MIG_9.10_MigrationFramework_Fix1
- MIG_9.12_MigrationFramework_Fix4,
- WFF_10.1_Fix2

Release 10.2

- IS_8.2_SP2_Core_Fix24
- IS_9.0_SP1_Core_Fix21
- IS_9.5_SP1_Core_Fix18
- IS_9.6_Core_Fix18
- IS_9.7_Core_Fix22
- IS_9.8_Core_Fix18
- IS_9.9_Core_Fix22
- IS_9.10_Core_Fix11
- IS_9.12_Core_Fix14
- IS_9.12_SPM_Fix4
- IS_10.0_Core_Fix3
- IS_10.0_WmCloud_Fix3
- IS_10.1_Core_Fix3
- IS_10.1_SPM_Fix1
- MIG_9.12_MigrationFramework_Fix3
- MIG_10.1_MigrationFramework_Fix1
- WFF_9.7_Fix6
- WFF_9.9_Fix4

- WFF_9.12_Fix3

Release 10.1

- IS_8.2_SP2_Core_Fix23
- IS_9.0_SP1_Core_Fix20
- IS_9.5_SP1_Core_Fix17
- IS_9.6_Core_Fix16
- IS_9.7_Core_Fix19
- IS_9.8_Core_Fix15
- IS_9.8_Tanuki_Fix1
- IS_9.9_Core_Fix15
- IS_9.9_SPM_Fix4
- IS_9.10_Core_Fix9
- IS_9.10_SPM_Fix2
- IS_9.10_Tanuki_Fix
- IS_9.12_Core_Fix7
- IS_9.12_SPM_Fix2
- IS_9.12_WmCloud_Fix2
- IS_10.0_Core_Fix1
- IS_10.0_WmCloud_Fix2
- MIG_9.12_MigrationFramework_Fix1
- WAR_9.7_Fix3
- WAR_9.8_Fix4
- WAR_9.9_Fix2
- WAR_9.10_Fix3
- WAR_9.12_Fix1
- WFF_9.6_Fix5

- WFF_9.9_Fix3
- WFF_9.10_Fix1
- WFF_9.12_Fix1

Release 10.0

- IS_8.2_SP2_Core_Fix22
- IS_9.0_SP1_Core_Fix18
- IS_9.5_SP1_Core_Fix14
- IS_9.6_Core_Fix13
- IS_9.7_Core_Fix14
- IS_9.7_SPM_Fix3
- IS_9.7_SubVersion_Fix1
- IS_9.7_Tanuki_Fix1
- IS_9.7_VCS_Fix1
- IS_9.7_WmCloud_Fix4
- IS_9.8_Core_Fix11
- IS_9.8_SPM_Fix2
- IS_9.8_VCS_Fix1
- IS_9.8_WmCloud_Fix1
- IS_9.9_Core_Fix9
- IS_9.9_SPM_Fix3
- IS_9.9_Tanuki_Fix1
- IS_9.9_VCS_Fix1
- IS_9.9_WmCloud_Fix1
- IS_9.10_Core_Fix6
- IS_9.10_SPM_Fix1
- IS_9.10_VCS_Fix1

- IS_9.10_WmCloud_Fix1
- IS_9.12_Core_Fix4
- IS_9.12_WmCloud_Fix1
- WAR_9.6_Fix5

Release 9.12

- IS_8.0_SP1_Core_Fix32
- IS_8.2_SP2_Core_Fix20
- IS_9.0_SP1_Core_Fix14
- IS_9.5_SP1_Core_Fix11
- IS_9.7_Core_Fix8
- IS_9.7_Tomcat6_Fix2
- IS_9.8_Core_Fix5
- IS_9.9_Core_Fix2
- IS_9.9_SPM_Fix2
- IS_9.10_Core_Fix1
- IS_9.10_OData_Fix1
- WAR_9.7_Fix2
- WAR_9.8_Fix3
- WAR_9.10_Fix2
- WFF_8.2_SP2_Fix6
- WFF_9.5_SP1_Fix4
- WFF_9.6_Fix4
- WFF_9.8_Fix1
- WFF_9.9_Fix1

Release 9.10

- IS_7.1.3_Core_Fix28
- IS_8.2_SP2_Core_Fix19
- IS_9.0_SP1_Core_Fix13
- IS_9.5_SP1_Core_Fix10
- IS_9.5_SP1_Portal_Fix3
- IS_9.6_Core_Fix9
- IS_9.7_Core_Fix5
- IS_9.7_Portal_Fix4
- IS_9.8_SPM_Fix1
- IS_9.9_Core_Fix1
- IS_9.9_SPM_Fix1
- WAR_9.5_SP1_Fix6
- WAR_9.8_Fix2
- WFF_8.2_SP2_Fix5
- WFF_9.0_SP1_Fix2
- WFF_9.5_SP1_Fix3
- WFF_9.6_Fix1
- WFF_9.7_Fix4

Release 9.9

- IS_8.2_SP2_Core_Fix17
- IS_9.0_SP1_Core_Fix10
- IS_9.0_SP1_WmCloud_Fix1
- IS_9.5_SP1_Core_Fix8
- IS_9.5_SP1_WmCloud_Fix1
- IS_9.6_Core_Fix7

- IS_9.6_MobileSupport_Fix1
- IS_9.6_SubVersion_Fix1
- IS_9.6_Tomcat6_Fix3
- IS_9.7_Core_Fix4
- IS_9.7_Migration_Fix1
- IS_9.7_SPM_Fix2
- IS_9.8_Core_Fix2
- WAR_9.5_SP1_Fix5
- WAR_9.7_Fix1

Release 9.8

- IS_7.1.2_Core_Fix47
- IS_7.1.3_Core_Fix27
- IS_8.2_SP2_Tanuki_Fix1
- IS_8.2_SP2_Tomcat6_Fix7
- IS_9.0_SP1_Core_Fix8
- IS_9.0_SP1_Tanuki_Fix1
- IS_9.5_SP1_Migration_Fix1
- IS_9.5_SP1_Portal_Fix2
- IS_9.5_SP1_Tanuki_Fix1
- IS_9.5_SP1_Tomcat6_Fix1
- IS_9.6_Core_Fix4
- IS_9.6_Migration_Fix2
- IS_9.6_Portal_Fix1
- IS_9.6_Tanuki_Fix1
- IS_9.6_Tomcat6_Fix1
- IS_9.7_AssetPublisher_Fix1

- IS_9.7_Core_Fix2
- IS_9.7_Portal_Fix2
- IS_9.7_Tomcat6_Fix1
- IS_9.7_WmCloud_Fix1
- WAR_8.2_SP2_Fix6
- WAR_9.0_SP1_Fix2
- WAR_9.5_SP1_Fix4
- WAR_9.6_Fix3
- WFF_9.0_SP1_Fix2
- WFF_9.5_SP1_Fix3
- WFF_9.6_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- PIE-48958 [IS_10.1_Core_Fix5]
When creating a document type from XML string in Integration Server, an XML external entity attack was possible during the validation of XML string.
The issue is now resolved. After the fix, Integration Server rejects such XML with the following message - "XML provided is not well-formed or external references encountered while parsing XML - <specific error message>". - "
- PIE-47905 [IS_10.2_Core_Fix2, IS_9.10_Core_Fix12, IS_9.12_Core_Fix15]
Application Platform does not initialize properly when Integration Server startup does not complete within 5 minutes.
To resolve this issue, Integration Server registers the OSGi services before continuing with the rest of startup. This allows Application Platform to initialize properly even if Integration Server takes longer than 5 minutes to complete startup.
- PIE-50428 [IS_10.2_Core_Fix2, IS_9.12_Core_Fix16]
Element in outbound SOAP message is associated with the incorrect namespaces.
When an attribute on an element redefines the XML namespace prefix for an element to be a different URL from the one defined in the WSDL document and WS-Security processing is

engaged, the element in the outbound SOAP message is associated with the incorrect namespace. This issue is now resolved.

- PIE-50562 [IS_10.2_Core_Fix2, IS_9.12_Core_Fix16]
Generation of a consumer web service descriptor or WSDL first provider web service descriptor fails with a WSDLException.
If a WSDL document contains an empty targetNamespace attribute, an attempt to create a web service descriptor from the WSDL document fails with the following exception:
WSDLException: faultCode=PARSER_ERROR: Problem parsing '- WSDL Document -':
org.xml.sax.SAXParseException: The value of the attribute "prefix="xmlns",localpart="tns",rawname="xmlns:tns"" is invalid. Prefixed namespace bindings may not be empty.
Now, when creating a web service descriptor from a WSDL document that contains an empty targetNamespace attribute, Integration Server no longer generates the xmlns:tns= attribute.
Note: This fix resolves the issue for consumer web service descriptors completely. However, to fully resolve the issue for WSDL first provider web service descriptors, you must also install a Web Services Stack fix that includes WSSTACK-2783.
- PIE-51285 [IS_10.2_Core_Fix2, IS_9.12_Core_Fix17]
The enhanced XML parser throws an ArrayIndexOutOfBoundsException when more than 20 attributes are present on a node.
With this fix, there is longer a limit to the number of attributes on a node which prevents the ArrayIndexOutOfBoundsException.
- PIE-50185 [IS_10.2_Core_Fix2]
Integration Server does not close a socket connection after SSL handshake fails.
If Integration Server establishes the socket connection using JSSE and then if the SSL handshake fails, the socket connection remains open.
The issue is now resolved. Integration Server now closes the socket connection after SSL handshake fails.
- PIE-51486 [IS_10.2_Core_Fix2]
When entering quiesce mode Integration Server shuts down all cache managers available in a JVM instead of just the cache managers started by Integration Server.
This issue is now resolved.
- PIE-51047 [IS_9.10_Core_Fix14, IS_9.12_Core_Fix17, IS_9.7_Core_Fix24, IS_9.8_Core_Fix21, IS_9.9_Core_Fix25]
When editing existing keystore and truststore aliases, the configured "Type" and "Provider Type" fields show incorrect input.
When editing existing keystore and truststore aliases properties, the values or the "Type" and "Provider" fields are reset to "JKS" and "SUN" instead of the configured values set during the creation of keystore and truststore aliases.
The issue is resolved. Integration Server now preserves the settings used during the creation of keystore and truststore aliases.
- PIE-51909 [IS_9.10_Core_Fix14, IS_9.12_Core_Fix17, IS_9.7_Core_Fix24, IS_9.8_Core_Fix21,

IS_9.9_Core_Fix25]

Long latencies observed when using SFTP.

Concurrent execution of the `pub.client.sftp:login` service and/or methods in the underlying class `com.wm.app.b2b.server.sftp.client.SFTPSessionManager` may result in long latencies which are caused by synchronization.

To address this issue and improve multi-threading support, synchronization statements deemed unnecessary were removed.

- PIE-49804 [IS_9.10_Core_Fix14, IS_9.12_Core_Fix17, IS_9.9_Core_Fix25]
Enhancements in web service connectors to process messages in an order.
When creating a consumer web service descriptor from a WSDL document, Integration Server creates a web service connector for each operation contained in the WSDL document. These connectors do not provide a facility to process messages in an order.
The issue is now resolved. Integration Server now uses message numbers that are unique identifiers used by the reliable messaging sequence.
- PIE-51892 [IS_9.10_Core_Fix14, IS_9.12_Core_Fix17, IS_9.9_Core_Fix25]
FTP thread hangs during FTP put operation.
During an FTP file transfer using the FTP put command from client to server, where Integration Server acts as the server, if a network issue occurs, then the FTP thread hangs and it never times out. This issue happens only in Passive mode.
The issue is now resolved.
- PIE-51663 [IS_9.10_Core_Fix14, IS_9.12_Core_Fix17]
Integration Server acting as FTPS client cannot connect to an FTPS server.
An Integration Server acting as FTPS client cannot connect to an FTPS server using JSSE.
Integration Server uses JSSE when the `secure/useJSSE` input parameter for the `pub.client.ftp*` service is set to `yes`.
The issue is now resolved.
- PIE-52091 [IS_9.10_Core_Fix14, IS_9.8_Core_Fix21, IS_9.9_Core_Fix26]
When `watt.net.http401.throwException` is `false` and the `pub.client:http` service does not get a response from the server to which it is trying to connect, Integration Server throws a `NullPointerException` instead of a `ServiceException`.
This issue is now resolved.
- PIE-51877 [IS_9.10_Core_Fix14, IS_9.9_Core_Fix25]
Integration Server throws a `ConcurrentModificationException` when initializing a connection from a JDBC connection pool.
This issue is resolved by updating methods in an internal class to use locking.
- PIE-49739 [IS_9.10_Core_Fix14]
Public service `setKeyAndChainFromBytes` does not work properly if the SSL key differs from the default SSL key in Integration Server Administrator.
If an SSL key is configured in the Integration Server Administrator (Security > Certificates) is different from the one set using the `setKeyAndChainFromBytes` service, then Integration Server does not send the SSL key set by `setKeyAndChainFromBytes` service for connections using JSSE.

Normally, SSL key set using the setKeyAndChainFromBytes service takes precedence over the one set in the Integration Server Administrator.

This issue is resolved now.

- PIE-50123 [IS_9.10_Core_Fix15, IS_9.12_Core_Fix17]
ODATA \$filter query fails when there is an ampersand (&) in the search string.
When using the Integration Server OData implementation to query the OData entity with a filter containing the ampersand character (&). For example: \$filter=SAMPLE eq 'Text1 & Text2', Integration Server returns an incorrect result.
Integration Server now returns a proper result; however, the query string that uses & must be properly encoded before Integration Server receives the query. For example:
\$filter=SAMPLE%20eq%20%27Text1%20%26%20Text2%27
- PIE-51631 [IS_9.10_Core_Fix15, IS_9.7_Core_Fix25]
The pub.document:searchDocuments service behaves differently than expected.
The pub.document:searchDocuments service functions differently from the expected behavior, which is documented in the webMethods Integration Server Built-In Services Reference.
This issue is now resolved.
- PIE-51101 [IS_9.12_Core_Fix16, IS_9.12_Core_Fix17]
No option to set custom truststore while invoking pub.client:http service.
The pub.client:http service uses the default truststore alias (DEFAULT_IS_TRUSTSTORE) while establishing a secure connection with HTTP server. Integration Server does not provide the option to set custom truststore while invoking this service.
This issue is resolved. Now, a new input parameter "trustStore" is included in pub.client:http service to set the custom truststore alias while invoking this service.
- PIE-49598 [IS_9.12_Core_Fix17]
Integration Server does not validate the SSL certificate expiry while using JSSE.
Integration Server does not validate the SSL certificate expiry in a certificate chain of an incoming connection request from an Internet resource while it is configured to use JSSE. Hence, even if the certificate has expired, Integration Server does not reject the request.
This issue is now resolved.
- PIE-50404 [IS_9.12_Core_Fix17]
Input parameter value of scheduled task is overwritten with the latest value of input parameter in flow service.
An assigned input value in scheduler task is overwritten with the latest value set for the corresponding flow service. This impacts the value of the input parameter in the scheduled task.
This issue is now resolved.
- PIE-51293 [IS_9.12_Core_Fix17]
Execution of a web service connector ends with a NullPointerException.
Execution of a web service connector for a consumer web service descriptor generated from a WSDL document containing multiple service definitions ends with a NullPointerException. This occurs because Integration Server did not create the BRANCH steps correctly when creating the connector.

Now, Integration Server generates the correct BRANCH steps for web service connectors created from a WSDL document with multiple service definitions.

Note: After applying this fix, you must recreate or refresh the consumer web service descriptor to generate web service connectors with the correct BRANCH steps.

- PIE-51300 [IS_9.12_Core_Fix17]

webMethods messaging trigger ends with the exception

`com.google.protobuf.InvalidProtocolBufferException: Protocol message contained an invalid tag (zero).`

If a publishable document type specifies an encoding type of Protocol buffers and saving changes to the document type results in warning messages about field names not being valid for protocol buffer encoding, trigger processing fails for instances of the publishable document type with the following exception:

`com.wm.app.b2b.server.dispatcher.exceptions.MessagingCoderException: java.io.IOException: com.google.protobuf.InvalidProtocolBufferException: Protocol message contained an invalid tag (zero)`

This issue occurs because of an error in how Integration Server encodes the `UnknownFieldSet` when publishing a document. The `UnknownFieldSet` contains fields that cannot be represented in a protocol buffer message descriptor.

This issue is resolved by changing the way in which Integration Server encodes the `UnknownFieldSet` at the time of publication. This encoding change affects only those documents published after the fix is installed. Existing, unprocessed documents that use the improperly encoded `UnknownFieldSet` must be removed to prevent the occurrence of `InvalidProtocolBufferException: Protocol message contained an invalid tag (zero)`. Make sure the client side queue for the Universal Messaging connection alias that publishes instances of the document type is empty. Additionally, make sure to use Universal Messaging Enterprise Manager to delete the channel associated with the publishable document type. Deleting the channel removes any instance documents encoded with the invalid zero key. Integration Server recreates the channel when it is restarted after fix installation.

- PIE-51613 [IS_9.12_Core_Fix17]

Integration Server does not start if the distributed service results cache contains invalid entries.

If the distributed service results cache contains invalid entries, Integration Server exits with an error similar to the following.

Error occurred while initializing server: `java.lang.StringIndexOutOfBoundsException: String index out of range: -1 at java.lang.String.substring(String.java:1967) at com.wm.app.b2b.server.ostore.ServiceCacheImpl.getKeySvc(ServiceCacheImpl.java:350) at com.wm.app.b2b.server.ostore.ServerCache.load(ServerCache.java:110) at com.wm.app.b2b.server.CacheManager.startSweeper(CacheManager.java:128) at com.wm.app.b2b.server.Server.run(Server.java:644)`

This issue is now resolved.

- PIE-52025 [IS_9.12_Core_Fix17]

Unable to restart Integration Server in a clustered environment.

After installing a fix that contains PIE-45163, restarting Integration Server in a clustered environment fails if there is scheduled task with target set to 'All'. Also, the

pub.scheduler:getTaskInfo service returns incorrect status of a running task.
These issues are now resolved.

- PIE-50807 [IS_9.7_Core_Fix24]
Integration Server fails to read the restore file.
Integration Server throws an exception while restoring pipeline from file using the pub.flow:restorePipelineFromFile service. The issue has occurred because an incorrect data type was defined to one of the input fields in the file while saving pipeline.
This issue is now resolved.
- PIE-50102
Integration Server fails to update the REST API descriptor(RAD) containing REST V2 resources. In Designer, while making changes to the REST V2 resources or the services associated with the operations of the resources, Integration Server fails to update the RAD that contains the REST V2 resources.
The issue is now resolved.
- PIE-50180
Decoding a dynamic parameter with unicode characters fails to decode accurately. Integration Server fails to correctly decode the unicode characters in the dynamic parameter of a REST request.
This issue is now resolved.
- PIE-50348
Integration Server fails to add comments to the generated document.
When creating a REST API descriptor from a Swagger document, if a definition in the Swagger document contains comments, Integration Server fails to add those comments to the corresponding Comments tab of generated docTypes.
This issue is now resolved.
- PIE-50352
In a REST API descriptor, variables of type File get converted to type String.
When creating a REST API descriptor from a Swagger document, Integration Server represents a file type as a String instead of a document.
This issue is resolved. Since Integration Server does not support the File type, variables of type File are converted to Object type.
- PIE-50359
Integration Server clears the response code from a REST API descriptor.
When adding a new response code to a resource in REST API descriptor and then moving the resource from one package to another, Integration Server removes all the new response codes from REST API descriptor.
This issue is now resolved.
- PIE-50616
Unable to create a REST API Descriptor for REST resources with documents with cyclic references. Creating a REST API descriptor for REST resources with services that have documents with cyclic

references fail.

This issue is now resolved.

- PIE-50639
Clicking the Log Off link in Integration Server Administrator causes Internet Explorer to log the user out of all Integration Servers in all Internet Explorer tabs.
This issue is resolved. Clicking the Log Off link in an Internet Explorer tab now logs the user out of the Integration Server in the current tab only. If the user is logged in to the same Integration Server through multiple tabs, logging off the Integration Server on one tab logs the user off of that same Integration Server on the other tabs as well.
- PIE-50642
Integration Server displays '405 method not found' error while executing a URL at run time that is added to a REST API descriptor(RAD).
While adding two similar URLs to a RAD with different HTTP methods, Integration Server might display '405 method not found' error while executing one of the URLs during run time.
The issue is now resolved.
- PIE-50780
The pub.client:http service ends with a NullPointerException if useJSSE is set to yes and the default truststore is not configured.
If the default truststore is not configured, the watt.security.cert.wmChainVerifier.trustByDefault parameter is set to false, the pub.client:http service sets useJSSE to yes, the pub.client:https service ends with a NullPointerException but should not.
This issue is now resolved.
- PIE-51052
When migrating JDBC connection pools, Integration Server migration utility reports the following error. "Error message: String index out of range: -1"
This issue occurs because of the non-XML files present in the <IntegrationServer_installDirectory>\instances\This issue is now resolved. Integration Server migration utility correctly migrates JDBC connection pools.
- PIE-51268
Integration Server displays incorrect error messages when certain services belonging to pub.string package are invoked without the required inputs.
Integration Server throws incorrect error messages when the pub.string:tokenize , pub.string:numericFormat ,pub.string:padLeft , pub.string:padRight services are invoked.
- When invoked without the required inputs com.wm.app.b2b.server.ServiceException: java.lang.NullPointerException is thrown and com.wm.app.b2b.server.ServiceException: java.lang.NumberFormatException is thrown when invoked with invalid inputs
This issue is now resolved. Now, Integration Server displays the following appropriate error messages:
com.wm.app.b2b.server.ServiceException: [ISS.0086.9249] Missing Parameter for incomplete inputs

com.wm.app.b2b.server.ServiceException: [ISS.0086.9250] Parameter is not of type for invalid inputs

- PIE-51641
Package deployment fails with a NullPointerException when the Compile Java Services option is set to Yes.
Deploying a package that contains a Java service fails with a NullPointerException similar to the following when the Compile Java Services option is set to Yes:
java.lang.NullPointerException: null
at com.wm.lang.ns.NSService.setValues(NSService.java:717)
at com.wm.lang.ns.NSNode.<init>(NSNode.java:93)
at com.wm.lang.ns.NSService.<init>(NSService.java:149)
at com.wm.app.b2b.server.BaseService.<init>(BaseService.java:201)
This issue is now resolved.
- PIE-51723
Enterprise Gateway blocks the IP address of the proxy used.
When a proxy is used between a client and Enterprise Gateway, then Enterprise Gateway blocks the IP address of the proxy. This is because, Enterprise Gateway ignores the X-Forwarded-For header in the request and hence during a Denial of Service attack check, instead of using the client IP address it uses the IP address of the proxy server.
This issue is resolved. Now, Integration Server checks for X-Forwarded-For header in request and if it is present, then Enterprise Gateway uses the client IP address from this header.
- PIE-52012
Invoking pub.string:numericFormat service with a decimal value for the 'num' parameter fails with error.
Invoking the pub.string:numericFormat service by providing a decimal value for the input parameter 'num' fails with following error: [ISS.0086.9250] Parameter [num] is not of type: [Integer]
This issue is now resolved.
- PIE-52017
Integration Server supports string constraints in Swagger document.
Integration Server supports to add string field constraints such as MinLength, MaxLength, and Pattern to the Swagger document generated for REST V2 resources. Integration Server generates the constraints along with the Swagger document that are set as part of the fields in the referred definition or service.
This is a new feature.
- PIE-52089
Integration Server rolls back the messages to Universal Messaging if message processing fails with a decoding error.
While processing a message using webMethods messaging trigger that receives documents from Universal Messaging, if Integration Server encounters any decoding errors, Integration Server rolls back the message to the message provider (in this case, Universal Messaging). As the decoding errors are non-transient, the same message rolls back each time Integration Server starts processing

that message.

This issue is now resolved. If a webMethods messaging trigger encounters a decoding exception while processing a message, Integration Server acknowledges the message to messaging provider. The message text for [ISS.0153.0089C] has also changed to "Trigger <trigger_name> failed because of message decoding exception: <exception_message>. Message has been acknowledged to messaging provider."

- PIE-52220

Passing an empty string as an input in pub.string:tokenize service fails with an error.

In the pub.string:tokenize service when an empty string is passed as an input for the "inString" parameter, Integration Server throws the following error:

com.wm.app.b2b.server.ServiceException: [ISS.0086.9272] inString cannot be empty when empty string is passed as an input for parameter "inString".

This issue is now resolved. Now, pub.string:tokenize service accept empty string as an input parameter.

- PIE-52300

After applying a fix that includes PIE-36402 or migrating to a version of Integration Server that includes PIE-36402, execution of a web services that use multi-level document type references exhibits a performance degradation in Integration Server as compared to older releases.

Web services that contain multiple levels of document type references (in which a document reference field includes a field that is a document reference field which in turn also includes a field that is a document reference field, and so forth) exhibit a decrease in performance. This issue is observed after applying a fix containing PIE-36402 (IS_9.8_Core_Fix2) on Integration Server 9.8 or in Integration Server versions 9.9 and higher.

The performance degradation has been remedied by identifying and removing performance bottlenecks.

- PIE-52360

An enabled webMethods messaging trigger does not have a registered listener on Universal Messaging but the trigger cannot be restarted.

In some situations, a webMethods messaging trigger that receives messages from Universal Messaging does not create the associated listener on the Universal Messaging server as part of trigger startup. Without the listener, the trigger will not receive messages from Universal Messaging. Even though there is not a listener for the trigger, the trigger remains in an enabled state which prevents Integration Server from restarting the trigger.

This issue is observed in the following scenarios:

- During startup of the webMethods messaging trigger, the connection to Universal Messaging becomes unavailable but is quickly re-established. However, the listener for the trigger is not created on the Universal Messaging server. In Integration Server Administrator, the trigger state indicates that it is enabled but not connected (On the Settings > Messaging > webMethods Messaging Trigger Management screen, the Active property displays Yes (Not Connected) for the trigger.) In this state, the trigger cannot be re-enabled manually. The Universal Messaging connection alias used by the trigger must be restarted for the trigger to be enabled. This scenario is most frequently observed when Integration Server connects to an active-active Universal Messaging cluster.

- During startup of the webMethods messaging trigger, Universal Messaging throws an exception while creating the listener for the trigger but the Universal Messaging connection alias remains active. This can occur for a variety of reasons but it most often occurs when the trigger request to create the listener times out or when the Universal Messaging connection alias and the trigger are connecting to different realms.

To resolve the scenarios in which a listener is not created on Universal Messaging as part of startup of the webMethods messaging trigger, Integration Server now attempts to restart any webMethods messaging trigger that is enabled, associated with an active Universal Messaging connection alias, and does not have a registered listener on Universal Messaging server.

- **PIEAR-1086**
Assertion errors related to Adapter Connections are logged when releasing the connection or making the connection available. This happens when the parent service has set a timeout in the flow services.
This issue is now resolved.
- **PIEAR-1093**
Error copying an existing connection as the default values for the connection properties are not copied.
The issue is now resolved.

Release 10.2

- **PIEAR-1052**
In webMethods Adapter for SAP, the connection is not enabled, as the script file was not loaded. The issue is resolved. Now the connection is enabled and ART retains the backward compatibility of the adapters which are referring to the java scripts with the extension .js.txt.
- **PIEAR-1056**
In webMethods Adapter for Runtime, an error occurs when you view the listeners in Integration Server Administrator.
This issue occurs when the listener is not loaded in the Integration Server which is referred by one of the notifications.
This issue is now resolved.

Release 10.1

- **PIE-45041**
The Integration Server server log contains the active Session ID even though masking of Session IDs is enabled.
The Integration Server server log contains the active Session ID when the maskSession ID is set to "true" and logging level is set to "Trace". The active Session ID is mentioned even though masking of Session IDs is enabled.
This issue is now resolved.
- **PIE-45064**

Moving or renaming folders containing flow services results in broken references.

When a folder containing a flow service is moved or renamed, any document references present in the flow service are not correctly updated. This results in the flow service containing broken references.

The issue is now resolved.

- PIE-45087
Designer does not honor the protocol buffer encoding type for a publishable document type created in an earlier version of Integration Server.
When using Designer 9.10 or higher to view or edit a publishable document type created on an Integration Server version 9.10 or earlier, Designer may display the IData as the Encoding type even though the assigned encoding type is protocol buffers. Additionally, if the Encoding type is changed to Protocol buffers, Designer reverts the Encoding type to IData upon save.
This issue is now resolved.
- PIE-45125
Java services that reference Ehcache classes directly cannot be compiled.
This issue is resolved.
- PIE-45131
Issues with configuring a restV2 resource.
When configuring a restV2 resource, Integration Server does not display any error on specifying a URL format containing only dynamic parameters for a REST resource. This is incorrect because a URL format must include at least one static parameter.
Integration Server throws an exception on specifying a URL format with only dynamic parameters.
- PIE-45172
From Command Central, Integration Server instance creation using a YAML template and specifying the dbtype in lower case prevents any update to Audit Logging Destination.
When using Command Central to create an Integration Server instance using a YAML template and specifying the dbtype in lowercase prevents any attempt to change the Audit Logging Destination to 'Database' for an Audit Logger in the Edit Session Logger Details page (Settings> Logging> Edit Session Logger Details). Additionally, the following error occurs on changing the Session Logger: RESTART is required due to inability to update in Integration Server.
This issue is resolved. Now, the dbtype is case insensitive in the YAML template, allowing the choice of "Database" as the destination when the ISCoreAudit Functional Pool is set to a valid JDBC pool.
- PIE-45177
When using Command Central to create an Integration Server instance using a YAML template, specifying the dbtype in lower case causes the functional description to be unavailable.
When creating an Integration Server instance with Command Central, using YAML template and specifying the dbtype in lowercase causes the functional description of functional alias to be unavailable for viewing or editing on the Settings > JDBC Pools > Functional Definitions page.
This issue is resolved. Now, the dbtype is case insensitive in the YAML template and hence, the function description appears correctly.

- PIE-45320
 Unable to add IPv6 address in Integration Server to access a port.
 While updating the IP access of a port in the Integration Server Administrator on the Security > Ports > IP Access screen, Integration Server does not allow a user to add an Ipv6 address in the allow/deny lists of IP address.
 This issue is now resolved. Integration Server now allows an IPv6 address in the allow/deny lists.
- PIE-45366
 Searching for Integration Server elements results in a NullPointerException.
 Searching for Integration Server elements using the Service Development perspective of Designer in a package for which the manifest.v3 file has the system_package attribute missing results in a NullPointerException.
 This issue is now resolved.
- PIE-45543
 Executing the is_container script with the createLeanDockerfile option creates a Docker image that does not include the WmCloud package.
 This issue is now resolved.
- PIE-45588
 When using a stand-alone Java client created for Integration Server, the client ignores client certificates when establishing an outbound HTTP connection using JSSE.
 When a stand-alone Java client uses the Integration Server method `com.wm.app.b2b.client.BaseContext.setSSLCertificates()` to provide client certificates for the purpose of establishing an SSL connection using JSSE, the client did not provide the destination HTTP server with the client certificates needed to establish the connection.
 This issue is now resolved.
- PIE-45797
 Java service compilation fails with an error if the service uses the Common Directory Services API. If a Java service uses the Common Directory Service API, compilation of the Java service fails with the following error:
`class file for com.webmethods.sc.LocalizedException not found`
 This issue is now resolved.
- PIE-46024
 Integration Server now supports migration when source and target version are same.
 The migration utility can now be used for migration where the source and target versions of Integration Server are the same. This can be useful for data center or machine moves.
- PIE-46407
 Unable to change the logging level for Integration Server by using composite templates in Command Central.
 When using a composite template in Command Central to change the logging level for an Integration Server, Command Central throws a `ConfigurationValidationException` and the logging level does not change.

This issue is now resolved.

- PIE-46654
The Integration Server migration utility does not migrate the quiesce port settings.
This issue is now resolved.
- PIEAR-1002
In webMethods Adapter Runtime 10.1, when you create an adapter connection, the Pool Increment Size value in connection management property cannot be greater than Maximum Pool Size value.
This issue is resolved. Pool Increment Size is now validated with Maximum Pool Size value.
- PIEAR-1004
In webMethods Adapter Runtime 10.1, the connection pool reset does not happen when adapter connection exception occurs in the design time while creating or configuring the adapter services.
This issue is now resolved.
- PIEAR-1012
In webMethods Adapter Runtime 10.1, when you navigate to the Connections screen from the About screen, the left navigation pane of the Connections screen still shows the information related to About screen.
This issue is now resolved.

Release 10.0

- WFF-259
An exception causes file polling ports to automatically disable.
When processing large number of files, the file polling port is automatically disabled and the following exception is displayed in Integration Server Administrator.
"java.lang.IllegalArgumentException: Comparison method violates its general contract!"
The disabled port can only be enabled by reloading the package.
This issue occurs because of the change in the sorting algorithm in JDK 1.7.
This issue is resolved.
- WFF-261
In webMethods Integration Server, the pub.flatFile:convertToString service eliminates the values or fields that contain only white spaces which results in incorrect outputs.
This issue is resolved.

Release 9.12

- PIE-39870 (IS_9.0_SP1_Core_Fix14, IS_9.5_SP1_Core_Fix11, IS_9.9_Core_Fix2, IS_9.10_Core_Fix1)
Service fails to run automatically after the cache expires when the Prefetch parameter is set to True.
When the Prefetch parameter is set to True and the cache expires, the service fails to run automatically. The following exception is displayed in the server logs. "[ISS.0086.9249] Missing Parameter:num1".
This issue is resolved.

- PIE-39177 (IS_9.0_SP1_Core_Fix14, IS_9.9_Core_Fix2)
 Integration Server logs contain duplicate entries after a port is enabled and disabled.
 When a port is enabled and disabled, Integration Server creates two entries for each action in the server logs. This issue occurs if the logging level is set to Debug. Integration Server logs the same information in the Debug log and the Info log which causes duplicates.
 This issue is resolved. Now, if the logging level is set to Debug Integration Server logs information related to enabling and disabling of ports in the Info log.
- PIE-36924 (IS_9.5_SP1_Core_Fix11)
 An additional prefix is included in an XML document input when restored from the pipeline.
 Integration Server includes an additional prefix dx: at the root of an XML document instance.
 This issue occurs when the XML document is updated as specified in the following sequence of steps:
 (1) The XML document is provided as input to an operation in a provider web service descriptor.
 (2) The document is saved to a pipeline.
 (3) The pipeline is restored.
 The issue is now resolved.
- PIE-39114 (IS_9.7_Core_Fix8, IS_9.9_Core_Fix2)
 Discrepancy in session count on Server > Statistics page and Server > Statistics > Session page.
 In Integration Server Administrator, the current total sessions displayed on the Server > Statistics page does not match the number of rows for Current Sessions displayed on the Server > Statistics > Sessions page.
 This issue is now resolved.
- PIEAR-746 (IS_9.7_Core_Fix8)
 The threads waiting for the connection and the threads releasing the connection from the connectionPool are blocked in the ConnectionPool.
 When the connection creation thread acquires a lock on the ConnectionPool, the thread goes to the wait state and the state of this thread does not change. This prevents the connection from being released.
 To resolve this issue, Integration Sever now includes the following server configuration parameter:
 watt.server.jca.connectionPool.createConnection.interrupt.waitTime Specifies the wait time, measured in milliseconds, that elapses before Integration Server interrupts a connection creation thread that is in a wait state. There is no default value. You must restart Integration Sever for changes to this parameter to take effect.
- PIE-39355 (IS_9.7_Core_Fix8)
 Integration Server does not indicate when it is disconnected from a cluster.
 Integration Server does not log an error message when it is disconnected from a cluster, preventing automatic detection of the situation.
 Now, Integration Server logs the following error message when it is disconnected from the cluster.
 [ISS.0033.151] The cluster is now not operational.
 Additionally, Integration Server logs the following error message when it rejoins the cluster.
 [ISS.0033.152] The cluster is now operational.

- PIE-34518 (IS_9.8_Core_Fix5)
 Addition of CDATA block support to outbound SOAP processing.
 When processing an outbound SOAP message, Integration Server ignores CDATA delimiters in String fields.
 If a String field contained text in a CDATA block, Integration Server treats the text as regular text instead of character text and url-encodes special characters in the delimiters and in the text block. Integration Server now provides CDATA block support for processing of outbound SOAP messages only when Integration Server hosts the web service provider. When a service used as an operation in a web service provider returns String values containing CDATA blocks, when encoding the IData into a SOAP message, Integration Server places the CDATA text in the outbound SOAP message in a CDATA section and does not url-encode special characters in the delimiters or text block.
 Keep the following information in mind:
 - A CDATA block begins with <![CDATA[and ends with]]> - Multiple CDATA blocks may be used in a single String value.
 - CDATA blocks may not overlap or be nested.
 Note: When Integration Server is acting as the web service client, Integration Server does not provide CDATA block support when processing outbound SOAP messages. If a String value containing the request is passed to the web service connector and the string contains CDATA, the contents of CDATA block will be treated as regular text and special characters in the delimiters and text block will be url-encoded in the outbound SOAP request.
- PIE-35132 (IS_9.8_Core_Fix5)
 Changes to Integration Server to address the security vulnerabilities identified during internal security testing.
 This fix resolves the security issues found during internal security testing.
- PIE-38427 (IS_9.8_Core_Fix5)
 A NullPointerException occurs when modifying or saving a flow service if dependency checking features are disabled.
 A NullPointerException occurs in Software AG Designer when modifying or saving a flow service if the server configuration parameter watt.server.ns.dependencyManager is set to false.
 This issue is resolved.

PIE-38649 (IS_9.8_Core_Fix5)
 Host name of an email port is displayed incorrectly in the View Email Client Details page in Integration Server Administrator.
 The host name of an email port is incorrect and contains garbled characters when the email port is viewed in the Security > Ports > View Email Client Details page in Integration Server Administrator.
 This issue is resolved. The host name is now displayed correctly in the Ports > View Email Client Details page in Integration Server Administrator.
- PIE-38920 (IS_9.8_Core_Fix5)
 Certification of Integration Server with MySQL version 5.6.
 Integration Server 9.8 is now certified for use with MySQL version 5.6

PIE-39009 (IS_9.9_Core_Fix2)

Messages are rolled back to Universal Messaging incorrectly if the webMethods messaging trigger is configured to Suspend and Retry Later.

If a webMethods messaging trigger specifies Suspend and Retry Later for On Retry Failure, Integration Server rolls back a message to Universal Messaging if a transient error causes the trigger to fail. However, instead of rolling back a single message, Integration Server rolls back all of the received but unacknowledged messages for the trigger. For concurrent triggers, this can cause messages to be reprocessed. For serial triggers, this can cause messages to be lost.

Now, when a webMethods messaging trigger specifies Suspend and Retry Later and a transient error prevents the trigger from executing successfully, Integration Server rolls back a single message at a time to Universal Messaging. Additionally, Integration Server clears the trigger queue on the Integration Server immediately after suspending the trigger. Clearing the queue removes any messages that the trigger received but did not process. These messages will be redelivered.

- PIE-39287 (IS_9.9_Core_Fix2)

Integration Server displays the predefined Client Prefix instead of the user-defined Client Prefix after a restart.

After restarting Integration Server, the user-defined Client Prefix for a new Broker Connection Alias is replaced with the predefined Client Prefix that Integration Server creates.

This issue is resolved. Now, Integration Server displays the user-defined Client Prefix correctly after a restart.

- PIE-39295 (IS_9.9_Core_Fix2)

An attempt to create a web service descriptor from a WSDL document fails with a NullPointerException if the WSDL document contains multiple services but the services are not associated with all of the binding and portType definitions in the WSDL document.

Creating a consumer web service descriptor or a WSDL first provider web service descriptor from a WSDL document fails with a NullPointerException if the WSDL document defines multiple services and every service is not associated with every binding and portType defined in the WSDL document.

This issue is resolved. Each web service descriptor generated from a service in a WSDL document exposes only the binding and portTypes associated with the service.

- PIE-40157 (IS_9.10_Core_Fix1)

Correction to a spelling error in Queue Provider field.

On the Settings > Logging > Edit <loggerName> Details page, Integration Server Administrator lists Universal Messaging instead of Universal Messaging as one of the Queue Provider values.

The spelling error is now corrected.

- PIE-37272

Deadlock among threads in XA recovery store prevents XA transactions from completing.

The XA recovery store contains information about each XA transaction, including the transaction ID (XID), the global state of the transaction at each point in the transaction, and the state of each resources participating in the transaction. During an XA transaction, a deadlock between threads accessing the XA recovery store occurred because an exception occurred after a thread acquired a lock. The exception prevented the release of the lock.

This issue is now resolved. In addition to resolving the issue described above, Integration Server

now includes server configuration parameters to control recovery logging.

`watt.server.transaction.xastore.performXALogging`

Specifies whether or not Integration Server writes transaction information to the XA recovery store. Set to true to instruct Integration Server to log information about the state and progress of each XA transaction. Set to false to instruct Integration Server to skip logging XA transaction information.

The default is true.

Important! If you set `watt.server.transaction.xastore.performXALogging` to false, Integration Server does not log any information to the XA recovery story while processing a transaction, making transaction recovery impossible. If you want Integration Server to automatically resolve incomplete transactions or you want to manually resolve incomplete transactions, Integration Server must perform XA logging.

You must restart Integration Server for changes to this parameter to take effect.

`watt.server.transaction.xastore.maxTxnPerFile`

Specifies the maximum number of unique XA transactions in an XA recovery log file. When the XA recovery log file reaches the maximum number of transactions, Integration Server creates a new file. The default is 2000 transactions.

Consider increasing the maximum number of unique XA transactions for the XA recovery log file if there are more than 2000 active XA transactions and Integration Server exhibits a performance delay due to input/output. Increasing the number of unique XA transactions allowed per file decreases the number of files used for the XA recovery log, which, in turn, may result in fewer files for Integration Server to search when performing XA recovery.

Decreasing the number of unique XA transactions stored in file may help during transaction recovery as it might decrease the time to read and consolidate open transactions.

- **PIE-37566**
Executing anonymous services creates persistent sessions.
Some anonymous services in the WmRoot package create persistent sessions. Repeated execution of these services can consume all of Integration Server's licensed sessions.
This has been fixed. Anonymous services in WmRoot are now stateless which means that Integration Server creates sessions to execute these services and discards the sessions immediately
- **PIE-38112**
Integration Server does not restart after improper shut down.
If Integration Server does not shut down properly, which can be caused by a JVM crash or a machine crash, configuration files such as `acls*.cnf` become corrupted or are reduced to a size of zero. In turn, this causes a restart of Integration Server to fail. To recover, data must be restored manually from a backup directory. This issue results from how Integration Server persists data into the file system. Prior to this fix, Integration Server tried to overwrite the existing file in the file system. If Integration Server shut down improperly right after the file was recreated but before the new content was written to the file system, the file content became corrupted or the file was reduced to a size of zero.
With this fix, Integration Server changes how it saves changes to configuration files. When saving changes to configuration files, Integration Server first saves the configuration changes in a temporary file in the `IntegrationServer_directory/instances/instanceName/config/work` directory. After saving the changes in a temporary file, Integration Server moves the temporary file to the actual configuration file. This ensures that if unexpected behavior occurs before the configuration

changes are initially saved to the temporary file, only the temporary file is impacted. The actual configuration file is not corrupted. At start up, if Integration Server detects files in in the `IntegrationServer_directory/instances/instanceName/config/work`, it suggests that changes to a configuration file were not saved to the temporary file and that, therefore, the changes were not made to the actual configuration file. Use the contents of the `IntegrationServer_directory/instances/instanceName/config/work` directory to determine which configuration files were in the process of being changed. Decide whether or not you want to redo the changes to the configuration files. Delete the files under the directory and redo the configuration change if you so choose.

- **PIE-38470**
The `xsd:any` element and attributes are not generated for a web service descriptor when the `Allow Unspecified Fields` property is true.
The WSDL document for a web service descriptor does not include the `xsd:any` element and attributes when the web service descriptor uses a `Document` variable for which the `Allow unspecified fields` property is set to true. This issue occurs even when the server configuration parameter `watt.core.schema.createSchema.omitXSDAny` is set to false.
To address this issue, the web service descriptor now includes a property, `Omit xsd:any` from WSDL. When set to false, the WSDL document generated by Integration Server includes an `xsd:any` element. When set to true, the WSDL document does not include the `xsd:any` element. The default value is true. For changes to this property to take effect, after saving the change to the property, either refresh the web service descriptor or reload the package that contains the web service descriptor.
- **PIE-38658**
When a client sends multiple HTTP PUT requests to Integration Server, every second request fails with a 400 Bad Request response.
Now, alternating HTTP PUT requests from the same client will not fail. Integration Server handles multiple HTTP PUT request from the same client correctly.
- **PIE-38686**
GET request mandatorily adds a default value to the `Content-Type` header.
If `Content-Type` header is not specified in a GET request, the `pub.client.http` service adds a default `Content-Type:"application/x-www-form-urlencoded"`. According to HTTP 1.1, it is not mandatory to specify the `Content-Type` header. If the `Content-Type` header is not specified, the `pub.client.http` service should not add a default `Content-Type`.
Now, if no `Content-Type` header is specified, `pub.client.http` service does not add a default `Content-Type` to the request. However, if you pass the data using 'args' or 'table' keys, default `Content-Type:"application/x-www-form-urlencoded"` is added.
- **PIE-38751**
In Integration Server, sometimes publishing a guaranteed document to Universal Messaging server fails due to transaction failure.
This issue occurs when the Universal Messaging server does not respond to the transaction within the specified `EvenTimeout`.
This issue is resolved. A new server configuration property,

watt.server.um.producer.transaction.commitRetryCount is introduced in the server configuration file. This property specifies the number of retry attempts Integration Server makes to publish the message to the Universal Messaging server. The maximum number of retries is 9. If you try to assign a value greater than 9, Integration Server automatically sets the value of the property to 9. The default is 0. When setting a retry value, you must ensure that the total transaction time does not exceed the MaxTransactionTime. The total transaction time is calculated by multiplying the total number of attempts with the EvenTimeout. For example, if the retry value is set to 9, and the EvenTimeout is set to 60s, the total transaction time is $60,000(9+1) = 600s$.

- PIE-38932
Integration Server loads a package more than once during deployment.
During deployment of multiple packages at the same time, Integration Server reloads the packages more than once.
Now, when a deployment operation includes multiple packages, Integration Server loads each package only once.
- PIE-39017
In a clustered environment, Integration Server sometimes does not create child tasks when a new server is added to the cluster or when an existing server is restarted.
When a task is scheduled to run on all servers in a clustered environment, Integration Server creates a parent task and a child task for each server in the cluster. When a new server is added to the cluster or when an existing server in the cluster is restarted, Integration Server creates a corresponding child task upon server restart. However, Integration Server sometimes does not create the child task for the newly added server or for the server that was restarted. As a result, the complete information for all servers in the cluster is not available on the Scheduler screen.
This issue is resolved.
- PIE-39164
SSL handshake fails as no client certificate is sent when a new connection is opened through proxy.
When Integration Server tries to open a connection to web server that requires client certificate through proxy, the SSL handshake using JSSE fails as no client certificate is sent. This happens only when the keyStoreAlias and keyAlias parameters are set using pub.security.keystore:setKeyAndChain service and not when they are set using the Integration Server Administrator (Security > Certificates). This issue occurred because the client certificate attachment was missing in the request.
This issue is now resolved. Now, client certificate is sent to web server when a connection is opened through proxy.
- PIE-39178
Repository-based deployment fails when deploying locally publishable documents on the target Integration Server.
When deploying locally publishable documents on the target Integration Server using a repository-based deployment, Integration Server cannot find a messaging connection alias for the locally publishable document. This causes the deployment to fail. When the publishable document type is set to locally only, there is no messaging connection alias attached to it.
This issue is resolved. Now, Integration Server does not check for a messaging connection alias

during deployment when the publishable document type in Integration Server is set to locally only.

- PIE-39210

Integration Server experiences memory leak due to orphaned entries of type `com.wm.app.b2b.server.ostore.FileCache$InvokeCounter` located in `com.wm.app.b2b.server.ostore.FileCache`.

This issue is now resolved.

- PIE-39268

Enhancement to Integration Server to use a file for specifying allowed cipher suites.

The following server configuration properties identify the list of cipher suites for use with inbound and outbound SSL connections.

`watt.net.ssl.client.cipherSuiteList`

`watt.net.ssl.server.cipherSuiteList`

`watt.net.jsse.client.enabledCipherSuiteList`

`watt.net.jsse.server.enabledCipherSuiteList`

Prior to this enhancement, the properties accepted a comma-separated list of cipher suites.

However, specifying a long list of cipher suites can be cumbersome. To make it easier to specify a long list of cipher suites, Integration Server now allows specifying a file as the value for the cipher suite server configuration properties. In the file, specify each cipher suite on a different line. For

each cipher suite server configuration property for which you want to specify a file instead of a list of cipher suites, specify the following as the value of the property: `file:directoryName\filename` For example: `watt.net.jsse.server.enabledCipherSuiteList=file:c:\ssl\ciphers.txt`.

Note: You can set the value of a cipher suite server configuration property to a comma-separated list, default, or the absolute path to a file. You cannot specify a combination of these. Integration Server loads the file and its list of supported cipher suites at start up. Changes to the contents of the file that are made after Integration Server starts will not take effect until the next time Integration Server starts. Integration Server throws the following exception if it cannot find the specified file: `ISS.0070.9048E Integration Server cannot find the file {0} specified for the server configuration parameter {1}`.

Cause The specified server configuration parameter uses a file to identify the allowed cipher suites; however, Integration Server cannot find the file.

Action Make sure the server configuration parameter specifies the correct location of an existing file.

- PIE-39278

Message not found for messageKey 68.29 and 68.30.

If an email port has "Log out after each mail check=Yes", Integration Server fails to retrieve the error messages for messageKey 68.28 and messageKey 68.30.

Following messages appear in the server log:

For IMAP: `ISP.0068.0029I] Message not found for messageKey 68.29. For POP3: ISP.0068.0029I] Message not found for messageKey 68.30.`

This issue is now resolved. Now, correct messages are displayed for messageKey 68.28 and messageKey 68.30.

- PIE-39298

Error in getting SFTP server host key, if a key exchange algorithm is not supported by SFTP server. Jsch has a default key exchange algorithm order.

During the handshake, jsch checks the client key exchange algorithms one by one with SFTP server key-exchange algorithms. The first matching algorithm is used as the key-exchange algorithm between SFTP client and SFTP server. However, Jsch does not support 2048-bit keys for diffie-hellman-group-exchange-sha256 and diffie-hellman-group-exchange-sha1 key exchange algorithms in Java 1.7 and earlier versions. Consequently, if the Integration Server runs with Java 1.7 or earlier version and SFTP server expects 2048-bit keys for these algorithms, then the handshake between SFTP server and SFTP client fails.

To avoid this issue, the order of these key exchange can be changed using the `watt.ssh.jsch.kex` parameter so that, any other matching key exchange algorithm can be selected as the key exchange algorithm between the SFTP client and SFTP server.

To address this issue, Integration Server now include a server configuration parameter to change the order of the key exchange algorithm.

`watt.ssh.jsch.kex` Specifies the order of the key exchange algorithm for Jsch. The specified order overrides the default key exchange algorithms order supported by Jsch.

For example: `watt.ssh.jsch.kex=diffie-hellman-group-exchange-sha1, diffie-hellman-group1-sha1, diffie-hellman-group14-sha1` If the SFTP server expects 2048-bit keys for diffie-hellman-group-exchange-sha1, then the order of this algorithm can be changed so that, any other matching algorithm can be selected as key exchange algorithm between the SFTP client and SFTP server.

`watt.ssh.jsch.kex=diffie-hellman-group1-sha1, diffie-hellman-group14-sha1, diffie-hellman-group-exchange-sha1` Integration Server must be restarted for changes to this parameter to take effect.

- **PIE-39357**
Integration Server fails to retrieve the SFTP Get Host Key during the SFTP Server Alias creation. SFTP Server Alias creation fails with 'Auth Cancel' exception, as Integration Server fails to retrieve the SFTP Get Host Key.
The issue is now resolved.
- **PIE-39380**
Integration Server issues an Access Denied error message during the logon process and logs an authentication exception in the server log.
Integration Server issues the following error message during the logon process and logs the exception in the server log:
Access to Integration Server is denied because of the following authentication exception:
LoginModule "com.wm.app.b2b.server.auth.jaas.X509LoginModule" unavailable.
The issue is now resolved.
- **PIE-39574**
Web service connector does not capture all the Set-Cookie HTTP response headers sent back by the web service provider.
When a web service connector sends a request to a web service provider that sends back multiple Set-Cookie response headers, the connector captures only one Set-Cookie response header.
This issue is resolved. Now, if the web service provider sends back multiple Set-Cookie HTTP response headers, the connector returns all of the headers in its output.

- PIE-39585

Missing fields in an IS document type generated from an XML Schema Definition (XSD) that has complex type definitions referring to group elements defined later in the schema.

When an Integration Server document type is generated from an XSD where the complex type definitions contain references to group elements defined later in the schema, the generated document type does not contain the fields corresponding to such references.

This issue is now resolved.
- PIE-39701

Integration Server migration utility reports an exception during migration of Trading Networks package.

During migration of Integration Server, if the source Integration Server contains a Trading Networks package, the migration utility throws an exception if JDBC pool information was not selected during migration of configuration files and JDBC pool information was specified during installation of Trading Networks.

Trading Networks data and configuration file Migrator : Unable to locate the database configuration information. File

<IntegrationServer_installDirectory>\bin\migrate\..\..\instances\default\config\jdbc\pool\<poolName>.xml does not exist. Where poolName refers to the pool name specified for the Trading Networks functional alias.

This issue is now resolved. Integration Server migration utility correctly migrates Trading Networks data.
- PIE-39735

Synchronization of publishable documents with the messaging provider fails when using a startup service to run pub.publish:syncToProvider.

When the pub.publish:syncToProvider service runs as part of a startup service, Integration Server reloads the webMethods messaging triggers but fails to update the state of the triggers.

This issue is resolved.
- PIE-39762

REST API descriptor treats parameter of type byte[] as byte.

When creating a REST API descriptor, if a selected REST resource contains a service with byte[] in the service signature, the REST API descriptor treats the parameter as a byte instead of byte[].

This issue is now resolved.
- PIE-39819

An error occurs when you create or edit a file polling port if the path to the monitoring directory contains a backslash '\ '.

When you create or edit a file polling port and the path to the monitoring directory contains a backslash '\ ', the following error message is displayed. "No listener defined with the specified key: FilePollingListener: c: mp" This issue occurs because the Integration Server Administrator uses the wrong encodingType.

This issue is resolved.
- PIE-39825

A synchronous or asynchronous publish and wait does not receive a reply.

If a publishable document type is empty, that is, it does not contain any fields besides the `_env` field, and values are mapped to fields the `_env` field before publishing the document using `pub.publish:publishAndWait`, Integration Server does not receive a reply to the published request.

This occurs for synchronous and asynchronous publish and wait requests.

This issue is now resolved.

- PIE-39839

Universal Messaging does not reuse the session on Integration Server even though `watt.server.trigger.reuseSession` is set to true.

When the server configuration property, `watt.server.trigger.reuseSession` is set to true and Broker is the messaging provider, Broker reuses the session on Integration Server. Whereas, Universal Messaging as the messaging provider does not reuse the session.

This issue is resolved.

- PIE-39847

JDBC connection pools are blocked after the database restarts.

After the database used by a JDBC pool restarts, Integration Server does not release connections from the pool because of an unexpected exception thrown by the JDBC driver.

Now, Integration Server exception handling prevents the exception thrown by the JDBC driver from blocking the release of connections from the JDBC pool.

- PIE-39848

After migrating to Integration Server 9.5 or later, Integration Server displays an exception when calling a web service and using MTOM streaming.

After migrating 2 to Integration Server 9.5 or later, sending a web service request that uses MTOM streaming for which more than one chunk is sent, the following exception occurs: "Exception --> org.apache.axis2.AxisFault: Connection reset by peer: socket write error"

This issue is now resolved.

- PIE-39853

Unable to view assigned input values for services in Integration Server Administrator when the server configuration property `watt.server.disableXSSFilter=true`.

When creating a scheduled task, assigning input values using the "Assign Inputs" button displays an empty input field even though the assigned value is saved in the input field. Since the XSS filter is disabled by setting the server configuration property `watt.server.disableXSSFilter=true`,

Integration Server is unable to encrypt quotation marks (") in the input values. Therefore, the assigned input values are not displayed in the input field in Integration Server Administrator.

This issue is resolved. Integration Server is now able to encrypt quotation marks (") in input values when the server configuration property `watt.server.disableXSSFilter=true`.

- PIE-39876

Swagger document generated by Integration Server does not represent REST resources with required list parameters correctly.

If a REST API descriptor contains REST resources that refer to a list parameter, such as String list, Document list, Document Reference list, and Object list, and the list parameter is required, the definitions section of the generated Swagger document does not indicate that the parameter is

required.

This issue is now resolved.

- PIE-39877
If a REST API descriptor contains a REST resource that refers to a parameter of type String table, the generated Swagger document does not indicate the type of the parameter as "array".
This issue is now resolved.
- PIE-39938
Reliable messaging sequences on Integration Server are timed out when the inactivity timeout interval is set to a value of -1.
This issue is now resolved. The reliable messaging sequences do not get timed out when the inactivity timeout interval is set to -1 in the Integration Server Administrator (Settings > Web Services > Reliable Messaging > Edit Configuration).
- PIE-39967
Service error statistics counter causes memory leak.
An internal mechanism used to report the last 60 seconds worth of service failures has a memory leak. The memory leak occurs when a steady stream of exceptions, at least one every 60 seconds, are thrown without interruption.
To resolve the memory leak, Integration Server clears the service error statistics counter when new entries are added.
- PIE-40014
Selected Authentication Type does not get populated under HTTP Transport Properties in consumer web service descriptor endpoint alias.
When creating a consumer web service descriptor endpoint alias, the selected Authentication Type is not populated under HTTP Transport Properties.
The issue is now resolved.
- PIE-40027
Integration Server logs the wrong message when it cannot find the encoder "esapi".
When Integration Server cannot find the encoder "esapi", it logs the following wrong error message: [ISC.0072.0023E] Couldnt initialize encoder "{0}".
Whereas, Integration Server should log the following message: [ISC.0072.0023E] Failed to initialize the bundle for encoder 'esapi'.
This issue is resolved now.
- PIE-40048
In the Service Usage screen, some of the values are displayed as instead of the actual value. In the Service Usage screen of Integration Server Administrator, some of the values in the Count and Last Run columns are displayed as instead of the actual value. This issue occurs because of encoding issues in Integration Server.
This issue is resolved. Now, the values in the Count and Last Run columns are displayed correctly.
- PIE-40109
The pub.xml:getNextXMLNode service incorrectly returns a NullPointerException when the

NodeIterator does not have XML nodes to return.

This issue is resolved. The `pub.xml:getNextXMLNode` service returns null when there are no XML nodes to return.

- **PIE-40126**
Results window does not show parameter names when using Natural CALC subprogram.
From the Natural CALC subprogram, the IDL and IS connection are created. When using Integration Server and Adapter 9.9, and running the example CALC flow service in Software Designer from the Service Development perspective, the results window does not show the parameter names. The field name abbreviator (as used for `XmlData`) truncates field names that start or end with #.
With this fix, the Field name abbreviator no longer truncates field names that start or end with #.
- **PIE-40139**
Integration Server becomes unresponsive due to an `OutOfMemoryError` caused by lack of PermGen space. A memory leak in the package classloader may result in a `java.lang.OutOfMemoryError: PermGen space`, which causes Integration Server to become unresponsive.
The memory leak in the package classloader is now repaired.
- **PIE-40141**
The `pub.event.routing*` services are not working properly in Integration Server .
The `pub.event.routing*` services of `send`, `subscribe`, and `unsubscribe` are not working properly. For example, the `send` service throws the following `ServiceException`: `Could not run 'send'`
`com.wm.app.b2b.server.ServiceException: com.wm.app.b2b.server.ServiceException: Event Routing service not available.`
This issue is resolved now.
- **PIE-40183**
Different error messages for primary and regular HTTP ports.
When Integration Server receives a client request for a web service that does not exist, it returns different error messages depending on whether the request was received through the primary port or an HTTP port.
Now, Integration Server returns the same error message regardless of the port through which it receives the request.
- **PIE-40189**
Missing schema definition for the envelope (`_env`) field in the WSDL document when a service containing reference to a publishable document type is exposed as a web service.
When a service containing reference to a publishable document type is exposed as a web service, the resulting WSDL document does not contain the schema definition for the envelope (`_env`) field.
This issue is now resolved.
- **PIE-40194**
A `webMethods` messaging trigger that receives messages from a Universal Messaging cluster becomes disconnected and does not reconnect.
When a Universal Messaging connection alias that specifies a cluster of Universal Messaging

servers and the network between the Universal Messaging servers fails, one or more webMethods messaging triggers that use the alias might disconnect and then not reconnect. This might happen even if the trigger can successfully connect to one of the Universal Messaging servers but not the other servers in the cluster.

Now, if a webMethods messaging trigger becomes disconnected from a cluster of Universal Messaging servers, the trigger reconnects only when the cluster has a quorum. In addition to resolving the issue described above, Integration Server now redirects the Universal Messaging client log entries from the default stdout to the Integration Server's log directory, `Integration Server_directory/instances/instanceName/logs/umClient.log`. The `umClient.log` file can be used when debugging Universal Messaging issues.

- **PIE-40195**
Integration Server does not validate a Kerberos ticket sent by an Internet browser.
If Integration Server receives a request on a port configured to accept Kerberos tickets, Integration Server returns a 401 status code with a "Negotiate" header challenge to the Internet browser. Upon receiving the Negotiate header challenge, a properly configured Internet browser generates a Kerberos ticket and sends the request, along with the Kerberos ticket, to Integration Server. Integration Server should validate the Kerberos ticket and either allow or deny the client request based on the ACL settings. However, Integration Server could not process the Kerberos ticket because a Kerberos ticket sent by an Internet browser is structurally different from tickets generated by a Java client. Because Integration Server could not process the ticket, Integration Server could not validate the Kerberos ticket. Instead, Integration Server returned a 401 status code and prompted the client for username and password credentials.
Integration Server can now process a Kerberos ticket generated by an Internet browser.
- **PIE-40202**
JDBC connection pool for ISInternal functional alias is blocked.
Integration Server does not release connections from the JDBC connection pool used by the ISInternal functional alias because of an unexpected exception thrown by the JDBC driver. Now, Integration Server exception handling prevents the exception thrown by the JDBC driver from blocking the release of connections from the JDBC connection pool.
- **PIE-40212**
Enhancement for using a public cache, including a distributed cache, for service results caching. Previously, Integration Server stored cached service results in the ServiceResults system cache which is part of the SoftwareAG.IS.Services system cache manager.
With this enhancement, a local or distributed public cache can now be used for service results caching. By using a distributed cache as the service results cache, multiple Integration Servers can access cached service results.
Keep the following information in mind when using a public cache for service results caching:
 - The cache must be configured such that elements do not expire once they are placed in the cache. That is, the Eternal check box must be selected for the cache. The duration of cached service results depends on the Cache expire property value for the service and the `watt.sever.cache.flushMins` server configuration parameter value.
 - When using a distributed cache as a service results cache, make sure that all the Integration Servers that share the service results cache have the same packages.

-When returning cached results for a service, by default, Integration server returns a reference to the cached results instead of the actual value of the cached results. If you want Integration Server to return the actual value instead of a reference, make sure that the Copy on Read and Copy on Write check boxes are selected for the public cache.

-If you want to be able to use Integration Server Administrator or the `pub.cache.serviceResults:listCache` service to view the cached elements for a service, make sure that the service results cache is searchable and that the cache allows automatic indexing for keys. That is, for the service results cache, the Searchable check box must be selected and the Key check box next to Allow Automatic Indexing must be selected.

-When a public cache used for service results caching is disabled or a public cache manager that contains the cache used for service results caching is shut down, Integration Server does not cache or retrieve service results. Instead of using cached results, Integration Server executes the service.

-When a public cache used for service results caching is enabled or the public cache manager that contains the public cache used for service results is started, Integration Server re-initializes the cache.

For detailed information about creating a public cache, public cache manager, and a distributed cache, see the webMethods Integration Server Administrator's Guide.

Note: In Integration Server Administrator, the Server > Service Usage page displays statistics about service results. For a distributed cache, this statistics corresponds to the current Integration Server instance only. Integration Server Administrator does not provide aggregated statistics for all the Integration Servers using the same distributed cache for service results caching.

To configure Integration Server to use a public cache for service results caching, you specify the name of the cache and cache manager in the server configuration parameters `watt.server.serviceResults.cache` and `watt.server.serviceResults.cacheManger`, respectively.

`watt.server.serviceResults.cache`

Specifies the name of the public cache to use for service results caching. If no value is specified for the `watt.server.serviceResults.cache` parameter, Integration Server uses the `ServiceResults` cache in the cache manger specified in the `watt.server.serviceResults.cacheManager` parameter as the service results cache. If the cache manager in the `watt.server.serviceResults.cacheManager` parameter does not contain a cache named `ServiceResults`, Integration Server throws an error at start up and does not cache service results. You must restart Integration Server for changes to this parameter to take effect.

`watt.server.serviceResults.cacheManager`

Specifies the name of the public cache manager that contains the public cache to use for service results caching. If no value is specified for this parameter, Integration Server uses the `SoftwareAG.IS.Services` system cache manager as the service results cache manager. If the `SoftwareAG.IS.Services` system cache does not contain a cache with a name that matches the value of the `watt.server.serviceResults.cache`, Integration Server throws an error at startup and does not cache service results. You must restart Integration Server for changes to this parameter to take effect.

Note: To use the `ServiceResults` system cache located in the `SoftwareAG.IS.Services` system cache manager as the service results cache, do not specify a value for `watt.server.serviceResults.cache` or `watt.server.serviceResults.cacheManager`.

- PIE-40246

The `pub.client:soapClient` service does not use the private key and certificate chain set using the `pub.security.keystore:setKeyAndChain`.
This issue is now resolved.

- **PIE-40259**
Using the delete icon to delete an OpenID Provider on the Security > OpenID page does not delete the OpenID Provider.
In the Security > OpenID page of Integration Server Administrator, clicking the delete icon in the Delete Provider column invokes an unknown service, resulting in the display of the following message:
[ISC.0072.9001] Unknown service: `wm.server.security.openid:deleteProvider`
Furthermore, the OpenID Provider is not deleted.
Now, clicking the delete icon in the Delete Provider column on the Security > OpenID page results in Integration Server deleting the OpenID Provider.
- **PIE-40261**
Use JSSE option is missing on external port if the internal port is set to HTTP.
On Integration Server Administrator, when you view a port for which the Enterprise Gateway External Port is set to HTTPS and Enterprise Gateway Registration Port is set to HTTP, the "Use JSSE" option does not appear. The "Use JSSE" option appears only if the Enterprise Gateway Registration Port is set to HTTPS.
This issue is now resolved.
- **PIE-40275**
Enhancement to allow the default locale for `pub.date*` services to be the server locale instead of the client locale.
When executing a `pub.date*` service with a locale input parameter for which no locale is specified Integration Server uses the locale from the session used by the client that invoked the service.
Integration Server now includes a server configuration parameter that you can use to specify that the default locale for `pub.date*` services should be the server locale.
`watt.server.session.locale.ignore`
Specifies whether the default locale for the `pub.date*` services is the server locale or the locale from the session used by the client that invoked the service. When set to true, when executing a `pub.date*` service for which a locale input parameter value is not specified, Integration Server uses the server locale as the value of the locale parameter. When set to false, when executing a `pub.date*` service for which a locale input parameter value is not specified, Integration Server uses the locale from the session used by the client that invoked the service. The default is false.
You do not need to restart Integration Server for changes to this parameter to take effect.
- **PIE-40300**
Under heavy load, Integration Server might generate duplicate contextIDs for audit log messages resulting in an `AuditLogManagerException`.
Under heavy load, Integration Server might generate duplicate contextIDs for audit log messages, causing Integration Server to write the following `AuditLogManagerException` to the `server.log`:
[ISS.0095.9998] `AuditLogManager Exception:`
`com.webmethods.sc.auditing.api.logger.WmAuditLoggerException: Null or duplicate context`

given to logger 'Error Logger'

Now Integration Server generates unique contextIDs even under heavy load.

- **PIE-40324**
Integration Server throws an error when an incoming message contains a pre-populated contextID and audit contextID.
Integration Server write the following error to the server.log when an incoming message contains a pre-populated context ID and audit contextID.
[BAA.0000.0061] This context has already been used in the current context stack.
Integration Server now handles a message with a pre-populated contextIDs and audit contextID and no longer logs the above error.

- **PIE-40362**
Unable to publish a package to multiple subscribers.
When publishing a package to multiple subscribers, clicking the 'Send Release' button in Integration Server Administrator prompts you to select a subscriber even though subscribers are selected.
This issue is resolved.

- **PIE-40363**
UserInfo service does not receive error information.
If an OpenID Provider's UserInfo Endpoint returns an error, information about the error should be passed to the userInfoError input variable in the UserInfo service registered for the OpenID Provider. This is not happening.
This issue is now resolved.
Note: Previously, the userInfoError input variable was named error.

- **PIE-40372**
Reply messages are sometimes not received with asynchronous request-reply using webMethods messaging and Universal Messaging as the messaging provider.
In an asynchronous request-reply for webMethods messaging, the pub.publish:publishAndWait service is first invoked followed by the pub.publish:waitForReply. When the messaging provider is Universal Messaging, some reply messages are not received if Integration Server receives the reply message before invocation of the pub.publish:waitForReply service.
This issue is now resolved.

- **PIE-40408**
Enhancements for managing a service results cache. Integration Server now includes built-in services that you can use to manage a service results cache, including:
pub.cache.serviceResults:resetServerCache resets the entire cache.
pub.cache.serviceResults:resetServiceCache resets the cache for a particular service.
pub.cache.serviceResults:listServiceCache lists the cached results for a particular service.
In addition to the above services, Integration Server Administrator now includes a way to view the cached service results for a particular service. To use Integration Server Administrator to view the cached service results, do the following:

1. Open Integration Server Administrator if it is not already open.
2. In the Packages menu of the Navigation Panel, click Management.
3. In the Packages list, click the package containing the service for which you want to view cached service results.
4. Click Browse Services in packageName.
5. In the Services list, click the name of the service for which you want to view the cached service results.
6. On the Packages > Management > packageName > Services > serviceName page, click List Service Cache. Integration Server displays a list of the cached results for the service. For each cached element, Integration Server displays the key for the cached element, the cached service inputs, and the associated cached service outputs.

Notes:

- You can also access the Packages > Management > packageName > Services > serviceName page in the following way: Under Server, click Service Usage. On the Server > Service Usage page, click the name of the service for which you want to list cached results.
- To return a list of cached result for a service, the services results must be searchable and that the cache allows automatic indexing for keys. That is, for the service results cache, the Searchable check box must be selected and the Key check box next to Allow Automatic Indexing must be selected. Note that exposing the contents of the service results cache may represent a security risk.
- You can view cached service results for a public service results cache only. You cannot view cached service results in the ServiceResults system cache.

Below is more information about each of the new built-in services.

pub.cache.serviceResults:listServiceCache WmPublic.

Returns a list of the cached service results for a particular service.

Input Parameters

serviceName String. Name of the service for which you want to view the cached service results.

Output Parameters elements Document List. Conditional. A document list (IData) containing the cached service results for the specified service. The pub.cache.serviceResults:listServiceCache service returns the elements output only if the service results cache contains cached results for the specified service. For each set of cached service results, the

pub.cache.serviceResults:listServiceCache returns the following information:

key String. Optional. Key for the cached element containing the service results.

input. Document. Optional. An IData containing the key/value pairs for the cached service input.

output Document. Optional. An IData containing the key/value pairs for the cached service output

Usage Notes:

- If serviceName specifies a service that does not exist or a service for which Integration Server does not cache service results, Integration Server returns an empty elements output parameter.
- You can use the pub.cache.serviceResults:listServiceCache with a public service results cache only. You cannot use the pub.cache.serviceResults:listServiceCache with the ServiceResults system cache.
- For the pub.cache.serviceResults:listServiceCache service to return results, make sure that the service results cache is searchable and that the cache allows automatic indexing for keys. That is, for the service results cache, the Searchable check box must be selected and the Key check box next to Allow Automatic Indexing must be selected.
- Exposing the contents of the service results cache via the listCacheService may represent a security risk.

pub.cache.serviceResults:resetServerCache

WmPublic. Resets the cache for all services in the service results cache, resulting in the removal of all cached service results for all services from the service results cache.

Input Parameters None.

Output Parameters message String. Message indicating whether or not Integration Server cleared the service results cache successfully.

- "Cache reset successfully" indicates that Integration Server cleared the entire service results cache successfully.

- "Error resetting cache!" indicates that Integration Server did not clear the entire service results cache successfully. Review the sever log and error log to determine why Integration Server did not clear the service results cache successfully.

pub.cache.serviceResults:resetServiceCache

WmPublic. Resets the cache for specific service, resulting in the removal of cached service results for the service.

Input Parameters serviceName String. Fully qualified name of the service in the format folder.subfolder:serviceName for which you want to remove cached service results.

Output Parameters message String. Message indicating whether or not Integration Server cleared the service results cache for the specified service successfully.

- "Cache reset successfully" indicates that Integration Server cleared the cached service results for the specified service successfully.

- "Error resetting cache!" indicates that Integration Server did not clear the cached service results for the specified service successfully. Review the sever log and error log to determine why Integration Server did not clear the service results cache successfully.

Note: To avoid revealing whether or not a service exists, if serviceName specifies a service that does not exist, the message output parameter returns the message "Cache reset successfully"

- PIE-40422

Integration Server grants access to a user account disabled by the external user manager.

Integration Server caches information for users who provide valid credentials. If the user later provides invalid credentials, Integration Server denies access but does not remove the cached information about the user. Consequently, if the user later provides valid credentials, Integration Server grants access even if an external user manager disabled the user account.

Now, when a user provides invalid credentials, Integration Server removes the user information from the cache.

- PIE-40454

The pub.storage:get service fails in a cluster.

Integration Server improves the performance of the pub.storage* services by caching the DATASTORE_ID values from the IS_DATASTORE table. However, in a cluster, a cached DATASTORE_ID value might become stale due to actions taken by other Integration Servers in the cluster. A pub.storage* service fails when it attempts to use a stale DATASTORE_ID.

Now, when a pub.storage* service attempts to use a stale DATASTORE_ID, Integration Server replaces it with the current DATASTORE_ID.

- PIE-40467

Corrections for cosmetic issues in Integration Server Administrator.

Integration Server Administrator displays some cosmetic issues, such as empty cells, deeply nested

tables, and missing graphics, that are now repaired.

- PIE-40480
When restarting Integration Server fix after applying a fix, expected changes are not made to the embedded database.
If the ISInternal functional alias uses the embedded, internal database and application of an Integration Server fix made changes made to the database structure, Integration Server should perform some database updates upon restart of Integration Server. However, this was not happening.
This issue is now resolved.
- PIE-40504
A NullPointerException occurs when Integration Server enters quiesce mode and the JMS subsystem has not been initialized.
This issue is resolved. Integration Server can now enter quiesce mode even if the JMS subsystem has not been initialized.
- PIE-40505
Memory leak when invoking pub.jms:reply Integration Server did not correctly release JMS Session and MessageProducer objects when invoking the pub.jms:reply service, resulting in a memory leak.
The issue is now resolved.
- PIE-40516
In a cluster of Integration Servers, the scheduled task for which the target node is set to "Any Node" and "Repeat After Completion" executes the same service simultaneously on different cluster nodes when the Terracotta Server Array becomes unavailable.
This issue is now resolved. Now, in a cluster of Integration Servers, a scheduled task with target node set to "Any Node" and "Repeat After Completion", executes the service only on one of the cluster nodes at a time when the Terracotta Server Array becomes unavailable.
- PIE-40517
Specifying a value of true for the watt.net.ssl.client.useJSSE server configuration property does not use JSSE for all of the outbound HTTPS connections from Integration Server.
After applying a fix or upgrading to a release that includes PIE-38599, Integration Server no longer honors the value of watt.net.ssl.client.useJSSE for outbound HTTPS connections. This occurs because PIE-38599 changed the default value of the useJSSE input parameter in the pub.client:http service to "no" from a null value. A value of "yes" or "no" for the useJSSE input parameter overrides the value of the watt.net.ssl.client.useJSSE server configuration property. A null value for the useJSSE input parameter causes the service to defer to the value of the watt.net.ssl.client.useJSSE server configuration property.
Now, the default value of the useJSSE input parameter for the pub.client:http service is null, which allows the watt.net.ssl.client.useJSSE server configuration property to determine the default behavior for outbound HTTPS connections.
- PIE-40548
Performance degradation observed in Integration Server.
Integration Server exhibits performance degradation in the GA versions 9.8, 9.9, and 9.10.
Integration Server versions 9.6 and 9.7 exhibit a similar performance degradation after applying the latest fix.

The cause of the apparent performance degradation is now resolved.

- PIE-40561
During the migration of Integration Server from 9.0 to a later release, the migration utility also migrates the server configuration parameters `watt.core.schema.validateIncomingXSDUsingXerces` and `watt.server.wsdl.validateWSDLSchemaUsingXerces`.
The migration utility need not migrate these server configuration parameters during the migration of Integration Server from 9.0 to a later release because the functionalities provided by the two parameters are replaced in releases starting with 9.0.
 - The 'Validate schemas using Xerces' option in the New Web Service Descriptor wizard replaces the functionality of the `watt.core.schema.validateIncomingXSDUsingXerces` parameter.
 - The value of the 'Validate schemas using Xerces' option is stored as the web service descriptor property 'validateSchemaUsingXerces' (which replaces the functionality of the `watt.server.wsdl.validateWSDLSchemaUsingXerces` parameter).The issue is resolved. The specified server configuration parameters are removed from Integration Server starting with release 9.0.
- PIE-40569
Integration Server logs a message about JDBC connection pool waiting threads threshold count being exceeding erroneously.
Integration Server should log the following message only when a thread is waiting for the JDBC connection pool to have an available connection.
[ISS.0096.0009I] JDBC Connection pool waiting threads threshold exceeded, <number> threads waiting for connection for pool <JDBCPoolName> Integration Server should not log the above message if the JDBC pool is empty or the JDBC driver threw an exception when Integration Server attempts to create a connection. In these cases, there is not actually a waiting thread.
This issue is now resolved.
- PIE-40576
SFTP transfers fail due to timestamp parsing failure.
A change in the Log Timestamp Format (Settings > Logging > View Server Logger Details > Log Timestamp Format) changes the timestamp format returned by `pub.client.sftp:ls` service. This causes the SFTP transfers to fail due to the timestamp parsing failure.
To address this issue, Integration Server now includes a server configuration parameter which specifies the timestamp format for SFTP client public services.
`watt.server.sftp.dateStampFmt`
Specifies the format of date to be used in the SFTP client public services.
To specify the date format to use, you can use any format that is supported by the Java class `java.text.SimpleDateFormat`. For example, to display the date with the format 08-12-02 14:44:33:1235, specify `dd-MM-yy HH:mm:ss:SSSS`. The default format for `watt.server.sftp.dateStampFmt` property is `yyyy-MM-dd HH:mm:ss z`.
It is not necessary to restart Integration Server after you change the value of this parameter.
- PIE-40578
Reloading the Packages > Management page in Integration Server Administrator results in a re-execution of the last command on the page.
The Packages > Management page in Integration Server Administrator encodes the last action as part of the URL. Web browsers remember the last action as part of the history, resulting in the re-

execution of the last action when reloading the frame.

To resolve this issue, for HTML5-compatible browsers, Integration Server alters the browser history so that the URL for the Packages > Management page does not include the last action as part of the URL. As a result, when reloading the frame, the last action will not be re-executed.

- PIE-40629

A concurrent webMethods messaging trigger may not utilize all available threads.

When a concurrent webMethods messaging trigger uses the maximum available threads for message processing, the next request for a thread must wait for a thread to be returned to the thread pool before another message can be processed. Integration Server returns a thread to the thread pool once message processing completes. When a thread becomes available, the waiting request should begin executing. However, instead of the request using a thread as soon as it becomes available, the request waits until the number of threads used by the trigger reaches 0 (zero). This results in periods of time when the trigger is not using all of the available threads. Note: A trigger uses the maximum available threads when the number of messages being processed by the trigger equals the Max execution threads property value. For example, if Max execution threads is set to 10, the trigger uses the maximum available threads when it is processing 10 messages.

Now, a concurrent webMethods messaging trigger will not wait for the number of the threads used by the trigger reaches zero before processing a waiting request. Instead, the trigger begins processing the waiting request as soon as a thread become available.

- PIE-40664

The JSSE-enabled HTTPS ports fail to use the updated certificate.

After adding a new certificate to the truststore and then reloading the truststore using the Integration Server Administrator (Security > Keystore), the JSSE-enabled ports do not use the added certificate.

This issue is now resolved. The JSSE-enabled HTTPS ports now use the updated certificate after the corresponding truststore is reloaded using Integration Server Administrator.

- PIE-40684

Integration Server Administrator sometimes displays two scrollbars right next to each other instead of a single scrollbar.

This issue is now resolved.

- PIE-40687

Display non-ASCII Unicode characters in the body of a Java service.

When you persist Java services, Integration Server encodes non-ASCII Unicode characters as ASCII Unicode escape sequences (for example, the Korean character '?' is saved as '\uD55C'). By default, Integration Server does not decode the escape sequences. Therefore, when Integration Server sends Java service code to Software AG Designer, escape sequences appear in Designer instead of the original Unicode characters.

This fix lets you configure Integration Server to decode the escape sequences. In Integration Server Administrator, go to Extended Settings and add "watt.server.ns.decodeJavaService=true." The change will take effect immediately (no server restart necessary).

Note: After this change, Unicode escape sequences will no longer display in the Java service code in Integration Server. For example, if you use the string "\uD55C" in Java service code, the string will

save correctly, but the editor will display it as "?".

- PIE-40688
Invoking `pub.storage:get` causes a `pub.storage` lock to be released immediately.
When using `pub.storage:get` to retrieve an item, Integration Server released the lock on the item immediately. However, when using `pub.storage:get` to retrieve an item, the lock on the item should remain until the lock is removed by a call to `pub.storage:unlock`, a call to `pub.storage:put`, or the lock expires.
This issue is now resolved.
- PIE-40693
Slow file transfer speed using `pub.client.ftp:put`.
While transferring files with large size (around 1 GB) using `pub.client.ftp:put` service, the file transfer speed is observed to be slow. Hence, it takes longer to complete the file transfer. This issue was due to the buffer limit in the amount of data that can be read and written to the stream (1KB). This issue is now resolved. Now, the buffer size is increased (32 KB) and hence, the transfer time for large files is less and is comparable with the FTP client on Microsoft Windows.
- PIE-40702
Change to Integration Server to address security vulnerability.
A certain form of URL, if executed, can cause a redirection that allows for the possibility of credential theft. The form of URL no longer causes a redirection. Instead, the Integration Server user receives an HTTP 404 response.
- PIE-40742
Package deployment fails because some packages are partially loaded.
When using Deployer to deploy IS packages, some packages only partially load. This causes deployment to fail.
This issue is now resolved. Packages are no longer partially loaded.
- PIE-40867
Modification to Integration Server to control the logging of messages about duplicate universal names for document types.
Whenever Integration Server loads a document type with an explicit universal name (such as when a package is loaded), Integration Server registers the universal name. If Integration Server loads a document type whose explicit universal name is a duplicate of one that is already registered, Integration Server logs the following error message:
"[ISC.0081.0002E] Error registering universal name <universal_name>, already registered to <document_type>" filling the IS logs
A user cannot use Designer or Developer to assign the same universal name to a document type. However, if the same WSDL document is used to generate multiple consumer Web service descriptors and/or multiple WSDL first provider Web service descriptors, Integration Server creates multiple document types with the same universal name explicit. When loading a package containing these document types, Integration Server logs the error message mentioned above

multiple times which can clutter the log file. To suppress the error message about registering a duplicate universal name, add the following to extended settings on the Settings > Extended > Edit Extended Settings page

```
watt.server.ns.logErrorsOnRegisteringMultipleDocTypesForAUniversalName=false
```

After you save your changes, you do need to restart Integration Server for these changes to take effect. If you want Integration Server to resume logging message about registering duplicate universal names, set `watt.server.ns.logErrorsOnRegisteringMultipleDocTypesForAUniversalName` to true. The default value is true.

Note: Setting `watt.server.ns.logErrorsOnRegisteringMultipleDocTypesForAUniversalName` to false suppresses the error messages about duplicate universal names only. It does not resolve the duplicate names.

- PIE-40940

OAuth authentication is not disabled for requests that contain an Authorization header with a Bearer access token even after setting the `watt.server.auth.oauth.accessToken.useHeaderFields` parameter to false.

When `watt.server.auth.oauth.accessToken.useHeaderFields` is set to false, Integration Server should not perform OAuth authentication if Authorization header field contains an `access_token`.

However, if the Authorization header field of an incoming request contains a Bearer access token and the `watt.server.auth.oauth.accessToken.useHeaderFields` is set to false, Integration Server writes the following messages to the server log:

```
[ISS.0012.0012W] Authentication of user "bearer" failed with exception: [ISS.0010.8044] Integration Server rejected the request to access this resource. The access token is either invalid or expired. [ISS.0053.0002C] Access denied for user bearer on port 5555 -> ...
```

This issue is now resolved. If `watt.server.auth.oauth.accessToken.useHeaderFields` is set to false and a request contains an Authorization header field with a Bearer access token, Integration Server disables OAuth authentication for the request.

- PIE-40950

Failure to close JSSE SSL connections after handling stateless requests may negatively impact performance.

When Integration Server finishes handling a stateless request received on a port that uses JSSE for SSL, Integration Server does not close the SSL connection. This causes Integration Server to build up stale connections and slows down port allocation, which affects performance.

This issue is now resolved.

- PIE-40962

The `encode` method of `IDataXMLCoder` class closes the `OutputStream` after encoding the `IData` object.

The `encode` method of `IDataXMLCoder` class, `encode(java.io.OutputStream os, IData data)` encodes the `IData` object and closes the `OutputStream` even though the `OutputStream` is created by the caller.

This issue is resolved.

- PIE-40984

Configuration property to determine whether missing SOAP headers result in an error message. Prior to Integration Server version 9.0, when processing a SOAP received by a web service descriptor, Integration Server did not properly validate that all of the SOAP headers were present. As a result, Integration Server did not throw an error when a SOAP response was missing a SOAP header. Note that all headers in a web service descriptor, whether generated from the original WSDL document or added to the web service descriptor, are treated as required. This is an application of the WS-I basic profile rules declaring that all headers in a WSDL be treated as required. Beginning in Integration Server version 9.0, Integration Server properly validates SOAP responses for required headers. If a required header is not present, Integration Server throws the following error: [ISS.0088.9443] One or more required Headers <headerName> are not present in the SOAP response."

After upgrading to Integration Server 9.0 or higher from an earlier version, web service connectors that previously succeeded when a required header was missing from a SOAP response now fail. While failure when a required header is missing is the correct and documented behavior, Integration Server now provides a configuration property to control whether missing required headers in a SOAP response results in an error. This can be useful in migration situations. When `watt.server.SOAP.ignoreMissingResponseHeader` is set to true, a SOAP response that does not contain a required header will not result in an error. The default is false, a SOAP response that does not contain a required header results in an error. Integration Server restart is not required for changes to take effect.
- PIE-40985

SOAP web service fixes for backward compatibility.

This fix bundles four separate fixes relating to upgrade and migration of web services. The fixes allow backward compatibility of behavior that has since been prohibited through stricter validation in newer releases.

(1) Allow 7.1.3 web service providers to process requests with mismatched SOAP versions.

A range of fix levels in 7.1.3 allowed web service providers to process SOAP requests with a SOAP version that did not match the SOAP version that was declared in the WSDL binding. This fix adds a new extended server setting to emulate the old, less strict behavior so that consumers will not have to update their SOAP requests. The setting only affects web service providers that were created in releases older than 8.2.2 and for which the property "Pre-8.2 compatibility mode"=true. The new parameter is `watt.server.SOAP.pre82WSD.ignoreVersionMismatch`. By default, this parameter is set to false. To use the parameter to emulate the old behavior, go to Integration Server Administrator and add `watt.server.SOAP.pre82WSD.ignoreVersionMismatch=true` to the extended settings.

(2) Correctly perform document type-directed decoding of a SOAP message when the corresponding namespace qualified document type field does not have a namespace prefix.

Starting with release 8.2.2, any document type field that contains a namespace must have a namespace prefix in its name in order to be used with web services. In 7.1.x, this prefix was not required. With this fix, document types migrated from 7.1.x that do not meet the 8.2.2 and later IS web service requirements will match the decoded IData representations of SOAP messages as they did in 7.1.x. Specifically, this issue applies in cases where the Decoder needs to choose between

converting a simple type value into a string field or into a mixed content DocType with a *body field.

(3) Allow empty or absent *body values to pass validation.

A validation error occurred in some 9.x releases during decoding of mixed content elements that have an enumeration restriction. The error occurred when optional missed content was absent, because an empty value was not listed as an option in the enumeration set for the *body field. This fix adds an extended setting to skip this validation and treat the *body as completely optional. The new parameter is `watt.core.validation.skipAbsentStarBody`. By default, this parameter is set to false.

To use the parameter to skip the new validation, go to Integration Server Administrator and add `watt.core.validation.skipAbsentStarBody=true` to the extended settings. (4) Process one-way SOAP request without a Null Pointer Exception. After receiving a SOAP request, some one-way web service providers return an error containing a Null Pointer Exception. This fix handles the condition that resulted in an error when processing the SOAP request.

- PIE-41066

When executing the `pub.soap.wsrn:createSequence` service without specifying the value of the `sequenceKey` input parameter, Integration Server incorrectly reports the messaging sequence as null.

This issue is now resolved. When the `pub.soap.wsrn:createSequence` service is executed without specifying the value of the `sequenceKey` input parameter, Integration Server returns the server Sequence ID associated with the messaging sequence.

- PIE-41090

Enhancement to Integration Server to use regular expressions for specifying the URIs for allowed origin servers.

When CORS is enabled, the `watt.server.cors.allowedOrigins` server configuration parameter indicates the origin servers from which Integration Server will accept requests. The `watt.server.cors.allowedOrigins` value can be a comma-separated list identifying the specific origin servers or a "*", meaning any origin server is allowed. A comma-separated list can become long and difficult to maintain.

To make the list of origin servers easier to maintain, Integration Server now supports the use of regular expressions in the comma-separated list of allowed origin servers. Integration Server treats any value in the comma-separated list that begins with "r:" as a regular expression. Integration Server treats any value that does not begin with "r:" as a simple string. The server configuration parameter uses the Java regular expression syntax, as documented at <https://docs.oracle.com/javase/7/docs/api/java/util/regex/Pattern.html>. A regular expression value must match the entire value of the Origin header in the HTTP request for it to be considered a match.

Example:

```
watt.server.cors.allowedOrigins=http://test1.domain.com,r:https?://.*test2.domain.com:[0-9]+,r:.\.[a-zA-Z]*-int.domain.com
```

Integration Server treats the first value, "http://test1.domain.com", as a simple string. If an Origin header contains this value, it will be allowed.

The second value, "r:https?://.*.test2.domain.com:[0-9]+", contains a regular expression. The "r:" is not part of the regular expression. The actual regular expression used to match supplied Origin headers is "https?://.*.test2.domain.com:[0-9]+".

The third value, "r:.\.[a-zA-Z]*-int.domain.com", contains a regular expression. The "r:" is not part of the regular expression. The actual regular expression used to match supplied Origin headers is ".\.[a-zA-Z]*-int.domain.com".

"Origin: http://test1.domain.com" will be allowed because it is equal to the first value.

"Origin: http://my.test2.domain.com:8080" will be allowed because it matches the second value.

"Origin: https://my.test2.domain.com:8088" will be allowed because it matches the second value.

"Origin: http://my.test2.domain.com" will not be allowed. If it had a port number, it would match the second value.

"Origin: nbps://example.prod-int.domain.com" will be allowed because it matches the third value.

"Origin: example.qa.staging-int.domain.com" will be allowed because it matches the third value.

"Origin: example.dev1-int.domain.com" will not be allowed. If the second token of the host name did not include any digits, it would have matched the third value.

watt.server.cors.allowedOrigins=*

The simple wildcard "*" continues to work as before. It indicates that any origin server will be allowed.

Regular expressions that match any host name, IP address and port (e.g. "r:+" and "r:*") will have the same effect as "*".

Note that when CORS is enabled, Integration Server evaluates the list of regular expressions in watt.server.cors.allowedOrigins sequentially for every request. Integration Server performs a regular expression match operation on each regular expression until a match is found or all regular expressions in the list have been evaluated. Software AG recommends that you put the more frequently matched regular expressions at the beginning of the comma-separated list.

- PIE-41109

Swagger document and REST Resources tab for REST API descriptor does not represent service input correctly when the service signature includes one or more Document, Document List, Document Reference, or Document Reference List field and another type of field.

The Swagger document and REST Resources tab for a REST API descriptor that includes a REST resource (service) whose service signature includes one or more Document, Document List, Document Reference, or Document Reference List fields in addition to another type of field does not correctly represent the service signature. Integration Server places all of the input parameters for that resource into a REST Definition and sets the source to Body which is incorrect. Integration Server should place the Document, Document List, Document Reference, or Document Reference List fields in the REST Operation as Body parameters that reference the REST Definitions and place the parameters that are not documents in the REST Operation as Header parameters.

This issue is now resolved.

- PIE-41121

Integration Server does not show reliable messaging sequence reports in certain situations.

When Integration Server exchanges messages with a reliable messaging client where the web service operation uses In-Only Message Exchange Pattern (MEP), the reliable messaging sequence

reports are not displayed on Integration Server.

The issue is now resolved. The reliable messaging sequence reports specifying the Server Sequence ID are displayed on Integration Server in situations where the web service operation uses In-Only MEP.

- **PIE-41147**
Integration Server Administrator returns a blank page when you run the `wm.server.query:getSettings` service from the `WmRoot` package.
This issue is resolved.

- **PIE-41152**
When `watt.net.http401.throwException` is set to false and the `pub.client:http` service receives a 401 error, the service does not include the body of the response in the output.
If the `watt.net.http401.throwException` server configuration property is set to false, when the `pub.client:http` service receives a 401 error response, the service places the HTTP response header and body in the output pipeline. However, the `pub.client:http` service was not placing the response body in the output pipeline.
This issue is now resolved.

- **PIE-41155**
Integration Server fails to act as an FTP server. An attempt by an FTP client to connect to an FTP port on Integration Server fails with a `NullPointerException`.
This issue is now resolved.

- **PIE-41176**
Web service fails with a `RampartException` while handling a holder-of-key SAML 2.0 assertion. When handling a holder-of-key SAML 2.0 assertion, a web service fails with the following exception: `RampartException: No crypto property file supplied for decryption`.
This issue is now resolved.

- **PIE-41281**
Integration Server Administrator displays incorrect values for fields in `Security > Ports`. Integration Server Administrator displays incorrect values (default values) for "Use JSSE" and "Client Authentication" fields in the Security Configurations section of `Security > Ports`.
This issue is now resolved.

- **PIE-41315**
When Integration Server receives a request with a REST-style URL and an OAuth Bearer token, Integration Server rejects the request with a 403 HTTP status code.
This issue is now resolved. An OAuth Bearer token can be used to access a REST resource that is in the scope for which the token was issued.
Note: Because the service name does not appear in a REST-style URL, do not include the service name when defining the OAuth scope. A scope for an Integration Server REST resource must

include the full name of the resource but not the name of the service.

- PIE-41320
Memory leak in transaction manager.
Transaction manager retains an association to `com.wm.app.b2b.server.ServerThread` which is not being removed during transaction manager cleanup. Consequently, the association between the transaction and the server thread is not being cleaned up, which prevents the transaction manager entry from being removed.
This issue is now resolved.
- PIE-41324
Integration Server Administrator displays a Package Load Error loading a package created on Integration Server 7.x or earlier.
Using Integration Server Administrator to load a package created on Integration Server 7.x might result in a Package Load Error caused by a `NullPointerException`.
This issue was originally resolved in fixes that included PIE-33326. Unfortunately, recent revisions of some Integration Server fixes introduced a regression that allowed the problem to reappear. This fix resolves the regression.
- PIE-41345
The `pub.utils.messaging:migrateDocTypesTriggersToUM` service does not migrate filters with parentheses properly.
When migrating a trigger filter condition that contains parentheses, the `pub.utils.messaging:migrateDocTypesTriggersToUM` service removes the parentheses from the filter. The `pub.utils.messaging:migrateDocTypesTriggersToUM` service now preserves parenthesis when migrating trigger filter conditions.
- PIE-41375
Integration Server does not indicate when it is disconnected from a cluster.
Integration Server does not log an error message when it is disconnected from a cluster, preventing automatic detection of the situation. Now, Integration Server logs the following error message when it is disconnected from the cluster.
[ISS.0033.151] The cluster is now not operational,
Additionally, Integration Server logs the following error message when it rejoins the cluster.
[ISS.0033.152] The cluster is now operational.
- PIE-41444
Integration Server throws a `NullPointerException` instead of logging trace level information when the HTTP Header (0038) server log facility is set to Trace and an incoming request does not contain any credentials.
This issue is now resolved.
- PIE-41464

Exception handling for the `pub.client:smtp` service results in a `ClassCastException` being thrown for a `SocketTimeoutException` or a `ConnectException`.

The `pub.client:smtp` incorrectly handles the exceptions `java.net.SocketTimeoutException` and `java.net.ConnectException` by throwing them as a `java.lang.ClassCastException`.

This issue is now resolved.

- **PIE-41497**
A request that includes a URL alias for a REST resource and includes an OAuth access token fails. When a URL alias exists for a REST resource and partial matching is enabled for URL aliases (`watt.server.url.alias.partialMatching=true`), the URL alias can be used with variable trailing tokens to create a request URL that invokes services for the REST resource and passes the `$resourceID`, `$path`, and custom variables to the services. (With the Bearer authorization scheme, the Authorization request header includes an OAuth access token instead of username and password.) However, if the request URL uses the Bearer authorization scheme, the request fails and Integration Server returns an HTTP 401 status code.
This issue is now resolved. A request that uses the Bearer authorization scheme can also use a URL alias to request a REST resource.

- **PIE-41502**
When acting as a web service client, Integration Server displays an error if the response from a web service provider contains the value of the content-encoding header as identity.
When acting as a web service client, Integration Server displays the following error when the response from a web service provider contains the value of the content-encoding header as identity: "Received unsupported content-encoding: identity"
This issue is now resolved.

- **PIE-41529**
Info message is logged continuously in the server log.
If you configure the email port to IMAP email server and select "Log out after each mail check" functionality, then the following Info message is continuously logged in the server log:
"[ISP.0068.0029I]Logging out of IMAP Server"
This issue is now resolved. Now, this message is moved to DEBUG level.

- **PIE-41582**
Integration Server Administrator does not allow Username/Password as the Client Authentication method if Realm URL specifies `nsps` or `nhps` as the protocol.
When creating a Universal Messaging Connection Alias, Integration Server Administrator performs a UI validation to check if Realm URL specifies `nsps` or `nhps` as the protocol. Integration Server Administrator displays the following message when you select Username/Password as the Client Authentication method. "Client authentication must be set to SSL if Realm URL specifies includes `nsps` or `nhps`."
This issue is resolved. The UI validation is now disabled which allows you to select Username/Password as the Client Authentication method if Realm URL specifies `nsps` or `nhps` as the protocol.

- PIE-41611

Client side queue for webMethods messaging does not drain completely.

When Integration Server drains the client side queue by publishing or delivering messages from the client side queue to the webMethods messaging provider, some failures may occur. Integration Server handles the failures based on the exception type. If the exception type is fatal, Integration Server writes the message to the audit log and removes it from the client side queue. If the exception type is transient, Integration Server retries publishing or delivering the message. However, if the client side queue contains published and delivered messages and fatal exception occurs during publish or delivery of a message, Integration Server might add the message back to the client side queue instead of writing it to the audit log. This prevents the client side queue from fully draining and may cause the queue to drain slowly.

This issue is now resolved.
- PIE-41677

Integration Server fails to clear the connections of failed remote service executions that were invoked using the `pub.remote:invoke` service.

This issue is now resolved. Now, if a remote service execution fails, then the connection to remote server is closed completely.
- PIE-41782

No option to select Java Secure Socket Extension (JSSE) socket factory for HTTPS outbound connections.

When accessing a web service through HTTPS protocol using the `pub.client:soapClient` service, there is no option to select JSSE for HTTPS outbound connections. The server configuration property `"watt.net.ssl.client:useJSSE"` applies to all outbound HTTPS connections and hence, user cannot select JSSE for individual web services call.

This issue is now resolved. Now, an optional input parameter `"useJSSE"` is added to the `pub.client:soapClient` service.

If the value of `"useJSSE"` field is left empty or unspecified, then Integration Server uses JSSE for outbound web service call based on the server configuration property `"watt.net.ssl.client:useJSSE"`. If the value of `"useJSSE"` field is set to `"yes"`, then the Integration Server uses JSSE for the outbound web services call.

If the value of `"useJSSE"` field is set to `"no"`, then the Integration Server uses Entrust IAIK library for the outbound web services call.
- PIE-41794

Changes to Integration Server to notify a caller that provides an expired session id.

After applying a fix or installing a release that includes PIE-37166, Integration Server prompts users for credentials if no matching session object can be found for a given session ID stored in a cookie. This behavior is controlled by the `watt.security.session.forceReauthOnExpiration` server configuration property. When set to true, the more secure behavior, Integration Server rejects requests that include a session id mapped to an expired or invalid session object and prompts the user for credentials. Setting the server configuration property to false instructs Integration Server to

create a new session object, assuming the session id is valid and trusted. In case of the server configuration property value set to true (the default), Integration Server does not notify the caller that a valid session object no longer exists. Nor does Integration Server request that the caller deletes the cookie with the expired session.

Now, when Integration Server receives a request with a session id mapped to a session object that no longer exists, Integration Server notifies the caller and requests that the cookie containing the expired session id be deleted. It is then up to the caller, usually a browser, to react to the notification.

- **PIE-41806**
Enhancement to allow loggers on multiple Integration Servers to share a Universal Messaging queue for logging across a Universal Messaging realm.
The naming convention for the Universal Messaging queue used by a logger now includes the client prefix if the Share Client Prefix check box is selected for the Universal Messaging connection alias used by the logger. By including the client prefix in the namespace of the queue name, loggers for Integration Servers in a stateless or stateful cluster can share same Universal Messaging queue across a Universal Messaging realm. That is, loggers on multiple Integration Servers can write log entries to and read log entries from one Universal Messaging queue shared across a Universal Messaging realm.
Previously, the Universal Messaging queue name did not include the client prefix as part of the queue namespace regardless of the state of the Share Client Prefix check box. If the Share Client Prefix check box is selected for the Universal Messaging connection alias, the Universal Messaging queue name uses the naming convention: `wm/is/audit/clientPrefix/logger_nameQueue` (for example, `wm/is/audit/myClientPrefix/SessionQueue`). If the Share Client Prefix check box is not selected for the Universal Messaging connection alias, the Universal Messaging queue name uses the naming convention: `wm/is/audit/logger_nameQueue` (for example, `wm/is/audit/SessionQueue`). If you change the state of the Share Client Prefix check box on the Universal Messaging connection alias is used by loggers, you must restart Integration Server for changes to the queue name to take effect. Additionally, you must make the same changes to other Integration Servers in the cluster that use the alias.
- **PIE-41825**
Cookies not included in some HTTP requests.
When the `pub.client:http` service is used to send requests to a remote server, and the server returns a cookie, in some cases the cookie is not included in subsequent calls to the server.
With this fix, the cookies are used on subsequent calls.
- **PIE-41880**
webMethods Messaging triggers do not recognize nested documents in a filter when parent and child documents have the same name.
The name of inline document fields are represented as "Message" names in the protobuf descriptors used by Universal Messaging filters. Because of the message name conflict, the filters are never satisfied and the triggers do not fire.
This fix corrects the problem by using the name of the parent plus the actual field as the protobuf

message name. After you install this fix, edit and save the root document type, then sync it with the UM Provider. The filters will begin to work properly.

- **PIE-41900**
The `pub.client.http` fails to set the auth token.
If the 'auth' type is set to Bearer, then the `pub.client.http` service fails to set the auth token into the Authorization header while sending a request to the HTTP server.
This issue is now resolved.

- **PIE-41986**
After installing a fix or a release that includes PIE-37166, a dynamic server page (DSP) request that includes a service invoke of a stateless service prompts for credentials even though the service and DSP are secured with the Anonymous ACL.
The resolution for PIE-37166 introduced the server configuration parameter `watt.security.session.forceReauthOnExpiration`, which, when set to true, causes Integration Server to reject any request that includes a cookie identifying an expired or invalid session even if the request includes valid user credentials. That is, when set to true, Integration Server does not implicitly create a new session for an expired session and Integration Server deletes the session object for the expired session. A result of this change is that a sequence a DSP requests that includes a service invoke of a stateless service prompts for credentials even though the service and DSP are secured with the Anonymous ACL.
Note: This issue does not occur when `watt.security.session.forceReauthOnExpiration` is set to false. Keep in mind that setting `watt.security.session.forceReauthOnExpiration` to true, the default value, offers more secure behavior.
Now, Integration Server preserves the session object.

- **PIE-42132**
Enhancement to limit the number of server log files that Integration Server keeps on the file system. Integration Server writes its server log to a file named `server.log`. When this file is rotated, the existing contents of `server.log` are saved to a new file named `server.log_<current-date>_<current-time>`. Over time, the number of archived server log files increases and may consume large amounts of disk space.
To address this issue, Integration Server provides the `watt.server.serverlogFilesToKeep` server configuration parameter to control the number of server log files that Integration Server maintains on the file system, including the current server log file. When Integration Server reaches the limit for the number of server log files, Integration Server deletes the oldest archived server log file each time Integration Server rotates the server log.
If the parameter value is 30, for example, Integration Server keeps the current server log file and up to 29 previous server log files.
If the parameter value is less than 1, Integration Server keeps an unlimited number of server log files.
If the parameter value is 1, Integration Server keeps the current server log file (`server.log`) and no previous (archived) server logs.
The default for `watt.server.serverlogFilesToKeep` is -1, which places no limit on the number of

server log files kept on the file system.

You must restart Integration Server for changes to this parameter to take effect.

- PIE-42173

New parameter for existing service `pub.cache.serviceResults:resetServiceCache` and new service `pub.cache.serviceResults:addCacheEntry` are added to Integration Server as part of this fix.

`pub.cache.serviceResults:addCacheEntry`

`WmPublic`. Adds cached entry into service results for the service without executing the actual service. This service can be useful to perform bulk load of service results at Integration Server startup.

Input Parameters `<serviceName>` String Required. Name of the service for which to add the cache entry into cached service results.

`<input>` Document Required. An IData containing the key/value pairs for the cached service input.

`<output>` Document Required. An IData containing the key/value pairs for the cached service output.

Output Parameters None.

Usage Notes If `<serviceName>` does not exist in Integration Server, or it is not enabled to cache service results, Integration Server throws an exception.

`pub.cache.serviceResults:resetServiceCache` An optional input parameter is added to delete specific cached elements for a particular service.

`<input>` Document Optional. An IData containing key/value pairs that indicate the cached elements to remove.

- PIE-42308

Support for session caching for transacted JMS connection aliases.

Previously, Integration Server provided session caching for non-transacted JMS connection aliases. Now, Integration Server provides support for session caching for transacted JMS connection aliases when the JMS provider is Universal Messaging 9.10 or WebSphere MQ 7.5. The following paragraphs provide more information about this feature.

When sending a JMS message, Integration Server creates and closes a new JMS session object and a JMS MessageProducer object for each message. This can introduce overhead for some JMS providers. To improve performance when sending JMS messages using a transacted JMS connection alias, you can configure session caching for a JMS connection alias.

For each JMS connection alias, Integration Server can create the following session pools:

- A default session pool containing JMS Session objects. When a default session pool is defined for a JMS connection alias, Integration Server draws from a pool of open JMS Sessions for sending a JMS message instead of opening and closing a JMS Session for each JMS message. Integration Server uses the default session pool only when sending a message to a destination that does not have its own pool. Integration Server creates a new MessageProducer each time it sends a JMS message.

- Destination-specific session pools containing JMS Session objects for sending JMS messages to identified destinations. Integration Server creates a pool for each specified destination. When sending a JMS message to one of the specified destinations, Integration Server uses a Session object from the pool instead of creating and closing a Session object for each JMS message. Integration Server creates a new MessageProducer each time it sends a JMS message.

Note: When using destination-specific session pools for a transacted JMS connection alias, Integration Server creates a new MessageProducer each time it sends a JMS message. This is different from the destination pools that Integration Server creates for a non-transacted JMS connection alias where each entry in the destination-specific pools contains a Session object and a Message Producer object.

Note: A transacted JMS connection alias specifies LOCAL_TRANSACTION or XA_TRANSACTION for the Transaction Type.

To configure session caching for a transacted JMS connection alias, do the following:

1. Using Integration Server Administrator, open the JMS connection alias for editing.
2. Under Producer caching, for Caching Mode, select ENABLED PER DESTINATION.
3. To configure the size of the default session pool for this alias, specify the following:
 - In the Minimum Pool Size field, specify the minimum number of entries in the default session pool for this alias. The default is 1.
 - In the Maximum Pool Size field, specify the maximum number of entries in the default session pool for this alias. The default is 30.

4. To configure the size of the session pools created for specific destinations, specify the following:
 - In the Minimum Pool Size Per Destination field, specify the minimum number of entries in each destination-specific pool.
 - In the Maximum Pool Size Per Destination field, specify the maximum number of entries in each destination-specific pool. A value of 0 (or blank) indicates that Integration Server does not create separate pools for any of the destinations associated with the JMS connection alias.

In the Destination Lookup Name List, specify a semicolon-delimited list of the lookup names for the destinations for which you want Integration Server to create separate session pools for this alias.

5. Click Save Changes.

This issue is now resolved.

- **PIEAR-799**

The threads which creates the connection and the threads which ends the connection from the connectionPool can go to blocked state.

To recover from such a situation, Connection pool now has a monitor thread which is a pool interrupter thread, to interrupt the server threads which are in blocked state while creating or ending the connection.

The following properties are introduced to configure the connection time outs:

1-> `watt.server.jca.connectionPool.threadInterrupter.sleepTime`. The default value of the `watt` property is 2000msec, which is the sleep time for the pool interrupter thread.

2-> `watt.server.jca.connectionPool.threadInterrupter.waitTime`. This property specifies the wait time, measured in milliseconds, that elapses before Integration Server Connection pool interrupts a connection creating or ending thread which is in a wait state. The pool interrupter thread will start monitoring the server threads, only if this property is set. There is no default value.

You must restart Integration Sever for changes to this parameter to take effect.

Use the following service to manage the connections which are hung:

`pub.art.connection:getInterruptedThreadStatus`. This service takes the connection alias name as input and lists the connection threads which are not responding even after interrupting by the connection pool interrupter. We recommend a manual intervention for the server threads which gets hung while creating or destroying the connections and also not responding to the interrupt

mechanism.

Release 9.10

- PIE-36529 (IS_8.2_SP2_Core_Fix18, IS_9.0_SP1_Core_Fix12, IS_9.5_SP1_Core_Fix9, IS_9.6_Core_Fix8)
An outbound web service request that used MTOM attachments causes out of memory issues if the attachments are large.
An outbound web service request incorrectly used a memory-buffered output stream when requests with large MTOM attachments were made to external endpoints.
Outbound web service requests that use MOTM attachments now use the correct output stream and chunk the large MTOM attachment.
- PIE-36506 (IS_8.2_SP2_Core_Fix19, IS_9.0_SP1_Core_Fix12, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
The pub.security.keystore:setKeyAndChain service clears security parameters after each outbound call instead of when the pub.security.keystore:clearKeyAndChain service executes.
In previous releases, Integration Server did not clear the security parameters configured for the outbound call by the pub.security.keystore:setKeyAndChain service until the pub.security.keystore:clearKeyAndChain executed. Now, Integration Server clears the security parameters after each outbound call. The new behavior is not backward compatible.
Now, the security values configured by pub.security.keystore:setKeyAndChain stay in effect until pub.security.keystore:clearKeyAndChain gets invoked.
- PIE-37676 (IS_8.2_SP2_Core_Fix19, IS_9.0_SP1_Core_Fix12, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
An attempt to authenticate a cache manager user fails with an `IllegalThreadStateException`.
When authenticating users of a cache manager, a race condition caused an `IllegalThreadStateException` to be thrown.
The race condition that caused the `IllegalThreadStateException` is now resolved.
- PIE-36620 (IS_8.2_SP2_Core_Fix19, IS_9.0_SP1_Core_Fix13, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
Integration Server returns an HTTP 500 error in response to successive requests made on persistent HTTP connections.
When client reuses a persistent HTTP connection to send multiple requests, Integration Server should handle the request and send a response. However, Integration Server sometimes incorrectly returned a HTTP 500 error, which caused the request to fail.
This issue is now resolved.
- PIE-37093 (IS_8.2_SP2_Core_Fix19, IS_9.0_SP1_Core_Fix13, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
When using the VCS Integration feature in Integration Server, delete and safe delete of a version-controlled node fails with an error.
This issue is now resolved.

- PIE-37325 (IS_8.2_SP2_Core_Fix19, IS_9.0_SP1_Core_Fix13, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
 Integration Server does not send HTTP cookies after a request is redirected.
 When the pub.client:http service sends a request to an HTTP server and the HTTP server responds with a redirection (a 300-level status code) and a Set-Cookie header, Integration Server includes the cookie in the request to the HTTP server to which the request is being redirected. However, subsequent requests to the second server do not include the cookie.
 Now, when a HTTP server includes a Set-Cookie header in a redirection response, Integration Server includes the cookie in the request and subsequent requests sent to the HTTP server to which the request is redirected.
- PIE-38245 (IS_8.2_SP2_Core_Fix19, IS_9.0_SP1_Core_Fix13)
 The pub.flow:transportInfo document type signature is incorrect as seen on the Input/Output tab. The signature for the pub.flow:transportInfo document type is missing 2 fields: filePolling/lastModified and filePolling/length.
 This issue is now resolved. The signature of the pub.flow:transportInfo document type now includes the filepolling/lastModified and filepolling/length parameters.
- PIE-38290 (IS_8.2_SP2_Core_Fix19, IS_9.0_SP1_Core_Fix13)
 Integration Server resets the central user management system when lookup for a user in the central user management fails with an error.
 The reset causes a failure of other operations on the central user management system.
 This issue is resolved.
- PIE-37898 (IS_8.2_SP2_Core_Fix19, IS_9.6_Core_Fix9)
 Integration Server becomes unresponsive during startup.
 Integration Server sometimes became unresponsive at startup when initializing the scheduler. This occurred because of a database deadlock.
 This issue is now resolved and the deadlock will no longer occur.
- PIE-36477 (IS_8.2_SP2_Core_Fix19)
 After transitioning to or from daylight savings time, scheduled tasks run twice or not at all. Integration Server runs scheduled tasks based on the time relative to the time zone. This caused issues when entering and exiting daylight savings time, specifically tasks ran twice or not at all. Now, Integration Server runs scheduled tasks based on coordinated universal time (UTC). Because Integration Server runs the tasks without regard to the relative time zone, the start and end of daylight savings time does not affect the execution of scheduled tasks.
- PIE-36386 (IS_9.0_SP1_Core_Fix11, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix8, IS_9.7_Core_Fix5)
 When a flow service invokes a service that does not exist, Integration Server handles operations on the pipeline first before issuing a runtime exception.
 When a flow service invokes a service that does not exist, Integration Server performs operations on the pipeline, such as removing the dropped variables from the pipeline, before issuing a com.wm.lang.flow.FlowException about the unknown service.
 This issue is resolved. Integration Server now issues the runtime exception when a flow service invokes a service that does not exist and will not proceed with the pipeline operations.

- PIE-35990 (IS_9.0_SP1_Core_Fix12, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix8)
 When using Oracle Streams Advanced Queuing (AQ) as the JMS provider, if the JMS connection alias is disabled due to an error from the JMS provider, the JMS connection continues to show the status as "in progress".
 If a JMS connection alias, when attempting to establish a connection with Oracle Streams Advanced Queuing (AQ) as the JMS provider, is disabled due to an error from the JMS provider, the JMS connection continues to show the status as "in progress" and cannot be enabled or disabled.
 This issue is resolved.
- PIE-37022 (IS_9.0_SP1_Core_Fix12, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix8)
 Integration Server logs the following error twice for the same port in the server logs while shutting down:
 [ISP.0046.0011I] Disabling HTTP Listener on port <port number>
 This issue is resolved. Integration Server now logs this message only once while shutting down.
- PIE-35873 (IS_9.0_SP1_Core_Fix12, IS_9.5_SP1_Core_Fix9, IS_9.6_Core_Fix8)
 Change to allow use of forward slash in a regular expression.
 Prior to this change, regular expressions used in BRANCH steps and trigger filters could not include a forward slash. Now, a forward slash can be used. However, the forward slash must be preceded by the backslash (\) escape character. For example, to use a regular expression to match a variable whose value contains the string "a/b", use the regular expression %variableName% = /a\b/
- PIE-37271 (IS_9.0_SP1_Core_Fix12, IS_9.5_SP1_Core_Fix9, IS_9.6_Core_Fix8)
 In certain scenarios, invoking the pub.xml:getNextXMLNode service fails with an exception. Invoking the pub.xml:getNextXMLNode service fails with a NullPointerException if the specified NodeIterator is returned by the pub.xml:getXMLNodeIterator service that has the criteria input parameter set to a string value that matches an element node of the XML node.
 This issue is resolved.
- PIE-34881 (IS_9.0_SP1_Core_Fix12)
 Integration Server does not behave as expected when validating an XML document against a document type created from an XML schema definition containing <xs:restriction base="xs:anyType">.
 When using the pub.schema:validate service to validate an XML document against a document type created from an XML schema definition containing <xs:restriction base="xs:anyType">, the validation does not fail even if the target element contains attributes other than the attributes defined in the XML schema definition.
 This issue is resolved. Now, validation of XML fails if there are any attributes other than the defined attributes.
- PIE-36217 (IS_9.0_SP1_Core_Fix13, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
 An outbound HTTPS web service request fails when using JSSE.
 If an outbound HTTPS web service request specifies the use of JSSE, the request fails because Integration Server does not send the client certificates to the endpoint.
 This issue is now resolved.

- PIE-37071 (IS_9.0_SP1_Core_Fix13, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
Integration Server error log does not include the names of the affected JDBC pools in the error messages.
When issuing error messages such as, “java.sql.SQLException: Could not get connection”, Integration Server error log does not include the names of the JDBC pools to which the error message is referring.
This issue is resolved. Integration Server error log now includes the name of the JDBC pools in its error messages.
- PIE-37551 (IS_9.0_SP1_Core_Fix13, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
Processing of webMethods messaging triggers fails with a java.lang.ClassCastException if the watt.server.trigger.local.checkTTL server configuration parameter is set to true.
Processing of webMethods messaging triggers fails with the following error if the watt.server.trigger.local.checkTTL server configuration parameter is set to true:
Unable to check document ttl: java.lang.ClassCastException: [B cannot be cast to com.wm.data.IData
This issue is now resolved.
- PIE-37645 (IS_9.0_SP1_Core_Fix13, IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
Incorrect logging level specified for error message.
Integration Server gives the logging level of the following error message of Trace logging level incorrectly as Info:
[ISC.0042.0001I] baseURL (Connection reset)
This issue is now resolved. The logging level of the message is corrected to Trace.
- PIE-38560 (IS_9.0_SP1_Core_Fix13, IS_9.5_SP1_Core_Fix10)
Integration Server logs a NullPointerException at one minute intervals.
Once per minute, the Integration Server scheduler uses a background thread to check for scheduled tasks in an invalid state. If Integration Server is in a cluster and the watt.server.scheduler.logical.hostname property is not set, a NullPointerException occurs and is written to the error log.
Now, the background thread used by the scheduler no longer throws a NullPointerException if Integration Server is in a cluster and the watt.server.scheduler.logical.hostname property is not set.
- PIE-35697 (IS_9.0_SP1_Core_Fix13)
After refreshing a consumer web service descriptor, response services reference the backup folders.
After refreshing a consumer web service descriptor, the response services contain references to the backup folders.
This issue is now resolved.
- PIE-37921 (IS_9.0_SP1_Core_Fix13)
The pub.client:http service does not include the supplied data in PUT requests.
When using the PUT method with the pub.client:http service, the request transmitted to the remote HTTP server does not include the value supplied for the data/args, data/string, data/table, data/bytes, data/stream or data/mimeStream input variables.
This issue is now resolved. When the PUT method is used with pub.client:http, the value of the

data/args, data/string, data/table, data/bytes, data/stream or data/mimeStream input variables is now included as the HTTP entity of the transmitted request.

- PIE-37988 (IS_9.0_SP1_Core_Fix13)
A NullPointerException occurs when SoftwareAG-IS-Services.xml configuration file is not present in the caching directory.
When SoftwareAG-IS-Services.xml configuration file is not present in the directory location <Integration Server_directory>\instances\<instance_name>\config\Caching, Integration Server throws a NullPointerException.
This issue is resolved. Integration Server now logs the following error message in the server logs to indicate that the configuration file is not present in the caching directory.
Cannot cache "{0}" service. The cache manager SoftwareAG.IS.Services is not initialized."
- PIE-38019 (IS_9.0_SP1_Core_Fix13)
Integration Server acting as an SFTP client faces issues while attempting to connect to an SFTP server.
When attempting to connect to an SFTP server, Integration Server acting as an SFTP client issues the following error:
[ISS.0147.9010] Cannot get host key from server [host_X]:22.
Details: com.jcraft.jsch.JSchException: Algorithm negotiation fail
This issue occurs because there is no common key exchange algorithm between the SFTP client and SFTP server.
This issue is now resolved by updating the jsch jar file from 0.1.51 version to 0.1.53 version. The 0.1.53 version supports most of the key exchange algorithms that are required to be present in the SFTP client to connect to SFTP server.
- PIE-38429 (IS_9.0_SP1_Core_Fix13)
Integration Server logs an exception when a service is invoked through a JSSE-enabled HTTPS port with client authentication set to "Username/Password" or "Request Client Certificates".
When a service is invoked through an HTTPS port that uses JSSE and has client authentication set to "Username/Password" or "Request Client Certificates", Integration Server logs the following exception in the error log:
javax.net.ssl.SSLPeerUnverifiedException: peer not authenticated.
The issue is now resolved. Integration Server does not log any exception upon invoking a service successfully through a JSSE-enabled HTTPS port with client authentication set to "Username/Password" or "Request Client Certificates".
- PIE-38599 (IS_9.0_SP1_Core_Fix13)
The pub.client:http service does not honor the value set for the useJSSE parameter.
The useJSSE parameter of the pub.client:http service indicates whether to enable the use of the Java Secure Socket Extension (JSSE) socket factory for creating outbound HTTPS connections. However, the pub.client:http service fails to consider the value set for the useJSSE parameter and does not use JSSE for SSL connection with proxy configuration even if the "useJSSE" parameter is set to yes.
This issue is now resolved. The pub.client:http service now honors the value set for the useJSSE parameter.
- If "useJSSE" is set to yes, Integration Server uses JSSE for HTTPS connection.

- If "useJSSE" is set to no, Integration Server uses Entrust IAIK library for HTTPS connection.

- PIE-39117 (IS_9.0_SP1_Core_Fix13)
Subsequent HTTPS requests through proxy to the server fail.
When you send repeated outbound HTTPS requests to a server using the pub.client:http service with useJSSE=yes and HTTPS proxy alias, the first request is sent successfully but the subsequent requests fail with exception.
The issue is now resolved.
- PIE-37937 (IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix8)
Publishing a document as a JMS message from Designer fails with a NamingException.
Using Designer to publish an instance of an IS document type as a JMS message fails with a NamingException. This occurs because the pub.jms:send service, which is used by Designer to publish the JMS message, includes a new input parameter named JMSMessage/header/replyTo that Designer populates with an empty String. Integration Server attempts a JNDI lookup using the empty String, which results in the NamingException.
Now, Integration Server verifies that JMSMessage/header/replyTo parameter is not empty before performing the JNDI lookup.
- PIE-34925 (IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
When executing a web service connector, Integration Server does not check the Execute ACL of the parent consumer web service descriptor.
When executing a web service connector contained in a consumer web service descriptor that has a Pre-8.2 compatibility mode value of false, Integration Server did not check the Execute ACL of the consumer web service descriptor. The documented behavior is to always verify the Execute ACL for a web service descriptor, but it was not being done.
Now, when executing a web service connector, Integration Server checks the Execute ACL of the parent consumer web service descriptor.
- PIE-37804 (IS_9.5_SP1_Core_Fix10, IS_9.6_Core_Fix9)
Integration Server KPI that Optimize uses to display lifetime statistics displays current statistics instead.
The Integration Server KPI, getNumCompletedRequests, which Optimize uses to display the number of completed requests over the lifetime of the Integration Server, returns the number of requests in the last polling period instead.
This issue is now resolved.
- PIE-37586 (IS_9.5_SP1_Core_Fix10)
Integration Server deletes the parent task when all the servers in a cluster are shut down. When you schedule a task to run on all servers in a cluster, and when one server in the cluster is shut down, Integration Server deletes the corresponding child task. However, when all the servers in the cluster are shut down, Integration Server deletes all the child tasks as well as the parent task. As a result, the parent task information is lost upon restart of Integration Server.
This issue is resolved.
- PIE-38131 (IS_9.5_SP1_Core_Fix10)
Change to Integration Server to allow the pub.client:http service to return response headers and

response entity when receiving a 501 to 599 level response from a remote HTTP server. HTTP servers indicate success or failure by including a status code in the response. The `pub.client:http` service returns the status code, response headers, and response body. When the HTTP response includes a status code in the 501 to 599 range, the `pub.client:http` service throws a `ServiceException`. Some HTTP servers include useful information in the response headers and entity when returning a 501 to 599 level status code. However, this information is lost when `pub.client:http` throws a `ServiceException`.

To address this issue, Integration Server now includes a server configuration parameter, `watt.net.http501-599.throwException`, which you can use to indicate how the `pub.client:http` service handles a 501 to 599 level response.

`watt.net.http501-599.throwException`

Specifies whether or not the `pub.client:http` service throws a `ServiceException` when receiving a 501 to 599 level response from a remote HTTP server. When set to `true`, the `pub.client:http` service throws a `ServiceException` when it receives a 501 to 599 level response from a remote HTTP server. When set to `false`, the `pub.client:http` service does not throw a `ServiceException` when it receives a 501 to 599 level response from a remote HTTP server. Instead, when the `pub.client:http` service returns a status code in the 501 to 599 range, the service returns the status code, response headers, and response body. The default is `true`. You do not need to restart Integration Server for changes to this parameter to take effect.

Note: When the remote HTTP server returns a response code of 500, the `pub.client:http` service returns the status code, response headers, and response body.

- **PIE-38442 (IS_9.5_SP1_Core_Fix10)**

Integration Server does not handle an element with `xsi:nil=1` correctly.

If an IS document type used by the web service contains a field of type `Object` for which the `Allow null` property is set to `true` and the XML instance document contains a corresponding element with an `xsi:nil=1` and an `xmlns:xsi=` attribute, Integration Server does not properly convert the element. Instead, Integration Server incorrectly converts the element to a `Document` field with no children instead of converting the element to a field of type `Object` with a "null" value.

This issue can also occur when the `pub.xml:xmlNodeToDocument` service executes and all of the following are true:

- The `preserveUndeclaredNS` input parameter is set to `true`
 - The IS document type in the `documentTypeName` field contains a field of type `Object` for which the `Allow null` property is set to `true`
 - The supplied node contains a corresponding element with an `xsi:nil=1` and an `xmlns:xsi=`
- Now, Integration Server properly converts the `xsi:nil=1` element to an field of type `Object` with a "null" value.

- **PIE-36837 (IS_9.5_SP1_Core_Fix9, IS_9.6_Core_Fix8)**

Sessions are not being shared among Integration Servers in a cluster.

When a dynamic server page (DSP) is requested by a client, a session is created in Integration Server and a `Set-Cookie` response header is returned with the session ID. If a subsequent request from the client includes the session ID but a different Integration Server in the cluster receives the request, the second server should find the session in the cluster's session store and then use the session to service the request. This was not happening. The first server did not save the session to the cluster's session store. As a result, the client's session was not available to the second server.

This has been fixed. When a clustered Integration Server receives a request for a DSP, the server saves the session to the cluster's session store.

- PIE-36942 (IS_9.5_SP1_Core_Fix9, IS_9.6_Core_Fix8)
Integration Server may become unresponsive when processing concurrent requests to disable file polling ports in different packages.
If Integration Server receives concurrent requests to disable a file polling port in a package and the ports are located in different packages, Integration Server may become unresponsive. Additionally, HTTP/S ports on Integration Server might become unavailable.
This issue is now resolved.
- PIE-37005 (IS_9.5_SP1_Core_Fix9, IS_9.6_Core_Fix8)
Enhancement to pub.jms:send service to allow specifying a destination for the JMSReplyTo header. Currently, if you want to specify the JMSReplyTo header for a JMS message that you are sending, you must use the pub.jms:sendAndWait service. The pub.jms:sendAndWait service sends a request message and waits for a response. The act of waiting for a response message comes with extra overhead for Integration Server which is unnecessary if you merely want to specify a JMSReplyTo destination but do not want the sending service to wait for a reply.
To address this issue, the pub.jms:send service has been enhanced to include a new input parameter for setting the JMSReplyTo header. When invoking the pub.jms:send service, you can set the JMSMessage/header/replyTo field which is an optional parameter of type String. Set this parameter to one of the following:
 - If the JMS connection alias used by the pub.jms:send service connects to the JMS provider using JNDI, set JMSMessage/header/replyTo to be the lookup name of the destination lookup object name.
 - If the JMS connection alias used by the pub.jms:send service connects to the JMS provider using a native Broker connection, set JMSMessage/header/replyTo to the Broker queue name. That is, if the JMS connection alias specifies the Broker as the JMS provider and uses the native webMethods API to connect directly to the webMethods Broker, specify the name of the queue on the Broker that should receive replies to the message.Note: When using the native webMethods API to connect to the Broker, the JMSMessage/header/replyTo destination must be a queue. Topics are not supported.
When executing the pub.jms:send service with a valid value for the JMSMessage/header/replyTo parameter, Integration Server creates the javax.jms.Destination and maps it to the JMSReplyTo field within the message header. Integration Server sends the message and returns immediately. The service does not wait for the response message.
If JMSMessage/header/replyTo is empty, then Integration Server does not set the JMSReplyTo header for the JMS message. If JMSMessage/header/replyTo is invalid, then Integration Server throws a ServiceException.
- PIE-37261 (IS_9.5_SP1_Core_Fix9, IS_9.6_Core_Fix8)
Integration Server logs the message "[B cannot be cast to com.wm.util.Values" in server.log file". If the ServiceResults cache has the Copy on Read and Copy on Write check boxes selected and the number of entries in the cache exceeds the value specified for Maximum Elements in Memory, Integration Server logs the following error message to the server log: [B cannot be cast to com.wm.util.Values

This issue is now resolved.

- PIE-37126 (IS_9.5_SP1_Core_Fix9, IS_9.6_Core_Fix9)
In the Integration Server Administrator page, the Routing option under Adapters is not available in some cases.
After a successful installation of the OnRamp for Commerce One Marketplace Adapter, the Routing option under Adapters in the Integration Server Administrator page is not available. The Integration Server console is unable to add this option in the Integration Server Administrators page because an incorrect configuration in the Server Log Facilities page results in a failure in the initialization process for the adapter.
This issue is resolved. The Routing option is now available under the Adapters section in the Integration Server Administrator page.
- PIE-35036 (IS_9.6_Core_Fix8, IS_9.7_Core_Fix5)
Integration Server does not reflect the changes made to the Create Temporary Queue option after the JMS connection alias is created.
If the Create Temporary Queue option is selected while creating a JMS connection alias and if this selection is cleared later, Integration Server does not reflect this change. The setting of the Create Temporary Queue option that was chosen while creating a JMS connection alias is maintained.
This issue is resolved. Integration Server now reflects the changes made to the Create Temporary Queue option after the JMS connection alias is created.
- PIE-37419 (IS_9.6_Core_Fix9)
File polling consumed server threads that were not terminated at the end of file polling process.
The thread leak related to file polling ports is now resolved.
- PIE-37581 (IS_9.6_Core_Fix9)
Integration Server erroneously logs a message about the connection pool threshold being exceeded.
Integration Server erroneously writes the following message to the server log:
[ISS.0096.0008I] JDBC Connection pool threshold exceeded, 0 available for pool
CentralUsers:CentralUsersPool
This issue is now resolved.
- PIE-37893 (IS_9.6_Core_Fix9)
The FTP command PWD returns incorrect structure in certain situations
The FTP command PWD sometimes returns an incorrect directory path .
The PWD command now returns a valid directory path.
- PIE-37268 (IS_9.6_Core_Fix9)
When JSSE is enabled for outbound HTTP connections from Integration Server, `watt.security.ssl.client.ignoreEmptyAuthoritiesList` does not work as expected.
When JSSE is enabled for outbound HTTP connections, Integration Server client accepts empty trusted authorities lists from the SSL server but does not return its CA certificate even if the `watt.security.ssl.client.ignoreEmptyAuthoritiesList` is set to true.
This issue is resolved. Now, when JSSE is enabled for outbound HTTP connections, Integration Server client accepts empty trusted authorities lists from the SSL server and returns its CA certificate if the `watt.security.ssl.client.ignoreEmptyAuthoritiesList` property is set to true.

- PIE-36514
 Integration Server creates an exception when you invoke a flow service exposed as a web service. Integration Server creates the following exception when you try to invoke a flow service exposed as a web service:
 ServiceException: Fault returned by invoked service.
 This exception which is created in the stack before the service is executed is not logged in the Integration Server log but, monitoring tools like Dynatrace might interpret the exception as an error even though the service is successfully executed.
 This issue is resolved.
- PIE-37042
 When invoking the pub.client:http service with the useJSSE input parameter set to yes, a java.lang.ClassCastException error occurs if the server configuration parameter, watt.security.ssl.keypurposeverification is set to true.
 This issue is resolved.
- PIE-37056
 When the pub.client:http service sends an HTTPS request, the SSL handshake process fails when the useJSSE parameter is set to yes.
 When the pub.client:http service sends an HTTPS request and the useJSSE input parameter is set to yes, during the SSL handshake process Integration Server sends its certificate even though no matching CA certificate from the other endpoint server is found in the Certificate Authorities list for the SSL handshake.
 This issue is resolved. Integration Server now sends its CA certificate during the SSL handshake process only if a matching CA certificate is available from the other endpoint server.
- PIE-37178
 The watt.server.compile parameter is not set correctly if Integration Server instance is created through migration utility.
 When running the migration utility, selecting the option to create an Integration Server instance during migration results in an incorrect value for the watt.server.compile server configuration parameter, specifically: `{javac.exe} -classpath {0} -d {1} {2}`
 Now, the migration utility substitutes the value of `{javac.exe}` to point to javac executable located in the JDK shipped with Integration Server.
- PIE-37308
 At start up, Integration Server logs a warning message about audit logging even though no audit loggers are configured.
 At start up, Integration Server attempts to determine if there are sufficient JDBC connections in the JDBC connection pool even when audit loggers are not configured. If there are no connections, Integration Server logs the following message, which is erroneous if there are no configured audit loggers:
`[ISS.0095.0022W] Audit Logging Initialization: Unable to verify the Max Connections setting for the Audit Logging database.`
 Now, Integration Server does not check for JDBC connections at start up if there are no configured audit loggers.

- PIE-37377

Update of scheduled tasks to use UTC fails.

At startup, if Integration Server updates scheduled tasks to use UTC (Coordinated Universal Time) instead of local time, Integration Server writes the following message to the server.log:
[ISS.0137.0035E] Migration of scheduled tasks to UTC timezone failed

When Integration Server updates the tasks to UTC, Integration Server also validates the tasks, which, for a task scheduled to run on another Integration Server in a cluster, includes checking that the Integration Server is a member of the cluster. If the Integration Server is not in the cluster, task validation fails and the task timestamp is not updated to UTC. However, Integration Server incorrectly considers that the task that failed validation is now in UTC when, in fact, the task is still in local time.

Now, the migration utility no longer validates the scheduled task during migration. Consequently a validation failure does not prevent the migration utility from updating the scheduled tasks.
- PIE-37457

A webMethods messaging request-reply fails when the encoding type of the reply document type is protocol buffers.

When encoding the reply message, Integration Server uses the encoding type specified for the publishable document type used as the reply. However, reply messages are sent to a dedicated reply-to channel on Universal Messaging. The channel is generic and is not associated with any specific document type. To receive a protocol buffer encoded message, a channel must be associated with a specific document type. Because the channel is generic, a reply message encoded as a protocol buffers cannot be processed.

To address this issue, Integration Server now always encodes reply message as IData.
- PIE-37560

Upgrade does not include layered products if the destination Integration Server does not have an instance with the same name as the source Integration Server.

When upgrading to an Integration Server instances that does not have the same name as the source Integration Server instance, upgrade does not include layered products such as webMethods Mediator and webMethods Monitor.

This issue is now resolved. Upgrade always includes layered products, regardless of whether or not the destination Integration Server instance is the same as the source Integration Server instance.
- PIE-37825

When the logging level is set to Trace, upon invoking the pub.client:http service, Integration Server logs an entry for the HTTP Get method in the server log irrespective of the HTTP request type. This issue is resolved. Upon invoking the pub.client:http service, Integration Server now logs entries according to the HTTP request type.\
- PIE-37844

After a database outage, Integration Server can run out of threads.

When Integration Server cannot connect to the audit logging database, either due a problem in the database or a problem in the network, all threads requesting database connections can pause indefinitely. If this situation persists, all threads in the server thread pool will be paused. No new requests will be accepted.

This issue has been fixed. A point of thread contention in the JDBC pool implementation was removed. Threads requesting database connections after a database outage no longer experience lengthy pauses.

- **PIE-36702 (IS_9.8_SPM_Fix1)**
Command Central cannot be used to set the all the JDBC connection pool alias properties. When using Command Central to create or edit a JDBC connection pool, the Available Connections Warning Threshold and Waiting Thread Threshold Count properties cannot be specified. The Available Connections Warning Threshold and Waiting Thread Threshold Count properties can now be set through Command Central.
- **PIE-34577**
Integration Server does not validate a certificate that uses the SHA-256 algorithm but should. The certificate chain verifier in Integration Server validates the certificates presented by SSL clients. The certificate chain verifier does not validate a certificate chain that uses the SHA-256 algorithm, but should. Instead Integration Server throws the following error:
[ISC.0009.9002] Error in certificate chain: Entrust cannot verify the certificate chain: [ISC.0009.9002]
Error in certificate chain
The certificate chain verifier in Integration Server now validates a certificate chain that uses the SHA-256 algorithm.
- **PIE-35422**
The jcode utility fails with a MalformedPatternException on Linux. Execution of jcode.sh on Linux fails with the following error: Exception in thread "main"
java.lang.NoClassDefFoundError: org/apache/oro/text/regex/MalformedPatternException
The exception occurs because one of the required jar files in common/lib/ext is missing from the jcode utility classpath.
The jcode.sh file is now updated to include the required jars in the classpath. This issue is now resolved.
- **PIE-35643**
After upgrading to version 9.7, when a webMethods messaging trigger, which has join conditions that are dependent on two or more documents, does not start because Integration Server cannot locate the publishable document types, Integration Server does not reload and start the trigger when the publishable document types are later loaded.
Integration Server does not start a webMethods messaging trigger, which has join conditions that are dependent on two or more publishable document types, if it cannot find the document types specified in the join condition. However, Integration Server issues a PDT_DOES_NOT_EXIST (InvalidDocumentException) exception stating the reason the trigger did not fully load and when Integration Server loads the package containing the publishable document types to which the trigger subscribes, Integration Server reloads the trigger. But, after upgrading to version 9.7, instead of the PDT_DOES_NOT_EXIST exception, Integration Server returns an INVALID (ServiceException) exception incorrectly. As a result, Integration Server fails to reload and start the trigger when the publishable document types are later loaded.
This issue is resolved. Integration Server now returns the PDT_DOES_NOT_EXIST exception correctly if it cannot find the document types specified in the join condition. In addition, when

Integration Server loads the package containing the publishable document types specified in the join condition, Integration Server reloads the trigger.

- PIE-35716
If the database associated with Integration Server is restarted abruptly, service invocations or database calls made through JDBC connection pool alias fail and do not return any records from the database.
When the database associated with Integration Server is restarted abruptly, Integration Server does not close and release the existing JDBC connections that are stale due to the abrupt database shutdown, and fails to return these connections to the JDBC connection pool. As a result, service invocations or database calls made through the JDBC connection pool alias fail and do not return any records from the database.
The issue is now resolved.
- PIE-35907
After migrating to Integration Server 9.5 or later, Integration Server displays an exception when calling a web service and using MTOM streaming.
After migrating 2 to Integration Server 9.5 or later, sending a web service request that uses MTOM streaming for which more than one chunk is sent, the following exception occurs:
"Exception --> org.apache.axis2.AxisFault: Connection reset by peer: socket write error"
This issue is now resolved.
- PIE-36224
When installed on Unix or Linux, scripts located in
IntegrationServer/instances/<instanceName>/packages/<packageName> directory, such as
IntegrationServer/instances/myInstance/packages/WmDeployer, do not have permission to execute.
This issue is now resolved.
- PIE-36288
Executing the jcode.bat/sh utility removes the name of the output template assigned to a service.
Running the jcode.bat/sh utility removes the value of the Output template Name property for services in the package containing the Java service.
This issue is now resolved.
- PIE-36399
Using pub.schema:createXSD to create an XML Schema definition for a document type ends with a NullPointerException.
Using the pub.schema:createXSD service to create an XML Schema definition for a document type ends with a NullPointerException if the document type contains a field named *body.
This issue is now resolved.
- PIE-36644
Memory leak with JMS request-reply.
Integration Server did not correctly close MessageProducer objects when invoking the pub.jms:reply service, resulting in a memory leak.
This issue is now fixed.

- PIE-36824

Users that are members of the Developers group cannot use Designer to build and upload processes.

When a user that belongs to the Developers group uses Designer to build and upload a process, Designer throws the following exception:

Error: Build of process <processName> failed.

```
com.webmethods.process.connection.is.IntegrationServerConnectionException: [ISC.0064.9314]
Authorization Required: [ISS.0084.9004] Access Denied
at
com.webmethods.process.generator.util.GeneratorUtils.getJMSPProviderData(GeneratorUtils.java:93
4)
at
com.webmethods.process.generator.util.GeneratorUtils.createJNDIDestinations(GeneratorUtils.java
:718)
```

This issue is now resolved. Members of the Developers group can now use Designer to build and upload processes.
- PIE-36962

Integration Server fails to enable email ports configured to use transport layer security.

Upon creating an email port configured to use transport layer security, Integration Server fails to enable the email port and issues the following error message:

Unsupported ciphersuite SSL_DH_DSS_WITH_3DES_EDE_CBC_SHA

This issue is resolved.
- PIE-36990

Duplicate port aliases are assigned during upgrade.

When upgrading Integration Server 9.5 or earlier to version 9.6 or later, Integration Server might assign the same port alias to multiple Internal Server ports. Upon startup of Integration Server, this may result in only one of the Internal Server ports becoming active and in the following warning: [ISS.0070.30] yyyy-mm-dd hh:mm:ss zone WARN: Duplicate alias

```
protocolListener_portNumber_packageName encountered creating protocol listener on port
portNumber.
```

This occurs because the naming convention used to assign a port alias to an existing port creates a duplicate alias if more than one Internal Server ports connect to an Enterprise Gateway Server through the same Registration port.

Now, to ensure that each port alias is unique, Integration Server includes the host name for the port in the port alias for migrated ports. The new naming convention is:

```
protocolListener_portNumber_hostName_packageName
```
- PIE-37004

Integration Server reloads packages more than once in a run-time-based deployment.

When there are dependencies across different Integration Server packages in a run-time-based deployment, Integration Server reloads these packages more than once.

Now, Integration Server reloads the packages just once.
- PIE-37041

While converting an XML node to a document, Integration Server does not issue any validation errors upon receiving empty fields that are not included in the enumeration list.

When converting an XML node to a document that contains fields with *body attributes, the text specified in *body represents the values of the document fields. These elements can have valid values specified in the enumeration fields. However, while converting, if Integration Server receives an empty value for a field and if the empty value is not included in the enumeration list, Integration Server should issue a validation error, but does not.

This issue is resolved. Integration Server now issues the following validation error upon receiving an empty field that is not included in the enumeration list:

No matching enumeration value.”

- PIE-37142
On Windows, the script for creating a new instance of Integration Server does not use the JVM bundled with the product installation.
The script for creating an Integration Server instance now uses the JVM bundled with the Integration Server product installation.
- PIE-37159
Users can log in to Integration Server with old and new passwords.
When central user management is configured for Integration Server and an authentication cache is enabled for Integration Server, users can log in with an old password even after successfully log in with the new password. This occurs because Integration Server does not remove the cached entry with the old password until after the time specified in `watt.server.auth.cache.timeout` elapses.
Now, once a user logs in with a new password, Integration Server clears the cached password.
- PIE-37166
Web browser users are not forced to supply credentials after their session expires.
When Integration Server receives a request that includes a cookie that identifies a session and valid user credentials, Integration Server will do one of two things:
 - If the session identified by the cookie is valid, Integration Server will use the existing session for the request.
 - If the session identified by the cookie has expired, or is otherwise invalid, Integration Server will use the supplied credentials to authenticate the client and create a new session for the request.Modern web browsers cache user credentials and send them to servers with each request. For Integration Server Administrator users, this means a user's session may expire but because the browser sends the user's credentials every time, a new session is created and the user may continue to use Integration Server Administrator without re-entering their user name and password. The only way to force the re-entry of a user's credentials is to close the browser. This may be considered a security flaw.
Integration Server addresses this situation by adding a new configuration parameter: `watt.security.session.forceReauthOnExpiration`. When set to true, Integration Server rejects any request that includes a cookie identifying an expired or invalid session, even if the request includes valid user credentials. The rejection response directs the browser to clear its session identifier and to prompt the user for credentials. When set to false, Integration Server creates a new session using the credentials in the cookie. The default value for `watt.security.session.forceReauthOnExpiration` is false. A value of true offers more secure behavior. Changes to

watt.security.session.forceReauthOnExpiration take effect immediately.

- PIE-37211
The pub.flow:getLastError service does not return a lastError document.
The pub.flow:getLastError service does not return a lastError document if a parent SEQUENCE step specifies a timeout value but a service called by an INVOKE step within the SEQUENCE causes the SEQUENCE to time out.
This issue is now resolved.
- PIE-37222
A signed XML document or a node in an XML document fails verification performed by the pub.security.xml:verifyXML service.
If the pub.security.xml:signXML service signs an XML document or a node in an XML document and the service input specifies "true" for the includeCertChain parameter or a value other than the default value "X509_CERTIFICATE" for the certData parameter, the resulting signed document fails verification performed by the pub.security.xml:verifyXML service.
This issue is resolved.
- PIE-37276
After migrating a consumer web service descriptor that uses Web Services Addressing (WS-Addressing) from Integration Server 8.2 to a later release, invoking a web service connector in the descriptor ends with SocketTimeoutException.
If a consumer web service descriptor was created from a WSDL document that declared both the Web Services Addressing namespace as defined in the World Wide Web Consortium (W3C) Recommendation and the namespace from the earlier W3C Submission, after migration from Integration Server 8.2, execution of a web service connector fails with the following:
java.net.SocketTimeoutException: Read timed out
The timeout occurs because Integration Server incorrectly uses the WS-Addressing namespace from the earlier W3C Submission of WS-Addressing when executing the web service connector. As a result, the web service provider does not respond in the expected manner which causes the request to time out.
Now, if a web service descriptor that uses WS-Addressing was created from a WSDL that declared namespace declarations for the WS-Address Recommendation and the Submission, Integration Server uses the namespace declarations defined in the Recommendation.
- PIE-37473
Package deployment fails when the package contains a document type.
Using Deployer to deploy a package that contains a publishable document type fails with the following error:
[DEP.0005.0326] An error occurred while deploying package "packageName". Item "documentTypeName" could not be loaded because of reason "[ISS.0026.9112] Document type documentTypeName has failed to load. Duplicate Broker document type name brokerDocumentTypName is also referenced by documentTypeName". The package may have partially loaded; please check your target server.
This issue is now resolved.

- PIE-37508
Integration Server logs an erroneous exception when executing web services without an outbound callback service.
When executing web service that is part of a provider web service descriptor for which an outbound callback service is not specified, Integration Server sometimes writes the following erroneous message to the error log:
ISC.0088.9998E Exception --> null.
This issue is now resolved. Integration Server no longer logs an exception when executing a web service that is part of a web service descriptor that does not specify an outbound callback service.
- PIE-37589
XSLT services experience intermittent XSLT transformation errors or exhibit slow transformation performance.
This fix addresses both issues.
- PIE-37790
Enhancement to use Universal Messaging for audit logging queues.
In asynchronous audit logging, Integration Server first writes a log entry to a queue and subsequently writes the log entry from the queue to the log destination. Previously, Integration Server provided only an internal queue, sometimes called the light-weight queue, to use as an audit logging queue. With this enhancement, Integration Server provides the option of using a Universal Messaging queue instead of the internal queue as the audit logging queue. Using Universal Messaging with audit logging offers increased performance for asynchronous and synchronous logging.
- PIE-37834
When using the jcode utility to compile Java services, Integration Server generates wrong jcode utility classpath.
When using the jcode utility to compile Java services, Integration Server generates wrong jcode utility classpath if the code or classes directory added to the classpath does not include path separator.
This issue is now resolved.
- PIE-37977
A web service connector throws a SOAPException about an invalid envelope.
When executing a web service connector for an InOnly or InOnlyRobust operation for which the parent consumer web service descriptor has the Pre-8.2 compatibility mode property set to true, Integration Server may log the following extraneous error message indicating an invalid SOAP Envelope has been received even though the connector executed successfully.
[ISS.0088.9155] this SOAPMessage does not contain a valid Envelope object
This fix eliminates the extraneous error message.
- PIE-38099
A trigger with an AND join fails when receiving messages concurrently across a cluster of Integration Servers or a non-clustered group of Integration Servers.
When a JMS trigger or a webMethods messaging trigger with an AND join receives messages at the

same time on two different Integration Servers, one of the messages might be lost. The lost message will not be processed which prevents the AND join from being satisfied and causes the trigger to fail. This situation occurs when the trigger resides on Integration Servers in a cluster or on a group of non-clustered Integration Servers.

This issue is now resolved.

- **PIE-38134**
Enhancement to provide the ability to configure the allowed protocols for JSSE on a per port basis. In Integration Server, the `watt.net.jsse.server.enabledProtocols` server configuration parameter specifies the allowed protocols for all JSSE ports. However, there might be times where you wish to allow specific protocols for use with a particular JSSE port only. Integration Server now provides the ability to specify the allowed protocols for JSSE on a per port basis.
Note: The 'jsseEnabledProtocols' value specified for the port record in the `listeners.cnf` file overrides the value set by `watt.net.jsse.server.enabledProtocols` server configuration parameter.
Note: When the logging facility 0006 Server SSL Interface is set to the Debug logging level, Integration Server writes messages about protocols used for inbound and outbound ports to the server log. At the Trace logging level, Integration Server writes messages about the enabled cipher suites. You can use these server log messages to confirm the enabled protocols for any JSSE port.
- **PIE-38158**
The `pub.utils.messaging:migrateDocTypesTriggersToUM` service incorrectly returns a message indicating a filter was successfully converted.
When the `pub.utils.messaging:migrateDocTypesTriggersToUM` service cannot convert a filter for a `webMethods` messaging trigger because of a filter conversion error, the service returns the error message in the `failedTriggers/reason` parameter. However, the service also returns a message stating that the filter was successfully converted, which is not correct.
If a filter cannot be converted successfully, the `pub.utils.messaging:migrateDocTypesTriggersToUM` no longer returns a message about successful conversion of the filter.
- **PIE-38244**
Web service fails with a `RampartException` while handling a holder-of-key SAML assertion. When handling a holder-of-key SAML assertion, a web service fails with the following exception:
`RampartException: Invalid signature algorithm for Asymmetric binding.`
This issue is now resolved.
- **PIE-38300**
A concurrent JMS trigger makes a retry attempt after Integration Server suspends the trigger because of a transient error.
When a concurrent JMS trigger encounters a transient error when processing a message, the trigger makes an extra retry attempt after the trigger is suspended. For example, if Max retry attempts is 3, Integration Server suspends the trigger after the third retry attempt fails. However, the trigger makes a fourth retry attempt.
This issue is resolved. When Integration Server suspends a concurrent JMS trigger because of a transient error, the trigger does not make an additional retry attempt.

- PIE-38391

In a clustered environment, Integration Server sometimes does not create child tasks when a new server is added to the cluster or when an existing server is restarted.

When a task is scheduled to run on all servers in a clustered environment, Integration Server creates a parent task and a child task for each server in the cluster. When a new server is added to the cluster or when an existing server in the cluster is restarted, Integration Server creates a corresponding child task upon server restart. However, Integration Server sometimes does not create the child task for the newly added server or for the server that was restarted. As a result, the complete information for all servers in the cluster is not available on the Scheduler screen. This issue is resolved.
- PIE-38404

Integration Server resumes document retrieval and/or processing for webMethods messaging triggers after package reload or server restart even when the Apply Change Permanently option was selected.

When using the Integration Server Administrator or the built-in services for suspending document retrieval and/or processing for a webMethods messaging trigger that receives documents from Universal Messaging, Integration Server does not honor the value of the Apply Change Permanently check box. When selected, the Apply Change Permanently check box indicates that Integration Server persists the change in document retrieval or document processing across package reloads and server restart. However, Integration Server reverts the state and enables retrieval and/or processing of documents when Integration Server restarts or when a package is reloaded. This issue is resolved.
- PIE-38473

While creating an Enterprise Gateway Server port that uses the HTTPS protocol, the 'Use JSSE' option is not available in the Edit Enterprise Gateway Server Configuration screen in Integration Server Administrator.

This issue is resolved. The 'Use JSSE' option is now available in the Edit Enterprise Gateway Server Configuration screen while creating an Enterprise Gateway Server port that uses the HTTPS protocol.
- PIE-38526

When creating an Internal Server port that uses the HTTPS protocol, the "Use JSSE" option is not available in the Edit Internal Server Configuration screen in Integration Server Administrator. This issue is resolved. The Edit Internal Server Configuration screen now includes the "Use JSSE" option when the selected protocol is HTTPS.
- PIE-38530

An HTTPS port that uses JSSE fails to start when a keystore is specified.

If Use JSSE is set to Yes for an HTTPS port and the key alias password is different from the password used for the keystore, the port does not start. This issue is now resolved.
- PIE-38536

The `pub.client:smtp` service completes successfully even though the service finishes with errors. Improper exception handling allowed the `pub.client:smtp` service to execute successfully even though the service encountered errors. This could lead to missing MIME parts in the email sent by the service.

Now, the `pub.client:smtp` service includes proper exception handling, which prevents successful completion of the service when the service encounters errors.

- **PIE-38557**
When entering quiesce mode, Integration Server writes messages to the client-side queue because Integration Server disables connection aliases before disabling packages.
When Integration Server enters quiesce mode, Integration Server disables the `webMethods` messaging connection aliases and JMS connection aliases before disabling packages. As a result, services that publish messages might execute after the needed connection alias is disabled, causing messages to be written to the client-side queue.
Now, when entering quiesce mode, Integration Server disables packages before disabling connection aliases. This will prevent new messages from being written to the client-side queue as Integration Server enters quiesce mode.
- **PIE-38660**
The `jcode` utility does not scan the jar files present in the static folders of the packages.
The jar files present in the static folders of the packages (package's code\`jars`\static folders) were not being scanned and added to the classpath by the `jcode` utility.
This issue is resolved.
- **PIE-38881**
When migrating from Integration Server 8.2 or later to a newer version of Integration Server, the migration utility overwrites server configuration parameter values set during an earlier migration. If you migrated Integration Server from version 7.x to version 8.2 or later and the later version introduces new behavior for existing functionality, the migration utility prompts you to choose the new behavior or the existing behavior and then sets a server configuration parameters in the `server.cnf` accordingly. When you migrate Integration Server from 8.2 or later to a newer version of Integration Server, the migration utility prompts to use the new or existing behavior for existing functionality that was changed in the new version. However, the Integration Server migration utility incorrectly overwrites some of the settings that were already set during earlier migrations. This issue is now resolved. Integration Server migration utility retains previously selected behavior and sets server configuration parameters for behavior introduced in the new version only.
- **PIE-38921**
Setting the `watt.server.db.connectionCache` server configuration parameter to `server` increases the number of database connections.
Setting the `watt.server.db.connectionCache` server configuration parameter to `server` tells Integration Server to maintain a pool of connections for each database. However, when a connection became stale, a new connection was getting created without the stale connection getting closed. This increased the number of connections even though the pool reached its maximum number of connections.
This issue is resolved. Integration Server now closes all the stale connections before creating new

connections.

Release 9.9

- PIEAR-616 (WAR_9.5_SP1_Fix5, WAR_9.7_Fix1)
The change in status of an adapter listener is not displayed in Integration Server Administrator if you query the listener using an existing search filter.
In Integration Server Administrator, if you query an adapter listener using an existing search filter, the status of the listener is not refreshed and the current status of the listener is not displayed correctly.
This issue is resolved. The status of an adapter listener is now refreshed on access to display the correct status using an existing search filter.

Release 9.8

- PIE-31623 (IS_7.1.2_Core_Fix47, IS_7.1.3_Core_Fix27, IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3, IS_9.7_Core_Fix1)
Sessions on remote servers are reused by different users. When Integration Server is acting as an HTTP client, it retains the HTTP cookies from the remote server. If two users connect to the same remote server, they use the same set of cookies. Since the session ID is often stored in a cookie, this can result in the two users using the same session on the remote server. Each user should use a unique session when connecting to a remote server.
This issue is resolved. HTTP cookies are now associated with a specific user as well as the remote server so that a separate set of cookies are used for each user.
- PIE-31372 (IS_7.1.3_Core_Fix27, IS_9.0_SP1_Core_Fix7, IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
Secure LDAP connections fail when running Integration Server on HP-UX.
When running Integration Server on HP-UX, configuring LDAP connections using SSL fails because the default secure random algorithm in the Entrust library fails with an exception.
This issue is resolved. Integration Server introduces the new `watt.net.ssl.randomAlgorithm` server configuration parameter to identify the random algorithm name. The default is `FIPS186_2usingSHA1`. If you change the setting of this parameter, you must restart Integration Server for the changes to take effect.
- PIE-34054 (IS_7.1.3_Core_Fix27, IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
Remove use of SSLv3 from any HTTPS or FTPS Integration Server ports.
In order to protect against POODLE vulnerability (CVE-2014-3566), this fix exposes server configuration parameters that allow you to disable the use of SSLv3.0 on Integration Server HTTPS and FTPS ports.

Depending on whether connections use the Entrust library (`entoolkit.jar`) or JSSE (where `useJSSE=true`), you use a different procedure to disable SSLv3.0. Follow the appropriate procedure as follows:

For connections that use Entrust (`entoolkit.jar`) library:

When Integration Server uses the Entrust library to handle inbound and outbound requests, you disable SSLv3.0 by setting the following server configuration parameters:

- watt.net.ssl.server.handshake.minVersion
- watt.net.ssl.server.handshake.maxVersion

Possible values for these server configuration parameters are "sslv3" and "tls" (the default). With this fix, these two parameters take the default value "tls", which indicates that all server side SSL listeners will support only TLSv1 and no longer accept SSLv3 connections.

When Integration Server acts as a client and makes an outbound request, it configures the allowed protocols using the following server configuration parameters:

- watt.net.ssl.client.handshake.minVersion=sslv2
- watt.net.ssl.client.handshake.maxVersion=tls

Possible values for these server configuration parameters are "sslv2", "sslv3", and "tls". If you want to disable the use of "sslv3", set watt.net.ssl.client.handshake.minVersion as follows:

```
watt.net.ssl.client.handshake.minVersion=tls
```

To change the values of the server configuration parameters, from Integration Server Administrator, navigate to Settings > Extended and add the parameters as follows:

```
watt.net.ssl.server.handshake.minVersion=tls  
watt.net.ssl.server.handshake.maxVersion=tls  
watt.net.ssl.client.handshake.minVersion=tls  
watt.net.ssl.client.handshake.maxVersion=tls
```

If any of your clients require SSLv3 to connect (the previous default), set watt.net.ssl.server.handshake.minVersion as follows:

```
watt.net.ssl.server.handshake.minVersion=sslv3
```

When making outbound connections, you can configure Integration Server to first try to connect using sslv3 and, if that fails, to use tlsv1, set watt.net.ssl.client.handshake.minVersion as follows:

```
watt.net.ssl.client.handshake.minVersion=sslv3
```

This will allow Integration Server to use sslv3 with endpoints that do not support tlsv1.

For connections that use JSSE (where useJSSE=true):

When Integration Server uses JSSE to handle inbound and outbound requests, you disable SSLv3.0 by setting the following server configuration parameters:

- watt.net.jsse.server.enabledProtocols
- watt.net.jsse.client.enabledProtocols

Possible values for these server configuration parameters are a comma-separated values consisting of one or more of the following:

- SSLv2Hello
- SSLv3
- TLSv1
- TLSv1.1
- TLSv1.2

With this fix, watt.net.jsse.server.enabledProtocols and watt.net.jsse.client.enabledProtocols are set to the default value of "TLSv1,TLSv1.1,TLSv1.2", which indicates that all server side SSL listeners and client side outbound connections that use JSSE will not accept any SSLv3 or SSLv2 connections.

To change the values of the parameters, from Integration Server Administrator, navigate to Settings > Extended and add the parameters as follows:-

```
watt.net.jsse.server.enabledProtocols=TLSv1,TLSv1.1,TLSv1.2
```

watt.net.jsse.client.enabledProtocols=TLSv1,TLSv1.1,TLSv1.2

Note: These values are case-sensitive. Specify the values exactly as shown.

If any of your clients need to connect using SSLv3, add SSLv3 to

watt.net.jsse.server.enabledProtocols, for example:

watt.net.jsse.server.enabledProtocols=TLSv1,TLSv1.1,TLSv1.2,SSLv3

When starting JSSE ports, at DEBUG level of logging facility 6 (Server SSL Interface), Integration Server logs a message to indicate what protocols are enabled for each JSSE port.

- PIE-34463 (IS_7.1.3_Core_Fix27, IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
When you invoke the pub.client:http service, Integration Server does not create a new session when the newSession parameter is set to yes.
This issue is resolved.
- PIE-33340 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3, IS_9.7_Core_Fix1)
While deploying BPM (ProcessModel) assets using webMethods Deployer, Integration Server issues an exception if a specified package does not exist in the source server.
While creating a deployment map and adding it to the target group to deploy BPM (ProcessModel) assets using webMethods Deployer, Integration Server issues a NullPointerException if a specified package does not exist in the source Integration Server.
This issue is resolved. In the above scenario, Integration Server now issues an error message stating that the specified package does not exist in the source server.
- PIE-32686 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
Integration Server returns a 401 Unauthorized error when it receives a request with no authentication scheme specified in the Authorization header.
Requests with no authentication scheme do not conform to the HTTP Authorization header specification. Integration Server versions prior to 8.2 CoreFix 12 did not strictly enforce the HTTP Authorization header specification, so requests from HTTP clients that did not conform to that standard still worked. However, starting with Integration Server version 8.2 CoreFix 12, Integration Server forces requests to have an authentication scheme in the Authorization header.
This issue is resolved. Now, Integration Server treats requests with no authentication scheme in the Authorization header as BASIC authentication requests and performs authentication for valid credentials.
- PIE-32800 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
In certain scenarios, SOAP fault that Integration Server generates includes the hostname and IP address of the endpoint reference.
Upon invoking a web service that does not exist in the Integration Server, the SOAP fault that Integration Server generates includes the hostname and IP address of the endpoint reference in the values specified for fault reasons and actor/role attributes.
This issue is resolved. This fix introduces a new server configuration parameter, watt.server.SOAP.hideEPRHostInFault, to hide the endpoint reference host name and IP address details in the SOAP fault. When this parameter is set to true, Integration Server replaces the host name and IP address with *.* in the SOAP fault. When this parameter is set to false, Integration Server includes the host name and IP address details of the endpoint reference in the SOAP fault. The default value of this parameter is false.

Note: This parameter applies only when the Pre-8.2 compatibility mode property of the web service descriptor is set to false.

- PIE-32920 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
Integration Server returns the wrong error information when the format of an incoming HTTP Authorization header value is invalid.
When Integration Server receives a request whose HTTP Authorization header value is in an invalid format, it returns a 500 Internal Server Error. Integration Server should return a 401 Unauthorized Error.
This issue is resolved.
- PIE-33354 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2) Integration Server logs an exception in the server logs while invoking web services that has no value set for the Outbound callback service property.
While invoking certain web services, Integration Server logs following message in the server logs: ISC.0088.9998E Exception --> null.
This issue occurs only if no value is set for the Outbound callback service property of the web service descriptor.
This issue is now resolved. Integration Server no longer logs an exception if a value is not set for the Outbound callback service property of the web service descriptor.
- PIE-33421 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
After applying IS_9.0_SP1_Core_Fix6, the Dynamic Server Pages in Integration Server Administrator are not cached.
This issue is resolved. This fix introduces a new server configuration parameter, `watt.cachedirective.exclude.packages` that you can use to specify a comma-separated list of packages whose Dynamic Server Pages you want the browser to cache. You can specify the packages as regular expressions. The asterisk (*) is the only wildcard character allowed in the regular expression. By default, the value of this parameter is empty, meaning none of the Dynamic Server Pages in the Integration Server Administrator are cached.
Note: Software AG recommends that you use `watt.cachedirective.exclude.packages` to cache the Dynamic Server Pages that are related to custom packages only.
Important: If you change the setting of this parameter, you must restart Integration Server for the changes to take effect.
- PIE-31376 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3)
Querying for a user in an LDAP directory results in a "size limit exceeded" error.
When Integration Server is configured to use LDAP for external user management, and Integration Server Administrator is used to query LDAP for a specific LDAP user or group of users, Integration Server retrieves all users from the LDAP directory instead of retrieving only the specified user(s).
This behavior results in the following error in the Integration Server server log:
ISS.0002.0044E Error querying for user(s) on (LDAP server) with search root (LDAP: error code 4 - Sizelimit Exceeded)
This issue is resolved.
- PIE-32725 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3)

In certain scenarios, the entries in the stats.log file become corrupted.
This issue is now resolved.

- PIE-33193 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3)
Even after modifying the database columns to make them wider, Integration Server truncates the length of data in the WMSERVICEACTIVITYLOG.FULLMESSAGE and WMSERVICECUSTOMFLDS.STRINGVALUE columns of the audit logging database. The WMSERVICEACTIVITYLOG.FULLMESSAGE and WMSERVICECUSTOMFLDS.STRINGVALUE columns of the audit logging database are hard-coded in Integration Server to be 1024 characters and 512 characters respectively. When you edit the width of the database columns to make them wider, Integration Server truncates the data to the hard-coded values before writing the data to the database table. This issue is resolved. You can now increase the widths of the WMSERVICEACTIVITYLOG.FULLMESSAGE and WMSERVICECUSTOMFLDS.STRINGVALUE columns in the audit logging database. Now, when the audit records corresponding to the WMSERVICEACTIVITYLOG and WMSERVICECUSTOMFLDS database tables are created during server initialization, Integration Server checks the database to determine the width of the WMSERVICEACTIVITYLOG.FULLMESSAGE and WMSERVICECUSTOMFLDS.STRINGVALUE columns, and sets the length accordingly. Keep the following points in mind when increasing the column widths:
 - The data written to these columns can contain multibyte characters. With multibyte characters, data can be truncated in the middle of a character, which could cause the last character written to the database column to be a character other than the intended character. To avoid this, Integration Server truncates the last character boundary before the maximum length of the field, meaning that the data might be slightly smaller than the maximum value set in the audit logging database.
 - Integration Server checks the database for column width by obtaining the metadata and examining the CHAR_OCTET_LENGTH field of the column. If the database vendor does not supply a CHAR_OCTET_LENGTH value for the column, Integration Server uses the hard-coded default lengths for the fields as follows:
 - WMSERVICEACTIVITYLOG.FULLMESSAGE = 1024
 - WMSERVICECUSTOMFLDS.STRINGVALUE = 512Integration Server introduces the following new server configuration properties:
 - The watt.server.audit.schemaName server configuration parameter specifies the user name of the ISCoreAudit JDBC functional alias. By default, Integration Server uses the user name from the ISCoreAudit JDBC functional alias.
 - The watt.server.audit.dbEncoding server configuration parameter specifies the character set that the audit logging database uses. The default is UTF-8. The value for this property must be a standard IANA-assigned character set name, as defined on <http://www.iana.org/assignments/character-sets>.If you change the setting of either of these server configuration parameters, you must restart Integration Server for the changes to take effect.
- PIE-33250 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3)
Settings within a package's node.ndf files are changed after the package is compiled during a repository-based deployment. When a package is deployed to a target Integration Server using webMethods Deployer, and the

Compile Package on Install global value is set to true, Integration Server performs a fragmentation step during compilation of the package. This step creates new node.ndf files for any Java services contained in the package. As a result, any settings previously defined in the node.ndf files are lost. This issue is resolved. This fix introduces a new global property - fragPackage (Fragment Package on Install), for package assets. A value of true indicates that you want to allow Integration Server to perform the fragmentation step and overwrite a package's node.ndf files when the package is compiled on the target server. A value of false indicates that you want to prevent the server from performing the fragmentation step, thereby preserving custom settings defined in the package's node.ndf files when the package is compiled on the target server. The default is true.

- PIE-33256 (IS_9.0_SP1_Core_Fix7, IS_9.6_Core_Fix3) Integration Server gives the datatype of the returnCode output parameter of the pub.client.sftp* services incorrectly as integer instead of correctly specifying it as string.
This issue is now resolved. The returnCode output parameter of the pub.client.sftp* services is now updated to string datatype.
- PIE-32235 (IS_9.0_SP1_Core_Fix7) Integration Server thread dump indicates a deadlock state between webMethods Broker polling and synchronization threads when Broker disconnects while a publishing event is in progress.
The BrokerPoller thread, which determines Broker's connection status, and the BrokerSynchronizer thread, which synchronizes documents between Integration Server and Broker, may become deadlocked. This can happen when Broker disconnects and/or reconnects while Integration Server is publishing a document to Broker.
This issue is resolved. Integration Server now prevents deadlocks from occurring between the two threads.
- PIE-32458 (IS_9.0_SP1_Core_Fix7)
Integration Server support for using user-defined prefixes with the document types created when creating or refreshing a consumer web service descriptor or a WSDL first provider web service descriptor.
This fix contains the server-side functionality required to support the Designer functionality described in WED-4598 which is available in a webMethods Service Development fix. Together, PIE-32458 and WED-4598 provide the ability to associate user-defined prefixes with the namespaces used in document types instead of the prefixes defined in the schema contained in or referenced by a WSDL document used as the source for a web service descriptor. For more information about this functionality, see the readme file for the webMethods Designer Service Development fix. For webMethods Service Development 9.6, WED-4598 is available in ESB_9.6_Fix2.
Note: The ability to refresh a web service descriptor is available in Integration Server and webMethods Service Development versions 9.0 SP1 and later.
- PIE-32990 (IS_9.0_SP1_Core_Fix7)
Copying and pasting Integration Server packages from one server to another results in a "no such remote server" error.
When a package is copied from an Integration Server and pasted to a remote Integration Server using Software AG Designer, the following error message is displayed in the server log:(ISS.0085.9102) No such remote server

This occurs even when the target server is running normally and has a valid remote server alias. This issue is resolved.

- PIE-32895 (IS_9.0_SP1_Core_Fix8, IS_9.5_SP1_Migration_Fix1, IS_9.6_Core_Fix3, IS_9.6_Migration_Fix2)
Integration Server issues a java.lang.NullPointerException error while migrating from Integration Server version 8.0 SP1 to Integration Server version 9.0 SP1 or 9.5 SP1 in a different installation directory.
This issue is now resolved.
- PIE-30419 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix3, IS_9.7_Core_Fix1)
Editing the connection details of a remote Integration Server does not work as expected. After a remote Integration Server connection is created and a successful connection is established, if the remote server connection settings are changed (for example, if a different port number is specified), Integration Server does not create a new session when subsequent connection attempts are made. As a result, Integration Server Administrator indicates that subsequent connections are successful, even if the revised remote server settings are incorrect (for example, if the revised port number is not valid).
This issue is resolved.
- PIE-32999 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix3, IS_9.7_Core_Fix1)
After applying a fix containing PIE-30630 or when using Integration Server 9.7, if Platform Manager is in use, Integration Server can have a high number of active stateful sessions. The number of active stateful sessions becomes high because sessions created by the Platform Manager were not being cleaned up upon disconnect but were not being removed from memory until the session time out limit elapsed. This issue was introduced by PIE-30630 which is included in Integration Server 9.7, IS_8.2_SP2_Core_Fix13, IS_9.0_SP1_Core_Fix6, IS_9.5_SP1_Core_Fix3, IS_9.6_Core_Fix1, and IS_9.6_Core_Fix2.
Integration Server now removes a session created by the Platform Manager from memory at the time the Platform Manager disconnects.
- PIE-31474 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
Integration Server creates additional session threads while executing triggers and displays a misleading expiration value. When `watt.server.trigger.reuseSession` (for Broker/local triggers in Integration Server version 9.0 SP1 and earlier or `webMethods` messaging triggers in version 9.5 SP1 and later) or `watt.server.jms.trigger.reuseSession` (for JMS triggers) is set to false, Integration Server displays an additional session thread for the trigger. In addition, regardless of the values set for `watt.server.trigger.reuseSession` and `watt.server.jms.trigger.reuseSession` server configuration parameters, Integration Server Administrator displays the session on the Server > Statistics > Session screen with a Session Expires value of 9223372036854775807 and the session never expires. This issue is resolved. When either the `watt.server.trigger.reuseSession` or `watt.server.jms.trigger.reuseSession` server configuration parameter is set to false, Integration Server no longer creates extra sessions for the respective trigger. For these sessions, Integration Server Administrator displays “upon service completion” in the Session Expires column on the Server > Statistics > Sessions screen for trigger-related sessions. This indicates that the session will

remain until the service executed by the trigger finishes. Once the service finishes, Integration Server removes the session.

When either the `watt.server.trigger.reuseSession` or `watt.server.jms.trigger.reuseSession` server configuration parameter is set to true, Integration Server shares one session for each execution of the trigger. In this case, Integration Server Administrator displays a value of "never" in the Session Expires column of the Server > Statistics > Sessions screen and the session does not expire.

- PIE-33336 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
In case of web services, Integration Server does not keep the undeclared namespaces in the resulting document (IData), when the endpoint service is invoked.
If an XML element that is part of a SOAP Message has elements with attributes containing undeclared namespaces, Integration Server does not keep the undeclared namespaces in the resulting document (IData), when the endpoint service is invoked.
This issue is resolved. The generated IData now includes the undeclared namespace definitions.
Note: In case of web services, the undeclared namespace functionality is available only if the datatype of the document is of type 'Object'.
- PIE-33632 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
The service results cache does not delete expired elements from Ehcache.
Expired service results remain in Ehcache even after the cache sweeper thread runs.
This issue is resolved.
- PIE-33376 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix3)
Integration Server issues a NullPointerException when it receives an HTTP request with no User-Agent header.
This issue is resolved.
- PIE-33601 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
Integration Server is unable to process incoming XML files if the XML files contain non-English characters, such as Greek or Japanese.
While processing an incoming XML file, Integration Server uses the charset encoding defined in the XML header. If the encoding is not defined in the XML header, Integration Server processes the XML file using the charset encoding of the request or the character encoding specified in the `watt.server.fileEncoding` server configuration parameter. However, after migrating to higher versions, using the character encoding specified in `watt.server.fileEncoding` parameter to process an incoming XML file causes Integration Server to return garbled messages.
This issue is resolved. To resolve this issue, this fix introduces a new server configuration parameter, `watt.server.xml.encoding`, that specifies the encoding that Integration Server must use when processing incoming XML files.
If an encoding is not defined in the XML header, Integration Server attempts to process the XML file using the charset encoding of the http or ftp request. If charset encoding is not available in the request header, then Integration Server uses the character encoding specified in the `att.server.xml.encoding` server configuration parameter. There is no default value for this parameter. You must restart Integration Server for changes to this parameter to take effect.
Note: If you have configured Integration Server to use the character encoding specified in the `watt.server.fileEncoding` parameter to process incoming XML files, after installing this fix or after

upgrading to a higher version of Integration Server, ensure that the value of `watt.server.fileEncoding` parameter is set to the same value specified for `watt.server.xml.encoding`. If you have not configured `watt.server.fileEncoding` for processing XML files previously, after installing this fix or after upgrading to a higher version of Integration Server, you can configure `watt.server.xml.encoding` to process incoming XML files. You can use `watt.server.fileEncoding` to process all files other than incoming XML files.

- PIE-33615 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
Integration Server is unable to parse incoming XML files if the XML files contain non-English characters, such as Greek or Japanese.
While processing an incoming XML file, Integration Server uses the charset encoding defined in the XML header. If the encoding is not defined in the XML header, Integration Server parses the XML file using the charset encoding of the request or the character encoding specified in the `watt.server.fileEncoding` server configuration parameter. However, after migrating to higher versions, using the character encoding specified in `watt.server.fileEncoding` parameter to process an incoming XML file causes Integration Server to return garbled messages.
This issue is resolved. To resolve this issue, this fix introduces a new server configuration parameter, `watt.server.xml.encoding`, to specify the encoding that Integration Server must use when processing incoming XML files.
If an encoding is not defined in the XML header, Integration Server attempts to process the XML file using the charset encoding of the http or ftp request. If charset encoding is not available in the request header, then Integration Server uses the character encoding specified in the `watt.server.xml.encoding` server configuration parameter. There is no default value for this parameter. You must restart Integration Server for changes to this parameter to take effect.
Note: If you have configured Integration Server to use the character encoding specified in the `watt.server.fileEncoding` parameter to process incoming XML files, after installing this fix or after upgrading to a higher version of Integration Server, ensure that the value of `watt.server.fileEncoding` parameter is set to the same value specified for `watt.server.xml.encoding`.
- PIE-33637 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
Integration Server generates an invalid WSDL document if it encounters identically named elements that are declared to be of different types but belonging to the same target namespace. When generating the WSDL document, if Integration Server encounters identically named elements that are declared to be of different types but belonging to the same target namespace, Integration Server cannot correctly represent this in a WSDL document. Instead, when generating the WSDL document, Integration Server replaces the element declaration it creates for the identically named element first with the element declaration that it generates last.
With this fix, when creating a service first web service descriptor, Integration Server issues a warning message stating that the element declaration it creates for the identically named element first is replaced with the element declaration that it generates last.
- PIE-33762 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
The `pub.cache.atomic:putIfAbsent` and `pub.cache.atomic:replaceIfKeyExists` services show the incorrect data type for the `oldValue` output parameter.
The `pub.cache.atomic:putIfAbsent` and `pub.cache.atomic:replaceIfKeyExists` services display the `oldValue` output parameter as a String data type, but should display the data type as Object.

This issue is resolved.

- PIE-33799 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)

When running flow services in debug mode, Integration Server cannot retrieve parent service information from a calling child service.

Integration Server cannot retrieve the parent service information from a calling child service in debug mode.

This issue is resolved. Integration Server introduces the new public service `pub.flow:getCallingService` that can be invoked from the calling child service and returns the service and package name of the parent service. The `pub.flow:getCallingService` service returns the following output parameters:

- `svcName` - String (optional) Fully qualified namespace name of the parent service.
- `pkgName` - String (optional) Package name of the parent service.

If `pub.flow:getCallingService` is invoked from a service that does not have a parent service (for example, if the service is a top level service), Integration Server does not return the output parameters.

- PIE-33938 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)

Integration Server continues to execute a flow service even after global variable substitution fails.

When a flow service expects an input through global variable substitution and if the expected global variable does not exist, Integration Server displays an error message and continues executing the flow service instead of stopping the service execution.

The issue is resolved. If the global variable that a flow service expects does not exist, Integration Server displays an error message and stops the flow service execution.

- PIE-34080 (IS_9.0_SP1_Core_Fix8, IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
 Adding an HTTP or HTTPS port in the Integration Server Administrator results in a blank Security > Ports screen.
 When the server configuration parameter `watt.server.http.listRequestVars` is set to "error" and a new HTTP or HTTPS port is added, Integration Server returns a blank Security > Ports screen and writes the following message to the server log:
 (ISC.0038.2) Duplicate query tokens found in URI: threadPool
 This issue is resolved.
- PIE-33821 (IS_9.0_SP1_Core_Fix8)
 The `watt.server.SOAP.hideEPRHostInFault` server configuration parameter is not available in the Extended Settings page in Integration Server Administrator.
 This issue is resolved. The `watt.server.SOAP.hideEPRHostInFault` server configuration parameter now appears in the Extended Settings page.
- PIE-32771 (IS_9.6_Core_Fix3, IS_9.7_Core_Fix1)
 JMS provider connection attempts are refused during the processing of messages.
 When a trigger service uses a transacted JMS connection alias, and that service sends JMS messages using the `pub.jms:send` service to a different transacted connection alias, the sessions on the JMS provider are not closed. As a result, connection attempts are refused because channel and process limits are reached.
 This issue is resolved.
- PIE-33468 (IS_9.6_Core_Fix3, IS_9.7_Core_Fix1)
 Web service descriptor does not use user-defined prefixes for fault and handler document types.
 When creating a consumer web service descriptor or a WSDL first provider web service descriptor, the user creating the web service descriptor can specify namespace prefixes to replace the prefixes used in the WSDL document. However, Integration Server was not using the user-defined prefixes for the IS document types generated for fault or handlers messages.
 This issue is now resolved.
- PIE-33531 (IS_9.6_Core_Fix3, IS_9.7_Core_Fix1)
 After installing a newly generated license file for Terracotta, Integration Server disables editing for BigMemory settings.
 The issue occurs because of a parsing error in the license file.
 This issue is resolved.
- PIE-33660 (IS_9.6_Core_Fix3, IS_9.7_Core_Fix1)
 Integration Sever does not acknowledge all of the messages received in a batch by a JMS trigger.
 When a standard JMS trigger receives and processes a batch of messages from the JMS provider, the JMS trigger should acknowledge the last message received in the batch. This results in acknowledgement of all the messages received in the batch. However, the JMS trigger currently acknowledges the first message received in a batch instead of the last which causes several messages to be unacknowledged.
 Now, a JMS trigger that performs batch processing acknowledges the last message in the batch.

- PIE-33552 (IS_9.6_Core_Fix3, IS_9.7_Core_Fix2)
 The pub.client:http service fails with an access denied HTTP response if the url input parameter contains special characters.
 If the encoded value of the url input parameter of the pub.client:http service contains hexadecimal characters that are greater than 7f, the authorization information for the resource specified in the url parameter is not submitted by the http service. As a result, the pub.client:http service fails with the following error:
 (ISC.0064.9314) Authorization Required: (ISS.0084.9004) Access Denied
 This issue is resolved.
- PIE-33498 (IS_9.6_Core_Fix4, IS_9.7_Core_Fix2) Integration Server generates an invalid WSDL document if it encounters identically named elements that are declared to be of different types but belonging to the same target namespace.
 When generating a WSDL document, if Integration Server encounters identically named elements that are declared to be of same type and belonging to the same target namespace, Integration Server issues a warning message stating that the element declaration it creates for the identically named element first is replaced with the element declaration that it generates last. Integration Server must do this only in case of identically named elements that are declared to be of different types but belonging to the same target namespace.
 This issue is resolved. Integration Server now issues a warning message only if the identically named elements are declared to be of different types but belonging to the same target namespace.
- PIE-33539 (IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
 Wrong message type identifier assigned to some messages of "0088 SOAP" server log facility. Integration Server assigns I (Info) as the message type identifier, instead of D (Debug), to some messages of "0088 SOAP" server log facility. As a result, there are discrepancies in the list of log messages displayed in the Logs > Server page of the Integration Server Administrator when Integration Server receives SOAP requests.
 The issue is resolved. The log messages of "0088 SOAP" server log facility now have the correct message type identifier.
- PIE-33764 (IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
 Wrong port shown in Mediator WSDL if multiple ports are configured in Integration Server. If a HTTP or HTTPS port is defined in Integration Server's Security > Ports page and added in the selected ports section in Solutions > Mediator > Administration > General page, the non-primary port with the lowest port number should be shown for the virtual service endpoint deployed in Mediator. However, Integration Server randomly chooses a port and makes the port available to the Mediator WSDL.
 This issue is resolved. The virtual service WSDL in Mediator will now see the non-primary port with the lowest port number if multiple ports are configured for Mediator in Integration Server.
- PIE-33811 (IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)
 Integration Server becomes unresponsive while processing requests from a JMS provider. In certain circumstances, thread cleanup tasks performed during the processing of JMS messages fail to release the lock on an object. Other server threads that need that object go into a wait state, which eventually causes the server to become unresponsive.

This issue is resolved.

- PIE-33886 (IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)

The `pub.flow:getLastError` service does not return any results when the invoke step of a flow service reaches its timeout threshold.

When a parent flow service (service A) invokes a child flow service (service B) with the Timeout parameter specified at the invoke step, and the child flow service invokes another flow service (service C), and timeout is triggered, `pub.flow:getLastError` in parent flow service (service A) returns no error information.

This issue is resolved. When you invoke the `pub.flow:getLastError` service in the parent flow service (service A), the parent flow service returns the `lastError` output parameter as an `errorType` element with a value of `"com.wm.lang.flow.FlowTimeoutException"`.

- PIE-34051 (IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)

Integration Server Administrator displays the number of completed requests over the lifetime of the Integration Server in the Current column on the Statistics screen.

Integration Server Administrator displays the number of completed requests in two columns in the Requests area of the Statistics screen: Current and Lifetime. The Current column should display the number of requests in the last polling period, and the Lifetime column should display the number of completed requests over the lifetime of the Integration Server. Instead, the Current column displays the number of requests over the lifetime of the Integration Server, and the Lifetime column does not display any value. In addition, Integration Server Administrator does not properly display the Average Time row.

This issue is resolved.

- PIE-34109 (IS_9.6_Core_Fix4, IS_9.7_Core_Fix2)

Integration Server does not honor the `watt.server.control.triggerInputControl.delays` or `watt.server.control.triggerInputControl.delayIncrementInterval` values.

When the values for `watt.server.control.triggerInputControl.delays` or `watt.server.control.triggerInputControl.delayIncrementInterval` are changed, Integration Server saves but does not use the specified values if an exception occurred when parsing the supplied values. Regardless of which parameter value caused the parsing error, Integration Server uses the default values for both parameters. However, there was no log message or other type of notification to inform the user that the default values would be used instead.

Now, Integration Server logs the following message if it cannot parse the values of the `watt.server.control.triggerInputControl.delays` or `watt.server.control.triggerInputControl.delayIncrementInterval` parameters:

```
ISS.0125.0015W
```

The trigger input control parameters,

`watt.server.control.triggerInputControl.delaysIncrementInterval` and

`watt.server.control.triggerInputControl.delays`, were set to their default values because an exception occurred when parsing the supplied values.

Cause

Integration Server could not set the trigger input control configuration parameter

`watt.server.control.triggerInputControl.delaysIncrementInterval` and/or

`watt.server.control.triggerInputControl.delays` to the new value because an exception occurred

when parsing the new value. Integration Server reset both configuration parameters to the default values.

Action

Use a valid value for the `watt.server.control.triggerInputControl.delaysIncrementInterval` or `watt.server.control.triggerInputControl.delays` parameter.

- **PIE-32407 (IS_9.7_Core_Fix2)**
While using the `pub.schema:validate` service to validate an object, Integration Server considers a string ending with a decimal point to be a valid long data type.
While validating an object using the `pub.schema:validate` service, Integration Server considers a string ending with a decimal point (for example, `<longType>5.</longType>`) to be a valid long data type.
This issue is resolved. Integration Server no longer considers a string ending with a decimal point to be a valid long data type.
- **PIE-33458 (IS_9.7_Core_Fix2)**
Validation of web service request or response fails because of an extraneous `*body` field.
When processing an inbound web service request or response that has an element that contains whitespace only and the associated field in the IS document types is defined as a document with optional children, Integration Server inserts a `*body` field to contain the whitespace. This is incorrect as Integration Server should ignore the whitespace. The presence of the extraneous `*body` field causes validation to fail because the associated IS document type does not contain a `*body` field.
This issue is now resolved.
- **PIE-33583 (IS_9.7_Core_Fix2)**
A thread dump of Integration Server suggests a thread contention issue occurs during the creation of secure outbound connections.
When Integration Server attempts to create multiple secure outbound connections at the same time, only one connection is created and other threads must wait.
This issue is resolved.
- **PIE-33990 (IS_9.7_Core_Fix2)**
An inbound HTTP/S request that includes `access_token` in the query parameters or header fields is rejected and results in an error message in the `security.log` file.
If an inbound HTTP/S request includes `access_token` in the query parameter or header fields, Integration Server performs OAuth authentication, denies the request, and logs the following message in the `security.log` file:
SYSTEM AUTHENTICATION Integration Server rejected the request to access this resource. The access token is either invalid or expired.
To address this issue, Integration Server now includes server parameters to enable or disable OAuth authentication by Integration Server when an inbound HTTP/S request `access_token` in the query parameters or header fields
`watt.server.auth.oauth.accessToken.useHeaderFields`
Specifies whether Integration Server performs OAuth authentication when an inbound HTTP/S request includes an `access_token` in the header fields. Specify `true` to perform OAuth

authentication. Specify false to skip OAuth authentication. The default is true.
For changes to this parameter to take effect, you must restart Integration Server.

watt.server.auth.oauth.accessToken.useQueryParameters

Specifies whether Integration Server performs OAuth authentication when an inbound HTTP/S request includes an access_token in the query parameter. Specify true to perform OAuth authentication. Specify false to skip OAuth authentication. The default is true.

For changes to this parameter to take effect, you must restart Integration Server.

- PIE-34248 (IS_9.7_Core_Fix2)

While using the extended character sets, Integration Server issues a java.io.UnsupportedEncodingException error.

This issue occurs because the wm-converters.jar file, which is required to support extended character sets, is not present in the Integration Server classpath.

To resolve this issue in Integration Server version 9.5 SP1, do the following:

1. Shut down Integration Server.
2. Using a text editor, navigate to and open the following file:
Software AG_directory/profiles/configuration/custom_wrapper.conf
3. Edit the custom_wrapper.conf file by adding the following jar entry:
wrapper.java.classpath.100=Software AG_directory\common\lib\wm-converters.jar
Where <Software AG_Directory> is the installation directory for Software AG products.
4. Save your changes to the custom_wrapper.conf file and then close the file.
5. Start Integration Server.

To resolve this issue in Integration Server versions 9.6 and 9.7, do the following:

1. Shut down Integration Server.
2. Using a text editor, navigate to and open the following file:
Software AG_directory/profiles/IS_instance_name/configuration/custom_wrapper.conf
3. Edit the custom_wrapper.conf file by adding the following jar entry:
wrapper.java.classpath.100=Software AG_directory\common\lib\wm-converters.jar
Where <Software AG_Directory> is the installation directory for Software AG products.
4. Save your changes to the custom_wrapper.conf file and then close the file.
5. Start Integration Server.

- PIE-34323 (IS_9.7_Core_Fix2)

While executing SQL queries, the Integration Server scheduler sometimes leaves the database cursor open, which causes the database cursor to reach its maximum limit.

The issue is now resolved.

- PIE-34330 (IS_9.7_Core_Fix2)

Integration Server returns different results in debug and run modes when an input variable to a MAP step is mapped to an output variable of the same name.

When an input variable to a MAP step is mapped to an output variable of the same name, Integration Server returns different results in debug mode than it does in run mode.

This issue is resolved.

- PIE-34444 (IS_9.7_Core_Fix2)

The pub.client:http service does not consider the Content-Type headers if the data/args and data/table input parameter value is empty.

If the data/args and data/table input parameter value of the pub.client:http service is not null, but empty, Integration Server uses the "application/x-www-form-urlencoded" content type and ignores the specified Content-Type headers.

The issue is resolved, If the data/args and data/table input parameter value of the pub.client:http service is empty, Integration Server now uses the "application/x-www-form-urlencoded" content type only if no Content-Type is specified as the value of input field /headers/Content-Type.
- PIE-34481 (IS_9.7_Core_Fix2)

Integration Server does not use service output templates for JSON requests.

When Integration Server receives a request containing the header "Accept: application/json" and the invoked service has an output template defined, Integration Server does not use the template to create the output.
- PIE-34482 (IS_9.7_Core_Fix2)

Integration Server throws a NullPointerException followed by a SocketTimeoutException.

If Integration Server sends an outbound HTTP request and the request times out before a response is received, Integration Server may throw the following superfluous NullPointerException before throwing a SocketTimeoutException:

```
java.lang.NullPointerException: null
at com.wm.app.b2b.server.ServerThread.removeListener(ServerThread.java:272)
at com.wm.util.lifecycle.LifecycleManager.unregisterLifecycleListener(LifecycleManager.java:103)
at com.wm.app.b2b.server.HTTPMessageHandler.process(HTTPMessageHandler.java:266)
at com.wm.app.b2b.server.HTTPDispatch.handleRequest(HTTPDispatch.java:173)
```

This issue is now resolved.
- PIE-34503 (IS_9.7_Core_Fix2)

The pub.string:bytesToString does not filter the byte order mark (BOM) characters while converting a byte array to string.

This issue is now resolved. This fix introduces a new optional input parameter, ignoreBOMChars, to the pub.string:bytesToString service.

If ignoreBOMChars is set to true and the value of the encoding input parameter is set to UTF-8, UTF-16, or UTF-32, Integration Server will remove the byte order mark (BOM) characters before converting the input byte array to string, if the byte array contains BOM characters.

If ignoreBOMChars is set to false and the value of the encoding input parameter is set to UTF-8, UTF-16, or UTF-32, Integration Server will include the byte order mark (BOM) characters while converting the input byte array to string, if the byte array contains BOM characters. The default is false.
- PIE-34661 (IS_9.7_Core_Fix2)

Integration Server connects to an SFTP server directly while retrieving the public key of an SFTP server, even if the connection between Integration Server and the SFTP server is through a proxy. While defining an SFTP server alias, upon clicking the Get Host Key button to retrieve the public

key of the SFTP server, Integration Server connects to the SFTP server directly even if the connection between Integration Server and the SFTP server is through a proxy.

The issue is now resolved. If the connection between Integration Server and an SFTP server is through a proxy, Integration Server connects to the SFTP server through the proxy while retrieving the public key of the SFTP server.

- PIE-34662 (IS_9.7_Core_Fix2)

When creating an IS schema from an XML document that does not reference a DTD, Integration Server throws a `NullPointerException`.

An IS schema can be created from an XML document only if the XML document references an existing DTD or contains a DTD inline. However, when creating an IS schema from an XML document that does not reference or contain an existing DTD, Integration Server throws a `NullPointerException` instead of a `ServiceError`.

This issue is now resolved.

- PIE-31363

Integration Server Administrator displays facility code 0090 as "Unknown".

On the View Server Logger Details Screen, Integration Server Administrator displays the facility name for code 0090 as "Unknown". The facility name for 0090 should be "pub Flow Services".

This issue is resolved.

- PIE-33148

When creating a WSDL first provider web service descriptor, the Addressing action property in the WSDL does not show up correctly in the web service descriptor.

Upon creating a WSDL first provider web service descriptor from a WSDL document containing the Addressing action property in the `prefix:namespace` format, Integration Server does not include the prefix in the Addressing action property of the newly created WSDL first provider web service descriptor.

The issue is now resolved. The same Addressing action property that is in the WSDL is included in the web service descriptor created from the WSDL.

- PIE-34287

Integration Server does not recycle the `stats.log` file at the correct time.

By default, Integration Server should recycle the `stats.log` file daily at midnight. However, the first time to recycle the `stats.log` file was incorrect. This caused the file to be recycled daily but at the wrong time.

This issue is now resolved. Integration Server now recycles the `stats.log` file daily at midnight.

- PIE-34509

After setting the server configuration property `watt.core.xml.expandGeneralEntities` to `false`, Integration Server does not encode the apostrophe properly.

This issue is now resolved.

- PIE-34627

Integration Server displays an error message when editing a JNDI provider alias if Integration Server Administrator is accessed via Mozilla Firefox or Google Chrome.

Integration Server displays the following error message when attempting to edit any field of a JNDI

provider alias using Integration Server Administrator: JNDI Alias Name must be specified. This issue occurs only if Integration Server Administrator is accessed via Mozilla Firefox or Google Chrome.

The issue is now resolved.

- PIE-34669
When Integration Server is installed as a service, the service is not unregistered when it is uninstalled.
While uninstalling Integration Server that is installed as a service on a Windows operating system, Integration Server does not uninstall the registered service.
This issue is resolved.
- PIE-34898
A scheduled task configured to run on any one of the Integration Servers connected to the same database does not run as expected and fails with an error.
When a scheduled task is configured to run on any of the Integration Servers that are part of a non-clustered group of Integration Servers in which the ISInternal functional alias on each server points to the same database, the scheduled task fails with the following error:
Could not complete last run
This issue is resolved.
- PIE-34899
The pub.client.ftp:get service does not consider files of 0 KB size to be large files even if the largefilethreshold input parameter is set to 0.
If the largefilethreshold input parameter of the pub.client.ftp:get service is set to 0, Integration Server must consider all files to be large files. The output parameter islargefile must be true and the file content must be returned in the output parameter contentstream as a java.io.InputStream object. However, the pub.client.ftp:get service does not behave as expected. The pub.client.ftp:get service does not consider files of 0 KB size to be large files even if the largefilethreshold input parameter is set to 0. The service returns the islargefile parameter as false and the file content is returned in the output parameter content.
This issue is resolved. The pub.client.ftp:get service now considers files of 0 KB size to be large files if the largefilethreshold input parameter is set to 0.
- PIE-35009
Integration Server appears to become unresponsive because of blocked client requests.
An internal component in Integration Server fails to release a lock when it should. Client threads wait indefinitely to acquire the lock, eventually causing requests to block. As result, Integration Server appears to be unresponsive.
This issue has been resolved.
- PIE-35012
At start up, Integration Server resets the persistence strategy of a cache to none.
When Integration Server starts, it resets the default persistence strategy for a cache to “none”.
Integration Server should change the default persistence strategy to “none” only when TerracottaConfiguration is set to “clustered”.

This issue is resolved.

- **PIE-35059**

Integration Server does not display an appropriate error message when an FTP client makes an active connection to the Integration Server FTP port, if there is a port in Integration Server with port number that is one less than the FTP port.

If the FTP port configured in Integration Server is running in active mode and if there is a port in Integration Server with port number that is one less than the FTP port, when the FTP client makes an active connection to the FTP port configured in Integration Server, the connection fails with a `NullPointerException` message.

The issue is resolved. Integration Server now issues the following error message to the FTP client: `Could not create data port <port number>. Try passive mode."`
- **PIE-35143**

After applying `IS_8.2_SP2_Core_Fix13` or higher, deserialization of SOAP messages to `IData` does not work as expected.

After applying `IS_8.2_SP2_Core_Fix13` or higher, while deserializing SOAP messages to `IData`, Integration Server erroneously adds a default namespace prefix of `"xmlns"` to those fields that are contained in an implicit namespace declaration. This results in broken endpoint service field mappings. This issue occurs only when the `Pre-8.2 compatibility mode property` of the web service descriptor is set to `true`.

This issue is now resolved.
- **PIE-35151**

Integration Server logs an `SQLException` during startup.

When Integration Server starts, it uses the schema name to:

 - Access the audit logging database to determine the length of the `WMSERVICECUSTOMFLDS.STRINGVALUE` and `WMSERVICEACTIVITYLOG.FULLMESSAGE` columns. Integration Server uses the lengths to automatically adjust the size of the values inserted into these columns.
 - Retrieve the database metadata.

By default, Integration Server uses the User ID specified in the `ISCoreAudit` functional alias as the schema name for the audit logging database. You can override this value by specifying a value for the `watt.server.audit.schemaName` server configuration parameter. However, if the User ID does not match the schema name specified in `watt.server.audit.schemaName`, Integration Server logs a `SQLException` to the server log.

This issue is resolved. Integration Server no longer uses the User ID of the `ISCoreAudit` functional alias as the default schema name. Now, Integration Server requires that you specify a value for the `watt.server.audit.schemaName` parameter to retrieve the database metadata and resize the audit logging values in the `WMSERVICECUSTOMFLDS.STRINGVALUE` and `WMSERVICEACTIVITYLOG.FULLMESSAGE` columns. If `watt.server.audit.schemaName` is not set, Integration Server does not retrieve the metadata and assumes the lengths of the `WMSERVICECUSTOMFLDS.STRINGVALUE` and `WMSERVICEACTIVITYLOG.FULLMESSAGE` columns are 512 and 1024, respectively.

Note: Some databases are case-sensitive. When specifying the value for `watt.server.audit.schemaName`, you should match the case of the schema name with the schema

name required by the database.

- **PIE-32619**
After fix IS_8.2_SP2_Core_Fix12 is installed, the SOAP response for a migrated web service contains a document instead of a document list.
Before the fix is installed, data elements are formatted in the SOAP response in a document list, as expected. After the fix is installed, these data elements are formatted as separate documents. This change in output structure makes it difficult to map the documents in the flow.
This issue is resolved. The SOAP response is formatted in the same way it was before fix IS_8.2_SP2_Core_Fix12 was installed.
- **PIE-32737**
Deployer fails when deploying a package that contains a new trigger that does not exist in the earlier version of the package on the target Integration Server.
When deploying a package that contains a trigger that does not exist in the same package on the target Integration Server, Deployer fails because the target Integration Server attempts to suspend the trigger that does not exist. Deployment might fail with one of the following messages:
(ISS.0098.9067) Trigger not found for triggerName: "triggerName"
(ISS.0098.9074) Unable to suspend document retrieval for Trigger "triggerName"
Now, when a package containing triggers is deployed to a target Integration Server, the target Integration Server suspends a trigger only after first verifying that the trigger exists on the target Integration Server.
- **PIE-32873**
It takes a long time for Integration Server to stop all JMS triggers once the triggers are disabled. All the JMS triggers on Integration Server can be disabled at the same time when Integration Server is shut down or when Integration Server Administrator is used to disable all JMS triggers. Once disabled, all of the JMS triggers stop receiving messages immediately. However, Integration Server closes the JMS Session and MessageConsumer objects sequentially. Some JMS providers, including WebSphere MQ, may take a second or two to close the objects for each JMS trigger. When many JMS triggers are disabled at once, closing the JMS Session and MessageConsumer objects can take a significant amount of time.
Now, Integration Server stops closes JMS Session and MessageConsumer objects simultaneously instead of sequentially.
- **PIE-33279**
Option to control how Integration Server decodes duplicates of nested elements in an element of type anyType in a SOAP request.
If the input signature of an IS service exposed as a web service contains a document that has a child variable of type object, the object is represented as an element of type anyType. When decoding a SOAP request for the service, Integration Server places duplicate elements in line in the resulting IData. However, some users want Integration Server to create an array for the duplicate elements in the resulting IData.
To accommodate this, Integration Server now includes a server configuration parameter that you can use to specify how Integration Server decodes duplicate elements nested in an anyType element.

watt.server.xml.xmlNodeToDocument.makeArrayforWS

Specifies how Integration Server decodes duplicate elements contained in an anyType Element.

- Set watt.server.xml.xmlNodeToDocument.makeArrayforWS to true if you want Integration Server to create an array for duplicate elements contained in an element of type anyType.

- Set this parameter to false if you want Integration Server to leave duplicate elements as separate, repeated elements in the element defined to be of type anyType. When set to false, Integration Server does not create an array for elements that appear more than once in the element defined to be of type anyType.

The default is false.

- PIE-33318
Integration Server displays the wrong message in the server log.
Integration Server logs the following message to the server log:
(ISC.0088.9443W) Message not found for messageKey 88.9443
This issue is resolved.
- PIE-33326
After IS_8.2_SP2_Core_Fix14 is installed, Integration Server issues a NullPointerException while loading some custom services.
This issue is resolved.
- PIE-33553
Logging off the Integration Server Administrator fails with an error.
Attempting to log off the Integration Server Administrator fails with the following error message:
Logoff Failed.
This issue is resolved. Upon clicking Log Off, Integration Server terminates the session and displays a message confirming that the session is terminated.
- PIE-33883
Integration Server does not include the initial SOAP request message in the SOAP fault that is generated when an error occurs upon invoking a web service.
Upon invoking a web service, in case of an error, the SOAP fault that Integration Server generates does not include the initial SOAP request even if the pub.soap.handler:getInitialSOAPMessage service is used to retrieve the initial SOAP request message in the outbound callback service.
This issue is resolved. Integration Server now includes the initial SOAP request message in the SOAP fault that is generated when an error occurs upon invoking a web service.
- PIE-33895
Enhancements to Integration Server to provide NTLM (Windows NT LAN Manager) authentication support to allow clients to access resources in web servers that support NTLM authentication. Prior to this fix, Integration Server could use Integrated Windows Authentication as a means of authenticating its identity while establishing connections between Integration Server and web servers on an intranet only if the Integration Server was running on a Windows platform. If Integration Server is running as an NT service, it uses the local system rights for authentication when responding to an Integrated Windows Authentication request. If you log on as a user, Integration Server uses the credentials associated with that session when responding to an

Integrated Windows Authentication request.

After installing this fix, when Integration Server is acting as a client to access resources in web servers, the authentication credentials must be provided by the user explicitly. You can specify NTLM as the authentication type while configuring the transport properties for web service endpoints to authenticate clients who are already logged into a domain using their existing credentials.

In addition, you can specify NTLM as the value for the `auth\` type parameter of `pub.client:http` or `pub.client:soapClient` services and web service connector. If you specify NTLM as the authentication type, you must specify the user name that the service will submit when requesting a protected resource in the following format: `domain_name/user_name`.

- **PIE-34213**
Enabling a Salesforce.com Adapter connection results in a `javax.net.ssl.SSLHandshakeException`. If the Salesforce.com Adapter is installed on an Integration Server for which the WmCloud package is enabled, enabling a Salesforce.com Adapter connection results in the following exception:
`javax.net.ssl.SSLHandshakeException: sun.security.validator.ValidatorException: PKIX path building failed: sun.security.provider.certpath.SunCertPathBuilderException: unable to find valid certification path to requested target`
This issue is now resolved.
- **PIE-34311**
The Polling Notifications page in localized versions of Integration Server Administrator displays an Adapter Runtime error if there are no scheduled tasks for polling notifications. When there are no scheduled tasks associated with adapter polling notifications, localized versions of Integration Server return a `SQLException` that cannot be verified by the Adapter Runtime causing the following message to be displayed in the Polling Notifications page:
(ART.116.3020) Adapter Runtime (Notification): Unable to get list of notification types supported by node JDBCAdapter. `java.sql.SQLException: Invalid task ID`
Now, when there are no scheduled tasks for polling notifications, a localized Integration Server returns a `SQLException` with a predefined error code that can be verified by the Adapter Runtime.
- **PIE-34373**
Integration Server throws a `java.lang.NoClassDefFoundError` when a user defined in the central user management attempts to log in. A jar file required for central user management, specifically `jsf-api.jar`, is not present in the Integration Server classpath. To resolve this issue in Integration Server versions prior to 9.5 SP1 do the following:
 1. Shut down Integration Server.
 2. Using a text editor, navigate to and open the following file:
`IntegrationServer_InstallDirectory/bin/ini.cnf`
 3. Edit the `ini.cnf` file by adding the following jar entry to the `application.classpath` parameter:
`<Software AG_Directory>/common/lib/ext/jsf-api.jar`
Where `<Software AG_Directory>` is the installation directory for Software AG products.
Note: Make sure to use the appropriate directory separator for the operating system.
 4. Save your changes to the `ini.cnf` file and then close the file.
 5. Start Integration Server.

Note: For versions of Integration Server 9.5 SP1 and later, the Software AG Update Manager will handle updates to the ini.cnf.

- PIE-35015
Updating webMethods Cloud account settings from Integration Server Administrator fails. Using Integration Server Administrator to update webMethods Cloud account settings results in the following error when changes to the account are saved:
The following error occurred while saving account settings :
com.wm.app.b2b.server.ServiceException:
iaik.security.ssl.SSLException: Server certificate rejected by ChainVerifier. See the error log for the full stack trace.
This issue is now resolved.
- PIEAR-625 (WAR_9.5_SP1_Fix5)
Exceptions thrown by adapter services are logged multiple times in the error log. The error log contains multiple entries of an exception thrown by an adapter service because the exception is logged by Adapter Runtime, Adapter Development Kit, and Integration Server.
This issue is resolved. The following two server configuration parameters are introduced to prevent error logging by Adapter Runtime and Adapter Development Kit for exceptions in adapter services:
 - watt.art.adapterService.disable.errorlogging
 - watt.adk.adapterService.disable.errorloggingThe default value of each parameter is false.
Add the new server configuration parameters to Extended Settings in Integration Server Administrator and set the parameters to true.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- Information about configuring the Universal Messaging client log has been moved from the *webMethods Audit Logging Guide* to the *webMethods Integration Server Administrator's Guide*.

Release 10.2

- The *Developing Microservices with webMethods Microservices Container* guide has been renamed *Developing Microservices with webMethods Microservices Runtime* to reflect the product name change from webMethods Microservices Container to webMethods Microservices Runtime.

Release 10.1

- The *Web Applications Developer's Guide* is no longer available. This guide explained how to use the WmTomcat package to incorporate web applications into the Integration Server environment. As of Integration Server 10.1, the WmTomcat package has been removed from the product.

Release 9.8

- Software AG documentation is no longer available on the Software AG installer. You can access all Software AG documentation on the [Documentation website](#).

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 10.3

Old Term	New Term
Named object	Durable subscription or durable. As of Universal Messaging version 10.2, the term <i>named object</i> has been replaced with <i>durable subscription</i> or its abbreviated form <i>durable</i> . A serial webMethods messaging trigger corresponds to a serial durable subscription (or the abbreviated serial durable) on Universal Messaging. A concurrent webMethods messaging trigger corresponds to a shared durable subscription (or the abbreviated shared durable) on Universal Messaging.

Release 10.2

Old Term	New Term
webMethods Microservices Container	webMethods Microservices Runtime

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Support for using the --time option (-t) with docker stop command.	The --time option specifies how long Docker waits before killing a container. Use the --time option to specify a waiting time long enough to allow Integration Server to shut down gracefully.
Custom security area for security logging.	The new method <code>com.wm.app.b2b.server.ServerAPI.logSecurity</code> makes it possible for applications to write entries to the security log as logging for the Custom security area.
SAG_IS_AUDIT_STDOUT_LOGGERS environment variable	Specifies the audit loggers to write to the console (STDOUT). When an audit logger writes to STDOUT it is considered an auxiliary output which means the logger will still write to the specified log destination of file or database.
EXTERNALIZE_PACKAGES environment variable	Instructs the Integration Server running in the Docker container to load the packages located in one of the specified directories at startup.
SAG_IS_LICENSE_FILE environment variable	Specifies the license key to be used with an Integration Server running in a Docker container which allows the license key to be changed without rebuilding the Docker image for the Integration Server.
Support for ICAP preview headers	Integration Server now supports an ICAP preview header that allows the ICAP server to scan the preview content instead of scanning the entire request from Enterprise Gateway.
Support for OAuth grant types Resource Owner Password Credentials and Client Credentials	Integration Server now supports the Resource Owner Password Credentials and Client Credentials grant types.
JMS trigger restart task	If a JMS trigger does not start when a JMS connection alias starts, Integration Server schedules a task to retry starting the JMS triggers and then continues with activities associated with starting the JMS connection alias. The trigger restart task, which runs in its own thread, attempts to restart the failed JMS triggers at a set interval.

Changed Item	Description
Updated messageNumber key for reliableMessagingProperties.	Specifies the message number in the message sequence. In cases where there are several message numbers in the message sequence, you can specify a custom message number.
Serial webMethods messaging triggers that receive documents from Universal Messaging now process documents from all publishers in publication order in a load-balanced fashion.	Previously, a webMethods messaging trigger with serial processing corresponded to a priority named object on a channel on Universal Messaging server. Now, a serial webMethods messaging trigger corresponds to a serial durable subscription (named objects in Universal Messaging are now called durable subscriptions). This provides processing in publishing order for a serial trigger in a cluster or a non-clustered group of Integration Servers. Over time, it allows for the Integration Server in a cluster or non-clustered group to process messages in a load balanced fashion.
Server log entries written to the console now include the identifier "ISSERVER"	To help differentiate server log messages from other messages written to the console, server log entries include the identifier "ISSERVER". Previously, there was no identifier.
Allowed Grants property for registering clients	When registering clients for use with an Integration Server acting as an authorization server for OAuth, you can specify the grant types a client can use. Previously, all registered clients could use the authorization code grant type and the implicit grant type. All registered clients migrated from an earlier version of Integration Server will have the Authorization Code Grant type and Implicit Grant type selected.
Token endpoint authorization property for global OAuth settings	Specifies whether the token endpoint accepts an existing session or requires credentials for authentication. Previously, the token endpoint service always accepted requests from clients that had an active session on Integration Server and did not provide an option to require authentication every time the client requests a new access token or refreshes an existing access token

Added Item	Description
<p>Improved visibility into sending messages from client side queue to Broker.</p>	<p>To improve visibility and control of sending messages from the CSQ to the Broker for webMethods messaging, Integration Server introduces the following:</p> <p>The maximum number of retry attempts that Integration Server makes when publishing a message from the CSQ to Broker is now configurable. Previously, the maximum number of retries was 5 and could not be changed. For details about the server configuration parameter <code>watt.server.publish.maxCSQRedeliveryCount</code>, see below.</p> <p>At the debug level for facility 0098 Dispatcher, the Integration Server now logs additional messages that indicate why an attempt to send a message from the CSQ to Broker failed.</p> <p>Existing log entries as well as the newly introduce log entries for facility 0098 Dispatcher now include the message ID and the name of the publishable document type for which the message is an instance document.</p>
<p>Ownership of files in Docker image is changed to non-root user</p>	<p>When running the <code>is_container.sh</code> script to create Docker images, ownership of the files is changed to non-root (sagadmin) user. The optional <code>-Dimage.createUser</code> parameter can be passed to the <code>createDockerfile</code>, <code>createLeanDockerfile</code>, or <code>createPackageDockerfile</code> commands to control the ownership of the files in the Docker image.</p>

Added Item	Description
<p>Client ID for webMethods messaging triggers that receive message from Universal Messaging</p>	<p>For webMethods messaging triggers created in Integration Server 10.3, the client ID of the trigger is now the trigger's shared durable name which is as follows:</p> <p><i>clientPrefix##triggerName</i></p> <p>Where <i>clientPrefix</i> is the Universal Messaging connection alias used by the trigger, <i>triggerName</i> is the fully qualified name of the trigger where periods and colons are replaced by double underscores. Previously, the client ID naming convention for a trigger that receives message from Broker was the same as the client ID naming convention for a trigger that receives messages from Universal Messaging.</p>

Release 10.2

Added Item	Description
<p>Enhanced messaging logging</p>	<p>Integration Server writes detailed log entries when sending or receiving and processing messages. The detailed logging makes it possible to track an individual message across your Integration Servers from the time the message is published through the time a trigger receives, processes, and acknowledges the message. Enhanced logging includes the introduction of the messaging audit log.</p>
<p>WebSocket support</p>	<p>Integration Server enables development of applications using the WebSocket protocol. The WebSocket protocol provides simultaneous two-way communication between a client endpoint and server endpoint over a single TCP connection.</p>
<p>Whitelist filtering</p>	<p>To prevent Integration Server from deserializing untrusted Java objects, Integration Server now performs whitelist filtering and includes a whitelist of classes that can be loaded and deserialized in Integration Server.</p>
<p>Support for default scope for Integration Server acting as the OAuth resource server</p>	<p>When configuring an external authorization server, you can specify a default scope in the Default Scope field.</p>

Added Item	Description
SSL field on the About page of Integration Server Administrator	<p>To help troubleshoot connectivity issues, the About page of Integration Server Administrator, the Software section now contains an SSL field that displays one of the following:</p> <ul style="list-style-type: none"> - The JCE Unlimited Strength Jurisdiction Policy File was not found. Please install it. - The JCE Unlimited Strength Jurisdiction Policy File was found
Support for security response headers	<p>To enhance the security of response headers, Integration Server now supports the following HTTP response security headers:</p> <ul style="list-style-type: none"> - X-Content-Type-Options - X-XSS-Protection - Strict-Transport-Security
Improved support of REST multipart messages	<p>Integration Server provides Java API that enables you to register your own services along with the associated coders for multipart content handler.</p>
Support for strong password polices	<p>To enhance the security, Integration Server now supports stronger password policies for user accounts.</p> <p>To achieve this, Integration Server now covers the following aspects of password security:</p> <ul style="list-style-type: none"> - Stronger password requirements - Password expiration requirements - Account locking
Circuit Breaker	<p>The circuit breaker feature provides the ability to configure a circuit breaker for any service residing on a Microservices Runtime or an appropriately licensed Integration Server.</p>

Added Item	Description
Any field type support for Digital Event Services	An Object or Object List with a Java wrapper type of UNKNOWN is included in the Digital Event Servers event type definition as an Any or Any[] field. Previously, an Object or Object List field with an UNKNOWN Java wrapper type were not included in the corresponding Digital Event Services type definition. Additionally, IS document types can be used to define the structure and content for an Any field in a document published to Digital Event Services.
Map field type support for Digital Event Services	An empty inline document variable configured to allow unspecified fields in a publishable document type is now represented as Map field in the corresponding Digital Event Services type definition.
Synchronizing document types with Digital Event Services automatically	Document types can be set to automatically synchronize with a corresponding Digital Event Services event type definition in the Digital Event Services repository upon save. Set this property to true for a document type that may be used to define the structure and content for the value of an Any field in a document that is published to Digital Event Services.

Added Item	Description
Migration Utility handles updates for hostname	<p>Prior to release 10.2, if you upgraded your Integration Server by installing the new release on a different machine, you had to update the database components below to reflect the host name of the new machine, as follows:</p> <ul style="list-style-type: none"> - If you had scheduled tasks that executed on Integration Server on specific machines in your old installation, you had to update database component ISInternal, table IS_USER_TASKS, column TARGET. - If you wanted to be able to resubmit services that ran before you upgraded, you had to update the following: <ul style="list-style-type: none"> - Database component ProcessAudit, table WMRULEDIST, column SERVID. - Database components IS CoreAudit, ProcessAudit; tables WMDOCUMENT, WMSERVICE, WMSERVICE4X, MSERVICEACTIVITYLOG, WMSERVICEASSOC, WMSERVICECUSTOMFLDS; column SERVERID. - If you wanted to be able to resubmit processes and process steps that ran before you upgraded, you had to update database component ProcessAudit, table PRA_PROCESS_STEP, SERVERID column. <p>The Integration Server migration utility now updates all of these tables for you automatically.</p>

Removed Item	Replacement, if any
No support for host-based name format.	Integration Server does not support the host-based name format to specify the Service Principal Name Format when adding or editing an HTTP(s) port.

Changed Item	Description
updateLanguagePack command for is_instance script.	Provides an option to specify the package and/or feature list to which to apply the language pack installation.
create command for is_instance script.	Provides an option for specifying a default IP address to which to bind ports on the new Integration Server instance.
Server log entries can be written to the console, a file, or both.	Previously, Integration Server could write server log entries to a file or the console (STDOUT). Now, the -log switch includes the both option to write server log information to the computer screen (STDOUT) and to the destination specified by the watt.debug.logfile parameter.
Docker container for an Integration Server Docker image writes the server log to the console (STDOUT).	When running a Docker image of Integration Server in a Docker container, Integration Server writes the server log to the console as well as to the server.log file. Many container deployment solutions provide the ability to view the console log STDOUT for a container.
Repeating tasks scheduled to execute in the Daylight Savings Time (DST) overlap.	If a task includes an hours mask (e.g., "1:15" for running every date at 0115), then the task will run only once, at the pre-overlap ("first") matching time. However, if a task does not have an hours mask (e.g., "hh:15", meaning run at 15 minutes past each hour), then the task will run at the pre-overlap time (the "first" 1:15), and also at the overlap time (the "second" 1:15). Previously, the absence of an hours mask did not result in the task executing twice.
Diagnostic collector	<p>To help with debugging, the Integration Server diagnostic collector returns information regarding whether or not the JCE Unlimited Strength Jurisdiction Policy File is applied to the JVM in the config\ServerAbout.txt file.</p> <p>Integration Server also adds the following file to the list of security providers returned with the diagnostic data: config\JCESecurityInfo.txt</p>

Changed Item**Description**

Digital Event Service type definition

With the introduction of support for Any fields and Map fields for Digital Event Services, the Digital Event Type definition generated for a publishable document type changes in the following ways:

- An Object or Object List with a Java wrapper type of UNKNOWN is included in the Digital Event Services event type definition as an Any or Any[] field. Previously, an Object or Object List field with an UNKNOWN Java wrapper type were not included in the corresponding Digital Event Services type definition
- An empty inline document variable in a publishable document type is now represented as Map field in the corresponding Digital Event Services type definition. Previously, an inline document variable became an empty nested event.

Release 10.1**Added Item****Description**

SFTP Host Key Checking field in the SFTP User Alias Advanced Settings screen

Allows Integration Server to verify the host key of SFTP server during connection.

Create JMS administered objects on demand.

Integration Server can create administered objects in the JNDI namespace automatically when the lookup for the object fails. This functionality, which is controlled by the Create Administered Objects On Demand option for a JMS connection alias, is available only when Universal Messaging is the JMS provider and the JNDI provider.

Support for using volumes when running an Integration Server image in a Docker container.

Docker volumes can be used for externalizing the contents of the logs directory for the Integration Server instance and the Integration Server profile as well as the config directory for the Integration Server instance running in the Docker container.

The is_container.sh script, which facilitates interaction with Docker, now provides an option for specifying a base image.

When using the createDockerFile or createLeanDockerfile command to create a Docker image for Integration Server, specify a base image using the argument -Dimage.name.

Added Item	Description
Support for using an Integration Server running in a Docker container as the local development server for the local service development feature in Designer.	When using the createDockerFile or createLeanDockerfile command to create a Docker image for Integration Sever, specify that the Integration Server will be used as the local development server using the argument -Dtarget.configuration=localdev
New flag, useAlternateNameForSegment, added in the WmFlatFile package.	useAlternateNameForSegment: Determines whether the flat file parser uses an alternate name for segments if an alternate name is provided.
Support for RFC 7662, OAuth 2.0 Token Introspection	Access tokens generated by an external authorization server can be used to access resources in Integration Server. Access tokens generated by an Integration Server authorization server can be used to access resources in a resource sever that is not an Integration Server.
Support for RFC 7009, OAuth 2.0 Token Revocation	Access tokens generated by Integration Server can be revoked.
Support for REST V2 resources	<p>Integration Server provides a flexible way of defining resources for REST requests. In the Service Development perspective, a developer can define a REST V2 resource with operations that include the following:</p> <ul style="list-style-type: none"> • The format of the URL that REST clients must follow when sending requests to Integration Server acting as the REST server. • The HTTP methods supported by the resource operation. • The flow service associated with a resource operation.
Support for JWT authentication	Integration Server provides support for JSON Web Token (JWT) authentication. JWT provides a secured means of exchanging claims between two parties.

Added Item	Description
HTTP Interceptor	Integration Server provides a framework for creating and registering an HTTP interceptor. An HTTP interceptor intercepts all received HTTP requests and outbound HTTP responses. Integration Server makes the raw HTTP request and response, including the HTTP header information, accessible to the HTTP interceptor.
Serial JMS triggers supported with Universal Messaging.	When using a connection factory configured for a durable subscriber, Integration Server now supports the use of serial JMS triggers with Universal Messaging.
Additional client side queue (CSQ) logging.	When facility code 134 is set to debug or trace levels, Integration Server provides additional logging when CSQ errors occur.
Integration Server now supports migration when source and target version are same.	The migration utility can now be used for migration where the source and target versions of Integration Server are the same. This can be useful for data center or machine moves

Removed Item	Replacement, if any
WmTomcat package	Existing web applications based on the WmTomcat package can be moved to webMethods Application Platform.

Changed Item	Description
Archived stats.log file name format.	Integration Server now uses the following naming format for the archived stats.log files: stats.yyyymmdd_hhmmss.log where the timestamp indicates the time at which Integration Server archived the log file. Previously, the archived stats.log name did not include the time portion which caused a naming conflict that prevented successful log rotation if Integration Server attempted to rotate the stats.log more than once on the same day.
Manage Destinations check box	The Manage Destinations check box for a JMS connection alias is now named Enable Destination Management with Designer.

Changed Item	Description
Share Client Prefix check box	The Share Client Prefix check box for webMethods messaging connection aliases is now named Client Prefix Is Shared. The field name now includes the text “prevents removal of shared messaging provider objects” in parentheses to clarify the purpose of the option.

Release 10.0

Added Item	Description
Allowed HTTP method per service	For each service, you can identify the HTTP methods that can be used to invoke the service.
Default web service provider endpoint alias	For HTTP and HTTPS, you can identify a provider web service endpoint alias as the default for each protocol. If a provider web service descriptor contains a binder that specifies the default endpoint alias or no alias for the Port alias property, Integration Server uses the information in the default alias when constructing the WSDL for the descriptor and during run-time processing.
Follow the master support for JMS connection aliases	When Universal Messaging is the JMS provider, you can configure the JMS connection alias to follow the master for consumer and producer connections.
JDBC pool configuration when Integration Server is offline	In conjunction with Command Central, Integration Server makes it possible for administrators to change the configuration of JDBC pools when Integration Server is offline.
JMS Trigger Groups	A JMS trigger group is a collection of two or more identical JMS triggers. Using the methods in the <code>com.wm.app.b2b.server.jms.consumer.JMSTriggerGroupFacade</code> class, users can quickly create JMS triggers for a trigger group. This can be especially helpful when needing to create several identical triggers that point different Universal Messaging realms, such as when using the new Universal Messaging round robin cluster feature for JMS.

Added Item	Description
PATCH support	<p>Integration Server offers support for HTTP PATCH method, which is used for partial updates. In Service Development, a developer can specify PATCH support when defining REST resources, Integration Server also supports the PATCH methods in the pub.client:http service as well as with CORS (Cross Origin Resource Sharing) requests.</p>
REST Resource URLs	<p>Integration Server provides a flexible way to define resource URLs for REST APIs. The new capability allows a developer to define a URL format for the service that does not adhere to the folder structure within the package. Additionally, you can define multiple REST resources for a single service with the HTTP methods of your choice.</p>
Retrieving and Setting HTTP Headers	<p>Integration Server provides the ability to get and set HTTP request and response headers easily.</p> <p>To get the details of an HTTP request for a service, you can add a document reference variable named \$httpRequest that references the pub.flow:HTTPRequest document type in the input signature of a service. While invoking a service that includes a \$httpRequest document reference variable, Integration Server populates the \$httpRequest variable with information from the from the HTTP request.</p> <p>To get the details of an HTTP request for a service, you can add a document reference variable named \$httpRequest that references the pub.flow:HTTPRequest document type in the input signature of a service. While invoking a service that includes a \$httpRequest document reference variable, Integration Server populates the \$httpRequest variable with information from the from the HTTP request.</p>
Searching for JMS Triggers	<p>You can search for or filter the displayed triggers using the Search Triggers link on the Settings > Messaging > JMS Trigger Management page. You can search by trigger name, JMS connection alias or destination to which the trigger subscribes.</p>

Added Item	Description
Session ID Masking in Logs	Session IDs in the session and server logs can now be secured by masking the ID. When you enable the option for securing Session IDs, Integration Server uses the asterisk (*) character to mask the Session ID strings in the logs which prevents user who access the log entries from viewing the actual Session IDs.

Changed Item	Description
Format of the <soap:address location> element in the WSDL of a provider web service descriptor.	The <soap:address location> element in the WSDL document generated for a service first provider web service descriptor will be in the following format regardless of specifying either a provider web service endpoint alias or a host and port as the endpoint: http://host_name.port/ws/namespace:descriptorname
Follow the master is configurable per Universal Messaging connection alias	For a Universal Messaging connection alias, you can now enable follow the master on a per connection alias basis. Additionally, you can decide whether message producers and/or consumers follow the master realm server using the “Enable Follow the Master for Producers “and “Enable Follow the Master for Consumers” options respectively. Previously, following the master was either enabled or disabled for all connections.

Changed Item	Description
JMS Trigger Management page	<p>The Settings > Messaging > JMS Trigger Management page includes the following changes:</p> <p>Clicking Search Triggers displays a simple search feature.</p> <p>In the JSM trigger list, columns are re-ordered to put the State column right next to the trigger name.</p> <p>The State column values can now be “Enabled”, “Disabled”, or “Suspended”. Previously, the possible State values were “Yes”, “No”, “Suspended”.</p> <p>The Status column is new. Possible values are “Running” or “Not Running” followed up by an explanation, such as “Not Running (trigger disabled)”.</p> <p>The SOAP-JMS triggers list is displayed only if Integration Server contains a loaded package with a SOAP-JMS trigger.</p>
Maximum Entries in Cache field	<p>For a distributed cache, the Maximum Entries in Cache value must be set and must be set to a value greater than 0.</p>
Universal Messaging connection alias Client Authentication	<p>The Client Authentication option named SSL is now named Certificate Based, which is more accurate.</p>

Release 9.12

Added Item	Description
IS_DES_CONNECTION messaging connection alias	<p>A predefined messaging connection alias used to establish a connection with a Universal Messaging server for purposes of sending and receiving events with Digital Event Services.</p>
Kill All Sessions Except Your Session option in the Server > Statistics > Sessions screen	<p>Use the Kill All Sessions Except Your Session option in the Current Sessions Screen to kill all the sessions except the session you are currently running.</p>
is_container scripts to create Integration Server images for use in Docker containers	<p>Use the is_container scripts, created by the Integration Server installation, to build Integration Server images for use in Docker containers. You can access the scripts from the following location: Integration Server_directory/docker.</p>

Added Item	Description
Caches and cache managers can be edited while in quiesce mode	Public and system cache managers and caches can be edited when Integration Server runs in quiesce mode.
Public cache can be used for service results caching.	A local or distributed public cache can now be used for service results caching. Previously, Integration Server stored cached service results in the ServiceResults system cache which is part of the SoftwareAG.IS.Services system cache manager.

Changed Item	Description
FTPS ports that use the HTTPS protocol can now be configured using the “Use JSSE” option.	FTPS ports that support TLS 1.1 or TLS 1.2 protocol can now be configured using the “Use JSSE” option in the Edit FTPS Port Configuration screen of Integration Server Administrator. Previously, this option was not available.
Allowed cipher suites can be specified in a file.	To make it easier to specify a long list of cipher suites for use with inbound and outbound SSL connections, Integration Server now allows specifying a file as the value for the cipher suite server configuration properties watt.net.ssl.client.cipherSuiteList, watt.net.ssl.server.cipherSuiteList, watt.net.jsse.client.enabledCipherSuiteList, watt.net.jsse.server.enabledCipherSuiteList.

Changed Item	Description
<p>Some screens in Integration Server Administrator are disabled if webMethods API Gateway is installed on Integration Server.</p>	<p>The following screens under Security screens are disabled:</p> <ul style="list-style-type: none"> • Enterprise Gateway Rules • Enterprise Gateway Rules > Default Alert Options • Enterprise Gateway Rules > Default Alert Options > Edit • Enterprise Gateway Rules > Denial of Service Options • Enterprise Gateway Rules > Denial of Service Options > Configure Global Denial of Service • Enterprise Gateway Rules > Denial of Service Options > Configure Denial of Service by IP Address • Enterprise Gateway Rules > Mobile Application Protection Options • Enterprise Gateway Rules > Mobile Application Protection Options > Device Types > Edit • Enterprise Gateway Rules > Mobile Application Protection Options > Mobile Applications > Edit • Enterprise Gateway Rules > Rules > Create
	<p>The following screens under Security > Ports > Add Port are disabled:</p> <ul style="list-style-type: none"> • Edit Enterprise Gateway Server Configuration • Edit Internal Server Configuration

Release 9.10

Added Item	Description
<p>Configure the allowed protocols for JSSE on a per port basis</p>	<p>Integration Server now provides the ability to specify the allowed protocols for JSSE on a per port basis.</p>

Added Item	Description
Out of the box support for Content-Type application/xml.	Integration Server content handler named ContentHandler_XML now includes support for the content type application/xml.
Kerberos authentication for outbound service requests.	The pub.client:http service now includes Kerberos-related parameters that you can use to acquire a Kerberos ticket for inclusion in the outbound service request.
Java API Classes for working with XMLData in Java services	A set of classes in com.wm.data for manipulating XMLData in Java services. For a list of classes, see the Added APIs for the Release 9.10 in section 11.0 Added, Removed, Deprecated, or Changed APIs
Universal Messaging connection alias can now be configured to connect to an SSL-enabled port on a Universal Messaging realm server	When configuring a Universal Messaging connection alias, you can specify SSL as the client authentication and provide the truststore and keystore information needed for Integration Server to establish an SSL connection with the Universal Messaging realm server. Previously, to establish a secure connection to the Universal Messaging realm server, you needed to configure the javax.net.ssl properties in the JVM used by Integration Server.
A queue on Universal Messaging can be used as the audit logging queue	Integration Server provides the option of using a Universal Messaging queue instead of the internal queue as the audit logging queue on a per logger basis.
Follow the master for webMethods messaging connections to Universal Messaging server	Integration Server now uses the Universal Messaging client setting “follow the master” which indicates that the client session always connects to the master realm server. The follow the master behavior takes precedence over the behavior indicated through the use of a comma-separated or semicolon-separated list of realm servers in the Realm URL field for a Universal Messaging connection alias.

Removed Item	Replacement, if any
EventBus predefined JMS connection alias	The EventBus alias is no longer available as a predefined JMS connection alias. That is, new Integration Server installations will not include this predefined JMS connection alias. However, if you migrated to Integration Server version 9.10 or later from an earlier version, then you might still have the EventBus alias.
EventBusJndiProvider predefined JNDI provider alias	The EventBusJndiProvider alias is no longer available as a predefined JNDI provider alias. That is, new Integration Server installations will not include this predefined JNDI provider alias. However, if you migrated to Integration Server version 9.10 or later from an earlier version, then you might still have the EventBusJndiProvider alias.

Deprecated Item	Replacement, if any
WmTomcat Package	Existing web applications based on the WmTomcat package can be moved to webMethods Application Platform.

Changed Item	Description
Client queue window size	The Universal Messaging window size for the client queue that corresponds to webMethods messaging trigger is now set to the sum of the Capacity and Max execution threads trigger properties. Previously, Universal Messaging determined the window size.

Changed Item	Description
<p>Filters in a webMethods messaging trigger must be identical if the conditions subscribe to the same publishable document type.</p>	<p>If more than one condition in the webMethods messaging trigger specifies the same publishable document type and the trigger receives messages from Universal Messaging, the provider filters must be identical in each condition but the local filters can be different. Specifically, the contents of the Provider Filter (UM) column must be identical for each condition that subscribes to the publishable document type. The contents of the Filter column can be different.</p> <p>When using <code>pub.trigger:createTrigger</code> to create a trigger, the contents of <code>conditions/messageTypeFilterPairs/providerFilter</code> must be the same for each condition. The contents of <code>conditions/messageTypeFilterPairs/filter</code> can be different for each condition.</p> <p>The filter requirement is unchanged for a webMethods messaging trigger that receives messages from Broker. That is, if more than one condition in the webMethods messaging trigger specifies the same publishable document type and the trigger receives messages from the Broker, the filters in the conditions must be the same.</p>
<p>Integration Server Administrator</p>	<p>The HTML-based utility used to administer the webMethods Integration Server has a new look and feel. Menu and screen locations have not changed.</p>
<p>Internal Server ports that use the HTTPS protocol can now be configured using the “Use JSSE” option.</p>	<p>Internal Server ports that support TLS 1.1 or TLS 1.2 protocol can now be configured using the “Use JSSE” option in the Edit Internal Server Configuration screen of Integration Server Administrator. Previously, this option was not available.</p>
<p>OAuth Errors now returned in the content type specified in the client request</p>	<p>Previously, Integration Server always returned OAuth errors as HTML. Now, Integration Server returns OAuth errors in the content type specified in the client request.</p>
<p>Reply messages for webMethods messaging routed through Universal Messaging.</p>	<p>Integration Server now always encodes reply message as IData even when the encoding type of the reply document type is protocol buffers.</p>

Release 9.9

Added Item	Description
Cluster synchronization for webMethods messaging triggers that receive documents from Universal Messaging.	If a webMethods messaging trigger receives documents from Universal Messaging resides on Integration Servers that is a member of a cluster, changes that you make for document retrieval, document processing, and for trigger properties can be propagated to other servers in the cluster automatically. Previously, cluster synchronization was available for webMethods messaging triggers that received documents from webMethods Broker only.
CDATA block support to outbound SOAP processing	Integration Server now provides CDATA block support for processing of outbound SOAP messages only when Integration Server hosts the web service provider. When a service used as an operation in a web service provider returns String values containing CDATA blocks, when encoding the IData into a SOAP message, Integration Server places the CDATA text in the outbound SOAP message in a CDATA section and does not url-encode special characters in the delimiters or text block. Previously, Integration Server ignored CDATA delimiters in String fields and treated text in a CDATA block as regular text.
Dedicated MessageConsumer for receiving synchronous replies per JMS connection alias	When a JMS connection alias has the Create Temporary Queue check box and the Enable Request-Reply Listener for Temporary Queue check box selected, Integration Server uses a dedicated consumer to retrieve replies to all requests sent using that JMS connection alias.
Default instance name can be defined by the user	The default instance of Integration Server can now be specified during the installation process. Previously, the default instance was always named “default”.
Fail-fast mode for a JDBC functional alias.	A JDBC functional alias can now be configured to enter fail-fast mode when a transient error caused by an unavailable database prevents the connection pool alias used by the JDBC functional alias from establishing a connection to the database.

Added Item	Description
Instances of Integration Server can be started and stopped from the Windows Start menu.	Any instance of Integration Server can be started or stopped from the Windows Start menu. The Integration Server Administrator can also be started from the Windows Start menu for any instance of Integration Server. Previously, you could start, stop, or launch Integration Server Administrator for the default instance only.
IS_LOCAL_CONNECTION messaging connection alias	A predefined messaging connection alias for use with publishable document types that will be published locally only.
New filter added to the Enterprise Gateway rule	Custom filter added to the list of filter that can be included in an Enterprise Gateway rule. You can use this filter to customize and invoke services in the Enterprise Gateway Server.
URL aliases can now have specific destinations per port and for the empty path	A URL alias can now identify a port-specific destination for the alias. Additionally, an alias can now be created for the empty path for a port.
XMLData and XML document types	XMLData is a new data type that more faithfully represents XML content. This enables Integration Server to support XML Schema constructs such a substitution groups, nested model groups, the any wildcard, and the anyAttribute wildcard. XMLData also provides improvements with regards to handling of XML namespaces. XMLData is surfaced in Integration Server and Designer through XML document types which are created from XML Schema definitions.

Removed Item	Replacement, if any
startup.bat/sh and shutdown.bat/sh scripts contained in the following directory: <i>Integration Server_directory\bin</i>	The startup.bat/sh and shutdown.bat/sh scripts contained in and <i>Integration Server_directory\bin</i> directory have been removed. These scripts are replaced by the startup.bat/sh and shutdown.bat/sh scripts respectively in the following directory: <i>Software</i> <i>AG_directory\profiles\IS_instance_name\bin</i>

Removed Item	Replacement, if any
<p>server.bat/sh scripts contained in the following directory: <i>Integration Server_directory</i>\bin</p>	<p>The server.bat/sh scripts contained in the <i>Integration Server_directory</i>\bin directory have been removed. These scripts are replaced by the startup.bat/sh scripts in the following directory: <i>Software</i> <i>AG_directory</i>\profiles\IS_instance_name\bin</p>
Deprecated Item	Replacement, if any
<p>WmVCS and VCS Integration feature</p>	<p>Use the local service development feature (Local Version Control Integration) to check package elements and their supporting files into and out of a version control system (VCS) directly from Designer.</p>
Changed Item	Description
<p>Destination List parameter renamed to Destination Lookup Name List</p>	<p>On the Create JMS Connection Alias, Edit JMS Connection Alias, and JMS Connection Alias details screens available under Settings > Messaging in Integration Server Administrator, the Destination List parameter was renamed to Destination Lookup Name List to clarify that the destination lookup names must be provided.</p>
<p>Default messaging connection alias</p>	<p>Previously, you did not have to select a default messaging connection alias for use with webMethods messaging. You could select [LOCAL ONLY] which would indicated that publishable document types that specified the DEFAULT messaging connection alias could be published locally only. Now, you must select a messaging connection alias as the default. If you want the default to be local publishing, specify IS_LOCAL_CONNECTION as the default messaging connection alias in Integration Server Administrator.</p>
<p>WmTomcat package</p>	<p>The WmTomcat package is still installed by default, but is no longer enabled by default. The WmTomcat must be disabled if you want to use webMethods Application Platform with Integration Server.</p>

Changed Item	Description
Client Principal and Client Principal Password fields renamed to Principal and Principal Password	On the Create, Edit, or View Web Services Consumer Endpoint Alias details screens available under Settings > Web Services > Create Web Service Endpoint Alias in Integration Server Administrator, under the Kerberos Properties section, the Client Principal and Client Principal Password fields were renamed to Principal and Principal Password.
Use Subject Credentials field renamed to Use Subject Credentials Only	On the Security > Kerberos and Security > Kerberos > Edit screens, the Use Subject Credentials field has been renamed to Use Subject Credentials Only.
Serial webMethods messaging triggers that receive documents from Universal Messaging now process documents from a publisher publication order.	Previously, a webMethods messaging trigger with serial processing corresponded to a shared named object on a channel on Universal Messaging server. Now, a serial webMethods messaging trigger corresponds to a priority named object. This provides processing in publishing order for a serial trigger in a cluster or a non-clustered group of Integration Server
Transient error handling during trigger preprocessing.	<p>The following changes were made to improve transient error handling during trigger preprocessing:</p> <p>If the <code>ISRuntimeException</code> occurs during trigger preprocessing, Integration Server checks the values of the <code>watt.server.trigger.preprocess.suspendAndRetryOnError</code> parameter and the <code>On Retry Failure</code> trigger property. If <code>watt.server.trigger.preprocess.suspendAndRetryOnError</code> is set to <code>true</code> or <code>On Retry Failure</code> is set to "Suspend and retry later", then Integration Server suspends the trigger.</p> <p>Previously, Integration Server checked the <code>watt.server.trigger.preprocess.suspendAndRetryOnError</code> server configuration property only for webMethods messaging triggers that received messages from webMethods Broker. Also previously, Integration Server checked the <code>On retry failure</code> property only for JMS triggers and webMethods messaging triggers that received</p>

Changed Item	Description
	<p>messages from Universal Messaging.</p> <p>The <code>watt.server.trigger.preprocess.suspendAndRetryOnError</code> parameter now applies to all trigger types and messaging providers. Previously, the behavior provided by this property applied only to <code>webMethods</code> messaging triggers that received messages from <code>webMethods</code> Broker. Now, this property also works with <code>webMethods</code> messaging triggers that receive messages from Universal Messaging as well as JMS triggers.</p> <p>Integration Server now includes a server configuration property, <code>watt.server.trigger.preprocess.monitorDatabaseOnConnectionException</code>, that determines how Integration Server handles a <code>ConnectionException</code> that causes a transient error. A <code>ConnectionException</code> occurs when the document history database is not enabled or is configured incorrectly.</p> <p>Typically, transient errors that occur during preprocessing occur during exactly-once processing.</p>
<p>Naming convention for port aliases for migrated ports</p>	<p>To ensure that each port alias is unique, Integration Server now includes the host name for the port in the port alias for migrated ports. The new naming convention is: <code>protocolListener_portNumber_hostName_packageName</code></p>
<p>Port number used while generating XIDs</p>	<p>Previously, Integration Server used the default Integration Server primary port number while generating the unique XIDs that are used to persist the state of XA transactions. Now, Integration Server uses the configured primary port number while generating the XIDs.</p>
<p>URL Path field renamed to Default URL Path</p>	<p>On the Settings > URL Alias > Create and Settings > URL Alias page, the URL Path field had been renamed to Default URL Path.</p>

Release 9.8

Added Item	Description
Basic client authentication performed when connecting Integration Server to a Universal Messaging realm server	When Universal Messaging is the webMethods messaging provider, connections between Integration Server and Universal Messaging servers can now be authenticated using user names and passwords. This authentication is specified in the Client Authentication Settings section on the Settings > Messaging > webMethods Messaging Settings > Universal Messaging Connection Alias > Create screen.
Use Secure Socket Layers to connect to a port on a Universal Messaging realm server	When Universal Messaging is the webMethods messaging provider, connections between Integration Server and Universal Messaging servers can now use one-way or two-way SSL once client-side parameters are configured on Integration Server.
Action on Startup Error option for clustering configuration	When configuring a cluster, you can now specify what action Integration Server takes when an error prevents the server from joining a cluster at startup. Previously, Integration Server would shut down if it could not connect to the cluster at start up. Now, you can start Integration Server as a standalone Integration Server, shut down Integration Server, or start the Integration Server in quiesce mode.
Security > Ports > Enterprise Gateway Registration Port Connections screen	The new Enterprise Gateway Registration Port Connections screen lists the connections from Internal Servers to the Enterprise Gateway registration port. To access this screen, go to the Ports Screen and click the port number of an Enterprise Gateway registration port. On the Security > Ports > View Enterprise Gateway Server Details screen, click Display Connections to Enterprise Gateway Registration Port.

Removed Item	Replacement, if any
WmPKI package	The WmPKI package which provides functionality for using PKI profiles in conjunction with Integration Server has been removed from the product. There is no replacement for the WmPKI package.
Changed Item	Description
JMS Trigger Management page	In Integration Server Administrator, the Settings > Messaging > JMS Trigger Management page now expands the Individual Standard JMS Trigger Controls and Individual SOAP JMS Trigger Controls tables by default. Previously, the tables were collapsed. Additionally, the page now includes links that you can use to jump from the top of one table to the other. This improves page navigation when there are a large number of JMS triggers.
Handling of undeclared namespaces in the resulting document (IData), when an endpoint service is invoked.	When an endpoint service is invoked, Integration Server now includes the undeclared namespace definitions in the resulting document (IData).
Realm URL parameter	<p>The Realm URL parameter on the on Settings > Messaging > webMethods Messaging Settings > Universal Messaging Connection Alias > Create and Edit pages now accepts a semicolon-separated list of URLs to the servers in a Universal Messaging cluster. Previously, the field accepted a comma-separated list only. Use a comma-separated list for Integration Server to always attempt to connect to the first Universal Messaging server in the list, trying the second server and so forth only if the first server becomes unavailable. Use a semicolon-separated list for Integration Server to connect to a randomly chosen URL from the list.</p> <p>You can now specify realm URLs that use the protocol nsps or nhps.</p>
Handling of HTTP requests with no authentication scheme specified in the Authorization header	Integration Server treats HTTP requests with no authentication scheme in the Authorization header as BASIC authentication requests and performs authentication for valid credentials. Previously, Integration Server did not force requests to have an

Changed Item	Description
User Names parameter	authentication scheme in the Authorization header. The User Names field on the Security > User Management > Add and Remove Users screen no longer allows specifying a <i>username ;password</i> combination per line. Passwords cannot be supplied in the User Names field.
JSON text with an array at the root	Integration Server now accepts JSON text containing an array at its root. If the supplied JSON text contains an array at its root and that array does not have a name, Integration Server uses a fixed name of "\$rootArray" for the array value.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Service	Description
pub.flow:getLastFailureCaught	Returns information about the last failure that was caught by a CATCH step.

Changed Service	Description
pub.client:http	A new input parameter <i>trustStore</i> has been added which specifies the alias for the truststore that contains the list of certificates that Integration Server uses to validate the trust relationship.
pub.mime*	The multipart MIME messages created by the pub.mime:* services now strip line folding from the header fields.
pub.oauth:getAccessToken	The service now supports the client credentials grant and the resource owner password credentials grant types.
pub.oauth:getToken	The service now supports the client credentials grant and the resource owner password credentials grant types.

Release 10.2

Added Service	Description
pub.client:websocket	Establishes a WebSocket connection to the URL captured in the identified WebSocket client endpoint.
pub.oauth:getToken	Requests an access token from the Integration Server acting as the authorization server. This service replaces the pub.oauth:getAccessToken and pub.oauth:refreshAccessToken services. Providing a single OAuth token endpoint for requesting an access token conforms to the OAuth standard, RFC 6749.
pub.oauth:removeExpiredAccessTokens	Removes expired access tokens from the database.
pub.websocket:close	Closes the WebSocket connection.
pub.websocket:disconnect	Closes the WebSocket connection abruptly.
pub.websocket:onBinary	Specification to use as the signature for a callback service related to WebSocket server or client endpoint that handles a binary payload.
pub.websocket:onClose	Specification to use as the signature for a callback service that gets invoked when a WebSocket session is closed gracefully or disconnected.
pub.websocket:onConnect	Specification to use as the signature for a callback service that gets invoked when a WebSocket session is successfully established.
pub.websocket:onError	Specification to use as the signature for a callback service that gets invoked when an error is encountered, resulting in WebSocket session termination.
pub.websocket:onText	Specification to use as the signature for a callback service that handles a text payload.
pub.websocket:send	Sends a message on a connected WebSocket session.
Deprecated Service	Replacement, if any
pub.jms.wmjms:receiveStream	None. webMethods Broker is deprecated, resulting in the deprecation of this service.
pub.jms.wmjms:sendStream	None. webMethods Broker is deprecated, resulting in the deprecation of this service.

Deprecated Service	Replacement, if any
pub.oauth:getAccessToken	pub.oauth:getToken
pub.oauth:refreshAccessToken	pub.oauth:getToken

Changed Service	Description
pub.client:http handling of a 307 or 308 status code	When the pub.client:http service sends a POST, PUT, DELETE, or PATCH request and receives a 307 or 308 response status code from an HTTP server, the service no longer changes the request method to GET when redirecting.
pub.publish:envelope	The <i>uuid</i> field can now be set in the document envelope when publishing a document to Universal Messaging using the pub.publish:publish service. Previously, the <i>uuid</i> field was read-only.

Release 10.1

Added Service	Description
pub.json:validate	Validates JSON content against a JSON schema.
pub.oauth:introspectToken	Checks if an access token or refresh token generated by an Integration Server acting as an authorization server is active.
pub.oauth:revokeToken	Revokes a token issued by an Integration Server acting as an authorization server
pub.xmldata:getGroupObjects	Returns information about the objects and their tags in a group value. This service is useful primarily when the structure of data is not known in advanced and must be discovered. Examples include any wildcard content, anyType content, substitution groups, and XmlData that was created without using an XML document type.
pub.xmldata:getGroupValues	Returns information about the values and their tags in a group value. This service is useful primarily when the structure of data is not known in advanced and must be discovered. Examples include any wildcard content, anyType content, substitution groups, and XmlData that was created without using an XML document type.

Added Service	Description
pub.xmldata:queryXMLNode	Queries an XML node and returns the results as XMLData.

Removed Service	Replacement, if any
pub.restV2:listAllRESTResources	None. REST V2 resources are visible in the Package Navigator view of Designer.

Changed Service	Description
pub.jms:sendBatch	The pub.jms:sendBatch service can now be used with Universal Messaging as the JMS provider.
pub.report*	Integration Server now executes the template file and any services therein, using the credentials of the user who invoked the pub.report* service.
pub.xml:loadEnhancedXMLNode	The inputProcessing\supportDTD input parameter now has a default value of false. The inputProcessing\isSupportingExternalEntities input parameter now has a default value of false.
pub.xml:XMLStringToEnhancedXMLNode	The inputProcessing\supportDTD input parameter now has a default value of false. The inputProcessing\isSupportingExternalEntities input parameter now has a default value of false

Release 10.0

Added Service	Description
pub.flow:HTTPRequest	Document type that represents information about the HTTP request received by Integration Server.
pub.flow:HTTPResponse	Document type that specifies the HTTP response information to be returned by Integration Server to the client.
pub.restV2:listAllRESTResources	Lists the REST resources configured using the URL template-based approach for a specified Integration Server service or for all the Integration Server services in a specified package. These REST resources are invoked using the restv2 directive.

Removed Service	Replacement, if any
pub.event.nerv:eventToDocument	No replacement service because the pub.event.routing:subscribe service, which replaces the deprecated pub.event.nerv:subscribe service, handles the conversion of the incoming JMS message into an IS document (IData).
pub.event.nerv:send	pub.event.routing:send
pub.event.nerv:subscribe	pub.event.routing:subscribe
pub.event.nerv:unsubscribe	pub.event.routing:unsubscribe

Changed Service	Description
pub.client:ftp	Updated the input parameter <i>secure</i> to include <i>useJSSE</i> as a child parameter.
pub.client.ftp:login	Updated the input parameter <i>secure</i> to include <i>useJSSE</i> as a child parameter.
pub.client:http	You can now supply a value in the data/bytes input variable when the method input variable is DELETE.
pub.security.xml:signXML	<p>Added input parameter <i>isDetached</i> to indicate whether the signature should be detached or not.</p> <p>Added input parameter <i>keyName</i> which is the name that is used by the signer to communicate a key identifier to the recipient.</p> <p>Added input parameter <i>keyNameValue</i> to indicate whether to include the key value (RSAKeyValue or DSAKeyValue), based on the certificate used for signing. The <i>KeyValue</i> element contains a single public key that can be used in validating the signature.</p> <p>The <i>certData</i> input parameter now includes <i>X509_CRL</i> as an option.</p>

Release 9.12

Added Service	Description
pub.cache.serviceResults:addCacheEntry	Adds cached entry into service results for the service without executing the actual service. This service can be useful to perform bulk load of service results at Integration Server startup.
pub.cache.serviceResults:listServiceCache	Returns a list of the cached service results for a particular service.
pub.cache.serviceResults:resetServerCache	Resets the cache for all services in the service results cache, resulting in the removal of all cached service results for all services from the service results cache.
pub.cache.serviceResults:resetServiceCache	Resets the cache for specific service, resulting in the removal of cached service results for the service.

Changed Service	Description
pub.client:http	<p>The default value of the <i>useJSSE</i> parameter is now null, which allows the <i>watt.net.ssl.client.useJSSE</i> server configuration property to determine the default behavior for outbound HTTPS connections.</p> <p>Added input parameter <i>delegation</i> to allow a user to execute a service on behalf of other user.</p> <p>Added input parameter <i>requestDelegatableToken</i> to specify if you want to request for a forwardable ticket granting ticket to send to the intermediary. The intermediary can use this forwardable ticket granting ticket for Kerberos delegation.Integration Server, which the server can use for delegation</p>
pub.client.ldap:search	Added input parameter <i>pageSize</i> to set the number of entries to return in a page. Added input and output parameter <i>ldapCookie</i> which contains the index of the page count for the search.
pub.client.ftp:login	Added input parameter <i>useJSSE</i> to allow use of JSSE for creating outbound FTPS connections.
pub.client:soapClient	Added input parameter <i>useJSSE</i> to allow use of JSSE for outbound web service invocation.

Changed Service	Description
pub.date*	Previously, if a value was not specified for the locale input parameter, Integration Server used the locale from the session used by the client that invoked the service. Now, Integration Server uses the value of the <code>watt.server.session.locale.ignore</code> server configuration parameter to determine whether the locale is obtained from the session used by the client that invoked the service or if the locale is the locale of Integration Server.
pub.flow:setResponse2	Added input variable <code>responseStreamTransferEncoding</code> to use chunked transfer encoding for the response and include the "Transfer-Encoding: chunked" response header.
pub.json:jsonStreamToDocument	Added input parameter <code>decodeRealAsString</code> to converts real numbers in the <code>jsonStream</code> to <code>String</code> .
pub.json:jsonStringToDocument	Added input parameter <code>decodeRealAsString</code> to converts real numbers in the <code>jsonStream</code> to <code>String</code> .
pub.security:userInfoSpec	The error input parameter is now named <code>userInfoError</code> .

Release 9.10

Added Service	Description
pub.date:compareDates	Compares two dates.
pub.date:incrementDate	Increments a date by a specified period.
pub.event.routing:eventAcknowledgement	Defines the input signature for a callback service that processes acknowledgments sent by the Event Routing framework.
pub.security:userInfoSpec	Specification for <code>UserInfo</code> service that performs custom processing based on the personally identifiable information in the OpenID Connect <code>UserInfo</code> token.
pub.string:compareStrings	Performs a case-sensitive comparison of two strings, and indicates whether the strings are identical.
pub.string:isAlphanumeric	Determines whether a string consists entirely of alphanumeric characters (in the ranges A–Z, a–z, or 0–9).

Added Service	Description
pub.string:isDate	Determines whether a string follows a specified date pattern.
pub.string:isNullOrBlank	Checks a string for a null or a blank value.
pub.string:isNumber	Determines whether the contents of a string can be converted to a float value.
pub.string:substitutePipelineVariables	Replaces a pipeline variable with its corresponding value.

Changed Service	Description
pub.client:http	<p>The <i>method</i> input parameter now supports the patch method.</p> <p>The pub.client:http service now includes fields for supplying Kerberos information that Integration Server uses to acquire a Kerberos ticket to include in the outbound service request. Specifically, the <i>auth</i> input parameter now contains a <i>kerberos</i> document in which you can specify <i>jaasContext</i>, <i>clientPrincipal</i>, <i>clientPassword</i>, <i>servicePrincipal</i>, and <i>servicePrincipalForm</i>.</p> <p>If the remote server redirected pub.client:http to a different location, <i>encodedURL</i> contain the URL that pub.client:http submitted to the server to which it was redirected.</p>
pub.event.routing:send	New input parameters <i>isAsync</i> , <i>service Name</i> , and <i>runAsUser</i> .
pub.jms:send	Added the <i>JMSMessage/header/replyTo</i> input parameter which can be used to specify a destination for replies without actually needing to wait for replies.
pub.security.keystore.pkcs7:sign	New input parameters <i>dataAsStream</i> and <i>signatureAsStream</i> .
pub.security.pkcs7:verify	New input parameters <i>signatureAsStream</i> and <i>dataAsStream</i> .
	New output parameter <i>contentAsStream</i> .
pub.security.util:createMessageDigest	New input parameter <i>inputAsStream</i> .
	New output parameter <i>outputAsStream</i>

Release 9.9

Added Service	Description
pub.assets:getChecksums	Retrieves the checksums for assets, specifically namespace elements, on Integration Server.
pub.event.routing:send	Sends events to the messaging provider using Software AG Event Routing.
pub.event.routing:subscribe	Creates a subscription to a particular type of event using Software AG Event Routing.
pub.event.routing:unsubscribe	Removes a subscription to an event type previously subscribed to using the pub.event.routing:subscribe service.
pub.security.enterpriseGateway:customFilterSpec	Specification for services that can be invoked by the custom filter in Enterprise Gateway rules.
pub.xmldata:domNodeToXMLData	Converts a DOM node to a document (XMLData object).
pub.xmldata:getAttributes	Retrieves the attribute values from an XMLData object.
pub.xmldata:getInstanceTag	Retrieves the instance (xsi) tag values from an XMLData object.
pub.xmldata:getNamespaceTag	Retrieves the namespace tags values from an XMLData object.
pub.xmldata:setAttribute	Sets the value of an attribute in an XMLData object.
pub.xmldata:setInstanceTag	Sets an instance tag value in an XMLData object.
pub.xmldata.setNamespaceTag	Sets a namespace tag value in an XMLData object.
pub.xmldata:xmlDataToXMLString	Converts a document (XMLData object) to an XML String.
Deprecated Service	Replacement, if any
pub.event.nerv:eventToDocument	No replacement service because the pub.event.routing:subscribe service, which replaces the deprecated pub.event.nerv:subscribe service, handles the conversion of the incoming JMS message into an IS document (IData) now.
pub.event.nerv:send	pub.event.routing:send
pub.event.nerv:subscribe	pub.event.routing:subscribe
pub.event.nerv:unsubscribe	pub.event.routing:unsubscribe

Changed Service	Description
pub.client.ftp:getCompletedNotification	The publishable document type now specifies the IS_LOCAL_CONNECTION alias as the connection alias used to publish and retrieve instances of this document type.
pub.client.ftp:putCompletedNotification	The publishable document type now specifies the IS_LOCAL_CONNECTION alias as the connection alias used to publish and retrieve instances of this document type.
pub.schema:validate	The service can now validate XMLData against an XML document type.
pub.remote:invoke	Integration Server now ignores the value of the \$close input parameter when a trigger service for a webMethods messaging trigger executes the pub.remote:invoke service, if the watt.server.trigger.reuseSession server configuration parameter is set to true.
pub.trigger:resumeProcessing	The <i>applyChangeAcrossCluster</i> input parameter now applies to webMethods messaging triggers that receive documents from Universal Messaging. Previously, the <i>applyChangeAcrossCluster</i> input parameter applied only to triggers that received documents from Broker.
pub.trigger:resumeRetrieval	The <i>applyChangeAcrossCluster</i> input parameter now applies to webMethods messaging triggers that receive documents from Universal Messaging. Previously, the <i>applyChangeAcrossCluster</i> input parameter applied only to triggers that received documents from Broker.
pub.trigger:suspendProcessing	The <i>applyChangeAcrossCluster</i> input parameter now applies to webMethods messaging triggers that receive documents from Universal Messaging. Previously, the <i>applyChangeAcrossCluster</i> input parameter applied only to triggers that received documents from Broker.

Changed Service	Description
pub.trigger:suspendRetrieval	The <i>applyChangeAcrossCluster</i> input parameter now applies to webMethods messaging triggers that receive documents from Universal Messaging. Previously, the <i>applyChangeAcrossCluster</i> input parameter applied only to triggers that received documents from Broker.

Release 9.8

Added Service	Description
pub.cache:getAll	Retrieves the values of the cached elements for the specified keys.
pub.cache:putAll	Populates a collection of elements in the cache with the specified key-value pairs.
pub.cache:removeAll	Removes the cached elements associated with a list of keys or, if no keys are specified, removes all elements from the cache.
pub.flow:getCallingService	Retrieves the service name and package name of the parent of the calling child service.
pub.event.nerv:subscribe	Subscribes to a particular type of event on the Network for Event Routing and Variation (NERV) and identifies the service that will act as the event handler.
pub.event.nerv:unsubscribe	Unsubscribes from an event type previously subscribed to using the pub.event.nerv:subscribe service.
pub.utils.messaging:migrateDocTypesTriggersToUM	Migrates the messaging provider for publishable document types and webMethods messaging triggers from webMethods Broker to Universal Messaging.
pub.utils:transcode	Transcodes data from one encoding to another.

Removed Service	Replacement, if any
pub.pki.pkcs7:sign	
pub.pki.pkcs7:verify	
pub.pki.smime:createSignedAndEncryptedData	

Removed Service	Replacement, if any
pub.pki.smime:createSignedData	
pub.pki.smime:processEncryptedData	
pub.pki.smime:processSignedData	

Changed Service	Description
pub.cache:remove	Added <i>useWriter</i> input parameter.
pub.flow:savePipelineToFile	Before writing the pipeline to a file, Integration Server verifies whether the provided path is specified in the <i>allowedWritePaths</i> parameter of the file access control configuration file (<i>fileAccessControl.cnf</i>). If it is not, Integration Server does not write the pipeline to a file.
pub.publish:deliver	Added the ability to deliver documents with Universal Messaging.
pub.publish:deliverAndWait	Added the ability to publish documents with Universal Messaging.
pub.publish:envelope	Universal Messaging now supports the read-only parameter <i>destID</i> .
pub.string:bytesToString	Added <i>ignoreBOMChars</i> input parameter.

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Parameter	Description
watt.net.jsse.server.SSLSessionTimeout	Specifies the amount of time in seconds for which Integration Server waits before timing out and removing an SSL session from the SSL cache.
watt.net.jsse.server.useCipherSuitesOrder	Specifies whether the local cipher suites preference should be honored by Integration Server during the SSL/TLS handshake when Integration Server acts as the SSL/TLS server and requires the use of JSSE

Added Parameter	Description
watt.security.kerberos.client.useSPNEGO	Specifies whether Integration Server generates a SPNEGO-based Kerberos ticket for all outbound requests that use Kerberos authentication.
watt.security.max.contentLength	Specifies the maximum size limit of the payload for an HTTP request.
watt.security.max.headerLength	Specifies the maximum length of the header for an HTTP request.
watt.security.max.urlLength	Specifies the maximum length of the URL for an HTTP request.
watt.server.autodeploy.enabled	<p>Specifies whether automatic deployment of packages is enabled or disabled for Microservices Runtime.</p> <p>Note: The automatic package deployment feature is available by default for Microservices Runtime. To use the automatic package deployment feature with Integration Server, your Integration Server must have additional licensing.</p>
watt.server.autodeploy.interval	<p>Specifies the interval, measured in minutes, at which Microservices Runtime executes the autodeploy system task.</p> <p>Note: The automatic package deployment feature is available by default for Microservices Runtime. To use the automatic package deployment feature with Integration Server, your Integration Server must have additional licensing.</p>
watt.server.autodeploy.alwaysUseHotDeployment	<p>Specifies whether or not Microservices Runtime always uses hot deployment for automatic deployment of packages.</p> <p>Note: The automatic package deployment feature is available by default for Microservices Runtime. To use the automatic package deployment feature with Integration Server, your Integration Server must have additional licensing.</p>

Added Parameter	Description
watt.server.checkPath.restorePipelineFromFile	Specifies whether Integration Server verifies that the value of the filename input parameter supplied to pub.flow:restorePipelineFromFile service is in the allowedReadPaths parameter of the file access control configuration file (fileAccessControl.cnf).
watt.server.checkPath.savePipelineToFile	Specifies whether Integration Server verifies that the value of filename input parameter supplied for the pub.flow:savePipelineToFile service is in the allowedWritePaths parameter of the file access control configuration file (fileAccessControl.cnf).
watt.server.coder.responseAsXML	Specifies how Integration Server receives the XML response for any REST API request -- in proper XML format or in converted XML format containing IData objects.
watt.server.jms.trigger.startupFailure.restartTaskRetryCount	Specifies the maximum number of retry attempts the trigger restart task makes to start the JMS triggers that fail to start when the JMS connection alias starts up
watt.server.jms.trigger.startupFailure.restartTaskRetryInterval	Specifies the number of seconds that the trigger restart task waits between attempts to restart JMS triggers that failed to start when the JMS connection alias started.
watt.server.oauth.token.endpoint.auth	Specifies whether the token endpoint accepts an existing session or requires credentials for authentication.
watt.server.publish.maxCSQRedeliveryCount	Specifies the maximum redelivery attempts Integration Server makes when publishing a message from the client side queue (CSQ) to the Broker.
watt.server.SOAP.inbound.CDATA.removeTags	Specifies whether Integration Server removes or preserves the CDATA delimiter tags found in an inbound SOAP request.

Removed Parameter	Replacement, if any
watt.ssl.iaik.clientAllowUnboundRenegotiate	None. This parameter is obsolete. Integration Server uses the Entrust security provider library which has been updated for RFC 5746 to support secure TLS/SSL renegotiation. Secure renegotiation cannot be disabled.
watt.ssl.iaik.serverAllowUnboundRenegotiate	None. This parameter is obsolete. Integration Server uses the Entrust security provider library which has been updated for RFC 5746 to support secure TLS/SSL renegotiation. Secure renegotiation cannot be disabled.

Deprecated Parameter	Replacement, if any
watt.server.publish.maxCSQRedeliveryCount	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.

Release 10.2

Added Parameter	Description
watt.adapters.withOnlineHelp	Specifies a comma-separated list of the adapter names that have online help content that needs to be accessible through the Help link on Integration Server Administrator.
watt.core.xsd.useKnownSchemaLocation	Specifies whether Integration Server includes a “known schema location” and the schemaLocation attribute for an import statement in the WSDL document generated for a provider web service descriptor. When the schemaLocation attribute is not present in the WSDL document, an Integration Server that consumes the WSDL document will not dereference the schemaLocation attribute value during web service processing. If the known schema locations are the only import statements that required namespace resolution, the absence of the schemaLocation attribute allows web service development to occur while not connected to the Internet.
watt.server.checkWhitelist	Specifies whether Integration Server uses a whitelist to filter the list of classes than can be used for deserialization.

Added Parameter	Description
watt.server.circuitBreaker.threadPoolMax	<p>Specifies the maximum number of threads that the server maintains in the circuit breaker thread pool.</p> <p>Note: The circuit breaker feature is available by default for a service that resides in a Microservices Runtime. To use the circuit breaker feature with Integration Server, your Integration Server must have additional licensing.</p>
watt.server.circuitBreaker.threadPoolMin	<p>Specifies the minimum number of threads that the server maintains in the circuit breaker thread pool.</p> <p>Note: The circuit breaker feature is available by default for a service that resides in a Microservices Runtime. To use the circuit breaker feature with Integration Server, your Integration Server must have additional licensing.</p>
watt.server.dumpWhitelist	<p>When whitelist class filtering is enabled, indicates whether or not Integration Server generates a log file that lists any classes for which deserialization was attempted but are not part of a <code>whitelistclasses.xml</code> file.</p>
watt.server.http.Strict-Transport-Security	<p>Specifies whether Integration Server includes Strict-Transport-Security header in response headers</p>
watt.server.http.X-Content-Type-Options	<p>Specifies whether Integration Server includes the X-Content-Type-Options header in response headers.</p>
watt.server.http.X-XSS-Protection	<p>Specifies whether Integration Server includes X-XSS-Protection in the response headers.</p>
watt.server.jms.csq.publishDelayWhileDraining	<p>Specifies the number of seconds that Integration Server waits before publishing a JMS message to the client side queue (CSQ) while the CSQ drains.</p>
watt.server.messaging.csq.publishDelayWhileDraining	<p>Specifies the number of seconds that Integration Server waits before publishing a message to the client side queue (CSQ) while the CSQ drains.</p>
watt.server.oauth.disableClient.disableTokens	<p>Specifies whether a client access token issued to a client account that is disabled can be used to access resources</p>

Added Parameter	Description
watt.server.password.historyLength	Specifies the maximum number of previously set passwords that Integration Server saves in the memory for a user.
watt.server.password.maxIdenticalCharsInARow	Specifies the maximum number of identical characters in a row a password can contain for non-Administrator users.
watt.server.password.maxLength	Specifies the maximum number of characters (alphabetic characters, digits, and special characters combined) the password must contain for non-Administrator users.
watt.server.serverlogMaskBearerToken	Specifies whether Integration Server masks the value of a bearer token when writing to the server log.
watt.server.SOAP.preserveCDATA	Specifies whether Integration Server encodes CDATA blocks in outbound messages.
watt.ssh.jsch.mac_c2s	Specifies the order of message authentication code (MAC) algorithms for client to server transmission.
watt.ssh.jsch.mac_s2c	Specifies the order of message authentication code (MAC) algorithms for server to client transmission.

Changed Parameter	Description
watt.server.password.minDigits	The default value of this parameter is now 0. Integration Server uses the new default value for new Integration Server instances only.
watt.server.password.minLowerChars	The default value of this parameter is now 0. Integration Server uses the new default value for new Integration Server instances only.
watt.server.password.minSpecialChars	The default value of this parameter is now 0. Integration Server uses the new default value for new Integration Server instances only.
watt.server.password.minUpperChars	The default value of this parameter is now 0. Integration Server uses the new default value for new Integration Server instances only.

Removed Parameter	Replacement, if any
watt.server.jms.debugTrace	Use enhanced logging for the JMS connection aliases used by the JMS triggers for which you want Integration Server to generate additional logging.
watt.server.SOAP.HTTP.useMailWriter	None. This parameter was for use with webMethods Mediator which reached end-of-life in 10.1.
watt.xslt.debug.facList	This parameter is obsolete. Use Integration Server Administrator to set the Server Logger configuration for the facilities in the WmXSLT package.
watt.xslt.debug.level	None. Use Integration Server Administrator to set the server logging level for the facilities in the WmXSLT package.
watt.xslt.debug.logfile	None. Integration Server writes log messages for the WmXSLT package to the server.log.

Deprecated Parameter	Replacement, if any
watt.broker.sync.enableBrokerSync	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.broker.sync.forceDispatcherInit	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.brokerCoder.verbose	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.core.brokerTypeCoder.verbose	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.core.brokerCoder.wireFormat	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.auditDocIdField	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.broker.producer.multiclient	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.broker.replyConsumer.fetchSize	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.broker.replyConsumer.multiclient	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.

Deprecated Parameter	Replacement, if any
watt.server.broker.replyConsumer.sweeperInterval	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.brokerTransport.dur	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.brokerTransport.max	None. WebMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.brokerTransport.ret	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.control.maxPersist	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.control.triggerInputControl.delayIncrementInterval	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.control.triggerInputControl.delays	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.dispatcher.comms.brokerPing	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.dispatcher.comms.connectionShareLimit	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.jms.trigger.maxPrefetchSize	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.jms.trigger.wmjms.clientIDSharing	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.jms.wmjms.lms.readTimeout	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.publish.useCSQ	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.publish.drainCSQInOrder	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.publish.usePipelineBrokerEvent	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.
watt.server.trigger.keepAsBrokerEvent	None. webMethods Broker is deprecated, resulting in the deprecation of this parameter.

Changed Parameter	Description
watt.server.content.type.mappings	Specifies a one-to-one mapping of content types for inbound and outbound requests. Previously, this parameter only mapped wildcards found in the Accept header field to a specific content type for the outbound content handler.
watt.server.http.interceptor.preprocess.sizeLimit	Integration Server now includes support for size units with this server configuration parameter. Set this property to N [KB MB GB], where N is any valid integer. Do not include any spaces between the integer and the unit of measure. If you do not specify a unit of measure, Integration Server treats the supplied N value as bytes.
watt.server.http.preserveUriReservedChars	The server configuration property watt.server.http.preserveUriReservedChars has been modified to include "space" as one of the reserved characters as well.

Release 10.1

Added Parameter	Description
watt.art.notification.publishToJMS.useCSQ	Specifies whether the asynchronous notification of Adapter Runtime can use CSQ (Client side Queueing) when publishing to JMS provider.
watt.server.http.interceptor.enabled	Specifies whether an HTTP interceptor is enabled for Integration Server.
watt.server.http.interceptor.impl	Specifies the fully qualified name of the java class for the HTTP interceptor implementation.
watt.server.http.interceptor.preprocess.sizeLimit	Specifies the maximum number of bytes that an HTTP interceptor reads during preprocessing.
watt.server.http.uriPath.decodePlus	Specifies whether or not the '+' character is interpreted as a ' ' when it appears in the path component of the request URI .
watt.server.jms.trigger.startupFailure.retryCount	Determines the maximum number of retry attempts that Integration Server makes to start a JMS trigger after the trigger fails to start.
watt.server.oauth.requirePost	Indicates whether Integration Server requires that client invoke the pub.oauth services via an HTTP POST request.

Added Parameter	Description
watt.server.rg.internalsocket.timeout	Specifies the length of time, in milliseconds, that Enterprise Gateway Server allows a client request to wait for a connection to the Internal Server before terminating the request with an HTTP 500 Internal Server Error.
watt.server.service.list.treatEmptyAsNull	Specifies whether Integration Server assigns a null value to all list data types like Document List, String List, Document Reference List, and Object list during the execution of a flow service without an input value.
watt.server.stats.logFilesToKeep	Specifies the number of stats.log files that Integration Server keeps on the file system, including the current log file. When Integration Server reaches the limit for the number of stats.log files, each time Integration Server rotates the stats.log, Integration Server deletes the oldest archived stats.log file.
watt.server.stats.logRotateSize	Specifies the file size at which Integration Server rolls over the stats.log.
watt.server.uri.decodePath	Specifies whether or not the '+' character is interpreted as a ' ' when it appears in the path component of the request URI.

Removed Parameter	Replacement, if any
watt.net.defaultBufferSize	None. This parameter specifies the maximum content length of an HTTP request that the WmTomcat package will process. The WmTomcat package has been removed from the product.
watt.net.webapp.cookies.useRelevantPath	None. This parameter specifies how WmTomcat can create fewer cookies to prevent the web application from logging out because of exceeding the browser cookie limit. The WmTomcat package has been removed from the product.

Changed Parameter	Description
watt.net.maxClientKeepaliveConns	The default value of this parameter is now 0. Integration Server uses the new default value for new Integration Server instances only.

Changed Parameter	Description
watt.server.http.preserveUriReservedChars	Changes to this property no longer require a restart of Integration Server to take effect. The changes take effect immediately.
watt.server.oauth.requireHTTPS	If you set the value of this property to true and the client application accesses any of the pub.oauth services over HTTP, Integration Server issues an HTTP 400 error response to the client and writes a service exception to the error log. An HTTP 400 error indicates a client error. Previously, Integration Server issued an HTTP 500 error, which indicates a server error. According to the OAuth Framework , it is a client error when the client does not use a secure channel.

Release 10.0

Added Parameter	Description
watt.core.schema.useUnboundedForMaxOccurs	Specifies the number at which a maxOccurs value greater than this number is treated as unbounded.
watt.net.ssl.client.ftps.useJSSE	<p>Controls the use of JSSE for all of the outbound FTPS connections from Integration Server. Set this parameter to true to use JSSE for all of the outbound FTPS connections. Set this property to false to indicate that JSSE is not used for outbound FTPS connections. The default is false.</p> <p>When executing the pub.client:ftp service or the pub.client:ftp:login service, the value of the useJSSE input parameter overrides the value of the watt.net.ssl.client.ftps.useJSSE server configuration parameter.</p>
watt.server.audit.logFilesToKeep	Specifies the number of audit log files, including the current log file for the audit logger, that Integration Server keeps on the file system for an audit logger that writes to a file. When Integration Server reaches the limit for the number of log files for the audit logger, each time Integration Server rotates the audit log, Integration Server deletes the oldest archived audit log file.

Added Parameter	Description
watt.server.audit.logRotateSize	Specifies the file size at which Integration Server rolls over the audit log for a logger that writes to a file.
watt.server.cache.maxEntriesInCache	Specifies the default value for the Maximum Entries in Cache property for a distributed system cache used in an Integration Server cluster.
watt.server.diagnostic.logFiles.maxMB	Specifies the maximum number of megabytes of data that Integration Server reads from the file system for an audit log while collecting diagnostic data. This parameter affects the collection of audit log files only. It does not affect audit log data read from the database, nor does it affect other log files such as the server log, stats log or terracotta-client logs. The default is 250 megabytes. You do not need to restart Integration Server for changes to this parameter to take effect.
watt.server.jms.trigger.groupTag	Specifies the group tag used in the names of JMS triggers that belong to a trigger group. Integration Server treats JMS triggers with the specified group tag in the name as members of a trigger group.
watt.server.remoteInvoke.queryCSRFToken	Indicates if, during remote service invocation, Integration Server queries the remote server for the CSRF token for the current session and then includes the token in the service request. If an Integration Server uses Cross-Site Request Forgery (CSRF) guard, requests sent to the server must include a CSRF token. If the request does not include a CSRF token, the server rejects the request. When an Integration Server performs a remote invoke to execute a service on another Integration Server that uses CSRF guard, the request needs to include the CSRF token. To ensure that the request includes a CSRF token, the requesting Integration Server obtains the CSRF token for the current session from the remote Integration Server. The requesting Integration Server then modifies the request to include the CSRF token. However, this is only necessary if the remote Integration Server uses CSRF guard.

Added Parameter	Description
watt.server.response.displayISErrorCode	<p>Indicates whether the response from Integration Server to a client application in the case of an error situation includes the Integration Server error code in the header and the body of the response.</p> <p>If you set the value of this parameter to false, the response during error situations includes the error message text without the Integration Server error code in both the header and the body of the response.</p> <p>If you set the value to true, the response during error situations includes the Integration Server error code and the corresponding error message text in the header and body of the response.</p> <p>The default value of the parameter is true.</p>
watt.server.SOAP.default.endpointHTTP	Specifies the default provider web service endpoint alias for the HTTP protocol.
watt.server.SOAP.default.endpointHTTPS	Specifies the default provider web service endpoint alias for the HTTPS protocol.
watt.server.SOAP.HTTP.useMailWriter	Configures Axis stack to use an alternate multipart writer implementation based on the JavaMail AP
watt.server.SOAP.identifyISGeneratedWSDL	When creating a web service descriptor from a WSDL document as well as the refresh, Integration Server detects whether the WSDL document was originated by Integration Server.

Removed Parameter	Replacement, if any
watt.server.event.nerv.subscribeService.user	None. The pub.event.nerv:subscribe service has been removed from the product as of Integration Server version 10.0.

Changed Parameter	Description
watt.net.ssl.client.useJSSE	<p>Controls the use of JSSE only for the outbound HTTPS connections from Integration Server.</p> <p>Note: This change does not impact any FTP connections created using the pub.client:ftp and the pub.client.ftp:login services.</p>

Release 9.12

Added Parameter	Description
watt.core.validation.skipAbsentStarBody	Specifies whether to skip a validation that Integration Server performs when decoding mixed content elements that have an enumeration restriction.
watt.server.apiportal.url	Specifies the URL for establishing a connection to API Portal and publishing a REST API descriptor. This parameter derives the API Portal URL from the following: <ul style="list-style-type: none"><li data-bbox="941 651 1461 735">• Host name and port number for the API Portal connection.<li data-bbox="941 756 1396 840">• Tenant for which the REST API descriptor is to be published.<li data-bbox="941 861 1396 945">• Specifications of the REST API descriptor.
watt.server.jca.connectionPool.threadInterrupter.waitTime	Specifies the maximum number of milliseconds that a thread can take while creating or closing a connection before the pool interrupter thread interrupts the thread. After the specified time elapses, the pool interrupter thread considers the thread to be blocked and interrupts it.
watt.server.jca.connectionPool.threadInterrupter.sleepTime	Specifies the number of milliseconds the pool interrupter thread sleeps between sweeps for server threads that became blocked while creating or closing a connection.
watt.server.json.decodeRealAsString	Converts a real number that Integration Server retrieves from JSON content to String.
watt.server.log.maxEntries	Specifies the default number of log entries to be displayed in the log viewing utility.
watt.server.mediator.directives	Specifies a comma-separated list of Mediator directives.

Added Parameter	Description
watt.server.messaging.debugTrace	Enables an extra level of verbose logging for webMethods messaging triggers that receive messages from Universal Messaging or through Digital Event Services. You can configure the additional logging globally or at the individual webMethods messaging trigger level.
watt.server.ns.decodeJavaService	Enables Integration Server to display non-ASCII Unicode characters in the body of a Java service.
watt.server.ns.logDuplicateDocTypeRegistrationAsError	<p>Indicates whether to suppress or continue logging of error messages related to registration of duplicate universal names for a document type. Set the value of the parameter to false to suppress the logging of the error messages and true to resume the logging. The default value of this parameter is true.</p> <p>Note: Setting the parameter value to false suppresses the error messages about duplicate universal names only. It does not resolve the duplicate names.</p>
watt.server.returnCurrentDateTimeString	Returns the current date and time for an Object field that is not of type java.util.Date and has the format "yyyy-MM-dd'T'HH:mm:ss.SSS'Z'".
watt.server.serverlogFilesToKeep	Specifies the number of server log files that Integration Server keeps on the file system, including the current server log file.
watt.server.session.locale.ignore	Specifies whether the default locale for the pub.date* services is the server locale or the locale from the session used by the client that invoked the service.
watt.server.SOAP.pre82WSD.ignoreVersionMismatch	For a web service provider that was created in an Integration Server release earlier than 8.2.2 and for which the Pre-8.2 compatibility mode property is set to true, specifies whether to emulate pre-8.2 behavior for process SOAP requests.

Added Parameter	Description
watt.server.sftp.dateStampFmt	Specifies the format of date to be used in the SFTP client public services, specifically the pub.client.sftp* services in the WmPublic package. To specify the date format to use, you can use any format that is supported by the Java class java.text.SimpleDateFormat. For example, to display the date with the format 08-12-02 14:44:33:1235, specify dd-MM-yy HH:mm:ss:SSSS. If the watt.server.sftp.dateStampFmt property is not set, Integration Server uses the default format, which is yyyy-MM-dd HH:mm:ss z.
watt.server.transaction.xastore.maxTxnPerFile	Specifies the maximum number of unique XA transactions in an XA recovery log file. When the XA recovery log file reaches the maximum number of transactions, Integration Server creates a new file.
watt.server.transaction.xastore.performXALogging	Specifies whether or not Integration Server writes transaction information to the XA recovery store. Set to true to instruct Integration Server to log information about the state and progress of each XA transaction. Set to false to instruct Integration Server to skip logging XA transaction information. The default is true.
watt.server.um.producer.transaction.commitRetryCount	Specifies the number of attempts made by Integration Server in publishing a guaranteed document to a Universal Messaging server, after the initial attempt at publishing fails because of a transaction failure.
watt.um.clientLog.level	Determines the information that is written to the Universal Messaging client log file, called umClient.log. Each level outputs log entries with that level or higher. Valid values are trace, debug, info, warn, error, fatal, and off. The default is error.

Added Parameter	Description
watt.um.clientLog.size	Maximum size, in MB, of the Universal Messaging client log file. When this size is reached, Integration Server rolls the file over to a backup called umClient (number).log and creates a new file.
watt.um.clientLog.fileDepth	Number of backup log files to keep on disk when using log rolling for the Universal Messaging client log file.

Changed Parameter	Description
watt.net.ftpDataConn	Now, when this parameter is set to true, Integration Server allows parallel downloads from multiple FTP sessions. When this parameter is set to false, Integration Server does not allow parallel downloads and reuses the same FTP session. The default is false.
watt.net.jsse.client.enabledCipherSuiteList	To make it easier to specify a long list of allowed cipher suites, Integration Server now allows specifying a file as the value for this parameter.
watt.net.jsse.server.enabledCipherSuiteList	To make it easier to specify a long list of allowed cipher suites, Integration Server now allows specifying a file as the value for this parameter.
watt.net.ssl.client.cipherSuiteList	To make it easier to specify a long list of allowed cipher suites, Integration Server now allows specifying a file as the value for this parameter.
watt.net.ssl.client.useJSSE	The default value of this parameter is now true, indicating that global default for outbound HTTP requests is to use JSSE. Individual outbound requests can override this setting.
watt.net.ssl.server.cipherSuiteList	To make it easier to specify a long list of allowed cipher suites, Integration Server now allows specifying a file as the value for this parameter.
watt.server.cors.allowedOrigins	Now supports the use of regular expressions in the comma-separated list of allowed origin servers. Integration Server treats any value in the comma-separated list that begins with "r:" as a regular expression.

Removed Parameter**Replacement, if any**

watt.ssh.jsch.kex

Release 9.10**Added Parameter****Description**

watt.net.http401.throwException

Specifies whether the pub.client:http service throws a NetException when receiving a 401 error response or, instead, places the HTTP response header and body in the pipeline.

watt.net.http501-599.throwException

Specifies whether the pub.client:http service throws a ServiceException or returns response headers and response body when receiving a 501 to 599 level response from a remote HTTP server.

watt.security.openid.logExceptions

Specifies whether Integration Server writes OpenID errors to the error log.

watt.security.session.forceReauthOnExpiration

Specifies whether Integration Server accepts or rejects a request that includes an expired or invalid session.

watt.server.audit.um.sessionPool.max

Specifies the maximum number of sessions in the Universal Messaging session pool for each Universal Messaging connection alias used by an audit logger.

watt.server.audit.um.sessionPool.min

Specifies the minimum number of sessions in the Universal Messaging session pool for each Universal Messaging connection alias used by an audit logger.

watt.server.audit.um.sessionPool.retryInterval

Specifies the number of seconds Integration Server waits between attempts to re-establish a session on the Universal Messaging server after an audit logger enters queue fail-fast mode.

watt.server.jca.connectionPool.
createConnection.interrupt.waitTime

Specifies the wait time, measured in milliseconds, that elapses before Integration Server interrupts a connection creation thread that is in a wait state

Added Parameter	Description
watt.server.package.pre82WSD.loadExternalResources	Specifies whether, at package load time, Integration Server loads external resources for a consumer web service descriptor or a WSDL first web descriptor created on a version of Integration Server prior to version 8.2 and for which the Pre-8.2 compatibility mode property is set to true.

Changed Parameter	Description
watt.server.oauth.custom.responseHeader	Specifies whether the OpenID redirection endpoint for Integration Server include a brief description of the error in the response header when an OpenID error or Integration Server exception occurs during authentication. Previously, this parameter applied to OAuth authorization server only.
watt.server.stats.pollTime	Restrictions for the value for the parameter. For a stand-alone Integration Server, the watt.server.stats.pollTime must be an integer greater than or equal to 0 (zero). For an Integration Server in a cluster, the watt.server.stats.pollTime must be an integer greater than 0 (zero) but less than or equal to 60.

Release 9.9

Added Parameter	Description
watt.core.validation. skipNoNamespaceReference	Indicates whether or not Integration Server skips validation of references to elements that are not namespace qualified made from within a namespace qualified element during XML validation against a schema.
watt.net.jsse.client.enabled CipherSuiteList	Specifies, using a comma-separated list, the cipher suites used on JSSE sockets that are used while making outbound HTTPS requests.
watt.net.ssl.client.useJSSE	Controls the use of JSSE for all of the outbound HTTPS connections from Integration Server.

Added Parameter	Description
watt.net.jsse.server.enabled CipherSuiteList	Specifies, using a comma-separated list, the cipher suites used on Integration Server ports that use JSSE and handle inbound requests.
watt.server.audit.failFastLoggers	Specifies a comma-separated list of the loggers that can enter into fail-fast mode. If this parameter is empty and fail-fast is enabled in the ISCoreAudit functional alias, all synchronous audit loggers with a database destination will have fail-fast capability.
watt.server.serverlogRotateSize	Specifies the file size at which Integration Server rolls over the server.log file.
watt.server.SOAP.ignoreMissing ResponseHeader	Determines whether missing required headers in a SOAP response results in an error.
watt.server.SOAP.treatNilAsNull	Indicates whether or not Integration Server generates an @xsi:nil field for an element for which the xsi:nil attribute is set to true.
watt.server.trigger.preprocess. monitorDatabaseOnConnectionException	Indicates whether Integration Server schedules a system task to monitor the document history database when a ConnectionException causes a transient error occurs during trigger preprocessing.

Changed Parameter	Description
watt.net.jsse.server.enabledProtocols	Modified to include “SSLv2Hello” as a default value.
watt.server.soap.decodeElementWithPrefix	Extended to work with the decoding of SOAP response messages received by a web service connector and with the pub.xml:xmlNodeToDocument service Previously, this parameter affected the decoding of SOAP request message received by a web service provider only.
watt.server.trigger.preprocess. suspendAndRetryOnError	This server configuration parameter now applies to all trigger types and messaging providers. Previously, the behavior provided by this property applied only to webMethods messaging triggers that received messages from webMethods Broker. Now, this property also works with webMethods messaging triggers that receive messages from Universal Messaging as well as JMS triggers.

Release 9.8

Added Parameter	Description
watt.cachedirective.exclude.packages	Specifies a comma-separated list of packages whose Dynamic Server Pages you want the browser to cache.
watt.debug.warnOnClasspathError	Specifies whether or not a warning message about a missing classpath entry will be written to standard out.
watt.net.jsse.client.enabledProtocols	Specifies the SSL protocol versions that Integration Server supports when acting as a client making outbound requests.
watt.net.jsse.server.enabledProtocols	Specifies the SSL protocol versions that Integration Server supports when acting as a server handling inbound requests.
watt.net.ssl.randomAlgorithm	Identifies the random algorithm name used by Integration Server on HP-UX.
watt.net.ssl.server.handshake. maxVersion	Specifies the maximum version of the SSL protocol that Integration Server supports when acting as the server handling inbound requests.
watt.net.ssl.server.handshake. minVersion	Specifies the minimum version of the SSL protocol that Integration Server supports when acting as the server handling inbound requests.
watt.server.cluster.action.errorOnStartup	Specifies how Integration Server responds when an error at start up prevents Integration Server from joining the cluster.
watt.server.auth.oauth.accessToken. useHeaderFields	Specifies whether Integration Server performs OAuth authentication when an inbound HTTP/S request includes an access_token in the header fields.
watt.server.auth.oauth.accessToken. useQueryParameters	Specifies whether Integration Server performs OAuth authentication when an inbound HTTP/S request includes an access_token in the query parameter
watt.server.enableHotDeployment	This is an internal property.
watt.server.event.nerv. subscribeService.user	Specifies the default user who will invoke the service specified in the pub.event.nerv:subscribe built-in service when an event is received for a subscribed event type.
watt.server.hotDeploymentTimeout	This is an internal property.
watt.server.hotDeployment AutoRecover	This is an internal property.

Added Parameter	Description
watt.server.json.allowUnquotedFieldNames	Specifies whether or not unquoted field names are allowed in JSON text sent to the pub.json:jsonStringToDocument and pub.json:jsonStreamToDocument services. This parameter also determines whether document types created from JSON text contains fields that correspond to unquoted fields as well as quoted fields
watt.server.json.quoteFieldNames	Specifies whether or not the pub.json:documentToJSONString service encloses all generated JSON field names in double quotes.
watt.server.SOAP.generateRequiredTags	Specifies whether or not a SOAP message generated by Integration Server includes empty element tags for required parameters for which a value was not supplied at run time.
watt.server.SOAP.hideEPRHostInFault	Hides the endpoint reference host name and IP address details in the SOAP fault.
watt.server.xml.encoding	Specifies the encoding that Integration Server must use when processing incoming XML files.
watt.server.xml.xmlNodeToDocument.makeArrayforWS	Specifies how Integration Server decodes duplicate elements contained in an anyType element.

Removed Parameter	Replacement, if any
watt.security.pki.jnditimeout	
watt.security.pki.performSync	

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added API	Description
com.wm.app.b2b.server.ServerAPI.logSecurity	Logs a message to the security log. When security logging is enabled and Custom is selected as a security area to audit, use of this method allows users' applications to write entries to the security log.

Deprecated API	Replacement, if any
com.webmethods.vcs.AbstractClient	Use the local service development feature (Local Version Control Integration) to check package elements and their supporting files into and out of a version control system (VCS) directly from Designer
com.webmethods.vcs.VCSClient	Use the local service development feature (Local Version Control Integration) to check package elements and their supporting files into and out of a version control system (VCS) directly from Designer
com.webmethods.vcs.VCSException	Use the local service development feature (Local Version Control Integration) to check package elements and their supporting files into and out of a version control system (VCS) directly from Designer
com.webmethods.vcs.VCSLog	Use the local service development feature (Local Version Control Integration) to check package elements and their supporting files into and out of a version control system (VCS) directly from Designer

Release 10.2

Added API	Description
com.wm.app.b2b.server.ServerAPI. registerCoderForMultipart	Registers a service and associated coder for a multipart content handler (ContentHandler_Multipart). The specified coder is the content handler for REST requests for that service.
com.wm.app.b2b.server.ServerAPI. removeCoderForMultipart	Unregisters the coder for the specified service from multipart content handler.

Deprecated API	Replacement, if any
com.wm.app.b2b.server.jms.producer. ProducerFacace.sendLargeMessageStream	None. webMethods Broker is deprecated, resulting in the deprecation of this method.
com.wm.app.b2b.server.jms.consumer. JMSTriggerFacade.getPrefetchSize	None. webMethods Broker is deprecated, resulting in the deprecation of this method.

Release 10.1

Added API	Description
<code>com.softwareag.is.interceptor.HttpInterceptorException</code>	Exception that can be thrown from an <code>HttpInterceptorIFC</code> implementation of the <code>preProcess()</code> method to interrupt normal processing of the HTTP request.
<code>com.softwareag.is.interceptor.HttpInterceptorIFC</code>	Defines a set of contracts that any <code>HttpInterceptor</code> must implement.
<code>com.wm.xmldata.XmlData</code>	Class for creating, getting, and setting <code>XmlData</code> content.
<code>com.wm.xmldata.XmlDataAnyTag</code>	Class for creating keys that are used as <code>XmlData</code> *any element wildcards.
<code>com.wm.xmldata.XmlDataAttributeTag</code>	Class for creating <code>XmlDataTags</code> for use as attribute names.
<code>com.wm.xmldata.XmlDataConstants</code>	Class implements static methods that server as shortcuts for various <code>XmlData</code> method names. By using a static import of this class, a program can significantly reduce the syntax clutter resulting from long class names and long method names.
<code>com.wm.xmldata.XmlDataContentTag</code>	Class that is a common superclass for the <code>XmlDataTags</code> that may appear in content models.
<code>com.wm.xmldata.XmlDataCopy</code>	Class that implements a structured copying utility for <code>XmlData</code> infosets.
<code>com.wm.xmldata.XmlDataCursor</code>	Class for navigating and manipulating the <code>XMLData</code> element content.
<code>com.wm.xmldata.XmlDataElementTag</code>	Class for creating keys that are used as <code>XmlData</code> element names
<code>com.wm.xmldata.XmlDataException</code>	Class that serves as the base class for all exceptions thrown by the <code>XMLData</code> feature.
<code>com.wm.xmldata.XmlDataGroupTag</code>	Class for constructing an <code>XmlData</code> key for group models.
<code>com.wm.xmldata.XmlDataIteratorTag</code>	Class that provides a standard implementation for creating <code>XmlData</code> iterator-tags.
<code>com.wm.xmldata.XmlDataMap</code>	Class that provides the direct manipulation of fields in an <code>XmlData</code> object without the use of cursors.

Added API	Description
com.wm.xmldata.XmlDataPath	Class to facilitate the encoding or decoding of an XmlData path as a String literal.
com.wm.xmldata.XmlDataSubstitutionTag	Class for creating specialized element tags that are the heads of substitution groups.
com.wm.xmldata.XmlDataTreeCursor	Class that provides additional capabilities beyond those of the XmlDataCursor. In particular, repeating values can be presented as if flattened so that nextItem() and previousItem() position to individual items rather than arrays of items.
com.wm.xmldata.XmlDataTypeTag	Class for creating an XmlDataTypeTag and returning the value of an XMLDataTypeTag.
com.wm.xmldata.XmlNamespaceMap	Class that maintains a mapping between prefixes and namespace URIs.
com.wm.xmldata.xmldocumenttype. SchemaConverterException	Class for throwing a SchemaConverterException.
com.wm.xmldata.xmldocumenttype. XmlDataSchemaConverter	Class that converts the scripted form of an XmlData document type specification to actual XmlData Document Type namespace nodes.
com.wm.xmldata.xmldocumenttype. XmlDataWorkspace	Class that provides a 'local' workspace in which XmlData document types and fields can be created on an ad hoc basis. This class also allows read-only access to the XmlData document types in the Integration Server namespace.

Removed API	Replacement, if any
com.wm.data.XmlData	com.wm.xmldata.XmlData
com.wm.data.XmlDataAnyTag	com.wm.xmldata.XmlDataAnyTag
com.wm.data.XmlDataAttributeTag	com.wm.xmldata.XmlDataAttributeTag
com.wm.data.XmlDataContentTag	com.wm.xmldata.XmlDataContentTag
com.wm.data.XmlDataCursor	com.wm.xmldata.XmlDataCursor
com.wm.data.XmlDataElementTag	com.wm.xmldata.XmlDataElementTag
com.wm.data.XmlDataException	com.wm.xmldata.XmlDataException
com.wm.data.XmlDataGroupTag	com.wm.xmldata.XmlDataGroupTag
com.wm.data.XmlDataSubstitutionTag	com.wm.xmldata.XmlDataSubstitutionTag

Removed API

com.wm.data.obsolete.XmlData

com.wm.data.obsolete.XmlDataCursor

Replacement, if any

com.wm.xmldata.XmlData

com.wm.xmldata.XmlDataCursor

Release 10.0**Added API**

com.wm.app.b2b.server.jms.consumer.
JMSTriggerGroupFacade

Description

Class containing methods for creating, viewing, and deleting JMS trigger groups.

Release 9.12**Added API**

com.wm.data.obsolete.XmlData

Description

Contains the 9.10 version of the com.wm.data.XmlData class. The com.wm.data.XmlData has been revised and simplified in 9.12.

com.wm.data.obsolete.XmlDataCursor

Contains the 9.10 version of the com.wm.data.XmlDataCursor class. The com.wm.data.XmlDataCursor has been revised and simplified in 9.12.

Changed API

Description

`com.wm.data.XmlData`

Revised to present a more consistent programming interface in which there are clearer distinctions between the underlying IData implementation of XmlData and the logical XmlData model as viewed by a typical application. Additionally, the API formalizes aspects of the IData implementation of XmlData to reduce the knowledge of the underlying XmlData implementation that is required to use the methods in the class.

For a detailed list of changes to this class, see the [webMethods Integration Server Java API Reference](#).

Note: If you have any existing Java classes that use this class, you must modify your Java classes to either use new APIs introduced in `com.wm.data.XmlData` or change the Java imports in to reference the 9.10 version of the class which is now contained in `com.wm.data.obsolete.XmlData`.

`com.wm.data.XmlDataCursor`

Revised to present a more consistent programming interface in which there are clearer distinctions between the underlying IData implementation of XmlData and the logical XmlData model as viewed by a typical application. Additionally, the API formalizes aspects of the IData implementation of XmlData to reduce the knowledge of the underlying XmlData implementation that is required to use the methods in the class.

For a detailed list of changes to this class, see the [webMethods Integration Server Java API Reference](#).

Note: If you have any existing Java classes that use this class, you must modify your Java classes to either use new APIs introduced in `com.wm.data.XmlDataCursor` or change the Java imports in to reference the 9.10 version of the class which is now contained in `com.wm.data.obsolete.XmlDataCursor`.

Release 9.10

Added API	Description
com.wm.data.XmlData	Class for creating, getting, and setting XmlData content.
com.wm.data.XmlDataAnyTag	Class for creating keys that are used as XmlData *any element wildcards.
com.wm.data.XmlDataAttributeTag	Class for creating XmlDataTags for use as attribute names.
com.wm.data.XmlDataContentTag	Class that is a common superclass for the XmlDataTags that may appear in content models.
com.wm.data.XmlDataCursor	Class for navigating and manipulating the XmlData element content.
com.wm.data.XmlDataElementTag	Class for creating keys that are used as XmlData element names
com.wm.data.XmlDataException	Class that serves as the base class for all exceptions thrown by the XmlData feature.
com.wm.data.XmlDataGroupTag	Class for constructing an XmlData key for group models.
com.wm.data.XmlDataSubstitutionTag	Class for creating specialized element tags that are the heads of substitution groups.

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses>. <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

IS-RM-103-20181015

webMethods Microgateway 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Microgateway 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	3
4.0	Fixes Included in Each Release.....	3
5.0	Other Resolved Issues.....	3
6.0	Documentation Changes	3
7.0	Terminology Changes	3
8.0	Added, Removed, Deprecated, or Changed Items.....	4
9.0	Copyright Information.....	5
10.0	Support.....	5

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- YAM-218
SSL calls to native service
When invoking native APIs over SSL Microgateway does not verify the service certificates correctly.
- YAM-202
No challenge headers in the response for /microgateway context
When Microgateway administration API is protected with user credentials it does not properly challenge clients. This means it does not add the challenge header to the 401 response.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

The following artifact have been introduced for Microgateway 10.3

- webMethods Microgateway User's Guide

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists features, functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Microgateway provisioning	The Microgateway provisioning allows customers to create multiple Microgateway instances from a single Microgateway installation. The Microgateway provisioning comes in 2 flavors: <ul style="list-style-type: none">- Instance based provisioning- Docker based provisioning
Asset provisioning	The Microgateway can be configured with assets including APIs, policies applications and aliases. Assets can be provisioned by reading them from a running API Gateway or by reading API Gateway export archives available on the file system.
Runtime policy enforcement	The Microgateway supports a basic set of runtime policies including: Require HTTP / HTTPS, Inbound Authentication - Transport, Identify & Authorize Application, Straight Through Routing, Log Invocation and Conditional Error Processing.

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

YAM-RM-103-20181015

webMethods Microservices Runtime 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Microservices Runtime 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

webMethods Microservices Runtime provides a superset of the functionality available in webMethods Integration Server. Review the webMethods Integration Server 10.3 readme for information about webMethods Integration Server 10.3.

1.0	Critical Information	2
2.0	Known Issues	2
3.0	Usage Notes	2
4.0	Fixes Included in Each Release	2
5.0	Other Resolved Issues	3
6.0	Documentation Changes	3
7.0	Terminology Changes	3
8.0	Added, Removed, Deprecated, or Changed Items	4
9.0	Added, Removed, Deprecated, or Changed Built-In Services	6
10.0	Added, Removed, Deprecated, or Changed Parameters	6
11.0	Copyright Information	7
12.0	Support	7

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- As of Microservices Runtime version 10.3, Microservices Runtime creates two predefined URL aliases named “health” and “metrics” which correspond to the health gauge and metrics gathering capabilities respectively. Software AG does not recommend editing the predefined “health” or “metrics” URL aliases.
- If you migrate to Microservices Runtime version 10.3 or higher from an earlier version and you already have a URL alias named “health” and/or “metrics”, Microservices Runtime does not create a health and/or metrics URL alias. Any invocations of the health or metrics endpoints will not result in execution of health indicators or metrics gathering, respectively. If you want to use the health gauge and/or metrics gathering, you need to rename your existing health URL alias. Microservices Runtime will create a new health and/or metrics URL alias that corresponds to the health endpoint and/or metrics functionality upon restart.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.1

- IS_10.0_WmConsul_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.2

- The *Developing Microservices with webMethods Microservices Container* guide has been renamed *Developing Microservices with webMethods Microservices Runtime* to reflect the product name change from webMethods Microservices Container to webMethods Microservices Runtime.

Release 10.0

- Information about using webMethods Microservices Container is located in *Developing Microservices with webMethods Microservices Container*.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 10.2

Old Term	New Term
webMethods Microservices Container	webMethods Microservices Runtime

8.0 Added, Removed, Deprecated, or Changed Items

This section lists features, functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Configuration Variables Template	A configuration variables template is a properties file that contains configuration data as a series of key-value pairs where the key name reflects the asset and particular asset property for which you can supply a value. The property values are set in the template and then applied by a Microservices Runtime at startup. By externalizing configuration information, a single Docker image created for a Microservices Runtime can be used across multiple environments, including different stages of the production cycle.
Automatic Package Deployment	Automatic deployment of packages allows Microservices Runtime to install or upgrade packages automatically without needing to use Deployer or Microservices Runtime Administrator. Automatically deploying packages can be particularly useful for a Microservices Runtime that runs in a Docker container because it allows new or updated packages to be automatically added to the Microservices Runtime running the container which removes the requirement to rebuild the Docker image each time you want to add or update a package.

Added Item	Description
Health Gauge	The health gauge returns an overall UP or DOWN status for the Microservices Runtime based on the collective status of enabled health indicators. When the health endpoint is invoked, Microservices Runtime executes all of the enabled health indicators. A health indicator determines the UP or DOWN status of a specific component of Microservices Runtime. If all of the health indicators return an UP status, the entire Microservices Runtime is considered to be up. If even one of the health indicators returns a DOWN status, the entire Microservices Runtime is considered to be down.
Metrics Gathering for Prometheus	Microservices Runtime includes a metrics endpoint that, when invoked, generates metrics about the server and services on the server. Microservices Runtime returns the statistics in a Prometheus format which the Prometheus server can use to provide insight to the operation of the Microservices Runtime and the services it contains.

Release 10.2

Added Item	Description
Circuit Breaker	The circuit breaker feature provides the ability to configure a circuit breaker for any service residing on a Microservices Runtime or an appropriately licensed Integration Server.

Release 10.0

Added Item	Description
WmConsul Package	Package used for configuring connections to Consul. The WmConsul package also contains public services for registering and deregistering microservices containers as well as locating a host for a specific microservice.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

Release 10.0

Added Service	Description
pub.consul.client:deregisterService	WmConsul. Deregisters a microservice from a Consul server.
pub.consul.client:getAllHostsForService	WmConsul. Queries the Consul server for a list of active hosts that have registered the given microservice with Consul.
pub.consul.client:getAnyHostForService	WmConsul. Queries the Consul server for a list of active hosts that have registered the given microservice with Consul and if there are multiple hosts for this microservice, randomly return one of those hosts.
pub.consul.client:registerService	WmConsul. Registers a microservice with a Consul server. Use as a startup service for the package being registered as a microservice.

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Parameter	Description
watt.server.autodeploy.alwaysUseHotDeployment	Specifies whether or not Microservices Runtime always uses hot deployment for automatic deployment of packages.
watt.server.autodeploy.enabled	Specifies whether automatic deployment of packages is enabled or disabled for Microservices Runtime.
watt.server.autodeploy.interval	Specifies the interval, measured in minutes, at which Microservices Runtime executes the autodeploy system task to check for new or updated packages to deploy.

Release 10.2

Added Parameter	Description
watt.server.circuitBreaker.threadPoolMax	Specifies the maximum number of threads that the server maintains in the circuit breaker thread pool.
watt.server.circuitBreaker.threadPoolMin	Specifies the minimum number of threads that the server maintains in the circuit breaker thread pool.

11.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

12.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

WMIC-RM-103-20181015

webMethods Mobile Suite 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Mobile Suite 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	1
3.0	Usage Notes.....	3
4.0	Fixes Included in Each Release.....	4
5.0	Other Resolved Issues.....	4
6.0	Documentation Changes	4
7.0	Added, Removed, Deprecated, or Changed Items.....	5
8.0	Added, Removed, Deprecated, or Changed Parameters.....	5
9.0	Added, Removed, Deprecated, or Changed APIs	8
10.0	Copyright Information.....	14
11.0	Support.....	15

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- MOBILE-4063
When executing a Jenkins build, the live console output of the build will only be available in

Software AG Designer if CSRF/XSS protection is disabled in your Jenkins server. If CSRF/XSS protection is enabled, the URL to the Jenkins console log is shown instead.

As a workaround, open the Jenkins console in your browser.

- MOBILE-4053
The Jenkins plugin might give access to private keys used to sign projects, for a specifically crafted project by a malicious actor.
There is currently no workaround for this issue. It will be fixed with 10.3 Fix1.
- MOBILE-4051
The Run in Emulator action might not always work for Android *.apk* files. The selected emulator will not start as expected. This issue is typically related to the local installation of Android Studio and SDK.
As a workaround, make sure the emulator executable is located in `<sdkroot>/emulator/emulator`. Note that with Android SDK 25.3.0, the location of the emulator executable changed. If Run in Emulator still does not work, upgrade Android Studio and SDK to latest version.
- MOBILE-4050
When using a header background image for a view, the code generation will result in a compile issue as the `PatternImage` element is not imported correctly.
As a workaround, either select the mobile project and click “Source > Organize Imports” after code generation, or use a method union to programmatically assign the header background image in the `ViewController` implementation.
- MOBILE-4054
The view’s header is not shown if no header text, but only a header image was set.
As a workaround, provide a header text with a space character.
- MOBILE-4049
When creating a vector graphic using the Asset Editor, any circle elements are not saved to the underlying asset file. While the original asset contains the circle - and all exported icons -, the circle cannot be restored when the asset file gets closed and opened again.
As a workaround, convert the circle into a SVG path.
- MOBILE-4071
When navigating to a `TabView` that has no tabs, a run time exception (`NullPointerException`) will be thrown, and the application stops.
As a workaround, do not add any `TabViews` to your application model without tabs.
- MOBILE-4064
When using a `TabView` with Android API 28, a run time exception (`NoSuchMethodError`) will be thrown, and the application stops.
There is currently no workaround for this issue. It will be fixed with 10.3 Fix1.
- MOBILE-4082
When creating a `ListView` in the application model with one `SwipeButton` on the left and one `SwipeButton` on the right, a run time exception (`ArrayIndexOutOfBoundsException`) will be

thrown, and the application stops.

As a workaround, implement the `SwipeButtons` programmatically by overriding the `AbstractListViewController` methods `getSwipeBehaviorRightToLeft()` or `getSwipeBehaviorLeftToRight()`.

- **MOBILE-4084**

In rare cases, an exception (`NullPointerException`) is thrown in the Outline Editor when selecting elements.

As a workaround, close and reopen all models to continue working.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- Mobile Designer will detect installations of Xcode as well as Android Studio and Android SDK automatically. However, if automatic detection fails or if you want to use different locations, update the according properties of the `sdk.properties` file in the root of your Mobile Designer installation. Note that on the Linux platform, the automatic detection is not supported and updating the `sdk.properties` file is mandatory for using Multi-Build or Run in Simulator features.
- The new `ConstraintLayout` templates are not available for simulation in Phoney. For user interface preview, use the integrated preview in Outline or the Layout Builder for the template. To test the `ConstraintLayout` templates at run time, do a simulator Multi-Build and use the new Run in Simulator action available in the Mobile Tools context menu item.
- As of Mobile Designer 10.1, the new run time does not use the Mobile Designer Midlet Thread that was used in all versions up to 9.12 for synchronizing user interface updates in the application. Instead, it now utilizes the main thread provided by the particular native platform for all user interface operations and synchronization. All operations now run on the (native) main thread. This is important for performance of the application and user experience. As in native applications, all heavy operations now need to run on new threads so as not to block the user interface during execution. A set of new APIs (`runAsync()` and `ICallable`) was introduced to make it easy to execute operations in new threads and synchronizing back to the main thread.
- It is also important to note that in case the user interface is not updated automatically, running `syncUI()` on `nUIViewDisplay` will synchronize all changes and update the user interface.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Mobile Designer

Release 10.3

- WWW_9.12_MobileDesigner_Fix7
- WWW_10.1_MobileDesigner_Fix4

Release 10.1

- WWW_9.12_MobileDesigner_Fix3

Mobile Development

Release 10.3

- WWG_9.12_MobileDevelopment_Fix4
- WWG_10.1_MobileDevelopment_Fix3

Release 10.1

- WWG_9.12_MobileDevelopment_Fix3

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Mobile Designer

Release 10.3

- Mobile Administrator guides were removed from the Mobile Suite documentation.

- Windows, Windows Phone, and Windows RT mentions were removed as the Windows platform is no longer supported.
- New Jenkins build feature was documented.
- Documentation was restructured.

Release 10.1

- The documentation was updated.

Mobile Development

Release 10.3

- Mobile Administrator guides were removed from the Mobile Suite documentation.
- Windows, Windows Phone, and Windows RT mentions were removed as the Windows platform is no longer supported.
- New Jenkins build feature and new run configurations were documented.
- New Run in Simulator/Run in Emulator features were documented.
- New Constraint Layout feature was documented.
- Documentation was restructured.

Release 10.1

- The documentation was updated.

7.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

Release 10.3

Mobile Designer

Build Related Parameter (_defaults_.xml)

Added Parameter	Description
android.keystore.properties.file	
android.release.keystore.file	Location of the keystore file used for signing the build.
android.release.keystore.password	Passphrase used to unlock the keystore.
android.release.key.alias	The alias of the key required for signing this build.
android.release.key.password	The password used for the key alias.
android.studio.gradle.android.plugin.version	Controls the version of the Gradle plugin that is used when doing Gradle builds with Android Studio.
android.studio.gradle.distribution.url	
ios.appstore.method	
ios.provisioning.profile.appstore	Points to provisioning profile for an App Store build.
ios.provisioning.profile.adhoc	Points to provisioning profile for an ad-hoc build.
ios.provisioning.profile.development	Points to provisioning profile for a development build.
ios.signing.identity.development	Use this signing identity for development builds. If empty, the signing identity from the provisioning profile will be used.
ios.signing.identity.distribution	Use this signing identity for Appstore, Enterprise and ad-hoc builds. If empty, the signing identity from the provisioning profile will be used.
ios.xcode.managed.signing	If set it to true, Xcode will manage code signing automatically. You also need to provide a Team ID.
ios.xcode.managed.signing.team.uid	Team ID for managed signing in Xcode.
Removed Parameter	Description
ios.xcode.app.path	Xcode installation will now be detected automatically.
ios.devcodesign	Replaced by ios.signing.identity.development.
ios.distcodesign	Replaced by ios.signing.identity.distribution.
ios.adhocprov	Replaced by ios.provisioning.profile.adhoc.
ios.appstoreprov	Replaced by ios.provisioning.profile.appstore.
microsoft.windows8.phone.path	Removed Windows platform support.

Added Parameter	Description
winphone.sdk.version	Removed Windows platform support.
microsoft.net.framework.path	Removed Windows platform support.
microsoft.xna.game.studio.path	Removed Windows platform support.
microsoft.ilmerge.path	Removed Windows platform support.
microsoft.winphone.profile.path	Removed Windows platform support.
microsoft.winphone.toolkit.7.0.path	Removed Windows platform support.
microsoft.winphone.toolkit.8.0.path	Removed Windows platform support.
microsoft.sdk.winphone.extensions.sqlite	Removed Windows platform support.
microsoft.sdk.winrt.extensions.sqlite	Removed Windows platform support.

Build Related Parameter (+Target-build)

Added Parameter	Replacement, if any
pprofile	Optional. Defines path to the iOS provisioning profile. The build type (AppStore, Enterprise, ad-hoc or development) will be deduced automatically.
keychain	Optional. Defines path to the iOS keychain including signing certificates.
extraXcodeArgs	Optional. Extra parameters for passed to iOS xcodebuild tool for generating Xcode archives.
buildnumber	Optional. Defines build number used for when running +Target-Build.

Release 10.1

Mobile Designer

Build Related Properties (_defaults_.xml)

Added Parameter	Description
android.manifest.permissions.exclude.SEND_SMS	To remove SMS_SEND permission form AndroidManifest.
ios.pn.device_token.style	Use via RuntimeInfo.setProperty() with value "raw" to get unformatted push tokens.

Added Parameter	Description
project.runtime.uses.nativeui.phoney	Enable to use new run-time classes.

Deprecated Parameter	Replacement, if any
project.handset.output.preedit.dir.root	
project.handset.output.postedit.dir.root.default	

9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added API	Description
com.softwareag.mobile.md.media.IImagePickerCallback com.softwareag.mobile.md.media.ImagePicker	New ImagePicker API.
com.softwareag.mobile.md.text.validation.IStringValidator com.softwareag.mobile.md.text.validation.RegExStringValidator	New StringValidator API used with entry fields.
com.softwareag.mobile.runtime.nui.nUIButtonAction com.softwareag.mobile.runtime.nui.IListActionListener com.softwareag.mobile.runtime.nui.SwipeBehavior com.softwareag.mobile.runtime.nui.SwipeToDeleteBehavior com.softwareag.mobile.runtime.nui.SwipeToEditBehavior com.softwareag.mobile.runtime.nui.IListProvider public SwipeBehavior getSwipeBehavior(int type, int swipeDirection) public nUIDisplayObject getPlaceholder()	nUIListView swipe API.
com.softwareag.mobile.runtime.nui.IListRenderer public nUIDisplayObject getHeader() public boolean isSpinnerVisible(int type)	
com.softwareag.mobile.runtime.nui.nUIFloatingEntry com.softwareag.mobile.runtime.nui.nUISearchNavbutton com.softwareag.mobile.runtime.nui.ISearchFieldListener	New UI elements.

Added API	Description
com.softwareag.mobile.runtime.nui.nUIConstraintLayout com.softwareag.mobile.runtime.nui.IDisplayObject com.softwareag.mobile.runtime.nui.IButtonElement com.softwareag.mobile.runtime.nui.ITextFieldElement com.softwareag.mobile.runtime.nui.IFloatingEntry com.softwareag.mobile.runtime.nui.IImageElement com.softwareag.mobile.runtime.nui.IEventDispatcher com.softwareag.mobile.runtime.nui.IEventListener	Constraint layout API.
com.softwareag.mobile.core.IMDApplication public boolean allowUnsecureSSLConnectionForURL(String theURL) com.softwareag.mobile.core.MDApplication public boolean allowUnsecureSSLConnectionForURL(String theURL)	
com.softwareag.mobile.runtime.nui.nUIButtonElement public void setFontSize(float points)	
com.softwareag.mobile.runtime.nui.nUIDisplayObject public void setElementIdentifier(String elementIdentifier) public String getElementIdentifier()	
com.softwareag.mobile.runtime.nui.nUIDropdownlistentry public void setIndicatorColor(int color) public int getIndicatorColor()	
com.softwareag.mobile.runtime.nui.nUIEntryElement public void setFontSize(float points) public void setHintTextColor(int argb) public int getHintTextColor();	
com.softwareag.mobile.runtime.nui.nUIObject public void setId(int id) public int getId()	
com.softwareag.mobile.runtime.nui.nUIListView public nUIDisplayObject getHeader() public boolean isSpinnerVisible(int type)	
com.softwareag.mobile.runtime.nui.nUIListElement public nUIDisplayObject getHeader() public boolean isSpinnerVisible(int type)	
com.softwareag.mobile.runtime.nui.nUITextFieldElement public void setFontSize(float points)	
com.softwareag.mobile.runtime.nui.nUIPopupMenuBuilder public nUIPopupMenuBuilder addItem(String item_title, Runnable action, String elementIdentifier)	

Added API	Description
com.softwareag.mobile.runtime.nui.nUIViewDisplay public void setHeaderBackground(IBackgroundDrawable drawable) public IBackgroundDrawable getHeaderBackground()	
com.softwareag.mobile.runtime.nui.nUIWindowDisplay public void setPaneDimensions(int pane, int dimensions[], String elementIdentifier)	
com.softwareag.mobile.runtime.nui.nUIWebView public void setURL(String url, String mimeType)	
com.softwareag.mobile.runtime.nui.nUI* public nUIDisplayObject() public nUIDisplayObject(String text) public nUIDisplayObject(Hashtable properties)	New constructors for <i>nUIDisplayObject</i> (and its subclasses). All constructors now using a <i>Hashtable</i> .
com.softwareag.mobile.runtime.toolkit.delegates.IDialogDelegate public void onDialogButtonPressed(AbstractDialog dialog, int buttonId)	Replaces previously used <i>onAlertDialogButtonPressed</i> (<i>AlertDialog</i> , <i>int</i>).
com.softwareag.mobile.runtime.toolkit.ui.dialog.AbstractAlertDialog	Updated package for <i>AlertDialog</i> .
com.softwareag.mobile.runtime.nui.nUIEntryElement public static final int FORMAT_PIN_HIDDEN = 3	Replaces previously used <i>FORMAT_NUMBER_HIDDEN</i> .
Removed API	Description
com.softwareag.mobile.runtime.toolkit.delegates.IDialogDelegate public void onAlertDialogButtonPressed(AbstractAlertDialog dialog, int buttonId)	Replaced by new API. See added APIs.
com.softwareag.mobile.runtime.toolkit.ui.AbstractAlertDialog	Package changed. See added API.
com.softwareag.mobile.runtime.nui.nUIEntryElement public static final int FORMAT_PIN_HIDDEN = 3	Name changed. See added APIs.
Deprecated API	Description
com.softwareag.mobile.runtime.media.CameraHandler com.softwareag.mobile.runtime.media.ICameraHandlerCallback	

com.softwareag.mobile.runtime.nui.nUIButtonElement
 public void setFontSize(int font_size)
 public int getFontSize()
 public void setFontSizeAbsolute(int size_in_pixels,
 boolean accessibility_adjusted)
 public void setFontSizeRelative(int rel_font_id, int scale)

com.softwareag.mobile.runtime.nui.nUIEntryElement
 public void setFontSize(int font_size)
 public int getFontSize()
 public void setFontSizeAbsolute(int size_in_pixels,
 boolean accessibility_adjusted)
 public void setFontSizeRelative(int rel_font_id, int scale)

com.softwareag.mobile.runtime.nui.nUITextfieldElement
 public void setFontSize(int font_size)
 public int getFontSize()
 public void setFontSizeAbsolute(int size_in_pixels,
 boolean accessibility_adjusted)
 public void setFontSizeRelative(int rel_font_id, int scale)

com.softwareag.mobile.runtime.nui.nUIPopupMenuBuilder
 public nUIPopupMenuBuilder addItem(String title, Runnable action)

com.softwareag.mobile.runtime.nui.nUIWindowDisplay
 public void setPaneDimensions(int pane, int dimensions[])

com.softwareag.mobile.runtime.nui.nUI*
 constructors with nuiid parameter

See added APIs for
 constructors to use.

Release 10.1

Added API	Description
com.softwareag.mobile.reshandler.AntTaskResourceHandler public void addDirContentAsAssetCatalogs(String dir)	
com.softwareag.mobile.runtime.nui.nUIDisplayObject public boolean isVisible() public void setVisible(boolean visible)	Hide/show <i>nUIDisplayObjects</i> at run time.
com.softwareag.mobile.runtime.nui.nUIWindowDisplay public IGlobalPropertiesIOS getIOSGlobalProperties() public IGlobalPropertiesAndroid getAndroidGlobalProperties()	Access to iOS and Android specific properties, e.g., tint colors of <i>nUINavButtons</i> .
com.softwareag.mobile.runtime.nui.IGlobalPropertiesIOS com.softwareag.mobile.runtime.nui.IGlobalPropertiesAndroid	

Added API	Description
com.softwareag.mobile.runtime.core.Application public void onStartAppFromPushNotification(PushNotification message) public PushNotification getStartPushNotification() public IPushNotificationListener setPushNotificationListener(IPushNotificationListener listener) com.softwareag.mobile.runtime.pn.PushNotification com.softwareag.mobile.runtime.pn.IPushNotificationListener	Push Notifications.
com.softwareag.mobile.md.digest.MD5Sum public String getDigest(String s) public String getDigest(String s, String encoding) public String getDigest(byte[] bytes)	MD5 Checksum support for <i>String</i> and <i>byte[]</i> types.
com.softwareag.mobile.core.MDApplication com.softwareag.mobile.core.IMDApplication com.softwareag.mobile.core.IMDApplicationListener com.softwareag.mobile.md.util.concurrent.IResultCallback	New entry point of every application.
com.softwareag.mobile.runtime.comms.Connection com.softwareag.mobile.runtime.comms.Response com.softwareag.mobile.runtime.comms.HttpResponse com.softwareag.mobile.runtime.comms.IConnectionCallback	New connection API for HTTP connections.
com.softwareag.mobile.runtime.nui.nUIListView com.softwareag.mobile.runtime.nui.nUIListElement com.softwareag.mobile.runtime.nui.IListRenderer com.softwareag.mobile.runtime.nui.IListProvider com.softwareag.mobile.runtime.nui.IListListener	New ListView API.
com.softwareag.mobile.runtime.RuntimeInfo com.softwareag.mobile.runtime.SystemInfo	Access to run time and system information.
com.softwareag.mobile.md.io.File	New file API for accessing local file systems.
com.softwareag.mobile.md.net.ConnectivityStatusRequester com.softwareag.mobile.md.net.IConnectivityWatcher	New connectivity monitoring API.
com.softwareag.mobile.md.imagetools.AssetImageLoader	AssetImage API to work with new asset catalogs.
com.softwareag.mobile.runtime.toolkit.operations.queue.BasicOperationQueue com.softwareag.mobile.runtime.toolkit.operations.queue.ConditionalOperationQueue	New operation queueing API.

Added API	Description
com.softwareag.mobile.runtime.toolkit.transformer.ImageTransformer	New image/asset transformer.
com.softwareag.mobile.runtime.toolkit.operations.cache.CacheFirstCacheHandler	New operation caching API.
com.softwareag.mobile.runtime.toolkit.operations.cache.CacheOnlyCacheHandler	
com.softwareag.mobile.runtime.toolkit.operations.cache.FileCacheManager	
com.softwareag.mobile.runtime.toolkit.operations.cache.IOperationCacheHandler	
com.softwareag.mobile.runtime.toolkit.operations.cache.ServerFirstCacheHandler	
com.softwareag.mobile.runtime.toolkit.operations.cache.ServerOnlyCacheHandler	
com.softwareag.mobile.runtime.nui.nUITableElement public void updateRelativeWidths(int[] new_rel_widths)	
com.softwareag.mobile.runtime.nui.nUIWebView	
com.softwareag.mobile.runtime.nui.nUIWebViewElement public String evaluateJavaScript(String script) public void evaluateJavaScript(String script, IJSCallback callback)	

Removed API	Replacement, if any
com.softwareag.mobile.runtime.toolkit.ui.controller.AbstractViewController boolean isVisible(final nUIDisplayObject element) boolean setVisible(final nUIDisplayObject element, final Boolean isVisible) boolean forceHide(final nUIDisplayObject element)	<i>nUIDisplayObject</i> now has methods to change visibility.
com.softwareag.mobile.runtime.toolkit.ui.controller.IResourceController public Image loadImage(final String name, final int viewBackgroundColor) public Image loadImage(final String name, final int viewBackgroundColor, final int containerWidth)	

Deprecated API	Replacement, if any
com.softwareag.mobile.runtime.core.Application com.softwareag.mobile.runtime.core.CanvasCore com.softwareag.mobile.runtime.core.CanvasBase com.softwareag.mobile.runtime.core.CanvasDimensions com.softwareag.mobile.runtime.core.CanvasInterrupts com.softwareag.mobile.runtime.core.CanvasMenu com.softwareag.mobile.runtime.core.CanvasNativeUI com.softwareag.mobile.runtime.core.CanvasSoftKeys com.softwareag.mobile.runtime.core.CanvasThreading com.softwareag.mobile.runtime.comms.HttpConnectionHandler com.softwareag.mobile.runtime.toolkit.ui.controller.AbstractViewController protected String getGeneralGraphicsFolder(final int viewBackgroundColor, final int containerWidth) protected Image tryLoadImage(final String image) protected String getPlatformGraphicsFolder(final int viewBackgroundColor) protected String getWinPhoneGraphicFolder(final int width, final int height, final int viewBackgroundColor) protected String getWinPhoneThemeFolder(final int backgroundColor) protected String getIOSGraphicsFolders(final int currentScreenPPI, final int viewBackgroundColor) protected String getAndroidGraphicsFolder(final int currentScreenPPI, final int viewBackgroundColor)	New <i>MDApplication</i> classes.

Changed API	Description
com.softwareag.mobile.runtime.toolkit.ui.controller.AbstractViewController protected Image loadImage(final String name, final int viewBackgroundColor) protected Image loadImage(final String name, final int viewBackgroundColor, final int containerWidth)	public to protected

10.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates

and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

MOB-RM-103-20181015

webMethods Monitor 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Monitor 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information	2
2.0	Known Issues	3
3.0	Usage Notes	4
4.0	Fixes Included in Each Release	4
5.0	Other Resolved Issues	7
6.0	Documentation Changes	9
7.0	Terminology Changes	9
8.0	Added, Removed, Deprecated, or Changed Built-In Services	9
9.0	Copyright Information	10
10.0	Support	10

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

- webMethods Monitor 10.3 requires that the program files and user interface are the same version. When installing webMethods Monitor 10.3, you must install webMethods Monitor 10.3 Program Files along with the 10.3 version of the Monitor User Interface located under My webMethods Server User Interfaces on the install tree.
- webMethods Monitor 10.3 requires My webMethods Server 10.3. Before you can use webMethods Monitor, you must configure My webMethods connection parameters from the WmMonitor Home page. To access the configuration page, on the Package Management page in Integration Server Administrator, click the Home icon for the WmMonitor package. For complete information about configuring My webMethods connection parameters, see webMethods Monitor User's Guide.
- webMethods Monitor 10.3 is compatible only with the 10.3 version of Optimize for Process and Optimize for Infrastructure. However, Monitor 10.3 is compatible with the latest version of these products in the 10.x versions of all other webMethods products.
- webMethods Monitor 10.3 lists process instances from the current day's activity by default. When you use Monitor to view process instances, Monitor lists only process instances from the current day's activity. To retrieve other process instances, you can specify an alternate date range in the Advanced tab on the Process Instances page.
- When you use Microsoft SQL Server and you create Process Audit Log database objects, a warning message is displayed stating that the index is too large. You can ignore this message.
- To use the archive feature, if the schema for the archive tables does not exist on the same database instance as the schemas for Process Audit Log and IS Core Audit Log, you must configure additional database properties:
 - *For Oracle:* Set up a DBLINK for the Process Audit Log and IS Core Audit Log databases. The DBLINK must contain the username and password for those databases. The parameters in the OPERATION_PARAMETER table on the archive database must match those in the DBLINKs created for the Process Audit Log and IS Core Audit Log databases.
 - *For SQL Server:* Add a linked server from the archive database to the Process Audit Log and IS Core Audit Log databases. The username and password must be identical on both database servers when using two different servers. In other words, the username and password that you use to log on to the archive database must be the same as the username and password on the target database to be archived. If you are using two different SQL Server databases, the Microsoft Distributed Transaction Coordinator (MSDTC) must be running on both servers. For more information, see the [Knowledge Base article](#) on the Microsoft Help and Support website and this [linked servers article](#)

on the Experts Exchange website.

- *For IBM DB2*: Archiving across database instances is not supported.

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- WMN-3970
With Internet Explorer 11, process model images may not render in Google Widget Toolkit.
When viewing process diagrams with Internet Explorer 11, process model images may not render.
Workaround: Clear the browser history and browser cache.
- WMN-3976
Process model images may not be rendered completely after upgrading the model to version 9.x.
After upgrading a process model, steps or transitions that are in negative canvas space will be cut off in the Google Widget Toolkit process diagram.
There is currently no workaround for this issue.
- WMN-4092
Process diagram step labels and transitions may not render in Google Widget Toolkit.
Step labels and transitions extending into negative coordinates will not be rendered.
There is currently no workaround for this issue.
- WMN-4119
Under Internet Explorer 11, external pools are rendered with solid lines in Google Widget Toolkit.
When viewing process diagrams with Internet Explorer 11, process models containing external pools are rendered with solid lines rather than dashed lines.
There is currently no workaround for this issue.
- WMN-4124
Swimlanes may contain horizontal lines in Google Widget Toolkit rendering.
Pools that overlap in Designer may paint in a different order in a Monitor process diagram rendered with Google Widget Toolkit.
Workaround: Ensure that pools do not overlap when drawing pools in Designer.
- WMN-4457
Processes defined with a custom ID cannot be triggered with logging levels 1 or 2.
If a process model uses the service `pub.prt.log:logCustomId` to define a custom ID, the process cannot be triggered if logging levels are set to 1 or 2.
There is currently no workaround for this issue.
- WMN-5003
Business Process page displays exception “No result set was produced.” when using SQL Server.
Under certain configurations, the Business Process page may display the exception “No result set was produced” when a list of process models is displayed under a SQL Server configuration.

There is currently no workaround for this issue.

- WMN-5241
Creating and saving a stage definition in the Edit Process page will cause the Business Processes page to be displayed rather than the Edit Process page.
There is currently no workaround for this issue.
- WMN-5246
Searching process instances using a custom date range may display incorrect results.
When searching for process instances using a custom date range, the resulting list of process instances do not take into account the local time of the browser and may include processes outside of the date range.
There is currently no workaround for this issue.
- WMN-6443
Service Archiving in Oracle environments might lead to the following error message:
“OTHER EXCEPTIONS OCCURRED!-2429ORA-02429: cannot drop index used for enforcement of unique/primary key' The issue occurs when Oracle SYS_XXX indexes exist on some tables (for example WMSERVICEACTIVITYLOG and WMERROR table).
To work around this issue, manually delete the SYS_XXX indexes created by Oracle for all affected tables.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- MON_9.9_Fix12
- MON_10.1_Fix4

Release 10.2

- MON_10.1_MWS_Fix2
- MON_10.1_Fix2

Release 10.1

- MON_9.12_Fix2
- MON_10.0_Fix1
- MON_10.0_Fix2

Release 10.0

- MON_9.0_SP1_Fix11
- MON_9.5_SP1_Fix6
- MON_9.7_Fix14
- MON_9.9_Fix7
- MON_9.12_Fix1

Release 9.12

- MON_8.2_SP1_Fix22
- MON_9.5_SP1_MWS_Fix8
- MON_9.6_Fix8
- MON_9.7_MWS_Fix6
- MON_9.7_Fix9
- MON_9.8_Fix7
- MON_9.10_Fix1

Release 9.10

- MON_9.5_SP1_MWS_Fix7
- MON_9.6_MWS_Fix10
- MON_9.7_MWS_Fix7
- MON_9.8_MWS_Fix2

Release 9.9

- MON_9.0_SP1_Fix6
- MON_9.0_SP1_MWS_Fix5
- MON_9.6_Fix7
- MON_9.7_MWS_Fix4
- MON_9.7_Fix5
- MON_9.8_Fix1
- MON_9.8_MWS_Fix2

Release 9.8

- MON_8.2_SP1_MWS_Fix7
- MON_9.5_SP1_MWS_Fix2
- MON_9.5_SP1_Fix3
- MON_9.6_Fix5
- MON_9.6_MWS_Fix7
- MON_9.7_Fix1
- MON_9.7_MWS_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.1

- WMN-5821
Execution status of a DBO process in “BAM and BPM” view may show incorrect status. In the Business Processes “BAM and BPM” page, if a DBO process is enabled or disabled for execution, the execution status may remain unchanged. The correct execution status will be displayed and can be modified in the “Edit Process” page if the process is subsequently edited or in the “BPM only” view.
This issue is now resolved.

Release 10.0

- WMN-5831
Processes with a status of Revised cannot be stopped or suspended in the Process Instance Detail page.
For processes with a status of Revised, the Stop or Suspend buttons are not displayed in the Process Instance Detail page.
This issue is now resolved.

Release 9.10

- WMN-5242
Defining a stage where the End Milestone is defined as a Start operation will cause the milestone to be displayed with a Completed operation.
The issue is resolved.

Release 9.8

- WMN-4529
Process models are not displayed in the Process Instance page and Business Process Edit Process page when those pages are opened with Internet Explorer 9 (IE9).
Newly developed process models do not display when Monitor is run under Internet Explorer 9.
This issue is now resolved.
- WMN-4525
The Date and Time fields in the Process Stage Timeline window always appear in English.
This issue is now resolved.

- WMN-4672
 Enable/ disable process works only with "Modify and Resubmit" privilege.
 This issue is now resolved. A new functional privilege is added to the Business Process.
 It is "Configure and Enable" - This is used to configure/edit business processes models in the Administration page.
 By default, the page/user has the grant permission.
 "Resubmit and Modify" Functional privilege will no longer affect the administration page.
 This requires that both MON_9.6_Fix5 & MON_9.6_MWS_Fix7 be installed, and IS must be restarted after any permission changes.
- WMN-4661
 When "pub.monitor.process.instanceControl:resubmitAllFailed" is run, it may result in MonitorException: Failed in trying to resubmit all: java.lang.NumberFormatException
 This issue is now resolved.
- WMN-4524
 BAM only process may always show as Used=No in the MWS/Monitor UI.
 This issue is now resolved.
- WMN-4182
 Process Archiving for DB2 may produce errors if invoked from IS/MWS.
 This could be caused due to compatibility with DataDirect driver update.
 This issue is now resolved.
- WMN-2932
 In the process instance detail page, download buttons are disabled after saving a pipeline to a file.
 This issue is now resolved.
- WMN-4442
 Process image may not display consistently in IE9 despite setting the response header to IE=9 as mentioned in the Monitor 9.6 User's Guide.
 This could be caused due to a developer option which forced the use of F12 Developer Tools mode in IE9 to enable the process diagram.
 This issue is now resolved. After installing the fix, the browser cache may need to be cleared on IE9 in order for the fix to be effective.
 Other notes: For IE9 and IE10 the MWS host needs to be added as a Trusted site in Internet Explorer > Internet Options > Security tab
 For the ability to run mixed versions of IE, a Response Header such as "IE=9, IE=10" or "IE=Edge" can be used.
- WMN-4546
 Business Process page may display "Unknown Exception" after migration from previous release.
 This issue is now resolved.

- WMN-3956
A NullPointerException is raised when doing any archiving from MWS UI (Data Management > Archive Audit Data page) if there were no process models present.
This issue is now resolved.
- WMN-4567
Process instance detail page results in NPE when process minimum log level is lower than 4.
This issue is now resolved.
- WMN-4551
Transition lines within a subprocess are not rendered properly.
When a subprocess inside a swimlane is expanded in the process diagram in Monitor, the transition lines are not rendered properly.
This issue is now resolved.
- WMN-4510
Viewing a process diagram on the Business Process Administration page causes an error.
Clicking on the process in Monitor Business Process Administration page causes the following error: [MON.0119.0016E] Could not create process image: java.lang.NullPointerException.
This issue is now resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

The Monitor User's Guide and Monitor Built-In Service Reference documentation is available as a combined webhelp set on the Software AG Empower website.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

Release 10.1

Changed Service	Description
pub.monitor.archive:setOperationParameters	Three new input parameters have been added: <ul style="list-style-type: none">• DBO_PROCESSES• DBO_PROCESS_STATUS_CRITERIA• USE_BATCH_ARCHIVE

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

MON-RM-103-20181015

My webMethods Server 10.3 Readme

October 2018

This file contains important information you must read before using My webMethods Server 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	7
6.0	Documentation Changes	11
7.0	Terminology Changes	12
8.0	Added, Removed, Deprecated, or Changed Items.....	12
9.0	Added, Removed, Deprecated, or Changed APIs	20
10.0	Copyright Information.....	115
11.0	Support.....	116

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- MWS-16536
When working with business rules in My webMethods, opening an event rule results in JavaScript errors and the rule is not rendered correctly.
When you open an event rule after a decision table is already open, the browser throws JavaScript errors and the event rule is not rendered correctly.
There is currently no workaround for this issue.
- MWS-24627
Upgrading a My webMethods Server instance that uses the embedded database to version 10.3 fails with one of the following error messages:
 - "Error during gathering data"
 - "Error while creating migrated server node".There is currently no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- My webMethods Server instances, installed on Windows Server 2016 might fail to initialize unless started with administrator permissions.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- MWS_10.2_Fix1
- MWS_10.1_Fix6
- MWS_10.1_SPM_Fix1
- MWS_10.0_Fix4
- MWS_10.0_SPM_Fix1

- MWS_9.12_Fix27
- MWS_9.12_SPM_Fix1
- MWS_9.12_SPM_TE_Fix1
- MWS_9.10_Fix28
- MWS_9.10_SPM_Fix1
- MWS_9.10_SPM_IS_Fix1
- MWS_9.9_Fix29
- MWS_9.9_SPM_Fix2
- MWS_9.9_GLUE_Fix2
- MWS_9.8_Fix39
- MWS_9.8_SPM_Fix5
- MWS_9.8_GLUE_Fix3
- MWS_9.7_Fix36
- MWS_9.7_SPM_Fix3

Release 10.2

- MWS_10.1_Fix2
- MWS_10.0_Fix4
- MWS_10.0_SPM_Fix1
- MWS_9.12_Fix18
- MWS_9.12_SPM_Fix1
- MWS_9.10_Fix25
- MWS_9.9_Fix22
- MWS_9.9_SPM_Fix2
- MWS_9.8_Fix36
- MWS_9.7_Fix34
- MWS_9.6_Fix26

- MWS_9.5_SP1_Fix31
- MWS_9.0_SP1_Fix16

Release 10.1

- MWS_10.0_Fix2
- MWS_9.12_Fix9
- TE_9.12_TC_Fix1
- MWS_9.10_Fix17
- MWS_9.9_Fix18
- TE_9.9_TC_Fix2
- MWS_9.8_Fix28
- MWS_9.8_GLUE_Fix3
- TE_9.8_TC_Fix1
- MWS_9.7_Fix29
- TE_9.7_TC_Fix2
- MWS_9.6_Fix23
- TE_9.6_TC_Fix2
- MWS_9.5_SP1_Fix29
- MWS_8.2_SP1_Fix31

Release 10.0

- MWS_9.12_Fix3
- MWS_9.10_Fix9
- MWS_9.9_Fix10
- MWS_9.8_Fix19
- MWS_9.8_GLUE_Fix2
- MWS_9.7_Fix23

- TE_9.7_TC_Fix2
- MWS_9.6_Fix18
- TE_9.6_TC_Fix2
- MWS_9.5_SP1_Fix23
- MWS_8.2_SP1_Fix29

Release 9.12

- MWS_9.10_Fix2
- MWS_9.10_SPM_Fix1
- MWS_9.10_SPM_IS_Fix1
- MWS_9.9_Fix5
- MWS_9.9_GLUE_Fix2
- MWS_9.9_SPM_Fix1
- MWS_9.8_Fix12
- MWS_9.8_SPM_Fix4
- MWS_9.7_Fix16
- MWS_9.6_Fix16
- MWS_9.6_SPM_Fix3
- MWS_9.5_SP1_Fix22
- MWS_9.0_SP1_Fix13
- MWS_8.2_SP1_Fix28
- TE_9.8_TC_Fix1
- TE_9.6_Fix1
- TE_9.5_SP1_TC_Fix3

Release 9.10

- MWS_9.9_Fix2

- MWS_9.9_GLUE_Fix1
- MWS_9.8_Fix8
- MWS_9.8_GLUE_Fix1
- MWS_9.7_Fix12
- MWS_9.6_Fix10
- MWS_9.6_GLUE_Fix1
- MWS_9.5_SP1_Fix15
- MWS_9.0_SP1_Fix9
- MWS_8.2_SP1_Fix26
- TE_9.7_TC_Fix1
- TE_8.2_SP1_TC_Fix7

Release 9.9

- MWS_9.8_Fix3
- MWS_9.7_Fix7
- MWS_9.6_Fix8
- MWS_9.5_SP1_Fix11
- MWS_9.0_SP1_Fix7
- MWS_8.2_SP1_Fix24

Release 9.8

- MWS_9.7_Fix3
- MWS_9.6_Fix5
- MWS_9.5_SP1_Fix6
- MWS_9.0_SP1_Fix5
- MWS_8.2_SP1_Fix19
- MWS_8.0_SP2_Fix20

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- MWS-23340
My webMethods Server fails to delete a user profile. The issue occurs if the user attempts to delete their profile immediately after exporting the profile data.
The issue is resolved.
- MWS-22700
A security issue with permissions to `wm_mws_diagnostics` components was discovered in My webMethods Server.
The issue is resolved.
- MWS-22696
A security issue with button controls vulnerable to XSS attacks was discovered in My webMethods Server.
The issue is resolved.
- MWS-23272
A security issue with unauthenticated access to server resources was discovered in My webMethods Server.
The issue is resolved.

Release 10.2

- MWSSOF-1714
A CSV injection vulnerability was discovered in My webMethods Server.
The issue is resolved.
- MWS-22327
My webMethods Server does not support session-based token generation for CSRF tokens.
The issue is resolved. Now you can configure the previously removed functionality for session-based token generation using the My webMethods Server user interface. To enable session-based CSRF token generation:
 1. Log in as `sysadmin` and navigate to `Folders > Administrative Folders > Administration Dashboard > Configuration > XSRF Security Configuration`.
 2. Clear the checkbox for the default setting, which is 'Use secret-based token generator'.
 3. Click Submit.My webMethods Server will now generate CSRF tokens per session.
- MWS-22659

Asset Build Environment does not allow the use of third-party libraries when building My webMethods Sever assets.

The issue is resolved. You can now add third-party libraries to use only at compile time for building My webMethods Sever assets.

To include third-party libraries, create a new directory in the root directory of the project, and name that directory 'lib-compile'. Any custom .jar files placed in the 'lib-compile' directory will be used only at compile time, and will not be included in the project build.

Release 10.1

- MWS-21673
A CSV injection vulnerability was discovered in My webMethods Server.
The issue is resolved.
- MWS-21252
A security issue with logging in debug mode was discovered in My webMethods Server.
The issue is resolved.

Release 10.0

- MWS-18703
When processing SOAP service calls, for example from the WmTaskClient package in Integration Server, My webMethods Server might cause increased memory consumption.
The issue is resolved.
- MWS-19947
Jackrabbit libraries should be updated to get the latest fixes.
The issue is resolved.
- MWS-20464
When you configure the JNDI URL of a standalone My webMethods Server or use My webMethods Server in a cluster, starting the Common Directory Services component logs JmsRemoteCommandTransport errors in the Integration Server log. The issue occurs when My webMethods Server loses connectivity to the Universal Messaging server.
The issue is resolved.

Release 9.12

- MWS-17522
Upgrading My webMethods Server to version 9.10 using a .zip file fails.
When you attempt to upgrade a My webMethods Server installation to version 9.10 using a .zip file as a source, the upgrade fails with multiple "ERROR: Missing file in source installation." errors. The issue occurs because the files in the *Software AG_directory/profiles/MWS_instanceName/configuration* directory are not included in the .zip file.
The issue is resolved.

- MWS-15586
 My webMethods Server returns an exception when connecting to webMethods Integration Server via a web application view.
 When a My webMethods Server web application attempts to connect to Integration Server using a web service connector with a basic or hybrid connection, the system returns an “unable to create user context” exception.
 The issue is resolved.
- WTN-3684
 On the Business Data page in My webMethods, the Intrinsic Task Metrics event maps are improperly set as user-defined.
 When you expand the Intrinsic Task Metrics node on the Administration > Analytics > KPIs > Business Data page in My webMethods, the DEFINED BY column for the Intrinsic Task Metrics event maps displays the value of "User". However, intrinsic event map and KPI definitions should be system-defined to prevent users from deleting or modifying the definitions.
 The issue is resolved. The DEFINED BY column for the Intrinsic Task Metrics event maps now has a value of "System".

Release 9.10

- MWS-16198
 After migration, the About page of My webMethods Server does not show the correct version.
 On the About page in My webMethods, when you click the My webMethods Server tab under Licensed Product, the tab still shows the old version instead of the current one.
 The issue is resolved.
- MWS-15647
 Web Services Stack logs multiple error messages in the My webMethods Server _server.log during asset deployment.
 When you deploy assets to My webMethods Server using webMethods Deployer, Web Services Stack logs multiple "No 'endpoint' property set and serverSide=true, cannot uniquely identify endpoint for service" error messages in the _server.log.
 The issue is resolved.
- MWS-15122
 The SOAP Monitor portlet fails to communicate with My webMethods Server.
 When you attempt to use the SOAP Monitor portlet in My webMethods Server, the SOAP monitor applet starts but shows the following error: "The SOAP Monitor is unable to communicate with the server".
 The issue is resolved.

Release 9.9

- MWS-14666
 After converting a Task List Management CAF portlet to OpenCAF, clicking the Return button on

the Task List Management page in My webMethods results in a `javax.portlet.PortletException` with the following message: "Cannot remove the same component twice".

This issue is now resolved.

- MWS-13158

The Principal Picker in webMethods Business Console does not display a scroll bar in the dialog box to scroll down and select users in the list.

While using Business Console in My webMethods Server, if a user attempts to assign a task instance using Assign To or Accept For on the Task List Management page, the Principal Picker does not display a scroll bar in the dialog box to scroll down and select users in the list.

This issue is now resolved.

Release 9.8

- MWS-13401

Integration Server sometimes throws a "cannot start CDS library" error when My webMethods Server and Integration Server are migrated together but Integration Server is started first.

When My webMethods Server and Integration Server are both migrated to the latest release, but Integration Server is started first after migration, the following error is displayed during Integration Server startup: "[POP.005.0040] Cannot start CDS library because MWS upgrade did not complete yet".

This issue is now resolved.

- MWS-13432

Some nodes remain in temporary maintenance mode after being restarted together with the default My webMethods Server node.

Some My webMethods Server cluster nodes still remain in temporary maintenance mode, even though they have been taken out of temporary maintenance and My webMethods Server has been restarted.

This issue is now resolved.

- MWS-13448 / MWS-13447

Maintenance mode is not in synch on all My webMethods Server nodes when the Universal Messaging Server is unavailable.

When My webMethods Server is configured to use Universal Messaging Server as a JMS provider and the Universal Messaging Server is unavailable, not all My webMethods Server nodes go into maintenance mode, which is the expected behavior.

This issue is now resolved.

- MWS-13453

When a role is granted only custom task permissions such as View Task: Data, Info and Audit, View Comments, the Security Realm > View Item permission for a task is automatically set to Deny. As a result, a role member cannot access the task instance details on the Task List Management page.

This issue is now resolved.

- MWS-13286
My webMethods Server login page is not localized.
When My webMethods Server is set to maintenance mode, the login page for the server administrator is not localized.
This issue is now resolved.
- MWS-13316
A NullPointerException occurs while editing the Administration portlet.
When a system administrator logs into My webMethods Server and attempts to edit the Administration portlet under Folders > System > Portlets, a NullPointerException error is displayed in the My webMethods Server user interface or the server logs, or in both.
This issue is now resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- The My webMethods Server documentation set is available as a webhelp on the Software AG Empower website.

Release 10.0

- The *Administering My webMethods Server* guide is available as a webhelp on the Software AG Empower website.
- A new chapter, “Sending Mobile Notifications from My webMethods Server”, has been added to the *Administering My webMethods Server* guide.

Release 9.12

A new chapter, “Using Command Central to Manage My webMethods Server”, has been added to the PDF guide *Administering My webMethods Server*. The chapter contains information about how you use the Software AG Command Central web user interface and command line interface to manage My webMethods Server.

Release 9.10

A new chapter, “Configuring the Time Zone in My webMethods”, has been added to the PDF guide *Working with My webMethods*.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Removed Item	Replacement, if any
--------------	---------------------

The My webMethods Server embedded database (Derby) is removed.

Changed Item	Description
--------------	-------------

The following properties of the Noodle skin for customizing the default color scheme of the My webMethods user interface:

The new default value is #1776BF. The old value was #0899CC.

shadow-background-color/banner

colors/leftnav1-bg

colors/titlebar-bg

colors/login-button-top

colors/login-button-bottom

colors/section-group-bg

colors/button-mini-bg

colors/button-mini-border-light

colors/dialog-modeless-border

colors/nav3-selected-bg

The new default value is #14629F. The old value was #379FC3.

colors/login-button-top-hover

The new default value is #1C8CE3. The old value was #04B2E0.

colors/login-button-bottom-hover

Changed Item	Description
colors/section-head-bg</name>	The new default value is #1776BF. The old value was #52B7DB.
colors/swap-head-bg	The new default value is #666666. The old value was #eaeaea.
colors/table-msg-bg	The new default value is #CDE6F9. The old value was #D7E9F1.
colors/notify-bg	
colors/notify-border	The new default value is #96CAF3. The old value was #BDDBE9.

Release 10.2

Added Item	Description
GDPR configuration portlet	

Removed Item	Replacement, if any
Support for Axis 1.4, which is used for exposing web services from My webMethods Server, is removed.	Now My webMethods Server web services use Axis 1.7.7.

Changed Item	Description
mws ping command	The mws ping command now requires Administrator credentials.
My webMethods Server cache configuration	The My webMethods Server cache configuration is enhanced.
My webMethods Server secret key storage	The My webMethods Server secret keys are stored using a passman store.
mws update command	The mws update command now enables you to rename a node in a My webMethods Server cluster.
My webMethods Server migration utility	The migration utility now enables you to rename a node in a My webMethods Server cluster.

Release 10.1

Added Item	Description
New additional JVM properties to configure secure connection to the Universal Messaging server.	<p>You can use the following additional JVM properties in the <code>custom_wrapper.conf</code> file to configure secure connection to the Universal Messaging server:</p> <ul style="list-style-type: none">- <code>nirvana.ssl.keystore.path</code>- <code>nirvana.ssl.keystore.pass</code>- <code>nirvana.ssl.keystore.cert</code>- <code>nirvana.ssl.truststore.path</code>- <code>nirvana.ssl.truststore.pass</code>- <code>nirvana.ssl.protocol</code> <p>For more information, see <i>Administering My webMethods Server</i>.</p>
Business Administration node in the installer tree under the My webMethods Server node.	<p>A new node named Business Administration has been added to the installer tree under the My webMethods Server node.</p>
MySQL support for use with Task Engine	<p>For more information about how to use MySQL with My webMethods Server and Task Engine, see <i>Administering My webMethods Server</i>.</p>

Deprecated Item	Replacement, if any
The My webMethods Server embedded database (Derby) is deprecated.	

Changed Item	Description
The font family has been changed to the standard Roboto font.	

Release 10.0

Added Item	Description
<p>New additional JVM properties to adjust the http client settings.</p>	<p>You can use the following additional JVM properties in the custom_wrapper.conf file to configure connection settings when making web service calls using the Axis SOAP client:</p> <ul style="list-style-type: none">- axisclient.DefaultMaxConnectionsPerHost- axisclient.MaxTotalConnections <p>For more information, see <i>Administering My webMethods Server</i>.</p>
<p>New additional JVM properties to configure a user name and password for connecting to Universal Messaging.</p>	<p>You can use the following additional JVM properties in the custom_wrapper.conf file to configure credentials for connecting to Universal Messaging:</p> <ul style="list-style-type: none">- lax.nl.env.PRINCIPAL- lax.nl.env.PASSWORD
Removed Item	Replacement, if any
<p>The localControl authentication option is removed from My webMethods Server commands.</p>	<p>The 'mws ping', 'mws import', and 'mws export' commands now require authentication.</p>
<p>Using the database as a JMS provider for My webMethods Server clusters is removed.</p>	<p>Using the My webMethods Server database as a JMS provider for cluster communication is removed. The replacement is using the Universal Messaging server. For more information, see <i>Administering My webMethods Server</i>.</p>
Changed Item	Description
<p>My webMethods users must provide their current password when attempting to change the password.</p>	<p>When updating their profile information, My webMethods users must supply their old password to set a new one. This does not apply to administrative users who change the password of other users.</p>
<p>Automatic reconnection settings for LDAP directory services.</p>	<p>You can enable the automatic reconnection to LDAP for directory services in My webMethods Server, and set a custom amount of time to wait between reconnection attempts.</p>

Release 9.12

Added Item	Description
Option to configure universally unique identifier (UUID) for My webMethods Server users accessed through an external user directory service.	<p>A utility is required to update the universally unique identifier (UUID) for My webMethods Server users accessed through an external user directory service. Additionally, an option is required to remove invalid users from My webMethods Server.</p> <p>By default, the external directory service configured with My webMethods Server uses distinguished names (DNs) to identify users. In this case, if a user is transferred from one organization unit to another, My webMethods Server cannot recognize that user because of a change in the user's DN. Moreover, My webMethods Server cannot recognize users who are deleted from a directory service or moved in a directory service, and such users are regarded as invalid users.</p> <p>You can configure My webMethods Server to use UUID, so that users are identified when the DN changes. You can run the <code>UserDirectory_UpdateUUID</code> utility to update the UUID for My webMethods Server users accessed through an external user directory service. To remove invalid users, you can run the <code>Cleanup_InvalidUsers</code> utility.</p> <p>For more information about those utilities, see <i>Administering My webMethods Server</i> and <i>My webMethods Server Portlet Reference</i>.</p>
Expose the Jetty JMX MBeans in the embedded Jetty container.	Enable all of the <code>org.eclipse.jetty.*</code> MBeans in the JMX console for My webMethods Server.

Deprecated Item	Replacement, if any
Support for Axis 1.x, which is used for exposing web services from My webMethods Server, is deprecated.	
Support for webMethods Glue	

Deprecated Item	Replacement, if any
Using the database as a JMS provider for My webMethods Server clusters is deprecated.	webMethods Universal Messaging

Changed Item	Description
Improved My webMethods Server logging	The width of log messages is shortened by using an enhanced pattern layout from <code>org.apache.log4j.EnhancedPatternLayout</code> .
My webMethods Server uses Apache Jackrabbit 2.x.	My webMethods Server now uses Apache Jackrabbit 2.x. The previous Apache Jackrabbit version that the server was using is no longer supported and contains security vulnerabilities.

Release 9.10

Added Item	Description
SAML 2.0 authentication	If you select the Hybrid authentication mode, SAML 2.0 is used by default. To use SAML Artifact Profile, set the <code>wsclient.hybrid.use.samlartifact</code> property to true in the <code>custom_wrapper.conf</code> file in the following My webMethods Server directory: <i>Software AG_directory/profiles/MWS_instanceName/</i> configuration.

Removed Item	Replacement, if any
SOAP Monitor portlet communication port	The SOAP Monitor portlet no longer uses the SOAP Monitor applet that communicated with My webMethods Server over a custom socket. For this reason, the SOAP Monitor portlet communication port (5001 by default) is no longer required or opened. If a My webMethods Administrator has the port open in their firewall, they can remove this configuration.

Changed Item	Description
The SOAP Monitor, Color Picker, and File Attachment applets have been converted to CAF components.	In more recent versions of Chrome and Firefox applets are disabled by default and must be manually enabled. They represent security risks.

Changed Item	Description
Redirecting of URLs	A redirect to a URL starting with // should not be used for a relative redirect URL.

Release 9.9

Added Item	Description
The following CSS properties of the Noodle skin for customizing the default login page of My webMethods Server, using the skin editor.	
align/login-remember-me	Defaults the "Remember me" text of the check box for remembering the login credentials to the left.
fonts/login-defaults	Allows editing the font style for labels, error messages, remember-me and placeholder text.
colors/login-input-border	Defines the color of the login page border.
colors/login-text-button	Defines the text color of the login button.
colors/login-button-top	Defines complex gradient colors for the login button.
colors/login-button-top-hover	Defines complex gradient colors for the login button.
colors/login-button-bottom	Defines complex gradient colors for the login button.
colors/login-button-bottom-hover	Defines complex gradient colors for the login button.
fonts/login-errors	Specifies changes to error message text.
fonts/login-button	Allows editing the font style of the login button text.

Removed Item	Replacement, if any
The following CSS properties of the Noodle skin for customizing the default login page of My webMethods Server:	
colors/login-title	
colors/login-title-bg	

Removed Item	Replacement, if any
fonts/login-title	
colors/login-description-bg	

Deprecated Item	Replacement, if any
The legacy approach for customizing the My webMethods Server Login page that entails using the skin editor to edit the CSS properties of the <code>wm_login</code> portlet.	In addition to the legacy customization approach, you can use the OpenCAF Shell Login template in Software AG Designer to customize the Login page of My webMethods Server. For more information about using OpenCAF, see <i>webMethods CAF Development Help</i> .

Changed Item	Description
The following CSS properties of the Noodle skin for customizing the default login page of My webMethods Server, using the skin editor:	
colors/login	The new default value is '#A9A9BB'. The old value was '#747d86'.
colors/login-bg	The new default value is '#f0f0f0'. The old value was '#E2E4D7'.
colors/login-border	The new default value is '#d9d9d9'. The old value was '#c3c8cc'.
fonts/login	The new default value is 'font-size: 18px'. The old value was 'line-height: 1; font-weight: normal;'.
fonts/login-link	Fonts/login-link is now fonts/login-remember-me. It defaults to empty.
The internal structure of the Import Template View CAF control	Instead of being direct children of the Import Template View control, the controls loaded from the imported view are now held in a new "__viewLoaded" facet. However, because a facet can contain only one component, the imported controls are wrapped in a UIPanel control. As a result, the direct parent of the imported controls is the UIPanel wrapper, and the Import Template View control, in turn, is the parent of the UIPanel wrapper.

Release 9.8

Added Item	Description
Jetty 9	My webMethods Server has upgraded to using Jetty 9.

Removed Item	Replacement, if any
File Content Migration Portlet (Wm_content_migration.war) and related Deployer component. The My webMethods Server File Content Migration portlet was deprecated in a previous release and is removed in this release.	
MWS start "-m" option. The "-m" command line option is now obsolete in all My webMethods Server 9.x versions.	

9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added API	Description
com.softwareag.mws.screens.BaseScreenClass	Class com.softwareag.mws.screens.BaseScreenClass added
com.softwareag.mws.screens.Constants	Class com.softwareag.mws.screens.Constants added
com.softwareag.mws.screens.MWSLoginLogoutScreen	Class com.softwareag.mws.screens.MWSLoginLogoutScreen added
com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen	Class com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen added
com.webmethods.bpm.process.impl.BpmProcess	Method 'protected void loadFromIS()' has been added
com.webmethods.bpm.process.impl.BpmProcessManager	Method 'public BpmProcessManager()' has been added
com.webmethods.bpm.process.impl.BpmProcessManager	Method 'public java.lang.String getDatasourceLibMode()' has been added

com.webmethods.bpm.process.impl.BpmProcessManagerIS: Class
com.webmethods.bpm.process.impl.BpmProcessManagerIS added

com.webmethods.bpm.process.impl.db.common.LoadProcessStepsIS: Class
com.webmethods.bpm.process.impl.db.common.LoadProcessStepsIS added

com.webmethods.caf.common.ServerCommon: Class com.webmethods.caf.common.ServerCommon
added

com.webmethods.caf.common.XMLUtil: Method 'public javax.xml.parsers.DocumentBuilderFactory
getBuilderFactory()' has been added

com.webmethods.caf.common.XMLUtil: Method 'public javax.xml.parsers.SAXParserFactory
getSAXParserFactory()' has been added

com.webmethods.caf.common.XMLUtil: Method 'public org.xml.sax.XMLReader
getXMLParser(java.lang.ClassLoader)' has been added

com.webmethods.caf.faces.application.CAFValueExpression: Method 'public java.lang.Object
getCAFValue(javax.el.ELContext)' has been added

com.webmethods.caf.faces.data.object.ObjectMethodContentProvider: Method 'protected boolean
isSessionExpired()' has been added

com.webmethods.caf.faces.data.task.TaskBusinessCalendarModel: Method 'protected
com.webmethods.sc.calendar.IWorkdayCalendar getCalendarByID(java.lang.String)' has been added

com.webmethods.caf.faces.data.ws.wss.WSSContentProvider: Method 'protected boolean
isSessionExpired()' has been added

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected java.lang.String
convertViewId(javax.faces.context.FacesContext, java.lang.String)' has been added

com.webmethods.caf.faces.render.html.input.DateInputRenderer: Method 'protected java.lang.Object
convertDate(javax.faces.context.FacesContext, javax.faces.component.UIComponent, java.lang.Object,
boolean, boolean)' has been added

com.webmethods.caf.wsclient.util.WSClientUtil: Method 'public java.util.Map
constructClientAPI(java.lang.Class, java.lang.String, java.lang.String)' has been added

com.webmethods.caf.wsclient.util.WSClientUtil: Method 'public void reloadResource(java.lang.Class)'
has been added

com.webmethods.caf.wsclient.util.XSDDateFormatMWS: Class
com.webmethods.caf.wsclient.util.XSDDateFormatMWS added

com.webmethods.portal.bizPolicy.command.install.InstallBootstrapComponentsWithDependencies:
Method 'protected boolean checkRealLocation(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.install.InstallBootstrapComponentsWithDependencies:
Method 'protected java.lang.String getComponentRealLocation(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContent: Method 'protected
boolean checkResourceExists(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS: Method 'protected java.io.InputStream getISTaskAppStream(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.impl.BootstrapPhase: Method 'protected void waitForOSGIServices()' has been added

com.webmethods.portal.jms.JMSPhaseProvider: Method 'protected void bindGlobalProvider(com.webmethods.portal.service.global.IGlobalProvider)' has been added

com.webmethods.portal.jms.JMSPhaseProvider: Method 'protected void bindRemoteEventDelivery(com.webmethods.portal.system.init.IInitializable)' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public com.webmethods.portal.service.meta2.IUserService getUserService()' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public com.webmethods.portal.service.meta2.thing.IThingID initializeUserWithResult(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public void initializeUser(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.install.impl.BasicInstallMechanics: Method 'protected boolean checkNeedsComponent(java.util.List, java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.BasicInstallMechanics: Method 'protected java.lang.String getComponentLocationToRealLocation(java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.InstallResolver: Method 'public void init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.PortletInstallMechanics: Method 'protected com.webmethods.portal.service.portlet.info.IPortletInfo loadPortletInfo(java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.UpgradeInstallComponentData: Method 'protected java.lang.String getComponentLocationToRealLocation(java.lang.String)' has been added

com.webmethods.portal.mech.portlet.IPortletProviderMechanics: Method 'public com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream, java.io.InputStream)' has been added to an interface

com.webmethods.portal.mech.portlet.impl.PortletProviderMechanics: Method 'public com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream, java.io.InputStream)' has been added

com.webmethods.portal.mech.portlet.impl.PortletProviderMechanics: Method 'public void init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.socialbpm.comments.impl.CommentsMechanics: Method 'public com.webmethods.portal.service.meta2.thing.IThingID getThingID(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.sql.impl.ConnectionManagerMechanicsIS: Class
com.webmethods.portal.mech.sql.impl.ConnectionManagerMechanicsIS added

com.webmethods.portal.mech.task.ITaskHelper: Method 'public
com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added to an
interface

com.webmethods.portal.mech.task.impl.TaskChangeHandler: Method 'public TaskChangeHandler()' has been added

com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS: Method 'public void
ensureTaskLwqFileExist(java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskCompletionHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskCompletionHandlerIS added

com.webmethods.portal.mech.task.impl.TaskHelper: Method 'public
com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.mech.task.impl.TaskHelperService: Method 'public
com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.mech.task.impl.TaskMechanics: Method 'protected void
initHandlers(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskMechanicsIS: Method 'protected void
initHandlers(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskScheduleHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskScheduleHandlerIS added

com.webmethods.portal.mech.task.impl.TaskTimedEventHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskTimedEventHandlerIS added

com.webmethods.portal.noodle.util.NoodleUtils: Method 'public boolean
isForceNewTab(com.webmethods.portal.service.view.IView)' has been added

com.webmethods.portal.service.dir.IDirPrincipal: Method 'public boolean isInitialized()' has been
added to an interface

com.webmethods.portal.service.dir.impl.DirSystem: Method 'public void
onSynchronousEvent(com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent)' has been added

com.webmethods.portal.service.install.impl.BaseInstallService: Method 'protected java.lang.String
getResourceLocation(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.service.install.impl.BaseInstallService: Method 'protected void
registerComponent(com.webmethods.portal.system.IInitializableComponentData, java.lang.String)' has been added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected
com.webmethods.portal.schema.wmportletapp.PortletType _loadPortletType(java.util.Map)' has been
added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected void _doRegisterComponent(java.util.Map)' has been added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected void _saveTempPortletInitData(java.util.Map)' has been added

com.webmethods.portal.service.meta2.util.ThingHelper: Class
com.webmethods.portal.service.meta2.util.ThingHelper added

com.webmethods.portal.service.portlet.IPortletProvider: Method 'public
com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream,
java.io.InputStream)' has been added to an interface

com.webmethods.portal.service.portlet.impl.PortletProvider: Method 'public
com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream,
java.io.InputStream)' has been added

com.webmethods.portal.service.socialbpm.comments.impl.CommentsServiceIS: Class
com.webmethods.portal.service.socialbpm.comments.impl.CommentsServiceIS added

com.webmethods.portal.service.sql.ISqlWorker: Method 'public void close()' has been added to an interface

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public boolean isCurrentlyInUse()' has been added

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public void close()' has been added

com.webmethods.portal.service.sql.runtime.base.CommentEntryUserDeleted: Class
com.webmethods.portal.service.sql.runtime.base.CommentEntryUserDeleted added

com.webmethods.portal.service.task.ITaskDefinition: Method 'public
com.softwareag.caf.shared.task.core.model.TaskDataDefTable getTaskDataTable()' has been added to an interface

com.webmethods.portal.service.task.ITaskSystem: Method 'public
com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added to an interface

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Method 'public boolean isHiddenUpdate()' has been added

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Method 'public void setHiddenUpdate(boolean)' has been added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Method 'public
java.net.URLClassLoader getTaskClassLoader(java.lang.String)' has been added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Method 'public void
removeTaskClassLoader(java.lang.String)' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public
com.softwareag.caf.shared.task.core.model.TaskDataDefTable getTaskDataTable()' has been added

com.webmethods.portal.service.task.impl.TaskDistributionServiceIS: Class
com.webmethods.portal.service.task.impl.TaskDistributionServiceIS added

com.webmethods.portal.service.task.impl.TaskProcessAuditServiceIS: Class
com.webmethods.portal.service.task.impl.TaskProcessAuditServiceIS added

com.webmethods.portal.service.task.impl.TaskSystem: Method 'protected void
bindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been
added

com.webmethods.portal.service.task.impl.TaskSystem: Method 'public
com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.system.BaseComponent: Method 'protected void
bindGlobalProvider(com.webmethods.portal.service.global.IGlobalProvider)' has been added

com.webmethods.portal.system.PortalSystem: Method 'public boolean isTELlibrary()' has been added

com.webmethods.portal.system.init.impl.ClusterPhaseProvider: Method 'protected java.lang.String
getLocalConfigRootPath()' has been added

com.webmethods.portal.system.init.impl.ClusterPhaseProvider: Method 'protected void
initDbConnection()' has been added

com.webmethods.portal.system.lock.impl.LockKey: Class
com.webmethods.portal.system.lock.impl.LockKey added

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Method 'protected
java.lang.String checkTaskAppVersionIsUptodate(java.lang.String)' has been added

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Method 'protected void
fixOldTaskClasses(java.io.File, java.lang.String)' has been added

com.webmethods.rtl.locator.impl.ClassLocator: Method 'public ClassLocator(java.lang.String,
java.lang.String)' has been added

com.webmethods.rtl.tools.PrettyProperties\$NameValue: Class
com.webmethods.rtl.tools.PrettyProperties\$NameValue added

com.webmethods.rtl.tools.PrettyProperties: Class com.webmethods.rtl.tools.PrettyProperties added

com.webmethods.rtl.util.xml.XMLUtil: Method 'public java.lang.String toString(org.w3c.dom.Node,
int, boolean)' has been added

com.webmethods.caf.faces.portlet.PortletViewHandler: Added
com.sun.faces.application.view.MultiViewHandler to the list of superclasses

com.webmethods.caf.jcr.faces.data.query.PropertySearchTerm: Added protected field sRandom

com.webmethods.caf.wsclient.proxy.impl.WSClientDynamicProxy: Added public field
REMOVE_WSDL_FROM_GLUE_CACHE

com.webmethods.mws.acdl.GenerateAcdlForProject: Added public field OPTION_IS_TASK_ENGINE

com.webmethods.portal.bizPolicy.command.task.webservice.QueueTaskWS: Added protected field

DELAY_DEFAULT_VALUE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field DB_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field DB_ATTR_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field LDAP_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field LDAP_ATTR_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field PROFILE_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field USER_INFORMATION_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added public field USER_PROFILE_ATTR_TITLE

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_CUSTOM_HOSTS_PROP

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_DISABLED_PROP

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_POLICY_ENABLED

com.webmethods.portal.service.dir.impl.DirSystem: Added

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent\$ISynchronousListener to the set of implemented interfaces

com.webmethods.portal.service.sql.ISqlWorker: Added java.lang.AutoCloseable to the set of implemented interfaces

com.webmethods.portal.service.sql.core.BaseSqlWorker: Added java.lang.AutoCloseable to the set of implemented interfaces

com.webmethods.portal.service.sql.core.ConnectionManager: Added public field ORACLE_URL_PARSER_EXPRESSION_SERVICENAME

com.webmethods.portal.service.sql.core.ConnectionManager: Added public field ORACLE_URL_TEMPLATE_SERVICENAME

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Added protected field hiddenUpdate

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Added public field TASK_ASSETS_HOME_PROP

com.webmethods.portal.system.PortalSystem: Added public field TASK_ENGINE_LIBRARY_MODE
com.webmethods.rtl.locator.impl.StreamLocatorFactory: Added public field TEMP_PROTOCOL

Removed API

Replacement, if any

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'public java.lang.Object getWrapped()' has been removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'public javax.faces.application.ViewHandler getWrapped()' has been removed

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource: Method 'protected java.util.List getProfileAttributes(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.service.dir.IDirPrincipal)' has been removed

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS: Method 'protected com.webmethods.portal.system.IURI importNode(com.webmethods.portal.bizPolicy.IContext, org.w3c.dom.Element, com.webmethods.portal.system.IURI, java.util.List)' has been removed, but an inherited definition exists.

com.webmethods.portal.event.impl.RemoteEventDeliveryInitializer: Method 'protected void bindJMSPhaseProvider(com.webmethods.portal.system.IComponent)' has been removed

com.webmethods.portal.framework.mech.install.PortletAppilcationInstallMechanics: Method 'protected void clearContextRequestAttributes(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.mech.task.ITaskHelper: Method 'public com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been removed

com.webmethods.portal.mech.task.impl.TaskHelperService: Method 'public com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been removed

com.webmethods.portal.mech.task.impl.TaskMechanicsIS: Method 'protected com.webmethods.portal.service.task.ITaskList listTasks(com.webmethods.portal.system.IURI, com.webmethods.portal.service.task.TaskSearchQuery, boolean, boolean)' has been removed, but an inherited definition exists.

com.webmethods.portal.service.task.ITaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has been removed

com.webmethods.portal.service.task.ITaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' has been removed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader: Class com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has been removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' has been removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public long getDbTimeOffset()' has been removed

com.webmethods.portal.system.lock.impl.ClusterLockingService: Method 'public long getDbTimeOffset()' has been removed

com.webmethods.rtl.util.PrettyProperties\$NameValue: Class
com.webmethods.rtl.util.PrettyProperties\$NameValue removed

com.webmethods.rtl.util.PrettyProperties: Class com.webmethods.rtl.util.PrettyProperties removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed field wrapped

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed javax.faces.FacesWrapper from the set of implemented interfaces

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed
javax.faces.application.ViewHandlerWrapper from the list of superclasses

com.webmethods.caf.jcr.faces.data.query.PropertySearchTerm: Removed field random

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field
MIN_INBOX_SEARCH_THREADS

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field
MIN_TASK_UPDATE_THREADS

Deprecated API

Replacement, if any

com.webmethods.portal.mech.task.impl.TaskHelper: Method 'public com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been deprecated

com.webmethods.portal.service.sql.ISqlWorker: Method 'public void release()' has been deprecated

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public void release()' has been deprecated

Changed API

Description

com.webmethods.caf.faces.component.output.ChartDataColumn: Parameter 1 of 'public void setItemValue(java.lang.Number)' has changed its type to java.lang.Object

com.webmethods.caf.faces.component.output.ChartDataColumn: Return type of method 'public java.lang.Number getItemValue()' has been changed to java.lang.Object

com.webmethods.caf.faces.portlet.PortletViewHandler: In method 'public PortletViewHandler(javax.faces.application.ViewHandler)' the number of arguments has changed

com.webmethods.caf.faces.render.html.input.DateInputRenderer: In method 'protected void writeTimeZone(javax.faces.context.FacesContext, javax.faces.component.UIComponent, java.util.Date)'

the number of arguments has changed

com.webmethods.portal.mech.task.impl.TaskMechanics: In method 'public void fireTaskChangedEvent(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, com.webmethods.portal.service.task.ITask, com.webmethods.portal.service.task.ITask, java.lang.Object, java.lang.Object, int, boolean)' the number of arguments has changed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: In method 'public java.lang.Object getTaskInstance(java.lang.String)' the number of arguments has changed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: In method 'public void addTaskClassLoader(com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader)' the number of arguments has changed

com.webmethods.portal.system.lock.IClusterLockingService: In method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' the number of arguments has changed

com.webmethods.portal.system.lock.IClusterLockingService: Parameter 2 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to long

com.webmethods.portal.system.lock.IClusterLockingService: Parameter 4 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to boolean

com.webmethods.portal.system.lock.impl.ClusterLockingService: In method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' the number of arguments has changed

com.webmethods.portal.system.lock.impl.ClusterLockingService: Parameter 2 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to long

com.webmethods.portal.system.lock.impl.ClusterLockingService: Parameter 4 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to boolean

com.webmethods.rtl.util.xml.XMLUtil: In method 'protected void _dumpXML(org.w3c.dom.Node, java.io.Writer, int, int)' the number of arguments has changed

Release 10.2

Added API

Description

com.softwareag.mws.screens.BaseScreenClass Class com.softwareag.mws.screens.BaseScreenClass added

com.softwareag.mws.screens.Constants Class com.softwareag.mws.screens.Constants added

com.softwareag.mws.screens.MWSLoginLogoutScreen Class
com.softwareag.mws.screens.MWSLoginLogoutScreen added

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen
Class

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen
added

com.webmethods.caf.common.cipher.MWSCipherDataStore Class
com.webmethods.caf.common.cipher.MWSCipherDataStore added

com.webmethods.caf.common.cipher.MWSCipherMasterPassword Class
com.webmethods.caf.common.cipher.MWSCipherMasterPassword added

com.webmethods.caf.common.cipher.SecretDS Class com.webmethods.caf.common.cipher.SecretDS
added

com.webmethods.caf.faces.component.util.ShadowComponentMapCacheEntry Class
com.webmethods.caf.faces.component.util.ShadowComponentMapCacheEntry added

com.webmethods.caf.faces.data.attachments.BasePortalContainerAttachmentsProvider Method 'public
java.lang.String getEncoding(java.lang.String)' has been added

com.webmethods.caf.faces.data.comments.impl.CommentsListProvider Method 'public
com.webmethods.portal.service.access.IAclManager createAclManager(java.lang.String,
java.lang.String)' has been added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskAuditBizPolicy Method 'public
java.util.Collection getWebServiceCommands(com.webmethods.portal.bizPolicy.IContext)' has been
added

com.webmethods.portal.bizPolicy.command.IJSONAdapter Method 'public java.util.Map
getSchemaFields(java.lang.Class, java.util.Map,
com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added to
an interface

com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory Method 'public java.util.Map
getSchemaFields(java.lang.Class, java.util.Map, java.util.Map)' has been added to an interface

com.webmethods.portal.bizPolicy.command.alias.SetThingAliases Method 'protected void
checkAccess(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.mech.alias.IAliasMechanics, com.webmethods.portal.system.IURI)' has been
added

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource Method 'protected
java.util.List getProfileAttributes(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.service.dir.IDirPrincipal)' has been added

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource Method 'public
javax.ws.rs.core.Response getPersonalData(javax.servlet.http.HttpServletRequest, java.lang.String)' has
been added

com.webmethods.portal.bizPolicy.command.dir.rs.DirJSONAdapter Method 'public java.util.Map
getSchemaFields(java.lang.Class, java.util.Map,
com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandBean Method 'protected java.text.SimpleDateFormat getSDF()' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandBean Method 'protected java.text.SimpleDateFormat getSDFDotNet()' has been added

com.webmethods.portal.bizPolicy.command.impl.JSONAdapterFactory Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.AbstractJSONAdapter Class
com.webmethods.portal.bizPolicy.command.impl.rs.AbstractJSONAdapter added

com.webmethods.portal.bizPolicy.command.impl.rs.BaseRestResource Method 'protected java.lang.String sanitizeMessage(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BaseRestResource Method 'protected javax.ws.rs.core.Response sendException(javax.servlet.http.HttpServletRequest, java.lang.Exception, java.lang.String, int)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'protected com.webmethods.portal.service.view.IView getView(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'protected void addIfNotSetAndNonNullValue(java.lang.String, java.lang.Object, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BizPolicyResource Class
com.webmethods.portal.bizPolicy.command.impl.rs.BizPolicyResource added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandDocBuilder Class
com.webmethods.portal.bizPolicy.command.impl.rs.CommandDocBuilder added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource Method 'public javax.ws.rs.core.Response getCommandSpecification(javax.servlet.http.HttpServletRequest, javax.servlet.http.HttpServletResponse, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource Method 'public javax.ws.rs.core.Response getSpecification(javax.servlet.http.HttpServletRequest)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.ConnectionInfoJSONAdapter Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.DefaultJSONAdapter Class
com.webmethods.portal.bizPolicy.command.impl.rs.DefaultJSONAdapter added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentList Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentList added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentMap added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentOrderedMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentOrderedMap added

com.webmethods.portal.bizPolicy.command.impl.rs.util.IFluentMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.IFluentMap added

com.webmethods.portal.bizPolicy.command.page.ModifyPage2IS Class
com.webmethods.portal.bizPolicy.command.page.ModifyPage2IS added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS Class
com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS Class
com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS added

com.webmethods.portal.bizPolicy.command.task.rs.TaskJSONAdapter Class
com.webmethods.portal.bizPolicy.command.task.rs.TaskJSONAdapter added

com.webmethods.portal.bizPolicy.command.task.webservice.UpdateTaskAttachmentWS\$updateTaskAttachmentCommandBean Method 'protected boolean excludePropertyDescriptor(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.task.webservice.UpdateTaskAttachmentWS\$updateTaskAttachmentCommandBean Method 'public void setAttachmentID(java.lang.String)' has been added

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public com.webmethods.portal.service.meta2.thing.IThingID getGetDirectoryServiceThingID()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public com.webmethods.portal.system.IURI getDirectoryURI()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public java.lang.String getEmail()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public java.lang.String getPrincipalDN()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalModifyEvent Method 'public java.lang.Object getPropertyOldValue()' has been added to an interface

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public DirPrincipalDeleteEvent(com.webmethods.portal.service.dir.IDirPrincipal, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public com.webmethods.portal.service.meta2.thing.IThingID getGetDirectoryServiceThingID()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public
com.webmethods.portal.system.IURI getDirectoryURI()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public
com.webmethods.portal.system.IURI getPrincipalURI()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public java.lang.String
getEmail()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public java.lang.String
getPrincipalDN()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public
DirPrincipalModifyEvent(com.webmethods.portal.system.IURI,
com.webmethods.portal.service.meta2.thing.IThingID, java.lang.String, java.lang.Object,
java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public
DirPrincipalModifyEvent(com.webmethods.portal.system.IURI, java.lang.String, java.lang.Object,
java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public java.lang.Object
getPropertyOldValue()' has been added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$IListener Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$IListener added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$ISynchronousListener Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$ISynchronousListener added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$Listeners Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$Listeners added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$SynchronousListeners Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$SynchronousListeners added

com.webmethods.portal.event.system.impl.DistributedConfigChangedEvent Class
com.webmethods.portal.event.system.impl.DistributedConfigChangedEvent added

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler Class
com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler added

com.webmethods.portal.framework.session.handlers.LoginScript Method 'protected void
bindSystemPolicy(com.webmethods.portal.bizPolicy.biz.system.ISystemPolicy)' has been added

com.webmethods.portal.framework.session.handlers.Validate Method 'protected void
bindJMSPHaseProvider(com.webmethods.portal.system.IComponent)' has been added

com.webmethods.portal.framework.session.impl.SessionManager Method 'protected void
bindAuthManager(com.webmethods.portal.framework.IAuthManager)' has been added

com.webmethods.portal.jms.db.impl.db2.PurgeEvents Method 'protected java.lang.String getDeleteEventsQuery()' has been added

com.webmethods.portal.jms.um.UmJMSConnProvider Method 'protected void registerJMSObjects(org.w3c.dom.Element)' has been added

com.webmethods.portal.mech.dir.IDirServiceMechanics Method 'public void fireDeletePrincipalEvent(com.webmethods.portal.service.dir.IDirPrincipal, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList)' has been added to an interface

com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics Method 'public void fireModifyPrincipalEvent(com.webmethods.portal.service.meta2.thing.IThingID, com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID, java.lang.String, java.lang.Object, java.lang.Object)' has been added to an interface

com.webmethods.portal.mech.dir.impl.DirServiceMechanics Method 'protected boolean isUserPrivacyEnabled()' has been added

com.webmethods.portal.mech.dir.impl.DirServiceMechanics Method 'public void fireDeletePrincipalEvent(com.webmethods.portal.service.dir.IDirPrincipal, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList)' has been added

com.webmethods.portal.mech.dir.impl.PrincipalAttributeMechanics Method 'public void fireModifyPrincipalEvent(com.webmethods.portal.service.meta2.thing.IThingID, com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID, java.lang.String, java.lang.Object, java.lang.Object)' has been added

com.webmethods.portal.mech.rules.impl.TEELContext Class
com.webmethods.portal.mech.rules.impl.TEELContext added

com.webmethods.portal.mech.rules.impl.TEExpressionResolver Class
com.webmethods.portal.mech.rules.impl.TEExpressionResolver added

com.webmethods.portal.mech.schedule.impl.ScheduleMechanicsIS Class
com.webmethods.portal.mech.schedule.impl.ScheduleMechanicsIS added

com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS Class
com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS added

com.webmethods.portal.mech.task.impl.TaskContextHelper Class
com.webmethods.portal.mech.task.impl.TaskContextHelper added

com.webmethods.portal.mech.task.impl.TaskDataHelper Method 'public java.lang.Object[] resolveTaskFields(com.webmethods.portal.service.task.ITask, com.webmethods.portal.service.task.ITaskData, java.lang.String[])' has been added

com.webmethods.portal.mech.task.impl.TaskMechanics Method 'protected void bindMechanicsManager(com.webmethods.portal.mech.IMechanicsManager)' has been added

com.webmethods.portal.mech.task.impl.TaskMechanicsIS Class

com.webmethods.portal.mech.task.impl.TaskMechanicsIS added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public TaskRuleContext(com.webmethods.caf.rules.IRuleContext, java.util.Map)' has been added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public java.util.Map getContextMap()' has been added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public void setContextMap(java.util.Map)' has been added

com.webmethods.portal.service.access.IAclManager Method 'public void setResourceType(java.lang.String)' has been added to an interface

com.webmethods.portal.service.access.IAclManager Method 'public void setUserID(java.lang.String)' has been added to an interface

com.webmethods.portal.service.cache.ICacheManager Method 'public void configureCache(java.lang.String, java.util.Map)' has been added to an interface

com.webmethods.portal.service.cache.impl.CacheManager Method 'protected java.util.Collection getRegistryBasedComponentCollection()' has been added

com.webmethods.portal.service.cache.impl.CacheManager Method 'protected void configureCacheFromRegisrty(java.lang.String)' has been added

com.webmethods.portal.service.cache.impl.CacheManager Method 'public void configureCache(java.lang.String, java.util.Map)' has been added

com.webmethods.portal.service.dir.IDirCache Method 'public void clearQueryCache()' has been added to an interface

com.webmethods.portal.service.dir.IDirServiceThing Class
com.webmethods.portal.service.dir.IDirServiceThing added

com.webmethods.portal.service.dir.IUserPrivacyService Class
com.webmethods.portal.service.dir.IUserPrivacyService added

com.webmethods.portal.service.dir.IUserPrivacyService\$NotificationType Class
com.webmethods.portal.service.dir.IUserPrivacyService\$NotificationType added

com.webmethods.portal.service.dir.impl.DirCache Method 'public void clearQueryCache()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected com.webmethods.portal.service.dir.IDirPrincipal getCurrentDirPrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected com.webmethods.portal.service.meta2.thing.IThingID getCurrentPrincipalThingID()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected long getCreatedTime()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected long

getLastModifiedTime()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected void deletePrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean canDeleteUser()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean isEditingSelf(com.webmethods.portal.bizPolicy.IContext)' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean isMemberOfAdminRole()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean isSysAdminPrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean isUserPrivacyEnabled()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public void DeleteUser()' has been added

com.webmethods.portal.service.portlet.impl.PortletProvider Method 'protected void bindThingIDService(com.webmethods.portal.service.meta2.IThingIDService)' has been added

com.webmethods.portal.service.portlet.impl.PortletProvider Method 'protected void bindXTypeService(com.webmethods.portal.service.meta2.IXTypeService)' has been added

com.webmethods.portal.service.scheduler.Scheduler Method 'protected void bindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been added

com.webmethods.portal.service.scheduler.Scheduler Method 'protected void unbindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.service.meta2.thing.IThingID getThingIDHelper(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI getURIHelper(java.lang.String)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI lookupPrincipalHelper(java.lang.Object)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI lookupPrincipalHelper(java.lang.Object, int)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public int getIntPriorityHelper(java.lang.String)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public

`int getIntStatusHelper(java.lang.String)`' has been added

`com.webmethods.portal.service.task.TaskSearchQuery` Method '`public boolean matches(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)`' has been added

`com.webmethods.portal.service.task.TaskSearchQueryTerm` Method '`public boolean matches(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)`' has been added

`com.webmethods.portal.service.task.TaskSearchQueryTerm` Method '`public java.util.List getFieldExpressionsString(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)`' has been added

`com.webmethods.portal.service.task.impl.TaskClassLoaderFactory` Class
`com.webmethods.portal.service.task.impl.TaskClassLoaderFactory` added

`com.webmethods.portal.service.task.impl.TaskClassLoaderFactory$ITaskClassLoader` Class
`com.webmethods.portal.service.task.impl.TaskClassLoaderFactory$ITaskClassLoader` added

`com.webmethods.portal.service.task.impl.TaskDBIndexManagerHelper` Class
`com.webmethods.portal.service.task.impl.TaskDBIndexManagerHelper` added

`com.webmethods.portal.service.task.impl.TaskIndexTableViewHelper` Class
`com.webmethods.portal.service.task.impl.TaskIndexTableViewHelper` added

`com.webmethods.portal.service.task.impl.TaskService` Method '`public void flushTaskInfoCache(com.webmethods.portal.system.IURI)`' has been added

`com.webmethods.portal.service.task.impl.TaskServiceIS` Class
`com.webmethods.portal.service.task.impl.TaskServiceIS` added

`com.webmethods.portal.service.task.impl.TaskSystem` Method '`protected createComponentData(com.webmethods.portal.system.IInitializableComponentData)`' has been added

`com.webmethods.portal.service.task.impl.TaskSystem` Method '`protected java.util.Collection getThingBasedComponentCollection()`' has been added

`com.webmethods.portal.system.PortalSystem` Method '`public java.lang.Boolean isLibraryMode()`' has been added

`com.webmethods.portal.webservices.SOAPMonitorConstants` Class
`com.webmethods.portal.webservices.SOAPMonitorConstants` added

`com.webmethods.portal.webservices.SOAPMonitorData` Method '`public SOAPMonitorData(java.lang.Integer, java.lang.Long, java.lang.String, java.lang.String, java.lang.String)`' has been added

`com.webmethods.portal.webservices.SOAPMonitorData` Method '`public java.lang.String getContentType()`' has been added

`com.webmethods.portal.webservices.SOAPMonitorData` Method '`public java.lang.String getMessageText()`' has been added

`com.webmethods.portal.webservices.SOAPMonitorData` Method '`public void`

setContentTypes(java.lang.String)' has been added

com.webmethods.portal.webservices.SOAPMonitorData Method 'public void setMessageText(java.lang.String)' has been added

com.webmethods.rtl.locator.impl.DBConfigLocator Method 'protected void fireConfigChangedEvent(java.lang.String)' has been added

com.webmethods.rtl.util.FileUtil Method 'public java.lang.String getRealLocationAtIS(java.lang.String)' has been added

com.webmethods.rtl.util.FileUtil Method 'public java.lang.String getRealLocationAtISatTaskApp(java.lang.String, java.lang.String)' has been added

Removed API

Replacement, if any

com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public java.lang.Class[] getExtraWsdlSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public org.apache.axis.description.ServiceDesc initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext, org.apache.axis.description.ServiceDesc)' has been removed

com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public org.apache.axis.handlers.soap.SOAPService initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed

com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.access.GetAcView Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.access.ListSecurityRealmObjects Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.alias.CreateAlias Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.dir.GetTypedAttributes Method 'public java.lang.Class[] getExtraWsdlSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.dir.GetTypedAttributes Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'protected java.beans.PropertyDescriptor[] getClassPropertyDescriptors(java.lang.Class)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'protected void registerWebServiceMarshallingFactories(java.lang.Class, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public org.apache.axis.description.ServiceDesc initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext, org.apache.axis.description.ServiceDesc)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public org.apache.axis.handlers.soap.SOAPService initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.WebServiceHelper Class
com.webmethods.portal.bizPolicy.command.impl.WebServiceHelper removed

com.webmethods.portal.bizPolicy.command.meta.GetSelectedList Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListChildrenFiltered Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListContainers Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListNotes Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.schedule.ListSchedulesCommand Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.page.ModifyPage2 Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.socialkeyword.GetKeyword Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,

javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.socialkeyword.ListKeywords Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.sql.ListDataSources Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.sql.ListDataSources Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.system.ImportFiles Class
com.webmethods.portal.bizPolicy.command.system.ImportFiles removed

com.webmethods.portal.bizPolicy.command.system.ImportFilesBean Class
com.webmethods.portal.bizPolicy.command.system.ImportFilesBean removed

com.webmethods.portal.bizPolicy.command.system.Ping Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.system.Ping Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.task.BaseTaskCommand Method 'protected java.beans.PropertyDescriptor[] getClassPropertyDescriptors(java.lang.Class)' has been removed

com.webmethods.portal.bizPolicy.command.task.GetTaskAudit Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.task.GetTaskAuditPaginated Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.version.ListVersionsCommand Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.webspace.ListWebSpaces Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.impl.ContextProvider Method 'protected
com.webmethods.portal.bizPolicy.IContext getContextBySessionId(java.lang.String)' has been removed

com.webmethods.portal.framework.dispatch.handlers.webservices.GetWSDL Class
com.webmethods.portal.framework.dispatch.handlers.webservices.GetWSDL removed

com.webmethods.portal.framework.propertyeditor.command.ListPropertyEditors Method 'public
void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public java.lang.Class[]
getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public
org.apache.axis.description.ServiceDesc
initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext,
org.apache.axis.description.ServiceDesc)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public
org.apache.axis.handlers.soap.SOAPService
initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.webservices.SOAPMonitorData Method 'public java.lang.String getSoap()' has been removed

com.webmethods.portal.webservices.SOAPMonitorData Method 'public void
setSoap(java.lang.String)' has been removed

com.webmethods.portal.webservices.configuration.MwsEngineConfigurationFactoryServlet Class
com.webmethods.portal.webservices.configuration.MwsEngineConfigurationFactoryServlet removed

com.webmethods.portal.webservices.configuration.MwsFileProvider Class
com.webmethods.portal.webservices.configuration.MwsFileProvider removed

com.webmethods.portal.webservices.configuration.UpgradeAxisConfiguration Class
com.webmethods.portal.webservices.configuration.UpgradeAxisConfiguration removed

com.webmethods.portal.webservices.encoding.AliasValueSerializer Class
com.webmethods.portal.webservices.encoding.AliasValueSerializer removed

com.webmethods.portal.webservices.encoding.AliasValueSerializerFactory Class
com.webmethods.portal.webservices.encoding.AliasValueSerializerFactory removed

com.webmethods.portal.webservices.encoding.BeanPropertiesTypeDesc Class
com.webmethods.portal.webservices.encoding.BeanPropertiesTypeDesc removed

com.webmethods.portal.webservices.encoding.CertificateSerializer Class
com.webmethods.portal.webservices.encoding.CertificateSerializer removed

com.webmethods.portal.webservices.encoding.CertificateSerializerFactory Class
com.webmethods.portal.webservices.encoding.CertificateSerializerFactory removed

com.webmethods.portal.webservices.encoding.CharacterSerializer Class
com.webmethods.portal.webservices.encoding.CharacterSerializer removed

com.webmethods.portal.webservices.encoding.CharacterSerializerFactory Class
com.webmethods.portal.webservices.encoding.CharacterSerializerFactory removed

com.webmethods.portal.webservices.encoding.ConnectionInfoSerializer Class
com.webmethods.portal.webservices.encoding.ConnectionInfoSerializer removed

com.webmethods.portal.webservices.encoding.ConnectionInfoSerializerFactory Class
com.webmethods.portal.webservices.encoding.ConnectionInfoSerializerFactory removed

com.webmethods.portal.webservices.encoding.DifferenceMapSerializer Class
com.webmethods.portal.webservices.encoding.DifferenceMapSerializer removed

com.webmethods.portal.webservices.encoding.DifferenceMapSerializerFactory Class
com.webmethods.portal.webservices.encoding.DifferenceMapSerializerFactory removed

com.webmethods.portal.webservices.encoding.DirServiceSerializer Class
com.webmethods.portal.webservices.encoding.DirServiceSerializer removed

com.webmethods.portal.webservices.encoding.DirServiceSerializerFactory Class
com.webmethods.portal.webservices.encoding.DirServiceSerializerFactory removed

com.webmethods.portal.webservices.encoding.IDataDeserializer Class
com.webmethods.portal.webservices.encoding.IDataDeserializer removed

com.webmethods.portal.webservices.encoding.IDataDeserializerFactory Class
com.webmethods.portal.webservices.encoding.IDataDeserializerFactory removed

com.webmethods.portal.webservices.encoding.IOutOnly Class
com.webmethods.portal.webservices.encoding.IOutOnly removed

com.webmethods.portal.webservices.encoding.ISoapComplexTypeBean Class
com.webmethods.portal.webservices.encoding.ISoapComplexTypeBean removed

com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializer Class
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializer removed

com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializerFactory Class
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializerFactory removed

com.webmethods.portal.webservices.encoding.ListViewSerializer Class
com.webmethods.portal.webservices.encoding.ListViewSerializer removed

com.webmethods.portal.webservices.encoding.ListViewSerializerFactory Class
com.webmethods.portal.webservices.encoding.ListViewSerializerFactory removed

com.webmethods.portal.webservices.encoding.LocaleDeserializer Class
com.webmethods.portal.webservices.encoding.LocaleDeserializer removed

com.webmethods.portal.webservices.encoding.LocaleDeserializerFactory Class
com.webmethods.portal.webservices.encoding.LocaleDeserializerFactory removed

com.webmethods.portal.webservices.encoding.LocaleSerializer Class
com.webmethods.portal.webservices.encoding.LocaleSerializer removed

com.webmethods.portal.webservices.encoding.LocaleSerializerFactory Class
com.webmethods.portal.webservices.encoding.LocaleSerializerFactory removed

com.webmethods.portal.webservices.encoding.PageDataDeserializer Class
com.webmethods.portal.webservices.encoding.PageDataDeserializer removed

com.webmethods.portal.webservices.encoding.PageDataDeserializerFactory Class
com.webmethods.portal.webservices.encoding.PageDataDeserializerFactory removed

com.webmethods.portal.webservices.encoding.PageDataSerializer Class
com.webmethods.portal.webservices.encoding.PageDataSerializer removed

com.webmethods.portal.webservices.encoding.PageDataSerializerFactory Class
com.webmethods.portal.webservices.encoding.PageDataSerializerFactory removed

com.webmethods.portal.webservices.encoding.PagingBeanDeserializer Class
com.webmethods.portal.webservices.encoding.PagingBeanDeserializer removed

com.webmethods.portal.webservices.encoding.PagingBeanDeserializerFactory Class
com.webmethods.portal.webservices.encoding.PagingBeanDeserializerFactory removed

com.webmethods.portal.webservices.encoding.PagingBeanSerializer Class
com.webmethods.portal.webservices.encoding.PagingBeanSerializer removed

com.webmethods.portal.webservices.encoding.PagingBeanSerializerFactory Class
com.webmethods.portal.webservices.encoding.PagingBeanSerializerFactory removed

com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializer Class
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializer removed

com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializerFactory Class
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializerFactory removed

com.webmethods.portal.webservices.encoding.PortalFileBeanSerializer Class
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializer removed

com.webmethods.portal.webservices.encoding.PortalFileBeanSerializerFactory Class
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializerFactory removed

com.webmethods.portal.webservices.encoding.RightSetDeserializer Class
com.webmethods.portal.webservices.encoding.RightSetDeserializer removed

com.webmethods.portal.webservices.encoding.RightSetDeserializerFactory Class
com.webmethods.portal.webservices.encoding.RightSetDeserializerFactory removed

com.webmethods.portal.webservices.encoding.RightSetSerializer Class
com.webmethods.portal.webservices.encoding.RightSetSerializer removed

com.webmethods.portal.webservices.encoding.RightSetSerializerFactory Class
com.webmethods.portal.webservices.encoding.RightSetSerializerFactory removed

com.webmethods.portal.webservices.encoding.SelectedListViewSerializer Class
com.webmethods.portal.webservices.encoding.SelectedListViewSerializer removed

com.webmethods.portal.webservices.encoding.SelectedListViewSerializerFactory Class
com.webmethods.portal.webservices.encoding.SelectedListViewSerializerFactory removed

com.webmethods.portal.webservices.encoding.ThingIDListSerializer Class
com.webmethods.portal.webservices.encoding.ThingIDListSerializer removed

com.webmethods.portal.webservices.encoding.ThingIDListSerializerFactory Class
com.webmethods.portal.webservices.encoding.ThingIDListSerializerFactory removed

com.webmethods.portal.webservices.encoding.ThingNameAtomSerializer Class
com.webmethods.portal.webservices.encoding.ThingNameAtomSerializer removed

com.webmethods.portal.webservices.encoding.ThingNameAtomSerializerFactory Class
com.webmethods.portal.webservices.encoding.ThingNameAtomSerializerFactory removed

com.webmethods.portal.webservices.encoding.URIDeserializer Class
com.webmethods.portal.webservices.encoding.URIDeserializer removed

com.webmethods.portal.webservices.encoding.URIDeserializerFactory Class
com.webmethods.portal.webservices.encoding.URIDeserializerFactory removed

com.webmethods.portal.webservices.encoding.URISerializer Class
com.webmethods.portal.webservices.encoding.URISerializer removed

com.webmethods.portal.webservices.encoding.URISerializerFactory Class
com.webmethods.portal.webservices.encoding.URISerializerFactory removed

com.webmethods.portal.webservices.encoding.ViewProperty Class
com.webmethods.portal.webservices.encoding.ViewProperty removed

com.webmethods.portal.webservices.encoding.ViewSerializer Class
com.webmethods.portal.webservices.encoding.ViewSerializer removed

com.webmethods.portal.webservices.encoding.ViewSerializerFactory Class
com.webmethods.portal.webservices.encoding.ViewSerializerFactory removed

com.webmethods.portal.webservices.handlers.CommandHandler Class
com.webmethods.portal.webservices.handlers.CommandHandler removed

com.webmethods.portal.webservices.handlers.CommandProvider Class
com.webmethods.portal.webservices.handlers.CommandProvider removed

com.webmethods.portal.webservices.handlers.SOAPMonitorHandler Class
com.webmethods.portal.webservices.handlers.SOAPMonitorHandler removed

com.webmethods.portal.webservices.servlet.PortalAxisServlet Class
com.webmethods.portal.webservices.servlet.PortalAxisServlet removed

Changed API	Description
	<p>com.webmethods.portal.bizPolicy.command.dir.DeletePrincipal In method 'protected void fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID, com.webmethods.portal.service.meta2.thing.IThingID, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList)' the number of arguments has changed</p>
	<p>com.webmethods.portal.bizPolicy.command.dir.ModifyPrincipal In method 'protected void fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics, com.webmethods.portal.system.IURI, java.lang.String, java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' the number of arguments has changed</p>
	<p>com.webmethods.portal.bizPolicy.command.dir.ModifyPrincipalEx In method 'protected void fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics, com.webmethods.portal.system.IURI, java.util.Map, com.webmethods.portal.service.meta2.thing.IThingID)' the number of arguments has changed</p>
	<p>com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource In method 'public javax.ws.rs.core.Response invokeCommandFromForm(javax.servlet.http.HttpServletRequest, javax.servlet.http.HttpServletResponse, java.lang.String)' the number of arguments has changed</p>

Release 10.1

Added API	Description
com.webmethods.portal.bizPolicy.biz.dir.IDirSystemBizPolicy	Method 'public com.webmethods.portal.service.dir.IDirUser authenticateUser(com.webmethods.portal.bizPolicy.IContext, java.lang.String, java.lang.String, boolean)' has been added to an interface
com.webmethods.portal.framework.IAuthManager	Method 'public com.webmethods.portal.framework.auth.IAuthInfo createAuthInfo()' has been added to an interface
com.webmethods.portal.service.task.ITaskDistributionService	Method 'public com.webmethods.portal.service.task.ITaskListIterator searchAllTasks(com.webmethods.portal.service.task.TaskSearchQuery, java.lang.Boolean)' has been added to an interface
com.webmethods.portal.service.task.ITaskLockingService	Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has been added to an interface
com.webmethods.portal.service.task.ITaskLockingService	Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' has been added to an interface
com.webmethods.portal.service.task.ITaskLockingService	Method 'public com.webmethods.portal.system.lock.IClusterLock getLock(com.webmethods.portal.system.IURI)' has been added to an interface
com.webmethods.portal.system.IURIResolver	Method 'public com.webmethods.portal.system.IURI acquireURI(java.lang.String, boolean)' has been added to an interface
com.webmethods.portal.system.init.IPhaseProvider	Method 'public void preInit(java.lang.String)' has been added to an interface
com.webmethods.portal.webservices.IWebService	Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been added to an interface

Removed API**Replacement, if any**

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo: Removed
com.webmethods.caf.faces.data.task.IQueryAggregationInfo from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxIndexedSearchContentProvider\$InboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxSearchContentProvider\$InboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskIndexedSearchContentProvider\$TaskData: Removed
com.webmethods.caf.faces.data.task.ITaskData from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.portal.mech.task.impl.TaskQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Removed
com.webmethods.portal.system.init.IInitializable from the set of implemented interfaces

com.webmethods.portal.socialbpm.charts.SocialBPMSearchQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.impl.TaskSearchQuery from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2 from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.impl.TaskSearchQuery from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2 from the list of superclasses

com.webmethods.caf.mobile.notify.impl.PushNotification: Removed
com.webmethods.portal.system.impl.BaseComponent from the list of superclasses

com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean: Removed
com.webmethods.rtl.util.obj.MapPropertyBag from the list of superclasses

com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean: Removed
com.webmethods.rtl.util.obj.MapPropertyBag from the list of superclasses

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus: Removed
com.webmethods.portal.system.impl.BaseComponent from the list of superclasses

com.webmethods.rtl.locator.ClassLocator: Removed com.webmethods.rtl.locator.FileLocator from the list of superclasses

com.webmethods.rtl.util.SystemPaths\$UserPathLocator: Removed
com.webmethods.rtl.locator.FileLocator from the list of superclasses

com.webmethods.caf.mobile.notify.task.APNSCleanUpThread: Removed field expiredID

com.webmethods.portal.service.portlet.impl.PortletProvider: Removed field
portletProviderFactoryServiceReg

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field
TASK_LOCK_MAX_TIME

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field
TASK_LOCK_MAX_WAIT_TIME

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field dbOffsetLastCalced

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field dbTimeOffsetMs

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm findTerm(java.lang.String,
java.lang.String)' has been removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm findTerm(java.lang.String)' has been removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.IQueryAggregationInfo getQueryAggregationInfo()' has been removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm[] getTerms()' has been removed

com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider: Method 'protected
java.util.Collection loadConfig(com.webmethods.portal.system.IComponentData)' has been removed

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void
includeBCScript(java.lang.String, java.util.Locale, java.io.Writer, boolean)' has been removed

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void stripBCScript(java.io.Reader,
java.io.Writer)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_sep_for_bc(int)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_unambiguous_sep_for_bc(int)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'public void stripBCScript(java.io.Reader, java.io.Writer)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected int strip_c_comment_for_bc(java.io.Reader, java.io.Writer)' has been removed

com.webmethods.portal.framework.auth.AuthInfo: Method 'public void copy(com.webmethods.portal.framework.auth.AuthInfo)' has been removed

com.webmethods.portal.framework.presentation.PresentationData: Method 'public com.webmethods.portal.framework.presentation.PresentationData init(java.lang.Object, int, java.util.HashMap)' has been removed

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Method 'public void init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been removed

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Method 'public void shutdown()' has been removed

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool: Method 'public void initialize(com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager, java.util.Map)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public javax.servlet.ServletContext getServletContext(java.lang.String)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public org.eclipse.jetty.webapp.WebAppContext getWebAppContext(java.lang.String)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void refreshBundle(org.osgi.framework.Bundle)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void refreshRemovalPendingBundles()' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void startBundle(org.osgi.framework.Bundle)' has been removed

com.webmethods.caf.faces.data.task.AggregationType: Class
com.webmethods.caf.faces.data.task.AggregationType removed

com.webmethods.caf.faces.data.task.IQueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.IQueryAggregationInfo removed

com.webmethods.caf.faces.data.task.IndexEngineType: Class
com.webmethods.caf.faces.data.task.IndexEngineType removed

com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider: Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider removed

com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher: Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestPingInfo: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestPingInfo removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestResource: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestResource removed

com.webmethods.portal.framework.presentation.handlers.djsp.FlexiblePoolBoy: Class
com.webmethods.portal.framework.presentation.handlers.djsp.FlexiblePoolBoy removed

com.webmethods.rtl.locator.BundleLocator: Class com.webmethods.rtl.locator.BundleLocator removed

com.webmethods.rtl.locator.ClusterConfigLocator: Class
com.webmethods.rtl.locator.ClusterConfigLocator removed

com.webmethods.rtl.locator.ConfigLocator: Class com.webmethods.rtl.locator.ConfigLocator removed

com.webmethods.rtl.locator.FileLocator: Class com.webmethods.rtl.locator.FileLocator removed

com.webmethods.rtl.locator.NullLocator: Class com.webmethods.rtl.locator.NullLocator removed

com.webmethods.rtl.locator.StreamLocatorFactory: Class
com.webmethods.rtl.locator.StreamLocatorFactory removed

com.webmethods.rtl.locator.WebResourceLocator: Class
com.webmethods.rtl.locator.WebResourceLocator removed

Release 10.0

Added API	Description
<code>com.webmethods.caf.faces.data.task.impl.TaskInboxIndexedSearchContentProvider\$InboxSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskInboxSearchContentProvider\$InboxSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider</code>	Added <code>com.webmethods.portal.event.modify.IUpdateEvent\$ISynchronousListener</code> to the set of implemented interfaces
<code>com.webmethods.caf.mobile.notify.task.NotificationSender</code>	Added <code>java.util.concurrent.Callable</code> to the set of implemented interfaces
<code>com.webmethods.portal.mech.task.impl.TaskQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAll</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllByTagCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllByTagPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllGroupedCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxes</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesByTagCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesByTagPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesCount: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesGroupedCount: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesPaged: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.socialbpm.charts.SocialBPMSearchQuery: Added
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended to the set of implemented interfaces

com.webmethods.caf.faces.render.html.table.MoveRowDownIconRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowDownLinkRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowUpIconRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowUpLinkRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Added
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper to the list of superclasses

com.webmethods.caf.common.deployer.MwsDeployerConstants: Added public field
PROJ_PROP_EXPORT_PAGE_DEPTH

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field IOS_CERT

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_HOST_NAME

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_HOST_PORT

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_PASSWORD

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
NOTIFIER_QUEUE_SIZE_THRESHOLD

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Added protected field
m_connPoolProvider

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Added public field
IOS_JASON_PAYLOAD_TEMPLATE

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field
PROPERTY_HPSTRA_INDEXTABLEDIS

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field

PROPERTY_HPSTRA_INDEX_JOB_STATUS

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field
PROPERTY_ISHPSTRAENABLED

com.webmethods.portal.bizPolicy.command.task.rs.BaseTaskResource: Added public field
DEFAULT_JSON_DATE_FORMAT

com.webmethods.portal.service.bcgadget.IBCGadgetConstants: Added public field
BC_GADGET_DEF_CONTAINER_NOT_FOUND_ERROR_MSG

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field
ATTR_PREFIX_LENGTH

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field
EDIT_ATTR_CURRPASSWORD

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field USERNAME

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field exceptionMessage

com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Added public field
TE_MAX_LAST_ACTIVE

com.webmethods.portal.service.task.impl.TaskDefinitionView: Added protected field
m_taskDetailGadgetURIs

com.webmethods.caf.common.ObjectUtil: Method 'public void sortObjectList(java.util.List,
java.lang.String, boolean)' has been added

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Method 'public boolean
isPropagateEvents()' has been added

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Method 'public void
setPropagateEvents(boolean)' has been added

com.webmethods.caf.faces.component.tree.AsyncTree: Method 'protected
com.webmethods.caf.faces.data.ITableContentProvider getContentProvider(boolean)' has been added

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Method 'public java.lang.String
getSearchEngineType()' has been added

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Method 'public void
setSearchEngineType(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider: Method 'public void
onSynchronousEvent(com.webmethods.portal.event.modify.IUpdateEvent)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public
com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails
getM_iOSConnectionDetails()' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public
java.util.concurrent.BlockingQueue getMessageQueue()' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public java.util.List scheduleCleanUpService(java.util.List)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public void setMessageQueue(java.util.concurrent.BlockingQueue)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public void stopExecutorService()' has been added

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Method 'public java.lang.String createMessage(com.webmethods.portal.service.task.event.ITaskChangedEvent)' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public java.util.List getAndroidSubscriptionList()' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public java.util.List getIOSSubscriptionList()' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public void setAndroidSubscriptionList(java.util.List)' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public void setIOSSubscriptionList(java.util.List)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public java.util.List call()' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public java.lang.Object call()' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] convertPayloadtoUTF8Bytes(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] decodeHex(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] formAPNSMessage(byte, byte[], byte[])' has been added

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Method 'public java.lang.String generateIOSPayload(java.util.List, java.lang.String, java.lang.String)' has been added

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void includeBCScript(java.lang.String, java.util.Locale, java.io.Writer, boolean)' has been added

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void stripBCScript(java.io.Reader, java.io.Writer)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_sep_for_bc(int)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_unambiguous_sep_for_bc(int)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'public void stripBCScript(java.io.Reader, java.io.Writer)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected int strip_c_comment_for_bc(java.io.Reader, java.io.Writer)' has been added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable createHpstraIndexTableFromXml(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.task.rs.TaskResource: Method 'public void convertJSONToJavaObj(java.util.Map, java.lang.Class)' has been added

com.webmethods.portal.framework.presentation.handlers.Nbsp: Method 'public java.lang.Object lookup(java.util.Map, java.lang.String, boolean)' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalListView: Method 'public java.util.Map getExceptions()' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalListView: Method 'public void setExceptions(java.util.Map)' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalProvider: Method 'protected void populateGroupMembership(com.webmethods.portal.service.dir.IDirPrincipal, java.util.Set, java.util.Map)' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'protected void EditPrincipalEx()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public void EditUserEx()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public boolean isAuthenticated(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Method 'protected java.lang.String getConditionalInsertStatement()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable getHpstraIndexTable()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public java.lang.String getTaskDetailGadgetURIs()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public boolean isHpstraEnabled()' has been added

com.webmethods.portal.system.cluster.impl.ClusterProvider: Method 'public void reloadClusterServers()' has been added

com.webmethods.portal.webapp.jetty7.MwsSessionManager: Method 'protected void addContextLocale(org.eclipse.jetty.server.session.AbstractSession)' has been added

com.webmethods.rtl.event.DeliveryService: Method 'public boolean isConfigLoaded()' has been added

com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics\$NameComparator: Method 'public int compare(com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics, com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics)' has been added

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected boolean isMaintenanceMode()' has been added

com.webmethods.rtl.script.nbsp.NBSPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.NBSPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.Object get(java.lang.String, java.lang.Class, java.lang.Object, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails getM_iOSConnectionDetails()' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public java.util.concurrent.BlockingQueue getMessageQueue()' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public java.util.List scheduleCleanUpService(java.util.List)' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public void setMessageQueue(java.util.concurrent.BlockingQueue)' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public void stopExecutorService()' has been added to an interface

com.webmethods.common.search.ISliceableSearchContext: Method 'public java.util.Map getExceptions()' has been added to an interface

com.webmethods.portal.mech.task.ITaskMechanics: Method 'public void fireTaskReindexStopEvent(com.webmethods.portal.service.task.ITaskDefinition, java.lang.String)' has been added to an interface

com.webmethods.portal.service.dir.IDirPrincipalList: Method 'public java.util.Map getExceptions()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable getHpstraIndexTable()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public java.lang.String

getTaskDetailGadgetURIs()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public boolean isHpstraEnabled()' has been added to an interface

com.webmethods.portal.service.task.ITaskDistributionService: Method 'public java.util.List getPrincipalActors(com.webmethods.portal.system.IURI[], boolean)' has been added to an interface

com.webmethods.portal.service.task.event.ITaskReindexStopEvent: Method 'public java.lang.String getIndexEngineType()' has been added to an interface

com.webmethods.portal.system.cluster.IClusterProvider: Method 'public void reloadClusterServers()' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPRuntime: Method 'public java.lang.Object lookup(java.util.Map, java.lang.String, boolean)' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added to an interface

com.softwareag.mws.screens.BaseScreenClass: Class com.softwareag.mws.screens.BaseScreenClass added

com.softwareag.mws.screens.Constants: Class com.softwareag.mws.screens.Constants added

com.softwareag.mws.screens.MWSLoginLogoutScreen: Class
com.softwareag.mws.screens.MWSLoginLogoutScreen added

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen: Class

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen added

com.webmethods.caf.faces.data.task.AggregationType: Class
com.webmethods.caf.faces.data.task.AggregationType added

com.webmethods.caf.faces.data.task.IQueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.IQueryAggregationInfo added

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Class
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended added

com.webmethods.caf.faces.data.task.IndexEngineType: Class
com.webmethods.caf.faces.data.task.IndexEngineType added

com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo added

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider: Class
com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider added

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearch
Query: Class
com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearch
Query added

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Class
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended added

com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer: Class
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer added

com.webmethods.caf.mobile.notify.impl.PushNotification: Class
com.webmethods.caf.mobile.notify.impl.PushNotification added

com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean: Class
com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean added

com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpEvent: Class
com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpEvent added

com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpHandler: Class
com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpHandler added

com.webmethods.caf.mobile.notify.task.APNSCleanUpThread: Class
com.webmethods.caf.mobile.notify.task.APNSCleanUpThread added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper\$DBIndexer: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper\$DBIndexer added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper\$Indexer: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper\$Indexer added

com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean added

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus added

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus\$StatusInfo: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus\$StatusInfo added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource: Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$Product: Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$Product added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$ProductHolder:
Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$ProductHolder

added

com.webmethods.portal.jms.um.QueueType: Class com.webmethods.portal.jms.um.QueueType added

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable: Class

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable added

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable\$DisplayField: Class

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable\$DisplayField added

com.webmethods.portal.service.sql.runtime.base.TaskPendingUpdatesCleanup: Class

com.webmethods.portal.service.sql.runtime.base.TaskPendingUpdatesCleanup added

com.webmethods.portal.service.sql.runtime.db2.TaskLockSetNew: Class

com.webmethods.portal.service.sql.runtime.db2.TaskLockSetNew added

com.webmethods.portal.service.sql.runtime.db2.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.db2.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.mssql.ThingNewPar: Class

com.webmethods.portal.service.sql.runtime.mssql.ThingNewPar added

com.webmethods.portal.service.sql.runtime.mssql.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.mssql.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.mysql.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.mysql.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.oracle.TaskLockSetNew: Class

com.webmethods.portal.service.sql.runtime.oracle.TaskLockSetNew added

com.webmethods.portal.service.sql.runtime.oracle.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.oracle.UpdateThingCounter added

com.webmethods.portal.service.task.ITaskIndexEngineConfiguration: Class

com.webmethods.portal.service.task.ITaskIndexEngineConfiguration added

com.webmethods.portal.service.task.ITaskIndexManager: Class

com.webmethods.portal.service.task.ITaskIndexManager added

com.webmethods.portal.service.task.ITaskInfoFieldConverters: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$AcceptedByListValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$AcceptedByListValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$CurrentUserValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$CurrentUserValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$DateValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$DateValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$PriorityValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$PriorityValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$StatusValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$StatusValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskIDValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskIDValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskTypeIDValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskTypeIDValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$URIValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$URIValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$UserValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$UserValueConverter added

com.webmethods.portal.service.task.SearchContext: Class
com.webmethods.portal.service.task.SearchContext added

com.webmethods.portal.service.task.SearchKey: Class com.webmethods.portal.service.task.SearchKey
added

com.webmethods.portal.service.task.SearchKey\$TE_SearchKeys: Class
com.webmethods.portal.service.task.SearchKey\$TE_SearchKeys added

com.webmethods.portal.service.task.TaskIndexEngineFactory: Class
com.webmethods.portal.service.task.TaskIndexEngineFactory added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$DistributionChangeType:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$DistributionChangeType
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$IListener: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$IListener added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$ISynchronousListener:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$ISynchronousListener
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$Listeners: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$Listeners added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners\$SynchronousListener: Class

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners\$SynchronousListener added

com.webmethods.portal.service.task.event.impl.TaskDistributionChangedEvent: Class

com.webmethods.portal.service.task.event.impl.TaskDistributionChangedEvent added

com.webmethods.portal.service.task.event.impl.TaskReindexStopEvent: Class

com.webmethods.portal.service.task.event.impl.TaskReindexStopEvent added

com.webmethods.portal.service.task.impl.TaskDBIndexConfiguration: Class

com.webmethods.portal.service.task.impl.TaskDBIndexConfiguration added

com.webmethods.portal.system.cluster.impl.ClusterNodeRegisteredNotifier: Class

com.webmethods.portal.system.cluster.impl.ClusterNodeRegisteredNotifier added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool: Class

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager: Class

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionProvider: Class

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionProvider added

com.webmethods.pushNotification.apns.connection.pool.APNSPoolableConnection: Class

com.webmethods.pushNotification.apns.connection.pool.APNSPoolableConnection added

com.webmethods.pushNotification.apns.connection.pool.IConnectionProvider: Class

com.webmethods.pushNotification.apns.connection.pool.IConnectionProvider added

com.webmethods.pushNotification.apns.connection.pool.IPoolableConnection: Class

com.webmethods.pushNotification.apns.connection.pool.IPoolableConnection added

Removed API**Replacement, if any**

com.webmethods.caf.mobile.notify.task.NotificationSender: Removed java.lang.Runnable from the set of implemented interfaces

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_ACCEPTED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_CANCELLED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_COMPLETED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_EXPIRED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_FAILED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_QUEUED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_REASSIGNED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_RELEASED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_RESUMED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_SUSPENDED

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Removed field reindexAllTaskExecutor

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Removed field reindexingTasks

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field USE_LIGHT_WEIGHT_EVENTS

Deprecated API**Replacement, if any**

com.webmethods.portal.service.task.impl.TaskDistributionService: Method 'public java.util.List getPrincipalActors(com.webmethods.portal.system.IURI[], boolean)' has been deprecated

com.webmethods.portal.service.task.impl.TaskDistributionService: Method 'protected java.util.List returnPagedTaskList(java.lang.String, java.lang.Object[], boolean)' has been deprecated

Changed API**Description**

com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails: Increased visibility of class from package to public

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Value of compile-time constant ANDROID_JASON_PAYLOAD_TEMPLATE has been changed

com.webmethods.caf.faces.bean.BaseFacesBean: Accessibility of field EMPTY_RESOURCES has been increased from package to public

com.webmethods.caf.mobile.notify.task.NotificationSender: In method 'public NotificationSender(java.util.concurrent.BlockingQueue, com.sun.jersey.api.client.WebResource\$Builder)' the number of arguments has changed

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: In method 'public com.webmethods.caf.mobile.notify.task.Message generatePayload(java.util.List, java.lang.String, java.lang.String)' the number of arguments has changed

com.webmethods.portal.jms.um.UmJMSClient: In method 'protected void createQueue(java.lang.String, boolean, int)' the number of arguments has changed

com.webmethods.portal.jms.um.UmJMSClient: In method 'protected void createTopic(java.lang.String, boolean, int)' the number of arguments has changed

com.webmethods.portal.mech.task.impl.TaskMechanics: In method 'public void fireTaskReindexStopEvent(com.webmethods.portal.service.task.ITaskDefinition)' the number of arguments has changed

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Return type of method 'public com.webmethods.caf.mobile.notify.task.Message generateAndroidPayload(java.util.List, java.lang.String, java.lang.String)' has been changed to java.lang.String

com.webmethods.portal.jms.db.DbJMSConnProvider: Accessibility of method 'public DbJMSConnProvider()' has been decreased from public to private

Release 9.12**Added API****Description**

com.webmethods.caf.common.thread.NamedThreadFactory: Method 'public NamedThreadFactory(java.lang.String, boolean)' has been added

com.webmethods.caf.faces.bean.mws_ui.HtmlHead: Method 'public java.lang.String getEffectsJS()' has been added

com.webmethods.caf.faces.convert.FormattedDateTimeConverter: Added protected field dateFormatDefault

com.webmethods.caf.faces.data.object.DateRange: Added protected field controlCalendar

com.webmethods.caf.faces.data.object.DateRange: Method 'protected java.util.Calendar

Added API**Description**

getControlCalendar(javax.faces.context.FacesContext)' has been added

com.webmethods.caf.faces.data.object.DateRange: Method 'public void setControlCalendar(java.util.Calendar)' has been added

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Class
com.webmethods.caf.mobile.notify.IMobileNotificationConstants added

com.webmethods.caf.mobile.notify.IMobileNotificationProvider: Class
com.webmethods.caf.mobile.notify.IMobileNotificationProvider added

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Class
com.webmethods.caf.mobile.notify.IMobileNotifierComponent added

com.webmethods.caf.mobile.notify.activator.MobileNotificationActivator: Class
com.webmethods.caf.mobile.notify.activator.MobileNotificationActivator added

com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider: Class
com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Class
com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent added

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Class
com.webmethods.caf.mobile.notify.impl.TaskEventsHandler added

com.webmethods.caf.mobile.notify.task.Message: Class
com.webmethods.caf.mobile.notify.task.Message added

com.webmethods.caf.mobile.notify.task.MonitorPendingNotificationMessages: Class
com.webmethods.caf.mobile.notify.task.MonitorPendingNotificationMessages added

com.webmethods.caf.mobile.notify.task.NotificationSender: Class
com.webmethods.caf.mobile.notify.task.NotificationSender added

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Class
com.webmethods.caf.mobile.notify.util.MobileNotifierUtil added

com.webmethods.caf.wssserver.auth.saml.SamlUtils: Method 'public org.w3c.dom.Element
marshallSamlObject(org.opensaml.xml.XMLObject)' has been added

com.webmethods.caf.wssserver.auth.saml.SamlUtils: Method 'public org.opensaml.xml.XMLObject
unmarshallElement(org.w3c.dom.Element)' has been added

com.webmethods.portal.bizPolicy.biz.dir.IGroupBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented
interfaces

com.webmethods.portal.bizPolicy.biz.dir.IPrincipalBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented
interfaces

Added API	Description
com.webmethods.portal.bizPolicy.biz.dir.IUserBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces
com.webmethods.portal.bizPolicy.biz.dir.impl.GroupBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces
com.webmethods.portal.bizPolicy.biz.dir.impl.GroupBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses
com.webmethods.portal.bizPolicy.biz.dir.impl.PrincipalBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces
com.webmethods.portal.bizPolicy.biz.dir.impl.PrincipalBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses
com.webmethods.portal.bizPolicy.biz.dir.impl.UserBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces
com.webmethods.portal.bizPolicy.biz.dir.impl.UserBizPolicy:	Added com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses
com.webmethods.portal.bizPolicy.biz.task.impl.TaskInfo:	Added java.io.Serializable to the set of implemented interfaces
com.webmethods.portal.bizPolicy.biz.task.impl.TaskInfoExtended:	Added java.io.Serializable to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.ICommandManager:	Method 'public com.webmethods.portal.bizPolicy.command.IRemoteCommandTransport getRemoteCommandTransport(java.lang.String)' has been added to an interface
com.webmethods.portal.bizPolicy.command.ICommandManager:	Method 'public java.util.List invokeClusterCommand(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.bizPolicy.command.ICommand, com.webmethods.portal.bizPolicy.command.ICommandBean)' has been added to an interface
com.webmethods.portal.bizPolicy.command.ICommandResponseEntry:	Class com.webmethods.portal.bizPolicy.command.ICommandResponseEntry added
com.webmethods.portal.bizPolicy.command.dir.GetPortalStyle:	Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IPrincipalMechanics, com.webmethods.portal.system.IURI)' has been added
com.webmethods.portal.bizPolicy.command.dir.SearchDirectory:	Method 'protected void

Added API	Description
checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.service.meta2.thing.IThingID)' has been added	
com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryEx: Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.service.meta2.thing.IThingID)' has been added	
com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryRefined: Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.service.meta2.thing.IThingID)' has been added	
com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryRefinedPaged: Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.service.meta2.thing.IThingID)' has been added	
com.webmethods.portal.bizPolicy.command.impl.CommandManager: Method 'public com.webmethods.portal.bizPolicy.command.IRemoteCommandTransport getRemoteCommandTransport(java.lang.String)' has been added	
com.webmethods.portal.bizPolicy.command.impl.CommandManager: Method 'public java.util.List invokeClusterCommand(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.bizPolicy.command.ICommand, com.webmethods.portal.bizPolicy.command.ICommandBean)' has been added	
com.webmethods.portal.bizPolicy.command.remote.RemoteCommand: Class com.webmethods.portal.bizPolicy.command.remote.RemoteCommand added	
com.webmethods.portal.bizPolicy.command.remote.RemoteCommandBean: Class com.webmethods.portal.bizPolicy.command.remote.RemoteCommandBean added	
com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport: Class com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport added	
com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport\$RemoteJmsException: Class	
com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport\$RemoteJmsException added	
com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteTransaction: Class com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteTransaction added	
com.webmethods.portal.bizPolicy.command.system.JndiRefreshCluster: Class	

Added API**Description**

com.webmethods.portal.bizPolicy.command.system.JndiRefreshCluster added

com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommand: Class
com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommand added

com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommandBean: Class
com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommandBean added

com.webmethods.portal.bizPolicy.command.task.jms.AddTaskAttachmentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.AddTaskAttachmentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.AddTaskCommentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.AddTaskCommentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskAttachmentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskAttachmentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskCommentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskCommentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAttachmentsJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAttachmentsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAuditJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAuditJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskCommentsJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.GetTaskCommentsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.GetTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.QueueTaskJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.QueueTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksFieldsJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksFieldsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksPagedJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksPagedJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksTotalCountJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksTotalCountJMS added

com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskAttachmentJMS: Class
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskAttachmentJMS added

Added API	Description
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskCommentJMS: Class com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskCommentJMS added	
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskJMS: Class com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskJMS added	
com.webmethods.portal.bizPolicy.command.task.jms.impl.TaskJMSUtils: Class com.webmethods.portal.bizPolicy.command.task.jms.impl.TaskJMSUtils added	
com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider: Class com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider added	
com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher: Class com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher added	
com.webmethods.portal.bizPolicy.command.task.webservice.SearchTasksFieldsWS: Added java.io.Serializable to the set of implemented interfaces	
com.webmethods.portal.bizPolicy.command.task.webservice.SearchTasksWS: Added java.io.Serializable to the set of implemented interfaces	
com.webmethods.portal.bizPolicy.command.task.webservice.Task: Added java.io.Serializable to the set of implemented interfaces	
com.webmethods.portal.bizPolicy.command.task.webservice.dotnet.SearchTasksDotNetWS: Added java.io.Serializable to the set of implemented interfaces	
com.webmethods.portal.bizPolicy.command.task.webservice.dotnet.SearchTasksFieldsDotNetWS: Added java.io.Serializable to the set of implemented interfaces	
com.webmethods.portal.bizPolicy.impl.upgrade.MoveVersionSystemComponentData: Class com.webmethods.portal.bizPolicy.impl.upgrade.MoveVersionSystemComponentData added	
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent: Class com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent added	
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$IListener: Class com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$IListener added	
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ISynchronousListener: Class com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ISynchronousListener added	
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$Listeners: Class com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$Listeners added	
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$QueueListeners: Class com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$QueueListeners added	
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$SynchronousListeners: Class com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$SynchronousListeners added	
com.webmethods.portal.event.dir.impl.DirPrincipalDNUpdateEvent: Class	

Added API	Description
com.webmethods.portal.event.dir.impl.DirPrincipalDNUpdateEvent	added
com.webmethods.portal.event.sso.ISSODataChangeEvent	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$IListener	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$ISynchronousListener	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$Listeners	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$QueueListeners	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$SynchronousListeners	Class added
com.webmethods.portal.event.sso.impl.SSODataChangeEvent	Class added
com.webmethods.portal.framework.dispatch.handlers.system.SAMLSSOHandler	Class added
com.webmethods.portal.framework.dispatch.preProcessors.OpenRedirectCheck	Class added
com.webmethods.portal.framework.dispatch.resolvers.SAMLAuthReqResolver	Class added
com.webmethods.portal.framework.impl.PortalServlet	Added public field PORTAL_SERVLET_LOCK_OBJ
com.webmethods.portal.framework.portletcontainer.servlet.JettyPortletRequestWrapper	Method 'public org.eclipse.jetty.util.MultiMap getParameterMultiMap()' has been added
com.webmethods.portal.framework.portletcontainer.servlet.JettyPortletRequestWrapper	Method 'public java.util.Map getParameters()' has been added
com.webmethods.portal.jms.JMSPhaseProvider	Added com.webmethods.portal.system.IComponent to the set of implemented interfaces
com.webmethods.portal.jms.JMSPhaseProvider	Added com.webmethods.portal.system.IConstants to the set of implemented interfaces
com.webmethods.portal.jms.JMSPhaseProvider	Added com.webmethods.portal.system.impl.BaseComponent to the list of superclasses
com.webmethods.portal.jms.JMSPhaseProvider	Added public field COMPONENT_NAME
com.webmethods.portal.jms.um.UmJMSClient	Added abstract modifier to class

Added API	Description
com.webmethods.portal.jms.um.UmJMSSClient: Added	
com.webmethods.portal.system.init.IInitializable	to the set of implemented interfaces
com.webmethods.portal.jms.um.UmJMSSClient: Added	com.webmethods.rtl.msg.jms.IJMSPProvider to the set of implemented interfaces
com.webmethods.portal.jms.um.UmJMSSClient: Added	com.webmethods.rtl.msg.jms.JMSPProvider to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSClient: Added	com.webmethods.rtl.msg.jms.JMSStdConnProvider to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSClient: Method	'protected boolean createInitialContext()' has been added
com.webmethods.portal.jms.um.UmJMSSClient: Method	'protected void registerFactory(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient: Method	'protected void registerQueue(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient: Method	'protected void registerTopic(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient: Method	'protected void resetContext()' has been added
com.webmethods.portal.jms.um.UmJMSSConnProvider: Added	com.webmethods.portal.jms.um.UmJMSSClient to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSConnProvider: Method	'protected void onDisconnect(boolean)' has been added
com.webmethods.portal.jms.um.UmJMSSConnProvider: Method	'public void onShutdown()' has been added
com.webmethods.portal.mech.dir.IDirServiceMechanics: Method	'public java.util.List updatePrincipalUUID(int)' has been added to an interface
com.webmethods.portal.mech.dir.IGroupMechanics: Added	com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces
com.webmethods.portal.mech.dir.IPrincipalMechanics: Added	com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces
com.webmethods.portal.mech.dir.IRoleMechanics: Added	com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces
com.webmethods.portal.mech.dir.IUserMechanics: Added	com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces
com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method	'public java.lang.String generateUUIDQuery(com.webmethods.portal.service.dir.IDirService, java.lang.String, int)' has been

Added API	Description
added	
com.webmethods.portal.mech.dir.impl.DirServiceMechanics:	Method 'public java.util.List updatePrincipalUUID(int)' has been added
com.webmethods.portal.mech.dir.impl.GroupMechanics:	Added com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces
com.webmethods.portal.mech.dir.impl.GroupMechanics:	Added com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses
com.webmethods.portal.mech.dir.impl.PrincipalMechanics:	Added com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces
com.webmethods.portal.mech.dir.impl.PrincipalMechanics:	Added com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses
com.webmethods.portal.mech.dir.impl.RoleMechanics:	Added com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces
com.webmethods.portal.mech.dir.impl.RoleMechanics:	Added com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses
com.webmethods.portal.mech.dir.impl.UserMechanics:	Added com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces
com.webmethods.portal.mech.dir.impl.UserMechanics:	Added com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses
com.webmethods.portal.mech.task.impl.RefreshTaskHandler:	Class com.webmethods.portal.mech.task.impl.RefreshTaskHandler added
com.webmethods.portal.mech.task.impl.TaskHelper:	Method 'public java.lang.ClassLoader getClassLoaderIfExists(com.webmethods.portal.service.task.ITaskDefinition)' has been added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics:	Method 'protected com.webmethods.portal.service.view.IPagingCookie createPagingCookie(com.webmethods.portal.service.meta2.thing.IThingID)' has been added
com.webmethods.portal.service.access.IAccessPrivilegeConfiguration:	Class com.webmethods.portal.service.access.IAccessPrivilegeConfiguration added
com.webmethods.portal.service.access.impl.DashboardAclManager:	Class com.webmethods.portal.service.access.impl.DashboardAclManager added
com.webmethods.portal.service.access.impl.DashboardAclManager\$DashboardAclResource:	Class com.webmethods.portal.service.access.impl.DashboardAclManager\$DashboardAclResource added
com.webmethods.portal.service.access.impl.DashboardContainerAclManager:	Class com.webmethods.portal.service.access.impl.DashboardContainerAclManager added
com.webmethods.portal.service.access.impl.DashboardContainerAclManager\$DashboardContainerAcl	

Added API	Description
Resource: Class	
com.webmethods.portal.service.access.impl.DashboardContainerAclManager\$DashboardContainerAclResource added	
com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'public java.util.Map getResultColumnMetadata()' has been added	
com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'public java.util.List searchResources(com.webmethods.caf.faces.search.query.ISearchQuery)' has been added	
com.webmethods.portal.service.access.impl.GadgetsAclManager\$GadgetAclResource: Method 'public java.lang.Object getValue(java.lang.Object)' has been added	
com.webmethods.portal.service.access.impl.WMApplsAclManager: Method 'public void addServiceTracker(org.osgi.framework.BundleContext)' has been added	
com.webmethods.portal.service.access.impl.WMApplsAclManager: Method 'public void stopServiceTracker()' has been added	
com.webmethods.portal.service.cache.impl.AliasCache: Added	
com.webmethods.portal.event.remove.IDeleteEvent\$ISynchronousListener to the set of implemented interfaces	
com.webmethods.portal.service.cache.impl.AliasCache: Method 'public void onSynchronousEvent(com.webmethods.portal.event.remove.IDeleteEvent)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Added public field UUIDUserResolution	
com.webmethods.portal.service.dir.DirectoryTools: Added protected field UUID_CONFIG	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public	
com.webmethods.portal.service.dir.IDirService	
getDirectoryService(com.webmethods.portal.system.IURI)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.util.List getEmptyUUIDUsers()' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.lang.Boolean getUUIDResolution()' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.lang.String getUserDNFromUserUUID(java.lang.String, com.webmethods.portal.service.meta2.IUserService)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public void invalidateGroupRoleCache(com.webmethods.portal.service.meta2.thing.IThingID)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public	
com.webmethods.portal.service.meta2.thing.IThingID	
resolveUserByUUID(com.webmethods.portal.service.dir.init.IInitializableUser)' has been added	

Added API	Description
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.util.List updatePrincipalUUID()' has been added	
com.webmethods.portal.service.dir.IDirConstants: Added public field USER_UUID	
com.webmethods.portal.service.dir.IDirQueryProvider: Method 'public com.webmethods.portal.service.dir.IDirPrincipal lookupByUUID(int, java.lang.String)' has been added to an interface	
com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public boolean isSirNameFirst(com.webmethods.portal.bizPolicy.IContext)' has been added	
com.webmethods.portal.service.dir.init.IInitializablePrincipal: Method 'public java.lang.String getUUID()' has been added to an interface	
com.webmethods.portal.service.dir.init.impl.InitializablePrincipal: Method 'public java.lang.String getUUID()' has been added	
com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.List getEmptyUUIDUsers()' has been added to an interface	
com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.Map getUserDetailsByURI(com.webmethods.portal.system.IURI)' has been added to an interface	
com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.Map getUserDetailsByUUID(java.lang.String)' has been added to an interface	
com.webmethods.portal.service.meta2.IUserService: Method 'public void invalidateUserUUID()' has been added to an interface	
com.webmethods.portal.service.meta2.IUserService: Method 'public void updateDistinguishedName(java.lang.String, java.lang.String, int)' has been added to an interface	
com.webmethods.portal.service.meta2.IUserService: Method 'public void updateUUID(java.lang.String, java.lang.String, int)' has been added to an interface	
com.webmethods.portal.service.meta2.directory.IUserInfo: Method 'public java.lang.String getUUID()' has been added to an interface	
com.webmethods.portal.service.meta2.directory.impl.User: Method 'public java.lang.String getUUID()' has been added	
com.webmethods.portal.service.meta2.directory.impl.UserInfo: Added protected field uuid	
com.webmethods.portal.service.meta2.directory.impl.UserInfo: Method 'public java.lang.String getUUID()' has been added	
com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.List getEmptyUUIDUsers()' has been added	
com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.Map getUserDetailsByURI(com.webmethods.portal.system.IURI)' has been added	

Added API	Description
com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.Map getUserDetailsByUUID(java.lang.String)' has been added	
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void invalidateUserUUID()' has been added	
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void updateDistinguishedName(java.lang.String, java.lang.String, int)' has been added	
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void updateUUID(java.lang.String, java.lang.String, int)' has been added	
com.webmethods.portal.service.socialbpm.chart.impl.ChartData: Method 'public java.lang.String getTaskTypeID()' has been added	
com.webmethods.portal.service.socialbpm.chart.impl.ChartData: Method 'public void setTaskTypeID(java.lang.String)' has been added	
com.webmethods.portal.service.socialbpm.chart.impl.ChartService: Method 'protected java.lang.String getTaskTypeID(java.lang.String)' has been added	
com.webmethods.portal.service.sql.runtime.base.EmptyUUIDUserList: Class com.webmethods.portal.service.sql.runtime.base.EmptyUUIDUserList added	
com.webmethods.portal.service.sql.runtime.base.InvalidateUserUUID: Class com.webmethods.portal.service.sql.runtime.base.InvalidateUserUUID added	
com.webmethods.portal.service.sql.runtime.base.SetUserGroupUUID: Class com.webmethods.portal.service.sql.runtime.base.SetUserGroupUUID added	
com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Class com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew added	
com.webmethods.portal.service.sql.runtime.base.UserDetailsByURI: Class com.webmethods.portal.service.sql.runtime.base.UserDetailsByURI added	
com.webmethods.portal.service.sql.runtime.base.UserDetailsByUUID: Class com.webmethods.portal.service.sql.runtime.base.UserDetailsByUUID added	
com.webmethods.portal.service.task.ITaskLockingService: Method 'public com.webmethods.portal.service.task.ITaskLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' has been added to an interface	
com.webmethods.portal.service.task.event.RefreshTaskEvent: Class com.webmethods.portal.service.task.event.RefreshTaskEvent added	
com.webmethods.portal.service.task.event.RefreshTaskEvent\$ISynchronousListener: Class com.webmethods.portal.service.task.event.RefreshTaskEvent\$ISynchronousListener added	
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners: Class com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners added	

Added API	Description
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners\$SynchronousListener: Class	
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners\$SynchronousListener added	
com.webmethods.portal.service.task.event.TaskChangedEventRetry: Class	
com.webmethods.portal.service.task.event.TaskChangedEventRetry added	
com.webmethods.portal.service.task.event.impl.RefreshTaskEvent: Class	
com.webmethods.portal.service.task.event.impl.RefreshTaskEvent added	
com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public	
com.webmethods.portal.service.task.ITaskLock acquireLock(com.webmethods.portal.system.IURI,	
com.webmethods.portal.system.IURI, long, long, boolean)' has been added	
com.webmethods.portal.system.ISAMLSSOConstants: Class	
com.webmethods.portal.system.ISAMLSSOConstants added	
com.webmethods.portal.system.cluster.IClusterProvider: Method 'public java.lang.String	
getClusterId()' has been added to an interface	
com.webmethods.portal.system.cluster.IClusterProvider: Method 'public boolean	
isCurrentServer(com.webmethods.portal.system.cluster.IServer)' has been added to an interface	
com.webmethods.portal.system.cluster.IClusterProvider: Method 'public void	
recreateJNDIConnection()' has been added to an interface	
com.webmethods.portal.system.cluster.IClusterProvider: Method 'public boolean	
reloadJNDIProviderURL()' has been added to an interface	
com.webmethods.portal.system.cluster.impl.ClusterProvider: Added public field	
CLUSTER_ID_PROP_KEY	
com.webmethods.portal.system.cluster.impl.ClusterProvider: Added public field s_logCategory	
com.webmethods.portal.system.cluster.impl.ClusterProvider: Method 'public java.lang.String	
getClusterId()' has been added	
com.webmethods.portal.system.cluster.impl.ClusterProvider: Method 'public boolean	
isCurrentServer(com.webmethods.portal.system.cluster.IServer)' has been added	
com.webmethods.portal.system.cluster.impl.ClusterProvider: Method 'public void	
recreateJNDIConnection()' has been added	
com.webmethods.portal.system.cluster.impl.ClusterProvider: Method 'public boolean	
reloadJNDIProviderURL()' has been added	
com.webmethods.portal.system.sso.saml.idp.SAMLIdentityProvider: Class	
com.webmethods.portal.system.sso.saml.idp.SAMLIdentityProvider added	
com.webmethods.portal.system.sso.saml.idp.SAMLSSODataChangeListener: Class	

Added API	Description
com.webmethods.portal.system.sso.saml.idp.SAMLSSODataChangeListener	added
com.webmethods.portal.system.sso.saml.idp.SAMLServiceProvider	Class added
com.webmethods.portal.system.sso.saml.idp.SAMLServiceProvider	added
com.webmethods.portal.system.sso.saml.idp.SSOIDPConfiguration	Class added
com.webmethods.portal.system.sso.saml.idp.SSOIDPConfiguration	added
com.webmethods.portal.system.sso.saml.idp.WebSSOPropsUtil	Class added
com.webmethods.portal.system.sso.saml.idp.WebSSOPropsUtil	added
com.webmethods.portal.taglib.TaglibUtil	Method 'public java.lang.String generateUniqueID()' has been added
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory	Method 'public org.opensaml.saml2.core.AuthnRequest getAuthnRequest(java.lang.String)' has been added
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory	Method 'public java.lang.String getResponse(java.net.URL, java.lang.String, java.util.Map, java.lang.String[], java.util.Map, org.opensaml.saml2.core.AuthnRequest)' has been added
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory	Method 'public void reInitSecurityTokenService()' has been added
com.webmethods.rtl.event.DeliveryService	Method 'public java.lang.String addClusterIdPrefix(java.lang.String)' has been added
com.webmethods.rtl.event.DeliveryService	Method 'public void setClusterId(java.lang.String)' has been added
com.webmethods.rtl.event.DeliveryService	Method 'public void startRemoteDelivery()' has been added
com.webmethods.rtl.event.DeliveryService	Method 'public void stopRemoteDelivery()' has been added
com.webmethods.rtl.event.Event	Method 'public java.lang.String getJcrSessionUserData()' has been added
com.webmethods.rtl.event.IEvent	Method 'public java.lang.String getJcrSessionUserData()' has been added to an interface
com.webmethods.rtl.jms.PortalClientOverJMS	Class com.webmethods.rtl.jms.PortalClientOverJMS added
com.webmethods.rtl.logging.EnhancedPatternLayout	Class added
com.webmethods.rtl.logging.EnhancedPatternLayout	added
com.webmethods.rtl.msg.jms.IJMSPProvider	Method 'public java.lang.String getEndpointAddress()' has been added to an interface
com.webmethods.rtl.msg.jms.IJMSPProvider	Method 'public boolean isConnected()' has been added to

Added API	Description
an interface	
com.webmethods.rtl.msg.jms.JMSProvider:	Added protected field m_endpointAddress
com.webmethods.rtl.msg.jms.JMSProvider:	Added protected field m_isConnected
com.webmethods.rtl.msg.jms.JMSProvider:	Method 'public java.lang.String getEndpointAddress()' has been added
com.webmethods.rtl.msg.jms.JMSProvider:	Method 'public boolean isConnected()' has been added
com.webmethods.rtl.msg.jms.JMSProvider:	Abstract method 'protected void stopConnections()' has been added
com.webmethods.rtl.msg.jms.JMSStdConnProvider:	Method 'protected void stopConnections()' has been added
com.webmethods.rtl.script.JspC:	Method 'public java.lang.String getExcludes()' has been added
com.webmethods.rtl.script.JspC:	Method 'public void setExcludes(java.lang.String)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'protected org.w3c.dom.Document _loadDocumentUncaught(org.xml.sax.InputSource)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromInputStreamUncaught(java.io.InputStream)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromReaderUncaught(java.io.Reader)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromXMLUncaught(java.lang.String)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentUncaught(java.lang.String)' has been added

Removed API	Replacement, if any
com.webmethods.caf.jcr.rmi.IRMITunnelHttpPortAware:	Class com.webmethods.caf.jcr.rmi.IRMITunnelHttpPortAware removed
com.webmethods.caf.jcr.rmi.JcrRMIHttpToCGISocketFactory:	Class com.webmethods.caf.jcr.rmi.JcrRMIHttpToCGISocketFactory removed
com.webmethods.caf.jcr.rmi.JcrRMIMasterSocketFactory:	Class com.webmethods.caf.jcr.rmi.JcrRMIMasterSocketFactory removed
com.webmethods.jackrabbit.server.io.DefaultHandler:	Class com.webmethods.jackrabbit.server.io.DefaultHandler removed
com.webmethods.jackrabbit.servlet.JCRWebdavServerServlet:	Class com.webmethods.jackrabbit.servlet.JCRWebdavServerServlet removed

Removed API**Replacement, if any**

com.webmethods.jackrabbit.servlet.SimpleWebdavServlet: Class
com.webmethods.jackrabbit.servlet.SimpleWebdavServlet removed

com.webmethods.portal.jms.um.UmJMSClient: Field DEFAULT_UM_REALM has been removed, but it was previously a constant

com.webmethods.portal.jms.um.UmJMSClient: Method 'public void init()' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Removed field gadgetExternalScripts

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Method 'public
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts
getGadgetExternalScripts()' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Method 'public void
setGadgetExternalScripts(com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternal
Scripts)' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts: Class
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts removed

com.webmethods.portal.schema.bcgadget.ObjectFactory: Method 'public
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts
createGadgetDefinitionGadgetExternalScripts()' has been removed

com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'protected java.lang.String
buildXPathQuery(java.util.Map)' has been removed, but an inherited definition exists.

com.webmethods.portal.service.access.impl.GadgetsAclManager\$GadgetAclResource: Method 'public
GadgetsAclManager\$GadgetAclResource(javax.jcr.Node, java.lang.String)' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'public void enableMessageDelivery()' has been
removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'public boolean hasInitialized()' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected void
setInstance(com.webmethods.rtl.msg.jms.JMSProvider)' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected void startConnections()' has been
removed

com.webmethods.rtl.msg.jms.JMSStdConnProvider: Method 'protected void startConnections()' has
been removed

Changed API**Description**

com.webmethods.caf.common.bnd.PortletXmlAnalyzer: Parameter 1 of 'public boolean
analyzeJar(aQute.lib.osgi.Analyzer)' has changed its type to aQute.bnd.osgi.Analyzer

Changed API**Description**

com.webmethods.caf.common.bnd.WebXmlAnalyzer: Parameter 1 of 'public boolean analyzeJar(aQute.lib.osgi.Analyzer)' has changed its type to aQute.bnd.osgi.Analyzer

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 2 of 'public void displayAssertion(java.io.PrintWriter, org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public java.lang.String getLoginName(org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLAssertion getSamlAssertion(java.lang.String, java.lang.String)' has been changed to org.opensaml.saml1.core.Assertion

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public org.opensaml.SAMLAssertion getSamlAssertion(org.opensaml.SAMLResponse)' has changed its type to org.opensaml.saml1.core.Response

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLAssertion getSamlAssertion(org.opensaml.SAMLResponse)' has been changed to org.opensaml.saml1.core.Assertion

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLResponse getSamlResponse(java.lang.String, java.lang.String)' has been changed to org.opensaml.saml1.core.Response

com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public java.lang.String verifyAssertion(org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public UmJMSClient()' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void closeUMSession(com.pcbSYS.nirvana.client.nSession)' has been decreased from public to private

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createConnectionFactory(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Return type of method 'public javax.naming.Context createJNDIContext()' has been changed to void

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public javax.naming.Context createJNDIContext()' has been decreased from public to private

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createQueue(java.lang.String, boolean, int)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void

Changed API**Description**

`createQueueConnectionFactory(java.lang.String)` has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `createStringVal(java.lang.String, java.lang.String)`' has been decreased from public to package

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `createTopic(java.lang.String, boolean, int)`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `createTopicConnectionFactory(java.lang.String)`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `createXAConnectionFactory(java.lang.String)`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `deleteConnectionFactory(java.lang.String)`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `deleteQueue(java.lang.String)`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `deleteQueueConnectionFactory(java.lang.String)`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `deleteTopic(java.lang.String)`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public void `deleteTopicConnectionFactory(java.lang.String)`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public `javax.naming.Context getJNDIContext()`' has been decreased from public to protected

`com.webmethods.portal.jms.um.UmJMSClient`: Accessibility of method 'public `com.pcbsys.nirvana.client.nSession getUMSession()`' has been decreased from public to private

`com.webmethods.portal.service.bcgadget.IBCGadgetProvider`: Return type of method 'public `java.util.List getAccessibleGadgets(com.webmethods.portal.service.meta2.thing.IThingID)`' has been changed to `java.util.Map`

`com.webmethods.portal.service.bcgadget.impl.BCGadgetProvider`: Return type of method 'public `java.util.List getAccessibleGadgets(com.webmethods.portal.service.meta2.thing.IThingID)`' has been changed to `java.util.Map`

`com.webmethods.portal.service.task.impl.TaskLockingService`: Accessibility of field `TASK_LOCK_MAX_TIME` has been increased from private to public

`com.webmethods.portal.service.task.impl.TaskLockingService`: Accessibility of field `TASK_LOCK_MAX_WAIT_TIME` has been increased from private to public

`com.webmethods.portal.service.task.impl.TaskLockingService`: In method 'protected `com.webmethods.portal.service.task.ITaskLock createDbLock(com.webmethods.portal.service.sql.ISqlWorker,`

Changed API**Description**

com.webmethods.portal.service.meta2.thing.IThingID, java.util.Date, java.util.Date)' the number of arguments has changed

com.webmethods.portal.system.PortalSystem: Accessibility of method 'private void initGuestUser()' has been increased from private to public

com.webmethods.rtl.msg.jms.JMSProvider: Accessibility of method 'public void onShutdown()' has been decreased from public to protected

com.webmethods.rtl.msg.jms.JMSProvider: Accessibility of method 'private void setMaintenanceMode(boolean)' has been increased from private to protected

com.webmethods.rtl.msg.jms.JMSStdConnProvider: Accessibility of method 'public JMSStdConnProvider()' has been decreased from public to protected

com.webmethods.portal.service.version.impl.dcv.DCVersionService: Value of compile-time constant VERSION_SERVICES_ROOT has been changed

Release 9.10

Added API/ Description

com.webmethods.portal.bizPolicy.biz.access.IAccessPolicy: Method 'public

com.webmethods.portal.service.view.IListView

listSecurityRealmObjects(com.webmethods.portal.bizPolicy.IContext,

com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.mech.subscription.ISubscribableMechanics: Method 'public void

checkViewSubscription(com.webmethods.portal.system.IURI,

com.webmethods.portal.service.meta2.thing.IThingID, java.util.Map,

com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.bizPolicy.biz.IBizPolicyResolver: Method 'public

com.webmethods.portal.bizPolicy.biz.IBizPolicy getBizPolicyByType(java.lang.String, java.util.Map)

has been added to an interface

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String

getAssertion(java.lang.String, java.lang.String[], java.util.Map)' has been added to an interface

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String

getAssertion(java.lang.String, java.lang.String[], java.util.Map, java.util.Map)' has been added to an

interface

com.webmethods.caf.wsclient.session.IWSClientSession: Method 'public java.util.Map

getSessionCookieMap()' has been added to an interface

com.webmethods.caf.wsclient.session.IWSClientSession: Method 'public void

setSessionCookieMap(java.util.Map)' has been added to an interface

com.webmethods.caf.wsclient.session.IWSClientSessionManager: Method 'public

com.webmethods.caf.wsclient.session.IWSClientSessionPool

getSessionPool(com.webmethods.caf.wsclient.proxy.IWSClientProxy, java.lang.String)' has been added

to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public java.util.Date getTaskScheduleDate()' has been added to an interface

has been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void setCreatedDate(java.util.Date)' has been added to an interface

has been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void

setTaskScheduleDate(java.util.Date)' has been added to an interface

com.webmethods.portal.service.task.ITask: Method 'public java.util.Date getTaskScheduleDate()' has been added to an interface

has been added to an interface

Changed API/ Description

com.webmethods.portal.event.system.ICriterionEvent\$IListener: Parameter 1 of 'public void onEvent(com.webmethods.portal.event.system.ISubscriptionEvent)' has changed its type to com.webmethods.portal.event.system.ICriterionEvent

com.webmethods.portal.event.system.ICriterionEvent\$ISynchronousListener: Parameter 1 of 'public void onSynchronousEvent(com.webmethods.portal.event.system.ISubscriptionEvent)' has changed its type to com.webmethods.portal.event.system.ICriterionEvent

com.webmethods.portal.service.access.impl.MwsObjectAclManager: In method 'protected int countAceProperties(java.util.List)' the number of arguments has changed

com.webmethods.caf.wsclient.session.impl.WSClientSessionManager: Parameter 2 of 'protected java.lang.String getSessionPoolID(com.webmethods.caf.wsclient.proxy.IWSClientProxy, com.webmethods.caf.wsclient.AuthCredentials)' has changed its type to java.lang.String

Removed API/ Description

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Removed field
COMPONENT_DELETE_RETRIES

com.webmethods.portal.service.global.impl.LanguagePackManager: Field QUERY_STRING has been
removed, but it was previously a constant

com.webmethods.caf.faces.convert.FormattedDateTimeConverter: Method 'protected
java.text.DateFormat setupGMTDateTimeFormatter(javax.faces.context.FacesContext)' has been
removed

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.util.List getTaskCommentsByProcessModelId(java.lang.String, int, int, int)' has been added to an
interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List
getPaginatedTaskCommentsByProcessModelId(java.lang.String, int, int, int)' has been added to an
interface

com.webmethods.portal.service.dir.IRoleSystem: Method 'public void
clearCache(com.webmethods.portal.service.dir.IDirPrincipal)' has been added to an interface

com.webmethods.portal.mech.dir.IPrincipalMechanics: Method 'public void
fireRoleMembershipEvent(com.webmethods.portal.service.meta2.thing.IThingID,
com.webmethods.portal.system.IURI, com.webmethods.portal.service.dir.IDirPrincipalList,
com.webmethods.portal.service.dir.IDirPrincipalList, int)' has been added to an interface

move the com.webmethods.jms.** packages from caf-server bundle to a unique package name

com.webmethods.jms.JMSPhaseProvider: Class com.webmethods.jms.JMSPhaseProvider removed

com.webmethods.jms.db.DbJMSClient: Class com.webmethods.jms.db.DbJMSClient removed

com.webmethods.jms.db.DbJMSConnProvider: Class com.webmethods.jms.db.DbJMSConnProvider
removed

com.webmethods.jms.db.impl.JMSConnection: Class com.webmethods.jms.db.impl.JMSConnection
removed

com.webmethods.jms.db.impl.JMSConnection\$CompressedObject: Class
com.webmethods.jms.db.impl.JMSConnection\$CompressedObject removed

com.webmethods.jms.db.impl.JMSDestination: Class com.webmethods.jms.db.impl.JMSDestination removed

com.webmethods.jms.db.impl.JMSDispatcherThread: Class
com.webmethods.jms.db.impl.JMSDispatcherThread removed

com.webmethods.jms.db.impl.JMSEvent: Class com.webmethods.jms.db.impl.JMSEvent removed

com.webmethods.jms.db.impl.JMSMessage: Class com.webmethods.jms.db.impl.JMSMessage removed

com.webmethods.jms.db.impl.JMSMessageConsumer: Class
com.webmethods.jms.db.impl.JMSMessageConsumer removed

com.webmethods.jms.db.impl.JMSMessageProducer: Class
com.webmethods.jms.db.impl.JMSMessageProducer removed

com.webmethods.jms.db.impl.JMSObjectMessage: Class
com.webmethods.jms.db.impl.JMSObjectMessage removed

com.webmethods.jms.db.impl.JMSPollThread: Class com.webmethods.jms.db.impl.JMSPollThread removed

com.webmethods.jms.db.impl.JMSQueue: Class com.webmethods.jms.db.impl.JMSQueue removed

com.webmethods.jms.db.impl.JMSQueuePollThread: Class
com.webmethods.jms.db.impl.JMSQueuePollThread removed

com.webmethods.jms.db.impl.JMSQueueReceiver: Class
com.webmethods.jms.db.impl.JMSQueueReceiver removed

com.webmethods.jms.db.impl.JMSQueueSender: Class
com.webmethods.jms.db.impl.JMSQueueSender removed

com.webmethods.jms.db.impl.JMSQueueSession: Class
com.webmethods.jms.db.impl.JMSQueueSession removed

com.webmethods.jms.db.impl.JMSSession: Class com.webmethods.jms.db.impl.JMSSession removed

com.webmethods.jms.db.impl.JMSTopic: Class com.webmethods.jms.db.impl.JMSTopic removed

com.webmethods.jms.db.impl.JMSTopicBatchMessage: Class
com.webmethods.jms.db.impl.JMSTopicBatchMessage removed

com.webmethods.jms.db.impl.JMSTopicPublisher: Class
com.webmethods.jms.db.impl.JMSTopicPublisher removed

com.webmethods.jms.db.impl.JMSTopicSession: Class com.webmethods.jms.db.impl.JMSTopicSession removed

com.webmethods.jms.db.impl.JMSTopicSubscriber: Class
com.webmethods.jms.db.impl.JMSTopicSubscriber removed

com.webmethods.jms.db.impl.QueueFactory: Class com.webmethods.jms.db.impl.QueueFactory removed

com.webmethods.jms.db.impl.TopicFactory: Class com.webmethods.jms.db.impl.TopicFactory removed

com.webmethods.jms.db.impl.db2.EventDelivered: Class
com.webmethods.jms.db.impl.db2.EventDelivered removed

com.webmethods.jms.db.impl.db2.EventPoll: Class com.webmethods.jms.db.impl.db2.EventPoll removed

com.webmethods.jms.db.impl.db2.EventSave: Class com.webmethods.jms.db.impl.db2.EventSave removed

com.webmethods.jms.db.impl.db2.GetSqlTime: Class com.webmethods.jms.db.impl.db2.GetSqlTime removed

com.webmethods.jms.db.impl.db2.PublishQueue: Class
com.webmethods.jms.db.impl.db2.PublishQueue removed

com.webmethods.jms.db.impl.db2.PurgeEvents: Class com.webmethods.jms.db.impl.db2.PurgeEvents removed

com.webmethods.jms.db.impl.db2.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.db2.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.db2.RegisterDestination: Class
com.webmethods.jms.db.impl.db2.RegisterDestination removed

com.webmethods.jms.db.impl.db2.RegisterSubscription: Class
com.webmethods.jms.db.impl.db2.RegisterSubscription removed

com.webmethods.jms.db.impl.db2.UnregisterSubscription: Class
com.webmethods.jms.db.impl.db2.UnregisterSubscription removed

com.webmethods.jms.db.impl.db2.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.db2.UpdateSubscriptions removed

com.webmethods.jms.db.impl.mssql.EventDelivered: Class
com.webmethods.jms.db.impl.mssql.EventDelivered removed

com.webmethods.jms.db.impl.mssql.EventPoll: Class com.webmethods.jms.db.impl.mssql.EventPoll removed

com.webmethods.jms.db.impl.mssql.EventSave: Class com.webmethods.jms.db.impl.mssql.EventSave removed

com.webmethods.jms.db.impl.mssql.GetSqlTime: Class
com.webmethods.jms.db.impl.mssql.GetSqlTime removed

com.webmethods.jms.db.impl.mssql.PublishQueue: Class
com.webmethods.jms.db.impl.mssql.PublishQueue removed

com.webmethods.jms.db.impl.mssql.PurgeEvents: Class
com.webmethods.jms.db.impl.mssql.PurgeEvents removed

com.webmethods.jms.db.impl.mssql.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.mssql.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.mssql.RegisterDestination: Class
com.webmethods.jms.db.impl.mssql.RegisterDestination removed

com.webmethods.jms.db.impl.mssql.RegisterSubscription: Class
com.webmethods.jms.db.impl.mssql.RegisterSubscription removed

com.webmethods.jms.db.impl.mssql.UnregisterSubscription: Class
com.webmethods.jms.db.impl.mssql.UnregisterSubscription removed

com.webmethods.jms.db.impl.mssql.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.mssql.UpdateSubscriptions removed

com.webmethods.jms.db.impl.mysql.EventDelivered: Class
com.webmethods.jms.db.impl.mysql.EventDelivered removed

com.webmethods.jms.db.impl.mysql.EventPoll: Class com.webmethods.jms.db.impl.mysql.EventPoll
removed

com.webmethods.jms.db.impl.mysql.EventSave: Class com.webmethods.jms.db.impl.mysql.EventSave
removed

com.webmethods.jms.db.impl.mysql.GetSqlTime: Class
com.webmethods.jms.db.impl.mysql.GetSqlTime removed

com.webmethods.jms.db.impl.mysql.PublishQueue: Class
com.webmethods.jms.db.impl.mysql.PublishQueue removed

com.webmethods.jms.db.impl.mysql.PurgeEvents: Class
com.webmethods.jms.db.impl.mysql.PurgeEvents removed

com.webmethods.jms.db.impl.mysql.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.mysql.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.mysql.RegisterDestination: Class
com.webmethods.jms.db.impl.mysql.RegisterDestination removed

com.webmethods.jms.db.impl.mysql.RegisterSubscription: Class
com.webmethods.jms.db.impl.mysql.RegisterSubscription removed

com.webmethods.jms.db.impl.mysql.UnregisterSubscription: Class
com.webmethods.jms.db.impl.mysql.UnregisterSubscription removed

com.webmethods.jms.db.impl.mysql.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.mysql.UpdateSubscriptions removed

com.webmethods.jms.db.impl.oracle.EventDelivered: Class
com.webmethods.jms.db.impl.oracle.EventDelivered removed

com.webmethods.jms.db.impl.oracle.EventPoll: Class com.webmethods.jms.db.impl.oracle.EventPoll
removed

com.webmethods.jms.db.impl.oracle.EventSave: Class com.webmethods.jms.db.impl.oracle.EventSave removed

com.webmethods.jms.db.impl.oracle.GetSqlTime: Class
com.webmethods.jms.db.impl.oracle.GetSqlTime removed

com.webmethods.jms.db.impl.oracle.PublishQueue: Class
com.webmethods.jms.db.impl.oracle.PublishQueue removed

com.webmethods.jms.db.impl.oracle.PurgeEvents: Class
com.webmethods.jms.db.impl.oracle.PurgeEvents removed

com.webmethods.jms.db.impl.oracle.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.oracle.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.oracle.RegisterDestination: Class
com.webmethods.jms.db.impl.oracle.RegisterDestination removed

com.webmethods.jms.db.impl.oracle.RegisterSubscription: Class
com.webmethods.jms.db.impl.oracle.RegisterSubscription removed

com.webmethods.jms.db.impl.oracle.UnregisterSubscription: Class
com.webmethods.jms.db.impl.oracle.UnregisterSubscription removed

com.webmethods.jms.db.impl.oracle.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.oracle.UpdateSubscriptions removed

com.webmethods.jms.db.impl.sybase.EventPoll: Class com.webmethods.jms.db.impl.sybase.EventPoll removed

com.webmethods.jms.db.impl.sybase.PublishQueue: Class
com.webmethods.jms.db.impl.sybase.PublishQueue removed

com.webmethods.jms.db.impl.sybase.PurgeEvents: Class
com.webmethods.jms.db.impl.sybase.PurgeEvents removed

com.webmethods.jms.um.UmJMSClient: Class com.webmethods.jms.um.UmJMSClient removed

com.webmethods.jms.um.UmJMSSConnProvider: Class
com.webmethods.jms.um.UmJMSSConnProvider removed

electric.util.holder.ArrayOfbyteInOut: Class electric.util.holder.ArrayOfbyteInOut removed

electric.util.holder.ArrayOfbyteOut: Class electric.util.holder.ArrayOfbyteOut removed

com.webmethods.portal.bizPolicy.command.system.xml.XMLImport: Field
OVERWRITE_PERMISSIONS_KEY has been removed, but it was previously a constant

com.webmethods.portal.service.dir.IDirService: Method 'public boolean supportsNestedGroups()' has been added to an interface

com.webmethods.caf.faces.application.CAFStateManager: Class
com.webmethods.caf.faces.application.CAFStateManager removed

com.webmethods.caf.faces.application.CAFStateManager\$TreeStructure: Class
com.webmethods.caf.faces.application.CAFStateManager\$TreeStructure removed

com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListener: Class
com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListener removed

com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListenerWrapper: Class
com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListenerWrapper removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected void
initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected void
renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been
removed

com.webmethods.caf.faces.render.html.command.CommandFormRenderer: In method 'protected
java.lang.String getTagName()' the number of arguments has changed

com.webmethods.caf.faces.render.html.command.DisjointFormRenderer: In method 'protected
java.lang.String getTagName()' the number of arguments has changed

com.webmethods.caf.faces.view.BaseViewHandler: Field STATE_KEY has been removed, but it was
previously a constant

com.webmethods.caf.faces.view.BaseViewHandler: Method 'protected void
initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.view.BaseViewHandler: Method 'protected void
renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been
removed

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field INJECT_STATE has been
removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field NO_RENDER has been removed,
but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field STATE_KEY has been removed,
but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field VIEW_FRAGMENT has been
removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field VIEW_FRAGMENT_CLIENT_ID
has been removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Return type of method 'protected void
initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been changed
to javax.faces.context.ResponseWriter

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Method 'protected void renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.view.ViewFragmentPhaseListener: Class
com.webmethods.caf.faces.view.ViewFragmentPhaseListener removed

Release 9.9

Added API/ Description

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public java.lang.Integer getIsMandatory()' has been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void setIsMandatory(java.lang.Integer)' has been added to an interface

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String validateSAMLResponse(javax.servlet.http.HttpServletRequest, java.lang.String)' has been added to an interface

com.webmethods.portal.bizPolicy.biz.access.IAccessPolicy: Method 'public
com.webmethods.portal.service.view.IListView
listSecurityRealmObjects(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.util.List getAllTaskAttachments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.lang.Integer getAllTaskAttachmentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.util.List getTaskComments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.lang.Integer getTaskCommentsCount(int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public
java.lang.Integer getTaskCommentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.mech.subscription.ISubscribableMechanics: Method 'public void
checkViewSubscription(com.webmethods.portal.system.IURI,
com.webmethods.portal.service.meta2.thing.IThingID, java.util.Map,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List
getAllTaskAttachments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public
java.lang.Integer getAllTaskAttachmentsCount(java.lang.String)' has been added to an interface

Added API/ Description

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List getTaskComments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.lang.Integer getTaskCommentsCount(int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.lang.Integer getTaskCommentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.service.task.ITask: Method 'public java.lang.Integer getIsMandatory()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public java.lang.String getTaskDescription()' has been added to an interface

Removed API/ Description

com.webmethods.caf.faces.component.gmap.GMarkerGroup: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.gmap.GMarkerList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.AsyncIterator: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.Import: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.ImportTemplate: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.Iterator: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.Breadcrumbs: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.FirstLevelList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.NavList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.PopupMenus: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.SecondLevelList: Removed javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.StaticMenus\$SubList: Removed

Removed API/ Description

javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.StaticMenus\$SubSubList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.ThirdLevelList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncListbox: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncTabsList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.DataList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.ListBox: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.TabsList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed
com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed
com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

Removed API/ Description

com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.rtl.script.JspC: Removed java.lang.Cloneable from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.ProjectComponent from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.Task from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.ProjectComponent from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.Task from the list of superclasses

com.webmethods.caf.faces.component.logic.Import: Method 'public boolean isListenerForSource(java.lang.Object)' has been removed

com.webmethods.caf.faces.component.logic.Import: Method 'public void processEvent(javax.faces.event.SystemEvent)' has been removed

com.webmethods.caf.faces.component.logic.ImportTemplate: Method 'public boolean isListenerForSource(java.lang.Object)' has been removed

com.webmethods.caf.faces.component.logic.ImportTemplate: Method 'public void processEvent(javax.faces.event.SystemEvent)' has been removed

Removed API/ Description

com.webmethods.caf.faces.component.nav.PopupMenus: Method 'protected javax.faces.component.UIColumn getColumn()' has been removed

com.webmethods.caf.faces.component.table.html.DataList: Method 'public boolean isListenerForSource(java.lang.Object)' has been removed

com.webmethods.caf.faces.component.table.html.DataList: Method 'public void processEvent(javax.faces.event.SystemEvent)' has been removed

com.webmethods.caf.faces.component.tree.DataTree: Method 'protected void autogenerate()' has been removed

com.webmethods.portal.service.install.impl.BaseInstallService: Method 'protected com.webmethods.portal.service.install.IInstallServiceConfig getConfig()' has been removed

com.webmethods.portal.service.sql.runtime.base.TaskSearchAll: Method 'protected void parseSearchQuery(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQuery, com.webmethods.portal.service.sql.runtime.base.TaskSearchAll\$QueryInfo)' has been removed

com.webmethods.portal.service.sql.runtime.base.TaskSearchAll: Method 'protected void parseSearchQueryTerm(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm, com.webmethods.portal.service.sql.runtime.base.TaskSearchAll\$QueryInfo)' has been removed

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesPaged: Method 'protected void parseSearchQueryTerm(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm, com.webmethods.portal.service.sql.runtime.base.TaskSearchAll\$QueryInfo)' has been removed

com.webmethods.rtl.script.JspC: Method 'public void init()' has been removed

com.softwareag.caf.controls.mwsx.PeoplePickerDialog\$FacetsMap: Class
com.softwareag.caf.controls.mwsx.PeoplePickerDialog\$FacetsMap removed

com.softwareag.caf.controls.mwsx.PeopleSwapBox\$FacetsMap: Class
com.softwareag.caf.controls.mwsx.PeopleSwapBox\$FacetsMap removed

com.webmethods.caf.faces.component.nav.StaticMenus\$ChildrenList: Class
com.webmethods.caf.faces.component.nav.StaticMenus\$ChildrenList removed

com.webmethods.caf.faces.component.nav.StaticMenus\$FacetsMap: Class
com.webmethods.caf.faces.component.nav.StaticMenus\$FacetsMap removed

com.webmethods.caf.faces.component.nav.ToggleMenus\$ChildrenList: Class
com.webmethods.caf.faces.component.nav.ToggleMenus\$ChildrenList removed

com.webmethods.caf.faces.component.nav.ToggleMenus\$FacetsMap: Class
com.webmethods.caf.faces.component.nav.ToggleMenus\$FacetsMap removed

com.webmethods.caf.faces.component.search.SearchBar\$FacetsMap: Class
com.webmethods.caf.faces.component.search.SearchBar\$FacetsMap removed

Removed API/ Description

com.webmethods.caf.faces.component.table.SelectRowCheckbox\$ChildrenList: Class
com.webmethods.caf.faces.component.table.SelectRowCheckbox\$ChildrenList removed

com.webmethods.caf.faces.component.table.SelectRowCheckbox\$FacetsMap: Class
com.webmethods.caf.faces.component.table.SelectRowCheckbox\$FacetsMap removed

com.webmethods.caf.faces.component.table.html.HtmlTableColumn\$FacetsMap: Class
com.webmethods.caf.faces.component.table.html.HtmlTableColumn\$FacetsMap removed

com.webmethods.caf.faces.component.table.specialized.Newsfeed\$ChildrenList: Class
com.webmethods.caf.faces.component.table.specialized.Newsfeed\$ChildrenList removed

com.webmethods.caf.faces.component.table.specialized.Newsfeed\$FacetsMap: Class
com.webmethods.caf.faces.component.table.specialized.Newsfeed\$FacetsMap removed

com.webmethods.caf.faces.component.util.BaseChildrenList: Class
com.webmethods.caf.faces.component.util.BaseChildrenList removed

com.webmethods.caf.faces.component.util.BaseFacetsAndChildrenIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsAndChildrenIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection\$BaseIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection\$BaseIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries\$EntrySetIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries\$EntrySetIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys\$KeySetIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys\$KeySetIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values\$ValuesIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values\$ValuesIterator removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseFileListTask: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseFileListTask removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseTask: Class

Removed API/ Description

com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseTask removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GenerateOSGiManifest: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GenerateOSGiManifest removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GetPortletInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GetPortletInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PostRegisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PostRegisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreRegisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreRegisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreUnregisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreUnregisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateSkinInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateSkinInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateThemeInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateThemeInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.GetSkinInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.GetSkinInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveSkinInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveSkinInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveThemeInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveThemeInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.CreateDBOTables: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.CreateDBOTables removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.DropDBOTables: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.DropDBOTables removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteCommand: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteCommand removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteTargetLoop: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteTargetLoop removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath removed

Removed API/ Description

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.InstallComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.InstallComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadClasses: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadClasses removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadConfig: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadConfig removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LookupComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LookupComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RegisterComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RegisterComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RunSQLScript: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RunSQLScript removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UninstallComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UninstallComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UnregisterComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UnregisterComponent removed

com.webmethods.portal.mech.install.impl.NativeInstallMechanics: Class
com.webmethods.portal.mech.install.impl.NativeInstallMechanics removed

com.webmethods.portal.service.install.IInstallServiceConfig: Class
com.webmethods.portal.service.install.IInstallServiceConfig removed

com.webmethods.portal.service.install.impl.InstallServiceConfig: Class
com.webmethods.portal.service.install.impl.InstallServiceConfig removed

com.webmethods.portal.service.install.impl.ant.AntInstallService: Class
com.webmethods.portal.service.install.impl.ant.AntInstallService removed

com.webmethods.portal.service.install.impl.ant.AntLogSupport: Class
com.webmethods.portal.service.install.impl.ant.AntLogSupport removed

com.webmethods.portal.service.install.impl.ant.AntRunner: Class
com.webmethods.portal.service.install.impl.ant.AntRunner removed

com.webmethods.portal.service.install.impl.ant.AntRunner\$AntPropertyHelper: Class

Removed API/ Description

com.webmethods.portal.service.install.impl.ant.AntRunner\$AntPropertyHelper removed

com.webmethods.portal.service.install.impl.ant.LpInstallService: Class
com.webmethods.portal.service.install.impl.ant.LpInstallService removed

com.webmethods.portal.service.install.impl.ant.WarLpInstallService: Class
com.webmethods.portal.service.install.impl.ant.WarLpInstallService removed

com.webmethods.rtl.logging.Mws13818Filter: Class com.webmethods.rtl.logging.Mws13818Filter removed

com.webmethods.rtl.util.msg.IRuntimeMessage: Class com.webmethods.rtl.util.msg.IRuntimeMessage removed

com.webmethods.rtl.util.msg.IRuntimeMessageCallback: Class
com.webmethods.rtl.util.msg.IRuntimeMessageCallback removed

com.webmethods.rtl.util.msg.IRuntimeMessageHook: Class
com.webmethods.rtl.util.msg.IRuntimeMessageHook removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeListeners: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeListeners removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeMessageListener: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeMessageListener removed

com.webmethods.rtl.util.obj.CyclicIterator: Class com.webmethods.rtl.util.obj.CyclicIterator removed

com.webmethods.rtl.util.obj.EmptyEnumeration: Class
com.webmethods.rtl.util.obj.EmptyEnumeration removed

com.webmethods.rtl.util.obj.EmptyIterator: Class com.webmethods.rtl.util.obj.EmptyIterator removed

com.webmethods.rtl.util.obj.FileClassLoader: Class com.webmethods.rtl.util.obj.FileClassLoader removed

com.webmethods.rtl.util.obj.IntMinMaxInfo: Class com.webmethods.rtl.util.obj.IntMinMaxInfo removed

com.webmethods.rtl.util.obj.IntStringMap: Class com.webmethods.rtl.util.obj.IntStringMap removed

com.webmethods.rtl.util.obj.IteratorTools: Class com.webmethods.rtl.util.obj.IteratorTools removed

com.webmethods.rtl.util.obj.PersistentMap: Class com.webmethods.rtl.util.obj.PersistentMap removed

com.webmethods.rtl.util.obj.PropertyGroup: Class com.webmethods.rtl.util.obj.PropertyGroup removed

com.webmethods.rtl.util.obj.PropertyGroups: Class com.webmethods.rtl.util.obj.PropertyGroups removed

Removed API/ Description

com.webmethods.rtl.util.obj.SortableArray: Class com.webmethods.rtl.util.obj.SortableArray removed

com.webmethods.rtl.util.thread.ReadWriteMutex: Class

com.webmethods.rtl.util.thread.ReadWriteMutex removed

com.softwareag.caf.controls.mwsx.PeoplePickerDialog: Removed field m_facets

com.softwareag.caf.controls.mwsx.PeopleSwapBox: Removed field m_facets

com.webmethods.caf.faces.component.behavior.BaseBehavior: Removed field m_for

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_allowDrag

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_cursor

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_move

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field
m_propagateEvent

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_allowDrop

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_handleDrop

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_hoverClass

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field
m_onDropSetValue

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_add

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field
m_allowDrag

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field
m_allowDrop

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_copy

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field
m_handleDrop

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field
m_hoverClass

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field
m_remove

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field
m_reorder

com.webmethods.caf.faces.component.behavior.DragToReorderColumnsBehavior: Removed field
m_storePreferences

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field

Removed API/ Description

m_resizeBottom

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeLeft

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeRight

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeTop

com.webmethods.caf.faces.component.behavior.DragToResizeColumnsBehavior: Removed field
m_storePreferences

com.webmethods.caf.faces.component.behavior.RaiseOnChangeBehavior: Removed field m_command

com.webmethods.caf.faces.component.behavior.SynchronizeValuesBehavior: Removed field m_with

com.webmethods.caf.faces.component.command.html.AsyncCommandButton: Removed field
m_refresh

com.webmethods.caf.faces.component.command.html.AsyncCommandIcon: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.AsyncCommandInterval: Removed field
m_interval

com.webmethods.caf.faces.component.command.html.AsyncCommandInterval: Removed field
m_waitUntilReloaded

com.webmethods.caf.faces.component.command.html.AsyncCommandLink: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.AsyncHiddenCommand: Removed field
m_refresh

com.webmethods.caf.faces.component.command.html.CommandForm: Removed field m_forms

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_alt

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_url

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field
m_urlMouseDown

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field
m_urlMouseover

com.webmethods.caf.faces.component.events.OpenAjaxScript: Removed field openAjaxTopic

com.webmethods.caf.faces.component.events.OpenAjaxScript: Removed field shouldSubscribe

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_converter

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_entriesProvider

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field
m_exportCharacterEncoding

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_exportFileName

Removed API/ Description

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_exportForceDownload
com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_feedProvider
com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_feedUrl
com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_for
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_height
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_initialAddress
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_initialCountry
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_key
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_latitude
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_longitude
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_type
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_width
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_zoom
com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_anchor
com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_offsetX
com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_offsetY
com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_type
com.webmethods.caf.faces.component.gmap.GMapGetCoordsScript: Removed field m_latitude
com.webmethods.caf.faces.component.gmap.GMapGetCoordsScript: Removed field m_longitude
com.webmethods.caf.faces.component.gmap.GMapKey: Removed field m_key
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_clickable
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_draggable
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_icon
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_iconSizeHeight
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_iconSizeWidth
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_initialAddress
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_initialCountry
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_latitude
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_longitude

Removed API/ Description

com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_selected
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_title
com.webmethods.caf.faces.component.gmap.GMarkerGroup: Removed field m_groupProvider
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_clickable
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_draggable
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_icon
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_iconSizeHeight
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_iconSizeWidth
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_initialAddress
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_initialCountry
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_latitude
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_longitude
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_multiple
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_title
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_multiple
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_title
com.webmethods.caf.faces.component.input.DateInput: Removed field m_pattern
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showMonthAndYearMenus
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showSeconds
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showTime
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showTimezone
com.webmethods.caf.faces.component.input.DateInput: Removed field m_timezone
com.webmethods.caf.faces.component.input.DateInput: Removed field m_valuePattern
com.webmethods.caf.faces.component.input.DateInput: Removed field m_yearMenuRange
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_futureRanges
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_label
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_layout
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_pastRanges
com.webmethods.caf.faces.component.logic.If: Removed field m_value

Removed API/ Description

com.webmethods.caf.faces.component.logic.Import: Removed field m_value
com.webmethods.caf.faces.component.logic.ImportTemplate: Removed field m_value
com.webmethods.caf.faces.component.logic.LoadResourceBundle: Removed field m_basename
com.webmethods.caf.faces.component.logic.LoadResourceBundle: Removed field m_var
com.webmethods.caf.faces.component.logic.VariableContainer: Removed field m_value
com.webmethods.caf.faces.component.logic.VariableContainer: Removed field m_var
com.webmethods.caf.faces.component.message.FormattedMessage: Removed field m_showDetail
com.webmethods.caf.faces.component.message.FormattedMessages: Removed field m_showDetail
com.webmethods.caf.faces.component.message.SpecificFormattedMessages: Removed field m_for
com.webmethods.caf.faces.component.message.SpecificMessages: Removed field m_for
com.webmethods.caf.faces.component.mws_ui.MwsResourceInclude: Removed field renderer
com.webmethods.caf.faces.component.mws_ui.MwsResourceInclude: Removed field uri
com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_appNavBean
com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_children
com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_facets
com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_appNavBean
com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_children
com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_facets
com.webmethods.caf.faces.component.output.Chart: Removed field m_barPadding
com.webmethods.caf.faces.component.output.Chart: Removed field m_barWidth
com.webmethods.caf.faces.component.output.Chart: Removed field m_color
com.webmethods.caf.faces.component.output.Chart: Removed field m_gridColor
com.webmethods.caf.faces.component.output.Chart: Removed field m_gridStyle
com.webmethods.caf.faces.component.output.Chart: Removed field m_height
com.webmethods.caf.faces.component.output.Chart: Removed field m_legendLocation
com.webmethods.caf.faces.component.output.Chart: Removed field m_legendStyleClass
com.webmethods.caf.faces.component.output.Chart: Removed field m_numberofGridLines
com.webmethods.caf.faces.component.output.Chart: Removed field m_padding
com.webmethods.caf.faces.component.output.Chart: Removed field m_rowColors

Removed API/ Description

com.webmethods.caf.faces.component.output.Chart: Removed field m_series

com.webmethods.caf.faces.component.output.Chart: Removed field m_showLegend

com.webmethods.caf.faces.component.output.Chart: Removed field m_type

com.webmethods.caf.faces.component.output.Chart: Removed field m_width

com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_color

com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_toolTip

com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_value

com.webmethods.caf.faces.component.output.ChartLabelColumn: Removed field m_label

com.webmethods.caf.faces.component.output.Custom: Removed field m_name

com.webmethods.caf.faces.component.output.Icon: Removed field m_converter

com.webmethods.caf.faces.component.output.Icon: Removed field m_label

com.webmethods.caf.faces.component.output.Icon: Removed field m_url

com.webmethods.caf.faces.component.output.Icon: Removed field m_urlMouseDown

com.webmethods.caf.faces.component.output.Icon: Removed field m_urlMouseover

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_accesskey

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_alt

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_dir

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_disabled

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_image

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_label

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_lang

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onblur

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onclick

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_ondblclick

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onfocus

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onkeydown

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseout

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseover

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseup

Removed API/ Description

com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_readonly
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_style
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_styleClass
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_tabindex
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_title
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_type
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_width
com.webmethods.caf.faces.component.output.html.HtmlLink: Removed field m_label
com.webmethods.caf.faces.component.output.refresh.RefreshButton: Removed field m_for
com.webmethods.caf.faces.component.output.refresh.RefreshIcon: Removed field m_for
com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_for
com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_interval
com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_waitUntilReloaded
com.webmethods.caf.faces.component.output.refresh.RefreshLink: Removed field m_for
com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_disableWhenHidden
com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_lazy
com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_refreshOnShow
com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_suppressInputs
com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_twoPass
com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_visible
com.webmethods.caf.faces.component.panel.OverlayPanel: Removed field m_hideEffect
com.webmethods.caf.faces.component.panel.OverlayPanel: Removed field m_showEffect
com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_click
com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_close
com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_closeOnClick
com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_forRightClick
com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hideEffect
com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hideEffectOptions

Removed API/ Description

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hover

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_position

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_showEffect

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_showEffectOptions

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_description

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_label

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_overflow

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_parentId

com.webmethods.caf.faces.component.panel.StackPanel: Removed field m_value

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_align

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_height

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_width

com.webmethods.caf.faces.component.panel.StaticRow: Removed field m_height

com.webmethods.caf.faces.component.panel.StaticRow: Removed field m_width

com.webmethods.caf.faces.component.search.BaseSearchControlHelper: Removed field fQuerySupplied

com.webmethods.caf.faces.component.search.BaseSearchControlHelper: Removed field fQuerySuppliedExpr

com.webmethods.caf.faces.component.search.SearchBar: Removed field m_facets

com.webmethods.caf.faces.component.select.FilterInput: Removed field m_labelText

com.webmethods.caf.faces.component.select.FilterInput: Removed field m_showGoButton

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_filter

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_other

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_sortByLabel

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_filter

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_other

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_sortByLabel

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_dir

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_disabled

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_lang

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_dir

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_disabled

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_lang

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_name

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onblur

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onchange

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onclick

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_ondblclick

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onfocus

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeydown

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeypress

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeyup

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmousedown

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmousemove

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseout

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseover

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseup

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_readonly

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_size

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_style

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_styleClass

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_tabindex

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_title

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_border

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_dir

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_disabled
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_disabledClass
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_enabledClass
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_lang
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_layout
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onblur
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onchange
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onclick
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_ondblclick
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onfocus
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeydown
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeypress
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeyup
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmousedown
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmousemove
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseout
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseover
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseup
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onselect
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_readonly
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_size
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_style
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_styleClass
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_tabindex
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onblur
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onchange
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onclick
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_ondblclick
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onfocus

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeydown
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeypress
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeyup
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmousedown
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmousemove
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseout
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseover
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseup
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onselect
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_readonly
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_size
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_style
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_styleClass
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_tabindex
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_title
com.webmethods.caf.faces.component.table.AddRow: Removed field m_addLastRowOnly
com.webmethods.caf.faces.component.table.AddRow: Removed field m_for
com.webmethods.caf.faces.component.table.AddRow: Removed field m_row
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_title
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_url
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_urlMouseDown
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_align
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_ascending
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_exportable
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_group
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_hidden
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_label
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_nowrap

Removed API/ Description

com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_optional
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_ordinal
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondary
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondaryEnd
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondaryStart
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_sort
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_valign
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_width
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_accesskey
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_disabled
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_multiple
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_tabindex
com.webmethods.caf.faces.component.table.DataPager: Removed field m_for
com.webmethods.caf.faces.component.table.DataPages: Removed field m_maxPages
com.webmethods.caf.faces.component.table.DataPages: Removed field m_showAlways
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_title
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_url
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_urlMouseDown
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_expandToEdges
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_nextIconUrl
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_nextText
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_prevIconUrl
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_prevText
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_showAlways
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_for
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_removeLastRow
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_row
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_title

Removed API/ Description

com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_url

com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_urlMouseDown

com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_urlMouseover

com.webmethods.caf.faces.component.table.SelectRow: Removed field m_accesskey

com.webmethods.caf.faces.component.table.SelectRow: Removed field m_disabled

com.webmethods.caf.faces.component.table.SelectRow: Removed field m_for

com.webmethods.caf.faces.component.table.SelectRow: Removed field m_multiple

com.webmethods.caf.faces.component.table.SelectRow: Removed field m_tabindex

com.webmethods.caf.faces.component.table.SelectRowCheckbox: Removed field m_children

com.webmethods.caf.faces.component.table.SelectRowCheckbox: Removed field m_facets

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferChunk

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferMax

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferMin

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_clientSideCache

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_flashOnChange

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_progressDelay

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_progressMsg

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_suppressInputs

com.webmethods.caf.faces.component.table.html.AsyncListbox: Removed field m_rowClasses

com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferChunk

com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferMax

com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferMin

com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_clientSideCache

com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_flashOnChange

com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_progressDelay

com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_progressMsg

com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_suppressInputs

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field dayVar

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field eventVar

Removed API/ Description

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_allDay

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_calendarEndDate

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_calendarStartDate

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_displayUnits

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_events

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_eventsSet

com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_initialDate

com.webmethods.caf.faces.component.table.html.DataList: Removed field m_marker

com.webmethods.caf.faces.component.table.html.DataList: Removed field m_selected

com.webmethods.caf.faces.component.table.html.DataList: Removed field m_selectedRowClass

com.webmethods.caf.faces.component.table.html.DataTable: Removed field createdToOriginalRowIds

com.webmethods.caf.faces.component.table.html.DataTable: Removed field filter

com.webmethods.caf.faces.component.table.html.DataTable: Removed field first

com.webmethods.caf.faces.component.table.html.DataTable: Removed field firstSet

com.webmethods.caf.faces.component.table.html.DataTable: Removed field originalToCreatedRowIds

com.webmethods.caf.faces.component.table.html.DataTable: Removed field var

com.webmethods.caf.faces.component.table.html.HtmlTableColumn: Removed field m_facets

com.webmethods.caf.faces.component.table.html.ListBox: Removed field m_rowClasses

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_children

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_facets

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_layout

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_size

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_url

com.webmethods.caf.faces.component.toggle.InitiateToggle: Removed field m_for

com.webmethods.caf.faces.component.toggle.OneWayToggle: Removed field m_for

com.webmethods.caf.faces.component.toggle.OneWayToggle: Removed field m_way

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_disabled

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_disabledClass

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field

Removed API/ Description

`m_enabledClass`

`com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle`: Removed field `m_width`

`com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggleCheckbox`: Removed field `m_checked`

`com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggleCheckbox`: Removed field `m_checkedWhenVisible`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_disabled`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_disabledClass`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_enabledClass`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_layout`

`com.webmethods.caf.faces.component.toggle.html.HtmlToggle`: Removed field `m_width`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_initialDepth`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_progressDelay`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_progressFlashOnComplete`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_progressMsg`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_refillDepth`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_refreshOnShow`

`com.webmethods.caf.faces.component.tree.AsyncTree`: Removed field `m_suppressInputs`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_collapseAllIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_collapseIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_expandAllIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_expandIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_leafIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_lineBottomIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_lineIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_lineNoneIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_lineTopIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_loadingIcon`

`com.webmethods.caf.faces.component.tree.BaseTreeControl`: Removed field `m_showSortLink`

`com.webmethods.caf.faces.view.BaseViewHandler`: Removed field `RE_FE_URL`

Removed API/ Description

com.webmethods.portal.faces.view.PortalViewHandler: Removed field RE_FE_URL

com.webmethods.portal.taglib.PortalIterationTagSupport: Removed field EMPTY_ITERATOR

Release 9.8

Added API

Description

In Java 8, a sort (Comparator) method was added to the java.util.List interface.

The My webMethods Server IListView interface extends the java.util.List interface, and has its own "sort" method with the same name but with a different method signature, which is not an allowed overwrite.

To resolve the issue, the "throws PortalException" declaration has been removed from the IListView#sort(Comparator) method, so that it is compatible with the method in the List interface.

10.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

MWS-RM-103-20181015

webMethods Optimize for Infrastructure 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Optimize for Infrastructure 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	5
6.0	Documentation Changes	11
7.0	Terminology Changes	14
8.0	Added, Removed, Deprecated, or Changed Items.....	14
9.0	Added, Removed, Deprecated, or Changed APIs	20
10.0	Copyright Information.....	20
11.0	Support.....	21

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

- webMethods Optimize for Infrastructure 10.3 monitors current and older supported versions of webMethods products. However, it requires Infrastructure Data Collector 10.3, Analytic Engine 10.3, Universal Messaging 10.3, and My webMethods Server 10.3 for execution.

- When using Broker Basic Authentication, do not set ACL on the Analysis client group.

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- WID-1540
You cannot install Infrastructure Data Collector as a Windows service by applying a Command Central template.
There is currently no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- webMethods Broker is deprecated for use beginning with webMethods 10.2. If you are starting development using webMethods 10.3, you should use webMethods Universal Messaging instead of webMethods Broker. If you are upgrading to webMethods 10.3, you should consider migrating to Universal Messaging. If you choose to continue to use webMethods Broker, you will still be fully supported, but only until the announced end-of-life dates for webMethods Broker.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- OPT_9.8_Fix22
- WID_9.9_Fix19
- WID_9.10_Fix13
- WID_9.12_Fix11
- OPT_10.0_Fix6
- OPT_10.1_Fix5
- CMP_9.8_Fix5

- CMP_9.9_Fix4
- CMP_9.10_Fix2
- CMP_9.12_Fix3
- CMP_10.0_Fix2
- CMP_10.1_Fix1

Release 10.2

- OPT_9.8_Fix22
- WID_9.9_Fix19
- OPT_9.10_Fix13
- OPT_9.12_Fix12
- OPT_10.0_Fix6
- OPT_10.1_Fix2
- CMP_9.8_Fix5
- CMP_9.9_Fix3
- CMP_9.10_Fix2
- CMP_9.12_Fix3
- CMP_10.0_Fix2

Release 10.1

- OPT_9.0_SP1_Fix16
- OPT_9.5_SP1_Fix16
- OPT_9.6_SP1_Fix12
- OPT_9.7_Fix20
- OPT_9.8_Fix19
- OPT_9.9_Fix15
- OPT_9.10_Fix7

- OPT_9.12_Fix7
- OPT_10.0_Fix4
- CMP_9.12_Fix1

Release 10.0

- OPT_9.0_SP1_Fix15
- OPT_9.5_SP1_Fix14
- OPT_9.6_SP1_Fix10
- OPT_9.7_Fix16
- OPT_9.8_Fix15
- OPT_9.9_Fix12
- OPT_9.10_Fix7
- CMP_9.12_Fix1

Release 9.12

- OPT_9.0_SP1_Fix14
- OPT_9.5_SP1_Fix13
- OPT_9.6_SP1_Fix9
- OPT_9.7_Fix13
- OPT_9.8_Fix11
- OPT_9.9_Fix9
- OPT_9.10_Fix4
- CMP_9.10_Fix1

Release 9.10

- OPT_9.0_SP1_Fix12
- OPT_9.5_SP1_Fix9
- OPT_9.6_SP1_Fix7

- OPT_9.7_Fix7
- OPT_9.8_Fix5
- CMP_9.8_Fix2
- OPT_9.9_Fix2
- CMP_9.9_Fix1

Release 9.9

- OPT_9.0_SP1_Fix9
- OPT_9.5_SP1_Fix7
- OPT_9.6_SP1_Fix4
- OPT_9.7_Fix5
- OPT_9.8_Fix3
- CMP_9.8_Fix1

Release 9.8

- OPT_8.2_SP1_Fix14
- OPT_9.0_SP1_Fix7
- OPT_9.5_SP1_Fix5
- OPT_9.6_SP1_Fix2
- OPT_9.7_Fix2

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- WID-1700
Infrastructure Data Collector does not support migration to the same version.

The issue is resolved.

- WID-1631
The Infrastructure Data Collector server log might contain the following error:
"StandardWrapper.Throwablejava.lang.IllegalStateException: InjectionManagerFactory not found."
The issue is resolved.
- WID-1672
The command-line help of the Infrastructure Data Collector migration utility is not consistent.
The issue is resolved.
- WID-1666
Infrastructure Data Collector stores sensitive user information in the log files.
The issue is resolved.
- WID-1629
Infrastructure Data Collector fails to start when using Java Service Wrapper version 3.5.29.
The issue is resolved.
- WID-1625
The Infrastructure Data Collector (IDC) process might crash while monitoring Apama and Terracotta servers.
When Infrastructure Data Collector monitors Apama and Terracotta servers, the IDC process might have very high memory usage and the process might crash. The issue occurs because of an out of memory exception.
The issue is resolved.
- WID-1574
Infrastructure Data Collector incorrectly emits diagnostic events for components that are not selected for monitoring. The issue occurs for components of discovered assets.
The issue is resolved.
- CMP-92
On the KPI Instance Details page in My webMethods, the reading of the OutstandingEvents KPI might be incorrect.
Infrastructure Data Collector might fail to properly capture the outstanding events information for Universal Messaging named objects. As a result, the KPI Instance Details page might display an incorrect value for the OutstandingEvents KPI.
The issue is resolved.

Release 10.2

- WID-1596
Optimize might fail to monitor Integration Server clusters.
Infrastructure Data Collector might fail to monitor an Integration Server cluster. The issue occurs when all nodes from the cluster were discovered using a non-primary port.
The issue is resolved.

- **WID-1590**
When Infrastructure Data Collector monitors a Terracotta Server, the BAM_EVENT_TMP and BAM_EVENT_TMP_ATTR tables might become very large. The issue occurs when the Terracotta Server is down.
The issue is resolved.
- **WID-1573**
The Optimize Monitored Components page might not display an Integration Server (IS) package.
The Monitored Components page in My webMethods might not display a discovered IS Package in the list of monitored components. As a result, you might not be able to monitor the IS package. The issue occurs when an IS package does not contain a service.
The issue is resolved.
- **WID-1554**
Infrastructure Data Collector might hang during a discovery process.
Infrastructure Data Collector might hang in "Running" status during a discovery process if uncaught throwable errors occur during the process.
The issue is resolved.
- **WID-1539**
Optimize does not display a warning when you delete an asset of type "JMX Configuration".
In the Discovered Assets panel on the Assets page in My webMethods, when you select an asset of type "JMX Configuration" and click Delete, Optimize does not display a warning message that all associated monitored components and associated KPIs will be deleted from the system.
The issue is resolved.
- **WID-1486**
When Infrastructure Data Collector monitors a Universal Messaging realm, and the realm is offline, the wrapper log starts filling with the following exception message:
"RealmUnreachableException: Realm is currently not reachable".
The issue is resolved.
- **CMP-73**
Platform Manager might hang while monitoring a Universal Messaging realm. The issue occurs when the Universal Messaging realm is configured incorrectly, or when the Universal Messaging realm is connected to a remote Universal Messaging realm, which is offline.
The issue is resolved.
- **CMP-56**
When Platform Manager is configured to monitor Universal Messaging (UM), the UM log might repeatedly log the same error message.
When Platform Manager attempts connecting to a Universal Messaging interface using the UM plug-in for Platform Manager, the following error might be logged repeatedly in the nirvana.log file:
"not authorised to connect on interface".
The issue occurs when the Allow Client Connections option is unchecked for the Universal

Messaging interface to which Platform Manager connects.
The issue is resolved.

Release 10.1

- JBP-6470
Optimize fails to create dimension instances for MashZone NextGen Catalina Server.
The issue is resolved.
- OBE-9260
The size of the Analytic Engine log file might grow rapidly.
Sometimes when you start Analytic Engine after a fresh installation, the Analytic Engine log file grows rapidly. The issue occurs when the Universal Messaging server that is configured for Analytic Engine did not start properly.
The issue is resolved.

Release 10.0

- WID-1474
Infrastructure Data Collector fails to monitor Integration Server assets that are configured to use a secure connection (SSL). As a result, no readings are generated for monitored Integration Server KPIs.
The issue is resolved.
- OBE-8414
When you change the display name of a measure attribute, the KPIs that are set for this measure stop functioning.
To work around this issue, set the display name back to the original display name.
The issue is resolved.
- OBE-8932
Back-populating rules in Optimize might fail.
In some cases, when you click the Generate Rule Violations button on the Rule List page, the initiated rule back-population operation fails. Although no error message appears, the status of the back-population job in the Job Audit page, is "Failed".
The issue is resolved.

Release 9.10

- WID-1221
The Asset page fails to display status "Refused" for Integration Server assets.
In My webMethods Server, on the Applications > Administration > Analytics > Infrastructure Components > Assets page, when you edit the connection parameters for an Integration Server asset and you accidentally enter an invalid password, the status of the asset is not updated to "Refused" but remains "Accepted," even though no new KPI readings are collected from this asset

because of the invalid password.
This issue has been resolved.

- OBE-7017
The Analytics Overview page continues to display KPI instances for deleted assets.
In My webMethods Server, after you delete an asset from the Applications > Administration > Analytics > Infrastructure Components > Assets page and you go to the Applications > Monitoring > System-Wide > Analytics Overview page, you can still see KPI data for the removed asset.
This issue has been resolved.
- OBE-7145
Data remains unprocessed in the Universal Messaging JMS queues when an Analytic Engine node is down.
When the Analytic Engine is running in a clustered environment, and some of the nodes are down, the data that is pushed to the respective Universal Messaging queue is not processed until the nodes come back up again.
This issue has been resolved.
- OBE-7597
On the KPI Instance Detail page, when you plot KPIs with collection intervals of 2, 4, or 8 hours, the graph displays incorrect times for reading values.
In My webMethods Server, when you plot KPIs on the KPI Instance Detail page with collection intervals of 2, 4, or 8 hours, the KPI reading values that are displayed on the graph are plotted at incorrect times.
This issue has been resolved.
- OBE-7536
The Advanced search tab on the Problems page does not return correct results.
In My webMethods Server, on the Applications > Monitoring > System-Wide > Problems page, when you use the Advanced search tab to filter problems setting the "Field Name" to "Duration" and selecting "Greater Than" or "Less Than" as operators, your search might be misleading, since they also contain problems with duration that is equal to the selected value.
This issue has been resolved. The "Greater Than" and "Less Than" operators no longer return problems with Duration equal to the selected filter Value. Also, the following operators have been added when filtering by duration:
"Greater Than or Equal To" and "Less Than or Equal To"
- OBE-7511
An error prevents you from editing or copying an instant rule with no user specified.
In My webMethods Server, on the KPI Instance Detail page, when you create an instant rule without specifying a user for the Send Alert To drop-down list, and then you navigate to the Applications > Administration > Analytics > Rules > Rule List Page, you cannot edit or copy the rule. The following error is displayed in the Alerts panel on the Add/Edit/Copy Rule page:
User is unknown or email address is undefined.
This issue has been resolved.

- OBE-7990
The Define Environments page allows you to create an environment with no name.
In My webMethods Server, on the Administration > System-Wide > Environments > Define Environment page, when you click Add Environment, you can save your environment with no value for Environment Name.
This issue has been resolved.
- OBE-7491
The KPI Instance Detail page incorrectly aggregates KPIs of type Sum or Count to the beginning of the hour.
In My webMethods Server, on the KPI Instance Detail page, when you plot KPIs of type Sum or Count, the KPI data values are incorrectly aggregated to the beginning of the hour, instead of the end.
This issue has been resolved.
- OBE-7485
The Select All icon on the Database Pool Configuration page does not select all listed pools.
In My webMethods Server, on the Applications > Administration > System-Wide > Environments > Database Pool Configuration, when you click the Select All icon, not all listed pools are selected.
This issue has been resolved.

Release 9.9

- WID-1189
IS Terracotta Cluster component fails to collect readings.
This issue is now resolved.
- WID-1196
Modifying the MWS discovery credentials to an invalid user/password should result in a discovery failure.
This issue is now resolved.

Release 9.8

- WID-1075/WID-1116
Service request counts for Integration Server count KPI may show negative values.
The Infrastructure Data Collector Integration Server Is Service long Count KPI may return negative values.
This issue has been resolved.
- OBE-6734
Central Configuration - Define Environment allows an empty environment to be created.
Central Configuration - Define Environment allows an empty environment to be created if a user presses the ENTER key before entering any value in the name field.
This issue has been resolved.

- OBE-6282
KPI Instance Detail graph is incorrectly plotting data points where a given data point is comprised of multiple events with the exact timestamp down to the millisecond.
This issue has been resolved.
- OBE-4182
Threshold rule expressions might fail if the underlying event map is renamed.
If the event map referenced by with a threshold rule expression was renamed, in some cases the threshold rule evaluation will fail.
This issue has been resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- An HTML version of the documentation for webMethods Optimize 10.3 has been added and is now available on the documentation site under the name *webMethods Optimize Help*. *webMethods Optimize Help* includes the information from the *webMethods Optimize User's Guide*, *Administering webMethods Optimize*, and *Configuring BAM* guides.
- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about Integration Server Native Messaging KPI definitions and Integration Server JMS Messaging KPI definitions.
- The “Integration between Optimize and PPM” chapter of the *Administering webMethods Optimize* guide has been removed.

Release 10.1

- The “Managing webMethods Optimize Environments” chapter of the *Configuring BAM* guide has been updated with information about configuring JMX resource module settings.
- The “Discovery Assets and Monitoring Components” chapter of the *Administering webMethods Optimize* guide has been updated with information about adding JMX assets for discovery.
- The “Discovery Assets and Monitoring Components” chapter of the *Administering webMethods Optimize* guide has been updated with information about setting the monitoring of MashZone NextGen Server components (10.1 release only).

- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about System Component Monitoring for Integration Server KPI definitions and System Component Monitoring for Infrastructure Data Collector KPI definitions.
- The information about the Integration Server KPI definitions and the Universal Messaging cluster KPI definitions in the “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated.
- Information about the Integration Server Long Running Thread rule has been added to the “Built-In Rules” chapter of the *Administering webMethods Optimize* guide.

Release 10.0

- The “Using Command Central to Manage Optimize” chapter has been moved from the *Administering webMethods Optimize* guide to the *Configuring BAM* guide. The chapter has been updated with procedures for configuring Optimize through Command Central.
- The “Managing webMethods Optimize Environments” chapter of the *Configuring BAM* guide has been updated with information about configuring Digital Event Services resource module settings.
- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about Digital Event Services KPI definitions.
- The information about the Universal Messaging KPI definitions in the “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated.
- The “Configuring the SNMP Data Collector” chapter of the *Administering webMethods Optimize* guide has been updated with information about monitoring memory consumption and processor load.
- The “Discovery Assets and Monitoring Components” chapter of the *Administering webMethods Optimize* guide has been updated with information about adding Digital Event Services assets for discovery.
- The “Discovery Assets and Monitoring Components” chapter of the *Administering webMethods Optimize* guide has been updated with information about setting a root context for My webMethods Server assets.
- The information about the Infrastructure Data Collector Queue Size KPI definitions in the “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated.

Release 9.12

- A new “Using Command Central to Manage Optimize” chapter has been added to the

Administering webMethods Optimize guide. This chapter is moved from the *Software AG Command Central Help*. The chapter describes the currently supported operations in Command Central for managing Optimize.

- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about KPI definitions for Event Routing.
- The “Built-In Rules” chapter of the *Administering webMethods Optimize* guide has been updated with information about Event Routing rules.
- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about KPI definitions for Universal Messaging named objects.
- The “Adding Terracotta Server and Terracotta Server Array Assets for Discovery” section of the *Administering webMethods Optimize* guide has been updated with information about monitoring Terracotta Server and Terracotta Server Array assets over HTTPS.
- The “The Assets Page” section of the *Administering webMethods Optimize* guide has been updated with information about monitoring My webMethods Server with a root context.
- The “Managing webMethods Optimize Environments” chapter of the *Configuring BAM* guide has been updated with information about configuring in-process event publication.

Release 9.10

- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about KPI definitions for MashZone NextGen, UM Cluster, and Presto delta KPIs.
- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide now contains information about newly added diagnostic KPIs about the following component types: InfrastructureDataCollector, ApamaCorrelator, BrokerServer, SNMP, IntergrationServer, ISCluster, MyWebMethodsServer, Presto, Universal Messaging Realm, and TerracottaConnection.
- The “Adding an Asset” section of the *Administering webMethods Optimize* guide now contains information about adding Universal Messaging Cluster and MashZone NextGen assets.

Release 9.9

The *Administering webMethods Optimize* guide has been revised as follows:

- The “Monitored KPI Definitions” chapter has been updated with information about KPI definitions for Apama, Presto Catalina, Presto UM, IS File Polling, and Terracotta monitoring.
- The “Adding an Asset” section of the guide now contains information about adding Apama, Presto, Terracotta, SNMP3, and Terracotta assets.

- The “Configuring and Using the Infrastructure Data Collector” section of the guide now contains information about configuring Infrastructure Data Collector for clustering.
- The “Configuring and Using the Infrastructure Data Collector” section also contains information about changing the Infrastructure Data Collector ports.
- The “Configuring Event Routing Settings for Optimize” section in this guide has also been updated with details regarding the setup of Software AG Event Routing in your Optimize system.

The *webMethods Optimize User’s Guide* now includes information about using the “Investigate” button to jump to Process Performance Manager and further investigate process-related intrinsic data from Optimize. You will also find information about creating an alert in Optimize from the PPM user interface.

The *Software AG Command Central* help contains information about administering the Optimize Analytic Engine using the Command Central user interface.

Release 9.8

- Universal Messaging Delta KPIs - Appendix A “Monitored KPI Definitions” of the “*Administering Optimize*” PDF publication now contains the “Universal Messaging KPI Definitions” section that lists and explains KPIs for monitoring Universal Messaging Servers has been updated with additional KPIs.
- Presto KPIs - Appendix A “Monitored KPI Definitions” of the “*Administering Optimize*” PDF publication now contains the “Presto KPI Definitions” section that lists and explains KPIs for monitoring Universal Messaging Servers has been updated with additional KPIs.
- Terracotta KPIs - Appendix A “Monitored KPI Definitions” of the “*Administering Optimize*” PDF publication now contains the “Terracotta KPI Definitions” section that lists and explains KPIs for monitoring Universal Messaging Servers has been updated with additional KPIs.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Integration Server “IS JMS Messaging” Component	KPIs introduced as part of this component: boolean ObjectStatus: Whether a connection alias exists int CSQCount: The number of Client Side Queue messages. boolean ConnectionAliasStatus: The status of the connection alias.
Integration Server “IS Native Messaging” Component	KPIs introduced as part of this component: boolean ObjectStatus: Whether a connection alias exists int CSQCount: The number of Client Side Queue messages. boolean ConnectionAliasStatus: The status of the connection alias.
Integration Server “IS Cache Manager” Component	KPIs introduced as part of this component: boolean ObjectStatus: Whether the Cache Manager exists. int CacheCount :The number of caches in a Cache Manager. boolean TSAConnectinStatus Terracotta Server Array connection status of a Cache Manager boolean CacheManagerConnectionStatus The connection status of the Cache Manager from Integration Server

Changed Item	Description
Add Components button	In My webMethods > Edit Component Type page, the Add Components button is now renamed to Enable Components.
Delete button	In My webMethods > Edit Component Type page, the Delete button is now renamed to Disable Components.

Release 10.1

Added Item	Description
JMX monitoring	The provider can connect to a JMX service and retrieve a set of mbeans' information. The user defines the mbean set in an mbean type filter. Different mbean sets require different filters (names).
Infrastructure Data Collector JMX	<p>The System Component discovery for Infrastructure Data Collector happens automatically when Infrastructure Data Collector starts. No input is needed from the user.</p> <p>The monitoring is using Infrastructure Data Collector JMX agent. The JMX port is retrieved through the Infrastructure Data Collector bundle context.</p>
Integration Server JMX	<p>The System Component discovery for Integration Server happens automatically with the Integration Server discovery. No additional input is needed from the user.</p> <p>The monitoring is using Integration Server JMX agent. The JMX port is retrieved through the WmISExtDC package.</p>
Integration Server "Long Running Threads" KPI	This KPI counts long-running service threads in Integration Server. By default it counts service threads that are running for more than 60000 milliseconds.
UM KPI additions	<p>boolean HasQuorum - Indicates if the cluster can form a quorum.</p> <p>boolean IsOnline - Indicates if the cluster is online.</p>

Added Item	Description
MashZone NextGen Server 10.1 monitoring	<p>The following lines must be added to the wrapper.conf file.</p> <pre> wrapper.java.additional.200=- Dcom.sun.management.jmxremote #wrapper.java.additional.201=- Dorg.tanukisoftwares.wrapper.WrapperManager.m bean=TRUE #wrapper.java.additional.202=- Dorg.tanukisoftwares.wrapper.WrapperManager.m bean.testing=TRUE wrapper.java.additional.203=- Dcom.sun.management.jmxremote.port=9088 wrapper.java.additional.204=- Dcom.sun.management.jmxremote.authenticate=fa lse wrapper.java.additional.205=- Dcom.sun.management.jmxremote.ssl=false </pre>

Release 10.0

Added Item	Description
Digital Event Services	Monitoring DES events.
SNMP provide sum average functions	A mechanism to do a sum or average across multiple PDUs. This is necessary for calculation of CPU or memory utilization when the values are represented per CPU or per running application.
Universal Messaging detects stale queues	Monitoring Universal Messaging queues capability is enhanced to detect the age of messages in the queue. When a message has been on a queue longer than a specified amount of time, a report or an alert can be sent.
Infrastructure Data Collector queue sizes	Monitoring Universal Messaging queue sizes which are used by Infrastructure Data Collector.
Optimize is configurable through Command Central.	You can now configure Optimize for Process and Optimize for Infrastructure through Command Central.

Added Item	Description
Support for MWS Root Context	The Optimize for Process and Optimize for Infrastructure user interfaces now support the MWS Root Context capability.

Release 9.12

Added Item	Description
EDA	Event routing framework is embedded in products like IS, Optimize, MWS etc. Monitoring of EDA to these products will be through a JMX port
MWS root context	Monitoring MWS with root context defined
Universal Messaging named objects	Monitoring of UM name objects
Terracotta HTTPS	Monitoring of Terracotta over HTTPS

Release 9.10

Added Item	Description
UM Cluster Monitoring	Monitoring of UM Cluster Nodes
Ability to delete Key Performance Indicators by date and name	You are now able to delete KPIs by date and name.

Changed Item	Description
Presto 9.10 only	Name changed to MashZone Next Gen

Release 9.9

Added Item	Description
Presto Catalina JMX	Presto Catalina monitoring
Presto UM	Presto UM monitoring
Apama	Apama monitoring
Integration Server File Polling	File Polling port monitoring
MWS HTTPS	MWS running HTTPS port enabled. Monitoring secure port.
SNMP v3 Support	SNMP v3 monitoring

Added Item	Description
Changing Infrastructure Data Collector ports after configuration	The properties file and location of the Infrastructure Data Collector port assigned during installation has been changed. See documentation on how to modify the Infrastructure Data Collector port after startup/configuration has completed.
Aesthetic enhancements for Process Dashboards	Aesthetic improvements have been made to the Process dashboards including: Principle picker now uses enter key to submit form when entering keyword characters, general control alignment and styling
Command Central integration for Analytic Engine	User can now start, stop, restart and receive the status for the Analytic Engine using Command Central. This includes configuring event routing for the Analytic Engine
Performance and scalability improvements	<ul style="list-style-type: none"> ▪ 100 times improvement in clustered Analytic Engine throughput performance ▪ 2 times faster Analytic Engine startup ▪ 500 percent increase in dimensional handling throughput ▪ 30% throughput improvement in State engine

Release 9.8

Added Item	Description
Universal Messaging Delta KPI's	New Universal Messaging Delta KPI's. The difference between the last 2 reading values of the target KPI.
Presto Monitoring	Presto Monitoring.
Terracotta Monitoring	Enhanced Terracotta monitoring to include Cache, Cache Manager, TSA, TSA Server, Terracotta Connection. Discover TMS by Group Name or discover Direct by TSA Name.
Intrinsic Stage Metrics available in the UI	The intrinsic metrics associated with Stages are now available for use in the Analytics Overview.

Added Item	Description
New KPI type - Counter	A new KPI type, called Counter, has been added. This KPI counts the number of data points received for a specific fact over a fixed aggregation period.
New Rule Violation/Resolution EDA event	Optimize now is able to emit Rule Violation/Resolution EDA events

Removed Item	Replacement, if any
Terracotta Monitoring	Removed TMC Connection for Terracotta Server.

Deprecated Item	Replacement, if any
Removal of BAM_AGG_... database tables	The BAM_AGG_... database tables usage is being removed from future releases. These tables are currently used for Optimize Only UI support and will no longer be used.

9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

10.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of

the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

OPTINF-RM-103-20181015

webMethods Optimize for Process 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Optimize for Process 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find the suite-related information listed below.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	1
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	5
6.0	Documentation Changes	9
7.0	Terminology Changes	11
8.0	Added, Removed, Deprecated, or Changed Items.....	12
9.0	Added, Removed, Deprecated, or Changed APIs	16
10.0	Copyright Information.....	17
11.0	Support.....	17

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

- webMethods Optimize for Process 10.3 is compatible for execution only with the latest 10.3 versions of other webMethods products.
- When using Broker Basic Authentication, do not set ACL on the Analysis client group.

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- OBE-9738
In Optimize, editing a standardized error type might fail.
In My webMethods, on the Instance Analytics tab in the Edit Process page, when you click the Edit Error Type icon for a standardized error type, the Edit Error Type dialog might not appear. As a result, you cannot edit the standardized error type. The issue occurs when you attempt editing a standardized error type more than once without leaving the Edit Process page between the attempts.
To work around this issue, navigate to another page and then open the Edit Process page again.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- webMethods Broker is deprecated for use beginning with webMethods 10.2. If you are starting development using webMethods 10.3, you should use webMethods Universal Messaging instead of webMethods Broker. If you are upgrading to webMethods 10.3, you should consider migrating to Universal Messaging. If you choose to continue to use webMethods Broker, you will still be fully supported, but only until the announced end-of-life dates for webMethods Broker.
- The integration between Optimize and ARIS Process Performance Manager (PPM) has been removed.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- OPT_9.5_SP1_Fix19
- OPT_9.7_Fix22
- OPT_9.9_Fix22
- OPT_9.10_Fix15

- OPT_9.12_Fix16
- OPT_10.1_Fix5
- OPT_10.2_Fix2

Release 10.2

- OPT_9.8_Fix22
- OPT_9.9_Fix18
- OPT_9.10_Fix13
- OPT_9.12_Fix12
- OPT_10.1_Fix2

Release 10.1

- OPT_9.0_SP1_Fix16
- OPT_9.5_SP1_Fix17
- OPT_9.6_SP1_Fix12
- OPT_9.7_Fix20
- OPT_9.8_Fix19
- OPT_9.9_Fix15
- OPT_9.10_Fix10
- OPT_9.12_Fix7
- OPT_10.0_Fix4

Release 10.0

- OPT_9.0_SP1_Fix15
- OPT_9.5_SP1_Fix14
- OPT_9.6_SP1_Fix10
- OPT_9.7_Fix16
- OPT_9.8_Fix15

- OPT_9.9_Fix12
- OPT_9.10_Fix7
- OPT_9.12_Fix4

Release 9.12

- OPT_9.0_SP1_Fix14
- OPT_9.5_SP1_Fix13
- OPT_9.6_SP1_Fix9
- OPT_9.7_Fix13
- OPT_9.8_Fix11
- OPT_9.9_Fix9
- OPT_9.10_Fix4

Release 9.10

- OPT_9.0_SP1_Fix12
- OPT_9.5_SP1_Fix9
- OPT_9.6_SP1_Fix7
- OPT_9.7_Fix7
- OPT_9.8_Fix6
- OPT_9.9_Fix2

Release 9.9

- OPT_9.0_SP1_Fix9
- OPT_9.5_SP1_Fix7
- OPT_9.6_SP1_Fix4
- OPT_9.7_Fix5
- OPT_9.8_Fix3

Release 9.8

- OPT_8.2_SP1_Fix14
- OPT_9.0_SP1_Fix7
- OPT_9.5_SP1_Fix5
- OPT_9.6_SP1_Fix2
- OPT_9.7_Fix2

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.2

- OBE-10176
Optimize might display an incorrect state of a process stage.
Optimize might incorrectly display an uncompleted stage as completed. The issue occurs when the end milestone step of a stage that comes from Dynamic Business Orchestrator is in a status that is not recognized by Optimize.
The issue is resolved.

Release 10.1

- OBE-9260
The size of the Analytic Engine log file might grow rapidly.
Sometimes when you start Analytic Engine after a fresh installation, the Analytic Engine log file grows rapidly. The issue occurs when the Universal Messaging server that is configured for Analytic Engine did not start properly.
The issue is resolved.

Release 10.0

- OBE-8414
When you change the display name of a measure attribute, the KPIs that are set for this measure stop functioning.
To work around this issue, set the display name back to the original display name.
The issue is resolved.

- OBE-8868
Optimize fails to extract large numbers of assets.
In the Asset Extraction page in Optimize, if a large number of assets is available and you select all the assets and try to export them, the page freezes.
The issue is resolved.
- OBE-8932
Back-populating rules in Optimize might fail.
In some cases, when you click the Generate Rule Violations button on the Rule List page, the initiated rule back-population operation fails. Although no error message appears, the status of the back-population job in the Job Audit page is "Failed".
The issue is resolved.

Release 9.12

- OBE-8602
In some cases, the Process Dashboards page in Optimize does not load.
In the Overview tab of the Process Dashboards page in Optimize, a "Loading Process models" message appears, indefinitely but the page does not load. The issue occurs when no process models that are enabled for analysis are deployed in the environment.
The issue is resolved.

Release 9.10

- OBE-7145
Data remains unprocessed in the Universal Messaging JMS queues when an Analytic Engine node is down.
When the Analytic Engine is running in a clustered environment, and some of the nodes are down, the data that is pushed to the respective Universal Messaging queue is not processed until the nodes come back up again.
This issue has been resolved.
- OBE-7597
On the KPI Instance Detail page, when you plot KPIs with collection intervals of 2, 4, or 8 hours, the graph displays incorrect times for reading values.
In My webMethods Server, when you plot KPIs on the KPI Instance Detail page with collection intervals of 2, 4, or 8 hours, the KPI reading values that are displayed on the graph are plotted at incorrect times.
This issue has been resolved.
- OBE-7888
Loading faulty KPI instances may lead to a NullPointerException when the Optimize Analytic Engine is restarted.
When a KPI definition contains a hierarchy with one or multiple dimensions, and Analytic Engine processes a related reading where some of the data for the dimensions is null, a faulty KPI instance

is created. As a result, when the Analytic Engine is restarted afterwards, a NullPointerException is observed.

This issue has been resolved.

- OBE-7518
The Delete button on the Business Processes section in the Data Level Security tab for a role becomes inactive when you move between table pages.
In My webMethods Server, on the Applications > Administration > System-Wide > User Management > Roles page, when you edit a role and go to the Business Process section in the Data Level Security tab, the Delete button becomes inactive when you move between table pages.
This issue has been resolved.
- OBE-7511
An error prevents you from editing or copying an instant rule with no user specified.
In My webMethods Server, on the KPI Instance Detail page, when you create an instant rule without specifying a user for the Send Alert To drop-down list, and then you navigate to the Applications > Administration > Analytics > Rules > Rule List Page, you cannot edit or copy the rule. The following error is displayed in the Alerts panel on the Add/Edit/Copy Rule page: User is unknown or email address is undefined.
This issue has been resolved.
- OBE-7990
The Define Environments page allows you to create an environment with no name.
In My webMethods Server, on the Administration > System-Wide > Environments > Define Environment page, when you click Add Environment, you can save your environment with no value for Environment Name.
This issue has been resolved.
- OBE-7536
The Advanced search tab on the Problems page does not return correct results.
In My webMethods Server, on the Applications > Monitoring > System-Wide > Problems page, when you use the Advanced search tab to filter problems setting the "Field Name" to "Duration" and selecting "Greater Than" or "Less Than" as operators, your search might be misleading, since they also contain problems with duration that is equal to the selected value.
This issue has been resolved. The "Greater Than" and "Less Than" operators no longer return problems with Duration equal to the selected filter Value. Also, the following operators have been added when filtering by duration:
"Greater Than or Equal To" and "Less Than or Equal To"
- OBE-7750
The swarm line density and colors are displayed incorrectly on the Process Diagram panel of the Process Analytics page.
In My webMethods Server, on the Applications > Monitoring > Business > Process Analytics page, the Process Diagram panel displays swarm lines with incorrect density and colors.
This issue has been resolved.
- OBE-7491

The KPI Instance Detail page incorrectly aggregates KPIs of type Sum or Count to the beginning of the hour.

In My webMethods Server, on the KPI Instance Detail page, when you plot KPIs of type Sum or Count, the KPI data values are incorrectly aggregated to the beginning of the hour, instead of the end.

This issue has been resolved.

- OBE-7485

The Select All icon on the Database Pool Configuration page does not select all listed pools.

In My webMethods Server, on the Applications > Administration > System-Wide > Environments > Database Pool Configuration, when you click the Select All icon, not all listed pools are selected.

This issue has been resolved.

- OBE-7558

Email notifications at the Process Dashboards panel fail to display the end time of a stage instance.

On the Stage Instances tab of the Process Dashboards panel, when you select a stage instance and you click the Forward as Email link, the email received mistakenly displays the Stage End Date as "n/a", instead of showing the value, displayed on the Stage Instances panel.

This issue has been resolved.

Release 9.8

- OBE-6748

The Process dashboards should not show processes that are not set for analysis.

The process selector within the Process Dashboards is allowing users to select processes set for analysis as well as processes that are not set for analysis. The user should only be shown processes set for analysis.

This issue has been resolved.

- OBE-6734

Central Configuration - Define Environment allows an empty environment to be created.

Central Configuration - Define Environment allows an empty environment to be created if a user presses the ENTER key before entering any value in the name field.

This issue has been resolved.

- OBE-6282

KPI Instance Detail graph is incorrectly plotting data points where a given data point is comprised of multiple events with the exact timestamp down to the millisecond.

This issue has been resolved.

- OBE-4182

Threshold rule expressions might fail if the underlying event map is renamed.

If the event map referenced by a threshold rule expression was renamed, in some cases the threshold rule evaluation will fail.

This issue has been resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- An HTML version of the documentation for webMethods Optimize 10.3 has been added and is now available on the documentation site under the name *webMethods Optimize Help*. *webMethods Optimize Help* includes the information from the *webMethods Optimize User's Guide*, *Administering webMethods Optimize*, and *Configuring BAM* guides.
- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about Integration Server Native Messaging KPI definitions and Integration Server JMS Messaging KPI definitions.
- The “Integration between Optimize and PPM” chapter of the *Administering webMethods Optimize* guide has been removed.

Release 10.1

- The “Managing webMethods Optimize Environments” chapter of the *Configuring BAM* guide has been updated with information about configuring JMX resource module settings.
- The “Discovery Assets and Monitoring Components” chapter of the *Administering webMethods Optimize* guide has been updated with information about adding JMX assets for discovery.
- The “Discovery Assets and Monitoring Components” chapter of the *Administering webMethods Optimize* guide has been updated with information about setting the monitoring of MashZone NextGen Server components (10.1 release only).
- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about System Component Monitoring for Integration Server KPI definitions and System Component Monitoring for Infrastructure Data Collector KPI definitions.
- The information about the Integration Server KPI definitions and the Universal Messaging cluster KPI definitions in the “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated.
- Information about the Integration Server Long Running Thread rule has been added to the “Built-In Rules” chapter of the *Administering webMethods Optimize* guide.

Release 10.0

- The “Using Command Central to Manage Optimize” chapter has been moved from the *Administering webMethods Optimize* guide to the *Configuring BAM* guide. The chapter has been updated with procedures for configuring Optimize through Command Central.
- The “Managing webMethods Optimize Environments” chapter of the *Configuring BAM* guide has been updated with information about configuring Digital Event Services resource module settings.
- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about Digital Event Services KPI definitions.
- The information about the Universal Messaging KPI definitions and the Infrastructure Data Collector KPI definitions in the “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated.
- The “Configuring the SNMP Data Collector” chapter of the *Administering webMethods Optimize* guide has been updated with information about monitoring memory consumption and processor load.
- The “Discovery Assets and Monitoring Components” chapter of the *Administering webMethods Optimize* guide has been updated with information about adding Digital Event Services assets for discovery.
- The “Discovery Assets and Monitoring Components” chapter of the *Administering webMethods Optimize* guide has been updated with information about setting a root context for My webMethods Server assets.

Release 9.12

- A new “Using Command Central to Manage Optimize” chapter has been added to the guide. This chapter is moved from the *Software AG Command Central Help*. The chapter describes the currently supported operations in Command Central for managing Optimize.
- The “Managing webMethods Optimize Environments” chapter of the *Configuring BAM* guide has been updated with information about configuring failover tuning for guaranteed consistency in Terracotta.
- The “Managing webMethods Optimize Environments” chapter of the *Configuring BAM* guide has been updated with information about configuring in-process event publication.
- The “Process Analytics” chapter of the *webMethods Optimize User’s Guide* has been updated with information about the new date range and refresh rate options, available on the Optimize Process Analytics page.

- The “Monitored KPI Definitions” chapter of the *Administering webMethods Optimize* guide has been updated with information about using additional JVM parameters for task event KPI definitions.

Release 9.10

The *Administering webMethods Optimize* guide has been revised as follows:

- The “Integration between Optimize and PPM” chapter has been added. It contains information you should have in mind when using the two products for extended analysis of business process data.

The *Configuring BAM Guide* now includes information about creating an alert in Optimize from the PPM user interface.

The *Software AG Command Central* help contains information about administering the Web Service Data Collector using the Command Central user interface.

Release 9.9

The *Administering webMethods Optimize* guide has been revised as follows:

- The “Monitored KPI Definitions” chapter has been updated with information about KPI definitions for Apama, Presto Catalina, Presto UM, IS File Polling, and Terracotta monitoring.
- The “Adding an Asset” section of the guide now contains information about adding Apama, Presto, Terracotta, SNMP3, and Terracotta assets.
- The “Configuring and Using the Infrastructure Data Collector” section of the guide now contains information about configuring Infrastructure Data Collector for clustering.
- The “Configuring and Using the Infrastructure Data Collector” section also contains information about changing the Infrastructure Data Collector ports.
- The “Configuring Event Routing Settings for Optimize” section in this guide has also been updated with details regarding the setup of Software AG Event Routing in your Optimize system.

The *webMethods Optimize User’s Guide* now includes information about using the “Investigate” button to jump to Process Performance Manager and further investigate process-related intrinsic data from Optimize. You will also find information about creating an alert in Optimize from the PPM user interface.

The *Software AG Command Central* help contains information about administering the Optimize Analytic Engine using the Command Central user interface.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Removed Item	Description
Process Dashboards in My webMethods	Process Dashboards are removed from My webMethods (Applications > Monitoring > Business > Process Dashboards) and can now only be accessed in Business Console.
View in PPM button	The View in PPM button in Process Dashboards is removed.

Changed Item	Description
Add Components button	In My webMethods > Edit Component Type page, the Add Components button is now renamed to Enable Components.
Delete button	In My webMethods > Edit Component Type page, the Delete button is now renamed to Disable Components.
Export Table button	In My webMethods > Analytics Overview page, the Export Table button is now renamed to Export Readings.

Release 10.2

Added Item	Description
Support for MySQL Enterprise Edition	You can now configure Optimize to use a MySQL Enterprise Edition database.

Release 10.0

Added Item	Description
Support for MWS Root Context	The Optimize for Process and Optimize for Infrastructure user interfaces now support the MWS Root Context capability.

Added Item	Description
508 Compliance for forms in the Optimize User Interface	The Optimize user interface is 508 Compliant for all forms.
Optimize is configurable through Command Central	You can now configure Optimize for Process and Optimize for Infrastructure through Command Central.

Release 9.10

Added Item	Description
Command Central integration for Web Service Data Collector	Users can now start, stop, restart, inventory and receive the status for Web Service Data Collector using Software AG Command Central.
Process Instance Control (PIC) and Process Step Instance Control (PSIC) content are now identical.	The content of the Process Instance Control (PIC) and Process Step Instance Control (PSIC) events are now identical for both orchestrated and un-orchestrated processes.
Launching the Process Performance Manager (PPM) no longer depends on a Java applet	PPM now is launched via Java web start which allows the PPM user interface to display properly in browsers where the Java Applet has been dropped such as Google Chrome.
Ability to delete Key Performance Indicators by date and name	You are now able to delete KPIs by date and name.
Ability to view custom MashZone Next Gen dashboards within Business Console	You are now able to view your custom dashboards within the Business Console.
Optimize User Interface provides 508 Compliance for images	The Optimize User Interface provides 508 Compliance for images ensuring all images have proper alt text.

Deprecated Item

Replacement, if any

KPI Instance Detail Portlet (9.9 and prior)

For 9.10, the KPI Instance Detail portlet was replaced with a revised version. The KPI Instance Detail portlet (wm_bam_monitor_detail) prior to 9.10 has been deprecated in 9.10, and will be removed in 9.12. While the previous portlet is no longer accessible through My webMethods navigation, the portlet will still be functional on a user's workspace until it is removed in the next release (9.12). Users migrating from a release prior to 9.10 who have a KPI Instance Detail portlet added to a workspace should manually remove the old portlet instance(s) from their workspace and re-add the new KPI Instance Detail portlet using the usual procedure (see steps below).

To re-add the KPI Instance Detail portlet to a workspace:

1. Open the workspace containing the KPI Instance Detail portlet.
2. Copy the KPI instance name shown above the graph.
3. Navigate to the Analytics Overview.
4. Select the Configuration appropriate for the KPI.
5. Search for the KPI instance name copied from step 2. Surround the name with quotes ("") for an exact match.
6. Expand the tree if necessary and view the detail for the KPI instance.
7. Render the detail using the desired time range.
8. Add the detail portlet to the desired workspace.
 - 8.1 Open the portlet menu.
 - 8.2 Select Add to Workspace.
 - 8.3 Select the desired workspace.

Release 9.9

Added Item	Description
Analytic Engine emits additional EDA Events	New EDA events emitted by the Analytic Engine include ProcessInstanceStatusChange, ProcessErrorCount, StepErrorCount and StepWaitTime
Jump from PPM to Optimize with context providing ability to create an alert	If PPM is installed and configured to interact with Optimize, the user is now able to jump from PPM with context while providing the ability to create an alert related to the passed context. The current context includes the Process model
Ability to investigate a Process related Optimize Intrinsic KPI further within PPM	If PPM is installed and configured to interact with Optimize, the user is now able to investigate a process related Optimize Intrinsic KPI further within PPM by clicking on the “investigate” button on the KPI Instance Detail page
Process Dashboards now retain Stage selection on return URLs	When a user has made Stage selections on the process dashboard, this information is now retained when returning from an email or task URL.
Aesthetic enhancements for Process Dashboards	Aesthetic improvements have been made to the Process dashboards including: Principle picker now uses enter key to submit form when entering keyword characters, general control alignment and styling
Command Central integration for Analytic Engine	Users can now start, stop, restart and receive the status for the Analytic Engine using Command Central. This includes configuring event routing for the Analytic Engine
Performance and scalability improvements	<ul style="list-style-type: none">▪ 100 times improvement in clustered Analytic Engine throughput performance▪ 2 times faster Analytic Engine startup▪ 500 percent increase in dimensional handling throughput▪ 30% throughput improvement in State engine

Release 9.8

Added Item	Description
Ability for user to jump from Optimize to PPM	If PPM is installed and configured to interact with Optimize, the user is now able to jump from the Process Analytic page and Process Dashboards to PPM. The navigation includes the current process model as context.
Principle picker on escalation dialog in the Process Dashboards	A principle picker has been added to the escalation dialog within the Process dashboards. It now allows the user to easily find and choose a specific user and include their email address or user id in the escalation.
Customers can now provide a custom process instance id for a given process instance	BAM only processes now support the ability to provide a custom process instance id, also known as a display name, for a given process instance. The display name is used in place of the underlying unique id, when provided throughout the user interface.
Intrinsic Stage Metrics available in the UI	The intrinsic metrics associated with Stages are now available for use in the Analytics Overview.
New KPI Counter type	A new KPI type has been added called Counter. This KPI counts the number of data points received for a specific fact over a fixed aggregation period.
New Rule Violation/Resolution EDA event	Optimize now is able to emit Rule Violation/Resolution EDA events.

Deprecated Item	Replacement, if any
Removal of BAM_AGG_... database tables	The BAM_AGG_... database tables usage is being removed from future releases. These tables are currently used for Optimize Only UI support and will no longer be used.

9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

10.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

OPTPROC-RM-103-20181015

webMethods Service Development 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Service Development 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information	1
2.0	Known Issues	2
3.0	Usage Notes	4
4.0	Fixes Included in Each Release	4
5.0	Other Resolved Issues	7
6.0	Documentation Changes	10
7.0	Terminology Changes	12
8.0	Added, Removed, Deprecated, or Changed Items	12
9.0	Copyright Information	20
10.0	Support	21

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- WED-7741
Cloud deployment fails as Integration Cloud solutions are not available for election.
Deploying Integration Server packages and configuration assets fail as Integration Cloud solutions to which the packages and assets should be deployed are not available for selection from Designer.
This issue is caused due to some schema changes done at Integration Cloud.
There is no workaround for this issue.
- WED-7728
Following issues exist related to the Landscape navigator, Configuration browser, and Asset Build Environment:
 - When using Configuration project, there is no support to deploy assets to cloud.
Workaround: Use Deploy to Cloud option in Designer to publish assets to cloud.
 - When creating Command Central definition, the connection to Command Central server is not enabled when using the Installation Directory.
Workaround: Use the Command Central URL directly. For example, <https://localhost:8091/cce>
 - Configuration Chooser dialog in the Cloud Publish wizard does not have a refresh option.
Workaround: Open the Landscape Navigator, refresh the required runtime, and then open the Cloud Publish wizard.
 - Default Asset Build Environment definition is not created in a new Designer workspace.
Workaround: Open the Asset Build Environment preference and create an Asset Build Environment definition by specifying the Software AG installation directory.
 - You should export only those configurations that are supported for Cloud deployment from the Landscape Navigator. However, Designer does not validate this and as all configurations can be exported.
Workaround: Selects configurations that are supported.
 - Labels and Messages from Landscape Navigator and Configuration Project are not localized.
There is no workaround to this issue.
- WED-7652
Compare and merge fails to work as expected for two flow services containing Try-Catch or Try-Finally flow steps.
Following issues exist when comparing and merging two flow services containing Try-Catch or Try-Finally flow steps:
 - Merge functionality is disabled.
 - Compare editor displays incorrect properties of flow services.There are no workarounds for these issues.
- WED-7651
The warning message icon is not displayed in the Layout tab for flow services containing Try-Catch or Try-Finally steps.
In the Layout tab, whenever an incorrect flow step is selected or an existing step is deleted after the

Try step, the icon displaying the warning message does not appear. However, it appears in the Tree tab.

There is no workaround for this issue.

- WED-7369

Swagger UI hangs upon clicking the Authorize button.

In Designer, on clicking the Authorize button and then the Close button on the Swagger UI tab of a REST API descriptor, the Swagger UI hangs.

To work around this issue, close and open the Swagger UI.

- WED-7127

Issues with compare and merge functionality for Adapter elements.

In Designer, compare and merge functionality for Adapter elements allows you to track and merge changes from the same server or from different servers and also from the version control history.

However, following issues exist with this functionality for Adapter elements:

- Sometimes, comparing two adapter services of SELECT template fails after updating the element, as the compare editor highlights only the empty rows and cells.

- For Adapter update Notification elements, row indexes are improperly calculated while merging the "Added" table data from left to right direction.

- In some cases merging two different Adapter Services fail with following exception:

"Internal error. Unexpected value at

```
'com.softwareag.is.ui.diffmerge.internal.UndoableMergeDiffNodeOperation#addTypedAdapter: 363'. Expected 'com.softwareag.is.compare.structure.IComparatorElement', actual 'null'."
```

There are no workarounds for these issues.

- WED-6713

In the IS Asset Compare view, you cannot merge the enabled or disabled property of a flow step or transformer obtained from comparing two Integration Server elements.

There is no workaround for this issue.

- WED-6227

During refactoring, preview of the new and old value is unavailable for webMethods messaging trigger.

There is no workaround for this issue.

- WEL-6

When you use Team Foundation Server (TFS) as your VCS client, TFS issues an `IllegalArgumentException` exception when sharing the local service development project.

To work around this issue, clear the 'Connect mapped projects to TFS automatically' check box in Window > Preferences > Team > Team Foundation Server before sharing the local service development project.

There is no workaround for this issue.

- WED-7129

Logged Fields view fails to reflect the updated signature structure.

If you merge a service signature structure, then the Logged Fields view does not reflect the updated

signature structure.

There is no workaround for this issue.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

Try it out option in Swagger UI – If GET operation has parameters that are not of type PATH, then before executing the operation inside the editor, change the parameter type to Query. This is because, the parameter defaults to FORMDATA and GET operation supports only FORMDATA.

In Designer, on clicking the Authorize button and then the Close button on the Swagger UI tab of a REST API descriptor, the Swagger UI hangs. To workaround this issue, close and open the Swagger UI.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- ESB_10.1_Fix6
- ESB_10.2_Fix2

Release 10.2

- ESB_9.6_Fix7
- ESB_9.7_Fix10
- ESB_9.8_Fix7
- ESB_9.9_Fix8
- ESB_9.10_Fix8
- ESB_9.12_Fix9
- ESB_10.1_Fix3

Release 10.1

- ESB_9.6_Fix6
- ESB_9.8_Fix6
- ESB_9.9_Fix7
- ESB_9.10_Fix5
- ESB_9.12_Fix6
- ESB_10.0_Fix2

Release 10.0

- ESB_9.5_SP1_Fix9
- ESB_9.7_Fix9
- ESB_9.8_Fix5
- ESB_9.9_Fix5
- ESB_9.10_Fix3
- ESB_9.12_Fix2

Release 9.12

- ESB_9.10_Fix2
- ESB_9.9_Fix3
- ESB_9.8_Fix4
- ESB_9.7_Fix7
- ESB_9.5_SP1_Fix8

Release 9.10

- ESB_9.9_Fix2
- ESB_9.8_Fix2
- ESB_9.7_Fix5
- ESB_9.6_Fix5

Release 9.9

- ESB_9.8_Fix1
- ESB_9.7_Fix4
- ESB_9.5_SP1_Fix7

Release 9.8

- ESB_8.2_SP3_Fix15
- ESB_9.0_SP1_Fix9
- ESB_9.5_SP1_Fix6
- ESB_9.6_Fix4
- ESB_9.7_Fix2

Release 9.7

- ESB_8.2_SP3_Fix14
- ESB_9.0_SP1_Fix6
- ESB_9.5_SP1_Fix5
- ESB_9.6_Fix3

Release 9.6

- ESB_8.2_SP3_Fix12
- ESB_9.0_SP1_Fix5
- ESB_9.5_SP1_Fix4

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.2

- WED-6898
The Designer session keeps retrying a connection if sessions are not closed explicitly by the user. When a user does not close the Designer sessions explicitly, Designer restores the connection to the Integration Server with old credentials and Integration Server raises a `flowTimeoutException`. The issue is now resolved. Designer identifies the condition when credentials are invalid and then stops the connection.
- WED-7121
Unable to create web service descriptor from Designer.
Creating a Web Service Provider and Consumer descriptor in Designer fails with following error:
'`http://apache.org/xml/features/disallow-doctype-decl`' not recognized.
This issue is now resolved.

Release 10.1

- WED-6957
Execute an Adapter service with `InputFieldType` (in the Which tab) '`java.lang.Byte`' by providing a value that exceeds the limit, an error message appears informing the same. Later, if you execute the same Adapter service by changing the `InputFieldType` to '`java.lang.String`', the same error message appears preventing the service execution, even if you provide correct values.
This issue is now fixed.
- WED-6846
In a transformer, if the output variables (Pipeline Out to Service Out or the reverse way) are mapped before the input variables (Pipeline In to Service In or the reverse way), the map step containing the transformer saves an incorrect value and hence, the flow service fails with incorrect results.
This issue is now fixed.
- WED-6434
When using Designer to invoke the `pub.flow:setResponseCode` service, if the `responseCode` input variable value is set to 204, the Results view displays an exception.
This issue is now fixed.

Release 10.0

- WED-6370

Dropping an input array variable that is part of a ForEach mapping results in an exception.
This issue is now fixed.

- WED-6311
Changes made in Pipeline view do not reflect in the Data Mapper view immediately.
This issue is now fixed.

Release 9.12

- WED-6034
Designer fails to handle the URL redirections while creating Integration Server elements.
In Designer, if the URL has redirection, creation of Integration Server elements, such as web service descriptors, document types, and Integration Server schema from external URL fail.
This issue is now fixed.
- WED-5592
Tooltips remain frozen in Designer.
In Designer, the document or flow editor tooltips remain on the screen even after closing the editor using the keyboard shortcut Ctrl+W.
This issue is now fixed.
- WED-5820
Designer fails to display the details of Forms tab for Custom Remedy Adapter.
Forms tab does not display the details of Custom Remedy Adapter service such as the 'Selected Form' details in Designer.
This issue is now fixed.
- WED-5611
Web service descriptor fails to generate xsd:any element and attributes when the 'Allow unspecified fields' property is set to true.
The WSDL document for a web service descriptor does not include the xsd:any element and attributes when the web service descriptor uses a Document variable for which the 'Allow unspecified fields' property is set to true. This issue occurs even if the server configuration parameter `watt.core.schema.createSchema.omitXSDAny` is set to false.
This issue is now fixed.
- WED-5210
When unresolved package issues are manually resolved in a Java service, Designer does not append the import details correctly to other Java services in the same folder of the package if they are also open in the editor.
While editing Java services, upon doing an Organize Imports operation in a Java service, Designer removes necessary import details of other Java services that are in the same folder in the package if they are currently open in the editor. If the import details that are removed from the other services are manually resolved, the import details of the first service get corrupted, instead of getting appended to the existing import details.
This issue is now fixed.

- WED-6204
The field name abbreviator, as used for XmlData, truncates the field names that start or end with '#'. When you run a flow service, Designer fails to display the parameter names that start or end with # in the Results window. The Field name abbreviator, as used for XmlData, truncates the field names that start or end with '#'.
This issue is now fixed.

Release 9.10

- WED-5339
After installing a fix or a version of Integration Server that includes PIE-30233, a pipeline link (map or mapping) where the destination is a Document reference variable with an unresolved document type reference, behaves differently at run time.
When executing the pipeline link, at run time, Integration Server ignores the field order defined in the target Document reference variable which results in unpredictable field ordering in IData.
This issue is now fixed.
Note: Integration Server versions 9.7, 9.8, and 9.9.
- WED-5692
There is no keyboard shortcut to drop variables from the pipeline.
This issue is now fixed. Ctrl+Shift+O is the new keyboard shortcut to drop variables from the pipeline.
- WED-5584
While searching for Integration Server elements in all packages, Designer does not work as expected when installed with a non-English language pack.
If you select **All Packages** option while searching for an Integration Server element in Designer (Search -> Integration Server), Designer searches for the element in all the packages before displaying the results. However, if Designer is installed with a language pack other than English, Designer does not search for the element in all packages. As a result, no results are displayed.
This issue is now fixed.
- WED-5397
Performance of Designer slows down when saving a flow service with a large number of service references. While saving a flow service, Designer checks whether the services referenced in the flow service exists. As a result, if there are a large number of service references in the flow service, the performance of Designer slows down.
This issue is now fixed. A new flow service editor preference is introduced. In the Flow Service Editor preferences page, if you do not want Designer to validate the referenced services while saving a flow service, clear the Validate service references while saving check box. Clearing this preference improves the performance of Designer while saving a flow service. By default, this check box is not selected. Select the Validate service references while saving check box if you want Designer to validate the referenced services while saving a flow service.
- WED-5210

When user selects Organize Imports to fix a JAVA service, it fixes the import statements of that service but the import statements in other JAVA services fails in the same folder.

This issue is now fixed.

- WED-5464

If Centrasite is selected as the source of the WSDL or XML schema definition, Designer does not display the child organizations when creating a web service descriptor or an IS document type.

When creating a consumer or WSDL first provider web service descriptor from a service asset in CentraSite or an IS document type from an XML Schema definition in CentraSite, Designer does not display the assets that belong to the child organizations.

This issue is now fixed. Now, if Centrasite is selected as the source of the WSDL or XML schema definition when creating a web service descriptor or an IS document type, Designer lists the child organizations

- WED-5465

If you set the Pre-8.2 compatibility mode property to true for a web service descriptor using Designer, StackOverflowException occurs.

If the web service descriptor contains a recursive document type reference, using Designer to set the Pre-8.2 compatibility mode property to true results in a StackOverflowException.

This issue is now fixed.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- Service Development Help contains a new chapter, "Deploying to Cloud", which explains how to deploy Integration Server packages and configuration assets (Integration Server and Universal Messaging configurations) to Integration Cloud using Designer.
- Service Development Help contains a new chapter, Command Central Preferences, which explains how to customize Landscape navigator view, monitoring, and project settings for Command Central runtime components using Designer.
- Service Development Help contains a new chapter, Integration Cloud Preferences, which describes the settings required for configuring an Integration Cloud connection.
- Service Development Help contains a new chapter, "Working with Recipes", which explains how to install or download and use recipes as a package using Designer.

Release 10.2

- Service Development Help contains a new chapter, “Publishing and Retracting Metadata for IS and TN Assets,” which explains how to publish and retract metadata for Integration Server (IS) assets, and Trading networks (TN) document types to and from the CentraSite shared registry.
- The *Developing Microservices with webMethods Microservices Container* guide has been renamed *Developing Microservices with webMethods Microservices Runtime* to reflect the product name change from webMethods Microservices Container to webMethods Microservices Runtime.
- Service Development Help contains a new chapter, “Working with WebSocket Endpoints”, which explains what a WebSocket endpoint is and how to create a WebSocket client endpoint and WebSocket Server endpoint.

Release 10.0

- Service Development Help contains a new topic, Building Map Services, which explains what is a map service and how to create a map service.

Release 9.9

- Service Development Help contains a new topic, Working with XML Document Types, which explains what XML document types are and how to create XML document types.
- Service Development Help contains a new topic, Comparing Integration Server Packages and Elements, which tells you how you can compare packages and elements in Integration Server using the compare tool.
- Service Development Help contains the Managing Cloud Connector Services topic, which was earlier available only in the documentation specific to your CloudStreams provider (for example, webMethods CloudStreams Provider for Salesforce.com Installation and User's Guide).

Release 9.8

- Service Development Help contains a new topic, Working with OData Services, which provides information about how to create and edit OData services.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 10.3

Old Term	New Term
Named object	Durable subscription or durable. As of Universal Messaging version 10.2, the term <i>named object</i> has been replaced with <i>durable subscription</i> or its abbreviated form <i>durable</i> . A serial webMethods messaging trigger corresponds to a serial durable subscription (or the abbreviated serial durable) on Universal Messaging. A concurrent webMethods messaging trigger corresponds to a shared durable subscription (or the abbreviated shared durable) on Universal Messaging.

Release 10.2

Old Term	New Term
webMethods Microservices Container	webMethods Microservices Runtime

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
EXIT step Exit from property value \$iteration	The Exit from property now includes \$iteration as a possible value to specify exiting from an iteration of the nearest ancestor LOOP or REPEAT flow step.

Added Item	Description
Enhancements to REST V2 resources for JSON API support	<ul style="list-style-type: none"> - Designer provides following options for JSON API support in the rest resource creation wizard: “Empty Rest resource and Document type based REST resource” while creating a rest resource. - Designer provides an additional tab called "Attribute configuration" for adding attributes to the REST V2 resource. - New property “Generate JSON API URLs” is added to the property view of a REST V2 resource.
Integration Cloud preference	Integration Cloud preference page enables Designer to connect to Integration Cloud (Window > Preference > Software AG > Integration Cloud).
Support for Recipes in Integration Server / Designer	A new view called ‘Recipes’ is added under Window > Show View > Other... for viewing, searching, installing, and downloading the Recipes in Designer.
Designer UI support for Try-catch block for flow services	<ul style="list-style-type: none"> - Designer now provides the following new flow steps for in the palette view and context menu: TRY-CATCH, TRY-FINALLY, CATCH, and FINALLY. - Designer provides a new context menu option called “Transform to > Try Catch Step / Try Finally Step” for SEQUENCE flow step. - Designer displays a warning icon along with the message upon mouse hover in the flow editor when user uses an invalid TRY-CATCH or TRY-FINNALLY combination.
Deployment to Integration Cloud	Using Designer you can now seamlessly deploy your on-premise Integration Server packages and configuration assets to solutions present on Integration Cloud.

Changed Item	Description
EXIT step Exit from property	The default value of the Exit from property is now \$parent which indicates the flow will exit from the parent flow step, regardless of the type of step. Previously, the default value was <blank> which equated to nearest ancestor LOOP or REPEAT flow step.
Serial webMethods messaging triggers that receive documents from Universal Messaging now process documents from a publisher in publication order in a load-balanced fashion.	Previously, a webMethods messaging trigger with serial processing corresponded to a priority named object on a channel on Universal Messaging server. Now, a serial webMethods messaging trigger corresponds to a serial durable subscription (named objects in Universal Messaging are now called durable subscriptions). This provides processing in publishing order for a serial trigger in a cluster or a non-clustered group of Integration Server. Over time, it allows for the Integration Server in a cluster or non-clustered group to process messages in a load balanced fashion.

Release 10.2

Added Item	Description
WebSocket Endpoints	You can configure WebSocket endpoint that act as a server or client type. Implementation of WebSocket endpoints and its accompanying services enable you to develop and deploy applications that communicate with clients.
Circuit Breaker	You can configure a circuit breaker feature for a service that resides in a webMethods Microservices Runtime. To configure a circuit breaker with a service running on Integration Server, your Integration Server must have additional licensing.
Sync to DES property for IS document types	Indicates whether Integration Server automatically synchronizes this document type with a corresponding Digital Event Services event type definition in the Digital Event Services repository upon save. Set this property to true if the document type is used to define the structure and content for the value of an “any” field in a document that is published to Digital Event Services.

Enhancements to REST API descriptor

- Designer provides a Swagger UI view that surfaces the open source Swagger UI and Try it out option developed for Swagger.
- Swagger Syntax Coloring preference page is now available to set the font color and styles of tokens in a Swagger document.
- Run option in the REST API descriptor editor enables execution of selected REST operations available in REST API descriptor.

Enhanced support for REST V2 resources

New properties are added to the property view of a REST V2 resource.

Removed Item

Creating an IS document type from a file in webMethods Content Service Platform

Replacement, if any

None. The webMethods Content Service Platform is no longer available.

Release 10.1

Added Item

Support for REST V2 resources

Description

REST V2 resources provide a flexible way of defining resources for REST requests. In the Service Development perspective, a developer can define a REST V2 resource with operations that include the following:

- The format of the URL that REST clients must follow when sending requests to Integration Server acting as the REST server.
- The HTTP methods supported by the resource operation.
- The flow service associated with a resource operation.

Support for REST API descriptors for REST V2 resources

In addition to creating REST API descriptors from resources that use the rest directive, the Service Development perspective now provides the ability to create REST API descriptors from REST V2 resources.

Added Item	Description
Support for REST API Descriptor from Swagger Document	The Service Development perspective now provides the ability to create REST API descriptors from external Swagger documents accessible through a URL, a REST resource on API Portal, or a REST resource residing in CentraSite.
Microservices Container running in a Docker container as local service development server.	Designer provides support for the local service development feature to use a Microservices Container running in a Docker container as the local development server.

Removed Item	Replacement, if any
REST Resource Configuration	<p>The REST Resource Configuration page of the Properties dialog box for a selected service option has been removed.</p> <p>An alternate option is provided through the creation of new REST V2 assets.</p>

Release 10.0

Added Item	Description
Case sensitive check box	The Case sensitive check box in the Integration Server Search tab of the Search menu allows you to perform a case-sensitive search for the names of Integration Server elements.
Exact match check box	The Exact match check box in the Integration Server Search tab of the Search menu allows you to search for an Integration Server element with a name that exactly matches the specified search string.
Map service	Designer allows you to create map services that can be reused in different flow services. A map service can be used to map document types of different formats.
PATCH check box	The PATCH check box in the New REST Resource configuration wizard of the Service Development perspective allows you to specify PATCH as a supported method for creating a REST resource.

Added Item	Description
REST Resource Configuration	The REST Resource Configuration page of the Properties dialog box for a selected service provides you with options to configure, edit, and delete REST resources for the particular service.
Convert to Local Service Development Project	Using the Convert to Local Service Development Project option in the context menu allows you to convert a non-Local Service Development package to a Local Service Development package by adding the VCS and Java project nature to packages that contain the Java and C/C++ services.
ForEach debugging	Designer now allows you to debug a ForEach mapping.
Allowed HTTP Methods property	The Allowed HTTP Methods property for a service enables you to select the HTTP methods that you can configure for the particular service. The supported methods are GET, HEAD, PUT, POST, PATCH, DELETE, and OPTIONS.

Removed Item	Replacement, if any
Add VCS project Nature	Convert to Local Service Development Project in the context menu allows you to add the VCS and Java nature to packages while you are working with local service development.

Changed Item	Description
Port alias property	For a binder in a provider web service descriptor, you can now set the Port alias property to the default provider endpoint alias when the binder uses the HTTP or HTTPS protocol.

Release 9.12

Added Item	Description
Comparing and merging JMS triggers, adapter services, and adapter connections	JMS triggers, adapter services, and adapter connections can now be visually compared and differences between versions can be merged. Previously, merging was available only for flow services and IS document types.

Added Item	Description
Debug to Here	Debug to Here option in the context menu allows you to debug a flow service up to the specified flow step.
Data Mapper	Data Mapper view in Designer allows you to execute, modify, and test a MAP step without saving the flow service.
ForEach mapping	Designer provides ForEach mapping approach in the pipeline view of a MAP step to simplify array mapping and array data processing.
Move project to Integration Server package as linked resource	Move project to Integration Server package as linked resource option in the Local Service Development Preferences, allows you to set any repository on your workspace as the local repository directory and a linked directory is created under the Integration Server_directory\instances\default\packages directory.
Digital Event Services (DES)	From Designer, a user can integrate with Digital Event Services using the existing webMethods Messaging infrastructure. Also, Annotations property is now available for publishable document types that use the IS_DES_CONNECTION messaging connection alias.
Search and Refactor	Search functionality now provides the ability to search for a particular variable and identify all references to that variable in other assets, such as flow services, document types, specifications, and triggers. The Refactor option in the context menu allows you to refactor the input/output variables of various Integration Server assets (for example, flow services, Java services, specifications, documents type).
API Portal	The API Portal metadata repository type in the Asset publish wizard helps a user to configure connections to API Portal and publish REST API descriptors.

Changed Item	Description
Processing mode property default	The default processing mode for JMS triggers and webMethods messaging trigger is now changed from Serial to Concurrent. The value for 'Max execution threads' is changed from 10 to 1.
Encoding type property default	The default encoding type for publishable document type associated with a Universal Messaging connection alias is now Protocol buffers. Previously, the default encoding type was IData.

Release 9.10

Added Item	Description
REST API Descriptor	A descriptor for a group of REST services on Integration Server.
Merging Integration Server Elements	Merge capability allows you to merge the differences between two elements on the same server or on different servers. Merging is available for flow services and Integration Server document types.
LCVI: Integration Server instance need not be named 'default' to use as LCVI.	Multiple Integration Server local instances can now be made as Local Version Control Integration Server (LCVI).
Validate service references while saving preference	Flow service editor preference for validating all of the referenced services in the flow service upon saving the service.
Rest API Descriptor Preference	Preference for specifying MIME type available for use with REST API descriptors.
OData service creation from external sources	OData service can now be created using an external source type.

Changed Item	Description
REST Resource folder icon	A folder that contains services that function as a REST resource now has a unique icon to differentiate it from a folder that does not contain any services or elements used as a REST resource.

Release 9.9

Added Item	Description
XML document type	An XML document type corresponds to a global element declaration, global attribute declaration, or global complex type definition in an XML schema definition.
Deprecated Item	Replacement, if any
WmVCS and VCS Integration feature	Use the local service development feature (Local Version Control Integration) to check package elements and their supporting files into and out of a version control system (VCS) directly from Designer.
Changed Item	Description
Serial webMethods messaging triggers that receive documents from Universal Messaging now process documents from a publisher publication order.	Previously, a webMethods messaging trigger with serial processing corresponded to a shared named object on a channel on Universal Messaging server. Now, a serial webMethods messaging trigger corresponds to a priority named object. This provides processing in publishing order for a serial trigger in a cluster or a non-clustered group of Integration Server

Release 9.8

Added Item	Description
OData service wizard and editor	New wizard and editor to create, view, and edit OData services.
Support for VCS operations from the Package Navigator view	VCS operations can now be performed on elements from Package Navigator view for Local Development.
Changed Item	Description
Default value of the Hide generated flow services preference.	The Hide generated flow services check box in the In the Preferences dialog box under Software AG > Service Development > Package Navigator is now cleared by default.

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA,

and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

SD-RM-103-20181015

webMethods Task Engine and wmTaskEngine 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Task Engine 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	3
4.0	Fixes Included in Each Release.....	3
5.0	Other Resolved Issues.....	8
6.0	Documentation Changes	9
7.0	Terminology Changes	10
8.0	Added, Removed, Deprecated, or Changed Items.....	10
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	12
10.0	Added, Removed, Deprecated, or Changed Parameters.....	15
11.0	Added, Removed, Deprecated, or Changed APIs	16
12.0	Copyright Information.....	111
13.0	Support.....	111

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- MWS-21070
When using an IS Document type to define the business data for a HPSTRA-enabled task, the Composite Application Framework might duplicate business data fields in the runtime. There is currently no workaround for this issue.
- WTN-4421
The wmTaskEngine package in Integration Server fails to add or modify task comments. Task Engine fails to add, update or delete task comments. This issue occurs when you use a Task Engine instance, running on Integration Server. The workaround for this issue is to create and initialize a My webMethods Server instance that uses the Integration Server database before using the wmTaskEngine package with task comments.
- WTN-4400
Deploying task projects to the wmTaskEngine package in Integration Server fails with an error. This issue occurs when you deploy a war file for the project and the war file does not include a jar file in the WEB-INF/lib directory. The workaround for this issue is to manually add a jar file with the compiled project contents in the WEB-INF/lib directory of the project before deploying the war file.
- WTN-4396
Opening the logging configuration page for the wmTaskEngine package in Integration Server displays a NullPointerException error message. There is currently no workaround for this issue.
- WTN-4370
When you configure a JMS provider for the wmTaskEngine package using the Command Central web user interface, you cannot set the field back to an empty value. There is currently no workaround for this issue.
- WTN-4352
The wmTaskEngine package in Integration Server fails to invoke services from task types with Assignment/Event rules. This issue occurs when the Assignment/Event rule that invokes the service is configured to trigger when you queue a new instance from the task type. There is currently no workaround for this issue.

- WTN-4434

When queueing a new task instance from a task type, Task Engine puts the new task instance in status Error. This issue occurs when using a Task Engine instance, running on Integration Server, and queueing task instances with the services from the wmTaskEngine package.

The workaround for this issue is to add the following lines to the ini.cnf file of the Integration Server instance:

```
%COMMON_LIB%wm-caf-ws-wss.jar;\
%COMMON_LIB%wm-caf-ws-glue.jar;\
%COMMON_LIB_TASK_ENGINE%reflections.jar;\
%COMMON_LIB_TASK_ENGINE%javassist.jar;\
```

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- WTN-4082

When you use Task Engine with a My SQL Community Edition database version 5.7.18, My SQL might truncate stored data for business data fields with numerical datatypes.

This is a database limitation.

- Task Engine instances, running on Integration Server can perform only regular and indexed task data searches. HPSTRA indexing and searches are not supported.
- Task Engine instances, running on Integration Server require Universal Messaging for clustering.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

- MWS_10.2_Fix1
- MWS_10.1_Fix6
- MWS_10.1_SPM_Fix1
- MWS_10.0_Fix4
- MWS_10.0_SPM_Fix1

- MWS_9.12_Fix27
- MWS_9.12_SPM_Fix1
- MWS_9.12_SPM_TE_Fix1
- MWS_9.10_Fix28
- MWS_9.10_SPM_Fix1
- MWS_9.10_SPM_IS_Fix1
- MWS_9.9_Fix29
- MWS_9.9_SPM_Fix2
- MWS_9.9_GLUE_Fix2
- MWS_9.8_Fix39
- MWS_9.8_SPM_Fix5
- MWS_9.8_GLUE_Fix3
- MWS_9.7_Fix36
- MWS_9.7_SPM_Fix3

Release 10.2

- MWS_10.1_Fix2
- MWS_10.0_Fix4
- MWS_10.0_SPM_Fix1
- MWS_9.12_Fix18
- MWS_9.12_SPM_Fix1
- MWS_9.10_Fix25
- MWS_9.9_Fix22
- MWS_9.9_SPM_Fix2
- MWS_9.8_Fix36
- MWS_9.7_Fix34
- MWS_9.6_Fix26

- MWS_9.5_SP1_Fix31
- MWS_9.0_SP1_Fix16

Release 10.1

- MWS_10.0_Fix2
- MWS_9.12_Fix9
- TE_9.12_TC_Fix1
- MWS_9.10_Fix17
- MWS_9.9_Fix18
- TE_9.9_TC_Fix2
- MWS_9.8_Fix28
- MWS_9.8_GLUE_Fix3
- TE_9.8_TC_Fix1
- MWS_9.7_Fix29
- TE_9.7_TC_Fix2
- MWS_9.6_Fix23
- TE_9.6_TC_Fix2
- MWS_9.5_SP1_Fix29
- MWS_8.2_SP1_Fix31

Release 10.0

- MWS_9.12_Fix3
- MWS_9.10_Fix9
- MWS_9.9_Fix10
- MWS_9.8_Fix20
- MWS_9.7_Fix23
- MWS_9.6_Fix19

- MWS_9.5_SP1_Fix24
- TE_9.9_TC_Fix1
- TE_9.7_TC_Fix2
- TE_9.6_TC_Fix2

Release 9.12

- MWS_9.10_Fix2
- MWS_9.10_SPM_Fix1
- MWS_9.10_SPM_IS_Fix1
- MWS_9.9_Fix5
- MWS_9.9_GLUE_Fix2
- MWS_9.9_SPM_Fix1
- MWS_9.8_Fix12
- MWS_9.8_SPM_Fix4
- MWS_9.7_Fix16
- MWS_9.6_Fix16
- MWS_9.6_SPM_Fix3
- MWS_9.5_SP1_Fix22
- MWS_9.0_SP1_Fix13
- MWS_8.2_SP1_Fix28
- TE_9.8_TC_Fix1
- TE_9.6_Fix1
- TE_9.5_SP1_TC_Fix3

Release 9.10

- MWS_9.9_Fix2
- MWS_9.9_GLUE_Fix1

- MWS_9.8_Fix8
- MWS_9.8_GLUE_Fix1
- MWS_9.7_Fix12
- MWS_9.6_Fix10
- MWS_9.6_GLUE_Fix1
- MWS_9.5_SP1_Fix15
- MWS_9.0_SP1_Fix9
- MWS_8.2_SP1_Fix26
- TE_9.7_TC_Fix1
- TE_8.2_SP1_TC_Fix7

Release 9.9

- MWS_9.8_Fix3
- MWS_9.7_Fix7
- MWS_9.6_Fix8
- MWS_9.5_SP1_Fix11
- MWS_9.0_SP1_Fix7
- MWS_8.2_SP1_Fix24

Release 9.8

- MWS_9.7_Fix3
- MWS_9.6_Fix5
- MWS_9.5_SP1_Fix6
- MWS_9.0_SP1_Fix5
- MWS_8.2_SP1_Fix19
- MWS_8.0_SP2_Fix20

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- MWS-23917

Task Engine might schedule and fire events at unexpected times.

This issue occurs for the following task event configurations:

- When you configure task events with binding expressions for schedule time offsets and the binding expressions do not resolve to a number. Task Engine schedules and fires the events immediately.

- When you configure task events without business calendar, but a default business calendar is configured in My webMethods Server. Task Engine will comply to the default business calendar, regardless of the event configuration.

The issue is resolved. Task Engine no longer schedules task events if the binding expression for date/time offset does not resolve to a numerical value.

Task Engine no longer uses the default business calendar when calculating event schedules. You can control this behavior by adding the following system property to the custom_wrapper.conf file for My webMethods Server:

- Dtask.events.use.default.calendar=true

By default the property is set to false (not present) and Task Engine does not use the default business calendar of a user when scheduling task events, as documented.

Release 10.2

- WTN-3733

My webMethods does not display details about a step in a collaboration process.

On the Collaboration Processes > Process Details page, when you select a step in a collaboration process, the Step Info, Task Info, Task Audit, and Task Comments tabs on the Details panel do not display any information about the step. Only the Process Info tab contains any information.

The issue is resolved.

Release 10.1

- WTN-4000
A security issue with password masking was discovered in the WmTaskClient package in Integration Server.
The issue is resolved.

Release 10.0

- WTN-2749
The WmTaskClient package does not support case-insensitive index searches.
You cannot use WmTaskClient package services to perform an indexed task search with a search query term that is case-insensitive.
The issue is resolved.

Release 9.12

- WTN-3684
On the Business Data page in My webMethods, the Intrinsic Task Metrics event maps are improperly set as user-defined.
When you expand the Intrinsic Task Metrics node on the Administration > Analytics > KPIs > Business Data page in My webMethods, the DEFINED BY column for the Intrinsic Task Metrics event maps displays the value of "User". However, intrinsic event map and KPI definitions should be system-defined to prevent users from deleting or modifying the definitions.
The issue is resolved. The DEFINED BY column for the Intrinsic Task Metrics event maps now has a value of "System".

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

The Task Engine documentation set is available as a webhelp on the Software AG Empower website.

Release 10.2

The *Task Engine User's Guide* is available as a webhelp on the Software AG Empower website.

Release 9.12

A new chapter, “Using Command Central to Manage Task Engine” is added to *webMethods Task Engine User’s Guide*. The chapter contains information about how you use Software AG Command Central to administer the WmTaskClient and Task Engine layered products.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Item	Description
Task Engine on Integration Server	You can install and run Task Engine as a package (wmTaskEngine) on Integration Server.

Release 10.2

Removed Item	Replacement, if any
Support for Axis 1.4, which is used for exposing web services from My webMethods Server, is removed.	Now My webMethods Server web services use Axis 1.7.7.
The Task Content portlet	
Support for Content Service Platform	

Release 10.1

Added Item	Description
Support for using MySQL with Task Engine	For more information about how to use MySQL with My webMethods Server and Task Engine, see <i>Administering My webMethods Server</i> .
Support for Digital Event Services (DES) events	Task Engine now supports the emission of Digital Event Services events.

Deprecated Item	Replacement, if any
The My webMethods Server embedded database (Derby) is deprecated.	

Release 10.0

Added Item	Description
Full-text search in task type inboxes	Task Engine now supports full-text search on task business data in task type inboxes.

Changed Item	Description
Task Type ID selection in the Tasks Migration portlet	The Tasks Migration portlet now supports the selection of the task type ID for all supported databases.

Release 9.12

Deprecated Item	Replacement, if any
Support for Axis 1.x, which is used for exposing web services from My webMethods Server, is deprecated.	
Support for webMethods Glue	

Release 9.10

Added Item	Description
webMethods Task Development now supports the String List data type when you configure task assignees with a webMethods Business Rules decision table in Software AG Designer.	You can assign a task to multiple user IDs by using a String List in the assignee field of your IS document type. For more information about working with task assignments, see <i>webMethods BPM Task Development Help</i> .
Scheduling of task instances	When you create a task instance, you can now schedule the task instance to start at a specified date and time. You specify or modify the schedule of a task instance, using: <ul style="list-style-type: none">• Task Engine built-in services• Task Engine RESTful services• webMethods Business Console user interface

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Service	Description
wmTaskEngine package	Services to administer and configure a Task Engine instance, running on Integration Server and services to deploy, queue, search, update, and delete tasks on an Integration Server runtime.

Release 10.1

Added Service	Description
pub.task.taskclient:searchTasksHPSTRA	The built-in service retrieves tasks that match specified search criteria. Applies to tasks with task data that the HPSTRA module in Task Engine stores in an ElasticSearch store.
pub.task.taskclient:countTasksIndexedHPSTRA	The built-in service counts the tasks that match the specified search criteria for tasks with indexed task business data. Applies to tasks with task data that the HPSTRA module in Task Engine stores in an ElasticSearch store.
pub.task.taskclient:searchTasksFieldsIndexedHPSTRA	The built-in service retrieves a collection of task data fields from tasks that match the specified search criteria. Applies to tasks with task data that the HPSTRA module in Task Engine stores in an ElasticSearch store.
pub.task.taskclient:searchTasksIndexedHPSTRA	The built-in service retrieves tasks that match specified search criteria. Applies to tasks with task data that the HPSTRA module in Task Engine stores in an ElasticSearch store.

Changed Service	Description
pub.task:TaskSearchQuery	The document type now includes a new parameter, <code>SearchEngineType</code> , which enables you to select a specific search engine to execute the search query.
pub.task:TaskSearchQueryV2	The document type now includes a new parameter, <code>SearchEngineType</code> , which enables you to select a specific search engine to execute the search query.

Release 10.0

Changed Service	Description
pub.task.taskclient:getTaskComments	The built-in service now returns the name of the ID parameter in uppercase instead of in lowercase.

Release 9.10

Changed Service	Description
pub.task.taskclient:queueTask	The built-in service now accepts the task schedule details for a task instance to be added to Task Engine's queue.
pub.task.taskclient:updateTask	The built-in service now allows changes to the new taskScheduleDate parameter if a task instance is in scheduled state.
pub.task.taskclient:getTask	The built-in service now retrieves the task schedule date along with other details of a task instance.

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added Parameter	Description
task.events.use.default.calendar	Additional JVM parameter that enables or disables the use of the default My webMethods Server calendar for scheduled task events that do not use a specific business calendar. The default value is 'false' - Task Engine does not use the default My webMethods Server calendar when scheduling tasks.

Release 10.0

Removed Parameter	Replacement, if any
task.event.lightweight	The additional JVM parameter task.event.lightweight that was deprecated in a previous release is now removed.

Release 9.10

Added Parameter	Description
taskScheduleDate	The taskScheduleDate parameter has been added to: <ul style="list-style-type: none">pub.task:TaskInfopub.task:TaskQueueInfoTaskInfo model used by RESTful services

Changed Parameter	Description
Status	The pub.task:TaskInfo service and the TaskInfo model used by RESTful services have been updated to include the new "scheduled" status.

11.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

Release 10.3

Added API	Description
com.softwareag.mws.screens.BaseScreenClass	Class com.softwareag.mws.screens.BaseScreenClass added
com.softwareag.mws.screens.Constants	Class com.softwareag.mws.screens.Constants added
com.softwareag.mws.screens.MWSLoginLogoutScreen	Class com.softwareag.mws.screens.MWSLoginLogoutScreen added
com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen	Class com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen added
com.webmethods.bpm.process.impl.BpmProcess	Method 'protected void loadFromIS()' has been added
com.webmethods.bpm.process.impl.BpmProcessManager	Method 'public BpmProcessManager()' has been added
com.webmethods.bpm.process.impl.BpmProcessManager	Method 'public java.lang.String getDatasourceLibMode()' has been added
com.webmethods.bpm.process.impl.BpmProcessManagerIS	Class com.webmethods.bpm.process.impl.BpmProcessManagerIS added
com.webmethods.bpm.process.impl.db.common.LoadProcessStepsIS	Class com.webmethods.bpm.process.impl.db.common.LoadProcessStepsIS added
com.webmethods.caf.common.ServerCommon	Class com.webmethods.caf.common.ServerCommon added
com.webmethods.caf.common.XMLUtil	Method 'public javax.xml.parsers.DocumentBuilderFactory getBuilderFactory()' has been added
com.webmethods.caf.common.XMLUtil	Method 'public javax.xml.parsers.SAXParserFactory getSAXParserFactory()' has been added
com.webmethods.caf.common.XMLUtil	Method 'public org.xml.sax.XMLReader getXMLParser(java.lang.ClassLoader)' has been added
com.webmethods.caf.faces.application.CAFValueExpression	Method 'public java.lang.Object getCAFValue(javax.el.ELContext)' has been added

com.webmethods.caf.faces.data.object.ObjectMethodContentProvider: Method 'protected boolean isSessionExpired()' has been added

com.webmethods.caf.faces.data.task.TaskBusinessCalendarModel: Method 'protected com.webmethods.sc.calendar.IWorkdayCalendar getCalendarByID(java.lang.String)' has been added

com.webmethods.caf.faces.data.ws.wss.WSSContentProvider: Method 'protected boolean isSessionExpired()' has been added

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected java.lang.String convertViewId(javax.faces.context.FacesContext, java.lang.String)' has been added

com.webmethods.caf.faces.render.html.input.DateInputRenderer: Method 'protected java.lang.Object convertDate(javax.faces.context.FacesContext, javax.faces.component.UIComponent, java.lang.Object, boolean, boolean)' has been added

com.webmethods.caf.wsclient.util.WSClientUtil: Method 'public java.util.Map constructClientAPI(java.lang.Class, java.lang.String, java.lang.String)' has been added

com.webmethods.caf.wsclient.util.WSClientUtil: Method 'public void reloadResource(java.lang.Class)' has been added

com.webmethods.caf.wsclient.util.XSDDateFormatMWS: Class
com.webmethods.caf.wsclient.util.XSDDateFormatMWS added

com.webmethods.portal.bizPolicy.command.install.InstallBootstrapComponentsWithDependencies: Method 'protected boolean checkRealLocation(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.install.InstallBootstrapComponentsWithDependencies: Method 'protected java.lang.String getComponentRealLocation(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContent: Method 'protected boolean checkResourceExists(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS: Method 'protected java.io.InputStream getISTaskAppStream(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.impl.BootstrapPhase: Method 'protected void waitForOSGIServices()' has been added

com.webmethods.portal.jms.JMSPhaseProvider: Method 'protected void bindGlobalProvider(com.webmethods.portal.service.global.IGlobalProvider)' has been added

com.webmethods.portal.jms.JMSPhaseProvider: Method 'protected void bindRemoteEventDelivery(com.webmethods.portal.system.init.IInitializable)' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public com.webmethods.portal.service.meta2.IUserService getUserService()' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public com.webmethods.portal.service.meta2.thing.IThingID initializeUserWithResult(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.dir.impl.DirMechanicsUtils: Method 'public void

initializeUser(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.install.impl.BasicInstallMechanics: Method 'protected boolean checkNeedsComponent(java.util.List, java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.BasicInstallMechanics: Method 'protected java.lang.String getComponentLocationToRealLocation(java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.InstallResolver: Method 'public void init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.PortletInstallMechanics: Method 'protected com.webmethods.portal.service.portlet.info.IPortletInfo loadPortletInfo(java.lang.String)' has been added

com.webmethods.portal.mech.install.impl.UpgradeInstallComponentData: Method 'protected java.lang.String getComponentLocationToRealLocation(java.lang.String)' has been added

com.webmethods.portal.mech.portlet.IPortletProviderMechanics: Method 'public com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream, java.io.InputStream)' has been added to an interface

com.webmethods.portal.mech.portlet.impl.PortletProviderMechanics: Method 'public com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream, java.io.InputStream)' has been added

com.webmethods.portal.mech.portlet.impl.PortletProviderMechanics: Method 'public void init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.socialbpm.comments.impl.CommentsMechanics: Method 'public com.webmethods.portal.service.meta2.thing.IThingID getThingID(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.mech.sql.impl.ConnectionManagerMechanicsIS: Class
com.webmethods.portal.mech.sql.impl.ConnectionManagerMechanicsIS added

com.webmethods.portal.mech.task.ITaskHelper: Method 'public com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added to an interface

com.webmethods.portal.mech.task.impl.TaskChangeHandler: Method 'public TaskChangeHandler()' has been added

com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS: Method 'public void ensureTaskLwqFileExist(java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskCompletionHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskCompletionHandlerIS added

com.webmethods.portal.mech.task.impl.TaskHelper: Method 'public com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.mech.task.impl.TaskHelperService: Method 'public

com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.mech.task.impl.TaskMechanics: Method 'protected void
initHandlers(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskMechanicsIS: Method 'protected void
initHandlers(com.webmethods.portal.system.IComponentData, java.lang.String)' has been added

com.webmethods.portal.mech.task.impl.TaskScheduleHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskScheduleHandlerIS added

com.webmethods.portal.mech.task.impl.TaskTimedEventHandlerIS: Class
com.webmethods.portal.mech.task.impl.TaskTimedEventHandlerIS added

com.webmethods.portal.noodle.util.NoodleUtils: Method 'public boolean
isForceNewTab(com.webmethods.portal.service.view.IView)' has been added

com.webmethods.portal.service.dir.IDirPrincipal: Method 'public boolean isInitialized()' has been
added to an interface

com.webmethods.portal.service.dir.impl.DirSystem: Method 'public void
onSynchronousEvent(com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent)' has been added

com.webmethods.portal.service.install.impl.BaseInstallService: Method 'protected java.lang.String
getResourceLocation(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.service.install.impl.BaseInstallService: Method 'protected void
registerComponent(com.webmethods.portal.system.IInitializableComponentData, java.lang.String)
has been added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected
com.webmethods.portal.schema.wmportletapp.PortletType _loadPortletType(java.util.Map)' has been
added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected void
_doRegisterComponent(java.util.Map)' has been added

com.webmethods.portal.service.install.impl.PdpInstallService: Method 'protected void
_saveTempPortletInitData(java.util.Map)' has been added

com.webmethods.portal.service.meta2.util.ThingHelper: Class
com.webmethods.portal.service.meta2.util.ThingHelper added

com.webmethods.portal.service.portlet.IPortletProvider: Method 'public
com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream,
java.io.InputStream)' has been added to an interface

com.webmethods.portal.service.portlet.impl.PortletProvider: Method 'public
com.webmethods.portal.service.portlet.info.IPortletInfo getPortletInfo(java.io.InputStream,
java.io.InputStream)' has been added

com.webmethods.portal.service.socialbpm.comments.impl.CommentsServiceIS: Class
com.webmethods.portal.service.socialbpm.comments.impl.CommentsServiceIS added

com.webmethods.portal.service.sql.ISqlWorker: Method 'public void close()' has been added to an interface

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public boolean isCurrentlyInUse()' has been added

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public void close()' has been added

com.webmethods.portal.service.sql.runtime.base.CommentEntryUserDeleted: Class
com.webmethods.portal.service.sql.runtime.base.CommentEntryUserDeleted added

com.webmethods.portal.service.task.ITaskDefinition: Method 'public
com.softwareag.caf.shared.task.core.model.TaskDataDefTable getTaskDataTable()' has been added to an interface

com.webmethods.portal.service.task.ITaskSystem: Method 'public
com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added to an interface

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Method 'public boolean isHiddenUpdate()' has been added

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Method 'public void setHiddenUpdate(boolean)' has been added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Method 'public
java.net.URLClassLoader getTaskClassLoader(java.lang.String)' has been added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Method 'public void removeTaskClassLoader(java.lang.String)' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public
com.softwareag.caf.shared.task.core.model.TaskDataDefTable getTaskDataTable()' has been added

com.webmethods.portal.service.task.impl.TaskDistributionServiceIS: Class
com.webmethods.portal.service.task.impl.TaskDistributionServiceIS added

com.webmethods.portal.service.task.impl.TaskProcessAuditServiceIS: Class
com.webmethods.portal.service.task.impl.TaskProcessAuditServiceIS added

com.webmethods.portal.service.task.impl.TaskSystem: Method 'protected void
bindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been added

com.webmethods.portal.service.task.impl.TaskSystem: Method 'public
com.webmethods.portal.system.lock.IClusterLockingService getLockingService()' has been added

com.webmethods.portal.system.BaseComponent: Method 'protected void
bindGlobalProvider(com.webmethods.portal.service.global.IGlobalProvider)' has been added

com.webmethods.portal.system.PortalSystem: Method 'public boolean isTELlibrary()' has been added

com.webmethods.portal.system.init.impl.ClusterPhaseProvider: Method 'protected java.lang.String
getLocalConfigRootPath()' has been added

com.webmethods.portal.system.init.impl.ClusterPhaseProvider: Method 'protected void
initDbConnection()' has been added

com.webmethods.portal.system.lock.impl.LockKey: Class
com.webmethods.portal.system.lock.impl.LockKey added

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Method 'protected
java.lang.String checkTaskAppVersionIsUptodate(java.lang.String)' has been added

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Method 'protected void
fixOldTaskClasses(java.io.File, java.lang.String)' has been added

com.webmethods.rtl.locator.impl.ClassLocator: Method 'public ClassLocator(java.lang.String,
java.lang.String)' has been added

com.webmethods.rtl.tools.PrettyProperties\$NameValue: Class
com.webmethods.rtl.tools.PrettyProperties\$NameValue added

com.webmethods.rtl.tools.PrettyProperties: Class com.webmethods.rtl.tools.PrettyProperties added

com.webmethods.rtl.util.xml.XMLUtil: Method 'public java.lang.String toString(org.w3c.dom.Node,
int, boolean)' has been added

com.webmethods.caf.faces.portlet.PortletViewHandler: Added
com.sun.faces.application.view.MultiViewHandler to the list of superclasses

com.webmethods.caf.jcr.faces.data.query.PropertySearchTerm: Added protected field sRandom

com.webmethods.caf.wsclient.proxy.impl.WSClientDynamicProxy: Added public field
REMOVE_WSDL_FROM_GLUE_CACHE

com.webmethods.mws.acdl.GenerateAcdlForProject: Added public field OPTION_IS_TASK_ENGINE

com.webmethods.portal.bizPolicy.command.task.webservice.QueueTaskWS: Added protected field
DELAY_DEFAULT_VALUE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added
public field DB_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added
public field DB_ATTR_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added
public field LDAP_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added
public field LDAP_ATTR_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added
public field PROFILE_ATTRIBUTES_PROVIDER

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added
public field USER_INFORMATION_TITLE

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler: Added

public field USER_PROFILE_ATTR_TITLE

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_CUSTOM_HOSTS_PROP

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_DISABLED_PROP

com.webmethods.portal.framework.presentation.renderers.DefaultRenderer: Added public field CONTENT_SECURITY_POLICY_ENABLED

com.webmethods.portal.service.dir.impl.DirSystem: Added

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent\$ISynchronousListener to the set of implemented interfaces

com.webmethods.portal.service.sql.ISqlWorker: Added java.lang.AutoCloseable to the set of implemented interfaces

com.webmethods.portal.service.sql.core.BaseSqlWorker: Added java.lang.AutoCloseable to the set of implemented interfaces

com.webmethods.portal.service.sql.core.ConnectionManager: Added public field ORACLE_URL_PARSER_EXPRESSION_SERVICENAME

com.webmethods.portal.service.sql.core.ConnectionManager: Added public field ORACLE_URL_TEMPLATE_SERVICENAME

com.webmethods.portal.service.task.event.impl.TaskChangedEvent: Added protected field hiddenUpdate

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: Added public field TASK_ASSETS_HOME_PROP

com.webmethods.portal.system.PortalSystem: Added public field TASK_ENGINE_LIBRARY_MODE

com.webmethods.rtl.locator.impl.StreamLocatorFactory: Added public field TEMP_PROTOCOL

Removed API

Replacement, if any

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'public java.lang.Object getWrapped()' has been removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'public javax.faces.application.ViewHandler getWrapped()' has been removed

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource: Method 'protected java.util.List getProfileAttributes(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.service.dir.IDirPrincipal)' has been removed

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS: Method 'protected com.webmethods.portal.system.IURI importNode(com.webmethods.portal.bizPolicy.IContext, org.w3c.dom.Element, com.webmethods.portal.system.IURI, java.util.List)' has been removed, but an inherited definition exists.

com.webmethods.portal.event.impl.RemoteEventDeliveryInitializer: Method 'protected void bindJMSPHaseProvider(com.webmethods.portal.system.IComponent)' has been removed

com.webmethods.portal.framework.mech.install.PortletAppilcationInstallMechanics: Method 'protected void clearContextRequestAttributes(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.mech.task.ITaskHelper: Method 'public com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been removed

com.webmethods.portal.mech.task.impl.TaskHelperService: Method 'public com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been removed

com.webmethods.portal.mech.task.impl.TaskMechanicsIS: Method 'protected com.webmethods.portal.service.task.ITaskList listTasks(com.webmethods.portal.system.IURI, com.webmethods.portal.service.task.TaskSearchQuery, boolean, boolean)' has been removed, but an inherited definition exists.

com.webmethods.portal.service.task.ITaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has been removed

com.webmethods.portal.service.task.ITaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' has been removed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader: Class com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has been removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' has been removed

com.webmethods.portal.service.task.impl.TaskLockingService: Method 'public long getDbTimeOffset()' has been removed

com.webmethods.portal.system.lock.impl.ClusterLockingService: Method 'public long getDbTimeOffset()' has been removed

com.webmethods.rtl.util.PrettyProperties\$NameValue: Class com.webmethods.rtl.util.PrettyProperties\$NameValue removed

com.webmethods.rtl.util.PrettyProperties: Class com.webmethods.rtl.util.PrettyProperties removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed field wrapped

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed javax.faces.FacesWrapper from the set of implemented interfaces

com.webmethods.caf.faces.portlet.PortletViewHandler: Removed
javax.faces.application.ViewHandlerWrapper from the list of superclasses

com.webmethods.caf.jcr.faces.data.query.PropertySearchTerm: Removed field random

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field
MIN_INBOX_SEARCH_THREADS

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field
MIN_TASK_UPDATE_THREADS

Deprecated API

Replacement, if any

com.webmethods.portal.mech.task.impl.TaskHelper: Method 'public
com.webmethods.portal.service.task.ITaskLockingService getTaskLockingService()' has been
deprecated

com.webmethods.portal.service.sql.ISqlWorker: Method 'public void release()' has been deprecated

com.webmethods.portal.service.sql.core.BaseSqlWorker: Method 'public void release()' has been
deprecated

Changed API

Description

com.webmethods.caf.faces.component.output.ChartDataColumn: Parameter 1 of 'public void
setItemValue(java.lang.Number)' has changed its type to java.lang.Object

com.webmethods.caf.faces.component.output.ChartDataColumn: Return type of method 'public
java.lang.Number getItemValue()' has been changed to java.lang.Object

com.webmethods.caf.faces.portlet.PortletViewHandler: In method 'public
PortletViewHandler(javax.faces.application.ViewHandler)' the number of arguments has changed

com.webmethods.caf.faces.render.html.input.DateInputRenderer: In method 'protected void
writeTimeZone(javax.faces.context.FacesContext, javax.faces.component.UIComponent, java.util.Date)
the number of arguments has changed

com.webmethods.portal.mech.task.impl.TaskMechanics: In method 'public void
fireTaskChangedEvent(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI,
com.webmethods.portal.service.task.ITask, com.webmethods.portal.service.task.ITask,
java.lang.Object, java.lang.Object, int, boolean)' the number of arguments has changed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: In method 'public java.lang.Object
getTaskInstance(java.lang.String)' the number of arguments has changed

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory: In method 'public void
addTaskClassLoader(com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLo
ader)' the number of arguments has changed

com.webmethods.portal.system.lock.IClusterLockingService: In method 'public
com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI,
com.webmethods.portal.system.IURI, long, long, boolean)' the number of arguments has changed

com.webmethods.portal.system.lock.IClusterLockingService: Parameter 2 of 'public

com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to long

com.webmethods.portal.system.lock.IClusterLockingService: Parameter 4 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to boolean

com.webmethods.portal.system.lock.impl.ClusterLockingService: In method 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)' the number of arguments has changed

com.webmethods.portal.system.lock.impl.ClusterLockingService: Parameter 2 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to long

com.webmethods.portal.system.lock.impl.ClusterLockingService: Parameter 4 of 'public com.webmethods.portal.system.lock.IClusterLock acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)' has changed its type to boolean

com.webmethods.rtl.util.xml.XMLUtil: In method 'protected void _dumpXML(org.w3c.dom.Node, java.io.Writer, int, int)' the number of arguments has changed

Release 10.2

Added API	Description
com.softwareag.mws.screens.BaseScreenClass	Class com.softwareag.mws.screens.BaseScreenClass added
com.softwareag.mws.screens.Constants	Class com.softwareag.mws.screens.Constants added
com.softwareag.mws.screens.MWSLoginLogoutScreen	Class com.softwareag.mws.screens.MWSLoginLogoutScreen added
com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen	Class com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen added
com.webmethods.caf.common.cipher.MWSCipherDataStore	Class com.webmethods.caf.common.cipher.MWSCipherDataStore added
com.webmethods.caf.common.cipher.MWSCipherMasterPassword	Class com.webmethods.caf.common.cipher.MWSCipherMasterPassword added
com.webmethods.caf.common.cipher.SecretDS	Class com.webmethods.caf.common.cipher.SecretDS added
com.webmethods.caf.faces.component.util.ShadowComponentMapCacheEntry	Class com.webmethods.caf.faces.component.util.ShadowComponentMapCacheEntry added
com.webmethods.caf.faces.data.attachments.BasePortalContainerAttachmentsProvider	Method 'public

java.lang.String getEncoding(java.lang.String)' has been added

com.webmethods.caf.faces.data.comments.impl.CommentsListProvider Method 'public com.webmethods.portal.service.access.IAclManager createAclManager(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskAuditBizPolicy Method 'public java.util.Collection getWebServiceCommands(com.webmethods.portal.bizPolicy.IContext)' has been added

com.webmethods.portal.bizPolicy.command.IJSONAdapter Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added to an interface

com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, java.util.Map)' has been added to an interface

com.webmethods.portal.bizPolicy.command.alias.SetThingAliases Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.alias.IAliasMechanics, com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource Method 'protected java.util.List getProfileAttributes(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.service.dir.IDirPrincipal)' has been added

com.webmethods.portal.bizPolicy.command.dir.rs.BasePrincipalResource Method 'public javax.ws.rs.core.Response getPersonalData(javax.servlet.http.HttpServletRequest, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.dir.rs.DirJSONAdapter Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandBean Method 'protected java.text.SimpleDateFormat getSDF()' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandBean Method 'protected java.text.SimpleDateFormat getSDFDotNet()' has been added

com.webmethods.portal.bizPolicy.command.impl.JSONAdapterFactory Method 'public java.util.Map getSchemaFields(java.lang.Class, java.util.Map, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.AbstractJSONAdapter Class
com.webmethods.portal.bizPolicy.command.impl.rs.AbstractJSONAdapter added

com.webmethods.portal.bizPolicy.command.impl.rs.BaseRestResource Method 'protected java.lang.String sanitizeMessage(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BaseRestResource Method 'protected javax.ws.rs.core.Response sendException(javax.servlet.http.HttpServletRequest, java.lang.Exception,

java.lang.String, int)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'protected
com.webmethods.portal.service.view.IView getView(com.webmethods.portal.system.IURI)' has been
added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'protected void
addIfNotSetAndNonNullValue(java.lang.String, java.lang.Object, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BasicJSONAdapter Method 'public java.util.Map
getSchemaFields(java.lang.Class, java.util.Map,
com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.BizPolicyResource Class
com.webmethods.portal.bizPolicy.command.impl.rs.BizPolicyResource added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandDocBuilder Class
com.webmethods.portal.bizPolicy.command.impl.rs.CommandDocBuilder added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource Method 'public
javax.ws.rs.core.Response getCommandSpecification(javax.servlet.http.HttpServletRequest,
javax.servlet.http.HttpServletResponse, java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource Method 'public
javax.ws.rs.core.Response getSpecification(javax.servlet.http.HttpServletRequest)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.ConnectionInfoJSONAdapter Method 'public
java.util.Map getSchemaFields(java.lang.Class, java.util.Map,
com.webmethods.portal.bizPolicy.command.IJSONAdapterFactory, java.util.Map)' has been added

com.webmethods.portal.bizPolicy.command.impl.rs.DefaultJSONAdapter Class
com.webmethods.portal.bizPolicy.command.impl.rs.DefaultJSONAdapter added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentList Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentList added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentMap added

com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentOrderedMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.FluentOrderedMap added

com.webmethods.portal.bizPolicy.command.impl.rs.util.IFluentMap Class
com.webmethods.portal.bizPolicy.command.impl.rs.util.IFluentMap added

com.webmethods.portal.bizPolicy.command.page.ModifyPage2IS Class
com.webmethods.portal.bizPolicy.command.page.ModifyPage2IS added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS Class
com.webmethods.portal.bizPolicy.command.system.xml.XMLImportContextIS added

com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS Class
com.webmethods.portal.bizPolicy.command.system.xml.XMLImportIncludeIS added

com.webmethods.portal.bizPolicy.command.task.rs.TaskJSONAdapter Class
com.webmethods.portal.bizPolicy.command.task.rs.TaskJSONAdapter added

com.webmethods.portal.bizPolicy.command.task.webservice.UpdateTaskAttachmentWS\$updateTaskAttachmentCommandBean Method 'protected boolean excludePropertyDescriptor(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.task.webservice.UpdateTaskAttachmentWS\$updateTaskAttachmentCommandBean Method 'public void setAttachmentID(java.lang.String)' has been added

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public com.webmethods.portal.service.meta2.thing.IThingID getGetDirectoryServiceThingID()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public com.webmethods.portal.system.IURI getDirectoryURI()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public java.lang.String getEmail()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalDeleteEvent Method 'public java.lang.String getPrincipalDN()' has been added to an interface

com.webmethods.portal.event.dir.IDirPrincipalModifyEvent Method 'public java.lang.Object getPropertyOldValue()' has been added to an interface

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public DirPrincipalDeleteEvent(com.webmethods.portal.service.dir.IDirPrincipal, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public com.webmethods.portal.service.meta2.thing.IThingID getGetDirectoryServiceThingID()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public com.webmethods.portal.system.IURI getDirectoryURI()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public com.webmethods.portal.system.IURI getPrincipalURI()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public java.lang.String getEmail()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalDeleteEvent Method 'public java.lang.String getPrincipalDN()' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public DirPrincipalModifyEvent(com.webmethods.portal.system.IURI,

com.webmethods.portal.service.meta2.thing.IThingID, java.lang.String, java.lang.Object, java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public DirPrincipalModifyEvent(com.webmethods.portal.system.IURI, java.lang.String, java.lang.Object, java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.event.dir.impl.DirPrincipalModifyEvent Method 'public java.lang.Object getPropertyOldValue()' has been added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$IListener Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$IListener added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$ISynchronousListener Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$ISynchronousListener added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$Listeners Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$Listeners added

com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$SynchronousListeners Class
com.webmethods.portal.event.system.IDistributedConfigChangedEvent\$SynchronousListeners added

com.webmethods.portal.event.system.impl.DistributedConfigChangedEvent Class
com.webmethods.portal.event.system.impl.DistributedConfigChangedEvent added

com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler Class
com.webmethods.portal.framework.dispatch.handlers.directory.ExportUserAttributesHandler added

com.webmethods.portal.framework.session.handlers.LoginScript Method 'protected void bindSystemPolicy(com.webmethods.portal.bizPolicy.biz.system.ISystemPolicy)' has been added

com.webmethods.portal.framework.session.handlers.Validate Method 'protected void bindJMSPhaseProvider(com.webmethods.portal.system.IComponent)' has been added

com.webmethods.portal.framework.session.impl.SessionManager Method 'protected void bindAuthManager(com.webmethods.portal.framework.IAuthManager)' has been added

com.webmethods.portal.jms.db.impl.db2.PurgeEvents Method 'protected java.lang.String getDeleteEventsQuery()' has been added

com.webmethods.portal.jms.um.UmJMSConnProvider Method 'protected void registerJMSObjects(org.w3c.dom.Element)' has been added

com.webmethods.portal.mech.dir.IDirServiceMechanics Method 'public void fireDeletePrincipalEvent(com.webmethods.portal.service.dir.IDirPrincipal, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList)' has been added to an interface

com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics Method 'public void fireModifyPrincipalEvent(com.webmethods.portal.service.meta2.thing.IThingID,

com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID, java.lang.String, java.lang.Object, java.lang.Object)' has been added to an interface

com.webmethods.portal.mech.dir.impl.DirServiceMechanics Method 'protected boolean isUserPrivacyEnabled()' has been added

com.webmethods.portal.mech.dir.impl.DirServiceMechanics Method 'public void fireDeletePrincipalEvent(com.webmethods.portal.service.dir.IDirPrincipal, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList)' has been added

com.webmethods.portal.mech.dir.impl.PrincipalAttributeMechanics Method 'public void fireModifyPrincipalEvent(com.webmethods.portal.service.meta2.thing.IThingID, com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID, java.lang.String, java.lang.Object, java.lang.Object)' has been added

com.webmethods.portal.mech.rules.impl.TEELContext Class
com.webmethods.portal.mech.rules.impl.TEELContext added

com.webmethods.portal.mech.rules.impl.TEEExpressionResolver Class
com.webmethods.portal.mech.rules.impl.TEEExpressionResolver added

com.webmethods.portal.mech.schedule.impl.ScheduleMechanicsIS Class
com.webmethods.portal.mech.schedule.impl.ScheduleMechanicsIS added

com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS Class
com.webmethods.portal.mech.task.impl.TaskChangeHandlerIS added

com.webmethods.portal.mech.task.impl.TaskContextHelper Class
com.webmethods.portal.mech.task.impl.TaskContextHelper added

com.webmethods.portal.mech.task.impl.TaskDataHelper Method 'public java.lang.Object[] resolveTaskFields(com.webmethods.portal.service.task.ITask, com.webmethods.portal.service.task.ITaskData, java.lang.String[])' has been added

com.webmethods.portal.mech.task.impl.TaskMechanics Method 'protected void bindMechanicsManager(com.webmethods.portal.mech.IMechanicsManager)' has been added

com.webmethods.portal.mech.task.impl.TaskMechanicsIS Class
com.webmethods.portal.mech.task.impl.TaskMechanicsIS added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public TaskRuleContext(com.webmethods.caf.rules.IRuleContext, java.util.Map)' has been added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public java.util.Map getContextMap()' has been added

com.webmethods.portal.mech.task.impl.TaskRuleContext Method 'public void setContextMap(java.util.Map)' has been added

com.webmethods.portal.service.access.IAclManager Method 'public void setResourceType(java.lang.String)' has been added to an interface

com.webmethods.portal.service.access.IAclManager Method 'public void setUserID(java.lang.String)' has been added to an interface

com.webmethods.portal.service.cache.ICacheManager Method 'public void configureCache(java.lang.String, java.util.Map)' has been added to an interface

com.webmethods.portal.service.cache.impl.CacheManager Method 'protected java.util.Collection getRegistryBasedComponentCollection()' has been added

com.webmethods.portal.service.cache.impl.CacheManager Method 'protected void configureCacheFromRegisrty(java.lang.String)' has been added

com.webmethods.portal.service.cache.impl.CacheManager Method 'public void configureCache(java.lang.String, java.util.Map)' has been added

com.webmethods.portal.service.dir.IDirCache Method 'public void clearQueryCache()' has been added to an interface

com.webmethods.portal.service.dir.IDirServiceThing Class
com.webmethods.portal.service.dir.IDirServiceThing added

com.webmethods.portal.service.dir.IUserPrivacyService Class
com.webmethods.portal.service.dir.IUserPrivacyService added

com.webmethods.portal.service.dir.IUserPrivacyService\$NotificationType Class
com.webmethods.portal.service.dir.IUserPrivacyService\$NotificationType added

com.webmethods.portal.service.dir.impl.DirCache Method 'public void clearQueryCache()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected com.webmethods.portal.service.dir.IDirPrincipal getCurrentDirPrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected com.webmethods.portal.service.meta2.thing.IThingID getCurrentPrincipalThingID()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected long getCreatedTime()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected long getLastModifiedTime()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'protected void deletePrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean canDeleteUser()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean isEditingSelf(com.webmethods.portal.bizPolicy.IContext)' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean isMemberOfAdminRole()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean isSysAdminPrincipal()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public boolean isUserPrivacyEnabled()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean Method 'public void DeleteUser()' has been added

com.webmethods.portal.service.portlet.impl.PortletProvider Method 'protected void bindThingIDService(com.webmethods.portal.service.meta2.IThingIDService)' has been added

com.webmethods.portal.service.portlet.impl.PortletProvider Method 'protected void bindXTypeService(com.webmethods.portal.service.meta2.IXTypeService)' has been added

com.webmethods.portal.service.scheduler.Scheduler Method 'protected void bindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been added

com.webmethods.portal.service.scheduler.Scheduler Method 'protected void unbindClusterLockingService(com.webmethods.portal.system.lock.IClusterLockingService)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.service.meta2.thing.IThingID getThingIDHelper(com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI getURIHelper(java.lang.String)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI lookupPrincipalHelper(java.lang.Object)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public com.webmethods.portal.system.IURI lookupPrincipalHelper(java.lang.Object, int)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public int getIntPriorityHelper(java.lang.String)' has been added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter Method 'public int getIntStatusHelper(java.lang.String)' has been added

com.webmethods.portal.service.task.TaskSearchQuery Method 'public boolean matches(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)' has been added

com.webmethods.portal.service.task.TaskSearchQueryTerm Method 'public boolean matches(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)' has been added

com.webmethods.portal.service.task.TaskSearchQueryTerm Method 'public java.util.List getFieldExpressionsString(java.util.Map, com.webmethods.caf.rules.IBindingExpressionEvaluator)' has been added

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory Class

com.webmethods.portal.service.task.impl.TaskClassLoaderFactory added
com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader Class
com.webmethods.portal.service.task.impl.TaskClassLoaderFactory\$ITaskClassLoader added
com.webmethods.portal.service.task.impl.TaskDBIndexManagerHelper Class
com.webmethods.portal.service.task.impl.TaskDBIndexManagerHelper added
com.webmethods.portal.service.task.impl.TaskIndexTableViewHelper Class
com.webmethods.portal.service.task.impl.TaskIndexTableViewHelper added
com.webmethods.portal.service.task.impl.TaskService Method 'public void
flushTaskInfoCache(com.webmethods.portal.system.IURI)' has been added
com.webmethods.portal.service.task.impl.TaskServiceIS Class
com.webmethods.portal.service.task.impl.TaskServiceIS added
com.webmethods.portal.service.task.impl.TaskSystem Method 'protected
com.webmethods.portal.system.IComponentData
createComponentData(com.webmethods.portal.system.IInitializableComponentData)' has been added
com.webmethods.portal.service.task.impl.TaskSystem Method 'protected java.util.Collection
getThingBasedComponentCollection()' has been added
com.webmethods.portal.system.PortalSystem Method 'public java.lang.Boolean isLibraryMode()' has
been added
com.webmethods.portal.webservices.SOAPMonitorConstants Class
com.webmethods.portal.webservices.SOAPMonitorConstants added
com.webmethods.portal.webservices.SOAPMonitorData Method 'public
SOAPMonitorData(java.lang.Integer, java.lang.Long, java.lang.String, java.lang.String,
java.lang.String)' has been added
com.webmethods.portal.webservices.SOAPMonitorData Method 'public java.lang.String
getContentTypes()' has been added
com.webmethods.portal.webservices.SOAPMonitorData Method 'public java.lang.String
getMessageText()' has been added
com.webmethods.portal.webservices.SOAPMonitorData Method 'public void
setContentTypes(java.lang.String)' has been added
com.webmethods.portal.webservices.SOAPMonitorData Method 'public void
setMessageText(java.lang.String)' has been added
com.webmethods.rtl.locator.impl.DBConfigLocator Method 'protected void
fireConfigChangedEvent(java.lang.String)' has been added
com.webmethods.rtl.util.FileUtil Method 'public java.lang.String
getRealLocationAtIS(java.lang.String)' has been added
com.webmethods.rtl.util.FileUtil Method 'public java.lang.String
getRealLocationAtISatTaskApp(java.lang.String, java.lang.String)' has been added

Removed API**Replacement, if any**

com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public org.apache.axis.description.ServiceDesc initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext, org.apache.axis.description.ServiceDesc)' has been removed

com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public org.apache.axis.handlers.soap.SOAPService initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed

com.webmethods.portal.bizPolicy.biz.impl.BizPolicy Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.access.GetAcView Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.access.ListSecurityRealmObjects Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.alias.CreateAlias Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.dir.GetTypedAttributes Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.dir.GetTypedAttributes Method 'public void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'protected java.beans.PropertyDescriptor[] getClassPropertyDescriptors(java.lang.Class)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'protected void registerWebServiceMarshallingFactories(java.lang.Class, javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public java.lang.Class[] getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public org.apache.axis.description.ServiceDesc initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext,

org.apache.axis.description.ServiceDesc)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public
org.apache.axis.handlers.soap.SOAPService
initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed

com.webmethods.portal.bizPolicy.command.impl.Command Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.impl.WebServiceHelper Class
com.webmethods.portal.bizPolicy.command.impl.WebServiceHelper removed

com.webmethods.portal.bizPolicy.command.meta.GetSelectedList Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListChildrenFiltered Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListContainers Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.ListNotes Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.meta.schedule.ListSchedulesCommand Method 'public
void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.page.ModifyPage2 Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.socialkeyword.GetKeyword Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.socialkeyword.ListKeywords Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.sql.ListDataSources Method 'public java.lang.Class[]
getExtraWsdlSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.sql.ListDataSources Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.system.ImportFiles Class
com.webmethods.portal.bizPolicy.command.system.ImportFiles removed

com.webmethods.portal.bizPolicy.command.system.ImportFilesBean Class
com.webmethods.portal.bizPolicy.command.system.ImportFilesBean removed

com.webmethods.portal.bizPolicy.command.system.Ping Method 'public java.lang.Class[]
getExtraWsdSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.bizPolicy.command.system.Ping Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus Method 'public
java.lang.Class[] getExtraWsdSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been
removed

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.task.BaseTaskCommand Method 'protected
java.beans.PropertyDescriptor[] getClassPropertyDescriptors(java.lang.Class)' has been removed

com.webmethods.portal.bizPolicy.command.task.GetTaskAudit Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.task.GetTaskAuditPaginated Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.version.ListVersionsCommand Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.command.webspace.ListWebSpaces Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.bizPolicy.impl.ContextProvider Method 'protected
com.webmethods.portal.bizPolicy.IContext getContextBySessionId(java.lang.String)' has been removed

com.webmethods.portal.framework.dispatch.handlers.webservices.GetWSDL Class
com.webmethods.portal.framework.dispatch.handlers.webservices.GetWSDL removed

com.webmethods.portal.framework.propertyeditor.command.ListPropertyEditors Method 'public
void initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public java.lang.Class[]
getExtraWsdSchemaClasses(com.webmethods.portal.bizPolicy.IContext)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public
org.apache.axis.description.ServiceDesc
initializeServiceDesc(com.webmethods.portal.bizPolicy.IContext,
org.apache.axis.description.ServiceDesc)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public
org.apache.axis.handlers.soap.SOAPService
initializeSOAPService(org.apache.axis.handlers.soap.SOAPService)' has been removed

com.webmethods.portal.webservices.IWebService Method 'public void
initializeSOAPMappingRegistry(com.webmethods.portal.bizPolicy.IContext,
javax.xml.rpc.encoding.TypeMapping)' has been removed

com.webmethods.portal.webservices.SOAPMonitorData Method 'public java.lang.String getSoap()' has been removed

com.webmethods.portal.webservices.SOAPMonitorData Method 'public void
setSoap(java.lang.String)' has been removed

com.webmethods.portal.webservices.configuration.MwsEngineConfigurationFactoryServlet Class
com.webmethods.portal.webservices.configuration.MwsEngineConfigurationFactoryServlet removed

com.webmethods.portal.webservices.configuration.MwsFileProvider Class
com.webmethods.portal.webservices.configuration.MwsFileProvider removed

com.webmethods.portal.webservices.configuration.UpgradeAxisConfiguration Class
com.webmethods.portal.webservices.configuration.UpgradeAxisConfiguration removed

com.webmethods.portal.webservices.encoding.AliasValueSerializer Class
com.webmethods.portal.webservices.encoding.AliasValueSerializer removed

com.webmethods.portal.webservices.encoding.AliasValueSerializerFactory Class
com.webmethods.portal.webservices.encoding.AliasValueSerializerFactory removed

com.webmethods.portal.webservices.encoding.BeanPropertiesTypeDesc Class
com.webmethods.portal.webservices.encoding.BeanPropertiesTypeDesc removed

com.webmethods.portal.webservices.encoding.CertificateSerializer Class
com.webmethods.portal.webservices.encoding.CertificateSerializer removed

com.webmethods.portal.webservices.encoding.CertificateSerializerFactory Class
com.webmethods.portal.webservices.encoding.CertificateSerializerFactory removed

com.webmethods.portal.webservices.encoding.CharacterSerializer Class
com.webmethods.portal.webservices.encoding.CharacterSerializer removed

com.webmethods.portal.webservices.encoding.CharacterSerializerFactory Class
com.webmethods.portal.webservices.encoding.CharacterSerializerFactory removed

com.webmethods.portal.webservices.encoding.ConnectionInfoSerializer Class
com.webmethods.portal.webservices.encoding.ConnectionInfoSerializer removed

com.webmethods.portal.webservices.encoding.ConnectionInfoSerializerFactory Class

com.webmethods.portal.webservices.encoding.ConnectionInfoSerializerFactory removed
com.webmethods.portal.webservices.encoding.DifferenceMapSerializer Class
com.webmethods.portal.webservices.encoding.DifferenceMapSerializer removed
com.webmethods.portal.webservices.encoding.DifferenceMapSerializerFactory Class
com.webmethods.portal.webservices.encoding.DifferenceMapSerializerFactory removed
com.webmethods.portal.webservices.encoding.DirServiceSerializer Class
com.webmethods.portal.webservices.encoding.DirServiceSerializer removed
com.webmethods.portal.webservices.encoding.DirServiceSerializerFactory Class
com.webmethods.portal.webservices.encoding.DirServiceSerializerFactory removed
com.webmethods.portal.webservices.encoding.IDataDeserializer Class
com.webmethods.portal.webservices.encoding.IDataDeserializer removed
com.webmethods.portal.webservices.encoding.IDataDeserializerFactory Class
com.webmethods.portal.webservices.encoding.IDataDeserializerFactory removed
com.webmethods.portal.webservices.encoding.IOutOnly Class
com.webmethods.portal.webservices.encoding.IOutOnly removed
com.webmethods.portal.webservices.encoding.ISoapComplexTypeBean Class
com.webmethods.portal.webservices.encoding.ISoapComplexTypeBean removed
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializer Class
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializer removed
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializerFactory Class
com.webmethods.portal.webservices.encoding.InterfaceAsBeanSerializerFactory removed
com.webmethods.portal.webservices.encoding.ListViewSerializer Class
com.webmethods.portal.webservices.encoding.ListViewSerializer removed
com.webmethods.portal.webservices.encoding.ListViewSerializerFactory Class
com.webmethods.portal.webservices.encoding.ListViewSerializerFactory removed
com.webmethods.portal.webservices.encoding.LocaleDeserializer Class
com.webmethods.portal.webservices.encoding.LocaleDeserializer removed
com.webmethods.portal.webservices.encoding.LocaleDeserializerFactory Class
com.webmethods.portal.webservices.encoding.LocaleDeserializerFactory removed
com.webmethods.portal.webservices.encoding.LocaleSerializer Class
com.webmethods.portal.webservices.encoding.LocaleSerializer removed
com.webmethods.portal.webservices.encoding.LocaleSerializerFactory Class
com.webmethods.portal.webservices.encoding.LocaleSerializerFactory removed
com.webmethods.portal.webservices.encoding.PageDataDeserializer Class
com.webmethods.portal.webservices.encoding.PageDataDeserializer removed
com.webmethods.portal.webservices.encoding.PageDataDeserializerFactory Class

com.webmethods.portal.webservices.encoding.PageDataDeserializerFactory removed
com.webmethods.portal.webservices.encoding.PageDataSerializer Class
com.webmethods.portal.webservices.encoding.PageDataSerializer removed
com.webmethods.portal.webservices.encoding.PageDataSerializerFactory Class
com.webmethods.portal.webservices.encoding.PageDataSerializerFactory removed
com.webmethods.portal.webservices.encoding.PagingBeanDeserializer Class
com.webmethods.portal.webservices.encoding.PagingBeanDeserializer removed
com.webmethods.portal.webservices.encoding.PagingBeanDeserializerFactory Class
com.webmethods.portal.webservices.encoding.PagingBeanDeserializerFactory removed
com.webmethods.portal.webservices.encoding.PagingBeanSerializer Class
com.webmethods.portal.webservices.encoding.PagingBeanSerializer removed
com.webmethods.portal.webservices.encoding.PagingBeanSerializerFactory Class
com.webmethods.portal.webservices.encoding.PagingBeanSerializerFactory removed
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializer Class
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializer removed
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializerFactory Class
com.webmethods.portal.webservices.encoding.PortalFileBeanDeserializerFactory removed
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializer Class
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializer removed
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializerFactory Class
com.webmethods.portal.webservices.encoding.PortalFileBeanSerializerFactory removed
com.webmethods.portal.webservices.encoding.RightSetDeserializer Class
com.webmethods.portal.webservices.encoding.RightSetDeserializer removed
com.webmethods.portal.webservices.encoding.RightSetDeserializerFactory Class
com.webmethods.portal.webservices.encoding.RightSetDeserializerFactory removed
com.webmethods.portal.webservices.encoding.RightSetSerializer Class
com.webmethods.portal.webservices.encoding.RightSetSerializer removed
com.webmethods.portal.webservices.encoding.RightSetSerializerFactory Class
com.webmethods.portal.webservices.encoding.RightSetSerializerFactory removed
com.webmethods.portal.webservices.encoding.SelectedListViewSerializer Class
com.webmethods.portal.webservices.encoding.SelectedListViewSerializer removed
com.webmethods.portal.webservices.encoding.SelectedListViewSerializerFactory Class
com.webmethods.portal.webservices.encoding.SelectedListViewSerializerFactory removed
com.webmethods.portal.webservices.encoding.ThingIDListSerializer Class
com.webmethods.portal.webservices.encoding.ThingIDListSerializer removed
com.webmethods.portal.webservices.encoding.ThingIDListSerializerFactory Class

com.webmethods.portal.webservices.encoding.ThingIDListSerializerFactory removed
 com.webmethods.portal.webservices.encoding.ThingNameAtomSerializer Class
 com.webmethods.portal.webservices.encoding.ThingNameAtomSerializer removed
 com.webmethods.portal.webservices.encoding.ThingNameAtomSerializerFactory Class
 com.webmethods.portal.webservices.encoding.ThingNameAtomSerializerFactory removed
 com.webmethods.portal.webservices.encoding.URIDeserializer Class
 com.webmethods.portal.webservices.encoding.URIDeserializer removed
 com.webmethods.portal.webservices.encoding.URIDeserializerFactory Class
 com.webmethods.portal.webservices.encoding.URIDeserializerFactory removed
 com.webmethods.portal.webservices.encoding.URISerializer Class
 com.webmethods.portal.webservices.encoding.URISerializer removed
 com.webmethods.portal.webservices.encoding.URISerializerFactory Class
 com.webmethods.portal.webservices.encoding.URISerializerFactory removed
 com.webmethods.portal.webservices.encoding.ViewProperty Class
 com.webmethods.portal.webservices.encoding.ViewProperty removed
 com.webmethods.portal.webservices.encoding.ViewSerializer Class
 com.webmethods.portal.webservices.encoding.ViewSerializer removed
 com.webmethods.portal.webservices.encoding.ViewSerializerFactory Class
 com.webmethods.portal.webservices.encoding.ViewSerializerFactory removed
 com.webmethods.portal.webservices.handlers.CommandHandler Class
 com.webmethods.portal.webservices.handlers.CommandHandler removed
 com.webmethods.portal.webservices.handlers.CommandProvider Class
 com.webmethods.portal.webservices.handlers.CommandProvider removed
 com.webmethods.portal.webservices.handlers.SOAPMonitorHandler Class
 com.webmethods.portal.webservices.handlers.SOAPMonitorHandler removed
 com.webmethods.portal.webservices.servlet.PortalAxisServlet Class
 com.webmethods.portal.webservices.servlet.PortalAxisServlet removed

Changed API	Description
com.webmethods.portal.bizPolicy.command.dir.DeletePrincipal com.webmethods.portal.bizPolicy.command.dir.ModifyPrincipal	In method 'protected void fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IDirServiceMechanics, com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList)' the number of arguments has changed

fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics, com.webmethods.portal.system.IURI, java.lang.String, java.lang.Object, com.webmethods.portal.service.meta2.thing.IThingID)' the number of arguments has changed

com.webmethods.portal.bizPolicy.command.dir.ModifyPrincipalEx In method 'protected void fireEvents(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IPrincipalAttributeMechanics, com.webmethods.portal.system.IURI, java.util.Map, com.webmethods.portal.service.meta2.thing.IThingID)' the number of arguments has changed

com.webmethods.portal.bizPolicy.command.impl.rs.CommandResource In method 'public javax.ws.rs.core.Response invokeCommandFromForm(javax.servlet.http.HttpServletRequest, javax.servlet.http.HttpServletResponse, java.lang.String)' the number of arguments has changed

Release 10.1

Added API	Description
<code>com.webmethods.portal.bizPolicy.biz.dir.IDirSystemBizPolicy</code>	Method 'public
<code>com.webmethods.portal.service.dir.IDirUser</code>	
<code>authenticateUser(com.webmethods.portal.bizPolicy.IContext, java.lang.String, java.lang.String, boolean)</code>	' has been added to an interface
<code>com.webmethods.portal.framework.IAuthManager</code>	Method 'public
<code>com.webmethods.portal.framework.auth.IAuthInfo</code>	<code>createAuthInfo()</code> has been added to an interface
<code>com.webmethods.portal.service.task.ITaskDistributionService</code>	Method 'public
<code>com.webmethods.portal.service.task.ITaskListIterator</code>	
<code>searchAllTasks(com.webmethods.portal.service.task.TaskSearchQuery, java.lang.Boolean)</code>	' has been added to an interface
<code>com.webmethods.portal.service.task.ITaskLockingService</code>	Method 'public
<code>com.webmethods.portal.system.lock.IClusterLock</code>	<code>acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long)</code> has been added to an interface
<code>com.webmethods.portal.service.task.ITaskLockingService</code>	Method 'public
<code>com.webmethods.portal.system.lock.IClusterLock</code>	<code>acquireLock(com.webmethods.portal.system.IURI, com.webmethods.portal.system.IURI, long, long, boolean)</code> has been added to an interface
<code>com.webmethods.portal.service.task.ITaskLockingService</code>	Method 'public
<code>com.webmethods.portal.system.lock.IClusterLock</code>	<code>getLock(com.webmethods.portal.system.IURI)</code> has been added to an interface
<code>com.webmethods.portal.system.IURIResolver</code>	Method 'public <code>com.webmethods.portal.system.IURI</code>
<code>acquireURI(java.lang.String, boolean)</code>	' has been added to an interface
<code>com.webmethods.portal.system.init.IPhaseProvider</code>	Method 'public void <code>preInit(java.lang.String)</code> has been added to an interface
<code>com.webmethods.portal.webservices.IWebService</code>	Method 'public <code>java.lang.Class[]</code>
<code>getExtraWsdlschemaClasses(com.webmethods.portal.bizPolicy.IContext)</code>	' has been added to an interface

Removed API**Replacement, if any**

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo: Removed
com.webmethods.caf.faces.data.task.IQueryAggregationInfo from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxIndexedSearchContentProvider\$InboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxSearchContentProvider\$InboxSearchQuery: Removed com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskIndexedSearchContentProvider\$TaskData: Removed
com.webmethods.caf.faces.data.task.ITaskData from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskConstants from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQuery from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryBase from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.portal.mech.task.impl.TaskQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Removed
com.webmethods.portal.system.init.IInitializable from the set of implemented interfaces

com.webmethods.portal.socialbpm.charts.SocialBPMSearchQuery: Removed
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended from the set of implemented interfaces

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed
com.webmethods.caf.faces.data.task.impl.TaskSearchQuery from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearchQuery: Removed
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2 from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.impl.TaskSearchQuery from the list of superclasses

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Removed
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2 from the list of superclasses

com.webmethods.caf.mobile.notify.impl.PushNotification: Removed
com.webmethods.portal.system.impl.BaseComponent from the list of superclasses

com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean: Removed
com.webmethods.rtl.util.obj.MapPropertyBag from the list of superclasses

com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean: Removed
com.webmethods.rtl.util.obj.MapPropertyBag from the list of superclasses

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus: Removed
com.webmethods.portal.system.impl.BaseComponent from the list of superclasses

com.webmethods.rtl.locator.ClassLocator: Removed com.webmethods.rtl.locator.FileLocator from the list of superclasses

com.webmethods.rtl.util.SystemPaths\$UserPathLocator: Removed
com.webmethods.rtl.locator.FileLocator from the list of superclasses

com.webmethods.caf.mobile.notify.task.APNSCleanUpThread: Removed field expiredID

com.webmethods.portal.service.portlet.impl.PortletProvider: Removed field
portletProviderFactoryServiceReg

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field
TASK_LOCK_MAX_TIME

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field
TASK_LOCK_MAX_WAIT_TIME

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field dbOffsetLastCalced

com.webmethods.portal.service.task.impl.TaskLockingService: Removed field dbTimeOffsetMs

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm findTerm(java.lang.String,
java.lang.String)' has been removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm findTerm(java.lang.String)' has been
removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.IQueryAggregationInfo getQueryAggregationInfo()' has been
removed

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Method 'public
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm[] getTerms()' has been removed

com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider: Method 'protected
java.util.Collection loadConfig(com.webmethods.portal.system.IComponentData)' has been removed

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void
includeBCScript(java.lang.String, java.util.Locale, java.io.Writer, boolean)' has been removed

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void stripBCScript(java.io.Reader,
java.io.Writer)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_sep_for_bc(int)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_unambiguous_sep_for_bc(int)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'public void stripBCScript(java.io.Reader, java.io.Writer)' has been removed

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected int strip_c_comment_for_bc(java.io.Reader, java.io.Writer)' has been removed

com.webmethods.portal.framework.auth.AuthInfo: Method 'public void copy(com.webmethods.portal.framework.auth.AuthInfo)' has been removed

com.webmethods.portal.framework.presentation.PresentationData: Method 'public com.webmethods.portal.framework.presentation.PresentationData init(java.lang.Object, int, java.util.HashMap)' has been removed

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Method 'public void init(com.webmethods.portal.system.IComponentData, java.lang.String)' has been removed

com.webmethods.portal.service.sql.core.JNDIDataSourceFactory: Method 'public void shutdown()' has been removed

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool: Method 'public void initialize(com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager, java.util.Map)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public javax.servlet.ServletContext getServletContext(java.lang.String)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public org.eclipse.jetty.webapp.WebAppContext getWebAppContext(java.lang.String)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void refreshBundle(org.osgi.framework.Bundle)' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void refreshRemovalPendingBundles()' has been removed

com.webmethods.rtl.util.RuntimeUtil: Method 'public void startBundle(org.osgi.framework.Bundle)' has been removed

com.webmethods.caf.faces.data.task.AggregationType: Class
com.webmethods.caf.faces.data.task.AggregationType removed

com.webmethods.caf.faces.data.task.IQueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.IQueryAggregationInfo removed

com.webmethods.caf.faces.data.task.IndexEngineType: Class
com.webmethods.caf.faces.data.task.IndexEngineType removed

com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider: Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider removed

com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher: Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestPingInfo: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestPingInfo removed

com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestResource: Class
com.webmethods.portal.bizPolicy.command.task.rs.RestApplication\$RestResource removed

com.webmethods.portal.framework.presentation.handlers.djsp.FlexiblePoolBoy: Class
com.webmethods.portal.framework.presentation.handlers.djsp.FlexiblePoolBoy removed

com.webmethods.rtl.locator.BundleLocator: Class com.webmethods.rtl.locator.BundleLocator removed

com.webmethods.rtl.locator.ClusterConfigLocator: Class
com.webmethods.rtl.locator.ClusterConfigLocator removed

com.webmethods.rtl.locator.ConfigLocator: Class com.webmethods.rtl.locator.ConfigLocator removed

com.webmethods.rtl.locator.FileLocator: Class com.webmethods.rtl.locator.FileLocator removed

com.webmethods.rtl.locator.NullLocator: Class com.webmethods.rtl.locator.NullLocator removed

com.webmethods.rtl.locator.StreamLocatorFactory: Class
com.webmethods.rtl.locator.StreamLocatorFactory removed

com.webmethods.rtl.locator.WebResourceLocator: Class
com.webmethods.rtl.locator.WebResourceLocator removed

Release 10.0

Added API	Description
<code>com.webmethods.caf.faces.data.task.impl.TaskInboxIndexedSearchContentProvider\$InboxSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskInboxSearchContentProvider\$InboxSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskSearchQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.faces.data.task.impl.TaskSearchQueryV2</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider</code>	Added <code>com.webmethods.portal.event.modify.IUpdateEvent\$ISynchronousListener</code> to the set of implemented interfaces
<code>com.webmethods.caf.mobile.notify.task.NotificationSender</code>	Added <code>java.util.concurrent.Callable</code> to the set of implemented interfaces
<code>com.webmethods.portal.mech.task.impl.TaskQuery</code>	Added <code>com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAll</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllByTagCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllByTagPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllGroupedCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchAllPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxes</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesByTagCount</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces
<code>com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesByTagPaged</code>	Added <code>com.webmethods.portal.service.task.ITaskInfoFieldConverters</code> to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesCount: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesGroupedCount: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesPaged: Added
com.webmethods.portal.service.task.ITaskInfoFieldConverters to the set of implemented interfaces

com.webmethods.portal.socialbpm.charts.SocialBPMSearchQuery: Added
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended to the set of implemented interfaces

com.webmethods.caf.faces.render.html.table.MoveRowDownIconRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowDownLinkRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowUpIconRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.caf.faces.render.html.table.MoveRowUpLinkRenderer: Added
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer to the list of superclasses

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Added
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper to the list of superclasses

com.webmethods.caf.common.deployer.MwsDeployerConstants: Added public field
PROJ_PROP_EXPORT_PAGE_DEPTH

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field IOS_CERT

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_HOST_NAME

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_HOST_PORT

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
IOS_PASSWORD

com.webmethods.caf.mobile.notify.IMobileNotificationConstants: Added public field
NOTIFIER_QUEUE_SIZE_THRESHOLD

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Added protected field
m_connPoolProvider

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Added public field
IOS_JASON_PAYLOAD_TEMPLATE

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field
PROPERTY_HPSTRA_INDEXTABLEDIS

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field

PROPERTY_HPSTRA_INDEX_JOB_STATUS

com.webmethods.portal.bizPolicy.biz.task.ITaskDefinitionConstants: Added public field
PROPERTY_ISHPSTRAENABLED

com.webmethods.portal.bizPolicy.command.task.rs.BaseTaskResource: Added public field
DEFAULT_JSON_DATE_FORMAT

com.webmethods.portal.service.bcgadget.IBCGadgetConstants: Added public field
BC_GADGET_DEF_CONTAINER_NOT_FOUND_ERROR_MSG

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field
ATTR_PREFIX_LENGTH

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field
EDIT_ATTR_CURRPASSWORD

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field USERNAME

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Added public field exceptionMessage

com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Added public field
TE_MAX_LAST_ACTIVE

com.webmethods.portal.service.task.impl.TaskDefinitionView: Added protected field
m_taskDetailGadgetURIs

com.webmethods.caf.common.ObjectUtil: Method 'public void sortObjectList(java.util.List,
java.lang.String, boolean)' has been added

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Method 'public boolean
isPropagateEvents()' has been added

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Method 'public void
setPropagateEvents(boolean)' has been added

com.webmethods.caf.faces.component.tree.AsyncTree: Method 'protected
com.webmethods.caf.faces.data.ITableContentProvider getContentProvider(boolean)' has been added

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Method 'public java.lang.String
getSearchEngineType()' has been added

com.webmethods.caf.faces.data.task.impl.TaskSearchQuery: Method 'public void
setSearchEngineType(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider: Method 'public void
onSynchronousEvent(com.webmethods.portal.event.modify.IUpdateEvent)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public
com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails
getM_iOSConnectionDetails()' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public
java.util.concurrent.BlockingQueue getMessageQueue()' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public java.util.List scheduleCleanUpService(java.util.List)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public void setMessageQueue(java.util.concurrent.BlockingQueue)' has been added

com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent: Method 'public void stopExecutorService()' has been added

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Method 'public java.lang.String createMessage(com.webmethods.portal.service.task.event.ITaskChangedEvent)' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public java.util.List getAndroidSubscriptionList()' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public java.util.List getIOSSubscriptionList()' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public void setAndroidSubscriptionList(java.util.List)' has been added

com.webmethods.caf.mobile.notify.task.Message: Method 'public void setIOSSubscriptionList(java.util.List)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public java.util.List call()' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public java.lang.Object call()' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] convertPayloadtoUTF8Bytes(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] decodeHex(java.lang.String)' has been added

com.webmethods.caf.mobile.notify.task.NotificationSender: Method 'public byte[] formAPNSMessage(byte, byte[], byte[])' has been added

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Method 'public java.lang.String generateIOSPayload(java.util.List, java.lang.String, java.lang.String)' has been added

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void includeBCScript(java.lang.String, java.util.Locale, java.io.Writer, boolean)' has been added

com.webmethods.caf.script.servlet.ScriptServlet: Method 'protected void stripBCScript(java.io.Reader, java.io.Writer)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_sep_for_bc(int)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected boolean is_unambiguous_sep_for_bc(int)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'public void stripBCScript(java.io.Reader, java.io.Writer)' has been added

com.webmethods.caf.script.util.JavascriptStripper: Method 'protected int strip_c_comment_for_bc(java.io.Reader, java.io.Writer)' has been added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable createHpstraIndexTableFromXml(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.task.rs.TaskResource: Method 'public void convertJSONToJavaObj(java.util.Map, java.lang.Class)' has been added

com.webmethods.portal.framework.presentation.handlers.Nbsp: Method 'public java.lang.Object lookup(java.util.Map, java.lang.String, boolean)' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalListView: Method 'public java.util.Map getExceptions()' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalListView: Method 'public void setExceptions(java.util.Map)' has been added

com.webmethods.portal.service.dir.impl.DirPrincipalProvider: Method 'protected void populateGroupMembership(com.webmethods.portal.service.dir.IDirPrincipal, java.util.Set, java.util.Map)' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'protected void EditPrincipalEx()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public void EditUserEx()' has been added

com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public boolean isAuthenticated(java.lang.String, java.lang.String)' has been added

com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Method 'protected java.lang.String getConditionalInsertStatement()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable getHpstraIndexTable()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public java.lang.String getTaskDetailGadgetURIs()' has been added

com.webmethods.portal.service.task.impl.TaskDefinitionView: Method 'public boolean isHpstraEnabled()' has been added

com.webmethods.portal.system.cluster.impl.ClusterProvider: Method 'public void reloadClusterServers()' has been added

com.webmethods.portal.webapp.jetty7.MwsSessionManager: Method 'protected void addContextLocale(org.eclipse.jetty.server.session.AbstractSession)' has been added

com.webmethods.rtl.event.DeliveryService: Method 'public boolean isConfigLoaded()' has been added

com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics\$NameComparator: Method 'public int compare(com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics, com.webmethods.rtl.msg.jms.JMSDestination\$LiveStatistics)' has been added

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected boolean isMaintenanceMode()' has been added

com.webmethods.rtl.script.nbsp.NBSPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.NBSPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.Object get(java.lang.String, java.lang.Class, java.lang.Object, boolean)' has been added

com.webmethods.rtl.script.nbsp.PooledNBSPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails getM_iOSConnectionDetails()' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public java.util.concurrent.BlockingQueue getMessageQueue()' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public java.util.List scheduleCleanUpService(java.util.List)' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public void setMessageQueue(java.util.concurrent.BlockingQueue)' has been added to an interface

com.webmethods.caf.mobile.notify.IMobileNotifierComponent: Method 'public void stopExecutorService()' has been added to an interface

com.webmethods.common.search.ISliceableSearchContext: Method 'public java.util.Map getExceptions()' has been added to an interface

com.webmethods.portal.mech.task.ITaskMechanics: Method 'public void fireTaskReindexStopEvent(com.webmethods.portal.service.task.ITaskDefinition, java.lang.String)' has been added to an interface

com.webmethods.portal.service.dir.IDirPrincipalList: Method 'public java.util.Map getExceptions()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public com.webmethods.portal.service.meta2.dbo.HpstraIndexTable getHpstraIndexTable()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public java.lang.String

getTaskDetailGadgetURIs()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public boolean isHpstraEnabled()' has been added to an interface

com.webmethods.portal.service.task.ITaskDistributionService: Method 'public java.util.List getPrincipalActors(com.webmethods.portal.system.IURI[], boolean)' has been added to an interface

com.webmethods.portal.service.task.event.ITaskReindexStopEvent: Method 'public java.lang.String getIndexEngineType()' has been added to an interface

com.webmethods.portal.system.cluster.IClusterProvider: Method 'public void reloadClusterServers()' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPRuntime: Method 'public java.lang.Object lookup(java.util.Map, java.lang.String, boolean)' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPPage: Method 'public java.lang.Object get(java.lang.String, boolean)' has been added to an interface

com.webmethods.rtl.script.nbsp.INBSPPage: Method 'public java.lang.String getString(java.lang.String, java.lang.String, boolean)' has been added to an interface

com.softwareag.mws.screens.BaseScreenClass: Class com.softwareag.mws.screens.BaseScreenClass added

com.softwareag.mws.screens.Constants: Class com.softwareag.mws.screens.Constants added

com.softwareag.mws.screens.MWSLoginLogoutScreen: Class
com.softwareag.mws.screens.MWSLoginLogoutScreen added

com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen: Class
com.softwareag.mws.screens.applications.administration.systemwide.usermanagement.UsersScreen added

com.webmethods.caf.faces.data.task.AggregationType: Class
com.webmethods.caf.faces.data.task.AggregationType added

com.webmethods.caf.faces.data.task.IQueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.IQueryAggregationInfo added

com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended: Class
com.webmethods.caf.faces.data.task.ITaskSearchQueryExtended added

com.webmethods.caf.faces.data.task.IndexEngineType: Class
com.webmethods.caf.faces.data.task.IndexEngineType added

com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo: Class
com.webmethods.caf.faces.data.task.impl.QueryAggregationInfo added

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider: Class
com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider added

com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearch
Query: Class
com.webmethods.caf.faces.data.task.impl.TaskInboxHpstraSearchContentProvider\$HpstraInboxSearch
Query added

com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended: Class
com.webmethods.caf.faces.data.task.impl.TaskSearchQueryExtended added

com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer: Class
com.webmethods.caf.faces.render.html.table.MoveRowLinkRenderer added

com.webmethods.caf.mobile.notify.impl.PushNotification: Class
com.webmethods.caf.mobile.notify.impl.PushNotification added

com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean: Class
com.webmethods.caf.mobile.notify.impl.PushNotification\$PushNotificationCommandBean added

com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpEvent: Class
com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpEvent added

com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpHandler: Class
com.webmethods.caf.mobile.notify.impl.SubscriptionCleanUpHandler added

com.webmethods.caf.mobile.notify.task.APNSCleanUpThread: Class
com.webmethods.caf.mobile.notify.task.APNSCleanUpThread added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper\$DBIndexer: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper\$DBIndexer added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper added

com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper\$Indexer: Class
com.webmethods.portal.bizPolicy.biz.task.impl.TaskIndexHelper\$Indexer added

com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeStatusBean added

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus added

com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus\$StatusInfo: Class
com.webmethods.portal.bizPolicy.command.system.RuntimeTimeStatus\$StatusInfo added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource: Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$Product: Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$Product added

com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$ProductHolder:
Class
com.webmethods.portal.bizPolicy.command.task.rs.LayeredProductVerionResource\$ProductHolder

added

com.webmethods.portal.jms.um.QueueType: Class com.webmethods.portal.jms.um.QueueType added

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable: Class

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable added

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable\$DisplayField: Class

com.webmethods.portal.service.meta2.dbo.HpstraIndexTable\$DisplayField added

com.webmethods.portal.service.sql.runtime.base.TaskPendingUpdatesCleanup: Class

com.webmethods.portal.service.sql.runtime.base.TaskPendingUpdatesCleanup added

com.webmethods.portal.service.sql.runtime.db2.TaskLockSetNew: Class

com.webmethods.portal.service.sql.runtime.db2.TaskLockSetNew added

com.webmethods.portal.service.sql.runtime.db2.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.db2.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.mssql.ThingNewPar: Class

com.webmethods.portal.service.sql.runtime.mssql.ThingNewPar added

com.webmethods.portal.service.sql.runtime.mssql.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.mssql.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.mysql.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.mysql.UpdateThingCounter added

com.webmethods.portal.service.sql.runtime.oracle.TaskLockSetNew: Class

com.webmethods.portal.service.sql.runtime.oracle.TaskLockSetNew added

com.webmethods.portal.service.sql.runtime.oracle.UpdateThingCounter: Class

com.webmethods.portal.service.sql.runtime.oracle.UpdateThingCounter added

com.webmethods.portal.service.task.ITaskIndexEngineConfiguration: Class

com.webmethods.portal.service.task.ITaskIndexEngineConfiguration added

com.webmethods.portal.service.task.ITaskIndexManager: Class

com.webmethods.portal.service.task.ITaskIndexManager added

com.webmethods.portal.service.task.ITaskInfoFieldConverters: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$AcceptedByListValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$AcceptedByListValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$CurrentUserValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$CurrentUserValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$DateValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$DateValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter: Class

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$FieldValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$PriorityValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$PriorityValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$StatusValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$StatusValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskIDValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskIDValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskTypeIDValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$TaskTypeIDValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$URIValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$URIValueConverter added

com.webmethods.portal.service.task.ITaskInfoFieldConverters\$UserValueConverter: Class
com.webmethods.portal.service.task.ITaskInfoFieldConverters\$UserValueConverter added

com.webmethods.portal.service.task.SearchContext: Class
com.webmethods.portal.service.task.SearchContext added

com.webmethods.portal.service.task.SearchKey: Class com.webmethods.portal.service.task.SearchKey
added

com.webmethods.portal.service.task.SearchKey\$TE_SearchKeys: Class
com.webmethods.portal.service.task.SearchKey\$TE_SearchKeys added

com.webmethods.portal.service.task.TaskIndexEngineFactory: Class
com.webmethods.portal.service.task.TaskIndexEngineFactory added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$DistributionChangeType:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$DistributionChangeType
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$IListener: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$IListener added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$ISynchronousListener:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$ISynchronousListener
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$Listeners: Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$Listeners added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners:
Class
com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners
added

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners\$SynchronousListener: Class

com.webmethods.portal.service.task.event.ITaskDistributionChangedEvent\$SynchronousListeners\$SynchronousListener added

com.webmethods.portal.service.task.event.impl.TaskDistributionChangedEvent: Class

com.webmethods.portal.service.task.event.impl.TaskDistributionChangedEvent added

com.webmethods.portal.service.task.event.impl.TaskReindexStopEvent: Class

com.webmethods.portal.service.task.event.impl.TaskReindexStopEvent added

com.webmethods.portal.service.task.impl.TaskDBIndexConfiguration: Class

com.webmethods.portal.service.task.impl.TaskDBIndexConfiguration added

com.webmethods.portal.system.cluster.impl.ClusterNodeRegisteredNotifier: Class

com.webmethods.portal.system.cluster.impl.ClusterNodeRegisteredNotifier added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool: Class

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPool added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager: Class

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionPoolManager added

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionProvider: Class

com.webmethods.pushNotification.apns.connection.pool.APNSConnectionProvider added

com.webmethods.pushNotification.apns.connection.pool.APNSPoolableConnection: Class

com.webmethods.pushNotification.apns.connection.pool.APNSPoolableConnection added

com.webmethods.pushNotification.apns.connection.pool.IConnectionProvider: Class

com.webmethods.pushNotification.apns.connection.pool.IConnectionProvider added

com.webmethods.pushNotification.apns.connection.pool.IPoolableConnection: Class

com.webmethods.pushNotification.apns.connection.pool.IPoolableConnection added

Removed API**Replacement, if any**

com.webmethods.caf.mobile.notify.task.NotificationSender: Removed java.lang.Runnable from the set of implemented interfaces

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_ACCEPTED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_CANCELLED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_COMPLETED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_EXPIRED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_FAILED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_QUEUED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_REASSIGNED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_RELEASED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_RESUMED

com.webmethods.caf.mobile.notify.impl.TaskEventsHandler: Removed field OPERATION_SUSPENDED

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Removed field reindexAllTaskExecutor

com.webmethods.portal.bizPolicy.biz.task.impl.TaskDBOHelper: Removed field reindexingTasks

com.webmethods.portal.mech.task.impl.TaskMechanics: Removed field USE_LIGHT_WEIGHT_EVENTS

Deprecated API**Replacement, if any**

com.webmethods.portal.service.task.impl.TaskDistributionService: Method 'public java.util.List getPrincipalActors(com.webmethods.portal.system.IURI[], boolean)' has been deprecated

com.webmethods.portal.service.task.impl.TaskDistributionService: Method 'protected java.util.List returnPagedTaskList(java.lang.String, java.lang.Object[], boolean)' has been deprecated

Changed API**Description**

com.webmethods.caf.mobile.notify.impl.AppleMessagingCloudConnectionDetails: Increased visibility of class from package to public

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Value of compile-time constant ANDROID_JASON_PAYLOAD_TEMPLATE has been changed

com.webmethods.caf.faces.bean.BaseFacesBean: Accessibility of field EMPTY_RESOURCES has been increased from package to public

com.webmethods.caf.mobile.notify.task.NotificationSender: In method 'public NotificationSender(java.util.concurrent.BlockingQueue, com.sun.jersey.api.client.WebResource\$Builder)' the number of arguments has changed

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: In method 'public com.webmethods.caf.mobile.notify.task.Message generatePayload(java.util.List, java.lang.String, java.lang.String)' the number of arguments has changed

com.webmethods.portal.jms.um.UmJMSClient: In method 'protected void createQueue(java.lang.String, boolean, int)' the number of arguments has changed

com.webmethods.portal.jms.um.UmJMSClient: In method 'protected void createTopic(java.lang.String, boolean, int)' the number of arguments has changed

com.webmethods.portal.mech.task.impl.TaskMechanics: In method 'public void fireTaskReindexStopEvent(com.webmethods.portal.service.task.ITaskDefinition)' the number of arguments has changed

com.webmethods.caf.mobile.notify.util.MobileNotifierUtil: Return type of method 'public com.webmethods.caf.mobile.notify.task.Message generateAndroidPayload(java.util.List, java.lang.String, java.lang.String)' has been changed to java.lang.String

com.webmethods.portal.jms.db.DbJMSConnProvider: Accessibility of method 'public DbJMSConnProvider()' has been decreased from public to private

Release 9.12**Added API****Description**

com.webmethods.caf.common.thread.NamedThreadFactory: Method 'public NamedThreadFactory(java.lang.String, boolean)' has been added

com.webmethods.caf.faces.bean.mws_ui.HtmlHead: Method 'public java.lang.String getEffectsJS()' has been added

com.webmethods.caf.faces.convert.FormattedDateTimeConverter: Added protected field dateFormatDefault

com.webmethods.caf.faces.data.object.DateRange: Added protected field controlCalendar

com.webmethods.caf.faces.data.object.DateRange: Method 'protected java.util.Calendar

Added API	Description
getControlCalendar(javax.faces.context.FacesContext)	' has been added
com.webmethods.caf.faces.data.object.DateRange:	Method 'public void setControlCalendar(java.util.Calendar)' has been added
com.webmethods.caf.mobile.notify.IMobileNotificationConstants:	Class
com.webmethods.caf.mobile.notify.IMobileNotificationConstants	added
com.webmethods.caf.mobile.notify.IMobileNotificationProvider:	Class
com.webmethods.caf.mobile.notify.IMobileNotificationProvider	added
com.webmethods.caf.mobile.notify.IMobileNotifierComponent:	Class
com.webmethods.caf.mobile.notify.IMobileNotifierComponent	added
com.webmethods.caf.mobile.notify.activator.MobileNotificationActivator:	Class
com.webmethods.caf.mobile.notify.activator.MobileNotificationActivator	added
com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider:	Class
com.webmethods.caf.mobile.notify.impl.MobileNotificationProvider	added
com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent:	Class
com.webmethods.caf.mobile.notify.impl.MobileNotifierComponent	added
com.webmethods.caf.mobile.notify.impl.TaskEventsHandler:	Class
com.webmethods.caf.mobile.notify.impl.TaskEventsHandler	added
com.webmethods.caf.mobile.notify.task.Message:	Class
com.webmethods.caf.mobile.notify.task.Message	added
com.webmethods.caf.mobile.notify.task.MonitorPendingNotificationMessages:	Class
com.webmethods.caf.mobile.notify.task.MonitorPendingNotificationMessages	added
com.webmethods.caf.mobile.notify.task.NotificationSender:	Class
com.webmethods.caf.mobile.notify.task.NotificationSender	added
com.webmethods.caf.mobile.notify.util.MobileNotifierUtil:	Class
com.webmethods.caf.mobile.notify.util.MobileNotifierUtil	added
com.webmethods.caf.wssserver.auth.saml.SamlUtils:	Method 'public org.w3c.dom.Element marshalSamlObject(org.opensaml.xml.XMLObject)' has been added
com.webmethods.caf.wssserver.auth.saml.SamlUtils:	Method 'public org.opensaml.xml.XMLObject unmarshalElement(org.w3c.dom.Element)' has been added
com.webmethods.portal.bizPolicy.biz.dir.IGroupBizPolicy:	Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy:	Added to the set of implemented interfaces
com.webmethods.portal.bizPolicy.biz.dir.IPrincipalBizPolicy:	Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy:	Added to the set of implemented interfaces

Added API**Description**

com.webmethods.portal.bizPolicy.biz.dir.IUserBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.dir.impl.GroupBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.dir.impl.GroupBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses

com.webmethods.portal.bizPolicy.biz.dir.impl.PrincipalBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.dir.impl.PrincipalBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses

com.webmethods.portal.bizPolicy.biz.dir.impl.UserBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.IViewableContainerPolicy to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.dir.impl.UserBizPolicy: Added
com.webmethods.portal.bizPolicy.biz.view.impl.ViewableContainerPolicy to the list of superclasses

com.webmethods.portal.bizPolicy.biz.task.impl.TaskInfo: Added java.io.Serializable to the set of implemented interfaces

com.webmethods.portal.bizPolicy.biz.task.impl.TaskInfoExtended: Added java.io.Serializable to the set of implemented interfaces

com.webmethods.portal.bizPolicy.command.ICommandManager: Method 'public com.webmethods.portal.bizPolicy.command.IRemoteCommandTransport getRemoteCommandTransport(java.lang.String)' has been added to an interface

com.webmethods.portal.bizPolicy.command.ICommandManager: Method 'public java.util.List invokeClusterCommand(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.bizPolicy.command.ICommand, com.webmethods.portal.bizPolicy.command.ICommandBean)' has been added to an interface

com.webmethods.portal.bizPolicy.command.ICommandResponseEntry: Class
com.webmethods.portal.bizPolicy.command.ICommandResponseEntry added

com.webmethods.portal.bizPolicy.command.dir.GetPortalStyle: Method 'protected void checkAccess(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.mech.dir.IPrincipalMechanics, com.webmethods.portal.system.IURI)' has been added

com.webmethods.portal.bizPolicy.command.dir.SearchDirectory: Method 'protected void

Added API**Description**

checkAccess(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.mech.dir.IDirServiceMechanics,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryEx: Method 'protected void
checkAccess(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.mech.dir.IDirServiceMechanics,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryRefined: Method 'protected void
checkAccess(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.mech.dir.IDirServiceMechanics,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.bizPolicy.command.dir.SearchDirectoryRefinedPaged: Method 'protected
void checkAccess(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.mech.dir.IDirServiceMechanics,
com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandManager: Method 'public
com.webmethods.portal.bizPolicy.command.IRemoteCommandTransport
getRemoteCommandTransport(java.lang.String)' has been added

com.webmethods.portal.bizPolicy.command.impl.CommandManager: Method 'public java.util.List
invokeClusterCommand(com.webmethods.portal.bizPolicy.IContext,
com.webmethods.portal.bizPolicy.command.ICommand,
com.webmethods.portal.bizPolicy.command.ICommandBean)' has been added

com.webmethods.portal.bizPolicy.command.remote.RemoteCommand: Class
com.webmethods.portal.bizPolicy.command.remote.RemoteCommand added

com.webmethods.portal.bizPolicy.command.remote.RemoteCommandBean: Class
com.webmethods.portal.bizPolicy.command.remote.RemoteCommandBean added

com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport: Class
com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport added

com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport\$RemoteJmsE
xception: Class

com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteCommandTransport\$RemoteJmsE
xception added

com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteTransaction: Class
com.webmethods.portal.bizPolicy.command.remote.jms.JmsRemoteTransaction added

com.webmethods.portal.bizPolicy.command.system.JndiRefreshCluster: Class

Added API**Description**

com.webmethods.portal.bizPolicy.command.system.JndiRefreshCluster added

com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommand: Class

com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommand added

com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommandBean: Class

com.webmethods.portal.bizPolicy.command.task.jms.AbstractTaskCommandBean added

com.webmethods.portal.bizPolicy.command.task.jms.AddTaskAttachmentJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.AddTaskAttachmentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.AddTaskCommentJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.AddTaskCommentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskAttachmentJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskAttachmentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskCommentJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskCommentJMS added

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.DeleteTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAttachmentsJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAttachmentsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAuditJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskAuditJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskCommentsJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskCommentsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.GetTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.QueueTaskJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.QueueTaskJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksFieldsJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksFieldsJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksPagedJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksPagedJMS added

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksTotalCountJMS: Class

com.webmethods.portal.bizPolicy.command.task.jms.SearchTasksTotalCountJMS added

com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskAttachmentJMS: Class

Added API	Description
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskAttachmentJMS	added
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskCommentJMS	Class
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskCommentJMS	added
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskJMS	Class
com.webmethods.portal.bizPolicy.command.task.jms.UpdateTaskJMS	added
com.webmethods.portal.bizPolicy.command.task.jms.impl.TaskJMSUtils	Class
com.webmethods.portal.bizPolicy.command.task.jms.impl.TaskJMSUtils	added
com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider	Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSCustomDispatchProvider	added
com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher	Class
com.webmethods.portal.bizPolicy.command.task.rs.MWSRequestDispatcher	added
com.webmethods.portal.bizPolicy.command.task.webservice.SearchTasksFieldsWS	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.task.webservice.SearchTasksWS	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.task.webservice.Task	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.task.webservice.dotnet.SearchTasksDotNetWS	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.command.task.webservice.dotnet.SearchTasksFieldsDotNetWS	Added
java.io.Serializable	to the set of implemented interfaces
com.webmethods.portal.bizPolicy.impl.upgrade.MoveVersionSystemComponentData	Class
com.webmethods.portal.bizPolicy.impl.upgrade.MoveVersionSystemComponentData	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ILListener	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ILListener	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ISynchronousListener	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$ISynchronousListener	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$Listeners	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$Listeners	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$QueueListeners	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$QueueListeners	added
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$SynchronousListeners	Class
com.webmethods.portal.event.dir.IDirPrincipalDNUpdateEvent\$SynchronousListeners	added

Added API	Description
com.webmethods.portal.event.dir.impl.DirPrincipalDNUpdateEvent	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$IListener	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$ISynchronousListener	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$Listeners	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$QueueListeners	Class added
com.webmethods.portal.event.sso.ISSODataChangeEvent\$SynchronousListeners	Class added
com.webmethods.portal.event.sso.impl.SSODataChangeEvent	Class added
com.webmethods.portal.framework.dispatch.handlers.system.SAMLSSOHandler	Class added
com.webmethods.portal.framework.dispatch.preProcessors.OpenRedirectCheck	Class added
com.webmethods.portal.framework.dispatch.resolvers.SAMLAuthReqResolver	Class added
com.webmethods.portal.framework.impl.PortalServlet	Added public field PORTAL_SERVLET_LOCK_OBJ
com.webmethods.portal.framework.portletcontainer.servlet.JettyPortletRequestWrapper	Method 'public org.eclipse.jetty.util.MultiMap getParameterMultiMap()' has been added
com.webmethods.portal.framework.portletcontainer.servlet.JettyPortletRequestWrapper	Method 'public java.util.Map getParameters()' has been added
com.webmethods.portal.jms.JMSPhaseProvider	Added com.webmethods.portal.system.IComponent to the set of implemented interfaces
com.webmethods.portal.jms.JMSPhaseProvider	Added com.webmethods.portal.system.IConstants to the set of implemented interfaces
com.webmethods.portal.jms.JMSPhaseProvider	Added com.webmethods.portal.system.impl.BaseComponent to the list of superclasses
com.webmethods.portal.jms.JMSPhaseProvider	Added public field COMPONENT_NAME

Added API	Description
com.webmethods.portal.jms.um.UmJMSSClient:	Added abstract modifier to class
com.webmethods.portal.jms.um.UmJMSSClient:	Added
com.webmethods.portal.system.init.IInitializable	to the set of implemented interfaces
com.webmethods.portal.jms.um.UmJMSSClient:	Added com.webmethods.rtl.msg.jms.IJMSPProvider to the set of implemented interfaces
com.webmethods.portal.jms.um.UmJMSSClient:	Added com.webmethods.rtl.msg.jms.JMSPProvider to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSClient:	Added
com.webmethods.rtl.msg.jms.JMSStdConnProvider	to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected boolean createInitialContext()' has been added
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected void registerFactory(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected void registerQueue(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected void registerTopic(org.w3c.dom.Element)' has been added
com.webmethods.portal.jms.um.UmJMSSClient:	Method 'protected void resetContext()' has been added
com.webmethods.portal.jms.um.UmJMSSConnProvider:	Added
com.webmethods.portal.jms.um.UmJMSSClient	to the list of superclasses
com.webmethods.portal.jms.um.UmJMSSConnProvider:	Method 'protected void onDisconnect(boolean)' has been added
com.webmethods.portal.jms.um.UmJMSSConnProvider:	Method 'public void onShutdown()' has been added
com.webmethods.portal.mech.dir.IDirServiceMechanics:	Method 'public java.util.List updatePrincipalUUID(int)' has been added to an interface
com.webmethods.portal.mech.dir.IGroupMechanics:	Added
com.webmethods.portal.mech.view.IViewableContainerMechanics	to the set of implemented interfaces
com.webmethods.portal.mech.dir.IPrincipalMechanics:	Added
com.webmethods.portal.mech.view.IViewableContainerMechanics	to the set of implemented interfaces
com.webmethods.portal.mech.dir.IRoleMechanics:	Added
com.webmethods.portal.mech.view.IViewableContainerMechanics	to the set of implemented interfaces
com.webmethods.portal.mech.dir.IUserMechanics:	Added
com.webmethods.portal.mech.view.IViewableContainerMechanics	to the set of implemented interfaces
com.webmethods.portal.mech.dir.impl.DirMechanicsUtils:	Method 'public java.lang.String

Added API**Description**

generateUUIDQuery(com.webmethods.portal.service.dir.IDirService, java.lang.String, int)' has been added

com.webmethods.portal.mech.dir.impl.DirServiceMechanics: Method 'public java.util.List updatePrincipalUUID(int)' has been added

com.webmethods.portal.mech.dir.impl.GroupMechanics: Added
com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces

com.webmethods.portal.mech.dir.impl.GroupMechanics: Added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses

com.webmethods.portal.mech.dir.impl.PrincipalMechanics: Added
com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces

com.webmethods.portal.mech.dir.impl.PrincipalMechanics: Added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses

com.webmethods.portal.mech.dir.impl.RoleMechanics: Added
com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces

com.webmethods.portal.mech.dir.impl.RoleMechanics: Added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses

com.webmethods.portal.mech.dir.impl.UserMechanics: Added
com.webmethods.portal.mech.view.IViewableContainerMechanics to the set of implemented interfaces

com.webmethods.portal.mech.dir.impl.UserMechanics: Added
com.webmethods.portal.mech.view.impl.ViewableContainerMechanics to the list of superclasses

com.webmethods.portal.mech.task.impl.RefreshTaskHandler: Class
com.webmethods.portal.mech.task.impl.RefreshTaskHandler added

com.webmethods.portal.mech.task.impl.TaskHelper: Method 'public java.lang.ClassLoader getClassLoaderIfExists(com.webmethods.portal.service.task.ITaskDefinition)' has been added

com.webmethods.portal.mech.view.impl.ViewableContainerMechanics: Method 'protected
com.webmethods.portal.service.view.IPagingCookie
createPagingCookie(com.webmethods.portal.service.meta2.thing.IThingID)' has been added

com.webmethods.portal.service.access.IAccessPrivilegeConfiguration: Class
com.webmethods.portal.service.access.IAccessPrivilegeConfiguration added

com.webmethods.portal.service.access.impl.DashboardAclManager: Class
com.webmethods.portal.service.access.impl.DashboardAclManager added

com.webmethods.portal.service.access.impl.DashboardAclManager\$DashboardAclResource: Class
com.webmethods.portal.service.access.impl.DashboardAclManager\$DashboardAclResource added

com.webmethods.portal.service.access.impl.DashboardContainerAclManager: Class
com.webmethods.portal.service.access.impl.DashboardContainerAclManager added

Added API	Description
com.webmethods.portal.service.access.impl.DashboardContainerAclManager\$DashboardContainerAclResource: Class	
com.webmethods.portal.service.access.impl.DashboardContainerAclManager\$DashboardContainerAclResource added	
com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'public java.util.Map getResultColumnMetadata()' has been added	
com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'public java.util.List searchResources(com.webmethods.caf.faces.search.query.ISearchQuery)' has been added	
com.webmethods.portal.service.access.impl.GadgetsAclManager\$GadgetAclResource: Method 'public java.lang.Object getValue(java.lang.Object)' has been added	
com.webmethods.portal.service.access.impl.WMAppsAclManager: Method 'public void addServiceTracker(org.osgi.framework.BundleContext)' has been added	
com.webmethods.portal.service.access.impl.WMAppsAclManager: Method 'public void stopServiceTracker()' has been added	
com.webmethods.portal.service.cache.impl.AliasCache: Added	com.webmethods.portal.event.remove.IDeleteEvent\$ISynchronousListener to the set of implemented interfaces
com.webmethods.portal.service.cache.impl.AliasCache: Method 'public void onSynchronousEvent(com.webmethods.portal.event.remove.IDeleteEvent)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Added public field UUIDUserResolution	
com.webmethods.portal.service.dir.DirectoryTools: Added protected field UUID_CONFIG	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public com.webmethods.portal.service.dir.IDirService getDirectoryService(com.webmethods.portal.system.IURI)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.util.List getEmptyUUIDUsers()' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.lang.Boolean getUUIDResolution()' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.lang.String getUserDNFromUserUUID(java.lang.String, com.webmethods.portal.service.meta2.IUserService)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public void invalidateGroupRoleCache(com.webmethods.portal.service.meta2.thing.IThingID)' has been added	
com.webmethods.portal.service.dir.DirectoryTools: Method 'public com.webmethods.portal.service.meta2.thing.IThingID	

Added API	Description
resolveUserByUUID(com.webmethods.portal.service.dir.init.IInitializableUser)	' has been added
com.webmethods.portal.service.dir.DirectoryTools: Method 'public java.util.List updatePrincipalUUID()'	has been added
com.webmethods.portal.service.dir.IDirConstants:	Added public field USER_UUID
com.webmethods.portal.service.dir.IDirQueryProvider: Method 'public com.webmethods.portal.service.dir.IDirPrincipal lookupByUUID(int, java.lang.String)'	has been added to an interface
com.webmethods.portal.service.dir.impl.DirServicePortletBean: Method 'public boolean isSirNameFirst(com.webmethods.portal.bizPolicy.IContext)'	has been added
com.webmethods.portal.service.dir.init.IInitializablePrincipal: Method 'public java.lang.String getUUID()'	has been added to an interface
com.webmethods.portal.service.dir.init.impl.InitializablePrincipal: Method 'public java.lang.String getUUID()'	has been added
com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.List getEmptyUUIDUsers()'	has been added to an interface
com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.Map getUserDetailsByURI(com.webmethods.portal.system.IURI)'	has been added to an interface
com.webmethods.portal.service.meta2.IUserService: Method 'public java.util.Map getUserDetailsByUUID(java.lang.String)'	has been added to an interface
com.webmethods.portal.service.meta2.IUserService: Method 'public void invalidateUserUUID()'	has been added to an interface
com.webmethods.portal.service.meta2.IUserService: Method 'public void updateDistinguishedName(java.lang.String, java.lang.String, int)'	has been added to an interface
com.webmethods.portal.service.meta2.IUserService: Method 'public void updateUUID(java.lang.String, java.lang.String, int)'	has been added to an interface
com.webmethods.portal.service.meta2.directory.IUserInfo: Method 'public java.lang.String getUUID()'	has been added to an interface
com.webmethods.portal.service.meta2.directory.impl.User: Method 'public java.lang.String getUUID()'	has been added
com.webmethods.portal.service.meta2.directory.impl.UserInfo:	Added protected field uuid
com.webmethods.portal.service.meta2.directory.impl.UserInfo: Method 'public java.lang.String getUUID()'	has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.List getEmptyUUIDUsers()'	has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.Map	

Added API	Description
getUserDetailsByURI(com.webmethods.portal.system.IURI)	' has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public java.util.Map getUserDetailsByUUID(java.lang.String)'	' has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void invalidateUserUUID()'	' has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void updateDistinguishedName(java.lang.String, java.lang.String, int)'	' has been added
com.webmethods.portal.service.meta2.impl.UserService: Method 'public void updateUUID(java.lang.String, java.lang.String, int)'	' has been added
com.webmethods.portal.service.socialbpm.chart.impl.ChartData: Method 'public java.lang.String getTaskTypeID()'	' has been added
com.webmethods.portal.service.socialbpm.chart.impl.ChartData: Method 'public void setTaskTypeID(java.lang.String)'	' has been added
com.webmethods.portal.service.socialbpm.chart.impl.ChartService: Method 'protected java.lang.String getTaskTypeID(java.lang.String)'	' has been added
com.webmethods.portal.service.sql.runtime.base.EmptyUUIDUserList: Class	com.webmethods.portal.service.sql.runtime.base.EmptyUUIDUserList added
com.webmethods.portal.service.sql.runtime.base.InvalidateUserUUID: Class	com.webmethods.portal.service.sql.runtime.base.InvalidateUserUUID added
com.webmethods.portal.service.sql.runtime.base.SetUserGroupUUID: Class	com.webmethods.portal.service.sql.runtime.base.SetUserGroupUUID added
com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew: Class	com.webmethods.portal.service.sql.runtime.base.TaskLockSetNew added
com.webmethods.portal.service.sql.runtime.base.UserDetailsByURI: Class	com.webmethods.portal.service.sql.runtime.base.UserDetailsByURI added
com.webmethods.portal.service.sql.runtime.base.UserDetailsByUUID: Class	com.webmethods.portal.service.sql.runtime.base.UserDetailsByUUID added
com.webmethods.portal.service.task.ITaskLockingService: Method 'public	com.webmethods.portal.service.task.ITaskLock acquireLock(com.webmethods.portal.system.IURI,
com.webmethods.portal.system.IURI, long, long, boolean)'	' has been added to an interface
com.webmethods.portal.service.task.event.RefreshTaskEvent: Class	com.webmethods.portal.service.task.event.RefreshTaskEvent added
com.webmethods.portal.service.task.event.RefreshTaskEvent\$ISynchronousListener: Class	com.webmethods.portal.service.task.event.RefreshTaskEvent\$ISynchronousListener added
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners: Class	com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners: Class

Added API	Description
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners	added
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners\$SynchronousListener	Class
com.webmethods.portal.service.task.event.RefreshTaskEvent\$SynchronousListeners\$SynchronousListener	added
com.webmethods.portal.service.task.event.TaskChangedEventRetry	Class
com.webmethods.portal.service.task.event.TaskChangedEventRetry	added
com.webmethods.portal.service.task.event.impl.RefreshTaskEvent	Class
com.webmethods.portal.service.task.event.impl.RefreshTaskEvent	added
com.webmethods.portal.service.task.impl.TaskLockingService	Method 'public
com.webmethods.portal.service.task.ITaskLock	acquireLock(com.webmethods.portal.system.IURI,
com.webmethods.portal.system.IURI, long, long, boolean)'	has been added
com.webmethods.portal.system.ISAMLSSOConstants	Class
com.webmethods.portal.system.ISAMLSSOConstants	added
com.webmethods.portal.system.cluster.IClusterProvider	Method 'public java.lang.String
getClusterId()'	has been added to an interface
com.webmethods.portal.system.cluster.IClusterProvider	Method 'public boolean
isCurrentServer(com.webmethods.portal.system.cluster.IServer)'	has been added to an interface
com.webmethods.portal.system.cluster.IClusterProvider	Method 'public void
recreateJNDIConnection()'	has been added to an interface
com.webmethods.portal.system.cluster.IClusterProvider	Method 'public boolean
reloadJNDIProviderURL()'	has been added to an interface
com.webmethods.portal.system.cluster.impl.ClusterProvider	Added public field
CLUSTER_ID_PROP_KEY	
com.webmethods.portal.system.cluster.impl.ClusterProvider	Added public field s_logCategory
com.webmethods.portal.system.cluster.impl.ClusterProvider	Method 'public java.lang.String
getClusterId()'	has been added
com.webmethods.portal.system.cluster.impl.ClusterProvider	Method 'public boolean
isCurrentServer(com.webmethods.portal.system.cluster.IServer)'	has been added
com.webmethods.portal.system.cluster.impl.ClusterProvider	Method 'public void
recreateJNDIConnection()'	has been added
com.webmethods.portal.system.cluster.impl.ClusterProvider	Method 'public boolean
reloadJNDIProviderURL()'	has been added
com.webmethods.portal.system.sso.saml.idp.SAMLIdentityProvider	Class
com.webmethods.portal.system.sso.saml.idp.SAMLIdentityProvider	added

Added API	Description
com.webmethods.portal.system.sso.saml.idp.SAMLSSODataChangeListener: Class com.webmethods.portal.system.sso.saml.idp.SAMLSSODataChangeListener added	
com.webmethods.portal.system.sso.saml.idp.SAMLServiceProvider: Class com.webmethods.portal.system.sso.saml.idp.SAMLServiceProvider added	
com.webmethods.portal.system.sso.saml.idp.SSOIDPConfiguration: Class com.webmethods.portal.system.sso.saml.idp.SSOIDPConfiguration added	
com.webmethods.portal.system.sso.saml.idp.WebSSOPropsUtil: Class com.webmethods.portal.system.sso.saml.idp.WebSSOPropsUtil added	
com.webmethods.portal.taglib.TaglibUtil: Method 'public java.lang.String generateUniqueID()' has been added	
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory: Method 'public org.opensaml.saml2.core.AuthnRequest getAuthnRequest(java.lang.String)' has been added	
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory: Method 'public java.lang.String getResponse(java.net.URL, java.lang.String, java.util.Map, java.lang.String[], java.util.Map, org.opensaml.saml2.core.AuthnRequest)' has been added	
com.webmethods.portal.webservices.wsclient.PortalArtifactFactory: Method 'public void reInitSecurityTokenService()' has been added	
com.webmethods.rtl.event.DeliveryService: Method 'public java.lang.String addClusterIdPrefix(java.lang.String)' has been added	
com.webmethods.rtl.event.DeliveryService: Method 'public void setClusterId(java.lang.String)' has been added	
com.webmethods.rtl.event.DeliveryService: Method 'public void startRemoteDelivery()' has been added	
com.webmethods.rtl.event.DeliveryService: Method 'public void stopRemoteDelivery()' has been added	
com.webmethods.rtl.event.Event: Method 'public java.lang.String getJcrSessionUserData()' has been added	
com.webmethods.rtl.event.IEvent: Method 'public java.lang.String getJcrSessionUserData()' has been added to an interface	
com.webmethods.rtl.jms.PortalClientOverJMS: Class com.webmethods.rtl.jms.PortalClientOverJMS added	
com.webmethods.rtl.logging.EnhancedPatternLayout: Class com.webmethods.rtl.logging.EnhancedPatternLayout added	
com.webmethods.rtl.msg.jms.IJMSPProvider: Method 'public java.lang.String getEndpointAddress()' has been added to an interface	

Added API	Description
com.webmethods.rtl.msg.jms.IJMSPProvider:	Method 'public boolean isConnected()' has been added to an interface
com.webmethods.rtl.msg.jms.JMSPProvider:	Added protected field m_endpointAddress
com.webmethods.rtl.msg.jms.JMSPProvider:	Added protected field m_isConnected
com.webmethods.rtl.msg.jms.JMSPProvider:	Method 'public java.lang.String getEndpointAddress()' has been added
com.webmethods.rtl.msg.jms.JMSPProvider:	Method 'public boolean isConnected()' has been added
com.webmethods.rtl.msg.jms.JMSPProvider:	Abstract method 'protected void stopConnections()' has been added
com.webmethods.rtl.msg.jms.JMSStdConnProvider:	Method 'protected void stopConnections()' has been added
com.webmethods.rtl.script.JspC:	Method 'public java.lang.String getExcludes()' has been added
com.webmethods.rtl.script.JspC:	Method 'public void setExcludes(java.lang.String)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'protected org.w3c.dom.Document _loadDocumentUncaught(org.xml.sax.InputSource)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromInputStreamUncaught(java.io.InputStream)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromReaderUncaught(java.io.Reader)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentFromXMLUncaught(java.lang.String)' has been added
com.webmethods.rtl.util.xml.XMLUtil:	Method 'public org.w3c.dom.Document loadDocumentUncaught(java.lang.String)' has been added

Removed API	Replacement, if any
com.webmethods.caf.jcr.rmi.IRMITunnelHttpPortAware:	Class com.webmethods.caf.jcr.rmi.IRMITunnelHttpPortAware removed
com.webmethods.caf.jcr.rmi.JcrRMIMHttpToCGISocketFactory:	Class com.webmethods.caf.jcr.rmi.JcrRMIMHttpToCGISocketFactory removed
com.webmethods.caf.jcr.rmi.JcrRMIMMasterSocketFactory:	Class com.webmethods.caf.jcr.rmi.JcrRMIMMasterSocketFactory removed
com.webmethods.jackrabbit.server.io.DefaultHandler:	Class com.webmethods.jackrabbit.server.io.DefaultHandler removed

Removed API**Replacement, if any**

com.webmethods.jackrabbit.servlet.JCRWebdavServerServlet: Class
com.webmethods.jackrabbit.servlet.JCRWebdavServerServlet removed

com.webmethods.jackrabbit.servlet.SimpleWebdavServlet: Class
com.webmethods.jackrabbit.servlet.SimpleWebdavServlet removed

com.webmethods.portal.jms.um.UmJMSClient: Field DEFAULT_UM_REALM has been removed, but it was previously a constant

com.webmethods.portal.jms.um.UmJMSClient: Method 'public void init()' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Removed field gadgetExternalScripts

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Method 'public
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts
getGadgetExternalScripts()' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition: Method 'public void
setGadgetExternalScripts(com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternal
Scripts)' has been removed

com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts: Class
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts removed

com.webmethods.portal.schema.bcgadget.ObjectFactory: Method 'public
com.webmethods.portal.schema.bcgadget.GadgetDefinition\$GadgetExternalScripts
createGadgetDefinitionGadgetExternalScripts()' has been removed

com.webmethods.portal.service.access.impl.GadgetsAclManager: Method 'protected java.lang.String
buildXPathQuery(java.util.Map)' has been removed, but an inherited definition exists.

com.webmethods.portal.service.access.impl.GadgetsAclManager\$GadgetAclResource: Method 'public
GadgetsAclManager\$GadgetAclResource(javax.jcr.Node, java.lang.String)' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'public void enableMessageDelivery()' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'public boolean hasInitialized()' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected void
setInstance(com.webmethods.rtl.msg.jms.JMSProvider)' has been removed

com.webmethods.rtl.msg.jms.JMSProvider: Method 'protected void startConnections()' has been removed

com.webmethods.rtl.msg.jms.JMSStdConnProvider: Method 'protected void startConnections()' has been removed

Changed API	Description
	com.webmethods.caf.common.bnd.PortletXmlAnalyzer: Parameter 1 of 'public boolean analyzeJar(aQute.lib.osgi.Analyzer)' has changed its type to aQute.bnd.osgi.Analyzer
	com.webmethods.caf.common.bnd.WebXmlAnalyzer: Parameter 1 of 'public boolean analyzeJar(aQute.lib.osgi.Analyzer)' has changed its type to aQute.bnd.osgi.Analyzer
	com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 2 of 'public void displayAssertion(java.io.PrintWriter, org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion
	com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public java.lang.String getLoginName(org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion
	com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLAssertion getSamlAssertion(java.lang.String, java.lang.String)' has been changed to org.opensaml.saml1.core.Assertion
	com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public org.opensaml.SAMLAssertion getSamlAssertion(org.opensaml.SAMLResponse)' has changed its type to org.opensaml.saml1.core.Response
	com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLAssertion getSamlAssertion(org.opensaml.SAMLResponse)' has been changed to org.opensaml.saml1.core.Assertion
	com.webmethods.caf.wsserver.auth.saml.SamlUtils: Return type of method 'public org.opensaml.SAMLResponse getSamlResponse(java.lang.String, java.lang.String)' has been changed to org.opensaml.saml1.core.Response
	com.webmethods.caf.wsserver.auth.saml.SamlUtils: Parameter 1 of 'public java.lang.String verifyAssertion(org.opensaml.SAMLAssertion)' has changed its type to org.opensaml.saml1.core.Assertion
	com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public UmJMSClient()' has been decreased from public to protected
	com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void closeUMSession(com.pcbssystem.nirvana.client.nSession)' has been decreased from public to private
	com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createConnectionFactory(java.lang.String)' has been decreased from public to protected
	com.webmethods.portal.jms.um.UmJMSClient: Return type of method 'public javax.naming.Context createJNDIContext()' has been changed to void
	com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public javax.naming.Context createJNDIContext()' has been decreased from public to private

Changed API**Description**

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createQueue(java.lang.String, boolean, int)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createQueueConnectionFactory(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createStringVal(java.lang.String, java.lang.String)' has been decreased from public to package

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createTopic(java.lang.String, boolean, int)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createTopicConnectionFactory(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void createXAConnectionFactory(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void deleteConnectionFactory(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void deleteQueue(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void deleteQueueConnectionFactory(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void deleteTopic(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public void deleteTopicConnectionFactory(java.lang.String)' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public javax.naming.Context getJNDIContext()' has been decreased from public to protected

com.webmethods.portal.jms.um.UmJMSClient: Accessibility of method 'public com.pcbsys.nirvana.client.nSession getSession()' has been decreased from public to private

com.webmethods.portal.service.bcgadget.IBCGadgetProvider: Return type of method 'public java.util.List getAccessibleGadgets(com.webmethods.portal.service.meta2.thing.IThingID)' has been changed to java.util.Map

com.webmethods.portal.service.bcgadget.impl.BCGadgetProvider: Return type of method 'public java.util.List getAccessibleGadgets(com.webmethods.portal.service.meta2.thing.IThingID)' has been changed to java.util.Map

com.webmethods.portal.service.task.impl.TaskLockingService: Accessibility of field TASK_LOCK_MAX_TIME has been increased from private to public

com.webmethods.portal.service.task.impl.TaskLockingService: Accessibility of field

Changed API**Description**

TASK_LOCK_MAX_WAIT_TIME has been increased from private to public

com.webmethods.portal.service.task.impl.TaskLockingService: In method 'protected com.webmethods.portal.service.task.ITaskLock createDbLock(com.webmethods.portal.service.sql.ISqlWorker, com.webmethods.portal.service.meta2.thing.IThingID, java.util.Date, java.util.Date)' the number of arguments has changed

com.webmethods.portal.system.PortalSystem: Accessibility of method 'private void initGuestUser()' has been increased from private to public

com.webmethods.rtl.msg.jms.JMSProvider: Accessibility of method 'public void onShutdown()' has been decreased from public to protected

com.webmethods.rtl.msg.jms.JMSProvider: Accessibility of method 'private void setMaintenanceMode(boolean)' has been increased from private to protected

com.webmethods.rtl.msg.jms.JMSStdConnProvider: Accessibility of method 'public JMSStdConnProvider()' has been decreased from public to protected

com.webmethods.portal.service.version.impl.dcv.DCVersionService: Value of compile-time constant VERSION_SERVICES_ROOT has been changed

Release 9.10

Added API/ Description

com.webmethods.portal.bizPolicy.biz.access.IAccessPolicy: Method 'public

com.webmethods.portal.service.view.IListView

listSecurityRealmObjects(com.webmethods.portal.bizPolicy.IContext,

com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.mech.subscription.ISubscribableMechanics: Method 'public void

checkViewSubscription(com.webmethods.portal.system.IURI,

com.webmethods.portal.service.meta2.thing.IThingID, java.util.Map,

com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.bizPolicy.biz.IBizPolicyResolver: Method 'public

com.webmethods.portal.bizPolicy.biz.IBizPolicy getBizPolicyByType(java.lang.String, java.util.Map)'

has been added to an interface

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String

getAssertion(java.lang.String, java.lang.String[], java.util.Map)' has been added to an interface

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String

getAssertion(java.lang.String, java.lang.String[], java.util.Map, java.util.Map)' has been added to an

interface

com.webmethods.caf.wsclient.session.IWSClientSession: Method 'public java.util.Map

getSessionCookieMap()' has been added to an interface

com.webmethods.caf.wsclient.session.IWSClientSession: Method 'public void

setSessionCookieMap(java.util.Map)' has been added to an interface

com.webmethods.caf.wsclient.session.IWSClientSessionManager: Method 'public

com.webmethods.caf.wsclient.session.IWSClientSessionPool

getSessionPool(com.webmethods.caf.wsclient.proxy.IWSClientProxy, java.lang.String)' has been added

to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public java.util.Date getTaskScheduleDate()'

has been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void setCreatedDate(java.util.Date)' has

been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void

setTaskScheduleDate(java.util.Date)' has been added to an interface

com.webmethods.portal.service.task.ITask: Method 'public java.util.Date getTaskScheduleDate()' has

been added to an interface

Changed API	Description
POST a New Task Instance	The Task Engine RESTful web service in My webMethods Server now accepts the task schedule details for a task instance to be added to Task Engine's queue.
PUT Information in a Task Instance	The Task Engine RESTful web service in My webMethods Server now allows changes to the new taskScheduleDate parameter if a task instance is in scheduled state.
GET Task Instance Information	The Task Engine RESTful web service in My webMethods Server now retrieves the task schedule date along with other details of a task instance.
com.webmethods.portal.event.system.ICriterionEvent\$IListener: Parameter 1 of 'public void onEvent(com.webmethods.portal.event.system.ISubscriptionEvent)' has changed its type to com.webmethods.portal.event.system.ICriterionEvent	
com.webmethods.portal.event.system.ICriterionEvent\$ISynchronousListener: Parameter 1 of 'public void onSynchronousEvent(com.webmethods.portal.event.system.ISubscriptionEvent)' has changed its type to com.webmethods.portal.event.system.ICriterionEvent	
com.webmethods.portal.service.access.impl.MwsObjectAclManager: In method 'protected int countAceProperties(java.util.List)' the number of arguments has changed	
com.webmethods.caf.wsclient.session.impl.WSClientSessionManager: Parameter 2 of 'protected java.lang.String getSessionPoolID(com.webmethods.caf.wsclient.proxy.IWSClientProxy, com.webmethods.caf.wsclient.AuthCredentials)' has changed its type to java.lang.String	

Removed API/ Description

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.portal.webapp.jetty7.WebApplicationInstallService: Removed field
COMPONENT_DELETE_RETRIES

com.webmethods.portal.service.global.impl.LanguagePackManager: Field QUERY_STRING has been removed, but it was previously a constant

com.webmethods.caf.faces.convert.FormattedDateTimeConverter: Method 'protected java.text.DateFormat setupGMTDateTimeFormater(javax.faces.context.FacesContext)' has been removed

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public java.util.List getTaskCommentsByProcessModelId(java.lang.String, int, int, int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List getPaginatedTaskCommentsByProcessModelId(java.lang.String, int, int, int)' has been added to an interface

com.webmethods.portal.service.dir.IRoleSystem: Method 'public void clearCache(com.webmethods.portal.service.dir.IDirPrincipal)' has been added to an interface

com.webmethods.portal.mech.dir.IPrincipalMechanics: Method 'public void fireRoleMembershipEvent(com.webmethods.portal.service.meta2.thing.IThingID, com.webmethods.portal.system.IURI, com.webmethods.portal.service.dir.IDirPrincipalList, com.webmethods.portal.service.dir.IDirPrincipalList, int)' has been added to an interface

move the com.webmethods.jms.** packages from caf-server bundle to a unique package name

com.webmethods.jms.JMSPhaseProvider: Class com.webmethods.jms.JMSPhaseProvider removed

com.webmethods.jms.db.DbJMSSClient: Class com.webmethods.jms.db.DbJMSSClient removed

com.webmethods.jms.db.DbJMSSConnProvider: Class com.webmethods.jms.db.DbJMSSConnProvider removed

com.webmethods.jms.db.impl.JMSConnection: Class com.webmethods.jms.db.impl.JMSConnection removed

com.webmethods.jms.db.impl.JMSConnection\$CompressedObject: Class com.webmethods.jms.db.impl.JMSConnection\$CompressedObject removed

com.webmethods.jms.db.impl.JMSDestination: Class com.webmethods.jms.db.impl.JMSDestination removed

com.webmethods.jms.db.impl.JMSDispatcherThread: Class com.webmethods.jms.db.impl.JMSDispatcherThread removed

com.webmethods.jms.db.impl.JMSEvent: Class com.webmethods.jms.db.impl.JMSEvent removed

com.webmethods.jms.db.impl.JMSMessage: Class com.webmethods.jms.db.impl.JMSMessage removed

com.webmethods.jms.db.impl.JMSMessageConsumer: Class com.webmethods.jms.db.impl.JMSMessageConsumer removed

com.webmethods.jms.db.impl.JMSMessageProducer: Class com.webmethods.jms.db.impl.JMSMessageProducer removed

com.webmethods.jms.db.impl.JMSObjectMessage: Class
com.webmethods.jms.db.impl.JMSObjectMessage removed

com.webmethods.jms.db.impl.JMSPollThread: Class com.webmethods.jms.db.impl.JMSPollThread
removed

com.webmethods.jms.db.impl.JMSQueue: Class com.webmethods.jms.db.impl.JMSQueue removed

com.webmethods.jms.db.impl.JMSQueuePollThread: Class
com.webmethods.jms.db.impl.JMSQueuePollThread removed

com.webmethods.jms.db.impl.JMSQueueReceiver: Class
com.webmethods.jms.db.impl.JMSQueueReceiver removed

com.webmethods.jms.db.impl.JMSQueueSender: Class
com.webmethods.jms.db.impl.JMSQueueSender removed

com.webmethods.jms.db.impl.JMSQueueSession: Class
com.webmethods.jms.db.impl.JMSQueueSession removed

com.webmethods.jms.db.impl.JMSSession: Class com.webmethods.jms.db.impl.JMSSession removed

com.webmethods.jms.db.impl.JMSTopic: Class com.webmethods.jms.db.impl.JMSTopic removed

com.webmethods.jms.db.impl.JMSTopicBatchMessage: Class
com.webmethods.jms.db.impl.JMSTopicBatchMessage removed

com.webmethods.jms.db.impl.JMSTopicPublisher: Class
com.webmethods.jms.db.impl.JMSTopicPublisher removed

com.webmethods.jms.db.impl.JMSTopicSession: Class com.webmethods.jms.db.impl.JMSTopicSession
removed

com.webmethods.jms.db.impl.JMSTopicSubscriber: Class
com.webmethods.jms.db.impl.JMSTopicSubscriber removed

com.webmethods.jms.db.impl.QueueFactory: Class com.webmethods.jms.db.impl.QueueFactory
removed

com.webmethods.jms.db.impl.TopicFactory: Class com.webmethods.jms.db.impl.TopicFactory
removed

com.webmethods.jms.db.impl.db2.EventDelivered: Class
com.webmethods.jms.db.impl.db2.EventDelivered removed

com.webmethods.jms.db.impl.db2.EventPoll: Class com.webmethods.jms.db.impl.db2.EventPoll
removed

com.webmethods.jms.db.impl.db2.EventSave: Class com.webmethods.jms.db.impl.db2.EventSave
removed

com.webmethods.jms.db.impl.db2.GetSqlTime: Class com.webmethods.jms.db.impl.db2.GetSqlTime
removed

com.webmethods.jms.db.impl.db2.PublishQueue: Class
com.webmethods.jms.db.impl.db2.PublishQueue removed

com.webmethods.jms.db.impl.db2.PurgeEvents: Class com.webmethods.jms.db.impl.db2.PurgeEvents removed

com.webmethods.jms.db.impl.db2.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.db2.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.db2.RegisterDestination: Class
com.webmethods.jms.db.impl.db2.RegisterDestination removed

com.webmethods.jms.db.impl.db2.RegisterSubscription: Class
com.webmethods.jms.db.impl.db2.RegisterSubscription removed

com.webmethods.jms.db.impl.db2.UnregisterSubscription: Class
com.webmethods.jms.db.impl.db2.UnregisterSubscription removed

com.webmethods.jms.db.impl.db2.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.db2.UpdateSubscriptions removed

com.webmethods.jms.db.impl.mssql.EventDelivered: Class
com.webmethods.jms.db.impl.mssql.EventDelivered removed

com.webmethods.jms.db.impl.mssql.EventPoll: Class com.webmethods.jms.db.impl.mssql.EventPoll removed

com.webmethods.jms.db.impl.mssql.EventSave: Class com.webmethods.jms.db.impl.mssql.EventSave removed

com.webmethods.jms.db.impl.mssql.GetSqlTime: Class
com.webmethods.jms.db.impl.mssql.GetSqlTime removed

com.webmethods.jms.db.impl.mssql.PublishQueue: Class
com.webmethods.jms.db.impl.mssql.PublishQueue removed

com.webmethods.jms.db.impl.mssql.PurgeEvents: Class
com.webmethods.jms.db.impl.mssql.PurgeEvents removed

com.webmethods.jms.db.impl.mssql.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.mssql.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.mssql.RegisterDestination: Class
com.webmethods.jms.db.impl.mssql.RegisterDestination removed

com.webmethods.jms.db.impl.mssql.RegisterSubscription: Class
com.webmethods.jms.db.impl.mssql.RegisterSubscription removed

com.webmethods.jms.db.impl.mssql.UnregisterSubscription: Class
com.webmethods.jms.db.impl.mssql.UnregisterSubscription removed

com.webmethods.jms.db.impl.mssql.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.mssql.UpdateSubscriptions removed

com.webmethods.jms.db.impl.mysql.EventDelivered: Class
com.webmethods.jms.db.impl.mysql.EventDelivered removed

com.webmethods.jms.db.impl.mysql.EventPoll: Class com.webmethods.jms.db.impl.mysql.EventPoll
removed

com.webmethods.jms.db.impl.mysql.EventSave: Class com.webmethods.jms.db.impl.mysql.EventSave
removed

com.webmethods.jms.db.impl.mysql.GetSqlTime: Class
com.webmethods.jms.db.impl.mysql.GetSqlTime removed

com.webmethods.jms.db.impl.mysql.PublishQueue: Class
com.webmethods.jms.db.impl.mysql.PublishQueue removed

com.webmethods.jms.db.impl.mysql.PurgeEvents: Class
com.webmethods.jms.db.impl.mysql.PurgeEvents removed

com.webmethods.jms.db.impl.mysql.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.mysql.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.mysql.RegisterDestination: Class
com.webmethods.jms.db.impl.mysql.RegisterDestination removed

com.webmethods.jms.db.impl.mysql.RegisterSubscription: Class
com.webmethods.jms.db.impl.mysql.RegisterSubscription removed

com.webmethods.jms.db.impl.mysql.UnregisterSubscription: Class
com.webmethods.jms.db.impl.mysql.UnregisterSubscription removed

com.webmethods.jms.db.impl.mysql.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.mysql.UpdateSubscriptions removed

com.webmethods.jms.db.impl.oracle.EventDelivered: Class
com.webmethods.jms.db.impl.oracle.EventDelivered removed

com.webmethods.jms.db.impl.oracle.EventPoll: Class com.webmethods.jms.db.impl.oracle.EventPoll
removed

com.webmethods.jms.db.impl.oracle.EventSave: Class com.webmethods.jms.db.impl.oracle.EventSave
removed

com.webmethods.jms.db.impl.oracle.GetSqlTime: Class
com.webmethods.jms.db.impl.oracle.GetSqlTime removed

com.webmethods.jms.db.impl.oracle.PublishQueue: Class
com.webmethods.jms.db.impl.oracle.PublishQueue removed

com.webmethods.jms.db.impl.oracle.PurgeEvents: Class
com.webmethods.jms.db.impl.oracle.PurgeEvents removed

com.webmethods.jms.db.impl.oracle.PurgeInactiveSubscriptions: Class
com.webmethods.jms.db.impl.oracle.PurgeInactiveSubscriptions removed

com.webmethods.jms.db.impl.oracle.RegisterDestination: Class
com.webmethods.jms.db.impl.oracle.RegisterDestination removed

com.webmethods.jms.db.impl.oracle.RegisterSubscription: Class
com.webmethods.jms.db.impl.oracle.RegisterSubscription removed

com.webmethods.jms.db.impl.oracle.UnregisterSubscription: Class
com.webmethods.jms.db.impl.oracle.UnregisterSubscription removed

com.webmethods.jms.db.impl.oracle.UpdateSubscriptions: Class
com.webmethods.jms.db.impl.oracle.UpdateSubscriptions removed

com.webmethods.jms.db.impl.sybase.EventPoll: Class com.webmethods.jms.db.impl.sybase.EventPoll removed

com.webmethods.jms.db.impl.sybase.PublishQueue: Class
com.webmethods.jms.db.impl.sybase.PublishQueue removed

com.webmethods.jms.db.impl.sybase.PurgeEvents: Class
com.webmethods.jms.db.impl.sybase.PurgeEvents removed

com.webmethods.jms.um.UmJMSClient: Class com.webmethods.jms.um.UmJMSClient removed

com.webmethods.jms.um.UmJMSConnProvider: Class
com.webmethods.jms.um.UmJMSConnProvider removed

electric.util.holder.ArrayOfbyteInOut: Class electric.util.holder.ArrayOfbyteInOut removed

electric.util.holder.ArrayOfbyteOut: Class electric.util.holder.ArrayOfbyteOut removed

com.webmethods.portal.bizPolicy.command.system.xml.XMLImport: Field
OVERWRITE_PERMISSIONS_KEY has been removed, but it was previously a constant

com.webmethods.portal.service.dir.IDirService: Method 'public boolean supportsNestedGroups()' has been added to an interface

com.webmethods.caf.faces.application.CAFStateManager: Class
com.webmethods.caf.faces.application.CAFStateManager removed

com.webmethods.caf.faces.application.CAFStateManager\$TreeStructure: Class
com.webmethods.caf.faces.application.CAFStateManager\$TreeStructure removed

com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListener: Class
com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListener removed

com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListenerWrapper: Class
com.webmethods.caf.faces.portlet.PortletViewFragmentPhaseListenerWrapper removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected void
initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.portlet.PortletViewHandler: Method 'protected void
renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.render.html.command.CommandFormRenderer: In method 'protected java.lang.String getTagName()' the number of arguments has changed

com.webmethods.caf.faces.render.html.command.DisjointFormRenderer: In method 'protected java.lang.String getTagName()' the number of arguments has changed

com.webmethods.caf.faces.view.BaseViewHandler: Field STATE_KEY has been removed, but it was previously a constant

com.webmethods.caf.faces.view.BaseViewHandler: Method 'protected void initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.view.BaseViewHandler: Method 'protected void renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field INJECT_STATE has been removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field NO_RENDER has been removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field STATE_KEY has been removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field VIEW_FRAGMENT has been removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Field VIEW_FRAGMENT_CLIENT_ID has been removed, but it was previously a constant

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Return type of method 'protected void initResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been changed to javax.faces.context.ResponseWriter

com.webmethods.caf.faces.view.CafViewDeclarationLanguage: Method 'protected void renderResponse(javax.faces.context.FacesContext, javax.faces.component.UIViewRoot)' has been removed

com.webmethods.caf.faces.view.ViewFragmentPhaseListener: Class
com.webmethods.caf.faces.view.ViewFragmentPhaseListener removed

Release 9.9

Added API/ Description

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public java.lang.Integer getIsMandatory()' has been added to an interface

com.webmethods.caf.faces.data.task.ITaskInfo: Method 'public void setIsMandatory(java.lang.Integer)' has been added to an interface

Added API/ Description

com.webmethods.caf.wsclient.saml.IArtifactFactory: Method 'public java.lang.String validateSAMLResponse(javax.servlet.http.HttpServletRequest, java.lang.String)' has been added to an interface

com.webmethods.portal.bizPolicy.biz.access.IAccessPolicy: Method 'public com.webmethods.portal.service.view.IListView listSecurityRealmObjects(com.webmethods.portal.bizPolicy.IContext, com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public java.util.List getAllTaskAttachments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public java.lang.Integer getAllTaskAttachmentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public java.util.List getTaskComments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public java.lang.Integer getTaskCommentsCount(int)' has been added to an interface

com.webmethods.portal.mech.socialbpm.comments.ICommentsMechanics: Method 'public java.lang.Integer getTaskCommentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.mech.subscription.ISubscribableMechanics: Method 'public void checkViewSubscription(com.webmethods.portal.system.IURI, com.webmethods.portal.service.meta2.thing.IThingID, java.util.Map, com.webmethods.portal.service.meta2.thing.IThingID)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List getAllTaskAttachments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.lang.Integer getAllTaskAttachmentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.util.List getTaskComments(java.lang.String, int, int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.lang.Integer getTaskCommentsCount(int)' has been added to an interface

com.webmethods.portal.service.socialbpm.comments.ICommentsService: Method 'public java.lang.Integer getTaskCommentsCount(java.lang.String)' has been added to an interface

com.webmethods.portal.service.task.ITask: Method 'public java.lang.Integer getIsMandatory()' has been added to an interface

com.webmethods.portal.service.task.ITaskDefinition: Method 'public java.lang.String getTaskDescription()' has been added to an interface

Removed API/ Description

com.webmethods.caf.faces.component.gmap.GMarkerGroup: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.gmap.GMarkerList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.AsyncIterator: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.Import: Removed javax.faces.event.SystemEventListener
from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.ImportTemplate: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.logic.Iterator: Removed javax.faces.event.SystemEventListener
from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.Breadcrumbs: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.FirstLevelList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.NavList: Removed javax.faces.event.SystemEventListener
from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.PopupMenus: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.SecondLevelList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.StaticMenus\$SubList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.StaticMenus\$SubSubList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.nav.ThirdLevelList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncListbox: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.AsyncTabsList: Removed
javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.DataList: Removed

Removed API/ Description

javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.ListBox: Removed

javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.caf.faces.component.table.html.TabsList: Removed

javax.faces.event.SystemEventListener from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.ISystemMechanics: Removed

com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.access.IAccessMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.IClipboardMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.IBasicMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.ISubscribableMechanics from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.IViewableMechanics from the set of implemented interfaces

com.webmethods.rtl.script.JspC: Removed java.lang.Cloneable from the set of implemented interfaces

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

Removed API/ Description

com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.ProjectComponent from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.Task from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.clipboard.impl.ClipboardMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.storage.impl.BasicMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.subscription.impl.SubscribableMechanics from the list of superclasses

com.webmethods.portal.mech.system.impl.SystemMechanics: Removed

com.webmethods.portal.mech.view.impl.ViewableMechanics from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.ProjectComponent from the list of superclasses

com.webmethods.rtl.script.JspC: Removed org.apache.tools.ant.Task from the list of superclasses

com.webmethods.caf.faces.component.logic.Import: Method 'public boolean isListenerForSource(java.lang.Object)' has been removed

com.webmethods.caf.faces.component.logic.Import: Method 'public void processEvent(javax.faces.event.SystemEvent)' has been removed

com.webmethods.caf.faces.component.logic.ImportTemplate: Method 'public boolean isListenerForSource(java.lang.Object)' has been removed

com.webmethods.caf.faces.component.logic.ImportTemplate: Method 'public void processEvent(javax.faces.event.SystemEvent)' has been removed

com.webmethods.caf.faces.component.nav.PopupMenus: Method 'protected javax.faces.component.UIColumn getColumn()' has been removed

com.webmethods.caf.faces.component.table.html.DataList: Method 'public boolean isListenerForSource(java.lang.Object)' has been removed

com.webmethods.caf.faces.component.table.html.DataList: Method 'public void processEvent(javax.faces.event.SystemEvent)' has been removed

com.webmethods.caf.faces.component.tree.DataTree: Method 'protected void autogenerate()' has been removed

com.webmethods.portal.service.install.impl.BaseInstallService: Method 'protected com.webmethods.portal.service.install.IInstallServiceConfig getConfig()' has been removed

com.webmethods.portal.service.sql.runtime.base.TaskSearchAll: Method 'protected void parseSearchQuery(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQuery,

Removed API/ Description

com.webmethods.portal.service.sql.runtime.base.TaskSearchAll\$QueryInfo) has been removed

com.webmethods.portal.service.sql.runtime.base.TaskSearchAll: Method 'protected void parseSearchQueryTerm(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm, com.webmethods.portal.service.sql.runtime.base.TaskSearchAll\$QueryInfo)' has been removed

com.webmethods.portal.service.sql.runtime.base.TaskSearchFromInboxesPaged: Method 'protected void parseSearchQueryTerm(int, java.util.Map, com.webmethods.caf.faces.data.task.impl.TaskSearchQueryTerm, com.webmethods.portal.service.sql.runtime.base.TaskSearchAll\$QueryInfo)' has been removed

com.webmethods.rtl.script.JspC: Method 'public void init()' has been removed

com.softwareag.caf.controls.mwsx.PeoplePickerDialog\$FacetsMap: Class
com.softwareag.caf.controls.mwsx.PeoplePickerDialog\$FacetsMap removed

com.softwareag.caf.controls.mwsx.PeopleSwapBox\$FacetsMap: Class
com.softwareag.caf.controls.mwsx.PeopleSwapBox\$FacetsMap removed

com.webmethods.caf.faces.component.nav.StaticMenus\$ChildrenList: Class
com.webmethods.caf.faces.component.nav.StaticMenus\$ChildrenList removed

com.webmethods.caf.faces.component.nav.StaticMenus\$FacetsMap: Class
com.webmethods.caf.faces.component.nav.StaticMenus\$FacetsMap removed

com.webmethods.caf.faces.component.nav.ToggleMenus\$ChildrenList: Class
com.webmethods.caf.faces.component.nav.ToggleMenus\$ChildrenList removed

com.webmethods.caf.faces.component.nav.ToggleMenus\$FacetsMap: Class
com.webmethods.caf.faces.component.nav.ToggleMenus\$FacetsMap removed

com.webmethods.caf.faces.component.search.SearchBar\$FacetsMap: Class
com.webmethods.caf.faces.component.search.SearchBar\$FacetsMap removed

com.webmethods.caf.faces.component.table.SelectRowCheckbox\$ChildrenList: Class
com.webmethods.caf.faces.component.table.SelectRowCheckbox\$ChildrenList removed

com.webmethods.caf.faces.component.table.SelectRowCheckbox\$FacetsMap: Class
com.webmethods.caf.faces.component.table.SelectRowCheckbox\$FacetsMap removed

com.webmethods.caf.faces.component.table.html.HtmlTableColumn\$FacetsMap: Class
com.webmethods.caf.faces.component.table.html.HtmlTableColumn\$FacetsMap removed

com.webmethods.caf.faces.component.table.specialized.Newsfeed\$ChildrenList: Class
com.webmethods.caf.faces.component.table.specialized.Newsfeed\$ChildrenList removed

com.webmethods.caf.faces.component.table.specialized.Newsfeed\$FacetsMap: Class
com.webmethods.caf.faces.component.table.specialized.Newsfeed\$FacetsMap removed

com.webmethods.caf.faces.component.util.BaseChildrenList: Class
com.webmethods.caf.faces.component.util.BaseChildrenList removed

Removed API/ Description

com.webmethods.caf.faces.component.util.BaseFacetsAndChildrenIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsAndChildrenIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection\$BaseIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$BaseCollection\$BaseIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries\$EntrySetIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Entries\$EntrySetIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys\$KeySetIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Keys\$KeySetIterator removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values removed

com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values\$ValuesIterator: Class
com.webmethods.caf.faces.component.util.BaseFacetsMap\$Values\$ValuesIterator removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseFileListTask: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseFileListTask removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseTask: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.AntBaseTask removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GenerateOSGiManifest: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GenerateOSGiManifest removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GetPortletInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.GetPortletInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PostRegisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PostRegisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreRegisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreRegisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreUnregisterPortlet: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.portlet.PreUnregisterPortlet removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateSkinInstance: Class

Removed API/ Description

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateSkinInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateThemeInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.CreateThemeInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.GetSkinInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.GetSkinInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveSkinInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveSkinInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveThemeInstance: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.skin.RemoveThemeInstance removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.CreateDBOTables: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.CreateDBOTables removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.DropDBOTables: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.DropDBOTables removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteCommand: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteCommand removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteTargetLoop: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.ExecuteTargetLoop removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetComponentInfo removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetIsOSGiRuntime removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.GetSystemPath removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.InstallComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.InstallComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadClasses: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadClasses removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadConfig: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LoadConfig removed

Removed API/ Description

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LookupComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.LookupComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RegisterComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RegisterComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RunSQLScript: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.RunSQLScript removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UninstallComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UninstallComponent removed

com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UnregisterComponent: Class
com.webmethods.portal.bizPolicy.command.install.taskdefs.system.UnregisterComponent removed

com.webmethods.portal.mech.install.impl.NativeInstallMechanics: Class
com.webmethods.portal.mech.install.impl.NativeInstallMechanics removed

com.webmethods.portal.service.install.IInstallServiceConfig: Class
com.webmethods.portal.service.install.IInstallServiceConfig removed

com.webmethods.portal.service.install.impl.InstallServiceConfig: Class
com.webmethods.portal.service.install.impl.InstallServiceConfig removed

com.webmethods.portal.service.install.impl.ant.AntInstallService: Class
com.webmethods.portal.service.install.impl.ant.AntInstallService removed

com.webmethods.portal.service.install.impl.ant.AntLogSupport: Class
com.webmethods.portal.service.install.impl.ant.AntLogSupport removed

com.webmethods.portal.service.install.impl.ant.AntRunner: Class
com.webmethods.portal.service.install.impl.ant.AntRunner removed

com.webmethods.portal.service.install.impl.ant.AntRunner\$AntPropertyHelper: Class
com.webmethods.portal.service.install.impl.ant.AntRunner\$AntPropertyHelper removed

com.webmethods.portal.service.install.impl.ant.LpInstallService: Class
com.webmethods.portal.service.install.impl.ant.LpInstallService removed

com.webmethods.portal.service.install.impl.ant.WarLpInstallService: Class
com.webmethods.portal.service.install.impl.ant.WarLpInstallService removed

com.webmethods.rtl.logging.Mws13818Filter: Class com.webmethods.rtl.logging.Mws13818Filter
removed

com.webmethods.rtl.util.msg.IRuntimeMessage: Class com.webmethods.rtl.util.msg.IRuntimeMessage
removed

com.webmethods.rtl.util.msg.IRuntimeMessageCallback: Class
com.webmethods.rtl.util.msg.IRuntimeMessageCallback removed

com.webmethods.rtl.util.msg.IRuntimeMessageHook: Class

Removed API/ Description

com.webmethods.rtl.util.msg.IRuntimeMessageHook removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeListeners: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeListeners removed

com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeMessageListener: Class
com.webmethods.rtl.util.msg.RuntimeMessageUtil\$RuntimeMessageListener removed

com.webmethods.rtl.util.obj.CyclicIterator: Class com.webmethods.rtl.util.obj.CyclicIterator removed

com.webmethods.rtl.util.obj.EmptyEnumeration: Class
com.webmethods.rtl.util.obj.EmptyEnumeration removed

com.webmethods.rtl.util.obj.EmptyIterator: Class com.webmethods.rtl.util.obj.EmptyIterator removed

com.webmethods.rtl.util.obj.FileClassLoader: Class com.webmethods.rtl.util.obj.FileClassLoader removed

com.webmethods.rtl.util.obj.IntMinMaxInfo: Class com.webmethods.rtl.util.obj.IntMinMaxInfo removed

com.webmethods.rtl.util.obj.IntStringMap: Class com.webmethods.rtl.util.obj.IntStringMap removed

com.webmethods.rtl.util.obj.IteratorTools: Class com.webmethods.rtl.util.obj.IteratorTools removed

com.webmethods.rtl.util.obj.PersistentMap: Class com.webmethods.rtl.util.obj.PersistentMap removed

com.webmethods.rtl.util.obj.PropertyGroup: Class com.webmethods.rtl.util.obj.PropertyGroup removed

com.webmethods.rtl.util.obj.PropertyGroups: Class com.webmethods.rtl.util.obj.PropertyGroups removed

com.webmethods.rtl.util.obj.SortableArray: Class com.webmethods.rtl.util.obj.SortableArray removed

com.webmethods.rtl.util.thread.ReadWriteMutex: Class
com.webmethods.rtl.util.thread.ReadWriteMutex removed

com.softwareag.caf.controls.mwsx.PeoplePickerDialog: Removed field m_facets

com.softwareag.caf.controls.mwsx.PeopleSwapBox: Removed field m_facets

com.webmethods.caf.faces.component.behavior.BaseBehavior: Removed field m_for

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_allowDrag

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_cursor

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_move

com.webmethods.caf.faces.component.behavior.CustomDragBehavior: Removed field m_propagateEvent

Removed API/ Description

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_allowDrop

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_handleDrop

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_hoverClass

com.webmethods.caf.faces.component.behavior.CustomDropBehavior: Removed field m_onDropSetValue

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_add

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_allowDrag

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_allowDrop

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_copy

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_handleDrop

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_hoverClass

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_remove

com.webmethods.caf.faces.component.behavior.DragToMoveRowsBehavior: Removed field m_reorder

com.webmethods.caf.faces.component.behavior.DragToReorderColumnsBehavior: Removed field m_storePreferences

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeBottom

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeLeft

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeRight

com.webmethods.caf.faces.component.behavior.DragToResizeBehavior: Removed field m_resizeTop

com.webmethods.caf.faces.component.behavior.DragToResizeColumnsBehavior: Removed field m_storePreferences

com.webmethods.caf.faces.component.behavior.RaiseOnChangeBehavior: Removed field m_command

com.webmethods.caf.faces.component.behavior.SynchronizeValuesBehavior: Removed field m_with

com.webmethods.caf.faces.component.command.html.AsyncCommandButton: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.AsyncCommandIcon: Removed field m_refresh

Removed API/ Description

com.webmethods.caf.faces.component.command.html.AsyncCommandInterval: Removed field m_interval

com.webmethods.caf.faces.component.command.html.AsyncCommandInterval: Removed field m_waitUntilReloaded

com.webmethods.caf.faces.component.command.html.AsyncCommandLink: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.AsyncHiddenCommand: Removed field m_refresh

com.webmethods.caf.faces.component.command.html.CommandForm: Removed field m_forms

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_alt

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_url

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_urlMouseDown

com.webmethods.caf.faces.component.command.html.CommandIcon: Removed field m_urlMouseover

com.webmethods.caf.faces.component.events.OpenAjaxScript: Removed field openAjaxTopic

com.webmethods.caf.faces.component.events.OpenAjaxScript: Removed field shouldSubscribe

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_converter

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_entriesProvider

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_exportCharacterEncoding

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_exportFileName

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_exportForceDownload

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_feedProvider

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_feedUrl

com.webmethods.caf.faces.component.export.AtomFeedIcon: Removed field m_for

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_height

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_initialAddress

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_initialCountry

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_key

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_latitude

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_longitude

Removed API/ Description

com.webmethods.caf.faces.component.gmap.GMap: Removed field m_type
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_width
com.webmethods.caf.faces.component.gmap.GMap: Removed field m_zoom
com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_anchor
com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_offsetX
com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_offsetY
com.webmethods.caf.faces.component.gmap.GMapControl: Removed field m_type
com.webmethods.caf.faces.component.gmap.GMapGetCoordsScript: Removed field m_latitude
com.webmethods.caf.faces.component.gmap.GMapGetCoordsScript: Removed field m_longitude
com.webmethods.caf.faces.component.gmap.GMapKey: Removed field m_key
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_clickable
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_draggable
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_icon
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_iconSizeHeight
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_iconSizeWidth
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_initialAddress
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_initialCountry
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_latitude
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_longitude
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_selected
com.webmethods.caf.faces.component.gmap.GMarker: Removed field m_title
com.webmethods.caf.faces.component.gmap.GMarkerGroup: Removed field m_groupProvider
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_clickable
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_draggable
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_icon
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_iconSizeHeight
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_iconSizeWidth
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_initialAddress
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_initialCountry

Removed API/ Description

com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_latitude
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_longitude
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_multiple
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_title
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_multiple
com.webmethods.caf.faces.component.gmap.GMarkerList: Removed field m_title
com.webmethods.caf.faces.component.input.DateInput: Removed field m_pattern
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showMonthAndYearMenus
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showSeconds
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showTime
com.webmethods.caf.faces.component.input.DateInput: Removed field m_showTimezone
com.webmethods.caf.faces.component.input.DateInput: Removed field m_timezone
com.webmethods.caf.faces.component.input.DateInput: Removed field m_valuePattern
com.webmethods.caf.faces.component.input.DateInput: Removed field m_yearMenuRange
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_futureRanges
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_label
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_layout
com.webmethods.caf.faces.component.input.DateRangeInput: Removed field m_pastRanges
com.webmethods.caf.faces.component.logic.If: Removed field m_value
com.webmethods.caf.faces.component.logic.Import: Removed field m_value
com.webmethods.caf.faces.component.logic.ImportTemplate: Removed field m_value
com.webmethods.caf.faces.component.logic.LoadResourceBundle: Removed field m_basename
com.webmethods.caf.faces.component.logic.LoadResourceBundle: Removed field m_var
com.webmethods.caf.faces.component.logic.VariableContainer: Removed field m_value
com.webmethods.caf.faces.component.logic.VariableContainer: Removed field m_var
com.webmethods.caf.faces.component.message.FormattedMessage: Removed field m_showDetail
com.webmethods.caf.faces.component.message.FormattedMessages: Removed field m_showDetail
com.webmethods.caf.faces.component.message.SpecificFormattedMessages: Removed field m_for
com.webmethods.caf.faces.component.message.SpecificMessages: Removed field m_for

Removed API/ Description

com.webmethods.caf.faces.component.mws_ui.MwsResourceInclude: Removed field renderer

com.webmethods.caf.faces.component.mws_ui.MwsResourceInclude: Removed field uri

com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_appNavBean

com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_children

com.webmethods.caf.faces.component.nav.StaticMenus: Removed field m_facets

com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_appNavBean

com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_children

com.webmethods.caf.faces.component.nav.ToggleMenus: Removed field m_facets

com.webmethods.caf.faces.component.output.Chart: Removed field m_barPadding

com.webmethods.caf.faces.component.output.Chart: Removed field m_barWidth

com.webmethods.caf.faces.component.output.Chart: Removed field m_color

com.webmethods.caf.faces.component.output.Chart: Removed field m_gridColor

com.webmethods.caf.faces.component.output.Chart: Removed field m_gridStyle

com.webmethods.caf.faces.component.output.Chart: Removed field m_height

com.webmethods.caf.faces.component.output.Chart: Removed field m_legendLocation

com.webmethods.caf.faces.component.output.Chart: Removed field m_legendStyleClass

com.webmethods.caf.faces.component.output.Chart: Removed field m_numberofGridLines

com.webmethods.caf.faces.component.output.Chart: Removed field m_padding

com.webmethods.caf.faces.component.output.Chart: Removed field m_rowColors

com.webmethods.caf.faces.component.output.Chart: Removed field m_series

com.webmethods.caf.faces.component.output.Chart: Removed field m_showLegend

com.webmethods.caf.faces.component.output.Chart: Removed field m_type

com.webmethods.caf.faces.component.output.Chart: Removed field m_width

com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_color

com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_toolTip

com.webmethods.caf.faces.component.output.ChartDataColumn: Removed field m_value

com.webmethods.caf.faces.component.output.ChartLabelColumn: Removed field m_label

com.webmethods.caf.faces.component.output.Custom: Removed field m_name

com.webmethods.caf.faces.component.output.Icon: Removed field m_converter

Removed API/ Description

com.webmethods.caf.faces.component.output.Icon: Removed field m_label
com.webmethods.caf.faces.component.output.Icon: Removed field m_url
com.webmethods.caf.faces.component.output.Icon: Removed field m_urlMousedown
com.webmethods.caf.faces.component.output.Icon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_accesskey
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_alt
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_dir
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_disabled
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_image
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_label
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_lang
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onblur
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onclick
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_ondblclick
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onfocus
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onkeydown
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseout
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseover
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_onmouseup
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_readonly
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_style
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_styleClass
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_tabindex
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_title
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_type
com.webmethods.caf.faces.component.output.html.HtmlButton: Removed field m_width
com.webmethods.caf.faces.component.output.html.HtmlLink: Removed field m_label
com.webmethods.caf.faces.component.output.refresh.RefreshButton: Removed field m_for
com.webmethods.caf.faces.component.output.refresh.RefreshIcon: Removed field m_for

Removed API/ Description

com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_for

com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_interval

com.webmethods.caf.faces.component.output.refresh.RefreshInterval: Removed field m_waitUntilReloaded

com.webmethods.caf.faces.component.output.refresh.RefreshLink: Removed field m_for

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_disableWhenHidden

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_lazy

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_refreshOnShow

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_suppressInputs

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_twoPass

com.webmethods.caf.faces.component.panel.BaseHideablePanel: Removed field m_visible

com.webmethods.caf.faces.component.panel.OverlayPanel: Removed field m_hideEffect

com.webmethods.caf.faces.component.panel.OverlayPanel: Removed field m_showEffect

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_click

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_close

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_closeOnClick

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_forRightClick

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hideEffect

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hideEffectOptions

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_hover

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_position

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_showEffect

com.webmethods.caf.faces.component.panel.PopupPanel: Removed field m_showEffectOptions

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_description

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_label

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_overflow

com.webmethods.caf.faces.component.panel.PropertyLine: Removed field m_parentId

com.webmethods.caf.faces.component.panel.StackPanel: Removed field m_value

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_align

Removed API/ Description

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_height

com.webmethods.caf.faces.component.panel.StaticCell: Removed field m_width

com.webmethods.caf.faces.component.panel.StaticRow: Removed field m_height

com.webmethods.caf.faces.component.panel.StaticRow: Removed field m_width

com.webmethods.caf.faces.component.search.BaseSearchControlHelper: Removed field fQuerySupplied

com.webmethods.caf.faces.component.search.BaseSearchControlHelper: Removed field fQuerySuppliedExpr

com.webmethods.caf.faces.component.search.SearchBar: Removed field m_facets

com.webmethods.caf.faces.component.select.FilterInput: Removed field m_labelText

com.webmethods.caf.faces.component.select.FilterInput: Removed field m_showGoButton

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_filter

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_other

com.webmethods.caf.faces.component.select.SelectMany: Removed field m_sortByLabel

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_filter

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_other

com.webmethods.caf.faces.component.select.SelectOne: Removed field m_sortByLabel

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_dir

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_disabled

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_lang

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_dir

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_disabled

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_lang

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_name

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onblur

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onchange

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onclick

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_ondblclick

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onfocus

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeydown

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeypress

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onkeyup

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmousedown

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmousemove

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseout

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseover

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_onmouseup

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_readonly

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_size

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_style

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_styleClass

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_tabindex

com.webmethods.caf.faces.component.select.html.HtmlSelectBoolean: Removed field m_title

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_accesskey

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_border

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_dir

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_disabled

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_disabledClass

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_enabledClass

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_lang

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_layout

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onblur

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onchange

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onclick

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_ondblclick

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onfocus

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeydown
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeypress
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onkeyup
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmousedown
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmousemove
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseout
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseover
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onmouseup
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_onselect
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_readonly
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_size
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_style
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_styleClass
com.webmethods.caf.faces.component.select.html.HtmlSelectMany: Removed field m_tabindex
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onblur
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onchange
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onclick
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_ondblclick
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onfocus
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeydown
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeypress
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onkeyup
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmousedown
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmousemove
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseout
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseover
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onmouseup
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_onselect
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_readonly

Removed API/ Description

com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_size
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_style
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_styleClass
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_tabindex
com.webmethods.caf.faces.component.select.html.HtmlSelectOne: Removed field m_title
com.webmethods.caf.faces.component.table.AddRow: Removed field m_addLastRowOnly
com.webmethods.caf.faces.component.table.AddRow: Removed field m_for
com.webmethods.caf.faces.component.table.AddRow: Removed field m_row
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_title
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_url
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_urlMouseDown
com.webmethods.caf.faces.component.table.AddRowIcon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_align
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_ascending
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_exportable
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_group
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_hidden
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_label
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_nowrap
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_optional
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_ordinal
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondary
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondaryEnd
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_secondaryStart
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_sort
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_valign
com.webmethods.caf.faces.component.table.BaseExtendedColumn: Removed field m_width
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_accesskey
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_disabled

Removed API/ Description

com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_multiple
com.webmethods.caf.faces.component.table.BaseSelectRow: Removed field m_tabindex
com.webmethods.caf.faces.component.table.DataPager: Removed field m_for
com.webmethods.caf.faces.component.table.DataPages: Removed field m_maxPages
com.webmethods.caf.faces.component.table.DataPages: Removed field m_showAlways
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_title
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_url
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_urlMouseDown
com.webmethods.caf.faces.component.table.MoveRowIcon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_expandToEdges
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_nextIconUrl
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_nextText
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_prevIconUrl
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_prevText
com.webmethods.caf.faces.component.table.PrevNext: Removed field m_showAlways
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_for
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_removeLastRow
com.webmethods.caf.faces.component.table.RemoveRow: Removed field m_row
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_title
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_url
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_urlMouseDown
com.webmethods.caf.faces.component.table.RemoveRowIcon: Removed field m_urlMouseover
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_accesskey
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_disabled
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_for
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_multiple
com.webmethods.caf.faces.component.table.SelectRow: Removed field m_tabindex
com.webmethods.caf.faces.component.table.SelectRowCheckbox: Removed field m_children
com.webmethods.caf.faces.component.table.SelectRowCheckbox: Removed field m_facets

Removed API/ Description

com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferChunk
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferMax
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_bufferMin
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_clientSideCache
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_flashOnChange
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_progressDelay
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_progressMsg
com.webmethods.caf.faces.component.table.html.AsyncList: Removed field m_suppressInputs
com.webmethods.caf.faces.component.table.html.AsyncListbox: Removed field m_rowClasses
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferChunk
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferMax
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_bufferMin
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_clientSideCache
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_flashOnChange
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_progressDelay
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_progressMsg
com.webmethods.caf.faces.component.table.html.AsyncTable: Removed field m_suppressInputs
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field dayVar
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field eventVar
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_allDay
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_calendarEndDate
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_calendarStartDate
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_displayUnits
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_events
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_eventsSet
com.webmethods.caf.faces.component.table.html.CalendarTable: Removed field m_initialDate
com.webmethods.caf.faces.component.table.html.DataList: Removed field m_marker
com.webmethods.caf.faces.component.table.html.DataList: Removed field m_selected
com.webmethods.caf.faces.component.table.html.DataList: Removed field m_selectedRowClass

Removed API/ Description

com.webmethods.caf.faces.component.table.html.DataTable: Removed field createdToOriginalRowIds

com.webmethods.caf.faces.component.table.html.DataTable: Removed field filter

com.webmethods.caf.faces.component.table.html.DataTable: Removed field first

com.webmethods.caf.faces.component.table.html.DataTable: Removed field firstSet

com.webmethods.caf.faces.component.table.html.DataTable: Removed field originalToCreatedRowIds

com.webmethods.caf.faces.component.table.html.DataTable: Removed field var

com.webmethods.caf.faces.component.table.html.HtmlTableColumn: Removed field m_facets

com.webmethods.caf.faces.component.table.html.ListBox: Removed field m_rowClasses

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_children

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_facets

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_layout

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_size

com.webmethods.caf.faces.component.table.specialized.Newsfeed: Removed field m_url

com.webmethods.caf.faces.component.toggle.InitiateToggle: Removed field m_for

com.webmethods.caf.faces.component.toggle.OneWayToggle: Removed field m_for

com.webmethods.caf.faces.component.toggle.OneWayToggle: Removed field m_way

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_disabled

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_disabledClass

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_enabledClass

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggle: Removed field m_width

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggleCheckbox: Removed field m_checked

com.webmethods.caf.faces.component.toggle.html.HtmlOneWayToggleCheckbox: Removed field m_checkedWhenVisible

com.webmethods.caf.faces.component.toggle.html.HtmlToggle: Removed field m_disabled

com.webmethods.caf.faces.component.toggle.html.HtmlToggle: Removed field m_disabledClass

com.webmethods.caf.faces.component.toggle.html.HtmlToggle: Removed field m_enabledClass

com.webmethods.caf.faces.component.toggle.html.HtmlToggle: Removed field m_layout

com.webmethods.caf.faces.component.toggle.html.HtmlToggle: Removed field m_width

Removed API/ Description

com.webmethods.caf.faces.component.tree.AsyncTree: Removed field m_initialDepth
com.webmethods.caf.faces.component.tree.AsyncTree: Removed field m_progressDelay
com.webmethods.caf.faces.component.tree.AsyncTree: Removed field m_progressFlashOnComplete
com.webmethods.caf.faces.component.tree.AsyncTree: Removed field m_progressMsg
com.webmethods.caf.faces.component.tree.AsyncTree: Removed field m_refillDepth
com.webmethods.caf.faces.component.tree.AsyncTree: Removed field m_refreshOnShow
com.webmethods.caf.faces.component.tree.AsyncTree: Removed field m_suppressInputs
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_collapseAllIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_collapseIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_expandAllIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_expandIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_leafIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_lineBottomIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_lineIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_lineNoneIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_lineTopIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_loadingIcon
com.webmethods.caf.faces.component.tree.BaseTreeControl: Removed field m_showSortLink
com.webmethods.caf.faces.view.BaseViewHandler: Removed field RE_FE_URL
com.webmethods.portal.faces.view.PortalViewHandler: Removed field RE_FE_URL
com.webmethods.portal.taglib.PortalIterationTagSupport: Removed field EMPTY_ITERATOR

12.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

13.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

TE-RM-103-20181015

webMethods Trading Networks 10.3 and webMethods Optimize for B2B 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Trading Networks 10.3 and webMethods Optimize for B2B 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find the suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	2
4.0	Fixes Included in Each Release.....	2
5.0	Other Resolved Issues.....	8
6.0	Documentation Changes	10
7.0	Terminology Changes	12
8.0	Added, Removed, Deprecated, or Changed Items.....	13
9.0	Added, Removed, Deprecated, or Changed Built-In Services.....	18
10.0	Added, Removed, Deprecated, or Changed Parameters.....	20
11.0	Copyright Information.....	21
12.0	Support.....	21

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- Trading Networks Server configuration with 'TN Config Name' (My webMethods Server) field set to a value with special character, or leading, trailing space do not get listed in Command Central as Trading Networks Server Configuration.
- Document types in disabled state cannot be uninstalled through Command Central.
- When My WebMethods Server is installed along with the Trading Networks user interface component without Integration Server, Trading Networks user interface does not appear after you log into the My webMethods user interface.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Trading Networks

Release 10.3

- TNS_10.2_Fix1

- TN_10.2_MWS_Fix1
- TN_10.1_MWS_Fix3
- TNS_10.1_Fix4
- TN_9.12_MWS_Fix9
- TNS_9.12_Fix9
- TN_9.10_MWS_Fix7
- TNS_9.10_Fix9
- TN_9.9_MWS_Fix6
- TNS_9.9_Fix9
- TN_9.8_MWS_Fix7
- TNS_9.8_Fix9
- TNS_9.7_Fix13
- TN_9.7_MWS_Fix12
- TN_9.6_MWS_Fix7
- TNS_9.6_Fix11
- TN_9.5_SP1_MWS_Fix6
- TNS_9.5_SP1_Fix12
- TN_9.0_SP1_MWS_Fix8
- TNS_9.0_SP1_Fix9

Release 10.2

- TN_10.1_MWS_Fix2
- TNS_10.1_Fix2
- TN_9.12_MWS_Fix8
- TNS_9.12_Fix8
- TN_9.10_MWS_Fix6
- TNS_9.10_Fix8
- TN_9.9_MWS_Fix6
- TNS_9.9_Fix8
- TN_9.8_MWS_Fix7

- TNS_9.8_Fix9
- TNS_9.7_Fix12
- TN_9.7_MWS_Fix12
- TN_9.6_MWS_Fix7
- TNS_9.6_Fix11
- TN_9.5_SP1_MWS_Fix6
- TNS_9.5_SP1_Fix12
- TN_9.0_SP1_MWS_Fix8
- TNS_9.0_SP1_Fix9

Release 10.1

- TN_9.12_MWS_Fix4
- TNS_9.12_Fix4
- TN_9.10_MWS_Fix3
- TNS_9.10_Fix5
- TN_9.9_MWS_Fix5
- TNS_9.9_Fix7
- TN_9.8_MWS_Fix6
- TNS_9.8_Fix8
- TN_9.7_MWS_Fix11
- TNS_9.7_Fix11
- TN_9.6_MWS_Fix6
- TNS_9.6_Fix10
- TN_9.5_SP1_MWS_Fix6
- TNS_9.5_SP1_Fix12
- TN_9.0_SP1_MWS_Fix8
- TNS_9.0_SP1_Fix9

Release 10.0

- TN_9.12_MWS_Fix2
- TNS_9.12_Fix2
- TN_9.10_MWS_Fix2
- TNS_9.10_Fix3
- TN_9.9_MWS_Fix4
- TNS_9.9_Fix5
- TN_9.8_MWS_Fix5
- TNS_9.8_Fix7
- TN_9.7_MWS_Fix10
- TNS_9.7_Fix10
- TN_9.6_MWS_Fix6
- TNS_9.6_Fix10
- TN_9.5_SP1_MWS_Fix6
- TNS_9.5_SP1_Fix12
- TN_9.0_SP1_MWS_Fix8
- TNS_9.0_SP1_Fix9

Release 9.12

- TN_9.10_MWS_Fix2
- TNS_9.10_Fix2
- TNS_9.9_Fix3
- TN_9.8_MWS_Fix5
- TNS_9.8_Fix7
- TN_9.7_MWS_Fix9
- TNS_9.7_Fix9
- TN_9.6_MWS_Fix6
- TNS_9.6_Fix10
- TNS_9.5_SP1_Fix12

- TNS_9.0_SP1_Fix9

Release 9.10

- TN_9.9_MWS_Fix1
- TNS_9.9_Fix1
- TN_9.8_MWS_Fix3
- TNS_9.8_Fix5
- TN_9.7_MWS_Fix5
- TNS_9.7_Fix6
- TNS_9.6_Fix7
- TNS_9.5_SP1_Fix9

Release 9.9

- TN_9.8_MWS_Fix2
- TNS_9.8_Fix3
- TN_9.7_MWS_Fix3
- TNS_9.7_Fix3
- TN_9.6_MWS_Fix4
- TNS_9.6_Fix5
- TN_9.5_SP1_MWS_Fix6
- TNS_9.5_SP1_Fix7
- TN_9.0_SP1_MWS_Fix7
- TNS_9.0_SP1_Fix8
- TNS_8.2_SP2_Fix27

Release 9.8

- TN_9.7_MWS_Fix1
- TNS_9.7_Fix1
- TN_9.6_MWS_Fix3
- TNS_9.6_Fix3
- TN_9.5_SP1_MWS_Fix5
- TNS_9.5_SP1_Fix6
- TN_9.0_SP1_MWS_Fix6
- TNS_9.0_SP1_Fix6
- TN_8.2_SP2_MWS_Fix24
- TNS_8.2_SP2_Fix26

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Trading Networks

Release 10.3

- OTN-19362

When you click the EDIINT document type on either the Transactions page or Document Types page, the My webMethods user interface displays an error - Could not find out a Document Type editor for the selected Document type. This issue is resolved.

- OTN-19116

When a partner profile has many externalIDs (around ~700), the external IDs table stops rendering the information after a certain number of pages. This is because client side caching is enabled for the table in My webMethods Server user interface. Navigating to next the page adds rows in the HTML form on the client side. The form size keeps growing resulting in "Form too Large" errors. The issue is now resolved by disabling the client side caching for external ID table in the Partner Profile page.

- OTN-19364

The '&' and '?' characters can be used in the contact and email fields of a Partner Profile.

Release 9.12

- OTN-16377

Inbuilt 'Unknown' document details in Trading Networks are changed using the import and export feature. Exporting, modifying, and importing an 'Unknown' document results in a change of the document name. This issue is resolved.

- OTN-16197

Inbuilt 'Unknown' partner profile details in Trading Networks are changed using the import and export feature. Exporting, modifying, and importing an 'Unknown' partner profile results in a change of the partner profile name. This issue is resolved.

- OTN-15070

In My webMethods: Administration > Partner Profiles > Delivery Settings > Suspend Delivery Schedule page, 'Time Zone' is not localized.

This issue occurs if localizations are not handled for 'Time Zone.'

This issue is resolved.

- OTN-15067

In My webMethods: Administration > Partner Profiles > Delivery Settings > Suspend Delivery Schedule page, 'Recurrence Pattern' is not localized.

This issue occurs if localizations are not handled for 'Recurrence Pattern.'

This issue is resolved.

- OTN-15045

In My webMethods: Administration > Partner Profiles > Delivery Settings page, the 'Status' icon tooltip is not localized.

This issue occurs if localizations are not handled for the 'Status' icon tooltip.

This issue is resolved.

- OTN-15044

In My webMethods: Administration > Partner Profiles > Delivery Settings > Suspend Delivery Schedule page, the 'Days' selection is not localized.

This issue occurs if localizations are not handled for the 'Days' selection.

This issue is resolved.

- OTN-15043

In My webMethods: Administration > Partner Profiles > Delivery Settings page, 'Suspend Delivery Schedule' is not localized.

This issue occurs if localizations are not handled for 'Suspend Delivery Schedule.'

This issue is resolved.

- OTN-15624

Updation or creation of a partner profile fails with the following error in the Integration Server log: [SoftwareAG][SQLServer JDBC Driver][SQLServer]Invalid column name 'LastModified'.

This issue occurs because the column name is not in Pascal.

This issue is resolved.

- OTN-15788

The Clear button is enabled before creating a certificate in the Certificates Tab under the Partner Profiles page.

The Clear button is enabled due to a CAF update.

This issue is resolved.

- OTN-15472

While using the Lookup of Address or Contact in Partner Profile an exception occurs.

When a user uses the lookup for Address or Contact in partner profile with TN database pointed to DB2, the following exception is displayed:

"Failed to evaluate binding expression: "#{ContactsPage.impactdPartners}"

This issue is resolved.

Release 9.8

- OTN-14125
My webMethods throws an exception when you view the details of a transaction that has an eBXML Envelope.
When you try to view the details of a transaction that has an eBXML Envelope, My webMethods throws an exception related to the content encoding not being supported. It is observed that the content encoding value is enclosed in double quotes.
This issue is resolved.
- OTN-13995
Document attributes of type STRING that contain Chinese characters are not extracted properly. If a document attribute of type STRING contains Chinese characters, Trading Networks replaces the Chinese characters with special characters. This can be noticed when you view the details of the corresponding transaction in My webMethods.
This issue is resolved.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Trading Networks

Release 10.3

The following information is added in *webMethods Trading Networks Administrator's Guide*:

- Monitoring API Usage
- Size Limit for Delivering Large Documents

The following information is modified in *webMethods Trading Networks Administrator's Guide*:

- Configuring Trading Networks for MySQL Enterprise Edition

Release 10.2

The following conceptual and procedural information is added in *webMethods Trading Networks Administrator's Guide*:

- SFTP delivery method
- Managing partner access to APIs

- Using Command Central to Manage Trading Networks
- Configuring Trading Networks MySQL 5.7 Community Edition
- Configuring Trading Networks MySQL 5.7 Enterprise Edition
- Understanding the Trading Networks Terminology
- Monitoring Transactions
- Summary of the Configuration Steps

The following public services are added in *webMethods Trading Networks Built-In Services Reference*:

- wm.tn.transport:Sftp
- wm.tn.transport:primarySftp
- wm.tn.transport:secondarySftp
- wm.tn.rec:SftpDeliveryServiceOutput
- wm.tn.rec:SftpOutput

The following section is added in *webMethods Trading Networks User's Guide*:

- Managing APIs

Release 10.1

The following conceptual and procedural information is added in *webMethods Trading Networks Administrator's Guide*:

- Stored Procedure in About Archiving and Deleting Documents
- Setting Up Stored Procedure Archive and Deletion

The following service is added in *webMethods Trading Networks Built-In Services Reference*:

- wm.tn.archive:archiveByStoredProc

Release 9.12

The Trading Networks Webhelp is not available as a standalone document on the Empower website. The contents of the Trading Networks Webhelp are available in the B2B Integration compendium.

Release 9.10

The following procedural information has been added to the *webMethods Trading Networks Administrator's Guide*:

- Copying or Sharing Addresses
- Copying or Sharing Contacts
- Adding a Custom Immediate Delivery Method to a Profile
- Copying or Sharing Custom Immediate Delivery Methods

Release 9.9

The following conceptual and procedural information has been added to the *webMethods Trading Networks Administrator's Guide*:

- Database Partitioning
 - Partitioning Trading Networks Database
 - Using a partitioned database for archiving data
 - Deleting run-time and archived data from a partitioned database
 - Dropping tables from a partitioned database

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Trading Networks

Release 10.3

Added Item	Description
Install and Uninstall Trading Network assets through command Central	Trading network assets can be installed and uninstalled through Command Central.
Large document handling support	Trading Networks provides the ability to deliver large documents by using Active Transfer.
API Usage Monitoring	Trading Networks provides the capability to monitor trading partner's API usage from: Monitoring > Integration > B2B > API Usage.

Release 10.2

Added Item	Description
Manage API Access to Partners	Trading Networks provides the ability to connect to an API Gateway instance to manage partner access to APIs.
Integration with Command Central	Command central supports management of Trading Networks configurations including management of Trading Networks instances and properties related to Trading Networks servers. It also enables template-based provisioning of Trading Networks instances.

Added Item	Description
SFTP Document Delivery Method	Trading Networks allows you to deliver documents using the SFTP protocol.
GDPR Compliance	Trading Networks server is now in compliance with General Data Protection Regulation (GDPR) for removing user's data from the system permanently.
My SQL 5.7 Enterprise and Community Edition support	You can configure MySQL Enterprise Edition 5.7 and MySQL Community Edition 5.7 with Trading Networks Server 10.2.

Release 10.1

Added Item	Description
Stored Procedure	Trading Networks provides the ability to archive and delete documents from the production and archive tables using the stored procedure archive script.

Release 9.12

Added Item	Description
Integration with ActiveTransfer	Trading Networks provides an ability to deliver documents through ActiveTransfer. Administrators can select ActiveTransfer as the delivery method in Trading Networks and set the end points that ActiveTransfer will connect with to transfer files.
Configure User Status	Administrators can configure user statuses and allow it to be set only from a predefined set of values.
Transport Status	Trading Networks allows you to search and view the status of a service for a delivery task.

Release 9.10

Added Item	Description
Reusability of Address, Contacts, and Delivery Methods.	Trading Networks allows you to reuse configuration items across multiple partners. The configuration items that are made reusable are address, contacts, and delivery methods.

Release 9.9

Added Item	Description
Suspending document delivery to a partner using suspension schedules	Trading Networks allows you to schedule a document delivery suspension to a partner. The delivery suspensions can be scheduled once, daily, weekly, monthly, or on a yearly basis.
Database Partitioning	Trading Networks database can be partitioned logically to separate one set of data from another. Database partitioning is useful especially when you archive data from production tables to archive tables because it provides the flexibility to perform operations at partition level.
Routing run-time events using Event Routing	Trading Networks supports run-time event notification using Software AG Event Routing.

Added Item	Description
tn.portal.rule.preventValidation	Whether to validate a processing rule name. Set this property to true or false. If the value is true, Trading Networks does not validate the processing rule name (allows special characters). If the value is false, Trading Networks validates the processing rule name and prompts you to provide a valid name.

Release 9.8

Added Item	Description
Dashboards and Charts	Trading Networks provides a set of dashboards and charts that give you a graphical view of the transaction volume and total value trend for a document attribute, summary of successful and failed transactions, and the late FA violations by partners.
Usability Enhancements	<p>Includes the following:</p> <ul style="list-style-type: none"> • The keyword search criteria for Trading Partner Agreements (TPAs) based on agreement IDs has been added. This is in addition to the already existing search criteria based on sender name or receiver name. This is enabled on TPA page and Import/Export page for TPAs. • On the Public Queues page, the option to save the searches as 'Public' or 'Private' has been added. Initially, all searches would be saved as Private. • Import of Trading Networks assets functionality has been extended to include importing using a zip file. This is in addition to the already existing functionality that allows importing using a binary or an xml file. • Trading Networks maintains context sensitivity across all its screens.

Added Item	Description
Editing a TPA	While editing a TPA, if another user tries to edit at the same time, Trading Networks ensures that data written by you is not over written by the other user and vice versa. While saving the TPA, Trading Networks ensures that you are working on the latest version of data, and notify you if another transaction has modified the TPA. In that case, you have to cancel the changes you have made, and reopen the TPA for edit.
Document Attribute Added run-time event	Trading Networks publishes this event when a new attribute is added to a document or an existing attribute in a document is updated.
tn.eda.events.emittableDocumentAttributeName Filter	Determines the set of document attributes for which Trading Networks will publish the Document Attribute Added run-time event. By default, Trading Networks publishes this event when Late FA document attribute is added or updated. To enable Trading Networks to publish this event for any other document attribute apart from Late FA attribute, set this property to a fully qualified custom java class. This class should include the set of document attributes apart from Late FA attribute that will enable Trading Networks to publish the event when the specified set of document attributes are added or updated.
Removed Item	Replacement
WmTNPki package	The WmTNPki package which provides functionality for using PKI profiles with Trading Networks has been deprecated. There is no replacement for the WmTNPki package.

9.0 Added, Removed, Deprecated, or Changed Built-In Services

A release is listed in this section only if changes occurred in that release.

Trading Networks

Release 10.2

Added Service	Description
wm.tn.transport:activeTransfer	Three new variables namely success, transactionId, and message can be utilized while designing a flow service using Designer.

Release 10.1

Added Service	Description
wm.tn.archive:archiveByStoredProc	Archives documents and deletes documents from the Trading Networks database using the stored procedure archive script.

Release 9.12

Added Service	Description
wm.tn.transport:activeTransfer	Delivers documents using webMethods ActiveTransfer.
wm.tn.rec:activeTransferOutput	If a task uses the ActiveTransfer delivery service to deliver documents, use this IS document type to map the output from the delivery service.
wm.tn.doc:addConfigUserStatusList	Adds new user status values to the configured list of user status values.
wm.tn.doc:deleteConfigUserStatusList	Deletes user status values from the configured list of user status values.
wm.tn.doc:getConfigUserStatusList	Provides the configured list of user status values.

Release 9.9

Added Service	Description
wm.tn.archive:purgeBizdocUniqueKeysData	Purges data from BizDocUniqueKeys and ARCHIVE_BizDocUniqueKeys tables.

Added Service	Description
wm.tn.archive:purgeEDITrackingData	Purges data from EDITracking and ARCHIVE_EDITracking tables.

Changed Service	Description
wm.tn.rec:BizDocEnvelope	<p>Four new fields have been added to BizDocEnvelope document type.</p> <ul style="list-style-type: none"> -VERSION_NO - Version of Trading Networks. -ReceiveSvc - For resubmitting the document. This is extracted from TN_parms/\$receiveSvc from the pipeline. -Comments - Comments associated with transactions. -Duplicate - Whether the document is duplicate or not. Valid values are true and false.

Release 9.8

Added Service	Description
wm.tn.charting: populateSummaryData	During migration, purges existing records from the dashboard tables, and populates records in the dashboard tables from runtime tables.

Changed Service	Description
wm.tn.purge:TransactionSummaryData	<p>Modified the service so that it can purge records from the newly added dashboard tables. The dashboard tables include:</p> <ul style="list-style-type: none"> - TransactionSummaryData - CustomAttributeVolumeValue - TransactionSuccessFailedData - SuccessFailedChartDocIdMap - TransactionLateFADData

Changed Service	Description
wm.tn.mime:createSignedAndEncryptedData wm.tn.mime:createSignedData wm.tn.mime:processEncryptedData wm.tn.mime:processSignedData wm.tn.mime:sign wm.tn.mime:verify	<p><i>profileAlias</i> is an input parameter to these services. It is an alias of the PKI profile that contains the private key, signer cert, and certificates you wish to use to sign the message. However, the WmTNPki package which provides functionality for using PKI profiles with Trading Networks has been removed, and there is no replacement for the WmTNPki package. Hence, the <i>profileAlias</i> parameter has been removed from these services.</p>

10.0 Added, Removed, Deprecated, or Changed Parameters

A release is listed in this section only if changes occurred in that release.

Release 10.2

Added Parameter	Description
tn.api.gateway.server.alias	This parameter is to set the alias in Trading Networks to point to the Integration Server configured API Gateway.

11.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

12.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

TNOPTB2B-RM-103-20181015

webMethods Unit Test Framework 10.3 Readme

October 2018

This file contains important information you must read before using webMethods Unit Test Framework 10.3. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information	1
2.0	Known Issues	2
3.0	Usage Notes	2
4.0	Fixes Included in Each Release	2
5.0	Other Resolved Issues	3
6.0	Documentation Changes	4
7.0	Terminology Changes	4
8.0	Added, Removed, Deprecated, or Changed Items	5
9.0	Copyright Information	5
10.0	Support	6

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

Release 10.3

GWM_10.1_wMTestSuiteDesigner_Fix3

GWM_10.1_wMTestSuiteServer_Fix3

GWM_10.2_wMTestSuiteDesigner_Fix1

GWM_10.2_wMTestSuiteCommonLib_Fix1

GWM_10.2_wMTestSuiteServer_Fix1

Release 10.2

GWM_10.1_wMTestSuiteDesigner_Fix1

5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

Release 10.3

- GWM-124

Issues with webMethods code coverage HTML report rendering.

Unit Test Framework allows integration of the Code Coverage HTML report with continuous integration build tools. However, following issues exist with code coverage rendering:

- HTML report of Code Coverage does not have a summary section.
- Certain widgets does not render correctly when hosted in Jenkins.
- The web report is not compatible with Internet Explorer version 11.

This issue is now fixed.

- GWM-125

Issues with generating Code Coverage report from the executed tests.

Unit Test Framework supports generating Code Coverage report from the executed tests. However, following issues exist with generating Code Coverage report from the executed tests.

- Tests are reported under unrooted test tree in Junit view.
- Test that is run from the Code Coverage Configuration dialog fails with exception.
- Code coverage report is not generated correctly for mocked services.
- Test execution with disabled mocked services does not update the configuration.

This issue is now fixed.

Release 10.0

- GWM-12

Pipeline compare, where service output is compared with a predefined expected output, fails to

assert two structures, if it contains "com.wm.util.Table" objects. These objects are used in SAP adapter backend.

This issue is now fixed.

- GWM-12

Mock adapter service of SAP template fails during execution. During the execution, mock adapter service of SAP template with predefined pipeline that contains "com.wm.util.Table" object, fails with NotSerializableException.

This issue is now fixed.

- GWM- 18

Even though the license validation is optional during the installation of Unit Test Framework from Command Central, the installation fails if the license file is not provided.

This issue is now fixed.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- Environment details are updated.
- “Headless Execution” is renamed as “Continuous Integration” and added new topic “Configuring a Test Suite Executor”.
- Properties under “Coverage Analysis in Headless Mode” are updated.

Release 10.2

- A new chapter Code Coverage Analysis is added to the webMethods Unit Test Framework Help document, which describes the support for recording and analyzing flow steps and map actions executed during a particular test launch.

Release 9.12

- Working with WmTestSuite guide was renamed to Unit Test Framework. All the occurrences of WmTestSuite were replaced by Unit Test Framework in the document.

Release 9.9

- Working with WmTestSuite 2.2.1 was introduced which describes how to install, design, and execute test cases using WmTestSuite.

7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

Release 9.12

Old Term

WmTestSuite

New Term

Unit Test Framework

8.0 Added, Removed, Deprecated, or Changed Items

This section lists functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

Release 10.2

Added Item	Description
Code coverage analysis	This feature allows you to record and analyze which flow steps and map actions of your flow service(s) are executed during a particular test launch.
Custom Junit runner	A custom runner specific to Unit Test Framework is added along with supporting Ant build script. This allows batch execution of multiple Test Suites over a server session and also provides a better HTML reporting.
Ignore namespace prefix	Output Comparison now allows ignoring the namespace prefix from the service results.

Release 10.1

Added Item	Description
Generating Test Suites using Service Execution Results	Test Suite allows you to generate tests from the details of recently run services present in the Result view.

Changed Item	Description
Unit Test Framework preference is replaced by the default Integration Server definition.	Integration Server preferences in Designer describe the connection to for Test Suite. In Designer, the Test Suite Server preference has been replaced by the default Integration Server definition specified in Integration Server preferences.

9.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

10.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

GWM-RM-103-20181015

Software AG Universal Messaging 10.3 Readme

October 2018

This file contains important information you must read before using Software AG Universal Messaging 10.3. You can find system requirements, user documentation, and installation and upgrade instructions on the Documentation website at <http://documentation.softwareag.com/> or the TECHcommunity website at <http://techcommunity.softwareag.com/>. At those locations, you can also find suite-related security and globalization information.

Included in this file is information about functionality that has been added, removed, deprecated, or changed for this product. Deprecated functionality continues to work and is supported by Software AG, but may be removed in a future release. Software AG recommends against using deprecated functionality in new projects.

1.0	Critical Information.....	2
2.0	Known Issues.....	2
3.0	Usage Notes.....	4
4.0	Fixes Included in Each Release.....	5
5.0	Resolved Issues	5
6.0	Documentation Changes	7
7.0	Terminology Changes	7
8.0	Added, Removed, Deprecated, or Changed Items.....	8
9.0	Added, Removed, Deprecated, or Changed Parameters.....	8
10.0	Added, Removed, Deprecated, or Changed APIs	8
11.0	Copyright Information.....	8
12.0	Support.....	8

1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the Empower website at <https://empower.softwareag.com/>.

2.0 Known Issues

2.1 Issues originating in the Current Release

- NUM-10799
Uninstallation may not remove UM Windows service.
Windows services created during or after installation of Universal Messaging may not be removed when the product is uninstalled. Users should check whether any such services still exist after uninstallation and manually remove them if so, using the Windows Services control panel.
- NUM-10743
MQTT QoS-2 connections are not downgraded to QoS-1.
The MQTT implementation in Universal Messaging does not support MQTT QoS level 2. Connections requesting QoS-2 should be downgraded to QoS-1 as permitted by the MQTT specification, but this does not currently happen. MQTT applications should avoid requesting QoS-2 connections to Universal Messaging until this defect is resolved.
- NUM-10210
UM instance manager crashes if instance name is too long.
The Universal Messaging instance manager tool may crash when run on Windows with an instance name longer than 42 characters, although the instance may still be created. The only workaround is to use a shorter instance name.
- NUM-10177
Clients may need to reconnect for changed realm properties to take effect.
Some Universal Messaging realm properties, such as the AMQP Message Transformation setting, are applied on a per-connection basis, meaning that clients must re-connect to pick up a change in the realm-wide value. The Universal Messaging documentation will be updated to reflect which configuration properties are affected by this behavior.

2.2 Issues originating in Previous Releases

- NUM-8944
Enterprise Manager should not be able to connect to two clusters with the same name.
If you sequentially create two clusters with the same name but with different realms in Enterprise Manager, Enterprise Manager displays a single cluster node that lists only the realms of the first cluster in the tree panel. If you have two existing clusters with the same name and sequentially add a realm from each cluster in Enterprise Manager, Enterprise Manager displays a single cluster node that lists the realms of both clusters in the tree panel.
- NUM-9489
JMS API allows creation of multiple exclusive durables with the same name.
Since the 9.12 release, the JMS Session.createDurableSubscriber allows creating more than one exclusive durable subscriber with the same name, with no exception thrown or other indication that this has occurred.
Workaround: Client code should ensure that all exclusive durables have unique names.
- NUM-9263
nRealmUnreachableException when UM C++ client creates more than 16 sessions per client process. The client API for C++ has a hard-coded limit of 16 sessions per client process, and any attempt to create more sessions than this will fail.
There is currently no workaround for this issue.
- NUM-7839
If an exclusive asynchronous durable is created, closed and then re-subscribed immediately, it is possible for the client to receive an exception that the subscriber is already bound. This is caused because the session disconnected operation does not wait for all resources to be cleaned. If a client waits for a while before the second subscription, all resources on the server are cleaned so the subscription is successful, but there is no way currently to ensure the exact point of time at which everything is cleaned.
- NUM-6873
Out of order event after restarting shared durable receiver
Disordering of events can occur when re-starting a shared durable subscriber with unacknowledged events using the queued shared durable implementation.
A workaround for this is to ensure that the “Fanout Config -> SyncQueuePublisher” realm configuration property is set to false. This however may cause excess events to build up on server queues in scenarios where consumers do not keep up with publishers.
Note that for a Universal Messaging delivery as part of a webMethods bundle, the configuration property defaults to false anyway.

- NUM-6147
P2P hidden channel appearing
When upgrading an installation from 9.10, a channel with the name "-p2p/serviceinfo" may be visible within the namespace of Universal Messaging. This channel can safely be removed as it is an artifact of a deprecated and now removed feature P2P. If not removed it will have no adverse effect on Universal Messaging.
- Shared memory drivers are currently not supported on HP-UX systems
On HP-UX® systems, shared memory drivers are currently not supported.
There is currently no workaround for this issue.
- NUM-2211
Paged Store type is unsupported in Solaris / SPARC with JDK 1.8.
Currently, the Paged Storage feature is not supported in a Solaris® / SPARC® environment with JDK 1.8.
Workaround: Consider using JDK 1.7 instead.

3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

- The Java®-based components of Universal Messaging are now built to require a Java 8 virtual machine at runtime. Releases before 10.2 would run against older Java virtual machine versions but these are no longer supported in this release. The minimum Java virtual machine version that should be used is the one included in the product installation.
- Issues related to the “Pause Publishing” feature:
 - Modifying JNDI entries is not possible while publishing is paused. This is because JNDI entries are stored in a Universal Messaging channel.
 - Clients created using an API from a product release prior to v10.1 will not throw the intended nSessionPauseException while publishing is paused. Java® publish / commit operations will throw nBaseClientException, whereas C++ and C# will throw nUnexpectedResponseException.
 - If publishing is paused, editing a store through Enterprise Manager will cause the events on the store to be lost, as they cannot be republished on the re-created store.
- The set of Windows Start Menu entries created for each Universal Messaging instance has been simplified. In the 10.3 release each instance will have a Start Menu entry for an “Examples Command Prompt” and for a “Realm Server Command Prompt”. The language-specific command prompt entries created by previous releases have been removed, and the documentation updated to describe how to configure the environment to develop with Universal Messaging using these languages.

- The server-side event filtering functionality in Universal Messaging does not support filtering of Google Protocol Buffer events using the “map” container type available in recent versions of the Google Protocol Buffer language.
- A significant number of realm server configuration properties have been removed in the 10.3 release. See the Release Notes document for further details of these changes.

4.0 Fixes Included in Each Release

For detailed information about available fixes that have been applied in current or previous product releases, go to the Knowledge Center on the Empower website.

5.0 Resolved Issues

The current release resolves many functional, robustness and performance issues that arose in previous releases. This section provides a short summary of the resolved issues that may be of most interest to customers.

Release 10.3

- NUM-10389
Possible memory leak when deleting channels.
A memory leak of cached Google Protocol Buffer definitions that could be triggered by deleting channels from the Universal Messaging realm server has been resolved.
- NUM-10317
JAVA_HOME environment variable not tailored correctly on Windows.
The JAVA_HOME environment variable was not being correctly tailored to point to the installed Java Virtual Machine when opening one of the Universal Messaging command prompts from the Windows Start Menu. The variable will now be set correctly.
- NUM-10313
Enterprise Manager hangs after 10 minutes.
The Universal Messaging Enterprise Manager tool could hang after a period of time when connected to a realm server under heavy load. This issue has been resolved.
- NUM-9719
AMQP/JMS mapping header mismatch.
The AMQP to JMS mapping supported by Universal Messaging has been updated to include some additional mappings defined in the latest updates to the AMQP specification.

Release 10.2

- NUM-9143

It is not possible to import a realm configuration exported from UM 10.1.

Previous releases allowed realm configurations containing clustered Simple and Transient channels to be imported even though these configurations are unsupported. The import tooling has been updated to detect such invalid configurations and allow automatic upgrading of these channels to Mixed type if requested by the user.

- NUM-9326

UM's SPM should set connection name for admin connection.

The Software AG Platform Manager (SPM) plugin for Universal Messaging will now set the "connection name" property when making an administrative connect to the Universal Messaging server. This allows easier identification of the clients connecting to a particular server.

6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

Release 10.3

- The Universal Messaging Clustering Guide, which was previously released as a PDF file complementing the product documentation set, has now been incorporated into the Universal Messaging Concepts Guide.
- Detailed documentation of the AMQP (Advanced Message Queueing Protocol) implementation in Universal Messaging has been added to the product documentation set.
- The differences in functionality available through the Universal Messaging management UIs in Enterprise Manager and Command Central have been documented.

Release 10.2

In previous releases of the documentation, the terms “named object” and “durable subscription” were used to mean the same thing. In this release all use of “named object” has been dropped in favor of the terms “durable subscription” or just “durable”.

Release 9.12

The description of how to use Command Central to perform administrative tasks on Universal Messaging has moved from the Command Central documentation set to the Administration Guide of the Universal Messaging documentation set.

7.0 Terminology Changes

Information for a release is listed in this section only if changes occurred in that release. Added, Removed, Deprecated, or Changed Items

See the *Release Notes* document in the Universal Messaging documentation.

8.0 Added, Removed, Deprecated, or Changed Items

See the Release Notes document in the Universal Messaging documentation.

9.0 Added, Removed, Deprecated, or Changed Parameters

See the *Release Notes* document in the Universal Messaging documentation.

10.0 Added, Removed, Deprecated, or Changed APIs

See the *Release Notes* document in the Universal Messaging documentation.

11.0 Copyright Information

Copyright © 2018 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

12.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos and tutorials, technical information, samples, useful resources, online discussion forums, and more.

UM-RM-103-20181015